



STATE OF MICHIGAN
DEPARTMENT OF LICENSING AND REGULATORY AFFAIRS

MIOSHA SAFETY & HEALTH STANDARDS
FOR AGRICULTURAL OPERATIONS

PART 51. AGRICULTURAL TRACTORS (1928.51)

PART 53. FARM FIELD EQUIPMENT (1928.57)

1928.21 AGRICULTURAL OPERATIONS

Visit our website at: www.michigan.gov/mioshastandards

TABLE OF CONTENTS

PART 51. AGRICULTURAL TRACTORS	3
R 408.45101 Adoption by reference of federal standard	3
1928.51	3
(a) Definitions	3
(b) General requirements	3
(c) Labeling	4
(d) Operating instructions	4
APPENDIX A	4
PART 53. FARM FIELD EQUIPMENT	5
R 408.45301 Adoption of federal standard	5
1928.57	5
(a) General	5
(b) Farm field equipment	6
(c) Farmstead equipment	6
(d) Cotton ginning equipment	7
1928.21 AGRICULTURAL OPERATIONS	9

DEPARTMENT OF LICENSING AND REGULATORY AFFAIRS

DIRECTOR'S OFFICE

SAFETY STANDARDS FOR AGRICULTURE

Filed with the Secretary of State on April 29, 1977 (as amended February 13, 1997)

This rule takes effect 15 days after filing with the Secretary of State

(By authority conferred on the director of the department of consumer and industry services by sections 16 and 21 of Act No. 154 of the Public Acts of 1974, as amended, and Executive Reorganization Order No. 1996-2, being §§408.1016, 408.1021, and 445.2001 of the Michigan Compiled Laws)

R 408.45101 of the Michigan Administrative Code, appearing on page 4260 of the 1979 Michigan Administrative Code, is amended to read as follows:

PART 51. AGRICULTURAL TRACTORS

R 408.45101 Adoption by reference of federal standard.

Rule 5101. Effective 15 days after this rule is filed with the secretary of state, a tractor used in agricultural operations shall be as prescribed in 29 C.F.R. §1928.51, which is adopted in these rules by reference and which may be inspected at the Lansing office of the department of consumer and industry services. 29 C.F.R. §1928.51 was published in the March 7, 1996, Federal Register and may be purchased at a cost of 75 cents from the Superintendent of Documents, Washington, DC 20402, or from the Occupational Safety and Health Administration Area Office, 801 S. Waverly Road, Lansing, MI 48917. The section is also available at no cost from the Michigan Department of Consumer and Industry Services, 7150 Harris Drive, P.O. Box 30643, Lansing, Michigan 48909-8143.

1928.51

ROLL-OVER PROTECTIVE STRUCTURES (ROPS) FOR TRACTORS USED IN AGRICULTURAL OPERATIONS

(a) Definitions.

As used in this subpart -

"Agricultural tractor" means a two or four-wheel drive type vehicle, or track vehicle, of more than 20 engine horsepower, designed to furnish the power to pull, carry, propel, or drive implements that are designed for agriculture. All self-propelled implements are excluded.

"Low profile tractor" means a wheeled tractor possessing the following characteristics:

- (1) The front wheel spacing is equal to the rear wheel spacing, as measured from the centerline of each right wheel to the centerline of the corresponding left wheel.
- (2) The clearance from the bottom of the tractor chassis to the ground does not exceed 18 inches.
- (3) The highest point of the hood does not exceed 60 inches, and

(4) The tractor is designed so that the operator straddles the transmission when seated.

"Tractor weight" includes the protective frame or enclosure, all fuels, and other components required for normal use of the tractor. Ballast shall be added as necessary to achieve a minimum total weight of 110 lb. (50.0 kg.) per maximum power take-off horse power at the rated engine speed or the maximum, gross vehicle weight specified by the manufacturer, whichever is the greatest. From end weight shall be at least 25 percent of the tractor test weight. In case power take-off horsepower is not available, 95 percent of net engine flywheel horsepower shall be used.

(b) General requirements.

Agricultural tractors manufactured after October 25, 1976, shall meet the following requirements:

(1) **Roll-over protective structures (ROPS).** A roll-over protective structures (ROPS) shall be provided by the employer for each tractor operated by an employee. Except as provided in paragraph (b)(5) of this section, ROPS used on wheel-type tractors shall meet the test and performance requirements of the American Society of Agricultural Engineers Standard (ASAE) Standard S306.3-1974 entitled "Protective Frame for Agricultural Tractors--Test Procedures and Performance Requirements" and Society of Automotive Engineers (SAE) Standard J334-1970, entitled "Protective Frame Test Procedures and Performance Requirements" (formerly codified in 29 CFR 1928.52); or ASAE Standard S336.1-1974, entitled "Protective Enclosures for Agricultural Tractors--Test Procedures and Performance Requirements" and SAE J168-1970, entitled "Protective Enclosures--Test Procedures and Performance Requirements" (formerly codified in 29 CFR 1928.53)¹; or 1926.1002 of OSHA's construction standards. These ASAE and SAE standards are incorporated by reference and have been approved by the Director of the Federal Register in accordance with 5 U.S.C. 552(a) and 1 CFR part 51. Copies may be obtained from either the American Society of

Agricultural Engineers Standard, 2950 Niles Road, Post Office Box 229, St. Joseph, MI 49085, or the Society of Automotive Engineers, 485 Lexington Avenue, New York, NY 10017. Copies may be inspected at the OSHA Docket Office, U.S. Department of Labor, 200 Constitution Ave., NW., Room N2634, or at the Office of the Federal Register, 800 North Capitol St., NW., Suite 700, Washington, D.C. ROPS used on track-type tractors shall meet the test and performance requirement of 1926.1001 of this title.

Footnote¹ In March 1977, the American Society of Agricultural Engineers merged S306 and S336, along with Standard 305, entitled "Operator Protection for Wheel Type Agricultural Tractors," into ASAE S383, which addresses ROPS for wheeled agricultural tractors.

(2) Seatbelts.

(i) Where ROPS are required by this section, the employer shall:

(A) Provide each tractor with a seatbelt which meets the requirements of this paragraph;

(B) Ensure that each employee tightens the seatbelt sufficiently to confine the employee to the protected area provided by the ROPS.

(ii) Each seatbelt shall meet the requirements set forth in Society of Automotive Engineer Standard SAE J4C, 1965 Motor Vehicle Seat Belt Assemblies², except as noted hereafter:

Footnote² Copies may be obtained from the Society of Automotive Engineers, 400 Commonwealth Drive, Warrendale, Pa. 15096.

(A) Where a suspended seat is used, the seatbelt shall be fastened to the movable portion of the seat to accommodate a ride motion of the operator.

(B) The seatbelt anchorage shall be capable of withstanding a static tensile load of 1,000 pounds (453.6 kg) at 45 degrees to the horizontal equally divided between the anchorages. The seat mounting shall be capable of withstanding this load plus a load equal to four times the weight of all applicable seat components applied at 45 degrees to the horizontal in a forward and upward direction. In addition, the seat mounting shall be capable of withstanding a 500 pound (226.8 kg) belt load plus two times the weight of all applicable seat components both applied at 45 degrees to the horizontal in and upward and rearward direction. Floor and seat deformation is acceptable provided there is not structural failure or release of the seat adjusted mechanism or other locking device.

(C) The seatbelt webbing material shall have a resistance to acids, alkalis, mildew, aging, moisture, and sunlight equal to or better than that of untreated polyester fiber.

(3) Protection from spillage. Batteries, fuel tanks, oil reservoirs, and coolant systems shall be constructed and located or sealed to assure that spillage will not occur which may come in contact with the operator in the event of an upset.

(4) Protection from sharp surfaces. All sharp edges and corners at the operator's station shall be designed to minimize operator injury in the event of an upset.

(5) Exempted uses. Paragraphs (b)(1) and (b)(2) of this section do not apply to the following uses:

(i) "**Low profile**" tractors while they are used in orchards, vineyards or hop yards where the vertical clearance requirements would substantially interfere with normal operations, and while their use is incidental to the work performed therein.

(ii) "**Low profile**" tractors while used inside a farm building or greenhouse in which the vertical clearance is insufficient to allow a ROPS equipped tractor to operate, and while their use is incidental to the work performed therein.

(iii) Tractors while used with mounted equipment which is incompatible with ROPS (e.g. cornpickers, cotton strippers, vegetable pickers and fruit harvesters).

(6) Remounting. Where ROPS are removed for any reason, they shall be remounted so as to meet the requirements of this paragraph.

(c) Labeling.

Each ROPS shall have a label, permanently affixed to the structure, which states:

(1) Manufacturer's or fabricator's name and address;

(2) ROPS model number, if any;

(3) Tractor makes, models, or series numbers that the structure is designed to fit; and

(4) That the ROPS model was tested in accordance with the requirements of this subpart.

(d) Operating instructions.

Every employee who operates an agricultural tractor shall be informed of the operating practices contained in Appendix A of this part and of any other practices dictated by the work environment. Such information shall be provided at the time of initial assignment and at least annually thereafter.

[61 FR 9227, March 7, 1996]

APPENDIX A

EMPLOYEE OPERATING INSTRUCTION

1. Securely fasten your seat belt if the tractor has a ROPS.

2. Where possible, avoid operating the tractor near ditches, embankments, and holes.

3. Reduce speed when turning, crossing slopes, and on rough, slick, or muddy surfaces.

4. Stay off slopes too steep for safe operation.

5. Watch where you are going, especially at row ends, on roads, and around trees.

6. Do not permit others to ride.

7. Operate the tractor smoothly - no jerky turns, starts, or stops.

8. Hitch only to the drawbar and hitch points recommended by tractor manufacturers.

9. When tractor is stopped, set brakes securely and use park lock if available.

DEPARTMENT OF LICENSING AND REGULATORY AFFAIRS

DIRECTOR'S OFFICE

SAFETY STANDARDS FOR AGRICULTURE

Filed with the Secretary of State on **April 29, 1977**

This rule takes effect 15 days after filing with the Secretary of State

(By authority conferred on the director of the department of consumer and industry services by sections 16 and 21 of Act No. 154 of the Public Acts of 1974, as amended, and Executive Reorganization Order No. 1996-2, being §§408.1016, 408.1021, and 445.2001 of the Michigan Compiled Laws)

PART 53. FARM FIELD EQUIPMENT

R 408.45301 Adoption of federal standard.

Rule 1201. (1) Farm field equipment used in agricultural operations shall be as prescribed in paragraphs (a) to (c) of 29 C.F.R. §1928.57, OSHA safety and health regulations for the guarding of farm field equipment, farmstead equipment, and cotton gins, which are incorporated herein by reference and may be inspected at the Lansing office of the department of consumer and industry services. This section was published in the March 9, 1976 and October 22, 1976, Federal Registers and may be purchased at a cost of 75 cents from the Superintendent of Documents, Washington, DC 20402, or from the OSHA Area Office, 801 S. Waverly Road, Lansing, MI 48917. This section may also be purchased from the Michigan Department of Consumer and Industry Services, 7150 Harris Drive, P.O. Box 30643, Lansing, Michigan 48909-8143.

(2) Notwithstanding the effective dates contained in paragraph (a)(3) of the referenced regulation, the effective dates shall be 15 days after filing with the Secretary of State.

1928.57

GUARDING OF FARM FIELD EQUIPMENT, FARMSTEAD EQUIPMENT, AND COTTON GINS

(a) General

(1) Purpose. The purpose of this section is to provide for the protection of employees from the hazards associated with moving machinery parts of farm field equipment, farmstead equipment, and cotton gins used in any agricultural operation.

(2) Scope. Paragraph (a) of this section contains general requirements which apply to all covered equipment. In addition, paragraph (b) of this section applies to farm field equipment, paragraph (c) of this section applies to farmstead equipment, and paragraph (d) of this section applies to cotton gins.

(3) Application. This section applies to all farm field equipment, farmstead equipment, and cotton gins, except that paragraphs (b)(2), (b)(3), and (b)(4) (ii)(A), and (c)(2), (c)(3), and (c)(4) (ii)(A) do not apply to equipment manufactured before October 25, 1976.

(4) Effective date. This section takes effect on October 25, 1976, except that paragraph (d) of this section is effective on June 30, 1977.

(5) Definitions -

"Cotton gins" are systems of machines which condition seed cotton, separate lint from seed, convey materials, and package lint cotton.

"Farm field equipment" means tractors or implements, including self-propelled implements, or any combination thereof used in agricultural operations.

"Farmstead equipment" means agricultural equipment normally used in a stationary manner. This includes, but is not limited to, materials handling equipment and accessories for such equipment whether or not the equipment is an integral part of a building.

"Ground driven components" are components which are powered by the turning motion of a wheel as the equipment travels over the ground.

A **"guard"** or **"shield"** is a barrier designed to protect against employee contact with a hazard created by a moving machinery part.

"Power take-off shafts" are the shafts and knuckles between the tractor, or other power source, and the first gear set, pulley, sprocket, or other components on power take-off shaft driven equipment.

(6) Operating instructions. At the time of initial assignment and at least annually thereafter, the employer shall instruct every employee in the safe operation and servicing of all covered equipment with which he is or will be involved, including at least the following safe operating practices:

(i) Keep all guards in place when the machine is in operation;

(ii) Permit no riders on farm field equipment other than persons required for instruction or assistance in machine operation;

(iii) Stop engine, disconnect the power source, and wait for all machine movement to stop before servicing, adjusting, cleaning, or unclogging the equipment, except where the machine must be running to be properly serviced or maintained, in which case the employer shall instruct employees as to all steps and procedures which are necessary to safely service or maintain the equipment;

(iv) Make sure everyone is clear of machinery before starting the engine, engaging power, or operating the machine;

(v) Lock out electrical power before performing maintenance or service on farmstead equipment.

(7) Methods of guarding. Except as otherwise provided in this subpart, each employer shall protect employees from coming into contact with hazards created by moving machinery parts as follows:

(i) Through the installation and use of a guard or shield or guarding by location;

(ii) Whenever a guard or shield or guarding by location is infeasible, by using a guardrail or fence.

(8) Strength and design of guards.

(i) Where guards are used to provide the protection required by this section, they shall be designed and located to protect against inadvertent contact with the hazard being guarded.

(ii) Unless otherwise specified, each guard and its supports shall be capable of withstanding the force that a 250 pound individual, leaning on or falling against the guard, would exert upon that guard.

(iii) Guards shall be free from burrs, sharp edges, and sharp corners, and shall be securely fastened to the equipment or building.

(9) Guarding by location. A component is guarded by location during operation, maintenance, or servicing when, because of its location, no employee can inadvertently come in contact with the hazard during such operation, maintenance, or servicing. Where the employer can show that any exposure to hazards results from employee conduct which constitutes an isolated and unforeseeable event, the component shall also be considered guarded by location.

(10) Guarding by railings. Guardrails or fences shall be capable of protecting against employees inadvertently entering the hazardous area.

(11) Servicing and maintenance. Whenever a moving machinery part presents a hazard during servicing or maintenance, the engine shall be stopped, the power source disconnected, and all machine movement stopped before servicing or maintenance is performed, except where the employer can establish that:

(i) The equipment must be running to be properly serviced or maintained;

(ii) The equipment cannot be serviced or maintained while a guard or guards otherwise required by this standard are in place; and

(iii) The servicing or maintenance can be safely performed.

(b) Farm field equipment

(1) Power take-off guarding.

(i) All power take-off shafts, including rear, mid- or side-mounted shafts, shall be guarded either by a master shield, as provided in paragraph (b)(1)(ii) of this section, or by other protective guarding.

(ii) All tractors shall be equipped with an agricultural tractor master shield on the rear power

take-off except where removal of the tractor master shield is permitted by paragraph (b)(1)(iii) of this section. The master shield shall have sufficient strength to prevent permanent deformation of the shield when a 250 pound operator mounts or dismounts the tractor using the shield as a step.

(iii) Power take-off driven equipment shall be guarded to protect against employee contact with positively driven rotating members of the power drive system. Where power take-off driven equipment is of a design requiring removal of the tractor master shield, the equipment shall also include protection from that portion of the tractor power take-off shaft which protrudes from the tractor.

(iv) Signs shall be placed at prominent locations on tractors and power take-off driven equipment specifying that power drive system safety shields must be kept in place.

(2) Other power transmission components.

(i) The mesh or nip-points of all power driven gears, belts, chains, sheaves, pulleys, sprockets, and idlers shall be guarded.

(ii) All revolving shafts, including projections such as bolts, keys, or set screws, shall be guarded, except smooth shaft ends protruding less than one-half the outside diameter of the shaft and its locking means.

(iii) Ground driven components shall be guarded in accordance with paragraphs (b)(2)(i) and (b)(2)(ii) of this section if any employee may be exposed to them while the drives are in motion.

(3) Functional components. Functional components, such as snapping or husking rolls, straw spreaders and choppers, cutterbars, flail rotors, rotary beaters, mixing augers, feed rolls, conveying augers, rotary tillers, and similar units, which must be exposed for proper function, shall be guarded to the fullest extent which will not substantially interfere with normal functioning of the component.

(4) Access to moving parts.

(i) Guards, shields, and access doors shall be in place when the equipment is in operation.

(ii) Where removal of a guard or access door will expose an employee to any component which continues to rotate after the power is disengaged, the employer shall provide, in the immediate area, the following:

(A) A readily visible or audible warning of rotation; and

(B) A safety sign warning the employee to:

(1) Look and listen for evidence of rotation; and

(2) Not remove the guard or access door until all components have stopped.

(c) Farmstead equipment

(1) Power take-off guarding.

(i) All power take-off shafts, including rear, mid-, or side-mounted shafts, shall be guarded either by a master shield as provided in paragraph (b)(1)(ii) of this section or other protective guarding.

(ii) Power take-off driven equipment shall be guarded to protect against employee contact with

positively driven rotating members of the power drive system. Where power take-off driven equipment is of a design requiring removal of the tractor master shield, the equipment shall also include protection from that portion of the tractor power take-off shaft which protrudes from the tractor.

(iii) Signs shall be placed at prominent locations on power take-off driven equipment specifying that power drive system safety shields must be kept in place.

(2) Other power transmission components.

(i) The mesh or nip-points of all power driven gears, belts, chains, sheaves, pulleys, sprockets, and idlers shall be guarded.

(ii) All revolving shafts, including projections such as bolts, keys, or set screws, shall be guarded, with the exception of:

(A) Smooth shafts and shaft ends (without any projecting bolts, keys or set screws), revolving at less than 10 rpm, on feed handling equipment used on the top surface of materials in bulk storage facilities; and

(B) Smooth shaft ends protruding less than one-half the outside diameter of the shaft and its locking means.

(3) Functional components.

(i) Functional components, such as choppers, rotary beaters, mixing augers, feed rolls, conveying augers, grain spreaders, stirring augers, sweep augers, and feed augers, which must be exposed for proper function, shall be guarded to the fullest extent which will not substantially interfere with the normal functioning of the component.

(ii) Sweep arm material gathering mechanisms used on the top surface of materials within silo structures shall be guarded. The lower or leading edge of the guard shall be located no more than 12 inches above the material surface and no less than 6 inches in front of the leading edge of the rotating member of the gathering mechanism. The guard shall be parallel to, and extend the fullest practical length of, the material gathering mechanism.

(iii) Exposed auger flighting on portable grain augers shall be guarded with either grating type guards or solid baffle style covers as follows:

(A) The largest dimensions or openings in grating type guards through which materials are required to flow shall be 4 3/4 inches. The area of each opening shall be no larger than 10 square inches. The opening shall be located no closer to the rotating flighting than 2 1/2 inches.

(B) Slotted openings in solid baffle style covers shall be no wider than 1 1/2 inches, or closer than 3 1/2 inches to the exposed flighting.

(4) Access to moving parts.

(i) Guards, shields, and access doors shall be in place when the equipment is in operation.

(ii) Where removal of a guard or access door will expose an employee to any component which continues to rotate after the power is disengaged, the employer shall provide, in the immediate area, the following:

(A) A readily visible or audible warning of rotation; and

(B) A safety sign warning the employee to:

(1) Look and listen for evidence of rotation; and

(2) Not remove the guard or access door until all components have stopped.

(5) Electrical disconnect means.

(i) Application of electrical power from a location not under the immediate and exclusive control of the employee or employees maintaining or servicing equipment shall be prevented by:

(A) Providing an exclusive, positive locking means on the main switch which can be operated only by the employee or employees performing the maintenance or servicing; or

(B) In the case of material handling equipment located in a bulk storage structure, by physically locating on the equipment an electrical or mechanical means to disconnect the power.

(ii) All circuit protection devices, including those which are an integral part of a motor, shall be of the manual reset type, except where:

(A) The employer can establish that because of the nature of the operation, distances involved, and the count of time normally spent by employees in the area of the affected equipment, use of the manual reset device would be infeasible;

(B) There is an electrical disconnect switch available to the employee within 15 feet of the equipment upon which maintenance or service is being performed; and

(C) A sign is prominently posted near each hazardous component which warns the employee that, unless the electrical disconnect switch is utilized, the motor could automatically reset while the employee is working on the hazardous component.

(d) Cotton ginning equipment

(1) Power transmission components.

(i) The main drive and miscellaneous drives of gin stands shall be completely enclosed, guarded by location, or guarded by railings (consistent with the requirements of paragraph (a)(7) of this section). Drives between gin stands shall be guarded so as to prevent access to the area between machines.

(ii) When guarded by railings, any hazardous component within 15 horizontal inches of the rail shall be completely enclosed. Railing height shall be approximately 42 inches off the floor, platform, or other working surface, with a midrail between the top-rail and the working surface. Panels made of materials conforming to the requirements in Table D-1, or equivalent, may be substituted for midrails. Guardrails shall be strong enough to withstand at least 200 pounds force on the top rail.

(iii) Belts guarded by railings shall be inspected for defects at least daily. The machinery shall not be operated until all defective belts are replaced.

TABLE D-1 EXAMPLES OF MINIMUM REQUIREMENTS FOR GUARD PANEL MATERIALS

Material	Clearance from moving part at all points (in inches)	Largest mesh or opening allowable (in inches)	Minimum gage (U.S. standard or thickness)
Woven wire	Under 2	3/8	16
	2 to 4	1/2	16
	4 to 15	2	12
Expanded Metal	Under 4	1/2	18
	4 to 15	2	13
Perforated Metal	Under 4	1/2	20
	4 to 15	2	14
Sheet Metal	Under 4		22
	4 to 15		22
Plastic	Under 4		1
	4 to 15		1

Footnote¹: Tensile strength of 10,000 lb./in²

(iv) Pulleys of V-belt drives shall be completely enclosed or guarded by location whether or not railings are present. The open end of the pulley guard shall be not less than 4 inches from the periphery of the pulleys.

(v) Chains and sprockets shall be completely enclosed, except that they may be guarded by location if the bearings are packed or if accessible extension lubrication fittings are used.

(vi) Where complete enclosure of a component is likely to cause a fire hazard due to excessive deposits of lint, only the face section of nip-point and pulley guards is required. The guard shall extend at least 6 inches beyond the rim of the pulley on the in-running and off-running sides of the belt, and at least 2 inches from the rim and face of the pulley in all other directions.

(vii) Projecting shaft ends not guarded by location shall present a smooth edge and end, shall be guarded by non-rotating caps or safety sleeves, and may not protrude more than one-half the outside diameter of the shaft.

(viii) In power plants and power development rooms where access is limited to authorized personnel, guard railings may be used in place of guards or guarding by location. Authorized employees having access to power plants and power development rooms shall be instructed in the safe operation and maintenance of the equipment in accordance with paragraph (a)(6) of this section.

(2) Functional components.

(i) Gin stands shall be provided with a permanently installed guard designed to preclude contact with the gin saws while in motion. The saw blades in the roll box shall be considered guarded by location if they do not extend through the ginning ribs into the roll box when the breast is in the out position.

(ii) Moving saws on lint cleaners which have doors giving access to the saws shall be guarded by fixed barrier guards or their equivalent which prevent direct finger or hand contact with the saws while the saws are in motion.

(iii) An interlock shall be installed on all balers so that the upper gates cannot be opened while the trampler is operating.

(iv) Top panels of burr extractors shall be hinged and equipped with a sturdy positive latch.

(v) All accessible screw conveyors shall be guarded by substantial covers or gratings, or with an inverted horizontally slotted guard of the trough type, which will prevent employees from coming into contact with the screw conveyor. Such guards may consist of horizontal bars spaced so as to allow material to be fed into the conveyor, and supported by arches which are not more than 8 feet apart. Screw conveyors under gin stands shall be considered guarded by location.

(3) Warning device. A warning device shall be installed in all gins to provide an audible signal which will indicate to employees that any or all of the machines comprising the gin are about to be started. The signal shall be of sufficient volume to be heard by employees, and shall be sounded each time before starting the gin.

[41 FR 10195, Mar. 9, 1976; 41 FR 11022, Mar. 16, 1976; 41 FR 22268, June 2, 1976, as amended at 41 FR 46598, Oct. 22, 1976]

DEPARTMENT OF LICENSING AND REGULATORY AFFAIRS**DIRECTOR'S OFFICE****SAFETY STANDARDS FOR AGRICULTURE**

These rules take effect **January 1, 1975**

(By authority conferred on the director of the department of consumer and industry services by sections 16 and 21 of Act No. 154 of the Public Acts of 1974, as amended, and Executive Reorganization Order no. 1996-2, being §§408.1016, 408.1021, and 445.2001 of the Michigan Compiled Laws)

1928.21 AGRICULTURAL OPERATIONS

(a)(1) The standards referenced in the remaining subparagraphs of this paragraph apply to the indicated operations, whether or not they include as a part of, agricultural operations.

(2) Administered by the Division of Occupational Health.

(3) Storage and handling of anhydrous ammonia--§1910.111 (a) and (b).

(4) Pulpwood logging--general industry standard Part 51. Logging.

(5) Slow-moving vehicles--general industry standard Part 37. Accident Prevention Signs and Tags.

(b) Except to the extent specified in paragraph (a) of this section, the balance of general industry standards do not apply to agricultural operations.

(c) The development of standards having more general application to agricultural operations shall be prescribed in section 21(4) of Act 154 of the Public Acts of 1974.



Michigan Occupational Safety and Health Administration
PO Box 30643
Lansing, Michigan 48909-8143
Ph: 517.322.1845

The Department of Licensing and Regulatory Affairs will not discriminate against any individual or group because of race, sex, religion, age, national origin, color, marital status, disability, or political beliefs. Auxiliary aids, services and other reasonable accommodations are available upon request to individuals with disabilities.