



APPENDIX B

TRUCK QUESTIONNAIRE FORMS

ALL BIDDERS MUST COMPLETE AND RETURN A QUESTIONNAIRE FORM WITH THE BID FOR EACH TRUCK ITEM TO BE CONSIDERED FOR AWARD OF THAT ITEM. Bids submitted without an adequately completed questionnaire form for EACH TRUCK ITEM will not be considered for award of that item. It is the responsibility of each bidder to copy this form in sufficient quantity to submit to Purchasing Operations prior to the scheduled bid due date. A single form may apply to more than one item, simply list the item numbers to which the questionnaire applies in the appropriate space. If part of the questionnaire does not apply, simply indicate "not applicable" in those spaces.

NAME OF BIDDER: Red Holman Pontiac Gmc ITEM NO(s). Spec # 3958-0101
 MAKE OF TRUCK: GMC MODEL: Savana T633803GVWR 10000 lbs.
 PAYLOAD: 5148 # W.B. 159" C.A. 100" C.E. 168.50"
 ENGINE: (GAS - DIESEL) GAS MAKE: Gm MODEL: LY6, 6.0 SAE H.P. 323
 FUEL TANK(S) CAPACITY: 57 (GALS. TOTAL) TRANSMISSION: Gm Hydraulic MTI 4spd
 SPRING CAP. @ GROUND EACH: FRONT 2050 lbs. REAR 3750 lbs. AUX. N/A lbs.
 AXLES: FRONT 4100 lbs. REAR 7500 lbs. REAR RATIO 4.10
 ALTERNATOR: 145 amps. BATTERY 600 cca.
 TIRE SIZE: FRONT T225/75R16E PR REAR T225/75R16 PR SINGLE _____ DUAL M&S _____
 TIRE: MAKE TBD STYLE NO. TBD MFG. CODE XHF
 HOIST: MAKE N/A MODEL N/A INSTALLING CO. N/A
 BODY: MAKE N/A MODEL N/A INSTALLING CO. N/A
 POWER LIFT GATE: MAKE N/A MODEL N/A CAPACITY N/A lbs.
 PLATFORM SIZE: N/A

OTHER EQUIPMENT INSTALLED BY BODY EQUIPMENT SUPPLIER AND/OR COMMENTS

This information must be returned with the bid document to Purchasing Operations, on or before the bid due date and time. However, if returned separately, it must be received by Purchasing Operations on or before the bid due date and time, and must comply with the sealed bid instructions as outlined in the ITB.

TRUCK: CUT-AWAY VAN AND BODY DUAL REAR WHEELS

(G.V.W.R. 11,000 lbs., min.)*

MODEL-2008 CURRENT NEW

	CHEV/ GMC <u>G33903</u>	FORD <u>E-350 Cut-Away</u>
Wheel base (inches)	177	158 for (14' & 15' body)
Engine: Gasoline	6.0L	6.8L
Type & No. of Cylinders	V-8	V-10
Net H.P.-S.A.E.	323	305
Transmission: Automatic		
Axle, Min. Cap.-lbs.		
Front	TBD	5,000
Rear	TBD	8,500
Springs, Min. Cap. At Ground		
Front-lbs. Each	TBD	2,300
Rear-lbs. Each	TBD	4,300

Tires, Truck, Tubeless, Radial, to meet G.V.W.R. Rear duals, Mud and Snow or All Season.

*See Mich. SPEC. # 3958-0102 or 3958-0103 for body

TO BE STANDARD FACTORY EQUIPPED AS FOLLOWS:

The items listed below are to be supplied on all trucks, even though they may be optional with the manufacturer. Therefore, these specifications are to be furnished on all vehicles:

- 12 Volt auxiliary outlet
- Air Conditioning - All trucks
- Anti-freeze protection, to -30°F.
- Arm Rest-Driver's side.
- Color-Manufacturers Standard to be selected.
- Coolant System-Maximum Size Available, including the Heaviest Duty Radiator
- Dome Light.
- Electric wiring-All wiring passing through holes in metal or non-metal wearing surfaces, which could cause wear of the insulation, shall be adequately protected by rubber or plastic grommets, and/or non-metallic conduit. Ends of all wires shall be adequately anchored to prevent loosening.
- Frame length-on all body installations without hoists the cab to end of frame length shall be the same length as the body being mounted, plus the length of any setback.

- ☑ Fuel Tanks, Diesel, with sending unit and magnetic drain plug, on all trucks over 21,000 G.V.W.R., painted Black and labeled "Diesel Fuel Only".
- ☑ Hub caps on all pickups and vans up to and including 10,000 G.V.W.R. If not available from dealer cap nuts shall be furnished.
- ☑ Keys-(2) sets with code numbers; shall be with vehicle at time of delivery.
- ☑ Mirrors-All trucks are to be equipped with R.H. and L.H. outside rear-view mirrors to comply with Michigan laws; all trucks up to and including 15,000 G.V.W.R. shall be equipped with inside rear-view mirror. In all cases, outside R.H. & L.H. rear view mirrors shall provide full vision past all body installations. Mirrors shall be of stainless steel or high impact plastic construction unless denoted otherwise in individual truck specifications. All West Coast Type or Below Eye Level Camper Style Mirrors shall have stainless steel or high impact plastic heads, brackets, and hardware.
- ☑ Mud flaps, Anti-Sail Type, when required, are to be plain, rubber 1/4" thick, without advertising on either side.
- ☑ Painting-preclean and metal prep, any bare metal surfaces prior to applying a compatible red oxide or zinc chromate primer. When painting over a manufacturer's standard paint, metal prepping and primer may be omitted, provided an acceptable bond can be achieved.
- ☑ Equipment mounting- when mounting equipment on truck cab and chassis, all holes shall be drilled or punched. There shall be no flame cutting or welding on the frame side rails.
- ☑ Paint codes-factory paint codes shall be furnished with all vehicles; for all after market painting both the brand and paint code shall be furnished.
- ☑ Pre-delivery inspection and servicing.
- ☑ Radio - AM/FM Manufacturers Standard, Factory Installed
- ☑ Seat Belts with Shoulder Harness (3-Point Restraint System for Driver & Passenger)
- ☑ Seats-Split Bench type, unless otherwise specified GMC: Bucket Seats
- ☑ Shock absorbers-(Heaviest Duty Available), front all trucks. Rear, up to and including 15,000 G.V.W.R.
- ☑ Spare tire, or Rim, not to be furnished unless specified. If specified, tires to be of same mfg., tread design to be same as front tires.
- ☑ Speed Control, Factory Installed
- ☑ Steering-Power, Tilt Wheel
- ☑ Sun visors-dual.
- ☑ Jack-Furnish on trucks up to and including 12,000 G.V.W.R. GMC: Not Avail
- ☑ Windshield wipers-dual, intermittent speed electric, with automatic type washers.

All items removed for installation of optional equipment shall be returned to the State of Michigan.

TO BE EQUIPPED IN COMPLIANCE WITH ALL APPLICABLE FEDERAL MOTOR VEHICLE SAFETY STANDARDS AND REGULATIONS. ALL VEHICLES MUST BE EQUIPPED TO COMPLY WITH ALL REQUIREMENTS OF THE MICHIGAN MOTOR VEHICLE CODE.

- **Delete: On GM vehicles, OnStar and XM radio are deleted.**

ADDITIONAL OPTIONS:

These options are in addition to the options listed above as “STANDARD FACTORY EQUIPPED” and are to be included on this vehicle.

- Alternator-80 amp., min.
- Battery 12 Volt; 600 CCA, minimum
- Brakes-Power
- Front Fender splash guards GMC: Dealer Installed
- Fuel capacity-largest available from mfg.
- Gauges-temperature, oil pressure, and amp meter or volt meter.
- Mirrors-Rear View, Inside. Outside R.H. and L.H. shall provide full Vision past body installation.
- Mirror shall be duplex head; 1 convex, 1 standard glass, with stainless steel or powder coated steel heads, brackets, and hardware. GMC: Composite Head
- Spare Wheel and Tire
- Steering-Power
- Wrench-Wheel GMC: No wrench available from factory

ADDITIONAL MDOT OPTIONS: (Note: These options are not included in the MiDEAL price)

These options are in addition to the options listed above as “STANDARD FACTORY EQUIPPED” and are to be included on this MDOT vehicle.

- Keys – (1) additional set (total of 3 sets) with code numbers; shall be with the vehicle at the time of delivery.
- Seats-High Back, Driver and Passenger

PRICING SHEET

TRUCK: CUT-AWAY VAN AND BODY DUAL REAR WHEELS (G.V.W.R. 11,000 lbs., min.)* Mich. Spec. #3958-0108	
Standard Equipped Per above Specification (Including options as specified above)	Standard Equipped Cost
Make: GMC Model: Savana Spl F.O.B. - Dealership Delivery Cost Per Mile \$1.00	\$18,721.00*
Final Point of Assembly: Wentzville, MO	
Dealer Information	
Dealer Name: Red Holman Pontiac GMC	
Street Address: 35300 Ford Road	
City: Westland	State: MI
Zip: 48185	
Contact Name: Albert Li	
Telephone: (800) 482-3032	
Cell: (734) 637-6643	
E-mail: aclixx@hotmail.com	

*Please Note: A vehicle order confirmation sheet is included for each vehicle. These documents shall include all the "standard options" as listed for the State of Michigan standard specification.

Vehicle Order Confirmation Sheet
Spec # 3958-0108

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclix@hotmail.com

2008 Fleet/Non-Retail GMC Savana Cutaway 177" WB C7N DRW TG33903

SELECTED MODEL & OPTIONS

SELECTED MODEL - 2008 Fleet/Non-Retail TG33903 177" WB C7N DRW

<u>Code</u>	<u>Description</u>	<u>MSRP</u>
TG33903	2008 GMC Savana Cutaway 177" WB C7N DRW	\$25,915.00

SELECTED VEHICLE COLORS - 2008 Fleet/Non-Retail TG33903 177" WB C7N DRW

<u>Code</u>	<u>Description</u>
93W	Interior: Medium Pewter
50U	Exterior 1: Summit White
-	Exterior 2: No color has been selected.

SELECTED OPTIONS - 2008 Fleet/Non-Retail TG33903 177" WB C7N DRW

CATEGORY

<u>Code</u>	<u>Description</u>	<u>MSRP</u>
BODY CODE		
ZW9	BODY, STANDARD	\$0.00
GVWR		
C7N	GVWR, 12,300 LBS. (5579 KG)	\$0.00
EMISSIONS		
FE9	EMISSIONS, FEDERAL REQUIREMENTS	\$0.00
ENGINE		
LY6	ENGINE, VORTEC 6.0L V8 SFI (323 HP [240.8 KW] @ 4600 RPM, 373 LB-FT OF TORQUE [503.6 N-M] @ 4400 RPM)	\$0.00
TRANSMISSION		
MT1	TRANSMISSION, 4-SPEED AUTOMATIC, HEAVY-DUTY, ELECTRONICALLY CONTROLLED WITH OVERDRIVE, TOW/HAUL MODE AND INTERNAL TRANSMISSION OIL COOLER	\$0.00
DIFFERENTIAL		
—	NO LOCKING REAR DIFFERENTIAL	\$0.00

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.0, Data updated 12/11/2007 11:05:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 19, 2007 4:01:47 PM

Page 1

Prepared By:
 Albert Li
 Red Holman Pontiac GMC
 35300 Ford Rd
 Westland, MI 48185
 Phone: (734) 721-1144
 Fax: (734) 721-1780
 Email: aclix@hotmail.com

2008 Fleet/Non-Retail GMC Savana Cutaway 177" WB C7N DRW TG33903

SELECTED MODEL & OPTIONS

SELECTED OPTIONS - 2008 Fleet/Non-Retail TG33903 177" WB C7N DRW

<u>CATEGORY</u>	<u>Code</u>	<u>Description</u>	<u>MSRP</u>
AXLE	GT5	REAR AXLE, 4.10 RATIO	\$0.00
PREFERRED EQUIPMENT GROUP	1WT	1WT PREFERRED EQUIPMENT GROUP	\$0.00
SEATING ARRANGEMENT	ZX2	SEATING ARRANGEMENT, DRIVER AND FRONT PASSENGER HIGHBACK BUCKET, ADJUSTABLE,	\$0.00
SEAT TYPE	AR7	SEATS, FRONT BUCKET WITH VINYL TRIM AND OUTBOARD HEAD RESTRAINTS	\$0.00
SEAT TRIM	_W	VINYL SEAT TRIM	\$0.00
PAINT	ZY1	PAINT, SOLID	\$0.00
AIR CONDITIONING	C60	AIR CONDITIONING, SINGLE ZONE MANUAL	\$0.00
RADIO	UM7	AUDIO SYSTEM, AM/FM STEREO	\$150.00
ADDITIONAL OPTIONS	ZQ3	CONVENIENCE PACKAGE, TILT-WHEEL AND CRUISE CONTROL	\$395.00
	V14	TRANSMISSION OIL COOLER, EXTERNAL	INC
	D31	MIRROR, INSIDE REARVIEW MANUAL DAY/NIGHT	\$10.00
	DAA	VISORS, DRIVER AND FRONT PASSENGER, VINYL in lieu of standard cloth	INC
	DHC	MIRRORS, OUTSIDE WIDE-STANCE SAIL PANEL MOUNTED (VELVAC).	\$250.00
	NE7	FUEL TANK CAPACITY, APPROXIMATELY 57 GALLONS (215.7L)	\$165.00
	VQ1	FLEET PROCESSING OPTION	\$0.00

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.0, Data updated 12/11/2007 11:05:00 AM
 ©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.
 Customer File:

December 19, 2007 4:01:47 PM

Page 2

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclix@hotmail.com

2008 Fleet/Non-Retail GMC Savana Cutaway 177" WB C7N DRW TG33903

SELECTED MODEL & OPTIONS

SELECTED OPTIONS - 2008 Fleet/Non-Retail TG33903 177" WB C7N DRW

CATEGORY

<u>Code</u>	<u>Description</u>	<u>MSRP</u>
OPTIONS TOTAL		\$970.00

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.0, Data updated 12/11/2007 11:05:00 AM

©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 19, 2007 4:01:47 PM

Page 3

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclix@hotmail.com

2008 Fleet/Non-Retail GMC Savana Cutaway 177" WB C7N DRW TG33903
STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TG33903 177" WB C7N DRW

EXTERIOR

- Paint, solid
- Body, standard
- Bumper, front painted Black with step-pad (Not available with (ZR7) Appearance Package or (YF1) RV Package.)
- Grille, Black composite with single rectangular halogen headlamps (Not available with (ZR7) Chrome Appearance Package.)
- License plate kit, front
- Daytime Running Lamps
- Mirrors, outside delete
- Glass, Solar-Ray light-tinted, all windows
- Wipers, front intermittent wet-arm with pulse washers

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.0, Data updated 12/11/2007 11:05:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 19, 2007 4:01:47 PM

Page 4

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclix@hotmail.com

2008 Fleet/Non-Retail GMC Savana Cutaway 177" WB C7N DRW TG33903

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TG33903 177" WB C7N DRW

INTERIOR

- Seats, front bucket with vinyl trim and outboard head restraints (Requires (**W) trim. Not available with SEO (ZP0) delete driver and passenger seats.)
- Seating arrangement, driver and front passenger highback bucket, adjustable, includes head restraints and vinyl or cloth trim
- Floor covering, Black rubberized-vinyl front
- Theft-deterrent system, vehicle, PASS-Key III
- Instrumentation, analog with speedometer, odometer with trip odometer, fuel level, voltmeter, engine temperature and oil pressure
- Driver Information Center, includes fuel range, average speed, oil life, fuel used, ice warning, engine hours, average fuel economy, tachometer, and maintenance reminders. Compass and outside temperature available if equipped.
- Tow/haul mode selector, instrument panel-mounted
- Warning tones, headlamp on and key-in-ignition
- Oil life monitor
- Air conditioning, single-zone manual
- Heater and defogger with front and side window defoggers
- Defogger, side windows
- Audio system, radio provisions only. Includes alarm warning chimes, radio wiring harness, radio antenna and 2 front door speakers
- Cup holders, 3 on the engine console cover
- Power outlets, 2 auxiliary on engine console cover with covers, 12-volt
- Headliner, cloth, over driver and passenger
- Visors, driver and front passenger, padded
- Assist handle, front passenger
- Lighting, interior with dome light and door handle-activated switches

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.0, Data updated 12/11/2007 11:05:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 19, 2007 4:01:47 PM

Page 5

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclix@hotmail.com

2008 Fleet/Non-Retail GMC Savana Cutaway 177" WB C7N DRW TG33903

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TG33903 177" WB C7N DRW

MECHANICAL

- Engine, Vortec 6.0L V8 SFI (323 hp [240.8 kW] @ 4600 rpm, 373 lb-ft of torque [503.6 N-m] @ 4400 rpm) (Standard on the *G33803 and *G33903 models. Available on *G33503 model. Includes external oil cooler. Reference the Engine/Axle page for availability.)
- Transmission, 4-speed automatic, heavy-duty, electronically controlled with overdrive, tow/haul mode and internal transmission oil cooler (Not available with (LMM) Duramax 6.6L Turbo Diesel V8 engine or (C7F) 14,050 lbs. (6373 kg.) GVWR. Reference the Engine/Axle page for availability.)
- Transmission oil cooler, external (Included with (LMM) Duramax 6.6L Turbo Diesel V8 engine, (LY6) Vortec 6.0L V8 engine or (YF1) RV Package. On the *G33503, when the (LY6) Vortec 6.0L V8 engine is ordered, (V14) transmission oil cooler is required.)
- Brake/transmission shift interlock, for automatic transmissions
- Rear wheel drive
- Battery, 600 cold-cranking amps, maintenance-free with rundown protection and retained accessory power
- Alternator, 145 amps
- Frame, ladder-type
- Incomplete vehicle certification
- GVWR, 12,300 lbs. (5579 kg) (Includes (R05) dual rear, 6 - 16" x 6.5" (40.6 cm x 16.5 cm) wheels on the *G33503 model. Not available with (R04) single rear 4 - 16" x 6.5" (40.6 cm x 16.5 cm) wheels. Reference the Engine/Axle page for availability.)
- Suspension, front independent with coil springs and stabilizer bar
- Suspension, rear hypoid drive axle with multi-leaf springs
- Rear axle, 4.10 ratio (Not available with (LMM) Duramax 6.6L Turbo Diesel V8 engine. Reference the Engine/Axle page for availability.)
- Tires, front LT225/75R16E all-season, blackwall (Included and only available with (C7F) 14,050 lbs. (6373 kg) GVWR or (R05) dual rear 6 - 16" x 6.5" Gray-painted steel wheels.)
- Tires, rear LT225/75R16E all-season, blackwall (Included and only available with (C7F) 14,050 lbs. (6373 kg) GVWR or (R05) dual rear 6 - 16" x 6.5" Gray-painted steel wheels.)
- Tire, spare LT225/75R16E all-season blackwall (Requires (C7F) 14,050 lbs. (6373 kg) GVWR or (R05) dual rear 6 - 16" x 6.5" Gray-painted steel wheels.)

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.0, Data updated 12/11/2007 11:05:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 19, 2007 4:01:47 PM

Page 6

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclbx@hotmail.com

2008 Fleet/Non-Retail GMC Savana Cutaway 177" WB C7N DRW TG33903

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TG33903 177" WB C7N DRW

- Tire valve stems, brass Brass metal valve stem in lieu of standard. Also included on spare when furnished (Included with RPO (YF1) RV Package and with RPO (C7N) 12,300 lbs. (5443 kg.) GVWR or RPO (C7F) 14,050 lbs. (6373 kg.) GVWR. Not available with RPO (YF1) RV Package when ordered with RPO (C6Y) 9600 lbs. (4354 kg.) GVWR or RPO (C7A) 10,000 lbs. (4536 kg.) GVWR.
 - Wheels, 6 - 16" x 6.5" (40.6 cm x 16.5 cm) Gray-painted steel (dual rear) (Standard on the *G33803 and *G33903 models. On the *G33503 model, included and only available with (C7A) 10,000 lbs. (4536 kg.) GVWR or (C7N) 12,300 lbs. (5579 kg.) GVWR. Not available with (C6Y) 9600 lbs. (4354 kg) GVWR, (XHH) front LT245/75R16E all-season blackwall tires, (YHH) rear LT245/75R16E all-season blackwall tires, (ZHH) spare LT245/75R16E all-season blackwall tires or (R04) single rear, 4 - 16" x 6.5" (40.6 cm x 16.5 cm) wheels.)
 - Steering, power
 - Brakes, 4-wheel antilock, 4-wheel disc
 - Exhaust, aluminized stainless-steel muffler and tailpipe
- SAFETY
- Brakes, 4-wheel antilock, 4-wheel disc
 - Air bags, frontal, driver and right-front passenger (Not available with (ZX1) driver only high-back bucket seat. Always use safety belts and the correct child restraints for your child's age and size, even in vehicles equipped with air bags. Children are safer when properly secured in a rear seat. See the vehicle's Owners Manual and child safety seat instructions for more safety information.)
 - Air bag deactivation switch, frontal, passenger-side (Never place a rear-facing infant restraint in the front seat of any vehicle equipped with an active frontal air bag. Always use safety belts and the correct child restraints for your child's age and size. See the vehicle's Owners Manual and child safety seat instructions for more safety information.)
 - Brake/transmission shift interlock, for automatic transmissions
 - Daytime Running Lamps

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.0, Data updated 12/11/2007 11:05:00 AM

©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 19, 2007 4:01:47 PM

Page 7



APPENDIX B

TRUCK QUESTIONNAIRE FORMS

ALL BIDDERS MUST COMPLETE AND RETURN A QUESTIONNAIRE FORM WITH THE BID FOR EACH TRUCK ITEM TO BE CONSIDERED FOR AWARD OF THAT ITEM. Bids submitted without an adequately completed questionnaire form for EACH TRUCK ITEM will not be considered for award of that item. It is the responsibility of each bidder to copy this form in sufficient quantity to submit to Purchasing Operations prior to the scheduled bid due date. A single form may apply to more than one item, simply list the item numbers to which the questionnaire applies in the appropriate space. If part of the questionnaire does not apply, simply indicate "not applicable" in those spaces.

NAME OF BIDDER: Red Holman Pontiac GMC ITEM NO(s). Spec # 3958-0108

MAKE OF TRUCK: GMC MODEL: Savana TG 33903 GVWR 12300 lbs.

PAYLOAD: 7401 # W.B. 177" ✓ C.A. 118" C.E. 186.50"

ENGINE: (GAS - DIESEL) Gas MAKE: Gm MODEL: LY6, 6.0 SAE H.P. 323 ✓

FUEL TANK(S) CAPACITY: 57 (GALS. TOTAL) TRANSMISSION: Gm Hydramatic MT1 - 4spd ✓

SPRING CAP. @ GROUND EACH: FRONT TBD lbs. REAR TBD lbs. AUX. N/A lbs.

AXLES: FRONT TBD lbs. REAR TBD lbs. REAR RATIO 4.10

ALTERNATOR: 145 amps. BATTERY 600 cca.

TIRE SIZE: FRONT (T225/75R16E PR REAR (T225/75R16E PR SINGLE _____ DUAL M&S _____

TIRE: MAKE TBD STYLE NO. TBD MFG. CODE XHF

HOIST: MAKE N/A MODEL N/A INSTALLING CO. N/A

BODY: MAKE N/A MODEL N/A INSTALLING CO. N/A

POWER LIFT GATE: MAKE N/A MODEL N/A CAPACITY N/A lbs.

PLATFORM SIZE: N/A

OTHER EQUIPMENT INSTALLED BY BODY EQUIPMENT SUPPLIER AND/OR COMMENTS

This information must be returned with the bid document to Purchasing Operations, on or before the bid due date and time. However, if returned separately, it must be received by Purchasing Operations on or before the bid due date and time, and must comply with the sealed bid instructions as outlined in the ITB.

TRUCK: CUT-AWAY VAN AND BODY DUAL REAR WHEEL

(G.V.W.R. 14,000 lbs., min.)*

MODEL-2008 CURRENT NEW

	CHEV/ GMC <u>C4V042</u>	FORD <u>E-450 Cut-Away</u>
Wheel base (inches)	184	158 for (14' & 15' body)
Engine: Gasoline	8.1L	6.8L
Type & No. of Cylinders	V-8	V-10
Net H.P.-S.A.E.	325	305
Transmission: Automatic		
Axle, Min. Cap.-lbs.		
Front	7,000	5,000
Rear	11,000	9,500
Springs, Min. Cap. At Ground		
Front-lbs. Each	3,500	2,500
Rear-lbs. Each	5,500	4,750

Tires, Truck, Tubeless, Radial, to meet G.V.W.R. Rear duals, Mud and Snow or All Season.

*See Mich. SPEC. # 3958-0102 or 3958-0103 for body

TO BE STANDARD FACTORY EQUIPPED AS FOLLOWS:

The items listed below are to be supplied on all trucks, even though they may be optional with the manufacturer. Therefore, these specifications are to be furnished on all vehicles:

- 12 Volt auxiliary outlet
- Air Conditioning - All trucks
- Anti-freeze protection, to -30°F.
- Arm Rest-Driver's side.
- Color-Manufacturers Standard to be selected.
- Coolant System-Maximum Size Available, including the Heaviest Duty Radiator
- Dome Light.
- Electric wiring-All wiring passing through holes in metal or non-metal wearing surfaces, which could cause wear of the insulation, shall be adequately protected by rubber or plastic grommets, and/or non-metallic conduit. Ends of all wires shall be adequately anchored to prevent loosening.
- Frame length-on all body installations without hoists the cab to end of frame length shall be the same length as the body being mounted, plus the length of any setback.

- ☑ Fuel Tanks, Diesel, with sending unit and magnetic drain plug, on all trucks over 21,000 G.V.W.R., painted Black and labeled "Diesel Fuel Only".
- ☑ Hub caps on all pickups and vans up to and including 10,000 G.V.W.R. If not available from dealer cap nuts shall be furnished.
- ☑ Keys-(2) sets with code numbers; shall be with vehicle at time of delivery.
- ☑ Mirrors-All trucks are to be equipped with R.H. and L.H. outside rear-view mirrors to comply with Michigan laws; all trucks up to and including 15,000 G.V.W.R. shall be equipped with inside rear-view mirror. In all cases, outside R.H. & L.H. rear view mirrors shall provide full vision past all body installations. Mirrors shall be of stainless steel or high impact plastic construction unless denoted otherwise in individual truck specifications. All West Coast Type or Below Eye Level Camper Style Mirrors shall have stainless steel or high impact plastic heads, brackets, and hardware.
- ☑ Mud flaps, Anti-Sail Type, when required, are to be plain, rubber 1/4" thick, without advertising on either side.
- ☑ Painting-preclean and metal prep, any bare metal surfaces prior to applying a compatible red oxide or zinc chromate primer. When painting over a manufacturer's standard paint, metal prepping and primer may be omitted, provided an acceptable bond can be achieved.
- ☑ Equipment mounting- when mounting equipment on truck cab and chassis, all holes shall be drilled or punched. There shall be no flame cutting or welding on the frame side rails.
- ☑ Paint codes-factory paint codes shall be furnished with all vehicles; for all after market painting both the brand and paint code shall be furnished.
- ☑ Pre-delivery inspection and servicing.
- ☑ Radio - AM/FM Manufacturers Standard, Factory Installed
- ☑ Seat Belts with Shoulder Harness (3-Point Restraint System for Driver & Passenger)
- ☑ Seats-Split Bench type, unless otherwise specified
- ☑ Shock absorbers-(Heaviest Duty Available), front all trucks. Rear, up to and including 15,000 G.V.W.R.
- ☑ Spare tire, or Rim, not to be furnished unless specified. If specified, tires to be of same mfg., tread design to be same as front tires.
- ☑ Speed Control, Factory Installed
- ☑ Steering-Power, Tilt Wheel
- ☑ Sun visors-dual.
- ☑ Jack-Furnish on trucks up to and including 12,000 G.V.W.R.
- ☑ Windshield wipers-dual, intermittent speed electric, with automatic type washers.

All items removed for installation of optional equipment shall be returned to the State of Michigan.

TO BE EQUIPPED IN COMPLIANCE WITH ALL APPLICABLE FEDERAL MOTOR VEHICLE SAFETY STANDARDS AND REGULATIONS. ALL VEHICLES MUST BE EQUIPPED TO COMPLY WITH ALL REQUIREMENTS OF THE MICHIGAN MOTOR VEHICLE CODE.

- **Delete: On GM vehicles, OnStar and XM radio are deleted.**

ADDITIONAL OPTIONS:

These options are in addition to the options listed above as “STANDARD FACTORY EQUIPPED” and are to be included on this vehicle.

- Alternator-80 amp., min.
- Battery 12 Volt; 600 CCA, minimum
- Brakes-Power
- Front Fender splash guards
- Fuel capacity-largest available from mfg.
- Gauges-temperature, oil pressure, and amp meter or volt meter.
- Mirrors-Rear View, Inside. Outside R.H. and L.H. shall provide full Vision past body installation.
- Mirror shall be duplex head; 1 convex, 1 standard glass, with stainless steel or powder coated steel heads, brackets, and hardware. GMC: Composite Heads
- Spare Wheel and Tire GMC: Spare wheel only – Tire not available
- Steering-Power
- Wrench-Wheel GMC: No wrench available

ADDITIONAL MDOT OPTIONS: (Note: These options are not included in the MiDEAL price)

These options are in addition to the options listed above as “STANDARD FACTORY EQUIPPED” and are to be included on this MDOT vehicle.

- Keys – (1) additional set (total of 3 sets) with code numbers; shall be with the vehicle at the time of delivery.
- Seats-High Back, Driver and Passenger

PRICING SHEET

<u>TRUCK: CUT-AWAY VAN AND BODY DUAL REAR WHEEL</u> (G.V.W.R. 14,000 lbs., min.)* Mich. Spec. #3958-0109	
Standard Equipped Per above Specification (Including options as specified above)	Standard Equipped Cost
Make: GMC Model: C4500 Cutaway F.O.B. - Dealership Delivery Cost Per Mile \$1.50	\$22,776.00*
Final Point of Assembly: Flint, MI	
<u>Dealer Information</u>	
Dealer Name: Red Holman Pontiac GMC	
Street Address: 35300 Ford Road	
City: Westland	State: MI Zip: 48185
Contact Name: Albert Li	
Telephone: (800) 482-3032	
Cell: (734) 637-6643	
E-mail: aclixx@hotmail.com	

*Please Note: A vehicle order confirmation sheet is included for each vehicle. These documents shall include all the "standard options" as listed for the State of Michigan standard specification.

Vehicle Order Confirmation Sheet
 Spec # 3958-0109

Prepared By:
 Albert Li
 Red Holman Pontiac GMC
 35300 Ford Rd
 Westland, MI 48185
 Phone: (734) 721-1144
 Fax: (734) 721-1780
 Email: aclixx@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

SELECTED MODEL & OPTIONS

SELECTED MODEL - 2008 Fleet/Non-Retail TC4V042 Commercial Cutaway

<u>Code</u>	<u>Description</u>	<u>MSRP</u>
TC4V042	2008 GMC TC4500 Commercial Cutaway	\$29,290.00

SELECTED VEHICLE COLORS - 2008 Fleet/Non-Retail TC4V042 Commercial Cutaway

<u>Code</u>	<u>Description</u>
69V	Interior: Very Dark Pewter
50U	Exterior 1: Summit White
50L	Exterior 2: Summit White

SELECTED OPTIONS - 2008 Fleet/Non-Retail TC4V042 Commercial Cutaway

CATEGORY

<u>Code</u>	<u>Description</u>	<u>MSRP</u>
PREFERRED EQUIPMENT GROUP		
C4V042	CUSTOM/BASE MODEL	\$0.00
GASOLINE ENGINE		
LRW	VORTEC 8.1L MD GASOLINE V8, 325 HP (239 KW) @ 4000 RPM AND 450 LB-FT TORQUE (610 N-M) @ 2800 RPM.	\$0.00
GVWR		
C7R	16,500 LBS. (7484 KG) CAPACITY	\$0.00
EMISSION		
FE9	FEDERAL REQUIREMENTS	INC
ALTERNATOR		
KG4	AD244, DELCO-REMY 150-AMP MAXIMUM	\$0.00
BATTERY		
TM1	SINGLE AC DELCO, 600 CCA, 12V	\$0.00
EXHAUST SYSTEM		
N1B	SIDE EXIT FORWARD OF RIGHT REAR WHEELS	INC

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.0, Data updated 12/11/2007 11:05:00 AM
 ©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 19, 2007 7:09:50 PM

Page 1

Prepared By:
 Albert Li
 Red Holman Pontiac GMC
 35300 Ford Rd
 Westland, MI 48185
 Phone: (734) 721-1144
 Fax: (734) 721-1780
 Email: acli@hotmai.com

2008 Fleet/Non-Retail GMC TC4500

SELECTED MODEL & OPTIONS

SELECTED OPTIONS - 2008 Fleet/Non-Retail TC4V042 Commercial Cutaway

CATEGORY

<u>Code</u>	<u>Description</u>	<u>MSRP</u>
POWER TAKE OFF		
PTX	OPTION PTO NOT REQUIRED	\$0.00
TRANSMISSION		
MBV	AUTOMATIC, ALLISON 1000 HS/RDS SERIES 6-SPEED	\$0.00
TRANSMISSION FLUID		
MBT	TRANSYND SYNTHETIC AUTOMATIC TRANSMISSION FLUID	INC
FRONT AXLE		
FM7	7000 LBS. (3175 KG) CAPACITY	INC
FRONT SUSPENSION		
FK6	TAPERED LEAF, 7000 LBS. (3175 KG) CAPACITY	INC
FRONT WHEEL		
Q91	19.5" X 6.0" (49.5 CM X 15.2 CM), STEEL DISC	INC
FRONT TIRE		
XTN	225/70R19.5F	\$0.00
FRONT TIRE BRAND		
R4A	GOODYEAR	\$0.00
FRONT TIRE TREAD		
R3C	PREMIUM, HIGHWAY	\$0.00
SINGLE SPEED REAR AXLE		
GL4	SINGLE SPEED, 11,000 LBS. (4990 KG) CAPACITY	\$0.00
AXLE RATIO		
058	5.13:1	INC
REAR SUSPENSION		
GR3	MULTI-LEAF, 11,000 LBS. (4990 KG) CAPACITY	INC
BOLTED OR RIVETED SUSPENSION		
EV8	REAR SUSPENSION BRACKETS ARE RIVETED TO FRAME IN LIEU OF BOLTS	\$0.00
REAR SHOCK ABSORBER		

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.0, Data updated 12/11/2007 11:05:00 AM
 ©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 19, 2007 7:09:50 PM

Page 2

Prepared By:
 Albert Li
 Red Holman Pontiac GMC
 35300 Ford Rd
 Westland, MI 48185
 Phone: (734) 721-1144
 Fax: (734) 721-1780
 Email: aclbox@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

SELECTED MODEL & OPTIONS

SELECTED OPTIONS - 2008 Fleet/Non-Retail TC4V042 Commercial Cutaway

CATEGORY

<u>Code</u>	<u>Description</u>	<u>MSRP</u>
REAR SHOCK ABSORBER		
SAN	REAR SHOCK ABSORBER NOT DESIRED	\$0.00
REAR WHEEL		
Q92	19.5" X 6.0" (49.5 CM X 15.2 CM), STEEL DISC	INC
REAR TIRE		
YTN	225/70R19.5F	\$0.00
REAR TIRE BRAND		
S4A	GOODYEAR	\$0.00
REAR TIRE TREAD		
S3H	HIGHWAY TRACTION	\$0.00
SPARE WHEEL		
SNF	FRONT	\$128.00
WHEELBASE		
EC2	184" (467.4 CM)	\$112.00
FUEL TANK		
NH4	SINGLE, 40-GALLON (151L) FUEL CAPACITY	INC
DRIVER CONVENIENCE PACKAGES		
ZQ3	DRIVER CONVENIENCE PACKAGE	\$245.00
MISCELLANEOUS CAB EQUIPMENT		
N33	TILT-WHEEL ADJUSTABLE STEERING	INC
K34	CRUISE CONTROL,	INC
AIR CONDITIONING		
C60	AIR CONDITIONING	\$852.00
INSIDE REARVIEW MIRRORS		
D36	INSIDE DAY/NIGHT REARVIEW MIRROR	\$19.00
DRIVER SEAT		
AS4	HIGH-BACK BUCKET, FIXED HEIGHT, MANUAL ADJUSTER	INC
PASSENGER SEAT		

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.0, Data updated 12/11/2007 11:05:00 AM
 ©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 19, 2007 7:09:50 PM

Page 3

Prepared By:
 Albert Li
 Red Holman Pontiac GMC
 35300 Ford Rd
 Westland, MI 48185
 Phone: (734) 721-1144
 Fax: (734) 721-1780
 Email: acli@hotmai.com

2008 Fleet/Non-Retail GMC TC4500

SELECTED MODEL & OPTIONS

SELECTED OPTIONS - 2008 Fleet/Non-Retail TC4V042 Commercial Cutaway

CATEGORY

<u>Code</u>	<u>Description</u>	<u>MSRP</u>
PASSENGER SEAT		
AE1	HIGH-BACK BUCKET, FIXED HEIGHT, MANUAL BACK ANGLE ADJUSTER	INC
AIRBAGS		
AL3	SUPPLEMENTAL INFLATABLE RESTRAINTS NOT INCLUDED	INC
RADIO		
UM7	DELCO AM-FM STEREO RADIO	\$150.00
EXTERIOR MIRRORS		
DB5	MANUAL, 102" (259 CM) WIDE LOAD, INTEGRAL ARM, INTEGRAL CONVEX MIRROR	INC
PAINT		
ZY1	SOLID NON-METALLIC PAINT	INC
INTERIOR TRIM		
69I	VERY DARK PEWTER	INC
SEAT TRIM		
_V	VINYL SEAT TRIM	INC
ADDITIONAL OPTIONS		
VQ1	FLEET PROCESSING OPTION	\$0.00
OPTIONS TOTAL		\$1,506.00

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.0, Data updated 12/11/2007 11:05:00 AM
 ©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 19, 2007 7:09:50 PM

Page 4

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclbx@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC4V042 Commercial Cutaway

EXTERIOR

- Paint scheme, solid, upper color, Summit White
- Paint scheme, solid, lower color, Summit White
- Exterior roof drip moldings
- Bumper, front, steel, 96" (243.8 cm) wide - styled to minimized wall to wall turn diameter painted argent
- Steps under cab doors
- Front mud flaps
- Integral grille and fenders - The grille is the same color as hood with single halogen headlamps.
- Roof marker lamps
- Daytime running lamps
- Windows, Solar-Ray tinted. Light tinted windshield and side window glass with light transmissivity of 70%
- Mirrors, manual, 102" (259 cm) wide load, integral arm, integral convex mirror - black molded composite 12" x 7" (30.5 cm x 17.8 cm) with 6" x 7" (15.2 cm x 17.8 cm) convex section
- Windshield wipers, 2-speed and intermittent, with pulse washers
- Provisions for mounting front license plate
- Positive door stops

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.0, Data updated 12/11/2007 11:05:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 19, 2007 7:09:50 PM

Page 5

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclixx@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC4V042 Commercial Cutaway

INTERIOR

- Seat, driver, high-back bucket, fixed height, manual adjuster - storage in the seat riser with a small lip at the front to stop contents from sliding out
- Seat, passenger, high-back bucket, fixed height, manual back angle adjuster - storage in the seat riser with a small lip at the front to stop contents from sliding out
- Seat trim, vinyl, Very Dark Pewter
- Interior trim, Very Dark Pewter (Requires 69V Very Dark Pewter vinyl or 69C Very Dark Pewter cloth)
- Trim console - located next to driver's seat and two cupholders
- Molded vinyl floor covering
- Steering wheel 16"
- Two sided single common key for doors and ignition
- Headlamp warning buzzer
- Warning tone, key-in-ignition
- Tachometer
- Electronic engine hour meter
- Engine "Check Gauges" telltale light and buzzer, oil pressure gauge
- Gauges, low oil pressure and coolant level, high coolant and engine oil temperature
- Vinyl door trim panels - with storage pocket on front doors, beverage holders, and reflector on all doors
- Stepwell storage areas at each door front and rear. Includes storage cover.
- Cloth headliner
- Sunshades, passenger side and driver side, vinyl-covered
- Coat hooks (2) located on cab back panel
- Provisions for stereo - Includes AM/FM antenna, lead wiring for speakers, and separate door chime module (N/A with ZQ2 power convenience option)
- Air conditioning not desired - this option should be ordered only when a customer does not require air conditioning
- Powerpoints - two in-cab power sources (in addition to optional cigarette lighter) for electrical plug-in accessories

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.0, Data updated 12/11/2007 11:05:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 19, 2007 7:09:50 PM

Page 6

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclix@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC4V042 Commercial Cutaway

- Underhood bodybuilder connections accessory power supply - Provides 12V power supply from the battery with two separate 30 amp fused circuits

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.0, Data updated 12/11/2007 11:05:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 19, 2007 7:09:50 PM

Page 7

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclix@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC4V042 Commercial Cutaway

MECHANICAL

- GVWR, 16,500 lbs. (7484 kg) capacity - GCWR limited to 24,000 lb. (10,866 kg) (Requires FM7 7000 lbs. (3175 kg) front axle) NOTE: Trucks that are used primarily to tow a trailer may be liable to Federal Excise Tax (FET). A New Law (Highway Transportation Bill HR3) was passed on August 10, 2005 - Check with IRS for guidelines
- Engine, Vortec 8.1L MD gasoline V8, 325 hp (239 kw) @ 4000 rpm and 450 lb-ft torque (610 N-m) @ 2,800 rpm. - Maximum engine speed 5000 rpm. Oil Level Sensor: Warning sensor for low oil levels
- Air cleaner, dry type
- Cooling, anti-freeze protection temperature - -40 degrees F (-40 degrees C)
- Road speed governor, controlled by the speed rating of the tires ordered which will be less than or equal to 85 mph (137 kph)
- Alternator, AD244 Delco-Remy 150-amp maximum (N/A with ANM Fire and Rescue or YF2 Ambulance Packages)
- Battery, single AC Delco, 600 CCA, 12V - 115-minute reserve capacity @ 27 degrees C, 600 CCA @ -18 degrees C grounded directly to starter, (Requires gasoline engine)
- Exhaust, side exit forward of right rear wheels. With diesel engines, oxidation catalyst, diesel particulate filter and exhaust gas cooler. (N/A with ANC shuttle bus or B3D school bus package)
- Option PTO not required - This option should only be ordered when a customer specifically does not require an electric hand throttle for use with power-take-off provisions. (Note: Will delete transmission PTO gear.)
- Transmission, automatic, Allison 1000 HS/RDS Series 6-speed - With parking pawl and column shift, includes 4th Generation Electronic Controls and 0.61 overdrive. Torque Rating: 660 lb-ft (895 N-m) with shift energy management. Available with a Gross Vehicle Weight up to 19,500 lbs. (8845 kg) and a Gross Combination Weight Rating up to 26,000 lbs. (11,790 kg). To include PTO gear, please order with RPO PTO for Allison 1000 RDS Rugged Duty Series transmission. Includes transmission-oil cooler located inside radiator. With Option PTX the truck will be equipped with the Allison 1000 HS Highway Series transmission. (N/A with ANM Fire and Rescue or YF2 Ambulance Package)
- TranSynd synthetic automatic transmission fluid
- Front axle, 7000 lbs. (3175 kg) capacity - I-beam Wide-trac. Up to 53 degree turn angle, includes 4-piston brake apply callipers. Steering Gear Series: ZF8014
- Front suspension, tapered leaf, 7000 lbs. (3175 kg) capacity (includes stabilizer)
- Front shock absorber, diameter 1.375" (35mm)
- Front stabilizer bar, 2" x 2" square tube (5 cm x 5 cm)

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.0, Data updated 12/11/2007 11:05:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.
Customer File:

December 19, 2007 7:09:50 PM

Page 8

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclix@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC4V042 Commercial Cutaway

- Front wheels, 19.5" x 6.0" (49.5 cm x 15.2 cm), steel disc - 8-hole. 7280 lbs. (3302 kg) capacity (N/A with ANC Shuttle Bus or B3D School Bus Packages)
- Front tire size, 225/70R19.5F - 7280 lbs. (3802 kg) capacity, (With R4A Goodyear or R4L Michelin requires R3C front premium highway tread)
- Front tire manufacturer code, Goodyear (Requires S4A Goodyear)
- Front tread, premium, highway (Requires R4A Goodyear or R4L Michelin)
- Rear axle, single speed, 11,000 lbs. (4990 kg) capacity - full floating, includes 2-piston brake applied calipers
- Rear wheel drive
- Rear axle ratio, 5.13:1 (Requires gasoline engine)
- Rear suspension, multi-leaf, 11,000 lbs. (4990 kg) capacity (Requires GL4 single speed rear axle)
- Rear suspension brackets are riveted to frame in lieu of bolts
- Rear shock absorber not desired (N/A with tapered leaf springs)
- Rear wheels, 19.5" x 6.0" (49.5 cm x 15.2 cm), steel disc - 8-hole. 14,560 lbs (6604 kg) capacity (N/A with ANC shuttle bus or B3D school bus packages)
- Rear tire size, 225/70R19.5F - 13,660 lbs. (6196 kg) capacity, (With S4A Goodyear, requires S3C rear premium highway tread or S3H rear traction tread; with S4L Michelin, requires S3C rear premium highway tread or S3J rear highway traction tread)
- Rear tire manufacturer code, Goodyear (Requires R4A Goodyear)
- Rear tread, premium, highway (Requires S4A Goodyear or S4L Michelin)
- Wheelbase, 166" (421.6 cm) - with 100" (254 cm) CA with 171" (434.3 cm) CE. Includes a 6 mm 80,000 psi (551,600 kPa) yield strength, steel frame, RBM: 610,400 Section Modulus 7.63
- Frame, 6mm - 80,000 psi (551,600 kPa) yield strength, steel frame, RBM: 610,400 Section Modulus 7.63
- Fuel tank, single, 40-gallon (151L) fuel capacity - gas or diesel, located behind rear axle with fuel fill neck through frame rail and a black tethered fuel cap with gasoline engine and green un-tethered fuel cap with diesel engines. DRIVER SIDE FILL NECK ONLY. NO AUXILIARY PORTS. MINIMUM OVERHANG = 60" (5 FEET)
- Fuel sender assembly. Robust fuel pump
- Tethered fuel cap
- Steering, power - ZF variable ratio power

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.0, Data updated 12/11/2007 11:05:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 19, 2007 7:09:50 PM

Page 9

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclix@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC4V042 Commercial Cutaway

- Brakes, front, power, 4-wheel disc, 4 channel ABS 2-piston - (See front axle options for more detail)
- Brakes, rear, power, 4-wheel disc, 4 channel ABS 2-piston - (See rear axle options for more detail)
- Park brake, foot pedal operated transmission mounted drum brake

SAFETY

- 4-wheel disc, 4-channel ABS
- Air bags, Supplemental Inflatable Restraints not included.
- Seat belt warning indicator
- Daytime running lamps

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.0, Data updated 12/11/2007 11:05:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 19, 2007 7:09:50 PM

Page 10

APPENDIX B

TRUCK QUESTIONNAIRE FORMS

ALL BIDDERS MUST COMPLETE AND RETURN A QUESTIONNAIRE FORM WITH THE BID FOR EACH TRUCK ITEM TO BE CONSIDERED FOR AWARD OF THAT ITEM. Bids submitted without an adequately completed questionnaire form for EACH TRUCK ITEM will not be considered for award of that item. It is the responsibility of each bidder to copy this form in sufficient quantity to submit to Purchasing Operations prior to the scheduled bid due date. A single form may apply to more than one item, simply list the item numbers to which the questionnaire applies in the appropriate space. If part of the questionnaire does not apply, simply indicate "not applicable" in those spaces.

NAME OF BIDDER: Red Holman Pontiac GMC ITEM NO(s): Spec # 3958-0109

MAKE OF TRUCK: GMC MODEL: C4500 TC4V042 GVWR 16500 lbs.

PAYLOAD: 9051 # ✓ W.B. 184" ✓ C.A. 118" C.E. 202"

ENGINE: (GAS - DIESEL) Gas ✓ MAKE: Gm MODEL: LRW, 8.1 ✓ SAE H.P. 325 ✓

FUEL TANK(S) CAPACITY: 40 (GALS. TOTAL) TRANSMISSION: Allison 1000 MBV 6-spd ✓

SPRING CAP. @ GROUND EACH: FRONT 3500 ✓ lbs. REAR 5500 ✓ lbs. AUX. N/A lbs.

AXLES: FRONT 7000 ✓ lbs. REAR 11000 ✓ lbs. REAR RATIO 5.13

ALTERNATOR: 150 ✓ amps. BATTERY 600 ✓ cca.

TIRE SIZE: FRONT 225/70R19.5 FPR REAR 225/70R19.5 FPR SINGLE _____ DUAL _____ ✓ M&S _____

TIRE: MAKE Goodyear STYLE NO. TBD MFG. CODE XTN/YTN

HOIST: MAKE N/A MODEL N/A INSTALLING CO. N/A

BODY: MAKE N/A MODEL N/A INSTALLING CO. N/A

POWER LIFT GATE: MAKE N/A MODEL N/A CAPACITY N/A lbs.

PLATFORM SIZE: N/A

OTHER EQUIPMENT INSTALLED BY BODY EQUIPMENT SUPPLIER AND/OR COMMENTS

This information must be returned with the bid document to Purchasing Operations, on or before the bid due date and time. However, if returned separately, it must be received by Purchasing Operations on or before the bid due date and time, and must comply with the sealed bid instructions as outlined in the ITB.

TRUCK: CAB AND CHASSIS
 (G.V.W.R. 14,500 LBS., min.)

MODEL-2008 CURRENT NEW

	CHEVY/ GMC	FORD
	C4500	
	<u>C4C042</u>	<u>F-450SD</u>
G.V.W.R. (lbs.)	16,500	16,000
Wheelbase (inches)	128	140.8
C.A. (inches)	60	60
Engine: Gasoline	8100	Triton
Type & No. of Cylinders	V-8	V-10
Net H.P.-S.A.E.	325	362

Transmission: Automatic:
 with maximum capacity transmission oil cooler, Factory installed.

Axle, Min. Cap.-lbs.		
Front	7,000	7,000
Rear	11,000	12,000
Springs, Min. Cap. at Ground		
Front-lbs. each	3,500	2,400
Rear-lbs. each	5,500	6,000

Tires, Truck, Tubeless, Radial, to meet G.V.W.R. Rear duals, mud and snow.

TO BE STANDARD FACTORY EQUIPPED AS FOLLOWS:

The items listed below are to be supplied on all trucks, even though they may be optional with the manufacturer. Therefore, these specifications are to be furnished on all vehicles:

- 12 Volt auxiliary outlet
- Air Conditioning - All trucks
- Anti-freeze protection, to -30°F.
- Arm Rest-Driver's side.
- Color-Manufacturers Standard to be selected.
- Coolant System-Maximum Size Available, including the Heaviest Duty Radiator
- Dome Light.
- Electric wiring-All wiring passing through holes in metal or non-metal wearing surfaces, which could cause wear of the insulation, shall be adequately protected by

rubber or plastic grommets, and/or non-metallic conduit. Ends of all wires shall be adequately anchored to prevent loosening.

- ☑ Frame length-on all body installations without hoists the cab to end of frame length shall be the same length as the body being mounted, plus the length of any setback.
- ☑ Fuel Tanks, Diesel, with sending unit and magnetic drain plug, on all trucks over 21,000 G.V.W.R., painted Black and labeled "Diesel Fuel Only".
- ☑ Hub caps on all pickups and vans up to and including 10,000 G.V.W.R. If not available from dealer cap nuts shall be furnished.
- ☑ Keys-(2) sets with code numbers; shall be with vehicle at time of delivery.
- ☑ Mirrors-All trucks are to be equipped with R.H. and L.H. outside rear-view mirrors to comply with Michigan laws; all trucks up to and including 15,000 G.V.W.R. shall be equipped with inside rear-view mirror. In all cases, outside R.H. & L.H. rear view mirrors shall provide full vision past all body installations. Mirrors shall be of stainless steel or high impact plastic construction unless denoted otherwise in individual truck specifications. All West Coast Type or Below Eye Level Camper Style Mirrors shall have stainless steel or high impact plastic heads, brackets, and hardware.
- ☑ Mud flaps, Anti-Sail Type, when required, are to be plain, rubber 1/4" thick, without advertising on either side.
- ☑ Painting-preclean and metal prep, any bare metal surfaces prior to applying a compatible red oxide or zinc chromate primer. When painting over a manufacturer's standard paint, metal prepping and primer may be omitted, provided an acceptable bond can be achieved.
- ☑ Equipment mounting- when mounting equipment on truck cab and chassis, all holes shall be drilled or punched. There shall be no flame cutting or welding on the frame side rails.
- ☑ Paint codes-factory paint codes shall be furnished with all vehicles; for all after market painting both the brand and paint code shall be furnished.
- ☑ Pre-delivery inspection and servicing.
- ☑ Radio - AM/FM Manufacturers Standard, Factory Installed
- ☑ Seat Belts with Shoulder Harness (3-Point Restraint System for Driver & Passenger)
- ☑ Seats-Split Bench type, unless otherwise specified
- ☑ Shock absorbers-(Heaviest Duty Available), front all trucks. Rear, up to and including 15,000 G.V.W.R.
- ☑ Spare tire, or Rim, not to be furnished unless specified. If specified, tires to be of same mfg., tread design to be same as front tires.
- ☑ Speed Control, Factory Installed
- ☑ Steering-Power, Tilt Wheel
- ☑ Sun visors-dual.
- ☑ Jack-Furnish on trucks up to and including 12,000 G.V.W.R.
- ☑ Windshield wipers-dual, intermittent speed electric, with automatic type washers.

All items removed for installation of optional equipment shall be returned to the State of Michigan.

TO BE EQUIPPED IN COMPLIANCE WITH ALL APPLICABLE FEDERAL MOTOR VEHICLE SAFETY STANDARDS AND REGULATIONS. ALL VEHICLES MUST BE EQUIPPED TO COMPLY WITH ALL REQUIREMENTS OF THE MICHIGAN MOTOR VEHICLE CODE.

- **Delete: On GM vehicles, OnStar and XM radio are deleted.**

ADDITIONAL OPTIONS:

These options are in addition to the options listed above as “STANDARD FACTORY EQUIPPED” and are to be included on this vehicle.

- Alternator-95 amp., min.
- Battery-12 Volt, 600 CCA, minimum.
- Brakes-Power.
- Fuel capacity-largest available from mfg.
- Mirrors-Rear View, Inside. Outside R.H. and L.H., below eye level, extended reach, swing away type, 51 sq. in., minimum. Installed, with stainless steel or powder coated steel heads, brackets, and hardware. GMC: Composite Head
- Spare tire and wheel. GMC: Spare Wheel only – No tire avail
- Steering-Power.
- Wrench-wheel. GMC: Wrench not available

ADDITIONAL MDOT OPTIONS: (Note: These options are not included in the MiDEAL price)

These options are in addition to the options listed above as “STANDARD FACTORY EQUIPPED” and are to be included on this MDOT vehicle.

- Axle Rear Limited slip
- Keys – (1) additional set (total of 3 sets) with code numbers; shall be with the vehicle at the time of delivery.
- Switches, upfitter for auxillary – GMC: Panel only, switches avail from body company
- Throttle, Electronic, High Idle Engine RPM Control.
- Towing package: Heaviest duty available from manufacturer (MDOT) GMC: Standard
- Trailer brake controller, factory installed GMC: Not available on chassis
- Trailer Hitch, Class III Receiver Type GMC: Not available on chassis

PRICING SHEET

<u>TRUCK: CAB AND CHASSIS</u> (G.V.W.R. 14,500 LBS., min.) Mich. Spec. #3958-0110	
Standard Equipped Per above Specification (Including options as specified above)	Standard Equipped Cost
Make: GMC Model: C4500 <i>F.O.B. - Dealership</i> Delivery Cost Per Mile \$1.50	\$22,661.00*
Final Point of Assembly: Flint, MI	
<u>Dealer Information</u>	
Dealer Name: Red Holman Pontiac GMC	
Street Address: 35300 Ford Road	
City: Westland	State: MI Zip: 48185
Contact Name: Albert Li	
Telephone: (800) 482-3032	
Cell: (734) 637-6643	
E-mail: aclixx@hotmail.com	

*Please Note: A vehicle order confirmation sheet is included for each vehicle. These documents shall include all the "standard options" as listed for the State of Michigan standard specification.

Vehicle Order Confirmation Sheet
 Spec # 3958-0110

Prepared By:
 Albert Li
 Red Holman Pontiac GMC
 35300 Ford Rd
 Westland, MI 48185
 Phone: (734) 721-1144
 Fax: (734) 721-1780
 Email: aclbx@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

SELECTED MODEL & OPTIONS

SELECTED MODEL - 2008 Fleet/Non-Retail TC4C042 Regular Cab 2WD

<u>Code</u>	<u>Description</u>	<u>MSRP</u>
TC4C042	2008 GMC TC4500 Regular Cab 2WD	\$28,890.00

SELECTED VEHICLE COLORS - 2008 Fleet/Non-Retail TC4C042 Regular Cab 2WD

<u>Code</u>	<u>Description</u>
-	Interior: No color has been selected.
-	Exterior 1: No color has been selected.
-	Exterior 2: No color has been selected.

SELECTED OPTIONS - 2008 Fleet/Non-Retail TC4C042 Regular Cab 2WD

<u>CATEGORY</u>		<u>MSRP</u>
<u>Code</u>	<u>Description</u>	
PREFERRED EQUIPMENT GROUP		
C4C042	CUSTOM/BASE MODEL	\$0.00
GASOLINE ENGINE		
LRW	VORTEC 8.1L MD GASOLINE V8, 325 HP (239 KW) @ 4000 RPM AND 450 LB-FT TORQUE (610 N-M) @ 2800 RPM.	\$0.00
GVWR		
C7R	16,500 LBS. (7484 KG) CAPACITY	\$0.00
EMISSION		
FE9	FEDERAL REQUIREMENTS	INC
ALTERNATOR		
KG4	AD244, DELCO-REMY 150-AMP MAXIMUM	\$0.00
BATTERY		
TM1	SINGLE AC DELCO, 600 CCA, 12V	\$0.00
EXHAUST SYSTEM		

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.0, Data updated 12/11/2007 11:05:00 AM
 ©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 19, 2007 7:36:58 PM

Page 1

Prepared By:
 Albert Li
 Red Holman Pontiac GMC
 35300 Ford Rd
 Westland, MI 48185
 Phone: (734) 721-1144
 Fax: (734) 721-1780
 Email: acli@hotmai.com

2008 Fleet/Non-Retail GMC TC4500

SELECTED MODEL & OPTIONS

SELECTED OPTIONS - 2008 Fleet/Non-Retail TC4C042 Regular Cab 2WD

<u>CATEGORY</u>		<u>MSRP</u>
<u>Code</u>	<u>Description</u>	
EXHAUST SYSTEM		
NB5	SINGLE HORIZONTAL-PASSENGER SIDE MOUNTED INSIDE FRAME RAIL	INC
POWER TAKE OFF		
PTX	OPTION PTO NOT REQUIRED	\$0.00
TRANSMISSION		
MBV	AUTOMATIC, ALLISON 1000 HS/RDS SERIES 6-SPEED	\$0.00
TRANSMISSION FLUID		
MBT	TRANSYND SYNTHETIC AUTOMATIC TRANSMISSION FLUID	INC
TRANSMISSION EQUIPMENT		
KNP	AUXILIARY TRANSMISSION OIL COOLER	\$95.00
FRONT AXLE		
FM7	7000 LBS. (3175 KG) CAPACITY	INC
FRONT SUSPENSION		
FK6	TAPERED LEAF, 7000 LBS. (3175 KG) CAPACITY	INC
FRONT WHEEL		
Q82	19.5" X 6.75" (49.5 CM X 17.1 CM), STEEL DISC	\$37.00
FRONT TIRE		
XTN	225/70R19.5F	\$0.00
FRONT TIRE BRAND		
R4A	GOODYEAR	\$0.00
FRONT TIRE TREAD		
R3C	PREMIUM, HIGHWAY	\$0.00
SINGLE SPEED REAR AXLE		
GL4	SINGLE SPEED, 11,000 LBS. (4990 KG) CAPACITY	INC
AXLE RATIO		
008	4.88:1	\$0.00
REAR SUSPENSION		

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.0, Data updated 12/11/2007 11:05:00 AM
 ©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 19, 2007 7:36:58 PM

Page 2

Prepared By:
 Albert Li
 Red Holman Pontiac GMC
 35300 Ford Rd
 Westland, MI 48185
 Phone: (734) 721-1144
 Fax: (734) 721-1780
 Email: acibx@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

SELECTED MODEL & OPTIONS

SELECTED OPTIONS - 2008 Fleet/Non-Retail TC4C042 Regular Cab 2WD

CATEGORY

<u>Code</u>	<u>Description</u>	<u>MSRP</u>
REAR SUSPENSION		
GR3	MULTI-LEAF, 11,000 LBS. (4990 KG) CAPACITY	INC
BOLTED OR RIVETED SUSPENSION		
EV8	REAR SUSPENSION BRACKETS ARE RIVETED TO FRAME IN LIEU OF BOLTS	\$0.00
REAR SHOCK ABSORBER		
SAN	REAR SHOCK ABSORBER NOT DESIRED	\$0.00
REAR WHEEL		
Q83	19.5" X 6.75" (49.5 CM X 17.1 CM), STEEL DISC	\$74.00
REAR TIRE		
YTN	225/70R19.5F	\$0.00
REAR TIRE BRAND		
S4A	GOODYEAR	\$0.00
REAR TIRE TREAD		
S3C	PREMIUM HIGHWAY	\$0.00
S3H	HIGHWAY TRACTION	\$0.00
SPARE WHEEL		
SNF	FRONT	\$128.00
WHEELBASE		
EC9	128" (325.1 CM)	\$0.00
FUEL TANK		
NG6	DUAL, TOTAL FUEL CAPACITY OF 40-GALLONS (151L)	\$122.00
DRIVER CONVENIENCE PACKAGES		
ZQ3	DRIVER CONVENIENCE PACKAGE	\$245.00
MISCELLANEOUS CAB EQUIPMENT		
N33	TILT-WHEEL ADJUSTABLE STEERING	INC
K34	CRUISE CONTROL,	INC
AIR CONDITIONING		

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.0, Data updated 12/11/2007 11:05:00 AM
 ©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 19, 2007 7:36:58 PM

Page 3

Prepared By:
 Albert Li
 Red Holman Pontiac GMC
 35300 Ford Rd
 Westland, MI 48185
 Phone: (734) 721-1144
 Fax: (734) 721-1780
 Email: acli@hotmai.com

2008 Fleet/Non-Retail GMC TC4500

SELECTED MODEL & OPTIONS

SELECTED OPTIONS - 2008 Fleet/Non-Retail TC4C042 Regular Cab 2WD

<u>CATEGORY</u>		<u>Code</u>	<u>Description</u>	<u>MSRP</u>
AIR CONDITIONING		C60	AIR CONDITIONING	\$852.00
INSIDE REARVIEW MIRRORS		D36	INSIDE DAY/NIGHT REARVIEW MIRROR	\$19.00
DRIVER SEAT		AS4	HIGH-BACK BUCKET, FIXED HEIGHT, MANUAL ADJUSTER	INC
PASSENGER SEAT		A59	TWO-PERSON, WITHOUT STORAGE	\$180.00
AIRBAGS		AL3	SUPPLEMENTAL INFLATABLE RESTRAINTS NOT INCLUDED	INC
RADIO		UM7	DELCO AM-FM STEREO RADIO	\$150.00
EXTERIOR MIRRORS		DB5	MANUAL, 102" (259 CM) WIDE LOAD, INTEGRAL ARM, INTEGRAL CONVEX MIRROR	INC
PAINT		ZY1	SOLID NON-METALLIC PAINT	INC
INTERIOR TRIM		69I	VERY DARK PEWTER	INC
SEAT TRIM		_V	VINYL SEAT TRIM	INC
ADDITIONAL OPTIONS		VQ1	FLEET PROCESSING OPTION	\$0.00
OPTIONS TOTAL				\$1,902.00

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.0, Data updated 12/11/2007 11:05:00 AM
 ©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 19, 2007 7:36:58 PM

Page 4

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclix@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC4C042 Regular Cab 2WD

EXTERIOR

- Paint scheme, solid, upper color, Summit White
- Paint scheme, solid, lower color, Summit White
- Exterior roof drip moldings
- Bumper, front, steel, 96" (243.8 cm) wide - styled to minimized wall to wall turn diameter painted argent
- Steps under cab doors
- Front mud flaps
- Integral grille and fenders - The grille is the same color as hood with single halogen headlamps.
- Roof marker lamps
- Daytime running lamps
- Windows, Solar-Ray tinted. Light tinted windshield and side window glass with light transmissivity of 70%
- Mirrors, manual, 102" (259 cm) wide load, integral arm, integral convex mirror - black molded composite 12" x 7" (30.5 cm x 17.8 cm) with 6" x 7" (15.2 cm x 17.8 cm) convex section
- Windshield wipers, 2-speed and intermittent, with pulse washers
- Provisions for mounting front license plate
- Positive door stops

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.0, Data updated 12/11/2007 11:05:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 19, 2007 7:36:58 PM

Page 5

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclix@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC4C042 Regular Cab 2WD

INTERIOR

- Seat, driver, high-back bucket, fixed height, manual adjuster - storage in the seat riser with a small lip at the front to stop contents from sliding out
- Seat, passenger, high-back bucket, fixed height, manual back angle adjuster - storage in the seat riser with a small lip at the front to stop contents from sliding out
- Seat trim, vinyl, Very Dark Pewter
- Interior trim, Very Dark Pewter (Requires 69V Very Dark Pewter vinyl or 69C Very Dark Pewter cloth)
- Trim console - located next to driver's seat and two cupholders
- Molded vinyl floor covering
- Steering wheel 16"
- Two sided single common key for doors and ignition
- Headlamp warning buzzer
- Warning tone, key-in-ignition
- Tachometer
- Electronic engine hour meter
- Engine "Check Gauges" telltale light and buzzer, oil pressure gauge
- Gauges, low oil pressure and coolant level, high coolant and engine oil temperature
- Vinyl door trim panels - with storage pocket on front doors, beverage holders, and reflector on all doors
- Stepwell storage areas at each door front and rear. Includes storage cover.
- Cloth headliner
- Sunshades, passenger side and driver side, vinyl-covered
- Coat hooks (2) located on cab back panel
- Provisions for stereo - Includes AM/FM antenna, lead wiring for speakers, and separate door chime module (N/A with ZQ2 power convenience option)
- Air conditioning not desired - this option should be ordered only when a customer does not require air conditioning
- Powerpoints - two in-cab power sources (in addition to optional cigarette lighter) for electrical plug-in accessories

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.0, Data updated 12/11/2007 11:05:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 19, 2007 7:36:58 PM

Page 6

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclix@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC4C042 Regular Cab 2WD

- Underhood bodybuilder connections accessory power supply - Provides 12V power supply from the battery with two separate 30 amp fused circuits

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.0, Data updated 12/11/2007 11:05:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 19, 2007 7:36:58 PM

Page 7

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclix@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC4C042 Regular Cab 2WD

MECHANICAL

- GWR, 16,500 lbs. (7484 kg) capacity - GCWR limited to 24,000 lb. (10,866 kg) (Requires FM7 7000 lbs. (3175 kg) front axle) NOTE: Trucks that are used primarily to tow a trailer may be liable to Federal Excise Tax (FET). A New Law (Highway Transportation Bill HR3) was passed on August 10, 2005 - Check with IRS for guidelines
- Engine, Vortec 8.1L MD gasoline V8, 325 hp (239 kw) @ 4000 rpm and 450 lb-ft torque (610 N-m) @ 2,800 rpm. - Maximum engine speed 5000 rpm. Oil Level Sensor: Warning sensor for low oil levels
- Air cleaner, dry type
- Cooling, anti-freeze protection temperature - -40 degrees F (-40 degrees C)
- Road speed governor, controlled by the speed rating of the tires ordered. - which will be less than or equal to 85 mph (137 kph); 80 mph (129 kph) with EC9 128" wheelbase/60" CA, ML6 manual transmission and 008 4.88 rear axle ratio; 75 mph (120 kph) with EC9 128" wheelbase/60" CA, M74 automatic transmission and HD2 rear axle
- Alternator, AD244 Delco-Remy 150-amp maximum (N/A with YW2 wrecker package)
- Battery, single AC Delco, 600 CCA, 12V - 115-minute reserve capacity @ 27 degrees C, 600 CCA @ -18 degrees C grounded directly to starter, (Requires gasoline engine; N/A with ANQ Snow Plow Prep package or YW2 Wrecker package)
- Exhaust, single horizontal - passenger side mounted inside frame rail, with gasoline engine stainless-steel exhaust with catalytic converter, with diesel engines, stainless-steel exhaust, oxidation catalyst, diesel particulate filter and exhaust gas cooler
- Option PTO not required - This option should only be ordered when a customer specifically does not require an electric hand throttle for use with power-take-off provisions. (Note: Will delete transmission PTO gear.)
- Transmission, automatic, Allison 1000 HS/RDS Series 6-speed - With parking pawl and column shift, includes 4th Generation Electronic Controls and 0.61 overdrive. Torque Rating: 660 lb-ft (895 N-m) with shift energy management. Available with a Gross Vehicle Weight up to 19,500 lbs. (8845 kg) and a Gross Combination Weight Rating up to 26,000 lbs. (11,790 kg). To include PTO gear, please order with RPO PTO for Allison 1000 RDS Rugged Duty Series transmission. Includes transmission-oil cooler located inside radiator. With Option PTX the truck will be equipped with the Allison 1000 HS Highway Series transmission. (N/A with ANM Fire and Rescue or YF2 Ambulance Package)
- TranSynd synthetic automatic transmission fluid
- Front axle, 7000 lbs. (3175 kg) capacity - I-beam Wide-trac. Up to 53 degree turn angle, includes 4-piston brake apply calipers. Steering Gear Series: ZF8014
- Front suspension, tapered leaf, 7000 lbs. (3175 kg) capacity (includes stabilizer)

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.0, Data updated 12/11/2007 11:05:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 19, 2007 7:36:58 PM

Page 8

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclibx@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC4C042 Regular Cab 2WD

- Front shock absorber, diameter 1.375" (35mm)
- Front stabilizer bar, 2" x 2" square tube (5 cm x 5 cm)
- Front wheels, 19.5" x 6.0" (49.5 cm x 15.2 cm), steel disc - 8-hole. 7280 lbs. (3302 kg) capacity
- Front tire size, 225/70R19.5F - 7280 lbs. (3802 kg) capacity, (With R4A Goodyear or R4L Michelin requires R3C front premium highway tread)
- Front tire manufacturer code, Goodyear (Requires S4A Goodyear)
- Front tread, premium, highway (Requires R4A Goodyear or R4L Michelin)
- Rear axle, single speed, 11,000 lbs. (4990 kg) capacity - full floating, Includes 2-piston brake applied calipers
- Rear wheel drive
- Rear axle ratio, 5.13:1 (Requires gasoline engine)
- Rear suspension, multi-leaf, 11,000 lbs. (4990 kg) capacity (Requires GL4 single speed rear axle)
- Rear suspension brackets are riveted to frame in lieu of bolts
- Rear shock absorber not desired (N/A with tapered leaf springs)
- Rear wheels, 19.5" x 6.0" (49.5 cm x 15.2 cm), steel disc - 8-hole. 14,560 lbs (6604 kg) capacity
- Rear tire size, 225/70R19.5F - 13,660 lbs. (6196 kg) capacity, (With S4A Goodyear, requires S3C rear premium highway tread or S3H rear traction tread; with S4L Michelin, requires S3C rear premium highway tread or S3J rear highway traction tread)
- Rear tire manufacturer code, Goodyear (Requires R4A Goodyear)
- Rear tread, premium, highway (Requires S4A Goodyear or S4L Michelin)
- Wheelbase, 128" (325.1 cm) - with 60" (152.4 cm) CA and 100" (254 cm) CE. Includes a 6 mm 80,000 psi (551,600 kPa) yield strength, steel frame, RBM: 610,400 Section Modulus 7.63 (Requires KYW 75 mph (120 kph) road speed governor and HD2 13,500 lbs. (6123 kg) capacity rear axle)
- Frame, 6mm - 80,000 psi (551,600 kPa) yield strength, steel frame, RBM: 610,400 Section Modulus 7.63
- Fuel tank, single, 25-gallon (95L) fuel capacity - gas or diesel located midship between the frame rails, with fuel fill neck through the frame rail (this option uses the mid-frame tank included in the NG6 dual tank option) Tethered fuel cap is black with gasoline engines, and green un-tethered fuel cap with diesel engines. MINIMUM OVERHANG = 36" (3 FEET) (Required in YW2 Wrecker Package, standard on 60" (152.4 cm) CA, optional on all other CA's)

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.0, Data updated 12/11/2007 11:05:00 AM

©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 19, 2007 7:36:58 PM

Page 9

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: acliix@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC4C042 Regular Cab 2WD

- Fuel sender assembly. Robust fuel pump
- Tethered fuel cap
- Steering, power - ZF variable ratio power
- Brakes, front, power, 4-wheel disc, 4 channel ABS 2-piston - (See front axle options for more detail)
- Brakes, rear, power, 4-wheel disc, 4 channel ABS 2-piston - (See rear axle options for more detail)
- Parking brake, hand lever operated transmission mounted drum brake

SAFETY

- 4-wheel disc, 4-channel ABS
- Air bags, Supplemental Inflatable Restraints not included.
- This vehicle does not include any air bags
- Seat belt warning indicator
- Daytime running lamps

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.0, Data updated 12/11/2007 11:05:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 19, 2007 7:36:58 PM

Page 10



APPENDIX B

TRUCK QUESTIONNAIRE FORMS

ALL BIDDERS MUST COMPLETE AND RETURN A QUESTIONNAIRE FORM WITH THE BID FOR EACH TRUCK ITEM TO BE CONSIDERED FOR AWARD OF THAT ITEM. Bids submitted without an adequately completed questionnaire form for EACH TRUCK ITEM will not be considered for award of that item. It is the responsibility of each bidder to copy this form in sufficient quantity to submit to Purchasing Operations prior to the scheduled bid due date. A single form may apply to more than one item, simply list the item numbers to which the questionnaire applies in the appropriate space. If part of the questionnaire does not apply, simply indicate "not applicable" in those spaces.

NAME OF BIDDER: Red Holman Pontiac GMC ITEM NO(s). Spec # 3958-0110
 MAKE OF TRUCK: GMC MODEL: C4500 TC4C042 GVWR 16500 lbs.
 PAYLOAD: 9207 W.B. 128" ✓ C.A. 60" ✓ C.E. 100" ✓
 ENGINE: (GAS - DIESEL) Gas MAKE: GM MODEL: LRW, 8.1 ✓ SAE H.P. 325 ✓
 FUEL TANK(S) CAPACITY: 40 (GALS. TOTAL) TRANSMISSION: Allison 1000M2V 6-spd
 SPRING CAP. @ GROUND EACH: FRONT 3500 ✓ lbs. REAR 5500 ✓ lbs. AUX. N/A lbs.
 AXLES: FRONT 7000 ✓ lbs. REAR 11000 ✓ lbs. REAR RATIO 4.88
 ALTERNATOR: 150 ✓ amps. BATTERY 600 ✓ cca. ✓
 TIRE SIZE: FRONT 225/70R19.5F PR REAR 225/70R19.5F PR SINGLE _____ DUAL ✓ M&S ✓
 TIRE: MAKE Goodyear STYLE NO. TBD MFG. CODE XTN/YTN
 HOIST: MAKE N/A MODEL N/A INSTALLING CO. N/A
 BODY: MAKE N/A MODEL N/A INSTALLING CO. N/A
 POWER LIFT GATE: MAKE N/A MODEL N/A CAPACITY N/A lbs.
 PLATFORM SIZE: N/A

OTHER EQUIPMENT INSTALLED BY BODY EQUIPMENT SUPPLIER AND/OR COMMENTS

This information must be returned with the bid document to Purchasing Operations, on or before the bid due date and time. However, if returned separately, it must be received by Purchasing Operations on or before the bid due date and time, and must comply with the sealed bid instructions as outlined in the ITB.

TRUCK: CAB AND CHASSIS REAR DUAL WHEELS
(G.V.W.R. 14,500 LBS., min.)

MODEL-2008 CURRENT NEW

	CHEVY/ GMC C4500 <u>C4C042</u>	FORD <u>F-450SD</u>	DODGE <u>DM4L63</u>
G.V.W.R. (lbs.)	16,500	16,000	16,000
Wheelbase (inches)	128	140.8	144.5
C.A. (inches)	60	60	60
Engine: Diesel	6.6L	6.4L	6.7L
Type & No. of Cylinders	V-8	V-8 Turbo	L-6 Turbo
Net H.P.-S.A.E.	300	325	305

Transmission: Automatic:
with maximum capacity transmission oil cooler, Factory installed.

Axle, Min. Cap.-lbs.			
Front	7,000	7,000	7,000
Rear	11,000	12,000	13,500
Springs, Min. Cap. at Ground			
Front-lbs. each	3,500	2,600	TBD
Rear-lbs. each	5,500	6,000	TBD

Tires, Truck, Tubeless, Radial, to meet G.V.W.R. Rear duals, mud and snow.

TO BE STANDARD FACTORY EQUIPPED AS FOLLOWS:

The items listed below are to be supplied on all trucks, even though they may be optional with the manufacturer. Therefore, these specifications are to be furnished on all vehicles:

- 12 Volt auxiliary outlet
- Air Conditioning - All trucks
- Anti-freeze protection, to -30°F.
- Arm Rest-Driver's side.
- Color-Manufacturers Standard to be selected.
- Coolant System-Maximum Size Available, including the Heaviest Duty Radiator
- Dome Light.
- Electric wiring-All wiring passing through holes in metal or non-metal wearing surfaces, which could cause wear of the insulation, shall be adequately protected by

rubber or plastic grommets, and/or non-metallic conduit. Ends of all wires shall be adequately anchored to prevent loosening.

- ☑ Frame length-on all body installations without hoists the cab to end of frame length shall be the same length as the body being mounted, plus the length of any setback.
- ☑ Fuel Tanks, Diesel, with sending unit and magnetic drain plug, on all trucks over 21,000 G.V.W.R., painted Black and labeled "Diesel Fuel Only".
- ☑ Hub caps on all pickups and vans up to and including 10,000 G.V.W.R. If not available from dealer cap nuts shall be furnished.
- ☑ Keys-(2) sets with code numbers; shall be with vehicle at time of delivery.
- ☑ Mirrors-All trucks are to be equipped with R.H. and L.H. outside rear-view mirrors to comply with Michigan laws; all trucks up to and including 15,000 G.V.W.R. shall be equipped with inside rear-view mirror. In all cases, outside R.H. & L.H. rear view mirrors shall provide full vision past all body installations. Mirrors shall be of stainless steel or high impact plastic construction unless denoted otherwise in individual truck specifications. All West Coast Type or Below Eye Level Camper Style Mirrors shall have stainless steel or high impact plastic heads, brackets, and hardware.
- ☑ Mud flaps, Anti-Sail Type, when required, are to be plain, rubber 1/4" thick, without advertising on either side.
- ☑ Painting-preclean and metal prep, any bare metal surfaces prior to applying a compatible red oxide or zinc chromate primer. When painting over a manufacturer's standard paint, metal prepping and primer may be omitted, provided an acceptable bond can be achieved.
- ☑ Equipment mounting- when mounting equipment on truck cab and chassis, all holes shall be drilled or punched. There shall be no flame cutting or welding on the frame side rails.
- ☑ Paint codes-factory paint codes shall be furnished with all vehicles; for all after market painting both the brand and paint code shall be furnished.
- ☑ Pre-delivery inspection and servicing.
- ☑ Radio - AM/FM Manufacturers Standard, Factory Installed
- ☑ Seat Belts with Shoulder Harness (3-Point Restraint System for Driver & Passenger)
- ☑ Seats-Split Bench type, unless otherwise specified
- ☑ Shock absorbers-(Heaviest Duty Available), front all trucks. Rear, up to and including 15,000 G.V.W.R.
- ☑ Spare tire, or Rim, not to be furnished unless specified. If specified, tires to be of same mfg., tread design to be same as front tires.
- ☑ Speed Control, Factory Installed
- ☑ Steering-Power, Tilt Wheel
- ☑ Sun visors-dual.
- ☑ Jack-Furnish on trucks up to and including 12,000 G.V.W.R.
- ☑ Windshield wipers-dual, intermittent speed electric, with automatic type washers.

All items removed for installation of optional equipment shall be returned to the State of Michigan.

TO BE EQUIPPED IN COMPLIANCE WITH ALL APPLICABLE FEDERAL MOTOR VEHICLE SAFETY STANDARDS AND REGULATIONS. ALL VEHICLES MUST BE EQUIPPED TO COMPLY WITH ALL REQUIREMENTS OF THE MICHIGAN MOTOR VEHICLE CODE.

- **Delete: On GM vehicles, OnStar and XM radio are deleted.**

ADDITIONAL OPTIONS:

These options are in addition to the options listed above as “STANDARD FACTORY EQUIPPED” and are to be included on this vehicle.

- Alternator-95 amp., min.
- Battery-12 Volt, Dual
- Brakes-Power.
- Fuel capacity-largest available from mfg.
- Mirrors-Rear View, Inside. Outside R.H. and L.H., below eye level, extended reach, swing away type, 51 sq. in., minimum. Installed, with stainless steel or powder coated steel heads, brackets, and hardware. GMC: Composite Mirror Heads
- Spare tire and wheel. GMC: Spare Wheel only – Tire Not Avail
- Steering-Power.
- Wrench-wheel. GMC: Wrench not available

ADDITIONAL MDOT OPTIONS: (Note: These options are not included in the MiDEAL price)

These options are in addition to the options listed above as “STANDARD FACTORY EQUIPPED” and are to be included on this MDOT vehicle.

- Axle Rear Limited slip
- Keys – (1) additional set (total of 3 sets) with code numbers; shall be with the vehicle at the time of delivery.
- Switches, upfitter for auxillary GMC: Panel only – switches avail from body upfitter
- Throttle, Electronic, High Idle Engine RPM Control.
- Towing package: Heaviest duty available from manufacturer GMC: Standard
- Trailer brake controller, factory installed GMC: Not available

PRICING SHEET

<u>TRUCK: CAB AND CHASSIS REAR DUAL WHEELS</u> (G.V.W.R. 14,500 LBS., min.) Mich. Spec. #3958-0111	
Standard Equipped Per above Specification (Including options as specified above)	Standard Equipped Cost
Make: GMC Model: C4500 F.O.B. - Dealership Delivery Cost Per Mile \$1.50	\$30,397.00*
Final Point of Assembly: Flint, MI	
<u>Dealer Information</u>	
Dealer Name: Red Holman Pontiac GMC	
Street Address: 35300 Ford Road	
City: Westland	State: MI
Zip: 48185	
Contact Name: Albert Li	
Telephone: (800) 482-3032	
Cell: (734) 637-6643	
E-mail: aclixx@hotmail.com	

*Please Note: A vehicle order confirmation sheet is included for each vehicle. These documents shall include all the "standard options" as listed for the State of Michigan standard specification.

Vehicle Order Confirmation Sheet
Spec # 3958-0111

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclix@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

SELECTED MODEL & OPTIONS

SELECTED MODEL - 2008 Fleet/Non-Retail TC4C042 Regular Cab 2WD

<u>Code</u>	<u>Description</u>	<u>MSRP</u>
TC4C042	2008 GMC TC4500 Regular Cab 2WD	\$28,890.00

SELECTED VEHICLE COLORS - 2008 Fleet/Non-Retail TC4C042 Regular Cab 2WD

<u>Code</u>	<u>Description</u>
-	Interior: No color has been selected.
-	Exterior 1: No color has been selected.
-	Exterior 2: No color has been selected.

SELECTED OPTIONS - 2008 Fleet/Non-Retail TC4C042 Regular Cab 2WD

CATEGORY

<u>Code</u>	<u>Description</u>	<u>MSRP</u>
PREFERRED EQUIPMENT GROUP		
C4C042	CUSTOM/BASE MODEL	\$0.00
DIESEL ENGINE		
LRX	DURAMAX DIESEL 6.6L, 300 HP (223 KW) @ 3000 RPM, 520 LB-FT (705 N-M) TORQUE @ 1600 RPM	\$9,259.00
GVWR		
C7R	16,500 LBS. (7484 KG) CAPACITY	\$0.00
EMISSION		
FE9	FEDERAL REQUIREMENTS	INC
ALTERNATOR		
KG4	AD244, DELCO-REMY 150-AMP MAXIMUM	\$0.00
BATTERY		
TNL	DUAL AC DELCO, 750 CCA, 12V	INC
ENGINE SHUTDOWN		
KPJ	AUTOMATIC ENGINE SHUTDOWN WITH ALARM	INC

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.0, Data updated 12/11/2007 11:05:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 19, 2007 8:00:50 PM

Page 1

Prepared By:
 Albert Li
 Red Holman Pontiac GMC
 35300 Ford Rd
 Westland, MI 48185
 Phone: (734) 721-1144
 Fax: (734) 721-1780
 Email: aclibx@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

SELECTED MODEL & OPTIONS

SELECTED OPTIONS - 2008 Fleet/Non-Retail TC4C042 Regular Cab 2WD

<u>CATEGORY</u>		<u>MSRP</u>
<u>Code</u>	<u>Description</u>	
EXHAUST SYSTEM		
NB5	SINGLE HORIZONTAL-PASSENGER SIDE MOUNTED INSIDE FRAME RAIL	INC
POWER TAKE OFF		
PTX	OPTION PTO NOT REQUIRED	\$0.00
TRANSMISSION		
MBV	AUTOMATIC, ALLISON 1000 HS/RDS SERIES 6-SPEED	\$0.00
TRANSMISSION FLUID		
MBT	TRANSYND SYNTHETIC AUTOMATIC TRANSMISSION FLUID	INC
TRANSMISSION EQUIPMENT		
KNP	AUXILIARY TRANSMISSION OIL COOLER	\$95.00
FRONT AXLE		
FM7	7000 LBS. (3175 KG) CAPACITY	INC
FRONT SUSPENSION		
FK6	TAPERED LEAF, 7000 LBS. (3175 KG) CAPACITY	INC
FRONT WHEEL		
Q82	19.5" X 6.75" (49.5 CM X 17.1 CM), STEEL DISC	\$37.00
FRONT TIRE		
XTN	225/70R19.5F	\$0.00
FRONT TIRE BRAND		
R4A	GOODYEAR	\$0.00
FRONT TIRE TREAD		
R3C	PREMIUM, HIGHWAY	\$0.00
SINGLE SPEED REAR AXLE		
GL4	SINGLE SPEED, 11,000 LBS. (4990 KG) CAPACITY	INC
AXLE RATIO		
008	4.88:1	\$0.00
REAR SUSPENSION		

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.0, Data updated 12/11/2007 11:05:00 AM
 ©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.
 Customer File:

December 19, 2007 8:00:50 PM

Page 2

Prepared By:
 Albert Li
 Red Holman Pontiac GMC
 35300 Ford Rd
 Westland, MI 48185
 Phone: (734) 721-1144
 Fax: (734) 721-1780
 Email: aclix@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

SELECTED MODEL & OPTIONS

SELECTED OPTIONS - 2008 Fleet/Non-Retail TC4C042 Regular Cab 2WD

<u>CATEGORY</u>		<u>MSRP</u>
<u>Code</u>	<u>Description</u>	
REAR SUSPENSION		INC
GR3	MULTI-LEAF, 11,000 LBS. (4990 KG) CAPACITY	
BOLTED OR RIVETED SUSPENSION		\$0.00
EV8	REAR SUSPENSION BRACKETS ARE RIVETED TO FRAME IN LIEU OF BOLTS	
REAR SHOCK ABSORBER		\$0.00
SAN	REAR SHOCK ABSORBER NOT DESIRED	
REAR WHEEL		\$74.00
Q83	19.5" X 6.75" (49.5 CM X 17.1 CM), STEEL DISC	
REAR TIRE		\$0.00
YTN	225/70R19.5F	
REAR TIRE BRAND		\$0.00
S4A	GOODYEAR	
REAR TIRE TREAD		\$0.00
S3H	HIGHWAY TRACTION	
SPARE WHEEL		\$128.00
SNF	FRONT	
WHEELBASE		\$0.00
EC9	128" (325.1 CM)	
FUEL TANK		\$122.00
NG6	DUAL, TOTAL FUEL CAPACITY OF 40-GALLONS (151L)	
DRIVER CONVENIENCE PACKAGES		\$245.00
ZQ3	DRIVER CONVENIENCE PACKAGE	
MISCELLANEOUS CAB EQUIPMENT		INC
N33	TILT-WHEEL ADJUSTABLE STEERING	
K34	CRUISE CONTROL,	INC
AIR CONDITIONING		\$852.00
C60	AIR CONDITIONING	

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.0, Data updated 12/11/2007 11:05:00 AM
 ©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 19, 2007 8:00:50 PM

Page 3

Prepared By:
 Albert Li
 Red Holman Pontiac GMC
 35300 Ford Rd
 Westland, MI 48185
 Phone: (734) 721-1144
 Fax: (734) 721-1780
 Email: aclbx@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

SELECTED MODEL & OPTIONS

SELECTED OPTIONS - 2008 Fleet/Non-Retail TC4C042 Regular Cab 2WD

<u>CATEGORY</u>		<u>MSRP</u>
<u>Code</u>	<u>Description</u>	
INSIDE REARVIEW MIRRORS		
D36	INSIDE DAY/NIGHT REARVIEW MIRROR	\$19.00
DRIVER SEAT		
AS4	HIGH-BACK BUCKET, FIXED HEIGHT, MANUAL ADJUSTER	INC
PASSENGER SEAT		
A59	TWO-PERSON, WITHOUT STORAGE	\$180.00
AIRBAGS		
AL3	SUPPLEMENTAL INFLATABLE RESTRAINTS NOT INCLUDED	INC
RADIO		
UM7	DELCO AM-FM STEREO RADIO	\$150.00
EXTERIOR MIRRORS		
DB5	MANUAL, 102" (259 CM) WIDE LOAD, INTEGRAL ARM, INTEGRAL CONVEX MIRROR	INC
PAINT		
ZY1	SOLID NON-METALLIC PAINT	INC
INTERIOR TRIM		
69I	VERY DARK PEWTER	INC
SEAT TRIM		
_V	VINYL SEAT TRIM	INC
ADDITIONAL OPTIONS		
VQ1	FLEET PROCESSING OPTION	\$0.00
OPTIONS TOTAL		\$11,161.00

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.0, Data updated 12/11/2007 11:05:00 AM
 ©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 19, 2007 8:00:50 PM

Page 4

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclix@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC4C042 Regular Cab 2WD

EXTERIOR

- Paint scheme, solid, upper color, Summit White
- Paint scheme, solid, lower color, Summit White
- Exterior roof drip moldings
- Bumper, front, steel, 96" (243.8 cm) wide - styled to minimized wall to wall turn diameter painted argent
- Steps under cab doors
- Front mud flaps
- Integral grille and fenders - The grille is the same color as hood with single halogen headlamps.
- Roof marker lamps
- Daytime running lamps
- Windows, Solar-Ray tinted. Light tinted windshield and side window glass with light transmissivity of 70%
- Mirrors, manual, 102" (259 cm) wide load, integral arm, integral convex mirror - black molded composite 12" x 7" (30.5 cm x 17.8 cm) with 6" x 7" (15.2 cm x 17.8 cm) convex section
- Windshield wipers, 2-speed and intermittent, with pulse washers
- Provisions for mounting front license plate
- Positive door stops

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.0, Data updated 12/11/2007 11:05:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 19, 2007 8:00:50 PM

Page 5

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: actixx@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC4C042 Regular Cab 2WD

INTERIOR

- Seat, driver, high-back bucket, fixed height, manual adjuster - storage in the seat riser with a small lip at the front to stop contents from sliding out
- Seat, passenger, high-back bucket, fixed height, manual back angle adjuster - storage in the seat riser with a small lip at the front to stop contents from sliding out
- Seat trim, vinyl, Very Dark Pewter
- Interior trim, Very Dark Pewter (Requires 69V Very Dark Pewter vinyl or 69C Very Dark Pewter cloth)
- Trim console - located next to driver's seat and two cupholders
- Molded vinyl floor covering
- Steering wheel 16"
- Two sided single common key for doors and ignition
- Headlamp warning buzzer
- Warning tone, key-in-ignition
- Tachometer
- Electronic engine hour meter
- Engine "Check Gauges" telltale light and buzzer, oil pressure gauge
- Gauges, low oil pressure and coolant level, high coolant and engine oil temperature
- Vinyl door trim panels - with storage pocket on front doors, beverage holders, and reflector on all doors
- Stepwell storage areas at each door front and rear. Includes storage cover.
- Cloth headliner
- Sunshades, passenger side and driver side, vinyl-covered
- Coat hooks (2) located on cab back panel
- Provisions for stereo - Includes AM/FM antenna, lead wiring for speakers, and separate door chime module (N/A with ZQ2 power convenience option)
- Air conditioning not desired - this option should be ordered only when a customer does not require air conditioning
- Powerpoints - two in-cab power sources (in addition to optional cigarette lighter) for electrical plug-in accessories

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.0, Data updated 12/11/2007 11:05:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.
Customer File:

December 19, 2007 8:00:50 PM

Page 6

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclbx@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC4C042 Regular Cab 2WD

- Underhood bodybuilder connections accessory power supply - Provides 12V power supply from the battery with two separate 30 amp fused circuits

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.0, Data updated 12/11/2007 11:05:00 AM

©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 19, 2007 8:00:50 PM

Page 7

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclixx@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC4C042 Regular Cab 2WD

MECHANICAL

- GVWR, 16,500 lbs. (7484 kg) capacity - GCWR limited to 24,000 lb. (10,866 kg) (Requires FM7 7000 lbs. (3175 kg) front axle) NOTE: Trucks that are used primarily to tow a trailer may be liable to Federal Excise Tax (FET). A New Law (Highway Transportation Bill HR3) was passed on August 10, 2005 - Check with IRS for guidelines
- Engine, Vortec 8.1L MD gasoline V8, 325 hp (239 kw) @ 4000 rpm and 450 lb-ft torque (610 N-m) @ 2,800 rpm. - Maximum engine speed 5000 rpm. Oil Level Sensor: Warning sensor for low oil levels
- Air cleaner, dry type
- Cooling, anti-freeze protection temperature - -40 degrees F (-40 degrees C)
- Road speed governor, controlled by the speed rating of the tires ordered. - which will be less than or equal to 85 mph (137 kph); 80 mph (129 kph) with EC9 128" wheelbase/60" CA, ML6 manual transmission and 008 4.88 rear axle ratio; 75 mph (120 kph) with EC9 128" wheelbase/60" CA, M74 automatic transmission and HD2 rear axle
- Alternator, AD244 Delco-Remy 150-amp maximum (N/A with YW2 wrecker package)
- Battery, single AC Delco, 600 CCA, 12V - 115-minute reserve capacity @ 27 degrees C, 600 CCA @ -18 degrees C grounded directly to starter, (Requires gasoline engine; N/A with ANQ Snow Plow Prep package or YW2 Wrecker package)
- Exhaust, single horizontal - passenger side mounted inside frame rail, with gasoline engine stainless-steel exhaust with catalytic converter, with diesel engines, stainless-steel exhaust, oxidation catalyst, diesel particulate filter and exhaust gas cooler
- Option PTO not required - This option should only be ordered when a customer specifically does not require an electric hand throttle for use with power-take-off provisions. (Note: Will delete transmission PTO gear.)
- Transmission, automatic, Allison 1000 HS/RDS Series 6-speed - With parking pawl and column shift, includes 4th Generation Electronic Controls and 0.61 overdrive. Torque Rating: 660 lb-ft (895 N-m) with shift energy management. Available with a Gross Vehicle Weight up to 19,500 lbs. (8845 kg) and a Gross Combination Weight Rating up to 26,000 lbs. (11,790 kg). To include PTO gear, please order with RPO PTO for Allison 1000 RDS Rugged Duty Series transmission. Includes transmission-oil cooler located inside radiator. With Option PTX the truck will be equipped with the Allison 1000 HS Highway Series transmission. (N/A with ANM Fire and Rescue or YF2 Ambulance Package)
- TranSynd synthetic automatic transmission fluid
- Front axle, 7000 lbs. (3175 kg) capacity - I-beam Wide-trac. Up to 53 degree turn angle, includes 4-piston brake apply calipers. Steering Gear Series: ZF8014
- Front suspension, tapered leaf, 7000 lbs. (3175 kg) capacity (includes stabilizer)

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.0, Data updated 12/11/2007 11:05:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 19, 2007 8:00:50 PM

Page 8

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclixx@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC4C042 Regular Cab 2WD

- Front shock absorber, diameter 1.375" (35mm)
- Front stabilizer bar, 2" x 2" square tube (5 cm x 5 cm)
- Front wheels, 19.5" x 6.0" (49.5 cm x 15.2 cm), steel disc - 8-hole. 7280 lbs. (3302 kg) capacity
- Front tire size, 225/70R19.5F - 7280 lbs. (3802 kg) capacity, (With R4A Goodyear or R4L Michelin requires R3C front premium highway tread)
- Front tire manufacturer code, Goodyear (Requires S4A Goodyear)
- Front tread, premium, highway (Requires R4A Goodyear or R4L Michelin)
- Rear axle, single speed, 11,000 lbs. (4990 kg) capacity - full floating, Includes 2-piston brake applied calipers
- Rear wheel drive
- Rear axle ratio, 5.13:1 (Requires gasoline engine)
- Rear suspension, multi-leaf, 11,000 lbs. (4990 kg) capacity (Requires GL4 single speed rear axle)
- Rear suspension brackets are riveted to frame in lieu of bolts
- Rear shock absorber not desired (N/A with tapered leaf springs)
- Rear wheels, 19.5" x 6.0" (49.5 cm x 15.2 cm), steel disc - 8-hole. 14,560 lbs (6604 kg) capacity
- Rear tire size, 225/70R19.5F - 13,660 lbs. (6196 kg) capacity, (With S4A Goodyear, requires S3C rear premium highway tread or S3H rear traction tread; with S4L Michelin, requires S3C rear premium highway tread or S3J rear highway traction tread)
- Rear tire manufacturer code, Goodyear (Requires R4A Goodyear)
- Rear tread, premium, highway (Requires S4A Goodyear or S4L Michelin)
- Wheelbase, 128" (325.1 cm) - with 60" (152.4 cm) CA and 100" (254 cm) CE. Includes a 6 mm 80,000 psi (551,600 kPa) yield strength, steel frame, RBM: 610,400 Section Modulus 7.63 (Requires KYW 75 mph (120 kph) road speed governor and HD2 13,500 lbs. (6123 kg) capacity rear axle)
- Frame, 6mm - 80,000 psi (551,600 kPa) yield strength, steel frame, RBM: 610,400 Section Modulus 7.63
- Fuel tank, single, 25-gallon (95L) fuel capacity - gas or diesel located midship between the frame rails, with fuel fill neck through the frame rail (this option uses the mid-frame tank included in the NG6 dual tank option) Tethered fuel cap is black with gasoline engines, and green un-tethered fuel cap with diesel engines. MINIMUM OVERHANG = 36" (3 FEET) (Required in YW2 Wrecker Package, standard on 60" (152.4 cm) CA, optional on all other CA's)

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.0, Data updated 12/11/2007 11:05:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 19, 2007 8:00:50 PM

Page 9

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclixx@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC4C042 Regular Cab 2WD

- Fuel sender assembly, Robust fuel pump
- Tethered fuel cap
- Steering, power - ZF variable ratio power
- Brakes, front, power, 4-wheel disc, 4 channel ABS 2-piston - (See front axle options for more detail)
- Brakes, rear, power, 4-wheel disc, 4 channel ABS 2-piston - (See rear axle options for more detail)
- Parking brake, hand lever operated transmission mounted drum brake

SAFETY

- 4-wheel disc, 4-channel ABS
- Air bags, Supplemental Inflatable Restraints not included.
- This vehicle does not include any air bags
- Seat belt warning indicator
- Daytime running lamps

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.0, Data updated 12/11/2007 11:05:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 19, 2007 8:00:50 PM

Page 10



APPENDIX B

TRUCK QUESTIONNAIRE FORMS

ALL BIDDERS MUST COMPLETE AND RETURN A QUESTIONNAIRE FORM WITH THE BID FOR EACH TRUCK ITEM TO BE CONSIDERED FOR AWARD OF THAT ITEM. Bids submitted without an adequately completed questionnaire form for EACH TRUCK ITEM will not be considered for award of that item. It is the responsibility of each bidder to copy this form in sufficient quantity to submit to Purchasing Operations prior to the scheduled bid due date. A single form may apply to more than one item, simply list the item numbers to which the questionnaire applies in the appropriate space. If part of the questionnaire does not apply, simply indicate "not applicable" in those spaces.

NAME OF BIDDER: Red Holman Pontiac GMC ITEM NO(s). Spec # 3958-0111
 MAKE OF TRUCK: GMC MODEL: C4500 TCY042 GVWR 16500 lbs. ✓
 PAYLOAD: 8916 W.B. 128" ✓ C.A. 60" ✓ C.E. 100" ✓
 ENGINE: (GAS - DIESEL) Diesel MAKE: Gm Duramax MODEL: LRX. 6.6 SAE H.P. 300 ✓
 FUEL TANK(S) CAPACITY: 40 (GALS. TOTAL) TRANSMISSION: Allison 1000 MBV 6-spd ✓
 SPRING CAP. @ GROUND EACH: FRONT 3500 lbs. REAR 5500 lbs. AUX. N/A lbs. ✓
 AXLES: FRONT 7000 lbs. REAR 11000 lbs. REAR RATIO 4.88 ✓
 ALTERNATOR: 150 amps. BATTERY Dual 750 ? cca. ✓
 TIRE SIZE: FRONT 225/70R14.5F PR REAR 225/70R14.5F PR SINGLE _____ DUAL ✓ M&S ✓
 TIRE: MAKE Goodyear STYLE NO. TBD MFG. CODE XTN/YTN
 HOIST: MAKE N/A MODEL N/A INSTALLING CO. N/A
 BODY: MAKE N/A MODEL N/A INSTALLING CO. N/A
 POWER LIFT GATE: MAKE N/A MODEL N/A CAPACITY N/A lbs.
 PLATFORM SIZE: N/A

OTHER EQUIPMENT INSTALLED BY BODY EQUIPMENT SUPPLIER AND/OR COMMENTS

This information must be returned with the bid document to Purchasing Operations, on or before the bid due date and time. However, if returned separately, it must be received by Purchasing Operations on or before the bid due date and time, and must comply with the sealed bid instructions as outlined in the ITB.

TRUCK: CAB AND CHASSIS DUAL REAR WHEELS
(G.V.W.R. 14,500 LBS., min.) (4 x 4)

MODEL-2008 CURRENT NEW

	CHEVY/GMC	FORD
	K4500	
	<u>C4C044</u>	<u>F-450</u>
G.V.W.R. (lbs.)	17,500	16,000
Wheelbase (inches)	152	140.8
C.A. (inches)	84	60
Engine: Gasoline	8100	Triton
Type & No. of Cylinders	V-8	V-10
Net H.P.-S.A.E.	325	362
Transmission: Automatic: with maximum capacity transmission oil cooler, Factory installed.		
Axle, Min. Cap.-lbs.		
Front	8,000	7,000
Rear	13,500	12,000
Springs, Min. Cap. at Ground		
Front-lbs. each	4,000	2,600
Rear-lbs. each	6,750	6,000

Tires, Truck, Tubeless, Radial, to meet G.V.W.R. Rear duals, mud and snow.

TO BE STANDARD FACTORY EQUIPPED AS FOLLOWS:

The items listed below are to be supplied on all trucks, even though they may be optional with the manufacturer. Therefore, these specifications are to be furnished on all vehicles:

- 12 Volt auxiliary outlet
- Air Conditioning - All trucks
- Anti-freeze protection, to -30°F.
- Arm Rest-Driver's side.
- Color-Manufacturers Standard to be selected.
- Coolant System-Maximum Size Available, including the Heaviest Duty Radiator
- Dome Light.
- Electric wiring-All wiring passing through holes in metal or non-metal wearing surfaces, which could cause wear of the insulation, shall be adequately protected by

rubber or plastic grommets, and/or non-metallic conduit. Ends of all wires shall be adequately anchored to prevent loosening.

- ☑ Frame length-on all body installations without hoists the cab to end of frame length shall be the same length as the body being mounted, plus the length of any setback.
- ☑ Fuel Tanks, Diesel, with sending unit and magnetic drain plug, on all trucks over 21,000 G.V.W.R., painted Black and labeled "Diesel Fuel Only".
- ☑ Hub caps on all pickups and vans up to and including 10,000 G.V.W.R. If not available from dealer cap nuts shall be furnished.
- ☑ Keys-(2) sets with code numbers; shall be with vehicle at time of delivery.
- ☑ Mirrors-All trucks are to be equipped with R.H. and L.H. outside rear-view mirrors to comply with Michigan laws; all trucks up to and including 15,000 G.V.W.R. shall be equipped with inside rear-view mirror. In all cases, outside R.H. & L.H. rear view mirrors shall provide full vision past all body installations. Mirrors shall be of stainless steel or high impact plastic construction unless denoted otherwise in individual truck specifications. All West Coast Type or Below Eye Level Camper Style Mirrors shall have stainless steel or high impact plastic heads, brackets, and hardware.
- ☑ Mud flaps, Anti-Sail Type, when required, are to be plain, rubber 1/4" thick, without advertising on either side.
- ☑ Painting-preclean and metal prep, any bare metal surfaces prior to applying a compatible red oxide or zinc chromate primer. When painting over a manufacturer's standard paint, metal prepping and primer may be omitted, provided an acceptable bond can be achieved.
- ☑ Equipment mounting- when mounting equipment on truck cab and chassis, all holes shall be drilled or punched. There shall be no flame cutting or welding on the frame side rails.
- ☑ Paint codes-factory paint codes shall be furnished with all vehicles; for all after market painting both the brand and paint code shall be furnished.
- ☑ Pre-delivery inspection and servicing.
- ☑ Radio - AM/FM Manufacturers Standard, Factory Installed
- ☑ Seat Belts with Shoulder Harness (3-Point Restraint System for Driver & Passenger)
- ☑ Seats-Split Bench type, unless otherwise specified
- ☑ Shock absorbers-(Heaviest Duty Available), front all trucks. Rear, up to and including 15,000 G.V.W.R.
- ☑ Spare tire, or Rim, not to be furnished unless specified. If specified, tires to be of same mfg., tread design to be same as front tires.
- ☑ Speed Control, Factory Installed
- ☑ Steering-Power, Tilt Wheel
- ☑ Sun visors-dual.
- ☑ Jack-Furnish on trucks up to and including 12,000 G.V.W.R.
- ☑ Windshield wipers-dual, intermittent speed electric, with automatic type washers.

All items removed for installation of optional equipment shall be returned to the State of Michigan.

TO BE EQUIPPED IN COMPLIANCE WITH ALL APPLICABLE FEDERAL MOTOR VEHICLE SAFETY STANDARDS AND REGULATIONS. ALL VEHICLES MUST BE EQUIPPED TO COMPLY WITH ALL REQUIREMENTS OF THE MICHIGAN MOTOR VEHICLE CODE.

- **Delete: On GM vehicles, OnStar and XM radio are deleted.**

ADDITIONAL OPTIONS:

These options are in addition to the options listed above as “STANDARD FACTORY EQUIPPED” and are to be included on this vehicle.

- Alternator-95 amp., min.
- Battery-12 Volt, 600 CCA, minimum.
- Brakes-Power.
- Fuel capacity-largest available from mfg.
- Mirrors-Rear View, Inside. Outside R.H. and L.H., below eye level, extended reach, swing away type, 51 sq. in., minimum. Installed, with stainless steel or powder coated steel heads, brackets, and hardware. GMC: Composite Mirror Head
- Spare tire and wheel. GMC: Spare wheel only – spare tire not available
- Steering-Power.
- Wrench-wheel. GMC: wrench not available

ADDITIONAL MDOT OPTIONS: (Note: These options are not included in the MiDEAL price)

These options are in addition to the options listed above as “STANDARD FACTORY EQUIPPED” and are to be included on this MDOT vehicle.

- Axle Rear Limited slip
- Hubs autolocking on front GMC: manual locking only
- Keys – (1) additional set (total of 3 sets) with code numbers; shall be with the vehicle at the time of delivery.
- Switches, upfitter for auxillary GMC: Panel only – switches avail from body upfitter
- Throttle, Electronic, High Idle Engine RPM Control.
- Towing package: Heaviest duty available from manufacturer GMC: standard
- Trailer brake controller, factory installed GMC: not available on chassis

PRICING SHEET

<u>TRUCK: CAB AND CHASSIS REAR DUAL WHEELS</u> (G.V.W.R. 14,500 LBS., min.) (4 x 4) Mich. Spec. #3958-0112	
Standard Equipped Per above Specification (Including options as specified above)	Standard Equipped Cost
Make: GMC Model: C4500 F.O.B. - Dealership Delivery Cost Per Mile \$1.50	\$28,615.00*
Final Point of Assembly: Flint, MI	
<u>Dealer Information</u>	
Dealer Name: Red Holman Pontiac GMC	
Street Address: 35300 Ford Road	
City: Westland	State: MI
	Zip: 48185
Contact Name: Albert Li	
Telephone: (800) 482-3032	
Cell: (734) 637-6643	
E-mail: aclixx@hotmail.com	

*Please Note: A vehicle order confirmation sheet is included for each vehicle. These documents shall include all the "standard options" as listed for the State of Michigan standard specification.

Vehicle Order Confirmation Sheet
 Spec # 3958-0112

Prepared By:
 Albert Li
 Red Holman Pontiac GMC
 35300 Ford Rd
 Westland, MI 48185
 Phone: (734) 721-1144
 Fax: (734) 721-1780
 Email: aclbx@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

SELECTED MODEL & OPTIONS

SELECTED MODEL - 2008 Fleet/Non-Retail TC4C044 Regular Cab 4WD

<u>Code</u>	<u>Description</u>	<u>MSRP</u>
TC4C044	2008 GMC TC4500 Regular Cab 4WD	\$35,860.00

SELECTED VEHICLE COLORS - 2008 Fleet/Non-Retail TC4C044 Regular Cab 4WD

<u>Code</u>	<u>Description</u>
-	Interior: No color has been selected.
-	Exterior 1: No color has been selected.
-	Exterior 2: No color has been selected.

SELECTED OPTIONS - 2008 Fleet/Non-Retail TC4C044 Regular Cab 4WD

CATEGORY

<u>Code</u>	<u>Description</u>	<u>MSRP</u>
PREFERRED EQUIPMENT GROUP		
C4C044	CUSTOM/BASE MODEL	\$0.00
GASOLINE ENGINE		
LRW	VORTEC 8.1L MD GASOLINE V8, 325 HP (239 KW) @ 4000 RPM AND 450 LB-FT TORQUE (610 N-M) @ 2800 RPM.	\$0.00
GVWR		
GZX	17,500 LBS. (7938 KG) CAPACITY	INC
EMISSION		
FE9	FEDERAL REQUIREMENTS	INC
ROAD SPEED GOVERNOR		
KYW	75 MPH (120 KPH) SPEED GOVERNOR	INC
ALTERNATOR		
KG4	AD244, DELCO-REMY 150-AMP MAXIMUM	\$0.00
BATTERY		
TM1	SINGLE AC DELCO, 600 CCA, 12V	\$0.00

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.0, Data updated 12/11/2007 11:05:00 AM
 ©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 19, 2007 8:35:44 PM

Page 1

Prepared By:
 Albert Li
 Red Holman Pontiac GMC
 35300 Ford Rd
 Westland, MI 48185
 Phone: (734) 721-1144
 Fax: (734) 721-1780
 Email: aclix@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

SELECTED MODEL & OPTIONS

SELECTED OPTIONS - 2008 Fleet/Non-Retail TC4C044 Regular Cab 4WD

<u>CATEGORY</u>		<u>MSRP</u>
<u>Code</u>	<u>Description</u>	
EXHAUST SYSTEM		
NB5	SINGLE HORIZONTAL-DRIVER SIDE MOUNTED INSIDE FRAME RAIL,	INC
POWER TAKE OFF		
PTX	OPTION PTO NOT REQUIRED	\$0.00
TRANSMISSION		
MBV	AUTOMATIC, ALLISON 1000 HS/RDS SERIES 6-SPEED	\$0.00
TRANSMISSION FLUID		
MBT	TRANSYND SYNTHETIC AUTOMATIC TRANSMISSION FLUID	INC
TRANSMISSION EQUIPMENT		
KNP	AUXILIARY TRANSMISSION OIL COOLER	\$95.00
TRANSFER CASE		
NP1	NEW VENTURE GEAR-MODEL NV273 TWO-SPEED	INC
FRONT AXLE		
G38	8000 LBS. (3629 KG) CAPACITY	\$0.00
FRONT SUSPENSION		
FSN	TAPERED LEAF, 8000 LBS. (3629 KG) CAPACITY	\$0.00
FRONT STABILIZER BAR		
F59	STABILIZER BAR	INC
FRONT WHEEL		
Q82	19.5" X 6.75" (49.5 CM X 17.1 CM), STEEL DISC	\$0.00
FRONT TIRE		
XTY	245/70R19.5G	\$0.00
FRONT TIRE BRAND		
R4A	GOODYEAR	\$0.00
FRONT TIRE TREAD		
R3H	HIGHWAY TRACTION	INC
SINGLE SPEED REAR AXLE		
HD2	SINGLE SPEED, DANA S110 13,500 LBS. (6123 KG) CAPACITY	INC

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.0, Data updated 12/11/2007 11:05:00 AM
 ©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 19, 2007 8:35:44 PM

Page 2

Prepared By:
 Albert Li
 Red Holman Pontiac GMC
 35300 Ford Rd
 Westland, MI 48185
 Phone: (734) 721-1144
 Fax: (734) 721-1780
 Email: aclix@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

SELECTED MODEL & OPTIONS

SELECTED OPTIONS - 2008 Fleet/Non-Retail TC4C044 Regular Cab 4WD

<u>CATEGORY</u>		<u>MSRP</u>
<u>Code</u>	<u>Description</u>	
AXLE RATIO		
058	5.13:1	INC
TRACTION CONTROL		
G80	REAR LIMITED SLIP DIFFERENTIAL	INC
REAR SUSPENSION		
GR4	MULTI-LEAF, 13,500 LBS. (6123 KG) CAPACITY	INC
BOLTED OR RIVETED SUSPENSION		
EV8	REAR SUSPENSION BRACKETS ARE RIVETED TO FRAME IN LIEU OF BOLTS	\$0.00
REAR SHOCK ABSORBER		
SAN	REAR SHOCK ABSORBER NOT DESIRED	\$0.00
REAR WHEEL		
Q83	19.5" X 6.75" (49.5 CM X 17.1 CM), STEEL DISC	\$0.00
REAR TIRE		
YTY	245/70R19.5G	\$0.00
REAR TIRE BRAND		
S4A	GOODYEAR	\$0.00
REAR TIRE TREAD		
S3H	HIGHWAY TRACTION	INC
SPARE WHEEL		
SNF	FRONT	\$128.00
WHEELBASE		
EG9	152" (386.1 CM)	\$0.00
FUEL TANK		
NH4	SINGLE, 40-GALLON (151L) FUEL CAPACITY	INC
PARKING BRAKE		
J69	REAR IN-WHEEL PARK BRAKE	INC
DRIVER CONVENIENCE PACKAGES		

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.0, Data updated 12/11/2007 11:05:00 AM
 ©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 19, 2007 8:35:44 PM

Page 3

Prepared By:
 Albert Li
 Red Holman Pontiac GMC
 35300 Ford Rd
 Westland, MI 48185
 Phone: (734) 721-1144
 Fax: (734) 721-1780
 Email: aclix@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

SELECTED MODEL & OPTIONS

SELECTED OPTIONS - 2008 Fleet/Non-Retail TC4C044 Regular Cab 4WD

<u>CATEGORY</u>		<u>MSRP</u>
<u>Code</u>	<u>Description</u>	
DRIVER CONVENIENCE PACKAGES		
ZQ3	DRIVER CONVENIENCE PACKAGE	\$245.00
MISCELLANEOUS CAB EQUIPMENT		
N33	TILT-WHEEL ADJUSTABLE STEERING	INC
K34	CRUISE CONTROL,	INC
AIR CONDITIONING		
C60	AIR CONDITIONING	\$852.00
DRIVER SEAT		
AS4	HIGH-BACK BUCKET, FIXED HEIGHT, MANUAL ADJUSTER	INC
PASSENGER SEAT		
A59	TWO-PERSON, WITHOUT STORAGE	\$180.00
AIRBAGS		
AL3	SUPPLEMENTAL INFLATABLE RESTRAINTS NOT INCLUDED	INC
RADIO		
UM7	DELCO AM-FM STEREO RADIO	\$150.00
EXTERIOR MIRRORS		
DB5	MANUAL, 102" (259 CM) WIDE LOAD, INTEGRAL ARM, INTEGRAL CONVEX MIRROR	INC
PAINT		
ZY1	SOLID NON-METALLIC PAINT	INC
INTERIOR TRIM		
69I	VERY DARK PEWTER	INC
SEAT TRIM		
_V	VINYL SEAT TRIM	INC
ADDITIONAL OPTIONS		
VQ1	FLEET PROCESSING OPTION	\$0.00

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.0, Data updated 12/11/2007 11:05:00 AM
 ©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 19, 2007 8:35:44 PM

Page 4

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclbx@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

SELECTED MODEL & OPTIONS

SELECTED OPTIONS - 2008 Fleet/Non-Retail TC4C044 Regular Cab 4WD

CATEGORY

<u>Code</u>	<u>Description</u>	<u>MSRP</u>
OPTIONS TOTAL		\$1,650.00

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.0, Data updated 12/11/2007 11:05:00 AM

©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 19, 2007 8:35:44 PM

Page 5

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclbx@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC4C044 Regular Cab 4WD

EXTERIOR

- Paint scheme, solid, upper color, Summit White
- Paint scheme, solid, lower color, Summit White
- Exterior roof drip moldings
- Bumper, front, steel, 96" (243.8 cm) wide - styled to minimized wall to wall turn diameter painted argent
- Steps under cab doors
- Front mud flaps
- Integral grille and fenders - The grille is the same color as hood with single halogen headlamps.
- Roof marker lamps
- Daytime running lamps
- Windows, Solar-Ray tinted. Light tinted windshield and side window glass with light transmissivity of 70%
- Mirrors, manual, 102" (259 cm) wide load, integral arm, integral convex mirror - black molded composite 12" x 7" (30.5 cm x 17.8 cm) with 6" x 7" (15.2 cm x 17.8 cm) convex section
- Windshield wipers, 2-speed and intermittent, with pulse washers
- Provisions for mounting front license plate
- Positive door stops

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.0, Data updated 12/11/2007 11:05:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 19, 2007 8:35:44 PM

Page 6

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclixx@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC4C044 Regular Cab 4WD

INTERIOR

- Seat, driver, high-back bucket, fixed height, manual adjuster - storage in the seat riser with a small lip at the front to stop contents from sliding out
- Seat, passenger, high-back bucket, fixed height, manual back angle adjuster - storage in the seat riser with a small lip at the front to stop contents from sliding out
- Seat trim, vinyl, Very Dark Pewter
- Interior trim, Very Dark Pewter (Requires 69V Very Dark Pewter vinyl or 69C Very Dark Pewter cloth)
- Trim console - located next to driver's seat and two cupholders
- Molded vinyl floor covering
- Steering wheel 16"
- Two sided single common key for doors and ignition
- Headlamp warning buzzer
- Warning tone, key-in-ignition
- Tachometer
- Electronic engine hour meter
- Engine "Check Gauges" telltale light and buzzer, oil pressure gauge
- Gauges, low oil pressure and coolant level, high coolant and engine oil temperature
- Vinyl door trim panels - with storage pocket on front doors, beverage holders, and reflector on all doors
- Stepwell storage areas at each door front and rear. Includes storage cover.
- Cloth headliner
- Sunshades, passenger side and driver side, vinyl-covered
- Coat hooks (2) located on cab back panel
- Provisions for stereo - Includes AM/FM antenna, lead wiring for speakers, and separate door chime module (N/A with ZQ2 power convenience option)
- Air conditioning not desired - this option should be ordered only when a customer does not require air conditioning
- Powerpoints - two in-cab power sources (in addition to optional cigarette lighter) for electrical plug-in accessories

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.0, Data updated 12/11/2007 11:05:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 19, 2007 8:35:44 PM

Page 7

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: acli@hotmai.com

2008 Fleet/Non-Retail GMC TC4500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC4C044 Regular Cab 4WD

- Underhood bodybuilder connections accessory power supply - Provides 12V power supply from the battery with two separate 30 amp fused circuits

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.0, Data updated 12/11/2007 11:05:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 19, 2007 8:35:44 PM

Page 8

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclbxx@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC4C044 Regular Cab 4WD

MECHANICAL

- GVWR, 17,500 lbs. (7938 kg) capacity - GVWR. Maximum GCWR 26,000 lb. Note: Trucks that are used primarily to tow a trailer may be liable to Federal Excise Tax (FET). A New Law (Highway Transportation Bill HR3) was passed on August 10, 2005 - Check with IRS for guidelines
- Engine, Vortec 8.1L MD gasoline V8, 325 hp (239 kw) @ 4000 rpm and 450 lb-ft torque (610 N-m) @ 2,800 rpm. - Maximum engine speed 5000 rpm. Oil Level Sensor: Warning sensor for low oil levels
- Air cleaner, dry type
- Cooling, anti-freeze protection temperature - -40 degrees F (-40 degrees C)
- 75 mph (120 kph) speed governor - Required by the speed rating of the tires ordered
- Alternator, AD244 Delco-Remy 150-amp maximum (N/A with ANM Fire and Rescue or YF2 Ambulance Packages)
- Battery, single AC Delco, 600 CCA, 12V - 115-minute reserve capacity @ 27 degrees C, 600 CCA @ -18 degrees C grounded directly to starter, (Requires gasoline engine; N/A with ANQ Snow Plow Prep)
- Exhaust, single horizontal - driver side mounted inside frame rail, with gasoline engine stainless-steel exhaust with catalytic converter, with diesel engines, stainless-steel exhaust, oxidation catalyst, diesel particulate filter and exhaust gas cooler
- Option PTO not required - This option should only be ordered when a customer specifically does not require an electric hand throttle for use with power-take-off provisions. (Note: Will delete transmission PTO gear.)
- Transmission, automatic, Allison 1000 HS/RDS Series 6-speed - With parking pawl and column shift, includes 4th Generation Electronic Controls and 0.61 overdrive. Torque Rating: 660 lb-ft (895 N-m) with shift energy management. Available with a Gross Vehicle Weight up to 19,500 lbs. (8845 kg) and a Gross Combination Weight Rating up to 26,000 lbs. (11,790 kg). To include PTO gear, please order with RPO PTO for Allison 1000 RDS Rugged Duty Series transmission. Includes transmission-oil cooler located inside radiator. With Option PTX the truck will be equipped with the Allison 1000 HS Highway Series transmission. (N/A with ANM Fire and Rescue or YF2 Ambulance Package)
- TranSynd synthetic automatic transmission fluid
- Transfer case, New Venture Gear - model NV273 two-speed, electrically actuated, IP mounted switch, includes shield
- Front axle, 8000 lbs. (3629 kg) capacity - Solid drive axle. Up to 45 degree turn angle, includes 4 piston brake apply calipers and manual locking hubs
- Front suspension, tapered leaf, 8000 lbs. (3629 kg) capacity

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.0, Data updated 12/11/2007 11:05:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 19, 2007 8:35:44 PM

Page 9

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclix@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC4C044 Regular Cab 4WD

- Front shock absorber, diameter 1.375" (35mm)
- Front stabilizer bar, Solid bar style, 1.5" (38mm)
- Front wheels, 19.5" x 6.75" (49.5 cm x 17.1 cm), steel disc - 8-hole. 10,000 lbs. (4536 kg) capacity, (Requires Q83 steel rear wheel and XTY or XNC front tires)
- Front tire size, 245/70R19.5G - 9090 lbs. (4123 kg) capacity (Requires KYR 65 mph or KYW 75 mph (120 kph) road speed governor, Q82 or RPM front wheels. With R4A Goodyear tire, requires R3H highway traction tread)
- Front tire manufacturer code, Goodyear (Requires S4A Goodyear)
- Front tread, highway traction
- Rear axle, single speed, Dana S110 13,500 lbs. (6123 kg) capacity - full floating, includes 2-piston brake applied calipers
- Four-wheel drive
- Rear axle ratio, 5.13:1 (Requires HD2 single speed rear axle)
- Rear limited slip differential
- Rear suspension, multi-leaf, 13,500 lbs. (6123 kg) capacity
- Rear suspension brackets are riveted to frame in lieu of bolts
- Rear shock absorber not desired (N/A with tapered leaf springs)
- Rear wheels, 19.5" x 6.75" (49.5 cm x 17.1 cm), steel disc - 8-hole, 20,000 lbs. (9072 kg) capacity (Requires Q82 front wheels and YTY or YNC rear tires)
- Rear tire size, 245/70R19.5G - 17,500 lbs. (7938 kg) capacity (Requires KYR 65 mph or KYW 75 mph (120 kph) road speed governor and Q83 or RPW rear wheels. With S4A Goodyear tire, requires S3H highway traction tread)
- Rear tire manufacturer code, Goodyear (Requires R4A Goodyear)
- Rear tread, highway traction
- Wheelbase, 152" (386.1 cm) - with 84" (213.4 cm) CA and 146" (370.8 cm) CE. Includes a 6mm 80,000 psi (551,600 kPa) yield strength, steel frame, RBM: 610,400 Section Modulus 7.63
- Frame, 8mm - 80,000 psi (551,600 kPa) yield strength, steel frame, RBM: 610,400 Section Modulus 7.63
- Fuel tank, single, 40-gallon (151L) fuel capacity - gas or diesel, located behind rear axle with fuel fill neck through frame rail and a black tethered fuel cap with gasoline engine and green un-tethered fuel cap with diesel engines. DRIVER SIDE FILL NECK ONLY. NO AUXILIARY PORTS. MINIMUM OVERHANG = 60" (5 FEET)

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.0, Data updated 12/11/2007 11:05:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.
Customer File:

December 19, 2007 8:35:44 PM

Page 10

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclix@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC4C044 Regular Cab 4WD

- Fuel sender assembly. Robust fuel pump
- Tethered fuel cap
- Steering, power - ZF variable ratio power
- Brakes, front, power, 4-wheel disc, 4 channel ABS 4-piston - (See front axle options for more detail)
- Brakes, rear, power, 4-wheel disc, 4 channel ABS 2-piston - (See rear axle options for more detail)
- Parking brake, rear in-wheel park brake - hand lever operated

SAFETY

- 4-wheel disc, 4-channel ABS
- Air bags, Supplemental Inflatable Restraints not included.
- This vehicle does not include any air bags
- Seat belt warning indicator
- Daytime running lamps

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.0, Data updated 12/11/2007 11:05:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 19, 2007 8:35:44 PM

Page 11



APPENDIX B

TRUCK QUESTIONNAIRE FORMS

ALL BIDDERS MUST COMPLETE AND RETURN A QUESTIONNAIRE FORM WITH THE BID FOR EACH TRUCK ITEM TO BE CONSIDERED FOR AWARD OF THAT ITEM. Bids submitted without an adequately completed questionnaire form for EACH TRUCK ITEM will not be considered for award of that item. It is the responsibility of each bidder to copy this form in sufficient quantity to submit to Purchasing Operations prior to the scheduled bid due date. A single form may apply to more than one item, simply list the item numbers to which the questionnaire applies in the appropriate space. If part of the questionnaire does not apply, simply indicate "not applicable" in those spaces.

NAME OF BIDDER: Red Holman Pontiac Gmc ITEM NO(s). Spec # 3958-0112

MAKE OF TRUCK: Gmc MODEL: C4500 TC4C044 GVWR 17500 lbs.

PAYLOAD: 9146 # W.B. 152" C.A. 84" C.E. 146"

ENGINE: (GAS - DIESEL) Gas MAKE: Gm MODEL: LRW, P.1SAE H.P. 325

FUEL TANK(S) CAPACITY: 40 (GALS. TOTAL) TRANSMISSION: Allison 1000 MBV 6spd

SPRING CAP. @ GROUND EACH: FRONT 4000 lbs. REAR 6750 lbs. AUX. N/A lbs.

AXLES: FRONT 8000 lbs. REAR 13500 lbs. REAR RATIO 5.13

ALTERNATOR: 150 amps. BATTERY 600 cca

TIRE SIZE: FRONT 245/70R19.5G PR REAR 245/70R19.5G PR SINGLE _____ DUAL M&S

TIRE: MAKE Goodyear STYLE NO. TBD MFG. CODE XTY/YTY

HOIST: MAKE N/A MODEL N/A INSTALLING CO. N/A

BODY: MAKE N/A MODEL N/A INSTALLING CO. N/A

POWER LIFT GATE: MAKE N/A MODEL N/A CAPACITY N/A lbs.

PLATFORM SIZE: N/A

OTHER EQUIPMENT INSTALLED BY BODY EQUIPMENT SUPPLIER AND/OR COMMENTS

This information must be returned with the bid document to Purchasing Operations, on or before the bid due date and time. However, if returned separately, it must be received by Purchasing Operations on or before the bid due date and time, and must comply with the sealed bid instructions as outlined in the ITB.

TRUCK: CAB AND CHASSIS DUAL REAR WHEELS
(G.V.W.R. 14,500 LBS., min.) (4 x 4)

MODEL-2008 CURRENT NEW

	CHEVY/ GMC <u>C4C044</u>	FORD <u>F-450</u>	DODGE <u>DM9L63</u>
G.V.W.R. (lbs.)	17,500	16,000	16,500
Wheelbase (inches)	152	140.8	144.5
C.A. (inches)	84	60	60
Engine: Diesel	6.6L	6.4L	6.7L
Type & No. of Cylinders	V-8	V-8 Turbo	L-6 Turbo
Net H.P.-S.A.E.	300	325	305

Transmission: Automatic:
with maximum capacity transmission oil cooler, Factory installed.

Axle, Min. Cap.-lbs.			
Front	8,000	7,000	7,000
Rear	13,500	12,000	13,500
Springs, Min. Cap. at Ground			
Front-lbs. each	4,000	2,800	TBD
Rear-lbs. each	6,750	6,000	TBD

Tires, Truck, Tubeless, Radial, to meet G.V.W.R. Rear duals, mud and snow.

TO BE STANDARD FACTORY EQUIPPED AS FOLLOWS:

The items listed below are to be supplied on all trucks, even though they may be optional with the manufacturer. Therefore, these specifications are to be furnished on all vehicles:

- 12 Volt auxiliary outlet
- Air Conditioning - All trucks
- Anti-freeze protection, to -30°F.
- Arm Rest-Driver's side.
- Color-Manufacturers Standard to be selected.
- Coolant System-Maximum Size Available, including the Heaviest Duty Radiator
- Dome Light.
- Electric wiring-All wiring passing through holes in metal or non-metal wearing surfaces, which could cause wear of the insulation, shall be adequately protected by

rubber or plastic grommets, and/or non-metallic conduit. Ends of all wires shall be adequately anchored to prevent loosening.

- ☑ Frame length-on all body installations without hoists the cab to end of frame length shall be the same length as the body being mounted, plus the length of any setback.
- ☑ Fuel Tanks, Diesel, with sending unit and magnetic drain plug, on all trucks over 21,000 G.V.W.R., painted Black and labeled "Diesel Fuel Only".
- ☑ Hub caps on all pickups and vans up to and including 10,000 G.V.W.R. If not available from dealer cap nuts shall be furnished.
- ☑ Keys-(2) sets with code numbers; shall be with vehicle at time of delivery.
- ☑ Mirrors-All trucks are to be equipped with R.H. and L.H. outside rear-view mirrors to comply with Michigan laws; all trucks up to and including 15,000 G.V.W.R. shall be equipped with inside rear-view mirror. In all cases, outside R.H. & L.H. rear view mirrors shall provide full vision past all body installations. Mirrors shall be of stainless steel or high impact plastic construction unless denoted otherwise in individual truck specifications. All West Coast Type or Below Eye Level Camper Style Mirrors shall have stainless steel or high impact plastic heads, brackets, and hardware.
- ☑ Mud flaps, Anti-Sail Type, when required, are to be plain, rubber 1/4" thick, without advertising on either side.
- ☑ Painting-preclean and metal prep, any bare metal surfaces prior to applying a compatible red oxide or zinc chromate primer. When painting over a manufacturer's standard paint, metal prepping and primer may be omitted, provided an acceptable bond can be achieved.
- ☑ Equipment mounting- when mounting equipment on truck cab and chassis, all holes shall be drilled or punched. There shall be no flame cutting or welding on the frame side rails.
- ☑ Paint codes-factory paint codes shall be furnished with all vehicles; for all after market painting both the brand and paint code shall be furnished.
- ☑ Pre-delivery inspection and servicing.
- ☑ Radio - AM/FM Manufacturers Standard, Factory Installed
- ☑ Seat Belts with Shoulder Harness (3-Point Restraint System for Driver & Passenger)
- ☑ Seats-Split Bench type, unless otherwise specified
- ☑ Shock absorbers-(Heaviest Duty Available), front all trucks. Rear, up to and including 15,000 G.V.W.R.
- ☑ Spare tire, or Rim, not to be furnished unless specified. If specified, tires to be of same mfg., tread design to be same as front tires.
- ☑ Speed Control, Factory Installed
- ☑ Steering-Power, Tilt Wheel
- ☑ Sun visors-dual.
- ☑ Jack-Furnish on trucks up to and including 12,000 G.V.W.R.
- ☑ Windshield wipers-dual, intermittent speed electric, with automatic type washers.

All items removed for installation of optional equipment shall be returned to the State of Michigan.

TO BE EQUIPPED IN COMPLIANCE WITH ALL APPLICABLE FEDERAL MOTOR VEHICLE SAFETY STANDARDS AND REGULATIONS. ALL VEHICLES MUST BE EQUIPPED TO COMPLY WITH ALL REQUIREMENTS OF THE MICHIGAN MOTOR VEHICLE CODE.

- **Delete: On GM vehicles, OnStar and XM radio are deleted.**

ADDITIONAL OPTIONS:

These options are in addition to the options listed above as “STANDARD FACTORY EQUIPPED” and are to be included on this vehicle.

- Alternator-95 amp., min.
- Battery-12 Volt, 600 CCA, minimum.
- Brakes-Power.
- Fuel capacity-largest available from mfg.
- Mirrors-Rear View, Inside. Outside R.H. and L.H., below eye level, extended reach, swing away type, 51 sq. in., minimum. Installed, with stainless steel or powder coated steel heads, brackets, and hardware. GMC: Composite mirror heads
- Spare tire and wheel. GMC: spare wheel only – Tire not available
- Steering-Power.
- Wrench-wheel. GMC: Wrench not available

ADDITIONAL MDOT OPTIONS: (Note: These options are not included in the MiDEAL price)

These options are in addition to the options listed above as “STANDARD FACTORY EQUIPPED” and are to be included on this MDOT vehicle.

- Axle Rear Limited slip
- Hubs autolocking on front GMC: manual locking front hubs only
- Keys – (1) additional set (total of 3 sets) with code numbers; shall be with the vehicle at the time of delivery.
- Switches, upfitter for auxillary GMC: panel std, switches avail from body upfitter
- Throttle, Electronic, High Idle Engine RPM Control.
- Towing package: Heaviest duty available from manufacturer GMC: standard
- Trailer brake controller, factory installed GMC: Not available on chassis

PRICING SHEET

<u>TRUCK: CAB AND CHASSIS DUAL REAR WHEELS</u> (G.V.W.R. 14,500 LBS., min.) (4 x 4) Mich. Spec. #3958-0113		
Standard Equipped Per above Specification (Including options as specified above)	Standard Equipped Cost	
Make: GMC Model: C4500 F.O.B. - Dealership Delivery Cost Per Mile \$1.50	\$36,362.00*	
Final Point of Assembly: Flint, MI		
<u>Dealer Information</u>		
Dealer Name: Red Holman Pontiac GMC		
Street Address: 35300 Ford Road		
City: Westland	State: MI	Zip: 48185
Contact Name: Albert Li		
Telephone: (800) 482-3032		
Cell: (734) 637-6643		
E-mail: aclixx@hotmail.com		

*Please Note: A vehicle order confirmation sheet is included for each vehicle. These documents shall include all the "standard options" as listed for the State of Michigan standard specification.

Vehicle Order Confirmation Sheet
 Spec # 3958-0113

Prepared By:
 Albert Li
 Red Holman Pontiac GMC
 35300 Ford Rd
 Westland, MI 48185
 Phone: (734) 721-1144
 Fax: (734) 721-1780
 Email: aclix@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

SELECTED MODEL & OPTIONS

SELECTED MODEL - 2008 Fleet/Non-Retail TC4C044 Regular Cab 4WD

<u>Code</u>	<u>Description</u>	<u>MSRP</u>
TC4C044	2008 GMC TC4500 Regular Cab 4WD	\$35,860.00

SELECTED VEHICLE COLORS - 2008 Fleet/Non-Retail TC4C044 Regular Cab 4WD

<u>Code</u>	<u>Description</u>
69V	Interior: Very Dark Pewter
50U	Exterior 1: Summit White
50L	Exterior 2: Summit White

SELECTED OPTIONS - 2008 Fleet/Non-Retail TC4C044 Regular Cab 4WD

CATEGORY

<u>Code</u>	<u>Description</u>	<u>MSRP</u>
PREFERRED EQUIPMENT GROUP		
C4C044	CUSTOM/BASE MODEL	\$0.00
DIESEL ENGINE		
LRX	DURAMAX DIESEL 6.6L, 300 HP (223 KW) @ 3000 RPM, 520 LB-FT (705 N-M) TORQUE @ 1600 RPM	\$9,259.00
GVWR		
GZX	17,500 LBS. (7938 KG) CAPACITY	INC
EMISSION		
FE9	FEDERAL REQUIREMENTS	INC
ROAD SPEED GOVERNOR		
KYW	75 MPH (120 KPH) SPEED GOVERNOR	INC
ALTERNATOR		
KG4	AD244, DELCO-REMY 150-AMP MAXIMUM	\$0.00
BATTERY		
TNL	DUAL AC DELCO, 750 CCA, 12V	INC

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.0, Data updated 12/11/2007 11:05:00 AM
 ©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 19, 2007 8:44:54 PM

Page 1

Prepared By:
 Albert Li
 Red Holman Pontiac GMC
 35300 Ford Rd
 Westland, MI 48185
 Phone: (734) 721-1144
 Fax: (734) 721-1780
 Email: aclbx@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

SELECTED MODEL & OPTIONS

SELECTED OPTIONS - 2008 Fleet/Non-Retail TC4C044 Regular Cab 4WD

CATEGORY		MSRP
Code	Description	
ENGINE SHUTDOWN		
KPJ	AUTOMATIC ENGINE SHUTDOWN WITH ALARM	INC
EXHAUST SYSTEM		
NB5	SINGLE HORIZONTAL-DRIVER SIDE MOUNTED INSIDE FRAME RAIL,	INC
POWER TAKE OFF		
PTX	OPTION PTO NOT REQUIRED	\$0.00
TRANSMISSION		
MBV	AUTOMATIC, ALLISON 1000 HS/RDS SERIES 6-SPEED	\$0.00
TRANSMISSION FLUID		
MBT	TRANSYND SYNTHETIC AUTOMATIC TRANSMISSION FLUID	INC
TRANSMISSION EQUIPMENT		
KNP	AUXILIARY TRANSMISSION OIL COOLER	\$95.00
TRANSFER CASE		
NP1	NEW VENTURE GEAR-MODEL NV273 TWO-SPEED	INC
FRONT AXLE		
G38	8000 LBS. (3629 KG) CAPACITY	\$0.00
FRONT SUSPENSION		
FSN	TAPERED LEAF, 8000 LBS. (3629 KG) CAPACITY	\$0.00
FRONT STABILIZER BAR		
F59	STABILIZER BAR	INC
FRONT WHEEL		
Q82	19.5" X 6.75" (49.5 CM X 17.1 CM), STEEL DISC	\$0.00
FRONT TIRE		
XTY	245/70R19.5G	\$0.00
FRONT TIRE BRAND		
R4A	GOODYEAR	\$0.00
FRONT TIRE TREAD		
R3H	HIGHWAY TRACTION	INC

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.0, Data updated 12/11/2007 11:05:00 AM
 ©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.
 Customer File:

December 19, 2007 8:44:54 PM

Page 2

Prepared By:
 Albert Li
 Red Holman Pontiac GMC
 35300 Ford Rd
 Westland, MI 48185
 Phone: (734) 721-1144
 Fax: (734) 721-1780
 Email: aclbx@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

SELECTED MODEL & OPTIONS

SELECTED OPTIONS - 2008 Fleet/Non-Retail TC4C044 Regular Cab 4WD

<u>CATEGORY</u>		<u>MSRP</u>
<u>Code</u>	<u>Description</u>	
SINGLE SPEED REAR AXLE		
HD2	SINGLE SPEED, DANA S110 13,500 LBS. (6123 KG) CAPACITY	INC
AXLE RATIO		
058	5.13:1	INC
TRACTION CONTROL		
G80	REAR LIMITED SLIP DIFFERENTIAL	INC
REAR SUSPENSION		
GR4	MULTI-LEAF, 13,500 LBS. (6123 KG) CAPACITY	INC
BOLTED OR RIVETED SUSPENSION		
EV8	REAR SUSPENSION BRACKETS ARE RIVETED TO FRAME IN LIEU OF BOLTS	\$0.00
REAR SHOCK ABSORBER		
SAN	REAR SHOCK ABSORBER NOT DESIRED	\$0.00
REAR WHEEL		
Q83	19.5" X 6.75" (49.5 CM X 17.1 CM), STEEL DISC	\$0.00
REAR TIRE		
YTY	245/70R19.5G	\$0.00
REAR TIRE BRAND		
S4A	GOODYEAR	\$0.00
REAR TIRE TREAD		
S3H	HIGHWAY TRACTION	INC
SPARE WHEEL		
SNF	FRONT	\$128.00
WHEELBASE		
EG9	152" (386.1 CM)	\$0.00
FUEL TANK		
NH4	SINGLE, 40-GALLON (151L) FUEL CAPACITY	INC
PARKING BRAKE		

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.0, Data updated 12/11/2007 11:05:00 AM
 ©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 19, 2007 8:44:54 PM

Page 3

Prepared By:
 Albert Li
 Red Holman Pontiac GMC
 35300 Ford Rd
 Westland, MI 48185
 Phone: (734) 721-1144
 Fax: (734) 721-1780
 Email: acli@hotmai.com

2008 Fleet/Non-Retail GMC TC4500

SELECTED MODEL & OPTIONS

SELECTED OPTIONS - 2008 Fleet/Non-Retail TC4C044 Regular Cab 4WD

<u>CATEGORY</u>		<u>Code</u>	<u>Description</u>	<u>MSRP</u>
PARKING BRAKE		J69	REAR IN-WHEEL PARK BRAKE	INC
DRIVER CONVENIENCE PACKAGES		ZQ3	DRIVER CONVENIENCE PACKAGE	\$245.00
MISCELLANEOUS CAB EQUIPMENT		N33	TILT-WHEEL ADJUSTABLE STEERING	INC
		K34	CRUISE CONTROL,	INC
AIR CONDITIONING		C60	AIR CONDITIONING	\$852.00
DRIVER SEAT		AS4	HIGH-BACK BUCKET, FIXED HEIGHT, MANUAL ADJUSTER	INC
PASSENGER SEAT		A59	TWO-PERSON, WITHOUT STORAGE	\$180.00
AIRBAGS		AL3	SUPPLEMENTAL INFLATABLE RESTRAINTS NOT INCLUDED	INC
RADIO		UM7	DELCO AM-FM STEREO RADIO	\$150.00
EXTERIOR MIRRORS		DB5	MANUAL, 102" (259 CM) WIDE LOAD, INTEGRAL ARM, INTEGRAL CONVEX MIRROR	INC
PAINT		ZY1	SOLID NON-METALLIC PAINT	INC
INTERIOR TRIM		69I	VERY DARK PEWTER	INC
SEAT TRIM		_V	VINYL SEAT TRIM	INC
ADDITIONAL OPTIONS		VQ1	FLEET PROCESSING OPTION	\$0.00

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.0, Data updated 12/11/2007 11:05:00 AM
 ©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 19, 2007 8:44:54 PM

Page 4

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclix@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

SELECTED MODEL & OPTIONS

SELECTED OPTIONS - 2008 Fleet/Non-Retail TC4C044 Regular Cab 4WD

CATEGORY

<u>Code</u>	<u>Description</u>	<u>MSRP</u>
	OPTIONS TOTAL	\$10,909.00

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.0, Data updated 12/11/2007 11:05:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 19, 2007 8:44:54 PM

Page 5

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: acliix@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC4C044 Regular Cab 4WD

EXTERIOR

- Paint scheme, solid, upper color, Summit White
- Paint scheme, solid, lower color, Summit White
- Exterior roof drip moldings
- Bumper, front, steel, 96" (243.8 cm) wide - styled to minimized wall to wall turn diameter painted argent
- Steps under cab doors
- Front mud flaps
- Integral grille and fenders - The grille is the same color as hood with single halogen headlamps.
- Roof marker lamps
- Daytime running lamps
- Windows, Solar-Ray tinted. Light tinted windshield and side window glass with light transmissivity of 70%
- Mirrors, manual, 102" (259 cm) wide load, integral arm, integral convex mirror - black molded composite 12" x 7" (30.5 cm x 17.8 cm) with 6" x 7" (15.2 cm x 17.8 cm) convex section
- Windshield wipers, 2-speed and intermittent, with pulse washers
- Provisions for mounting front license plate
- Positive door stops

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.0, Data updated 12/11/2007 11:05:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.
Customer File:

December 19, 2007 8:44:54 PM

Page 6

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclix@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC4C044 Regular Cab 4WD

INTERIOR

- Seat, driver, high-back bucket, fixed height, manual adjuster - storage in the seat riser with a small lip at the front to stop contents from sliding out
- Seat, passenger, high-back bucket, fixed height, manual back angle adjuster - storage in the seat riser with a small lip at the front to stop contents from sliding out
- Seat trim, vinyl, Very Dark Pewter
- Interior trim, Very Dark Pewter (Requires 69V Very Dark Pewter vinyl or 69C Very Dark Pewter cloth)
- Trim console - located next to driver's seat and two cupholders
- Molded vinyl floor covering
- Steering wheel 16"
- Two sided single common key for doors and ignition
- Headlamp warning buzzer
- Warning tone, key-in-ignition
- Tachometer
- Electronic engine hour meter
- Engine "Check Gauges" telltale light and buzzer, oil pressure gauge
- Gauges, low oil pressure and coolant level, high coolant and engine oil temperature
- Vinyl door trim panels - with storage pocket on front doors, beverage holders, and reflector on all doors
- Stepwell storage areas at each door front and rear. Includes storage cover.
- Cloth headliner
- Sunshades, passenger side and driver side, vinyl-covered
- Coat hooks (2) located on cab back panel
- Provisions for stereo - Includes AM/FM antenna, lead wiring for speakers, and separate door chime module (N/A with ZQ2 power convenience option)
- Air conditioning not desired - this option should be ordered only when a customer does not require air conditioning
- Powerpoints - two in-cab power sources (in addition to optional cigarette lighter) for electrical plug-in accessories

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.0, Data updated 12/11/2007 11:05:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 19, 2007 8:44:54 PM

Page 7

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: acliix@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC4C044 Regular Cab 4WD

- Underhood bodybuilder connections accessory power supply - Provides 12V power supply from the battery with two separate 30 amp fused circuits

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.0, Data updated 12/11/2007 11:05:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 19, 2007 8:44:54 PM

Page 8

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclix@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC4C044 Regular Cab 4WD

MECHANICAL

- GVWR, 17,500 lbs. (7938 kg) capacity - GVWR. Maximum GCWR 26,000 lb. Note: Trucks that are used primarily to tow a trailer may be liable to Federal Excise Tax (FET). A New Law (Highway Transportation Bill HR3) was passed on August 10, 2005 - Check with IRS for guidelines
- Engine, Vortec 8.1L MD gasoline V8, 325 hp (239 kw) @ 4000 rpm and 450 lb-ft torque (610 N-m) @ 2,800 rpm. - Maximum engine speed 5000 rpm. Oil Level Sensor: Warning sensor for low oil levels
- Air cleaner, dry type
- Cooling, anti-freeze protection temperature - -40 degrees F (-40 degrees C)
- 75 mph (120 kph) speed governor - Required by the speed rating of the tires ordered
- Alternator, AD244 Delco-Remy 150-amp maximum (N/A with ANM Fire and Rescue or YF2 Ambulance Packages)
- Battery, single AC Delco, 600 CCA, 12V - 115-minute reserve capacity @ 27 degrees C, 600 CCA @ -18 degrees C grounded directly to starter. (Requires gasoline engine; N/A with ANQ Snow Plow Prep)
- Exhaust, single horizontal - driver side mounted inside frame rail, with gasoline engine stainless-steel exhaust with catalytic converter, with diesel engines, stainless-steel exhaust, oxidation catalyst, diesel particulate filter and exhaust gas cooler
- Option PTO not required - This option should only be ordered when a customer specifically does not require an electric hand throttle for use with power-take-off provisions. (Note: Will delete transmission PTO gear.)
- Transmission, automatic, Allison 1000 HS/RDS Series 6-speed - With parking pawl and column shift, includes 4th Generation Electronic Controls and 0.61 overdrive. Torque Rating: 660 lb-ft (895 N-m) with shift energy management. Available with a Gross Vehicle Weight up to 19,500 lbs. (8845 kg) and a Gross Combination Weight Rating up to 26,000 lbs. (11,790 kg). To include PTO gear, please order with RPO PTO for Allison 1000 RDS Rugged Duty Series transmission. Includes transmission-oil cooler located inside radiator. With Option PTX the truck will be equipped with the Allison 1000 HS Highway Series transmission. (N/A with ANM Fire and Rescue or YF2 Ambulance Package)
- TranSynd synthetic automatic transmission fluid
- Transfer case, New Venture Gear - model NV273 two-speed, electrically actuated, IP mounted switch, includes shield
- Front axle, 8000 lbs. (3629 kg) capacity - Solid drive axle. Up to 45 degree turn angle, includes 4 piston brake apply calipers and manual locking hubs
- Front suspension, tapered leaf, 8000 lbs. (3629 kg) capacity

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.0, Data updated 12/11/2007 11:05:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 19, 2007 8:44:54 PM

Page 9

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: acli@hotmai.com

2008 Fleet/Non-Retail GMC TC4500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC4C044 Regular Cab 4WD

- Front shock absorber, diameter 1.375" (35mm)
- Front stabilizer bar, Solid bar style, 1.5" (38mm)
- Front wheels, 19.5" x 6.75" (49.5 cm x 17.1 cm), steel disc - 8-hole, 10,000 lbs. (4536 kg) capacity, (Requires Q83 steel rear wheel and XTY or XNC front tires)
- Front tire size, 245/70R19.5G - 9090 lbs. (4123 kg) capacity (Requires KYR 65 mph or KYW 75 mph (120 kph) road speed governor, Q82 or RPM front wheels. With R4A Goodyear tire, requires R3H highway traction tread)
- Front tire manufacturer code, Goodyear (Requires S4A Goodyear)
- Front tread, highway traction
- Rear axle, single speed, Dana S110 13,500 lbs. (6123 kg) capacity - full floating, includes 2-piston brake applied calipers
- Four-wheel drive
- Rear axle ratio, 5.13:1 (Requires HD2 single speed rear axle)
- Rear limited slip differential
- Rear suspension, multi-leaf, 13,500 lbs. (6123 kg) capacity
- Rear suspension brackets are riveted to frame in lieu of bolts
- Rear shock absorber not desired (N/A with tapered leaf springs)
- Rear wheels, 19.5" x 6.75" (49.5 cm x 17.1 cm), steel disc - 8-hole, 20,000 lbs. (9072 kg) capacity (Requires Q82 front wheels and YTY or YNC rear tires)
- Rear tire size, 245/70R19.5G - 17,500 lbs. (7938 kg) capacity (Requires KYR 65 mph or KYW 75 mph (120 kph) road speed governor and Q83 or RPW rear wheels. With S4A Goodyear tire, requires S3H highway traction tread)
- Rear tire manufacturer code, Goodyear (Requires R4A Goodyear)
- Rear tread, highway traction
- Wheelbase, 152" (386.1 cm) - with 84" (213.4 cm) CA and 146" (370.8 cm) CE. Includes a 6mm 80,000 psi (551,600 kPa) yield strength, steel frame, RBM: 610,400 Section Modulus 7.63
- Frame, 8mm - 80,000 psi (551,600 kPa) yield strength, steel frame, RBM: 610,400 Section Modulus 7.63
- Fuel tank, single, 40-gallon (151L) fuel capacity - gas or diesel, located behind rear axle with fuel fill neck through frame rail and a black tethered fuel cap with gasoline engine and green un-tethered fuel cap with diesel engines. DRIVER SIDE FILL NECK ONLY. NO AUXILIARY PORTS. MINIMUM OVERHANG = 60" (5 FEET)

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.0, Data updated 12/11/2007 11:05:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.
Customer File:

December 19, 2007 8:44:54 PM

Page 10

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclbx@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC4C044 Regular Cab 4WD

- Fuel sender assembly. Robust fuel pump
- Tethered fuel cap
- Steering, power - ZF variable ratio power
- Brakes, front, power, 4-wheel disc, 4 channel ABS 4-piston - (See front axle options for more detail)
- Brakes, rear, power, 4-wheel disc, 4 channel ABS 2-piston - (See rear axle options for more detail)
- Parking brake, rear in-wheel park brake - hand lever operated

SAFETY

- 4-wheel disc, 4-channel ABS
- Air bags, Supplemental Inflatable Restraints not included.
- This vehicle does not include any air bags
- Seat belt warning indicator
- Daytime running lamps

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.0, Data updated 12/11/2007 11:05:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 19, 2007 8:44:54 PM

Page 11



APPENDIX B

TRUCK QUESTIONNAIRE FORMS

ALL BIDDERS MUST COMPLETE AND RETURN A QUESTIONNAIRE FORM WITH THE BID FOR EACH TRUCK ITEM TO BE CONSIDERED FOR AWARD OF THAT ITEM. Bids submitted without an adequately completed questionnaire form for EACH TRUCK ITEM will not be considered for award of that item. It is the responsibility of each bidder to copy this form in sufficient quantity to submit to Purchasing Operations prior to the scheduled bid due date. A single form may apply to more than one item, simply list the item numbers to which the questionnaire applies in the appropriate space. If part of the questionnaire does not apply, simply indicate "not applicable" in those spaces.

NAME OF BIDDER: Red Holman Pontiac GMC ITEM NO(s). Spec# 3958-0113
 MAKE OF TRUCK: Gmc MODEL: C4500 TCY044 GVWR 17500 lbs.
 PAYLOAD: 8860 # W.B. 152" C.A. 84" C.E. 146"
 ENGINE: (GAS - DIESEL) Diesel MAKE: Gm Duramax MODEL: LRX, 6.6 SAE H.P. 300
 FUEL TANK(S) CAPACITY: 40 (GALS. TOTAL) TRANSMISSION: Allison 1000 M6V 6-spd
 SPRING CAP. @ GROUND EACH: FRONT 4000 lbs. REAR 6750 lbs. AUX. N/A lbs.
 AXLES: FRONT 8000 lbs. REAR 13500 lbs. REAR RATIO 5.13
 ALTERNATOR: 150 amps. BATTERY Dual 750 cca.
 TIRE SIZE: FRONT 245/70R19.5G PR REAR 245/70R19.5 6PR SINGLE DUAL M&S
 TIRE: MAKE Goodyear STYLE NO. TBD MFG. CODE XTY/YTY
 HOIST: MAKE N/A MODEL N/A INSTALLING CO. N/A
 BODY: MAKE N/A MODEL N/A INSTALLING CO. N/A
 POWER LIFT GATE: MAKE N/A MODEL N/A CAPACITY N/A lbs.
 PLATFORM SIZE: N/A

OTHER EQUIPMENT INSTALLED BY BODY EQUIPMENT SUPPLIER AND/OR COMMENTS

This information must be returned with the bid document to Purchasing Operations, on or before the bid due date and time. However, if returned separately, it must be received by Purchasing Operations on or before the bid due date and time, and must comply with the sealed bid instructions as outlined in the ITB.

TRUCK: CAB AND CHASSIS
(G.V.W.R. 15,000 LBS., min.)

MODEL-2008 CURRENT NEW

	CHEV/ GMC C4500 <u>C4C042</u>	FORD <u>F-450</u>
G.V.W.R. (lbs.)	16,500	16,000
Wheelbase (inches)	152	164.8
C.A. (inches)	84	84
Engine: Gasoline	8100	Triton
Type & No. of Cylinders	V-8	V-10
Net H.P.-S.A.E.	325	362

Transmission: Automatic:
with maximum capacity transmission oil cooler. Factory installed.

Axle, Min. Cap.-lbs.		
Front	7,000	7,000
Rear	11,000	12,000
Springs, Min. Cap. at Ground		
Front-lbs. each	3,500	2,800
Rear-lbs. each	5,500	6,000

Tires, Truck, Tubeless, Radial, to meet G.V.W.R. Rear duals, mud and snow.

TO BE STANDARD FACTORY EQUIPPED AS FOLLOWS:

The items listed below are to be supplied on all trucks, even though they may be optional with the manufacturer. Therefore, these specifications are to be furnished on all vehicles:

- 12 Volt auxiliary outlet
- Air Conditioning - All trucks
- Anti-freeze protection, to -30°F.
- Arm Rest-Driver's side.
- Color-Manufacturers Standard to be selected.
- Coolant System-Maximum Size Available, including the Heaviest Duty Radiator
- Dome Light.
- Electric wiring-All wiring passing through holes in metal or non-metal wearing surfaces, which could cause wear of the insulation, shall be adequately protected by

rubber or plastic grommets, and/or non-metallic conduit. Ends of all wires shall be adequately anchored to prevent loosening.

- ☑ Frame length-on all body installations without hoists the cab to end of frame length shall be the same length as the body being mounted, plus the length of any setback.
- ☑ Fuel Tanks, Diesel, with sending unit and magnetic drain plug, on all trucks over 21,000 G.V.W.R., painted Black and labeled "Diesel Fuel Only".
- ☑ Hub caps on all pickups and vans up to and including 10,000 G.V.W.R. If not available from dealer cap nuts shall be furnished.
- ☑ Keys-(2) sets with code numbers; shall be with vehicle at time of delivery.
- ☑ Mirrors-All trucks are to be equipped with R.H. and L.H. outside rear-view mirrors to comply with Michigan laws; all trucks up to and including 15,000 G.V.W.R. shall be equipped with inside rear-view mirror. In all cases, outside R.H. & L.H. rear view mirrors shall provide full vision past all body installations. Mirrors shall be of stainless steel or high impact plastic construction unless denoted otherwise in individual truck specifications. All West Coast Type or Below Eye Level Camper Style Mirrors shall have stainless steel or high impact plastic heads, brackets, and hardware.
- ☑ Mud flaps, Anti-Sail Type, when required, are to be plain, rubber 1/4" thick, without advertising on either side.
- ☑ Painting-preclean and metal prep, any bare metal surfaces prior to applying a compatible red oxide or zinc chromate primer. When painting over a manufacturer's standard paint, metal prepping and primer may be omitted, provided an acceptable bond can be achieved.
- ☑ Equipment mounting- when mounting equipment on truck cab and chassis, all holes shall be drilled or punched. There shall be no flame cutting or welding on the frame side rails.
- ☑ Paint codes-factory paint codes shall be furnished with all vehicles; for all after market painting both the brand and paint code shall be furnished.
- ☑ Pre-delivery inspection and servicing.
- ☑ Radio - AM/FM Manufacturers Standard, Factory Installed
- ☑ Seat Belts with Shoulder Harness (3-Point Restraint System for Driver & Passenger)
- ☑ Seats-Split Bench type, unless otherwise specified
- ☑ Shock absorbers-(Heaviest Duty Available), front all trucks. Rear, up to and including 15,000 G.V.W.R.
- ☑ Spare tire, or Rim, not to be furnished unless specified. If specified, tires to be of same mfg., tread design to be same as front tires.
- ☑ Speed Control, Factory Installed
- ☑ Steering-Power, Tilt Wheel
- ☑ Sun visors-dual.
- ☑ Jack-Furnish on trucks up to and including 12,000 G.V.W.R.
- ☑ Windshield wipers-dual, intermittent speed electric, with automatic type washers.

All items removed for installation of optional equipment shall be returned to the State of Michigan.

TO BE EQUIPPED IN COMPLIANCE WITH ALL APPLICABLE FEDERAL MOTOR VEHICLE SAFETY STANDARDS AND REGULATIONS. ALL VEHICLES MUST BE EQUIPPED TO COMPLY WITH ALL REQUIREMENTS OF THE MICHIGAN MOTOR VEHICLE CODE.

- **Delete: On GM vehicles, OnStar and XM radio are deleted.**

ADDITIONAL OPTIONS:

These options are in addition to the options listed above as “STANDARD FACTORY EQUIPPED” and are to be included on this vehicle.

- Air Conditioning – Factory Installed
- Alternator-80 amp., min.
- Battery-12 Volt, 600 CCA, minimum.
- Brakes-Power.
- Fuel capacity-largest available from mfg.
- Mirrors-Rear View, Inside. Outside R.H. and L.H., below eye level, extended reach, swing away type, 51 sq. in., minimum. Installed, with stainless steel or powder coated steel heads, brackets, and hardware. GMC: Composite Mirror Heads
- Spare tire and wheel. GMC: Spare Wheel Only: No Tire Available
- Steering-Power.
- Wrench-wheel. GMC: No wrench available

ADDITIONAL MDOT OPTIONS: (Note: These options are not included in the MiDEAL price)

These options are in addition to the options listed above as “STANDARD FACTORY EQUIPPED” and are to be included on this MDOT vehicle.

- Axle Rear Limited slip
- Hubs autolocking on front GMC: not available on 2 wd chassis
- Keys – (1) additional set (total of 3 sets) with code numbers; shall be with the vehicle at the time of delivery.
- Switches, upfitter for auxillary GMC: panel only – switches available from body upfitter
- Throttle, Electronic, High Idle Engine RPM Control.
- Towing package: Heaviest duty available from manufacturer GMC: standard
- Trailer brake controller, factory installed GMC – Not available

PRICING SHEET

<u>TRUCK: CAB AND CHASSIS</u> (G.V.W.R. 15,000 LBS., min.) Mich. Spec. #3958-0114	
Standard Equipped Per above Specification (Including options as specified above)	Standard Equipped Cost
Make: GMC Model: C4500 <i>F.O.B. - Dealership</i> Delivery Cost Per Mile \$1.50	\$22,834.00*
Final Point of Assembly: Flint, MI	
<u>Dealer Information</u>	
Dealer Name: Red Holman Pontiac GMC	
Street Address: 35300 Ford Road	
City: Westland	State: MI Zip: 48185
Contact Name: Albert Li	
Telephone: (800) 482-3032	
Cell: (734) 637-6643	
E-mail: aclixx@hotmail.com	

*Please Note: A vehicle order confirmation sheet is included for each vehicle. These documents shall include all the "standard options" as listed for the State of Michigan standard specification.

Vehicle Order Confirmation Sheet
Spec # 3958-0114

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclbx@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

SELECTED MODEL & OPTIONS

SELECTED MODEL - 2008 Fleet/Non-Retail TC4C042 Regular Cab 2WD

<u>Code</u>	<u>Description</u>	<u>MSRP</u>
TC4C042	2008 GMC TC4500 Regular Cab 2WD	\$28,890.00

SELECTED VEHICLE COLORS - 2008 Fleet/Non-Retail TC4C042 Regular Cab 2WD

<u>Code</u>	<u>Description</u>
-	Interior: No color has been selected.
-	Exterior 1: No color has been selected.
-	Exterior 2: No color has been selected.

SELECTED OPTIONS - 2008 Fleet/Non-Retail TC4C042 Regular Cab 2WD

CATEGORY

<u>Code</u>	<u>Description</u>	<u>MSRP</u>
PREFERRED EQUIPMENT GROUP		
C4C042	CUSTOM/BASE MODEL	\$0.00
GASOLINE ENGINE		
LRW	VORTEC 8.1L MD GASOLINE V8, 325 HP (239 KW) @ 4000 RPM AND 450 LB-FT TORQUE (610 N-M) @ 2800 RPM.	\$0.00
GVWR		
C7R	16,500 LBS. (7484 KG) CAPACITY	\$0.00
EMISSION		
FE9	FEDERAL REQUIREMENTS	INC
ALTERNATOR		
KG4	AD244, DELCO-REMY 150-AMP MAXIMUM	\$0.00
BATTERY		
TM1	SINGLE AC DELCO, 600 CCA, 12V	\$0.00
EXHAUST SYSTEM		

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.0, Data updated 12/11/2007 11:05:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 19, 2007 9:19:46 PM

Page 1

Prepared By:
 Albert Li
 Red Holman Pontiac GMC
 35300 Ford Rd
 Westland, MI 48185
 Phone: (734) 721-1144
 Fax: (734) 721-1780
 Email: aclixx@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

SELECTED MODEL & OPTIONS

SELECTED OPTIONS - 2008 Fleet/Non-Retail TC4C042 Regular Cab 2WD

<u>CATEGORY</u>		<u>MSRP</u>
<u>Code</u>	<u>Description</u>	
EXHAUST SYSTEM		
NB5	SINGLE HORIZONTAL-PASSENGER SIDE MOUNTED INSIDE FRAME RAIL	INC
POWER TAKE OFF		
PTX	OPTION PTO NOT REQUIRED	\$0.00
TRANSMISSION		
MBV	AUTOMATIC, ALLISON 1000 HS/RDS SERIES 6-SPEED	\$0.00
TRANSMISSION FLUID		
MBT	TRANSYND SYNTHETIC AUTOMATIC TRANSMISSION FLUID	INC
TRANSMISSION EQUIPMENT		
KNP	AUXILIARY TRANSMISSION OIL COOLER	\$95.00
FRONT AXLE		
FM7	7000 LBS. (3175 KG) CAPACITY	INC
FRONT SUSPENSION		
FK6	TAPERED LEAF, 7000 LBS. (3175 KG) CAPACITY	INC
FRONT WHEEL		
Q82	19.5" X 6.75" (49.5 CM X 17.1 CM), STEEL DISC	\$37.00
FRONT TIRE		
XTN	225/70R19.5F	\$0.00
FRONT TIRE BRAND		
R4A	GOODYEAR	\$0.00
FRONT TIRE TREAD		
R3C	PREMIUM, HIGHWAY	\$0.00
SINGLE SPEED REAR AXLE		
GL4	SINGLE SPEED, 11,000 LBS. (4990 KG) CAPACITY	INC
AXLE RATIO		
008	4.88:1	\$0.00
REAR SUSPENSION		

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.0, Data updated 12/11/2007 11:05:00 AM
 ©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 19, 2007 9:19:46 PM

Page 2

Prepared By:
 Albert Li
 Red Holman Pontiac GMC
 35300 Ford Rd
 Westland, MI 48185
 Phone: (734) 721-1144
 Fax: (734) 721-1780
 Email: aclix@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

SELECTED MODEL & OPTIONS

SELECTED OPTIONS - 2008 Fleet/Non-Retail TC4C042 Regular Cab 2WD

CATEGORY		MSRP
Code	Description	
REAR SUSPENSION		
GR3	MULTI-LEAF, 11,000 LBS. (4990 KG) CAPACITY	INC
BOLTED OR RIVETED SUSPENSION		
EV8	REAR SUSPENSION BRACKETS ARE RIVETED TO FRAME IN LIEU OF BOLTS	\$0.00
REAR SHOCK ABSORBER		
SAN	REAR SHOCK ABSORBER NOT DESIRED	\$0.00
REAR WHEEL		
Q83	19.5" X 6.75" (49.5 CM X 17.1 CM), STEEL DISC	\$74.00
REAR TIRE		
YTN	225/70R19.5F	\$0.00
REAR TIRE BRAND		
S4A	GOODYEAR	\$0.00
REAR TIRE TREAD		
S3H	HIGHWAY TRACTION	\$0.00
SPARE WHEEL		
SNF	FRONT	\$128.00
WHEELBASE		
EG9	152" (386.1 CM)	\$163.00
FUEL TANK		
NG6	DUAL, TOTAL FUEL CAPACITY OF 40-GALLONS (151L)	\$122.00
DRIVER CONVENIENCE PACKAGES		
ZQ3	DRIVER CONVENIENCE PACKAGE	\$245.00
MISCELLANEOUS CAB EQUIPMENT		
N33	TILT-WHEEL ADJUSTABLE STEERING	INC
K34	CRUISE CONTROL,	INC
AIR CONDITIONING		
C60	AIR CONDITIONING	\$852.00

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.0, Data updated 12/11/2007 11:05:00 AM
 ©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 19, 2007 9:19:46 PM

Page 3

Prepared By:
 Albert Li
 Red Holman Pontiac GMC
 35300 Ford Rd
 Westland, MI 48185
 Phone: (734) 721-1144
 Fax: (734) 721-1780
 Email: aclbx@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

SELECTED MODEL & OPTIONS

SELECTED OPTIONS - 2008 Fleet/Non-Retail TC4C042 Regular Cab 2WD

CATEGORY		MSRP
Code	Description	
INSIDE REARVIEW MIRRORS		
D36	INSIDE DAY/NIGHT REARVIEW MIRROR	\$19.00
DRIVER SEAT		
AS4	HIGH-BACK BUCKET, FIXED HEIGHT, MANUAL ADJUSTER	INC
PASSENGER SEAT		
A59	TWO-PERSON, WITHOUT STORAGE	\$180.00
AIRBAGS		
AL3	SUPPLEMENTAL INFLATABLE RESTRAINTS NOT INCLUDED	INC
RADIO		
UM7	DELCO AM-FM STEREO RADIO	\$150.00
EXTERIOR MIRRORS		
DB5	MANUAL, 102" (259 CM) WIDE LOAD, INTEGRAL ARM, INTEGRAL CONVEX MIRROR	INC
PAINT		
ZY1	SOLID NON-METALLIC PAINT	INC
INTERIOR TRIM		
69I	VERY DARK PEWTER	INC
SEAT TRIM		
_V	VINYL SEAT TRIM	INC
ADDITIONAL OPTIONS		
VQ1	FLEET PROCESSING OPTION	\$0.00
OPTIONS TOTAL		\$2,065.00

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.0, Data updated 12/11/2007 11:05:00 AM
 ©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 19, 2007 9:19:47 PM

Page 4

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclix@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC4C042 Regular Cab 2WD

EXTERIOR

- Paint scheme, solid, upper color, Summit White
- Paint scheme, solid, lower color, Summit White
- Exterior roof drip moldings
- Bumper, front, steel, 96" (243.8 cm) wide - styled to minimized wall to wall turn diameter painted argent
- Steps under cab doors
- Front mud flaps
- Integral grille and fenders - The grille is the same color as hood with single halogen headlamps.
- Roof marker lamps
- Daytime running lamps
- Windows, Solar-Ray tinted. Light tinted windshield and side window glass with light transmissivity of 70%
- Mirrors, manual, 102" (259 cm) wide load, integral arm, integral convex mirror - black molded composite 12" x 7" (30.5 cm x 17.8 cm) with 6" x 7" (15.2 cm x 17.8 cm) convex section
- Windshield wipers, 2-speed and intermittent, with pulse washers
- Provisions for mounting front license plate
- Positive door stops

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.0, Data updated 12/11/2007 11:05:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 19, 2007 9:19:47 PM

Page 5

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclixx@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC4C042 Regular Cab 2WD

INTERIOR

- Seat, driver, high-back bucket, fixed height, manual adjuster - storage in the seat riser with a small lip at the front to stop contents from sliding out
- Seat, passenger, high-back bucket, fixed height, manual back angle adjuster - storage in the seat riser with a small lip at the front to stop contents from sliding out
- Seat trim, vinyl, Very Dark Pewter
- Interior trim, Very Dark Pewter (Requires 69V Very Dark Pewter vinyl or 69C Very Dark Pewter cloth)
- Trim console - located next to driver's seat and two cupholders
- Molded vinyl floor covering
- Steering wheel 16"
- Two sided single common key for doors and ignition
- Headlamp warning buzzer
- Warning tone, key-in-ignition
- Tachometer
- Electronic engine hour meter
- Engine "Check Gauges" telltale light and buzzer, oil pressure gauge
- Gauges, low oil pressure and coolant level, high coolant and engine oil temperature
- Vinyl door trim panels - with storage pocket on front doors, beverage holders, and reflector on all doors
- Stepwell storage areas at each door front and rear. Includes storage cover.
- Cloth headliner
- Sunshades, passenger side and driver side, vinyl-covered
- Coat hooks (2) located on cab back panel
- Provisions for stereo - Includes AM/FM antenna, lead wiring for speakers, and separate door chime module (N/A with ZQ2 power convenience option)
- Air conditioning not desired - this option should be ordered only when a customer does not require air conditioning
- Powerpoints - two in-cab power sources (in addition to optional cigarette lighter) for electrical plug-in accessories

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.0, Data updated 12/11/2007 11:05:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 19, 2007 9:19:47 PM

Page 6

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclix@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC4C042 Regular Cab 2WD

- Underhood bodybuilder connections accessory power supply - Provides 12V power supply from the battery with two separate 30 amp fused circuits

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.0, Data updated 12/11/2007 11:05:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 19, 2007 9:19:47 PM

Page 7

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclbxx@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC4C042 Regular Cab 2WD

MECHANICAL

- GVWR, 16,500 lbs. (7484 kg) capacity - GCWR limited to 24,000 lb. (10,866 kg) (Requires FM7 7000 lbs. (3175 kg) front axle) NOTE: Trucks that are used primarily to tow a trailer may be liable to Federal Excise Tax (FET). A New Law (Highway Transportation Bill HR3) was passed on August 10, 2005 - Check with IRS for guidelines
- Engine, Vortec 8.1L MD gasoline V8, 325 hp (239 kw) @ 4000 rpm and 450 lb-ft torque (610 N-m) @ 2,800 rpm. - Maximum engine speed 5000 rpm. Oil Level Sensor: Warning sensor for low oil levels
- Air cleaner, dry type
- Cooling, anti-freeze protection temperature - -40 degrees F (-40 degrees C)
- Road speed governor, controlled by the speed rating of the tires ordered. - which will be less than or equal to 85 mph (137 kph); 80 mph (129 kph) with EC9 128" wheelbase/60" CA, ML6 manual transmission and 008 4.88 rear axle ratio; 75 mph (120 kph) with EC9 128" wheelbase/60" CA, M74 automatic transmission and HD2 rear axle
- Alternator, AD244 Delco-Remy 150-amp maximum (N/A with YW2 wrecker package)
- Battery, single AC Delco, 600 CCA, 12V - 115-minute reserve capacity @ 27 degrees C, 600 CCA @ -18 degrees C grounded directly to starter, (Requires gasoline engine; N/A with ANQ Snow Plow Prep package or YW2 Wrecker package)
- Exhaust, single horizontal - passenger side mounted inside frame rail, with gasoline engine stainless-steel exhaust with catalytic converter, with diesel engines, stainless-steel exhaust, oxidation catalyst, diesel particulate filter and exhaust gas cooler
- Option PTO not required - This option should only be ordered when a customer specifically does not require an electric hand throttle for use with power-take-off provisions. (Note: Will delete transmission PTO gear.)
- Transmission, automatic, Allison 1000 HS/RDS Series 6-speed - With parking pawl and column shift, includes 4th Generation Electronic Controls and 0.61 overdrive. Torque Rating: 660 lb-ft (895 N-m) with shift energy management. Available with a Gross Vehicle Weight up to 19,500 lbs. (8845 kg) and a Gross Combination Weight Rating up to 26,000 lbs. (11,790 kg). To include PTO gear, please order with RPO PTO for Allison 1000 RDS Rugged Duty Series transmission. Includes transmission-oil cooler located inside radiator. With Option PTX the truck will be equipped with the Allison 1000 HS Highway Series transmission. (N/A with ANM Fire and Rescue or YF2 Ambulance Package)
- TranSynd synthetic automatic transmission fluid
- Front axle, 7000 lbs. (3175 kg) capacity - I-beam Wide-trac. Up to 53 degree turn angle, includes 4-piston brake apply calipers. Steering Gear Series: ZF8014
- Front suspension, tapered leaf, 7000 lbs. (3175 kg) capacity (includes stabilizer)

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.0, Data updated 12/11/2007 11:05:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 19, 2007 9:19:47 PM

Page 8

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclix@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC4C042 Regular Cab 2WD

- Front shock absorber, diameter 1.375" (35mm)
- Front stabilizer bar, 2" x 2" square tube (5 cm x 5 cm)
- Front wheels, 19.5" x 6.0" (49.5 cm x 15.2 cm), steel disc - 8-hole. 7280 lbs. (3302 kg) capacity
- Front tire size, 225/70R19.5F - 7280 lbs. (3802 kg) capacity, (With R4A Goodyear or R4L Michelin requires R3C front premium highway tread)
- Front tire manufacturer code, Goodyear (Requires S4A Goodyear)
- Front tread, premium, highway (Requires R4A Goodyear or R4L Michelin)
- Rear axle, single speed, 11,000 lbs. (4990 kg) capacity - full floating, Includes 2-piston brake applied calipers
- Rear wheel drive
- Rear axle ratio, 5.13:1 (Requires gasoline engine)
- Rear suspension, multi-leaf, 11,000 lbs. (4990 kg) capacity (Requires GL4 single speed rear axle)
- Rear suspension brackets are riveted to frame in lieu of bolts
- Rear shock absorber not desired (N/A with tapered leaf springs)
- Rear wheels, 19.5" x 6.0" (49.5 cm x 15.2 cm), steel disc - 8-hole. 14,560 lbs (6604 kg) capacity
- Rear tire size, 225/70R19.5F - 13,660 lbs. (6196 kg) capacity, (With S4A Goodyear, requires S3C rear premium highway tread or S3H rear traction tread; with S4L Michelin, requires S3C rear premium highway tread or S3J rear highway traction tread)
- Rear tire manufacturer code, Goodyear (Requires R4A Goodyear)
- Rear tread, premium, highway (Requires S4A Goodyear or S4L Michelin)
- Wheelbase, 128" (325.1 cm) - with 60" (152.4 cm) CA and 100" (254 cm) CE. Includes a 6 mm 80,000 psi (551,600 kPa) yield strength, steel frame, RBM: 610,400 Section Modulus 7.63 (Requires KYW 75 mph (120 kph) road speed governor and HD2 13,500 lbs. (6123 kg) capacity rear axle)
- Frame, 6mm - 80,000 psi (551,600 kPa) yield strength, steel frame, RBM: 610,400 Section Modulus 7.63
- Fuel tank, single, 25-gallon (95L) fuel capacity - gas or diesel located midship between the frame rails, with fuel fill neck through the frame rail (this option uses the mid-frame tank included in the NG6 dual tank option) Tethered fuel cap is black with gasoline engines, and green un-tethered fuel cap with diesel engines. **MINIMUM OVERHANG = 36" (3 FEET)** (Required in YW2 Wrecker Package, standard on 60" (152.4 cm) CA, optional on all other CA's)

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.0, Data updated 12/11/2007 11:05:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 19, 2007 9:19:47 PM

Page 9

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclixx@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC4C042 Regular Cab 2WD

- Fuel sender assembly. Robust fuel pump
- Tethered fuel cap
- Steering, power - ZF variable ratio power
- Brakes, front, power, 4-wheel disc, 4 channel ABS 2-piston - (See front axle options for more detail)
- Brakes, rear, power, 4-wheel disc, 4 channel ABS 2-piston - (See rear axle options for more detail)
- Parking brake, hand lever operated transmission mounted drum brake

SAFETY

- 4-wheel disc, 4-channel ABS
- Air bags, Supplemental Inflatable Restraints not included.
- This vehicle does not include any air bags
- Seat belt warning indicator
- Daytime running lamps

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.0, Data updated 12/11/2007 11:05:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 19, 2007 9:19:47 PM

Page 10

APPENDIX B

TRUCK QUESTIONNAIRE FORMS

ALL BIDDERS MUST COMPLETE AND RETURN A QUESTIONNAIRE FORM WITH THE BID FOR EACH TRUCK ITEM TO BE CONSIDERED FOR AWARD OF THAT ITEM. Bids submitted without an adequately completed questionnaire form for EACH TRUCK ITEM will not be considered for award of that item. It is the responsibility of each bidder to copy this form in sufficient quantity to submit to Purchasing Operations prior to the scheduled bid due date. A single form may apply to more than one item, simply list the item numbers to which the questionnaire applies in the appropriate space. If part of the questionnaire does not apply, simply indicate "not applicable" in those spaces.

NAME OF BIDDER: Red Holman Pontiac GMC ITEM NO(s). Spec # 3958-0114
 MAKE OF TRUCK: GMC MODEL: C4500 TC4642 GVWR 16500 lbs.
 PAYLOAD: 9084 W.B. 152" C.A. 84" C.E. 146"
 ENGINE: (GAS - DIESEL) Gas MAKE: Gm MODEL: LRW, 8.1 SAE H.P. 325
 FUEL TANK(S) CAPACITY: 40 (GALS. TOTAL) TRANSMISSION: Allison 1000 MBV 6spd
 SPRING CAP. @ GROUND EACH: FRONT 3500 lbs. REAR 5500 lbs. AUX. N/A lbs.
 AXLES: FRONT 2000 lbs. REAR 11000 lbs. REAR RATIO 4.88
 ALTERNATOR: 150 amps. BATTERY 600 cca.
 TIRE SIZE: FRONT 225/70R19.5 F PR REAR 225/70R19.5 F PR SINGLE DUAL M&S
 TIRE: MAKE Goodyear STYLE NO. TBD MFG. CODE XTN/YTN
 HOIST: MAKE N/A MODEL N/A INSTALLING CO. N/A
 BODY: MAKE N/A MODEL N/A INSTALLING CO. N/A
 POWER LIFT GATE: MAKE N/A MODEL N/A CAPACITY N/A lbs.
 PLATFORM SIZE: N/A

OTHER EQUIPMENT INSTALLED BY BODY EQUIPMENT SUPPLIER AND/OR COMMENTS

This information must be returned with the bid document to Purchasing Operations, on or before the bid due date and time. However, if returned separately, it must be received by Purchasing Operations on or before the bid due date and time, and must comply with the sealed bid instructions as outlined in the ITB.

TRUCK: CAB AND CHASSIS DUAL REAR WHEELS
 (G.V.W.R. 15,000 LBS., min.)

MODEL-2008 CURRENT NEW

	CHEV/GMC C4500 <u>C4C042</u>	FORD <u>F-450SD</u>	DODGE <u>DM4L64</u>
G.V.W.R. (lbs.)	16,500	16,000	16,500
Wheelbase (inches)	152	164.8	168.5
C.A. (inches)	84	84	84
Engine: Diesel	6.6L	6.4L	6.7L
Type & No. of Cylinders	V-8	V-8 Turbo	L-6 Turbo
Net H.P.-S.A.E.	300	325	305

Transmission: Automatic:
 with maximum capacity transmission oil cooler. Factory installed.

Axle, Min. Cap.-lbs.			
Front	7,000	7,000	7,000
Rear	11,000	12,000	12,000
Springs, Min. Cap. at Ground			
Front-lbs. each	3,500	3,000	TBD
Rear-lbs. each	5,500	6,000	TBD

Tires, Truck, Tubeless, Radial, to meet G.V.W.R. Rear duals, mud and snow.

TO BE STANDARD FACTORY EQUIPPED AS FOLLOWS:

The items listed below are to be supplied on all trucks, even though they may be optional with the manufacturer. Therefore, these specifications are to be furnished on all vehicles:

- 12 Volt auxiliary outlet
- Air Conditioning - All trucks
- Anti-freeze protection, to -30°F.
- Arm Rest-Driver's side.
- Color-Manufacturers Standard to be selected.
- Coolant System-Maximum Size Available, including the Heaviest Duty Radiator
- Dome Light.
- Electric wiring-All wiring passing through holes in metal or non-metal wearing surfaces, which could cause wear of the insulation, shall be adequately protected by

rubber or plastic grommets, and/or non-metallic conduit. Ends of all wires shall be adequately anchored to prevent loosening.

- ☑ Frame length-on all body installations without hoists the cab to end of frame length shall be the same length as the body being mounted, plus the length of any setback.
- ☑ Fuel Tanks, Diesel, with sending unit and magnetic drain plug, on all trucks over 21,000 G.V.W.R., painted Black and labeled "Diesel Fuel Only".
- ☑ Hub caps on all pickups and vans up to and including 10,000 G.V.W.R. If not available from dealer cap nuts shall be furnished.
- ☑ Keys-(2) sets with code numbers; shall be with vehicle at time of delivery.
- ☑ Mirrors-All trucks are to be equipped with R.H. and L.H. outside rear-view mirrors to comply with Michigan laws; all trucks up to and including 15,000 G.V.W.R. shall be equipped with inside rear-view mirror. In all cases, outside R.H. & L.H. rear view mirrors shall provide full vision past all body installations. Mirrors shall be of stainless steel or high impact plastic construction unless denoted otherwise in individual truck specifications. All West Coast Type or Below Eye Level Camper Style Mirrors shall have stainless steel or high impact plastic heads, brackets, and hardware.
- ☑ Mud flaps, Anti-Sail Type, when required, are to be plain, rubber 1/4" thick, without advertising on either side.
- ☑ Painting-preclean and metal prep, any bare metal surfaces prior to applying a compatible red oxide or zinc chromate primer. When painting over a manufacturer's standard paint, metal prepping and primer may be omitted, provided an acceptable bond can be achieved.
- ☑ Equipment mounting- when mounting equipment on truck cab and chassis, all holes shall be drilled or punched. There shall be no flame cutting or welding on the frame side rails.
- ☑ Paint codes-factory paint codes shall be furnished with all vehicles; for all after market painting both the brand and paint code shall be furnished.
- ☑ Pre-delivery inspection and servicing.
- ☑ Radio - AM/FM Manufacturers Standard, Factory Installed
- ☑ Seat Belts with Shoulder Harness (3-Point Restraint System for Driver & Passenger)
- ☑ Seats-Split Bench type, unless otherwise specified
- ☑ Shock absorbers-(Heaviest Duty Available), front all trucks. Rear, up to and including 15,000 G.V.W.R.
- ☑ Spare tire, or Rim, not to be furnished unless specified. If specified, tires to be of same mfg., tread design to be same as front tires.
- ☑ Speed Control, Factory Installed
- ☑ Steering-Power, Tilt Wheel
- ☑ Sun visors-dual.
- ☑ Jack-Furnish on trucks up to and including 12,000 G.V.W.R.
- ☑ Windshield wipers-dual, intermittent speed electric, with automatic type washers.

All items removed for installation of optional equipment shall be returned to the State of Michigan.

TO BE EQUIPPED IN COMPLIANCE WITH ALL APPLICABLE FEDERAL MOTOR VEHICLE SAFETY STANDARDS AND REGULATIONS. ALL VEHICLES MUST BE EQUIPPED TO COMPLY WITH ALL REQUIREMENTS OF THE MICHIGAN MOTOR VEHICLE CODE.

- **Delete: On GM vehicles, OnStar and XM radio are deleted.**

ADDITIONAL OPTIONS:

These options are in addition to the options listed above as “STANDARD FACTORY EQUIPPED” and are to be included on this vehicle.

- Air Conditioning – Factory Installed
- Alternator- 80 amp., min.
- Battery-12 Volt, dual
- Brakes-Power.
- Fuel capacity-largest available from mfg.
- Mirrors-Rear View, Inside. Outside R.H. and L.H., below eye level, extended reach, swing away type, 51 sq. in., minimum. Installed, with stainless steel or powder coated steel heads, brackets, and hardware. GMC: composite mirror heads
- Spare tire and wheel. GMC: Spare wheel only – No tire
- Steering-Power.
- Wrench-wheel. GMC: No wrench available

ADDITIONAL MDOT OPTIONS: (Note: These options are not included in the MiDEAL price)

These options are in addition to the options listed above as “STANDARD FACTORY EQUIPPED” and are to be included on this MDOT vehicle.

- Axle Rear Limited slip
- Hubs autolocking on front GMC: locking hubs not available on 2 wd chassis
- Keys – (1) additional set (total of 3 sets) with code numbers; shall be with the vehicle at the time of delivery.
- Switches, upfitter for auxillary GMC: Panel only – switches available from body upfitter
- Throttle, Electronic, High Idle Engine RPM Control.
- Towing package: Heaviest duty available from manufacturer GMC: standard
- Trailer brake controller, factory installed GMC: not available

PRICING SHEET

<u>TRUCK: CAB AND CHASSIS DUAL REAR WHEELS</u> (G.V.W.R. 15,000 LBS., min.) Mich. Spec. #3958-0115	
Standard Equipped Per above Specification (Including options as specified above)	Standard Equipped Cost
Make: GMC Model: C4500 F.O.B. - Dealership Delivery Cost Per Mile \$1.50	\$ 30,625.00*
Final Point of Assembly: Flint, MI	
<u>Dealer Information</u>	
Dealer Name: Red Holman Pontiac GMC	
Street Address: 35300 Ford Road	
City: Westland	State: MI
Zip: 48185	
Contact Name: Albert Li	
Telephone: (800) 482-3032	
Cell: (734) 637-6643	
E-mail: aclixx@hotmail.com	

*Please Note: A vehicle order confirmation sheet is included for each vehicle. These documents shall include all the "standard options" as listed for the State of Michigan standard specification.

Vehicle Order Confirmation Sheet
 Spec # 3958-0115

Prepared By:
 Albert Li
 Red Holman Pontiac GMC
 35300 Ford Rd
 Westland, MI 48185
 Phone: (734) 721-1144
 Fax: (734) 721-1780
 Email: aclbx@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

SELECTED MODEL & OPTIONS

SELECTED MODEL - 2008 Fleet/Non-Retail TC4C042 Regular Cab 2WD

<u>Code</u>	<u>Description</u>	<u>MSRP</u>
TC4C042	2008 GMC TC4500 Regular Cab 2WD	\$28,890.00

SELECTED VEHICLE COLORS - 2008 Fleet/Non-Retail TC4C042 Regular Cab 2WD

<u>Code</u>	<u>Description</u>
-	Interior: No color has been selected.
-	Exterior 1: No color has been selected.
-	Exterior 2: No color has been selected.

SELECTED OPTIONS - 2008 Fleet/Non-Retail TC4C042 Regular Cab 2WD

CATEGORY

<u>Code</u>	<u>Description</u>	<u>MSRP</u>
PREFERRED EQUIPMENT GROUP		
C4C042	CUSTOM/BASE MODEL	\$0.00
DIESEL ENGINE		
LRX	DURAMAX DIESEL 6.6L, 300 HP (223 KW) @ 3000 RPM, 520 LB-FT (705 N-M) TORQUE @ 1600 RPM	\$9,259.00
GVWR		
C7R	16,500 LBS. (7484 KG) CAPACITY	\$0.00
EMISSION		
FE9	FEDERAL REQUIREMENTS	INC
ALTERNATOR		
KG4	AD244, DELCO-REMY 150-AMP MAXIMUM	\$0.00
BATTERY		
TNL	DUAL AC DELCO, 750 CCA, 12V	INC
ENGINE SHUTDOWN		
KPJ	AUTOMATIC ENGINE SHUTDOWN WITH ALARM	INC

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.0, Data updated 12/11/2007 11:05:00 AM
 ©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 19, 2007 9:10:29 PM

Page 1

Prepared By:
 Albert Li
 Red Holman Pontiac GMC
 35300 Ford Rd
 Westland, MI 48185
 Phone: (734) 721-1144
 Fax: (734) 721-1780
 Email: aclbx@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

SELECTED MODEL & OPTIONS

SELECTED OPTIONS - 2008 Fleet/Non-Retail TC4C042 Regular Cab 2WD

<u>CATEGORY</u>		<u>MSRP</u>
<u>Code</u>	<u>Description</u>	
EXHAUST SYSTEM		
NB5	SINGLE HORIZONTAL-PASSENGER SIDE MOUNTED INSIDE FRAME RAIL	INC
POWER TAKE OFF		
PTX	OPTION PTO NOT REQUIRED	\$0.00
TRANSMISSION		
MBV	AUTOMATIC, ALLISON 1000 HS/RDS SERIES 6-SPEED	\$0.00
TRANSMISSION FLUID		
MBT	TRANSYND SYNTHETIC AUTOMATIC TRANSMISSION FLUID	INC
TRANSMISSION EQUIPMENT		
KNP	AUXILIARY TRANSMISSION OIL COOLER	\$95.00
FRONT AXLE		
FM7	7000 LBS. (3175 KG) CAPACITY	INC
FRONT SUSPENSION		
FK6	TAPERED LEAF, 7000 LBS. (3175 KG) CAPACITY	INC
FRONT WHEEL		
Q82	19.5" X 6.75" (49.5 CM X 17.1 CM), STEEL DISC	\$37.00
FRONT TIRE		
XTN	225/70R19.5F	\$0.00
FRONT TIRE BRAND		
R4A	GOODYEAR	\$0.00
FRONT TIRE TREAD		
R3C	PREMIUM, HIGHWAY	\$0.00
SINGLE SPEED REAR AXLE		
GL4	SINGLE SPEED, 11,000 LBS. (4990 KG) CAPACITY	INC
AXLE RATIO		
008	4.88:1	\$0.00
REAR SUSPENSION		

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.0, Data updated 12/11/2007 11:05:00 AM
 ©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 19, 2007 9:10:29 PM

Page 2

Prepared By:
 Albert Li
 Red Holman Pontiac GMC
 35300 Ford Rd
 Westland, MI 48185
 Phone: (734) 721-1144
 Fax: (734) 721-1780
 Email: acibx@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

SELECTED MODEL & OPTIONS

SELECTED OPTIONS - 2008 Fleet/Non-Retail TC4C042 Regular Cab 2WD

CATEGORY

<u>Code</u>	<u>Description</u>	<u>MSRP</u>
REAR SUSPENSION		
GR3	MULTI-LEAF, 11,000 LBS. (4990 KG) CAPACITY	INC
BOLTED OR RIVETED SUSPENSION		
EV8	REAR SUSPENSION BRACKETS ARE RIVETED TO FRAME IN LIEU OF BOLTS	\$0.00
REAR SHOCK ABSORBER		
SAN	REAR SHOCK ABSORBER NOT DESIRED	\$0.00
REAR WHEEL		
Q83	19.5" X 6.75" (49.5 CM X 17.1 CM), STEEL DISC	\$74.00
REAR TIRE		
YTN	225/70R19.5F	\$0.00
REAR TIRE BRAND		
S4A	GOODYEAR	\$0.00
REAR TIRE TREAD		
S3H	HIGHWAY TRACTION	\$0.00
SPARE WHEEL		
SNF	FRONT	\$128.00
WHEELBASE		
EG9	152" (386.1 CM)	\$163.00
FUEL TANK		
NG6	DUAL, TOTAL FUEL CAPACITY OF 40-GALLONS (151L)	\$122.00
DRIVER CONVENIENCE PACKAGES		
ZQ3	DRIVER CONVENIENCE PACKAGE	\$245.00
MISCELLANEOUS CAB EQUIPMENT		
N33	TILT-WHEEL ADJUSTABLE STEERING	INC
K34	CRUISE CONTROL,	INC
AIR CONDITIONING		
C60	AIR CONDITIONING	\$852.00

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.0, Data updated 12/11/2007 11:05:00 AM
 ©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 19, 2007 9:10:29 PM

Page 3

Prepared By:
 Albert Li
 Red Holman Pontiac GMC
 35300 Ford Rd
 Westland, MI 48185
 Phone: (734) 721-1144
 Fax: (734) 721-1780
 Email: acli@hotmai.com

2008 Fleet/Non-Retail GMC TC4500

SELECTED MODEL & OPTIONS

SELECTED OPTIONS - 2008 Fleet/Non-Retail TC4C042 Regular Cab 2WD

<u>CATEGORY</u>		<u>MSRP</u>
<u>Code</u>	<u>Description</u>	
INSIDE REARVIEW MIRRORS		
D36	INSIDE DAY/NIGHT REARVIEW MIRROR	\$19.00
DRIVER SEAT		
AS4	HIGH-BACK BUCKET, FIXED HEIGHT, MANUAL ADJUSTER	INC
PASSENGER SEAT		
A59	TWO-PERSON, WITHOUT STORAGE	\$180.00
AIRBAGS		
AL3	SUPPLEMENTAL INFLATABLE RESTRAINTS NOT INCLUDED	INC
RADIO		
UM7	DELCO AM-FM STEREO RADIO	\$150.00
EXTERIOR MIRRORS		
DB5	MANUAL, 102" (259 CM) WIDE LOAD, INTEGRAL ARM, INTEGRAL CONVEX MIRROR	INC
PAINT		
ZY1	SOLID NON-METALLIC PAINT	INC
INTERIOR TRIM		
69I	VERY DARK PEWTER	INC
SEAT TRIM		
_V	VINYL SEAT TRIM	INC
ADDITIONAL OPTIONS		
VQ1	FLEET PROCESSING OPTION	\$0.00
OPTIONS TOTAL		\$11,324.00

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.0, Data updated 12/11/2007 11:05:00 AM
 ©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 19, 2007 9:10:29 PM

Page 4

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclbox@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC4C042 Regular Cab 2WD

EXTERIOR

- Paint scheme, solid, upper color, Summit White
- Paint scheme, solid, lower color, Summit White
- Exterior roof drip moldings
- Bumper, front, steel, 96" (243.8 cm) wide - styled to minimized wall to wall turn diameter painted argent
- Steps under cab doors
- Front mud flaps
- Integral grille and fenders - The grille is the same color as hood with single halogen headlamps.
- Roof marker lamps
- Daytime running lamps
- Windows, Solar-Ray tinted. Light tinted windshield and side window glass with light transmissivity of 70%
- Mirrors, manual, 102" (259 cm) wide load, integral arm, integral convex mirror - black molded composite 12" x 7" (30.5 cm x 17.8 cm) with 6" x 7" (15.2 cm x 17.8 cm) convex section
- Windshield wipers, 2-speed and intermittent, with pulse washers
- Provisions for mounting front license plate
- Positive door stops

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.0, Data updated 12/11/2007 11:05:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 19, 2007 9:10:29 PM

Page 5

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclbx@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC4C042 Regular Cab 2WD

INTERIOR

- Seat, driver, high-back bucket, fixed height, manual adjuster - storage in the seat riser with a small lip at the front to stop contents from sliding out
- Seat, passenger, high-back bucket, fixed height, manual back angle adjuster - storage in the seat riser with a small lip at the front to stop contents from sliding out
- Seat trim, vinyl, Very Dark Pewter
- Interior trim, Very Dark Pewter (Requires 69V Very Dark Pewter vinyl or 69C Very Dark Pewter cloth)
- Trim console - located next to driver's seat and two cupholders
- Molded vinyl floor covering
- Steering wheel 16"
- Two sided single common key for doors and ignition
- Headlamp warning buzzer
- Warning tone, key-in-ignition
- Tachometer
- Electronic engine hour meter
- Engine "Check Gauges" telltale light and buzzer, oil pressure gauge
- Gauges, low oil pressure and coolant level, high coolant and engine oil temperature
- Vinyl door trim panels - with storage pocket on front doors, beverage holders, and reflector on all doors
- Stepwell storage areas at each door front and rear. Includes storage cover.
- Cloth headliner
- Sunshades, passenger side and driver side, vinyl-covered
- Coat hooks (2) located on cab back panel
- Provisions for stereo - Includes AM/FM antenna, lead wiring for speakers, and separate door chime module (N/A with ZQ2 power convenience option)
- Air conditioning not desired - this option should be ordered only when a customer does not require air conditioning
- Powerpoints - two in-cab power sources (in addition to optional cigarette lighter) for electrical plug-in accessories

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.0, Data updated 12/11/2007 11:05:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 19, 2007 9:10:29 PM

Page 6

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclix@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC4C042 Regular Cab 2WD

- Underhood bodybuilder connections accessory power supply - Provides 12V power supply from the battery with two separate 30 amp fused circuits

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.0, Data updated 12/11/2007 11:05:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 19, 2007 9:10:29 PM

Page 7

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclixx@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC4C042 Regular Cab 2WD

MECHANICAL

- GVWR, 16,500 lbs. (7484 kg) capacity - GCWR limited to 24,000 lb. (10,866 kg) (Requires FM7 7000 lbs. (3175 kg) front axle) NOTE: Trucks that are used primarily to tow a trailer may be liable to Federal Excise Tax (FET). A New Law (Highway Transportation Bill HR3) was passed on August 10, 2005 - Check with IRS for guidelines
- Engine, Vortec 8.1L MD gasoline V8, 325 hp (239 kw) @ 4000 rpm and 450 lb-ft torque (610 N-m) @ 2,800 rpm. - Maximum engine speed 5000 rpm. Oil Level Sensor: Warning sensor for low oil levels
- Air cleaner, dry type
- Cooling, anti-freeze protection temperature - -40 degrees F (-40 degrees C)
- Road speed governor, controlled by the speed rating of the tires ordered. - which will be less than or equal to 85 mph (137 kph); 80 mph (129 kph) with EC9 128" wheelbase/60" CA, ML6 manual transmission and 008 4.88 rear axle ratio; 75 mph (120 kph) with EC9 128" wheelbase/60" CA, M74 automatic transmission and HD2 rear axle
- Alternator, AD244 Delco-Remy 150-amp maximum (N/A with YW2 wrecker package)
- Battery, single AC Delco, 600 CCA, 12V - 115-minute reserve capacity @ 27 degrees C, 600 CCA @ -18 degrees C grounded directly to starter, (Requires gasoline engine; N/A with ANQ Snow Plow Prep package or YW2 Wrecker package)
- Exhaust, single horizontal - passenger side mounted inside frame rail, with gasoline engine stainless-steel exhaust with catalytic converter, with diesel engines, stainless-steel exhaust, oxidation catalyst, diesel particulate filter and exhaust gas cooler
- Option PTO not required - This option should only be ordered when a customer specifically does not require an electric hand throttle for use with power-take-off provisions. (Note: Will delete transmission PTO gear.)
- Transmission, automatic, Allison 1000 HS/RDS Series 6-speed - With parking pawl and column shift, includes 4th Generation Electronic Controls and 0.61 overdrive. Torque Rating: 660 lb-ft (895 N-m) with shift energy management. Available with a Gross Vehicle Weight up to 19,500 lbs. (8845 kg) and a Gross Combination Weight Rating up to 26,000 lbs. (11,790 kg). To include PTO gear, please order with RPO PTO for Allison 1000 RDS Rugged Duty Series transmission. Includes transmission-oil cooler located inside radiator. With Option PTX the truck will be equipped with the Allison 1000 HS Highway Series transmission. (N/A with ANM Fire and Rescue or YF2 Ambulance Package)
- TranSynd synthetic automatic transmission fluid
- Front axle, 7000 lbs. (3175 kg) capacity - I-beam Wide-trac. Up to 53 degree turn angle, includes 4-piston brake apply calipers. Steering Gear Series: ZF8014
- Front suspension, tapered leaf, 7000 lbs. (3175 kg) capacity (includes stabilizer)

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.0, Data updated 12/11/2007 11:05:00 AM

©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 19, 2007 9:10:29 PM

Page 8

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclix@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC4C042 Regular Cab 2WD

- Front shock absorber, diameter 1.375" (35mm)
- Front stabilizer bar, 2" x 2" square tube (5 cm x 5 cm)
- Front wheels, 19.5" x 6.0" (49.5 cm x 15.2 cm), steel disc - 8-hole. 7280 lbs. (3302 kg) capacity
- Front tire size, 225/70R19.5F - 7280 lbs. (3802 kg) capacity, (With R4A Goodyear or R4L Michelin requires R3C front premium highway tread)
- Front tire manufacturer code, Goodyear (Requires S4A Goodyear)
- Front tread, premium, highway (Requires R4A Goodyear or R4L Michelin)
- Rear axle, single speed, 11,000 lbs. (4990 kg) capacity - full floating, includes 2-piston brake applied calipers
- Rear wheel drive
- Rear axle ratio, 5.13:1 (Requires gasoline engine)
- Rear suspension, multi-leaf, 11,000 lbs. (4990 kg) capacity (Requires GL4 single speed rear axle)
- Rear suspension brackets are riveted to frame in lieu of bolts
- Rear shock absorber not desired (N/A with tapered leaf springs)
- Rear wheels, 19.5" x 6.0" (49.5 cm x 15.2 cm), steel disc - 8-hole. 14,560 lbs (6604 kg) capacity
- Rear tire size, 225/70R19.5F - 13,660 lbs. (6196 kg) capacity, (With S4A Goodyear, requires S3C rear premium highway tread or S3H rear traction tread; with S4L Michelin, requires S3C rear premium highway tread or S3J rear highway traction tread)
- Rear tire manufacturer code, Goodyear (Requires R4A Goodyear)
- Rear tread, premium, highway (Requires S4A Goodyear or S4L Michelin)
- Wheelbase, 128" (325.1 cm) - with 60" (152.4 cm) CA and 100" (254 cm) CE. Includes a 6 mm 80,000 psi (551,600 kPa) yield strength, steel frame, RBM: 610,400 Section Modulus 7.63 (Requires KYW 75 mph (120 kph) road speed governor and HD2 13,500 lbs. (6123 kg) capacity rear axle)
- Frame, 6mm - 80,000 psi (551,600 kPa) yield strength, steel frame, RBM: 610,400 Section Modulus 7.63
- Fuel tank, single, 25-gallon (95L) fuel capacity - gas or diesel located midship between the frame rails, with fuel fill neck through the frame rail (this option uses the mid-frame tank included in the NG6 dual tank option) Tethered fuel cap is black with gasoline engines, and green un-tethered fuel cap with diesel engines. MINIMUM OVERHANG = 36" (3 FEET) (Required in YW2 Wrecker Package, standard on 60" (152.4 cm) CA, optional on all other CA's)

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.0, Data updated 12/11/2007 11:05:00 AM

©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 19, 2007 9:10:29 PM

Page 9

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclixx@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC4C042 Regular Cab 2WD

- Fuel sender assembly, Robust fuel pump
- Tethered fuel cap
- Steering, power - ZF variable ratio power
- Brakes, front, power, 4-wheel disc, 4 channel ABS 2-piston - (See front axle options for more detail)
- Brakes, rear, power, 4-wheel disc, 4 channel ABS 2-piston - (See rear axle options for more detail)
- Parking brake, hand lever operated transmission mounted drum brake

SAFETY

- 4-wheel disc, 4-channel ABS
- Air bags, Supplemental Inflatable Restraints not included.
- This vehicle does not include any air bags
- Seat belt warning indicator
- Daytime running lamps

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.0, Data updated 12/11/2007 11:05:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 19, 2007 9:10:29 PM

Page 10



APPENDIX B

TRUCK QUESTIONNAIRE FORMS

ALL BIDDERS MUST COMPLETE AND RETURN A QUESTIONNAIRE FORM WITH THE BID FOR EACH TRUCK ITEM TO BE CONSIDERED FOR AWARD OF THAT ITEM. Bids submitted without an adequately completed questionnaire form for EACH TRUCK ITEM will not be considered for award of that item. It is the responsibility of each bidder to copy this form in sufficient quantity to submit to Purchasing Operations prior to the scheduled bid due date. A single form may apply to more than one item, simply list the item numbers to which the questionnaire applies in the appropriate space. If part of the questionnaire does not apply, simply indicate "not applicable" in those spaces.

NAME OF BIDDER: Red Holman Pontiac Gmc ITEM NO(s). Spec # 3958-0115
 MAKE OF TRUCK: Gmc MODEL: C4500 TC4C042GVWR 16500 lbs.
 PAYLOAD: 8799 W.B. 152" C.A. 84" C.E. 146"
 ENGINE: (GAS - DIESEL) Diesel MAKE: Gm Duramax MODEL: LRX, 6.6 SAE H.P. 300
 FUEL TANK(S) CAPACITY: 40 (GALS. TOTAL) TRANSMISSION: Allison 1000 MBV 6-spd
 SPRING CAP. @ GROUND EACH: FRONT 3500 lbs. REAR 5500 lbs. AUX. N/A lbs.
 AXLES: FRONT 7000 lbs. REAR 11000 lbs. REAR RATIO 4.88
 ALTERNATOR: 150 amps. BATTERY Dual 750 cca.
 TIRE SIZE: FRONT 225/70R19.5 F PR REAR 225/70R19.5 F PR SINGLE DUAL M&S
 TIRE: MAKE Goodyear STYLE NO. TBP MFG. CODE XTN/YTN
 HOIST: MAKE N/A MODEL N/A INSTALLING CO. N/A
 BODY: MAKE N/A MODEL N/A INSTALLING CO. N/A
 POWER LIFT GATE: MAKE N/A MODEL N/A CAPACITY N/A lbs.
 PLATFORM SIZE: N/A

OTHER EQUIPMENT INSTALLED BY BODY EQUIPMENT SUPPLIER AND/OR COMMENTS

This information must be returned with the bid document to Purchasing Operations, on or before the bid due date and time. However, if returned separately, it must be received by Purchasing Operations on or before the bid due date and time, and must comply with the sealed bid instructions as outlined in the ITB.

TRUCK: CAB AND CHASSIS
(G.V.W.R. 15,000 LBS., min.) (4 x 4)

MODEL-2008 CURRENT NEW

	CHEV/GMC <u>C4C044</u>	FORD <u>F-450</u>
G.V.W.R. (lbs.)	17,500	16,000
Wheelbase (inches)	152	164.8
C.A. (inches)	84	84
Engine: Gasoline	8100	Triton
Type & No. of Cylinders	V-8	V-10
Net H.P.-S.A.E.	325	362

Transmission: Automatic:
with maximum capacity transmission oil cooler with P.T.O. Provision. Factory installed.

Axle, Min. Cap.-lbs.		
Front	8,000	7,000
Rear	13,500	12,000
Springs, Min. Cap. at Ground		
Front-lbs. each	4,000	2,800
Rear-lbs. each	6,750	6,000

Tires, Truck, Tubeless, Radial, to meet G.V.W.R. Rear duals, mud and snow.

TO BE STANDARD FACTORY EQUIPPED AS FOLLOWS:

The items listed below are to be supplied on all trucks, even though they may be optional with the manufacturer. Therefore, these specifications are to be furnished on all vehicles:

- 12 Volt auxiliary outlet
- Air Conditioning - All trucks
- Anti-freeze protection, to -30°F.
- Arm Rest-Driver's side.
- Color-Manufacturers Standard to be selected.
- Coolant System-Maximum Size Available, including the Heaviest Duty Radiator
- Dome Light.
- Electric wiring-All wiring passing through holes in metal or non-metal wearing surfaces, which could cause wear of the insulation, shall be adequately protected by

rubber or plastic grommets, and/or non-metallic conduit. Ends of all wires shall be adequately anchored to prevent loosening.

- ☑ Frame length-on all body installations without hoists the cab to end of frame length shall be the same length as the body being mounted, plus the length of any setback.
- ☑ Fuel Tanks, Diesel, with sending unit and magnetic drain plug, on all trucks over 21,000 G.V.W.R., painted Black and labeled "Diesel Fuel Only".
- ☑ Hub caps on all pickups and vans up to and including 10,000 G.V.W.R. If not available from dealer cap nuts shall be furnished.
- ☑ Keys-(2) sets with code numbers; shall be with vehicle at time of delivery.
- ☑ Mirrors-All trucks are to be equipped with R.H. and L.H. outside rear-view mirrors to comply with Michigan laws; all trucks up to and including 15,000 G.V.W.R. shall be equipped with inside rear-view mirror. In all cases, outside R.H. & L.H. rear view mirrors shall provide full vision past all body installations. Mirrors shall be of stainless steel or high impact plastic construction unless denoted otherwise in individual truck specifications. All West Coast Type or Below Eye Level Camper Style Mirrors shall have stainless steel or high impact plastic heads, brackets, and hardware.
- ☑ Mud flaps, Anti-Sail Type, when required, are to be plain, rubber 1/4" thick, without advertising on either side.
- ☑ Painting-preclean and metal prep, any bare metal surfaces prior to applying a compatible red oxide or zinc chromate primer. When painting over a manufacturer's standard paint, metal prepping and primer may be omitted, provided an acceptable bond can be achieved.
- ☑ Equipment mounting- when mounting equipment on truck cab and chassis, all holes shall be drilled or punched. There shall be no flame cutting or welding on the frame side rails.
- ☑ Paint codes-factory paint codes shall be furnished with all vehicles; for all after market painting both the brand and paint code shall be furnished.
- ☑ Pre-delivery inspection and servicing.
- ☑ Radio - AM/FM Manufacturers Standard, Factory Installed
- ☑ Seat Belts with Shoulder Harness (3-Point Restraint System for Driver & Passenger)
- ☑ Seats-Split Bench type, unless otherwise specified
- ☑ Shock absorbers-(Heaviest Duty Available), front all trucks. Rear, up to and including 15,000 G.V.W.R.
- ☑ Spare tire, or Rim, not to be furnished unless specified. If specified, tires to be of same mfg., tread design to be same as front tires.
- ☑ Speed Control, Factory Installed
- ☑ Steering-Power, Tilt Wheel
- ☑ Sun visors-dual.
- ☑ Jack-Furnish on trucks up to and including 12,000 G.V.W.R.
- ☑ Windshield wipers-dual, intermittent speed electric, with automatic type washers.

All items removed for installation of optional equipment shall be returned to the State of Michigan.

TO BE EQUIPPED IN COMPLIANCE WITH ALL APPLICABLE FEDERAL MOTOR VEHICLE SAFETY STANDARDS AND REGULATIONS. ALL VEHICLES MUST BE EQUIPPED TO COMPLY WITH ALL REQUIREMENTS OF THE MICHIGAN MOTOR VEHICLE CODE.

- **Delete: On GM vehicles, OnStar and XM radio are deleted.**

ADDITIONAL OPTIONS:

These options are in addition to the options listed above as “STANDARD FACTORY EQUIPPED” and are to be included on this vehicle.

- Air Conditioning – Factory Installed
- Alternator-80 amp., min.
- Battery-12 Volt, 600 CCA, minimum.
- Brakes-Power.
- Fuel capacity-largest available from mfg.
- Mirrors-Rear View, Inside. Outside R.H. and L.H., below eye level, extended reach, swing away type, 51 sq. in., minimum. Installed, with stainless steel or powder coated steel heads, brackets, and hardware. GMC: Composite Mirror Heads
- Spare tire and wheel. GMC: Spare wheel only
- Steering-Power.
- Wrench-wheel. GMC: wrench not avail

ADDITIONAL MDOT OPTIONS: (Note: These options are not included in the MiDEAL price)

These options are in addition to the options listed above as “STANDARD FACTORY EQUIPPED” and are to be included on this MDOT vehicle.

- Axle Rear Limited slip
- Hubs autolocking on front GMC: manual locking hubs only
- Keys – (1) additional set (total of 3 sets) with code numbers; shall be with the vehicle at the time of delivery.
- Switches, upfitter for auxillary GMC: Panel std – switches available from body upfitter
- Throttle, Electronic, High Idle Engine RPM Control.
- Towing package: Heaviest duty available from manufacturer GMC: Standard
- Trailer brake controller, factory installed GMC: Not availabe

PRICING SHEET

<u>TRUCK: CAB AND CHASSIS</u> (G.V.W.R. 15,000 LBS., min.) (4 x 4) Mich. Spec. #3958-0116	
Standard Equipped Per above Specification (Including options as specified above)	Standard Equipped Cost
Make: GMC Model: C4500 <i>F.O.B. - Dealership</i> Delivery Cost Per Mile \$1.50	\$28,774.00*
Final Point of Assembly: Flint, MI	
<u>Dealer Information</u>	
Dealer Name: Red Holman Pontiac GMC	
Street Address: 35300 Ford Road	
City: Westland	State: MI
	Zip: 48185
Contact Name: Albert Li	
Telephone: (800) 482-3032	
Cell: (734) 637-6643	
E-mail: aclixx@hotmail.com	

*Please Note: A vehicle order confirmation sheet is included for each vehicle. These documents shall include all the "standard options" as listed for the State of Michigan standard specification.

Vehicle Order Confirmation Sheet
Spec # 3958-0116

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclix@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

SELECTED MODEL & OPTIONS

SELECTED MODEL - 2008 Fleet/Non-Retail TC4C044 Regular Cab 4WD

<u>Code</u>	<u>Description</u>	<u>MSRP</u>
TC4C044	2008 GMC TC4500 Regular Cab 4WD	\$35,860.00

SELECTED VEHICLE COLORS - 2008 Fleet/Non-Retail TC4C044 Regular Cab 4WD

<u>Code</u>	<u>Description</u>
-	Interior: No color has been selected.
-	Exterior 1: No color has been selected.
-	Exterior 2: No color has been selected.

SELECTED OPTIONS - 2008 Fleet/Non-Retail TC4C044 Regular Cab 4WD

CATEGORY

<u>Code</u>	<u>Description</u>	<u>MSRP</u>
PREFERRED EQUIPMENT GROUP		
C4C044	CUSTOM/BASE MODEL	\$0.00
GASOLINE ENGINE		
LRW	VORTEC 8.1L MD GASOLINE V8, 325 HP (239 KW) @ 4000 RPM AND 450 LB-FT TORQUE (610 N-M) @ 2800 RPM.	\$0.00
GWR		
GZX	17,500 LBS. (7938 KG) CAPACITY	INC
EMISSION		
FE9	FEDERAL REQUIREMENTS	INC
ROAD SPEED GOVERNOR		
KYW	75 MPH (120 KPH) SPEED GOVERNOR	INC
ALTERNATOR		
KG4	AD244, DELCO-REMY 150-AMP MAXIMUM	\$0.00
BATTERY		
TM1	SINGLE AC DELCO, 600 CCA, 12V	\$0.00

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.2, Data updated 12/25/2007 10:41:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 27, 2007 11:10:42 PM

Page 1

Prepared By:
 Albert Li
 Red Holman Pontiac GMC
 35300 Ford Rd
 Westland, MI 48185
 Phone: (734) 721-1144
 Fax: (734) 721-1780
 Email: acliix@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

SELECTED MODEL & OPTIONS

SELECTED OPTIONS - 2008 Fleet/Non-Retail TC4C044 Regular Cab 4WD

<u>CATEGORY</u>		<u>MSRP</u>
<u>Code</u>	<u>Description</u>	
EXHAUST SYSTEM		
NB5	SINGLE HORIZONTAL-DRIVER SIDE MOUNTED INSIDE FRAME RAIL,	INC
POWER TAKE OFF		
PTO	ELECTRONIC ACTIVATION SWITCH, (ELECTRIC HAND THROTTLE), IP MOUNTED	\$225.00
TRANSMISSION		
MBV	AUTOMATIC, ALLISON 1000 HS/RDS SERIES 6-SPEED	\$0.00
TRANSMISSION FLUID		
MBT	TRANSYND SYNTHETIC AUTOMATIC TRANSMISSION FLUID	INC
TRANSMISSION EQUIPMENT		
KNP	AUXILIARY TRANSMISSION OIL COOLER	\$95.00
TRANSFER CASE		
NP1	NEW VENTURE GEAR-MODEL NV273 TWO-SPEED	INC
FRONT AXLE		
G38	8000 LBS. (3629 KG) CAPACITY	\$0.00
FRONT SUSPENSION		
FSN	TAPERED LEAF, 8000 LBS. (3629 KG) CAPACITY	\$0.00
FRONT STABILIZER BAR		
F59	STABILIZER BAR	INC
FRONT WHEEL		
Q82	19.5" X 6.75" (49.5 CM X 17.1 CM), STEEL DISC	\$0.00
FRONT TIRE		
XTY	245/70R19.5G	\$0.00
FRONT TIRE BRAND		
R4A	GOODYEAR	\$0.00
FRONT TIRE TREAD		
R3H	HIGHWAY TRACTION	INC
SINGLE SPEED REAR AXLE		

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.2, Data updated 12/25/2007 10:41:00 AM
 ©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.
 Customer File:

December 27, 2007 11:10:42 PM

Page 2

Prepared By:
 Albert Li
 Red Holman Pontiac GMC
 35300 Ford Rd
 Westland, MI 48185
 Phone: (734) 721-1144
 Fax: (734) 721-1780
 Email: aclix@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

SELECTED MODEL & OPTIONS

SELECTED OPTIONS - 2008 Fleet/Non-Retail TC4C044 Regular Cab 4WD

<u>CATEGORY</u>		<u>MSRP</u>
<u>Code</u>	<u>Description</u>	
SINGLE SPEED REAR AXLE		
HD2	SINGLE SPEED, DANA S110 13,500 LBS. (6123 KG) CAPACITY	INC
AXLE RATIO		
058	5.13:1	INC
TRACTION CONTROL		
G80	REAR LIMITED SLIP DIFFERENTIAL	INC
REAR SUSPENSION		
GR4	MULTI-LEAF, 13,500 LBS. (6123 KG) CAPACITY	INC
BOLTED OR RIVETED SUSPENSION		
EV8	REAR SUSPENSION BRACKETS ARE RIVETED TO FRAME IN LIEU OF BOLTS	\$0.00
REAR SHOCK ABSORBER		
SAN	REAR SHOCK ABSORBER NOT DESIRED	\$0.00
REAR WHEEL		
Q83	19.5" X 6.75" (49.5 CM X 17.1 CM), STEEL DISC	\$0.00
REAR TIRE		
YTY	245/70R19.5G	\$0.00
REAR TIRE BRAND		
S4A	GOODYEAR	\$0.00
REAR TIRE TREAD		
S3H	HIGHWAY TRACTION	INC
SPARE WHEEL		
SNF	FRONT	\$128.00
WHEELBASE		
EG9	152" (386.1 CM)	\$0.00
FUEL TANK		
NH4	SINGLE, 40-GALLON (151L) FUEL CAPACITY	INC
PARKING BRAKE		

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.2, Data updated 12/25/2007 10:41:00 AM
 ©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 27, 2007 11:10:42 PM

Page 3

Prepared By:
 Albert Li
 Red Holman Pontiac GMC
 35300 Ford Rd
 Westland, MI 48185
 Phone: (734) 721-1144
 Fax: (734) 721-1780
 Email: aclbx@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

SELECTED MODEL & OPTIONS

SELECTED OPTIONS - 2008 Fleet/Non-Retail TC4C044 Regular Cab 4WD

<u>CATEGORY</u>		<u>MSRP</u>
<u>Code</u>	<u>Description</u>	
PARKING BRAKE		
J69	REAR IN-WHEEL PARK BRAKE	INC
DRIVER CONVENIENCE PACKAGES		
ZQ3	DRIVER CONVENIENCE PACKAGE	\$155.00
MISCELLANEOUS CAB EQUIPMENT		
N33	TILT-WHEEL ADJUSTABLE STEERING	INC
K34	CRUISE CONTROL,	INC
AIR CONDITIONING		
C60	AIR CONDITIONING	\$852.00
INSIDE REARVIEW MIRRORS		
D36	INSIDE DAY/NIGHT REARVIEW MIRROR	\$19.00
DRIVER SEAT		
AS4	HIGH-BACK BUCKET, FIXED HEIGHT, MANUAL ADJUSTER	INC
PASSENGER SEAT		
A59	TWO-PERSON, WITHOUT STORAGE	\$180.00
AIRBAGS		
AL3	SUPPLEMENTAL INFLATABLE RESTRAINTS NOT INCLUDED	INC
RADIO		
UM7	DELCO AM-FM STEREO RADIO	\$150.00
EXTERIOR MIRRORS		
DB5	MANUAL, 102" (259 CM) WIDE LOAD, INTEGRAL ARM, INTEGRAL CONVEX MIRROR	INC
PAINT		
ZY1	SOLID NON-METALLIC PAINT	INC
INTERIOR TRIM		
69I	VERY DARK PEWTER	INC
SEAT TRIM		
_V	VINYL SEAT TRIM	INC

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.2, Data updated 12/25/2007 10:41:00 AM
 ©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 27, 2007 11:10:42 PM

Page 4

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclix@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

SELECTED MODEL & OPTIONS

SELECTED OPTIONS - 2008 Fleet/Non-Retail TC4C044 Regular Cab 4WD

CATEGORY

<u>Code</u>	<u>Description</u>	<u>MSRP</u>
ADDITIONAL OPTIONS		
VQ1	FLEET PROCESSING OPTION	\$0.00
OPTIONS TOTAL		\$1,804.00

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.2, Data updated 12/25/2007 10:41:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 27, 2007 11:10:42 PM

Page 5

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclbx@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC4C044 Regular Cab 4WD

EXTERIOR

- Paint scheme, solid, upper color, Summit White
- Paint scheme, solid, lower color, Summit White
- Exterior roof drip moldings
- Bumper, front, steel, 96" (243.8 cm) wide - styled to minimized wall to wall turn diameter painted argent
- Steps under cab doors
- Front mud flaps
- Integral grille and fenders - The grille is the same color as hood with single halogen headlamps.
- Roof marker lamps
- Daytime running lamps
- Windows, Solar-Ray tinted. Light tinted windshield and side window glass with light transmissivity of 70%
- Mirrors, manual, 102" (259 cm) wide load, integral arm, integral convex mirror - black molded composite 12" x 7" (30.5 cm x 17.8 cm) with 6" x 7" (15.2 cm x 17.8 cm) convex section
- Windshield wipers, 2-speed and intermittent, with pulse washers
- Provisions for mounting front license plate
- Positive door stops

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.2, Data updated 12/25/2007 10:41:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.
Customer File:

December 27, 2007 11:10:42 PM

Page 6

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclix@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC4C044 Regular Cab 4WD

INTERIOR

- Seat, driver, high-back bucket, fixed height, manual adjuster - storage in the seat riser with a small lip at the front to stop contents from sliding out
- Seat, passenger, high-back bucket, fixed height, manual back angle adjuster - storage in the seat riser with a small lip at the front to stop contents from sliding out
- Seat trim, vinyl, Very Dark Pewter
- Interior trim, Very Dark Pewter (Requires 69V Very Dark Pewter vinyl or 69C Very Dark Pewter cloth)
- Trim console - located next to driver's seat and two cupholders
- Molded vinyl floor covering
- Steering wheel 16"
- Two sided single common key for doors and ignition
- Headlamp warning buzzer
- Warning tone, key-in-ignition
- Tachometer
- Electronic engine hour meter
- Engine "Check Gauges" telltale light and buzzer, oil pressure gauge
- Gauges, low oil pressure and coolant level, high coolant and engine oil temperature
- Vinyl door trim panels - with storage pocket on front doors, beverage holders, and reflector on all doors
- Stepwell storage areas at each door front and rear. Includes storage cover.
- Cloth headliner
- Sunshades, passenger side and driver side, vinyl-covered
- Coat hooks (2) located on cab back panel
- Provisions for stereo - Includes AM/FM antenna, lead wiring for speakers, and separate door chime module (N/A with ZQ2 power convenience option)
- Air conditioning not desired - this option should be ordered only when a customer does not require air conditioning
- Powerpoints - two in-cab power sources (in addition to optional cigarette lighter) for electrical plug-in accessories

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.2, Data updated 12/25/2007 10:41:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 27, 2007 11:10:42 PM

Page 7

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: acli@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC4C044 Regular Cab 4WD

- Underhood bodybuilder connections accessory power supply - Provides 12V power supply from the battery with two separate 30 amp fused circuits

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.2, Data updated 12/25/2007 10:41:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 27, 2007 11:10:42 PM

Page 8

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclbx@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC4C044 Regular Cab 4WD

MECHANICAL

- GVWR, 17,500 lbs. (7938 kg) capacity - GVWR. Maximum GCWR 26,000 lb. Note: Trucks that are used primarily to tow a trailer may be liable to Federal Excise Tax (FET). A New Law (Highway Transportation Bill HR3) was passed on August 10, 2005 - Check with IRS for guidelines
- Engine, Vortec 8.1L MD gasoline V8, 325 hp (239 kw) @ 4000 rpm and 450 lb-ft torque (610 N-m) @ 2,800 rpm. - Maximum engine speed 5000 rpm. Oil Level Sensor: Warning sensor for low oil levels
- Air cleaner, dry type
- Cooling, anti-freeze protection temperature - -40 degrees F (-40 degrees C)
- 75 mph (120 kph) speed governor - Required by the speed rating of the tires ordered
- Alternator, AD244 Delco-Remy 150-amp maximum (N/A with ANM Fire and Rescue or YF2 Ambulance Packages)
- Battery, single AC Delco, 600 CCA, 12V - 115-minute reserve capacity @ 27 degrees C, 600 CCA @ -18 degrees C grounded directly to starter, (Requires gasoline engine; N/A with ANQ Snow Plow Prep)
- Exhaust, single horizontal - driver side mounted inside frame rail, with gasoline engine stainless-steel exhaust with catalytic converter, with diesel engines, stainless-steel exhaust, oxidation catalyst, diesel particulate filter and exhaust gas cooler
- Option PTO not required - This option should only be ordered when a customer specifically does not require an electric hand throttle for use with power-take-off provisions. (Note: Will delete transmission PTO gear.)
- Transmission, automatic, Allison 1000 HS/RDS Series 6-speed - With parking pawl and column shift, includes 4th Generation Electronic Controls and 0.61 overdrive. Torque Rating: 660 lb-ft (895 N-m) with shift energy management. Available with a Gross Vehicle Weight up to 19,500 lbs. (8845 kg) and a Gross Combination Weight Rating up to 26,000 lbs. (11,790 kg). To include PTO gear, please order with RPO PTO for Allison 1000 RDS Rugged Duty Series transmission. Includes transmission-oil cooler located inside radiator. With Option PTX the truck will be equipped with the Allison 1000 HS Highway Series transmission. (N/A with ANM Fire and Rescue or YF2 Ambulance Package)
- TranSynd synthetic automatic transmission fluid
- Transfer case, New Venture Gear - model NV273 two-speed, electrically actuated, IP mounted switch, includes shield
- Front axle, 8000 lbs. (3629 kg) capacity - Solid drive axle. Up to 45 degree turn angle, includes 4 piston brake apply calipers and manual locking hubs
- Front suspension, tapered leaf, 8000 lbs. (3629 kg) capacity

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.2, Data updated 12/25/2007 10:41:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 27, 2007 11:10:42 PM

Page 9

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclixx@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC4C044 Regular Cab 4WD

- Front shock absorber, diameter 1.375" (35mm)
- Front stabilizer bar, Solid bar style, 1.5" (38mm)
- Front wheels, 19.5" x 6.75" (49.5 cm x 17.1 cm), steel disc - 8-hole, 10,000 lbs. (4536 kg) capacity, (Requires Q83 steel rear wheel and XTY or XNC front tires)
- Front tire size, 245/70R19.5G - 9090 lbs. (4123 kg) capacity (Requires KYR 65 mph or KYW 75 mph (120 kph) road speed governor, Q82 or RPM front wheels. With R4A Goodyear tire, requires R3H highway traction tread)
- Front tire manufacturer code, Goodyear (Requires S4A Goodyear)
- Front tread, highway traction
- Rear axle, single speed, Dana S110 13,500 lbs. (6123 kg) capacity - full floating, includes 2-piston brake applied calipers
- Four-wheel drive
- Rear axle ratio, 5.13:1 (Requires HD2 single speed rear axle)
- Rear limited slip differential
- Rear suspension, multi-leaf, 13,500 lbs. (6123 kg) capacity
- Rear suspension brackets are riveted to frame in lieu of bolts
- Rear shock absorber not desired (N/A with tapered leaf springs)
- Rear wheels, 19.5" x 6.75" (49.5 cm x 17.1 cm), steel disc - 8-hole, 20,000 lbs. (9072 kg) capacity (Requires Q82 front wheels and YTY or YNC rear tires)
- Rear tire size, 245/70R19.5G - 17,500 lbs. (7938 kg) capacity (Requires KYR 65 mph or KYW 75 mph (120 kph) road speed governor and Q83 or RPW rear wheels. With S4A Goodyear tire, requires S3H highway traction tread)
- Rear tire manufacturer code, Goodyear (Requires R4A Goodyear)
- Rear tread, highway traction
- Wheelbase, 152" (386.1 cm) - with 84" (213.4 cm) CA and 146" (370.8 cm) CE. Includes a 6mm 80,000 psi (551,600 kPa) yield strength, steel frame, RBM: 610,400 Section Modulus 7.63
- Frame, 8mm - 80,000 psi (551,600 kPa) yield strength, steel frame, RBM: 610,400 Section Modulus 7.63
- Fuel tank, single, 40-gallon (151L) fuel capacity - gas or diesel, located behind rear axle with fuel fill neck through frame rail and a black tethered fuel cap with gasoline engine and green un-tethered fuel cap with diesel engines. DRIVER SIDE FILL NECK ONLY. NO AUXILIARY PORTS. MINIMUM OVERHANG = 60" (5 FEET)

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.2, Data updated 12/25/2007 10:41:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.
Customer File:

December 27, 2007 11:10:42 PM

Page 10

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclix@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC4C044 Regular Cab 4WD

- Fuel sender assembly. Robust fuel pump
- Tethered fuel cap
- Steering, power - ZF variable ratio power
- Brakes, front, power, 4-wheel disc, 4 channel ABS 4-piston - (See front axle options for more detail)
- Brakes, rear, power, 4-wheel disc, 4 channel ABS 2-piston - (See rear axle options for more detail)
- Parking brake, rear in-wheel park brake - hand lever operated

SAFETY

- 4-wheel disc, 4-channel ABS
- Air bags, Supplemental Inflatable Restraints not included.
- This vehicle does not include any air bags
- Seat belt warning indicator
- Daytime running lamps

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.2, Data updated 12/25/2007 10:41:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 27, 2007 11:10:42 PM

Page 11



APPENDIX B

TRUCK QUESTIONNAIRE FORMS

ALL BIDDERS MUST COMPLETE AND RETURN A QUESTIONNAIRE FORM WITH THE BID FOR EACH TRUCK ITEM TO BE CONSIDERED FOR AWARD OF THAT ITEM. Bids submitted without an adequately completed questionnaire form for EACH TRUCK ITEM will not be considered for award of that item. It is the responsibility of each bidder to copy this form in sufficient quantity to submit to Purchasing Operations prior to the scheduled bid due date. A single form may apply to more than one item, simply list the item numbers to which the questionnaire applies in the appropriate space. If part of the questionnaire does not apply, simply indicate "not applicable" in those spaces.

NAME OF BIDDER: Red Holman Pontiac Gmc ITEM NO(s). Spec # 3958-0116

MAKE OF TRUCK: Gmc MODEL: C4500 TC4C044 GVWR 17500 lbs.

PAYLOAD: 9146 # W.B. 152" C.A. 84" C.E. 146"

ENGINE: (GAS - DIESEL) Gas MAKE: Gm MODEL: LRW, P.1SAE H.P. 325

FUEL TANK(S) CAPACITY: 40 (GALS. TOTAL) TRANSMISSION: Allison 1000 MBV 6spd

SPRING CAP. @ GROUND EACH: FRONT 4000 lbs. REAR 6750 lbs. AUX. N/A lbs.

AXLES: FRONT 8000 lbs. REAR 13500 lbs. REAR RATIO 5.13

ALTERNATOR: 150 amps. BATTERY 600 cca.

TIRE SIZE: FRONT 245/70R14.5G PR REAR 245/70R14.5G PR SINGLE DUAL M&S

TIRE: MAKE Goodyear STYLE NO. TBD MFG. CODE XTY/YTY

HOIST: MAKE N/A MODEL N/A INSTALLING CO. N/A

BODY: MAKE N/A MODEL N/A INSTALLING CO. N/A

POWER LIFT GATE: MAKE N/A MODEL N/A CAPACITY N/A lbs.

PLATFORM SIZE: N/A

OTHER EQUIPMENT INSTALLED BY BODY EQUIPMENT SUPPLIER AND/OR COMMENTS

This information must be returned with the bid document to Purchasing Operations, on or before the bid due date and time. However, if returned separately, it must be received by Purchasing Operations on or before the bid due date and time, and must comply with the sealed bid instructions as outlined in the ITB.

TRUCK: CAB AND CHASSIS
 (G.V.W.R. 15,000 LBS., min.) (4 x 4)

MODEL-2008 CURRENT NEW

	CHEV/GMC C4C044	FORD F-450	DODGE DM9L64
G.V.W.R. (lbs.)	17,500	16,000	16,500
Wheelbase (inches)	152	164.8	168.5
C.A. (inches)	84	84	84
Engine: Diesel	6.6L	6.4L	6.7L
Type & No. of Cylinders	V-8	V-8 Turbo	L-6 Turbo
Net H.P.-S.A.E.	300	325	305

Transmission: Automatic:
 with maximum capacity transmission oil cooler with P.T.O. Provision. Factory installed.

Axle, Min. Cap.-lbs.			
Front	8,000	7,000	7,000
Rear	13,500	12,000	12,000
Springs, Min. Cap. at Ground			
Front-lbs. each	4,000	3,000	TBD
Rear-lbs. each	6,750	6,000	TBD

Tires, Truck, Tubeless, Radial, to meet G.V.W.R. Rear duals, mud and snow.

TO BE STANDARD FACTORY EQUIPPED AS FOLLOWS:

The items listed below are to be supplied on all trucks, even though they may be optional with the manufacturer. Therefore, these specifications are to be furnished on all vehicles:

- 12 Volt auxiliary outlet
- Air Conditioning - All trucks
- Anti-freeze protection, to -30°F.
- Arm Rest-Driver's side.
- Color-Manufacturers Standard to be selected.
- Coolant System-Maximum Size Available, including the Heaviest Duty Radiator
- Dome Light.
- Electric wiring-All wiring passing through holes in metal or non-metal wearing surfaces, which could cause wear of the insulation, shall be adequately protected by rubber or plastic grommets, and/or non-metallic conduit. Ends of all wires shall be adequately anchored to prevent loosening.

- ☑ Frame length-on all body installations without hoists the cab to end of frame length shall be the same length as the body being mounted, plus the length of any setback.
- ☑ Fuel Tanks, Diesel, with sending unit and magnetic drain plug, on all trucks over 21,000 G.V.W.R., painted Black and labeled "Diesel Fuel Only".
- ☑ Hub caps on all pickups and vans up to and including 10,000 G.V.W.R. If not available from dealer cap nuts shall be furnished.
- ☑ Keys-(2) sets with code numbers; shall be with vehicle at time of delivery.
- ☑ Mirrors-All trucks are to be equipped with R.H. and L.H. outside rear-view mirrors to comply with Michigan laws; all trucks up to and including 15,000 G.V.W.R. shall be equipped with inside rear-view mirror. In all cases, outside R.H. & L.H. rear view mirrors shall provide full vision past all body installations. Mirrors shall be of stainless steel or high impact plastic construction unless denoted otherwise in individual truck specifications. All West Coast Type or Below Eye Level Camper Style Mirrors shall have stainless steel or high impact plastic heads, brackets, and hardware.
- ☑ Mud flaps, Anti-Sail Type, when required, are to be plain, rubber 1/4" thick, without advertising on either side.
- ☑ Painting-preclean and metal prep, any bare metal surfaces prior to applying a compatible red oxide or zinc chromate primer. When painting over a manufacturer's standard paint, metal prepping and primer may be omitted, provided an acceptable bond can be achieved.
- ☑ Equipment mounting- when mounting equipment on truck cab and chassis, all holes shall be drilled or punched. There shall be no flame cutting or welding on the frame side rails.
- ☑ Paint codes-factory paint codes shall be furnished with all vehicles; for all after market painting both the brand and paint code shall be furnished.
- ☑ Pre-delivery inspection and servicing.
- ☑ Radio - AM/FM Manufacturers Standard, Factory Installed
- ☑ Seat Belts with Shoulder Harness (3-Point Restraint System for Driver & Passenger)
- ☑ Seats-Split Bench type, unless otherwise specified
- ☑ Shock absorbers-(Heaviest Duty Available), front all trucks. Rear, up to and including 15,000 G.V.W.R.
- ☑ Spare tire, or Rim, not to be furnished unless specified. If specified, tires to be of same mfg., tread design to be same as front tires.
- ☑ Speed Control, Factory Installed
- ☑ Steering-Power, Tilt Wheel
- ☑ Sun visors-dual.
- ☑ Jack-Furnish on trucks up to and including 12,000 G.V.W.R.
- ☑ Windshield wipers-dual, intermittent speed electric, with automatic type washers.

All items removed for installation of optional equipment shall be returned to the State of Michigan.

TO BE EQUIPPED IN COMPLIANCE WITH ALL APPLICABLE FEDERAL MOTOR VEHICLE SAFETY STANDARDS AND REGULATIONS. ALL VEHICLES MUST BE EQUIPPED TO COMPLY WITH ALL REQUIREMENTS OF THE MICHIGAN MOTOR VEHICLE CODE.

- **Delete: On GM vehicles, OnStar and XM radio are deleted.**

ADDITIONAL OPTIONS:

These options are in addition to the options listed above as “STANDARD FACTORY EQUIPPED” and are to be included on this vehicle.

- Air Conditioning-Factory Installed
- Alternator-80 amp., min.
- Battery-12 Volt, dual
- Brakes-Power.
- Fuel Capacity -largest available from mfg.
- Mirrors-Rear View, Inside. Outside R.H. and L.H., below eye level, extended reach, swing away type, 51 sq. in., minimum. Installed, with stainless steel or powder coated steel heads, brackets, and hardware. GMC: Composite Mirror Heads
- Spare tire and wheel. GMC: Spare wheel only – No tire
- Steering-Power.
- Wrench-wheel. GMC – Wrench not available

ADDITIONAL MDOT OPTIONS: (Note: These options are not included in the MiDEAL price)

These options are in addition to the options listed above as “STANDARD FACTORY EQUIPPED” and are to be included on this MDOT vehicle.

- Axle rear limited slip
- Hub autolocking on front GMC: Manual locking front hubs only
- Keys – (1) additional set (total of 3 sets) with code numbers; shall be with the vehicle at the time of delivery.
- Switches, upfitter for auxillary GMC: Panel only – Switches avail from body upfitter
- Throttle, Electronic, High Idle Engine RPM Control.
- Towing package: Heaviest duty available from manufacturer GMC- Standard
- Trailer brake controller, factory installed GMC- Not available

PRICING SHEET

<u>TRUCK: CAB AND CHASSIS</u> (G.V.W.R. 15,000 LBS., min.) (4 x 4) Mich. Spec. #3958-0117	
Standard Equipped Per above Specification (Including options as specified above)	Standard Equipped Cost
Make: GMC Model: C4500 <i>F.O.B. - Dealership</i> Delivery Cost Per Mile \$1.50	\$36,475.00*
Final Point of Assembly: Flint, MI	
<u>Dealer Information</u>	
Dealer Name: Red Holman Pontiac GMC	
Street Address: 35300 Ford Road	
City: Westland	State: MI
Zip: 48185	
Contact Name: Albert Li	
Telephone: (800) 482-3032	
Cell: (734) 637-6643	
E-mail: aclixx@hotmail.com	

*Please Note: A vehicle order confirmation sheet is included for each vehicle. These documents shall include all the "standard options" as listed for the State of Michigan standard specification.

Vehicle Order Confirmation Sheet
 Spec # 3958-0117

Prepared By:
 Albert Li
 Red Holman Pontiac GMC
 35300 Ford Rd
 Westland, MI 48185
 Phone: (734) 721-1144
 Fax: (734) 721-1780
 Email: aclix@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

SELECTED MODEL & OPTIONS

SELECTED MODEL - 2008 Fleet/Non-Retail TC4C044 Regular Cab 4WD

<u>Code</u>	<u>Description</u>	<u>MSRP</u>
TC4C044	2008 GMC TC4500 Regular Cab 4WD	\$35,860.00

SELECTED VEHICLE COLORS - 2008 Fleet/Non-Retail TC4C044 Regular Cab 4WD

<u>Code</u>	<u>Description</u>
-	Interior: No color has been selected.
-	Exterior 1: No color has been selected.
-	Exterior 2: No color has been selected.

SELECTED OPTIONS - 2008 Fleet/Non-Retail TC4C044 Regular Cab 4WD

CATEGORY

<u>Code</u>	<u>Description</u>	<u>MSRP</u>
PREFERRED EQUIPMENT GROUP		
C4C044	CUSTOM/BASE MODEL	\$0.00
DIESEL ENGINE		
LRX	DURAMAX DIESEL 6.6L, 300 HP (223 KW) @ 3000 RPM, 520 LB-FT (705 N-M) TORQUE @ 1600 RPM	\$9,259.00
GVWR		
GZX	17,500 LBS. (7938 KG) CAPACITY	INC
EMISSION		
FE9	FEDERAL REQUIREMENTS	INC
ROAD SPEED GOVERNOR		
KYW	75 MPH (120 KPH) SPEED GOVERNOR	INC
ALTERNATOR		
KG4	AD244, DELCO-REMY 150-AMP MAXIMUM	\$0.00
BATTERY		
TNL	DUAL AC DELCO, 750 CCA, 12V	INC

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.2, Data updated 12/25/2007 10:41:00 AM
 ©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 27, 2007 11:22:34 PM

Page 1

Prepared By:
 Albert Li
 Red Holman Pontiac GMC
 35300 Ford Rd
 Westland, MI 48185
 Phone: (734) 721-1144
 Fax: (734) 721-1780
 Email: aclixx@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

SELECTED MODEL & OPTIONS

SELECTED OPTIONS - 2008 Fleet/Non-Retail TC4C044 Regular Cab 4WD

<u>CATEGORY</u>		<u>MSRP</u>
<u>Code</u>	<u>Description</u>	
ENGINE SHUTDOWN		
KPJ	AUTOMATIC ENGINE SHUTDOWN WITH ALARM	INC
EXHAUST SYSTEM		
NB5	SINGLE HORIZONTAL-DRIVER SIDE MOUNTED INSIDE FRAME RAIL,	INC
POWER TAKE OFF		
PTO	ELECTRONIC ACTIVATION SWITCH, (ELECTRIC HAND THROTTLE), IP MOUNTED	\$225.00
TRANSMISSION		
MBV	AUTOMATIC, ALLISON 1000 HS/RDS SERIES 6-SPEED	\$0.00
TRANSMISSION FLUID		
MBT	TRANSYND SYNTHETIC AUTOMATIC TRANSMISSION FLUID	INC
TRANSMISSION EQUIPMENT		
KNP	AUXILIARY TRANSMISSION OIL COOLER	\$95.00
TRANSFER CASE		
NP1	NEW VENTURE GEAR-MODEL NV273 TWO-SPEED	INC
FRONT AXLE		
G38	8000 LBS. (3629 KG) CAPACITY	\$0.00
FRONT SUSPENSION		
FSN	TAPERED LEAF, 8000 LBS. (3629 KG) CAPACITY	\$0.00
FRONT STABILIZER BAR		
F59	STABILIZER BAR	INC
FRONT WHEEL		
Q82	19.5" X 6.75" (49.5 CM X 17.1 CM), STEEL DISC	\$0.00
FRONT TIRE		
XTY	245/70R19.5G	\$0.00
FRONT TIRE BRAND		
R4A	GOODYEAR	\$0.00
FRONT TIRE TREAD		

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.2, Data updated 12/25/2007 10:41:00 AM
 ©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 27, 2007 11:22:34 PM

Page 2

Prepared By:
 Albert Li
 Red Holman Pontiac GMC
 35300 Ford Rd
 Westland, MI 48185
 Phone: (734) 721-1144
 Fax: (734) 721-1780
 Email: aclix@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

SELECTED MODEL & OPTIONS

SELECTED OPTIONS - 2008 Fleet/Non-Retail TC4C044 Regular Cab 4WD

CATEGORY

<u>Code</u>	<u>Description</u>	<u>MSRP</u>
FRONT TIRE TREAD		
R3H	HIGHWAY TRACTION	INC
SINGLE SPEED REAR AXLE		
HD2	SINGLE SPEED, DANA S110 13,500 LBS. (6123 KG) CAPACITY	INC
AXLE RATIO		
058	5.13:1	INC
TRACTION CONTROL		
G80	REAR LIMITED SLIP DIFFERENTIAL	INC
REAR SUSPENSION		
GR4	MULTI-LEAF, 13,500 LBS. (6123 KG) CAPACITY	INC
BOLTED OR RIVETED SUSPENSION		
EV8	REAR SUSPENSION BRACKETS ARE RIVETED TO FRAME IN LIEU OF BOLTS	\$0.00
REAR SHOCK ABSORBER		
SAN	REAR SHOCK ABSORBER NOT DESIRED	\$0.00
REAR WHEEL		
Q83	19.5" X 6.75" (49.5 CM X 17.1 CM), STEEL DISC	\$0.00
REAR TIRE		
YTY	245/70R19.5G	\$0.00
REAR TIRE BRAND		
S4A	GOODYEAR	\$0.00
REAR TIRE TREAD		
S3H	HIGHWAY TRACTION	INC
SPARE WHEEL		
SNF	FRONT	\$128.00
WHEELBASE		
EG9	152" (386.1 CM)	\$0.00
FUEL TANK		

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.2, Data updated 12/25/2007 10:41:00 AM
 ©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 27, 2007 11:22:34 PM

Page 3

Prepared By:
 Albert Li
 Red Holman Pontiac GMC
 35300 Ford Rd
 Westland, MI 48185
 Phone: (734) 721-1144
 Fax: (734) 721-1780
 Email: aclix@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

SELECTED MODEL & OPTIONS

SELECTED OPTIONS - 2008 Fleet/Non-Retail TC4C044 Regular Cab 4WD

<u>CATEGORY</u>		<u>MSRP</u>
<u>Code</u>	<u>Description</u>	
FUEL TANK		
NH4	SINGLE, 40-GALLON (151L) FUEL CAPACITY	INC
PARKING BRAKE		
J69	REAR IN-WHEEL PARK BRAKE	INC
DRIVER CONVENIENCE PACKAGES		
ZQ3	DRIVER CONVENIENCE PACKAGE	\$155.00
MISCELLANEOUS CAB EQUIPMENT		
N33	TILT-WHEEL ADJUSTABLE STEERING	INC
K34	CRUISE CONTROL,	INC
AIR CONDITIONING		
C60	AIR CONDITIONING	\$852.00
INSIDE REARVIEW MIRRORS		
D36	INSIDE DAY/NIGHT REARVIEW MIRROR	\$19.00
DRIVER SEAT		
AS4	HIGH-BACK BUCKET, FIXED HEIGHT, MANUAL ADJUSTER	INC
PASSENGER SEAT		
A59	TWO-PERSON, WITHOUT STORAGE	\$180.00
AIRBAGS		
AL3	SUPPLEMENTAL INFLATABLE RESTRAINTS NOT INCLUDED	INC
RADIO		
UM7	DELCO AM-FM STEREO RADIO	\$150.00
EXTERIOR MIRRORS		
DB5	MANUAL, 102" (259 CM) WIDE LOAD, INTEGRAL ARM, INTEGRAL CONVEX MIRROR	INC
PAINT		
ZY1	SOLID NON-METALLIC PAINT	INC
INTERIOR TRIM		
69I	VERY DARK PEWTER	INC

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.2, Data updated 12/25/2007 10:41:00 AM
 ©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 27, 2007 11:22:34 PM

Page 4

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclix@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

SELECTED MODEL & OPTIONS

SELECTED OPTIONS - 2008 Fleet/Non-Retail TC4C044 Regular Cab 4WD

CATEGORY

<u>Code</u>	<u>Description</u>	<u>MSRP</u>
SEAT TRIM		
_V	VINYL SEAT TRIM	INC
ADDITIONAL OPTIONS		
VQ1	FLEET PROCESSING OPTION	\$0.00
OPTIONS TOTAL		\$11,063.00

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.2, Data updated 12/25/2007 10:41:00 AM

©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 27, 2007 11:22:34 PM

Page 5

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclixx@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC4C044 Regular Cab 4WD

EXTERIOR

- Paint scheme, solid, upper color, Summit White
- Paint scheme, solid, lower color, Summit White
- Exterior roof drip moldings
- Bumper, front, steel, 96" (243.8 cm) wide - styled to minimized wall to wall turn diameter painted argent
- Steps under cab doors
- Front mud flaps
- Integral grille and fenders - The grille is the same color as hood with single halogen headlamps.
- Roof marker lamps
- Daytime running lamps
- Windows, Solar-Ray tinted. Light tinted windshield and side window glass with light transmissivity of 70%
- Mirrors, manual, 102" (259 cm) wide load, integral arm, integral convex mirror - black molded composite 12" x 7" (30.5 cm x 17.8 cm) with 6" x 7" (15.2 cm x 17.8 cm) convex section
- Windshield wipers, 2-speed and intermittent, with pulse washers
- Provisions for mounting front license plate
- Positive door stops

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.2, Data updated 12/25/2007 10:41:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 27, 2007 11:22:34 PM

Page 6

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclixx@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC4C044 Regular Cab 4WD

INTERIOR

- Seat, driver, high-back bucket, fixed height, manual adjuster - storage in the seat riser with a small lip at the front to stop contents from sliding out
- Seat, passenger, high-back bucket, fixed height, manual back angle adjuster - storage in the seat riser with a small lip at the front to stop contents from sliding out
- Seat trim, vinyl, Very Dark Pewter
- Interior trim, Very Dark Pewter (Requires 69V Very Dark Pewter vinyl or 69C Very Dark Pewter cloth)
- Trim console - located next to driver's seat and two cupholders
- Molded vinyl floor covering
- Steering wheel 16"
- Two sided single common key for doors and ignition
- Headlamp warning buzzer
- Warning tone, key-in-ignition
- Tachometer
- Electronic engine hour meter
- Engine "Check Gauges" telltale light and buzzer, oil pressure gauge
- Gauges, low oil pressure and coolant level, high coolant and engine oil temperature
- Vinyl door trim panels - with storage pocket on front doors, beverage holders, and reflector on all doors
- Stepwell storage areas at each door front and rear. Includes storage cover.
- Cloth headliner
- Sunshades, passenger side and driver side, vinyl-covered
- Coat hooks (2) located on cab back panel
- Provisions for stereo - includes AM/FM antenna, lead wiring for speakers, and separate door chime module (N/A with ZQ2 power convenience option)
- Air conditioning not desired - this option should be ordered only when a customer does not require air conditioning
- Powerpoints - two in-cab power sources (in addition to optional cigarette lighter) for electrical plug-in accessories

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.2, Data updated 12/25/2007 10:41:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.
Customer File:

December 27, 2007 11:22:35 PM

Page 7

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclix@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC4C044 Regular Cab 4WD

- Underhood bodybuilder connections accessory power supply - Provides 12V power supply from the battery with two separate 30 amp fused circuits

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.2, Data updated 12/25/2007 10:41:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 27, 2007 11:22:35 PM

Page 8

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclix@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC4C044 Regular Cab 4WD

MECHANICAL

- GVWR, 17,500 lbs. (7938 kg) capacity - GVWR. Maximum GCWR 26,000 lb. Note: Trucks that are used primarily to tow a trailer may be liable to Federal Excise Tax (FET). A New Law (Highway Transportation Bill HR3) was passed on August 10, 2005 - Check with IRS for guidelines
- Engine, Vortec 8.1L MD gasoline V8, 325 hp (239 kw) @ 4000 rpm and 450 lb-ft torque (610 N-m) @ 2,800 rpm. - Maximum engine speed 5000 rpm. Oil Level Sensor: Warning sensor for low oil levels
- Air cleaner, dry type
- Cooling, anti-freeze protection temperature - -40 degrees F (-40 degrees C)
- 75 mph (120 kph) speed governor - Required by the speed rating of the tires ordered
- Alternator, AD244 Delco-Remy 150-amp maximum (N/A with ANM Fire and Rescue or YF2 Ambulance Packages)
- Battery, single AC Delco, 600 CCA, 12V - 115-minute reserve capacity @ 27 degrees C, 600 CCA @ -18 degrees C grounded directly to starter, (Requires gasoline engine; N/A with ANQ Snow Plow Prep)
- Exhaust, single horizontal - driver side mounted inside frame rail, with gasoline engine stainless-steel exhaust with catalytic converter, with diesel engines, stainless-steel exhaust, oxidation catalyst, diesel particulate filter and exhaust gas cooler
- Option PTO not required - This option should only be ordered when a customer specifically does not require an electric hand throttle for use with power-take-off provisions. (Note: Will delete transmission PTO gear.)
- Transmission, automatic, Allison 1000 HS/RDS Series 6-speed - With parking pawl and column shift, includes 4th Generation Electronic Controls and 0.61 overdrive. Torque Rating: 660 lb-ft (895 N-m) with shift energy management. Available with a Gross Vehicle Weight up to 19,500 lbs. (8845 kg) and a Gross Combination Weight Rating up to 26,000 lbs. (11,790 kg). To include PTO gear, please order with RPO PTO for Allison 1000 RDS Rugged Duty Series transmission. Includes transmission-oil cooler located inside radiator. With Option PTX the truck will be equipped with the Allison 1000 HS Highway Series transmission. (N/A with ANM Fire and Rescue or YF2 Ambulance Package)
- TranSynd synthetic automatic transmission fluid
- Transfer case, New Venture Gear - model NV273 two-speed, electrically actuated, IP mounted switch, includes shield
- Front axle, 8000 lbs. (3629 kg) capacity - Solid drive axle. Up to 45 degree turn angle, includes 4 piston brake apply calipers and manual locking hubs
- Front suspension, tapered leaf, 8000 lbs. (3629 kg) capacity

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.2, Data updated 12/25/2007 10:41:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 27, 2007 11:22:35 PM

Page 9

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclbx@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC4C044 Regular Cab 4WD

- Front shock absorber, diameter 1.375" (35mm)
- Front stabilizer bar, Solid bar style, 1.5" (38mm)
- Front wheels, 19.5" x 6.75" (49.5 cm x 17.1 cm), steel disc - 8-hole, 10,000 lbs. (4536 kg) capacity, (Requires Q83 steel rear wheel and XTY or XNC front tires)
- Front tire size, 245/70R19.5G - 9090 lbs. (4123 kg) capacity (Requires KYR 65 mph or KYW 75 mph (120 kph) road speed governor, Q82 or RPM front wheels. With R4A Goodyear tire, requires R3H highway traction tread)
- Front tire manufacturer code, Goodyear (Requires S4A Goodyear)
- Front tread, highway traction
- Rear axle, single speed, Dana S110 13,500 lbs. (6123 kg) capacity - full floating, includes 2-piston brake applied calipers
- Four-wheel drive
- Rear axle ratio, 5.13:1 (Requires HD2 single speed rear axle)
- Rear limited slip differential
- Rear suspension, multi-leaf, 13,500 lbs. (6123 kg) capacity
- Rear suspension brackets are riveted to frame in lieu of bolts
- Rear shock absorber not desired (N/A with tapered leaf springs)
- Rear wheels, 19.5" x 6.75" (49.5 cm x 17.1 cm), steel disc - 8-hole, 20,000 lbs. (9072 kg) capacity (Requires Q82 front wheels and YTY or YNC rear tires)
- Rear tire size, 245/70R19.5G - 17,500 lbs. (7938 kg) capacity (Requires KYR 65 mph or KYW 75 mph (120 kph) road speed governor and Q83 or RPW rear wheels. With S4A Goodyear tire, requires S3H highway traction tread)
- Rear tire manufacturer code, Goodyear (Requires R4A Goodyear)
- Rear tread, highway traction
- Wheelbase, 152" (386.1 cm) - with 84" (213.4 cm) CA and 146" (370.8 cm) CE. Includes a 6mm 80,000 psi (551,600 kPa) yield strength, steel frame, RBM: 610,400 Section Modulus 7.63
- Frame, 8mm - 80,000 psi (551,600 kPa) yield strength, steel frame, RBM: 610,400 Section Modulus 7.63
- Fuel tank, single, 40-gallon (151L) fuel capacity - gas or diesel, located behind rear axle with fuel fill neck through frame rail and a black tethered fuel cap with gasoline engine and green un-tethered fuel cap with diesel engines. DRIVER SIDE FILL NECK ONLY. NO AUXILIARY PORTS. MINIMUM OVERHANG = 60" (5 FEET)

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.2, Data updated 12/25/2007 10:41:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.
Customer File:

December 27, 2007 11:22:35 PM

Page 10

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclixx@hotmail.com

2008 Fleet/Non-Retail GMC TC4500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC4C044 Regular Cab 4WD

- Fuel sender assembly. Robust fuel pump
- Tethered fuel cap
- Steering, power - ZF variable ratio power
- Brakes, front, power, 4-wheel disc, 4 channel ABS 4-piston - (See front axle options for more detail)
- Brakes, rear, power, 4-wheel disc, 4 channel ABS 2-piston - (See rear axle options for more detail)
- Parking brake, rear in-wheel park brake - hand lever operated

SAFETY

- 4-wheel disc, 4-channel ABS
- Air bags, Supplemental Inflatable Restraints not included.
- This vehicle does not include any air bags
- Seat belt warning indicator
- Daytime running lamps

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.2, Data updated 12/25/2007 10:41:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 27, 2007 11:22:35 PM

Page 11



APPENDIX B

TRUCK QUESTIONNAIRE FORMS

ALL BIDDERS MUST COMPLETE AND RETURN A QUESTIONNAIRE FORM WITH THE BID FOR EACH TRUCK ITEM TO BE CONSIDERED FOR AWARD OF THAT ITEM. Bids submitted without an adequately completed questionnaire form for EACH TRUCK ITEM will not be considered for award of that item. It is the responsibility of each bidder to copy this form in sufficient quantity to submit to Purchasing Operations prior to the scheduled bid due date. A single form may apply to more than one item, simply list the item numbers to which the questionnaire applies in the appropriate space. If part of the questionnaire does not apply, simply indicate "not applicable" in those spaces.

NAME OF BIDDER: Red Holman Pontiac GMC ITEM NO(S). Spec# 3958-0117
 MAKE OF TRUCK: GMC MODEL: C4500 TC4044 GVWR 17500 lbs.
 PAYLOAD: 8860 # W.B. 152" C.A. 84" C.F. 146"
 ENGINE: (GAS - DIESEL) Diesel MAKE: Gm Duramax MODEL: LRX, 6.6 SAE H.P. 300
 FUEL TANK(S) CAPACITY: 40 (GALS. TOTAL) TRANSMISSION: Allison 1000 max 6-spd
 SPRING CAP. @ GROUND EACH: FRONT 4000 lbs. REAR 6750 lbs. AUX. N/A lbs.
 AXLES: FRONT 8200 lbs. REAR 13500 lbs. REAR RATIO 5.13
 ALTERNATOR: 150 amps. BATTERY Dual 750 cca.
 TIRE SIZE: FRONT 245/70R19.5G PR REAR 245/70R19.5G PR SINGLE _____ DUAL M&S
 TIRE: MAKE Goodyear STYLE NO. TBD MFG. CODE XTY/YTY
 HOIST: MAKE N/A MODEL N/A INSTALLING CO. N/A
 BODY: MAKE N/A MODEL N/A INSTALLING CO. N/A
 POWER LIFT GATE: MAKE N/A MODEL N/A CAPACITY N/A lbs.
 PLATFORM SIZE: N/A

OTHER EQUIPMENT INSTALLED BY BODY EQUIPMENT SUPPLIER AND/OR COMMENTS

This information must be returned with the bid document to Purchasing Operations, on or before the bid due date and time. However, if returned separately, it must be received by Purchasing Operations on or before the bid due date and time, and must comply with the sealed bid instructions as outlined in the ITB.

TRUCK: CAB AND CHASSIS (G.V.W.R. 21,000 lbs., min.)*
LOW PROFILE

MODEL-2008 CURRENT NEW

	<u>FORD</u> <u>F650</u>	<u>INT'L</u> <u>4300M7</u>	<u>CHEV./GMC</u> <u>C5C042</u>
Wheelbase (inches)	158	152	152
C.A. (inches)	84	85	84
Engine: Diesel	Cummins ISB Maxx Force M7 Duramax		
Type & No. of Cylinders	I-6	V-8	V-8
Net H.P.-S.A.E.	200	200 Gross	300
Transmission: 5-speed w/ PTO Allison Auto. 2000/2400 Series			
Axle, Min. Cap-lbs.			
Front, 7,000 minimum	8,500	8,000	8,000
Rear, 17,500 minimum	17,500	17,500	19,000
Ratio for minimum loaded road speed of approx. 68 mph			
Springs, Min. Cap. at Ground			
Front- lbs. each	4,250**	4,000**	4,000**
Rear- lbs. each	8,750**	9,250**	9,500**
**includes shock absorbers			

*SEE Mich. 3958-0137 or 3958-0141 for body.

Tires, Truck, Tubeless, Radial, 245/70R19.5 (16PR) Minimum. Front to be Highway Tread, Rear duals-Traction Drive Tread, Goodyear Unisteel G-164 RTD or approved equal. Same Mfg. Front and Rear.

TO BE STANDARD FACTORY EQUIPPED AS FOLLOWS:

The items listed below are to be supplied on all trucks, even though they may be optional with the manufacturer. Therefore, these specifications are to be furnished on all vehicles:

- 12 Volt auxiliary outlet
- Air Conditioning - All trucks
- Anti-freeze protection, to -30°F.
- Arm Rest-Driver's side.

- ☑ Color-Manufacturers Standard to be selected.
- ☑ Coolant System-Maximum Size Available, including the Heaviest Duty Radiator
- ☑ Dome Light.
- ☑ Electric wiring-All wiring passing through holes in metal or non-metal wearing surfaces, which could cause wear of the insulation, shall be adequately protected by rubber or plastic grommets, and/or non-metallic conduit. Ends of all wires shall be adequately anchored to prevent loosening.
- ☑ Frame length-on all body installations without hoists the cab to end of frame length shall be the same length as the body being mounted, plus the length of any setback.
- ☑ Fuel Tanks, Diesel, with sending unit and magnetic drain plug, on all trucks over 21,000 G.V.W.R., painted Black and labeled "Diesel Fuel Only".
- ☑ Hub caps on all pickups and vans up to and including 10,000 G.V.W.R. If not available from dealer cap nuts shall be furnished.
- ☑ Keys-(2) sets with code numbers; shall be with vehicle at time of delivery.
- ☑ Mirrors-All trucks are to be equipped with R.H. and L.H. outside rear-view mirrors to comply with Michigan laws; all trucks up to and including 15,000 G.V.W.R. shall be equipped with inside rear-view mirror. In all cases, outside R.H. & L.H. rear view mirrors shall provide full vision past all body installations. Mirrors shall be of stainless steel or high impact plastic construction unless denoted otherwise in individual truck specifications. All West Coast Type or Below Eye Level Camper Style Mirrors shall have stainless steel or high impact plastic heads, brackets, and hardware.
- ☑ Mud flaps, Anti-Sail Type, when required, are to be plain, rubber 1/4" thick, without advertising on either side.
- ☑ Painting-preclean and metal prep, any bare metal surfaces prior to applying a compatible red oxide or zinc chromate primer. When painting over a manufacturer's standard paint, metal prepping and primer may be omitted, provided an acceptable bond can be achieved.
- ☑ Equipment mounting- when mounting equipment on truck cab and chassis, all holes shall be drilled or punched. There shall be no flame cutting or welding on the frame side rails.
- ☑ Paint codes-factory paint codes shall be furnished with all vehicles; for all after market painting both the brand and paint code shall be furnished.
- ☑ Pre-delivery inspection and servicing.
- ☑ Radio - AM/FM Manufacturers Standard, Factory Installed
- ☑ Seat Belts with Shoulder Harness (3-Point Restraint System for Driver & Passenger)
- ☑ Seats-Split Bench type, unless otherwise specified
- ☑ Shock absorbers-(Heaviest Duty Available), front all trucks. Rear, up to and including 15,000 G.V.W.R.
- ☑ Spare tire, or Rim, not to be furnished unless specified. If specified, tires to be of same mfg., tread design to be same as front tires.
- ☑ Speed Control, Factory Installed
- ☑ Steering-Power, Tilt Wheel
- ☑ Sun visors-dual.
- ☑ Jack-Furnish on trucks up to and including 12,000 G.V.W.R.
- ☑ Windshield wipers-dual, intermittent speed electric, with automatic type washers.

All items removed for installation of optional equipment shall be returned to the State of Michigan.

TO BE EQUIPPED IN COMPLIANCE WITH ALL APPLICABLE FEDERAL MOTOR VEHICLE SAFETY STANDARDS AND REGULATIONS. ALL

VEHICLES MUST BE EQUIPPED TO COMPLY WITH ALL REQUIREMENTS OF THE MICHIGAN MOTOR VEHICLE CODE.

- **Delete: On GM vehicles, OnStar and XM radio are deleted.**

ADDITIONAL OPTIONS:

These options are in addition to the options listed above as “STANDARD FACTORY EQUIPPED” and are to be included on this vehicle.

- Air Conditioning-Factory Installed
- Alternator-100 amp. min., Reference 22SI or approved equal
- Battery(s)-12 Volt, 1,100 CCA minimum.
- Brakes-Power. Current FMVSS.
- Cab assist handles-right and left.
- Fuel Tank-50 gallon each, minimum, L.H. and R.H. Step Tanks. GMC: Single In-rail Fuel Tank. 40 Gal.
- Hood, Tilt.
- Mirrors-Rear View, Outside. L.H. and R.H. West Coast type, 6" x 16", installed, with stainless steel or powder coated steel or composite heads, brackets, and hardware.
- Shock Absorbers, Front and Rear
- Steering-Power.
- Switches (6), outfitter, with remote power module (MDOT) GMC: Switch panel only, unless supplied by upfitter
- Tachometer.
- Throttle, Electronic, High Idle Engine RPM Control.
- Wheels, Hub Pilot Disc Type

PRICING SHEET

<u>TRUCK: CAB AND CHASSIS (G.V.W.R. 21,000 lbs., min.)*</u>	
<u>LOW PROFILE</u>	
Mich. Spec. #3958-0134	
Standard Equipped Per above Specification (Including options as specified above)	Standard Equipped Cost
Make: GMC Model: Topkick C5500 F.O.B. - Dealership Delivery Cost Per Mile \$1.50	\$40,746.00*
Final Point of Assembly: Flint, MI	
<u>Dealer Information</u>	
Dealer Name: Red Holman Pontiac GMC	
Street Address: 35300 Ford Road	
City: Westland	State: MI
	Zip: 48185
Contact Name: Albert Li	
Telephone: (800) 482-3032	
Cell: (734) 637-6643	
E-mail: aclixx@hotmail.com	

*Please Note: A vehicle order confirmation sheet is included for each vehicle. These documents shall include all the "standard options" as listed for the State of Michigan standard specification.

Prepared By:
 Albert Li
 Red Holman Pontiac GMC
 35300 Ford Rd
 Westland, MI 48185
 Phone: (734) 721-1144
 Fax: (734) 721-1780
 Email: aclix@hotmail.com

2008 Fleet/Non-Retail GMC TC5500

SELECTED MODEL & OPTIONS

SELECTED MODEL - 2008 Fleet/Non-Retail TC5C042 Regular Cab 2WD

<u>Code</u>	<u>Description</u>	<u>MSRP</u>
TC5C042	2008 GMC TC5500 Regular Cab 2WD	\$37,740.00

SELECTED VEHICLE COLORS - 2008 Fleet/Non-Retail TC5C042 Regular Cab 2WD

<u>Code</u>	<u>Description</u>
-	Interior: No color has been selected.
-	Exterior 1: No color has been selected.
-	Exterior 2: No color has been selected.

SELECTED OPTIONS - 2008 Fleet/Non-Retail TC5C042 Regular Cab 2WD

CATEGORY

<u>Code</u>	<u>Description</u>	<u>MSRP</u>
PREFERRED EQUIPMENT GROUP		
C5C042	CUSTOM/BASE MODEL	\$0.00
DIESEL ENGINE		
LRX	DURAMAX DIESEL 6.6L, 300 HP (223 KW) @ 3000 RPM, 520 LB-FT (705 N-M) TORQUE @ 1600 RPM	\$10,219.00
GVWR		
GW4	26,000 LBS. (11,794 KG) GVWR SALES PACKAGE,	\$5,457.00
C6V	26,000 LBS. (11,794 KG) CAPACITY	INC
EMISSION		
FE9	FEDERAL REQUIREMENTS	INC
ROAD SPEED GOVERNOR		
KYW	75 MPH (120 KPH) SPEED GOVERNOR	\$0.00
ALTERNATOR		
KG4	AD244, DELCO-REMY 150-AMP MAXIMUM	INC
BATTERY		

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.2, Data updated 12/25/2007 10:41:00 AM
 ©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.
 Customer File:

Prepared By:
 Albert Li
 Red Holman Pontiac GMC
 35300 Ford Rd
 Westland, MI 48185
 Phone: (734) 721-1144
 Fax: (734) 721-1780
 Email: aclixx@hotmail.com

2008 Fleet/Non-Retail GMC TC5500

SELECTED MODEL & OPTIONS

SELECTED OPTIONS - 2008 Fleet/Non-Retail TC5C042 Regular Cab 2WD

CATEGORY

<u>Code</u>	<u>Description</u>	<u>MSRP</u>
BATTERY		
TNL	DUAL AC DELCO, 750 CCA, 12V	INC
ENGINE SHUTDOWN		
KPJ	AUTOMATIC ENGINE SHUTDOWN WITH ALARM	INC
EXHAUST SYSTEM		
NB5	SINGLE HORIZONTAL-PASSENGER SIDE MOUNTED INSIDE FRAME RAIL	INC
POWER TAKE OFF		
PTO	ELECTRONIC ACTIVATION SWITCH, (ELECTRIC HAND THROTTLE), IP MOUNTED	\$250.00
TRANSMISSION		
MBZ	AUTOMATIC, ALLISON 2200 HS/RDS SERIES 6-SPEED	\$985.00
TRANSMISSION FLUID		
MBT	TRANSYND SYNTHETIC AUTOMATIC TRANSMISSION FLUID	INC
FRONT AXLE		
FM8	8000 LBS. (3629 KG) CAPACITY	INC
FRONT SUSPENSION		
FSN	TAPERED LEAF, 8000 LBS. (3629 KG) CAPACITY	\$82.00
FRONT WHEEL		
Q82	19.5" X 6.75" (49.5 CM X 17.1 CM), STEEL DISC	INC
FRONT TIRE		
XNC	245/70R19.5H	\$118.00
FRONT TIRE BRAND		
R4A	GOODYEAR	\$0.00
FRONT TIRE TREAD		
R3C	PREMIUM HIGHWAY	\$0.00
SINGLE SPEED REAR AXLE		
HPK	DANA 19060S, 19,000 LBS. (8618 KG) CAPACITY	INC
AXLE RATIO		

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.2, Data updated 12/25/2007 10:41:00 AM
 ©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.
 Customer File:

December 27, 2007 11:51:14 PM

Page 2

Prepared By:
 Albert Li
 Red Holman Pontiac GMC
 35300 Ford Rd
 Westland, MI 48185
 Phone: (734) 721-1144
 Fax: (734) 721-1780
 Email: aclixx@hotmail.com

2008 Fleet/Non-Retail GMC TC5500

SELECTED MODEL & OPTIONS

SELECTED OPTIONS - 2008 Fleet/Non-Retail TC5C042 Regular Cab 2WD

<u>CATEGORY</u>		<u>MSRP</u>
<u>Code</u>	<u>Description</u>	
AXLE RATIO		
006	4.63:1	\$0.00
REAR SUSPENSION		
GN0	MULTI-LEAF, 19,000 LBS. (8618 KG) CAPACITY	\$66.00
BOLTED OR RIVETED SUSPENSION		
EV8	REAR SUSPENSION BRACKETS ARE RIVETED TO FRAME IN LIEU OF BOLTS	\$0.00
REAR SHOCK ABSORBER		
G68	REAR SHOCK ABSORBER	\$58.00
REAR WHEEL		
Q83	19.5" X 6.75" (49.5 CM X 17.1 CM), STEEL DISC	INC
REAR TIRE		
YNC	245/70R19.5H	\$386.00
REAR TIRE BRAND		
S4A	GOODYEAR	\$0.00
REAR TIRE TREAD		
S3H	HIGHWAY TRACTION	\$0.00
WHEELBASE		
EG9	152" (386.1 CM)	\$184.00
REINFORCEMENT		
F08	"L" CHANNEL	INC
FUEL TANK		
NG6	DUAL, TOTAL FUEL CAPACITY OF 40-GALLONS (151L)	\$136.00
DRIVER CONVENIENCE PACKAGES		
ZQ3	DRIVER CONVENIENCE PACKAGE	\$173.00
MISCELLANEOUS CAB EQUIPMENT		
N33	TILT-WHEEL ADJUSTABLE STEERING	INC
K34	CRUISE CONTROL,	INC

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.2, Data updated 12/25/2007 10:41:00 AM
 ©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 27, 2007 11:51:14 PM

Page 3

Prepared By:
 Albert Li
 Red Holman Pontiac GMC
 35300 Ford Rd
 Westland, MI 48185
 Phone: (734) 721-1144
 Fax: (734) 721-1780
 Email: aclixx@hotmail.com

2008 Fleet/Non-Retail GMC TC5500

SELECTED MODEL & OPTIONS

SELECTED OPTIONS - 2008 Fleet/Non-Retail TC5C042 Regular Cab 2WD

<u>CATEGORY</u>		<u>MSRP</u>
<u>Code</u>	<u>Description</u>	
AIR CONDITIONING		
C60	AIR CONDITIONING	\$939.00
DRIVER SEAT		
AS4	HIGH-BACK BUCKET, FIXED HEIGHT, MANUAL ADJUSTER	INC
PASSENGER SEAT		
A59	TWO-PERSON, WITHOUT STORAGE	\$200.00
AIRBAGS		
AL3	SUPPLEMENTAL INFLATABLE RESTRAINTS NOT INCLUDED	INC
RADIO		
UM7	DELCO AM-FM STEREO RADIO	\$165.00
EXTERIOR MIRRORS		
DB5	MANUAL, 102" (259 CM) WIDE LOAD, INTEGRAL ARM, INTEGRAL CONVEX MIRROR	INC
PAINT		
ZY1	SOLID NON-METALLIC PAINT	INC
INTERIOR TRIM		
69I	VERY DARK PEWTER	INC
SEAT TRIM		
_V	VINYL SEAT TRIM	INC
OPTIONS TOTAL		\$19,418.00

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.2, Data updated 12/25/2007 10:41:00 AM
 ©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 27, 2007 11:51:14 PM

Page 4

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclix@hotmail.com

2008 Fleet/Non-Retail GMC TC5500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC5C042 Regular Cab 2WD

EXTERIOR

- Paint scheme, solid, upper color, Summit White
- Paint scheme, solid, lower color, Summit White
- Exterior roof drip moldings
- Bumper, front, steel, 96" (243.8 cm) wide - styled to minimized wall to wall turn diameter painted argent
- Steps under cab doors
- Front mud flaps
- Integral grille and fenders - The grille is the same color as hood with single halogen headlamps.
- Roof marker lamps
- Daytime running lamps
- Windows, Solar-Ray tinted. Light tinted windshield and side window glass with light transmissivity of 70%
- Mirrors, manual, 102" (259 cm) wide load, integral arm, integral convex mirror - black molded composite 12" x 7" (30.5 cm x 17.8 cm) with 6" x 7" (15.2 cm x 17.8 cm) convex section
- Windshield wipers, 2-speed and intermittent, with pulse washers
- Provisions for mounting front license plate
- Positive door stops

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.2, Data updated 12/25/2007 10:41:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 27, 2007 11:51:14 PM

Page 5

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: acli@hotmai.com

2008 Fleet/Non-Retail GMC TC5500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC5C042 Regular Cab 2WD

INTERIOR

- Seat, driver, high-back bucket, fixed height, manual adjuster - storage in the seat riser with a small lip at the front to stop contents from sliding out
- Seat, passenger, high-back bucket, fixed height, manual back angle adjuster - storage in the seat riser with a small lip at the front to stop contents from sliding out
- Seat trim, vinyl, Very Dark Pewter
- Interior trim, Very Dark Pewter (Requires 69V Very Dark Pewter vinyl or 69C Very Dark Pewter cloth)
- Trim console - located next to driver's seat, and two cupholder
- Molded vinyl floor covering
- Steering wheel 16"
- Two sided single common key for doors and ignition
- Headlamp warning buzzer
- Warning tone, key-in-ignition
- Tachometer with automatic and manual transmissions
- Electronic engine hour meter
- Engine "Check Gauges" telltale light and buzzer, oil pressure gauge
- Gauges, low oil pressure and coolant level, high coolant and engine oil temperature
- Vinyl door trim panels - with storage pocket on front doors, beverage holders, and reflector on all doors
- Stepwell storage areas at each door front and rear. Includes storage cover.
- Cloth headliner
- Sunshades, passenger side and driver side, vinyl-covered
- Coat hooks (2) located on cab back panel
- Provisions for stereo - Includes AM/FM antenna, lead wiring for speakers, and separate door chime module, (N/A with ZQ2 driver convenience package)
- Air conditioning not desired - this option should be ordered only when a customer does not require air conditioning
- Powerpoints - two in-cab power sources (in addition to optional cigarette lighter) for electrical plug-in accessories

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.2, Data updated 12/25/2007 10:41:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.
Customer File:

December 27, 2007 11:51:14 PM

Page 6

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclix@hotmail.com

2008 Fleet/Non-Retail GMC TC5500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC5C042 Regular Cab 2WD

- Underhood bodybuilder connections accessory power supply - Provides 12V power supply from the battery with two separate 30 amp fused circuits

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.2, Data updated 12/25/2007 10:41:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 27, 2007 11:51:14 PM

Page 7

Prepared By:

Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclixx@hotmail.com

2008 Fleet/Non-Retail GMC TC5500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC5C042 Regular Cab 2WD

MECHANICAL

- GVWR, 19,500 lbs. (8845 kg) capacity - GCWR limited to 26,000 lb. (11,794 kg) or 30,000 lb. with optional Allison 2350 Series transmissions (MHE/MHD). NOTE: Trucks that are used primarily to tow a trailer may be liable to Federal Excise Tax (FET). A New Law (Highway Transportation Bill HR3) was passed on August 10, 2005 - Check with IRS for guidelines
- Engine, Vortec 8.1L MD gasoline V8, 325 hp (239 kw) @ 4000 rpm and 450 lb-ft torque (610 N-m) @ 2,800 rpm. - Maximum engine speed 5000 rpm. Oil Level Sensor: Warning sensor for low oil levels
- Air cleaner, dry type
- Cooling, anti-freeze protection temperature - -40 degrees F (-40 degrees C)
- Road Speed Governor, controlled by the speed rating of the tires ordered. - which will be less than or equal to 85 mph (137 kph); 80 mph (129 kph) with EC9 128" wheelbase/60" CA, ML6 manual transmission and 008 4.88 rear axle ratio; 75 mph (120 kph) with EC9 128" wheelbase/60" CA, M74 automatic transmission and HD2 rear axle
- Alternator, AD244 Delco-Remy 150-amp maximum (N/A with YW2 Wrecker package, ANM Fire and Rescue package or YF2 Ambulance package)
- Battery, single AC Delco, 600 CCA, 12V - 115-minute reserve capacity @ 27 degrees C, 600 CCA @ -18 degrees C grounded directly to starter. (Requires gasoline engine) (N/A with ANQ Snow Plow Prep package or YW2 Wrecker package)
- Exhaust, single horizontal - passenger side mounted inside frame rail. With gasoline engines, stainless-steel exhaust with catalytic converter. With diesel engines, stainless-steel exhaust, oxidation catalyst, diesel particulate filter and exhaust gas cooler.
- Option PTO not required - This option should only be ordered when a customer specifically does not require an electric hand throttle for use with power-take-off provisions. (Note: Will delete transmission PTO gear.)
- Transmission, automatic, Allison 1000 HS/RDS Series 6-speed - With parking pawl and column shift, includes 4th Generation Electronic Controls and 0.61 overdrive. Torque Rating: 660 lb-ft (895 N-m) with shift energy management. Available with a Gross Vehicle Weight up to 19,500 lbs. (8845 kg) and a Gross Combination Weight Rating up to 26,000 lbs. (11,790 kg). To include PTO gear, please order with RPO PTO for Allison 1000 RDS Rugged Duty Series transmission. Includes transmission-oil cooler located inside radiator. With Option PTX the truck will be equipped with the Allison 1000 HS Highway Series transmission. (N/A with ANM Fire and Rescue or YF2 Ambulance Package; N/A with GW2 or GW4 Sales Packages)
- TranSynd synthetic automatic transmission fluid

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.2, Data updated 12/25/2007 10:41:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.
Customer File:

December 27, 2007 11:51:14 PM

Page 8

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclix@hotmail.com

2008 Fleet/Non-Retail GMC TC5500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC5C042 Regular Cab 2WD

- Front axle, 7000 lbs. (3175 kg) capacity - I-beam Wide-trac. Up to 53 degree turn angle, includes 4-piston brake apply calipers. Steering Gear Series: ZF8014, (Requires GZG or GZJ GVWRs)
- Front suspension, tapered leaf, 7000 lbs. (3175 kg) capacity (includes stabilizer) (Requires GZG or GZJ GVWRs)
- Front shock absorber, diameter 1.375" (35mm)
- Front stabilizer bar, 2" x 2" square tube (5 cm x 5 cm)
- Front wheels, 19.5" x 6.75" (49.5 cm x 17.1 cm), steel disc - 8-hole. 10,000 lbs. (4536 kg) capacity, (Requires Q83 steel rear wheel)
- Front tire size, 225/70R19.5F - 7280 lbs. (3302 kg) capacity, (With R4A Goodyear or R4L Michelin, requires R3C front premium highway tread)
- Front tire manufacturer code, Goodyear (Requires S4A Goodyear)
- Front tread, premium, highway (Requires R4A Goodyear or R4L Michelin)
- Rear axle, single speed, Dana S110 13,500 lbs. (6123 kg) capacity - full floating, Includes 2-piston brake applied calipers. (Requires GZG or GZJ GVWR)
- Rear wheel drive
- Rear axle ratio, 5.13:1 (Requires gasoline engine and HD2 or HD1 single speed rear axles)
- Rear suspension, multi-leaf, 15,000 lbs. (6804 kg) capacity (Requires GZG or GZJ GVW and HD2 single speed rear axle)
- Rear suspension brackets are riveted to frame in lieu of bolts
- Rear shock absorber not desired (N/A with tapered leaf springs)
- Rear wheels, 19.5" x 6.75" (49.5 cm x 17.1 cm), steel disc - 8-hole, 20,000 lbs. (9072 kg) capacity, (Requires Q82 steel front wheel)
- Rear tire size, 225/70R19.5F - 13,660 lbs. (6196 kg) capacity, (With S4A Goodyear, requires S3C rear premium highway tread or S3H rear traction tread; with S4L Michelin, requires S3C rear premium highway tread or S3J rear highway traction tread)
- Rear tire manufacturer code, Goodyear (Requires R4A Goodyear)
- Rear tread, premium, highway (Requires S4A Goodyear or S4L Michelin)
- Wheelbase, 128" (325.1 cm) - with 60" (152.4 cm) CA and 100" (254 cm) CE. Includes a 6mm 80,000 psi (551,600 kPa) yield strength, steel frame, RBM: 610,400 Section Modulus 7.63 (Requires KYW 75 mph (120 kph) road speed governor with and HD2 13,500 lbs. (6123 kg) capacity rear axle)

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.2, Data updated 12/25/2007 10:41:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 27, 2007 11:51:14 PM

Page 9

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclixx@hotmail.com

2008 Fleet/Non-Retail GMC TC5500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC5C042 Regular Cab 2WD

- Frame, 6mm - 80,000 psi (551,600 kPa) yield strength, steel frame, RBM: 610,400 Section Modulus 7.63
 - Fuel tank, single, 25-gallon (95L) fuel capacity - gas or diesel located midship between the frame rails, with fuel fill neck through the frame rail (this option uses the mid-frame tank included in the NG6 dual tank option) Tethered fuel cap is black with gasoline engines, and green un-tethered fuel cap with diesel engines. (Required in YW2 Wrecker Package) (Standard on 60" (152.4 cm) CA), (Optional on all other CA's) MINIMUM OVERHANG = 36" (3 FEET)
 - Fuel sender assembly. Robust fuel pump
 - Tethered fuel cap
 - Steering, power - ZF variable ratio power
 - Brakes, front, power, 4-wheel disc, 4 channel ABS 4-piston - (See Front Axle options more more details)
 - Brakes, rear, power, 4-wheel disc, 4 channel ABS 2-piston - (See Rear Axle options for more detail)
 - Parking brake, hand lever operated transmission mounted drum brake
- SAFETY**
- 4-wheel disc, 4-channel ABS
 - Air bags, Supplemental Inflatable Restraints not included. This vehicle does not include any air bags
 - Seat belt warning indicator
 - Daytime running lamps

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.2, Data updated 12/25/2007 10:41:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 27, 2007 11:51:14 PM

Page 10

APPENDIX B

TRUCK QUESTIONNAIRE FORMS

ALL BIDDERS MUST COMPLETE AND RETURN A QUESTIONNAIRE FORM WITH THE BID FOR EACH TRUCK ITEM TO BE CONSIDERED FOR AWARD OF THAT ITEM. Bids submitted without an adequately completed questionnaire form for EACH TRUCK ITEM will not be considered for award of that item. It is the responsibility of each bidder to copy this form in sufficient quantity to submit to Purchasing Operations prior to the scheduled bid due date. A single form may apply to more than one item, simply list the item numbers to which the questionnaire applies in the appropriate space. If part of the questionnaire does not apply, simply indicate "not applicable" in those spaces.

NAME OF BIDDER: Red Holman Pontiac GMC ITEM NO(s): Spec # 3958-0134
 MAKE OF TRUCK: GMC MODEL: C5500 TC5042 GVWR 26000 lbs. ^{Topkick}
 PAYLOAD: 17,751 # W.B. 152" ✓ C.A. 84" ✓ C.E. 146" ✓
 ENGINE: (GAS - DIESEL) Diesel MAKE: GM Duramax MODEL: LRX, 6.6 SAE H.P. 300 ✓
 FUEL TANK(S) CAPACITY: 40 (GALS. TOTAL) TRANSMISSION: Allison 2200 6-spd
 SPRING CAP. @ GROUND EACH: FRONT 4000 lbs. REAR 9500 lbs. AUX. N/A lbs.
 AXLES: FRONT 8000 lbs. REAR 19000 lbs. REAR RATIO 4.63
 ALTERNATOR: 150 amps. BATTERY Dual 750 1,500 cca. per remark
 TIRE SIZE: FRONT 245/70R19.5 HPR REAR 245/70R19.5 HPR SINGLE _____ DUAL ✓ M&S Rear
 TIRE: MAKE Goodyear STYLE NO. TBD MFG. CODE XNC/YNC
 HOIST: MAKE N/A MODEL N/A INSTALLING CO. N/A
 BODY: MAKE N/A MODEL N/A INSTALLING CO. N/A
 POWER LIFT GATE: MAKE N/A MODEL N/A CAPACITY N/A lbs.
 PLATFORM SIZE: N/A

OTHER EQUIPMENT INSTALLED BY BODY EQUIPMENT SUPPLIER AND/OR COMMENTS

This information must be returned with the bid document to Purchasing Operations, on or before the bid due date and time. However, if returned separately, it must be received by Purchasing Operations on or before the bid due date and time, and must comply with the sealed bid instructions as outlined in the ITB.

TRUCK: CAB AND CHASSIS (G.V.W.R. 21,000 lbs., min.)*

MODEL-2008 CURRENT NEW

	FORD <u>F650</u>	INT'L <u>4300 M7</u>	CHEV./ GMC <u>C6C042</u>
Wheelbase (inches)	158	152	152
C.A. (inches)	84	85	84
Engine: Diesel	Cummins ISB MaxxForce M7		Duramax
Type & No. of Cylinders	I-6	V-8	I-6
Net H.P.-S.A.E.	200	200 Gross	215
Transmission: 5-speed w/ PTO			Allison 2200RDS 6 spd w/park pawl
Allison Auto. 2000 Series			
Axle, Min. Cap-lbs.			
Front, 7,000 minimum	8,500	8,000	8,000
Rear, 17,500 minimum	17,500	17,500	19,000
Ratio for minimum loaded road speed of approx. 68 mph			
Springs, Min. Cap. at Ground			
Front- lbs. each	4,250**	4,000**	4,000**
Rear- lbs. each	8,750**	9,250**	9,500**
**includes shock absorbers			

*SEE Mich. 3958-0137 or 3958-0141 for body.

Tires, Truck, Tubeless, Radial, 9R22.5F (12PR) Minimum. Front to be Highway Tread, Rear duals-Traction Drive Tread, Goodyear Unisteel G-164 RTD or approved equal. Same Mfg. Front and Rear.

TO BE STANDARD FACTORY EQUIPPED AS FOLLOWS:

The items listed below are to be supplied on all trucks, even though they may be optional with the manufacturer. Therefore, these specifications are to be furnished on all vehicles:

- ☑ 12 Volt auxiliary outlet
- ☑ Air Conditioning - All trucks
- ☑ Anti-freeze protection, to -30°F.
- ☑ Arm Rest-Driver's side.
- ☑ Color-Manufacturers Standard to be selected.
- ☑ Coolant System-Maximum Size Available, including the Heaviest Duty Radiator
- ☑ Dome Light.
- ☑ Electric wiring-All wiring passing through holes in metal or non-metal wearing surfaces, which could cause wear of the insulation, shall be adequately protected by rubber or plastic grommets, and/or non-metallic conduit. Ends of all wires shall be adequately anchored to prevent loosening.
- ☑ Frame length-on all body installations without hoists the cab to end of frame length shall be the same length as the body being mounted, plus the length of any setback.
- ☑ Fuel Tanks, Diesel, with sending unit and magnetic drain plug, on all trucks over 21,000 G.V.W.R., painted Black and labeled "Diesel Fuel Only".
- ☑ Hub caps on all pickups and vans up to and including 10,000 G.V.W.R. If not available from dealer cap nuts shall be furnished.
- ☑ Keys-(2) sets with code numbers; shall be with vehicle at time of delivery.
- ☑ Mirrors-All trucks are to be equipped with R.H. and L.H. outside rear-view mirrors to comply with Michigan laws; all trucks up to and including 15,000 G.V.W.R. shall be equipped with inside rear-view mirror. In all cases, outside R.H. & L.H. rear view mirrors shall provide full vision past all body installations. Mirrors shall be of stainless steel or high impact plastic construction unless denoted otherwise in individual truck specifications. All West Coast Type or Below Eye Level Camper Style Mirrors shall have stainless steel or high impact plastic heads, brackets, and hardware.
- ☑ Mud flaps, Anti-Sail Type, when required, are to be plain, rubber 1/4" thick, without advertising on either side.
- ☑ Painting-preclean and metal prep, any bare metal surfaces prior to applying a compatible red oxide or zinc chromate primer. When painting over a manufacturer's standard paint, metal prepping and primer may be omitted, provided an acceptable bond can be achieved.
- ☑ Equipment mounting- when mounting equipment on truck cab and chassis, all holes shall be drilled or punched. There shall be no flame cutting or welding on the frame side rails.
- ☑ Paint codes-factory paint codes shall be furnished with all vehicles; for all after market painting both the brand and paint code shall be furnished.
- ☑ Pre-delivery inspection and servicing.
- ☑ Radio - AM/FM Manufacturers Standard, Factory Installed
- ☑ Seat Belts with Shoulder Harness (3-Point Restraint System for Driver & Passenger)
- ☑ Seats-Split Bench type, unless otherwise specified
- ☑ Shock absorbers-(Heaviest Duty Available), front all trucks. Rear, up to and including 15,000 G.V.W.R.
- ☑ Spare tire, or Rim, not to be furnished unless specified. If specified, tires to be of same mfg., tread design to be same as front tires.
- ☑ Speed Control, Factory Installed
- ☑ Steering-Power, Tilt Wheel

- ☑ Sun visors-dual.
- ☑ Jack-Furnish on trucks up to and including 12,000 G.V.W.R.
- ☑ Windshield wipers-dual, intermittent speed electric, with automatic type washers.

All items removed for installation of optional equipment shall be returned to the State of Michigan.

TO BE EQUIPPED IN COMPLIANCE WITH ALL APPLICABLE FEDERAL MOTOR VEHICLE SAFETY STANDARDS AND REGULATIONS. ALL VEHICLES MUST BE EQUIPPED TO COMPLY WITH ALL REQUIREMENTS OF THE MICHIGAN MOTOR VEHICLE CODE.

- **Delete: On GM vehicles, OnStar and XM radio are deleted.**

ADDITIONAL OPTIONS:

These options are in addition to the options listed above as “STANDARD FACTORY EQUIPPED” and are to be included on this vehicle.

- ☑ Air Conditioning-Factory Installed
- ☑ Alternator-100 amp. min., Reference 22SI or approved equal
- ☑ Battery(s)-12 Volt, 1,100 CCA minimum.
- ☑ Brakes-Power. Current FMVSS.
- ☑ Cab assist handles-right and left.
- ☑ Fuel Tank-45 gallon each, minimum, L.H. and R.H. Step Tanks.
- ☑ Hood, Tilt.
- ☑ Mirrors-Rear View, Outside. L.H. and R.H. West Coast type, 6" x 16", installed, with stainless steel or powder coated steel heads, brackets, and hardware. GMC: Composite Heads
- ☑ Shock Absorbers, Front and Rear
- ☑ Steering-Power.
- ☑ Switches (6), outfitter, with remote power module (MDOT) GMC: Panel only, unless supplied by upfitter
- ☑ Tachometer.
- ☑ Throttle, Electronic, High Idle Engine RPM Control.
- ☑ Wheels, Hub Pilot Disc Type

PRICING SHEET

<u>TRUCK: CAB AND CHASSIS (G.V.W.R. 21,000 lbs., min.)*</u>	
Mich. Spec. #3958-0135	
Standard Equipped Per above Specification (Including options as specified above)	Standard Equipped Cost
Make: GMC Model: Topkick C6500 F.O.B. - Dealership Delivery Cost Per Mile \$1.50	\$46,108.00*
Final Point of Assembly: Flint, MI	
<u>Dealer Information</u>	
Dealer Name: Red Holman Pontiac GMC	
Street Address: 35300 Ford Road	
City: Westland	State: MI
	Zip: 48185
Contact Name: Albert Li	
Telephone: (800) 482-3032	
Cell: (734) 637-6643	
E-mail: aclixx@hotmail.com	

*Please Note: A vehicle order confirmation sheet is included for each vehicle. These documents shall include all the "standard options" as listed for the State of Michigan standard specification.

Vehicle Order Confirmation Sheet
Spec # 3958-0135

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclix@hotmail.com

2008 Fleet/Non-Retail GMC TC6500

SELECTED MODEL & OPTIONS

SELECTED MODEL - 2008 Fleet/Non-Retail TC6C042 Regular Cab

<u>Code</u>	<u>Description</u>	<u>MSRP</u>
TC6C042	2008 GMC TC6500 Regular Cab	\$45,200.00

SELECTED VEHICLE COLORS - 2008 Fleet/Non-Retail TC6C042 Regular Cab

<u>Code</u>	<u>Description</u>
-	Interior: No color has been selected.
-	Exterior 1: No color has been selected.
-	Exterior 2: No color has been selected.

SELECTED OPTIONS - 2008 Fleet/Non-Retail TC6C042 Regular Cab

CATEGORY

<u>Code</u>	<u>Description</u>	<u>MSRP</u>
PREFERRED EQUIPMENT GROUP		
C6C042	CUSTOM/BASE MODEL	\$0.00
VEHICLE APPLICATION		
RQ2	TRUCK APPLICATION	INC
GVWR		
GZI	RATES GVWR AT 25,950 LBS. (11,736 KG) CAPACITY,	\$0.00
EMISSION		
FE9	FEDERAL REQUIREMENTS	INC
DIESEL ENGINE		
LYA	ISUZU DIESEL 6H 7.8L I6, 215 HP (160 KW) @ 2200 RPM AND 560 LB-FT TORQUE (759 N-M) @ 1450 RPM	\$16,466.00
AIR CLEANER		
KNB	DRY-TYPE STANDARD FILTER ELEMENT	\$0.00
FUEL/WATER SEPARATOR		
NWB	RACOR FRAME-MOUNTED SPIN-ON TYPE	INC

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.2, Data updated 12/25/2007 10:41:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 28, 2007 12:15:14 AM

Page 1

Prepared By:
 Albert Li
 Red Holman Pontiac GMC
 35300 Ford Rd
 Westland, MI 48185
 Phone: (734) 721-1144
 Fax: (734) 721-1780
 Email: aclix@hotmail.com

2008 Fleet/Non-Retail GMC TC6500

SELECTED MODEL & OPTIONS

SELECTED OPTIONS - 2008 Fleet/Non-Retail TC6C042 Regular Cab

<u>CATEGORY</u>		<u>MSRP</u>
<u>Code</u>	<u>Description</u>	
ALTERNATOR		
K60	22SI, DELCO 100-AMP MAXIMUM	\$0.00
BATTERY		
TNL	DUAL AC DELCO, 750 CCA, 12V	\$0.00
ALARM		
KPJ	AUTOMATIC ENGINE SHUTDOWN WITH ALARM	INC
EXHAUST SYSTEM		
NB5	SINGLE HORIZONTAL-DRIVER SIDE MOUNTED INSIDE FRAME RAIL	\$0.00
POWER TAKE OFF		
PTO	ELECTRONIC ACTIVATION SWITCH, (ELECTRIC HAND THROTTLE), IP MOUNTED	\$250.00
AUTOMATIC TRANSMISSION		
MBZ	ALLISON 2200 HS/RDS SERIES 6-SPEED	\$555.00
TRANSMISSION FLUID		
MBT	TRANSYND SYNTHETIC AUTOMATIC TRANSMISSION FLUID	INC
FRONT AXLE		
FM8	8000 LBS. (3629 KG) CAPACITY	INC
FRONT SUSPENSION		
FSN	TAPERED LEAF, 8000 LBS. (3629 KG) CAPACITY	\$0.00
FRONT WHEEL		
QH3	22.5" X 7.5" (58.9 CM X 19 CM), STEEL DISC	INC
FRONT TIRE		
XWJ	10R22.5F-10,300 LBS. (4672 KG) CAPACITY	\$120.00
FRONT TIRE BRAND		
R4A	GOODYEAR	\$0.00
FRONT TIRE TREAD		
R3C	PREMIUM, HIGHWAY	\$0.00
SINGLE SPEED REAR AXLE		

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.2, Data updated 12/25/2007 10:41:00 AM
 ©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 28, 2007 12:15:14 AM

Page 2

Prepared By:
 Albert Li
 Red Holman Pontiac GMC
 35300 Ford Rd
 Westland, MI 48185
 Phone: (734) 721-1144
 Fax: (734) 721-1780
 Email: aclix@hotmail.com

2008 Fleet/Non-Retail GMC TC6500

SELECTED MODEL & OPTIONS

SELECTED OPTIONS - 2008 Fleet/Non-Retail TC6C042 Regular Cab

<u>CATEGORY</u>		<u>MSRP</u>
<u>Code</u>	<u>Description</u>	
SINGLE SPEED REAR AXLE		
HPK	DANA 19060S, 19,000 LBS. (8618 KG) CAPACITY	\$203.00
AXLE RATIO		
017	6.50:1	INC
REAR SUSPENSION		
GN0	MULTI-LEAF, 19,000 LBS. (8618 KG) CAPACITY	\$41.00
REAR SHOCK ABSORBER		
G68	REAR SHOCK ABSORBER	\$58.00
REAR WHEEL		
QH4	22.5" X 7.5" (58.9 CM X 19 CM), STEEL DISC	INC
REAR TIRE		
YWJ	10R22.5F-19,500 LBS. (8845 KG) CAPACITY	\$320.00
REAR TIRE BRAND		
S4A	GOODYEAR	\$0.00
REAR TIRE TREAD		
S3H	HIGHWAY TRACTION	\$0.00
WHEELBASE		
EG9	152" (386.1 CM)	\$0.00
FRAME RAIL		
FD5	RAIL, PAINTED SEMI-GLOSS BLACK 8MM-80,000 PSI (551,600 KPA) YIELD STRENGTH,	\$155.00
FUEL TANK		
NNQ	DUAL, 100-GALLON (380L) TOTAL FUEL CAPACITY,	\$370.00
BRAKE SYSTEM		
JE3	HYDRAULIC, SPLIT BRAKE SYSTEM	INC
AIR COMPRESSOR		
KK3	HALDEX 292 WATER-COOLED 12.9 CFM	INC
DRIVER CONVENIENCE PACKAGES		

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.2, Data updated 12/25/2007 10:41:00 AM
 ©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 28, 2007 12:15:14 AM

Page 3

Prepared By:
 Albert Li
 Red Holman Pontiac GMC
 35300 Ford Rd
 Westland, MI 48185
 Phone: (734) 721-1144
 Fax: (734) 721-1780
 Email: aclibx@hotmail.com

2008 Fleet/Non-Retail GMC TC6500

SELECTED MODEL & OPTIONS

SELECTED OPTIONS - 2008 Fleet/Non-Retail TC6C042 Regular Cab

CATEGORY

<u>Code</u>	<u>Description</u>	<u>MSRP</u>
DRIVER CONVENIENCE PACKAGES		
ZQ3	DRIVER CONVENIENCE PACKAGE	\$172.00
MISCELLANEOUS CAB EQUIPMENT		
N33	TILT-WHEEL ADJUSTABLE STEERING	INC
K34	CRUISE CONTROL,	INC
AIR CONDITIONING		
C60	AIR CONDITIONING	\$939.00
INSIDE REARVIEW MIRRORS		
D36	INSIDE DAY/NIGHT REARVIEW MIRROR	\$21.00
DRIVER SEAT		
AS4	HIGH-BACK BUCKET, FIXED HEIGHT, MANUAL ADJUSTER	INC
PASSENGER SEAT		
A59	TWO-PERSON, WITHOUT STORAGE	\$200.00
AIRBAGS		
AL3	SUPPLEMENTAL INFLATABLE RESTRAINTS NOT INCLUDED	INC
RADIO		
UM7	DELCO AM-FM STEREO RADIO	\$165.00
EXTERIOR MIRRORS		
DB5	MANUAL, 102" (259 CM) WIDE LOAD, INTEGRAL ARM, INTEGRAL CONVEX MIRROR	INC
PAINT		
ZY1	SOLID NON-METALLIC PAINT	INC
INTERIOR TRIM		
69I	VERY DARK PEWTER	INC
SEAT TRIM		
_V	VINYL SEAT TRIM	INC

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.2, Data updated 12/25/2007 10:41:00 AM
 ©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 28, 2007 12:15:14 AM

Page 4

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclix@hotmail.com

2008 Fleet/Non-Retail GMC TC6500

SELECTED MODEL & OPTIONS

SELECTED OPTIONS - 2008 Fleet/Non-Retail TC6C042 Regular Cab

CATEGORY

<u>Code</u>	<u>Description</u>	<u>MSRP</u>
	OPTIONS TOTAL	\$20,035.00

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.2, Data updated 12/25/2007 10:41:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 28, 2007 12:15:14 AM

Page 5

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclixx@hotmail.com

2008 Fleet/Non-Retail GMC TC6500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC6C042 Regular Cab

EXTERIOR

- Paint, solid, upper color, Summit White
- Paint, solid, lower color, Summit White
- Exterior roof drip moldings
- Bumpers, front steel, painted argent - Bumper thickness 3.9 mm
- Steps under cab doors
- Front mud flaps
- Integral grille and fenders - The grille is the same color as hood with single halogen headlamps. Entry steps under cab doors are based upon fuel tank type
- Roof marker lamps
- Daytime running lamps
- Windows, Solar-Ray tinted. Light tinted windshield and side window glass with light transmissivity of 70%
- Mirrors, manual, 102" (259 cm) wide load, integral arm, integral convex mirror - black molded composite 12" x 7" (30.5cm x 17.8 cm) with 6" x 7" (15.2cm x 17.8cm) convex section
- Windshield wipers, 2-speed and intermittent, with pulse washers
- Provisions for mounting front license plate
- Positive door stops
- Horn, single electric mounted inside engine compartment

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.2, Data updated 12/25/2007 10:41:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 28, 2007 12:15:14 AM

Page 6

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclix@hotmail.com

2008 Fleet/Non-Retail GMC TC6500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC6C042 Regular Cab

INTERIOR

- Seat, driver, High-back bucket, Fixed height, manual adjuster - storage in the seat riser with a small lip at the front to help prevent contents from sliding out
- Seat, passenger, High-back bucket, Fixed height, manual back angle adjuster - storage in the seat riser with a small lip at the front to stop contents from sliding out
- Seat trim, vinyl, Very Dark Pewter
- Interior trim, Very Dark Pewter (Requires 69V Very Dark Pewter Vinyl or 69C Very Dark Pewter Cloth)
- Center console - located next to driver's seat and two cupholders
- Molded vinyl floor covering
- Steering wheel 16"
- Two sided single common key for doors and ignition
- Headlamp warning buzzer
- Warning tone, key-in-ignition
- Tachometer
- Electronic engine hour meter
- Engine "Check gauges" telltale light and buzzer, oil pressure gauge
- Gauges, low oil pressure and coolant level, high coolant and engine oil temperature
- Vinyl door trim panels - with storage pockets, beverage holders, and reflectors
- Stepwell storage areas at each door. Includes storage cover
- Cloth headliner
- Sunshades, passenger side and driver side, vinyl-covered
- Coat hooks (2) located on cab back panel
- Provisions for stereo - Includes AM/FM antenna, lead wiring for speakers, and separate door chime module (N/A with ZQ2 driver convenience package)
- Air conditioning not desired - this option should be ordered only when a customer does not require air conditioning
- Powerpoints - two in-cab power sources (in addition to optional cigarette lighter) for electrical plug-in accessories

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.2, Data updated 12/25/2007 10:41:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.
Customer File:

December 28, 2007 12:15:14 AM

Page 7

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclix@hotmail.com

2008 Fleet/Non-Retail GMC TC6500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC6C042 Regular Cab

- Underhood bodybuilder connections accessory power supply - Provides 12V power supply from the battery with two separate 30 amp fused circuits

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.2, Data updated 12/25/2007 10:41:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 28, 2007 12:15:14 AM

Page 8

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclixx@hotmail.com

2008 Fleet/Non-Retail GMC TC6500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC6C042 Regular Cab

MECHANICAL

- Truck application NOTE: Trucks that are used primarily to tow a trailer may be liable to Federal Excise Tax (FET) - check with IRS for guidelines
- Engine, Vortec 8.1L MD gasoline V8, 295 hp (220 kw) @ 3600 rpm and 440 lb-ft (594 N-m) torque @ 3,200 rpm - Oil Level Sensor: Warning sensor for low oil levels
- Air cleaner, dry-type standard filter element (Requires gasoline engine)
- Underhood air cleaner restriction gauge
- Road Speed Governor, controlled by the speed rating of the tires ordered. All vehicles with 19.5" tire sizes and with most 22.5" tires have speed governed to a maximum of 75 mph (120 kph). A few aggressive tire tread patterns may have lower maximum speed ratings that limit governed speed to 65 or 55 mph - see tire company's specifications for details.
- Alternator, AD244, Delco-Remy 150-amp maximum (Requires gasoline engine)
- Battery, single AC Delco, 600 CCA, 12V. - 115-minute reserve capacity @ 27 degrees C, 600 CCA @ -18 degrees C, (Requires gasoline engine)
- Exhaust system, single horizontal - driver side mounted inside frame rail, with gasoline engine stainless-steel exhaust with catalytic converter, with diesel engines 409 stainless-steel exhaust system, integrated oxidation catalyst on Isuzu engine, Diesel Particulate Filter (DPF) and exhaust gas cooler (N/A with FQT wheelbase with Isuzu diesel engines and not available with EG9 wheelbase with Caterpillar engine)
- Option PTO not required - This option should only be ordered when a customer specifically does not require an electric hand throttle for use with power-take-off provisions. NOTE: Deletes transmission PTO gear with Allison MTX/MBZ 2200HS, MTY 2300HS, MHE 2350HS, MPS 2500HS, and MPQ 2550HS Series transmissions.
- Transmission, automatic, Allison 2300 HS/RDS Series (Close Ratio) 5-speed - No parking pawl. Includes 4th Generation Electronic Controls and 0.71 overdrive. Torque rating: 450 lb-ft (610 N-m), Available with a Gross Vehicle Weight up to 33,000 lbs. (15,000 kg) and a Gross Combined Weight up to 33,000 lbs. (15,000 kg). When "PTX" is selected, it does not include power take-off gear in the Allison 2300 HS Highway Series transmission. To include PTO gear please order with RPO "PTO" for Allison 2300 RDS Rugged Duty Series transmission. Includes transmission oil cooler in radiator, increased cooling and column shift. (Requires gasoline engine, HD1 or HPK single speed rear axles)
- Transynd synthetic automatic transmission fluid (Available with automatic transmissions only)
- Front axle, 8000 lbs. (3629 kg) capacity - Up to 53 degree turn angle. Steering Gear Series: ZF8014
- Front suspension, tapered leaf, 8000 lbs. (3629 kg) capacity (Requires FM8 front axle)

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.2, Data updated 12/25/2007 10:41:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 28, 2007 12:15:14 AM

Page 9

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclbxx@hotmail.com

2008 Fleet/Non-Retail GMC TC6500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC6C042 Regular Cab

- Front shock absorber, diameter 1.375" (35mm)
- Front wheels, 22.5" x 7.5" (58.9 cm x 19 cm), steel disc - Accuride 10-hole, flange nut, hub piloted, 11.25" (28.5 cm) bolt circle, painted Gray (E-Coat), 13,220 lbs. (5996 kg) capacity, (Requires QH4 rear wheels)
- Front tire size, 245/75R22.5G - 9350 lbs. (4241 kg) capacity, (With R4A Goodyear requires R3C front premium tread; N/A with Michelin)
- Front tire manufacturer code, Goodyear (Requires S4A Goodyear)
- Front tire tread, premium highway
- Rear axle, single-speed, Dana S130-S, 15,000 lbs. (6804 kg) capacity - 40,000 lbs. (18,144 kg) GCWR
- Rear wheel drive
- Rear axle ratio, 6.50:1 (Requires HD1 or HPK single speed rear axle)
- Rear suspension, multi-leaf, 15,000 lbs. (6804 kg) capacity (Requires HD1 single speed rear axle)
- Rear wheels, 22.5" x 7.5" (58.9 cm x 19 cm), steel disc - Accuride 10-hole, flange nut, hub piloted, 11.25" (28.5 cm) bolt circle, painted Gray (E-Coat) 26,440 lbs. (11,993 kg) capacity, (Requires HPK or HD1 single speed rear axle or HPM two-speed rear axle and 22.5" tires)
- Rear tire size, 245/75R22.5G - 17,640 lbs. (8001 kg) capacity (With S4A Goodyear requires S3C rear premium tread or S3H rear highway traction tread; N/A with Michelin)
- Rear tire manufacturer code, Goodyear (Requires R4A Goodyear)
- Rear tire tread, premium highway
- Wheelbase, 128" (325.1 cm) - with 60" (152.4 cm) CA and 135.3" (343.7 cm) CE. Includes a 6 mm 50,000 psi (344,750 kPa) yield strength, steel frame, RBM: 479,000 Section Modulus 9.58 cu. in. (N/A with diesel engine)
- Frame, painted semi-gloss black 6mm rail - 50,000 psi (344,750 kPa) yield strength, steel frame, SAE J1392-050XLK steel, dimensions 9 1/2" x 3" x 1/4" section modulus 9.58 cu. in., RBM 479,000
- Fuel tank, single, 50-gallon (189.2L) fuel capacity - driver side, steel top tread plate, sump, drain and steps under cab on front passenger side. Provides clean back of cab and a black tethered fuel cap with gasoline engines, and a brass tethered fuel cap with diesel engines (Requires QH4, RPR or RNN 22.5" wheels; N/A with GPG Lo-Pro option)
- Steering, power - ZF variable ratio power

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.2, Data updated 12/25/2007 10:41:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.
Customer File:

December 28, 2007 12:15:14 AM

Page 10

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclix@hotmail.com

2008 Fleet/Non-Retail GMC TC6500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC6C042 Regular Cab

- Brake system, hydraulic, split - with 4-channel ABS disc-type Bosch Hydro Max high performance booster, tandem master cylinder provides independent front and rear circuits, front and rear disc Meritor calipers: 15 3/8" (391 mm) rotor diameter, 1 1/2" (39.1 mm) rotor thickness with (4) 2 1/2" (64 mm) diameter pistons with 8,000 lb. (3629 kg) front axle, (70 mm) diameter pistons with 10,000 lb. (4536 kg) front axle
- Parking brake, hand lever operated transmission mounted drum brake

SAFETY

- Brake system, hydraulic, split - with 4-channel ABS
- Air bags, Supplemental Inflatable Restraints not included
- Seat belt warning indicator
- Daytime running lamps

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.2, Data updated 12/25/2007 10:41:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 28, 2007 12:15:14 AM

Page 11



APPENDIX B

TRUCK QUESTIONNAIRE FORMS

ALL BIDDERS MUST COMPLETE AND RETURN A QUESTIONNAIRE FORM WITH THE BID FOR EACH TRUCK ITEM TO BE CONSIDERED FOR AWARD OF THAT ITEM. Bids submitted without an adequately completed questionnaire form for EACH TRUCK ITEM will not be considered for award of that item. It is the responsibility of each bidder to copy this form in sufficient quantity to submit to Purchasing Operations prior to the scheduled bid due date. A single form may apply to more than one item, simply list the item numbers to which the questionnaire applies in the appropriate space. If part of the questionnaire does not apply, simply indicate "not applicable" in those spaces.

NAME OF BIDDER: Red Holman Pontiac Gmc ITEM NO(s): Spec # 3958-0135

MAKE OF TRUCK: Gmc MODEL: Topkick C6500TC66042GVWR 25950 lbs.

PAYLOAD: 16,893 W.B. 152" C.A. 84" C.E. 135.30"

ENGINE: (GAS - DIESEL) Diesel MAKE: Gm/Isuzu/Duramax MODEL: LYA, 7.8 SAE H.P. 215

FUEL TANK(S) CAPACITY: 100 (GALS. TOTAL) TRANSMISSION: Allison 2200 6-spd

SPRING CAP. @ GROUND EACH: FRONT 4000 lbs. REAR 9500 lbs. AUX. N/A lbs.

AXLES: FRONT 8000 lbs. REAR 19000 lbs. REAR RATIO 6.50

ALTERNATOR: 100 amps. BATTERY Dual 750 1,500 cca. Permanone

TIRE SIZE: FRONT 10R22.5 F PR REAR 10R22.5 F PR SINGLE _____ DUAL M&S Rear

TIRE: MAKE Goodyear STYLE NO. 7BD MFG. CODE XWJ/YWJ

HOIST: MAKE N/A MODEL N/A INSTALLING CO. N/A

BODY: MAKE N/A MODEL N/A INSTALLING CO. N/A

POWER LIFT GATE: MAKE N/A MODEL N/A CAPACITY N/A lbs.

PLATFORM SIZE: N/A

OTHER EQUIPMENT INSTALLED BY BODY EQUIPMENT SUPPLIER AND/OR COMMENTS

This information must be returned with the bid document to Purchasing Operations, on or before the bid due date and time. However, if returned separately, it must be received by Purchasing Operations on or before the bid due date and time, and must comply with the sealed bid instructions as outlined in the ITB.

TRUCK: CAB AND CHASSIS (G.V.W.R. 23,500 lbs., min.)*

MODEL-2008 CURRENT NEW

	<u>FORD</u> <u>F650</u>	<u>INTL</u> <u>4300 M7</u>	<u>CHEVY/GMC</u> <u>C7C042</u>
Wheelbase (inches)	158	152	152
C.A. (inches)	84	85	84
Engine: Diesel, Type	Cummins ISB	MaxxForce 7	Duramax
Size	6.7L	6.0L	7.8L
No. of Cylinders	I-6	V-8	6
Gross H.P., 170 min.	200	200	215
Torque	520	520	560
Transmission: 5-speed			Allison 2200RDS 6 spd w/park pawl
Allison w/ PTO Auto. 2000/2400			
Axle, Min. Cap.-lbs.			
Front, 7,000 minimum	8,500	8,000	8,000
Rear, 17,500 minimum	17,500	17,500	19,000
Ratio for minimum loaded road speed of approx. 68 mph.			
Springs, Min. Cap. at Ground			
Front-lbs. each	4,250**	4,000**	4,000**
Rear-lbs. each	8,750**	9,250**	9,500**
Aux.-lbs. each	2,250	2,250	no rating
**includes shock absorbers			

*SEE Mich. 3958-0137 or 3958-0141 for body.

Tires, Truck, Tubeless, Radial, 9R22.5F (12PR) Minimum. Front to be Highway Tread, Rear duals-Traction Drive Tread, Goodyear Unisteel G-164 RTD or approved equal. Same Mfg. - Front and Rear.

TO BE STANDARD FACTORY EQUIPPED AS FOLLOWS:

The items listed below are to be supplied on all trucks, even though they may be optional with the manufacturer. Therefore, these specifications are to be furnished on all vehicles:

- ☑ 12 Volt auxiliary outlet
- ☑ Air Conditioning - All trucks
- ☑ Anti-freeze protection, to -30°F.
- ☑ Arm Rest-Driver's side.
- ☑ Color-Manufacturers Standard to be selected.
- ☑ Coolant System-Maximum Size Available, including the Heaviest Duty Radiator
- ☑ Dome Light.
- ☑ Electric wiring-All wiring passing through holes in metal or non-metal wearing surfaces, which could cause wear of the insulation, shall be adequately protected by rubber or plastic grommets, and/or non-metallic conduit. Ends of all wires shall be adequately anchored to prevent loosening.
- ☑ Frame length-on all body installations without hoists the cab to end of frame length shall be the same length as the body being mounted, plus the length of any setback.
- ☑ Fuel Tanks, Diesel, with sending unit and magnetic drain plug, on all trucks over 21,000 G.V.W.R., painted Black and labeled "Diesel Fuel Only".
- ☑ Hub caps on all pickups and vans up to and including 10,000 G.V.W.R. If not available from dealer cap nuts shall be furnished.
- ☑ Keys-(2) sets with code numbers; shall be with vehicle at time of delivery.
- ☑ Mirrors-All trucks are to be equipped with R.H. and L.H. outside rear-view mirrors to comply with Michigan laws; all trucks up to and including 15,000 G.V.W.R. shall be equipped with inside rear-view mirror. In all cases, outside R.H. & L.H. rear view mirrors shall provide full vision past all body installations. Mirrors shall be of stainless steel or high impact plastic construction unless denoted otherwise in individual truck specifications. All West Coast Type or Below Eye Level Camper Style Mirrors shall have stainless steel or high impact plastic heads, brackets, and hardware.
- ☑ Mud flaps, Anti-Sail Type, when required, are to be plain, rubber 1/4" thick, without advertising on either side.
- ☑ Painting-preclean and metal prep, any bare metal surfaces prior to applying a compatible red oxide or zinc chromate primer. When painting over a manufacturer's standard paint, metal prepping and primer may be omitted, provided an acceptable bond can be achieved.
- ☑ Equipment mounting- when mounting equipment on truck cab and chassis, all holes shall be drilled or punched. There shall be no flame cutting or welding on the frame side rails.
- ☑ Paint codes-factory paint codes shall be furnished with all vehicles; for all after market painting both the brand and paint code shall be furnished.
- ☑ Pre-delivery inspection and servicing.
- ☑ Radio - AM/FM Manufacturers Standard, Factory Installed
- ☑ Seat Belts with Shoulder Harness (3-Point Restraint System for Driver & Passenger)
- ☑ Seats-Split Bench type, unless otherwise specified
- ☑ Shock absorbers-(Heaviest Duty Available), front all trucks. Rear, up to and including 15,000 G.V.W.R.
- ☑ Spare tire, or Rim, not to be furnished unless specified. If specified, tires to be of same mfg., tread design to be same as front tires.
- ☑ Speed Control, Factory Installed
- ☑ Steering-Power, Tilt Wheel

- ☑ Sun visors-dual.
- ☑ Jack-Furnish on trucks up to and including 12,000 G.V.W.R.
- ☑ Windshield wipers-dual, intermittent speed electric, with automatic type washers.

All items removed for installation of optional equipment shall be returned to the State of Michigan.

TO BE EQUIPPED IN COMPLIANCE WITH ALL APPLICABLE FEDERAL MOTOR VEHICLE SAFETY STANDARDS AND REGULATIONS. ALL VEHICLES MUST BE EQUIPPED TO COMPLY WITH ALL REQUIREMENTS OF THE MICHIGAN MOTOR VEHICLE CODE.

- **Delete: On GM vehicles, OnStar and XM radio are deleted.**

ADDITIONAL OPTIONS:

These options are in addition to the options listed above as “STANDARD FACTORY EQUIPPED” and are to be included on this vehicle.

- ☑ Alternator-100 amp. min., Reference 22SI or approved equal
- ☑ Battery(s)-12 Volt; 1,100 CCA minimum.
- ☑ Brakes-Full air. Current FMVSS. Dust plates. Air dryer with spin on filter, Automatic Drain Valves. Automatic slack adjusters.
- ☑ Cab assist handles-right and left.
- ☑ Fuel/Water Separator with Heater.
- ☑ Fuel Tanks-45 gallon each L.H. and R.H. Step tanks.
- ☑ Heater-engine block, 110/120 VAC
- ☑ Hood, Tilt.
- ☑ Mirrors, Rear View-Outside. L.H. & R.H. West Coast Type. 6" x 16", installed, with stainless steel or powder coated steel heads, brackets, and hardware. GMC: Composite Mirror Heads
- ☑ Shock absorbers-Front and Rear, double acting, telescopic.
- ☑ Starting Aid-Cold weather, ether type or glow plug. GMC: Intake heater
- ☑ Steering-Power.
- ☑ Switches (6), outfitter, with remote power module (MDOT) GMC: Panel only, switches not available unless supplied by upfitter
- ☑ Tachometer.
- ☑ Throttle, Electronic, High Idle Engine RPM Control.
- ☑ Wheels-Hub Piloted disc.

PRICING SHEET

<u>TRUCK: CAB AND CHASSIS (G.V.W.R. 23,500 lbs., min.)*</u>	
Mich. Spec. #3958-0136	
Standard Equipped Per above Specification (Including options as specified above)	Standard Equipped Cost
Make: GMC Model: Topkick C7500 F.O.B. - Dealership Delivery Cost Per Mile \$1.80	\$47,194.00*
Final Point of Assembly: Flint, MI	
<u>Dealer Information</u>	
Dealer Name: Red Holman Pontiac GMC	
Street Address: 35300 Ford Road	
City: Westland	State: MI
	Zip: 48185
Contact Name: Albert Li	
Telephone: (800) 482-3032	
Cell: (734) 637-6643	
E-mail: aclixx@hotmail.com	

*Please Note: A vehicle order confirmation sheet is included for each vehicle. These documents shall include all the "standard options" as listed for the State of Michigan standard specification.

Vehicle Order Confirmation Sheet
 Spec # 3958-0136

Prepared By:
 Albert Li
 Red Holman Pontiac GMC
 35300 Ford Rd
 Westland, MI 48185
 Phone: (734) 721-1144
 Fax: (734) 721-1780
 Email: aclbx@hotmail.com

2008 Fleet/Non-Retail GMC TC7500

SELECTED MODEL & OPTIONS

SELECTED MODEL - 2008 Fleet/Non-Retail TC7C042 Regular Cab

<u>Code</u>	<u>Description</u>	<u>MSRP</u>
TC7C042	2008 GMC TC7500 Regular Cab	\$45,975.00

SELECTED VEHICLE COLORS - 2008 Fleet/Non-Retail TC7C042 Regular Cab

<u>Code</u>	<u>Description</u>
-	Interior: No color has been selected.
-	Exterior 1: No color has been selected.
-	Exterior 2: No color has been selected.

SELECTED OPTIONS - 2008 Fleet/Non-Retail TC7C042 Regular Cab

CATEGORY

<u>Code</u>	<u>Description</u>	<u>MSRP</u>
PREFERRED EQUIPMENT GROUP		
C7C042	CUSTOM/BASE MODEL	\$0.00
VEHICLE APPLICATION		
RQ2	TRUCK APPLICATION	INC
GVWR		
	NO 25,950# GVWR RATING DESIRED	\$0.00
EMISSION		
FE9	FEDERAL REQUIREMENTS	INC
DIESEL ENGINE		
LYA	ISUZU DIESEL 6H 7.8L I6, 215 HP (160 KW) @ 2200 RPM AND 560 LB-FT TORQUE (759 N-M) @ 1450 RPM	\$16,466.00
AIR CLEANER		
KNB	DRY-TYPE STANDARD FILTER ELEMENT	\$0.00
FUEL/WATER SEPARATOR		
NWB	RACOR FRAME-MOUNTED SPIN-ON TYPE	INC

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.2, Data updated 12/25/2007 10:41:00 AM
 ©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 28, 2007 11:58:28 AM

Page 1

Prepared By:
 Albert Li
 Red Holman Pontiac GMC
 35300 Ford Rd
 Westland, MI 48185
 Phone: (734) 721-1144
 Fax: (734) 721-1780
 Email: aclbx@hotmail.com

2008 Fleet/Non-Retail GMC TC7500

SELECTED MODEL & OPTIONS

SELECTED OPTIONS - 2008 Fleet/Non-Retail TC7C042 Regular Cab

<u>CATEGORY</u>		<u>MSRP</u>
<u>Code</u>	<u>Description</u>	
ENGINE BLOCK HEATER		
KB3	1250-WATT, 110V	\$50.00
ALTERNATOR		
K60	22SI, DELCO 100-AMP MAXIMUM	\$0.00
BATTERY		
TNL	DUAL AC DELCO, 750 CCA, 12V	\$0.00
ALARM		
KPJ	AUTOMATIC ENGINE SHUTDOWN WITH ALARM	INC
EXHAUST SYSTEM		
NB5	SINGLE HORIZONTAL-DRIVER SIDE MOUNTED INSIDE FRAME RAIL	\$0.00
POWER TAKE OFF		
PTO	ELECTRONIC ACTIVATION SWITCH, (ELECTRIC HAND THROTTLE), IP MOUNTED	\$250.00
AUTOMATIC TRANSMISSION		
MBZ	ALLISON 2200 HS/RDS SERIES 6-SPEED	\$555.00
TRANSMISSION FLUID		
MBT	TRANSYND SYNTHETIC AUTOMATIC TRANSMISSION FLUID	INC
FRONT AXLE		
FM8	8000 LBS. (3629 KG) CAPACITY	-\$459.00
FRONT SUSPENSION		
FSN	TAPERED LEAF, 8000 LBS. (3629 KG) CAPACITY	-\$51.00
FRONT WHEEL		
QH3	22.5" X 7.5" (58.9 CM X 19 CM), STEEL DISC	\$0.00
FRONT TIRE		
XUE	9R22.5F-9080 LBS. (4118 KG) CAPACITY	\$69.00
FRONT TIRE BRAND		
R4A	GOODYEAR	\$0.00
FRONT TIRE TREAD		

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.2, Data updated 12/25/2007 10:41:00 AM
 ©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 28, 2007 11:58:28 AM

Page 2

Prepared By:
 Albert Li
 Red Holman Pontiac GMC
 35300 Ford Rd
 Westland, MI 48185
 Phone: (734) 721-1144
 Fax: (734) 721-1780
 Email: aclixx@hotmail.com

2008 Fleet/Non-Retail GMC TC7500

SELECTED MODEL & OPTIONS

SELECTED OPTIONS - 2008 Fleet/Non-Retail TC7C042 Regular Cab

CATEGORY

<u>Code</u>	<u>Description</u>	<u>MSRP</u>
FRONT TIRE TREAD		
R3C	PREMIUM, HIGHWAY	\$0.00
SINGLE SPEED REAR AXLE		
HPK	DANA 19060S, 19,000 LBS. (8618 KG) CAPACITY	INC
AXLE RATIO		
022	7.17:1	INC
REAR SUSPENSION		
GN0	MULTI-LEAF, 19,000 LBS. (8618 KG) CAPACITY	\$0.00
REAR SHOCK ABSORBER		
G68	REAR SHOCK ABSORBERS	\$58.00
REAR WHEEL		
QH4	22.5" X 7.5" (58.9 CM X 19 CM), STEEL DISC	\$0.00
REAR TIRE		
YUE	9R22.5F-17,200 LBS. (7802 KG) CAPACITY	\$160.00
REAR TIRE BRAND		
S4A	GOODYEAR	\$0.00
REAR TIRE TREAD		
S3H	HIGHWAY TRACTION	\$0.00
WHEELBASE		
EG9	152" (386.1 CM)	\$0.00
FRAME RAIL		
FD0	PAINTED SEMI-GLOSS BLACK 6MM RAIL-50,000 PSI (344,750 KPA) YIELD STRENGTH,	INC
FUEL TANK		
NNQ	DUAL, 100-GALLON (380L) TOTAL FUEL CAPACITY,	\$370.00
BRAKE SYSTEM		
JE4	AIR, ABS-4-CHANNEL BENDIX BRAKE SYSTEM 'S' CAM TYPE MERITOR,	\$1,778.00
BRAKE EQUIPMENT		

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.2, Data updated 12/25/2007 10:41:00 AM
 ©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 28, 2007 11:58:28 AM

Page 3

Prepared By:
 Albert Li
 Red Holman Pontiac GMC
 35300 Ford Rd
 Westland, MI 48185
 Phone: (734) 721-1144
 Fax: (734) 721-1780
 Email: aclixx@hotmail.com

2008 Fleet/Non-Retail GMC TC7500

SELECTED MODEL & OPTIONS

SELECTED OPTIONS - 2008 Fleet/Non-Retail TC7C042 Regular Cab

<u>CATEGORY</u>		<u>MSRP</u>
<u>Code</u>	<u>Description</u>	
BRAKE EQUIPMENT		
JRF	REAR DUST SHIELDS	\$0.00
AIR COMPRESSOR		
KK3	HALDEX 292 WATER-COOLED 12.9 CFM	INC
DRIVER CONVENIENCE PACKAGES		
ZQ3	DRIVER CONVENIENCE PACKAGE	\$172.00
MISCELLANEOUS CAB EQUIPMENT		
N33	TILT-WHEEL ADJUSTABLE STEERING	INC
K34	CRUISE CONTROL,	INC
AIR CONDITIONING		
C60	AIR CONDITIONING	\$939.00
INSIDE REARVIEW MIRRORS		
D36	INSIDE DAY/NIGHT REARVIEW MIRROR	\$21.00
DRIVER SEAT		
AS4	HIGH-BACK BUCKET, FIXED HEIGHT, MANUAL ADJUSTER	INC
PASSENGER SEAT		
A59	TWO-PERSON, WITHOUT STORAGE	\$200.00
AIRBAGS		
AL3	SUPPLEMENTAL INFLATABLE RESTRAINTS NOT INCLUDED	INC
RADIO		
UM7	DELCO AM-FM STEREO RADIO	\$165.00
EXTERIOR MIRRORS		
DB5	MANUAL, 102" (259 CM) WIDE LOAD, INTEGRAL ARM, INTEGRAL CONVEX MIRROR	INC
PAINT		
ZY1	SOLID NON-METALLIC PAINT	INC
INTERIOR TRIM		
69I	VERY DARK PEWTER	INC

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.2, Data updated 12/25/2007 10:41:00 AM
 ©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 28, 2007 11:58:28 AM

Page 4

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclix@hotmail.com

2008 Fleet/Non-Retail GMC TC7500

SELECTED MODEL & OPTIONS

SELECTED OPTIONS - 2008 Fleet/Non-Retail TC7C042 Regular Cab

CATEGORY

<u>Code</u>	<u>Description</u>	<u>MSRP</u>
SEAT TRIM		
<u> </u> V	VINYL SEAT TRIM	INC
OPTIONS TOTAL		\$20,743.00

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.2, Data updated 12/25/2007 10:41:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 28, 2007 11:58:28 AM

Page 5

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclixx@hotmail.com

2008 Fleet/Non-Retail GMC TC7500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC7C042 Regular Cab

EXTERIOR

- Paint, solid, upper color, Summit White
- Paint, solid, lower color, Summit White
- Exterior roof drip moldings
- Bumpers, front steel, painted argent - Bumper thickness 3.9 mm
- Steps under cab doors
- Front mud flaps
- Integral grille and fenders - The grille is the same color as hood with single halogen headlamps. Entry steps under cab doors are based upon fuel tank type
- Roof marker lamps
- Daytime running lamps
- Windows, Solar-Ray tinted. Light tinted windshield and side window glass with light transmissivity of 70%
- Mirrors, manual, 102" (259 cm) wide load, integral arm, integral convex mirror - black molded composite 12" x 7" (30.5cm x 17.8 cm) with 6" x 7" (15.2cm x 17.8cm) convex section
- Windshield wipers, 2-speed and intermittent, with pulse washers
- Provisions for mounting front license plate
- Positive door stops
- Horn, single electric mounted inside engine compartment

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.2, Data updated 12/25/2007 10:41:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 28, 2007 11:58:28 AM

Page 6

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclix@hotmail.com

2008 Fleet/Non-Retail GMC TC7500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC7C042 Regular Cab

INTERIOR

- Seat, driver, high-back bucket, Fixed height, manual adjuster - storage in the seat riser with a small lip at the front to help prevent contents from sliding out.
- Seat, passenger, high-back bucket, Fixed height, manual back angle adjuster - storage in the seat riser with a small lip at the front to stop contents from sliding out
- Seat trim, vinyl, Very Dark Pewter
- Interior trim, Very Dark Pewter (Requires 69V Very Dark Pewter Vinyl or 69C Very Dark Pewter Cloth)
- Center console - located next to driver's seat and two cupholders
- Molded vinyl floor covering
- Steering wheel 16"
- Two sided single common key for doors and ignition
- Headlamp warning buzzer
- Warning tone, key-in-ignition
- Tachometer
- Electronic engine hour meter
- Engine "Check gauges" telltale light and buzzer, oil pressure gauge
- Gauges, low oil pressure and coolant level, high coolant and engine oil temperature
- Vinyl door trim panels - with storage pockets, beverage holders, and reflectors
- Stepwell storage areas at each door. Includes storage cover
- Cloth headliner
- Sunshades, passenger side and driver side, vinyl-covered
- Coat hooks (2) located on cab back panel
- Provisions for stereo - Includes AM/FM antenna, lead wiring for speakers, and separate door chime module (N/A with ZQ2 power convenience option)
- Air conditioning not desired - this option should be ordered only when a customer does not require air conditioning
- Powerpoints - two in-cab power sources (in addition to optional cigarette lighter) for electrical plug-in accessories

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.2, Data updated 12/25/2007 10:41:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.
Customer File:

December 28, 2007 11:58:28 AM

Page 7

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclbx@hotmail.com

2008 Fleet/Non-Retail GMC TC7500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC7C042 Regular Cab

- Underhood bodybuilder connections accessory power supply - Provides 12V power supply from the battery with two separate 30 amp fused circuits

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.2, Data updated 12/25/2007 10:41:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 28, 2007 11:58:28 AM

Page 8

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: acliix@hotmail.com

2008 Fleet/Non-Retail GMC TC7500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC7C042 Regular Cab

MECHANICAL

- Truck application NOTE: Federal Excise Tax (FET) of 12% must be paid on the final selling price for trucks with GVWR's of 33,001 lbs. and above. Trucks that are used primarily to tow a trailer may be liable to Federal Excise Tax (FET) - check with IRS for guidelines. PLEASE NOTE: The 12% FET tax is NOT included in AutoBook Pricing.
- Engine, Vortec 8.1L MD gasoline V8, 295 hp (220 kw) @ 3600 rpm, 440 lb-ft (594 N-m) torque @ 3,200 rpm. - Oil Level Sensor: Warning sensor for low oil levels
- Air cleaner, dry-type standard filter element (Requires gasoline engine)
- Underhood air cleaner restriction gauge
- Road Speed Governor, controlled by the speed rating of the tires ordered. All vehicles with 19.5" tire sizes and with most 22.5" and 24.5" tires have speed governed to a maximum of 75 mph (120 kph). A few aggressive tire tread patterns may have lower maximum speed ratings that limit governed speed to 65 or 55 mph - see tire company specifications for details.
- Alternator, AD244, Delco-Remy 150-amp maximum (Requires gasoline engine)
- Battery, single AC Delco, 600 CCA, 12V - 115-minute reserve capacity @ 27 degrees C, 600 CCA @ -18 degrees C, (Requires gasoline engine)
- Exhaust system, single horizontal - driver side mounted inside frame rail, with gasoline engine stainless-steel exhaust with catalytic converter. With diesel engines 409 stainless-steel exhaust system, integrated oxidation catalyst on Isuzu diesel, Diesel Particulate Filter (DPF) and exhaust gas cooler. (N/A with FQT wheelbase with Isuzu diesel engines and not available with EG9 wheelbase with Caterpillar engine)
- Option PTO not required - This option should only be ordered when a customer specifically does not require an electric hand throttle for use with power-take-off provisions. NOTE: Deletes transmission PTO gear with Allison MTX/MBZ 2200HS, MTY 2300HS, MHE 2350HS, MPS 2500HS, and MPQ 2550HS Series transmissions.
- Transmission, automatic, Allison 2300 HS/RDS (Close Ratio) 5-speed - No parking pawl. Includes 4th Generation Electronic Controls and 0.71 overdrive. Torque rating: 450 lb-ft (610 N-m), Available with a Gross Vehicle Weight up to 33,000 lbs. (15,000 kg) and a Gross Combined Weight up to 33,000 lbs. (15,000 kg). When "PTX" is selected, it does not include power take-off gear in the Allison 2300 HS Highway Series transmission. To include PTO gear please order with RPO "PTO" for Allison 2300 RDS Rugged Duty Series transmission. Includes transmission oil cooler in radiator, increased cooling and column shift. (Requires gasoline engine and HPK, HPL, HPM, HPN, HPP or H15 rear axles)
- TranSynd synthetic automatic transmission fluid (Available with automatic transmissions only)
- Front axle, 10,000 lbs. (4536 kg) capacity - Up to 53 degree turn angle. Steering Gear Series: ZF8016

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.2, Data updated 12/25/2007 10:41:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.
Customer File:

December 28, 2007 11:58:28 AM

Page 9

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclbx@hotmail.com

2008 Fleet/Non-Retail GMC TC7500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC7C042 Regular Cab

- Front suspension, tapered leaf, 10,000 lbs. (4536 kg) capacity (Requires FM8 and FM6 front axle)
- Front shock absorber, diameter 1.375" (35mm)
- Front wheels, 22.5" x 7.5" (58.9 cm x 19 cm), steel disc - Accuride 10-hole, flange nut, hub piloted, 11.25" (28.5 cm) bolt circle, painted Gray (E- Coat), 13,220 lbs. (5996 kg) capacity, (Requires QH4 rear wheels; N/A with FL3 front axle)
- Front tire size, 245/75R22.5G - 9350 lbs. (4241 kg) capacity, (With R4A Goodyear requires R3C front premium tread; N/A with Michelin)
- Front tire manufacturer code, Goodyear (Requires S4A Goodyear)
- Front tire tread, premium highway
- Rear axle, single-speed, Dana 19060S, 19,000 lbs. (8618 kg) capacity - includes 75W-90 synthetic lubricant and National brand oil seals (Requires GN0, GN2, GN8, GR9, GP1, GP0 or G40 rear suspension) (N/A with FL3 front axle)
- Rear wheel drive
- Rear axle ratio, 7.17:1 (Requires HPK, HPL, HPN, HPP or HPT single speed rear axle or HPM, H15 two-speed rear axle)
- Rear suspension, multi-leaf, 19,000 lbs. (8618 kg) capacity (Requires HPK or HPL single rear axle or HPM two-speed rear axle)
- Rear wheels, 22.5" x 7.5" (58.9 cm x 19 cm), steel disc - Accuride 10-hole, flange nut, hub piloted, 11.25" (28.5 cm) bolt circle, painted Gray (E-Coat) 26,440 lbs. (11,993 kg) capacity, (Requires HPK, HPL, HPN, HPP or HPT single speed rear axle, or HPM, H15 or H25 two-speed rear axle) (Not available with YWM, YWP or YRN 22.5" rear tires)
- Rear tire size, 245/75R22.5G - 17,200 lbs. (7802 kg) capacity (With S4A Goodyear requires S3C rear premium tread or S3H rear highway traction tread; N/A with Michelin)
- Rear tire manufacturer code, Goodyear (Requires R4A Goodyear)
- Rear tire tread, premium highway
- Wheelbase, 140" (355.6 cm) - with 72" (182.9 cm) CA and 135.3" (343.7 cm) CE, (With diesel engine requires NPY exhaust)
- Frame, painted semi-gloss black 6mm rail - 50,000 psi (344,750 kPa) yield strength, steel frame, SAE J1392-050XLK steel, dimensions 9 1/2" x 3" x 1/4" section modulus 9.58 cu. in., RBM 479,000

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.2, Data updated 12/25/2007 10:41:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 28, 2007 11:58:28 AM

Page 10

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclix@hotmail.com

2008 Fleet/Non-Retail GMC TC7500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC7C042 Regular Cab

- Fuel tank, single, 50-gallon (189.2L) fuel capacity - driver side, steel top tread plate, sump, drain and steps under cab on front passenger side. Provides clean back of cab and a black tethered fuel cap with gasoline engines, and a brass tethered fuel cap with diesel engines
- Steering, power - ZF variable ratio power
- Brake system, hydraulic, split - with 4-channel ABS disc-type Bosch Hydro Max high performance booster, tandem master cylinder provides independent front and rear circuits, front and rear disc Meritor calipers: 15 3/8" (391 mm) rotor diameter, 1 1/2" (39.1 mm) rotor thickness with (4) 2 1/2" (64 mm) diameter pistons with 8,000 lb. (3629 kg) front axle, (70 mm) diameter pistons with 10,000 lb. (4536 kg) front axle
- Parking brake, hand lever operated transmission mounted drum brake

SAFETY

- Brake system, hydraulic, split - with 4-channel ABS
- Air bags, Supplemental Inflatable Restraints not included
- Seat belt warning indicator
- Daytime running lamps

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.2, Data updated 12/25/2007 10:41:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 28, 2007 11:58:28 AM

Page 11

APPENDIX B

TRUCK QUESTIONNAIRE FORMS

ALL BIDDERS MUST COMPLETE AND RETURN A QUESTIONNAIRE FORM WITH THE BID FOR EACH TRUCK ITEM TO BE CONSIDERED FOR AWARD OF THAT ITEM. Bids submitted without an adequately completed questionnaire form for EACH TRUCK ITEM will not be considered for award of that item. It is the responsibility of each bidder to copy this form in sufficient quantity to submit to Purchasing Operations prior to the scheduled bid due date. A single form may apply to more than one item, simply list the item numbers to which the questionnaire applies in the appropriate space. If part of the questionnaire does not apply, simply indicate "not applicable" in those spaces.

NAME OF BIDDER: Red Holman Pontiac Gmc ITEM NO(s): Spec # 3958-0136
 MAKE OF TRUCK: Gmc MODEL: C7500 C7500Z GVWR 24,200 # lbs. ^{Topkick}
 PAYLOAD: 15356 # W.B. 152 " C.A. 84 " C.E. 135.30 "
 ENGINE: (GAS - DIESEL) Diesel MAKE: Gm-Isuzu-Duramax MODEL: LYA, 7.8 SAE H.P. 215
 FUEL TANK(S) CAPACITY: 100 (GALS. TOTAL) TRANSMISSION: Allison 2200 6-spd
 SPRING CAP. @ GROUND EACH: FRONT 4000 lbs. REAR 9500 lbs. AUX. N/A lbs.
 AXLES: FRONT 8000 lbs. REAR 19000 lbs. REAR RATIO 5.57
 ALTERNATOR: 100 amps. BATTERY Dual 750 1950 cca. Permanit
 TIRE SIZE: FRONT 9R22.5 F PR REAR 9R22.5 F PR SINGLE _____ DUAL ✓ M&S Rear
 TIRE: MAKE Goodyear STYLE NO. TBD MFG. CODE XUE/YUE
 HOIST: MAKE N/A MODEL N/A INSTALLING CO. N/A
 BODY: MAKE N/A MODEL N/A INSTALLING CO. N/A
 POWER LIFT GATE: MAKE N/A MODEL N/A CAPACITY N/A lbs.
 PLATFORM SIZE: N/A

OTHER EQUIPMENT INSTALLED BY BODY EQUIPMENT SUPPLIER AND/OR COMMENTS

* Note GVWR & Payload Can be increased to 26000# / 17062 by upgrading to 10R22.5 F Tires. at \$1010⁰⁰ additional

This information must be returned with the bid document to Purchasing Operations, on or before the bid due date and time. However, if returned separately, it must be received by Purchasing Operations on or before the bid due date and time, and must comply with the sealed bid instructions as outlined in the ITB.

TRUCK: CAB AND CHASSIS (G.V.W.R. 33,000 lbs., min.)*

MODEL-2008 CURRENT NEW

	<u>INT'L</u> <u>4400/7400</u>	<u>CHEV/GMC</u> <u>C7C042</u>	<u>FORD</u> <u>F750</u>
Wheelbase (inches)	169	170	182
C.A. (inches)	102	102	108
Engine: Diesel, Type	DT 466	Duramax	CAT C7
Size	7.8L	7.8L	7.2L
No. of Cylinders	6	6	6
Gross H.P.,250 min.	260	260	275
Torque	800/1400	660@1450	800/1440
Transmission: 6-Speed, 3000RDS		Allison 3000RDS or 3500RDS	
Axle, Min. Cap. lbs.	12,000	12,000	12,000
Front, 12,000 minimum			
Rear, 21,000 minimum, with Single Speed Rear Axle, with Driver Controlled Locking Differential	21,000	21,000	21,000
Ratios for minimum loaded road speed of approx. 68 mph.			
Springs, Min. Cap. at Ground			
Front-lbs. each	6,000	6,000	6,000
Rear-lbs. each, 11,750 minimum	11,750	11,750	11,750
Aux. lbs. each, multi-leaf	2,250	4,500	2,250

*Body specs.: 0158/Dump Body, 0161/Stake Body, 0165/Alum. Van Body, 0167/Painted Van Body

Tires, Truck, Tubeless, Radial, 11R22.5G (14PR) minimum. Front to be Highway Tread, Rear duals-Traction Drive Tread, Goodyear Unisteel G-164 RTD or approved equal. Same Mfg. Front and Rear.

TO BE STANDARD FACTORY EQUIPPED AS FOLLOWS:

The items listed below are to be supplied on all trucks, even though they may be optional with the manufacturer. Therefore, these specifications are to be furnished on all vehicles:

- 12 Volt auxiliary outlet
- Air Conditioning - All trucks
- Anti-freeze protection, to -30°F.
- Arm Rest-Driver's side.
- Color-Manufacturers Standard to be selected.
- Coolant System-Maximum Size Available, including the Heaviest Duty Radiator
- Dome Light.
- Electric wiring-All wiring passing through holes in metal or non-metal wearing surfaces, which could cause wear of the insulation, shall be adequately protected by rubber or plastic grommets, and/or non-metallic conduit. Ends of all wires shall be adequately anchored to prevent loosening.
- Frame length-on all body installations without hoists the cab to end of frame length shall be the same length as the body being mounted, plus the length of any setback.
- Fuel Tanks, Diesel, with sending unit and magnetic drain plug, on all trucks over 21,000 G.V.W.R., painted Black and labeled "Diesel Fuel Only".
- Hub caps on all pickups and vans up to and including 10,000 G.V.W.R. If not available from dealer cap nuts shall be furnished.
- Keys-(2) sets with code numbers; shall be with vehicle at time of delivery.
- Mirrors-All trucks are to be equipped with R.H. and L.H. outside rear-view mirrors to comply with Michigan laws; all trucks up to and including 15,000 G.V.W.R. shall be equipped with inside rear-view mirror. In all cases, outside R.H. & L.H. rear view mirrors shall provide full vision past all body installations. Mirrors shall be of stainless steel or high impact plastic construction unless denoted otherwise in individual truck specifications. All West Coast Type or Below Eye Level Camper Style Mirrors shall have stainless steel or high impact plastic heads, brackets, and hardware.
- Mud flaps, Anti-Sail Type, when required, are to be plain, rubber 1/4" thick, without advertising on either side.
- Painting-preclean and metal prep, any bare metal surfaces prior to applying a compatible red oxide or zinc chromate primer. When painting over a manufacturer's standard paint, metal prepping and primer may be omitted, provided an acceptable bond can be achieved.
- Equipment mounting- when mounting equipment on truck cab and chassis, all holes shall be drilled or punched. There shall be no flame cutting or welding on the frame side rails.
- Paint codes-factory paint codes shall be furnished with all vehicles; for all after market painting both the brand and paint code shall be furnished.
- Pre-delivery inspection and servicing.
- Radio - AM/FM Manufacturers Standard, Factory Installed
- Seat Belts with Shoulder Harness (3-Point Restraint System for Driver & Passenger)
- Seats-Split Bench type, unless otherwise specified
- Shock absorbers-(Heaviest Duty Available), front all trucks. Rear, up to and including 15,000 G.V.W.R.

- ☑ Spare tire, or Rim, not to be furnished unless specified. If specified, tires to be of same mfg., tread design to be same as front tires.
- ☑ Speed Control, Factory Installed
- ☑ Steering-Power, Tilt Wheel
- ☑ Sun visors-dual.
- ☑ Jack-Furnish on trucks up to and including 12,000 G.V.W.R.
- ☑ Windshield wipers-dual, intermittent speed electric, with automatic type washers.

All items removed for installation of optional equipment shall be returned to the State of Michigan.

TO BE EQUIPPED IN COMPLIANCE WITH ALL APPLICABLE FEDERAL MOTOR VEHICLE SAFETY STANDARDS AND REGULATIONS. ALL VEHICLES MUST BE EQUIPPED TO COMPLY WITH ALL REQUIREMENTS OF THE MICHIGAN MOTOR VEHICLE CODE.

- **Delete: On GM vehicles, OnStar and XM radio are deleted.**

ADDITIONAL OPTIONS:

These options are in addition to the options listed above as “STANDARD FACTORY EQUIPPED” and are to be included on this vehicle.

- ☑ Alternator-100 amp., minimum, Reference 22SI or approved equal.
- ☑ Battery(s)-12 Volt; 1,250 CCA minimum.
- ☑ Brakes-Full air. Current FMVSS. Dust plates. Air dryer with spin on filter, Automatic Drain Valves. Automatic slack adjusters.
- ☑ Cab assist handles-right and left.
- ☑ Engine Safety Devices-Warning light and audible alarm system activated when
- ☑ engine oil pressure falls below safe operating limit or when water temperature exceeds safe operating limit. Automatic engine shut-down with low oil pressure or high coolant temperature.
- ☑ Frame-Resisting bending moment 1,275,200 in.-lbs., min., Single Rail Frame
- ☑ Fuel Tanks-50 gallon each L.H. & R.H., center step tanks.
- ☑ Fuel/Water Separator with Heater.
- ☑ Heater-Engine block, 110/120 VAC
- ☑ Hood, Tilt type, with Butterfly Opening. GMC: Butterfly openings not available
- ☑ Horns-Dual, air, Single Base, with Covers.
- ☑ Mirrors, Rear View, Outside. L.H. & R.H. West Coast Type, 6" x 16", installed, with stainless steel, powder coated steel, or composite heads, brackets, and hardware.
- ☑ Shock absorbers, Heavy Duty, Front and Rear.
- ☑ Starting Aid-Cold weather, ether type or glow plug. GMC: Intake heater
- ☑ Steering-Power.
- ☑ Switches (6), outfitter, with remote power module (MDOT) GMC: Panel only – Switches & Power module must be supplied by body upfitter
- ☑ Tachometer.
- ☑ Throttle, Electronic, High Idle Engine RPM Control.
- ☑ Wheels-Hub Piloted disc.

PRICING SHEET

<u>TRUCK: CAB AND CHASSIS (G.V.W.R. 33,000 lbs., min.)*</u>	
Mich. Spec. #3958-0160	
Standard Equipped Per above Specification (Including options as specified above)	Standard Equipped Cost
Make: GMC Model: Topkick C7500 F.O.B. - Dealership Delivery Cost Per Mile \$1.80	\$55,191.00*
Final Point of Assembly: Flint, MI	
<u>Dealer Information</u>	
Dealer Name: Red Holman Pontiac GMC	
Street Address: 35300 Ford Road	
City: Westland	State: MI Zip: 48185
Contact Name: Albert Li	
Telephone: (800) 482-3032	
Cell: (734) 637-6643	
E-mail: aclixx@hotmail.com	

*Please Note: A vehicle order confirmation sheet is included for each vehicle. These documents shall include all the "standard options" as listed for the State of Michigan standard specification.

Vehicle Order Confirmation Sheet
Spec # 3958-0160

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclbx@hotmail.com

2008 Fleet/Non-Retail GMC TC7500

SELECTED MODEL & OPTIONS

SELECTED MODEL - 2008 Fleet/Non-Retail TC7C042 Regular Cab

<u>Code</u>	<u>Description</u>	<u>MSRP</u>
TC7C042	2008 GMC TC7500 Regular Cab	\$45,975.00

SELECTED VEHICLE COLORS - 2008 Fleet/Non-Retail TC7C042 Regular Cab

<u>Code</u>	<u>Description</u>
-	Interior: No color has been selected.
-	Exterior 1: No color has been selected.
-	Exterior 2: No color has been selected.

SELECTED OPTIONS - 2008 Fleet/Non-Retail TC7C042 Regular Cab

CATEGORY

<u>Code</u>	<u>Description</u>	<u>MSRP</u>
PREFERRED EQUIPMENT GROUP		
C7C042	CUSTOM/BASE MODEL	\$0.00
VEHICLE APPLICATION		
RQ2	TRUCK APPLICATION	INC
GVWR		
___	NO 25,950# GVWR RATING DESIRED	\$0.00
EMISSION		
FE9	FEDERAL REQUIREMENTS	INC
DIESEL ENGINE		
LYC	ISUZU DIESEL 6H 7.8L I6, 260 HP (194 KW) @ 2200 RPM AND 660 LB-FT TORQUE (895 N-M) @ 1450 RPM	\$19,942.00
AIR CLEANER		
KNB	DRY-TYPE STANDARD FILTER ELEMENT	\$0.00
FUEL/WATER SEPARATOR		
NWB	RACOR FRAME-MOUNTED SPIN-ON TYPE	INC

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.2, Data updated 12/25/2007 10:41:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 29, 2007 10:30:46 AM

Page 1

Prepared By:
 Albert Li
 Red Holman Pontiac GMC
 35300 Ford Rd
 Westland, MI 48185
 Phone: (734) 721-1144
 Fax: (734) 721-1780
 Email: aclix@hotmail.com

2008 Fleet/Non-Retail GMC TC7500

SELECTED MODEL & OPTIONS

SELECTED OPTIONS - 2008 Fleet/Non-Retail TC7C042 Regular Cab

<u>CATEGORY</u>		<u>MSRP</u>
<u>Code</u>	<u>Description</u>	
ENGINE BLOCK HEATER		
KB3	1250-WATT, 110V	\$50.00
ALTERNATOR		
K60	22SI, DELCO 100-AMP MAXIMUM	\$0.00
BATTERY		
TNL	DUAL AC DELCO, 750 CCA, 12V	\$0.00
ALARM		
KPJ	AUTOMATIC ENGINE SHUTDOWN WITH ALARM	INC
EXHAUST SYSTEM		
NB5	SINGLE HORIZONTAL-DRIVER SIDE MOUNTED INSIDE FRAME RAIL	\$0.00
POWER TAKE OFF		
PTO	ELECTRONIC ACTIVATION SWITCH, (ELECTRIC HAND THROTTLE), IP MOUNTED	\$100.00
AUTOMATIC TRANSMISSION		
MWZ	ALLISON 3500 RDS SERIES (WIDE RATIO) 6-SPEED	\$4,150.00
TRANSMISSION FLUID		
MBT	TRANSYND SYNTHETIC AUTOMATIC TRANSMISSION FLUID	INC
FRONT AXLE		
FS7	12,000 LBS. (5443 KG) CAPACITY	\$203.00
FRONT SUSPENSION		
F25	MULTI-LEAF, 12,000 LBS. (5443 KG) CAPACITY	\$25.00
FRONT WHEEL		
RPQ	22.5" X 8.25" (58.9 CM X 21 CM), STEEL DISC	\$0.00
FRONT TIRE		
XWL	11R22.5G-12,350 LBS. (5602 KG) CAPACITY	\$220.00
FRONT TIRE BRAND		
R4A	GOODYEAR	\$0.00
FRONT TIRE TREAD		

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.2, Data updated 12/25/2007 10:41:00 AM
 ©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 29, 2007 10:30:46 AM

Page 2

Prepared By:
 Albert Li
 Red Holman Pontiac GMC
 35300 Ford Rd
 Westland, MI 48185
 Phone: (734) 721-1144
 Fax: (734) 721-1780
 Email: aclix@hotmail.com

2008 Fleet/Non-Retail GMC TC7500

SELECTED MODEL & OPTIONS

SELECTED OPTIONS - 2008 Fleet/Non-Retail TC7C042 Regular Cab

CATEGORY

<u>Code</u>	<u>Description</u>	<u>MSRP</u>
FRONT TIRE TREAD		
R3C	PREMIUM, HIGHWAY	\$0.00
SINGLE SPEED REAR AXLE		
HPN	DANA 21060D, 21,000 LBS. (9526 KG) CAPACITY	\$1,421.00
AXLE RATIO		
009	5.29:1	\$0.00
REAR SUSPENSION		
GP1	MULTI-LEAF, 23,500 LBS. (10,660 KG) CAPACITY,	\$41.00
REAR AUXILIARY SPRINGS		
GG8	MULTI-LEAF, 4500 LBS. (2041 KG), CAPACITY	\$135.00
REAR SHOCK ABSORBER		
G68	REAR SHOCK ABSORBERS	\$58.00
REAR WHEEL		
RPR	22.5" X 8.25" (58.9 CM X 21 CM), STEEL DISC	\$0.00
REAR TIRE		
YWL	11R22.5G-23,000 LBS. (10,430 KG) CAPACITY	\$460.00
REAR TIRE BRAND		
S4A	GOODYEAR	\$0.00
REAR TIRE TREAD		
S3J	HIGHWAY TRACTION BLOCK	\$0.00
WHEELBASE		
EH8	170" (431.8 CM)	\$152.00
FRAME RAIL		
F02	RAIL, PAINTED SEMI-GLOSS BLACK 10MM-120,000 PSI (827,400 KPA) YIELD STRENGTH,	\$569.00
FUEL TANK		
NNQ	DUAL, 100-GALLON (380L) TOTAL FUEL CAPACITY,	\$370.00
BRAKE SYSTEM		

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.2, Data updated 12/25/2007 10:41:00 AM
 ©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 29, 2007 10:30:46 AM

Page 3

Prepared By:
 Albert Li
 Red Holman Pontiac GMC
 35300 Ford Rd
 Westland, MI 48185
 Phone: (734) 721-1144
 Fax: (734) 721-1780
 Email: aclix@hotmail.com

2008 Fleet/Non-Retail GMC TC7500

SELECTED MODEL & OPTIONS

SELECTED OPTIONS - 2008 Fleet/Non-Retail TC7C042 Regular Cab

<u>CATEGORY</u>		<u>MSRP</u>
<u>Code</u>	<u>Description</u>	
BRAKE SYSTEM		
JE4	AIR, ABS-4-CHANNEL BENDIX BRAKE SYSTEM 'S' CAM TYPE MERITOR,	\$1,778.00
BRAKE EQUIPMENT		
JRF	REAR DUST SHIELDS	\$0.00
AIR COMPRESSOR		
KK3	HALDEX 292 WATER-COOLED 12.9 CFM	INC
HORN		
UUE	SINGLE, DUAL-TRUMPET AIR	\$84.00
DRIVER CONVENIENCE PACKAGES		
ZQ3	DRIVER CONVENIENCE PACKAGE	\$172.00
MISCELLANEOUS CAB EQUIPMENT		
N33	TILT-WHEEL ADJUSTABLE STEERING	INC
K34	CRUISE CONTROL,	INC
AIR CONDITIONING		
C60	AIR CONDITIONING	\$939.00
DRIVER SEAT		
AS4	HIGH-BACK BUCKET, FIXED HEIGHT, MANUAL ADJUSTER	INC
PASSENGER SEAT		
A59	TWO-PERSON, WITHOUT STORAGE	\$200.00
AIRBAGS		
AL3	SUPPLEMENTAL INFLATABLE RESTRAINTS NOT INCLUDED	INC
RADIO		
UM7	DELCO AM-FM STEREO RADIO	\$165.00
EXTERIOR MIRRORS		
DB5	MANUAL, 102" (259 CM) WIDE LOAD, INTEGRAL ARM, INTEGRAL CONVEX MIRROR	INC
PAINT		
ZY1	SOLID NON-METALLIC PAINT	INC

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.2, Data updated 12/25/2007 10:41:00 AM

©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 29, 2007 10:30:46 AM

Page 4

Prepared By:
 Albert Li
 Red Holman Pontiac GMC
 35300 Ford Rd
 Westland, MI 48185
 Phone: (734) 721-1144
 Fax: (734) 721-1780
 Email: acliix@hotmail.com

2008 Fleet/Non-Retail GMC TC7500

SELECTED MODEL & OPTIONS

SELECTED OPTIONS - 2008 Fleet/Non-Retail TC7C042 Regular Cab

<u>CATEGORY</u>		<u>MSRP</u>
<u>Code</u>	<u>Description</u>	
INTERIOR TRIM		
69I	VERY DARK PEWTER	INC
SEAT TRIM		
_V	VINYL SEAT TRIM	INC
OPTIONS TOTAL		\$31,234.00

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.2, Data updated 12/25/2007 10:41:00 AM
 ©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 29, 2007 10:30:46 AM

Page 5

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclbx@hotmail.com

2008 Fleet/Non-Retail GMC TC7500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC7C042 Regular Cab

EXTERIOR

- Paint, solid, upper color, Summit White
- Paint, solid, lower color, Summit White
- Exterior roof drip moldings
- Bumpers, front steel, painted argent - Bumper thickness 3.9 mm
- Steps under cab doors
- Front mud flaps
- Integral grille and fenders - The grille is the same color as hood with single halogen headlamps. Entry steps under cab doors are based upon fuel tank type
- Roof marker lamps
- Daytime running lamps
- Windows, Solar-Ray tinted. Light tinted windshield and side window glass with light transmissivity of 70%
- Mirrors, manual, 102" (259 cm) wide load, integral arm, integral convex mirror - black molded composite 12" x 7" (30.5cm x 17.8 cm) with 6" x 7" (15.2cm x 17.8cm) convex section
- Windshield wipers, 2-speed and intermittent, with pulse washers
- Provisions for mounting front license plate
- Positive door stops
- Horn, single electric mounted inside engine compartment

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.2, Data updated 12/25/2007 10:41:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 29, 2007 10:30:46 AM

Page 6

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclix@hotmail.com

2008 Fleet/Non-Retail GMC TC7500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC7C042 Regular Cab

INTERIOR

- Seat, driver, high-back bucket, Fixed height, manual adjuster - storage in the seat riser with a small lip at the front to help prevent contents from sliding out.
- Seat, passenger, high-back bucket, Fixed height, manual back angle adjuster - storage in the seat riser with a small lip at the front to stop contents from sliding out
- Seat trim, vinyl, Very Dark Pewter
- Interior trim, Very Dark Pewter (Requires 69V Very Dark Pewter Vinyl or 69C Very Dark Pewter Cloth)
- Center console - located next to driver's seat and two cupholders
- Molded vinyl floor covering
- Steering wheel 16"
- Two sided single common key for doors and ignition
- Headlamp warning buzzer
- Warning tone, key-in-ignition
- Tachometer
- Electronic engine hour meter
- Engine "Check gauges" telltale light and buzzer, oil pressure gauge
- Gauges, low oil pressure and coolant level, high coolant and engine oil temperature
- Vinyl door trim panels - with storage pockets, beverage holders, and reflectors
- Stepwell storage areas at each door. Includes storage cover
- Cloth headliner
- Sunshades, passenger side and driver side, vinyl-covered
- Coat hooks (2) located on cab back panel
- Provisions for stereo - Includes AM/FM antenna, lead wiring for speakers, and separate door chime module (N/A with ZQ2 power convenience option)
- Air conditioning not desired - this option should be ordered only when a customer does not require air conditioning
- Powerpoints - two in-cab power sources (in addition to optional cigarette lighter) for electrical plug-in accessories

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.2, Data updated 12/25/2007 10:41:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 29, 2007 10:30:46 AM

Page 7

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclix@hotmail.com

2008 Fleet/Non-Retail GMC TC7500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC7C042 Regular Cab

- Underhood bodybuilder connections accessory power supply - Provides 12V power supply from the battery with two separate 30 amp fused circuits

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.2, Data updated 12/25/2007 10:41:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 29, 2007 10:30:46 AM

Page 8

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclix@hotmail.com

2008 Fleet/Non-Retail GMC TC7500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC7C042 Regular Cab

MECHANICAL

- Truck application NOTE: Federal Excise Tax (FET) of 12% must be paid on the final selling price for trucks with GVWR's of 33,001 lbs. and above. Trucks that are used primarily to tow a trailer may be liable to Federal Excise Tax (FET) - check with IRS for guidelines. PLEASE NOTE: The 12% FET tax is NOT included in AutoBook Pricing.
- Engine, Vortec 8.1L MD gasoline V8, 295 hp (220 kw) @ 3600 rpm, 440 lb-ft (594 N-m) torque @ 3,200 rpm. - Oil Level Sensor: Warning sensor for low oil levels
- Air cleaner, dry-type standard filter element (Requires gasoline engine)
- Underhood air cleaner restriction gauge
- Road Speed Governor, controlled by the speed rating of the tires ordered. All vehicles with 19.5" tire sizes and with most 22.5" and 24.5" tires have speed governed to a maximum of 75 mph (120 kph). A few aggressive tire tread patterns may have lower maximum speed ratings that limit governed speed to 65 or 55 mph - see tire company specifications for details.
- Alternator, AD244, Delco-Remy 150-amp maximum (Requires gasoline engine)
- Battery, single AC Delco, 600 CCA, 12V - 115-minute reserve capacity @ 27 degrees C, 600 CCA @ -18 degrees C, (Requires gasoline engine)
- Exhaust system, single horizontal - driver side mounted inside frame rail, with gasoline engine stainless-steel exhaust with catalytic converter. With diesel engines 409 stainless-steel exhaust system, integrated oxidation catalyst on Isuzu diesel, Diesel Particulate Filter (DPF) and exhaust gas cooler. (N/A with FQT wheelbase with Isuzu diesel engines and not available with EG9 wheelbase with Caterpillar engine)
- Option PTO not required - This option should only be ordered when a customer specifically does not require an electric hand throttle for use with power-take-off provisions. NOTE: Deletes transmission PTO gear with Allison MTX/MBZ 2200HS, MTY 2300HS, MHE 2350HS, MPS 2500HS, and MPQ 2550HS Series transmissions.
- Transmission, automatic, Allison 2300 HS/RDS (Close Ratio) 5-speed - No parking pawl. Includes 4th Generation Electronic Controls and 0.71 overdrive. Torque rating: 450 lb-ft (610 N-m), Available with a Gross Vehicle Weight up to 33,000 lbs. (15,000 kg) and a Gross Combined Weight up to 33,000 lbs. (15,000 kg). When "PTX" is selected, it does not include power take-off gear in the Allison 2300 HS Highway Series transmission. To include PTO gear please order with RPO "PTO" for Allison 2300 RDS Rugged Duty Series transmission. Includes transmission oil cooler in radiator, increased cooling and column shift. (Requires gasoline engine and HPK, HPL, HPM, HPN, HPP or H15 rear axles)
- TranSynd synthetic automatic transmission fluid (Available with automatic transmissions only)
- Front axle, 10,000 lbs. (4536 kg) capacity - Up to 53 degree turn angle. Steering Gear Series: ZF8016

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.2, Data updated 12/25/2007 10:41:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.
Customer File:

December 29, 2007 10:30:46 AM

Page 9

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclbx@hotmail.com

2008 Fleet/Non-Retail GMC TC7500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC7C042 Regular Cab

- Front suspension, tapered leaf, 10,000 lbs. (4536 kg) capacity (Requires FM8 and FM6 front axle)
- Front shock absorber, diameter 1.375" (35mm)
- Front wheels, 22.5" x 7.5" (58.9 cm x 19 cm), steel disc - Accuride 10-hole, flange nut, hub piloted, 11.25" (28.5 cm) bolt circle, painted Gray (E-Coat), 13,220 lbs. (5996 kg) capacity, (Requires QH4 rear wheels; N/A with FL3 front axle)
- Front tire size, 245/75R22.5G - 9350 lbs. (4241 kg) capacity, (With R4A Goodyear requires R3C front premium tread; N/A with Michelin)
- Front tire manufacturer code, Goodyear (Requires S4A Goodyear)
- Front tire tread, premium highway
- Rear axle, single-speed, Dana 19060S, 19,000 lbs. (8618 kg) capacity - includes 75W-90 synthetic lubricant and National brand oil seals (Requires GN0, GN2, GN8, GR9, GP1, GP0 or G40 rear suspension) (N/A with FL3 front axle)
- Rear wheel drive
- Rear axle ratio, 7.17:1 (Requires HPK, HPL, HPN, HPP or HPT single speed rear axle or HPM, H15 two-speed rear axle)
- Rear suspension, multi-leaf, 19,000 lbs. (8618 kg) capacity (Requires HPK or HPL single rear axle or HPM two-speed rear axle)
- Rear wheels, 22.5" x 7.5" (58.9 cm x 19 cm), steel disc - Accuride 10-hole, flange nut, hub piloted, 11.25" (28.5 cm) bolt circle, painted Gray (E-Coat) 26,440 lbs. (11,993 kg) capacity, (Requires HPK, HPL, HPN, HPP or HPT single speed rear axle, or HPM, H15 or H25 two-speed rear axle) (Not available with YWM, YWP or YRN 22.5" rear tires)
- Rear tire size, 245/75R22.5G - 17,200 lbs. (7802 kg) capacity (With S4A Goodyear requires S3C rear premium tread or S3H rear highway traction tread; N/A with Michelin)
- Rear tire manufacturer code, Goodyear (Requires R4A Goodyear)
- Rear tire tread, premium highway
- Wheelbase, 140" (355.6 cm) - with 72" (182.9 cm) CA and 135.3" (343.7 cm) CE, (With diesel engine requires NPY exhaust)
- Frame, painted semi-gloss black 6mm rail - 50,000 psi (344,750 kPa) yield strength, steel frame, SAE J1392-050XLK steel, dimensions 9 1/2" x 3" x 1/4" section modulus 9.58 cu. in., RBM 479,000

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.2, Data updated 12/25/2007 10:41:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 29, 2007 10:30:46 AM

Page 10

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclixx@hotmail.com

2008 Fleet/Non-Retail GMC TC7500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC7C042 Regular Cab

- Fuel tank, single, 50-gallon (189.2L) fuel capacity - driver side, steel top tread plate, sump, drain and steps under cab on front passenger side. Provides clean back of cab and a black tethered fuel cap with gasoline engines, and a brass tethered fuel cap with diesel engines
- Steering, power - ZF variable ratio power
- Brake system, hydraulic, split - with 4-channel ABS disc-type Bosch Hydro Max high performance booster, tandem master cylinder provides independent front and rear circuits, front and rear disc Meritor calipers: 15 3/8" (391 mm) rotor diameter, 1 1/2" (39.1 mm) rotor thickness with (4) 2 1/2" (64 mm) diameter pistons with 8,000 lb. (3629 kg) front axle, (70 mm) diameter pistons with 10,000 lb. (4536 kg) front axle
- Parking brake, hand lever operated transmission mounted drum brake

SAFETY

- Brake system, hydraulic, split - with 4-channel ABS
- Air bags, Supplemental Inflatable Restraints not included
- Seat belt warning indicator
- Daytime running lamps

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.2, Data updated 12/25/2007 10:41:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 29, 2007 10:30:46 AM

Page 11



APPENDIX B

TRUCK QUESTIONNAIRE FORMS

ALL BIDDERS MUST COMPLETE AND RETURN A QUESTIONNAIRE FORM WITH THE BID FOR EACH TRUCK ITEM TO BE CONSIDERED FOR AWARD OF THAT ITEM. Bids submitted without an adequately completed questionnaire form for EACH TRUCK ITEM will not be considered for award of that item. It is the responsibility of each bidder to copy this form in sufficient quantity to submit to Purchasing Operations prior to the scheduled bid due date. A single form may apply to more than one item, simply list the item numbers to which the questionnaire applies in the appropriate space. If part of the questionnaire does not apply, simply indicate "not applicable" in those spaces.

NAME OF BIDDER: Red Holman Pontiac GMC ITEM NO(S). Spec # 3958-0160
 MAKE OF TRUCK: GMC MODEL: C7500 ^{Topkick} C7C042 GVWR 33000 lbs. ✓
 PAYLOAD: 22536 # W.B. 170" ✓ C.A. 102" ✓ C.E. 171.10" ✓
 ENGINE: (GAS - DIESEL) Diesel ✓ MAKE: Gm/Isuzu Duramax MODEL: LYC, 7.8 SAE H.P. 260 ✓
 FUEL TANK(S) CAPACITY: 100 (GALS. TOTAL) TRANSMISSION: Allison 3500 6-spd ✓
 SPRING CAP. @ GROUND EACH: FRONT 6000 lbs. REAR 11750 lbs. AUX. 4500 lbs. ✓
 AXLES: FRONT 12000 lbs. REAR 21000 lbs. REAR RATIO 5.29 ✓
 ALTERNATOR: 100 amps. BATTERY Dual 750 cca. ✓
 TIRE SIZE: FRONT 11R22.5 F PR REAR 11R22.5 F PR SINGLE _____ DUAL ✓ M&S ✓
 TIRE: MAKE Goodyear STYLE NO. TBD MFG. CODE XWL/YWL
 HOIST: MAKE N/A MODEL N/A INSTALLING CO. N/A
 BODY: MAKE N/A MODEL N/A INSTALLING CO. N/A
 POWER LIFT GATE: MAKE N/A MODEL N/A CAPACITY N/A lbs.
 PLATFORM SIZE: N/A

OTHER EQUIPMENT INSTALLED BY BODY EQUIPMENT SUPPLIER AND/OR COMMENTS

This information must be returned with the bid document to Purchasing Operations, on or before the bid due date and time. However, if returned separately, it must be received by Purchasing Operations on or before the bid due date and time, and must comply with the sealed bid instructions as outlined in the ITB.

TRUCK: CAB AND CHASSIS (G.V.W.R. 27,000 LBS., MIN.)*

MODEL-2008 CURRENT NEW

	<u>FORD</u> <u>F750</u>	<u>INTL</u> <u>4300 M7</u>	<u>CHEV/GMC</u> <u>C7C042</u>
Wheelbase (inches)	230	217	224
C.A. (inches)	156	150	153
Engine: Diesel, Type	Cummins ISB	MaxxForce 7	Duramax
Size	6.7L	6.4L	7.8L
Gross HP-210 min.	220	215	215
Transmission: 5 speed			Allison 2350HS 6 spd w/park pawl
Allison Auto, 2000 series			
Axle, Min. Cap.-lbs.			
Front	8,500	8,000	8,000
Rear	19,000	19,000	19,000
Ratio for minimum loaded road speed of approx. 68 mph.			
Springs, Min. Cap. at Ground			
Front-lbs. each	4,250	4,000	4,000
Rear-lbs. each	10,000	10,000	10,500
Aux. lbs. each	2,250	2,250	no rating

*See Mich. 3958-0165 or 3958-0167 for body.

Tires, Truck, Tubeless, Radial, 11R22.5G (14PR) minimum. Front to be Highway Tread, Rear duals-Traction Drive Tread, Goodyear Unisteel, G-164 RTD or approved equal. Same Mfg. Front and Rear.

TO BE STANDARD FACTORY EQUIPPED AS FOLLOWS:

The items listed below are to be supplied on all trucks, even though they may be optional with the manufacturer. Therefore, these specifications are to be furnished on all vehicles:

- ☑ 12 Volt auxiliary outlet
- ☑ Air Conditioning - All trucks
- ☑ Anti-freeze protection, to -30°F.
- ☑ Arm Rest-Driver's side.
- ☑ Color-Manufacturers Standard to be selected.
- ☑ Coolant System-Maximum Size Available, including the Heaviest Duty Radiator
- ☑ Dome Light.
- ☑ Electric wiring-All wiring passing through holes in metal or non-metal wearing surfaces, which could cause wear of the insulation, shall be adequately protected by rubber or plastic grommets, and/or non-metallic conduit. Ends of all wires shall be adequately anchored to prevent loosening.
- ☑ Frame length-on all body installations without hoists the cab to end of frame length shall be the same length as the body being mounted, plus the length of any setback.
- ☑ Fuel Tanks, Diesel, with sending unit and magnetic drain plug, on all trucks over 21,000 G.V.W.R., painted Black and labeled "Diesel Fuel Only".
- ☑ Hub caps on all pickups and vans up to and including 10,000 G.V.W.R. If not available from dealer cap nuts shall be furnished.
- ☑ Keys-(2) sets with code numbers; shall be with vehicle at time of delivery.
- ☑ Mirrors-All trucks are to be equipped with R.H. and L.H. outside rear-view mirrors to comply with Michigan laws; all trucks up to and including 15,000 G.V.W.R. shall be equipped with inside rear-view mirror. In all cases, outside R.H. & L.H. rear view mirrors shall provide full vision past all body installations. Mirrors shall be of stainless steel or high impact plastic construction unless denoted otherwise in individual truck specifications. All West Coast Type or Below Eye Level Camper Style Mirrors shall have stainless steel or high impact plastic heads, brackets, and hardware.
- ☑ Mud flaps, Anti-Sail Type, when required, are to be plain, rubber 1/4" thick, without advertising on either side.
- ☑ Painting-preclean and metal prep, any bare metal surfaces prior to applying a compatible red oxide or zinc chromate primer. When painting over a manufacturer's standard paint, metal prepping and primer may be omitted, provided an acceptable bond can be achieved.
- ☑ Equipment mounting- when mounting equipment on truck cab and chassis, all holes shall be drilled or punched. There shall be no flame cutting or welding on the frame side rails.
- ☑ Paint codes-factory paint codes shall be furnished with all vehicles; for all after market painting both the brand and paint code shall be furnished.
- ☑ Pre-delivery inspection and servicing.
- ☑ Radio - AM/FM Manufacturers Standard, Factory Installed
- ☑ Seat Belts with Shoulder Harness (3-Point Restraint System for Driver & Passenger)
- ☑ Seats-Split Bench type, unless otherwise specified
- ☑ Shock absorbers-(Heaviest Duty Available), front all trucks. Rear, up to and including 15,000 G.V.W.R.
- ☑ Spare tire, or Rim, not to be furnished unless specified. If specified, tires to be of same mfg., tread design to be same as front tires.
- ☑ Speed Control, Factory Installed
- ☑ Steering-Power, Tilt Wheel

- ☑ Sun visors-dual.
- ☑ Jack-Furnish on trucks up to and including 12,000 G.V.W.R.
- ☑ Windshield wipers-dual, intermittent speed electric, with automatic type washers.

All items removed for installation of optional equipment shall be returned to the State of Michigan.

TO BE EQUIPPED IN COMPLIANCE WITH ALL APPLICABLE FEDERAL MOTOR VEHICLE SAFETY STANDARDS AND REGULATIONS. ALL VEHICLES MUST BE EQUIPPED TO COMPLY WITH ALL REQUIREMENTS OF THE MICHIGAN MOTOR VEHICLE CODE.

- **Delete: On GM vehicles, OnStar and XM radio are deleted.**

ADDITIONAL OPTIONS:

These options are in addition to the options listed above as “STANDARD FACTORY EQUIPPED” and are to be included on this vehicle.

- ☑ Alternator-100 amp., minimum, Reference 22SI or approved equal.
- ☑ Battery(s)-12 Volts; 1500 CCA, Min.
- ☑ Brakes-Full air. Current FMVSS. Dust plates. Air dryer with spin on filter, Automatic Drain Valves. Automatic slack adjusters.
- ☑ Cab assist handles-right and left.
- ☑ Exhaust (PIPE ONLY) - Vertical installation.
- ☑ Fuel Tanks-L.H. and R.H. 45 (min.) gallon tanks, frame mounted.
- ☑ Fuel/Water Separator with Heater.
- ☑ Heater-Engine block, 110/120 VAC
- ☑ Hood, Tilt.
- ☑ Horns-Electric, dual.
- ☑ Mirrors-Rear View, Outside. L.H. and R.H. West Coast type. 6' x 16"; installed, with stainless steel or powder coated steel heads, brackets, and hardware. GMC: Composite Heads
- ☑ Oil Seals (wet)-front axle.
- ☑ Shock absorbers, Heavy Duty, Front and Rear.
- ☑ Starting Aid-Cold weather, ether type or glow plug. GMC: Intake Heater
- ☑ Steering-Power.
- ☑ Switches (6), outfitter, with remote power module (MDOT) GMC: Panel only, switches & remote power module available through upfitter of body
- ☑ Tachometer.
- ☑ Throttle, Electronic, High Idle Engine RPM Control.
- ☑ Wheels-Hub Piloted disc.

PRICING SHEET

<u>TRUCK: CAB AND CHASSIS (G.V.W.R. 27,000 LBS., MIN.)*</u>	
Mich. Spec. #3958-0164	
Standard Equipped Per above Specification (Including options as specified above)	Standard Equipped Cost
Make: GMC Model: Topkick C7500 F.O.B. - Dealership Delivery Cost Per Mile \$1.80	\$48,574.00*
Final Point of Assembly: Flint, MI	
<u>Dealer Information</u>	
Dealer Name: Red Holman Pontiac GMC	
Street Address: 35300 Ford Road	
City: Westland	State: MI
	Zip: 48185
Contact Name: Albert Li	
Telephone: (800) 482-3032	
Cell: (734) 637-6643	
E-mail: aclixx@hotmail.com	

*Please Note: A vehicle order confirmation sheet is included for each vehicle. These documents shall include all the "standard options" as listed for the State of Michigan standard specification.

Vehicle Order Confirmation Sheet
 Spec # 3958-0164

Prepared By:
 Albert Li
 Red Holman Pontiac GMC
 35300 Ford Rd
 Westland, MI 48185
 Phone: (734) 721-1144
 Fax: (734) 721-1780
 Email: aclix@hotmail.com

2008 Fleet/Non-Retail GMC TC7500

SELECTED MODEL & OPTIONS

SELECTED MODEL - 2008 Fleet/Non-Retail TC7C042 Regular Cab

<u>Code</u>	<u>Description</u>	<u>MSRP</u>
TC7C042	2008 GMC TC7500 Regular Cab	\$45,975.00

SELECTED VEHICLE COLORS - 2008 Fleet/Non-Retail TC7C042 Regular Cab

<u>Code</u>	<u>Description</u>
-	Interior: No color has been selected.
-	Exterior 1: No color has been selected.
-	Exterior 2: No color has been selected.

SELECTED OPTIONS - 2008 Fleet/Non-Retail TC7C042 Regular Cab

CATEGORY

<u>Code</u>	<u>Description</u>	<u>MSRP</u>
PREFERRED EQUIPMENT GROUP		
C7C042	CUSTOM/BASE MODEL	\$0.00
VEHICLE APPLICATION		
RQ2	TRUCK APPLICATION	INC
GVWR		
	NO 25,950# GVWR RATING DESIRED	\$0.00
EMISSION		
FE9	FEDERAL REQUIREMENTS	INC
DIESEL ENGINE		
LYA	ISUZU DIESEL 6H 7.8L I6, 215 HP (160 KW) @ 2200 RPM AND 560 LB-FT TORQUE (759 N-M) @ 1450 RPM	\$16,466.00
AIR CLEANER		
KNB	DRY-TYPE STANDARD FILTER ELEMENT	\$0.00
FUEL/WATER SEPARATOR		
NWB	RACOR FRAME-MOUNTED SPIN-ON TYPE	INC

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.2, Data updated 12/25/2007 10:41:00 AM
 ©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 29, 2007 12:34:35 PM

Page 1

Prepared By:
 Albert Li
 Red Holman Pontiac GMC
 35300 Ford Rd
 Westland, MI 48185
 Phone: (734) 721-1144
 Fax: (734) 721-1780
 Email: aclbx@hotmail.com

2008 Fleet/Non-Retail GMC TC7500

SELECTED MODEL & OPTIONS

SELECTED OPTIONS - 2008 Fleet/Non-Retail TC7C042 Regular Cab

<u>CATEGORY</u>		<u>MSRP</u>
<u>Code</u>	<u>Description</u>	
ENGINE BLOCK HEATER		
KB3	1250-WATT, 110V	\$50.00
HIGH IDLE SWITCH		
UF3	HIGH IDLE SWITCH	\$31.00
ALTERNATOR		
K60	22SI, DELCO 100-AMP MAXIMUM	\$0.00
BATTERY		
TNL	DUAL AC DELCO, 750 CCA, 12V	\$0.00
ALARM		
KPJ	AUTOMATIC ENGINE SHUTDOWN WITH ALARM	INC
EXHAUST SYSTEM		
NPY	DRIVER SIDE HORIZONTAL EXHAUST WITH VERTICAL TAIL PIPE	\$518.00
POWER TAKE OFF		
PTX	OPTION PTO NOT REQUIRED	\$0.00
AUTOMATIC TRANSMISSION		
MHE	ALLISON 2350 HS/RDS SERIES 6-SPEED	\$705.00
TRANSMISSION FLUID		
MBT	TRANSYND SYNTHETIC AUTOMATIC TRANSMISSION FLUID	INC
FRONT AXLE		
FM8	8000 LBS. (3629 KG) CAPACITY	-\$459.00
FRONT OIL SEALS		
FF1	FRONT OIL SEALS WITH CLEAR CAPS	\$21.00
FRONT SUSPENSION		
FSN	TAPERED LEAF, 8000 LBS. (3629 KG) CAPACITY	-\$51.00
FRONT WHEEL		
RPQ	22.5" X 8.25" (58.9 CM X 21 CM), STEEL DISC	\$0.00
FRONT TIRE		
XWL	11R22.5G-12,350 LBS. (5602 KG) CAPACITY	\$220.00

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.2, Data updated 12/25/2007 10:41:00 AM
 ©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 29, 2007 12:34:35 PM

Page 2

Prepared By:
 Albert Li
 Red Holman Pontiac GMC
 35300 Ford Rd
 Westland, MI 48185
 Phone: (734) 721-1144
 Fax: (734) 721-1780
 Email: aclix@hotmail.com

2008 Fleet/Non-Retail GMC TC7500

SELECTED MODEL & OPTIONS

SELECTED OPTIONS - 2008 Fleet/Non-Retail TC7C042 Regular Cab

<u>CATEGORY</u>		<u>MSRP</u>
<u>Code</u>	<u>Description</u>	
FRONT TIRE BRAND		
R4A	GOODYEAR	\$0.00
FRONT TIRE TREAD		
R3C	PREMIUM, HIGHWAY	\$0.00
SINGLE SPEED REAR AXLE		
HPK	DANA 19060S, 19,000 LBS. (8618 KG) CAPACITY	INC
AXLE RATIO		
009	5.29:1	\$0.00
REAR SUSPENSION		
GN8	MULTI-LEAF, 21,000 LBS. (9526 KG) CAPACITY	\$20.00
REAR AUXILIARY SPRINGS		
G60	SINGLE TAPERED LEAF, NOT RATED	\$88.00
REAR SHOCK ABSORBER		
G68	REAR SHOCK ABSORBERS	\$58.00
REAR WHEEL		
RPR	22.5" X 8.25" (58.9 CM X 21 CM), STEEL DISC	\$0.00
REAR TIRE		
YWL	11R22.5G-23,000 LBS. (10,430 KG) CAPACITY	\$460.00
REAR TIRE BRAND		
S4A	GOODYEAR	\$0.00
REAR TIRE TREAD		
S3J	HIGHWAY TRACTION BLOCK	\$0.00
WHEELBASE		
EK6	224" (568.9 CM)	\$619.00
FRAME RAIL		
FD5	RAIL, PAINTED SEMI-GLOSS BLACK 8MM-80,000 PSI (551,600 KPA) YIELD STRENGTH,	\$0.00
FUEL TANK		

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.2, Data updated 12/25/2007 10:41:00 AM
 ©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 29, 2007 12:34:35 PM

Page 3

Prepared By:
 Albert Li
 Red Holman Pontiac GMC
 35300 Ford Rd
 Westland, MI 48185
 Phone: (734) 721-1144
 Fax: (734) 721-1780
 Email: aclixx@hotmail.com

2008 Fleet/Non-Retail GMC TC7500

SELECTED MODEL & OPTIONS

SELECTED OPTIONS - 2008 Fleet/Non-Retail TC7C042 Regular Cab

<u>CATEGORY</u>		<u>MSRP</u>
<u>Code</u>	<u>Description</u>	
FUEL TANK		
NNQ	DUAL, 100-GALLON (380L) TOTAL FUEL CAPACITY,	\$370.00
BRAKE SYSTEM		
JE4	AIR, ABS-4-CHANNEL BENDIX BRAKE SYSTEM 'S' CAM TYPE MERITOR,	\$1,778.00
BRAKE EQUIPMENT		
JRF	REAR DUST SHIELDS	\$0.00
AIR COMPRESSOR		
KK3	HALDEX 292 WATER-COOLED 12.9 CFM	INC
HORN		
U08	DUAL-NOTE, ELECTRIC	\$21.00
DRIVER CONVENIENCE PACKAGES		
ZQ3	DRIVER CONVENIENCE PACKAGE	\$223.00
MISCELLANEOUS CAB EQUIPMENT		
N33	TILT-WHEEL ADJUSTABLE STEERING	INC
K34	CRUISE CONTROL,	INC
AIR CONDITIONING		
C60	AIR CONDITIONING	\$939.00
DRIVER SEAT		
AS4	HIGH-BACK BUCKET, FIXED HEIGHT, MANUAL ADJUSTER	INC
PASSENGER SEAT		
A59	TWO-PERSON, WITHOUT STORAGE	\$200.00
AIRBAGS		
AL3	SUPPLEMENTAL INFLATABLE RESTRAINTS NOT INCLUDED	INC
RADIO		
UM7	DELCO AM-FM STEREO RADIO	\$165.00
EXTERIOR MIRRORS		
DB5	MANUAL, 102" (259 CM) WIDE LOAD, INTEGRAL ARM, INTEGRAL CONVEX MIRROR	INC

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.2, Data updated 12/25/2007 10:41:00 AM
 ©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 29, 2007 12:34:35 PM

Page 4

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclix@hotmail.com

2008 Fleet/Non-Retail GMC TC7500

SELECTED MODEL & OPTIONS

SELECTED OPTIONS - 2008 Fleet/Non-Retail TC7C042 Regular Cab

<u>CATEGORY</u>		<u>MSRP</u>
<u>Code</u>	<u>Description</u>	
PAINT		
ZY1	SOLID NON-METALLIC PAINT	INC
INTERIOR TRIM		
69I	VERY DARK PEWTER	INC
SEAT TRIM		
_V	VINYL SEAT TRIM	INC
OPTIONS TOTAL		\$22,442.00

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.2, Data updated 12/25/2007 10:41:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 29, 2007 12:34:35 PM

Page 5

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclix@hotmail.com

2008 Fleet/Non-Retail GMC TC7500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC7C042 Regular Cab

EXTERIOR

- Paint, solid, upper color, Summit White
- Paint, solid, lower color, Summit White
- Exterior roof drip moldings
- Bumpers, front steel, painted argent - Bumper thickness 3.9 mm
- Steps under cab doors
- Front mud flaps
- Integral grille and fenders - The grille is the same color as hood with single halogen headlamps. Entry steps under cab doors are based upon fuel tank type
- Roof marker lamps
- Daytime running lamps
- Windows, Solar-Ray tinted. Light tinted windshield and side window glass with light transmissivity of 70%
- Mirrors, manual, 102" (259 cm) wide load, integral arm, integral convex mirror - black molded composite 12" x 7" (30.5cm x 17.8 cm) with 6" x 7" (15.2cm x 17.8cm) convex section
- Windshield wipers, 2-speed and intermittent, with pulse washers
- Provisions for mounting front license plate
- Positive door stops
- Horn, single electric mounted inside engine compartment

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.2, Data updated 12/25/2007 10:41:00 AM

©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 29, 2007 12:34:35 PM

Page 6

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclix@hotmail.com

2008 Fleet/Non-Retail GMC TC7500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC7C042 Regular Cab

INTERIOR

- Seat, driver, high-back bucket, Fixed height, manual adjuster - storage in the seat riser with a small lip at the front to help prevent contents from sliding out.
- Seat, passenger, high-back bucket, Fixed height, manual back angle adjuster - storage in the seat riser with a small lip at the front to stop contents from sliding out
- Seat trim, vinyl, Very Dark Pewter
- Interior trim, Very Dark Pewter (Requires 69V Very Dark Pewter Vinyl or 69C Very Dark Pewter Cloth)
- Center console - located next to driver's seat and two cupholders
- Molded vinyl floor covering
- Steering wheel 16"
- Two sided single common key for doors and ignition
- Headlamp warning buzzer
- Warning tone, key-in-ignition
- Tachometer
- Electronic engine hour meter
- Engine "Check gauges" telltale light and buzzer, oil pressure gauge
- Gauges, low oil pressure and coolant level, high coolant and engine oil temperature
- Vinyl door trim panels - with storage pockets, beverage holders, and reflectors
- Stepwell storage areas at each door. Includes storage cover
- Cloth headliner
- Sunshades, passenger side and driver side, vinyl-covered
- Coat hooks (2) located on cab back panel
- Provisions for stereo - Includes AM/FM antenna, lead wiring for speakers, and separate door chime module (N/A with ZQ2 power convenience option)
- Air conditioning not desired - this option should be ordered only when a customer does not require air conditioning
- Powerpoints - two in-cab power sources (in addition to optional cigarette lighter) for electrical plug-in accessories

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.2, Data updated 12/25/2007 10:41:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.
Customer File:

December 29, 2007 12:34:35 PM

Page 7

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclix@hotmail.com

2008 Fleet/Non-Retail GMC TC7500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC7C042 Regular Cab

- Underhood bodybuilder connections accessory power supply - Provides 12V power supply from the battery with two separate 30 amp fused circuits

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.2, Data updated 12/25/2007 10:41:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 29, 2007 12:34:35 PM

Page 8

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclix@hotmail.com

2008 Fleet/Non-Retail GMC TC7500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC7C042 Regular Cab

MECHANICAL

- Truck application NOTE: Federal Excise Tax (FET) of 12% must be paid on the final selling price for trucks with GVWR's of 33,001 lbs. and above. Trucks that are used primarily to tow a trailer may be liable to Federal Excise Tax (FET) - check with IRS for guidelines. PLEASE NOTE: The 12% FET tax is NOT included in AutoBook Pricing.
- Engine, Vortec 8.1L MD gasoline V8, 295 hp (220 kw) @ 3600 rpm, 440 lb-ft (594 N-m) torque @ 3,200 rpm. - Oil Level Sensor: Warning sensor for low oil levels
- Air cleaner, dry-type standard filter element (Requires gasoline engine)
- Underhood air cleaner restriction gauge
- Road Speed Governor, controlled by the speed rating of the tires ordered. All vehicles with 19.5" tire sizes and with most 22.5" and 24.5" tires have speed governed to a maximum of 75 mph (120 kph). A few aggressive tire tread patterns may have lower maximum speed ratings that limit governed speed to 65 or 55 mph - see tire company specifications for details.
- Alternator, AD244, Delco-Remy 150-amp maximum (Requires gasoline engine)
- Battery, single AC Delco, 600 CCA, 12V - 115-minute reserve capacity @ 27 degrees C, 600 CCA @ -18 degrees C, (Requires gasoline engine)
- Exhaust system, single horizontal - driver side mounted inside frame rail, with gasoline engine stainless-steel exhaust with catalytic converter. With diesel engines 409 stainless-steel exhaust system, integrated oxidation catalyst on Isuzu diesel, Diesel Particulate Filter (DPF) and exhaust gas cooler. (N/A with FQT wheelbase with Isuzu diesel engines and not available with EG9 wheelbase with Caterpillar engine)
- Option PTO not required - This option should only be ordered when a customer specifically does not require an electric hand throttle for use with power-take-off provisions. NOTE: Deletes transmission PTO gear with Allison MTX/MBZ 2200HS, MTY 2300HS, MHE 2350HS, MPS 2500HS, and MPQ 2550HS Series transmissions.
- Transmission, automatic, Allison 2300 HS/RDS (Close Ratio) 5-speed - No parking pawl. Includes 4th Generation Electronic Controls and 0.71 overdrive. Torque rating: 450 lb-ft (610 N-m), Available with a Gross Vehicle Weight up to 33,000 lbs. (15,000 kg) and a Gross Combined Weight up to 33,000 lbs. (15,000 kg). When "PTX" is selected, it does not include power take-off gear in the Allison 2300 HS Highway Series transmission. To include PTO gear please order with RPO "PTO" for Allison 2300 RDS Rugged Duty Series transmission. Includes transmission oil cooler in radiator, increased cooling and column shift. (Requires gasoline engine and HPK, HPL, HPM, HPN, HPP or H15 rear axles)
- TranSynd synthetic automatic transmission fluid (Available with automatic transmissions only)
- Front axle, 10,000 lbs. (4536 kg) capacity - Up to 53 degree turn angle. Steering Gear Series: ZF8016

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.2, Data updated 12/25/2007 10:41:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 29, 2007 12:34:35 PM

Page 9

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclibx@hotmail.com

2008 Fleet/Non-Retail GMC TC7500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC7C042 Regular Cab

- Front suspension, tapered leaf, 10,000 lbs. (4536 kg) capacity (Requires FM8 and FM6 front axle)
- Front shock absorber, diameter 1.375" (35mm)
- Front wheels, 22.5" x 7.5" (58.9 cm x 19 cm), steel disc - Accuride 10-hole, flange nut, hub piloted, 11.25" (28.5 cm) bolt circle, painted Gray (E- Coat), 13,220 lbs. (5996 kg) capacity, (Requires QH4 rear wheels; N/A with FL3 front axle)
- Front tire size, 245/75R22.5G - 9350 lbs. (4241 kg) capacity, (With R4A Goodyear requires R3C front premium tread; N/A with Michelin)
- Front tire manufacturer code, Goodyear (Requires S4A Goodyear)
- Front tire tread, premium highway
- Rear axle, single-speed, Dana 19060S, 19,000 lbs. (8618 kg) capacity - includes 75W-90 synthetic lubricant and National brand oil seals (Requires GN0, GN2, GN8, GR9, GP1, GP0 or G40 rear suspension) (N/A with FL3 front axle)
- Rear wheel drive
- Rear axle ratio, 7.17:1 (Requires HPK, HPL, HPN, HPP or HPT single speed rear axle or HPM, H15 two-speed rear axle)
- Rear suspension, multi-leaf, 19,000 lbs. (8618 kg) capacity (Requires HPK or HPL single rear axle or HPM two-speed rear axle)
- Rear wheels, 22.5" x 7.5" (58.9 cm x 19 cm), steel disc - Accuride 10-hole, flange nut, hub piloted, 11.25" (28.5 cm) bolt circle, painted Gray (E-Coat) 26,440 lbs. (11,993 kg) capacity, (Requires HPK, HPL, HPN, HPP or HPT single speed rear axle, or HPM, H15 or H25 two-speed rear axle) (Not available with YWM, YWP or YRN 22.5" rear tires)
- Rear tire size, 245/75R22.5G - 17,200 lbs. (7802 kg) capacity (With S4A Goodyear requires S3C rear premium tread or S3H rear highway traction tread; N/A with Michelin)
- Rear tire manufacturer code, Goodyear (Requires R4A Goodyear)
- Rear tire tread, premium highway
- Wheelbase, 140" (355.6 cm) - with 72" (182.9 cm) CA and 135.3" (343.7 cm) CE, (With diesel engine requires NPY exhaust)
- Frame, painted semi-gloss black 6mm rail - 50,000 psi (344,750 kPa) yield strength, steel frame, SAE J1392-050XLK steel, dimensions 9 1/2" x 3" x 1/4" section modulus 9.58 cu. in., RBM 479,000

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.2, Data updated 12/25/2007 10:41:00 AM

©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 29, 2007 12:34:35 PM

Page 10

Prepared By:
Albert Li
Red Holman Pontiac GMC
35300 Ford Rd
Westland, MI 48185
Phone: (734) 721-1144
Fax: (734) 721-1780
Email: aclix@hotmail.com

2008 Fleet/Non-Retail GMC TC7500

STANDARD EQUIPMENT

STANDARD EQUIPMENT - 2008 Fleet/Non-Retail TC7C042 Regular Cab

- Fuel tank, single, 50-gallon (189.2L) fuel capacity - driver side, steel top tread plate, sump, drain and steps under cab on front passenger side. Provides clean back of cab and a black tethered fuel cap with gasoline engines, and a brass tethered fuel cap with diesel engines
- Steering, power - ZF variable ratio power
- Brake system, hydraulic, split - with 4-channel ABS disc-type Bosch Hydro Max high performance booster, tandem master cylinder provides independent front and rear circuits, front and rear disc Meritor calipers: 15 3/8" (391 mm) rotor diameter, 1 1/2" (39.1 mm) rotor thickness with (4) 2 1/2" (64 mm) diameter pistons with 8,000 lb. (3629 kg) front axle, (70 mm) diameter pistons with 10,000 lb. (4536 kg) front axle
- Parking brake, hand lever operated transmission mounted drum brake

SAFETY

- Brake system, hydraulic, split - with 4-channel ABS
- Air bags, Supplemental Inflatable Restraints not included
- Seat belt warning indicator
- Daytime running lamps

Report content is based on current data version referenced. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

GM AutoBook, Data Version: 133.2, Data updated 12/25/2007 10:41:00 AM
©Copyright 1986-2005 Chrome Systems Corporation. All rights reserved.

Customer File:

December 29, 2007 12:34:35 PM

Page 11



APPENDIX B

TRUCK QUESTIONNAIRE FORMS

ALL BIDDERS MUST COMPLETE AND RETURN A QUESTIONNAIRE FORM WITH THE BID FOR EACH TRUCK ITEM TO BE CONSIDERED FOR AWARD OF THAT ITEM. Bids submitted without an adequately completed questionnaire form for EACH TRUCK ITEM will not be considered for award of that item. It is the responsibility of each bidder to copy this form in sufficient quantity to submit to Purchasing Operations prior to the scheduled bid due date. A single form may apply to more than one item, simply list the item numbers to which the questionnaire applies in the appropriate space. If part of the questionnaire does not apply, simply indicate "not applicable" in those spaces.

NAME OF BIDDER: Red Holman Pontiac GMC ITEM NO(s). Spec # 3958-0164
 MAKE OF TRUCK: GMC MODEL: Topkick C7500 TC7042GVWR 27000 lbs.
 PAYLOAD: 17081 # W.B. 224 ✓ C.A. 153 ✓ C.E. 249.1"
 ENGINE: (GAS - DIESEL) Diesel ✓ MAKE: Gm/Isuzu Duramax MODEL: LYA, 7.8 SAE H.P. 215 ✓
 FUEL TANK(S) CAPACITY: 100 (GALS. TOTAL) TRANSMISSION: Allison 2350 6-spd ✓
 SPRING CAP. @ GROUND EACH: FRONT 4000 lbs. REAR 10500 lbs. AUX. Not Rated lbs.
 AXLES: FRONT 8000 lbs. REAR 19000 lbs. REAR RATIO 5.29
 ALTERNATOR: 100 amps. BATTERY Dual 750 cca.
 TIRE SIZE: FRONT 11R22.5G PR REAR 11R22.5G PR SINGLE _____ DUAL ✓ M&S Rear
 TIRE: MAKE Goodyear STYLE NO. TBD MFG. CODE XWL/YWL
 HOIST: MAKE N/A MODEL N/A INSTALLING CO. N/A
 BODY: MAKE N/A MODEL N/A INSTALLING CO. N/A
 POWER LIFT GATE: MAKE N/A MODEL N/A CAPACITY N/A lbs.
 PLATFORM SIZE: N/A

OTHER EQUIPMENT INSTALLED BY BODY EQUIPMENT SUPPLIER AND/OR COMMENTS

This information must be returned with the bid document to Purchasing Operations, on or before the bid due date and time. However, if returned separately, it must be received by Purchasing Operations on or before the bid due date and time, and must comply with the sealed bid instructions as outlined in the ITB.