

**CS Part 20. Demolition  
Compared With  
29 C.F.R. 1926 Subpart T – Demolition**

**As June 2015**

**Summary:** The significant differences between CS Part 20. Demolition and 29 C.F.R. 1926 Subpart T – Demolition are in:

- Demolition generally
- Material chutes and drops

The comparisons show only those provisions where MIOSHA rules are different than OSHA or where MIOSHA rules are not included in 29 C.F.R.

\*\*\*\*means there is a comparable OSHA rule to this paragraph

<b>MIOSHA</b>	<b>OSHA</b>
<p><b>R 408.42031 Demolition generally.</b>  <b>Rule 2031.</b> (1) Before the start of a demolition operation, an employer shall ensure that all of the following are done:</p> <p style="padding-left: 40px;">(a)****</p> <p style="padding-left: 40px;">(b) An employer shall ensure that there is a written report of the survey at the field office until the completion of the job. The report shall include information such as the name of the person conducting the survey, date of the survey, and hazardous substances and dangerous conditions found and their location. In an emergency situation, a survey is not required. If a field office does not exist at the demolition site, then an employer shall file the written report of the survey at the employer's main office.</p> <p style="padding-left: 40px;">(c) to (d)****</p> <p style="padding-left: 40px;">(2) to (8)****</p>	<p><b>No comparable OSHA provisions</b></p> <p>Equivalent</p> <p><b>No comparable OSHA provisions</b></p> <p>Equivalent</p> <p>Equivalent</p>
<p><b>R 408.42034 Material chutes and drops.</b>  <b>Rule 2034.</b> (1)****</p> <p style="padding-left: 40px;">(2) Where material is dropped through more than 1 level, the opening shall be enclosed between the upper and lower levels, an enclosed chute shall be provided, or the intermediate levels shall be barricaded as prescribed in subrule (1) of this rule. If the drop is more than 40 feet inside the building, only an enclosed opening or chute shall be used. The chute or enclosure shall extend through the ceiling of the receiving level.</p> <p style="padding-left: 40px;">(3) to (5)****</p>	<p>Equivalent</p> <p><b>No comparable OSHA provisions</b></p> <p>Equivalent</p>

Disclaimer:

Documents available from this server were prepared as a courtesy for informal guidance and assistance. This information is not intended to replace or supercede the actual MIOSHA standard or rule requirement.

Please reference the specific MIOSHA standard or rule for the actual rule requirement language.

All information published online by MIOSHA is subject to change without notice.

Every effort is made to ensure that the information provided at this site is accurate and up-to-date, but no legal responsibility is accepted for any errors, omissions, or misleading statement.