

APPENDIX A

Phase II ESA Boring Logs

Project: Michigan State Fairgrounds	Date Begin: 07/06/09	Date End: 07/06/09
Client: City of Grand Rapids		
Location: Grand Rapids, MI		
Drill Type: Geoprobe		
Crew Chief: RM		
Field Eng.: SY/JV		
Rev. By: <u>SY</u>		
Elevation: ft. +/-		
Datum:		
Notes: 59' W, 25' 5" S of NW Coliseum Corner Former Fuel Spill	Depth Drilled: 15.0 ft.	
	Plugging Rcrd: Backfilled with excavated soil cuttings and bentonite.	

	Type	Dia.	Groundwater, ft.	
Casing	Probe	2"	During	None
Sampler			End	NA
Core			Seepage	
Tube			Date	Depth, ft.

Component Percentages: Trace < 5%, Few 5-10%, Little 15-25%, Some 30-45%, Mostly 50-100% PID = Photoionization Detector (ppm)

Elev. FT.	Depth FT.	Sample Number	Recov. FT.	Penetration (Blows Per 6") ASTM D 1586	*Unified Soil Class.	*DESCRIPTION	REMARKS	PID
	1					3" HMA	1.0'+/-	
	2				SP	Brown poorly graded SAND with gravel; trace silty fines, mostly medium sand, little coarse sand, little gravel	Collected soil Sample B-3 (1.0'-2.0')	0
	3				CL			
	4		2.5			Brown lean CLAY with sand; little medium sand, trace gravel, moist, plastic		
	5							
	6							
	7							
	8		4.0			Grades to brown stiff sandy lean CLAY; some medium trace gravel at 1.6'		0
	9							
	10							
	11							
	12		4.0			Grades to grey at 12.0'		0
	13							
	14							
	15		3.0					0
	16					End of Boring at 15.0'		
	17							
	18							
	19							
	20							
	21							
	22							
	23							
	24							
	25							
	26							
	27							
	28							
	29							
	30							
	31							
	32							
	33							
	34							
	35							
	36							
	37							
	38							
	39							
	40							

* Visual estimate following ASTM D 2488 unless laboratory testing has been performed

Project: Michigan State Fairgrounds
 Client: City of Grand Rapids
 Location: Grand Rapids, MI
 Drill Type: Geoprobe
 Crew Chief: RM
 Field Eng.: SY/JV
 Rev. By: SY
 Elevation: ft. +/-
 Datum:

Date Begin: 07/06/09 Date End: 07/06/09

	Type	Dia.	Groundwater, ft.	
Casing	Probe	2"	During	None
Sampler			End	NA
Core			Seepage	
Tube			Date	Depth, ft.

Notes: 62' W, 67' S of NW Coliseum Corner
 Former Fuel Spill

Depth Drilled: 15.0 ft.

Plugging Rcrd: Backfilled with excavated soil cuttings and bentonite.

Component Percentages: Trace < 5%, Few 5-10%, Little 15-25%, Some 30-45%, Mostly 50-100% PID = Photoionization Detector (ppm)

Elev. FT.	Depth FT.	Sample Number	Recov. FT.	Penetration (Blows Per 6") ASTM D 1586	*Unified Soil Class.	*DESCRIPTION	REMARKS	PID
	1							
	2							
	3							
	4		4.0		SP	Silty SAND with gravel; little silty fines, mostly fine to medium sand, little gravel, fill	0.5'+/-	
	5						1.8'+/-	
	6						Collected soil	
	7						Sample B-4	
	8		4.0		CL	Poorly graded SAND with gravel; trace fines, mostly medium sand, little coarse sand, little fine gravel	(0.0'-1.8')	0
	9							
	10							
	11							
	12		4.0					0
	13							
	14							
	15		3.0					0
	16					Grades to grey at 12.0'		
	17							
	18							
	19							
	20							
	21							
	22							
	23							
	24							
	25							
	26							
	27							
	28							
	29							
	30							
	31							
	32							
	33							
	34							
	35							
	36							
	37							
	38							
	39							
	40							

* Visual estimate following ASTM D 2488 unless laboratory testing has been performed

Project: Michigan State Fairgrounds	Date Begin: 07/06/09	Date End: 07/06/09
Client: City of Grand Rapids		
Location: Grand Rapids, MI		
Drill Type: Geoprobe		
Crew Chief: RM		
Field Eng.: SY/JV		
Rev. By: <u>SY</u>		
Elevation: _____ ft. +/-		
Datum: _____		
Notes: 10' E, 10' N of SW fence corner SW Corner across from Solomon Gas Mart	Depth Drilled: 15.0 ft.	
	Plugging Rcrd: Backfilled with excavated soil cuttings and bentonite.	

	Type	Dia.	Groundwater, ft.	
Casing	Probe	2"	During	None
Sampler			End	NA
Core			Seepage	
Tube			Date	Depth, ft.

Component Percentages: Trace < 5%, Few 5-10%, Little 15-25%, Some 30-45%, Mostly 50-100% PID = Photoionization Detector (ppm)

Elev. FT.	Depth FT.	Sample Number	Recov. FT.	Penetration (Blows Per 6") ASTM D 1586	*Unified Soil Class.	*DESCRIPTION	REMARKS	PID
	1					3" HMA		
	2				SM	Brown silty SAND; some silt, little clay, some fine to medium sand	Collected soil Sample B-6 (0.5'-2.5')	
	3							
	4		3.0		CL	Brown stiff sandy lean CLAY; some medium sand, trace gravel		0
	5							
	6							
	7							
	8		4.0					0
	9							
	10							
	11							
	12		4.0			Grades to grey at 12.0'		0
	13							
	14							
	15		3.0					0
	16					End of Boring at 15.0'		
	17							
	18							
	19							
	20							
	21							
	22							
	23							
	24							
	25							
	26							
	27							
	28							
	29							
	30							
	31							
	32							
	33							
	34							
	35							
	36							
	37							
	38							
	39							
	40							

* Visual estimate following ASTM D 2488 unless laboratory testing has been performed

Project: Michigan State Fairgrounds
 Client: City of Grand Rapids
 Location: Grand Rapids, MI
 Drill Type: Geoprobe
 Crew Chief: RM
 Field Eng.: SY/JV
 Rev. By: SY
 Elevation: _____ ft. +/-
 Datum:
 Notes: 25' S, 77' E of fence
 Fmr Maintenance Bldg

Date Begin: 07/06/09		Date End: 07/06/09	
	Type	Dia.	Groundwater, ft.
Casing	Probe	2"	During None
Sampler			End NA
Core			Seepage
Tube			Date Depth, ft.
Depth Drilled: 14.0 ft.		Plugging Rcrd: Backfilled with excavated soil cuttings and bentonite.	

Component Percentages: Trace < 5%, Few 5-10%, Little 15-25%, Some 30-45%, Mostly 50-100% PID = Photoionization Detector (ppm)

Elev. FT.	Depth FT.	Sample Number	Recov. FT.	Penetration (Blows Per 6") ASTM D 1586	*Unified Soil Class.	*DESCRIPTION	REMARKS	PID
	1					3" HMA		
	2				GP	Poorly graded GRAVEL with sand; trace silty fines, some medium sand, little coarse sand	1.2+/- 2.5+/- Collected soil Sample B-7 (1.2'-2.0')	
	3							
	4		4.0			Black organic rich cinders; some coarse sand, some fine gravel, fill		0
	5							
	6				CL	Brown stiff sandy lean CLAY; some medium sand, trace gravel		
	7							
	8		3.0					0
	9							
	10							
	11		3.0					0
	12					Grades to grey at 12.0'		
	13							
	14		3.0					0
	15					End of Boring at 14.0'		
	16							
	17							
	18							
	19							
	20							
	21							
	22							
	23							
	24							
	25							
	26							
	27							
	28							
	29							
	30							
	31							
	32							
	33							
	34							
	35							
	36							
	37							
	38							
	39							
	40							

* Visual estimate following ASTM D 2488 unless laboratory testing has been performed

Project: Michigan State Fairgrounds	Date Begin: 07/06/09	Date End: 07/06/09
Client: City of Grand Rapids		
Location: Grand Rapids, MI		
Drill Type: Geoprobe		
Crew Chief: RM		
Field Eng.: SY/JV		
Rev. By: <u>SY</u>		
Elevation: ft. +/-		
Datum:		
Notes: 109' E, 42' N of fence Fmr Maintenance Bldg	Depth Drilled: 15.0 ft. Plugging Rcrd: Backfilled with excavated soil cuttings and bentonite.	

	Type	Dia.	Groundwater, ft.	
Casing	Probe	2"	During	None
Sampler			End	NA
Core			Seepage	
Tube			Date	Depth, ft.

Component Percentages: Trace < 5%, Few 5-10%, Little 15-25%, Some 30-45%, Mostly 50-100% PID = Photoionization Detector (ppm)

Elev. FT.	Depth FT.	Sample Number	Recov. FT.	Penetration (Blows Per 6") ASTM D 1586	*Unified Soil Class.	*DESCRIPTION	REMARKS	PID
	1					3" HMA	1.0'+/-	
	2				SP	Silty SAND with gravel; little fines, mostly fine to medium sand, little angular gravel	Collected soil Sample B-8 (1.0'-2.7')	
	3							
	4		3.8		GP	Poorly graded GRAVEL with sand; mostly angular gravel, some medium to coarse sand, black stained	2.7'+/-	0
	5				CL	Blue-grey stiff sandy lean CLAY; some medium sand, trace gravel, grades to brown at 4.0'		
	6							
	7							
	8		4.0					
	9							
	10							
	11							
	12		4.0			Grades to grey at 12.0'		0
	13							
	14							
	15		3.0					0
	16					End of Boring at 15.0'		
	17							
	18							
	19							
	20							
	21							
	22							
	23							
	24							
	25							
	26							
	27							
	28							
	29							
	30							
	31							
	32							
	33							
	34							
	35							
	36							
	37							
	38							
	39							
	40							

* Visual estimate following ASTM D 2488 unless laboratory testing has been performed

**MATERIALS
TESTING
CONSULTANTS, INC.**

**LOG
OF
BORING**

Project No.: 081563
Boring No.: B-9
Sheet: 1 of 1

Project: Michigan State Fairgrounds

Client: City of Grand Rapids

Location: Grand Rapids, MI

Drill Type: Geoprobe

Crew Chief: RM

Field Eng.: SY/JV

Rev. By: SY

Elevation: _____ ft. +/-

Datum:

Notes: 11' E, 43' S of SW transformer fence corner
Midway

Date Begin: 07/06/09

Date End: 07/06/09

	Type	Dia.	Groundwater, ft.	
Casing	Probe	2"	During	None
Sampler			End	NA
Core			Seepage	
Tube			Date	Depth, ft.

Depth Drilled: 13.0 ft.

Plugging Rcrd: Backfilled with excavated soil cuttings and bentonite.

Component Percentages: Trace < 5%, Few 5-10%, Little 15-25%, Some 30-45%, Mostly 50-100%

PID = Photoionization Detector (ppm)

Elev. FT.	Depth FT.	Sample Number	Recov. FT.	Penetration (Blows Per 6") ASTM D 1586	*Unified Soil Class.	*DESCRIPTION	REMARKS	PID
	1					3" HMA	0.3'+/-	
	2				CL	Brown stiff sandy lean CLAY; some fine sand, trace gravel	1.5'+/-	Collected soil Sample B-9 (0.0'-1.8')
	3				CL		1.8'+/-	
	4		3.8			Black stained sandy lean CLAY; some medium sand few angular gravel		0
	5							
	6				CL	Brown stiff sandy lean CLAY; some medium sand, trace gravel		
	7							
	8		4.0					0
	9							
	10							
	11		3.0					0
	12							
	13		2.0			Grades to grey at 12.0'		0
	14					End of Boring at 13.0'		
	15							
	16							
	17							
	18							
	19							
	20							
	21							
	22							
	23							
	24							
	25							
	26							
	27							
	28							
	29							
	30							
	31							
	32							
	33							
	34							
	35							
	36							
	37							
	38							
	39							
	40							

* Visual estimate following ASTM D 2488 unless laboratory testing has been performed

MATERIALS TESTING CONSULTANTS, INC.	LOG OF BORING	Project No.: 081563 Boring No.: B-11 Sheet: 1 of 1
--	------------------------------	--

Project: Michigan State Fairgrounds	Date Begin: 07/07/09	Date End: 07/07/09
Client: City of Grand Rapids		
Location: Grand Rapids, MI		
Drill Type: Geoprobe		
Crew Chief: RM		
Field Eng.: SY/JV		
Rev. By: <u>SY</u>		
Elevation: ft. +/-		
Datum:		
Notes: 32' S, 53' W of SW corner light pole Confirmed UST Release Area	Depth Drilled: 16.0 ft.	Plugging Rcrd: Backfilled with excavated soil cuttings and bentonite.

	Type	Dia.	Groundwater, ft.	
Casing	Probe	2"	During	None
Sampler			End	NA
Core			Seepage	
Tube			Date	Depth, ft.

Component Percentages: Trace < 5%, Few 5-10%, Little 15-25%, Some 30-45%, Mostly 50-100% PID = Photoionization Detector (ppm)

Elev. FT.	Depth FT.	Sample Number	Recov. FT.	Penetration (Blows Per 6") ASTM D 1586	*Unified Soil Class.	*DESCRIPTION	REMARKS	PID
	1					3" HMA		
	2				SP	Brown poorly graded SAND with gravel; mostly medium sand, little coarse sand, little fine gravel	1.2'+/- Collected soil Sample B-11 (0.3'-1.2')	
	3							
	4		3.6		CL	Dark grey stiff sandy lean CLAY; some medium sand, trace gravel, grades to brown at 3.0'		0
	5							
	6							
	7							
	8		4.0					0
	9							
	10							
	11							
	12		4.0			Grades to grey at 12.0'		0
	13							
	14							
	15							
	16		4.0					0
	17					End of Boring at 16.0'		
	18							
	19							
	20							
	21							
	22							
	23							
	24							
	25							
	26							
	27							
	28							
	29							
	30							
	31							
	32							
	33							
	34							
	35							
	36							
	37							
	38							
	39							
	40							

* Visual estimate following ASTM D 2488 unless laboratory testing has been performed

Project: Michigan State Fairgrounds	Date Begin: 07/07/09	Date End: 07/07/09
Client: City of Grand Rapids		
Location: Grand Rapids, MI		
Drill Type: Geoprobe		
Crew Chief: RM		
Field Eng.: SY/JV		
Rev. By: <u>SY</u>		
Elevation: ft. +/-		
Datum:		
Notes: 15' S, 22' W of SW corner light post Confirmed UST Release Area	Depth Drilled: 14.0 ft.	Plugging Rcrd: Backfilled with excavated soil cuttings and bentonite.

	Type	Dia.	Groundwater, ft.	
Casing	Probe	2"	During	None
Sampler			End	NA
Core			Seepage	
Tube			Date	Depth, ft.

Component Percentages: Trace < 5%, Few 5-10%, Little 15-25%, Some 30-45%, Mostly 50-100% PID = Photoionization Detector (ppm)

Elev. FT.	Depth FT.	Sample Number	Recov. FT.	Penetration (Blows Per 6") ASTM D 1586	*Unified Soil Class.	*DESCRIPTION	REMARKS	PID
	1					3" HMA		
	2				SR-SM	Black poorly graded SAND with silt; few fines, mostly medium sand, few coarse sand, few fine gravel, moist	Collected soil Sample B-12 (3.5'-4.5')	0
	3				CL			
	4		3.8			Brown stiff gravelly lean CLAY; some fine gravel, grades with less gravel		
	5				SP	Grey poorly graded SAND with gravel; mostly medium sand, some coarse sand, few fine gravel, moist to wet	4.0'+/- 4.5'+/-	0
	6				CL			
	7							
	8		4.0			Brown stiff sandy lean CLAY; some medium sand, trace gravel		0
	9							
	10							
	11		3.0					
	12					Grades to grey at 12.0'		0
	13							
	14		3.0					
	15					End of Boring at 14.0'	Probe refusal	
	16							
	17							
	18							
	19							
	20							
	21							
	22							
	23							
	24							
	25							
	26							
	27							
	28							
	29							
	30							
	31							
	32							
	33							
	34							
	35							
	36							
	37							
	38							
	39							
	40							

* Visual estimate following ASTM D 2488 unless laboratory testing has been performed

MATERIALS TESTING CONSULTANTS, INC.	LOG OF BORING	Project No.: 081563 Boring No.: B-13 Sheet: 1 of 1
--	------------------------------	--

Project: Michigan State Fairgrounds	Date Begin: 07/07/09	Date End: 07/07/09	
Client: City of Grand Rapids			
Location: Grand Rapids, MI			
Drill Type: Geoprobe			
Crew Chief: RM			
Field Eng.: SY/JV			
Rev. By: <u>SY</u>			
Elevation: _____ ft. +/-			
Datum:			
Notes: 28' S, 1.5' W of SW corner light post Confirmed UST Release Area			

	Type	Dia.	Groundwater, ft.	
Casing	Probe	2"	During	None
Sampler			End	NA
Core			Seepage	
Tube			Date	Depth, ft.

Depth Drilled: 14.0 ft.
Plugging Rcrd: Backfilled with excavated soil cuttings and bentonite.

Component Percentages: Trace < 5%, Few 5-10%, Little 15-25%, Some 30-45%, Mostly 50-100% PID = Photoionization Detector (ppm)

Elev. FT.	Depth FT.	Sample Number	Recov. FT.	Penetration (Blows Per 6") ASTM D 1586	*Unified Soil Class.	*DESCRIPTION	REMARKS	PID
	1					3" HMA		
	2				SP	Poorly graded SAND with silt; few silty fines,	0.7'+/-	
	3				SP-SM	mostly medium sand, trace gravel	1.4'+/-	
	4		3.8			Silty SAND with gravel; some silty fines,	Collected soil	
	5				CL	mostly medium sand, little gravel	Sample B-13	
	6					Brown stiff sandy lean CLAY; some medium sand,	(0.7'-1.4')	0
	7					trace gravel		
	8		4.0					0
	9							
	10							
	11		3.0					0
	12					Grades to grey at 12.0'		
	13							
	14		3.0					0
	15					End of Boring at 14.0'	Probe refusal	
	16							
	17							
	18							
	19							
	20							
	21							
	22							
	23							
	24							
	25							
	26							
	27							
	28							
	29							
	30							
	31							
	32							
	33							
	34							
	35							
	36							
	37							
	38							
	39							
	40							

* Visual estimate following ASTM D 2488 unless laboratory testing has been performed

MATERIALS TESTING CONSULTANTS, INC.	LOG OF BORING	Project No.: 081563 Boring No.: B-14 Sheet: 1 of 1
--	------------------------------	--

Project: Michigan State Fairgrounds	Date Begin: 07/07/09	Date End: 07/07/09		
Client: City of Grand Rapids				
Location: Grand Rapids, MI				
Drill Type: Geoprobe				
Crew Chief: RM				
Field Eng.: SY/JV				
Rev. By: <u>SY</u>				
Elevation: ft. +/-				
Datum:				
Notes: 53' S, 24' W of SW corner light post Confirmed UST Release Area	Depth Drilled: 14.0 ft.		Plugging Rcrd: Backfilled with excavated soil cuttings and bentonite.	

	Type	Dia.	Groundwater, ft.	
Casing	Probe	2"	During	None
Sampler			End	NA
Core			Seepage	
Tube			Date	Depth, ft.

Component Percentages: Trace < 5%, Few 5-10%, Little 15-25%, Some 30-45%, Mostly 50-100% PID = Photoionization Detector (ppm)

Elev. FT.	Depth FT.	Sample Number	Recov. FT.	Penetration (Blows Per 6") ASTM D 1586	*Unified Soil Class.	*DESCRIPTION	REMARKS	PID
	1					3" HMA		
	2				SP-SM	Poorly graded SAND with silt; few silty fines,	0.7'+/-	
	3				SM	mostly medium sand, trace gravel	2.0'+/-	Collected soil
	4		3.8		CL	Silty SAND; little silty fines, mostly fine sand, moist		Sample B-14
	5					Brown stiff sandy lean CLAY; some medium sand,		(0.7'-2.0')
	6					trace gravel		0.7
	7							
	8		4.0					0
	9							
	10							
	11		3.0					0
	12					Grades to grey at 12.0'		
	13							
	14		3.0					0
	15					End of Boring at 14.0'	Probe refusal	
	16							
	17							
	18							
	19							
	20							
	21							
	22							
	23							
	24							
	25							
	26							
	27							
	28							
	29							
	30							
	31							
	32							
	33							
	34							
	35							
	36							
	37							
	38							
	39							
	40							

* Visual estimate following ASTM D 2488 unless laboratory testing has been performed

MATERIALS TESTING CONSULTANTS, INC.	LOG OF BORING	Project No.: 081563 Boring No.: B-15 Sheet: 1 of 1
--	------------------------------	--

Project: Michigan State Fairgrounds	Date Begin: 07/07/09	Date End: 07/07/09		
Client: City of Grand Rapids				
Location: Grand Rapids, MI				
Drill Type: Geoprobe				
Crew Chief: RM				
Field Eng.: SY/JV				
Rev. By: SY				
Elevation: ft. +/-				
Datum:				
Notes: 11' S, 14' W of fence post, 4' W of gas tank	Depth Drilled: 10.0 ft.			
Boring located in stressed vegetation	Plugging Rcrd: Backfilled with excavated soil cuttings and bentonite.			
Gas AST				

	Type	Dia.	Groundwater, ft.	
Casing	Probe	2"	During	None
Sampler			End	NA
Core			Seepage	
Tube			Date	Depth, ft.

Component Percentages: Trace < 5%, Few 5-10%, Little 15-25%, Some 30-45%, Mostly 50-100% PID = Photoionization Detector (ppm)

Elev. FT.	Depth FT.	Sample Number	Recov. FT.	Penetration (Blows Per 6") ASTM D 1586	*Unified Soil Class.	*DESCRIPTION	REMARKS	PID
	1				OL	Topsoil; black, organic, rich	0.3'+/- gasoline odor	10
	2				CL	Dark grey stiff sandy lean CLAY; mostly medium sand, trace gravel	1.2'+/-	27
	3				SM		3.0'+/- gasoline odor	33
	4		3.7			Poorly graded SAND with silt; mostly medium sand, grades to silt, moist to wet		
	5						Collected soil	
	6				CL	Brown stiff sandy lean CLAY; some medium sand, trace gravel	Sample B-15	
	7						(1.0'-3.0')	
	8		4.0					0
	9							
	10		2.0				PID 72 in hole	
	11					End of Boring at 10.0'	Probe refusal	
	12							
	13							
	14							
	15							
	16							
	17							
	18							
	19							
	20							
	21							
	22							
	23							
	24							
	25							
	26							
	27							
	28							
	29							
	30							
	31							
	32							
	33							
	34							
	35							
	36							
	37							
	38							
	39							
	40							

* Visual estimate following ASTM D 2488 unless laboratory testing has been performed

Project: Michigan State Fairgrounds	Date Begin: 07/07/09	Date End: 07/07/09		
Client: City of Grand Rapids				
Location: Grand Rapids, MI				
Drill Type: Geoprobe				
Crew Chief: RM				
Field Eng.: SY/JV				
Rev. By: <u>SY</u>				
Elevation: _____ ft. +/-				
Datum:				
Notes: 14' N of B-15 Diesel AST				

	Type	Dia.	Groundwater, ft.	
Casing	Probe	2"	During	None
Sampler			End	NA
Core			Seepage	
Tube			Date	Depth, ft.

Depth Drilled: 10.0 ft.
Plugging Rcrd: Backfilled with excavated soil cuttings and bentonite.

Component Percentages: Trace < 5%, Few 5-10%, Little 15-25%, Some 30-45%, Mostly 50-100% PID = Photoionization Detector (ppm)

Elev. FT.	Depth FT.	Sample Number	Recov. FT.	Penetration (Blows Per 6") ASTM D 1586	*Unified Soil Class.	*DESCRIPTION	REMARKS	PID
	1					Topsoil; black, organic, rich		
	2				CL	Dark grey stiff sandy lean CLAY; mostly medium sand, trace gravel	Collected soil Sample B-16 (1.0'-2.5')	0
	3				SM			
	4		3.8					
	5					Poorly graded SAND with silt; mostly medium sand, grades to silt, moist to wet		
	6				CL	Brown stiff sandy lean CLAY; some medium sand, trace gravel		0
	7		3.0					
	8							0
	9							0
	10		3.0					0
	11					End of Boring at 10.0'	Probe refusal	
	12							
	13							
	14							
	15							
	16							
	17							
	18							
	19							
	20							
	21							
	22							
	23							
	24							
	25							
	26							
	27							
	28							
	29							
	30							
	31							
	32							
	33							
	34							
	35							
	36							
	37							
	38							
	39							
	40							

* Visual estimate following ASTM D 2488 unless laboratory testing has been performed

Project: Michigan State Fairgrounds	Date Begin: 07/07/09	Date End: 07/07/09		
Client: City of Grand Rapids				
Location: Grand Rapids, MI				
Drill Type: Geoprobe				
Crew Chief: RM				
Field Eng.: SY/JV				
Rev. By: <u>SY</u>				
Elevation: ft. +/-				
Datum:				
Notes: 116' W, 8' S of SE corner of Dodge Pavillion Dodge Pavillion UST				

	Type	Dia.	Groundwater, ft.	
Casing	Probe	2"	During	None
Sampler			End	NA
Core			Seepage	
Tube			Date	Depth, ft.

Depth Drilled: 11.0 ft.
Plugging Rcrd: Backfilled with excavated soil cuttings and bentonite.

Component Percentages: Trace < 5%, Few 5-10%, Little 15-25%, Some 30-45%, Mostly 50-100% PID = Photoionization Detector (ppm)

Elev. FT.	Depth FT.	Sample Number	Recov. FT.	Penetration (Blows Per 6") ASTM D 1586	*Unified Soil Class.	*DESCRIPTION	REMARKS	PID
	1					3" HMA	0.6'+/-	
	2					Concrete	1.2'+/-	
	3				SP	Black poorly graded SAND with gravel; trace fines, mostly medium sand, little coarse sand, little fine gravel, moist	Collected soil Sample B-17 (0.6'-1.2')	0
	4		3.8					
	5				CL			
	6				Black stiff sandy lean CLAY; some medium sand, trace gravel, black to grey, grades to brown at 6.0'			
	7							
	8		4.0					0
	9							
	10							
	11		3.0					0
	12					End of Boring at 11.0'	Probe refusal	
	13							
	14							
	15							
	16							
	17							
	18							
	19							
	20							
	21							
	22							
	23							
	24							
	25							
	26							
	27							
	28							
	29							
	30							
	31							
	32							
	33							
	34							
	35							
	36							
	37							
	38							
	39							
	40							

* Visual estimate following ASTM D 2488 unless laboratory testing has been performed

Project: Michigan State Fairgrounds	Date Begin: 07/07/09	Date End: 07/07/09	
Client: City of Grand Rapids			
Location: Grand Rapids, MI			
Drill Type: Geoprobe			
Crew Chief: RM			
Field Eng.: SY/JV			
Rev. By: <u>SY</u>			
Elevation: ft. +/-			
Datum:			
Notes: 94' W, 8' S of SE corner Dodge Pavillion Dodge Pavillion UST	Depth Drilled: 11.0 ft. Plugging Rcrd: Backfilled with excavated soil cuttings and bentonite.		

	Type	Dia.	Groundwater, ft.	
Casing	Probe	2"	During	None
Sampler			End	NA
Core			Seepage	
Tube			Date	Depth, ft.

Component Percentages: Trace < 5%, Few 5-10%, Little 15-25%, Some 30-45%, Mostly 50-100% PID = Photoionization Detector (ppm)

Elev. FT.	Depth FT.	Sample Number	Recov. FT.	Penetration (Blows Per 6") ASTM D 1586	*Unified Soil Class.	*DESCRIPTION	REMARKS	PID
	1					3" HMA		
	2					Concrete	0.6'+/- 1.2'+/-	
	3				SP	Black poorly graded SAND with gravel; trace fines, mostly medium sand, little coarse sand, little fine gravel, moist	Collected soil Sample B-18 (0.6'-1.2')	0
	4		3.8					
	5				CL	Black stiff sandy lean CLAY; some medium sand, trace gravel, black to grey		
	6					Grades to brown at 6.0'		
	7							
	8		4.0					0
	9							
	10							
	11		3.0					0
	12					End of Boring at 11.0'	Probe refusal	
	13							
	14							
	15							
	16							
	17							
	18							
	19							
	20							
	21							
	22							
	23							
	24							
	25							
	26							
	27							
	28							
	29							
	30							
	31							
	32							
	33							
	34							
	35							
	36							
	37							
	38							
	39							
	40							

* Visual estimate following ASTM D 2488 unless laboratory testing has been performed