

OH Rule 3402 Control Measures in Pulp, Paper, and Paperboard Mills
OH Rule 3403 Control Measures in Textiles
OH Rule 3404 Control Measures in Bakery Equipment
OH Rule 3406 Control Measures in Sawmills
Compared With
29 C.F.R. 1910.261 Pulp, paper, and paperboard mills.
29 C.F.R. 1910.262 Textiles.
29 C.F.R. 1910.263 Bakery equipment.
29 C.F.R. 1910.265 Sawmills.

Summary: OH Rule 3402 Control Measures in Pulp, Paper, and Paperboard Mills is similar to 29 C.F.R.: 1910.261 Pulp, paper, and paperboard mills, except for the following:

- Applicability.
- Inspecting and repairing digester.
- Vessel entry.

Summary: OH Rule 3403 Control Measures in Textiles is similar to 29 C.F.R. 1910.262 Textiles, except for the following:

- Applicability.
- Workroom ventilation.

Summary: OH Rule 3404 Control Measures in Bakery Equipment is similar to 29 C.F.R. 1910.263 Bakery equipment, except for the following:

- Applicability.
- Miscellaneous equipment.

Summary: OH Rule 3406 Control Measures in Sawmills is similar to 29 C.F.R. 1910.265 Sawmills, except for the following:

- Applicability.
- Exhaust pipes.
- Log handling, sorting and storage.

The below comparison show only those provisions where MIOSHA rules are different than OSHA or where MIOSHA rules are not included in 29 C.F.R.

****means there is a comparable OSHA rule to this paragraph

MIOSHA	OSHA
OH Rule 3402 Control Measures in Pulp, Paper, and Paperboard Mills	
(1) Applicability. This rule applies only to those establishments covered by Rule 5001 and supplements general occupational health standards pursuant to Rule 1106(3).	No comparable OSHA provisions

MIOSHA	OSHA
<p>(2)****</p> <p>(a) Safety Code for Ventilation and Operation of Open-Surface Tanks, Z9.1-1951.</p> <p>(b) Fundamentals Governing the Design and Operation of Local Exhaust Systems, Z9.2-1960.</p> <p>(c)****</p> <p>(d) Practices for Respiratory Protection, Z88.2-1969.</p> <p>(3)(a) to 4(a)****</p> <p>(b) Inspecting and repairing digester. The concentration of lead dust in the air shall not exceed the limits specified in Chapter II.</p> <p>(4)(c) to (5)(b)****</p> <p>(6) Vessel entry. See Rule 3303(3) for specific vessel entry procedures supplementing the general procedures of Rules 3301 and 3302.</p>	<p>Equivalent</p> <p>No comparable OSHA provisions</p> <p>No comparable OSHA provisions</p> <p>Equivalent</p> <p>No comparable OSHA provisions</p> <p>Equivalent</p> <p>1910.261(g)(15)(iv) All employees entering digesters for inspection or repair work shall be provided with protective headgear. Eye protection and dust masks shall be provided to workmen while the old brick lining is being removed, in accordance with American National Standards, Z87.1 - 1968, Z88.2 - 1969, and Z99.1 - 1969.</p> <p>Equivalent</p> <p>No comparable OSHA provisions</p>
<p>OH Rule 3403 Control Measures in Textiles</p>	
<p>(1) Applicability. This rule applies only to those establishments and processes subject to Rule 5002 and supplements the general occupational health standards pursuant to Rule 1106(3).</p> <p>(2) to (4) ****</p> <p>(5) Workroom ventilation. In all workrooms in which potentially toxic substances are used, the maximum allowable concentrations listed in Chapter II shall be maintained. Open-surface tanks shall conform to the requirements of Rule 3220.</p>	<p>No comparable OSHA provisions</p> <p>Equivalent</p> <p>No comparable OSHA provisions</p>

MIOSHA	OSHA
OH Rule 3404 Control Measures in Bakery Equipment	
<p>(1) Applicability. This rule applies to all equipment, processes and establishments subject to Rule 5003.</p> <p>(2) to (3)****</p> <p>(4) Miscellaneous equipment. (a) Pan-washing tanks. Power-ventilated exhaust hoods shall be provided over the tanks.</p> <p>(b)(i) to (5)****</p>	<p>No comparable OSHA provisions</p> <p>Equivalent</p> <p>No comparable OSHA provisions</p> <p>Equivalent</p>
OH Rule 3406 Control Measures in Sawmills	
<p>(1) Applicability. This rule applies to all sawmill operations subject to Rule 5005.</p> <p>(2)(a) to (c)(iii)****</p> <p>(iv) Exhaust pipes. Exhaust pipes shall be of such construction and internal dimensions as to minimize the possibility of clogging. They should be accessible for cleaning.</p> <p>(v)****</p> <p>(3) Log handling, sorting, and storage. Log unloading and storage areas. Pond boats and rafts. Adequate ventilation shall be provided for the cabin area on enclosed cabin-type boats to prevent accumulation of harmful gases or vapors.</p>	<p>No comparable OSHA provisions</p> <p>Equivalent</p> <p>No comparable OSHA provisions</p> <p>Equivalent</p> <p>1910.265(d) Log handling, sorting, and storage 1910.265(d)(2) Log unloading and storage areas - 1910.265(d)(2)(iv) Pond boats and rafts. The applicable provisions of the Standard for Fire Protection for Motorcraft, NFPA No. 302-1968, which is incorporated by reference as specified in Sec. 1910.6, shall be complied with.</p>

Disclaimer:

Documents available from this server were prepared as a courtesy for informal guidance and assistance. This information is not intended to replace or supercede the actual MIOSHA standard or rule requirement. Please reference the specific MIOSHA standard or rule for the actual rule requirement language.

All information published online by MIOSHA is subject to change without notice. Every effort is made to ensure that the information provided at this site is accurate and up-to-date, but no legal responsibility is accepted for any errors, omissions, or misleading statement.