


Prepared For: **3958 - 0134**  
~~2958 - 0135~~

Prepared By:  
 Administrator  
 Your Dealership Name Here



**Selected Options**

**2011 Ford F-650 Pro Loader**

Regular Cab XL Kick-Up Frame (F6G)

<b>Vehicle Snapshot</b>	<b>Engine:</b> Cummins (6.7L) ISB 200 HP @ 2300 RPM, Governed @ 2600 RPM <b>Transmission:</b> Allison 2500 5-Speed, RDS Series On-Off <b>Rear Axle Ratio:</b> 0.00 <b>Brakes:</b> Hydraulic Brakes - Quadraulic Split System for 64mm Diameter Pistons - 19.5" Wheels <b>GVWR:</b> 22,000 lbs
-------------------------	---

Code	Description
F6G	Base Vehicle Price (F6G)
<b>Wheelbase</b>	
194WB	194" Wheelbase/120" CA/75" AF/308" OAL
<b>1 - Frame</b>	
537	<b>Single Channel - Tapered 10.75 SM, 80,000 PSI</b> <i>High strength low alloy steel; 9.125" x 3.062" x 0.312" (231.8mm x 77.8mm x 8.0mm). With transition to 6.500" x 3.062" x 0.312" (165.1mm x 77.8mm x 8.0mm) 386.7" (9822mm) maximum OAL.</i>
<b>2 - Axle, Front/Suspension, Front</b>	
43G	<b>I-Beam Type - 8,500 lb. Cap. Non-Driving - Meritor MFS-08-153B</b> <i>Steering Wheel - Two Spoke, Black PVC, 15.5" Dia. ; Includes tilt and cruise controls. Includes Ross TAS-40 integral power steering.</i>
61B	<b>Taper-Leaf Springs, Parabolic - 8,500 lb. Cap</b> <i>Includes shock absorbers.</i>
<b>3 - Axle, Rear/Suspension, Rear</b>	
471	<b>13,500 lb. Single-Speed - Meritor MS-17-14X-3DFL</b> <i>Single reduction with 190 wheel ends. NOTE: When specifying an axle ratio, check performance guidelines for startability and gradeability.</i>
68W	<b>Multi-Leaf Springs - Vari-Rate, High Rate</b>

Prices and content availability as shown, are subject to change and should be treated as estimates only. Actual be estimate because of special local pricing, availability or pricing adjustments not reflected in the dealer's computer Reference CT05208691 12/23/2009