


Prepared For:

3958-0135

Prepared By:

Administrator
Your Dealership Name Here



Selected Options

2011 Ford F-650

Regular Cab XL (F6F)

Vehicle Snapshot	Engine: Cummins (6.7L) ISB 200 HP @ 2300 RPM, Governed @ 2600 RPM Transmission: Allison 2500 5-Speed, RDS Series On-Off Rear Axle Ratio: 0.00 Brakes: Hydraulic Brakes - Quadraulic Split System for 70mm Diameter Pistons - 22.5" Wheels GVWR: 25,999 lbs
-------------------------	---

Code	Description
F6F	Base Vehicle Price (F6F)
Wheelbase	
194WB	194" Wheelbase/120" CA/75" AF/308" OAL
1 - Frame	
534	Single Channel - Straight 'C' 12.64 SM, 50,000 PSI <i>High strength low alloy steel; 10.125" x 3.062" x 0.312" (257.2mm x 77.8mm x 8.0mm) 437.9" (11122mm) maximum OAL.</i>
20Y	Special Rating GVWR - Limited to 25,999 lb. GVWR
2 - Axle, Front/Suspension, Front	
43G	I-Beam Type - 8,500 lb. Cap. Non-Driving - Meritor MFS-08-153B <i>Steering Wheel - Two Spoke, Black PVC, 15.5" Dia. : Includes tilt and cruise controls. Includes Ross TAS-40 integral power steering.</i>
61B	Taper-Leaf Springs, Parabolic - 8,500 lb. Cap <i>Includes shock absorbers.</i>
3 - Axle, Rear/Suspension, Rear	
473	17,500 lb. Single-Speed - Meritor MS-17-14X-3DLF <i>Single reduction with 190 wheel ends. NOTE: When specifying an axle ratio, check performance guidelines for startability and gradeability.</i>

Prices and content availability as shown, are subject to change and should be treated as estimates only. Actual estimate because of special local pricing, availability or pricing adjustments not reflected in the dealer's computer Reference CT05208691 12/23/2009