


Prepared For:

McDeal

Prepared By:

Administrator
Your Dealership Name Here

3958-0164D



Selected Options

2011 Ford F-750

Regular Cab XL (F7F)

Vehicle Snapshot

Engine: Cummins (6.7L) ISB 220 HP @ 2300 RPM, Governed @ 2600 RPM
Transmission: Allison 2500 5-Speed, HS Series
Rear Axle Ratio: 5.57
Brakes: Air Brakes - Straight Truck w/16.5x7.0 Rear Pads - 22.5" Wheels
GVWR: 31,000 lbs

Code	Description
F7F	Base Vehicle Price (F7F)
Wheelbase	
194WB	194" Wheelbase/120" CA/75" AF/308" OAL
1 - Frame	
535	Single Channel - Straight 'C' 15.14 SM, 80,000 PSI - For GVW Ratings 33,000 lbs. Maximum <i>High strength low alloy steel; 10.250" x 3.092" x 0.375" (260.4mm x 78.5mm x 9.5mm), 437.9" (11122mm) maximum OAL.</i>
2 - Axle, Front/Suspension, Front	
43H	I-Beam Type - 10,000 lb. Cap. Non-Driving - Meritor MFS-10-122A <i>Steering Wheel - Two Spoke, Black PVC, 17.5" Dia. ; Includes Ross TAS-66 power steering gear.</i>
61C	Taper-Leaf Springs, Parabolic - 10,000 lb. Cap <i>Includes shock absorbers.</i>
3 - Axle, Rear/Suspension, Rear	
475	21,000 lb. Single-Speed - Meritor MS-21-14X-3DLF <i>Single reduction with 190 wheel ends. NOTE: When specifying an axle ratio, check performance guidelines for startability and gradeability.</i>
68R	Multi-Leaf Springs - Vari-Rate Suspension 23,500 lb. Cap <i>Includes 4500 lb. auxiliary rubber spring.</i>

Prices and content availability as shown, are subject to change and should be treated as estimates only. Actual estimate because of special local pricing, availability or pricing adjustments not reflected in the dealer's comp Reference CT05208691 12/23/2009

Printed on September 12, 2010 at 20:25

Price Level: 115

QuoteID: <None>