

Prepared For:
STATE OF MICHIGAN
OFFICE OF PURCHASING
DEPT. OF MGT. & BUDGET
LANSING, MI 48909-
(517)373 - 0330
Reference ID: MiDEAL- 0178D
MiDEAL 3958-0178D.

Presented By:
TRI COUNTY INTL TRUCKS
Mark J Caracciolo
5701 WYOMING St.
DEARBORN MI 48126 -
(313)584-7090



Model Profile
2011 7600 SBA 6X4 2010 (SF667)

APPLICATION:	Low-Boy Tractor
MISSION:	Requested GCWR: 80000. Calc. GVWR: 52000 Calc. Start / Grade Ability: 14.60% / 0.99% @ 55 MPH Calc. Geared Speed: 76.9 MPH
FUEL ECONOMY:	5.41 MPG @ 55 MPH
DIMENSION:	Wheelbase: 160.00, CA: 92.90, Axle to Frame: 57.00
ENGINE, DIESEL:	{MaxxFORCE 11} EPA 10, 330 HP @ 1700 RPM, 1250 lb-ft Torque @ 1000 RPM, 2100 RPM Governed Speed, 330 Peak HP (Max)
TRANSMISSION, MANUAL:	{Fuller FRO-13210C} 10-Speed Manual, With Overdrive, With Air Shift
CLUTCH:	{Eaton Fuller EP1552} Easy-Pedal Plus, Two-Plate, Cast Angle Spring; Ceramic, 15.5" Diameter, Soft Clutch 7-Spring Damper, Mechanical Pull-Type Control, With Kwik-Adjust(Manual) Feature, 1700 lb-ft Torque Capacity
AXLE, FRONT NON-DRIVING:	{Meritor MFS-12-143A} Wide Track, I-Beam Type, 12,000-lb Capacity
AXLE, REAR, TANDEM:	{Dana Spicer DS405/RS405} Single Reduction, 40,000-lb Capacity, 200 Wheel Ends Gear Ratio: 4.63
CAB:	Conventional
TIRE, FRONT:	(2) 11R22.5 G661 HSA (GOODYEAR) 497 rev/mile, load range H, 16 ply
TIRE, REAR:	(8) 12R22.5 UNISTEEL G177 (GOODYEAR) 478 rev/mile, load range H, 16 ply
SUSPENSION, REAR, TANDEM:	{International} 4-Spring Type, Multileaf, 52" Axle Spacing; 40,000-lb Capacity
PAINT:	Cab schematic 100GS Location 1: 0311, Omaha Orange (Std) Chassis schematic N/A

<u>Code</u>	<u>Description</u>	<u>F/R Wt</u> (lbs)	<u>Tot Wt</u> (lbs)
SF66700	Base Chassis, Model 7600 SBA 6X4 2010 with 160.00 Wheelbase, 92.90 CA, and 57.00 Axle to Frame.	7815/6963	14778
1570	TOW HOOK, FRONT (2) Frame Mounted	8/0	8
1616	FRAME RAILS WITH TAPERED REAR	0/0	0
1CAG	FRAME RAILS Heat Treated Alloy Steel (120,000 PSI Yield); 10.250" x 3.610" x 0.375" (260.4mm x 91.7mm x 9.5mm); 456.0" (11582mm) Maximum OAL	110/93	203
1LLA	BUMPER, FRONT Steel, Swept Back	0/0	0
	<u>Includes</u> : BUMPER, FRONT Powder Coated Gray (Argent) Color		
1WHN	WHEELBASE RANGE 152" (385cm) Through and Including 181" (460cm)	0/0	0
1WLX	DECK PLATE Aluminum; Bustin, (2) Section Flush Mounted	0/0	0
2ARW	AXLE, FRONT NON-DRIVING {Meritor MFS-12-143A} Wide Track, I-Beam Type, 12,000-lb Capacity	11/0	11
	<u>Notes</u> : The following features should be considered when calculating Front GAWR: Front Axles; Front Suspension; Brake System; Brakes, Front Air Cam; Wheels; Tires.		
3ADC	SUSPENSION, FRONT, SPRING Parabolic, Taper Leaf; 12,000-lb Capacity; With Shock Absorbers	0/0	0
	<u>Includes</u> : SPRING PINS Rubber Bushings, Maintenance-Free		
	<u>Notes</u> : The following features should be considered when calculating Front GAWR: Front Axles; Front Suspension; Brake System; Brakes, Front Air Cam; Wheels; Tires.		
4092	BRAKE SYSTEM, AIR Dual System for Tractor Applications	0/0	0
	<u>Includes</u> : BRAKE LINES Color and Size Coded Nylon : DRAIN VALVE Twist-Type : GAUGE, AIR PRESSURE (2) Air 1 and Air 2 Gauges; Located in Instrument Cluster : GLAD HANDS (2) One for Service and One for Emergency; Trailer Hoses from Cab : HAND CONTROL VALVE, AIR Mounted on Steering Column : HOSE TENDER Back of Cab Mounted : PARKING BRAKE CONTROL Yellow and Red Knobs, Located on Instrument Panel : PARKING BRAKE VALVE Combination Valve for Tractor and Trailer : QUICK RELEASE VALVE Bendix On Rear Axle for Spring Brake Release: 1 for Forward Rear Axle : SLACK ADJUSTERS, FRONT Automatic : SLACK ADJUSTERS, REAR Automatic : SWITCH, AUXILIARY Interrupter for Cab and Trailer Clearance/Marker Lights (Blinks Lights with Headlight Switch in "OFF" or "ON" Position) Instrument Panel Mounted : TRACTOR PROTECTION VALVE : TRAILER HOSES AND CABLES 12' Coiled Trailer Lighting Cable and with 7-Way Connector and with 12' Coiled Nylon Trailer Brake Hose		
	<u>Notes</u>		

<u>Code</u>	<u>Description</u>	<u>F/R Wt</u> (lbs)	<u>Tot Wt</u> (lbs)
	: Front and Rear Dust Shields not Included : Rear Axle is Limited to 40,000-lb GAWR with Code 04092 BRAKE SYSTEM, AIR and Standard Rear Air Cam Brakes Regardless of Axle/Suspension Ordered.		
4722	DRAIN VALVE {Bendix DV-2} Automatic; With Heater; for Air Tank	1/0	1
4AZA	AIR BRAKE ABS {Bendix AntiLock Brake System} Full Vehicle Wheel Control System (4-Channel)	0/0	0
4EBD	AIR DRYER {Meritor Wabco System Saver 1200} with Heater	10/8	18
	<u>Includes</u> : AIR DRYER LOCATION Inside Left Rail, Back of Cab		
4ESX	BRAKE CHAMBERS, FRONT AXLE {Haldex} 20 Sqn	0/0	0
4EVH	BRAKE CHAMBERS, REAR AXLE {MGM TR3030LP3TSHD} 30/30 Spring Brake	0/0	0
	<u>Includes</u> : BRAKE CHAMBERS, SPRING (2) Rear Parking; WITH TRUCK BRAKES: All 4x2, 4x4; WITH TRACTOR BRAKES: All 4x2, 4x4; 6x4 & 6x6 with Rear Tandem Axles Less Than 46,000-lb. or GVWR Up To 54,000-lb. : BRAKE CHAMBERS, SPRING (4) Rear Parking; WITH TRUCK BRAKES: All 6x4, 6x6; WITH TRACTOR BRAKES: 6x4 & 6x6 with Rear Tandem Axles 46,000-lb. or Greater or GVWR of 54,000-lb. or Greater		
4JCJ	BRAKES, FRONT, AIR CAM S-Cam; 16.5" x 5.0"; Includes 20 Sq. In. Long Stroke Brake Chambers	0/0	0
	<u>Notes</u> : The following features should be considered when calculating Front GAWR: Front Axles; Front Suspension; Brake System; Brakes, Front Air Cam; Wheels; Tires.		
4NDB	BRAKES, REAR, AIR CAM S-Cam; 16.5" x 7.0"; Includes 30/30 Sq.In. Long Stroke Brake Chamber and Spring Actuated Parking Brake	0/0	0
	<u>Notes</u> : The following features should be considered when calculating Rear GAWR: Rear Axles; Rear Suspension; Brake System; Brakes, Rear Air Cam; Brake Shoes, Rear; Special Rating, GAWR; Wheels; Tires.		
4SPM	AIR COMPRESSOR {Bendix} 15.9 CFM Capacity, Single Cylinder	0/0	0
4WBX	DUST SHIELDS, FRONT BRAKE for Air Brakes	4/0	4
4WDM	DUST SHIELDS, REAR BRAKE for Air Brakes	0/11	11
5708	STEERING COLUMN Tilting	10/0	10
5CAL	STEERING WHEEL 2-Spoke, 18" Diam., Black	0/0	0
5PSA	STEERING GEAR {Sheppard M-100} Power	0/0	0
7BDS	EXHAUST SYSTEM Single, Vertical Aftertreatment Device Frame Mounted Right Side; Includes Vertical Tail Pipe & Guard	0/0	0
	<u>Includes</u> : EXHAUST HEIGHT 10' Exhaust Height - Based on Empty Chassis with Standard Components (+ or - 1" Height) : MUFFLER/TAIL PIPE GUARD Non-Bright Finish		
7WAZ	TAIL PIPE (1) Turnback Type, Non-Bright, for Single Exhaust	0/0	0
8000	ELECTRICAL SYSTEM 12-Volt, Standard Equipment	0/0	0

<u>Code</u>	<u>Description</u>	<u>F/R Wt</u> (lbs)	<u>Tot Wt</u> (lbs)
	<u>Includes</u> : BATTERY BOX Steel with Fiberglass Cover : DATA LINK CONNECTOR For Vehicle Programming and Diagnostics In Cab : FUSES, ELECTRICAL SAE Blade-Type : HAZARD SWITCH Push On/Push Off, Located on Top of Steering Column Cover : HEADLIGHT DIMMER SWITCH Integral with Turn Signal Lever : HEADLIGHTS (2) Sealed Beam, Round, with Chrome Plated Bezels : HORN, ELECTRIC Single : JUMP START STUD Located on Positive Terminal of Outermost Battery : PARKING LIGHT Integral with Front Turn Signal and Rear Tail Light : RUNNING LIGHT (2) Daytime, Included With Headlights : STARTER SWITCH Electric, Key Operated : STOP, TURN, TAIL & B/U LIGHTS Dual, Rear, Combination with Reflector : TURN SIGNAL SWITCH Self-Cancelling for Trucks, Manual Cancelling for Tractors, with Lane Change Feature : TURN SIGNALS, FRONT Includes Reflectors and Auxiliary Side Turn Signals, Solid State Flashers; Flush Mounted : WINDSHIELD WIPER SWITCH 2-Speed with Wash and Intermittent Feature (5 Pre-Set Delays), Integral with Turn Signal Lever : WINDSHIELD WIPERS Single Motor, Electric, Cowl Mounted : WIRING, CHASSIS Color Coded and Continuously Numbered		
8518	CIGAR LIGHTER Includes Ash Cup	1/0	1
8540	HORN, ELECTRIC (2)	2/0	2
8GGN	ALTERNATOR {Bosch LH160} Brush Type, 12 Volt 160 Amp. Capacity, Pad Mounted	0/0	0
8MKL	BATTERY SYSTEM {International} Maintenance-Free, (3) 12-Volt 1950CCA Total	0/0	0
8RJV	RADIO {International} AM/FM Stereo With Weatherband, Clock, Auxiliary Input, Includes Multiple Speakers	0/0	0
	<u>Includes</u> : SPEAKERS IN CAB (2) Dual-Cone with Deluxe Interior : SPEAKERS IN CAB (4) Coaxial with Premium Interior		
8WCL	HORN, AIR Black, Single Trumpet, Air Solenoid Operated	0/0	0
8WML	HEADLIGHTS Long Life Halogen; for Two Light System	0/0	0
8WXG	STARTING MOTOR {Mitsubishi Electric Automotive America 105P} 12-Volt, with Soft-Start	0/0	0
	<u>Notes</u> : This starter is designed to work reliably without the need for thermal overcrank protection and provides the same warranty coverage as starters with thermal overcrank protection.		
8XAH	CIRCUIT BREAKERS Manual-Reset (Main Panel) SAE Type III With Trip Indicators, Replaces All Fuses Except For 5-Amp Fuses	0/0	0
8XBK	SWITCH, AUXILIARY Switch 40 amp Circuit for Customer Use; Includes Wiring Connection at PDC and Control in Cab	2/0	2
9585	FENDER EXTENSIONS Rubber	0/0	0
9HAN	INSULATION, UNDER HOOD for Sound Abatement	0/0	0
9HBM	GRILLE Stationary, Chrome	5/0	5

<u>Code</u>	<u>Description</u>	<u>F/R Wt</u> (lbs)	<u>Tot Wt</u> (lbs)
9WBK	FRONT END Tilting, Fiberglass, With Three Piece Construction Includes Long Hood	0/0	0
10060	PAINT SCHEMATIC, PT-1 Single Color, Design 100 <u>Includes</u> : PAINT SCHEMATIC ID LETTERS "GS"	0/0	0
10761	PAINT TYPE Base Coat/Clear Coat, 1-2 Tone	0/0	0
10GCH	FIFTH WHEEL, AIR SLIDE {Fontaine SL7ATB775024} 24" Slide, Cast Top Plate, 7.75" Above Top of Frame; Left Side Release	41/502	543
10WPT	MUD FLAP HOLDER Spring Loaded, Painted Black; With 45-Degree End, With Red and White Reflective Tape; Less Flaps	0/34	34
10WSX	MUD FLAPS, REAR Black Poly, With International Logo; Less Holders	0/8	8
11MDE	CLUTCH {Eaton Fuller EP1552} Easy-Pedal Plus, Two-Plate, Cast Angle Spring; Ceramic, 15.5" Diameter, Soft Clutch 7-Spring Damper, Mechanical Pull-Type Control, With Kwik-Adjust(Manual) Feature, 1700 lb-ft Torque Capacity <u>Includes</u> : CLUTCH RELEASE BEARING Greasable	0/0	0
12926	RADIATOR HOSES Silicone; Molded	0/0	0
12BAR	ENGINE, DIESEL {MaxxForce 11} EPA 10, 330 HP @ 1700 RPM, 1250 lb-ft Torque @ 1000 RPM, 2100 RPM Governed Speed, 330 Peak HP (Max) <u>Includes</u> : AIR COMPRESSOR AIR SUPPLY LINE Naturally-Aspirated : COLD STARTING EQUIPMENT Automatic; With Engine ECM Control : CRUISE CONTROL Electronic; Controls Integral to Steering Wheel : ENGINE BLOCK Compacted Graphite Iron : ENGINE SHUTDOWN Electric, Key Operated : FUEL FILTER Top Access, Cartridge Type Filter Element; Engine Mounted : FUEL SYSTEM High Pressure Common Rail : GOVERNOR Electronic : HEAT MANAGEMENT SYSTEM Eco-Therm : OIL FILTER, ENGINE Drop-In Cartridge Type : OIL PAN Laminate Steel Composite : TURBO Twin Series : WET TYPE CYLINDER SLEEVES	0/0	0
12THJ	FAN DRIVE {Horton Drivemaster} Automatic On/Off Type, With Normally Closed Temperature Control <u>Includes</u> : FAN Nylon	0/0	0
12UBL	RADIATOR Aluminum; Welded, Front to Back CrossFlow System, 1593 SqIn, 1929 SqIn Dual CAC, 1548 SqIn 3 Core LTR <u>Includes</u> : ANTI-FREEZE Yellow Shell Rotella Extended Life Coolant; -40 Degrees F/ -40 Degrees C; for MaxxForce 2010 Engines : DEAERATION SYSTEM with Clear Fill/Surge Tank : HOSE CLAMPS, RADIATOR HOSES Gates Shrink Band Type; Thermoplastic Coolant Hose Clamps : RADIATOR HOSES Premium, Rubber	0/0	0
12UXJ	FEDERAL EMISSIONS for 2010; MaxxForce 11 Engines	0/0	0

<u>Code</u>	<u>Description</u>	<u>F/R Wt</u> (lbs)	<u>Tot Wt</u> (lbs)
12VBC	AIR CLEANER Single Element <u>Includes</u> : AIR CLEANER with Vacuator : GAUGE, AIR CLEANER RESTRICTION Air Cleaner Mounted	0/0	0
12WCT	BLOCK HEATER, ENGINE {Phillips} 120 Volt/1500 Watt With "Y" Cord for Fuel Heater; Cord to Operate Both Heaters <u>Includes</u> : BLOCK HEATER SOCKET Receptacle Type; Mounted below Drivers Door	3/0	3
12WEG	COLD STARTING EQUIPMENT Automatic; With Engine ECM Control	4/0	4
12WTA	FAN DRIVE SPECIAL EFFECTS Fan Cooling Ring with Fan Shroud Effects, Engine Mounted	15/0	15
12WZE	EMISSION COMPLIANCE Federal, Does Not Comply With California Clean Air Regulations	0/0	0
13GHC	TRANSMISSION, MANUAL {Fuller FRO-13210C} 10-Speed Manual, With Overdrive, With Air Shift <u>Includes</u> : CLUTCH BRAKE Torque Limiting : FILL PLUG, MAGNETIC	0/0	0
13WAN	OIL COOLER,MANUAL TRANSMISSION Air to Oil Type, for International, Fuller, Meritor or Spicer Transmission, Mounted on Radiator, (REQUIRES TRANSMISSION LUBE PUMP)	13/7	20
13WAP	TRANSMISSION LUBE PUMP for International, Fuller, Meritor or Spicer Transmissions; USE ONLY WHEN PUMP IS NOT INCLUDED STANDARD IN TRANSMISSION	8/2	10
14GEP	AXLE, REAR, TANDEM {Dana Spicer DS405/RS405} Single Reduction, 40,000-lb Capacity, 200 Wheel Ends . Gear Ratio: 4.63 <u>Includes</u> : POWER DIVIDER LOCK Electric over Air Operated, Cab Control with Indicator Light : REAR AXLE DRAIN PLUG (2) Magnetic, For Tandem Rear Axle <u>Notes</u> : When Specifying Axle Ratio, Check Performance Guidelines and TCAPE for Startability and Performance	0/0	0
14UNA	SUSPENSION, REAR, TANDEM {International} 4-Spring Type, Multileaf, 52" Axle Spacing; 40,000-lb Capacity <u>Includes</u> : CROSSMEMBER, SUSPENSION Stamped Steel Double Dogbone <u>Notes</u> : The following features should be considered when calculating Rear GAWR: Rear Axles; Rear Suspension; Brake System; Brakes, Rear Air Cam; Brake Shoes, Rear; Special Rating, GAWR; Wheels; Tires.	0/126	126
15DMT	FUEL TANK (2) Top Draw; D Style, Non Polished Aluminum, 80 U.S. Gal., Total Capacity 160 U.S. Gal., 606 L; 23" Tank Depth, Mounted Under Cab Left and Right Side	0/0	0

<u>Code</u>	<u>Description</u>	<u>F/R Wt</u> (lbs)	<u>Tot Wt</u> (lbs)
15LKY	FUEL/WATER SEPARATOR {Davco Fuel Pro 382} 120 Volt Pre Heater and Fuel Heated, Thermostatic Fuel Temperature Control, Includes Water-In-Fuel Light, Mounted In Standard Position	3/-2	1
16030	CAB Conventional <u>Includes</u> : ARM REST (2) Molded Plastic; One Each Door : CLEARANCE/MARKER LIGHTS (5) Flush Mounted : COAT HOOK, CAB Located on Rear Wall, Centered Above Rear Window : CUP HOLDERS Two Cup Holders, Located in Lower Center of Instrument Panel : DOME LIGHT, CAB Rectangular, Door Activated and Push On-Off at Light Lens, Timed Theater Dimming, Integral to Console, Center Mounted : GLASS, ALL WINDOWS Tinted : GRAB HANDLE, CAB INTERIOR (1) "A" Pillar Mounted, Passenger Side : GRAB HANDLE, CAB INTERIOR (2) Front of "B" Pillar Mounted, One Each Side : INTERIOR SHEET METAL Upper Door (Above Window Ledge) Painted Exterior Color : STEP (4) Two Steps Per Door	0/0	0
16975	HEATER HOSES Silicone	0/0	0
16HBA	GAUGE CLUSTER English With English Electronic Speedometer <u>Includes</u> : GAUGE CLUSTER (6) Engine Oil Pressure (Electronic), Water Temperature (Electronic), Fuel (Electronic), Tachometer (Electronic), Voltmeter, Washer Fluid Level : ODOMETER DISPLAY, Miles, Trip Miles, Engine Hours, Trip Hours, Fault Code Readout : WARNING SYSTEM Low Fuel, Low Oil Pressure, High Engine Coolant Temp, and Low Battery Voltage (Visual and Audible)	0/0	0
16HHE	GAUGE, AIR CLEANER RESTRICTION {Filter-Minder} With Black Bezel Mounted in Instrument Panel	2/0	2
16HKT	IP CLUSTER DISPLAY On Board Diagnostics Display of Fault Codes in Gauge Cluster	0/0	0
16JNV	SEAT, DRIVER {National 2000} Air Suspension, High Back With Integral Headrest, Cloth, Isolator, 1 Chamber Lumbar, 2 Position Front Cushion Adjust, -3 to +14 Degree Back Angle Adjust <u>Includes</u> : SEAT BELT 3-Point, Lap and Shoulder Belt Type	0/0	0
16RPX	SEAT, PASSENGER {National} Air-Suspension, High Back With Integral Headrest, Cloth, Isolated, 1 Chamber Lumbar, 2 Position Front Cushion Adjustment, -3 to +14 Degree Seat Back Adjustment	51/28	79
16SDJ	MIRRORS (2) {Lang Mekra} Rectangular, 7.44" x 14.84" & 7.44" sq. Convex Both Sides, 102" Inside Spacing, Breakaway Type, Black Heads, Brackets & Arms	2/0	2
16SEE	GRAB HANDLE Chrome; Towel Bar Type With Anti-Slip Rubber Inserts; for Cab Entry Mounted Left Side Only at "B" Pillar	3/0	3
16WBY	ARM REST, RIGHT, DRIVER SEAT	3/0	3
16WBZ	ARM REST, LEFT, PASSENGER SEAT	3/0	3
16WCT	AIR CONDITIONER {Blend-Air} With Integral Heater & Defroster <u>Includes</u>	0/0	0

<u>Code</u>	<u>Description</u>	<u>F/R Wt</u> (lbs)	<u>Tot Wt</u> (lbs)
	: CLAMPS, HEATER HOSE Mubea Constant Tension Clamps : HEATER HOSES Premium : REFRIGERANT Hydrofluorocarbon HFC-134A		
16WJT	INSTRUMENT PANEL Center Section, Ergonomic Panel	0/0	0
16WKY	FRESH AIR FILTER for HVAC	4/0	4
16WLE	STORAGE POCKET, DOOR Molded Plastic, Full Width; Mounted on Passenger Door	0/0	0
16WRX	CAB INTERIOR TRIM Deluxe <u>Includes</u> : "A" PILLAR COVER Molded Plastic : CAB INTERIOR TRIM PANELS Cloth Covered Molded Plastic, Full Height; All Exposed Interior Sheet Metal is Covered Except for the Following: with a Two-Man Passenger Seat or with a Full Bench Seat the Back Panel is Completely Void of Covering : CAB, INTERIOR TRIM, CLOSEOUT Lower Dash Closeout Panel; Molded Plastic; Under Instrument Panel Driver Side : CONSOLE, OVERHEAD Molded Plastic; With Dual Storage Pockets with Retainer Nets and CB Radio Pocket : DOOR TRIM PANELS Molded Plastic; Driver and Passenger Doors : FLOOR COVERING Rubber, Black : HEADLINER Soft Padded Cloth : INSTRUMENT PANEL TRIM Molded Plastic with Black Center Section : STORAGE POCKET, DOOR (1) Molded Plastic, Full-Length; Driver Door : SUN VISOR (2) Padded Vinyl with Driver Side Toll Ticket Strap, Integral to Console	0/0	0
16WSK	CAB REAR SUSPENSION Air Bag Type	0/0	0
16ZGU	ACCESS, FRAME Bustin, Step Mounted Left Side, With One Flush Mounted Deck Plate and Grab Handle	0/0	0
27DMA	WHEELS, FRONT DISC; 22.5" Painted Steel, 2 Hand Hole, 10 Stud (285.75MM BC) Hub Piloted, Flanged Nut, Metric Mount, 8.25 DC Rims; With Steel Hubs <u>Includes</u> : PAINT IDENTITY, FRONT WHEELS White : WHEEL SEALS, FRONT Oil Lubricated, Includes Wheel Bearings <u>Notes</u> : Compatible Tire Sizes: 11R22.5, 12R22.5, 255/70R22.5, 255/80R22.5, 265/75R22.5, 275/70R22.5, 275/80R22.5, 295/75R22.5, 295/80R22.5	0/0	0
28DMA	WHEELS, REAR DUAL DISC; 22.5" Painted Steel, 2 Hand Hole, 10-Stud (285.75MM BC) Hub Piloted, Flanged Nut, Metric Mount, 8.25 DC Rims; With Steel Hubs <u>Includes</u> : PAINT IDENTITY, REAR WHEELS White : WHEEL SEALS, REAR Oil Lubricated, Includes Wheel Bearings <u>Notes</u> : Compatible Tire Sizes: 11R22.5, 12R22.5, 255/70R22.5, 255/80R22.5, 265/75R22.5, 275/70R22.5, 275/80R22.5, 295/75R22.5, 295/80R22.5	0/0	0
29WLA	WHEEL BEARING, FRONT, LUBE {EmGard 50W} Synthetic Oil	0/0	0

<u>Code</u>	<u>Description</u>	<u>F/R Wt</u> (lbs)	<u>Tot Wt</u> (lbs)
7382138107	(2) TIRE, FRONT 11R22.5 G661 HSA (GOODYEAR) 497 rev/mile, load range H, 16 ply	4/0	4
7382150162	(8) TIRE, REAR 12R22.5 UNISTEEL G177 (GOODYEAR) 478 rev/mile, load range H, 16 ply	0/312	312
810000	FIFTH WHEEL LOCATION On Rear Axle Centerline	0/0	0
	Total Component Weight:	8138/8092	16230
	MiDEAL Spec Requirements	0/0	0
	Total Goods Purchased:	0/0	0

The weight calculations included in this proposal are an estimate of future vehicle weight. The actual weight as manufactured may be different from the estimated weight. Navistar, Inc. shall not be liable for any consequences resulting from any differences between the estimated weight of a vehicle and the actual weight.

<u>Description</u>	<u>(USA DOLLAR)</u>	<u>Price</u>
Factory List Prices:		
Product Items	\$149,248.00	
Service Items	\$0.00	
Total Factory List Price Including Options:		\$149,248.00
Total Goods Purchased:		\$1,265.00
Freight Charge	\$1,505.00	
Freight Surcharge	\$250.00	
Total Freight:		\$1,755.00
Total Factory List Price Including Freight:		\$152,268.00
Less Customer Allowance:		(\$58,748.00)
Total Vehicle Price:		\$93,520.00
Total Sale Price:		\$93,520.00
Total Per Vehicle Sales Price:		\$93,520.00
Total Net Sales Excluding Taxes:		\$93,520.00
Michigan Title Fee	\$15.00	
Total License, Title:		\$15.00
Net Sales Price:		\$93,535.00

Please feel free to contact me regarding these specifications should your interests or needs change. I am confident you will be pleased with the quality and service of an International vehicle.

Approved by Seller:

Accepted by Purchaser:

Official Title and Date

Firm or Business Name

Authorized Signature

Authorized Signature and Date

This proposal is not binding upon the seller without Seller's Authorized Signature

Official Title and Date