LINCOLN PARK
ECORSE
Hosp
St Henry Sch
Mark Twain Sch
White Sch
Visger Sch
Miller Sch
Lafayette Sch
Hospital
City Hall
BM 587
John F Kennedy Sch
High Sch
Ecorse High Sch
Ecorse Sch No 2
Goodell Sch
Keppen Sch
School No 3
Ecorse Sch
Municipal Bldg
Memorial Park
Mixter Sch
Calvary Sch
Ford Park
Carr Sch
La Blanc Field
Playground
Woodruff Sch
Wilson Jr High Sch
Jefferson Sch
Labadie Sch
Taft Sch
Park
Ecorse Park
Mud Island
Ecorse Channel
BM 577
BM 578
BM 588
Light
Light 164
Lights
Grassy Island
Fighting Island
AQUEDUCT
DETROIT RIVER
CHANNEL
WAYNE CO
ESSEX CO
4679
CORP
BDY
Cem
Branch

CITY OF ECORSE MS
5555-16
NORTH ECORSE CREEK
SCALE 1" = 800'
--- COMMUNITY BOUNDARY
FLOODED OUTLINE

00BREAK00

1) COUNTY: Wayne

2) STUDY NAME: City of Ecorse

3) WATERCOURSE: North Ecorse Creek

4) DOCUMENT TYPE: 100 year

00BREAK00

100-year

WATERCOURSE: North Branch Ecorse Creek
CITY/TOWNSHIP: Ecorse
COUNTY: Wayne

STATION	LOCATION	CWSEL	EG	Q
1	Confluence of Ecorse & Detroit Rivers	574.90	575.51	4410
30	29' u/s of confluence	574.95	575.55	4410
60	1' d/s of Jefferson Street Br.	574.99	575.60	4410
61	d/s face of Jefferson Street Br.	574.93	575.66	4410
136	u/s face of Jefferson Street Br.	575.16	575.84	4410
137	1' u/s of Jefferson Street Br.	575.34	575.88	4410
187	51' u/s of Jefferson Street Br.	575.36	575.98	4410
362	226' u/s of Jefferson Street Br.	575.94	576.25	4410
737	51' d/s of d/s face of R.R. Br. #1	576.24	576.50	4410
787	1' d/s of d/s face of R.R. Br. #1	576.20	576.48	4410
788	d/s face of (T & I) R.R. Br. #1	576.15	576.67	4410
797	u/s face of (T & I) R.R. Br. #1	576.19	576.71	4410
798	1' u/s of (T & I) R.R. Br. #1	576.32	576.78	4410
844	47' u/s of (T & I) R.R. Br. #1	576.37	576.87	4410
845	d/s face of (T & I) R.R. Br. #2	576.33	576.81	4410
859	u/s face of (T & I) R.R. Br. #2	576.38	576.85	4410
860	1' u/s of (T & I) R.R. Br. #2	576.48	576.88	4410
910	50' u/s of (T & I) R.R. Br. #2	576.56	576.92	4410
911	d/s face of (T & I) R.R. Br. #3	576.52	576.96	4410
921	u/s face of (T & I) R.R. Br. #3	576.55	576.99	4410
922	1' u/s of (T & I) R.R. Br. #3	576.66	577.02	4410
953	1' d/s of (T & I) R.R. Br. #4	576.53	577.14	4410
954	d/s face of (T & I) R.R. Br. #4	576.44	577.29	4410
985	u/s face of (T & I) R.R. Br. #4	576.66	577.47	4410
986	1' u/s of (T & I) R.R. Br. #4	576.07	577.57	4410
1036	51' u/s of (T & I) R.R. Br. #4	577.24	577.64	4410
1736	700' d/s of confluence of N. Ecorse Ri.	577.86	578.18	4410
2436	Confluence of N. Ecorse Ri. & Sexton-Kilfoil	578.27	578.57	4410
2736	Confluence of N. Branch and Sexton-Kilfoil	578.62	578.76	2100
3436	1000' u/s of confluence	578.89	579.04	2100
3836	989' d/s of Mill Street Br.	579.06	579.20	2100
4311	534' d/s of Mill Street Br.	579.40	579.63	2100
4786	39' d/s of Mill Street Br.	579.73	579.89	2100
4825	d/s face of Mill Street Br.	579.77	579.91	2100
4846	u/s face of Mill Street Br.	579.87	580.01	2100
4847	1' u/s of Mill Street Br.	579.87	580.01	2100
5436	590' u/s of Mill Street Br.	580.10	580.29	2100
5936	1090' u/s of Mill St. at White Street	580.38	580.55	2100
6416	1200' d/s of Southfield Road	580.60	580.87	2100
6786	50' d/s of Southfield Road	580.88	581.24	2100
6836	1' d/s of Southfield Road	581.08	581.29	2100
6917	1' u/s of Southfield Road	581.54	581.83	2100
7436	520' u/s of Southfield Road	582.00	582.23	2100
7936	1020' u/s of Southfield Rd @ Russell St.	582.30	582.51	2100
8536	1620' u/s of Southfield Road	582.63	582.80	2100
9136	2220' u/s of Southfield Rd. @ Montie Road	582.87	583.01	2100
9586	2670' u/s of Southfield Road	583.01	583.17	2100
9596	2680' u/s of Southfield Road	583.04	583.18	2100
10286	3220' u/s of Southfield Rd. & 50' d/s of Empire	583.37	583.48	2100
10336	3270' u/s of Southfield Rd. @ Empire St.	583.35	583.55	2100
10636	3570' u/s of Southfield Rd.	583.53	583.74	2100
11536	4270' u/s of Southfield Rd.	584.34	584.46	2100

```
C
C      25
C      61        D/S FACE JEFFERSON STREET BRIDGE
C     136        U/S FACE JEFFERSON STREET BRIDGE
C     788        D/S FACE RR BRIDGE #1
C     797        U/S FACE RR BRIDGE #1
C     845        D/S FACE RR BRIDGE #2
C     859        U/S FACE RR BRIDGE #2
C     911        D/S FACE RR BRIDGE #3
C     921        U/S FACE RR BRIDGE #3
C     954        D/S FACE RR BRIDGE #4
C     985        U/S FACE RR BRIDGE #4
C    2436  CONFLUENCE OF THE NORTH ECORSE RIVER @ SEXTON-KILFOIL DRAIN
C    2736        2089 FT D/S OF MILL ST BR
C    3836        989 FEET D/S OF MILL STREET BRIDGE
C    4786        39 FEET D/S OF MILL STREET BRIDGE
C    4825        D/S FACE OF MILL STREET BRIDGE-TRUSS BRIDGE
C    4846        U/S FACE OF MILL STREET BRIDGE
C    5936        1090 FEET U/S OF MILL STREET BRIDGE AT WHITE STREET
C    6786        49 FEET D/S OF SOUTHFIELD ROAD BRIDGE
C    6836        D/S FACE OF SOUTHFIELD ROAD BRIDGE-SINGLE PIER-CONCRETE
C    6916        U/S FACE OF SOUTHFIELD ROAD BRIDGE
C    7936        1020 FEET U/S OF SOUTHFIELD ROAD BRIDGE AT RUSSELL STREET
C    9136        2220 FEET U/S OF SOUTHFIELD ROAD BRIDGE AT MONTIE AVENUE
C   10286        50 FT D/S OF EMPIRE STREET
C   10336        AT EMPIRE STREET
C   11536        1200 FT U/S OF EMPIRE ST
T1        CITY OF ECORSE  5555-16
T2       NORTH BRANCH OF ECORSE CREEK
T3         10 YEAR FLOOD-1500 CFS
J1   -10       2                                                    574.90
J2     1       -1
J3     1    34     4     10     11     25     26
NC 0.035 0.035 0.032   0.3    0.5
QT     4  3165  4100  4410  5160
X1     1    41   500   619
GR 576.2     0 575.9   100 576.6   200 578.5   300 581.1   400
GR 584.6   500 582.8   500 582.6   505 581.9   510 581.1   515
GR 579.2   520 575.4   525 574.8   530 572.8   535 569.2   540
GR 569.2   540 565.5 543.5 565.5 543.5 565.5   545 563.9   555
GR 566.1   560 565.3   565 565.4   570 564.1   575 566.2   580
GR 566.2   580 565.3 583.5 565.3 583.5 565.3   585 563.4   590
GR 564.4   595 565.4   600 567.7   605 571.1   610 573.5   615
GR 574.0   619 584.6   619 582.3   700 579.6   800 579.0   890
GR 578.7  1000
X1    30                     29     29     29
X1    60    41   500   619    30     30     30
GR 576.2     0 575.9   100 576.6   200 578.5   300 581.1   400
GR 584.6   500 582.8   500 582.6   505 581.9   510 581.1   515
GR 579.2   520 575.4   525 574.8   530 572.8   535 569.2   540
GR 569.2   540 565.5 543.5 565.5 543.5 565.5   545 563.9   555
GR 566.1   560 565.3   565 565.4   570 564.1   575 566.2   580
GR 566.2   580 565.3 583.5 565.3 583.5 565.3   585 563.4   590
GR 564.4   595 565.4   600 567.7   605 571.1   610 573.5   615
GR 574.0   619 584.6   619 582.3   700 579.6   800 579.0   890
GR 578.7  1000
X1    61    41   500   619     1      1      1
BT     9 500.0 584.3 579.8 500.0 587.7 579.8 540.0 588.1 580.3
BT 543.5 588.1 580.3 560.0 588.3 580.3 580.0 588.1 580.3 583.5
BT 588.1 580.3 619.0 587.7 579.7 619.0 584.4 579.7
GR 576.2     0 575.9   100 576.6   200 578.5   300 581.1   400
GR 584.6   500 582.8   500 582.6   505 581.9   510 581.1   515
   579.2   520 575.4   525 574.8   530 572.8   535 569.2   540
       3   540 580.3 543.5 565.5 543.5 565.5   545 563.9   555
```

$$$$$$$$ $$$$$$ $$$$$$ $ $$$$$$$$ $$$$$ $ $$$$$ $$ $$$$$$
$$ $$ $$ $$ $$ $$ $$ $$ $$ $$ $$ $$ $$ $$ $$ $$
$$ $$ $$ $$ $$ $$ $$ $$ $$ $$ $$ $$ $$ $$ $$ $$
$$$$$$ $$ $$ $$ $ $$ $$ $$ $$ $ $$ $$ $$ $$ $$ $$ $$
$$ $$ $$ $$ $$ $$ $$ $$ $$ $$ $$ $$ $$ $$ $$ $$ $$ $$
$$ $$ $$ $$ $$$$ $$ $$ $$ $$ $$ $$$$$$$$ $$$$$$$$ $$
$$ $$ $$ $$ $$$$ $$ $$ $$ $$ $$ $$ $$ $$ $$ $$ $$
$$ $$ $$ $$ $$ $$ $$ $$ $$ $$ $$ $$ $$ $$ $$ $$ $$
$$$$$$$$$ $$$$$$$ $ $$$$$ $$$$ $ $$$$$$ $$ $$$$$$ $$ $$$$
ECOJ099 JAI DA 05/04/77 08.47.25 7600 JO

641C

640

DNR COPY

CITY OF ECORSE FIS
NORTH ECORSE CREEK

Review
Rec'd 8-11-77

S C O P E 2 L O A D M A P

LOADER VERSION 1.0 05/04/77 08.47.30 PAGE 1

PROGRAM WILL BE ENTERED AT HEC2 (373)

SCM LENGTH 146657 LCM LENGTH 0

BLOCK	ADDRESS	LENGTH
/ALPHA/	100	101
HEC2	201	11606
CARD	12007	1673
SUMPO	13702	1063
CHIMP	14765	1645
DC	16632	703
FLOOTS	17535	444
BLFLO	20201	1003
ADDPTS	21204	334
BWEIR	21540	1356
YCRIT	23115	122
SLARA	23240	256
SCALE	23516	246
XSEC	23764	1264
PROF	25250	1142
EXP	26412	102
/ECL.C./	26514	23
/Q8.IO./	26537	137
/HEADING/	26676	16
OUTC=	26714	1017
Q8 TRY=	27733	1
CO IO=	27734	44
ENDFIL=	30000	45
FECMSK=	30045	41
FLTIN=	30106	154
FLTOUT=	30262	314
FWTAP=	30576	372
FORSYS=	31170	556
FORUTL=	31746	16
GETFIT=	31764	43
INCOM=	32027	257
INPC=	32306	173
KODER=	32501	467
KRAKER=	33170	454
OUTCOM=	33644	203
RELIND=	34047	35
GOTOFR=	34104	14
ALOG	34120	77
ITOJ*	34217	52
SYSAID=	34271	1
SYS=1ST	34272	62
XTOY*	34354	55
//	34431	112225

```
**********************************************
HEC2 VERSION UPDATED JAN 1976
ERROR CORRECTIONS 01,02,03,04,05,06,07,08,09
MODIFICATIONS 52,53,54,55,56,57,58
**********************************************
```

```
C
1       CITY OF ECORSE   5555-16   DIC. ZANOTTI  P.E.
T2      10 YEAR FLOOD
T3      NORTH BRANCH OF ECORSE CREEK

J1  ICHECK     INQ        NINV       IDIR       STRT       METRIC     PRINS      Q          WSEL       FQ
        -0.        2.        -0.        -0.  -0.000000     -0.00      -0.0       -0.    574.400     -0.000

J2  NPROF      IPLOT      PRFVS      XSECV      XSECH      FN         ALLDC      IBW        CHNIM      ITRACE
      1.000     -0.000     -1.000     -0.000     -0.000     -0.000     -0.000     -0.000     -0.000     -0.000

J3      1.000     10.000     11.000     12.000     14.000      4.000      4.000     -0.000     -0.000     -0.000
NC       .035       .035       .030       .100       .500     -0.000     -0.000     -0.000     -0.000     -0.000
QT      4.000   3165.000   4100.000   4410.000   5160.000     -0.000     -0.000     -0.000     -0.000     -0.000

X1      1.000     41.000    500.000    619.000     -0.000     -0.000     -0.000     -0.000     -0.000     -0.000
GR    576.200      0.000    575.900    100.000    576.600    200.000    578.500    300.000    581.100    400.000
GR    584.600    500.000    582.300    500.000    582.600    505.000    581.900    510.000    581.100    515.000
GR    579.200    520.000    575.400    525.000    574.800    530.000    572.800    535.000    569.200    540.000
GR    569.200    540.000    565.500    543.500    565.500    543.500    565.500    545.000    563.900    555.000
GR    566.100    560.000    565.300    565.000    565.400    570.000    564.100    575.000    566.200    590.000
GR    566.200    580.000    565.300    543.500    565.300    543.500    565.300    585.000    563.400    590.000
GR    564.400    595.000    565.400    600.000    567.700    605.000    571.100    610.000    573.500    615.000
GR    574.000    619.000    584.600    619.000    582.300    700.000    579.600    800.000    579.000    690.000
GR    578.700   1000.000     -0.000     -0.000     -0.000     -0.000     -0.000     -0.000     -0.000     -0.000

X1     30.000     -0.000     -0.000     -0.000     29.000     29.000     29.000     -0.000     -0.000     -0.000

X1     60.000     41.000    500.000    619.000     30.000     30.000     30.000     -0.000     -0.000     -0.000
GR    576.200      0.000    575.900    100.000    576.600    200.000    578.500    300.000    581.100    400.000
GR    584.600    500.000    582.300    500.000    582.600    505.000    581.900    510.000    581.100    515.000
GR    579.200    520.000    575.400    525.000    574.800    530.000    572.800    535.000    569.200    540.000
GR    569.200    540.000    565.500    543.500    565.500    543.500    565.500    545.000    563.900    555.000
GR    566.100    560.000    565.300    565.000    565.400    570.000    564.100    575.000    566.200    590.000
GR    566.200    580.000    565.300    543.500    565.300    543.500    565.300    585.000    563.400    590.000
GR    564.400    595.000    565.400    600.000    567.700    605.000    571.100    610.000    573.500    615.000
GR    574.000    619.000    584.600    619.000    582.300    700.000    579.600    800.000    579.000    690.000
GR    578.700   1000.000     -0.000     -0.000     -0.000     -0.000     -0.000     -0.000     -0.000     -0.000

X1     61.000     41.000    500.000    619.000      1.000      1.000      1.000     -0.000     -0.000     -0.000
BT      9.000    500.000    584.600    579.400    500.000    587.700    579.800    540.000    588.100    580.300
BT    543.500    588.100    540.300    560.000    593.300    590.300    580.000    585.100    580.300    583.500
BT    588.100    580.300    619.000    587.700    579.700    619.000    584.400    579.700     -0.000     -0.000
GR    576.200      0.000    575.900    100.000    576.600    200.000    578.500    300.000    581.100    400.000
GR    584.600    500.000    582.300    500.000    582.600    505.000    581.900    510.000    581.100    515.000
GR    579.200    520.000    575.400    525.000    574.800    530.000    572.800    535.000    569.200    540.000
GR    580.300    540.000    580.300    543.500    565.500    543.500    565.500    545.000    563.400    555.000
GR    566.100    560.000    565.300    565.000    565.400    570.000    564.100    575.000    566.200    590.000
GR    580.300    580.000    580.300    543.500    565.300    543.500    565.300    585.000    563.400    590.000
GR    564.400    595.000    565.400    600.000    567.700    605.000    571.100    610.000    573.500    615.000
GR    574.000    619.000    584.600    619.000    582.300    700.000    579.600    800.000    579.000    690.000
GR    578.700   1000.000     -0.000     -0.000     -0.000     -0.000     -0.000     -0.000     -0.000     -0.000
```

X1	136.000	-0.000	500.000	619.000	75.000	75.000	75.000	-0.000	-0.000	-0.000
X2	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	1.000	-0.000	-0.000	-0.000
X1	137.000	41.000	500.000	619.000	1.000	1.000	1.000	-0.000	-0.000	-0.000
GR	576.200	0.000	575.900	100.000	576.600	200.000	578.500	300.000	581.100	400.000
GR	584.600	500.000	582.800	600.000	582.600	505.000	581.900	610.000	581.100	615.000
GR	579.200	520.000	575.400	525.000	574.800	530.000	572.800	535.000	569.200	540.000
GR	569.200	540.000	565.500	541.500	565.500	543.500	565.500	545.000	563.400	555.000
GR	566.100	560.000	565.300	565.000	565.400	570.000	564.100	575.000	566.200	580.000
GR	566.200	580.000	565.300	583.500	565.300	583.500	565.300	585.000	563.400	590.000
GR	564.400	595.000	565.400	600.000	567.700	605.000	571.100	610.000	573.500	615.000
GR	574.000	619.000	584.600	619.000	582.300	700.000	579.600	800.000	579.000	890.000
GR	578.700	1000.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000
NC	.035	.042	.030	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000
X1	187.000	27.000	331.000	441.000	50.000	50.000	50.000	-0.000	-0.000	-0.000
GR	575.800	0.000	576.600	41.000	578.500	141.000	580.600	241.000	583.100	331.000
GR	575.400	341.000	574.800	346.000	571.300	351.000	568.100	356.000	567.200	361.000
GR	565.700	366.000	565.100	371.000	565.500	376.000	565.100	381.000	564.700	391.000
GR	564.100	401.000	564.400	406.000	565.700	411.000	568.200	416.000	570.500	421.000
GR	572.800	426.000	574.800	432.000	580.200	441.000	583.600	454.000	581.000	541.000
GR	579.300	641.000	578.300	698.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000
NH	4.000	.035	244.000	.030	360.000	.070	400.000	.045	400.000	-0.000
X1	362.000	35.000	244.000	400.000	175.000	175.000	175.000	-0.000	.270	-0.000
GR	580.200	0.000	579.500	100.000	578.300	200.000	578.300	244.000	574.600	254.000
GR	573.600	255.000	571.500	260.000	569.800	265.000	568.500	270.000	567.600	275.000
GR	566.900	280.000	565.900	285.000	565.600	290.000	563.700	300.000	563.700	310.000
GR	564.300	320.000	565.800	330.000	568.200	340.000	569.800	345.000	571.100	350.000
GR	571.600	355.000	572.400	360.000	572.100	365.000	572.600	370.000	572.600	375.000
GR	572.800	380.000	572.800	385.000	572.900	390.000	574.600	395.000	576.900	400.000
GR	577.600	500.000	577.700	545.000	577.500	600.000	577.700	700.000	577.500	800.000
X1	737.000	35.000	244.000	400.000	375.000	375.000	375.000	-0.000	-0.000	-0.000
X3	-0.000	-0.000	-0.000	244.000	-0.000	373.000	-0.000	-0.000	-0.000	-0.000
GR	580.200	0.000	579.500	100.000	578.300	200.000	578.300	244.000	574.600	254.000
GR	573.600	255.000	571.500	260.000	569.800	265.000	568.500	270.000	567.600	275.000
GR	566.900	280.000	565.900	285.000	565.600	290.000	563.700	300.000	563.700	310.000
GR	564.300	320.000	565.800	330.000	568.200	340.000	569.800	345.000	571.100	350.000
GR	571.600	355.000	572.400	360.000	572.100	365.000	572.600	370.000	572.600	375.000
GR	572.800	380.000	572.800	385.000	572.900	390.000	574.600	395.000	576.900	400.000
GR	577.600	500.000	577.700	545.000	577.500	600.000	577.700	700.000	577.500	800.000
NC	.035	.042	.032	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000
X1	787.000	67.000	795.000	901.600	50.000	50.000	50.000	-0.000	-0.000	-0.000
GR	581.500	0.000	581.400	95.000	581.300	195.000	581.200	295.000	581.100	395.000
GR	581.100	495.000	581.100	595.000	581.000	695.000	581.000	795.000	575.200	795.000
GR	574.500	800.000	574.500	800.000	574.500	801.000	574.500	801.000	574.000	805.000
GR	573.200	810.000	573.200	810.000	573.200	811.000	573.200	811.000	570.900	815.000
GR	569.300	820.000	570.100	825.000	570.100	825.000	570.100	826.000	570.100	826.000
GR	566.600	829.900	566.600	829.900	566.600	831.200	566.600	831.200	565.500	835.000
GR	565.500	835.000	565.500	836.000	565.500	836.000	563.900	840.000	564.500	845.000
GR	564.500	845.000	564.500	846.000	564.500	846.000	564.300	850.000	564.900	855.000
GR	564.900	855.000	564.900	856.000	564.900	856.000	565.500	860.000	565.200	865.000
GR	565.200	865.000	565.200	866.300	565.300	866.300	566.000	870.000	566.000	875.000
GR	566.000	875.000	566.000	876.000	566.000	876.000	566.700	880.000	568.700	885.000
GR	568.300	890.000	569.700	895.000	571.700	900.000	571.700	901.600	581.000	901.600
GR	580.800	995.000	580.800	1095.000	580.600	1195.000	580.400	1295.000	580.100	1395.000
GR	579.900	1495.000	580.000	1540.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000
X1	788.000	67.000	795.000	901.600	1.000	1.000	1.000	-0.000	-0.000	-0.000
BT	4.000	795.000	581.000	577.200	830.000	581.000	577.200	1.000	581.000	577.200
BT	901.600	581.000	577.200	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000
GR	581.500	0.000	581.400	95.000	581.300	195.000	581.200	295.000	581.100	395.000
GR	581.100	495.000	581.100	595.000	581.000	695.000	581.000	795.000	575.200	795.000

GR	573.200	810.000	575.500	810.000	575.500	811.000	573.200	811.000	570.800	815.000
GR	569.300	820.000	570.100	825.000	575.500	825.000	575.500	826.000	570.100	826.000
GR	566.600	830.000	577.200	830.000	577.200	831.300	566.600	831.300	565.500	835.000
GR	575.500	835.000	575.500	836.000	565.500	836.000	563.900	840.000	564.500	845.000
GR	575.500	845.000	575.500	846.000	564.500	846.000	564.900	850.000	564.900	855.000
GR	575.500	855.000	575.500	856.000	564.900	856.000	565.500	860.000	565.200	865.000
GR	577.200	865.000	577.200	866.300	565.200	866.300	566.000	870.000	566.000	875.000
GR	575.500	875.000	575.500	876.000	566.000	876.000	566.700	880.000	568.700	885.000
GR	568.300	890.000	569.700	895.000	571.700	900.000	571.700	901.600	581.000	901.600
GR	580.800	995.000	580.800	1095.000	580.600	1195.000	580.400	1295.000	580.100	1395.000
GR	579.900	1495.000	580.000	1540.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000
X1	797.000	0.000	795.000	901.600	0.000	0.000	0.000	-0.000	-0.000	-0.000
X2	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	1.000	-0.000	-0.000	-0.000
X1	798.000	67.000	795.000	901.600	1.000	1.000	1.000	-0.000	-0.000	-0.000
GR	581.500	0.000	581.400	95.000	581.300	195.000	581.200	295.000	581.100	395.000
GR	581.100	495.000	581.100	595.000	581.000	695.000	581.000	795.000	575.200	795.000
GR	574.500	800.000	574.500	800.000	574.500	801.000	574.500	801.000	574.000	805.000
GR	573.200	810.000	573.200	810.000	573.200	811.000	573.200	811.000	570.800	815.000
GR	569.300	820.000	570.100	825.000	570.100	825.000	570.100	826.000	570.100	826.000
GR	566.600	829.900	566.600	829.900	566.600	831.200	566.600	831.200	565.500	835.000
GR	565.500	835.000	565.500	836.000	565.500	836.000	563.900	840.000	564.500	845.000
GR	564.500	845.000	564.500	846.000	564.500	846.000	564.900	850.000	564.900	855.000
GR	564.900	855.000	564.900	856.000	564.900	856.000	565.500	860.000	565.200	865.000
GR	565.200	865.000	565.200	866.300	565.300	866.300	566.000	870.000	566.000	875.000
GR	566.000	875.000	566.000	876.000	566.000	876.000	566.700	880.000	568.700	885.000
GR	568.300	890.000	569.700	895.000	571.700	900.000	571.700	901.600	581.000	901.600
GR	580.800	995.000	580.800	1095.000	580.600	1195.000	580.400	1295.000	580.100	1395.000
GR	579.900	1495.000	580.000	1540.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000
X1	844.000	58.000	815.000	924.000	46.000	46.000	45.000	-0.000	-0.000	-0.000
GR	583.400	0.000	583.400	15.000	583.100	115.000	582.900	215.000	582.800	315.000
GR	582.600	415.000	582.300	515.000	582.100	615.000	581.800	715.000	581.500	815.000
GR	576.100	815.000	574.200	820.000	572.700	825.000	570.000	829.000	570.000	829.000
GR	570.000	830.000	570.000	830.000	568.000	835.000	565.900	40.000	565.000	844.000
GR	565.000	844.000	565.000	845.000	565.000	845.000	565.000	55.000	566.000	854.000
GR	566.000	864.000	566.000	865.000	566.000	865.000	566.100	874.000	566.100	874.000
GR	566.100	875.000	566.100	875.000	565.800	884.000	565.300	884.000	565.400	885.000
GR	565.800	885.000	565.600	890.000	565.200	894.000	565.200	94.000	565.200	895.000
GR	565.200	895.000	567.600	900.000	570.300	905.000	572.000	909.000	572.000	909.000
GR	572.000	910.000	572.000	910.000	574.000	915.000	575.100	20.000	576.200	924.000
GR	581.400	924.000	581.300	1015.000	581.300	1115.000	581.100	1215.000	581.100	1315.000
GR	581.100	1415.000	581.200	1515.000	581.200	1565.000	-0.000	-0.000	-0.000	-0.000
X1	845.000	58.000	815.000	924.000	1.000	1.000	1.000	-0.000	-0.000	-0.000
BT	16.000	815.000	581.500	578.400	829.000	581.500	579.100	840.000	581.500	578.100
BT	844.000	581.500	577.900	845.000	581.500	577.900	864.000	581.500	577.500	855.000
BT	581.500	577.500	874.000	581.400	577.400	575.000	581.400	577.400	864.000	581.400
BT	577.200	885.000	581.400	577.200	894.000	581.400	577.000	895.000	581.400	577.000
BT	909.000	581.400	576.800	910.000	581.400	576.800	924.000	581.400	575.500	-0.000
GR	583.400	0.000	583.400	15.000	583.100	115.000	582.900	215.000	582.800	315.000
GR	582.600	415.000	582.300	515.000	582.100	615.000	581.800	715.000	581.500	815.000
GR	576.100	815.000	574.200	820.000	572.700	825.000	570.000	829.000	578.100	829.000
GR	578.100	830.000	570.000	830.000	568.000	835.000	565.900	40.000	565.000	844.000
GR	577.900	844.000	577.900	845.000	565.000	845.000	565.000	55.000	566.000	854.000
GR	577.500	864.000	577.500	865.000	566.000	865.000	566.100	874.000	577.400	874.000
GR	577.400	875.000	566.100	875.000	565.800	884.000	577.200	884.000	577.200	885.000
GR	565.800	885.000	565.600	890.000	565.200	894.000	577.000	894.000	577.000	885.000
GR	565.200	895.000	567.600	900.000	570.300	905.000	572.000	909.000	576.900	909.000
GR	576.800	910.000	572.000	910.000	574.000	915.000	575.100	20.000	578.200	924.000
GR	581.400	924.000	581.300	1015.000	581.300	1115.000	581.100	1215.000	581.100	1315.000
GR	581.100	1415.000	581.200	1515.000	581.200	1565.000	-0.001	-0.000	-0.000	-0.000
X1	859.000	-0.000	815.000	924.000	14.500	14.500	14.500	-0.100	-0.000	-0.000

	X1	860.000	58.000	815.000	924.000	1.000	1.000	1.000	-0.000	-0.000	-0.000
	GR	583.400	0.000	583.400	15.000	583.100	115.000	582.900	215.000	582.800	315.000
	GR	582.600	415.000	582.300	515.000	582.100	615.000	581.800	715.000	581.500	815.000
	GR	576.100	815.000	574.200	820.000	572.700	825.000	570.000	824.000	570.000	829.000
	GR	570.000	830.000	570.000	830.000	568.000	835.000	565.900	840.000	565.000	844.000
	GR	565.000	844.000	565.000	845.000	565.000	845.000	565.000	855.000	566.000	854.000
	GR	566.000	864.000	566.000	865.000	566.000	865.000	566.100	874.000	566.100	874.000
	GR	566.100	875.000	566.100	875.000	565.800	884.000	565.800	884.000	565.800	885.000
	GR	565.800	885.000	565.600	890.000	565.200	894.000	565.200	894.000	565.200	895.000
	GR	565.200	895.000	567.600	900.000	570.300	905.000	572.000	909.000	572.000	909.000
	GR	572.000	910.000	572.000	910.000	574.000	915.000	575.100	920.000	576.200	924.000
	GR	581.400	924.000	581.300	1015.000	581.300	1115.000	581.100	1215.000	581.100	1315.000
	GR	581.100	1415.000	581.200	1515.000	581.200	1565.000	-0.000	-0.000	-0.000	-0.000
	X1	910.000	64.000	835.000	942.000	50.000	50.000	50.000	-0.000	-0.000	-0.000
	GR	583.700	0.000	583.600	35.000	583.400	135.000	583.300	235.000	583.300	335.000
	GR	583.300	435.000	583.300	535.000	583.200	635.000	583.100	735.000	583.100	835.000
	GR	574.800	835.000	572.600	840.000	571.600	844.000	571.500	844.000	571.500	845.000
	GR	571.600	845.000	570.700	854.000	570.700	854.000	570.700	855.000	570.700	855.000
	GR	565.600	864.000	565.600	864.000	565.600	865.000	565.600	865.000	564.300	874.000
	GR	564.300	874.000	564.300	875.000	564.300	875.000	564.300	884.000	564.800	884.000
	GR	564.800	885.000	564.800	885.000	564.900	894.000	564.900	894.000	564.900	895.000
	GR	564.900	895.000	564.000	904.000	564.000	904.000	564.000	905.000	564.000	905.000
	GR	566.100	914.000	566.100	914.000	566.100	915.000	566.100	915.000	567.000	920.000
	GR	571.000	924.000	571.000	924.000	571.000	925.000	571.000	925.000	572.400	930.000
	GR	573.900	934.000	573.900	934.000	573.900	935.000	573.900	935.000	575.000	940.000
	GR	574.900	942.000	583.000	942.000	582.700	1035.000	582.600	1135.000	582.300	1235.000
	GR	582.100	1335.000	581.900	1435.000	581.800	1535.000	581.800	1585.000	-0.000	-0.000
	X1	911.000	64.000	835.000	942.000	1.000	1.000	1.000	-0.000	-0.000	-0.000
	BT	6.000	835.000	583.100	578.600	874.000	583.100	578.600	875.000	583.100	578.600
	BT	904.000	583.000	578.600	905.000	583.000	578.600	942.000	583.000	578.600	-0.000
	GR	583.700	0.000	583.600	35.000	583.400	135.000	583.300	235.000	583.300	335.000
	GR	583.300	435.000	583.300	535.000	583.200	635.000	583.100	735.000	583.100	835.000
	GR	574.800	835.000	572.600	840.000	571.600	844.000	575.500	844.000	575.500	845.000
	GR	571.600	845.000	570.700	854.000	575.500	854.000	575.500	855.000	570.700	855.000
	GR	565.600	864.000	575.500	864.000	575.500	865.000	565.600	865.000	564.300	874.000
	GR	578.600	874.000	578.600	875.000	564.300	875.000	564.800	884.000	575.500	884.000
	GR	575.500	885.000	564.800	885.000	564.900	894.000	575.500	894.000	575.500	895.000
	GR	564.900	895.000	564.000	904.000	578.600	904.000	578.600	905.000	564.000	905.000
	GR	566.100	914.000	575.500	914.000	575.500	915.000	566.100	915.000	567.000	920.000
	GR	571.000	924.000	575.500	924.000	575.500	925.000	571.000	925.000	572.400	930.000
	GR	573.900	934.000	575.500	934.000	575.500	935.000	573.900	935.000	575.000	940.000
	GR	574.900	942.000	583.000	942.000	582.700	1035.000	582.600	1135.000	582.300	1235.000
	GR	582.100	1335.000	581.900	1435.000	581.800	1535.000	581.800	1585.000	-0.000	-0.000
	X1	921.000	-0.000	835.000	942.000	10.000	10.000	10.000	-0.000	-0.000	-0.000
	X2	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	1.000	-0.000	-0.000	-0.000
	X1	922.000	64.000	835.000	942.000	1.000	1.000	1.000	-0.000	-0.000	-0.000
	GR	583.700	0.000	583.600	35.000	583.400	135.000	583.300	235.000	583.300	335.000
	GR	583.300	435.000	583.300	535.000	583.200	635.000	583.100	735.000	583.100	835.000
	GR	574.800	835.000	572.600	840.000	571.600	844.000	571.500	844.000	571.500	845.000
	GR	571.600	845.000	570.700	854.000	570.700	854.000	571.700	855.000	570.700	855.000
	GR	565.600	864.000	565.600	864.000	565.600	865.000	565.500	865.000	564.300	874.000
	GR	564.300	874.000	564.300	875.000	564.300	875.000	564.300	884.000	564.800	884.000
	GR	564.800	885.000	564.800	885.000	564.900	894.000	564.900	894.000	564.900	895.000
	GR	564.900	895.000	564.000	904.000	564.000	904.000	564.000	905.000	564.000	905.000
	GR	566.100	914.000	566.100	914.000	566.100	915.000	566.100	915.000	567.000	920.000
	GR	571.000	924.000	571.000	924.000	571.000	925.000	571.000	925.000	572.400	930.000
	GR	573.900	934.000	573.900	934.000	573.900	935.000	573.900	935.000	575.000	940.000
	GR	574.900	942.000	583.000	942.000	582.700	1035.000	582.600	1135.000	582.300	1235.000
	GR	582.100	1335.000	581.900	1435.000	581.800	1535.000	581.800	1585.000	-0.000	-0.000

X1	[illegible]	48.000	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]
GR	582.000	0.000	581.800	100.000	581.600	200.000	581.500	300.000	581.400	400.000
GR	581.200	500.000	581.000	600.000	571.000	600.000	568.100	605.000	566.900	610.000
GR	566.900	610.000	566.900	612.300	566.900	612.300	565.900	615.000	565.100	620.000
GR	565.100	620.000	565.100	622.300	565.100	622.300	566.300	625.000	566.200	630.000
GR	566.200	630.000	566.200	632.300	566.200	632.300	566.700	635.000	566.400	640.000
GR	566.100	645.000	566.400	650.000	566.400	650.000	566.400	652.300	566.400	652.300
GR	566.600	655.000	567.500	660.000	567.500	660.000	567.500	662.300	567.300	662.300
GR	567.500	665.000	569.900	670.000	569.900	670.000	569.900	672.300	569.900	672.300
GR	573.400	680.000	573.400	681.000	580.800	681.000	580.800	700.000	580.700	800.000
GR	580.600	900.000	590.600	1000.000	580.500	1100.000	-0.000	-0.000	-0.000	-0.000
X1	954.000	48.000	600.000	681.000	1.000	1.000	1.000	-0.000	-0.000	-0.000
BT	14.000	600.000	581.000	577.700	610.000	581.000	577.700	612.300	581.000	577.700
BT	620.000	581.000	577.700	622.300	581.000	577.700	630.000	580.900	577.700	632.300
BT	580.900	577.700	650.000	580.900	577.600	652.300	580.900	577.600	660.000	580.900
BT	577.600	662.300	580.800	577.600	670.000	580.800	577.600	672.300	580.800	577.600
BT	681.000	580.800	577.600	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000
GR	582.000	0.000	581.800	100.000	581.600	200.000	581.500	300.000	581.400	400.000
GR	581.200	500.000	581.000	600.000	571.000	600.000	568.100	605.000	566.900	610.000
GR	577.700	610.000	577.700	612.300	566.900	612.300	565.900	615.000	565.100	620.000
GR	577.700	620.000	577.700	622.300	565.100	622.300	566.300	625.000	566.200	630.000
GR	577.700	630.000	577.700	632.300	566.200	632.300	566.700	635.000	566.400	640.000
GR	566.100	645.000	566.400	650.000	577.600	650.000	577.600	652.300	566.400	652.300
GR	566.600	655.000	567.500	660.000	577.600	660.000	577.600	662.300	567.300	662.300
GR	567.500	665.000	569.900	670.000	577.600	670.000	577.600	672.300	569.900	672.300
GR	573.400	680.000	573.400	681.000	580.800	681.000	580.800	700.000	580.700	800.000
GR	580.600	900.000	590.600	1000.000	580.500	1100.000	-0.000	-0.000	-0.000	-0.000
X1	985.000	-0.000	600.000	681.000	30.500	30.500	30.500	-0.000	-0.000	-0.000
X2	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	1.000	-0.000	-0.000	-0.000
X1	986.000	48.000	600.000	681.000	1.000	1.000	1.000	-0.000	-0.000	-0.000
GR	582.000	0.000	581.800	100.000	581.600	200.000	581.500	300.000	581.400	400.000
GR	581.200	500.000	581.000	600.000	571.000	600.000	568.100	605.000	566.900	610.000
GR	566.900	610.000	566.900	612.300	566.900	612.300	565.900	615.000	565.100	620.000
GR	565.100	620.000	565.100	622.300	565.100	622.300	566.300	625.000	566.200	630.000
GR	566.200	630.000	566.200	632.300	566.200	632.300	566.700	635.000	566.400	640.000
GR	566.100	645.000	566.400	650.000	566.400	650.000	566.400	652.300	566.400	652.300
GR	566.600	655.000	567.500	660.000	567.500	660.000	567.500	662.300	567.500	662.300
GR	567.500	665.000	569.900	670.000	569.900	670.000	569.900	672.300	569.900	672.300
GR	573.400	680.000	573.400	681.000	580.800	681.000	580.800	700.000	580.700	800.000
GR	580.600	900.000	590.600	1000.000	580.500	1100.000	-0.000	-0.000	-0.000	-0.000
NC	.040	.035	.030	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000
X1	1036.000	37.000	565.000	700.000	50.000	50.000	50.000	-0.000	-0.000	-0.000
X3	10.000	-0.000	-0.000	-0.000	-0.000	700.000	-0.000	-0.000	-0.000	-0.000
GR	581.900	0.000	581.200	100.000	581.200	200.000	580.800	300.000	581.000	400.000
GR	579.900	500.000	581.100	555.000	575.400	587.300	574.900	590.000	574.400	595.000
GR	572.500	600.000	571.000	605.000	569.800	610.000	568.900	615.000	568.000	620.000
GR	567.400	625.000	566.600	630.000	566.300	635.000	566.200	640.000	566.300	650.000
GR	566.800	660.000	568.300	670.000	570.200	675.000	570.400	650.000	571.700	635.000
GR	573.100	690.000	574.800	695.000	574.900	696.000	577.700	700.000	577.500	800.000
GR	576.600	900.000	576.600	1000.000	577.000	1000.000	576.800	1100.000	577.500	1200.000
GR	578.300	1300.000	579.200	1345.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000
NC	.060	.035	.030	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000
X1	1736.000	40.000	374.000	492.500	700.000	700.000	700.000	-0.000	-0.000	-0.000
X3	10.000	-0.000	-0.000	374.000	-0.000	492.500	-0.000	-0.000	-0.000	-0.000
GR	580.400	0.000	580.400	167.000	579.500	283.700	575.800	336.300	575.100	374.000
GR	577.200	377.900	576.100	381.900	575.100	389.600	574.100	389.600	573.200	393.700
GR	572.400	397.700	571.500	401.600	570.300	405.600	569.400	409.500	568.400	413.500
GR	567.600	417.400	566.900	421.400	566.500	425.300	566.300	429.200	565.700	433.200
GR	565.500	437.200	565.400	441.100	565.500	445.000	565.500	449.000	565.400	453.000
GR	566.500	456.900	567.200	460.800	569.000	464.800	569.100	468.700	569.400	472.700
GR	570.600	476.600	571.700	480.600	573.400	484.500	575.100	488.500	577.500	492.500

X1	2436.000	31.000	183.000	285.000	700.000	700.000	700.000	-0.000	-0.000	-0.000
X3	-0.000	-0.000	-0.000	183.000	-0.000	285.000	-0.000	-0.000	-0.000	-0.000
GR	579.000	0.000	579.900	85.000	578.500	135.000	577.100	183.000	575.100	185.000
GR	573.500	190.000	572.200	195.000	571.100	200.000	570.200	205.000	568.500	210.000
GR	567.700	215.000	566.400	220.000	565.600	225.000	565.300	230.000	565.000	235.000
GR	564.600	240.000	564.600	245.000	565.200	250.000	566.400	255.000	567.800	260.000
GR	568.800	265.000	569.900	270.000	571.500	275.000	574.700	280.000	575.100	281.000
GR	577.400	285.000	577.300	385.000	578.200	485.000	577.700	557.000	578.600	585.000
GR	579.800	605.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000
NC	.035	.035	.033	.300	.500	-0.000	-0.000	-0.000	-0.000	-0.000
QT	4.000	1500.000	1950.000	2100.000	2495.000	-0.000	-0.000	-0.000	-0.000	-0.000
X1	2736.000	26.000	300.000	400.000	300.000	300.000	300.000	-0.000	-0.000	-0.000
X3	-0.000	-0.000	-0.000	300.000	-0.000	400.000	-0.000	-0.000	-0.000	-0.000
GR	578.400	0.000	577.700	100.000	578.500	200.000	578.600	300.000	575.100	310.000
GR	573.400	315.000	572.200	320.000	570.600	325.000	570.000	330.000	569.900	335.000
GR	569.700	340.000	569.100	350.000	569.100	360.000	569.700	370.000	570.400	375.000
GR	571.700	380.000	572.900	385.000	574.400	390.000	575.100	392.000	578.600	400.000
GR	581.000	500.000	581.300	600.000	581.400	700.000	581.300	800.000	582.100	900.000
GR	583.200	1100.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000
X1	3436.000	-0.000	-0.000	-0.000	700.000	700.000	700.000	-0.000	.380	-0.000
X3	10.000	-0.000	-0.000	300.000	-0.000	400.000	-0.000	-0.000	-0.000	-0.000
X1	3836.000	27.000	200.000	300.000	400.000	400.000	400.000	-0.000	-0.000	-0.000
X3	-0.000	-0.000	-0.000	200.000	-0.000	300.000	-0.000	-0.000	-0.000	-0.000
GR	580.700	0.000	579.200	100.000	578.500	200.000	575.000	207.000	574.000	210.000
GR	573.000	215.000	572.600	220.000	571.900	225.000	571.000	230.000	570.400	235.000
GR	570.000	240.000	569.700	245.000	570.000	250.000	570.700	255.000	572.100	260.000
GR	573.400	265.000	573.700	270.000	575.000	275.000	575.400	278.000	579.800	290.000
GR	580.300	300.000	580.400	400.000	581.000	500.000	581.500	600.000	582.200	700.000
GR	581.800	800.000	581.900	843.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000
X1	4311.000	-0.000	-0.000	-0.000	475.000	475.000	475.000	-0.000	.200	-0.000
X3	-0.000	-0.000	-0.000	200.000	-0.000	290.000	-0.000	-0.000	-0.000	-0.000
X1	4786.000	29.000	393.000	500.000	475.000	475.000	475.000	-0.000	-0.000	-0.000
X3	10.000	-0.000	-0.000	393.000	-0.000	500.000	-0.000	-0.000	-0.000	-0.000
GR	582.100	0.000	581.200	100.000	580.800	200.000	581.100	212.000	580.300	300.000
GR	580.100	393.000	578.600	400.000	574.800	408.000	574.100	410.000	573.600	415.000
GR	573.200	420.000	572.700	425.000	571.800	430.000	570.800	435.000	570.500	440.000
GR	570.400	445.000	570.200	450.000	570.100	455.000	570.400	460.000	570.600	465.000
GR	571.400	470.000	572.600	475.000	573.700	480.000	574.400	483.000	579.200	489.000
GR	579.500	500.000	579.700	600.000	579.600	653.000	581.200	700.000	-0.000	-0.000
X1	4825.000	37.000	500.000	598.000	39.000	39.000	39.000	-0.000	-0.000	-0.000
X3	-0.000	-0.000	-0.000	500.000	585.000	598.000	585.000	-0.000	-0.000	-0.000
GR	581.900	0.000	582.000	20.000	581.800	100.000	581.300	200.000	581.100	300.000
GR	580.500	400.000	579.400	500.000	576.800	500.000	576.300	505.000	575.300	510.000
GR	574.800	515.000	573.600	520.000	572.900	525.000	572.000	530.000	571.600	535.000
GR	571.600	540.000	571.200	545.000	570.800	550.000	571.200	555.000	571.200	560.000
GR	571.100	565.000	571.200	570.000	571.700	575.000	572.300	580.000	573.200	585.000
GR	574.000	590.000	574.300	595.000	574.300	598.000	579.600	598.000	579.700	600.000
GR	579.600	700.000	579.700	751.000	579.600	800.000	590.100	900.000	590.400	1000.000
GR	580.900	1100.000	581.200	1200.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000
SB	-0.000	1.300	2.500	-0.000	51.700	-0.000	538.000	3.170	570.800	570.800
X1	4846.000	-0.000	-0.000	-0.000	21.000	21.000	21.000	-0.000	-0.000	-0.000
X2	-0.000	-0.000	1.000	578.300	579.400	-0.000	-0.000	-0.000	-0.000	-0.000
X3	-0.000	-0.000	-0.000	500.000	585.000	598.000	585.000	-0.000	-0.000	-0.000
BT	10.000	0.000	581.900	0.000	20.000	232.000	0.000	100.000	581.800	0.000
BT	200.000	581.300	0.000	300.000	581.100	0.000	400.000	560.500	0.000	500.000
BT	579.400	578.200	598.000	579.600	578.300	600.000	579.700	0.000	700.000	579.600
BT	0.000	751.000	579.700	0.000	800.000	579.600	0.000	900.000	580.100	0.000

	X1	4847.000	-0.000	-0.000	-0.000	1.000	1.000	1.000	-0.000	-0.000	-0.000
	X3	-0.000	-0.000	-0.000	500.000	585.000	598.000	585.000	-0.000	-0.000	-0.000
	X1	5436.000	34.000	494.000	594.000	589.000	589.000	589.000	-0.000	-0.000	-0.000
	X3	10.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000
	GR	579.740	0.000	578.940	94.000	579.740	194.000	580.140	272.000	580.340	294.000
	GR	581.940	394.000	580.840	494.000	574.740	506.000	574.240	508.000	573.940	509.000
	GR	573.240	514.000	572.840	519.000	571.840	524.000	571.140	529.000	570.740	534.000
	GR	570.640	539.000	570.840	544.000	571.840	549.000	572.940	554.000	573.240	559.000
	GR	573.440	564.000	573.740	569.000	574.240	574.000	574.740	576.000	581.140	594.000
	GR	580.740	658.000	580.840	694.000	581.340	794.000	581.940	794.000	582.440	994.000
	GR	582.940	1094.000	583.240	1194.000	582.940	1294.000	582.640	1349.000	-0.000	-0.000
	X1	5936.000	34.000	494.000	594.000	500.000	500.000	500.000	-0.000	-0.000	-0.000
	X3	10.000	-0.000	-0.000	400.000	-0.000	600.000	-0.000	-0.000	-0.000	-0.000
	GR	579.600	0.000	578.800	94.000	579.600	194.000	580.000	272.000	580.200	294.000
	GR	581.800	394.000	580.700	494.000	574.600	506.000	574.200	508.000	573.800	509.000
	GR	573.100	514.000	572.700	519.000	571.700	524.000	571.000	529.000	570.600	534.000
	GR	570.500	539.000	570.700	544.000	571.700	549.000	572.800	554.000	573.100	559.000
	GR	573.300	564.000	573.600	569.000	574.100	574.000	574.600	576.000	581.000	594.000
	GR	580.600	658.000	580.700	694.000	581.200	794.000	581.800	894.000	582.300	994.000
	GR	582.800	1094.000	583.100	1194.000	582.800	1294.000	582.500	1349.000	-0.000	-0.000
	X1	6416.000	28.000	560.000	660.000	480.000	480.000	480.000	-0.000	-0.000	-0.000
	X3	10.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000
	GR	581.430	0.000	581.930	60.000	581.530	160.000	581.330	260.000	581.630	360.000
	GR	581.930	460.000	581.930	560.000	581.130	577.000	574.830	592.000	573.230	593.000
	GR	572.230	595.000	570.930	600.000	570.330	605.000	570.830	610.000	571.830	615.000
	GR	572.430	620.000	572.930	625.000	573.130	630.000	573.430	635.000	574.130	640.000
	GR	574.230	642.000	574.830	644.000	581.930	660.000	581.230	716.000	582.230	760.000
	GR	581.930	860.000	582.030	960.000	581.730	1010.000	-0.000	-0.000	-0.000	-0.000
	X1	6786.000	28.000	560.000	660.000	370.000	370.000	370.000	-0.000	-0.000	-0.000
	X3	10.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000
	GR	581.300	0.000	581.800	60.000	581.400	160.000	581.200	260.000	581.500	360.000
	GR	581.800	460.000	581.600	560.000	581.000	577.000	574.700	592.000	573.100	593.000
	GR	572.100	595.000	570.800	600.000	570.200	605.000	570.700	610.000	571.700	615.000
	GR	572.300	620.000	572.800	625.000	573.000	630.000	573.300	635.000	574.000	640.000
	GR	574.100	642.000	574.700	644.000	581.800	660.000	581.100	716.000	582.100	760.000
	GR	581.800	860.000	581.900	960.000	581.600	1010.000	-0.000	-0.000	-0.000	-0.000
	X1	6835.000	-0.000	-0.000	-0.000	49.000	49.000	49.000	-0.000	1.370	-0.000
	NC	-0.000	-0.000	.025	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000
	X1	6836.000	40.000	900.000	973.000	1.000	1.000	1.000	-0.000	-0.000	-0.000
	X3	10.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000
	GR	582.000	0.000	582.900	100.000	582.800	200.000	582.000	300.000	581.700	400.000
	GR	581.300	500.000	580.700	600.000	580.900	700.000	581.400	800.000	582.000	900.000
	GR	574.400	900.000	574.000	905.000	573.200	910.000	572.200	915.000	572.600	920.000
	GR	571.600	925.000	572.100	930.000	573.500	935.000	578.200	935.000	578.200	938.000
	GR	573.600	938.000	573.800	940.000	573.400	945.000	572.200	950.000	572.000	955.000
	GR	572.700	960.000	573.600	965.000	574.500	970.000	574.700	973.000	582.000	973.000
	GR	582.000	976.000	581.600	1000.000	581.200	1100.000	581.000	1200.000	580.900	1300.000
	GR	581.500	1400.000	582.000	1500.000	582.600	1600.000	582.800	1700.000	583.000	1807.000
	SH	.900	1.500	2.900	-0.000	73.000	2.800	385.100	-0.000	571.600	571.600
	X1	6916.000	-0.000	-0.000	-0.000	80.000	80.000	80.000	-0.000	-0.000	-0.000
	X2	-0.000	-0.000	1.000	578.300	583.000	-0.000	-0.000	-0.000	-0.000	-0.000
	X3	10.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	583.000	583.000	-0.000
	BT	23.000	0.000	582.000	0.000	100.000	582.900	0.000	200.000	582.800	0.000
	BT	300.000	582.000	0.000	400.000	581.700	0.000	500.000	581.300	0.000	600.000
	BT	580.700	0.000	700.000	580.900	0.000	800.000	581.400	0.000	900.000	582.000
	BT	578.300	935.000	582.000	578.200	938.000	582.000	578.200	973.000	582.000	578.200
	BT	976.000	582.000	0.000	1000.000	581.600	0.000	1100.000	581.200	0.000	1200.000

	BT	0.000	1600.000	582.600	0.000	1700.000	582.800	0.000	1607.000	583.000	0.000
	NC	-0.000	-0.000	.033	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000
	X1	6917.000	28.000	560.000	660.000	1.000	1.000	1.000	-0.000	1.400	-0.000
	X3	10.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000
1	GR	581.300	0.000	581.800	60.000	581.400	160.000	581.200	260.000	581.500	360.000
2	GR	581.800	460.000	581.800	560.000	581.000	577.000	574.700	592.000	573.100	593.000
3	GR	572.100	595.000	570.800	600.000	570.200	605.000	570.700	610.000	571.700	615.000
4	GR	572.300	620.000	572.800	625.000	573.000	630.000	573.300	635.000	574.000	640.000
5	GR	574.100	642.000	574.700	644.000	581.800	660.000	581.100	716.000	582.100	760.000
6	GR	581.800	860.000	581.900	960.000	581.600	1010.000	-0.000	-0.000	-0.000	-0.000
7											
8	X1	7436.000	-0.000	-0.000	-0.000	519.000	519.000	519.000	-0.000	-.400	-0.000
9	X3	10.000	-0.000	-0.000	560.000	-0.000	660.000	-0.000	-0.000	-0.000	-0.000
10											
11	X1	7936.000	22.000	436.000	516.000	500.000	500.000	500.000	-0.000	-0.000	-0.000
12	X3	10.000	-0.000	-0.000	436.000	-0.000	516.000	-0.000	-0.000	-0.000	-0.000
13	GR	581.800	0.000	581.700	116.000	581.100	216.000	580.900	316.000	582.500	416.000
14	GR	582.600	436.000	574.900	453.000	573.800	456.000	572.400	461.000	571.800	466.000
15	GR	571.200	471.000	570.800	476.000	571.000	481.000	571.500	486.000	572.300	491.000
16	GR	573.700	494.000	574.900	495.000	583.100	516.000	582.800	616.000	582.200	716.000
17	GR	582.200	866.000	581.700	891.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000
18											
19	X1	8536.000	40.000	305.500	383.000	600.000	600.000	600.000	-0.000	-0.000	-0.000
20	X3	10.000	-0.000	-0.000	150.000	-0.000	400.000	-0.000	-0.000	-0.000	-0.000
21	GR	583.000	0.000	582.400	100.000	581.600	221.200	581.800	260.000	581.700	305.500
22	GR	580.300	308.000	579.000	310.600	577.600	313.200	576.600	315.800	575.900	318.400
23	GR	575.200	320.900	574.600	323.500	573.900	326.100	573.300	328.700	572.900	331.300
24	GR	572.100	333.900	571.400	336.400	571.100	339.000	570.900	341.600	570.900	344.200
25	GR	571.100	346.800	571.300	349.400	571.600	351.900	572.200	354.500	572.800	357.100
26	GR	573.300	359.700	574.300	362.300	575.100	364.900	575.700	367.400	576.400	370.000
27	GR	577.200	372.600	578.400	375.200	579.600	377.800	580.800	380.400	582.100	383.000
	GR	582.000	400.000	581.800	490.000	581.600	598.000	581.800	705.000	582.400	813.000
	X1	9136.000	24.000	175.000	250.000	600.000	600.000	600.000	-0.000	-0.000	-0.000
	X3	-0.000	-0.000	-0.000	140.000	-0.000	310.000	-0.000	-0.000	-0.000	-0.000
	GR	584.300	0.000	583.800	40.000	582.200	140.000	580.800	175.000	575.500	184.000
	GR	574.900	194.000	574.500	195.000	573.600	200.000	571.300	205.000	570.900	210.000
	GR	571.300	215.000	572.000	220.000	573.600	225.000	574.300	230.000	574.700	235.000
	GR	574.900	237.000	575.500	240.000	581.100	250.000	581.200	350.000	581.000	376.000
	GR	580.900	450.000	581.300	550.000	581.700	650.000	583.200	735.000	-0.000	-0.000
	X1	9586.000	24.000	175.000	250.000	450.000	450.000	450.000	-0.000	.035	-0.000
	X3	-0.000	-0.000	-0.000	50.000	-0.000	250.000	-0.000	-0.000	-0.000	-0.000
	GR	584.300	0.000	583.800	40.000	582.200	140.000	580.800	175.000	575.500	184.000
	GR	574.900	194.000	574.500	195.000	573.600	200.000	571.300	205.000	570.900	210.000
	GR	571.300	215.000	572.000	220.000	573.600	225.000	574.300	230.000	574.700	235.000
	GR	574.900	237.000	575.500	240.000	581.100	250.000	581.200	350.000	581.000	376.000
	GR	580.900	450.000	581.300	550.000	581.700	650.000	583.200	735.000	-0.000	-0.000
	X1	9596.000	20.000	345.000	445.000	10.000	10.000	10.000	-0.000	.030	-0.000
	X3	-0.000	-0.000	-0.000	245.000	-0.000	445.000	-0.000	-0.000	-0.000	-0.000
	GR	583.950	0.000	581.350	45.000	580.950	145.000	580.550	245.000	581.850	345.000
	GR	579.950	385.000	575.750	399.000	574.950	407.000	574.250	410.000	573.050	415.000
	GR	572.750	420.000	572.950	425.000	571.650	430.000	570.950	435.000	573.050	440.000
	GR	574.650	445.000	583.450	445.000	580.250	448.000	581.250	545.000	582.450	645.000
	X1	10286.000	20.000	345.000	445.000	690.000	690.000	690.000	-0.000	-0.000	-0.000
	X3	-0.000	-0.000	-0.000	245.000	-0.000	445.000	-0.000	-0.000	-0.000	-0.000
	GR	584.000	0.000	581.400	45.000	581.000	145.000	580.900	245.000	581.900	345.000
	GR	580.000	385.000	575.800	399.000	575.000	407.000	574.300	410.000	573.100	415.000
	GR	572.800	420.000	573.000	425.000	571.700	430.000	571.000	435.000	571.500	440.000
	GR	574.700	445.000	583.500	445.000	580.300	448.000	581.300	545.000	582.500	645.000
	X1	10336.000	22.000	400.000	445.000	50.000	50.000	50.000	-0.000	-0.000	-0.000

	XJ	-0.000	-0.000	-0.000	550.000	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]
	GR	583.100	0.000	581.300	100.000	580.900	200.000	580.200	300.000	579.800	400.000
	GR	573.000	401.000	573.000	405.000	573.000	410.000	573.000	415.000	573.000	420.000
	GR	572.500	430.000	572.600	435.000	573.700	440.000	574.800	444.000	580.000	445.000
	GR	580.500	500.000	581.300	600.000	582.300	700.000	582.700	800.000	583.000	900.000
	GR	583.000	908.000	584.200	960.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000
	X1	10636.000	27.000	655.000	855.000	300.000	300.000	300.000	-0.000	-0.000	-0.000
	X3	10.000	-0.000	-0.000	655.000	-0.000	800.000	-0.000	-0.000	-0.000	-0.000
	GR	582.670	0.000	582.670	55.000	584.370	155.000	585.670	255.000	586.070	355.000
	GR	586.270	455.000	585.470	555.000	584.570	655.000	583.370	677.000	574.870	697.000
	GR	573.770	700.000	573.070	705.000	572.470	710.000	572.470	715.000	573.670	720.000
	GR	574.570	725.000	575.070	727.000	575.970	738.000	582.570	755.000	583.870	855.000
	GR	583.270	955.000	583.670	1055.000	583.970	1068.000	583.570	1155.000	583.370	1255.000
	GR	583.070	1355.000	583.070	1455.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000
	X1	11536.000	27.000	655.000	855.000	900.000	900.000	900.000	-0.000	-0.000	-0.000
	X3	10.000	-0.000	-0.000	655.000	-0.000	855.000	-0.000	-0.000	-0.000	-0.000
	GR	582.600	0.000	582.600	55.000	584.300	155.000	585.600	255.000	586.000	355.000
	GR	586.200	455.000	585.400	555.000	584.500	655.000	583.300	677.000	574.800	697.000
	GR	573.700	700.000	573.000	705.000	572.400	710.000	572.400	715.000	573.600	720.000
	GR	574.500	725.000	575.000	727.000	575.900	738.000	582.600	755.000	583.800	855.000
	GR	583.200	955.000	583.600	1055.000	583.900	1068.000	583.500	1155.000	583.300	1255.000
	GR	583.000	1355.000	583.000	1455.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000
	EJ	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000

CCHV= .300 CEHV= .500

SECNO	DEPTH	C/SEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TW	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST
1.00	11.50	574.90	0.00	574.90	575.22	.32	0.00	0.00	584.60
3165.	0.	3165.	0.	0.	701.	0.	0.	0.	584.60
0.00	0.00	4.51	0.00	.035	.030	.035	0.000	563.40	529.17
.000601	-0.	-0.	-0.	0	0	1	0.00	89.83	619.00
30.00	11.52	574.92	0.00	0.00	575.23	.31	.02	.00	584.60
3165.	0.	3165.	0.	0.	703.	0.	0.	0.	584.60
.00	0.00	4.50	0.00	.035	.030	.035	.029	563.40	529.02
.000598	29.	29.	29.	0	0	1	0.00	89.93	619.00
60.00	11.54	574.94	0.00	0.00	575.25	.31	.02	.00	584.60
3165.	0.	3165.	0.	0.	705.	0.	1.	0.	584.60
.00	0.00	4.49	0.00	.035	.030	.035	.029	563.40	528.87
.000595	30.	30.	30.	0	0	1	0.00	90.13	619.00

3265 DIVIDED FLOW

NORMAL BRIDGE,NRD= 9 MIN ELTRD= 534.30 MAX ELLC= 580.30

D/S FACE OF JEFFERSON STREET BRIDGE

61.00	11.51	574.91	0.00	0.00	575.28	.38	.00	.03	584.60
3165.	0.	3165.	0.	0.	644.	0.	1.	0.	584.60
.00	0.00	4.92	0.00	.035	.030	.035	.029	563.40	529.09
.001082	1.	1.	1.	2	0	1	0.00	92.91	619.00

3265 DIVIDED FLOW

NORMAL BRIDGE,NRD= 9 MIN ELTRD= 584.30 MAX ELLC= 580.30

U/S FACE OF JEFFERSON STREET BRIDGE SEC. A

CONCRETE TWO SPAN BRIDGE

CONCRETE RAILING, TWO PIERS, 75 FEET WIDE

136.00	11.60	575.00	0.00	0.00	575.37	.37	.08	.00	584.60
3165.	0.	3165.	0.	0.	651.	0.	2.	0.	584.60
.01	0.00	4.86	0.00	.035	.030	.035	.029	563.40	528.33
.001054	75.	75.	75.	2	0	1	0.00	43.67	619.00

SECNO	DEPTH	C/SEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV

TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST
137.00	11.69	575.09	0.00	0.00	575.39	.30	.00	.02	584.60
3165.	0.	3165.	0.	0.	718.	0.	2.	0.	584.60
.01	0.00	4.41	0.00	.035	.030	.035	.029	563.40	527.62
.000569	1.	1.	1.	2	0	1	0.00	91.38	619.00

50 FEET U/S OF JEFFERSON STREET BRIDGE SEC. B

187.00	10.99	575.09	0.00	0.00	575.44	.34	.03	.02	583.10
3165.	0.	3165.	0.	0.	672.	0.	3.	0.	580.20
.01	0.00	4.71	0.00	.035	.030	.042	.029	564.10	343.54
.000652	50.	50.	50.	2	0	1	0.00	89.95	432.49

1490 NH CARD USED

REPEATED SECTION OF 737

DOCKS ON RIGHT BANK

362.00	11.41	575.38	0.00	0.00	575.56	.19	.08	.05	578.57
3165.	0.	3165.	0.	0.	913.	0.	6.	1.	577.17
.03	0.00	3.47	0.00	.035	.031	.042	.029	563.97	252.63
.000321	175.	175.	175.	2	0	1	0.00	143.47	396.10

3470 ENCROACHMENT STATIONS= 244.0 373.0 TYPE= 1 TARGET= 129.000

50 FEET D/S OF RAILROAD BRIDGE NO. 1 SEC. C

ENCROACHED FOR EXPANSION

737.00	11.79	575.49	0.00	0.00	575.68	.19	.11	.00	578.30
3165.	0.	3165.	0.	0.	912.	0.	14.	2.	100000.00
.06	0.00	3.47	0.00	.035	.030	.042	.030	563.70	251.60
.000282	375.	375.	375.	2	0	1	0.00	121.40	373.00

787.00	11.57	575.47	0.00	0.00	575.74	.26	.02	.04	581.00
3165.	0.	3165.	0.	0.	769.	0.	15.	2.	581.00
.06	0.00	4.12	0.00	.035	.032	.042	.030	563.90	795.00
.000624	50.	50.	50.	2	0	1	0.00	106.60	901.60

3265 DIVIDED FLOW

NORMAL BRIDGE,NRD= 4 MIN ELTRD= 581.00 MAX ELLC= 577.20

D/S FACE OF RAILROAD BRIDGE NO. 1

788.00	11.54	575.44	0.00	0.00	575.77	.33	.00	.03	581.00
3165.	0.	3165.	0.	0.	691.	0.	15.	2.	581.00
.06	0.00	4.58	0.00	.035	.032	.042	.030	563.90	795.00
.002401	1.	1.	1.	2	0	1	0.00	97.00	901.60

3265 DIVIDED FLOW

NORMAL BRIDGE,NRD= 4 MIN ELTRD= 581.00 MAX ELLC= 577.20

U/S FACE OF RAILROAD BRIDGE NO. 1 SEC. D

STEEL I-BEAM BRIDGE WITH 2-STEEL BENT PIERS

9 FEET WIDE, 7 OLD BENT PILES-CUTOFF

797.00	11.56	575.46	0.00	0.00	575.79	.32	.02	.00	581.00
3165.	0.	3165.	0.	0.	692.	0.	15.	2.	581.00
.06	0.00	4.57	0.00	.035	.032	.042	.030	563.90	795.00
.002389	9.	9.	9.	0	0	1	0.00	97.00	801.60

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	QLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST
798.00	11.65	575.55	0.00	0.00	575.81	.26	.00	.02	581.00
3165.	0.	3165.	0.	0.	777.	0.	15.	2.	581.00
.06	0.00	4.07	0.00	.035	.032	.042	.030	563.90	795.00
.000602	1.	1.	1.	2	0	1	0.00	106.60	801.60
844.00	10.58	575.58	0.00	0.00	575.84	.26	.03	.00	581.60
3165.	0.	3165.	0.	0.	780.	0.	16.	2.	581.40
.06	0.00	4.06	0.00	.035	.032	.042	.030	565.00	816.36
.000559	46.	46.	46.	2	0	1	0.00	105.39	921.75

3265 DIVIDED FLOW

NORMAL BRIDGE,NRD=16 MIN ELTRD= 581.40 MAX ELLC= 578.40

D/S FACE OF RAILROAD BRIDGE NO. 2

845.00	10.56	575.56	0.00	0.00	575.86	.30	.00	.02	581.60
3165.	0.	3165.	0.	0.	719.	0.	16.	2.	581.40
.06	0.00	4.40	0.00	.035	.032	.042	.030	565.00	816.42
.001856	1.	1.	1.	2	0	1	0.00	98.26	921.67

3265 DIVIDED FLOW

NORMAL BRIDGE,NRD=16 MIN ELTRD= 581.40 MAX ELLC= 578.40

U/S FACE OF RAILROAD BRIDGE NO. 2 SEC. E

WOOD BRIDGE WITH BALLAST AND TIE DECK

14.5 FEET WIDE, 7 BENT PIERS OF WOOD

14.5 FEET WIDE, 7 BENT PIERS OF WOOD

859.00	10.59	575.59	0.00	0.00	575.89	.30	.03	.00	581.50
3165.	0.	3165.	0.	0.	721.	0.	16.	2.	581.40
.06	0.00	4.39	0.00	.035	.032	.042	.030	565.00	816.36
.001842	15.	15.	15.	1	0	1	0.00	98.40	921.76
860.00	10.65	575.65	0.00	0.00	575.90	.25	.00	.01	581.50
3165.	0.	3165.	0.	0.	788.	0.	16.	2.	581.40
.06	0.00	4.02	0.00	.035	.032	.042	.030	565.00	815.17
.000544	1.	1.	1.	2	0	1	0.00	105.84	922.01
910.00	11.70	575.70	0.00	0.00	575.94	.23	.03	.01	583.10
3165.	0.	3165.	0.	0.	817.	0.	17.	2.	583.00
.07	0.00	3.88	0.00	.035	.032	.042	.030	564.00	835.00
.000501	50.	50.	50.	1	0	1	0.00	107.00	942.00

3265 DIVIDED FLOW

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANKELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	FLMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

NORMAL BRIDGE,NRD= 6 MIN ELTRD= 583.00 MAX ELLC= 578.60

D/S FACE OF RAILROAD BRIDGE NO. 3

D/S FACE OF RAILROAD BRIDGE NO. 3

911.00	11.68	575.68	0.00	0.00	575.96	.29	.00	.03	583.10
3165.	0.	3165.	0.	0.	735.	0.	17.	2.	583.00
.07	0.00	4.31	0.00	.035	.032	.042	.030	564.00	835.00
.002246	1.	1.	1.	2	0	1	0.00	105.00	942.00

3265 DIVIDED FLOW

NORMAL BRIDGE,NRD= 6 MIN ELTRD= 583.00 MAX ELLC= 578.60

U/S FACE OF RAILROAD BRIDGE NO. 3 SEC. F

STEEL I-BEAM BRIDGE WITH 2 STEEL PIERS

10 FEET WIDE, 8 SETS OF OLD PIER BENTS-CUTOFF

921.00	11.70	575.70	0.00	0.00	575.99	.29	.02	.00	583.10

[illegible]	0.	3165.	0.	0.	757.	0.	17.	2.	583.00
.07	0.00	4.30	0.00	.035	.032	.042	.030	564.00	835.00
.002227	10.	10.	10.	1	0	1	0.00	105.00	942.00
922.00	11.78	575.76	0.00	0.00	576.00	.23	.00	.02	583.10
3165.	0.	3165.	0.	0.	824.	0.	17.	2.	583.00
.07	0.00	3.84	0.00	.035	.032	.042	.030	564.00	835.00
.000487	1.	1.	1.	2	0	1	0.00	107.00	942.00
953.00	10.63	575.73	0.00	0.00	576.08	.35	.02	.06	581.00
3165.	0.	3165.	0.	0.	669.	0.	18.	3.	580.80
.07	0.00	4.73	0.00	.035	.032	.042	.030	565.10	600.00
.000726	31.	31.	31.	2	0	1	0.00	81.00	681.00

3265 DIVIDED FLOW

NORMAL BRIDGE,NRD=14 MIN ELTRD= 580.80 MAX ELLC= 577.70

D/S FACE OF RAILROAD BRIDGE NO. 4

954.00	10.55	575.65	0.00	0.00	576.17	.53	.00	.09	581.00
3165.	0.	3165.	0.	0.	542.	0.	18.	3.	580.80
.07	0.00	5.84	0.00	.035	.032	.042	.030	565.10	600.00
.003647	1.	1.	1.	2	0	1	0.00	67.20	681.00

3265 DIVIDED FLOW

NORMAL BRIDGE,NRD=14 MIN ELTRD= 580.80 MAX ELLC= 577.70

U/S FACE OF RAILROAD BRIDGE NO. 4 SEC. 6

CONCRETE BRIDGE, BOX BEAM DECK

WITH BALLAST AND RAILS, 30.5 FEET WIDE

985.00	10.68	575.78	0.00	0.00	576.29	.51	.11	.01	581.00
3165.	0.	3165.	0.	0.	551.	0.	18.	3.	580.80
.07	0.00	5.74	0.00	.035	.032	.042	.030	565.10	600.00
.003504	31.	31.	31.	2	0	1	0.00	67.20	681.00

SECNO	DEPTH	CHSEL	CRIWS	WSELK	EG	HV	HL	QLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TW	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELTRD	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST
986.00	10.92	576.02	0.00	0.00	576.35	.32	.00	.06	581.00
3165.	0.	3165.	0.	0.	692.	0.	18.	3.	580.80
.07	0.00	4.57	0.00	.035	.032	.042	.030	565.10	600.00
.000653	1.	1.	1.	2	0	1	0.00	81.00	681.00

ENCROACHMENT STATIONS= .0 700.0 TYPE= 1 TARGET= 699.999

OVERBANK AREA ASSUMED NON-EFFECTIVE, ELLEA= 581.10 ELREA= 100000.00

50 FEET UPSTREAM OF RAILROAD BRIDGE NO. 4 SEC. H

1036.00	9.90	576.10	0.00	0.00	576.39	.29	.03	.01	581.10
3165.	0.	3165.	0.	0.	734.	0.	19.	3.	100000.00
.07	0.00	4.31	0.00	.040	.030	.035	.030	566.20	584.30
.000647	50.	50.	50.	2	0	1	0.00	113.42	647.71

3470 ENCROACHMENT STATIONS= 374.0 492.5 TYPE= 1 TARGET= 119.500

OVERBANK AREA ASSUMED NON-EFFECTIVE, ELLEA= 579.10 ELREA= 100000.00

AVERAGE SECTION

1736.00	11.14	576.54	0.00	0.00	576.79	.25	.39	.01	579.10
3165.	0.	3165.	0.	0.	792.	0.	31.	4.	100000.00
.12	0.00	4.00	0.00	.060	.030	.035	.030	565.40	350.26
.000489	700.	700.	700.	1	0	1	0.00	110.65	491.92

3470 ENCROACHMENT STATIONS= 183.0 285.0 TYPE= 1 TARGET= 102.000

1450 FEET U/S OF RAILROAD BRIDGE NO. 4 SEC. I

CONFLUENCE OF SEXTON-KILFOIL DRAIN, NORTH ECORSE CREEK

AND ECORSE CREEK

2436.00	12.27	576.87	0.00	0.00	577.11	.24	.31	.00	577.10
3165.	0.	3165.	0.	0.	812.	0.	44.	6.	100000.00
.17	0.00	3.90	0.00	.060	.030	.035	.030	564.60	193.23
.000405	700.	700.	700.	2	0	1	0.00	100.85	264.08

CCHV= .300 CEHV= .500

3470 ENCROACHMENT STATIONS= 300.0 400.0 TYPE= 1 TARGET= 100.000

2089 FEET D/S OF MILL STREET BRIDGE SEC. A

2736.00	8.04	577.14	0.00	0.00	577.26	.12	.12	.03	578.60
1500.	0.	1500.	0.	0.	530.	0.	49.	7.	100000.00
.20	0.00	2.83	0.00	.035	.033	.035	.030	569.10	304.18
.000398	300.	300.	300.	2	0	1	0.00	92.48	396.66

3470 ENCROACHMENT STATIONS= 300.0 400.0 TYPE= 1 TARGET= 100.000

OVERBANK AREA ASSUMED NON-EFFECTIVE, ELLEA= 578.98 ELREA= 100000.00

REPEATED SECTION OF 2736

3436.00	7.94	577.42	0.00	0.00	577.55	.13	.29	.00	578.98
1500.	0.	1500.	0.	0.	521.	0.	57.	8.	100000.00

.000419	700.	700.	700.	0	0	1	0.00	91.97	396.43

3470 ENCROACHMENT STATIONS= 200.0 300.0 TYPE= 1 TARGET= 100.000

989 FEET D/S OF MILL STREET BRIDGE SEC. B

3836.00	7.91	577.61	0.00	0.00	577.82	.21	.23	.04	578.50
1500.	0.	1500.	0.	0.	409.	0.	62.	9.	100000.00
.30	0.00	3.66	0.00	.035	.033	.035	.031	569.70	201.79
.000805	400.	400.	400.	2	0	1	0.00	82.23	294.02

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

3470 ENCROACHMENT STATIONS= 200.0 290.0 TYPE= 1 TARGET= 90.000

4311.00	8.09	577.99	0.00	0.00	578.18	.19	.36	.00	578.70
1500.	0.	1500.	0.	0.	424.	0.	66.	10.	100000.00
.34	0.00	3.53	0.00	.035	.033	.035	.031	569.90	201.42
.000724	475.	475.	475.	2	0	1	0.00	83.09	294.51

3470 ENCROACHMENT STATIONS= 393.0 500.0 TYPE= 1 TARGET= 107.000

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 580.10 ELREA= 100000.00

39 FEET D/S OF MILL STREET BRIDGE SEC. C

4786.00	8.22	578.32	0.00	0.00	578.46	.13	.25	.02	580.10
1500.	0.	1500.	0.	0.	515.	0.	71.	11.	100000.00
.38	0.00	2.91	0.00	.035	.033	.035	.031	570.10	400.58
.000411	475.	475.	475.	2	0	1	0.00	87.32	487.90

3470 ENCROACHMENT STATIONS= 500.0 598.0 TYPE= 1 TARGET= 98.000
ELENCL= 585.00 ELENCR= 585.00

D/S FACE OF MILL STREET BRIDGE

4825.00	7.56	578.36	0.00	0.00	578.48	.12	.02	.00	579.40
1500.	0.	1500.	0.	0.	548.	0.	72.	11.	585.00
.39	0.00	2.74	0.00	.035	.033	.035	.031	570.80	500.00
.000405	39.	39.	39.	1	0	1	0.00	98.00	598.00

SPECIAL BRIDGE

SB	XK	XKOR	COFQ	RDLEN	BWC	BWP	BAREA	SS	ELCHU	ELCHD
	-0.00	1.30	2.50	-0.00	51.70	-0.00	538.00	3.17	570.80	570.80

PRESSURE FLOW

EGPRS	EGLWC	H3	QWEIR	QPR	BAREA	ELLC	ELTRD	CLASS

578.52 578.48 0.00 0. 1500. 538. 578.30 579.40 10.00

3470 ENCROACHMENT STATIONS= 500.0 598.0 TYPE= 1 TARGET= 98.000
ELENCL= 585.00 ELENCR= 585.00

U/S FACE OF MILL STREET BRIDGE SEC. D

STEEL TRUSS BRIDGE, SINGLE SPAN

9.5 FEET WIDE

4846.00	7.60	578.40	0.00	0.00	578.52	.11	.04	0.00	579.40
1500.	0.	1500.	0.	0.	553.	0.	72.	11.	585.00
.39	0.00	2.71	0.00	.035	.033	.035	.031	570.80	500.00
.000394	21.	21.	21.	2	0	1	0.00	98.00	598.00

3470 ENCROACHMENT STATIONS= 500.0 598.0 TYPE= 1 TARGET= 98.000
ELENCL= 585.00 ELENCR= 585.00

4847.00	7.60	578.40	0.00	0.00	578.52	.11	.00	.00	579.40
1500.	0.	1500.	0.	0.	553.	0.	72.	11.	585.00
.39	0.00	2.71	0.00	.035	.033	.035	.031	570.80	500.00
.000393	1.	1.	1.	0	0	1	0.00	98.00	598.00

OVERBANK AREA ASSUMED NON-EFFECTIVE, ELLEA= 580.84 ELREA= 581.14

5436.00	8.02	578.66	0.00	0.00	578.82	.16	.28	.02	580.84
1500.	0.	1500.	0.	0.	468.	0.	79.	12.	581.14
.44	0.00	3.21	0.00	.035	.033	.035	.032	570.64	498.30
.000572	589.	589.	589.	2	0	1	0.00	88.72	587.02

SECNO	DEPTH	CWSEL	CRIWS	NSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

3470 ENCROACHMENT STATIONS= 400.0 600.0 TYPE= 1 TARGET= 200.000

OVERBANK AREA ASSUMED NON-EFFECTIVE, ELLEA= 580.70 ELREA= 581.00

1090 FEET U/S OF MILL STREET BRIDGE SEC. E

5936.00	8.44	578.94	0.00	0.00	579.08	.14	.25	.01	580.70
1500.	0.	1500.	0.	0.	506.	0.	84.	13.	581.00
.49	0.00	2.97	0.00	.035	.033	.035	.032	570.50	497.46
.000455	500.	500.	500.	2	0	1	0.00	90.75	589.21

OVERBANK AREA ASSUMED NON-EFFECTIVE, ELLEA= 581.93 ELREA= 581.93

6416.00	8.85	579.18	0.00	0.00	579.40	.22	.23	.04	581.93
1500.	0.	1500.	0.	0.	399.	0.	89.	14.	581.93
.52	0.00	3.76	0.00	.035	.033	.035	.032	570.33	581.64
.000757	480.	480.	480.	1	0	1	0.00	72.17	653.81

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 581.80 ELREA= 581.80

49 FEET D/S OF SOUTHFIELD ROAD BRIDGE SEC. F

6786.00	9.27	579.47	0.00	0.00	579.66	.19	.25	.01	581.80
1500.	0.	1500.	0.	0.	430.	0.	93.	15.	581.80
.55	0.00	3.49	0.00	.035	.033	.035	.032	570.20	580.65
.000615	370.	370.	370.	2	0	1	0.00	74.09	654.74
6835.00	7.87	579.44	0.00	0.00	579.76	.32	.04	.06	583.17
1500.	0.	1500.	0.	0.	331.	0.	93.	15.	583.17
.55	0.00	4.53	0.00	.035	.033	.035	.032	571.57	583.97
.001293	49.	49.	49.	2	0	1	0.00	67.64	651.60

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 582.00 ELREA= 582.00

D/S FACE OF SOUTHFIELD ROAD BRIDGE

6836.00	8.05	579.65	0.00	0.00	579.81	.16	.00	.05	582.00
1500.	0.	1500.	0.	0.	471.	0.	93.	15.	582.00
.55	0.00	3.19	0.00	.035	.025	.035	.032	571.60	900.00
.000333	1.	1.	1.	2	0	1	0.00	73.00	973.00

SPECIAL BRIDGE

SB	XK	XKOR	COFQ	RDLEN	BWC	BWP	BAREA	SS	ELCHU	ELCHD
	.90	1.50	2.90	-0.00	73.00	2.50	385.10	-0.00	571.60	571.60

PRESSURE FLOW

EGPRS	EGLWC	H3	QWEIR	QPR	BAREA	ELLC	ELTRD	CLASS
580.01	579.82	.00	0.	1500.	385.	578.30	583.00	10.00

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 583.00 ELREA= 583.00

U/S FACE OF SOUTHFIELD ROAD BRIDGE SEC. G

CONCRETE BRIDGE WITH I-BEAM STRINGERS

80 FEET WIDE, 1 PIER 2.5 FEET WIDE

6916.00	8.26	579.86	0.00	0.00	580.01	.15	.20	0.00	582.00
1500.	0.	1500.	0.	0.	485.	0.	94.	15.	582.00
.56	0.00	3.09	0.00	.035	.025	.035	.032	571.60	900.00
.000302	80.	80.	80.	2	0	1	0.00	73.00	973.00

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	QLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	ROB	VOL	TOA	LEFT/RIGHT

TITLE	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 583.20 ELREA= 583.20

6917.00	8.19	579.79	0.00	0.00	580.07	.28	.00	.07	583.20
1500.	0.	1500.	0.	0.	353.	0.	94.	15.	583.20
.56	0.00	4.25	0.00	.035	.033	.035	.032	571.60	583.20
.001077	1.	1.	1.	2	0	1	0.00	69.12	652.32

3470 ENCROACHMENT STATIONS= 560.0 660.0 TYPE= 1 TARGET= 100.000

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 582.80 ELREA= 100000.00

REPEATED SECTION OF 6917

7436.00	9.13	580.33	0.00	0.00	580.53	.20	.43	.02	582.40
1500.	0.	1500.	0.	0.	420.	0.	99.	16.	100000.00
.60	0.00	3.57	0.00	.035	.033	.035	.032	571.20	580.97
.000657	519.	519.	519.	2	0	1	0.00	73.46	654.44

3470 ENCROACHMENT STATIONS= 436.0 516.0 TYPE= 1 TARGET= 40.000

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 582.60 ELREA= 100000.00

1020 FEET U/S OF SOUTHFIELD ROAD BRIDGE SEC. H

7936.00	9.85	580.65	0.00	0.00	580.83	.18	.29	.01	582.60
1500.	0.	1500.	0.	0.	441.	0.	104.	17.	100000.00
.64	0.00	3.40	0.00	.035	.033	.035	.032	570.80	440.31
.000521	500.	500.	500.	2	0	1	0.00	69.40	509.72

3470 ENCROACHMENT STATIONS= 150.0 400.0 TYPE= 1 TARGET= 250.000

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 581.70 ELREA= 582.10

8536.00	10.07	580.97	0.00	0.00	581.12	.16	.29	.01	581.70
1500.	0.	1500.	0.	0.	471.	0.	110.	18.	582.10
.70	0.00	3.19	0.00	.035	.033	.035	.032	570.90	365.61
.000450	600.	600.	600.	2	0	1	0.00	73.92	380.73

3470 ENCROACHMENT STATIONS= 140.0 310.0 TYPE= 1 TARGET= 170.000

2220 FEET U/S OF SOUTHFIELD ROAD BRIDGE SEC. I

9136.00	10.34	581.24	0.00	0.00	581.38	.14	.25	.01	580.60
1500.	1.	1498.	1.	2.	497.	7.	117.	19.	581.10
.75	.31	3.01	.20	.035	.033	.035	.032	570.90	163.63
.000385	600.	600.	600.	1	0	1	0.00	146.17	310.00

3470 ENCROACHMENT STATIONS= 50.0 250.0 TYPE= 1 TARGET= 200.000

9586.00	10.48	581.41	0.00	0.00	581.55	.14	.17	.00	580.84

1200.	1.	1439.	0.	4.	507.	0.	122.	20.	100000.04
.79	.35	2.96	0.00	.035	.033	.035	.032	570.94	160.58
.000363	450.	450.	450.	2	0	1	0.00	99.42	250.00

3265 DIVIDED FLOW

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

3470 ENCROACHMENT STATIONS= 245.0 445.0 TYPE= 1 TARGET= 200.000

9596.00	10.42	581.40	0.00	0.00	581.57	.18	.01	.02	581.86
1500.	7.	1493.	0.	14.	443.	0.	122.	21.	100000.03
.79	.48	3.37	0.00	.035	.033	.035	.032	570.98	245.00
.000754	10.	10.	10.	1	0	1	0.00	142.67	445.00

3470 ENCROACHMENT STATIONS= 245.0 445.0 TYPE= 1 TARGET= 200.000

50 FEET D/S OF EMPIRE STREET SEC. J

WALL ON RIGHT BANK

10286.00	10.90	581.90	0.00	0.00	582.04	.13	.45	.01	581.90
1500.	32.	1468.	0.	50.	497.	0.	130.	23.	100000.00
.86	.64	2.96	0.00	.035	.033	.035	.032	571.00	245.00
.000572	690.	690.	690.	2	0	1	0.00	200.00	445.00

3470 ENCROACHMENT STATIONS= 350.0 445.0 TYPE= 1 TARGET= 95.000

EMPIRE STREET BRIDGE SEC. K

BRIDGE HAS BEEN REMOVED

10336.00	9.41	581.91	0.00	0.00	582.08	.17	.03	.02	579.80
1500.	145.	1355.	0.	101.	392.	0.	131.	23.	100000.00
.86	1.44	3.46	0.00	.035	.033	.035	.032	572.50	350.00
.000454	50.	50.	50.	2	0	1	0.00	95.00	445.00

3470 ENCROACHMENT STATIONS= 655.0 800.0 TYPE= 1 TARGET= 145.000

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 584.57 ELREA= 100000.00

10636.00	9.59	582.06	0.00	0.00	582.24	.18	.15	.00	584.57
1500.	0.	1500.	0.	0.	440.	0.	134.	24.	100000.00
.89	0.00	3.41	0.00	.035	.033	.035	.032	572.47	680.07
.000557	300.	300.	300.	0	0	1	0.00	73.39	753.46

3470 ENCROACHMENT STATIONS= 655.0 855.0 TYPE= 1 TARGET= 200.000

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 584.50 ELREA= 100000.00

1200 FEET U/S OF EMPIRE STREET SEC. 1

11536.00	10.14	582.54	0.00	0.00	582.69	.15	.44	.01	584.50
1500.	0.	1500.	0.	0.	480.	0.	143.	26.	100000.00
.97	0.00	3.13	0.00	.035	.033	.035	.032	572.40	673.42
.000438	900.	900.	900.	1	0	1	0.00	76.00	754.12

```
**********************************************
HEC2 VERSION UPDATED JAN 1976
ERROR CORRECTIONS 01,02,03,04,05,06,07,08,09
MODIFICATIONS 52,53,54,55,56,57,58
**********************************************


T1       CITY OF ECORSE   5555-16   DICK ZANOTTI  P.M.
T2       100 YEAR FLOOD
T3       NORTH BRANCH OF ECORSE CREEK

J1  ICHECK     INQ        NINV       IDIR       STRT       METRIC     HVINS      Q          WSEL       FQ
       -10.       4.        -0.        -0. -0.000000      -0.00       -0.0       -0.    574.900     -0.000

J2  NPROF      IPLOT      PRFVS      XSECV      XSECH      FN         ALLDC      IBW        CHNIM      ITRACE
     3.000     -0.000     -1.000     -0.000     -0.000     -0.000     -0.000     -0.000     -0.000     -0.000


CCHV=     .300 CEHV=     .500
    SECNO     DEPTH     CWSEL     CRIWS     WSELK     EG        HV        HL        OLOSS     BANK ELEV
        Q      QLOB      QCH       QROB      ALOB      ACH       AROB      VOL       TWA    LEFT/RIGHT
     TIME      VLOB      VCH       VROB      XNL       XNCH      XNR       VTN       ELMIN       SSTA
    SLOPE     XLOBL     XLCH      XLOBR     ITRIAL    IDC       ICONT     CORAR     TOPWID      ENDST

     1.00     11.50    574.90      0.00    574.90    575.51      .61      0.00      0.00     584.60
     4410.       0.     4410.        0.        0.       701.       0.        0.        0.     584.60
      0.00      0.00      6.29      0.00      .035      .030      .035     0.000    563.40     529.17
   .001167        -0.       -0.       -0.         0         0         1      0.00     99.83     619.00

    30.00     11.54    574.94      0.00      0.00    575.55      .61       .03       .00     584.60
     4410.       0.     4410.        0.        0.       704.       0.        0.        0.     584.60
      .00      0.00      6.26      0.00      .035      .030      .035      .029    563.40     529.98
   .001155       29.       29.       29.         0         0         1      0.00     90.12     619.00

    60.00     11.58    574.98      0.00      0.00    575.59      .60       .03       .00     584.60
     4410.       0.     4410.        0.        0.       708.       0.        1.        0.     584.60
      .00      0.00      6.23      0.00      .035      .030      .035      .029    563.40     529.54
   .001141       30.       30.       30.         1         0         1      0.00     90.46     619.00


3265 DIVIDED FLOW

NORMAL BRIDGE,NRD= 9 MIN ELTRD=  584.30 MAX ELLC=  580.30

                D/S FACE OF JEFFERSON STREET BRIDGE

    61.00     11.52    574.92      0.00      0.00    575.65      .73       .00       .06     584.60
     4410.       0.     4410.        0.        0.       645.       0.        1.        0.     584.60
      .00      0.00      6.84      0.00      .035      .030      .035      .029    563.40     529.98
   .002091        1.        1.        1.         2         0         1      0.00     83.02     619.00
```

3203 DIVIDED FLOW

NORMAL BRIDGE,NRD= 9 MIN ELTRD= 584.30 MAX ELLC= 580.30

U/S FACE OF JEFFERSON STREET BRIDGE SEC. 4

CONCRETE TWO SPAN BRIDGE

CONCRETE RAILING, TWO PIERS, 75 FEET WIDE

136.00	11.72	575.12	0.00	0.00	575.81	.69	.15	.01	584.60
4410.	0.	4410.	0.	0.	662.	0.	2.	0.	584.60
.01	0.00	6.67	0.00	.035	.030	.035	.029	563.40	527.31
.001976	75.	75.	75.	2	0	1	0.00	84.69	619.00

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	QLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOP WD	ENDST
137.00	11.90	575.30	0.00	0.00	575.85	.55	.00	.04	584.60
4410.	0.	4410.	0.	0.	738.	0.	2.	0.	584.60
.01	0.00	5.98	0.00	.035	.030	.035	.029	563.40	525.83
.001035	1.	1.	1.	2	0	1	0.00	93.17	619.00

50 FEET U/S OF JEFFERSON STREET BRIDGE SEC. B

187.00	11.22	575.32	0.00	0.00	575.95	.63	.06	.04	583.10
4410.	0.	4410.	0.	0.	692.	0.	3.	0.	580.20
.01	0.00	6.37	0.00	.035	.030	.042	.029	564.10	341.65
.001185	50.	50.	50.	2	0	1	0.00	91.18	432.86

1490 NH CARD USED

REPEATED SECTION OF 737

DOCKS ON RIGHT BANK

362.00	11.89	575.86	0.00	0.00	576.17	.31	.13	.10	578.57
4410.	0.	4410.	0.	0.	983.	0.	6.	1.	577.17
.02	0.00	4.48	0.00	.035	.031	.042	.029	563.97	251.32
.000515	175.	175.	175.	2	0	1	0.00	145.84	397.16

3470 ENCROACHMENT STATIONS= 244.0 373.0 TYPE= 1 TARGET= 129.000

50 FEET D/S OF RAILROAD BRIDGE NO. 1 SEC. C

ENCROACHED FOR EXPANSION

737.00	12.34	576.04	0.00	0.00	576.35	.31	.18	.00	578.50
4410.	0.	4410.	0.	0.	979.	0.	15.	2.	100000.00
.04	0.00	4.50	0.00	.035	.030	.042	.030	563.70	257.11
.000448	375.	375.	375.	2	0	1	0.00	122.89	373.00

787.00	12.11	576.01	0.00	0.00	576.45	.44	.03	.06	581.00
4410.	0.	4410.	0.	0.	826.	0.	16.	2.	581.00
.04	0.00	5.34	0.00	.035	.032	.042	.030	563.90	795.00
.000965	50.	50.	50.	2	0	1	0.00	106.60	901.60

3265 DIVIDED FLOW

NORMAL BRIDGE, NRD= 4 MIN ELTRD= 581.00 MAX ELLC= 577.20

D/S FACE OF RAILROAD BRIDGE NO. 1

788.00	12.06	575.96	0.00	0.00	576.50	.54	.00	.05	581.00
4410.	0.	4410.	0.	0.	744.	0.	16.	2.	581.00
.04	0.00	5.92	0.00	.035	.032	.042	.030	563.90	795.00
.003859	1.	1.	1.	2	0	1	0.00	104.00	901.60

3265 DIVIDED FLOW

NORMAL BRIDGE, NRD= 4 MIN ELTRD= 581.00 MAX ELLC= 577.20

U/S FACE OF RAILROAD BRIDGE NO. 1 SEC. D

STEEL I-BEAM BRIDGE WITH 2-STEEL BENT PIERS

9 FEET WIDE, 7 OLD BENT PILES-CUTOFF

797.00	12.10	576.00	0.00	0.00	576.54	.54	.03	.00	581.00
4410.	0.	4410.	0.	0.	749.	0.	16.	2.	581.00
.05	0.00	5.89	0.00	.035	.032	.042	.030	563.90	795.00
.003788	9.	9.	9.	2	0	1	0.00	104.00	901.60

SECNO	DEPTH	CHSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNP	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDSTA
798.00	12.25	576.15	0.00	0.00	576.57	.43	.00	.03	581.00
4410.	0.	4410.	0.	0.	841.	0.	16.	2.	581.00
.05	0.00	5.25	0.00	.035	.032	.042	.030	563.90	795.00
.000912	1.	1.	1.	2	0	1	0.00	106.60	901.60
844.00	11.20	576.20	0.00	0.00	576.62	.42	.04	.00	581.00
4410.	0.	4410.	0.	0.	846.	0.	17.	2.	581.40
.05	0.00	5.21	0.00	.035	.032	.042	.030	565.00	815.00
.000867	46.	46.	45.	2.	0	1	0.00	108.98	923.92

3265 DIVIDED FLOW

D/S FACE OF RAILROAD BRIDGE NO. 2

845.00	11.16	576.16	0.00	0.00	576.66	.50	.00	.04	581.50
4410.	0.	4410.	0.	0.	779.	0.	17.	2.	581.40
.05	0.00	5.66	0.00	.035	.032	.042	.030	565.00	815.00
.002965	1.	1.	1.	2	0	1	0.00	101.85	923.85

3265 DIVIDED FLOW

NORMAL BRIDGE.NRD=16 MIN ELTRD= 581.40 MAX ELLC= 578.40

U/S FACE OF RAILROAD BRIDGE NO. 2 SEC. E

WOOD BRIDGE WITH BALLAST AND TIE DECK

14.5 FEET WIDE, 7 BENT PIERS OF WOOD

14.5 FEET WIDE, 7 BENT PIERS OF WOOD

859.00	11.21	576.21	0.00	0.00	576.70	.49	.04	.00	581.50
4410.	0.	4410.	0.	0.	784.	0.	17.	2.	581.40
.05	0.00	5.62	0.00	.035	.032	.042	.030	565.00	815.00
.002915	15.	15.	15.	2	0	1	0.00	102.00	924.00

860.00	11.32	576.32	0.00	0.00	576.73	.41	.00	.02	581.50
4410.	0.	4410.	0.	0.	859.	0.	17.	2.	581.40
.05	0.00	5.13	0.00	.035	.032	.042	.030	565.00	815.00
.000826	1.	1.	1.	2	0	1	0.00	109.00	924.00

910.00	12.39	576.39	0.00	0.00	576.77	.38	.04	.01	583.10
4410.	0.	4410.	0.	0.	891.	0.	18.	2.	583.00
.05	0.00	4.95	0.00	.035	.032	.042	.030	564.00	835.00
.000739	50.	50.	50.	1	0	1	0.00	107.00	942.00

3265 DIVIDED FLOW

SECNO	DEPTH	CHSEL	CHINS	WSELK	EG	HV	HL	QLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

NORMAL BRIDGE.NRD= 6 MIN ELTRD= 583.00 MAX ELLC= 578.60

D/S FACE OF RAILROAD BRIDGE NO. 3

D/S FACE OF RAILROAD BRIDGE NO. 3

911.00	12.35	576.35	0.00	0.00	576.82	.47	.00	.04	583.10

...	0.	+410.	3.	0.	806.	0.	13.	2.	583.00
.05	0.00	5.47	0.00	.035	.032	.042	.030	564.00	835.00
.003268	1.	1.	1.	2	0	1	0.00	105.00	942.00

3265 DIVIDED FLOW

NORMAL BRIDGE,NRD= 6 MIN ELTRD= 583.00 MAX ELLC= 578.60

U/S FACE OF RAILROAD BRIDGE NO. 3 SEC. F

STEEL I-BEAM BRIDGE WITH 2 STEEL PIERS

10 FEET WIDE, 8 SETS OF OLD PIER BENTS-CUTOFF

921.00	12.39	576.39	0.00	0.00	576.85	.46	.03	.00	583.10
4410.	0.	4410.	0.	0.	809.	0.	18.	2.	583.00
.05	0.00	5.45	0.00	.035	.032	.042	.030	564.00	835.00
.003232	10.	10.	10.	1	0	1	0.00	105.00	942.00
922.00	12.51	576.51	0.00	0.00	576.88	.37	.00	.03	583.10
4410.	0.	4410.	0.	0.	902.	0.	18.	2.	583.00
.05	0.00	4.89	0.00	.035	.032	.042	.030	564.00	835.00
.000710	1.	1.	1.	2	0	1	0.00	107.00	942.00
953.00	11.34	576.44	0.00	0.00	577.01	.57	.03	.10	581.00
4410.	0.	4410.	0.	0.	726.	0.	19.	3.	580.80
.05	0.00	6.08	0.00	.035	.032	.042	.030	565.10	600.00
.001096	31.	31.	31.	2	0	1	0.00	81.00	681.00

3265 DIVIDED FLOW

NORMAL BRIDGE,NRD=14 MIN ELTRD= 580.80 MAX ELLC= 577.70

D/S FACE OF RAILROAD BRIDGE NO. 4

954.00	11.18	576.28	0.00	0.00	577.17	.88	.00	.15	581.00
4410.	0.	4410.	0.	0.	585.	0.	19.	3.	580.80
.05	0.00	7.53	0.00	.035	.032	.042	.030	565.10	600.00
.005859	1.	1.	1.	2	0	1	0.00	67.20	681.00

3265 DIVIDED FLOW

NORMAL BRIDGE,NRD=14 MIN ELTRD= 580.80 MAX ELLC= 577.70

U/S FACE OF RAILROAD BRIDGE NO. 4 SEC. G

CONCRETE BRIDGE, BOX BEAM DECK

WITH BALLAST AND RAILS, 30.3 FEET WIDE

985.00	11.42	576.52	0.00	0.00	577.35	.84	.17	.01	581.00
4410.	0.	4410.	0.	0.	601.	0.	19.	3.	580.80
.05	0.00	7.34	0.00	.035	.032	.042	.030	565.10	600.00
.005491	31.	31.	31.	2	0	1	0.00	67.20	681.00

SECNO	DEPTH	CHSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOP WID	ENDST
986.00	11.84	576.94	0.00	0.00	577.45	.51	.00	.10	581.00
4410.	0.	4410.	0.	0.	766.	0.	19.	3.	580.80
.05	0.00	5.75	0.00	.035	.032	.042	.030	565.10	600.00
.000927	1.	1.	1.	2	0	1	0.00	81.00	681.00

3470 ENCROACHMENT STATIONS= .0 700.0 TYPE= 1 TARGET= 699.999

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 581.10 ELREA= 100000.00

50 FEET UPSTREAM OF RAILROAD BRIDGE NO. 4 SEC. H

1036.00	10.90	577.10	0.00	0.00	577.52	.42	.04	.03	581.10
4410.	0.	4410.	0.	0.	850.	0.	20.	3.	100000.00
.06	0.00	5.19	0.00	.040	.030	.035	.030	566.20	580.44
.000822	50.	50.	50.	0	0	1	0.00	118.70	699.14

3470 ENCROACHMENT STATIONS= 374.0 492.5 TYPE= 1 TARGET= 118.500

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 579.10 ELREA= 100000.00

AVERAGE SECTION

1736.00	12.28	577.68	0.00	0.00	578.04	.36	.49	.02	579.10
4410.	0.	4410.	0.	0.	920.	0.	35.	5.	100000.00
.10	0.00	4.79	0.00	.060	.030	.035	.030	565.40	376.92
.000614	700.	700.	700.	2	0	1	0.00	115.58	492.50

3470 ENCROACHMENT STATIONS= 183.0 285.0 TYPE= 1 TARGET= 102.000

1450 FEET U/S OF RAILROAD BRIDGE NO. 4 SEC. I

CONFLUENCE OF SEXTON-KILFOIL DRAIN, NORTH ECORSE CREEK

AND ECORSE CREEK

2436.00	13.48	578.08	0.00	0.00	578.43	.35	.39	.00	577.10
4410.	0.	4410.	0.	0.	936.	0.	49.	5.	100000.00
.14	0.00	4.71	0.00	.060	.030	.035	.030	564.60	183.00
.000510	700.	700.	700.	2	0	1	0.00	102.00	285.00

CCHV= .300 CEHV= .500

3470 ENCROACHMENT STATIONS= 300.0 400.0 TYPE= 1 TARGET= 100.000

2089 FEET D/S OF MILL STREET BRIDGE SEC. A

2736.00	9.37	578.47	0.00	0.00	578.63	.16	.14	.06	578.60
2100.	0.	2100.	0.	0.	658.	0.	55.	7.	100000.00
.17	0.00	3.19	0.00	.035	.033	.035	.030	569.10	300.37
.000419	300.	300.	300.	2	0	1	0.00	99.34	399.70

3470 ENCROACHMENT STATIONS= 300.0 400.0 TYPE= 1 TARGET= 100.000

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 578.98 ELREA= 100000.00

REPEATED SECTION OF 2736

3436.00	9.29	578.77	0.00	0.00	578.93	.16	.30	.00	578.98
2100.	0.	2100.	0.	0.	649.	0.	65.	9.	100000.00
.23	0.00	3.23	0.00	.035	.033	.035	.031	569.44	300.61
.000435	700.	700.	700.	2	0	1	0.00	98.91	399.51

3470 ENCROACHMENT STATIONS= 200.0 300.0 TYPE= 1 TARGET= 100.000

989 FEET D/S OF MILL STREET BRIDGE SEC. B

3836.00	9.25	578.95	0.00	0.00	579.20	.25	.23	.04	578.50
2100.	0.	2100.	0.	0.	523.	0.	71.	9.	100000.00
.25	0.00	4.01	0.00	.035	.033	.035	.031	569.70	200.00
.000766	400.	400.	400.	1	0	1	0.00	87.67	287.67

SECNO	DEPTH	CHSEL	CRIWS	WSELK	EG	HV	HL	QLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	STN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

3470 ENCROACHMENT STATIONS= 200.0 290.0 TYPE= 1 TARGET= 90.000

4311.00	9.42	579.32	0.00	0.00	579.55	.24	.35	.00	578.70
2100.	0.	2100.	0.	0.	539.	0.	77.	10.	100000.00
.29	0.00	3.90	0.00	.035	.033	.035	.031	569.90	200.00
.000703	475.	475.	475.	2	0	1	0.00	88.14	288.14

3470 ENCROACHMENT STATIONS= 393.0 500.0 TYPE= 1 TARGET= 107.000

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 580.10 ELREA= 100000.00

39 FEET D/S OF MILL STREET BRIDGE SEC. C

4786.00	9.59	579.69	0.00	0.00	579.85	.17	.28	.02	580.10
2100.	0.	2100.	0.	0.	641.	0.	83.	11.	100000.00
.33	0.00	3.28	0.00	.035	.033	.035	.031	570.10	394.96
.000497	475.	475.	475.	1	0	1	0.00	105.02	500.00

3470 ENCROACHMENT STATIONS= 500.0 598.0 TYPE= 1 TARGET= 98.000

ELENCL= 585.00 ELENCR= 585.00

D/S FACE OF MILL STREET BRIDGE

4825.00	8.93	579.73	0.00	0.00	579.88	.15	.02	.01	579.40
2100.	0.	2100.	0.	0.	683.	0.	94.	12.	585.00
.33	0.00	3.08	0.00	.035	.033	.035	.031	570.80	500.00
.000394	39.	39.	39.	2	0	1	0.00	96.00	598.00

SPECIAL BRIDGE

SB	XK	XKOR	COFQ	RDLEN	BNC	BWP	BAREA	SS	ELCRD	ELCHD
	-0.00	1.30	2.50	-0.00	51.70	-0.00	538.00	3.17	570.80	570.80

PRESSURE AND WEIR FLOW

EGPRS	EGLWC	H3	QWEIR	QBR	BAREA	ELLC	ELTRD	CLASS
580.04	579.88	0.00	207.	1881.	538.	578.30	579.40	30.00

3470 ENCROACHMENT STATIONS= 500.0 598.0 TYPE= 1 TARGET= 98.000
ELENCL= 585.00 ELENCR= 585.00

U/S FACE OF MILL STREET BRIDGE SEC. D

STEEL TRUSS BRIDGE, SINGLE SPAN

9.5 FEET WIDE

4846.00	9.03	579.83	0.00	0.00	579.98	.14	.10	0.00	579.40
2100.	0.	2100.	0.	0.	693.	0.	84.	12.	585.00
.33	0.00	3.03	0.00	.035	.033	.035	.031	570.80	500.00
.000376	21.	21.	21.	2	0	3	0.00	98.00	598.00

3470 ENCROACHMENT STATIONS= 500.0 598.0 TYPE= 1 TARGET= 98.000
ELENCL= 585.00 ELENCR= 585.00

4847.00	9.03	579.83	0.00	0.00	579.98	.14	.00	.00	579.40
2100.	0.	2100.	0.	0.	693.	0.	84.	12.	585.00
.33	0.00	3.03	0.00	.035	.033	.035	.031	570.80	500.00
.000376	1.	1.	1.	0	0	1	0.00	98.00	598.00

3280 CROSS SECTION 5436.00 EXTENDED .32 FEET

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 580.84 ELREA= 581.14

5436.00	9.43	580.07	0.00	0.00	580.27	.19	.27	.02	580.84
2100.	0.	2100.	0.	0.	597.	0.	93.	13.	581.14
.38	0.00	3.52	0.00	.035	.033	.035	.032	570.64	495.53
.000550	589.	589.	589.	1	0	1	0.00	95.45	598.48

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	ATW	ELMIN	SSTA

SEC E XLOBL XLCH XLOBR ITRIAL IOC ICONT CORAR TOPWID ENDST

3470 ENCROACHMENT STATIONS= 400.0 600.0 TYPE= 1 TARGET= 200.000

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 580.70 ELREA= 581.00

1090 FEET U/S OF MILL STREET BRIDGE SEC. E

5936.00	9.85	580.35	0.00	0.00	580.52	.17	.25	.01	580.70
2100.	0.	2100.	0.	0.	639.	0.	100.	14.	581.00
.42	0.00	3.29	0.00	.035	.033	.035	.032	570.50	494.68
.000453	500.	500.	500.	2	0	1	0.00	97.50	592.18

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 581.93 ELREA= 581.93

6416.00	10.25	580.58	0.00	0.00	580.85	.27	.28	.05	581.93
2100.	0.	2100.	0.	0.	505.	0.	106.	15.	581.93
.45	0.00	4.16	0.00	.035	.033	.035	.032	570.33	578.29
.000762	480.	480.	480.	1	0	1	0.00	78.69	656.98

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 581.80 ELREA= 581.80

49 FEET D/S OF SOUTHFIELD ROAD BRIDGE SEC. F

6786.00	10.68	580.88	0.00	0.00	581.12	.24	.26	.01	581.80
2100.	0.	2100.	0.	0.	539.	0.	111.	16.	581.80
.48	0.00	3.90	0.00	.035	.033	.035	.032	570.20	577.26
.000636	370.	370.	370.	2	0	1	0.00	80.64	657.93

6835.00	9.29	580.86	0.00	0.00	581.22	.37	.04	.07	583.17
2100.	0.	2100.	0.	0.	431.	0.	111.	16.	583.17
.48	0.00	4.87	0.00	.035	.033	.035	.032	571.57	580.60
.001194	49.	49.	49.	2	0	1	0.00	74.18	654.79

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 582.00 ELREA= 582.00

D/S FACE OF SOUTHFIELD ROAD BRIDGE

6836.00	9.46	581.06	0.00	0.00	581.27	.21	.00	.05	582.00
2100.	0.	2100.	0.	0.	573.	0.	111.	16.	582.00
.48	0.00	3.66	0.00	.035	.025	.035	.032	571.60	900.00
.000351	1.	1.	1.	2	0	1	0.00	73.00	973.00

SPECIAL BRIDGE

SBX	XKOR	COFQ	RDLEN	BAC	BWP	BAREA	SS	ELCHU	ELCHD
.90	1.50	2.90	-0.00	73.00	2.50	385.10	-0.00	571.60	571.60

PRESSURE FLOW

EGPRS	EGLWC	WS	QWEIR	QPR	BAREA	ELLC	ELTRD	CLASS

581.76 581.28 .01 0. 2100. 385. 578.30 583.00 10.00

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 583.00 ELREA= 583.00

U/S FACE OF SOUTHFIELD ROAD BRIDGE SEC. G

CONCRETE BRIDGE WITH I-BEAM STRINGERS

80 FEET WIDE, 1 PIER 2.5 FEET WIDE

6916.00	9.97	581.57	0.00	0.00	581.76	.18	.48	0.00	582.00
2100.	0.	2100.	0.	0.	611.	0.	112.	16.	582.00
.49	0.00	3.44	0.00	.035	.025	.035	.032	571.60	900.00
.000289	80.	80.	80.	2	0	1	0.00	73.00	973.00

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 583.20 ELREA= 583.20

6917.00	9.92	581.52	0.00	0.00	581.82	.30	.00	.06	583.20
2100.	0.	2100.	0.	0.	479.	0.	112.	16.	583.20
.49	0.00	4.39	0.00	.035	.033	.035	.032	571.60	579.10
.000887	1.	1.	1.	2	0	1	0.00	77.10	656.21

3470 ENCROACHMENT STATIONS= 560.0 660.0 TYPE= 1 TARGET= 100.000

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 582.80 ELREA= 100000.00

REPEATED SECTION OF 6917

7436.00	10.79	581.99	0.00	0.00	582.21	.23	.38	.02	582.80
2100.	0.	2100.	0.	0.	548.	0.	118.	17.	100000.00
.53	0.00	3.83	0.00	.035	.033	.035	.032	571.20	577.33
.000609	519.	519.	519.	2	0	1	0.00	81.13	658.17

3280 CROSS SECTION 7936.00 EXTENDED .58 FEET

3470 ENCROACHMENT STATIONS= 436.0 516.0 TYPE= 1 TARGET= 80.000

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 582.60 ELREA= 100000.00

1020 FEET U/S OF SOUTHFIELD ROAD BRIDGE SEC. H

7936.00	11.48	582.28	0.00	0.00	582.50	.22	.24	.00	582.60
2100.	0.	2100.	0.	0.	561.	0.	125.	18.	100000.00
.56	0.00	3.74	0.00	.035	.033	.035	.032	570.80	435.70
.000529	500.	500.	500.	2	0	1	0.00	77.21	513.91

3280 CROSS SECTION 8536.00 EXTENDED .23 FEET

3470 ENCROACHMENT STATIONS= 150.0 400.0 TYPE= 1 TARGET= 250.000

8536.00	11.72	582.62	0.00	0.00	582.79	.16	.27	.02	581.70
2100.	100.	1994.	6.	133.	598.	10.	134.	20.	562.10
.62	.75	3.34	.58	.035	.033	.035	.032	570.90	150.00
.000384	600.	600.	600.	0	0	1	0.00	250.00	400.00

3470 ENCROACHMENT STATIONS= 140.0 310.0 TYPE= 1 TARGET= 170.000

2220 FEET U/S OF SOUTHFIELD ROAD BRIDGE SEC. I

9136.00	11.96	582.86	0.00	0.00	583.00	.14	.21	.01	580.80
2100.	44.	1944.	112.	47.	618.	104.	144.	23.	581.10
.67	.92	3.15	1.08	.035	.033	.035	.032	570.90	140.00
.000314	600.	600.	600.	2	0	1	0.00	170.00	310.00

3470 ENCROACHMENT STATIONS= 50.0 250.0 TYPE= 1 TARGET= 200.000

9586.00	12.06	583.00	0.00	0.00	583.16	.16	.15	.01	580.84
2100.	60.	2040.	0.	70.	626.	0.	152.	25.	100000.04
.71	.86	3.26	0.00	.035	.033	.035	.032	570.94	91.87
.000341	450.	450.	450.	1	0	1	0.00	154.13	250.00

3280 CROSS SECTION 9596.00 EXTENDED .58 FEET

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	KV	HL	QLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TRA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

3470 ENCROACHMENT STATIONS= 245.0 445.0 TYPE= 1 TARGET= 200.000

9596.00	12.05	583.03	0.00	0.00	583.17	.14	.00	.01	581.68
2100.	218.	1882.	0.	165.	603.	0.	152.	25.	100000.03
.71	1.32	3.12	0.00	.035	.033	.035	.032	570.98	245.00
.000498	10.	10.	10.	2	0	1	0.00	200.00	445.00

3280 CROSS SECTION 10286.00 EXTENDED .86 FEET

3470 ENCROACHMENT STATIONS= 245.0 445.0 TYPE= 1 TARGET= 200.000

50 FEET D/S OF EMPIRE STREET SEC. J

WALL ON RIGHT BANK

10286.00	12.36	583.36	0.00	0.00	583.48	.12	.30	.01	581.90
2100.	257.	1843.	0.	196.	642.	0.	165.	24.	100000.00
.78	1.31	2.87	0.00	.035	.033	.035	.032	571.00	245.00
.000389	690.	690.	690.	2	0	1	0.00	200.00	445.00

3470 ENCROACHMENT STATIONS= 350.0 445.0 TYPE= 1 TARGET= 95.000

EMPIRE STREET BRIDGE SEC. K

BRIDGE HAS BEEN REMOVED

10336.00	10.84	583.34	0.00	0.00	583.54	.20	.02	.04	579.80
2100.	359.	1741.	0.	172.	457.	0.	165.	28.	100000.00
.79	2.09	3.81	0.00	.035	.033	.035	.032	572.50	350.00
.000466	50.	50.	50.	2	0	1	0.00	95.00	445.00

3280 CROSS SECTION 10636.00 EXTENDED .46 FEET

3470 ENCROACHMENT STATIONS= 655.0 800.0 TYPE= 1 TARGET= 145.000

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 584.57 ELREA= 100000.00

10636.00	11.06	583.53	0.00	0.00	583.73	.20	.19	.00	584.57
2100.	0.	2100.	0.	0.	578.	0.	170.	29.	100000.00
.81	0.00	3.63	0.00	.035	.033	.035	.032	572.47	674.15
.000887	300.	300.	300.	2	0	1	0.00	125.85	800.00

3280 CROSS SECTION 11536.00 EXTENDED 1.33 FEET

3470 ENCROACHMENT STATIONS= 655.0 855.0 TYPE= 1 TARGET= 200.000

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 584.50 ELREA= 100000.00

1200 FEET U/S OF EMPIRE STREET SEC. L

11536.00	11.93	584.33	0.00	0.00	584.46	.12	.10	.02	584.50
2100.	0.	2100.	0.	0.	743.	0.	183.	32.	100000.00
.90	0.00	2.83	0.00	.035	.033	.035	.032	572.40	658.08
.000690	900.	900.	900.	2	0	1	0.00	196.91	855.00

00BREAK00

1) COUNTY: Wayne

2) STUDY NAME: City of Ecorse

3) WATERCOURSE: North Ecorse Creek

4) DOCUMENT TYPE: Report

00BREAK00

HYDRAULIC ANALYSIS

Introduction

The North Ecorse Creek drains portions of Romulus, Wayne, Dearborn Heights, Taylor, Allen Park, Lincoln Park and Ecorse before discharging into the Sexton-Kilfoil Drain at Wyandotte. It has a drainage area of approximately 14,400 acres. The study includes the Sexton-Kilfoil Drain from the Jefferson Avenue Bridge to section 2436, approximately 2389' downstream from the Mill Street Bridge, and nearly two miles of the North Ecorse Creek up to the Outer Drive Hospital, nearly 4300' upstream of Southfield Road. The flows were determined by analysis of drainage and retention patterns from Detroit Metropolitan Airport to the Detroit River. The flows have been approved by the Michigan Department of Natural Resources.

Method of Analysis

The flood profiles were calculated by the HEC-2 computer program developed by the U.S. Army Corps of Engineers. All bridges have been modeled by the requirements of the HEC-2 normal and special bridge routines.

Variables and Coefficients

The roughness factors (Manning's "n") were determined by comparing the descriptions in Ven Te Chow's Open-Channel Hydraulics (Reference 1) with photographs and field descriptions taken in Ecorse by survey crews in 1975.

In order to reflect the generally gradual changes in cross section geometry, the expansion and contraction coefficients used in this study were .3 and .5, respectively

Starting Point

The profile computations for the North Ecorse Creek and the section of the Sexton-Kilfoil Drain studied began below the Jefferson Avenue Bridge by inputting the mean Detroit River elevation 574.90 (USC&GS) as a known water-surface elevation. Stationing was recorded as river feet beginning from the Detroit River. In the Final Flood Insurance Study Report, the 10-, 50-, 100- and 500-year Detroit River flood elevations will be extended horizontally upstream until the corresponding Sexton-Kilfoil Drain profiles are intersected.

Discussion

The floodway and flooded outline from the Sexton-Kilfoil will be continued upstream to the North Ecorse Creek.

If overland flow occurs due to overtopping of banks, it is assumed that streets will carry the flow away from the stream; therefore, the flooded outline has been foreshortened in locations along the North Ecorse Creek.

References

1. Chow, Ven Te, Open-Channel Hydraulics, McGraw-Hill Engineering Series, 1959.

Cross Section Location

Cross Section	SECNO	Location
A	136	u/s face Jefferson Street Bridge
B	187	50' u/s of Jefferson Street Bridge
C	737	50' d/s of Railroad Bridge #1
D	797	u/s face Railroad Bridge #1
E	859	u/s face Railroad Bridge #2
F	921	u/s face Railroad Bridge #3
G	985	u/s face Railroad Bridge #4
H	1036	50' u/s of Railroad Bridge #4
I	2436	1450' u/s Railroad Bridge #4
J	2736	2089' d/s of Mill Street Bridge
K	3836	989' d/s of Mill Street Bridge
L	4786	39' d/s of Mill Street Bridge
M	4846	u/s face of Mill Street Bridge
N	5936	1090' u/s of Mill Street Bridge
O	6786	49' d/s of Southfield Road Bridge
P	6916	u/s face of Southfield Road Bridge
Q	7936	1020' u/s of Southfield Road Bridge
R	9136	2420' u/s of Southfield Road Bridge
S	10286	50' d/s of Empire Street
T	10336	At Empire Street
U	11536	1200' u/s of Empire Street

Changes in Reach Length

North Ecorse Creek

Section 1 was eliminated and the study was changed to include the Sexton-Kilfoil Drain from the Detroit River upstream to the confluence of the North Ecorse Creek and then about two miles up the North Ecorse Creek. Stationing starts at the Detroit River.

Station (Corrected Number)	Change	Location
2736	200' subtracted	2089' D/S Mill St. Bridge
3436	200' added	1389' D/S Mill St. Bridge
6416	170' subtracted	420' D/S Southfield Road Bridge
6786	130' subtracted	50' D/S Southfield Road Bridge
10286	150' added	50' D/S Empire Street
11536	200' added	1200' U/S Empire Street

00BREAK00

1) COUNTY: Wayne

2) STUDY NAME: City of Ecorse

3) WATERCOURSE: North Ecorse Creek

4) DOCUMENT TYPE: Summary

00BREAK00

SUMMARY PRINTOUT FOR MULTIPLE PROFILES

NORTH BRANCH OF ECORSE C

SECTION NUMBER	CHANNEL LENGTH	MIN EL OF ROADWAY	MAX EL OF LOW CHORD	MIN EL GROUND	DISCHARGE (CFS)	CWSEL	AV	HL	OLOSS	QCH	DEPTH	TOPWID
1.00	0.00	0.00	0.00	563.40	3165.00	574.90	.32	0.00	0.00	3165.00	11.50	89.83
1.00	0.00	0.00	0.00	563.40	4100.00	574.90	.53	0.00	0.00	4100.00	11.50	89.83
1.00	0.00	0.00	0.00	563.40	4410.00	574.90	.61	0.00	0.00	4410.00	11.50	89.83
1.00	0.00	0.00	0.00	563.40	5160.00	574.90	.94	0.00	0.00	5160.00	11.50	89.83
30.00	29.00	0.00	0.00	563.40	3165.00	574.92	.31	.02	.00	3165.00	11.52	89.98
30.00	29.00	0.00	0.00	563.40	4100.00	574.93	.53	.03	.00	4100.00	11.53	90.06
30.00	29.00	0.00	0.00	563.40	4410.00	574.94	.61	.03	.00	4410.00	11.54	90.12
30.00	29.00	0.00	0.00	563.40	5160.00	574.96	.83	.05	.00	5160.00	11.56	90.27
60.00	30.00	0.00	0.00	563.40	3165.00	574.94	.31	.02	.00	3165.00	11.54	90.13
60.00	30.00	0.00	0.00	563.40	4100.00	574.97	.52	.03	.00	4100.00	11.57	90.37
60.00	30.00	0.00	0.00	563.40	4410.00	574.98	.60	.03	.00	4410.00	11.58	90.46
60.00	30.00	0.00	0.00	563.40	5160.00	575.03	.81	.05	.00	5160.00	11.63	90.90
61.00	1.00	584.30	580.30	563.40	3165.00	574.91	.38	.00	.03	3165.00	11.51	82.91
61.00	1.00	584.30	580.30	563.40	4100.00	574.92	.63	.00	.05	4100.00	11.52	82.99
61.00	1.00	584.30	580.30	563.40	4410.00	574.92	.73	.00	.06	4410.00	11.52	83.02
61.00	1.00	584.30	580.30	563.40	5160.00	574.94	.99	.00	.09	5160.00	11.54	83.18
136.00	75.00	584.30	580.30	563.40	3165.00	575.00	.37	.03	.00	3165.00	11.60	83.67
136.00	75.00	584.30	580.30	563.40	4100.00	575.09	.60	.13	.01	4100.00	11.69	84.38
136.00	75.00	584.30	580.30	563.40	4410.00	575.12	.69	.15	.01	4410.00	11.72	84.69
136.00	75.00	584.30	580.30	563.40	5160.00	575.24	.92	.20	.02	5160.00	11.84	85.68
137.00	1.00	0.00	0.00	563.40	3165.00	575.09	.30	.00	.02	3165.00	11.69	91.38
137.00	1.00	0.00	0.00	563.40	4100.00	575.24	.49	.00	.03	4100.00	11.84	92.64
137.00	1.00	0.00	0.00	563.40	4410.00	575.30	.55	.00	.04	4410.00	11.90	93.17
137.00	1.00	0.00	0.00	563.40	5160.00	575.50	.72	.00	.06	5160.00	12.10	94.13
187.00	50.00	0.00	0.00	564.10	3165.00	575.09	.34	.03	.02	3165.00	10.99	88.95
187.00	50.00	0.00	0.00	564.10	4100.00	575.25	.55	.05	.03	4100.00	11.15	90.51
187.00	50.00	0.00	0.00	564.10	4410.00	575.32	.63	.06	.04	4410.00	11.22	91.18
187.00	50.00	0.00	0.00	564.10	5160.00	575.52	.82	.07	.05	5160.00	11.42	92.35
362.00	175.00	0.00	0.00	563.97	3165.00	575.38	.19	.08	.05	3165.00	11.41	143.47
362.00	175.00	0.00	0.00	563.97	4100.00	575.72	.28	.12	.08	4100.00	11.75	145.17
362.00	175.00	0.00	0.00	563.97	4410.00	575.86	.31	.13	.10	4410.00	11.89	145.84
362.00	175.00	0.00	0.00	563.97	5160.00	576.24	.38	.16	.13	5160.00	12.27	147.72
737.00	375.00	0.00	0.00	563.70	3165.00	575.49	.19	.11	.00	3165.00	11.79	121.40
737.00	375.00	0.00	0.00	563.70	4100.00	575.89	.28	.16	.00	4100.00	12.19	122.47
737.00	375.00	0.00	0.00	563.70	4410.00	576.04	.31	.18	.00	4410.00	12.34	122.89
737.00	375.00	0.00	0.00	563.70	5160.00	576.45	.39	.21	.00	5160.00	12.75	123.99
787.00	50.00	0.00	0.00	563.90	3165.00	575.47	.26	.02	.04	3165.00	11.57	106.60
787.00	50.00	0.00	0.00	563.90	4100.00	575.86	.40	.03	.06	4100.00	11.96	106.60
787.00	50.00	0.00	0.00	563.90	4410.00	576.01	.44	.03	.06	4410.00	12.11	106.60
787.00	50.00	0.00	0.00	563.90	5160.00	576.41	.55	.04	.08	5160.00	12.51	106.60

SECTION NUMBER	CHANNEL LENGTH	MIN EL OF ROADWAY	MAX EL OF LOW CHORD	MIN EL GROUND	DISCHARGE (CFS)	CWSEL	HV	HL	OLOSS	QCH	DEPTH	TOPWID
788.00	1.00	581.00	577.20	563.90	3165.00	575.44	.33	.00	.03	3165.00	11.54	97.00
788.00	1.00	581.00	577.20	563.90	4100.00	575.81	.49	.00	.05	4100.00	11.91	104.00
788.00	1.00	581.00	577.20	563.90	4410.00	575.96	.54	.00	.05	4410.00	12.06	104.00
788.00	1.00	581.00	577.20	563.90	5160.00	576.35	.67	.00	.06	5160.00	12.45	104.00
797.00	9.00	581.00	577.20	563.90	3165.00	575.46	.32	.02	.00	3165.00	11.56	97.00
797.00	9.00	581.00	577.20	563.90	4100.00	575.85	.49	.01	.00	4100.00	11.95	104.00
797.00	9.00	581.00	577.20	563.90	4410.00	576.00	.54	.03	.00	4410.00	12.10	104.00
797.00	9.00	581.00	577.20	563.90	5160.00	576.40	.66	.04	.00	5160.00	12.50	104.00
798.00	1.00	0.00	0.00	563.90	3165.00	575.55	.26	.00	.02	3165.00	11.65	106.60
798.00	1.00	0.00	0.00	563.90	4100.00	575.98	.39	.00	.03	4100.00	12.08	106.60
798.00	1.00	0.00	0.00	563.90	4410.00	576.15	.43	.00	.03	4410.00	12.25	106.60
798.00	1.00	0.00	0.00	563.90	5160.00	576.58	.53	.00	.04	5160.00	12.68	106.60
844.00	46.00	0.00	0.00	565.00	3165.00	575.58	.26	.03	.00	3165.00	10.58	105.39
844.00	46.00	0.00	0.00	565.00	4100.00	576.03	.38	.04	.00	4100.00	11.03	108.18
844.00	46.00	0.00	0.00	565.00	4410.00	576.20	.42	.04	.00	4410.00	11.20	108.98
844.00	46.00	0.00	0.00	565.00	5160.00	576.64	.52	.05	.00	5160.00	11.64	109.00
845.00	1.00	581.40	578.40	565.00	3165.00	575.56	.30	.00	.02	3165.00	10.56	98.26
845.00	1.00	581.40	578.40	565.00	4100.00	575.99	.45	.00	.03	4100.00	10.99	100.93
845.00	1.00	581.40	578.40	565.00	4410.00	576.16	.50	.00	.04	4410.00	11.16	101.85
845.00	1.00	581.40	578.40	565.00	5160.00	576.60	.61	.00	.05	5160.00	11.60	102.00
859.00	14.50	581.40	578.40	565.00	3165.00	575.59	.30	.03	.00	3165.00	10.59	98.40
859.00	14.50	581.40	578.40	565.00	4100.00	576.04	.44	.04	.00	4100.00	11.04	101.26
859.00	14.50	581.40	578.40	565.00	4410.00	576.21	.49	.04	.00	4410.00	11.21	102.00
859.00	14.50	581.40	578.40	565.00	5160.00	576.66	.60	.05	.00	5160.00	11.66	102.00
860.00	1.00	0.00	0.00	565.00	3165.00	575.65	.25	.00	.01	3165.00	10.65	105.84
860.00	1.00	0.00	0.00	565.00	4100.00	576.14	.37	.00	.02	4100.00	11.14	108.77
860.00	1.00	0.00	0.00	565.00	4410.00	576.32	.41	.00	.02	4410.00	11.32	109.00
860.00	1.00	0.00	0.00	565.00	5160.00	576.80	.50	.00	.03	5160.00	11.80	109.00
910.00	50.00	0.00	0.00	564.00	3165.00	575.70	.23	.03	.01	3165.00	11.70	107.00
910.00	50.00	0.00	0.00	564.00	4100.00	576.21	.34	.04	.01	4100.00	12.21	107.00
910.00	50.00	0.00	0.00	564.00	4410.00	576.39	.38	.04	.01	4410.00	12.39	107.00
910.00	50.00	0.00	0.00	564.00	5160.00	576.88	.47	.04	.01	5160.00	12.88	107.00
911.00	1.00	583.00	578.60	564.00	3165.00	575.68	.29	.00	.03	3165.00	11.68	105.00
911.00	1.00	583.00	578.60	564.00	4100.00	576.17	.42	.00	.04	4100.00	12.17	105.00
911.00	1.00	583.00	578.60	564.00	4410.00	576.35	.47	.00	.04	4410.00	12.35	105.00
911.00	1.00	583.00	578.60	564.00	5160.00	576.84	.56	.00	.05	5160.00	12.84	105.00
921.00	10.00	583.00	578.60	564.00	3165.00	575.70	.29	.02	.00	3165.00	11.70	105.00
921.00	10.00	583.00	578.60	564.00	4100.00	576.20	.42	.03	.00	4100.00	12.20	105.00
921.00	10.00	583.00	578.60	564.00	4410.00	576.39	.46	.03	.00	4410.00	12.39	105.00
921.00	10.00	583.00	578.60	564.00	5160.00	576.88	.56	.04	.00	5160.00	12.88	105.00

SECTION NUMBER	CHANNEL LENGTH	MIN EL OF ROADWAY	MAX EL OF LOW CHORD	MIN EL GROUND	DISCHARGE (CFS)	CWSEL	HV	HL	OLOSS	OCH	DEPTH	TOPWID
922.00	1.00	0.00	0.00	564.00	3165.00	575.78	.23	.00	.02	3165.00	11.78	107.00
922.00	1.00	0.00	0.00	564.00	4100.00	576.31	.34	.00	.02	4100.00	12.31	107.00
922.00	1.00	0.00	0.00	564.00	4410.00	576.51	.37	.00	.03	4410.00	12.51	107.00
922.00	1.00	0.00	0.00	564.00	5160.00	577.02	.45	.00	.03	5160.00	13.02	107.00
953.00	31.00	0.00	0.00	565.10	3165.00	575.73	.3[illegible]	.02	.06	3165.00	10.63	81.00
953.00	31.00	0.00	0.00	565.10	4100.00	576.25	.52	.03	.09	4100.00	11.15	81.00
953.00	31.00	0.00	0.00	565.10	4410.00	576.44	.57	.03	.10	4410.00	11.34	81.00
953.00	31.00	0.00	0.00	565.10	5160.00	576.92	.71	.03	.13	5160.00	11.82	81.00
954.00	1.00	580.80	577.70	565.10	3165.00	575.65	.53	.00	.09	3165.00	10.55	67.20
954.00	1.00	580.80	577.70	565.10	4100.00	576.11	.79	.00	.14	4100.00	11.01	67.20
954.00	1.00	580.80	577.70	565.10	4410.00	576.28	.88	.00	.15	4410.00	11.18	67.20
954.00	1.00	580.80	577.70	565.10	5160.00	576.73	1.09	.00	.19	5160.00	11.63	67.20
985.00	30.50	580.80	577.70	565.10	3165.00	575.78	.51	.11	.01	3165.00	10.68	67.20
985.00	30.50	580.80	577.70	565.10	4100.00	576.32	.76	.16	.01	4100.00	11.22	67.20
985.00	30.50	580.80	577.70	565.10	4410.00	576.52	.84	.17	.01	4410.00	11.42	67.20
985.00	30.50	580.80	577.70	565.10	5160.00	577.03	1.02	.21	.02	5160.00	11.93	67.20
986.00	1.00	0.00	0.00	565.10	3165.00	576.02	.32	.00	.06	3165.00	10.92	81.00
986.00	1.00	0.00	0.00	565.10	4100.00	576.69	.47	.00	.09	4100.00	11.59	81.00
986.00	1.00	0.00	0.00	565.10	4410.00	576.94	.51	.00	.10	4410.00	11.84	81.00
986.00	1.00	0.00	0.00	565.10	5160.00	577.56	.62	.00	.12	5160.00	12.46	81.00
1036.00	50.00	0.00	0.00	566.20	3165.00	576.10	.2[illegible]	.03	.01	3165.00	9.90	113.42
1036.00	50.00	0.00	0.00	566.20	4100.00	576.84	.39	.04	.02	4100.00	10.64	117.34
1036.00	50.00	0.00	0.00	566.20	4410.00	577.10	.42	.04	.03	4410.00	10.90	118.70
1036.00	50.00	0.00	0.00	566.20	5160.00	577.79	.47	.05	.04	5160.00	11.59	122.23
1736.00	700.00	0.00	0.00	565.40	3165.00	576.54	.25	.39	.01	3165.00	11.14	110.65
1736.00	700.00	0.00	0.00	565.40	4100.00	577.39	.33	.48	.02	4100.00	11.99	114.80
1736.00	700.00	0.00	0.00	565.40	4410.00	577.69	.36	.49	.02	4410.00	12.28	115.58
1736.00	700.00	0.00	0.00	565.40	5160.00	578.39	.41	.52	.02	5160.00	12.99	117.05
2436.00	700.00	0.00	0.00	564.60	3165.00	576.87	.24	.31	.00	3165.00	12.27	100.85
2436.00	700.00	0.00	0.00	564.60	4100.00	577.78	.32	.38	.00	4100.00	13.18	102.00
2436.00	700.00	0.00	0.00	564.60	4410.00	578.08	.35	.39	.00	4410.00	13.48	102.00
2436.00	700.00	0.00	0.00	564.60	5160.00	578.82	.41	.42	.00	5160.00	14.22	102.00
2736.00	300.00	0.00	0.00	569.10	1500.00	577.14	.12	.12	.03	1500.00	8.04	92.48
2736.00	300.00	0.00	0.00	569.10	1950.00	578.14	.15	.14	.05	1950.00	9.04	97.63
2736.00	300.00	0.00	0.00	569.10	2100.00	578.47	.16	.14	.06	2100.00	9.37	99.34
2736.00	300.00	0.00	0.00	569.10	2495.00	579.26	.18	.15	.07	2495.00	10.16	100.00
3436.00	700.00	0.00	0.00	569.48	1500.00	577.42	.13	.29	.00	1500.00	7.94	91.97
3436.00	700.00	0.00	0.00	569.48	1950.00	578.44	.16	.30	.00	1950.00	8.96	97.20
3436.00	700.00	0.00	0.00	569.48	2100.00	578.77	.16	.30	.00	2100.00	9.29	98.91
3436.00	700.00	0.00	0.00	569.48	2495.00	579.56	.19	.30	.00	2495.00	10.08	100.00

SECTION NUMBER	CHANNEL LENGTH	MIN EL OF ROADWAY	MAX EL OF LOW CHORD	MIN EL GROUND	DISCHARGE (CFS)	CWSEL	HV	HL	OLOSS	QCH	DEPTH	TOPWID
3836.00	400.00	0.00	0.00	569.70	1500.00	577.61	.21	.23	.04	1500.00	7.91	82.23
3836.00	400.00	0.00	0.00	569.70	1950.00	578.62	.24	.23	.04	1950.00	8.92	86.76
3836.00	400.00	0.00	0.00	569.70	2100.00	578.95	.25	.23	.04	2100.00	9.25	87.67
3836.00	400.00	0.00	0.00	569.70	2495.00	579.73	.27	.22	.05	2495.00	10.03	89.30
4311.00	475.00	0.00	0.00	569.90	1500.00	577.99	.19	.36	.00	1500.00	8.09	83.09
4311.00	475.00	0.00	0.00	569.90	1950.00	578.99	.23	.35	.00	1950.00	9.09	87.26
4311.00	475.00	0.00	0.00	569.90	2100.00	579.32	.24	.35	.00	2100.00	9.42	88.14
4311.00	475.00	0.00	0.00	569.90	2495.00	580.09	.26	.34	.00	2495.00	10.19	90.00
4786.00	475.00	0.00	0.00	570.10	1500.00	578.32	.13	.25	.02	1500.00	8.22	87.32
4786.00	475.00	0.00	0.00	570.10	1950.00	579.35	.16	.27	.02	1950.00	9.25	97.98
4786.00	475.00	0.00	0.00	570.10	2100.00	579.69	.17	.28	.02	2100.00	9.59	105.02
4786.00	475.00	0.00	0.00	570.10	2495.00	580.47	.18	.27	.02	2495.00	10.37	107.00
4825.00	39.00	0.00	0.00	570.80	1500.00	578.36	.12	.02	.00	1500.00	7.56	98.00
4825.00	39.00	0.00	0.00	570.80	1950.00	579.40	.14	.02	.01	1950.00	8.60	98.00
4825.00	39.00	0.00	0.00	570.80	2100.00	579.73	.15	.02	.01	2100.00	8.93	98.00
4825.00	39.00	0.00	0.00	570.80	2495.00	580.50	.17	.02	.00	2495.00	9.70	98.00
4846.00	21.00	579.40	578.30	570.80	1500.00	578.40	.11	.04	0.00	1500.00	7.60	98.00
4846.00	21.00	579.40	578.30	570.80	1950.00	579.52	.13	.12	0.00	1950.00	8.72	98.00
4846.00	21.00	579.40	578.30	570.80	2100.00	579.83	.14	.10	0.00	2100.00	9.03	98.00
4846.00	21.00	579.40	578.30	570.80	2495.00	580.50	.17	0.00	0.00	2495.00	9.70	98.00
4847.00	1.00	0.00	0.00	570.80	1500.00	578.40	.11	.00	.00	1500.00	7.60	98.00
4847.00	1.00	0.00	0.00	570.80	1950.00	579.52	.13	.00	.00	1950.00	8.72	98.00
4847.00	1.00	0.00	0.00	570.80	2100.00	579.83	.14	.00	.00	2100.00	9.03	98.00
4847.00	1.00	0.00	0.00	570.80	2495.00	580.50	.17	.00	.00	2495.00	9.70	98.00
5436.00	589.00	0.00	0.00	570.64	1500.00	578.66	.16	.28	.02	1500.00	8.02	88.72
5436.00	589.00	0.00	0.00	570.64	1950.00	579.76	.18	.27	.02	1950.00	9.12	93.94
5436.00	589.00	0.00	0.00	570.64	2100.00	580.07	.19	.27	.02	2100.00	9.43	95.45
5436.00	589.00	0.00	0.00	570.64	2495.00	580.76	.22	.28	.03	2495.00	10.12	98.72
5936.00	500.00	0.00	0.00	570.50	1500.00	578.94	.14	.25	.01	1500.00	8.44	90.75
5936.00	500.00	0.00	0.00	570.50	1950.00	580.04	.16	.25	.01	1950.00	9.54	95.99
5936.00	500.00	0.00	0.00	570.50	2100.00	580.35	.17	.25	.01	2100.00	9.85	97.50
5936.00	500.00	0.00	0.00	570.50	2495.00	581.05	.19	.25	.01	2493.32	10.55	137.93
6416.00	480.00	0.00	0.00	570.33	1500.00	579.18	.24	.28	.04	1500.00	8.85	72.17
6416.00	480.00	0.00	0.00	570.33	1950.00	580.26	.26	.29	.05	1950.00	9.93	77.22
6416.00	480.00	0.00	0.00	570.33	2100.00	580.58	.27	.28	.05	2100.00	10.25	78.69
6416.00	480.00	0.00	0.00	570.33	2495.00	581.29	.31	.29	.06	2495.00	10.96	85.09
6786.00	370.00	0.00	0.00	570.20	1500.00	579.47	.19	.25	.01	1500.00	9.27	74.02
6786.00	370.00	0.00	0.00	570.20	1950.00	580.56	.22	.25	.01	1950.00	10.36	79.16
6786.00	370.00	0.00	0.00	570.20	2100.00	580.88	.24	.26	.01	2100.00	10.68	80.64
6786.00	370.00	0.00	0.00	570.20	2495.00	581.64	.26	.30	.01	2495.00	11.44	96.23

SECTION NUMBER	CHANNEL LENGTH	MIN EL OF ROADWAY	MAX EL OF LOW CHORD	MIN EL GROUND	DISCHARGE (CFS)	CWSEL	HV	HL	OLOSS	QCH	DEPTH	TOPWID
6835.00	49.00	0.00	0.00	571.57	1500.00	579.44	.32	.04	.06	1500.00	7.87	67.64
6835.00	49.00	0.00	0.00	571.57	1950.00	580.54	.36	.04	.07	1950.00	8.97	72.70
6835.00	49.00	0.00	0.00	571.57	2100.00	580.86	.37	.04	.07	2100.00	9.29	74.18
6835.00	49.00	0.00	0.00	571.57	2495.00	581.62	.40	.05	.07	2495.00	10.05	77.70
6836.00	1.00	0.00	0.00	571.60	1500.00	579.65	.16	.00	.05	1500.00	8.05	73.00
6836.00	1.00	0.00	0.00	571.60	1950.00	580.75	.20	.00	.05	1950.00	9.15	73.00
6836.00	1.00	0.00	0.00	571.60	2100.00	581.06	.21	.00	.05	2100.00	9.46	73.00
6836.00	1.00	0.00	0.00	571.60	2495.00	581.82	.24	.00	.05	2495.00	10.22	73.00
6916.00	80.00	583.00	578.30	571.60	1500.00	579.86	.15	.20	0.00	1500.00	8.26	73.00
6916.00	80.00	583.00	578.30	571.60	1950.00	581.17	.17	.40	0.00	1950.00	9.57	73.00
6916.00	80.00	583.00	578.30	571.60	2100.00	581.57	.18	.48	0.00	2100.00	9.97	73.00
6916.00	80.00	583.00	578.30	571.60	2495.00	582.60	.21	.73	0.00	2495.00	11.00	73.00
6917.00	1.00	0.00	0.00	571.60	1500.00	579.79	.28	.00	.07	1500.00	8.19	69.12
6917.00	1.00	0.00	0.00	571.60	1950.00	581.11	.29	.00	.06	1950.00	9.51	75.21
6917.00	1.00	0.00	0.00	571.60	2100.00	581.52	.30	.00	.06	2100.00	9.92	77.10
6917.00	1.00	0.00	0.00	571.60	2495.00	582.55	.31	.00	.05	2495.00	10.95	84.62
7436.00	519.00	0.00	0.00	571.20	1500.00	580.33	.20	.43	.02	1500.00	9.13	73.46
7436.00	519.00	0.00	0.00	571.20	1950.00	581.39	.22	.39	.02	1950.00	10.39	79.31
7436.00	519.00	0.00	0.00	571.20	2100.00	581.99	.23	.38	.02	2100.00	10.79	81.13
7436.00	519.00	0.00	0.00	571.20	2495.00	583.03	.23	.38	.02	2495.00	11.83	100.00
7936.00	500.00	0.00	0.00	570.80	1500.00	580.65	.18	.29	.01	1500.00	9.85	69.40
7936.00	500.00	0.00	0.00	570.80	1950.00	581.69	.21	.29	.00	1950.00	11.09	75.35
7936.00	500.00	0.00	0.00	570.80	2100.00	582.28	.22	.29	.00	2100.00	11.48	77.21
7936.00	500.00	0.00	0.00	570.80	2495.00	583.31	.23	.29	.00	2495.00	12.51	80.00
8536.00	600.00	0.00	0.00	570.90	1500.00	580.97	.16	.29	.01	1500.00	10.07	73.92
8536.00	600.00	0.00	0.00	570.90	1950.00	582.22	.17	.28	.01	1911.49	11.32	250.00
8536.00	600.00	0.00	0.00	570.90	2100.00	582.62	.16	.27	.02	1994.42	11.72	250.00
8536.00	600.00	0.00	0.00	570.90	2495.00	583.67	.14	.23	.03	2141.66	12.77	250.00
9136.00	600.00	0.00	0.00	570.90	1500.00	581.24	.14	.25	.01	1497.84	10.34	146.17
9136.00	600.00	0.00	0.00	570.90	1950.00	582.48	.14	.22	.01	1846.95	11.58	170.00
9136.00	600.00	0.00	0.00	570.90	2100.00	582.86	.14	.21	.01	1943.91	11.96	170.00
9136.00	600.00	0.00	0.00	570.90	2495.00	583.84	.14	.17	.00	2174.64	12.94	170.00
9586.00	450.00	0.00	0.00	570.94	1500.00	581.41	.14	.17	.00	1498.53	10.48	89.42
9586.00	450.00	0.00	0.00	570.94	1950.00	582.63	.16	.15	.01	1916.40	11.70	134.70
9586.00	450.00	0.00	0.00	570.94	2100.00	583.00	.16	.15	.01	2040.15	12.06	158.13
9586.00	450.00	0.00	0.00	570.94	2495.00	583.95	.16	.13	.01	2312.51	13.02	200.00
9596.00	10.00	0.00	0.00	570.98	1500.00	581.40	.18	.01	.02	1493.37	10.42	142.67
9596.00	10.00	0.00	0.00	570.98	1950.00	582.65	.15	.00	.00	1801.51	11.67	200.00
9596.00	10.00	0.00	0.00	570.98	2100.00	583.03	.14	.00	.01	1882.08	12.05	200.00
9596.00	10.00	0.00	0.00	570.98	2495.00	584.01	.12	.00	.01	2084.12	13.03	200.00

SECTION NUMBER	CHANNEL LENGTH	MIN EL OF ROADWAY	MAX EL OF LOW CHORD	MIN EL GROUND	DISCHARGE (CFS)	CWSEL	HV	HL	OLOSS	QCH	DEPTH	TOPWID
10286.00	690.00	0.00	0.00	571.00	1500.00	581.90	.13	.45	.01	1467.59	10.90	200.00
10286.00	690.00	0.00	0.00	571.00	1950.00	583.02	.12	.34	.01	1755.11	12.02	200.00
10286.00	690.00	0.00	0.00	571.00	2100.00	583.36	.12	.30	.01	1842.56	12.36	200.00
10286.00	690.00	0.00	0.00	571.00	2495.00	584.26	.11	.24	.00	2059.61	13.26	200.00
10336.00	50.00	0.00	0.00	572.50	1500.00	581.91	.17	.03	.02	1355.21	9.41	95.00
10336.00	50.00	0.00	0.00	572.50	1950.00	583.01	.19	.02	.04	1647.63	10.51	95.00
10336.00	50.00	0.00	0.00	572.50	2100.00	583.34	.20	.02	.04	1740.58	10.84	95.00
10336.00	50.00	0.00	0.00	572.50	2495.00	584.23	.21	.02	.05	1970.89	11.73	95.00
10636.00	300.00	0.00	0.00	572.47	1500.00	582.06	.18	.15	.00	1500.00	9.59	73.39
10636.00	300.00	0.00	0.00	572.47	1950.00	583.19	.20	.19	.01	1950.00	10.72	120.39
10636.00	300.00	0.00	0.00	572.47	2100.00	583.53	.20	.19	.00	2100.00	11.06	125.85
10636.00	300.00	0.00	0.00	572.47	2495.00	584.43	.20	.18	.00	2495.00	11.96	142.35
11536.00	900.00	0.00	0.00	572.40	1500.00	582.54	.15	.44	.01	1500.00	10.14	76.00
11536.00	900.00	0.00	0.00	572.40	1950.00	584.04	.13	.75	.02	1950.00	11.64	191.55
11536.00	900.00	0.00	0.00	572.40	2100.00	584.33	.12	.70	.02	2100.00	11.93	196.91
11536.00	900.00	0.00	0.00	572.40	2495.00	585.11	.12	.58	.02	2495.00	12.71	200.00

SECTION NUMBER	DISCHARGE CFS	CWSEL	CWSEL DIFF EACH Q	CWSEL DIFF EACH SECTION	CWSEL-WSELK	TOPWID	T.W. DIFF	LENGTH
1.000	3165.000	574.900	0.000	0.000	0.000	89.833	0.000	-0.000
1.000	4100.000	574.900	0.000	0.000	0.000	89.833	0.000	-0.000
1.000	4410.000	574.900	0.000	0.000	0.000	89.833	0.000	-0.000
1.000	5160.000	574.900	0.000	0.000	0.000	89.833	0.000	-0.000
30.000	3165.000	574.919	0.000	.019	0.000	89.979	0.000	29.000
30.000	4100.000	574.934	.015	.034	0.000	90.077	-.098	29.000
30.000	4410.000	574.941	.006	.041	0.000	90.115	-.137	29.000
30.000	5160.000	574.961	.020	.061	0.000	90.272	-.293	29.000
60.000	3165.000	574.939	0.000	.020	0.000	90.123	0.000	30.000
60.000	4100.000	574.970	.031	.036	0.000	90.370	-.241	30.000
60.000	4410.000	574.983	.013	.043	0.000	90.461	-.333	30.000
60.000	5160.000	575.028	.044	.067	0.000	90.398	-.769	30.000
61.000	3165.000	574.909	0.000	-.030	0.000	92.906	0.000	1.000
61.000	4100.000	574.913	.010	-.052	0.000	92.985	-.080	1.000
61.000	4410.000	574.923	.005	-.061	0.000	93.023	-.117	1.000
61.000	5160.000	574.942	.019	-.086	0.000	93.182	-.276	1.000
136.000	3165.000	575.000	0.000	.091	0.000	93.668	0.000	75.000
136.000	4100.000	575.085	.085	.167	0.000	84.376	-.709	75.000
136.000	4410.000	575.122	.037	.200	0.000	84.688	-1.020	75.000
136.000	5160.000	575.242	.119	.300	0.000	55.584	-2.016	75.000
137.000	3165.000	575.086	0.000	.085	0.000	91.381	0.000	1.000
137.000	4100.000	575.236	.150	.151	0.000	92.635	-1.255	1.000
137.000	4410.000	575.300	.064	.178	0.000	93.172	-1.791	1.000
137.000	5160.000	575.495	.195	.254	0.000	94.127	-2.747	1.000
187.000	3165.000	575.095	0.000	.009	0.000	88.947	0.000	50.000
187.000	4100.000	575.251	.156	.015	0.000	90.512	-1.564	50.000
187.000	4410.000	575.318	.066	.018	0.000	91.177	-2.229	50.000
187.000	5160.000	575.518	.200	.023	0.000	92.350	-3.403	50.000
362.000	3165.000	575.377	0.000	.283	0.000	143.475	0.000	175.000
362.000	4100.000	575.724	.346	.472	0.000	145.168	-1.693	175.000
362.000	4410.000	575.862	.138	.544	0.000	145.843	-2.368	175.000
362.000	5160.000	576.244	.383	.726	0.000	147.720	-4.245	175.000

737.000	3165.000	575.490	0.000	.113	0.000	121.404	0.000	375.000
737.000	4100.000	575.887	.397	.163	0.000	122.475	-1.071	375.000
737.000	4410.000	576.040	.153	.179	0.000	122.886	-1.483	375.000
737.000	5160.000	576.454	.413	.209	0.000	123.994	-2.590	375.000
787.000	3165.000	575.472	0.000	-.018	0.000	106.600	0.000	50.000
787.000	4100.000	575.858	.387	-.029	0.000	106.600	0.000	50.000
787.000	4410.000	576.008	.149	-.032	0.000	106.600	0.000	50.000
787.000	5160.000	576.412	.404	-.042	0.000	106.600	0.000	50.000
788.000	3165.000	575.442	0.000	-.030	0.000	97.000	0.000	1.000
788.000	4100.000	575.814	.372	-.045	0.000	104.000	-7.000	1.000
788.000	4410.000	575.958	.145	-.049	0.000	104.000	-7.000	1.000
788.000	5160.000	576.353	.394	-.059	0.000	104.000	-7.000	1.000
797.000	3165.000	575.465	0.000	.023	0.000	97.000	0.000	9.000
797.000	4100.000	575.851	.386	.037	0.000	104.000	-7.000	9.000
797.000	4410.000	576.001	.151	.043	0.000	104.000	-7.000	9.000
797.000	5160.000	576.404	.403	.052	0.000	104.000	-7.000	9.000
798.000	3165.000	575.553	0.000	.088	0.000	106.600	0.000	1.000
798.000	4100.000	575.984	.431	.134	0.000	106.600	0.000	1.000
798.000	4410.000	576.147	.163	.146	0.000	106.600	0.000	1.000
798.000	5160.000	576.583	.435	.178	0.000	106.600	0.000	1.000
844.000	3165.000	575.582	0.000	.029	0.000	105.391	0.000	46.000
844.000	4100.000	576.027	.445	.043	0.000	108.181	-2.789	46.000
844.000	4410.000	576.195	.168	.048	0.000	108.983	-3.592	46.000
844.000	5160.000	576.641	.446	.059	0.000	109.000	-3.609	46.000
845.000	3165.000	575.561	0.000	-.022	0.000	98.255	0.000	1.000
845.000	4100.000	575.995	.434	-.033	0.000	100.975	-2.720	1.000
845.000	4410.000	576.159	.164	-.036	0.000	101.851	-3.595	1.000
845.000	5160.000	576.596	.437	-.045	0.000	102.000	-3.745	1.000
859.000	3165.000	575.590	0.000	.029	0.000	99.400	0.000	14.500
859.000	4100.000	576.040	.451	.046	0.000	101.263	-2.363	14.500
859.000	4410.000	576.210	.170	.051	0.000	102.000	-3.600	14.500
859.000	5160.000	576.661	.451	.065	0.000	102.000	-3.600	14.500
860.000	3165.000	575.653	0.000	.064	0.000	105.838	0.000	1.000
860.000	4100.000	576.137	.484	.097	0.000	108.773	-2.935	1.000
860.000	4410.000	576.318	.181	.108	0.000	109.000	-3.162	1.000
860.000	5160.000	576.797	.479	.136	0.000	109.000	-3.162	1.000
910.000	3165.000	575.702	0.000	.049	0.000	107.000	0.000	50.000
910.000	4100.000	576.208	.505	.070	0.000	107.000	0.000	50.000
910.000	4410.000	576.395	.187	.076	0.000	107.000	0.000	50.000
910.000	5160.000	576.883	.489	.086	0.000	107.000	0.000	50.000
911.000	3165.000	575.676	0.000	-.027	0.000	105.000	0.000	1.000
911.000	4100.000	576.170	.494	-.038	0.000	105.000	0.000	1.000
911.000	4410.000	576.354	.184	-.041	0.000	105.000	0.000	1.000
911.000	5160.000	576.836	.482	-.047	0.000	105.000	0.000	1.000
921.000	3165.000	575.700	0.000	.024	0.000	105.000	0.000	10.000
921.000	4100.000	576.204	.504	.034	0.000	105.000	0.000	10.000
921.000	4410.000	576.390	.186	.037	0.000	105.000	0.000	10.000
921.000	5160.000	576.860	.490	.045	0.000	105.000	0.000	10.000
922.000	3165.000	575.776	0.000	.076	0.000	107.000	0.000	1.000
922.000	4100.000	576.313	.537	.109	0.000	107.000	0.000	1.000
922.000	4410.000	576.510	.197	.119	0.000	107.000	0.000	1.000
922.000	5160.000	577.020	.510	.139	0.000	107.000	0.000	1.000

953.000	4100.000	576.248	.513	-.065	0.000	81.000	0.000	31.000
953.000	4410.000	576.436	.188	-.074	0.000	81.000	0.000	31.000
953.000	5160.000	576.924	.488	-.096	0.000	81.000	0.000	31.000
954.000	3165.000	575.646	0.000	-.089	0.000	67.200	0.000	1.000
954.000	4100.000	576.112	.466	-.136	0.000	67.200	0.000	1.000
954.000	4410.000	576.284	.172	-.152	0.000	67.200	0.000	1.000
954.000	5160.000	576.733	.450	-.190	0.000	67.200	0.000	1.000
985.000	3165.000	575.776	0.000	.131	0.000	67.200	0.000	30.500
985.000	4100.000	576.317	.541	.205	0.000	67.200	0.000	30.500
985.000	4410.000	576.515	.198	.232	0.000	67.200	0.000	30.500
985.000	5160.000	577.028	.513	.295	0.000	67.200	0.000	30.500
986.000	3165.000	576.021	0.000	.245	0.000	81.000	0.000	1.000
986.000	4100.000	576.693	.672	.376	0.000	81.000	0.000	1.000
986.000	4410.000	576.936	.243	.421	0.000	81.000	0.000	1.000
986.000	5160.000	577.556	.620	.528	0.000	81.000	0.000	1.000
1036.000	3165.000	576.100	0.000	.079	0.000	113.418	0.000	50.000
1036.000	4100.000	576.838	.738	.145	0.000	117.340	-3.922	50.000
1036.000	4410.000	577.105	.267	.169	0.000	115.699	-5.280	50.000
1036.000	5160.000	577.792	.688	.236	0.000	122.233	-8.815	50.000
1736.000	3165.000	576.545	0.000	.444	0.000	110.653	0.000	700.000
1736.000	4100.000	577.388	.843	.550	0.000	114.797	-4.144	700.000
1736.000	4410.000	577.679	.291	.574	0.000	115.581	-4.928	700.000
1736.000	5160.000	578.394	.715	.601	0.000	117.049	-6.396	700.000
2436.000	3165.000	576.872	0.000	.327	0.000	100.852	0.000	700.000
2436.000	4100.000	577.781	.910	.394	0.000	101.999	-1.147	700.000
2436.000	4410.000	578.085	.304	.406	0.000	101.999	-1.147	700.000
2436.000	5160.000	578.818	.733	.424	0.000	101.999	-1.147	700.000
2736.000	1500.000	577.137	0.000	.266	0.000	92.478	0.000	300.000
2736.000	1950.000	578.139	1.001	.358	0.000	97.629	-5.151	300.000
2736.000	2100.000	578.471	.332	.386	0.000	99.336	-6.859	300.000
2736.000	2495.000	579.263	.792	.445	0.000	99.999	-7.521	300.000
3436.000	1500.000	577.421	0.000	.284	0.000	91.970	0.000	700.000
3436.000	1950.000	578.435	1.014	.296	0.000	97.198	-5.228	700.000
3436.000	2100.000	578.768	.333	.297	0.000	98.907	-6.938	700.000
3436.000	2495.000	579.556	.790	.295	0.000	99.999	-8.029	700.000
3836.000	1500.000	577.607	0.000	.186	0.000	82.235	0.000	400.000
3836.000	1950.000	578.620	1.013	.185	0.000	86.763	-4.529	400.000
3836.000	2100.000	578.950	.330	.183	0.000	87.667	-5.432	400.000
3836.000	2495.000	579.734	.784	.176	0.000	89.802	-7.567	400.000
4311.000	1500.000	577.989	0.000	.381	0.000	83.091	0.000	475.000
4311.000	1950.000	578.994	1.006	.374	0.000	87.256	-4.165	475.000
4311.000	2100.000	579.317	.323	.367	0.000	88.136	-5.045	475.000
4311.000	2495.000	580.093	.776	.358	0.000	89.999	-6.908	475.000
4786.000	1500.000	578.323	0.000	.335	0.000	87.322	0.000	475.000
4786.000	1950.000	579.352	1.029	.354	0.000	97.940	-10.618	475.000
4786.000	2100.000	579.686	.334	.369	0.000	105.019	-17.698	475.000
4786.000	2495.000	580.466	.780	.373	0.000	106.799	-19.477	475.000
4825.000	1500.000	578.359	0.000	.036	0.000	97.999	0.000	39.000
4825.000	1950.000	579.395	1.036	.043	0.000	97.999	-.000	39.000
4825.000	2100.000	579.729	.333	.043	0.000	98.000	-.000	39.000
4825.000	2495.000	580.503	.775	.037	0.000	98.000	-.000	39.000
4846.000	1500.000	578.402	0.000	.043	0.000	97.999	0.000	21.000

4846.000	2100.000	579.833	.316	.104	0.000	98.000	-.000	21.000
4846.000	2495.000	580.504	.671	.000	0.000	98.000	-.000	21.000
4847.000	1500.000	578.402	0.000	.000	0.000	97.999	0.000	1.000
4847.000	1950.000	579.517	1.115	.000	0.000	98.000	-.000	1.000
4847.000	2100.000	579.833	.316	.000	0.000	98.000	-.000	1.000
4847.000	2495.000	580.504	.671	.000	0.000	98.000	-.000	1.000
5436.000	1500.000	578.656	0.000	.254	0.000	88.720	0.000	589.000
5436.000	1950.000	579.758	1.102	.241	0.000	93.938	-5.219	589.000
5436.000	2100.000	580.074	.316	.241	0.000	95.450	-6.731	589.000
5436.000	2495.000	580.758	.684	.254	0.000	98.720	-10.000	589.000
5936.000	1500.000	578.941	0.000	.284	0.000	90.748	0.000	500.000
5936.000	1950.000	580.037	1.096	.279	0.000	95.988	-5.240	500.000
5936.000	2100.000	580.354	.317	.280	0.000	97.504	-6.756	500.000
5936.000	2495.000	581.051	.697	.294	0.000	137.931	-47.183	500.000
6416.000	1500.000	579.177	0.000	.236	0.000	72.169	0.000	480.000
6416.000	1950.000	580.265	1.088	.228	0.000	77.216	-5.047	480.000
6416.000	2100.000	580.582	.317	.227	0.000	78.696	-6.517	480.000
6416.000	2495.000	581.289	.708	.238	0.000	85.087	-12.918	480.000
6786.000	1500.000	579.467	0.000	.290	0.000	74.044	0.000	370.000
6786.000	1950.000	580.561	1.093	.296	0.000	74.161	-5.067	370.000
6786.000	2100.000	580.881	.320	.299	0.000	80.545	-6.551	370.000
6786.000	2495.000	581.639	.759	.350	0.000	96.230	-22.136	370.000
6835.000	1500.000	579.445	0.000	-.023	0.000	67.640	0.000	49.000
6835.000	1950.000	580.536	1.092	-.024	0.000	72.700	-5.060	49.000
6835.000	2100.000	580.856	.320	-.025	0.000	74.181	-6.541	49.000
6835.000	2495.000	581.615	.759	-.024	0.000	77.698	-10.059	49.000
6836.000	1500.000	579.655	0.000	.210	0.000	73.000	0.000	1.000
6836.000	1950.000	580.745	1.091	.209	0.000	73.000	0.000	1.000
6836.000	2100.000	581.065	.320	.209	0.000	73.000	0.000	1.000
6836.000	2495.000	581.824	.759	.209	0.000	73.000	0.000	1.000
6916.000	1500.000	579.860	0.000	.205	0.000	73.000	0.000	80.000
6916.000	1950.000	581.168	1.308	.422	0.000	73.000	0.000	80.000
6916.000	2100.000	581.574	.406	.509	0.000	73.000	0.000	80.000
6916.000	2495.000	582.596	1.022	.772	0.000	73.000	0.000	80.000
6917.000	1500.000	579.794	0.000	-.065	0.000	69.129	0.000	1.000
6917.000	1950.000	581.108	1.314	-.059	0.000	75.211	-6.090	1.000
6917.000	2100.000	581.517	.409	-.057	0.000	77.134	-7.984	1.000
6917.000	2495.000	582.545	1.029	-.050	0.000	84.617	-15.496	1.000
7436.000	1500.000	580.331	0.000	.537	0.000	73.462	0.000	519.000
7436.000	1950.000	581.592	1.261	.484	0.000	79.306	-5.845	519.000
7436.000	2100.000	581.986	.394	.469	0.000	81.134	-7.672	519.000
7436.000	2495.000	583.026	1.040	.481	0.000	99.999	-26.537	519.000
7936.000	1500.000	580.647	0.000	.316	0.000	69.404	0.000	500.000
7936.000	1950.000	581.894	1.248	.302	0.000	75.353	-5.949	500.000
7936.000	2100.000	582.284	.389	.297	0.000	77.210	-7.806	500.000
7936.000	2495.000	583.313	1.030	.287	0.000	79.999	-10.595	500.000
8536.000	1500.000	580.955	0.000	.319	0.000	73.419	0.000	600.000
8536.000	1950.000	582.224	1.268	.329	0.000	249.999	-176.080	600.000
8536.000	2100.000	582.622	.398	.338	0.000	249.999	-176.080	600.000
8536.000	2495.000	583.668	1.046	.354	0.000	249.999	-176.080	600.000
9136.000	1500.000	581.237	0.000	.271	0.000	146.166	0.000	500.000
9136.000	1950.000	582.493	1.246	.260	0.000	169.999	-23.833	500.000

9136.000	2100.000	582.857	.374	.255	0.000	169.999	-23.333	600.000
9136.000	2495.000	583.635	.978	.167	0.000	169.999	-23.333	600.000
9586.000	1500.000	581.412	0.000	.175	0.000	89.419	0.000	450.000
9586.000	1950.000	582.630	1.218	.147	0.000	134.701	-45.282	450.000
9586.000	2100.000	582.996	.366	.139	0.000	158.126	-68.707	450.000
9586.000	2495.000	583.955	.959	.119	0.000	199.999	-110.580	450.000
9596.000	1500.000	581.397	0.000	-.015	0.000	142.669	0.000	10.000
9596.000	1950.000	582.646	1.249	.016	0.000	199.999	-57.330	10.000
9596.000	2100.000	583.029	.383	.033	0.000	199.999	-57.330	10.000
9596.000	2495.000	584.008	.979	.053	0.000	199.999	-57.330	10.000
10286.000	1500.000	581.904	0.000	.507	0.000	199.999	0.000	690.000
10286.000	1950.000	583.020	1.116	.374	0.000	199.999	-.000	690.000
10286.000	2100.000	583.361	.341	.333	0.000	199.999	-.000	690.000
10286.000	2495.000	584.262	.901	.255	0.000	199.999	-.000	690.000
10336.000	1500.000	581.910	0.000	.006	0.000	94.999	0.000	50.000
10336.000	1950.000	583.005	1.095	-.015	0.000	94.999	-.000	50.000
10336.000	2100.000	583.341	.335	-.020	0.000	94.999	-.000	50.000
10336.000	2495.000	584.229	.889	-.033	0.000	94.999	-.000	50.000
10636.000	1500.000	582.056	0.000	.146	0.000	73.389	0.000	300.000
10636.000	1950.000	583.190	1.134	.134	0.000	120.889	-47.500	300.000
10636.000	2100.000	583.526	.336	.145	0.000	125.853	-52.464	300.000
10636.000	2495.000	584.426	.900	.196	0.000	142.354	-68.965	300.000
11536.000	1500.000	582.536	0.000	.480	0.000	75.998	0.000	900.000
11536.000	1950.000	584.040	1.504	.850	0.000	191.552	-115.554	900.000
11536.000	2100.000	584.332	.292	.807	0.000	196.914	-120.916	900.000
11536.000	2495.000	585.105	.773	.680	0.000	199.999	-124.001	900.000

DATA FOR LAST CROSS SECTION

PROFILE	TYPE ENC	TARGET	TOP WIDTH AREA-ACRES	TOP WIDTH AREA-DIFF
1	0.000	200.000	25.525	0.000
2	0.000	200.000	31.586	6.061
3	0.000	200.000	32.083	6.558
4	0.000	200.000	33.650	8.125

00BREAK00

1) COUNTY: Wayne

2) STUDY NAME: City of Flat Rock

3) WATERCOURSE: Cook and Gladding Drain

4) DOCUMENT TYPE: Floodway

00BREAK00

```
**************************************************
  REC2 RELEASE DATED NOV 76 UPDATED FEB 1977
  ERROR CORR -  01
  MODIFICATION -  50,51,52
**************************************************

  T1      FLATROCK
  T2      ENCROACHMENT RUN
  T3      COOKE & GLADDING BRAIN

J1  ICHECK    INC       NINV      IDIR      STRT      METRIC    HVINS     Q         USEL      FQ
          0.        5.        0.        0.  0.000000      0.00      0.0       0.   585.500     0.000

J2  NPROF     IPLOT     PRFVS     XSECV     XSECH     FK        ALPHA     THR       CHRIN     ITRACE
     15.000     0.000    -1.000     0.000     0.030     0.000     0.000     0.000     0.000     0.000
```

PRINTED IN U.S.A.
FORM 1611-GB PRINTED BY ROTARY MANIFOLD FORMS

*PROF 2

CCHV= 0.300 CEHV= 0.500

*SECNO ****

SECNO	DEPTH	CWSEL	CRIWS	LSELK	FQ	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IN2	ICONT	CORAR	TOPWID	ENDST

3470 ENCROACHMENT STATIONS= 1.0 151.0 TYPE= 1 TARGET= 150.000

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 586.00 ELREA= 586.00

D/S FACE OF HURON RIVER DRIVE.

0.00	4.50	585.50	0.00	585.40	585.53	0.03	0.00	0.00	588.00
27.	0.	27.	0.	0.	20.	0.	0.	0.	588.00
0.00	0.00	1.33	0.00	0.060	0.035	0.060	0.000	581.00	75.00
0.000574	3.	0.	0.	0	0	0	0.00	4.50	79.50

SPECIAL BRIDGE

SW	XK	XKOR	COFQ	RDLEN	BPC	XRP	BAREA	SS	ELCHD	ELCHD
	0.00	1.50	3.00	0.00	3.53	0.00	10.90	0.00	581.10	581.00

*SECNO 54.000

OD/O,LOW FLOW BY NORMAL BRIDGE

EGPRS= 585.587 EGUNC= 585.633 ELLC= 535.000 POWER= 585.500 ELTRD= 588.000

5370 NORMAL BRIDGE,NRD= 12 MIN ELTRD= 588.00 MAX ELLC= 585.60

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 581.00 ELREA= 581.00

U/S FACE HURON RIVER DRIVE

54.00	4.49	585.53	0.00	585.43	585.57	0.04	0.03	0.01	583.35
27.	0.	27.	0.	0.	17.	0.	0.	0.	585.35
0.01	0.00	1.63	0.00	0.060	0.035	0.000	0.334	581.10	88.00
0.000702	54.	54.	54.	2	0	0	-11.23	4.50	92.50

*SECNO 300.000

300.00	26.33	USEL=	588.54	EVC,01=	26.32	,SEL=	585.54	RATIO=	0.0000
LAT 01=	20.	RATIOS LOB/CH,ROB=	0.1084	0.8033	0.0883	USEL=	585.64		

3470 ENCROACHMENT STATIONS= 294.1 305.8 TYPE= 4 TARGET= 0.051

VALLEY SECTION BASED ON FIELD BOOK SECTION 10434

300.00	4.12	585.63	0.00	585.54	585.64	0.01	0.37	0.11	582.26
27.	2.	25.	2.	7.	22.	7.	2.	7.	604.36
0.10	0.33	1.02	0.24	0.060	0.035	0.050	0.035	581.5	294.20
0.000175	300.	300.	300.	1	0	0	0.00	4.75	305.00

PRINTED IN U.S.A.
FORM 1411-OB-PRINTED BY ROTARY MANIFOLD FORMS.

CCHV= 0.100 CEHV= 0.300
*SECNO 1300.000
2800 NAT Q1= 15.45 USEL= 585.69 ENC Q1= 15.45 WSEL= 585.79 RATIO= 0.0000
NAT Q1= 17. RATIOS LOB,CH,ROB= 0.0426 0.8977 0.0597 WSEL= 585.79

3470 ENCROACHMENT STATIONS= 275.9 285.1 TYPE= 4 TARGET= 0.081

VALLEY SECTION BASED ON FIELD BOOK SECTION 9434

1300.00	2.78	585.79	0.00	585.69	585.81	0.03	0.17	0.00	583.66
27.	0.	26.	1.	0.	20.	2.	1.	0.	583.66
0.31	0.06	1.35	0.24	0.060	0.035	0.080	0.035	583.01	275.92
0.000311	1000.	1000.	1000.	2	0	0	0.00	9.17	285.09

CCHV= 0.300 CEHV= 0.500
*SECNO 1600.000

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	QLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IH2	ICONT	CORAR	TOPWID	ELDST

3470 ENCROACHMENT STATIONS= 1.0 600.0 TYPE= 1 TARGET= 599.000

XSECTION D/S GIBRALTAR RD.BASED ON FIELD BOOK " QUAD MAP

1600.20	2.68	585.97	0.00	585.88	586.06	0.09	0.22	0.03	584.50
27.	1.	24.	2.	1.	10.	2.	1.	0.	584.50
0.35	0.67	2.54	0.41	0.080	0.050	0.080	0.038	583.29	296.11
0.003249	300.	300.	300.	2	0	0	0.00	9.35	305.46

*SECNO 1700.000

3470 ENCROACHMENT STATIONS= 1.8 600.0 TYPE= 1 TARGET= 599.000

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 590.00 ELREA= 590.00

D/S FACE OF GIBRALTAR RD. REMOVED 1987 SOC

1700.00	1.35	584.49	0.00	586.48	586.78	0.29	0.62	0.10	585.14
27.	0.	27.	0.	0.	6.	0.	1.	0.	585.14
0.35	0.00	4.36	0.00	0.020	0.050	0.080	0.036	585.14	297.50
0.015873	100.	100.	100.	3	0	0	0.00	7.60	302.10

SPECIAL BRIDGE

SK	XCOR	COEC	NOLEN	QWC	BWF	DAR	SS	ELCRD	ELCHD
0.00	8.98	3.00	3.00	3.59	0.00	0.34	0.00	586.21	585.14

*SECNO 1835.000

QOVD= 0.01 FLOW BY NORMAL BRIDGE

ESPRS= 0.005 FELLC= 587.890 CLLC= 586.900 PCWSB= 586.487 ELTRD= 592.630

3570 NORMAL DEPTH SLOPE= 0.0124 ELTRD= 592.00 MAX ELLC= 590.50

PRINTED IN U.S.A.

FORM 1411-08 PRINTED BY ROTARY MANIFOLD FORMS

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 593.40 ELREA= 593.40

U/S FACE OF GIBRALTAR RD.

1836.00	1.94	588.18	0.00	589.19	588.34	0.16	1.52	0.04	586.90
27.	0.	27.	0.	0.	8.	0.	1.	0.	586.90
0.36	0.00	3.20	0.00	0.080	0.045	0.080	0.039	586.24	295.00
0.008255	136.	136.	136.	2	0	0	-6.83	4.60	299.60

*SECNO 1861.000

3470 ENCROACHMENT STATIONS= 270.0 325.0 TYPE= 1 TARGET= 55.000

XCSECT.076 OF GIBRALTAR RD. REPEATED SECT.

1861.00	2.16	588.42	0.00	589.43	588.46	0.04	0.59	0.03	586.90
27.	2.	19.	6.	2.	10.	9.	1.	0.	586.90
0.37	0.64	1.96	0.69	0.080	0.050	0.080	0.039	586.24	291.92
0.002004	25.	25.	25.	2	0	0	0.00	19.52	311.44

CCHV= 0.100 CEHV= 0.300

*SECNO 2284.000

2800 NAT Q1= 51.94 WSEL= 588.51 ENC Q1= 51.94 WSEL= 588.61 RATIO= 0.0000

NAT Q1= 57. RATIOS LOB,CH,ROB= 0.2150 0.4603 0.3247 WSEL= 588.61

3470 ENCROACHMENT STATIONS= 275.0 342.0 TYPE= 4 TARGET= 0.085

VALLEY SECTION BASED ON FIELD COOK SECTION 8450

2284.00	3.01	589.51	0.00	588.51	588.51	0.00	0.04	0.00	585.60
27.	5.	14.	0.	25.	47.	57.	2.	1.	585.60
0.85	0.15	0.34	0.17	0.050	0.053	0.080	0.041	585.50	275.05
0.000131	425.	423.	423.	2	2	0	0.00	56.96	342.01

*SECNO 2941.000

SECNO	DEPTH	CWSEL	CVELS	HSTL2	SB	AV	AL	CLOSS	BANK ELEV
@	WLOS	XSH	XSQS	XLOB	ACH	AROB	WOL	TOA	LEFT/RIGHT
TIME	WLOB	VCH	VSQS	XCH	AROB	XCH	WCH	WPEL	SSTA
SLOPE	XLOCL	XLCH	XLOCR	ITRIAL	IH2	ICONT	CORAR	TOPWID	ENDST

3470 ENCROACHMENT STATIONS= 191.0 254.0 TYPE= 1 TARGET= 36.000

100 FEET D/S OF 54" CULVERT

2941.00	3.04	588.54	0.00	588.54	588.54	0.00	0.03	0.00	585.90
27.	4.	13.	4.	23.	29.	37.	3.	2.	585.90
1.33	0.17	0.32	0.27	0.065	0.750	0.080	0.043	585.50	191.00
0.000076	657.	657.	657.	2	0	0	0.00	56.00	247.00

CCHV= 0.300 CEHV= 0.500

*SECNO 3041.000

3470 ENCROACHMENT STATIONS= 1.0 332.0 TYPE= 4 TARGET= 351.000

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 589.50 ELREA= 589.50

PRINTED IN U.S.A.
FORM 1411-08 PRINTED BY ROTARY MANIFOLD FORMS.

D/S FACE OF 54" CULVERT

	3041.00	3.23	588.53	0.00	588.53	588.59	0.06	0.02	0.03	585.55
	27.	0.	27.	0.	0.	14.	0.	4.	2.	585.55
	1.34	0.00	1.89	0.00	0.080	0.050	0.030	0.043	585.30	214.00
	0.001527	100.	100.	100.	1	0	0	0.00	4.50	218.50

SPECIAL BRIDGE

SO	XK	XKOR	COFC	RDLEN	BNC	BWP	CAREA	SS	ELCHU	ELCHD
	0.00	3.01	3.00	0.00	3.16	0.00	7.90	0.00	586.70	585.30

*SECNO 3210.000

60/0,LOW FLOW BY NORMAL BRIDGE

EGPRS= 589.077 EGLOC= 589.986 ELLC= 589.200 PCLSE= 588.531 ELTRD= 590.000

53/0 NORMAL BRIDGE,NRD= 9 MIN ELTRD= 590.00 MAX ELLC= 589.20

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLOA= 591.00 ELROA= 591.00

U/S END 54) CULVERT REPEATED SECT

	3210.00	2.27	588.97	0.00	588.97	589.11	0.14	0.44	0.04	586.95
	27.	0.	27.	0.	0.	9.	0.	4.	2.	586.95
	1.36	0.00	2.99	0.00	0.080	0.050	0.090	0.043	586.70	214.00
	0.007626	169.	169.	169.	4	0	0	-20.00	4.50	218.50

*SECNO 3255.000

3470 ENCROACHMENT STATIONS= 191.0 247.0 TYPE= 1 TARGET= 55.000

XSECTION BETWEEN 54)CULVERT & SHEEKS RD CULVERT

3255.00	2.46	589.16	0.00	589.16	589.16	0.00	0.51	0.04	586.95
27.	7.	7.	15.	5.	11.	61.	4.	2.	586.85
1.38	0.20	0.46	0.25	0.080	0.050	0.080	0.043	586.70	191.00
0.000370	25.	25.	25.	2	0	0	0.00	36.00	247.00

*SECNO 3324.000

3470 ENCROACHMENT STATIONS= 217.0 305.0 TYPE= 1 TARGET= 88.000

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLOA= 589.50 ELROA= 589.50

D/S END SHEEKS RD. CULVERT

	3324.00	3.37	589.17	0.00	589.17	589.30	0.03	0.02	0.01	586.10
	27.	0.	27.	0.	0.	19.	0.	4.	2.	586.10
	1.41	0.03	1.40	0.00	0.080	0.050	0.090	0.044	586.10	297.00
	0.000677	149.	149.	149.	2	0	0	0.00	6.30	263.30

SPECIAL BRIDGE

PRINTED IN U.S.A.
FORM 1451-08-PRINTED BY ROTARY MANIFOLD FORMS

SP	XK	XKOR	COFQ	RDLEN	BNC	BWP	BAREA	SS	ELCHU	ELCHD
	0.00	3.32	3.00	0.00	3.82	0.00	15.80	1.00	586.10	586.10

*SECNO 3548.000									
SECNO	DEPTH	CWSEL	CRIWS	HSELF	EG	HV	HL	QLOSS	BANK ELEV
0	0.00	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IH2	ICONT	CORAR	TOPWID	ENDST

PRESSURE FLOW

EGPRS	EGLWC	KQ	QWEIR	QPR	BAREA	TRAPEZOID AREA	ELLC	ELTRD
589.32	589.29	0.00	0.	27.	16.	16.	586.60	590.00

3470 ENCROACHMENT STATIONS= 217.0 305.0 TYPE= 1 TARGET= 88.000

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 590.00 ELREA= 590.00

U/S FACE OF SHEEKS'RD CULVERT (76"X 48" ELLIPTICAL CONCRETE)

3548.00	3.29	589.29	0.00	589.29	589.32	0.03	0.12	0.00	586.10
27.	3.	27.	0.	0.	20.	0.	4.	2.	586.10
1:43	0.30	1.34	0.00	0.080	0.050	0.080	0.044	586.10	257.00
0.000605	164.	164.	164.	2	2	0	0.00	6.30	263.30

*SECNO 3600.002

3470 ENCROACHMENT STATIONS= 145.0 225.0 TYPE= 1 TARGET= 110.000

XSECT. U/S OF SHEEKS RD.AND D/S OF SENECA RD.

3600.00	2.93	589.33	0.00	589.33	589.33	0.00	0.01	0.01	586.50
27.	2.	9.	13.	11.	33.	39.	4.	2.	586.58
1.51	0.19	0.47	0.10	0.080	0.050	0.000	0.044	586.40	183.65
0.000643	52.	32.	52.	0	1	1	0.00	60.59	253.30

*SECNO 3792.000

3470 ENCROACHMENT STATIONS= 1.0 310.0 TYPE= 1 TARGET= 309.000

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 591.30 ELREA= 590.10

D/S END SENECA 30. CULVERT

3792.00	1.51	589.21	0.00	589.21	589.32	0.11	0.03	0.16	588.75
27.	0.	27.	0.	0.	4.	0.	4.	2.	588.75
1.52	0.00	4.50	0.00	0.080	0.050	0.050	0.044	587.70	223.00
0.022735	192.	192.	192.	2	0	0	0.00	4.53	227.50

SPECIAL BRIDGE

SP	XK	XKOR	COFQ	RDLEN	BNC	BWP	BAREA	SS	ELCHU	ELCHD

PRINTED IN U.S.A.
FORM 1411-BD PRINTED BY ROTARY MANIFOLD FORMS

0.00	1.63	3.00	0.00	2.71	0.00	12.20	0.00	587.70	587.70

*SECNO 3835.000

OC/D,LOW FLOW BY NORMAL BRIDGE

EGPRS= 0.000 EGLOC= 589.521 ELLC= 591.000 PCWSE= 589.209 ELTRD= 590.500

3370 NORMAL BRIDGE,NRD= 8 MIN ELTRD= 590.50 MAX ELLC= 591.00

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 591.80 ELREA= 590.70

U/S FACE OF SENECA RD. CULVERT

3833.00	2.35	590.05	0.00	590.05	590.17	0.13	0.61	0.05	588.75
27.	0.	27.	0.	0.	9.	0.	4.	2.	588.75
1.52	0.00	2.94	0.00	0.080	0.050	0.066	0.044	587.70	223.00
0.010612	41.	41.	41.	4	3	0	-1.66	4.50	227.50

*SECNO 3863.000

2800 NAT QI= 6.06 WSEL= 590.35 ENC QI= 6.09 WSEL= 590.45 RATIO= 0.0000

XAT QI= 7. RATIOS LOS,CH,ROB= 0.0328 0.7051 0.1921 WSEL= 590.45

3470 ENCROACHMENT STATIONS= 223.0 234.4 TYPE= 4 TARGET= 0.146

XSECT. U/S OF SENECA RD REPEATED SECT. 3833.

3863.00	2.70	590.40	0.00	590.35	590.46	0.07	0.26	0.02	588.75
27.	0.	25.	2.	0.	11.	6.	4.	2.	588.75
1.53	0.00	2.17	0.66	0.080	0.050	0.030	0.044	587.70	223.00
0.002997	50.	50.	50.	2	0	0	0.00	11.43	234.43

*SECNO 4337.000

SECNO	DEPTH	CWSEL	CRIWS	WSELK	ES	HV	HL	QLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TRA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	LTN	CLP IN	SSTA
SLOPE	XLOBL	XLCT	XLOBR	ITRIAL	IHZ	ICONT	KODE	TOPWID	BWDST

3470 ENCROACHMENT STATIONS= 268.0 323.0 TYPE= 1 TARGET= 55.000

XSECT. D/S OF COOKE RD

4337.00	3.06	590.59	0.00	590.52	590.59	0.00	0.11	0.02	587.50
27.	3.	16.	3.	39.	28.	19.	5.	3.	587.50
1.83	0.20	0.56	0.17	0.080	0.050	0.000	0.045	587.50	268.00
0.000060	350.	454.	500.	3	3	0	0.00	55.00	323.00

*SECNO 4437.000

3470 ENCROACHMENT STATIONS= 1.0 525.0 TYPE= 1 TARGET= 525.000

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 591.00 ELREA= 591.00

D/S FACE OF COOKE RD CULVERT

4437.00	3.24	590.59	0.00	590.53	590.62	0.04	0.02	0.02	587.35

PRINTED IN U.S.A.
FORM 1411-08 PRINTED BY ROTARY MANIFOLD FORMS

27.	0.	27.	0.	0.	13.	0.	5.	3.	587.35	
1.85	0.00	1.52	0.00	0.080	0.050	0.080	0.045	587.35	293.00	
0.000937	100.	100.	100.	2	0	0	0.00	5.50	298.50	

SPECIAL BRIDGE

SD	XR	XXOR	COFQ	RDLEN	BWC	B-P	BAREA	SS	ELCHU	ELCHD
	0.00	1.93	3.00	0.00	3.93	0.00	4.91	0.00	587.35	587.35

*SECND 4479.000
PRESSURE FLOW

EGPRS	EGLWC	H3	QWEIR	QPR	BAREA	TRAPEZOID AREA	ELLC	ELTRD
591.49	590.62	0.00	0.	27.	5.	5.	588.60	591.70

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 592.00 ELREA= 592.00

U/S FACE OF COOKE RD. CULVERT

4479.00	4.12	591.47	0.00	591.41	591.49	0.02	0.87	0.00	587.35
27.	0.	27.	0.	0.	23.	0.	5.	3.	587.35
1.86	0.00	1.19	0.00	0.080	0.050	0.080	0.045	587.35	293.00
0.000479	42.	42.	42.	2	0	0	0.00	5.50	298.50

*SECND 4504.000

5470 ENCROACHMENT STATIONS= 268.0 523.0 TYPE= 1 TARGET= 55.000

XSECTION U/S COOKE RD

4504.00	4.15	591.50	0.07	591.44	591.50	0.00	0.00	0.01	587.35	
27.	10.	9.	0.	50.	23.	51.	5.	3.	587.35	
1.80	0.18	0.41	0.19	0.300	0.050	0.080	0.045	587.35	268.00	
0.000029	25.	25.	25.	1	0	0	0.00	55.00	323.00	

CCHV= 0.100 CEHV= 0.300
*SECND 4853.000

5470 ENCROACHMENT STATIONS= 438.0 543.0 TYPE= 1 TARGET= 125.000

VALLEY SECTION BASED ON FIELD BOOK SECT.5081

4853.00	3.80	591.51	0.00	591.46	591.51	0.00	0.01	0.00	589.41	
27.	9.	13.	5.	130.	62.	56.	5.	3.	589.35	
2.56	0.09	0.31	0.09	0.100	0.050	0.150	0.043	587.71	438.00	
0.000016	349.	349.	349.	2	0	0	0.01	103.07	541.07	

CCHV= 0.300 CEHV= 0.500
*SECND 5034.000
5800 WAT QT= 49.01 WSEL= 591.65 ENG CT= 49.01 WSEL= 591.55 RATIO= 0.3030
WAT QT= 51. RATIOS LOB,CH,ROB= 0.0936 0.3531 0.0936 WSEL= 589.59

SECNO	DEPTH	CWSEL	CRIWS	WSELK	ZEG	AREA	VOL	CLOSS	RANK SLOP
	FLOW	SCH	SROU	ALOB	ASC	ROBA	VOL	TAB	LEFT/RIGHT
	TOP	6.03	630.	VTOP	KE	ANCH	PREV	PATH	PLAN	SE

PRINTED IN U.S.A.
FORM 1411.08 PRINTED BY ROTARY MANIFOLD FORMS.

	SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IN2	ICONT	CORAR	TOPWID	ENDST
3470 ENCROACHMENT STATIONS=		590.5	609.5	TYPE=	4	TARGET=		0.035		
XSECTION D/S OF TELEGRAPH RD.										
	5053.00	5.14	591.51	0.00	591.45	591.51	0.00	0.00	0.00	586.37
	27.	2.	23.	2.	14.	57.	14.	7.	4.	586.37
	2.69	0.13	0.41	0.13	0.100	0.060	0.100	0.047	586.37	590.55
	0.000031	200.	200.	200.	0	0	0	0.00	18.90	609.45

*SECNO 5253.000

3470 ENCROACHMENT STATIONS=		1.0	1200.0	TYPE=	1	TARGET=	1199.000.			
3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLOB=		592.00-ELREA=		592.00						
D/S FACE TELEGRAPH RD.										
	5253.00	5.17	591.51	0.00	591.46	591.51	0.03	0.02	0.01	586.40
	27.	0.	27.	0.	0.	27.	0.	7.	4.	586.40
	2.73	0.00	1.32	0.00	0.100	0.050	0.100	0.047	586.40	495.00
	0.000426	200.	200.	200.	0	0	0	0.00	4.00	499.00

SPECIAL BRIDGE

SB	XK	XKOR	COFQ	RDLEN	BWC	SUP	BAREA	SS	ELCHU	ELCHD
	0.00	5.79	5.00	0.00	3.63	0.00	10.90	0.00	587.30	586.40

*SECNO 5299.000
PRESS FLOW BECAUSE SOLNG OF 592.07 EXCEEDS 1.5 DEPTH
PRESSURE FLOW

EGPRS	SOLNG	HS	VOCH	S-R	SAREA	TRAPEZOID AREA	ELLO	ELTIO
592.07	592.44	0.00	0.	27.	11.	11.	590.30	594.40

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLOB=		594.40 ELREA=		594.40						
U/S FACE OF TELEGRAPH RD.										
	5299.00	4.73	592.03	0.00	591.98	592.07	0.03	0.52	0.00	588.50
	27.	3.	27.	0.	3.	19.	0.	7.	4.	590.90
	2.74	3.00	1.43	0.00	0.100	0.050	0.100	0.047	587.30	495.00
	0.000373	46.	46.	46.	2	0	0	0.00	4.00	499.00

*SECNO 5349.000

3000 KAT 21=	14.04	WSEL=	592.03	EGL CT=	14.06	HSEL=	348.15	RATIO=	0.3003	
IT 11=	15.	RATIOS LOB,CH,ROB=	0.1504	0.5797	0.1699	ESEL=	592.13			
3470 ENCROACHMENT STATIONS=		491.3	503.2	TYPE=	4	TARGET=		0.046		
HSEL= U/S OF TELEGRAPH RD										

PRINTED IN U.S.A.
FORM 1411-SB PRINTED BY ROTARY MANIFOLD FORMS

5349.00	4.79	592.09	0.00	592.03	592.10	0.01	0.03	0.01	588.50	
27.	4.	19.	4.	9.	19.	10.	7.	4.	588.50	
2.75	0.40	1.00	0.41	0.100	0.060	0.100	0.047	587.30	491.27	
0.000376	50.	50.	50.	2	0	0	0.00	17.93	303.19	

*SECNO 5676.000
2800 NAT Q1= 39.54 WSEL= 592.08 ENC Q1= 39.54 WSEL= 592.18 RATIO= 0.0000
NAT Q1= 51. RATIOS LOB,CH,ROB= 0.2631 0.6699 0.0669 WSEL= 592.18

3265 DIVIDED FLOW

3470 ENCROACHMENT STATIONS= 328.6 405.0 TYPE= 4 TARGET= 0.227

XSECT. D/S OF R.R. TRACKS

5676.00	4.27	592.19	0.00	592.08	592.15	0.00	0.05	0.00	587.40
27.	4.	23.	0.	29.	48.	0.	8.	4.	587.40
2.97	0.15	0.47	0.00	0.100	0.060	0.100	0.048	587.28	328.60
0.000075	527.	527.	527.	0	0	0	0.00	35.67	405.00

CCHV= 0.300 CEHV= 0.300
*SECNO 5776.000

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	QLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTH	CLMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IM2	ICONT	CORAR	TOPWID	ENDST

3470 ENCROACHMENT STATIONS= 1.0 436.0 TYPE= 1 TARGET= 485.000

3493 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEN= 597.00 ELREA= 594.00

D/S FACE OF R.R. CULVERT

5776.00	3.83	592.14	0.00	592.08	592.00	0.05	0.02	0.05	588.26
27.	0.	27.	0.	0.	14.	0.	4.	6.	530.26
2.99	0.00	1.99	0.00	0.120	0.060	0.120	0.03	588.24	399.00
0.001005	100.	100.	100.	2	0	0	0.00	3.50	402.50

SPECIAL BRIDGE

SD	XK	XKOR	COPG	RDLEN	BLC	BHP	BAREA	SS	ELCHU	ELCHD
	0.00	2.85	3.00	0.00	2.74	0.00	2.40	0.00	589.00	588.26

*SECNO 5851.300
PRESSURE FLOW

ESPRS	BSLNC	S3	CWEIR	QPR	BAREA	TRAPEZOID AREA	ELLC	ELTRD
597.74	592.94	0.03	0.	27.	2.	5.	590.75	589.43

3493 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEN= 601.10 ELREA= 600.30

PRINTED IN U.S.A.
FORM 1411-OD-PRINTED BY ROTARY MANIFOLD FORMS

U/S FACE OF 42" RAILROAD CULVERT

5851.00	8.73	597.73	0.00	597.65	597.74	0.01	5.54	0.00	589.00
27.	0.	27.	0.	0.	31.	0.	5.	4.	589.00
3.01	0.00	0.88	0.00	0.120	0.060	0.120	0.048	589.00	699.00
0.000365	75.	75.	75.	1	0	0	0.00	3.50	702.50

*SECNO 5876.000

3470 ENCROACHMENT STATIONS=	675.0	727.0	TYPE= 1	TARGET=	52.000

X-SECT. U/S OF R.R. TRACKS " D/S OF ARSENAL

5876.00	8.35	597.74	0.00	597.66	597.74	0.00	0.00	0.00	589.39
27.	8.	11.	8.	143.	84.	153.	8.	4.	589.39
3.09	0.05	0.13	0.05	0.120	0.060	0.120	0.048	589.39	675.00
0.000002	25.	25.	25.	1	0	0	0.00	52.00	727.00

*SECNO 5931.000

3470 ENCROACHMENT STATIONS=	760.0	340.0	TYPE= 1	TARGET=	80.000

D/S FACE ARSENAL CULVERTS

5931.00	8.34	597.74	0.00	597.66	597.75	0.00	0.00	0.00	589.40
27.	5.	14.	8.	39.	25.	50.	8.	4.	589.40
3.13	0.13	0.55	0.18	0.120	0.060	0.120	0.048	589.40	732.82
0.000329	55.	55.	55.	1	0	0	0.00	47.97	830.79

SPECIAL BRIDGE

SECND,VARIABLE ELCND OR ELCRD CN CARD IN NOT SPECIFIED

SB	XK	XKOR	COPD	RDLEN	BHC	BWP	AREA	SB	ELCND	ELCRD
	0.00	3.70	3.00	0.00	2.40	0.00	3.60	0.00	589.40	589.40

*SECNO 6006.000
WATER EL=XS ORDR= 597.351

U/S FACE ARSENAL CULVERT

6006.00	8.43	597.83	0.00	597.73	597.84	0.01	0.00	0.00	589.40
27.	6.	18.	3.	56.	25.	20.	9.	4.	589.40
3.17	0.15	0.73	0.10	0.120	0.060	0.120	0.048	589.40	782.45
0.000050	75.	75.	75.	1	0	0	0.00	53.21	852.67

*SECNO 6050.000

ZERO WAT EL=	36.70	WSEL=	597.71	ENC DP=	36.72	WSEL=	597.61	RATIO=	0.0030
MAT CLR	58.	RATIOS LOB,CH,ROB=	0.2157	0.6327	0.1026	ASEL=	597.85		
SECNO	DEPTH	CHSEL	OPSEL	ASEL	FB	HV	QI	CLOSS	BANK ELEV
0	CLOD	QCH	QROB	ALOB	VCH	AROB	VOL	TRA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	.TW	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IK2	ICONT	CORAR	TOPWID	ENDST

3470 ENCROACHMENT STATIONS= 709.5 809.5 TYPE= 4 TARGET= 0.051

X-SECTION U/S OF ARSENAL

FORM 1411-GB PRINTED BY ROTARY MANIFOLD FORMS.
PRINTED IN U.S.A.

6050.00	8.41	597.81	0.00	597.71	597.87	0.06	0.01	0.03	589.40
85.	17.	60.	8.	32.	25.	19.	9.	4.	589.40
3.18	0.54	2.38	0.40	0.120	0.060	0.120	0.049	589.40	789.49
0.000538	44.	44.	44.	2	0	0	0.00	23.02	809.52

CCHV= 0.100 CEHV= 0.300
*SECNO 7934.000

3470 ENCROACHMENT STATIONS= 583.0 718.0 TYPE= 1 TARGET= 135.000

VALLEY SECTION BASED ON FIELD BOOK SECT. 2800.

7954.00	9.08	597.94	0.00	597.85	597.94	0.00	0.06	0.01	589.76
85.	30.	24.	31.	280.	69.	288.	24.	7.	589.65
6.19	0.11	0.34	0.11	0.120	0.060	0.120	0.051	588.86	583.00
0.000011	1884.	1884.	1884.	2	0	0	3.00	135.00	718.00

*SECNO 8734.000

3470 ENCROACHMENT STATIONS= 382.0 518.0 TYPE= 1 TARGET= 136.000

VALLEY SECTION BASED ON FIELD BOOK SECT. 2000.

8734.00	6.77	597.96	0.00	597.86	597.96	0.00	0.01	0.00	591.49
85.	37.	17.	31.	255.	40.	227.	35.	10.	591.29
3.50	0.15	0.43	0.14	0.120	0.060	0.120	0.052	591.19	332.00
0.000024	300.	800.	800.	2	0	0	0.00	136.00	518.00

*SECNO 9734.000

3470 ENCROACHMENT STATIONS= 246.0 420.0 TYPE= 1 TARGET= 135.000

VALLEY SECTION BASED ON FIELD BOOK SECT. 1600.

9736.00	5.65	597.99	0.00	597.90	597.99	0.00	0.05	0.00	592.64
85.	27.	30.	26.	164.	55.	173.	45.	13.	592.54
8.24	3.17	0.34	0.14	0.120	0.060	0.120	0.033	592.54	265.00
0.000049	1000.	1000.	1000.	1	0	0	0.00	135.00	420.00

CCHV= 0.300 CEHV= 0.500
*SECNO 10613.000

3470 ENCROACHMENT STATIONS= 439.0 556.0 TYPE= 1 TARGET= 133.000

XSECT.D/S OF INKSTER RD

10613.00	6.15	598.05	0.00	597.96	598.05	0.00	0.06	0.00	591.90
85.	33.	17.	33.	110.	19.	106.	58.	19.	591.80
8.53	0.29	0.65	0.30	0.081	0.060	0.080	0.055	591.80	433.00
0.000107	879.	879.	879.	2	0	0	0.00	135.00	546.00

*SECNO 10713.000

SECNO	DEPTH	CHSEL	CRIWS	HSELK	EG	WV	HL	CLOSS	BANK ELEV
Q	XLOB	JCH	CROB	XLOB	ACH	AXOB	VOL	TWA	LEFT/RIGHT
FICS	VLOB	VCH	PROB	KNL	XCH	IKLR	MT	ELMIN	SSTA
SLOPE	XLOBL	XLCH	NLOOR	CTPWL	IH2	ICONT	CURAR	ZOPOD	ESDST

PRINTED IN U.S.A.
FORM 1411-08-PRINTED BY ROTARY MANIFOLD FORMS

3470 ENCROACHMENT STATIONS= 433.0 566.0 TYPE= 1 TARGET= 133.000

D/S FACE OF INKSTER RD CULVERT

10713.00	6.45	598.06	0.00	597.97	598.06	0.00	0.01	0.00	591.60	
85.	33.	17.	33.	117.	19.	116.	52.	16.	591.60	
8.90	0.29	0.88	0.30	0.080	0.060	0.060	0.053	591.60	435.00	
0.000105	100.	100.	100.	0	0	0	0.00	133.00	566.00	

SPECIAL BRIDGE

SK	XK	XKOR	COPO	RDLEN	DWC	BWP	BAREA	SS	ELCHD	ELCND
	0.00	2.60	3.00	0.00	2.40	0.00	3.60	0.00	593.54	591.62

*SECND 10754.000
PRESSURE AND WEIR FLOW

EGPRS	ZGLWC	HB	QWEIR	QPR	BAREA	TRAPEZOID AREA	ELLC	ELTRD
620.57	600.00	0.00	76.	9.	4.	4.	595.04	597.90

U/S FACE OF INKSTER RD. CULVERT

10754.00	4.76	598.30	0.00	598.30	598.39	0.00	0.24	0.00	593.54	
85.	42.	10.	33.	132.	14.	113.	53.	16.	593.54	
8.93	0.32	0.73	0.29	0.080	0.060	0.060	0.053	593.54	433.73	
0.000167	41.	41.	41.	0	0	3	0.00	132.42	566.20	

*SECND 10779.000
END OF DAT 01= 81.73 WSEL= 598.30 CRIT DEPTH= 81.75 HSEL= 598.40 RATIO= 0.0200
DAT 01= 88. RATIOS LOB,CH,ROB= 0.4922 0.1175 0.3903 WSEL= 598.40

3470 ENCROACHMENT STATIONS= 439.5 558.5 TYPE= 4 TARGET= 0.073

HOUSE U/S OF INKSTER RD.

10779.00	4.77	598.31	0.00	598.30	598.31	0.00	0.00	0.00	593.54	
85.	42.	11.	32.	122.	14.	102.	53.	16.	593.54	
8.95	0.34	0.78	0.31	0.080	0.060	0.030	0.053	593.54	439.50	
0.000124	25.	25.	25.	0	0	0	0.00	119.01	556.30	

PRINTED IN U.S.A.
FORM 1411-08-PRINTED BY ROTARY MANIFOLD FORMS.

****
HEC2 RELEASE DATED NOV 76 UPDATED FEB 1977
ERROR CORR - 01
MODIFICATION - 50,51,52
****

NOTE- ASTERISK (*) AT LEFT OF CROSS-SECTION NUMBER INDICATES MESSAGE IN SUMMARY OF ERRORS LIST

COOKE & GLADDING RIVER,

SUMMARY PRINTOUT TABLE 110

	SECNO	CHSEL	DIFKWS	ES	TOPWID	ALOB	ACH	ARCH	PERMEC	STENCL	STCHL	STCRP	STENDR
A	0.000	585.40	0.00	585.43	4.50	0.00	27.00	0.00	0.00	0.00	75.00	79.50	0.00
	0.000	585.50	0.10	585.53	4.50	0.00	27.00	0.00	150.00	1.00	75.00	79.50	151.00
B	54.000	585.45	0.00	585.47	4.50	0.00	27.00	0.00	0.00	0.00	88.00	92.50	0.00
	54.000	585.53	0.10	585.57	4.50	0.00	27.00	0.00	0.00	0.00	88.00	92.50	0.00
C	300.000	585.54	0.00	585.55	17.55	2.85	21.84	2.31	0.00	0.00	297.00	303.00	0.00
	300.000	585.63	0.09	585.64	11.75	2.33	22.88	1.74	0.05	294.38	297.00	303.00	305.55
D	1300.000	585.69	0.00	585.72	35.37	1.10	24.62	1.26	0.00	0.00	276.00	284.00	0.00
	1300.000	585.79	0.09	585.81	9.17	0.01	26.47	0.51	0.08	275.92	276.00	284.00	285.05
E	1600.000	585.88	0.00	585.98	9.04	0.63	24.53	1.84	0.00	0.00	297.50	302.10	0.00
	1600.000	585.97	0.09	586.06	9.35	0.69	24.30	2.01	599.00	1.00	297.50	302.10	600.00
F	1700.000	586.40	0.00	586.73	4.50	0.00	27.00	0.00	0.00	0.00	297.50	302.10	0.00
	1700.000	586.49	0.01	586.72	4.50	0.00	27.00	0.00	599.00	1.00	297.50	302.10	600.00
G	1836.000	588.19	0.00	588.35	4.50	0.00	27.00	0.00	0.00	0.00	295.00	299.60	0.00
	1836.000	588.18	-0.01	588.34	4.50	0.00	27.00	0.00	0.00	0.00	295.00	299.60	0.00
H	1861.000	588.43	0.00	588.62	19.68	1.52	19.24	4.23	55.00	270.00	295.00	299.60	325.00
	1861.000	588.43	-0.01	588.62	12.52	1.51	19.31	3.19	55.00	270.00	295.00	299.60	325.00
I	2284.000	588.51	0.00	588.51	136.93	5.60	12.04	3.68	0.00	0.00	293.00	307.00	0.00
	2284.000	588.51	-0.00	588.51	66.90	5.02	13.31	2.17	0.03	275.03	293.00	307.00	342.01
J	2941.000	588.54	0.00	588.56	56.00	4.95	15.24	7.62	56.00	191.00	214.00	224.00	247.00
	2941.000	588.54	-0.00	588.56	56.00	4.95	15.24	7.62	56.00	191.00	214.00	224.00	247.00
K	3041.000	588.53	0.00	588.59	4.50	0.00	27.00	0.00	0.00	0.00	214.00	218.50	0.00
	3041.000	588.53	-0.00	588.59	4.50	0.00	27.00	0.00	351.00	1.00	214.00	218.50	352.00
L	3210.000	588.97	0.00	589.11	4.50	0.00	27.00	0.00	0.00	0.00	214.00	218.50	0.00
	3210.000	588.97	-0.00	589.11	4.50	0.00	27.00	0.00	0.00	0.00	214.00	218.50	0.00
M	3235.000	589.16	0.00	589.16	56.00	6.94	4.82	15.24	56.00	191.00	214.00	218.50	247.00
	3235.000	589.16	-0.00	589.16	56.00	6.94	4.82	15.24	56.00	191.00	214.00	218.50	247.00

PRINTED IN U.S.A.
FORM 1411-08 PRINTED BY ROTARY MANIFOLD FORMS.

	SECNO	CWSEL	DIFKWS	EG	TOPWID	QLOB	QCH	QROB	PERENG	STENCL	STCHL	STCHR	STENCR
	3384.000	589.17	0.00	589.20	6.30	0.00	27.00	0.00	68.00	217.00	257.00	263.30	305.00
	3384.000	589.17	-0.00	589.20	6.30	0.00	27.00	0.00	68.00	217.00	257.00	263.30	305.00
	3548.000	589.29	0.00	589.32	6.30	0.00	27.00	0.00	68.00	217.00	257.00	263.30	305.00
	3548.000	589.29	-0.00	589.32	6.30	0.00	27.00	0.00	68.00	217.00	257.00	263.30	305.00
	3620.000	589.33	0.00	589.33	69.35	2.20	9.09	15.72	110.00	145.00	196.00	204.00	255.00
	3620.000	589.33	-0.00	589.33	69.35	2.20	9.09	15.72	110.00	145.00	196.00	204.00	255.00
	3792.000	589.21	0.00	589.52	4.50	0.00	27.00	0.00	0.00	0.00	223.00	227.50	0.00
	3792.000	589.21	-0.00	589.52	4.50	0.00	27.00	0.00	309.00	1.00	223.00	227.50	310.00
	3833.000	590.05	0.00	590.19	4.50	0.00	27.00	0.00	0.00	0.00	223.00	227.50	0.00
	3833.000	590.05	0.00	590.19	4.50	0.00	27.00	0.00	0.00	0.00	223.00	227.50	0.00
	3883.000	590.35	0.00	590.40	68.07	0.60	23.39	3.31	0.00	0.00	223.00	227.50	0.00
	3883.000	590.40	0.05	590.46	11.43	0.00	24.63	2.37	0.15	223.00	223.00	227.50	234.43
	4337.000	590.52	0.00	590.53	55.00	7.81	15.99	3.20	55.00	268.00	295.50	304.50	323.00
	4337.000	590.58	0.06	590.59	55.00	7.97	15.71	3.32	55.00	268.00	295.50	304.50	323.00
	4437.000	590.53	0.00	590.57	5.50	0.00	27.00	0.00	0.00	0.00	293.00	298.50	0.00
	4437.000	590.59	0.06	590.62	5.50	0.00	27.00	0.00	525.00	1.00	293.00	298.50	526.00
	4479.000	591.41	0.00	591.43	5.50	0.00	27.00	0.00	0.00	0.00	293.00	298.50	0.00
	4479.000	591.47	0.06	591.49	5.50	0.00	27.00	0.00	0.00	0.00	293.00	298.50	0.00
	4504.000	591.44	0.00	591.46	55.00	9.51	9.50	7.99	55.00	268.00	293.00	298.50	323.00
	4504.000	591.50	0.06	591.50	55.00	9.56	9.39	8.06	55.00	268.00	293.00	298.50	323.00
	4853.000	591.65	0.00	591.45	102.93	8.77	13.36	4.87	125.00	434.00	491.00	510.90	563.00
	4853.000	591.31	0.06	591.31	103.07	8.06	13.27	4.92	25.00	434.00	491.00	512.00	563.00
	5053.000	591.45	0.00	591.43	24.30	2.42	22.57	3.23	0.00	0.00	594.50	598.50	0.00
	5053.000	591.51	0.06	591.51	18.90	1.90	23.20	2.90	0.03	599.55	596.50	602.30	609.45
	5253.000	591.46	0.00	591.48	4.00	0.00	27.00	0.00	0.00	0.00	495.00	499.00	0.00
	5253.000	591.51	0.00	591.54	4.00	0.00	27.00	0.00	1199.00	1.00	495.00	499.00	1200.00
	5299.000	591.93	0.00	592.01	4.00	0.00	27.00	0.00	0.00	0.00	495.00	499.00	0.00
	5299.000	592.03	0.06	592.07	4.00	0.00	27.00	0.00	0.00	0.00	495.00	499.00	0.00
	5349.000	592.03	0.00	592.04	16.51	3.95	18.58	4.47	0.00	0.00	495.00	499.00	0.00
	5349.000	592.09	0.06	592.10	11.03	3.67	19.10	4.23	0.05	491.27	495.05	499.00	503.19
	5676.000	592.08	0.00	592.01	22.30	2.21	23.58	2.21	55.00	373.00	395.00	405.00	430.00
	5676.000	592.15	0.07	592.13	35.67	4.39	22.61	0.00	0.23	328.60	395.00	405.00	405.00
	5775.000	592.06	0.00	592.12	3.50	0.00	27.00	0.00	0.00	0.00	399.00	402.50	0.00
	5775.000	592.12	0.06	592.20	3.50	0.00	27.00	0.00	405.00	1.00	399.00	402.50	466.00
	5851.000	597.65	0.00	597.65	3.50	0.00	27.00	0.00	0.00	0.00	699.00	702.50	0.00
	5851.000	597.73	0.08	597.74	3.50	0.00	27.00	0.00	0.00	0.00	699.00	702.50	0.00
	5876.000	597.66	0.00	597.66	52.00	7.84	11.19	7.97	52.00	675.00	695.00	705.00	787.00
	5876.000	597.74	0.08	597.74	51.00	7.82	11.18	7.98	52.00	675.00	695.00	705.00	727.00

PRINTED IN U.S.A.
FORM 1411-08-PRINTED BY ROTARY MANIFOLD FORMS

	SECNO	CHSEL	DIFKWS	EG	TOPWID	QLOS	QCH	QROD	PERENC	STENCL	STCHL	STCHR	STENCR
	5931.000	597.66	0.00	597.67	45.20	5.15	13.77	8.08	80.00	760.00	799.00	802.00	840.00
	5931.000	597.74	0.08	597.75	47.97	5.22	13.66	0.43	80.00	760.00	799.00	802.00	840.00
*	6006.000	597.73	0.00	597.74	46.67	5.70	18.67	2.83	0.00	0.00	799.00	802.00	0.00
*	6006.000	597.83	0.10	597.84	50.21	5.82	18.38	2.80	0.00	0.00	799.00	802.00	0.00
	6050.000	597.71	0.00	597.77	46.41	17.93	58.83	8.25	0.00	0.00	799.00	802.00	0.00
	6050.000	597.81	0.10	597.87	20.02	17.36	59.98	7.65	0.03	789.49	799.00	802.00	859.52
	7934.000	597.85	0.00	597.85	135.00	29.69	24.10	31.21	135.00	583.00	646.00	654.00	718.00
	7934.000	597.94	0.10	597.94	135.00	29.84	23.82	31.34	135.00	583.00	646.00	654.00	718.00
	8734.000	597.86	0.00	597.86	136.00	37.19	17.38	30.43	136.00	382.00	447.00	453.00	518.00
	8734.000	597.96	0.10	597.96	136.00	37.24	17.13	30.63	136.00	382.00	447.00	453.00	518.00
	9734.000	597.90	0.00	597.90	135.00	24.90	31.43	27.61	135.00	285.00	345.00	353.00	420.00
	9734.000	597.99	0.09	597.99	135.00	27.15	29.92	27.95	135.00	285.00	345.00	353.00	420.00
	10613.000	597.96	0.00	597.97	133.00	32.93	17.87	34.20	133.00	433.00	498.00	501.00	566.00
	10613.000	598.05	0.09	598.05	133.00	33.33	17.14	34.52	133.00	433.00	498.00	501.00	566.00
	10713.000	597.97	0.00	597.98	133.00	32.97	17.60	34.24	133.00	433.00	498.00	501.00	566.00
	10713.000	598.06	0.09	598.06	133.00	33.37	17.08	34.55	133.00	433.00	498.00	501.00	566.00
	10754.000	598.30	0.00	598.30	132.42	41.81	10.41	32.77	0.00	0.00	498.00	501.00	0.00
	10754.000	598.30	0.01	598.31	132.42	41.82	10.38	32.80	0.00	0.00	498.00	501.00	0.00
	10779.000	598.30	0.00	598.30	132.42	41.82	10.41	32.78	0.00	0.00	498.00	501.00	0.00
	10779.000	598.31	0.01	598.31	119.01	41.76	11.16	52.09	0.07	439.50	498.00	501.00	558.50

PRINTED IN U.S.A.
FORM 1411-GD PRINTED BY ROTARY MANIFOLD FORMS.

COOKE & GLADDING RIVER,

SUMMARY PRINTOUT TABLE 150

SECNO	XLCH	ELTRD	ELLC	ELMIN	Q	CWSEL	CRIWS	EG	TOPWS	VCH	AREA	.01K
0.000	0.00	0.00	0.00	581.00	27.00	585.40	0.00	585.43	6.07	1.36	19.80	10.96
0.000	0.00	0.00	0.00	581.00	27.00	585.50	0.00	585.53	5.74	1.33	20.25	11.27
54.000	54.00	588.00	585.60	581.10	27.00	585.43	0.00	585.47	7.48	1.57	16.19	9.87
54.000	54.00	588.00	585.60	581.10	27.00	585.53	0.00	585.57	7.00	1.53	16.58	10.21
300.000	300.00	0.00	0.00	581.51	27.00	585.54	0.00	585.55	1.09	1.00	40.35	26.33
300.000	300.00	0.00	0.00	581.51	27.00	585.63	0.00	585.66	1.05	1.02	36.85	26.33
1300.000	1000.00	0.00	0.00	583.01	27.00	585.69	0.00	585.72	3.06	1.30	27.69	15.45
1300.000	1000.00	0.00	0.00	583.01	27.00	585.77	0.00	585.81	3.11	1.35	21.74	15.31
1600.000	300.00	0.00	0.00	583.29	27.00	585.88	0.00	585.90	38.67	2.69	12.19	4.34
1600.000	300.00	0.00	0.00	583.29	27.00	585.97	0.00	586.00	32.49	2.54	13.05	4.74
1700.000	100.00	0.00	0.00	585.14	27.00	586.48	0.00	586.78	162.05	4.38	6.16	2.12
1700.000	100.00	0.00	0.00	585.14	27.00	586.49	0.00	586.76	158.73	4.36	6.20	2.14
1836.000	136.00	592.80	588.90	586.24	27.00	588.19	0.00	588.35	82.53	3.20	8.44	2.97
1836.000	136.00	592.80	588.90	586.24	27.00	588.18	0.00	588.34	82.55	3.20	8.44	2.97
1861.000	25.00	0.00	0.00	586.24	27.00	588.43	0.00	588.47	19.66	1.95	21.36	6.69
1861.000	25.00	0.00	0.00	586.24	27.00	588.42	0.00	588.46	20.04	1.96	21.18	6.63
2284.000	423.00	0.00	0.00	585.50	27.00	588.51	0.00	588.51	0.27	0.31	173.11	51.94
2284.000	423.00	0.00	0.00	585.50	27.00	588.51	0.00	588.51	0.31	0.36	130.66	48.14
2961.000	677.00	0.00	0.00	585.50	27.00	588.54	0.00	588.54	0.74	0.52	39.13	31.29
2961.000	677.00	0.00	0.00	585.50	27.00	588.54	0.00	588.54	0.74	0.52	39.12	31.29
3061.000	100.00	0.00	0.00	585.30	27.00	588.53	0.00	588.59	15.27	1.89	14.32	6.91
3061.000	100.00	0.00	0.00	585.30	27.00	588.53	0.00	588.59	15.27	1.89	14.32	6.91
3210.000	149.00	590.00	585.20	584.70	27.00	588.97	0.00	589.11	72.36	2.59	9.02	5.10
3210.000	149.00	590.00	585.20	584.70	27.00	588.97	0.00	589.11	72.36	2.59	9.02	5.10
3235.000	25.00	0.00	0.00	586.70	27.00	589.16	0.00	589.16	0.70	0.64	106.69	32.54
3235.000	25.00	0.00	0.00	586.70	27.00	589.16	0.00	589.16	0.70	0.64	106.68	32.53
3384.000	149.00	0.00	0.00	586.10	27.00	589.17	0.00	589.20	5.77	1.40	19.33	10.35
3384.000	149.00	0.00	0.00	586.10	27.00	589.17	0.00	589.20	5.77	1.40	19.33	10.35
3548.000	164.00	590.00	588.60	586.10	27.00	589.29	0.00	589.32	6.04	1.34	20.10	10.98
3548.000	164.00	590.00	588.60	586.10	27.00	589.29	0.00	589.32	6.05	1.34	20.10	10.98
3600.000	52.00	0.00	0.00	586.40	27.00	589.33	0.00	589.33	0.43	0.40	127.10	41.04
3600.000	52.00	0.00	0.00	586.40	27.00	589.33	0.00	589.33	0.43	0.40	127.09	41.03
3792.000	192.00	0.00	0.00	587.70	27.00	589.21	0.00	589.52	227.22	4.50	6.01	1.79
3792.000	192.00	0.00	0.00	587.70	27.00	589.21	0.00	589.52	227.35	4.50	6.00	1.79
3853.000	61.00	590.50	591.00	587.70	27.00	590.05	0.00	590.19	106.12	2.96	9.17	2.62
3853.000	61.00	590.50	591.00	587.70	27.00	590.05	0.00	590.19	106.12	2.94	9.17	2.62

PRINTED IN U.S.A.
FORM 1411-GB PRINTED BY ROTARY MANIFOLD FORMS

SECNO	XLCH	ELTRD	ELLC	ELMIN	Q	CHSEL	CRIWS	EG	TOKAS	VCH	AREA	.01K
3883.000	50.00	0.00	0.00	587.70	27.00	590.35	0.00	590.40	19.85	2.08	22.87	6.06
3883.000	50.00	0.00	0.00	587.70	27.00	590.40	0.00	590.46	25.97	2.77	14.93	4.93
4337.000	454.00	0.00	0.00	587.50	27.00	590.32	0.00	590.53	0.89	0.59	82.76	28.05
4337.000	454.00	0.00	0.00	587.50	27.00	590.38	0.00	590.59	0.80	0.56	86.06	30.15
4437.000	100.00	0.00	0.00	587.35	27.00	590.53	0.00	590.57	9.87	1.54	17.48	3.59
4437.000	100.00	0.00	0.00	587.35	27.00	590.59	0.00	590.62	9.37	1.52	17.80	8.82
4479.000	42.00	591.70	588.61	587.35	27.00	591.41	0.00	591.43	4.99	1.21	22.34	12.09
4479.000	42.00	591.70	588.60	587.35	27.00	591.47	0.00	591.49	4.79	1.19	22.67	12.33
4504.000	25.00	0.00	0.00	587.35	27.00	591.46	0.00	591.44	0.31	0.42	120.09	48.49
4504.000	25.00	0.00	0.00	587.35	27.00	591.50	0.00	591.50	0.29	0.41	131.32	50.25
4853.000	349.00	0.00	0.00	587.71	27.00	591.45	0.00	591.45	0.17	0.22	248.72	65.42
4853.000	349.00	0.00	0.00	587.71	27.00	591.51	0.00	591.51	0.16	0.21	218.73	68.14
5053.000	200.00	0.00	0.00	586.37	27.00	591.45	0.00	591.46	0.30	0.40	89.82	49.01
5053.000	200.00	0.00	0.00	586.37	27.00	591.51	0.00	591.51	0.31	0.41	85.29	48.37
5253.000	200.00	0.00	0.00	586.40	27.00	591.46	0.00	591.48	4.39	1.33	20.23	12.89
5253.000	200.00	0.00	0.00	586.40	27.00	591.51	0.00	591.54	4.26	1.32	20.47	13.07
5299.000	46.00	594.40	590.30	587.30	27.00	591.98	0.00	592.01	10.07	1.44	13.70	8.51
5299.000	46.00	594.40	590.30	587.30	27.00	592.03	0.00	592.07	9.73	1.43	13.94	8.69
5349.000	50.00	0.00	0.00	587.30	27.00	592.03	0.00	592.04	3.70	0.92	41.05	14.04
5349.000	50.00	0.00	0.00	587.30	27.00	592.09	0.00	592.10	3.76	1.00	38.73	13.95
5676.000	327.00	0.00	0.00	587.26	27.00	592.08	0.00	592.08	0.47	0.68	76.12	39.56
5676.000	327.00	0.00	0.00	587.26	27.00	592.13	0.00	592.15	0.75	0.87	77.56	31.19
5776.000	100.00	0.00	0.00	586.26	27.00	592.06	0.00	592.12	19.05	2.05	13.80	6.19
5776.000	100.00	0.00	0.00	586.26	27.00	592.14	0.00	592.20	18.05	1.99	15.58	6.56
5851.000	75.00	599.40	590.73	589.00	27.00	597.65	0.00	597.66	3.73	0.89	30.29	13.94
5851.000	75.00	599.40	590.73	589.00	27.00	597.73	0.00	597.74	2.65	0.80	50.57	14.13
5876.000	25.00	0.00	0.00	589.39	27.00	597.66	0.00	597.66	0.08	0.14	275.58	202.57
5876.000	25.00	0.00	0.00	589.39	27.00	597.74	0.00	597.74	0.02	0.13	379.69	206.02
5931.000	55.00	0.00	0.00	589.40	27.00	597.66	0.00	597.67	0.30	0.35	110.49	49.26
5931.000	55.00	0.00	0.00	589.40	27.00	597.74	0.00	597.75	0.29	0.35	114.20	50.48
6036.000	75.00	100000.00	100000.00	589.40	27.00	597.75	0.00	597.74	0.54	0.73	34.70	56.79
6036.000	75.00	100000.00	100000.00	589.40	27.00	597.83	0.00	597.84	0.50	0.73	91.55	56.11
6050.000	64.00	0.00	0.00	589.40	85.00	597.71	0.00	597.77	5.36	2.36	86.36	36.70
6050.000	64.00	0.00	0.00	589.40	85.00	597.81	0.00	597.87	5.38	2.38	78.86	36.63
7934.000	1884.00	0.00	0.00	580.36	85.00	597.83	0.00	597.85	0.12	0.35	823.90	246.34
7934.000	1884.00	0.00	0.00	580.36	85.00	597.94	0.00	597.94	0.11	0.34	837.05	254.55
8734.000	800.00	0.00	0.00	591.19	85.00	597.86	0.00	597.86	0.26	0.44	501.13	167.17
8734.000	800.00	0.00	0.00	591.19	85.00	597.95	0.00	597.96	0.24	0.43	521.25	173.79

PRINTED IN U.S.A.
FORM 1411-GD PRINTED BY ROTARY MANIFOLD FORMS

SECNO	XLCH	ELTRD	ELLC	ELMIN	Q	CWSEL	CRIWS	LS	TOPAS	VCH	AREA	.01K
9734.000	1000.00	0.00	0.00	592.34	85.00	597.99	0.00	597.99	0.54	0.56	379.66	115.44
9734.000	1000.00	0.00	0.00	592.34	85.00	597.99	0.00	597.99	0.49	0.54	392.45	121.10
10613.000	879.00	0.00	0.00	591.60	85.00	597.99	0.00	597.97	1.21	0.94	239.69	77.19
10613.000	879.00	0.00	0.00	591.60	85.00	598.05	0.00	598.05	1.07	0.89	251.25	82.33
10713.000	100.00	0.00	0.00	591.60	85.00	597.97	0.00	597.98	1.20	0.93	240.89	77.72
10713.000	100.00	0.00	0.00	591.60	85.00	598.06	0.00	598.06	1.05	0.88	252.32	82.62
10754.000	41.00	597.90	595.04	593.54	85.00	598.30	0.00	598.30	1.08	0.73	258.17	81.68
10754.000	41.00	597.90	595.04	593.54	85.00	598.30	0.00	598.31	1.07	0.73	259.01	82.05
10779.000	25.00	0.00	0.00	593.54	85.00	598.30	0.00	598.30	1.08	0.73	258.27	81.73
10779.000	25.00	0.00	0.00	593.54	85.00	598.31	0.00	598.31	1.24	0.78	239.12	76.40

PRINTED IN U.S.A.
FORM 1411-OB-PRINTED BY ROTARY MANIFOLD FORMS.

FLOODWAY DATA, COOKE & GLADDING RIVER,
PROFILE NO. 2

STATION	FLOODWAY WIDTH (FT)	FLOODWAY SECTION AREA	FLOODWAY MEAN VELOCITY	WATER SURFACE ELEVATION WITH FLOODWAY	WATER SURFACE ELEVATION WITHOUT FLOODWAY	DIFFERENCE
0.030	5.	20.	1.3	585.5	585.4	0.1
54.000	5.	17.	1.6	585.5	585.4	0.1
500.000	12.	37.	0.7	585.6	585.5	0.1
1300.000	9.	22.	1.2	585.8	585.7	0.1
1600.000	9.	13.	2.1	586.0	585.9	0.1
1700.000	5.	6.	4.4	586.5	586.5	0.0
1856.000	5.	3.	3.2	588.2	588.2	0.0
1861.000	20.	21	1.3	585.6	585.6	0.0
2264.000	67.	131.	0.2	535.3	535.5	0.0
2941.000	56.	89.	0.3	588.5	588.5	0.0
3041.000	5.	14.	1.9	588.5	588.5	0.0
3210.000	5.	9.	3.0	589.0	589.0	0.0
3285.000	58.	107.	0.3	539.2	589.2	0.0
3354.000	5.	19.	1.4	589.2	589.2	0.0
3543.000	6.	20.	1.3	589.3	589.3	0.0
3600.000	69.	127.	0.2	589.3	589.3	0.0
3742.000	5.	6.	4.5	589.2	589.2	0.0
3836.000	5.	9.	2.9	590.1	590.1	0.0
3894.000	11.	15.	1.8	590.3	590.3	0.0
4337.000	55.	86.	0.3	590.6	590.5	0.1
4427.000	6.	18.	1.5	590.6	590.5	0.1
4479.000	8.	23.	1.2	591.5	591.4	0.1
4504.000	55.	131.	0.2	591.5	591.4	0.1
4855.000	103.	219.	0.1	591.5	591.5	0.1
5353.000	12.	35.	0.5	591.6	591.5	0.1
5253.000	4.	20.	1.3	591.6	591.5	0.1
5299.000	8.	19.	1.4	591.6	591.5	0.1
5349.000	12.	39.	0.7	592.1	592.0	0.1
5676.000	50.	78.	0.3	592.2	592.1	0.1
5776.000	4.	16.	2.0	592.2	592.1	0.1
5851.000	6.	31.	0.9	597.7	597.6	0.1
5876.000	52.	380.	0.1	597.8	597.7	0.1
5951.000	40.	114.	0.4	597.8	597.7	0.1
6000.000	50.	92.	0.3	597.8	597.7	0.1
6050.000	20.	77.	1.1	597.8	597.7	0.1
7994.000	135.	637.	0.1	597.9	597.8	0.1
8434.000	136.	521.	0.2	598.0	597.9	0.1
9734.000	135.	392.	0.2	598.0	597.9	0.1
10439.000	133.	251.	0.3	598.1	598.0	0.1
10713.000	133.	232.	0.3	598.1	598.0	0.1
10756.000	132.	259.	0.3	598.3	598.3	0.3
10774.000	114.	239.	0.4	598.3	598.3	0.3

PRINTED IN U.S.A.
FORM 1411.08 PRINTED BY ROTARY MANIFOLD FORMS.

1) COUNTY: Wayne

2) STUDY NAME: City of Flat Rock

3) WATERCOURSE: Cook and Gladding Drain

4) DOCUMENT TYPE: 100 year

HUD200907
9/13/79

```
**************************************************
   HEC2 RELEASE DATED NOV 76 UPDATED FEB 1977
   ERROR CORR -  01
   MODIFICATION -  50,51,52
**************************************************

C
T1CITY OF FLAT ROCK FIS HUD 2000-07 COOKE & GLADDING FROM SOUTH TO HWY.STEP RD.
T2 @ 10YR=50,50YR=75,100YR=85,500YR=120,,SEL=MEAN ANNUAL FLOOD OF HURON
T3       COOKE & GLADDING RIVER, FLAT ROCK

J1  ICHECK     INQ       NINV      IDIR      STRT      METRIC    HVINS     Q          WSEL      FQ
          0.        4.        3.        3.  0.000030     0.00      0.0       0.     565.400     0.000

J2  NPROF      IPLOT     PRFVS     XSECV     XSECH     FN        ALLOC     IDW        CHMIN     ITRACE
      1.000     0.000    -1.000     0.000     0.000     0.000     0.000     0.000     0.000    15.000

J3  VARIABLE CODES FOR SUMMARY PRINTOUT
    110.000   150.000   200.000     0.000     0.000     0.000     0.000     0.000     0.000     0.000

QT      5.000    21.000    21.000    27.000    27.000    37.000     0.000     0.000     0.000     0.000
NC      0.360     0.060     0.035     0.300     0.500     0.060     0.000     0.000     0.000     0.000
ET      0.000     0.000     0.000     0.000     5.100     0.000     0.000     0.000     1.000   151.000

D/S FACE OF HURON RIVER DRIVE.

X1      0.300     5.000    75.000    77.500     0.030     5.000     0.000     0.000     1.000     5.000
X3     30.300     0.000     0.000     0.000     7.000     0.000     0.000   546.000   546.000     0.000
CH    597.000     5.000   598.300     0.000   545.000    75.000   581.000    75.000   581.000    75.000
GR    588.000    79.500   538.000   150.000   597.000   151.000     0.000     0.000     0.000     0.000
SI      0.000     1.500     3.000     0.000     3.530     6.000    15.900     0.000   581.100   581.000
MC      0.060     0.080     0.035     0.000     0.000     0.000     0.000     0.000     0.000     0.000

U/S FACE HURON RIVER DRIVE

X1     54.000    14.700    80.000    92.500    54.000    54.000    54.000     0.300     0.000     0.300
X2      0.000     0.005     1.000   585.000   538.000     0.300     0.050     0.300     0.000     0.000
X3     10.000     0.000     0.030     0.000     0.300     0.300     0.000   588.300   588.000     0.300
CH     12.000     0.300   597.000     0.300     1.300   538.000     0.030    25.300   598.000     0.300
GR     56.000   597.000     0.000    58.300   597.300     0.300    67.000   568.000     0.000    54.000
OT    300.000   533.350    69.000   538.300   585.600    91.500   568.000   585.600    92.500   583.000
BT    583.350   175.300   308.000     0.000   176.000   597.000     0.000     0.000     0.000     0.000
FQ    597.000     0.000   308.000     1.000   585.700    35.000   597.000    36.000   597.000    66.000
ES    595.300    67.300   585.000    51.300   213.330    68.000   581.100    67.000   581.150    71.500
CO    583.350    92.500   584.000   100.000   597.000   175.000   597.000   175.000     0.000     0.000
EF      0.000     0.100     0.000     0.500     1.000     2.000     2.000     2.000     2.000     2.000

VALLEY SECTION BASED ON FIELD NOTE SECTION 10+36

X1    540.000    21.000   297.000   555.000   505.000   505.000   500.000     0.000     0.000     0.000
CH    597.000     0.000   590.000   543.100   505.000   111.000   596.000   110.100   594.000   585.900
GR    589.000                       0.000   597.000   200.000   586.140   290.000   542.260   297.000
GR    597.500   301.000   538.700   300.000   597.000   111.000   597.300   576.000   517.565   180.000
GR    595.500   552.100   535.500   300.000   597.000   376.000   538.700   290.000   594.      598.100
```

PRINTED IN U.S.A.
FORM 141-68-PRINTED BY ROTARY MANIFOLD FORMS.

GR	596.000	41		.000	0.000	0.000	0.000	0.000	0.000	0.000
NC	0.000	0.000	0.000	0.100	0.300	0.000	0.000	0.000	0.000	0.000

VALLEY SECTION BASED ON FIELD BOOK SECTION 9434

XT	1300.000	17.000	276.300	284.000	1000.000	1000.000	1000.300	0.000	0.000	0.000
GR	600.000	0.000	600.300	50.000	608.000	50.100	608.000	79.900	599.940	0.000
GR	593.490	180.000	585.810	273.000	583.660	276.000	593.010	280.000	583.660	284.000
GR	585.460	287.000	586.310	365.000	588.510	401.000	596.500	401.100	596.300	431.000
GR	588.600	431.100	590.000	990.000	0.000	0.000	0.000	0.000	0.000	0.000
NC	0.080	0.080	0.050	0.300	0.500	0.000	0.000	0.000	0.000	0.000
ET	0.800	0.000	0.000	0.200	0.100	0.000	0.300	0.000	1.000	600.000

XSECTION D/S GIBRALTAR RD.BASED ON FIELD BOOK " QUAD MAP

XT	1600.000	17.000	297.500	302.100	300.000	300.000	300.000	0.000	0.000	0.000
GR	604.300	0.000	396.000	0.100	555.430	80.000	603.400	80.100	603.400	310.000
GR	595.000	110.100	593.000	289.500	584.500	297.500	583.290	300.000	584.500	302.100
GR	589.500	313.500	590.000	400.000	590.500	450.000	598.500	450.100	598.500	480.000
GR	592.000	480.100	590.000	600.000	0.000	0.000	0.000	0.000	0.000	0.000
ET	0.000	0.000	0.000	0.000	0.100	0.000	0.000	0.000	1.000	600.000

D/S FACE OF GIBRALTAR RD. REPEATED SECT 1600

X1	1700.000	0.000	0.000	0.000	100.000	100.000	100.000	0.000	0.000	0.000
X3	10.000	535.140	0.000	0.000	0.300	0.000	0.000	590.000	590.000	0.000
SO	0.000	2.980	3.000	0.000	3.590	0.000	9.540	0.000	596.240	585.140
NC	0.000	0.000	0.040	0.000	0.300	0.000	0.000	0.000	0.000	0.000

U/S FACE OF GIBRALTAR RD.

X1	1086.000	10.000	295.000	299.600	134.200	134.000	134.000	0.000	0.000	0.000
X2	0.000	0.000	0.000	561.300	552.200	0.000	0.000	0.000	0.000	0.000
X3	10.000	586.240	0.000	0.000	0.000	0.000	0.000	593.000	593.000	0.000
BT	16.000	0.000	596.000	0.000	125.000	595.000	0.000	264.000	593.300	0.000
BT	295.000	592.800	586.900	295.300	592.800	567.900	295.000	592.000	588.500	296.500
BT	592.000	560.700	297.300	592.300	582.900	295.100	592.300	588.700	295.000	592.300
BT	588.900	299.400	592.400	587.300	299.600	592.800	586.900	323.000	592.000	0.000
BT	450.000	591.200	0.000	450.700	588.450	0.000	450.000	586.000	0.000	0.000
GR	596.000	0.000	595.000	135.000	593.300	262.000	586.900	295.000	585.700	295.300
GR	585.000	295.800	584.700	296.500	584.390	297.300	584.700	298.100	585.000	298.800
GR	585.700	299.400	586.900	299.600	589.900	323.000	590.000	450.000	592.000	600.000
GR	594.000	650.300	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
NC	0.000	0.300	0.050	0.300	0.000	0.000	0.000	0.000	0.000	0.000
ET	0.000	0.000	0.000	0.300	1.400	0.000	0.000	0.000	1.000	0.000

XSECT.U/S OF GIBRALTAR RD. REPEATED SECT.

X1	1561.300	0.000	0.000	0.000	25.000	25.000	25.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	299.000	0.000	325.000	0.000	0.000	0.000	0.000
NC	0.000	0.000	0.000	0.100	0.300	0.000	0.000	0.000	0.000	0.000
ET	0.000	0.000	0.000	0.000	1.410	0.000	0.000	0.000	0.000	0.000

VALLEY SECTION BASED ON FIELD BOOK SECTION 8450

	2264.000	11.000	295.300	307.000	425.000	425.300	425.000	0.000	0.000	0.000
GR	598.970	0.000	594.620	100.000	590.890	200.000	586.510	299.000	593.690	299.000
GR	585.510	300.000	586.400	307.000	586.600	312.000	588.500	451.000	585.500	500.000

PRINTED IN U.S.A.

FORM 1411-OD PRINTED BY ROTARY MANIFOLD FORMS.

GR	596.500	600.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000

100 FEET D/S OF 54" CULVERT

XT	2941.000	15.000	214.000	224.000	657.000	657.000	657.000	0.000	0.000	0.000
XB	0.000	0.000	0.000	191.000	0.000	247.000	0.000	0.000	0.000	0.000
GR	900.000	0.000	595.000	90.000	590.000	160.000	587.200	210.000	585.900	214.000
GR	585.500	217.250	585.500	220.750	585.900	224.000	587.000	226.000	587.500	350.000
GR	595.000	350.100	595.000	380.000	587.600	380.100	590.000	400.000	592.000	500.000
NC	0.300	0.000	0.300	0.300	0.500	0.000	0.000	0.000	0.000	0.000
ET	0.000	0.000	0.000	0.000	9.100	0.000	0.000	0.000	1.000	382.000

D/S FACE OF 54" CULVERT

X1	3041.000	12.000	214.000	218.500	100.000	100.000	100.000	0.000	0.000	0.000
X3	10.000	585.300	0.000	0.000	0.000	0.000	0.010	589.500	589.500	0.000
GR	600.000	0.000	600.000	160.300	590.000	165.000	587.200	210.000	585.590	214.000
GR	563.300	215.000	583.300	217.500	585.550	218.500	587.000	228.000	587.500	350.000
GR	590.000	351.000	595.000	352.000	0.000	0.000	0.000	0.000	0.000	0.000
SB	0.000	3.010	3.000	0.000	3.160	0.000	7.500	0.000	586.700	585.500

U/S END 54) CULVERT REPEATED SECT

X1	3210.000	12.000	214.000	218.500	169.000	169.000	169.000	0.000	0.000	0.000
X2	0.000	0.000	1.000	589.200	590.000	0.000	0.000	0.000	0.000	0.000
X3	10.000	586.700	0.000	0.000	0.000	0.000	0.000	591.000	591.000	0.000
GT	9.000	0.000	600.000	0.000	160.000	600.000	0.000	165.000	590.000	0.000
BT	214.000	590.000	586.950	215.000	590.000	589.200	217.500	590.000	589.200	210.500
BT	590.000	586.950	351.000	590.000	0.000	352.000	595.000	0.000	0.000	0.000
GR	600.000	0.000	600.000	160.000	590.000	165.000	587.200	210.000	586.950	214.000
GR	584.700	215.000	584.700	217.500	586.650	218.500	587.000	228.000	587.500	350.000
GL	590.000	351.000	595.000	352.000	0.000	0.000	0.000	0.000	0.000	0.000
ET	0.000	0.000	0.000	0.000	9.100	0.000	0.000	0.000	0.000	0.000

XSECTION BETWEEN 54)CULVERT " SHEEKS RD CULVERT

X1	3239.000	0.000	0.000	0.000	25.000	25.000	25.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	191.000	0.000	247.000	0.000	0.000	0.000	0.000
ET	0.000	0.000	0.000	0.000	9.100	0.000	0.000	0.000	194.000	459.100

D/S END SHEEKS RD. CULVERT

X1	3384.000	11.000	257.000	263.300	149.000	149.000	149.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	217.000	0.000	264.000	0.000	589.500	589.500	0.000
GR	600.000	232.000	600.000	232.000	590.000	233.000	588.600	255.000	586.100	257.000
GR	586.100	259.000	586.100	261.500	586.100	263.300	588.600	265.000	589.300	405.000
GR	600.000	405.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
SB	0.000	3.320	3.000	0.000	3.225	0.000	10.000	1.000	586.100	585.700

U/S FACE OF SHEEKS RD CULVERT (78"X 60" ELLIPTICAL CONCRETE)

X1	3543.000	0.000	0.000	0.000	164.000	164.000	164.000	0.000	0.000	0.000
X2	0.000	0.000	1.000	590.600	590.000	0.000	0.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	217.000	0.000	265.000	0.000	590.000	590.000	0.000
GT	12.000	232.000	600.000	0.000	232.000	600.000	0.000	255.000	590.000	0.000
BT	255.000	590.000	586.950	257.000	590.000	589.200	257.000	590.000	589.200	259.000
BT	590.000	586.600	261.500	590.000	0.000	263.300	590.000	587.600	263.300	591.000
GR	586.100	405.000	586.100	0.000	0.000	0.000	0.000	0.000	0.000	0.000

PRINTED IN U.S.A.
FORM 1411-GB PRINTED BY ROTARY MANIFOLD FORMS

ET	0.000	0.000	0.000	0.000	1.400	0.000	0.000	0.000	0.000	0.000

XSECT. U/S OF SHEEKS RD.AND D/S OF SENECA RD.

X1	3600.000	9.000	196.000	204.000	52.000	52.000	52.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	145.000	0.000	255.000	0.000	0.000	0.000	0.000
GR	600.000	0.000	595.000	100.000	589.500	135.000	586.500	196.000	586.400	200.000
GR	586.500	204.000	587.500	210.000	588.300	334.000	600.000	334.000	0.000	0.000
ET	0.000	0.000	0.000	0.000	9.100	0.000	0.000	0.500	1.000	310.000

D/S END SENECA RD. CULVERT

X1	3792.000	10.000	223.000	227.500	192.000	192.000	192.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	591.300	590.100	0.000
GR	600.000	0.000	595.000	100.000	591.000	221.000	588.750	223.000	587.700	224.000
GR	587.700	227.000	588.750	227.500	590.000	229.000	590.500	310.000	600.000	310.000
BR	0.000	1.530	3.000	0.000	2.710	0.000	12.200	0.000	587.705	587.700

U/S FACE OF SENECA RD. CULVERT

X1	3833.000	9.000	0.000	0.000	41.000	41.000	41.000	0.000	0.000	0.000
X2	0.000	0.000	1.000	5.500	590.500	0.000	0.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	591.000	590.700	0.000
BT	0.000	0.000	600.000	0.000	100.000	595.000	0.000	223.000	591.800	588.750
BT	224.000	591.800	591.000	226.500	591.800	591.000	227.500	591.800	588.750	310.000
BT	590.500	0.000	310.000	600.000	0.000	0.000	0.000	0.000	0.000	0.000
ET	0.000	0.000	0.000	0.000	1.400	0.000	0.000	0.000	0.000	0.000

XSECT. U/S OF SENECA RD REPEATED SECT. 3833.

X1	3883.000	0.000	0.000	0.000	30.000	52.000	98.000	0.000	0.000	0.000

XSECT. D/S OF COOKE RD

X1	4337.000	11.000	295.500	306.500	350.000	300.000	454.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	260.000	0.000	323.000	0.000	0.000	0.000	0.000
GR	600.000	0.000	595.000	130.000	590.000	200.000	589.200	290.000	587.350	293.000
GR	587.350	293.000	587.350	295.000	587.350	305.000	590.000	296.000	587.350	296.000
BT	587.350	293.000	587.350	296.500	587.700	305.000	590.000	300.000	590.000	416.000
BT	600.000	416.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
ET	0.000	1.930	3.000	0.000	3.930	0.000	4.910	0.000	587.350	587.350

U/S FACE OF COOKE RD. CULVERT

X1	4434.000	0.000	0.000	0.000	47.000	47.000	47.000	0.000	0.000	0.000
X2	0.000	0.000	1.000	589.600	590.700	0.000	0.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	592.000	590.800	0.000
BT	0.000	0.000	600.000	0.000	130.000	590.000	0.000	296.000	587.350	0.000

PRINTED IN U.S.A.
FORM 1411-05-PRINTED BY ROTARY MANIFOLD FORMS.

BT	293.000	591.700	587.350	293.500	591.700	588.600	295.000	591.700	588.600	295.500
BT	591.700	587.350	296.000	591.700	587.350	296.500	591.700	588.600	298.000	591.700
BT	588.600	298.500	591.700	587.350	350.000	591.700	0.000	416.000	592.700	0.000
BT	416.000	600.000	0.000	416.000	600.000	0.000	416.000	600.000	0.000	0.000
ET	0.000	0.000	0.000	0.000	1.450	0.000	0.000	0.000	0.000	0.000

XSECTION U/S COOKE RD

X1	4504.000	0.000	0.000	0.000	25.000	25.000	25.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	268.000	0.000	323.000	0.000	0.000	0.000	0.000
NC	0.100	0.100	0.060	0.100	0.300	0.000	0.000	0.000	0.000	0.000

VALLEY SECTION BASED ON FIELD BOOK SECT.5681

X1	4853.000	19.000	491.000	510.000	349.000	349.000	349.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	438.000	0.000	563.000	0.000	0.000	0.000	0.000
GS	600.000	0.000	595.650	200.000	595.990	300.000	594.060	370.000	590.060	341.000
ST	590.110	405.000	589.410	491.000	587.960	494.000	587.710	500.000	588.060	506.000
GR	589.850	510.000	589.300	536.000	596.710	553.000	594.420	591.000	594.370	600.000
GR	593.820	700.000	593.460	750.000	594.150	800.000	595.000	1050.000	0.000	0.000
NC	0.100	0.100	0.600	0.300	0.500	0.000	0.500	0.000	0.000	0.000

XSECTION S/S OF TELEGRAPH RD.

X1	5053.000	0.000	594.500	605.500	200.000	200.000	200.000	0.000	0.000	0.000
GS	600.000	0.000	595.000	150.000	594.000	584.500	586.370	594.300	586.370	605.500
GR	594.060	615.500	595.000	775.000	600.040	1200.000	0.000	0.000	0.000	0.000
ET	0.000	0.000	0.000	0.000	9.150	0.000	0.000	0.000	1.000	1200.000
NC	0.000	0.000	0.050	0.000	0.000	0.000	0.000	0.000	0.000	0.000

S/S FACE TELEGRAPH RD.

X1	5295.000	0.000	595.000	615.000	200.000	200.000	200.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	592.000	592.000	0.000
GS	600.000	0.000	595.000	50.000	594.500	484.500	586.400	595.000	586.400	499.000
GR	594.400	590.000	595.000	700.000	600.000	1200.000	0.000	0.000	0.000	0.000
SP	0.000	3.790	3.000	0.000	3.030	0.000	10.900	0.000	587.300	586.700

U/S FACE OF TELEGRAPH RD.

X1	5299.000	12.000	495.000	499.000	46.000	46.000	46.000	0.000	0.000	0.000
X3	0.000	0.000	1.000	570.300	594.463	0.000	0.000	0.000	0.000	0.000
GS	10.000	0.000	0.000	0.000	3.000	0.000	0.000	594.400	594.400	0.000
SR	1.000	594.400	445.700	0.000	0.000	0.000	0.000	0.000	0.000	0.000
DT	11.000	0.000	600.000	0.000	485.000	600.000	587.300	485.000	594.400	587.300
BT	495.000	594.400	588.500	495.500	594.400	590.000	497.000	594.400	590.300	498.500
BT	594.400	590.000	499.000	594.400	508.500	499.000	594.400	587.300	510.000	594.400
ET	0.000	590.000	600.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
TP	600.000	0.000	600.000	50.000	600.000	485.000	588.300	595.000	587.300	499.000
SR	587.300	499.500	587.300	587.000	587.300	496.500	587.200	589.500	588.500	599.500
SR	594.400	590.000	600.000	510.000	0.000	0.000	0.000	0.000	0.000	0.000
ET	0.000	0.000	0.000	0.000	1.400	0.000	0.000	0.000	0.000	0.000
NC	0.000	0.000	0.060	0.000	0.000	0.000	0.000	0.000	0.000	0.000

XSECT. U/S OF TELEGRAPH RD

X1	5349.000	4.000	0.000	0.000	50.000	99.000	99.000	0.000	0.000	0.000
ET	0.000	7.100	0.000	9.100	0.000	0.000	0.000	0.000	575.000	413.000

PRINTED IN U.S.A.
FORM 1411.00 PRINTED BY ROTARY MANIFOLD FORMS.

XSECT. D/S OF R.R. TRACKS

X1	5676.000	10.000	395.000	405.000	327.000	327.000	327.000	0.000	0.000	0.000
GR	600.000	0.000	595.000	250.000	590.000	320.000	595.000	385.000	587.400	395.000
GR	587.280	400.000	587.400	405.000	595.000	415.000	595.000	525.000	600.000	600.000
NC	0.120	0.120	0.060	0.300	0.500	0.000	0.000	0.000	0.000	0.000
ET	0.000	0.000	0.000	0.000	9.100	0.000	0.000	0.000	1.000	486.000

D/S FACE OF R.R. CULVERT

X1	5776.000	11.000	399.000	402.500	100.000	100.000	100.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	597.000	594.000	0.000
GR	600.000	0.000	595.000	250.000	590.000	320.000	590.000	385.000	588.260	395.000
GR	588.250	399.000	588.260	402.500	591.000	405.000	594.000	401.000	595.000	486.000
GR	600.000	486.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
SS	0.000	2.650	3.000	0.000	2.760	0.000	2.400	0.000	589.000	588.260

U/S FACE OF 42" RAILROAD CULVERT

X1	5831.000	29.000	699.000	702.500	75.000	75.000	75.000	0.000	0.000	0.000
X2	0.000	0.500	1.000	393.750	399.400	0.000	0.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	601.100	600.000	0.000
BT	16.000	0.000	604.000	0.000	200.000	603.000	0.000	300.000	602.600	0.000
BT	400.000	602.200	0.000	500.000	601.900	0.000	600.000	601.500	0.000	699.000
BT	601.100	589.000	699.250	601.100	589.250	700.750	601.100	590.750	702.250	601.100
BT	590.250	702.500	601.100	589.000	785.000	599.400	0.000	786.000	604.000	0.000
BT	876.000	604.000	0.000	876.000	604.000	0.000	876.000	604.000	0.000	0.000
GR	604.000	0.000	600.000	0.000	595.000	75.000	594.200	200.000	595.500	300.000
GR	592.900	400.000	592.200	500.000	591.600	600.000	591.000	685.000	589.000	695.000
GR	589.000	699.000	589.000	699.250	589.000	700.750	589.000	702.250	589.000	702.500
GR	591.000	705.000	595.000	795.000	595.000	785.000	606.000	786.000	604.000	876.000
GR	604.000	876.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
ET	0.000	0.700	0.000	0.000	1.400	0.000	0.000	0.000	574.000	720.000

XSECT. U/S OF R.R. TRACKS " L/S OF ARSENAL

X1	1076.000	9.000	595.000	705.000	25.000	35.000	25.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
GR	600.000	0.000	595.000	100.000	591.310	630.000	589.390	695.000	589.392	705.000
GR	591.010	715.000	595.000	800.000	600.000	950.000	950.000	1200.000	0.000	0.000
ET	0.000	0.000	0.000	0.000	9.100	0.000	0.000	0.000	1.000	1100.000

D/S FACE ARSENAL CULVERTS

X1	5931.000	13.000	799.000	802.000	55.000	55.000	55.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	750.000	0.000	840.000	0.000	593.000	593.400	0.000
GR	604.000	772.000	600.000	773.630	595.120	790.000	595.500	791.000	593.500	797.000
GR	589.430	799.000	589.400	802.000	591.000	801.000	596.500	810.000	597.100	811.000
GR	599.000	869.000	604.000	870.130	604.000	1100.000	0.000	0.000	0.000	0.000
SS	0.000	3.700	3.000	0.000	2.400	0.000	3.400	0.000	0.000	0.000

U/S FACE ARSENAL CULVERT

X1	6006.000	14.000	799.000	802.000	75.000	75.000	75.000	0.000	0.000	0.000
X2	0.000	0.000	1.000	593.000	399.100	0.000	0.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	596.400	596.500	0.000
GR	596.000	596.000	596.000	597.750	597.000	599.400	0.000	0.000	0.000	0.000

PRINTED IN U.S.A.
FORM 1411-08-PRINTED BY ROTARY MANIFOLD FORMS.

BT	13.000	772.000	604.000	0.000	772.000	604.000	0.000	773.000	600.000	0.000
BT	790.000	596.100	0.000	799.000	596.100	509.400	799.250	596.200	590.600	800.500
BT	596.300	590.900	801.750	596.400	590.600	802.000	596.500	589.400	805.000	596.500
BT	0.000	810.000	597.100	0.000	869.000	599.000	0.000	870.000	604.000	0.000
GR	604.000	772.000	600.000	773.000	600.000	772.000	596.100	790.000	595.500	795.000
GR	589.400	799.000	589.400	799.250	589.400	800.500	309.400	301.750	589.400	002.000
GR	596.500	805.000	597.100	810.000	599.000	869.000	604.000	870.000	0.000	0.000
QT	5.000	50.000	75.000	85.000	85.000	120.000	0.000	0.000	0.000	0.000
ET	0.000	0.000	0.000	0.000	1.400	0.000	0.000	0.000	0.000	0.000

X SECTION U/S OF ARSENAL.

X1	6050.000	0.000	0.000	0.000	44.000	44.000	44.000	0.000	0.000	0.000
NC	0.120	0.120	0.060	0.100	0.300	0.000	0.000	0.000	0.000	0.000

VALLEY SECTION BASED ON FIELD BOOK SECT. 2000.

X1	7934.000	12.000	646.000	654.000	1884.000	1884.000	1884.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	583.000	0.000	718.000	0.000	0.000	0.000	0.000
X4	1.000	605.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
GR	300.000	0.000	595.160	370.000	594.560	650.000	594.560	350.000	595.260	641.000
GR	589.760	646.000	590.860	650.000	589.650	654.000	595.150	661.000	594.850	750.000
GR	590.423	851.000	601.020	750.000	0.000	0.000	0.000	0.000	0.000	0.000

VALLEY SECTION BASED ON FIELD BOOK SECT. 2000.

X1	8734.000	13.000	647.000	655.000	800.000	800.000	800.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	582.000	0.000	518.000	0.000	0.000	0.000	0.000
X4	2.000	605.000	0.000	605.000	1001.000	0.000	0.000	0.000	0.000	0.000
GR	600.000	0.000	595.290	150.000	594.990	250.000	595.090	350.000	595.790	440.000
GR	591.490	447.000	591.190	450.000	591.290	453.000	594.190	458.000	595.490	550.000
GR	596.290	650.000	597.590	750.000	600.000	1000.000	0.000	0.000	0.000	0.000

VALLEY SECTION BASED ON FIELD BOOK SECT. 1050.

X1	9734.000	13.000	345.000	355.000	1000.000	1000.000	1030.300	0.000	0.000	0.000
X3	0.000	0.000	0.000	295.000	0.000	420.000	0.500	0.000	0.000	0.000
X4	2.000	605.000	0.000	605.000	701.000	0.000	0.500	0.000	0.000	0.000
GR	600.000	0.000	590.940	50.000	595.190	150.000	595.940	290.000	595.940	341.000
GR	592.640	345.000	592.440	350.000	592.540	355.000	595.340	358.000	595.470	450.000
GR	595.920	550.000	596.920	650.000	600.000	700.000	0.000	0.000	0.000	0.000
NC	0.080	0.080	0.060	0.300	0.500	0.000	0.000	0.000	0.000	0.000

X SECT. D/S OF INKSTER RD

X1	10613.000	16.000	490.000	501.000	879.000	879.000	879.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	435.000	0.000	566.000	0.000	0.000	0.000	0.000
GR	604.000	0.000	600.900	1.000	599.000	130.000	599.830	200.000	597.230	300.000
GR	595.400	492.000	591.600	494.000	591.600	551.000	595.630	559.000	597.310	650.000
GR	597.500	930.000	596.300	1000.000	599.000	1130.000	599.550	1200.000	600.000	1300.000
GR	604.000	1301.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
QT	0.000	0.000	0.000	0.000	9.105	0.000	0.000	0.000	1.000	1301.000

D/S FACE OF INKSTER RD CULVERT

X1	10713.000	0.000	0.000	0.000	100.000	100.000	100.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	435.000	0.000	156.000	0.000	0.000	0.000	0.000
SH	0.000	2.000	3.000	0.000	2.400	0.000	0.000	0.000	555.540	0.000

PRINTED IN U.S.A.
FORM 1411-08 PRINTED BY ROTARY MANIFOLD FORMS

U/S FACE OF INKSTER RD. CULVERT

X1	10754.000	15.000	498.000	501.000	41.000	41.000	41.000	0.000	0.000	0.000	
X2	0.000	0.000	1.000	595.040	597.900	0.000	0.000	0.000	0.300	0.500	
X3	10.000	0.000	0.000	0.000	0.000	0.300	0.000	597.900	597.700	0.000	
BT	13.000	433.000	604.000	0.000	433.000	604.300	0.000	433.000	604.000	0.000	
BT	433.000	604.000	0.000	433.000	604.000	0.000	434.000	597.900	0.000	498.000	
BT	597.900	593.540	498.250	597.900	594.790	499.500	597.900	593.040	500.750	597.900	
BT	594.790	501.000	597.900	593.540	566.000	596.200	0.300	567.000	604.000	0.000	
GR	604.000	433.000	604.000	433.000	604.000	433.000	604.900	433.000	604.000	433.000	
GR	596.700	434.000	596.200	430.000	593.540	496.000	593.540	496.250	593.540	499.500	
GR	593.540	500.750	593.540	501.000	596.700	510.000	596.900	566.000	604.000	567.000	
ET	0.000	0.000	0.000	0.000	1.400	0.000	0.000	0.000	0.000	0.000	

XSECT U/S OF INKSTER RD.

X1	10779.000	0.000	0.000	0.300	25.000	25.000	25.000	0.000	0.000	0.000	
EJ	0.000	0.000	0.060	0.000	0.000	0.000	0.000	0.000	0.000	0.000	

PRINTED IN U.S.A.
FORM 1411-GB-PRINTED BY ROTARY MANIFOLD FORMS.

*PROF 1

CCHV= 0.300 CEHV= 0.500

*SECNO ****									
SECNO	DEPTH	QWSEL	CRIWS	WSELK	EG	HV	HL	QLOSS	BANK ELEV
P	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TOA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IN2	ICONT	CORAR	TOPWID	ENDST
3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA=				586.00 ELREA=		586.00			
D/S FACE OF HURON RIVER DRIVE.									
0.30	5.40	585.40	0.00	585.40	585.43	0.05	0.00	0.00	568.00
27.	0.	27.	0.	0.	20.	0.	0.	0.	580.00
0.00	0.00	1.36	0.00	0.000	0.035	0.000	0.000	581.00	75.00
0.000607	0.	0.	0.	0	0	0	0.00	4.50	79.50

FLOW DISTRIBUTION FOR SECNO= 0.00 CWSEL= 585.40

STA= 75. 80.
PER Q= 100.0
AREA= 19.8
VEL= 1.4

SPECIAL BRIDGE

SB KK	XKOR	COFA	XOLEN	BHC	BYP	BAREA	SS	ELCHU	ELCHD
0.00	1.00	0.00	0.00	0.00	0.00	0.00	0.00	581.10	581.00

*SECNO 54.000

0.0/0.LOW FLOW BY NORMAL BRIDGE

ESPRS= 0.000	*SLOS= 585.387	ELC= 585.000	ECUSE= 585.400	ELTOP= 586.000			

S3/D NORMAL BRIDGE,PROJ IS LOW ELTOP= 587.27000 SLLC= 585.00

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 568.00 ELREA= 568.00

U/S FACE HURON RIVER DRIVE

54.00	4.33	585.43	0.30	0.00	585.47	0.04	0.14	0.01	583.35
27.	0.	27.	0.	0.	16.	0.	0.	0.	583.35
0.01	1.00	1.33	0.30	0.063	0.15	1.000	0.003	581.10	96.00
0.020743	54.	54.	54.	2	1	0	-10.45	1.55	92.50

FLOW DISTRIBUTION FOR SECNO= 54.00 CWSEL= 585.43

STA= 69. 93.
PER Q= 100.0
AREA= 14.2
VEL= 1.4

W.ELEV 580.100

* The 27cfs occurs when Huron @ 100 yr. flood stage 590.83

Huron River 100 yr stage ≈ 590.4

Reasonable

VALLEY SECTION BASED ON FIELD BOOK SECTION 10434

300.00	4.03	585.54	0.00	0.00	585.55	0.01	0.07	0.01	582.26
27.	3.	22.	2.	9.	22.	10.	6.	6.	582.36
0.11	0.32	1.00	0.24	0.060	0.035	0.080	0.035	581.51	291.54
0.000105	300.	300.	300.	2	0	0	0.00	17.55	309.09

FLOW DISTRIBUTION FOR SECNO= 300.00 CHSEL= 585.54

STA=	292.	297.	303.	309.
PER Q=	10.5	80.9	8.6	
AREA=	8.9	21.7	9.7	
VEL=	0.3	1.0	0.2	

CCHV= 0.100 CEHV= 0.300
*SECNO 1300.000

VALLEY SECTION BASED ON FIELD BOOK SECTION 9434

1300.00	2.68	585.69	0.00	0.00	585.72	0.02	0.17	0.00	583.66
27.	1.	25.	1.	3.	19.	6.	1.	1.	585.66
0.33	0.58	1.30	0.22	0.060	0.035	0.080	0.034	583.01	273.16
0.000505	1300.	1000.	1000.	2	0	0	0.00	35.37	308.53

FLOW DISTRIBUTION FOR SECNO= 1300.00 CHSEL= 585.69

STA=	273.	276.	284.	287.	309.
PER Q=	4.1	91.2	4.0	0.7	
AREA=	2.9	18.9	3.6	2.5	
VEL=	0.4	1.3	0.3	0.1	

CCHV= 0.300 CEHV= 0.500
*SECNO 1600.000

SEC ID									
	BCHIN	C.BCH	CHL.S	US LS	LC	RV	LC	ULOSS	BANK ELEV
D	ALOB	QCH	QROB	ALOB	ACH	AROB	VOL	T.I	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XSL	XBCH	XNR	LCH	LLOSS	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IN2	XCOLT	CONAR	TOPWID	ENDST

X-SECTION D/S GIBRALTAR RD.BASED ON FIELD BOOK " QUAD MAP

1600.00	2.59	585.88	0.00	0.00	585.98	0.10	0.22	0.04	564.55
27.	1.	25.	2.	1.	7.	2.	1.	1.	587.50
0.37	0.70	2.66	0.25	0.052	0.050	0.080	0.038	563.29	296.20
0.003857	300.	300.	300.	2	0	0	0.00	9.05	305.24

FLOW DISTRIBUTION FOR SECNO= 1600.00 CHSEL= 585.88

STA=	290.	298.	302.	305.
PER Q=	3.3	93.2	3.4	
AREA=	0.9	9.1	2.2	
VEL=	0.4	2.7	0.4	

*SECNO 1700.000

OVERBANK AREA ASSUMED NON-EFFECTIVE,SLEA= 550.00 ELREA= 590.00

D/S EACH OF GIBRALTAR RD. REPEATED SECT 1600

PRINTED IN U.S.A.
FORM 1411-08 PRINTED BY ROTARY MANIFOLD FORMS.

1700.00	1.34	586.48	0.00	0.00	586.78	0.30	0.70	0.10	585.14
27.	0.	27.	0.	0.	6.	0.	1.	1.	585.14
0.37	0.00	4.38	0.00	0.000	0.050	0.080	0.038	585.14	297.50
0.016205	100.	100.	100.	3	0	0	0.03	4.60	302.10

FLOW DISTRIBUTION FOR SECNO= 1700.00 CHSEL= 586.48

STA= 293. 307.

PER Q= 100.0
AREA= 6.2
VEL= 4.4

54" RCP 136 L.F.

SPECIAL BRIDGE

CD	XK	XBJO	CCFO	ADLEN	BHC	BLP	DAREA	CS	ELCHO	ELCHD
	0.30	2.90	3.00	0.00	1.50	5.00	9.54	0.00	585.24	585.14

*SECNO 1836.000

6070,LOW FLOW BY NORMAL BRIDGE

SGPRS= 0.000 EGLLC= 587.394 ELLC= 538.900 PCUSE= 306.679 ELTRD= 592.500

3370 NORMAL BRIDGE,NPD= 16 MIN ELTRD= 592.80 MAX ELLC= 588.90

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 593.40 ELREA= 593.40

U/S FACE OF GIBRALTAR RD.

1836.00	1.95	586.19	0.00	3.00	584.35	0.16	1.55	0.04	586.90
27.	0.	27.	3.	0.	4.	0.	1.	1.	586.90
0.39	0.00	3.20	0.00	0.000	0.045	0.080	1.055	585.24	293.00
0.008253	136.	136.	136.	3	0	0	-6.14	4.60	299.60

FLOW DISTRIBUTION FOR SECNO= 1836.00 CHSEL= 586.19

STA= 293. 308.

PER Q= 100.0
AREA= 9.6
VEL= 3.2

*SECNO 1361.000

3470 ENCROACHMENT STATIONS= 270.0 325.0 TYPE= 1 TARGET= 55.000

XHSECT.U/S OF GIBRALTAR RD. REPEATED SECT.

1361.00	2.19	586.43	0.00	7.00	584.47	0.34	2.06	1.03	586.90
27.	2.	19.	6.	2.	10.	4.	1.	1.	586.90
0.39	0.64	1.95	0.60	0.000	0.050	0.080	0.059	586.24	291.90
0.001963	25.	25.	25.	2	0	1	1.00	10.62	311.51

FLOW DISTRIBUTION FOR SECNO= 1361.00 CHSEL= 586.43

STA= 292. 295. 330. 312.

PER Q= 15.8 71.3 29.1

AREA= 1.2 9.2 2.6

```
     VEL=      0.6       1.9       0.7

   CCHV=   0.100 CEHV=   0.300
   ASECNO 2284.000
        VALLEY SECTION BASED ON FIELD BOOK SECTION 8450
    2284.00      3.01    588.51      0.00      0.00    588.51      0.00      0.04      0.00    585.60
       27.         6.       13.         8.       51.       41.       81.         2.         2.    585.80
      0.95       0.11      0.31      0.10     0.080     0.050     0.060     0.041    585.50    248.21
  0.000027       423.      423.      423.         3         0         0      0.00    136.93    385.15

   FLOW DISTRIBUTION FOR SECNO=   2284.00          CUSEL=    588.51

   STA=      248.      289.      293.      307.      312.      385.
     PER Q=    14.7       6.3      47.5       7.2      24.3
     AREA=     61.0       9.3      40.6      11.6      69.9
      VEL=      0.1       0.2       0.3       1.2       0.1

   *SECNO 2941.000
     SECNO     DEPTH     CUSEL     CRIWS     WSELK     EG        HV        HL        DLOSS     BANK ELEV
       Q       QLOB      QCH       QROB      ALOB      ACT       AROB      VOL       TWA    LEFT/RIGHT
      TIME     VLOB      VCH       VROB      XNL       XNCH      XNR       STN       LAMIN       SSTA
     SLOPE     XLOOL     XLCH      XLOJR     XTRIAL    1n2       ICONT     CORAR     TOPELD      ENDST

   5470 ENCROACHMENT STATIONS=      191.0      247.0  TYPE=      1  TARGET=      56.300
        100 FEET D/S OF  54" CULVERT
    2941.00      3.04    588.54      0.00      0.00    588.54      0.00      0.03      0.00    585.90
       27.         4.       15.         8.       23.       29.       37.         4.         3.    585.90
      1.44       0.17      0.52      0.21     0.250     0.070     0.060     0.043    585.50    191.00
  0.000074        657.      657.      657.         2         1         0      0.00     56.00    247.00

   FLOW DISTRIBUTION FOR SECNO=   2941.00          CUSEL=    588.54

   STA=      191.      210.      214.      234.      226.      247.
     PER Q=    7.4       7.2      58.1       7.9      21.1
     AREA=     15.5       7.3      23.1       6.9      30.5
      VEL=      0.1       0.2       0.5       0.3       0.2

   CCHV=   0.300 CEHV=   0.500
   *SECNO 3041.000

   3045 OVERBANK AREA ASSUMED NON-EFFECTIVE/BLOCK=      500.00 CL/OA=      589.50

        D/S FACE  OF  54" CULVERT
    3041.00      3.23    588.55      0.00      0.70    588.55      0.05      0.02      0.03    585.55
       27.         0.       27.         0.                  14.         0.         4.         3.    585.55
      1.46       0.00      1.89      0.00     0.080     0.050     0.080     0.043    585.30    274.00
  0.001527        100.      100.      100.         1         1         0      0.00      4.50    248.50

   FLOW DISTRIBUTION FOR SECNO=   3041.00          CUSEL=    588.55

   STA=      214.      218.
     PER Q=    100.0
     AREA=     114.3
```

PRINTED IN U.S.A.

FORM 1411-08-PRINTED BY ROTARY MANIFOLD FORMS

VEL= 1.9

SPECIAL BRIDGE

SB	XK	XKOR	COPR	RD.SN	BRC	B*P	DAREA	SS	ELCHU	ELCHD
	0.00	3.01	3.00	3.00	3.16	0.05	7.90	0.00	586.70	565.30

*SECND 3210.000

OD/U,LOW FLOW BY NORMAL BRIDGE

ECPRS= 589.077 EGLUC= 589.956 ELLC= 589.200 PCWSE= 588.552 ELTRD= 590.000

3370 NORMAL BRIDGE,NOD= 9 MIN ELTRD= 590.00 MAX ELLC= 589.20

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLBA= 591.00 ELREA= 591.00

U/S END 540 CULVERT REPEATED SECT

3210.00	2.27	588.97	0.00	0.00	589.11	0.14	0.28	0.04	586.95
27.	0.	27.	0.	0.	9.	0.	4.	3.	586.85
1.67	0.00	2.79	0.00	0.080	0.050	0.020	0.043	586.70	214.00
0.00/226	169.	169.	169.	4	0	0	-20.00	4.50	218.50

FLOW DISTRIBUTION FOR SECNO= 3210.00 CWSEL= 588.97

STA= 214. 219.
PER Q= 100.0
AREA= 9.0
VEL= 3.0

*SECNO 3235.000

3470 ENCROACHMENT STATIONS= 191.0 247.0 TYPE= 1 TARGET= 56.000

CROSS SECTION BETWEEN 540 CULVERT " SHEEKS RD CULVERT

3235.00	2.50	589.16	0.00	0.00	589.16	0.00	0.21	0.04	586.95
27.	9.	9.	19.	39.	11.	21.	4.	3.	586.85
1.50	0.20	0.44	0.35	0.080	0.050	0.000	0.043	586.70	191.00
0.000070	25.	25.	25.	2	0	0	0.50	56.00	247.00

FLOW DISTRIBUTION FOR SECNO= 3235.00 CWSEL= 589.16

STA= 191. 210. 214. 219. 228. 247.
PER Q= 17.9 7.8 17.9 20.8 35.6
AREA= 26.3 8.2 10.9 21.2 40.3
VEL= 0.2 0.3 0.6 1.3 2.2

*SECNO 3384.000

3470 ENCROACHMENT STATIONS= 217.0 305.0 TYPE= 1 TARGET= 80.000

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLBA= 589.50 ELREA= 589.50

D/S END SHEEKS RD. CULVERT

3384.00 5.37 589.17 0.00 0.00 589.20 0.03 0.31 0.04 586.17

PRINTED IN U.S.A.
FORM 1411-OD PRINTED BY ROTARY MANIFOLD FORMS

	27.	0.	27.	0.	0.	19.	0.	5.	3.	586.10
	1.53	0.00	1.40	0.00	0.080	0.050	0.080	0.044	586.10	257.00
0.000677		149.	149.	149.	2	0	0	0.00	6.30	263.30

FLOW DISTRIBUTION FOR SECNO= 3584.00 CWSEL= 589.17

STA= 257. 263.
PER Q= 100.0
AREA= 19.3
VEL= 1.4

SPECIAL BRIDGE

SD	XK	XKOR	COPD	RDLEN	BWC	BWP	BAREA	SS	ELCHU	ELCHD
	0.00	3.32	3.00	0.00	3.92	0.00	15.80	1.00	586.10	586.10

SECNO 3548.000

SECNO	DEPTH	CWSEL	CRINS	WSELK	EG	HV	HL	CLOSS	BANK ELEV LEFT/RIGHT
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	ALOBL	ALCH	XLOBR	ITRIAL	FAC	ICONT	JOBAR	TOPWID	ENDST

PRESSURE FLOW

CWFRS	ECLOC	MO	PLEID	QOR	CAREA	TRAPEZOIDAL AREA	ELLC	ELTRD
589.32	589.20	0.00	5.	27.	19.	16.	582.60	590.00

3470 ENCROACHMENT STATIONS= 217.0 305.0 TYPE= 1 TARGET= 30.000

3492 OVERBANK AREA REQUIRED FOR EFFECTIVE CLEAR 350.00 EXIST= 344.00

U/S FACE OF SHEEKS RD CULVERT (76"X 48" ELLIPTICAL CONCRETE)

3548.00	3.19	589.29	0.00	3.00	439.32	0.03	2.12	0.00	586.10
27.	0.	27.	0.	0.	20.	2.	5.	3.	586.10
1.36	0.00	1.34	0.00	0.000	0.000	0.000	0.044	586.10	257.00
0.000694	364.	164.	164.	2	0	0	0.00	6.30	263.30

FLOW DISTRIBUTION FOR SECNO= 3548.00 CWSEL= 589.29

STA= 257. 263.
PER Q= 100.0
AREA= 20.1
VEL= 1.3

SECNO 3600.000

3470 ENCROACHMENT STATIONS= 145.0 255.0 TYPE= 1 TARGET= 110.000

XSECT. U/S OF SHEEKS RD.AND D/S OF SENECA RD.

3600.000	2.93	589.83	0.00	0.00	589.33	0.00	0.01	0.21	586.50
27.	0.	9.	16.	15.	23.	39.	0.	3.	586.50
1.62	0.15	0.40	0.13	0.010	3.150	0.062	0.044	586.40	144.55
0.000843	32.	32.	32.	0	0	0	0.00	59.33	255.00

PRINTED IN U.S.A.
FORM 1411-GD-PRINTED BY ROTARY MANIFOLD FORMS.

FLOW DISTRIBUTION FOR SECNO= 3600.00 CWSEL= 589.33

STA=	186.	196.	204.	210.	255.
PER Q=	8.1	33.7	11.0	47.2	
AREA=	14.6	23.0	93.9	75.5	
VEL=	0.2	0.4	0.2	0.2	

*SECNO 3792.000

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 591.30 ELAREA= 590.10

D/S END SENECA RD. CULVERT

3792.00	1.51	589.21	0.00	0.70	589.52	0.31	0.03	0.16	588.75
27.	0.	27.	0.	0.	6.	0.	5.	4.	580.75
1.63	0.00	4.50	0.00	0.090	0.052	0.000	0.044	587.70	223.00
0.022722	192.	192.	192.	2	0	0	0.00	4.50	227.50

FLOW DISTRIBUTION FOR SECNO= 3792.00 CWSEL= 589.21

STA=	223. 228.
PER Q=	100.0
AREA=	6.0
VEL=	4.5

SPECIAL BRIDGE

SS	XK	XKOR	COFQ	RDLEN	BHC	BWP	BARCA	SS	ELCHU	ELCHD
	0.00	1.63	3.00	0.00	2.71	0.00	12.20	0.00	587.70	587.70

*SECNO 3833.000

6070.LOW FLOW BY NORMAL BRIDGE

ESPRS= 0.000 EGLWC= 589.521 ELLC= 591.000 PCWSE= 589.206 SLTRD= 590.500

5370 NORMAL BRIDGE,WRD= 5 TIE CLTIW= 590.50 BAR ELLC= 591.00

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 591.00 ELAREA= 590.70

D/S FACE OF SENECA RD. CULVERT

3833.00	2.35	590.05	0.00	0.00	590.19	0.13	0.01	0.05	588.75
27.	0.	27.	0.	0.	9.	0.	5.	4.	580.75
1.63	0.00	2.94	0.00	0.080	0.050	0.000	0.044	587.70	223.00
0.010612	61.	61.	61.	4	0	0	-1.66	4.50	227.50

FLOW DISTRIBUTION FOR SECNO= 3833.00 CWSEL= 590.05

STA=	223. 228.
PER Q=	100.0
AREA=	9.2
VEL=	2.9

*SECNO 3883.000

X-SECT. U/S OF SENECA RD REPEATED SECT. 3833.

	3883.00	2.65	590.35	0.00	0.00	590.40	0.06	0.19	0.02	588.75
	27.	1.	23.	3.	1.	11.	11.	5.	4.	588.75
1	1.64	0.54	2.09	0.31	0.080	0.050	0.080	0.044	587.70	221.59
2	0.001985	50.	50.	50.	2	0	0	0.00	62.07	280.66

FLOW DISTRIBUTION FOR SECNO= 3883.00 CWSEL= 590.35

STA=	222.	223.	228.	229.	234.
PER Q=	2.2	85.5	3.6	8.6	
AREA=	1.1	11.1	1.4	9.2	
VEL=	0.5	2.1	0.7	0.3	

*SECNO 4337.000

	SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	KV	FL	QLOSS	BANK ELEV
	Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
	TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	STN	ELMIN	SSTA
	SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IN2	ICONT	CORAR	TOPWID	ENDST

3470 ENCROACHMENT STATIONS= 258.0 323.0 TYPE= 1 TARGET= 55.000

X-SECT. D/S OF COOKE RD

	4337.00	3.02	590.52	0.00	0.00	590.53	0.00	0.11	0.02	587.50
	27.	8.	16.	3.	37.	27.	18.	6.	4.	587.50
	1.93	0.21	0.59	0.10	0.000	0.050	0.060	0.045	587.50	260.00
	0.000689	350.	454.	500.	3	0	0	0.00	55.00	323.00

FLOW DISTRIBUTION FOR SECNO= 4337.00 CWSEL= 590.52

STA=	268.	293.	296.	305.	308.	323.
PER Q=	32.3	5.6	52.2	7.1	0.7	
AREA=	30.6	3.6	27.3	5.0	12.4	
VEL=	0.2	0.3	0.6	0.2	0.1	

*SECNO 6437.000

6445 OVERBANK AREA ASSUMED LOW-EFFECTIVE FLOW= 591.00 ELMIN= 591.00

D/S FACE OF COOKE RD CULVERT

	6437.00	2.16	590.53	0.00	0.00	590.57	0.04	0.02	0.02	587.35
	27.	0.	27.	0.	0.	17.	6.	0.	4.	587.35
	1.95	0.00	1.54	0.00	0.000	0.050	0.020	0.045	587.35	293.00
	0.000987	100.	100.	100.	2	0	0	0.00	5.50	298.50

FLOW DISTRIBUTION FOR SECNO= 6437.00 CWSEL= 590.53

STA=	293.	299.
PER Q=	100.0	
AREA=	17.5	
VEL=	1.5	

SPECIAL CROSS

SO XS 3400 CCRD REGIT D 3 0 BANK ES

0.00	1.98	3.00	0.00	3.93	0.00	4.91	0.00	587.35	587.35

*SECNO 4479.000
PRESSURE FLOW

EGDRS	EGLOC	HS	QWEIR	QCR	AREA	TRAPEZOID AREA	ELLC	ELTRD
591.43	590.57	0.00	0.	27.	5.	5.	588.60	591.70

5495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLE= 592.20 ELNE= 592.00

U/S FACE OF COOKE RD. CULVERT

4479.00	4.04	591.41	0.00	0.00	591.43	0.02	0.17	0.00	587.35
27.	0.	27.	0.	0.	22.	0.	0.	4.	587.35
1.96	0.00	1.21	0.00	0.080	0.050	0.080	0.045	587.35	295.00
0.000499	42.	42.	42.	2	0	0	0.00	5.50	298.50

FLOW DISTRIBUTION FOR SECNO= 4479.00 C.SEL= 591.41

STA= 293. 299.
PER Q= 100.0
AREA= 22.5
VEL= 1.2

*SECNO 4504.000

3470 ENCROACHMENT STATIONS= 268.0 323.0 TYPE= 1 TARGET= 55.000

XSECTION U/S COOKE RD

4504.00	6.04	591.44	0.03	0.00	591.44	0.01	0.01	0.01	587.35
27.	10.	10.	0.	57.	22.	49.	6.	4.	587.35
1.98	0.17	0.42	0.16	0.080	0.050	0.080	0.045	587.35	266.00
0.000391	25.	25.	25.	1	0	0	0.00	55.00	323.00

FLOW DISTRIBUTION FOR SECNO= 4504.00 C.SEL= 591.44

STA= 268. 290. 293. 299. 305. 323.
PER Q= 28.2 7.0 35.2 14.2 15.4
AREA= 47.0 9.5 22.3 10.2 36.2
VEL= 0.2 0.2 0.4 0.2 0.1

COOW= 0.100 CEHV= 0.300
*SECNO 4853.000

3470 ENCROACHMENT STATIONS= 438.0 563.0 TYPE= 1 TARGET= 125.000

WILLEY SECTION BASED ON FIELD DOCK SURVEY

4853.00	3.74	591.35	0.00	0.00	591.45	0.10	0.01	0.00	589.40
27.	9.	13.	3.	97.	61.	54.	7.	5.	589.85
2.62	0.09	0.22	0.09	0.100	0.260	0.100	0.046	587.71	420.03
0.000117	349.	349.	349.	2	0	0	0.00	102.93	561.93

FLOW DISTRIBUTION FOR SECNO= 4853.00 CWSEL= 591.45

PRINTED IN U.S.A.
FORM 1411-GB-PRINTED BY ROTARY MANIFOLD FORMS

STA=	438.	491.	510.	536.	541.					
PER Q=	32.5	49.5	16.8	1.2						
AREA=	97.3	61.4	48.7	5.3						
VEL=	0.1	0.2	0.1	0.1						

CONV= 0.300 CENV= 0.500
*SECNO 5053.000

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	QLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	SLMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	TW2	ICONT	CORAR	TOPWID	ENDST

XOSECTION D/S OF TELEGRAPH RD.

5053.00	5.08	591.45	0.00	0.00	591.46	0.00	0.00	0.00	586.37
27.	2.	23.	2.	17.	56.	17.	1.	5.	586.37
2.77	0.13	0.48	0.13	0.100	0.050	0.100	0.047	586.37	587.84
0.000030	200.	200.	200.	0	0	0	0.00	24.33	612.16

FLOW DISTRIBUTION FOR SECNO= 5053.00 CWSEL= 591.45

STA=	580.	595.	606.	612.
PER Q=	8.2	83.6	8.2	
AREA=	16.9	55.9	16.9	
VEL=	0.1	0.4	0.1	

*SECNO 5253.000

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLOA= 592.00 ELROA= 592.00

D/S FACE TELEGRAPH RD.

5253.00	5.06	591.44	0.00	0.00	591.45	0.00	0.00	0.00	586.40
27.	0.	27.	0.	0.	20.	0.	8.	5.	586.40
2.81	0.00	1.33	0.00	0.100	0.050	0.100	0.047	586.40	495.20
0.000439	200.	220.	200.	0	0	0	0.00	4.00	499.20

FLOW DISTRIBUTION FOR SECNO= 5253.00 CWSEL= 591.45

STA=	495.	499.
PER Q=	100.0	
AREA=	20.2	
VEL=	1.3	

SPECIAL BRIDGE

SK	HKOR	COPC	COLSW	BWC	DWP	BAREA	SS	ELCHU	ELCHD
5.00	5.79	3.00	1.00	5.53	0.50	70.97	0.00	587.30	586.90

*SECNO 5299.000
PRESS FLOW BECAUSE EGLWC OF 592.39 EXCEEDS 4.5 DEPTH
PRESSURE FLOW

EGRS	EGLWC	KT	QWEIR	QTO	FAREA	TRAREA	ELCC	ELTRD
592.01	592.53	1.05	0.	87.	11.	11.	591.45	590.30

PRINTED IN U.S.A.
FORM 1411-00-PRINTED BY ROTARY MANIFOLD FORMS.

3475 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 594.40 ELREA= 594.40

U/S FACE OF TELEGRAPH RD.

5299.00	4.68	591.98	0.00	0.00	592.01	0.03	0.52	0.00	588.50
27.	0.	27.	0.	0.	19.	0.	8.	5.	588.50
2.82	0.00	1.44	0.00	0.100	0.090	0.130	0.047	587.30	493.00
0.301907	46.	46.	46.	2	0	0	0.00	4.00	499.00

FLOW DISTRIBUTION FOR SECNO= 5299.00 CWSEL= 591.98

STA= 495. 499.

PER Q= 100.0
AREA= 28.7
VEL= 1.4

*SECNO 5349.000

XLSECT. U/S OF TELEGRAPH RD

5349.00	4.93	592.03	0.00	0.00	592.04	0.01	0.03	0.01	588.50
27.	4.	19.	4.	10.	19.	12.	8.	5.	588.50
2.84	0.38	0.98	0.38	0.100	0.060	0.103	0.047	587.30	489.07
0.000370	50.	50.	50.	2	0	0	0.00	16.51	505.59

FLOW DISTRIBUTION FOR SECNO= 5349.00 CWSEL= 592.03

STA= 489. 495. 499. 506.

PER Q= 14.6 68.8 16.5
AREA= 10.5 18.9 11.8
VEL= 0.6 1.0 0.4

*SECNO 5676.000

3470 ENCROACHMENT STATIONS= 375.0 430.0 TYPE= 1 TARGET= 55.000

XSECT. D/S OF R.R. TRACKS

5676.00	4.80	592.08	0.00	0.00	592.08	0.00	0.03	0.00	587.40
27.	2.	23.	2.	14.	47.	14.	4.	5.	587.40
3.05	0.15	0.48	0.15	0.100	0.060	0.100	0.048	587.28	388.05
0.000047	327.	327.	327.	2	0	0	0.00	22.30	411.15

FLOW DISTRIBUTION FOR SECNO= 5676.00 CWSEL= 592.08

STA= 389. 395. 405. 411.

PER Q= 3.2 83.6 6.2
AREA= 14.4 47.4 14.4
VEL= 0.2 3.5 0.2

CONV= 0.300 DIV= 0.500
*SECNO 5778.000

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	LOSS	BANK ELEV
Q	WLOB	WCR	CWSE	ALOB	ACR	AMOC	WOL	TW	LEFT/RIGHT
TIME	VLOB	VCR	VMOC	XL	CWCH	XNR	STA	ELMIN	SST
SLOPE	VLCH	ALCH	WLOB2	ETRIA	IH2	SSCNT	CORAR	TOPWID	ESSA

PRINTED IN U.S.A.
FORM 1411-GB-PRINTED BY ROTARY MANIFOLD FORMS.

5495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 597.00 ELREA= 594.00

D/S FACE OF R.R. CULVERT

5776.00	3.80	592.06	0.00	3.00	592.12	0.06	0.01	0.03	598.26	
27.	0.	27.	0.	0.	13.	0.	9.	5.	588.26	
3.07	0.00	2.03	0.00	0.120	0.060	0.120	0.048	588.26	599.00	
0.001905	100.	100.	100.	2	0	0	0.00	3.50	402.50	

FLOW DISTRIBUTION FOR SECNO= 5776.00 CHSEL= 592.06

STA= 599. 403.
PER Q= 100.0
AREA= 15.3
VEL= 2.0

SPECIAL BRIDGE

SS	XK	XSOR	COPC	ROLEN	S.C	SNP	EAREA	SS	ELCHO	ELCFD
	0.00	2.83	3.00	3.00	2.74	0.00	2.40	0.30	589.06	583.26

*SECNO 5651.000
PRESSURE FLOW

ESPIS	EGLWC	HS	QWEIR	OPR	BAREA	TRAPEZOID AREA	ELLC	ELTRD
597.66	592.86	0.00	0.	27.	2.	5.	590.73	599.40

5493 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 601.10 ELREA= 600.00

U/S FACE OF 42" RAILROAD CULVERT

5651.00	4.63	597.65	0.00	3.00	597.66	0.01	0.01	0.03	609.60	
27.	0.	27.	0.	0.	90.	0.	9.	5.	589.00	
3.09	0.00	0.89	0.00	0.125	0.060	0.120	0.048	589.00	699.20	
0.000373	75.	75.	75.	1	0	0	0.00	3.50	702.50	

FLOW DISTRIBUTION FOR SECNO= 5651.00 CHSEL= 597.65

STA= 695. 703.
PER Q= 100.0
AREA= 30.5
VEL= 0.9

*SECNO 5576.000

5470 ENCROACHMENT STATIONS= 675.0 727.0 TYPE= 1 TARGET= 52.800

XSECT. U/S OF R.R. TRACKS " D/S OF ARSENAL

5473.00	8.28	592.66	0.00	0.00	592.66	0.00	0.00	0.00	599.39	
27.	0.	27.	0.	942.	83.	951.	9.	5.	589.39	
8.17	0.06	0.94	0.05	0.120	0.060	0.120	0.048	589.39	699.00	
0.000302	95.	25.	25.	1	0	5	0.00	52.80	727.80	

PRINTED IN U.S.A.
FORM 1411-GB PRINTED BY ROTARY MANIFOLD FORMS.

FLOW DISTRIBUTION FOR SECNO= 5876.00 CWSEL= 597.66

STA=	675.	680.	695.	705.	715.	727.
PER Q=	3.9	25.2	41.4	17.3	12.2	
AREA=	31.7	109.8	82.3	74.7	74.5	
VEL=	0.0	0.1	0.1	0.2	0.0	

*SECNO 5931.000

5470 ENCROACHMENT STATIONS= 750.0 840.0 TYPE= 1 TARGET= 80.000

D/S FACE ARSENAL CULVERTS

5931.00	8.26	597.66	0.00	0.00	597.67	0.00	0.00	0.00	589.40
27.	5.	14.	8.	30.	25.	48.	9.	6.	589.40
3.21	0.14	0.56	0.17	0.120	0.060	0.120	0.028	589.40	783.15
0.000050	55.	35.	55.	1	0	0	0.60	45.26	828.55

FLOW DISTRIBUTION FOR SECNO= 5931.00 CWSEL= 597.66

STA=	783.	790.	795.	797.	799.	802.	805.	810.	811.	828.
PER Q=	1.1	3.5	3.2	11.2	51.0	19.3	9.4	0.2	0.5	
AREA=	5.4	9.3	8.5	14.2	24.5	22.4	10.5	0.9	4.9	
VEL=	0.1	0.1	0.1	0.2	0.6	0.2	0.1	0.1	0.0	

SPECIAL BRIDGE

5070,VARIABLE ELCHD OR ELCOD ON CARD SB NOT SPECIFIED

SO	XK	XKOR	COFQ	ADLEN	BWC	BWP	BAREA	SS	ELCHD	ELCID
	0.00	3.70	3.00	0.00	2.40	0.00	3.60	0.00	589.40	589.40

*SECNO 6006.000

WATER EL=WS CAP= 597.730 ~~?~~ Rating curve indicates overflow will pass 85's @ 596.05 ↳100 yr. discharge, why input 597.73

D/S FACE ARSENAL CULVERT

6006.00	8.33	597.73	0.00	0.00	597.74	0.01	0.00	0.00	589.40
27.	5.	14.	8.	37.	25.	33.	9.	6.	589.40
3.25	0.14	0.79	0.19	1.130	0.062	0.120	0.031	589.40	782.40
0.000057	75.	75.	75.	1	1	0	0.60	49.17	829.56

FLOW DISTRIBUTION FOR SECNO= 6006.00 CWSEL= 597.73

STA=	783.	795.	795.	799.	802.	805.	810.	831.
PER Q=	1.7	5.0	14.4	61.1	7.3	1.5	1.0	
AREA=	5.8	9.6	21.1	25.0	14.3	4.5	6.2	
VEL=	0.1	0.1	0.2	0.7	0.1	0.1	0.0	

*SECNO 6050.007

SEC NO	DEPTH	CWSEL	CRIWS	HSELR	EG	EV	HL	CLOSS	BANK ELEV
Z	QLOB	QCH	QROB	XNUM	XCG1	XCG2	WTS	ELMIN	STA
TIME	VLOB	VCH	VROB	XNUM	XCG1	XCG2	WTS	ELMIN	STA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL		ICONT	CCOEF	XOFFD	ENDST

X SECTION U/S OF ARSENAL

6050.00	8.31			0.00	5.77	3.05	0.01		589.40
						25			585.41

PRINTED IN U.S.A.
FORM 141-6B-PRINTED BY ROTARY MANIFOLD FORMS

```
      3.26      0.49      2.36      0.33     0.120     0.060     0.120     0.049    589.40    782.93
  0.000536       44.       44.       44.         1         0         0      0.00     46.41    829.33

 FLOW DISTRIBUTION FOR SECNO=   8050.00          CWSEL=    597.71

 STA=      783.      790.      795.      799.      803.      805.      810.      829.
   PER Q=    1.7       5.0      14.4      69.2       7.3       1.5       0.9
    AREA=    5.7       9.6      21.1      25.0      14.3       4.6       6.0
     VEL=    0.2       0.4       0.6       2.4       0.4       0.3       0.1

 CCH= 0.100 CEH= 0.300
 *SECNO 7934.000

 3470 ENCROACHMENT STATIONS=     583.0     718.0  TYPE=      1  TARGET=     135.000

          VALLEY SECTION BASED ON FIELD BOOK SECT. 2800.

   7934.00      3.99    597.35      0.00      0.00    597.85      0.00      0.07      0.01    589.76
        85.       30.       24.       31.      274.       69.      202.       25.       10.    589.65
      6.19      0.11      0.35      0.11     0.120     0.060     0.120     0.051    588.86    583.00
  0.000012      1884.     1884.     1884.         2         0         0      0.00    135.00    718.00

 FLOW DISTRIBUTION FOR SECNO=   7934.00          CWSEL=    597.85

 STA=      583.      641.      646.      654.      661.      718.
   PER Q=   30.2       4.8      28.4       7.3      29.4
    AREA=  212.0      31.7      68.5      15.1     236.6
     VEL=    0.1       0.1       0.4       0.1       0.1

 *SECNO 8734.000

 3470 ENCROACHMENT STATIONS=     382.0     518.0  TYPE=      1  TARGET=     135.000

          VALLEY SECTION BASED ON FIELD BOOK SECT. 2500.

   8734.00      6.67    597.86      0.00      0.00    597.86      0.00      0.01      0.00    591.49
        85.       37.       17.       30.      248.       39.      220.       35.       12.    591.29
      7.27      0.13      0.64      0.14     0.120     0.060     0.120     0.052    591.19    362.00
  0.000226       800.      800.      800.         3         0         0      0.00    135.00    518.00

 FLOW DISTRIBUTION FOR SECNO=   8734.00          CWSEL=    597.86

 STA=      382.      440.      447.      453.      459.      518.
   PER Q=   39.9       7.9      30.3       5.1      16.7
    AREA=  211.6      38.3      39.4      20.6     196.0
     VEL=    0.1       0.2       0.8       0.2       0.1

 *SECNO 9734.000

 3470 ENCROACHMENT STATIONS=     283.0     420.0  TYPE=      1  TARGET=     135.000

          VALLEY SECTION BASED ON FIELD BOOK SECT. 1000.

   9734.00      5.56    597.90      0.00      0.00    597.90      0.00      0.04      0.00    592.64
        85.       27.       30.       28.      158.       54.      167.       45.       15.    592.54
      8.17      0.17      0.56      0.17     0.120     0.060     0.120     0.052    592.34    285.00
  0.000056      1000.     1000.     1000.         4         0         0      0.00     35.00    430.00

 FLOW DISTRIBUTION FOR SECNO=   9734.00          CWSEL=    597.90
```

PRINTED IN U.S.A.
FORM 1411.00 PRINTED BY ROTARY MANIFOLD FORMS.

```
 STA=      265.      341.      345.      355.      358.      420.
   PER Q=     27.7       4.0      35.9       2.6      29.9
    AREA=    142.2      16.2      54.2      11.8     155.2
     VEL=      0.2       0.2       0.6       0.2       0.2

 CCHV=   0.300 CEHV=   0.500
 *SECNO 10613.000

 5470 ENCROACHMENT STATIONS=      433.0      566.0  TYPE=      1  TARGET=      133.000

          XSECT.D/S OF INKSTER RD

 10613.00      6.36    597.96      0.00      0.70    597.97      0.00      0.07      0.00    591.60
       85.       33.       18.       34.      111.       19.      110.       52.       18.    591.60
     6.73      0.30      0.94      0.31     0.080     0.060     0.080     0.053    591.60    433.00
0.000121      879.      879.      879.         2         0         0      0.00    133.00    566.00


 FLOW DISTRIBUTION FOR SECNO=  10613.00          CWSEL=    597.96

 STA=      433.      492.      498.      501.      509.      566.
   PER Q=     25.6      12.1      21.0      17.2      23.0
    AREA=    85.0      23.7      19.1      31.7      78.4
     VEL=      0.3       0.4       0.5       0.5       0.2

 *SECNO 10713.000
    SECNO      DEPTH     CWSEL     CRIWS     WSELK     EG        HV        EL        CLOSS     BANK ELEV
    Q          Q:OB      QCH       QRCD      ALOB      ACH       AROB      VOL       TWA    LEFT/RIGHT
    TIME       VLOB      VCH       VRCD      XNL       X CH      XNR       WTR       ELMIN      ESTA
    SLOPE      XLOBL     XLCH      XLOBR     STRIKL    IA2       ICONT     CORAR     TOPWID     ENDSTA

 5470 ENCROACHMENT STATIONS=      433.0      566.0  TYPE=      1  TARGET=      133.000

          D/S FACE OF INKSTER RD CULVERT

 10713.00      6.37    597.97      0.00      0.00    597.98      0.00      0.01      0.00    591.60
       85.       33.       18.       34.      111.       19.      111.       52.       18.    591.60
     8.00      0.30      0.93      0.31     0.090     0.060     0.080     0.053    591.60    433.00
0.000120      100.      100.      100.         0         0         0      0.00    133.00    566.00


 FLOW DISTRIBUTION FOR SECNO=  10713.00          CWSEL=    597.97

 STA=      433.      492.      498.      501.      509.      566.
   PER Q=     26.7      12.1      20.9      17.2      23.1
    AREA=    87.5      23.9      19.1      31.1      78.9
     VEL=      0.3       0.4       0.5       0.5       0.2


 SPECIAL BRIDGE

 BR  XR        XKOR      CDFC      RDWR      D/C       B/P       BARLA     CD        ELUPW     ELCRE
       0.00      2.00      1.00      0.00      2.00      0.00      0.00      0.00    593.54    591.62

 *SECNO 10754.000
 PRESSURE AND WEIR FLOW

 CGRTB     BRLID     HI        QWEIR     NPR       BAREA     TRAPEZOID AREA    EL.C      ELTOP
 620.85    599.92    1.00      11        10.       4.        1.                593.54    594.00
```

PRINTED IN U.S.A.
FORM 1411-GB-PRINTED BY ROTARY MANIFOLD FORMS.

U/S FACE OF INKSTER RD. CULVERT

10754.00	4.76	598.30	0.00	0.00	598.30	0.00	0.32	0.30	593.54	
85.	42.	10.	33.	131.	14.	113.	52.	12.	593.54	
0.83	0.32	0.73	0.29	0.080	0.060	0.000	0.055	593.54	453.76	
0.000108	41.	41.	41.	0	0	8	0.00	132.42	566.20	

FLOW DISTRIBUTION FOR SECNO= 10754.00 CHSEL= 598.30

STA=	434.	490.	492.	501.	510.	566.	566.
PER Q=	35.5	13.7	12.2	13.5	25.0	0.0	
AREA=	103.7	27.4	14.3	28.6	84.0	0.1	
VEL=	0.3	0.4	0.7	0.4	0.3	0.0	

*SECNO 10779.000

XSSECT U/S OF INKSTER RD.

10779.00	4.76	598.30	0.00	0.00	598.30	0.00	0.00	0.00	593.54
85.	42.	10.	33.	131.	14.	113.	32.	10.	593.54
0.85	0.32	0.73	0.29	0.085	0.060	0.000	0.055	593.54	453.76
0.000108	25.	25.	25.	0	0	0	0.00	132.42	566.20

FLOW DISTRIBUTION FOR SECNO= 10779.00 CHSEL= 598.30

STA=	434.	490.	490.	501.	510.	566.	566.
PER Q=	35.5	13.7	12.2	13.5	25.0	0.0	
AREA=	103.8	27.4	14.3	28.6	84.0	0.1	
VEL=	0.5	0.4	0.7	0.4	0.3	0.0	

PRINTED IN U.S.A.
FORM 1411-GB-PRINTED BY ROTARY MANIFOLD FORMS.

00BREAK00

1) COUNTY: Wayne

2) STUDY NAME: City of Flat Rock

3) WATERCOURSE: Cook and Hadding Drain

4) DOCUMENT TYPE: Summary

00BREAK00

HUD 2009-07
9/13/79

```
*********************************************************
*  HEC2 RELEASE DATED NOV 76 UPDATED FEB 1977           *
*  ERROR CORR -  01                                     *
*  MODIFICATION -  50,51,52                             *
*********************************************************

C
C  CITY OF FLAT ROCK FIS HUD 2009-07 COOKE & GLADDING FROM MOUTH TO INKSTER RD.
C  FQ 10YR 59CTS 50YR 75 100YR 85 500YR 120 WATER ELEV HURON RIVER MEAN LEVEL
T3      COOKE & GLADDING DR.-FLAT ROCK

J1  ICHECK     INQ        NINV       IDIR       STRT       METRIC     ITRANS     C          LSEL       FQ
          0.         2.         0.         0.    0.000000    0.00       0.0        .3.     585.400    0.000

J2  NPROF      IPLOT      PRFVS      XSECV      XSECH      FN         ALLDC      IBW        CHNIM      ITRACE
      1.000      0.000     -1.000      0.000      0.000      0.000      0.000      0.000      0.000      0.000

J3  VARIABLE CODES FOR SUMMARY PRINTOUT
    150.000    201.000      0.000      0.000      0.000      0.000      0.000      0.000      0.000      0.000

J5  LPRNT      NUMSEC                    ********REQUESTED SECTION NUMBERS********
    -10.000    -10.000      0.000      0.000      0.000      0.000      0.000      0.000      0.000      0.000
CT      5.000     21.000     21.000     27.000     27.000     37.000      0.000      0.000      0.000      0.000
NC      3.060      0.060      0.035      0.300      0.500      0.000      0.000      0.000      0.000      0.000
ET     40.000      0.000      0.000      0.000      9.100      2.000      0.000      0.000      1.000    151.000

                D/S FACE OF HURON RIVER DRIVE.
X1      0.000      8.000     75.000     79.500      0.000      0.000      0.000      0.000      0.000      0.000
X3     10.000      0.000      0.000      0.000      0.000      0.000      0.000    586.000    586.000      0.000
SP    597.000      3.000    540.000      1.000    588.000     75.300    591.000     75.000    587.000     79.500
GF    581.000     79.500    586.000    130.000    597.000    131.300      0.000      0.000      0.000      0.000
XT      0.000      1.500      4.000      0.000      3.530      0.000     15.600      0.000    587.130    591.300
NC      0.060      0.030      0.035      0.030      0.000      0.000      0.000      0.000      0.000      0.000

                U/S FACE HURON RIVER DRIVE
X1     54.000     14.000     38.000     42.500     54.000     54.000     54.000      0.000      0.000      0.000
SP      2.000      0.300      1.000    595.600    300.000      0.000      0.300      0.300      0.000      0.000
X3     13.000      0.300      0.000      0.000      0.000      0.300      0.300    588.600    588.300      0.300
BT     12.000      0.300    597.000      0.000      1.000    588.700      0.300     34.300    588.600      0.000
BT     46.000    597.300      0.000     66.300    597.000      0.000     67.300    588.300      0.300     85.000
O     588.000    585.350     89.000    600.000    585.600     91.300    586.300    590.300     54.500    590.300
--    585.350    575.000    588.000      0.000    575.300    597.000      0.000      0.000      0.000      0.000
--    597.000      0.000    586.000      1.300    585.750     35.000    197.000     36.000    597.500     37.000
BB    585.300     67.000    585.000     39.300    589.350     38.000    591.000     39.000    587.400     91.500
CR    583.350     92.500    590.000    100.300    585.300     79.000    597.000    170.000      0.000      0.000
E       0.000      0.000      0.000      0.000      1.430      0.000      0.000      0.000      0.000      0.000

                VALLEY SECTION BASED ON FIELD BOOK SHEETS 10,32
```

PRINTED IN U.S.A.
FORM 1411-GB-PRINTED BY ROTARY MANIFOLD FORMS

GR	589.000	140.000	508.660	158.[illegible]		[illegible].000	586.460	290.000	582.260	297.000
GR	581.510	300.000	582.500	303.000	586.010	310.000	587.360	316.000	587.560	350.000
GR	595.500	359.100	595.500	369.900	587.600	370.000	588.000	390.000	596.000	390.100
GR	596.000	420.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
NC	0.000	0.000	0.000	0.100	0.300	0.000	0.000	0.000	0.000	0.000

VALLEY SECTION BASED ON FIELD BOOK SECTION 9434

X1	1300.000	17.000	276.000	284.000	1000.000	1000.000	1000.000	0.000	0.000	0.000
SR	600.000	0.000	600.000	50.000	608.000	50.100	608.000	99.900	599.900	50.000
GR	593.490	180.000	585.810	273.000	583.660	274.000	583.010	280.000	583.660	284.000
SR	585.460	287.000	586.310	365.000	583.510	401.000	596.500	401.100	596.500	431.000
GR	588.600	431.100	590.000	590.000	0.000	0.000	0.000	0.000	0.000	0.000
NC	0.080	0.080	0.050	0.300	0.500	0.000	0.000	0.000	0.000	0.000
ET	0.000	0.000	0.000	0.000	9.100	0.000	0.000	0.000	1.000	600.000

XWSECTION D/S GIBRALTAR RD.BASED ON FIELD BOOK " QUAD MAP

X1	1600.000	17.000	297.500	302.100	300.000	300.000	300.000	0.000	0.000	0.000
GR	604.000	0.000	596.000	0.100	595.400	80.000	603.400	80.100	603.400	110.000
GR	595.000	110.100	593.000	289.500	584.500	297.300	583.290	300.000	536.300	302.100
GR	589.500	313.900	590.000	400.000	590.500	430.000	598.500	450.100	598.500	480.000
GR	592.000	480.100	590.000	600.000	0.000	0.000	0.000	0.000	0.000	0.000
ET	0.000	0.000	0.000	0.000	9.100	0.000	0.000	0.000	1.000	600.000

D/S FACE OF GIBRALTAR RD. REPEATED SECT 1600

X1	1700.000	0.000	0.000	0.000	100.000	100.000	100.000	0.000	0.000	0.000
X5	10.000	585.140	0.000	0.000	0.000	0.000	0.000	590.000	590.000	0.000
SB	0.000	2.980	3.000	0.000	3.590	0.000	9.540	0.000	586.240	585.140
NC	0.000	0.000	0.045	0.000	0.000	0.000	0.000	0.000	0.000	0.000

U/S FACE OF GIBRALTAR RD.

X1	1836.000	16.000	295.000	299.600	136.000	136.000	136.000	0.000	0.000	0.000
X2	0.000	0.000	1.000	586.900	592.800	0.000	0.000	0.000	0.000	0.000
SB	10.000	589.240	0.000	0.000	0.590	0.000	0.000	590.400	590.400	0.000
BT	16.000	0.000	596.000	0.100	124.000	595.000	0.000	262.000	595.300	0.000
GT	295.000	592.000	586.900	295.300	592.810	297.540	295.000	592.800	588.500	294.500
BT	592.000	588.700	297.300	592.800	588.900	298.100	592.800	588.700	298.200	592.300
GT	588.500	292.400	592.800	587.900	292.600	592.800	586.900	323.000	588.000	0.000
ET	450.000	594.300	0.000	600.000	593.500	0.000	650.000	594.000	0.000	0.000
CB	596.000	0.300	595.000	325.000	593.300	292.000	586.900	295.000	585.700	295.300
BT	585.000	299.300	584.700	294.500	584.390	297.300	584.700	298.100	585.200	293.900
GT	585.700	299.400	585.900	299.500	599.900	323.000	590.000	450.300	592.000	600.300
ET	594.000	650.300	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
XS	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
ET	0.000	0.000	0.000	0.000	1.400	0.000	0.000	0.000	0.000	0.000

U/SECT.D/S OF GIBRALTAR RD. REPEATED SECT.

X1	1661.000	0.000	0.000	0.000	25.000	25.000	25.000	0.000	0.000	0.000
X5	0.000	0.000	0.000	270.000	0.000	625.000	0.000	0.000	0.000	0.000
BG	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
ET	0.000	0.000	0.000	0.000	1.400	0.000	0.000	0.000	0.000	0.000

VALLEY SECTION BASED ON FIELD BOOK SECTION 9457

PRINTED IN U.S.A.
FORM 1411-BB-PRINTED BY ROTARY MANIFOLD FORMS.

X1	2284.000	11.000	293.000	307.000	423.000	423.000	423.000	0.000	0.000	0.000
GR	598.970	0.000	598.620	100.000	590.890	200.000	586.500	289.000	585.600	293.000
GR	585.500	300.000	585.800	307.000	586.600	312.000	588.900	400.000	595.500	500.000
GR	596.500	630.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000

100 FEET D/S OF 54" CULVERT

X1	2941.000	15.000	214.000	224.000	657.000	657.000	657.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	191.000	0.000	247.000	0.000	0.000	0.000	0.000
GR	500.000	0.000	595.000	90.000	590.000	160.000	587.200	210.000	585.900	214.000
GR	585.500	217.250	585.500	220.750	585.900	224.000	587.000	228.000	587.500	350.000
GR	593.000	350.100	593.000	380.000	587.600	380.100	590.000	400.000	592.000	500.000
MC	0.000	0.000	0.000	0.300	0.500	0.000	0.000	0.000	0.000	0.000
ET	0.000	0.000	0.000	0.000	9.100	0.000	0.000	0.000	1.000	352.000

D/S FACE OF 54" CULVERT

X1	3041.000	12.000	214.000	218.500	100.000	100.000	100.000	0.000	0.000	0.000
X3	10.000	585.300	0.000	0.000	0.000	0.000	0.000	589.500	589.500	0.000
GR	600.000	0.000	600.000	160.000	590.000	165.000	587.200	210.000	585.550	214.000
GR	583.300	215.000	583.500	217.500	585.550	218.530	587.000	228.000	587.500	350.000
GR	590.000	351.000	595.000	352.000	0.000	0.000	0.000	0.000	0.000	0.000
SL	0.000	3.010	3.000	0.000	3.160	0.000	7.900	0.000	586.700	585.300

U/S END 54) CULVERT REPEATED SECT

X1	3210.000	12.000	214.000	218.500	169.000	169.000	169.000	0.000	0.000	0.000
X2	0.000	0.000	1.000	589.200	590.000	0.000	0.000	0.000	0.000	0.000
X3	10.000	586.700	0.000	0.000	0.000	0.000	0.000	591.000	591.000	0.000
BT	9.000	0.000	600.000	0.000	160.000	400.000	0.000	165.000	590.000	0.000
BT	214.000	590.000	586.950	215.000	590.000	589.200	217.500	590.000	589.200	216.500
BT	590.000	583.950	351.000	597.000	0.000	352.000	595.000	0.000	0.000	0.000
GR	600.000	0.000	600.000	160.000	590.000	165.000	587.200	210.000	586.950	214.000
GR	583.700	215.000	586.700	217.500	586.950	218.500	587.200	228.000	587.300	350.000
GR	590.000	351.000	595.000	352.000	0.000	0.000	0.000	0.000	0.000	0.000
ET	0.000	0.000	0.000	0.000	1.600	0.000	0.000	0.000	0.000	0.000

XSECTION BETWEEN 54) CULVERT " SHIEKS RD CULVERT

X1	3239.000	0.000	0.000	5.000	25.000	25.000	25.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	191.000	0.000	247.000	0.000	0.000	0.000	0.000
ET	0.000	0.000	0.000	0.000	9.100	0.000	0.000	0.000	176.000	405.000

D/S END SHEZKS RD. CULVERT

X1	3394.000	11.000	257.000	263.300	149.000	149.000	149.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	217.000	0.000	385.000	0.000	589.500	589.500	0.000
GR	600.000	252.000	600.000	232.000	590.000	233.000	588.600	253.000	588.700	257.000
GR	586.100	259.000	586.100	261.500	586.102	263.300	588.600	265.000	589.500	405.000
GR	600.000	405.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
ET	0.000	3.320	3.000	0.000	2.322	0.000	15.600	0.000	586.700	586.700

U/S FACE OF SHEEKS RD CULVERT TYPE "D" ELLIPTICAL CONCRETE

X1	3548.000	0.000	0.000	0.000	144.000	134.000	134.000	0.000	0.000	0.000
X2	0.000	0.000	0.000	589.200	590.000	0.000	0.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	217.000	0.000	383.000	0.000	590.000	591.000	0.000
ET	13.000	232.000	600.000	0.000	156.000	600.000	0.000	15.000	590.000	0.000

PRINTED IN U.S.A.
FORM 1411-OB-PRINTED BY ROTARY MANIFOLD FORMS.

BT	255.000	590.000	0.000	257.000	590.000	586.100	257.000	590.000	587.400	259.000
BT	590.000	588.600	261.500	590.000	588.600	263.300	590.000	587.400	263.300	590.000
BT	586.100	405.000	589.500	0.000	405.000	600.000	0.000	0.000	0.000	0.000
ET	0.000	0.000	0.000	0.000	1.400	0.000	0.000	0.000	0.000	0.000

XSECT. U/S OF SHEEKS RD. AND D/S OF SENECA RD.

X1	3600.000	9.000	196.000	204.000	52.000	52.000	52.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	145.000	0.000	255.000	0.000	0.000	0.000	0.000
GR	600.000	0.000	595.000	100.000	589.500	185.000	586.500	196.000	586.400	200.000
GR	586.500	204.000	587.500	270.000	588.300	334.000	600.000	334.000	0.000	0.000
ET	0.000	0.000	0.000	0.000	9.100	0.000	0.000	0.000	1.000	310.000

D/S END SENECA RD. CULVERT

X1	3792.000	10.000	223.000	227.500	192.000	192.000	192.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	591.300	590.700	0.000
GR	600.000	0.000	595.000	100.000	591.000	221.000	588.750	223.000	587.700	224.000
GR	587.700	227.000	588.750	227.500	590.000	229.000	590.500	310.000	600.000	310.000
SO	0.000	1.630	3.000	0.000	2.710	0.000	12.200	0.300	587.700	587.700

U/S FACE OF SENECA RD. CULVERT

X1	3833.000	0.000	0.000	0.000	41.000	41.000	41.000	0.000	0.000	0.000
X2	0.000	0.000	1.000	591.000	590.500	0.000	0.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	591.800	590.700	0.000
BT	0.000	0.000	600.000	0.000	100.000	595.000	0.000	223.000	591.800	588.750
BT	224.000	591.800	591.000	224.500	591.800	591.000	227.500	591.800	588.750	310.000
BT	590.500	0.000	310.000	600.000	0.000	0.000	0.000	0.000	0.000	0.000
ET	0.000	0.000	0.000	0.000	1.400	0.000	0.000	0.000	0.000	0.000

XSECT. U/S OF SENECA RD REPEATED SEC'N 3833.

X1	3883.000	0.000	0.000	0.000	50.000	50.000	50.000	0.000	0.000	0.000

XSECT. D/S OF COOKE RD

X1	4337.000	11.000	595.500	304.500	370.000	590.000	454.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	268.000	0.000	325.000	0.000	0.000	0.000	0.000
GR	600.000	0.000	595.000	130.000	590.000	200.000	589.170	292.500	587.500	295.500
GR	587.500	304.500	589.670	307.500	590.000	350.000	591.300	500.000	591.500	600.000
GR	593.000	1000.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
ET	0.000	0.000	0.000	0.000	9.100	0.000	0.000	0.000	1.000	526.000

D/S FACE OF COOKE RD CULVERT

X1	4437.000	14.000	293.000	253.500	100.000	100.000	100.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	591.300	591.000	0.000
GR	600.000	0.000	595.000	130.000	590.000	250.000	589.200	250.000	587.500	295.000
GR	587.350	293.000	587.350	295.000	587.350	293.500	587.350	296.000	587.500	298.000
GR	587.350	298.000	587.350	298.500	589.700	333.000	592.000	350.000	590.400	416.000
GR	600.000	416.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
ET	0.000	1.957	3.000	0.000	5.950	0.000	2.970	0.000	587.350	587.350

U/S FACE OF COOKE RD. CULVERT

X1	4473.000	0.000	0.000	0.000	42.000	42.000	42.000	0.000	0.000	0.000

FORM 1411-08 PRINTED BY ROTARY MANIFOLD FORMS, PRINTED IN U.S.A.

X2	0.000	0.300	1.000	598.600	591.700	0.000	0.000	0.000	0.000	0.000
X3	10.000	0.900	0.000	0.000	0.000	0.000	0.000	592.000	592.000	0.000
BT	16.000	0.300	600.000	0.000	130.000	598.000	0.000	200.000	594.000	0.000
BT	293.000	591.700	587.350	293.500	591.700	588.600	294.000	591.700	588.600	295.500
BT	591.700	587.350	296.000	591.700	587.350	296.500	591.700	588.600	298.000	591.700
BT	588.600	298.500	591.700	367.350	350.000	591.700	0.000	416.000	592.700	0.000
BT	416.000	600.000	0.000	416.000	600.000	0.000	416.000	600.000	0.000	0.000
ET	0.000	0.000	0.000	0.000	1.400	0.000	0.000	0.000	0.000	0.000

X-SECTION U/S COOKE RD

X1	4504.000	0.000	0.000	0.000	25.000	25.000	25.300	0.000	0.000	0.000
X3	0.000	0.000	0.000	268.000	0.000	323.000	0.000	0.000	0.000	0.000
NC	0.100	0.100	0.060	0.100	0.300	0.000	0.000	0.000	0.000	0.000

VALLEY SECTION BASED ON FIELD BOOK SECT.5301

X1	4853.000	19.000	491.000	510.000	349.000	349.000	349.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	438.000	0.000	563.000	0.000	0.000	0.000	0.000
GR	600.000	0.000	595.660	200.000	595.910	300.000	594.060	378.000	590.060	391.000
GR	590.110	400.000	589.410	491.000	587.930	494.000	587.710	500.000	588.060	506.000
GR	589.850	510.000	589.300	336.000	586.710	553.000	594.420	591.000	594.370	630.000
GR	593.020	700.300	593.440	750.000	594.150	600.000	595.000	1050.000	0.000	0.000
NC	0.100	0.100	0.060	0.300	0.500	0.000	0.000	0.000	0.000	0.000

X-SECTION D/S OF TELEGRAPH RD.

X1	5053.000	8.000	594.500	605.500	200.000	200.000	200.000	0.000	0.000	0.000
GR	600.000	0.000	595.000	150.000	594.000	594.500	586.370	594.500	586.370	605.500
GR	594.000	615.500	595.000	775.000	600.000	1230.000	0.000	0.000	0.000	0.000
ET	0.000	0.000	0.000	0.000	9.100	0.000	0.000	0.500	1.000	1200.000
NC	0.000	0.000	0.350	0.000	0.300	0.300	0.000	0.500	0.300	0.000

D/S FACE TELEGRAPH RD.

X1	5253.000	4.000	495.000	499.000	200.000	200.000	200.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.700	0.000	0.000	592.000	592.000	0.000
GR	600.000	0.000	595.000	50.000	594.000	597.000	586.400	495.000	586.400	499.000
GR	594.400	515.000	595.000	775.000	600.000	1230.000	0.000	0.000	0.000	0.000
SB	0.000	5.700	3.000	0.000	3.630	0.000	10.900	0.000	587.200	516.400

U/S FACE OF TELEGRAPH RD.

X1	5299.000	12.000	495.000	499.000	40.000	40.100	40.000	0.000	0.000	0.000
X2	0.000	0.000	1.000	590.300	594.400	0.000	0.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	594.400	594.400	0.000
X4	1.000	594.400	485.100	0.000	0.000	0.000	0.000	0.000	0.000	0.000
BT	11.000	0.100	600.000	0.000	485.000	600.000	307.300	525.000	594.400	587.200
BT	499.000	594.400	588.500	495.500	594.400	550.000	297.000	594.400	590.200	499.500
BT	594.400	300.000	499.000	594.400	580.500	799.000	594.400	587.200	613.000	594.400
BT	0.000	510.000	605.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
GR	600.000	0.000	600.000	50.000	600.000	485.000	586.300	495.000	587.300	495.000
GR	587.300	495.300	587.300	497.000	587.300	498.500	587.300	499.000	586.500	499.000
BP	594.400	510.000	505.000	510.000	0.000	0.000	0.000	0.000	0.000	0.000
ET	0.000	0.000	0.000	0.300	0.400	0.000	0.000	0.000	0.000	0.000
NC	0.000	0.000	0.000	0.300	0.000	0.000	0.000	0.000	0.000	0.000

X-SECT. U/S OF TELEGRAPH RD

PRINTED IN U.S.A.
FORM 1411-BB-PRINTED BY ROTARY MANIFOLD FORMS

X1	5349.000	0.000	0.000	0.000	50.000	50.000	50.000	0.000	0.000	0.000
ET	0.000	9.100	9.100	9.100	0.000	9.100	0.000	0.000	375.000	430.000

X@SECT. D/S OF R.R. TRACKS

X1	5676.000	10.000	395.000	405.000	327.000	327.000	327.000	0.000	0.000	0.000
GR	600.000	0.000	595.000	250.000	590.000	320.000	595.000	385.000	587.400	395.000
GR	587.280	400.000	587.400	405.000	595.000	415.000	395.000	525.000	600.000	600.000
MC	0.120	0.120	0.060	0.300	0.500	0.000	0.000	0.000	0.000	0.000
ET	0.000	0.000	0.000	0.000	9.100	0.000	0.000	0.000	1.000	486.000

D/S FACE OF R.R. CULVERT

X1	5776.000	11.000	399.000	602.500	100.000	100.200	100.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.050	0.000	0.000	0.000	597.000	594.000	0.000
GR	600.000	0.000	595.000	250.000	590.000	320.000	320.000	385.000	588.260	395.000
GR	588.260	399.000	588.260	402.500	591.000	405.000	594.000	408.000	594.000	486.000
GR	600.000	486.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
SB	0.000	2.850	3.000	0.000	2.740	0.000	2.400	0.000	589.000	588.260

U/S FACE OF 42" RAILROAD CULVERT

X1	5851.000	21.000	699.000	702.500	75.000	75.000	75.000	0.000	0.000	0.000
X2	0.000	0.000	1.000	590.750	599.400	0.000	0.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	601.100	600.000	0.000
BT	15.000	0.000	604.000	0.000	250.000	603.000	0.000	300.000	602.600	0.000
BT	400.000	602.200	0.000	500.000	601.900	0.000	600.000	601.500	0.000	699.000
BT	601.100	589.000	699.250	601.100	590.250	700.750	601.100	590.750	702.250	601.100
BT	590.250	702.500	601.100	589.000	785.000	599.400	0.000	786.000	604.000	0.000
BT	876.000	604.000	0.000	876.000	604.000	0.000	876.000	604.000	0.000	0.000
GR	604.000	0.000	600.000	0.000	595.000	75.000	594.200	200.000	592.600	350.000
GR	592.400	400.000	592.200	590.700	591.600	405.000	591.000	605.000	589.000	591.010
GR	589.000	699.200	589.000	699.250	595.000	700.750	589.000	702.250	589.000	702.500
GR	591.000	705.000	599.000	715.000	599.000	705.000	601.000	786.000	604.000	876.000
GP	604.000	876.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
ET	0.000	9.100	0.000	0.000	1.400	0.000	0.000	0.000	674.000	728.000

X@SECT. U/S OF R.R. TRACKS " D/S OF ARSENAL

X1	5876.000	9.000	695.000	705.000	25.000	25.000	25.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	675.000	0.000	727.000	0.000	0.000	0.000	0.000
GR	600.000	0.000	595.000	100.000	597.300	600.000	589.300	695.000	589.300	703.000
GR	597.010	715.000	595.000	800.000	650.000	957.000	600.000	1200.000	1.000	1.000
ET	0.000	0.000	9.000	0.000	9.100	0.000	0.000	0.000	1.000	1100.000

D/S FACE ARSENAL CULVERTS

X1	5931.000	13.000	799.000	802.000	55.000	55.000	55.000	0.000	0.000	0.000
X3	10.000	0.000	1.000	790.000	0.000	810.000	0.000	593.000	593.000	0.000
GR	604.000	772.000	600.000	773.000	596.100	790.000	595.000	795.000	591.000	797.000
GR	589.000	799.000	589.000	802.000	591.000	805.000	598.500	810.000	597.100	811.000
GP	599.000	809.000	604.000	870.000	604.000	1100.000	0.000	0.000	0.000	0.000
BU	0.000	5.700	0.000	0.000	2.400	0.000	2.600	0.000	0.000	0.000

U/S FACE ARSENAL CULVERT

X1	5986.000	14.000	799.000	802.000	75.000	75.000	75.000	0.000	0.000	0.000

PRINTED IN U.S.A.
FORM 1411-08 PRINTED BY ROTARY MANIFOLD FORMS.

X2	0.000	0.000	1.000	590.900	596.100	C.000	0.000	0.000	C.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	596.100	596.500	0.000
X5	5.000	596.000	596.000	597.730	597.830	599.860	0.000	0.000	0.000	0.000
BT	13.000	772.000	604.000	0.000	772.000	604.000	0.000	773.000	606.000	0.000
BT	790.000	596.100	1.000	799.000	596.100	$59.400	799.250	596.250	590.600	800.500
BT	596.300	590.900	801.750	596.400	590.600	802.000	596.500	589.400	805.000	596.510
BT	0.000	810.000	597.100	0.000	869.000	599.000	0.000	870.000	604.000	0.000
GR	604.000	772.000	600.000	773.000	600.000	773.000	596.100	790.000	595.500	795.000
GR	589.400	799.000	589.400	799.250	589.400	800.500	589.400	801.750	589.400	802.000
GR	596.500	805.000	597.100	810.000	599.000	869.000	604.000	870.000	0.000	0.000
QT	5.000	50.000	75.000	85.000	85.000	120.000	0.000	0.000	0.000	0.000
ET	0.000	0.000	0.000	0.000	1.400	0.500	0.000	0.000	0.000	0.000

X SECTION U/S OF ARSENAL.

X1	6050.000	0.000	0.000	0.000	44.000	44.000	44.000	0.000	0.000	0.000
NC	0.120	0.120	0.060	0.100	0.300	0.300	0.000	0.000	0.000	0.000

VALLEY SECTION BASED ON FIELD BOOK SECT. 2800.

X1	7934.000	12.000	666.000	654.000	1864.000	1804.000	1884.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	583.000	0.000	716.000	0.000	0.000	0.000	0.000
X4	1.000	605.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
GR	600.000	0.000	595.160	350.000	594.560	450.000	594.560	550.000	593.260	641.000
GR	589.760	646.000	588.860	650.000	589.650	654.000	593.150	661.000	594.850	750.000
GR	598.820	850.000	601.020	950.000	0.000	0.000	0.000	0.000	0.000	0.000

VALLEY SECTION BASED ON FIELD BOOK SECT. 2000.

X1	8734.000	13.000	447.000	453.000	800.000	800.000	900.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	382.000	0.000	518.000	0.000	0.000	0.000	0.000
X4	2.000	605.000	0.000	475.000	1001.200	0.000	0.000	0.000	0.000	0.000
GR	600.000	0.000	595.290	50.000	596.590	850.000	595.090	950.000	593.790	440.000
GR	591.690	442.000	591.195	450.000	591.290	452.000	596.190	450.000	595.690	530.000
GR	596.290	650.000	597.590	750.000	600.000	1000.000	0.000	0.000	0.000	0.000

VALLEY SECTION BASED ON FIELD BOOK SECT. 1000.

X1	9734.000	93.000	345.000	353.000	1005.000	1000.000	1050.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	285.000	0.000	420.000	0.000	0.000	0.000	0.000
X6	2.000	605.000	0.000	605.000	701.000	0.000	0.000	0.000	0.000	0.000
GR	600.000	0.000	598.940	50.000	598.140	150.000	596.040	250.000	595.240	341.000
GR	592.640	343.000	592.340	350.000	592.340	355.000	595.540	353.000	595.470	450.000
GR	595.920	550.000	596.920	650.000	600.000	730.000	0.000	0.000	0.000	0.000
NC	0.060	0.060	0.060	0.100	0.500	0.000	0.000	0.000	0.000	0.000

XSECT.D/S OF INKSTER RD

X1	10513.000	15.000	498.000	504.000	879.000	879.000	879.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	433.000	0.000	556.000	0.000	0.000	0.000	0.000
GR	604.000	0.000	600.000	0.000	599.000	100.000	598.000	200.000	597.000	300.000
GR	596.600	464.000	591.600	498.000	591.600	511.000	597.400	509.000	597.000	607.000
GR	597.500	900.000	598.000	1000.000	599.000	1100.000	599.500	1200.000	600.000	1300.000
ET	604.000	1301.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
CT	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	1.000	1301.000

D/S FACE OF INKSTER RD CULVERT

PRINTED IN U.S.A.
FORM 1411-60 PRINTED BY ROTARY MANIFOLD FORMS

X1	10713.000	3.000	0.000	0.000	100.000	100.000	130.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	433.000	0.000	566.000	0.000	0.000	0.000	0.000
SB	0.000	2.600	3.000	0.000	2.400	0.000	3.600	0.000	593.540	591.620

U/S FACE OF INKSTER RD. CULVERT

X1	10754.000	15.000	498.000	501.000	41.000	41.000	41.000	0.000	0.000	0.000
X2	0.000	0.000	1.000	595.040	597.900	0.000	0.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	597.900	597.900	0.000
BT	13.000	433.000	604.000	0.000	433.000	604.000	0.000	433.000	604.000	0.000
BT	433.000	604.000	0.000	433.000	604.000	0.000	434.000	597.900	0.000	498.000
BT	597.900	593.540	498.250	597.900	594.790	499.500	597.900	595.040	500.750	597.900
BT	594.790	501.000	597.900	593.540	566.000	598.200	0.000	567.000	604.000	0.000
GR	604.000	433.000	604.000	433.000	604.000	438.000	604.000	433.000	604.000	433.000
GR	596.700	434.000	596.200	490.000	593.540	498.000	593.540	498.250	593.540	499.500
GR	593.540	500.750	593.540	501.000	596.700	510.000	596.900	566.000	604.000	567.000
ET	0.000	0.000	0.000	0.000	1.400	0.000	0.000	0.000	0.000	0.000


XSECT U/S OF INKSTER RD.

X1	10779.000	0.000	0.000	0.000	25.000	25.000	25.000	0.000	0.000	0.000
GJ	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000

PRINTED IN U.S.A.
FORM 1411-GD PRINTED BY ROTARY MANIFOLD FORMS.

FORM 1411-GB PRINTED BY ROTARY MANIFOLD FORMS,

PRINTED IN U.S.A.



```
**************************************************
  HEC2 RELEASE DATED NOV 76 UPDATED FEB 1977
  ERROR CORR -  01
  MODIFICATION -  50,51,52
**************************************************

T1CITY OF FLAT ROCK FIS HUD 2009-07 COOKE & GLADDING FROM SOUTH TO INKETER RD.
T2       100 YR STORM
T3       COOKE & GLADDING DR.-FLAT ROCK

J1   ICHECK    INQ        NINV       IDIR       STRT       METRIC     HVIAS      G          USEL       FQ

          0.        5.         0.         0.  0.003000       0.00       0.0         0.   585.400       0.000


J2   NPROF     IPLOT      PRFVS      XSECV      XSECH      FN         ALLOC      XDV        CHNIM      XTRACE

       2.000      0.000     -1.000      0.000      0.000      0.000      0.000      0.000      0.000      0.000
```

PRINTED IN U.S.A.
FORM 1411-08 PRINTED BY ROTARY MANIFOLD FORMS.

FORM 1411-GB-PRINTED BY ROTARY MANIFOLD FORMS,

PRINTED IN U.S.A.



```
**************************************************
  HEC2 RELEASE DATED NOV 76 UPDATED FEB 1977
  ERROR CORR -  01
  MODIFICATION -  50,51,52
**************************************************


T1CITY OF FLAT ROCK FIS H00 2009-07 COOKE & GLADDING FROM MOUTH TO IRKSTER RD.
T2 0 10YR 50CTS 50YR 75 100YR 85 500YR 120 WATER ELEV HURON RIVER MEAN LEVEL
T3       COOKE & GLADDING DR.-FLAT ROCK

J1   ICHECK     INQ        NINV       IDIR       STRT       METRIC     HVINS      Q          WSEL       FQ
          0.        4.         0.         0.  0.000000       0.00       0.5        2.    585.400      0.000

J2   NPROF     IPLOT     PRFVS     XSECV     XSECH     FN        ALLDC     IEM       CHNIM     ITRACE
        3.000     0.000    -1.000     0.000     0.000     0.000     0.000     0.000     0.000     0.000
```

PRINTED IN U.S.A.
FORM 1411-GB PRINTED BY ROTARY MANIFOLD FORMS.

FORM 1411-GS-PRINTED BY ROTARY MANIFOLD FORMS.
PRINTED IN U.S.A.



```
**************************************************
    NEC2 RELEASE DATED NOV 76 UPDATED FEB 1977
    ERROR CORR -  01
    MODIFICATION -  50,51,52
**************************************************

  Y1CITY OF FLAT ROCK FIS HUD 2009-07 COOKE & GLADDING FROM MOUTH TO INKSTER RD.
  T2 Q 10YR 50CTS 50YR 75 100YR 85 500YR 120 WATER ELEV HURON RIVER MEAN LEVEL
  T5       COOKE & GLADDING DR.-FLAT ROCK

  J1  ICHECK     INQ        NINV       IDIT       STRT       METPIC     HVINS      Q          WSEL       FQ
            0.        6.         3.         0.  0.000000       0.00       0.0        0.    585.400      0.000

  J2  NPROF      IPLCT      PRFVS      XSECV      XSECH         ZZ         ALLOC      ISW        CHNIN      ITRNCE
      15.000      0.000     -1.000      0.000      0.000      0.000      0.000      0.000      0.000      0.000
```

PRINTED IN U.S.A.
FORM 1411-GD PRINTED BY ROTARY MANIFOLD FORMS -

****

HEC2 RELEASE DATED NOV 75 UPDATED FEB 1977
ERROR CORR - 01
MODIFICATION - 50,51,52

****

NOTE- ASTERISK (*) AT LEFT OF CROSS-SECTION NUMBER INDICATES MESSAGE IN SUMMARY OF ERRORS LIST

COOKE & GLADDING DR.-FLA

SUMMARY PRINTOUT TABLE 150

SECNO	XLOB	ELTRD	ELLC	ELMIN	Q	CWSEL	CRIWS	EG	TOPWID	VCH	AREA	.01K
0.000	0.00	0.00	0.00	581.00	21.00	585.40	0.00	585.42	3.67	1.06	19.80	10.96
0.000	0.00	0.00	0.00	581.00	21.00	585.40	0.00	585.42	3.67	1.06	19.80	10.96
0.000	0.00	0.00	0.00	581.00	27.00	585.40	0.00	585.43	6.07	1.36	19.80	10.96
0.000	0.00	0.00	0.00	581.00	37.00	585.40	0.00	585.45	11.60	1.87	19.80	10.96
54.000	54.00	588.00	585.60	581.10	21.00	585.42	0.00	585.44	4.56	1.30	16.15	9.84
54.000	54.00	588.00	585.60	581.10	21.00	585.42	0.00	585.44	4.56	1.30	16.15	9.84
54.000	54.00	588.00	585.60	581.10	27.00	585.43	0.00	585.47	7.48	1.67	16.19	9.87
54.000	54.00	588.00	585.60	581.10	37.00	585.45	0.00	585.53	13.87	2.27	16.29	9.98
300.000	300.00	0.00	0.00	581.51	21.00	585.46	0.00	585.49	0.67	0.80	39.44	25.61
300.000	300.00	0.00	0.00	581.51	21.00	585.46	0.00	585.49	0.67	0.80	39.44	25.61
300.000	300.00	0.00	0.00	581.51	27.00	585.54	0.00	585.55	1.05	1.00	40.35	26.33
300.000	300.00	0.00	0.00	581.51	37.00	585.64	0.00	585.67	1.76	1.33	42.28	27.87
1300.000	1000.00	0.00	0.00	583.01	21.00	585.59	0.00	585.61	2.20	1.07	34.46	14.15
1300.000	1000.00	0.00	0.00	583.01	21.00	585.59	0.00	585.61	2.20	1.07	26.48	14.15
1300.000	1000.00	0.00	0.00	583.01	27.00	585.69	0.00	585.72	3.05	1.36	27.69	15.45
1300.000	1000.00	0.00	0.00	583.01	37.00	585.89	0.00	585.93	4.09	1.59	36.48	18.30
1600.000	300.00	0.00	0.00	585.29	21.00	585.73	0.00	585.84	51.59	2.30	10.82	3.74
1600.000	300.00	0.00	0.00	585.29	21.00	585.73	0.00	585.84	51.59	2.30	10.82	3.74
1600.000	300.00	0.00	0.00	585.29	27.00	585.83	0.00	585.93	36.67	2.49	12.19	4.34
1600.000	300.00	0.00	0.00	585.29	37.00	586.03	0.00	586.27	46.25	3.19	14.58	5.44
1700.000	100.00	0.00	0.00	585.14	21.00	586.26	0.00	586.52	175.39	4.09	5.13	1.59
1700.000	100.00	0.00	0.00	585.14	21.00	586.26	0.00	586.52	175.39	4.09	5.13	1.59
1700.000	100.00	0.00	0.00	585.14	27.00	586.40	0.00	586.78	162.05	4.33	6.26	2.12
1700.000	100.00	0.00	0.00	585.14	37.00	586.79	0.00	587.16	134.51	4.84	7.83	2.96
1836.000	136.00	592.80	588.90	586.24	21.00	587.91	0.00	588.03	73.57	2.84	7.40	2.45
1836.000	136.00	592.80	588.90	586.24	21.00	587.91	0.00	588.03	73.57	2.84	7.40	2.45
1836.000	136.00	592.80	588.90	586.24	27.00	588.09	0.00	588.25	82.53	3.22	8.44	2.97
1836.000	136.00	592.80	588.90	586.24	37.00	588.34	0.00	588.64	145.49	3.87	10.29	5.07
1861.000	25.00	0.00	0.00	586.24	21.00	588.10	0.00	588.15	24.53	1.95	15.54	4.24
1861.000	25.00	0.00	0.00	586.24	21.00	588.10	0.00	588.15	24.53	1.95	15.54	4.24
1861.000	25.00	0.00	0.00	586.24	27.00	588.43	0.00	588.47	19.66	1.95	21.36	6.09
1861.000	25.00	0.00	0.00	586.24	37.00	589.32	0.00	589.55	7.23	1.49	47.95	13.71

PRINTED IN U.S.A.
FORM 1411-GB PRINTED BY ROTARY MANIFOLD FORMS

	SECNO	XLCH	ELTRD	ELLC	ELMIN	Q	CWSEL	CRIWS	EG	10K*S	VCH	AREA	.01K
	2284.000	423.00	0.00	0.00	585.50	21.00	588.20	0.00	588.20	0.30	0.31	132.97	38.61
	2284.000	423.00	0.00	0.00	585.50	21.00	588.20	0.00	588.20	0.30	0.31	132.97	38.61
	2284.000	423.00	0.00	0.00	585.50	27.00	588.51	0.00	588.51	0.27	0.31	173.11	51.94
	2284.000	423.00	0.00	0.00	585.50	37.00	589.36	0.00	589.36	0.12	0.25	308.99	105.56
	2941.000	657.00	0.00	0.00	585.50	21.00	588.23	0.00	588.23	0.78	0.50	71.62	23.71
	2941.000	657.00	0.00	0.00	585.50	21.00	588.23	0.00	588.23	0.78	0.50	71.62	23.71
	2941.000	657.00	0.00	0.00	585.50	27.00	588.54	0.00	588.54	0.74	0.52	99.13	31.29
	2941.000	657.00	0.00	0.00	585.50	37.00	589.38	0.00	589.38	0.43	0.47	136.15	56.43
	3041.000	100.00	0.00	0.00	585.30	21.00	588.23	0.00	588.27	12.22	1.62	12.94	6.01
	3041.000	100.00	0.00	0.00	585.30	21.00	588.23	0.00	588.27	12.22	1.62	12.94	6.01
	3041.000	100.00	0.00	0.00	585.30	27.00	588.53	0.00	588.59	15.27	1.69	14.32	6.91
	3041.000	100.00	0.00	0.00	585.30	37.00	589.36	0.00	589.42	15.42	2.05	18.01	9.42
	3210.000	169.00	590.00	589.20	586.70	21.00	588.60	0.00	588.72	74.33	2.78	7.56	2.44
	3210.000	169.00	590.00	589.20	586.70	21.00	588.60	0.00	588.72	74.33	2.78	7.56	2.44
	3210.000	169.00	590.00	589.20	586.70	27.00	588.97	0.00	589.11	72.26	2.99	9.02	3.18
	3210.000	169.00	590.00	589.20	586.70	37.00	589.95	0.00	590.05	27.90	2.56	14.43	7.01
	3235.000	25.00	0.00	0.00	586.70	21.00	588.77	0.00	588.77	0.88	0.44	84.72	22.59
	3235.000	25.00	0.00	0.00	586.70	21.00	588.77	0.00	588.77	0.86	0.44	84.72	22.59
	3235.000	25.00	0.00	0.00	586.70	27.00	589.16	0.00	589.16	0.79	0.44	106.69	32.54
	3235.000	25.00	0.00	0.00	586.70	37.00	590.09	0.00	590.09	0.38	0.40	158.56	60.36
	3584.000	149.00	0.00	0.00	586.10	21.00	588.73	0.00	588.81	6.07	1.24	16.90	8.52
	3584.000	149.00	0.00	0.00	586.10	21.00	588.73	0.00	588.81	6.07	1.24	16.90	8.52
	3584.000	149.00	0.00	0.00	586.10	27.00	589.17	0.00	589.20	6.77	1.40	19.33	10.38
	3584.000	149.00	0.00	0.00	586.10	37.00	590.09	0.00	590.10	1.03	0.76	107.25	56.40
	3548.000	164.00	590.00	589.60	586.10	21.00	588.85	0.00	588.87	5.64	1.21	17.33	8.84
	3548.000	164.00	590.00	589.60	586.10	21.00	588.85	0.00	588.87	5.64	1.21	17.33	8.84
	3548.000	164.00	590.00	589.60	586.10	27.00	589.32	0.00	589.32	6.04	1.34	20.10	10.92
	3548.000	164.00	590.00	589.60	586.10	37.00	590.10	0.00	590.11	4.04	0.75	106.24	56.51
	3600.000	52.00	0.00	0.00	585.60	21.00	588.09	0.00	588.09	0.59	0.41	96.75	27.44
	3600.000	52.00	0.00	0.00	585.60	21.00	588.09	0.00	588.09	0.59	0.41	96.75	27.44
	3600.000	52.00	0.00	0.00	585.60	27.00	589.33	0.00	589.33	1.42	0.60	127.10	51.04
	3600.000	52.00	0.00	0.00	585.60	37.00	590.11	0.00	590.11	0.27	0.37	304.64	71.34
*	3792.000	192.00	0.00	0.00	587.70	21.00	588.75	585.73	589.19	523.02	5.36	3.92	3.92
*	3792.000	192.00	0.00	0.00	587.70	21.00	588.75	585.75	589.19	523.02	5.36	3.92	3.92
	3792.000	192.00	0.00	0.00	587.70	27.00	589.21	0.00	589.52	227.22	4.50	6.01	1.79
	3792.000	192.00	0.00	0.00	587.70	37.00	590.01	0.00	590.25	103.03	3.65	9.62	3.65
	3833.000	41.00	590.50	590.00	587.20	21.00	589.72	0.00	589.82	57.12	2.61	8.04	2.78
	3833.000	41.00	590.50	590.00	587.20	21.00	589.72	0.00	589.82	57.12	2.61	8.04	2.78
	3833.000	41.00	590.30	591.00	587.70	27.00	590.05	0.00	590.19	106.12	2.94	9.17	2.62
	3833.000	41.00	590.50	591.00	587.70	37.00	590.54	0.00	590.74	139.56	3.56	10.39	3.13
	3883.000	50.00	0.00	0.00	587.70	21.00	589.05	0.00	589.07	26.69	2.16	10.86	4.01
	3883.000	50.00	0.00	0.00	587.70	21.00	589.05	0.00	589.07	26.69	2.16	10.86	4.01
	3883.000	50.00	0.00	0.00	587.70	27.00	590.35	0.00	590.40	19.85	2.08	23.87	6.06
	3883.000	50.00	0.00	0.00	587.70	37.00	590.87	0.00	590.88	6.47	1.35	47.34	14.54

PRINTED IN U.S.A.
FORM 1411-OD PRINTED BY ROTARY MANIFOLD FORMS.

	SECNO	XLCH	ELTRD	ELLC	ELMIN	Q	CWSEL	CRIWS	EG	10K*S	VCH	AREA	.01K
	4337.000	454.00	0.00	0.00	587.50	21.00	590.17	0.00	590.17	1.04	0.58	63.06	20.63
1	4337.000	454.00	0.00	0.00	587.50	21.00	590.17	0.00	590.17	1.04	0.58	63.06	20.63
2	4337.000	454.00	0.00	0.00	587.50	27.00	590.52	0.00	590.53	0.89	0.59	82.70	28.65
3	4337.000	454.00	0.00	0.00	587.50	37.00	590.97	0.00	590.97	0.85	0.63	136.78	40.22
5	4437.000	100.00	0.00	0.00	587.35	21.00	590.18	0.00	590.20	8.34	1.35	15.54	7.27
6	4437.000	100.00	0.00	0.00	587.35	21.00	590.18	0.00	590.20	8.34	1.35	15.54	7.27
7	4437.000	100.00	0.00	0.00	587.35	27.00	590.53	0.00	590.57	9.37	1.54	17.48	8.59
8	4437.000	100.00	0.00	0.00	587.35	37.00	590.96	0.00	591.02	12.95	1.86	19.86	10.98
9													
10	4479.000	42.00	591.70	588.60	587.35	21.00	590.70	0.00	590.72	5.13	1.14	18.45	9.27
11	4479.000	42.00	591.70	588.60	587.35	21.00	590.70	0.00	590.72	5.13	1.14	18.45	9.27
12	4479.000	42.00	591.70	588.60	587.35	27.00	591.41	0.00	591.43	4.99	1.21	22.34	12.09
13	4479.000	42.00	591.70	588.60	587.35	37.00	591.81	0.00	591.85	7.26	1.51	24.53	13.75
14													
15	4504.000	25.00	0.00	0.00	587.35	21.00	590.73	0.00	590.73	0.52	0.43	69.05	29.15
16	4504.000	25.00	0.00	0.00	587.35	21.00	590.73	0.00	590.73	0.52	0.48	69.05	29.15
17	4504.000	25.00	0.00	0.00	587.35	27.00	591.44	0.00	591.44	0.31	0.42	128.09	48.49
18	4504.000	25.00	0.00	0.00	587.35	37.00	591.86	0.00	591.86	0.36	0.49	151.18	61.51
19													
20	4853.000	349.00	0.00	0.00	587.71	21.00	590.75	0.00	590.75	0.33	0.26	140.89	36.30
21	4853.000	349.00	0.00	0.00	587.71	21.00	590.75	0.00	590.75	0.33	0.26	140.69	36.38
22	4853.000	349.00	0.00	0.00	587.71	27.00	591.45	0.00	591.45	0.17	0.22	212.72	65.42
23	4853.000	349.00	0.00	0.00	587.71	37.00	591.87	0.00	591.87	0.19	0.25	255.77	85.98
24													
25	5053.000	200.00	0.00	0.00	586.37	21.00	590.75	0.00	590.75	0.31	0.37	75.44	37.43
26	5053.000	200.00	0.00	0.00	586.37	21.00	590.75	0.00	590.75	0.31	0.37	75.44	37.43
27	5053.000	200.00	0.00	0.00	586.37	27.00	591.45	0.00	591.46	0.30	0.40	89.82	49.01
28	5053.000	200.00	0.00	0.00	586.37	37.00	591.87	0.00	591.87	0.43	0.50	100.12	56.64
29													
30	5253.000	200.00	0.00	0.00	586.40	21.00	590.76	0.00	590.78	3.09	1.20	17.44	10.65
31	5253.000	200.00	0.00	0.00	586.40	21.00	590.76	0.00	590.78	3.09	1.20	17.44	10.65
32	5253.000	200.00	0.00	0.00	586.40	27.00	591.46	0.00	591.48	4.59	1.53	20.33	12.69
33	5253.000	200.00	0.00	0.00	586.40	37.00	591.92	0.00	591.93	6.76	1.69	21.00	14.23
34													
35	5299.000	46.00	594.40	590.30	587.30	21.00	590.78	0.00	590.85	58.26	2.00	10.50	2.75
36	5299.000	46.00	594.40	590.30	587.30	21.00	590.78	0.00	590.85	58.26	2.00	10.50	2.75
37	5299.000	46.00	594.40	590.30	587.30	27.00	591.90	0.00	592.01	16.07	1.44	16.70	5.31
38	5299.000	46.00	594.40	590.30	587.30	37.00	592.46	0.00	592.51	11.80	1.46	22.76	10.71
39													
40	5349.000	50.00	0.00	0.00	587.30	21.00	590.92	0.00	590.94	7.21	1.15	24.97	7.82
41	5349.000	50.00	0.00	0.00	587.30	21.00	590.92	0.00	590.94	7.21	1.15	24.97	7.82
42	5349.000	50.00	0.00	0.00	587.30	27.00	592.03	0.00	592.04	3.70	0.98	41.03	14.04
43	5349.000	50.00	0.00	0.00	587.30	37.00	592.93	0.00	592.53	3.12	1.01	57.35	20.94
44													
45	5676.000	327.00	0.00	0.00	587.28	21.00	590.99	0.00	591.00	0.73	0.50	55.42	24.60
46	5676.000	327.00	0.00	0.00	587.28	21.00	590.99	0.00	591.00	0.73	0.50	55.42	24.60
47	5676.000	327.00	0.00	0.00	587.28	27.00	592.06	0.00	592.08	0.47	0.48	76.12	39.54
48	5676.000	327.00	0.00	0.00	587.28	37.00	592.97	0.00	592.98	0.46	0.53	97.23	54.52
49													
50	5776.000	100.00	0.00	0.00	586.26	21.00	590.92	0.00	591.05	28.66	2.21	9.59	5.62
51	5776.000	100.00	0.00	0.00	586.26	21.00	590.78	0.00	591.05	28.66	2.21	9.51	5.62
52	5776.000	100.00	0.00	0.00	586.26	27.00	592.56	0.00	592.72	19.05	2.03	13.30	8.19
53	5776.000	100.00	0.00	0.00	586.26	37.00	592.55	0.00	593.03	20.93	2.25	16.62	8.39
54													
55													
56													
57													

PRINTED IN U.S.A.
FORM 1411-OD-PRINTED BY ROTARY MANIFOLD FORMS.

	SECNO.	XLCH	ELTRD	ELLC	ELMIN	Q	CLSEL	CRIWS	EG	10K*S	VCH	AREA	.01K
	5851.000	75.00	599.40	590.75	589.00	21.00	594.35	0.00	594.37	7.28	1.12	18.71	7.78
1	5851.000	75.00	599.40	590.75	589.00	21.00	594.35	0.00	594.37	7.28	1.12	18.71	7.78
2	5851.000	75.00	599.40	590.75	589.00	27.00	597.64	0.00	597.66	3.73	0.89	30.29	13.98
3	5851.000	75.00	599.40	590.75	589.00	37.00	599.84	0.00	599.86	4.13	0.97	37.97	18.20
4													
5	5876.000	25.00	0.00	0.00	589.39	21.00	594.37	0.00	594.37	0.07	0.19	204.61	79.70
6	5876.000	25.00	0.00	0.00	589.39	21.00	594.37	0.00	594.37	0.07	0.19	204.61	79.70
7	5876.000	25.00	0.00	0.00	589.39	27.00	597.66	0.00	597.66	0.02	0.14	375.58	202.57
8	5876.000	25.00	0.00	0.00	589.39	37.00	599.86	0.00	599.86	0.01	0.11	489.32	306.08
9													
10	5931.000	55.00	0.00	0.00	589.40	21.00	594.37	0.00	594.38	1.46	0.87	42.86	17.38
11	5931.000	55.00	0.00	0.00	589.40	21.00	594.37	0.00	594.38	1.46	0.87	42.86	17.33
12	5931.000	55.00	0.00	0.00	589.40	27.00	597.66	0.00	597.67	0.30	0.56	110.49	49.26
13	5931.000	55.00	0.00	0.00	589.40	37.00	599.86	0.00	599.86	0.14	0.44	243.73	100.22
14													
15	☆ 6006.000	75.00	100000.00	100000.00	589.40	21.00	596.00	0.00	596.02	6.75	1.06	19.85	8.00
16	☆ 6006.000	75.00	100000.00	100000.00	589.40	21.00	596.00	0.00	596.02	6.75	1.06	19.80	8.08
17	☆ 6006.000	75.00	100000.00	100000.00	589.40	27.00	597.73	0.00	597.74	0.54	0.75	86.70	36.79
18	☆ 6006.000	75.00	100000.00	100000.00	589.40	37.00	599.86	0.00	599.86	0.18	0.50	255.03	87.18
19													
20	6050.000	44.00	0.00	0.00	589.40	50.00	596.01	0.00	596.06	5.42	2.03	44.43	21.40
21	6050.000	44.00	0.00	0.00	589.40	75.00	596.00	0.00	596.11	12.32	3.06	66.19	21.37
22	6050.000	44.00	0.00	0.00	589.40	85.00	597.71	0.00	597.77	5.36	2.36	86.36	36.70
23	6050.000	44.00	0.00	0.00	589.40	120.00	599.86	0.00	599.87	1.89	1.63	255.10	87.21
24													
25	7934.000	1304.00	0.00	0.00	585.86	50.00	596.15	0.00	596.15	6.15	0.32	393.45	125.24
26	7934.000	1304.00	0.00	0.00	588.86	75.00	596.29	0.00	596.29	0.30	0.49	414.55	137.61
27	7934.000	1304.00	0.00	0.00	588.86	85.00	597.85	0.00	597.85	0.12	0.35	623.90	246.84
28	7934.000	1984.00	0.00	0.00	588.86	120.00	599.92	0.00	599.92	0.08	0.33	903.36	429.84
29													
30	8736.000	802.00	0.00	0.00	591.19	50.00	596.17	0.00	596.17	0.52	0.52	278.10	69.03
31	8736.000	802.00	0.00	0.00	591.19	75.00	596.33	0.00	596.33	0.95	0.79	360.16	76.56
32	8736.000	802.00	0.00	0.00	591.19	85.00	597.86	0.00	597.86	0.26	0.64	509.13	167.17
33	8736.000	802.00	0.00	0.00	591.19	120.00	599.92	0.00	599.92	0.13	0.36	756.79	329.65
34													
35	9734.000	1000.00	0.00	0.00	592.34	50.00	596.25	0.00	596.26	4.75	0.80	159.04	27.79
36	9734.000	1000.00	0.00	0.00	592.34	75.00	596.46	0.00	596.49	2.67	1.02	169.13	45.91
37	9734.000	1000.00	0.00	0.00	592.34	85.00	597.91	0.00	597.90	0.55	0.36	379.66	115.26
38	9734.000	1000.00	0.00	0.00	592.34	120.00	599.94	0.00	599.94	0.21	0.46	656.02	260.06
39													
40	10613.000	879.00	0.00	0.00	591.60	50.00	596.50	0.00	596.52	5.64	1.70	51.91	21.06
41	10613.000	879.00	0.00	0.00	591.60	75.00	596.83	0.00	596.86	7.41	2.03	89.61	27.56
42	10613.000	879.00	0.00	0.00	591.60	85.00	597.96	0.00	597.97	1.21	0.94	239.69	77.19
43	10613.000	879.00	0.00	0.00	591.60	120.00	599.96	0.00	599.96	0.27	0.53	504.60	231.20
44													
45	10713.000	100.00	0.00	0.00	591.60	50.00	596.35	0.00	596.38	5.26	1.83	56.24	21.80
46	10713.000	100.00	0.00	0.00	591.60	75.00	596.91	0.00	596.93	6.31	1.91	99.29	29.83
47	10713.000	100.00	0.00	0.00	591.60	85.00	597.97	0.00	597.98	1.20	0.93	240.59	77.72
48	10713.000	100.00	0.00	0.00	591.60	120.00	599.96	0.00	599.96	0.27	0.53	505.75	232.02
49													
50	11754.000	41.00	597.90	595.04	593.54	50.00	596.13	0.00	596.13	0.49	0.48	235.91	71.17
51	11754.000	41.00	597.90	595.04	593.54	75.00	596.33	0.00	596.33	0.35	0.67	214.85	77.61
52	11754.000	41.00	597.90	595.04	593.54	85.00	596.80	0.00	596.80	1.00	0.73	258.77	61.68
53	11754.000	41.00	597.90	595.04	593.54	120.00	597.39	0.00	597.39	0.30	0.47	402.67	218.50
54													
55													
56													
57													

PRINTED IN U.S.A.
FORM 1417-6B-PRINTED BY ROTARY MANIFOLD FORMS.

SECNO	XLCN	ELTRD	ELLC	ELMIN	Q	CWSEL	CRIWS	EG	TOK*S	VCH	AREA	.01K
10779.000	25.00	0.00	0.00	593.54	50.00	598.13	0.00	598.13	0.49	0.48	236.42	71.54
10779.000	25.00	0.00	0.00	593.54	75.00	598.24	0.00	598.24	0.92	0.67	250.57	73.07
10779.000	25.00	0.00	0.00	593.54	85.30	598.30	0.00	598.30	1.08	0.73	253.27	81.73
10779.000	25.00	0.00	0.00	593.56	120.00	599.99	0.00	599.99	0.30	0.47	482.44	218.48

COOKE & GLADDING DR.-FLA

SUMMARY PRINTOUT TABLE 150

SECNO	Q	CWSE'	DIFWSP	DIFWSX	DIFRWS	TOPWID	XLOA
0.000	21.00	585.40	0.00	0.00	0.00	4.50	0.00
0.000	21.00	585.40	0.00	0.00	0.00	4.50	0.00
0.000	27.00	585.40	0.00	0.00	0.00	4.50	0.00
0.000	37.00	585.40	0.00	0.00	0.00	4.50	0.00
54.000	21.00	585.42	0.00	0.02	0.00	4.50	54.00
54.000	21.00	585.42	0.00	0.02	0.00	4.50	54.00
54.000	27.00	585.43	0.00	0.03	0.00	4.50	54.00
54.000	37.00	585.45	0.00	0.05	0.00	4.50	54.00
300.000	21.00	585.48	0.00	0.07	0.00	17.36	300.00
300.000	21.00	585.48	0.00	0.07	0.00	17.36	300.00
300.000	27.00	585.54	0.00	0.11	0.00	17.55	300.00
300.000	37.00	585.64	0.00	0.19	0.00	17.94	300.00
1300.000	21.00	585.59	0.00	0.11	0.00	25.54	1000.00
1300.000	21.00	585.59	0.00	0.11	0.00	25.54	1000.00
1300.000	27.00	585.69	0.00	0.16	0.00	35.37	1000.00
1300.000	37.00	585.89	0.00	0.25	0.00	54.54	1000.00
1600.000	21.00	585.72	0.00	0.13	0.00	6.54	300.00
1600.000	21.00	585.72	0.00	0.13	0.00	6.54	300.00
1600.000	27.00	585.88	0.00	0.18	0.00	9.04	300.00
1300.000	37.00	586.13	0.00	0.24	0.00	9.86	300.00
1700.000	21.00	586.26	0.00	0.53	0.00	6.50	100.00
1700.000	21.00	586.26	0.01	0.53	0.00	6.50	100.00
1700.000	27.00	586.60	0.00	0.50	0.00	6.50	100.00
1700.000	37.00	586.79	0.00	0.66	0.00	6.50	100.00
1836.000	21.00	587.91	0.00	1.65	0.00	6.50	136.00
1836.000	21.00	587.91	0.00	1.65	0.00	6.50	136.00
1836.000	27.00	588.19	0.00	1.71	0.00	6.50	136.00
1836.000	37.00	589.04	0.01	2.20	0.00	6.50	136.00
1961.000	21.00	588.10	0.00	0.20	0.00	16.44	25.00
1961.000	21.00	588.10	0.00	0.20	0.00	16.44	25.00
1861.000	27.00	588.43	0.00	0.26	0.00	19.52	25.00
1861.000	37.00	589.32	0.00	0.28	0.00	20.44	25.00
2284.000	21.00	588.20	0.00	0.09	0.00	118.56	423.00
2284.000	21.00	588.20	0.00	0.09	0.00	118.56	423.00
2284.000	27.00	588.31	0.00	0.03	0.00	136.03	423.00
2284.000	37.00	589.36	0.00	0.04	0.00	176.10	423.00
2941.000	21.00	588.23	0.00	0.03	0.00	55.29	657.00
2941.000	21.00	588.23	0.00	0.03	0.00	55.29	657.00
2941.000	27.00	588.34	0.00	0.03	0.00	66.00	657.00
2941.000	37.00	589.38	0.00	0.01	0.00	56.70	657.00
3041.000	21.00	588.23	0.00	0.00	0.00	4.50	100.00
3041.000	21.00	588.23	0.00	0.00	0.00	4.50	100.00
3041.000	27.00	588.33	0.00	0.01	0.00	4.50	100.00
3041.000	37.00	589.36	0.00	0.02	0.00	4.50	100.00

PRINTED IN U.S.A.
FORM 1411-68-PRINTED BY ROTARY MANIFOLD FORMS

	SECNO	Q	CWSEL	DIFWSP	DIFWSX	DIFKWS	TOPWID	XLCH
	3210.000	21.00	588.60	0.00	0.38	0.00	4.50	169.00
	3210.000	21.00	588.60	0.00	0.38	0.00	4.50	169.00
	3210.000	27.00	588.97	0.00	0.44	0.00	4.50	169.00
	3210.000	37.00	589.95	0.00	0.99	0.00	4.50	169.00
	3235.000	21.00	588.77	0.00	0.16	0.00	56.00	25.00
	3235.000	21.00	588.77	0.00	0.16	0.00	56.00	25.00
	3235.000	27.00	589.16	0.00	0.19	0.00	56.00	25.00
	3235.000	37.00	590.09	0.00	0.13	0.00	56.00	25.00
	3384.000	21.00	588.78	0.00	0.02	0.00	6.30	149.00
	3384.000	21.00	588.78	0.00	0.02	0.00	6.30	149.00
	3384.000	27.00	589.17	0.00	0.01	0.00	6.30	149.00
	3384.000	37.00	590.09	0.00	0.01	0.00	72.01	149.00
	3548.000	21.00	588.85	0.00	0.07	0.00	6.30	164.00
	3548.000	21.00	588.85	0.00	0.07	0.00	6.30	164.00
	3548.000	27.00	589.29	0.00	0.12	0.00	6.30	164.00
	3548.000	37.00	590.10	0.00	0.01	0.00	72.01	164.00
	3600.000	21.00	588.89	0.00	0.03	0.00	67.73	52.00
	3600.000	21.00	588.89	0.00	0.03	0.00	67.73	52.00
	3600.000	27.00	589.33	0.00	0.04	0.00	69.35	52.00
	3600.000	37.00	590.11	0.00	0.01	0.00	79.37	52.00
*	3792.000	21.00	588.75	0.00	-0.14	0.00	4.49	192.00
*	3792.000	21.00	588.75	0.00	-0.14	0.00	4.49	192.00
	3792.000	27.00	589.21	0.00	-0.13	0.00	4.50	192.00
	3792.000	37.00	590.01	0.00	-0.10	0.00	4.50	192.00
	3883.000	21.00	588.72	0.00	0.97	0.00	4.50	41.00
	3883.000	21.00	588.72	0.00	0.97	0.00	4.50	41.00
	3883.000	27.00	589.05	0.00	0.85	0.00	4.50	41.00
	3883.000	37.00	590.54	0.00	1.39	0.00	4.50	41.00
	3883.000	21.00	588.95	0.00	0.24	0.00	7.01	50.00
	3883.000	21.00	588.95	0.00	0.24	0.00	7.01	50.00
	3883.000	27.00	589.35	0.00	0.25	0.00	82.27	50.00
	3883.000	37.00	590.67	0.00	0.35	0.00	88.98	50.00
	4337.000	21.00	588.17	0.00	0.21	0.00	55.00	454.00
	4337.000	21.00	588.17	0.00	0.21	0.00	55.00	454.00
	4337.000	27.00	588.52	0.00	0.16	0.00	55.00	454.00
	4337.000	37.00	588.97	0.00	0.10	0.00	55.00	454.00
	4437.000	21.00	588.18	0.00	0.01	0.00	5.50	100.00
	4437.000	21.00	588.18	0.00	0.01	0.00	5.50	100.00
	4437.000	27.00	588.53	0.00	0.00	0.00	5.50	100.00
	4437.000	37.00	588.96	0.00	-0.00	0.00	5.50	100.00
	4479.000	21.00	588.70	0.00	0.88	0.00	5.50	42.00
	4479.000	21.00	588.70	0.00	0.88	0.00	5.50	42.00
	4479.000	27.00	589.41	0.00	0.86	0.00	5.50	42.00
	4479.000	37.00	590.41	0.00	0.85	0.00	5.50	42.00

PRINTED IN U.S.A.
FORM 1411-QD PRINTED BY ROTARY MANIFOLD FORMS.

SECNO	Q	CRSEL	DIFWSP	DIFWSX	DIFKWS	TOPWID	XLCN
4504.000	21.00	590.73	0.00	0.03	0.00	55.00	25.00
4504.000	21.00	590.73	0.00	0.03	0.00	55.00	25.00
4504.000	27.00	591.44	0.00	0.03	0.00	55.00	25.00
4504.000	37.00	591.86	0.00	0.03	0.00	55.00	25.00
4853.000	21.00	590.75	0.00	0.02	0.00	101.32	349.00
4853.000	21.00	590.75	0.00	0.02	0.00	101.32	349.00
4853.000	27.00	591.45	0.00	0.01	0.00	102.93	349.00
4853.000	37.00	591.87	0.00	0.01	0.00	103.89	349.00
5053.000	21.00	590.75	0.00	0.01	0.00	22.49	200.00
5053.000	21.00	590.75	0.00	0.01	0.00	22.49	200.00
5053.000	27.00	591.45	0.00	0.00	0.00	24.33	200.00
5053.000	37.00	591.87	0.00	0.00	0.00	25.42	200.00
5253.000	21.00	590.76	0.00	0.01	0.00	4.00	200.00
5253.000	21.00	590.76	0.00	0.01	0.00	4.00	200.00
5253.000	27.00	591.46	0.00	0.00	0.00	4.00	200.00
5253.000	37.00	591.87	0.00	0.00	0.00	4.00	200.00
5299.000	21.00	590.78	0.00	0.04	0.00	4.00	46.00
5299.000	21.00	590.78	0.00	0.03	0.00	4.00	46.00
5299.000	27.00	591.98	0.00	0.52	0.00	4.00	46.00
5299.000	37.00	592.86	0.00	0.99	0.00	4.00	46.00
5349.000	21.00	590.92	0.01	0.14	0.00	12.61	50.00
5349.000	21.00	590.92	0.00	0.14	0.00	12.61	50.00
5349.000	27.00	592.03	0.00	0.03	0.00	16.51	50.00
5349.000	37.00	592.93	0.00	0.07	0.00	19.70	50.00
5676.000	21.00	590.92	0.00	0.07	0.00	19.46	327.00
5676.000	21.00	590.89	0.00	0.07	0.00	19.46	327.00
5676.000	27.00	592.01	0.00	0.03	0.00	22.30	327.00
5676.000	37.00	592.97	0.00	0.03	0.00	24.97	327.00
5776.000	21.00	590.98	0.00	-0.01	0.00	3.50	100.00
5776.000	21.00	590.98	0.00	-0.01	0.00	3.50	100.00
5776.000	27.00	592.06	0.00	-0.02	0.00	3.50	100.00
5776.000	37.00	592.95	0.00	-0.02	0.00	3.50	100.00
5851.000	21.00	594.35	0.00	3.37	0.00	3.50	75.00
5851.000	21.00	594.35	0.00	3.37	0.00	3.50	75.00
5851.000	27.00	597.65	0.00	5.59	0.00	3.50	75.00
5851.000	37.00	599.04	0.00	5.05	0.00	3.50	75.00
5876.000	21.00	594.37	0.00	0.03	0.00	52.00	25.00
5876.000	21.00	594.37	0.00	0.03	0.00	52.00	25.00
5876.000	27.00	597.66	0.00	0.02	0.00	52.00	25.00
5876.000	37.00	599.06	0.00	0.02	0.00	52.00	25.00
5931.000	21.00	594.37	0.00	-0.00	0.00	12.37	55.00
5931.000	21.00	594.37	0.00	-0.00	0.00	12.37	55.00
5931.000	27.00	597.66	0.00	-0.00	0.00	45.30	55.00
5931.000	37.00	599.06	0.00	-0.00	0.00	66.42	55.00

PRINTED IN U.S.A.
FORM 1411-OD PRINTED BY ROTARY MANIFOLD FORMS.

	SECNO	Q	CNSEL	DIFWSP	DIFWSX	DIFKWS	TOPWID	XLCH
*	6006.000	21.00	596.00	0.00	1.63	0.00	3.00	75.00
*	6006.000	21.00	596.00	0.00	1.63	0.00	3.00	75.00
*	6006.000	27.00	597.73	0.00	0.07	1.73	46.67	75.00
*	6006.000	37.00	599.86	0.00	-0.00	3.86	95.56	75.00
	6050.000	50.00	596.01	0.00	0.01	0.00	14.07	44.00
	6050.000	75.00	596.00	0.00	-0.00	-0.01	13.92	44.00
	6050.000	85.00	597.71	0.00	-0.02	1.71	46.41	44.00
	6050.000	120.00	599.86	0.00	-0.00	3.85	95.57	44.00
	7934.000	50.00	596.15	0.00	0.14	0.00	135.00	1884.00
	7934.000	75.00	596.29	0.00	0.30	0.14	135.00	1884.00
	7934.000	85.00	597.85	0.00	0.13	1.70	135.00	1884.00
	7934.000	120.00	599.92	0.00	0.06	3.77	135.00	1884.00
	8734.000	50.00	596.17	0.00	0.12	0.00	136.00	800.00
	8734.000	75.00	596.33	0.00	0.04	0.16	136.00	800.00
	8734.000	85.00	597.86	0.00	0.01	1.69	136.00	800.00
	8734.000	120.00	599.92	0.00	0.01	3.76	136.00	800.00
	9734.000	50.00	596.25	0.00	0.00	0.00	135.00	1000.00
	9734.000	75.00	596.40	0.00	0.14	0.22	135.00	1000.00
	9734.000	85.00	597.90	0.00	0.04	1.64	135.00	1000.00
	9734.000	120.00	599.94	0.00	0.02	3.69	135.00	1000.00
	10613.000	50.00	596.50	0.00	0.24	0.00	63.04	879.00
	10613.000	75.00	596.83	0.00	0.36	0.33	133.00	879.00
	10613.000	85.00	597.96	0.00	0.07	1.47	133.00	879.00
	10613.000	120.00	599.96	0.00	0.02	3.46	133.00	879.00
	10713.000	50.00	596.55	0.00	0.06	0.00	89.78	100.00
	10713.000	75.00	596.91	0.00	0.00	0.39	133.00	100.00
	10713.000	85.00	597.97	0.00	0.01	1.42	133.00	100.00
	10713.000	120.00	599.96	0.00	0.00	3.41	133.00	100.00
	10754.000	50.00	596.13	0.00	1.57	0.00	132.37	41.00
	10754.000	75.00	596.23	0.00	1.33	0.10	132.40	41.00
	10754.000	85.00	597.30	0.00	0.23	0.97	132.42	41.00
	10754.000	120.00	599.99	0.00	0.01	1.96	132.39	41.00
	10779.000	50.00	596.13	0.00	0.00	0.00	132.37	25.00
	10779.000	75.00	596.24	0.00	0.00	0.11	132.40	25.00
	10779.000	85.00	598.30	0.00	0.00	0.17	132.42	25.00
	10779.000	120.00	599.99	0.00	0.00	1.96	132.39	25.00

SUMMARY OF ERRORS

CAUTION SECNO= 3792.000 PROFILE= 1 CRITICAL DEPTH ASSUMED
CAUTION SECNO= 3792.000 PROFILE= 1 MINIMUM SPECIFIC ENERGY
CAUTION SECNO= 3792.000 PROFILE= 2 CRITICAL DEPTH ASSUMED
CAUTION SECNO= 3792.000 PROFILE= 2 MINIMUM SPECIFIC ENERGY

NOTE SECNO= 6006.000 PROFILE= 1 WSEL BASED ON XS CARD
NOTE SECNO= 6006.000 PROFILE= 2 WSEL BASED ON XS CARD
NOTE SECNO= 6006.000 PROFILE= 3 WSEL BASED ON XS CARD
NOTE SECNO= 6006.000 PROFILE= 4 WSEL BASED ON XS CARD

PRINTED IN U.S.A.
FORM 1411-GD-PRINTED BY ROTARY MANIFOLD FORMS.

FLOOD INSURANCE ZONE DATA FOR COOKE & GLADDING DR.-FLA

FLOOD HAZARD FACTOR FOR ENTIRE REACH USING SECTIONS

SECTION NUMBER	CUMULATIVE DISTANCE	ELEVATION DIFFERENCE BETWEEN BASE FLOOD AND 10¢	2¢	0.2¢
0.000	0.	0.0	0.0	0.0
54.000	54.	-0.3	-0.0	0.0
300.000	354.	-0.1	-0.1	0.1
1300.000	1354.	-0.1	-0.1	0.2
1600.000	1654.	-0.2	-0.2	0.3
1700.000	1756.	-0.2	-0.2	0.7
1836.000	1890.	-0.3	-0.3	0.9
1841.000	1895.	-0.3	-0.3	0.9
2284.000	2338.	-0.3	-0.3	0.9
2941.000	2995.	-0.3	-0.3	0.8
3041.000	3095.	-0.3	-0.3	0.8
3210.000	3264.	-0.4	-0.4	1.0
3255.000	3309.	-0.4	-0.4	0.9
3384.000	3438.	-0.4	-0.4	0.9
3548.000	3602.	-0.4	-0.4	0.8
3600.000	3654.	-0.4	-0.4	0.8
3792.000	3846.	-0.5	-0.5	0.8
3835.000	3887.	-0.5	-0.5	0.5
3883.000	3937.	-0.4	-0.4	0.5
4357.000	4391.	-0.4	-0.4	0.4
4437.000	4491.	-0.4	-0.4	0.4
4479.000	4533.	-0.7	-0.7	0.4
4504.000	4558.	-0.7	-0.7	0.4
4853.000	4907.	-0.7	-0.7	0.6
5055.000	5109.	-0.7	-0.7	0.6
5253.000	5307.	-0.7	-0.7	0.6
5299.000	5353.	-1.2	-1.2	0.9
5349.000	5403.	-1.1	-1.1	0.9
5676.000	5730.	-1.1	-1.1	0.9
5776.000	5830.	-1.1	-1.1	0.9
5851.000	5905.	-3.3	-3.3	2.2
5876.000	5930.	-3.3	-3.3	2.2
5951.000	5985.	-3.3	-3.3	2.2
6006.000	6060.	-1.7	-1.7	2.1
6050.000	6104.	-1.7	-1.7	2.1
7934.000	7988.	-1.7	-1.6	2.1
8734.000	8788.	-1.7	-1.6	2.1
9716.000	9770.	-1.5	-1.5	2.0
10613.000	10667.	-1.5	-1.1	2.0
10713.000	10767.	-1.4	-1.1	2.0
10754.000	10808.	-0.2	-0.1	1.7
10779.200	10833.	-0.2	-0.1	1.7
WEIGHTED AVG FOR REACH		-1.0	-0.9	1.2

FHF FOR THE REACH = 010 WITH 13.73 OF THE REACH WITHIN 0.5 FEET

ZONE FOR THE REACH = A 2

PRINTED IN U.S.A.
FORM 1411-GB-PRINTED BY ROTARY MANIFOLD FORMS

CONTINUOUS FLOOD HAZARD FACTORS BY EVEN INCREMENTS

INC NO.	TOTAL LENGTH	AVG ELEVATION DATA 100	10	DIFF.	WTD. AVG.	FHF	PERCENT WITHIN
	0.				SEC.	0.000	
1	100.	585.4	585.4	-0.0	-0.0	005	100.
	54.				SEC.	54.000	
2	200.	585.4	585.5	-0.0	-0.0	005	100.
3	300.	585.5	585.5	-0.0	-0.0	005	100.
	54.				SEC.	300.000	
4	400.	585.5	585.5	-0.0	-0.0	005	100.
5	500.	585.5	585.6	-0.1	-0.0	005	100.
6	600.	585.5	585.6	-0.1	-0.0	005	100.
7	700.	585.5	585.6	-0.1	-0.0	005	100.
8	800.	585.5	585.6	-0.1	-0.0	005	100.
9	900.	585.5	585.6	-0.1	-0.1	005	100.
10	1000.	585.5	585.6	-0.1	-0.1	005	100.
11	1100.	585.6	585.6	-0.1	-0.1	005	100.
12	1200.	585.6	585.7	-0.1	-0.1	005	100.
13	1300.	585.6	585.7	-0.1	-0.1	005	100.
	1354.				SEC.	1300.000	
14	1400.	585.6	585.7	-0.1	-0.1	005	100.
15	1500.	585.6	585.8	-0.1	-0.1	005	100.
16	1600.	585.7	585.8	-0.1	-0.1	005	100.
	1654.				SEC.	1600.000	
17	1700.	585.8	586.0	-0.2	-0.1	005	100.
	1754.				SEC.	1700.000	
18	1800.	586.4	586.6	-0.2	-0.1	005	100.
	1890.				SEC.	1336.000	
19	1900.	587.4	587.7	-0.3	-0.1	005	100.
	1915.				SEC.	1861.000	
20	2000.	588.1	588.4	-0.3	-0.1	005	100.
21	2100.	588.1	588.5	-0.3	-0.1	005	100.
22	2200.	588.2	588.5	-0.3	-0.1	005	100.
23	2300.	588.2	588.5	-0.3	-0.1	005	100.
	2338.				SEC.	2284.000	
24	2400.	588.2	588.5	-0.3	-0.1	005	100.
25	2500.	588.2	588.5	-0.3	-0.1	005	100.
26	2600.	588.2	588.5	-0.3	-0.2	005	100.
27	2700.	588.2	588.5	-0.3	-0.2	005	100.
28	2800.	588.2	588.5	-0.3	-0.2	005	100.
29	2900.	588.2	588.5	-0.3	-0.2	005	100.
	2945.				SEC.	2841.000	
30	3000.	588.2	588.5	-0.3	-0.2	005	100.
	3045.				SEC.	3041.000	
31	3100.	588.2	588.5	-0.3	-0.2	005	100.
32	3200.	588.3	588.7	-0.4	-0.2	005	100.
	3264.				SEC.	3210.000	
	3289.				SEC.	3235.000	
33	3300.	588.8	589.2	-0.4	-0.2	005	100.
34	3400.	588.8	589.2	-0.4	-0.2	005	100.
	3438.				SEC.	3384.000	
35	3500.	588.8	589.2	-0.4	-0.2	005	100.
36	3600.	588.8	589.3	-0.4	-0.2	005	100.
	3652.				SEC.	3548.000	
	3654.				SEC.	3600.000	
37	3700.	588.9	589.3	-0.4	-0.2	005	100.
38	3800.	588.9	589.3	-0.5	-0.2	005	100.
	3842.				SEC.	3792.000	
	3867.				SEC.	3833.000	
39	3900.	589.7	590.1	-0.5	-0.2	005	100.
	3957				SEC.	1803.000	

PRINTED IN U.S.A.
FORM 1411-00 PRINTED BY ROTARY MANIFOLD FORMS.

	40	4000.	589.9	590.2	-0.4	-0.2	005	100.
	41	4100.	590.0	590.4	-0.4	-0.2	005	100.
	42	4200.	590.1	590.4	-0.4	-0.2	005	100.
	43	4300.	590.1	590.5	-0.4	-0.2	005	100.
		4391.				SEC.	4337.000	
	44	4400.	590.1	590.5	-0.4	-0.2	005	100.
		4491.				SEC.	4437.000	
	45	4500.	590.2	590.6	-0.4	-0.2	005	100.
		4533.				SEC.	4479.000	
		4558.				SEC.	4504.000	
	46	4600.	590.7	591.4	-0.7	-0.3	005	100.
	47	4700.	590.7	591.4	-0.7	-0.3	005	100.
	48	4800.	590.7	591.4	-0.7	-0.3	005	100.
	49	4900.	590.7	591.4	-0.7	-0.3	005	100.
		4907.				SEC.	4853.000	
	50	5000.	590.7	591.5	-0.7	-0.3	005	100.
	51	5100.	590.8	591.5	-0.7	-0.3	005	100.
		5107.				SEC.	5053.000	
	52	5200.	590.8	591.5	-0.7	-0.3	005	100.
	53	5300.	590.8	591.5	-0.7	-0.3	005	100.
		5307.				SEC.	5253.000	
		5355.				SEC.	5299.000	
	54	5400.	590.4	592.0	-1.2	-0.3	005	98.
		5439.				SEC.	5349.000	
	55	5500.	590.9	592.0	-1.1	-0.3	005	96.
	56	5600.	591.0	592.1	-1.1	-0.4	005	95.
	57	5700.	591.0	592.1	-1.1	-0.4	005	93.
		5730.				SEC.	5676.000	
	58	5800.	591.0	592.1	-1.1	-0.4	005	91.
		5850.				SEC.	5774.000	
	59	5900.	592.6	594.7	-2.1	-0.4	005	90.
		5905.				SEC.	5851.000	
		5950.				SEC.	5876.000	
		5985.				SEC.	5931.000	
	60	6000.	594.5	597.7	-3.1	-0.5	005	88.
		6050.				SEC.	6006.000	
	61	6100.	595.4	597.7	-2.3	-0.5	005	87.
		6104.				SEC.	6050.000	
	62	6200.	596.0	597.7	-1.7	-0.5	005	85.
	63	6300.	596.0	597.7	-1.7	-0.5	005	81.
	64	6400.	596.0	597.7	-1.7	-0.5	005	78.
	65	6500.	596.0	597.7	-1.7	-0.6	005	72.
	66	6600.	596.0	597.7	-1.7	-0.6	005	67.
	67	6700.	596.0	597.8	-1.7	-0.6	005	64.
	68	6800.	596.1	597.8	-1.7	-0.6	005	63.
	69	6900.	596.1	597.8	-1.7	-0.6	005	61.
	70	7000.	596.1	597.8	-1.7	-0.6	005	59.
	71	7100.	596.1	597.8	-1.7	-0.7	005	58.
	72	7200.	596.1	597.8	-1.7	-0.7	005	57.
	73	7300.	596.1	597.8	-1.7	-0.7	005	56.
	74	7400.	596.1	597.8	-1.7	-0.7	005	55.
	75	7500.	596.1	597.8	-1.7	-0.7	005	53.
	76	7600.	596.1	597.8	-1.7	-0.7	005	53.
	77	7700.	596.1	597.8	-1.7	-0.7	005	52.
	78	7800.	596.1	597.8	-1.7	-0.8	010	51.
	79	7900.	596.1	597.8	-1.7	-0.8	010	51.
		7983.				SEC.	7934.000	
	80	8000.	596.1	597.8	-1.7	-0.8	010	49.
	81	8100.	596.2	597.8	-1.7	-0.8	010	48.
	82	8200.	596.2	597.8	-1.7	-0.8	010	48.
	83	8300.	596.2	597.9	-1.7	-0.8	010	46.
	84	8400.	596.2	597.9	-1.7	-0.8	010	32.
	85	8500.	596.2	597.9	-1.7	-0.8	010	30.
	86	8600.	596.2	597.9	-1.7	-0.8	010	30.

PRINTED IN U.S.A.
FORM 1411-OD PRINTED BY ROTARY MANIFOLD FORMS.

87	8700.	596.2	597.9	-1.7	-0.9	010	29.
	8780.				SEC.	8734.000	
88	8800.	596.2	597.9	-1.7	-0.9	010	20.
89	8900.	596.2	597.9	-1.7	-0.9	010	25.
90	9000.	596.2	597.9	-1.7	-0.9	010	23.
91	9100.	596.2	597.9	-1.7	-0.9	010	22.
92	9200.	596.2	597.9	-1.7	-0.9	010	18.
93	9300.	596.2	597.9	-1.7	-0.9	010	17.
94	9400.	596.2	597.9	-1.7	-0.9	010	17.
95	9500.	596.2	597.9	-1.7	-0.9	010	17.
96	9600.	596.2	597.9	-1.7	-0.9	010	16.
97	9700.	596.2	597.9	-1.6	-0.9	010	15.
	9788.				SEC.	9734.000	
98	9800.	596.3	597.9	-1.6	-0.9	010	15.
99	9900.	596.3	597.9	-1.6	-0.9	010	14.
100	10000.	596.3	597.9	-1.6	-1.0	010	13.
101	10100.	596.3	597.9	-1.6	-1.0	010	13.
102	10200.	596.4	597.9	-1.6	-1.0	010	13.
103	10300.	596.4	597.9	-1.5	-1.0	010	13.
104	10400.	596.4	597.9	-1.5	-1.0	010	13.
105	10500.	596.4	597.9	-1.5	-1.0	010	12.
106	10600.	596.5	598.0	-1.5	-1.0	010	12.
	10687.				SEC.	10613.000	
107	10700.	596.5	598.0	-1.5	-1.0	010	16.
	10797.				SEC.	10713.000	
108	10800.	597.2	598.1	-0.9	-1.0	010	15.
	10808.				SEC.	10754.000	
	10833.				SEC.	10779.000	

THIS REACH CAN BE SUBDIVIDED BY INC NO. TO MEET FIA REQUIREMENTS
INPUT 20N WHERE N IS THE NUMBER OF REACHES AND THEN INPUT THE END
OF EACH REACH BY INC NO. FOR EXAMPLE: 202 63 100
A NEGATIVE INC NO. WILL SUPPRESS INTERMEDIATE INC OUTPUT.

PRINTED IN U.S.A.
FORM 1411-GD PRINTED BY ROTARY MANIFOLD FORMS.

00BREAK00

1) COUNTY: Wayne

2) STUDY NAME: City of Flat Rock

3) WATERCOURSE: Cook and Gladding Drain

Rating

4) DOCUMENT TYPE: Curve

00BREAK00

```
**************************************************
  HEC2 RELEASE DATED NOV 76 UPDATED FEB 1977
  ERROR CORR -- 01
  MODIFICATION -- 50,51,52
**************************************************
```

HUD 2009 07

9/13/79

T1OVERLAND FLOW RATING CURVE
T2COOKE & GLADDING DRAIN TO SILVER CREEK
T3 OVERLAND #1. RATING CURVE.

Appears to be 100 yr. flp. on Cooke, Gladding, reasonable ✓

J1	ICHECK	INQ	NINV	IDIR	STRT	METRIC	HVINS	Q	WSEL	FQ
	0.	2.	0.	0.	0.000000	0.00	0.0	0.	597.800	0.000

J2	NPROF	IPLOT	PRFVS	XSECV	XSECH	FN	ALLDC	IBW	CHNIM	ITRACE
	1.000	0.000	-1.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000

J5	LPRNT	NUMSEC	********REQUESTED SECTION NUMBERS********								
	-10.000	-10.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	
QT		9.000	50.000	100.000	150.000	200.000	250.000	300.000	350.000	400.000	500.000
NC		0.250	0.250	0.250	0.300	0.500	0.000	0.000	0.000	0.000	0.000
X1		2.000	5.000	1.000	1200.000	500.000	500.000	500.000	0.000	0.000	0.000
GR		999.000	1.000	600.000	100.000	597.000	550.000	600.000	1000.000	999.000	1200.000
X1		3.000	5.000	1.000	450.000	350.000	700.000	500.000	0.000	0.000	0.000
GR		999.000	1.000	600.000	50.000	598.000	200.000	600.000	300.000	999.000	450.000
X1		4.000	8.000	250.000	253.000	1050.000	1250.000	1150.000	0.000	0.000	0.000
X3		10.000	0.000	0.000	0.000	0.000	0.000	0.000	598.500	598.500	0.000
GR		1000.000	1.000	598.000	1.000	598.000	250.000	592.000	250.000	592.000	253.000
GR		598.000	253.000	598.000	800.000	1000.000	800.000	0.000	0.000	0.000	0.000
SB		1.000	2.170	3.000	800.000	2.500	0.100	7.000	0.000	592.000	592.000
X1		5.000	0.000	0.000	0.000	100.000	100.000	100.000	0.000	0.000	0.000
X2		0.000	0.000	1.000	595.000	600.000	0.000	0.000	0.000	0.000	0.000
X3		10.000	0.000	0.000	0.000	0.000	0.000	0.000	600.000	600.000	0.000
EJ		0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000

****
HEC2 RELEASE DATED NOV 76 UPDATED FEB 1977
ERROR CORR - 01
MODIFICATION - 50,51,52
****

NOTE- ASTERISK (*) AT LEFT OF CROSS-SECTION NUMBER INDICATES MESSAGE IN SUMMARY OF ERRORS LIST

OVERLAND #1, RATING CURV

SUMMARY PRINTOUT TABLE 150

	SECNO	XLCH	ELTRD	ELLC	ELMIN	Q	CWSEL	CRIWS	EG	10K*S	VCH	AREA	.01K
	2.000	500.00	0.00	0.00	597.00	50.00	597.80	0.00	597.80	260.43	0.52	96.01	3.10
	2.000	500.00	0.00	0.00	597.00	100.00	597.80	0.00	597.82	1041.73	1.04	96.01	3.10
	2.000	500.00	0.00	0.00	597.00	150.00	597.80	0.00	597.84	2343.90	1.56	96.01	3.10
	2.000	500.00	0.00	0.00	597.00	200.00	597.80	0.00	597.87	4166.93	2.08	96.01	3.10
	2.000	500.00	0.00	0.00	597.00	250.00	597.80	0.00	597.91	6510.83	2.60	96.01	3.10
	2.000	500.00	0.00	0.00	597.00	300.00	597.80	0.00	597.95	9375.60	3.12	96.01	3.10
	2.000	500.00	0.00	0.00	597.00	350.00	597.80	597.80	598.01	12555.54	3.62	96.60	3.12
	2.000	500.00	0.00	0.00	597.00	500.00	597.93	597.93	598.16	11740.43	3.86	129.44	4.61
	3.000	500.00	0.00	0.00	598.00	50.00	599.87	0.00	599.87	16.08	0.23	219.21	12.47
	3.000	500.00	0.00	0.00	598.00	100.00	600.37	0.00	600.37	16.09	0.29	341.46	24.93
	3.000	500.00	0.00	0.00	598.00	150.00	600.71	0.00	600.72	16.87	0.35	429.82	36.52
	3.000	500.00	0.00	0.00	598.00	200.00	601.01	0.00	601.01	17.72	0.40	503.86	47.52
	3.000	500.00	0.00	0.00	598.00	250.00	601.27	0.00	601.28	18.54	0.44	568.76	58.07
	3.000	500.00	0.00	0.00	598.00	300.00	601.52	599.07	601.52	19.26	0.48	627.70	68.35
	3.000	500.00	0.00	0.00	598.00	350.00	601.73	599.14	601.73	19.82	0.51	683.18	78.62
	3.000	500.00	0.00	0.00	598.00	500.00	602.28	599.31	602.28	22.07	0.61	820.81	106.45
	4.000	1150.00	0.00	0.00	592.00	50.00	599.92	0.00	599.92	0.12	0.03	1550.85	141.62
	4.000	1150.00	0.00	0.00	592.00	100.00	600.45	0.00	600.45	0.22	0.04	1978.24	212.44
	4.000	1150.00	0.00	0.00	592.00	150.00	600.83	0.00	600.83	0.31	0.05	2280.40	269.19
	4.000	1150.00	0.00	0.00	592.00	200.00	601.15	0.00	601.15	0.39	0.06	2533.60	320.78
	4.000	1150.00	0.00	0.00	592.00	250.00	601.44	0.00	601.44	0.45	0.06	2763.78	370.75
	4.000	1150.00	0.00	0.00	592.00	300.00	601.70	598.53	601.70	0.51	0.07	2974.46	418.96
	4.000	500.00	0.00	0.00	597.00	400.00	597.84	597.84	598.06	12532.08	3.74	106.85	3.57
	4.000	1150.00	0.00	0.00	592.00	500.00	602.53	598.56	602.53	0.73	0.08	3636.91	585.36
	5.000	100.00	600.00	595.00	592.00	50.00	600.06	0.00	600.06	0.10	0.03	1664.38	159.31
	5.000	100.00	600.00	595.00	592.00	100.00	600.46	0.00	600.46	0.22	0.04	1981.75	213.06
*	5.000	100.00	600.00	595.00	592.00	150.00	600.84	0.00	600.84	0.31	0.05	2285.28	270.15
*	5.000	100.00	600.00	595.00	592.00	200.00	601.16	0.00	601.16	0.38	0.06	2541.40	322.42
	5.000	100.00	600.00	595.00	592.00	250.00	601.45	0.00	601.45	0.45	0.06	2772.56	372.71
	5.000	100.00	600.00	595.00	592.00	300.00	601.71	0.00	601.71	0.51	0.07	2984.01	421.20
	5.000	500.00	0.00	0.00	598.00	400.00	601.93	599.20	601.93	20.60	0.55	732.06	88.12
	5.000	100.00	600.00	595.00	592.00	500.00	602.55	0.00	602.55	0.72	0.08	3649.78	568.81

```
**************************************************
  HEC2 RELEASE DATED NOV 76 UPDATED FEB 1977
  ERROR CORR - 01
  MODIFICATION -  50,51,52
**************************************************
```

1140 200907
9/13/79

```
C
T1      OVERLAND FLOW RATING CURVE BETWEEN HURON RIVER & COOKE & GLADDING.
T2      FLATROCK FIS
T3      OVERLAND FL.RATING CURVE.
```

J1	ICHECK	INQ	NINV	IDIR	STRT	METRIC	HVINS	Q	WSEL	FQ
	0.	2.	0.	0.	0.000000	0.00	0.0	0.	596.000	0.000

50yr on Huron?

J2	NPROF	IPLOT	PRFVS	XSECV	XSECH	FN	ALLDC	IBW	CHNIM	ITRACE
	1.000	0.000	-1.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000

J3	LPRNT	NUMSEC	********REQUESTED SECTION NUMBERS********								
	-10.000	-10.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	
QT	9.000	10.000	25.000	50.000	75.000	100.000	150.000	175.000	200.000	250.000	
NC	0.200	0.200	0.200	0.000	0.000	0.000	0.000	0.000	0.000	0.000	

```
        HURON RIVER DRIVE.
```

X1	2.000	6.000	1.000	2051.000	400.000	1200.000	900.000	0.000	0.000	0.000	
GR	605.000	1.000	600.000	400.000	595.000	800.000	595.000	1800.000	596.000	2050.000	
GR	605.000	2051.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	

```
        CONTROL SECTION FOR OVERLAND FLOW RATING CURVE.
```

X1	3.000	5.000	1.000	2200.000	350.000	350.000	350.000	0.000	0.000	0.000	
GR	605.000	1.000	600.000	700.000	595.000	1350.000	595.000	2150.000	605.000	2200.000	
EJ	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	

FORM 1411 GB PRINTED BY ROTARY KIMFOLD FOR IS

```
**************************************************
  HEC2 RELEASE DATED NOV 76 UPDATED FEB 1977
  ERROR CORR -  01
  MODIFICATION -  50,51,52
**************************************************
```

NOTE- ASTERISK (*) AT LEFT OF CROSS-SECTION NUMBER INDICATES MESSAGE IN SUMMARY OF ERRORS LIST

OVERLAND FL,RATING CURVE

SUMMARY PRINTOUT TABLE 150

SECNO	XLCH	ELTRD	ELLC	ELMIN	Q	CWSEL	CRIWS	EG	10K*S	VCH	AREA
2.000	900.00	0.00	0.00	595.00	10.00	596.00	0.00	596.00	0.02	0.01	1165.00
2.000	900.00	0.00	0.00	595.00	25.00	596.00	0.00	596.00	0.10	0.02	1165.00
2.000	900.00	0.00	0.00	595.00	50.00	596.00	0.00	596.00	0.40	0.04	1165.00
2.000	900.00	0.00	0.00	595.00	75.00	596.00	0.00	596.00	0.90	0.06	1165.00
2.000	900.00	0.00	0.00	595.00	100.00	596.00	0.00	596.00	1.59	0.09	1165.00
2.000	900.00	0.00	0.00	595.00	150.00	596.00	0.00	596.00	3.58	0.13	1165.00
2.000	900.00	0.00	0.00	595.00	175.00	596.00	0.00	596.00	4.88	0.15	1165.00
2.000	900.00	0.00	0.00	595.00	200.00	596.00	0.00	596.00	6.37	0.17	1165.00
2.000	900.00	0.00	0.00	595.00	250.00	596.00	0.00	596.00	9.95	0.21	1165.00
3.000	350.00	0.00	0.00	595.00	10.00	596.00	0.00	596.00	0.03	0.01	867.96
3.000	350.00	0.00	0.00	595.00	25.00	596.00	0.00	596.00	0.16	0.03	870.70
3.000	350.00	0.00	0.00	595.00	50.00	596.02	0.00	596.02	0.63	0.06	880.52
3.000	350.00	0.00	0.00	595.00	75.00	596.04	0.00	596.04	1.35	0.08	896.78
3.000	350.00	0.00	0.00	595.00	100.00	596.06	0.00	596.07	2.21	0.11	919.76
3.000	350.00	0.00	0.00	595.00	150.00	596.13	0.00	596.13	4.00	0.15	985.89
3.000	350.00	0.00	0.00	595.00	175.00	596.17	0.00	596.17	4.76	0.17	1029.03
3.000	350.00	0.00	0.00	595.00	200.00	596.21	0.00	596.21	5.50	0.19	1070.32
3.000	350.00	0.00	0.00	595.00	250.00	596.29	0.00	596.29	6.99	0.22	1143.65

```
**************************************************
   HEC2 RELEASE DATED NOV 76 UPDATED FEB 1977
   ERROR CORR -  U1
   MODIFICATION -  50,51,52
**************************************************
```

Cooke + Gladding Rating Curve

```
C
T1CITY OF FLAT ROCK FIS HUD 2009 07 HURON RIVER WITHIN FLAT ROCK
T2 Q10YR#6480 50#8750 100#10390 500#12100 CFS   1968 STORM PROFILE Q# 7700 CFS.
T3       HURON R.-FLAT ROCK                FROM ROCKWOOD FIS

J1  ICHECK     INQ       NINV      IDIR      STRT      METRIC    HVINS     Q         WSEL      FQ
         0.       2.        0.        0.  0.000000      0.00      0.0       0.   585.600     0.000

J2  NPROF      IPLOT     PRFVS     XSECV     XSECH     FN        ALLDC     IBW       CHNIM     ITRACE
     1.000     0.000    -1.000     0.000     0.000     0.000     0.000     0.000     0.000     0.000

J5  LPRNT      NUMSEC                    ********REQUESTED SECTION NUMBERS********
    -10.000   -10.000     0.000     0.000     0.000     0.000     0.000     0.000     0.000     0.000
QT    5.000    70.000    85.000   100.000   120.000   120.000     0.000     0.000     0.000     0.000
NC    0.060     0.060     0.035     0.300     0.500     0.000     0.000     0.000     0.000     0.000
ET    0.000     0.000     0.000     0.000     9.100     0.000     0.000     0.000     1.000   151.000


      D/S FACE OF HURON RIVER DRIVE.

X1    0.000     8.000    75.000    79.500     0.000     0.000     0.000     0.000     0.000     0.000
X3   10.000     0.000     0.000     0.000     0.000     0.000     0.000   586.000   586.000     0.000
GR  597.000     0.000   588.000     1.000   588.000    75.000   581.000    75.000   581.000    79.500
GR  588.000    79.500   588.000   150.000   597.000   151.000     0.000     0.000     0.000     0.000
SB    0.000     1.500     3.000     0.000     3.530     0.000    15.900     0.000   581.100   581.000
NC    0.060     0.080     0.035     0.000     0.000     0.000     0.000     0.000     0.000     0.000


                U/S FACE HURON RIVER DRIVE

X1   54.000    14.000    88.000    92.500    54.000    54.000    54.000     0.000     0.000     0.000
X2    0.000     0.000     1.000   585.600   588.000     0.000     0.000     0.000     0.000     0.000
X3   10.000     0.000     0.000     0.000     0.000     0.000     0.000   588.000   588.000     0.000
BT   12.000     0.000   597.000     0.000     1.000   588.000     0.000    35.000   588.000     0.000
BT   36.000   597.000     0.000    66.000   597.000     0.000    67.000   588.000     0.000    88.000
BT  588.000   583.350    89.000   588.000   585.600    91.500   588.000   585.600    92.500   588.000
BT  583.350   175.000   588.000     0.000   176.000   597.000     0.000     0.000     0.000     0.000
GR  597.000     0.000   588.000     1.000   585.700    35.000   597.000    36.000   597.000    66.000
GR  585.300    67.000   585.000    81.000   583.350    88.000   581.100    89.000   581.100    91.500
GR  583.350    92.500   585.000   100.000   588.000   175.000   597.000   176.000     0.000     0.000
ET    0.000     0.000     0.000     0.000     1.400     0.000     0.000     0.000     0.000     0.000


      VALLEY SECTION BASED ON FIELD BOOK SECTION 10434

X1  300.000    21.000   297.000   303.000   300.000   300.000   300.000     0.000     0.000     0.000
GR  597.000     0.000   590.000     0.100   589.000   110.000   596.000   110.100   596.000   139.900
GR  589.000   140.000   588.660   158.000   587.660   200.000   586.460   290.000   582.260   297.000
GR  581.510   300.000   582.360   303.000   586.010   310.000   587.360   318.000   587.560   350.000
GR  595.500   350.100   595.500   369.900   587.600   370.000   588.000   390.000   596.000   390.100
GR  596.000   420.000     0.000     0.000     0.000     0.000     0.000     0.000     0.000     0.000
```

NC	0.000	0.000	0.000	0.100	0.300	0.000	0.000	0.000	0.000	0.000

VALLEY SECTION BASED ON FIELD BOOK SECTION 9434

X1	1300.000	17.000	276.000	284.000	1000.000	1000.000	1000.000	0.000	0.000	0.000
GR	600.000	0.000	600.000	50.000	608.000	50.100	608.000	79.900	599.940	80.000
GR	593.490	180.000	585.810	273.000	583.660	276.000	583.010	280.000	583.660	284.000
GR	585.460	287.000	586.310	365.000	588.510	401.000	596.500	401.100	596.500	431.000
GR	588.600	431.100	590.000	590.000	0.000	0.000	0.000	0.000	0.000	0.000
NC	0.080	0.080	0.050	0.300	0.500	0.000	0.000	0.000	0.000	0.000

X@SECTION D/S GIBRALTAR RD.BASED ON FIELD BOOK " QUAD MAP

X1	1600.000	17.000	297.500	302.100	300.000	300.000	300.000	0.000	0.000	0.000
GR	604.000	0.000	596.000	0.100	595.400	80.000	603.400	80.100	603.400	110.000
GR	595.000	110.100	593.000	289.500	584.500	297.500	583.290	300.000	584.500	302.100
GR	589.500	313.500	590.000	400.000	590.500	450.000	598.500	450.100	598.500	480.000
GR	592.000	480.100	590.000	600.000	0.000	0.000	0.000	0.000	0.000	0.000
ET	0.000	0.000	0.000	0.000	9.100	0.000	0.000	0.000	1.000	600.000

D/S FACE OF GIBRALTAR RD. REPEATED SECT 1600

X1	1700.000	0.000	0.000	0.000	100.000	100.000	100.000	0.000	0.000	[illegible]
X3	10.000	585.140	0.000	0.000	0.000	0.000	0.000	590.000	590.000	[illegible]
SB	0.000	2.980	3.000	0.000	3.590	0.000	9.540	0.000	586.240	58[illegible].140
NC	0.000	0.000	0.045	0.000	0.000	0.000	0.000	0.000	0.000	[illegible]

U/S FACE OF GIBRALTAR RD.

X1	1836.000	16.000	295.000	299.600	136.000	136.000	136.000	0.000	0.000	[illegible]
X2	0.000	0.000	1.000	588.900	592.800	0.000	0.000	0.000	0.000	[illegible]
X3	10.000	586.240	0.000	0.000	0.000	0.000	0.000	593.400	593.400	[illegible]
BT	16.000	0.000	596.000	0.000	125.000	595.000	0.000	282.000	593.300	[illegible]
BT	295.000	592.800	586.900	295.300	592.800	587.900	295.800	592.800	588.500	29[illegible]
BT	592.800	588.700	297.300	592.800	588.900	298.100	592.800	588.700	298.800	59[illegible]
BT	588.500	299.400	592.800	587.900	299.600	592.800	586.900	323.000	593.000	[illegible]
BT	450.000	593.300	0.000	600.000	593.500	0.000	650.000	594.000	0.000	[illegible]
GR	596.000	0.000	595.000	125.000	593.300	282.000	586.900	295.000	585.700	29[illegible]
GR	585.000	295.800	584.700	296.500	584.390	297.300	584.700	298.100	585.000	29[illegible]
GR	585.700	299.400	586.900	299.600	589.900	323.000	590.000	450.000	592.000	60[illegible]
GR	594.000	650.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	[illegible]
NC	0.000	0.000	0.050	0.000	0.000	0.000	0.000	0.000	0.000	[illegible]
ET	0.000	0.000	0.000	0.000	1.400	0.000	0.000	0.000	0.000	[illegible]

X@SECT.U/S OF GIBRALTAR RD. REPEATED SECT.

X1	1861.000	0.000	0.000	0.000	25.000	25.000	25.000	0.000	0.000	[illegible]
X3	0.000	0.000	0.000	270.000	0.000	325.000	0.000	0.000	0.000	[illegible]
NC	0.000	0.000	0.000	0.100	0.300	0.000	0.000	0.000	0.000	[illegible]

VALLEY SECTION BASED ON FIELD BOOK SECTION 8450

X1	2284.000	11.000	293.000	307.000	423.000	423.000	423.000	0.000	0.000	0.[illegible]
GR	598.970	0.000	598.620	100.000	590.890	200.000	586.500	289.000	585.600	293.[illegible]
GR	585.500	300.000	585.300	307.000	586.600	312.000	588.900	400.000	595.500	500.[illegible]
GR	596.500	600.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.[illegible]

100 FEET D/S OF 54" CULVERT

X1	2941.000	15.000	214.000	224.000	657.000	657.000	657.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	0.000	0.000	376.000	0.000	0.000	0.000	0.000
GR	600.000	0.000	595.000	90.000	590.000	160.000	587.200	210.000	585.900	214.000
GR	585.500	217.250	585.500	220.750	585.900	224.000	587.000	228.000	587.500	350.000
GR	595.000	350.100	595.000	380.000	587.600	380.100	590.000	400.000	592.000	500.000
NC	0.000	0.000	0.000	0.300	0.500	0.000	0.000	0.000	0.000	0.000
ET	0.000	0.000	0.000	0.000	9.100	0.000	0.000	0.000	1.000	352.000

D/S FACE OF 54" CULVERT

X1	3041.000	12.000	214.000	218.500	100.000	100.000	100.000	0.000	0.000	0.000
X3	10.000	585.300	0.000	0.000	0.000	0.000	0.000	589.500	589.500	0.000
GR	600.000	0.000	600.000	160.000	590.000	165.000	587.200	210.000	585.550	214.000
GR	583.300	215.000	583.300	217.500	585.550	218.500	587.000	228.000	587.500	350.000
GR	590.000	351.000	595.000	352.000	0.000	0.000	0.000	0.000	0.000	0.000
SB	0.000	3.010	3.000	0.000	3.160	0.000	7.900	0.000	586.700	585.300

U/S END 54) CULVERT REPEATED SECT

X1	3210.000	12.000	214.000	218.500	169.000	169.000	169.000	0.000	0.000	0.000
X2	0.000	0.000	1.000	589.200	590.000	0.000	0.000	0.000	0.000	0.000
X3	10.000	586.700	0.000	0.000	0.000	0.000	0.000	590.000	590.000	0.000
BT	9.000	0.000	600.000	0.000	160.000	600.000	0.000	165.000	590.000	0.000
BT	214.000	590.000	586.950	215.000	590.000	589.200	217.500	590.000	589.200	218.500
BT	590.000	586.950	351.000	590.000	0.000	352.000	595.000	0.000	0.000	0.000
GR	600.000	0.000	600.000	160.000	590.000	165.000	587.200	210.000	586.950	214.000
GR	584.700	215.000	584.700	217.500	586.850	218.500	587.000	228.000	587.500	350.000
GR	590.000	351.000	595.000	352.000	0.000	0.000	0.000	0.000	0.000	0.000
ET	0.000	0.000	0.000	0.000	1.400	0.000	0.000	0.000	0.000	0.000

X@SECTION BETWEEN 54)CULVERT " SHEEKS RD CULVERT

X1	3255.000	0.000	0.000	0.000	25.000	25.000	25.000	0.000	0.000	0.000
ET	0.000	0.000	0.000	0.000	9.100	0.000	0.000	0.000	176.000	405.000

D/S END SHEEKS RD. CULVERT

X1	3584.000	11.000	257.000	263.300	149.000	149.000	149.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	589.000	589.000	0.000
GR	600.000	232.000	600.000	232.000	590.000	233.000	588.600	255.000	586.100	257.000
GR	586.100	259.000	586.100	261.500	586.100	263.300	588.600	265.000	589.500	405.000
GR	600.000	405.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
SB	0.000	3.320	3.000	0.000	3.820	0.000	15.800	1.000	586.100	586.100

U/S FACE OF SHEEKS RD CULVERT (76"X 48" ELLIPTICAL CONCRETE)

X1	3548.000	0.000	0.000	0.000	164.000	164.000	164.000	0.000	0.000	0.000
X2	0.000	0.000	1.000	588.600	590.000	0.000	0.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	590.000	590.000	0.000
BT	12.000	232.000	600.000	0.000	232.000	600.000	0.000	233.000	590.000	0.000
BT	255.000	590.000	0.000	257.000	590.000	586.100	257.000	590.000	587.400	259.000
BT	590.000	588.600	261.500	590.000	588.600	263.300	590.000	587.400	263.300	590.000
BT	586.100	405.000	589.500	0.000	405.000	600.000	0.000	0.000	0.000	0.000
ET	0.000	0.000	0.000	0.000	1.400	0.000	0.000	0.000	0.000	0.000

X@SECT. U/S OF SHEEKS RD.AND D/S OF SENECA RD.

X1	3600.000	9.000	196.000	204.000	52.000	52.000	52.000	0.000	0.000	0.000
GR	600.000	0.000	595.000	100.000	589.500	185.000	586.500	196.000	586.400	200.000
GR	586.500	204.000	587.500	210.000	588.300	334.000	600.000	334.000	0.000	0.000
ET	0.000	0.000	0.000	0.000	9.100	0.000	0.000	0.000	1.000	310.000

D/S END SENECA RD. CULVERT

X1	3792.000	10.000	223.000	227.500	192.000	192.000	192.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	591.300	590.100	0.000
GR	600.000	0.000	595.000	100.000	591.000	221.000	588.750	223.000	587.700	224.000
GR	587.700	227.000	588.750	227.500	590.000	229.000	590.500	310.000	600.000	310.000
SB	0.000	1.630	3.000	0.000	2.710	0.000	12.200	0.000	587.700	587.700

U/S FACE OF SENECA RD. CULVERT

X1	3833.000	0.000	0.000	0.000	41.000	41.000	41.000	0.000	0.000	0.000
X2	0.000	0.000	1.000	591.000	590.500	0.000	0.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	591.800	590.500	0.000
BT	8.000	0.000	600.000	0.000	100.000	595.000	0.000	223.000	591.800	588.750
BT	224.000	591.800	591.000	226.500	591.800	591.000	227.500	591.800	588.750	310.000
BT	590.500	0.000	310.000	600.000	0.000	0.000	0.000	0.000	0.000	0.000
ET	0.000	0.000	0.000	0.000	1.400	0.000	0.000	0.000	0.000	0.000

X@SECT. U/S OF SENECA RD REPEATED SECT. 3833.

X1	3883.000	0.000	0.000	0.000	50.000	50.000	50.000	0.000	0.000	0.000

X@SECT. D/S OF COOKE RD

X1	4437.000	11.000	295.500	304.500	350.000	500.000	454.000	0.000	0.000	0.000
GR	600.000	0.000	595.000	130.000	590.000	200.000	589.170	292.500	587.500	295.500
GR	587.500	304.500	589.670	307.500	590.000	350.000	591.000	500.000	591.500	600.000
GR	593.000	1000.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
ET	0.000	0.000	0.000	0.000	9.100	0.000	0.000	0.000	1.000	526.000

D/S FACE OF COOKE RD CULVERT

X1	4437.000	16.000	293.000	298.500	100.000	100.000	100.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	590.500	590.500	0.000
GR	600.000	0.000	595.000	130.000	590.000	200.000	589.200	290.000	587.350	293.000
GR	587.350	293.500	587.350	295.000	587.350	295.500	587.350	296.000	587.350	296.500
GR	587.350	298.000	587.350	298.500	589.700	305.000	590.000	350.000	590.400	416.000
GR	600.000	416.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
SB	0.000	1.930	3.000	0.000	3.930	0.000	4.910	0.000	587.350	587.350

U/S FACE OF COOKE RD. CULVERT

X1	4479.000	0.000	0.000	0.000	42.000	42.000	42.000	0.000	0.000	0.000
X2	0.000	0.000	1.000	588.600	591.700	0.000	0.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	591.700	591.700	0.000
BT	16.000	0.000	600.000	0.000	130.000	598.000	0.000	200.000	594.000	0.000
BT	293.000	591.700	587.350	293.500	591.700	588.600	295.000	591.700	588.600	295.500
BT	591.700	587.350	296.000	591.700	587.350	296.500	591.700	588.600	298.000	591.700
BT	588.600	298.500	591.700	587.350	350.000	591.700	0.000	416.000	592.700	0.000
BT	416.000	600.000	0.000	416.000	600.000	0.000	416.000	600.000	0.000	0.000
	0.000	0.000	0.000	0.000	1.400	0.000	0.000	0.000	0.000	0.000

PRINTED IN U.S.A.
PRINTED IN U.S.A.
FORM 1411 GO PRINTED BY ROTARY MANIFOLD FORMS

X@SECTION U/S COOKE RD

X1	4504.000	0.000	0.000	0.000	25.000	25.000	25.000	0.000	0.000	0.000
NC	0.100	0.100	0.060	0.100	0.300	0.000	0.000	0.000	0.000	0.000

VALLEY SECTION BASED ON FIELD BOOK SECT.5881

X1	4853.000	19.000	491.000	510.000	349.000	349.000	349.000	0.000	0.000	0.000
GR	600.000	0.000	595.660	200.000	595.910	300.000	594.060	378.000	590.060	391.000
GR	590.110	400.000	589.410	491.000	587.960	494.000	587.710	500.000	588.060	506.000
GR	589.850	510.000	589.300	536.000	596.710	553.000	594.420	591.000	594.370	600.000
GR	593.820	700.000	593.440	750.000	594.150	800.000	595.000	1050.000	0.000	0.000
NC	0.100	0.100	0.060	0.300	0.500	0.000	0.000	0.000	0.000	0.000

X@SECTION D/S OF TELEGRAPH RD.

X1	5053.000	8.000	594.500	605.500	200.000	200.000	200.000	0.000	0.000	0.000
GR	600.000	0.000	595.000	150.000	594.000	584.500	586.370	594.500	586.370	605.500
GR	594.000	615.500	595.000	775.000	600.000	1200.000	0.000	0.000	0.000	0.000
ET	0.000	0.000	0.000	0.000	9.100	0.000	0.000	0.000	1.000	1200.000
NC	0.000	0.000	0.050	0.000	0.000	0.000	0.000	0.000	0.000	0.000

D/S FACE TELEGRAPH RD.

X1	5253.000	8.000	495.000	499.000	200.000	200.000	200.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	592.000	592.000	0.000
GR	600.000	0.000	595.000	50.000	594.500	484.500	586.400	495.000	586.400	499.000
GR	594.400	510.000	595.000	700.000	600.000	1200.000	0.000	0.000	0.000	0.000
SB	0.000	5.790	3.000	0.000	3.630	0.000	10.900	0.000	587.300	586.400

U/S FACE OF TELEGRAPH RD.

X1	5299.000	12.000	495.000	499.000	46.000	46.000	46.000	0.000	0.000	0.000
X2	0.000	0.000	1.000	590.300	594.400	0.000	0.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	594.400	594.400	0.000
X4	1.000	594.400	485.100	0.000	0.000	0.000	0.000	0.000	0.000	0.000
BT	11.000	0.000	600.000	0.000	485.000	600.000	587.300	485.000	594.400	587.300
BT	495.000	594.400	588.500	495.500	594.400	590.000	497.000	594.400	590.300	498.500
BT	594.400	590.300	499.000	594.400	588.500	499.000	594.400	587.300	510.000	594.400
BT	0.000	510.000	600.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
GR	600.000	0.000	600.000	50.000	600.000	485.000	588.500	495.000	587.300	495.000
GR	587.300	495.500	587.300	497.000	587.300	498.500	587.300	499.000	588.500	499.000
GR	594.400	510.000	600.000	510.000	0.000	0.000	0.000	0.000	0.000	0.000
ET	0.000	0.000	0.000	0.000	1.400	0.000	0.000	0.000	0.000	0.000
NC	0.000	0.000	0.060	0.000	0.000	0.000	0.000	0.000	0.000	0.000

X@SECT. U/S OF TELEGRAPH RD

X1	5549.000	0.000	0.000	0.000	50.000	50.000	50.000	0.000	0.000	0.000
ET	0.000	9.100	0.000	0.000	0.000	0.000	0.000	0.000	375.000	430.000

X@SECT. D/S OF R.R. TRACKS

X1	5676.000	10.000	395.000	405.000	327.000	327.000	327.000	0.000	0.000	0.000
GR	600.000	0.000	595.000	250.000	590.000	320.000	595.000	385.000	587.400	395.000
GR	587.280	400.000	587.400	405.000	595.000	415.000	595.000	525.000	600.000	600.000
NC	0.120	0.120	0.060	0.300	0.500	0.000	0.000	0.000	0.000	0.000

ET	0.000	0.000	0.000	0.000	9.100	0.000	0.000	0.000	1.000	486.000

D/S FACE OF R.R. CULVERT

X1	5776.000	11.000	399.000	402.500	100.000	100.000	100.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	597.000	594.000	0.000
GR	600.000	0.000	595.000	250.000	590.000	320.000	590.000	385.000	588.260	395.000
GR	588.260	399.000	588.260	402.500	591.000	405.000	594.000	408.000	594.000	486.000
GR	600.000	486.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
SB	0.000	2.850	3.000	0.000	2.740	0.000	2.400	0.000	589.000	588.260

U/S FACE OF 42" RAILROAD CULVERT

X1	5851.000	21.000	699.000	702.500	75.000	75.000	75.000	0.000	0.000	0.000
X2	0.000	0.000	1.000	590.750	599.400	0.000	0.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	601.100	599.400	0.000
BT	16.000	0.000	604.000	0.000	200.000	603.000	0.000	300.000	602.600	0.000
BT	400.000	602.200	0.000	500.000	601.900	0.000	600.000	601.500	0.000	699.000
BT	601.100	589.000	699.250	601.100	590.250	700.750	601.100	590.750	702.250	601.100
BT	590.250	702.500	601.100	589.000	785.000	599.400	0.000	786.000	604.000	0.000
BT	876.000	604.000	0.000	876.000	604.000	0.000	876.000	604.000	0.000	0.000
GR	604.000	0.000	600.000	0.000	595.000	75.000	594.200	200.000	593.500	300.000
GR	592.900	400.000	592.200	500.000	591.600	600.000	591.000	685.000	589.000	695.000
GR	589.000	699.000	589.000	699.250	589.000	700.750	589.000	702.250	589.000	702.500
GR	591.000	705.000	599.000	715.000	599.000	785.000	604.000	786.000	604.000	876.000
GR	604.000	876.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
ET	0.000	9.100	0.000	0.000	1.400	0.000	0.000	0.000	674.000	728.000

XSECT. U/S OF R.R. TRACKS " D/S OF ARSENAL

X1	5876.000	9.000	695.000	705.000	25.000	25.000	25.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	675.000	0.000	811.000	0.000	0.000	0.000	0.000
GR	600.000	0.000	595.000	100.000	591.310	680.000	589.390	695.000	589.390	705.000
GR	591.010	715.000	595.000	800.000	600.000	950.000	600.000	1200.000	0.000	0.000
ET	0.000	0.000	0.000	0.000	9.100	0.000	0.000	0.000	1.000	1100.000

D/S FACE ARSENAL CULVERTS

X1	5931.000	13.000	799.000	802.000	55.000	55.000	55.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	593.000	593.400	0.000
GR	604.000	772.000	600.000	773.000	596.100	790.000	595.500	795.000	591.300	797.000
GR	589.400	799.000	589.400	802.000	591.000	805.000	596.500	810.000	597.100	811.000
GR	599.000	869.000	604.000	870.000	604.000	1100.000	0.000	0.000	0.000	0.000
SB	0.000	3.700	3.000	0.000	2.400	0.000	3.600	0.000	0.000	0.000

U/S FACE ARSENAL CULVERT

X1	6006.000	14.000	799.000	802.000	75.000	75.000	75.000	0.000	0.000	0.000
X2	0.000	0.000	1.000	590.900	596.100	0.000	0.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	596.100	596.500	0.000
BT	13.000	772.000	604.000	0.000	772.000	604.000	0.000	773.000	600.000	0.000
BT	790.000	596.100	0.000	799.000	596.100	589.400	799.250	596.200	590.600	800.500
BT	596.300	590.900	801.750	596.400	590.600	802.000	596.500	589.400	805.000	596.500
BT	0.000	810.000	597.100	0.000	869.000	599.000	0.000	870.000	604.000	0.000
GR	604.000	772.000	600.000	773.000	600.000	773.000	596.100	790.000	595.500	795.000
GR	589.400	799.000	589.400	799.250	589.400	800.500	589.400	801.750	589.400	802.500
GR	596.500	805.000	597.100	810.000	599.000	869.000	604.000	870.000	0.000	0.000
ET	0.000	0.000	0.000	0.000	1.400	0.000	0.000	0.000	0.000	

X SECTION U/S OF ARSENAL.

X1	6050.000	0.000	0.000	0.000	44.000	44.000	44.000	0.000	0.000	0.000
NC	0.120	0.120	0.060	0.100	0.300	0.000	0.000	0.000	0.000	0.000

VALLEY SECTION BASED ON FIELD BOOK SECT. 2800.

X1	7934.000	12.000	646.000	654.000	1884.000	1884.000	1884.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	583.000	0.000	718.000	0.000	0.000	0.000	0.000
X4	1.000	605.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
GR	600.000	0.000	595.160	350.000	594.560	450.000	594.560	550.000	593.260	641.000
GR	589.760	646.000	588.860	650.000	589.650	654.000	593.150	661.000	594.850	750.000
GR	598.820	850.000	601.020	950.000	0.000	0.000	0.000	0.000	0.000	0.000

VALLEY SECTION BASED ON FIELD BOOK SECT. 2000.

X1	8734.000	13.000	447.000	453.000	800.000	800.000	800.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	382.000	0.000	518.000	0.000	0.000	0.000	0.000
X4	2.000	605.000	0.000	605.000	1001.000	0.000	0.000	0.000	0.000	0.000
GR	600.000	0.000	595.290	150.000	594.990	250.000	595.090	350.000	593.790	440.000
GR	591.490	447.000	591.190	450.000	591.290	453.000	594.190	458.000	595.490	550.000
GR	596.290	650.000	597.590	750.000	600.000	1000.000	0.000	0.000	0.000	0.000

VALLEY SECTION BASED ON FIELD BOOK SECT. 1000.

X1	9734.000	13.000	345.000	355.000	1000.000	1000.000	1000.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	285.000	0.000	420.000	0.000	0.000	0.000	0.000
X4	2.000	605.000	0.000	605.000	701.000	0.000	0.000	0.000	0.000	0.000
GR	600.000	0.000	598.940	50.000	598.140	150.000	596.040	250.000	595.040	341.000
GR	592.640	345.000	592.340	350.000	592.540	355.000	595.340	358.000	595.470	450.000
GR	595.920	550.000	596.920	650.000	600.000	700.000	0.000	0.000	0.000	0.000
NC	0.080	0.080	0.060	0.300	0.500	0.000	0.000	0.000	0.000	0.000

X@SECT.D/S OF INKSTER RD

X1	10613.000	16.000	498.000	501.000	879.000	879.000	879.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	433.000	0.000	566.000	0.000	0.000	0.000	0.000
GR	604.000	0.000	600.900	1.000	599.800	100.000	598.800	200.000	597.000	300.000
GR	596.400	492.000	591.600	498.000	591.600	501.000	596.400	509.000	597.000	600.000
GR	597.500	900.000	598.000	1000.000	599.000	1100.000	599.500	1200.000	600.000	1300.000
GR	604.000	1301.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
ET	0.000	0.000	0.000	0.000	9.100	0.000	0.000	0.000	1.000	1301.000

D/S FACE OF INKSTER RD CULVERT

X1	10713.000	0.000	0.000	0.000	100.000	100.000	100.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	433.000	0.000	566.000	0.000	597.000	596.300	0.000
SB	0.000	2.600	3.000	0.000	2.400	0.000	3.600	0.000	593.540	591.620

U/S FACE OF INKSTER RD. CULVERT

X1	10754.000	15.000	498.000	501.000	41.000	41.000	41.000	0.000	0.000	0.000
X2	0.000	0.000	1.000	595.040	597.900	0.000	0.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	597.900	597.900	0.000
BT	13.000	433.000	604.000	0.000	433.000	604.000	0.000	433.000	604.000	0.000
BT	433.000	604.000	0.000	433.000	604.000	0.000	434.000	597.900	0.000	498.000
BT	597.900	593.540	498.250	597.900	594.790	498.500				

BT	594.790	501.000	597.900	593.540	566.000	598.200	0.000	567.000	604.000	0.000
GR	604.000	433.000	604.000	433.000	604.000	433.000	604.000	433.000	604.000	433.000
GR	596.700	434.000	596.200	490.000	593.540	498.000	593.540	498.250	593.540	499.500
GR	593.540	500.750	593.540	501.000	596.700	510.000	596.900	566.000	604.000	567.000
ET	0.000	0.000	0.000	0.000	1.400	0.000	0.000	0.000	0.000	0.000

X@SECT U/S OF INKSTER RD.

X1	10779.000	0.000	0.000	0.000	25.000	25.000	25.000	0.000	0.000	0.000
EJ	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000

PRINTED IN U.S.A.

SECNO	Q	CWSEL	DIFWSP	DIFWSX	DIFKWS	TOPWID	XLCH
6006.000	70.00	600.35	0.00	0.01	0.00	96.36	75.00
6006.000	85.00	600.47	0.00	0.02	0.00	96.41	75.00
6006.000	100.00	600.57	0.00	0.02	0.00	96.46	75.00
6006.000	120.00	600.69	0.00	0.02	0.00	96.52	75.00
6050.000	70.00	600.35	0.00	0.00	0.00	96.36	44.00
6050.000	85.00	600.47	0.00	0.00	0.00	96.41	44.00
6050.000	100.00	600.57	0.00	0.00	0.00	96.46	44.00
6050.000	120.00	600.70	0.00	0.00	0.00	96.51	44.00
7934.000	70.00	600.36	0.00	0.02	0.00	135.00	1884.00
7934.000	85.00	600.49	0.00	0.02	0.00	135.00	1884.00
7934.000	100.00	600.60	0.00	0.03	0.00	135.00	1884.00
7934.000	120.00	600.73	0.00	0.04	0.00	135.00	1884.00
8734.000	70.00	600.37	0.00	0.00	0.00	136.00	800.00
8734.000	85.00	600.49	0.00	0.00	0.00	136.00	800.00
8734.000	100.00	600.61	0.00	0.00	0.00	136.00	800.00
8734.000	120.00	600.74	0.00	0.01	0.00	136.00	800.00
9734.000	70.00	600.37	0.00	0.00	0.00	135.00	1000.00
9734.000	85.00	600.50	0.00	0.01	0.00	135.00	1000.00
9734.000	100.00	600.61	0.00	0.01	0.00	135.00	1000.00
9734.000	120.00	600.75	0.00	0.01	0.00	135.00	1000.00
10613.000	70.00	600.38	0.00	0.01	0.00	133.00	879.00
10613.000	85.00	600.51	0.00	0.01	0.00	133.00	879.00
10613.000	100.00	600.62	0.00	0.01	0.00	133.00	879.00
10613.000	120.00	600.76	0.00	0.01	0.00	133.00	879.00
10713.000	70.00	600.38	0.00	0.00	0.00	133.00	100.00
10713.000	85.00	600.51	0.00	0.00	0.00	133.00	100.00
10713.000	100.00	600.62	0.00	0.00	0.00	133.00	100.00
10713.000	120.00	600.76	0.00	0.00	0.00	133.00	100.00
10754.000	70.00	600.39	0.00	0.01	0.00	133.00	41.00
10754.000	85.00	600.52	0.00	0.02	0.00	133.03	41.00
10754.000	100.00	600.64	0.00	0.02	0.00	133.07	41.00
10754.000	120.00	600.79	0.00	0.02	0.00	133.11	41.00
10779.000	70.00	600.39	0.00	0.00	0.00	133.00	25.00
10779.000	85.00	600.52	0.00	0.00	0.00	133.03	25.00
10779.000	100.00	600.64	0.00	0.00	0.00	133.07	25.00
10779.000	120.00	600.79	0.00	0.00	0.00	133.11	25.00

SUMMARY OF ERRORS

CAUTION SECNO= 3792.000 PROFILE= 1 CRITICAL DEPTH ASSUMED
CAUTION SECNO= 3792.000 PROFILE= 1 MINIMUM SPECIFIC ENERGY

PRINTED IN U.S.A.
FORM 1411 GB PRINTED BY ROTARY MANIFOLD FORMS

	SECNO	XLCH	ELTRD	ELLC	ELMIN	Q	CWSEL	CRIWS	EG	10K*S	VCH	AREA	.01K
	5851.000	75.00	599.40	590.75	589.00	10.00	590.27	0.00	590.35	152.70	2.35	4.25	0.81
	5851.000	75.00	599.40	590.75	589.00	20.00	593.92	0.00	593.94	8.14	1.16	17.23	7.01
	5851.000	75.00	599.40	590.75	589.00	30.00	599.37	0.00	599.38	3.01	0.83	36.32	17.29
	5851.000	75.00	599.40	590.75	589.00	40.00	599.92	0.00	599.93	0.57	0.36	177.14	52.97
	5876.000	25.00	0.00	0.00	589.39	10.00	590.43	0.00	590.44	9.51	0.78	17.95	3.24
	5876.000	25.00	0.00	0.00	589.39	20.00	593.95	0.00	593.95	0.09	0.20	182.56	67.09
	5876.000	25.00	0.00	0.00	589.39	30.00	599.39	0.00	599.39	0.01	0.12	465.14	282.40
	5876.000	25.00	0.00	0.00	589.39	40.00	599.93	0.00	599.93	0.02	0.15	492.83	309.01
	5931.000	55.00	0.00	0.00	589.40	10.00	590.50	0.00	590.64	143.13	3.03	3.30	0.84
	5931.000	55.00	0.00	0.00	589.40	20.00	593.95	0.00	593.95	1.86	0.93	37.68	14.67
	5931.000	55.00	0.00	0.00	589.40	30.00	599.39	0.00	599.39	0.12	0.40	212.87	86.61
	5931.000	55.00	0.00	0.00	589.40	40.00	599.92	0.00	599.93	0.15	0.47	247.74	102.06
	6006.000	75.00	596.10	590.90	589.40	10.00	591.97	0.00	592.07	260.98	2.50	4.00	0.62
	6006.000	75.00	596.10	590.90	589.40	20.00	595.70	0.00	595.72	6.82	1.06	18.93	7.66
*	6006.000	75.00	596.10	590.90	589.40	30.00	599.39	0.00	599.40	0.18	0.48	211.22	71.52
	6006.000	75.00	596.10	590.90	589.40	40.00	599.93	0.00	599.94	0.20	0.53	262.35	89.97

SECNO	CH	ELTRD	ELLC	ELMIN	Q	CWSEL	CRIWS	EG	10K*S	VCH	AREA	.01K
5551.000	75.00	599.40	590.75	589.00	10.00	590.27	0.00	590.35	152.70	2.35	4.25	0.81
5551.000	75.00	599.40	590.75	589.00	25.00	596.42	0.00	596.44	4.60	0.96	26.01	11.66
5551.000	75.00	599.40	590.75	589.00	40.00	599.92	0.00	599.92	0.57	0.36	177.03	52.94
5551.000	75.00	599.40	590.75	589.00	55.00	600.18	0.00	600.18	0.87	0.45	199.01	59.08
5576.000	25.00	0.00	0.00	589.39	10.00	590.43	0.00	590.44	9.51	0.78	17.95	3.24
5576.000	25.00	0.00	0.00	589.39	25.00	596.44	0.00	596.44	0.01	0.10	556.97	218.46
5576.000	25.00	0.00	0.00	589.39	40.00	599.92	0.00	599.92	0.01	0.09	1029.45	549.74
5576.000	25.00	0.00	0.00	589.39	55.00	600.18	0.00	600.18	0.01	0.11	1064.94	579.50
5931.000	55.00	0.00	0.00	589.40	10.00	590.50	0.00	590.64	143.13	3.03	3.30	0.84
5931.000	55.00	0.00	0.00	589.40	25.00	596.44	0.00	596.44	0.53	0.66	75.17	34.28
5931.000	55.00	0.00	0.00	589.40	40.00	599.92	0.00	599.92	0.14	0.44	288.35	108.18
5931.000	55.00	0.00	0.00	589.40	55.00	600.18	0.00	600.18	0.21	0.56	312.98	118.68
6006.000	5.00	596.10	590.90	589.40	10.00	591.97	0.00	592.07	260.98	2.50	4.00	0.62
6006.000	5.00	596.10	590.90	589.40	25.00	596.70	0.00	596.71	0.89	0.88	55.84	26.57
6006.000	5.00	596.10	590.90	589.40	40.00	599.93	0.00	599.94	0.20	0.53	262.23	89.92
6006.000	5.00	596.10	590.90	589.40	55.00	600.19	0.00	600.19	0.30	0.67	287.10	99.95
6050.000	45.00	0.00	0.00	589.40	10.00	592.15	0.00	592.16	5.25	1.11	12.26	4.36
6050.000	45.00	0.00	0.00	589.40	25.00	596.71	0.00	596.72	0.89	0.88	55.72	26.52
6050.000	45.00	0.00	0.00	589.40	40.00	599.93	0.00	599.94	0.20	0.53	262.12	89.88
6050.000	45.00	0.00	0.00	589.40	55.00	600.19	0.00	600.20	0.30	0.67	286.94	99.88
7934.000	1000.00	0.00	0.00	588.86	10.00	592.37	0.00	592.38	0.47	0.36	37.07	14.51
7934.000	1000.00	0.00	0.00	588.86	25.00	596.73	0.00	596.73	0.02	0.14	473.25	165.58
7934.000	1000.00	0.00	0.00	588.86	40.00	599.94	0.00	599.94	0.01	0.11	906.72	432.27
7934.000	1000.00	0.00	0.00	588.86	55.00	600.20	0.00	600.20	0.01	0.14	942.05	458.13
8734.000	1000.00	0.00	0.00	591.19	10.00	592.47	0.00	592.50	21.14	1.27	9.80	2.17
8734.000	1000.00	0.00	0.00	591.19	25.00	596.73	0.00	596.73	0.07	0.20	354.73	97.69
8734.000	1000.00	0.00	0.00	591.19	40.00	599.94	0.00	599.94	0.01	0.13	792.21	331.86
8734.000	1000.00	0.00	0.00	591.19	55.00	600.20	0.00	600.20	0.02	0.16	827.64	355.28
9734.000	1000.00	0.00	0.00	592.34	10.00	593.69	0.00	593.70	7.75	0.79	13.89	3.59
9734.000	1000.00	0.00	0.00	592.34	25.00	596.74	0.00	596.74	0.20	0.29	224.36	56.51
9734.000	1000.00	0.00	0.00	592.34	40.00	599.94	0.00	599.94	0.02	0.14	657.21	261.56
9734.000	1000.00	0.00	0.00	592.34	55.00	600.21	0.00	600.21	0.04	0.19	692.70	283.47
10613.000	879.00	0.00	0.00	591.60	10.00	594.14	0.00	594.15	3.55	0.87	17.02	5.31
10613.000	879.00	0.00	0.00	591.60	25.00	596.77	0.00	596.78	0.94	0.72	80.27	25.76
10613.000	879.00	0.00	0.00	591.60	40.00	599.95	0.00	599.95	0.03	0.18	503.41	230.36
10613.000	879.00	0.00	0.00	591.60	55.00	600.21	0.00	600.21	0.05	0.22	538.51	255.76
10713.000	100.00	0.00	0.00	591.60	10.00	594.19	0.00	594.21	10.96	1.28	7.78	3.02
10713.000	100.00	0.00	0.00	591.60	25.00	596.79	0.00	596.79	2.67	0.76	48.68	15.31
10713.000	100.00	0.00	0.00	591.60	40.00	599.95	0.00	599.95	0.03	0.18	503.51	230.43
10713.000	100.00	0.00	0.00	591.60	55.00	600.21	0.00	600.21	0.05	0.22	538.71	255.91
* 10754.000	41.00	597.90	595.04	593.54	10.00	594.27	0.00	594.59	640.13	4.57	2.19	0.40
10754.000	41.00	597.90	595.04	593.54	25.00	597.99	0.00	597.99	0.16	0.27	216.61	62.83
* 10754.000	41.00	597.90	595.04	593.54	40.00	599.95	0.00	599.96	0.03	0.16	477.80	215.10
10754.000	41.00	597.90	595.04	593.54	55.00	600.22	0.00	600.22	0.05	0.20	513.33	241.51

00BREAK00

1) COUNTY: Wayne

2) STUDY NAME: City of Flat Rock

3) WATERCOURSE: Cook and Gladding Drain

4) DOCUMENT TYPE: Report

00BREAK00

HYDRAULIC REPORT
CITY OF FLAT ROCK-MICHIGAN

I. INTRODUCTION

The City of Flat Rock covers approximately 7 square miles. The City is basically a rural/residential community. This report summarizes the hydraulic studies taken to support detailed studies of approximately 3 miles of the Silver Creek, 2 miles of the Cook and Gladding Drain, and 4 miles of the Huron River. Furthermore, this report summarizes the approximate hydraulic study of approximately 3 miles of Smith Creek.

This study was conducted by Wade, Trim & Associates, Inc., Consulting Engineers, and Glen Roberts served as Project Manager.

III. COOK & GLADDING DRAIN (DETAILED)

Detailed studies of the Cook and Gladding Drain were performed from its confluence with the Huron River to the corporate boundary of Flat Rock at Inkster Road. A total of 7 valley and 9 bridge cross sections were field surveyed and completed in July, 1978. An additional 18 cross sections were used in this analysis. Field cross section data were supplemented by U.S.G.S. Quad Maps of the study area which consists of 5 foot interval contour data (Reference 2). The flood plain of the Cook and Gladding Drain within the study reach ranges from heavy brush to grassy lawns.

Cross section locations are shown in Exhibit 1. Table 3 cross references section designations by showing the computer section number which corresponds to the cross section letters shown in Exhibit 1.

Exhibit 5 contains bridge sketches as well as computations for total bridge loss coefficients. None of the 9 bridges are considered to be skewed.

Table 4 lists discharges that have been approved by the Michigan Department of Natural Resources (MDNR) for this Drain.

A. METHOD OF ANALYSIS

The HEC-2 backwater program was used in developing water surface profiles (Reference 3).

Table 4 also contains selected flood elevations from the HEC-2 printouts. HEC-2 printouts including computer cross section plots are presented as Exhibit 6. Water surface profiles resulting from the backwater analyses are presented as Exhibit 7. (Exhibit 6 is contained in the 11" x 15" folder enclosed with this report).

B. VARIABLES AND COEFFICIENTS

Roughness coefficients (Mannings "n") were estimated by field inspection at each cross section. Typical roughness values used for the main channel ranged from .015 to 0.06; roughness values for the overbank areas varied between .06 to .12 for all floods. These values are indicative of summer month conditions and are consistent with roughness values recommended and used in engineering practice.

C. HIGH WATER MARKS

No documented high water data exists for flood elevations on the Cook and Gladding Drain.

D. STARTING CONDITIONS

The starting water surface elevation used in all backwater computations which begin at the Huron River is the mean annual flood elevation of the Huron River (see Exhibit 5) at the confluence with Cooke and Gladding Drain. Since the drainage basin for Cooke and Gladding Drain is minor compared with that of the Huron River, it is unlikely that a major storm will occur in both basins at the same time.

E. SPECIAL PROBLEMS

The Arsenal Road and D.T.&I Railroad culverts cause extensive restrictions to flow on Cooke and Gladding Drain due to inadequate pipe sizing and siltation.

These restrictions cause a severe backwater condition and subsequent transfer of floodwater to the Huron River. Therefore, flow rates and elevations for the various floods investigated are controlled by the amount of flow diverted to the Huron River. Futhermore, flood elevations experienced on the Huron River are also experienced on Cooke and Gladding Drain when flow diversion occurs between the two streams.

Thus, the following flow diversion analysis (Exhibit 12) was performed to determine flow distributions and flood elevaions for Cooke and Gladding Drain:

1. A stage/discharge rating curve was developed upstream of the Arsenal Road culvert on Cooke and Gladding Drain (Exhibit 12, Page 1).

2. An overland flow stage/discharge rating curve was developed for flow that diverts from the Cooke and Gladding Drain to the Huron River (Exhibit 12, Page 1).

3. The two rating curves above were combined to form a total rating curve (Exhibit 12, Page 1) for the area upstream of the Arsenal Road culvert.

4. The 10, 50, 100 and 500 year flow rates for Cooke and Gladding Drain were applied to the total rating curve to determine the various flood elevations.

5. The flood elevations were applied to the rating curves for each flow area to determine the distribution of flow.

6. The 10, 50, 100 and 500 year elevations from the Huron River portion of the Flood Insurance Study were then compared with the elevations determined in the flow diversion analysis for Cooke and Gladding Drain. The higher of the two elevations was used for Cooke and Gladding Drain. Where Huron River elevations controlled, flow distribution was revised by application of the elevations to the rating curves. As modeled, 230cfs would be diverted to Cook-Gladding from Silver Creek

Results of this analysis (Exhibit 12, Page 2) indicate that Cooke and Gladding Drain flow rates are substantially reduced downstream of the Arsenal Road culvert. Flow which is diverted from Cooke and Gladding is negligible with respect to the magnitude of flows in the Huron River; therefore, there will be no impact on flood elevations to the Huron River.

F. GENERAL

Computed water-surface elevations were developed to an accuracy of 0.5 foot for floods of the selected recurrence intervals.

All elevations are referenced to the National Geodetic Vertical Datum of 1929 (NGVD). This datum is equivalent to the U.S. Geological Survey (USGS) datum.

The hydraulic analyses for this study are based only on the effects of flow unobstructed by ice or debris. The flood elevations are considered valid only if hydraulic structures, in general, remain unobstructed and do not fail.

TABLE 3
CITY OF FLAT ROCK
COOK & GLADDING DRAIN

CROSS SECTION	COMPUTER NO.	WTA FIELD BOOK NO.	DESCRIPTION
A	0		@ Huron River
B	54		u/s Face of Huron River Dri
C	300	10434	Valley Seciton
D	1300	9434	Valley Section
E	1700		d/s End of 54" Conc. Culver
		8973	℄ Gibraltar Road
F	1836		u/s End of 54" Conc. Culver
G	2284	8450	Valley Section
H	3041	7693	d/s End of 54" Conc. Culver
I	3210	7524	u/s End of 54" Conc. Culver
J	3384		d/s End of 48"X76" Conc. Culvert
		7271	℄ Sheeks Road
K	3548		u/s End of 48"X76" Conc. Culvert
L	3792		d/s End of 54" Culvert
		6921	℄ Seneca Road
M	3833		u/s End of 54" Culvert
N	4437		d/s End of Twin 30" Conc. Culverts
		6269	℄ of Cooke Road
O	4479		u/s End of Twin 30" Conc. Culverts
P	4853	5881	Valley Section
Q	5253		d/s End 48" Conc. Culvert
		5481	℄ Telegraph Road
R	5299		u/s End of 48" Conc. Culver
S	5776		d/s End of 42" Conc. Culver
T		4915	℄ D.T. & I. R.R.
U	5931		d/s End of 36" Conc. Culver
		4769	℄ Arsenal Road
V	6006		u/s End of 36" Conc. Culver
W	7934	2800	Valley Section
X	8734	2000	Valley Section
Y	9734	1000	Valley Section
Z	10713		d/s End of 36" Conc. Culver
		0	℄ Inkster Road
AA	10754		u/s End of 36" Conc. Culver

TABLE 4
CITY OF FLAT ROCK
COOK & GLADDING DRAIN FLOOD ELEVATIONS*

LOCATION	SELECTED FREQUENCIES 10 Yr. Q=21 CFS	50 Yr. Q=21 CFS	100 Yr. Q=27 CFS	500 Yr. Q=37 CFS
d/s of Gibraltar Road (0.3 Mi.)	586.3	586.3	586.5	586.8
d/s of Telegraph Road (1.0 Mi.)	590.8	590.8	591.5	591.9
u/s of Telegraph Road (1.0 Mi.)	590.8	590.8	592.0	592.9
d/s of R.R. (1.1 Mi.)	591.0	591.0	592.1	593.0
u/s of R.R. (1.1 Mi.)	594.4	594.4	597.7	599.8
	Q=50 CFS	Q=75 CFS	Q=75 CFS	Q=120 CFS
@ Corp. Limit (2.0 Mi.)	598.1	598.2	598.3	600.0

*N.G.V.D.

CITY OF FLAT ROCK

EXHIBIT 1

FIELD CROSS-SECTION LOCATION
AND 100 YEAR FLOOD PLAIN -
FLOODWAY MAP

HUD 2009-07

CITY OF FLAT ROCK
COOK AND GLADDING DRAIN

EXHIBIT 6

COMPUTER PRINTOUTS
HEC-2 BACKWATER ANALYSIS
(See Separate Folder)

CITY OF FLAT ROCK
COOK AND GLADDING DRAIN

EXHIBIT 7

STREAM PROFILE

HUD 2009-07

CITY OF FLATROCK

COOKE AND GLADING DRAIN

EXHIBIT 12

FLOW DIVERSION ANALYSIS




Exhibit 12

W.J Weaver
9/7/19

Pg 1 of 2
HUD 2009 07

46 1320

K&E 10 X 10 TO ½ INCH 7 X 10 INCHES
KEUFFEL & ESSER CO MADE IN U.S.A.

REFERENCE

Cooke + Gladding Flowrates

[A] Elev. 596 controls for all 4 storms (10, 50, 100, + 500) at the Arsenal Rd. Culvert (See Rating Curve pg. ___). This produces a flow distribution as follows:

① 21 cfs to Cooke + Gladding for all floods.

② The following flows divert to the Huron:

10 year – 29 cfs
50 year – .54 cfs
100 year – 64 cfs
500 year – 94 cfs

[B] Cooke + Gladding Drain will experience the following elevations due to floods on the Huron River:

Flood	Elev	Cooke + Gladding Q (See Intl. Curve)
10 year	– 594.10	0
50 year	– 595.95	20 cfs
100 year	– 597.73	27 cfs
500 year	– 599.86	37 cfs

[C] Analysis of the results in [A] + [B] above produces the following flows for Cooke + Gladding Drain and flood elevations upstream of the Arsenal Road Culvert:

Flood Event	Elev.	Q below Arsenal Culvert
10 yr.	596.0	21 cfs
50 yr.	596.0	21 cfs
100 yr.	597.73	20 cfs
500 yr.	599.86	39 cfs

SUBJECT	BY	CHK.	SHEET NO.	File Code No. (Job No.) Owner Project Suffix
Exhibit 12	W.J. Weaver		2 OF 2	HUD • 2009 • 07
	DATE 9/13/79	DATE		

00BREAK00

1) COUNTY: Wayne

2) STUDY NAME: City of Flat Rock

3) WATERCOURSE: Huron River

4) DOCUMENT TYPE: 100 year

00BREAK00

```
**************************************************
  HEC2 RELEASE DATED NOV 76 UPDATED FEB 1977
  ERROR CORR -  31
  MODIFICATION -  50,51,52
**************************************************

C
T1      CITY OF FLATROCK
T2      100 YEAR FLOW
T3      HURON RIVER

J1  ICHECK    INQ       NINV      IDIR      STRT      METRIC    HVINS     Q         WSEL      FQ
         0.        5.        0.        0.  0.000000      0.00      0.0         0.   587.660     0.000

J2  NPROF     IPLOT     PRFVS     XSECV     XSECH     FN        ALLDC     IBW       CHNIM     ITRACE
     1.000     0.000    -1.000     0.000     0.000     0.000     0.000     0.000     0.000     0.000

J3  VARIABLE CODES FOR SUMMARY PRINTOUT
   150.000   200.000     0.000     0.000     0.000     0.000     0.000     0.000     0.000     0.000

ET     0.000     0.000     0.000     0.000     0.000     0.000     1.400     0.000     0.000     0.000
QT     6.000  7700.000  6480.000  8750.000 10390.000 12100.000 10390.000     0.000     0.000     0.000
NC     0.120     0.120     0.035     0.300     0.500     0.000     0.000     0.000     0.000     0.000

      VALLEY SECTION FROM ROCKWOOD FIS

X1   500.000    21.000   100.000   218.000     0.000     0.000     0.000     0.000     0.000     0.000
GR   594.100     0.000   593.400    51.000   579.500   100.000   574.300   102.000   573.000   103.000
GR   572.800   108.000   571.100   113.000   569.600   118.000   569.200   128.000   569.200   138.000
GR   569.100   148.000   569.500   158.000   570.200   168.000   570.500   178.000   570.800   188.000
GR   570.900   193.000   571.100   198.000   571.200   203.000   572.300   208.000   582.300   218.000
GR   590.200   268.000     0.000     0.000     0.000     0.000     0.000     0.000     0.000     0.000
NC     0.000     0.000     0.050     0.000     0.000     0.000     0.000     0.000     0.000     0.000

      VALLEY SECTION FROM CORPS OF ENGINEERS SECTION V10

X1  1800.000    19.000  1460.000  1590.000   650.000   500.000  1300.000     0.000     0.000     0.000
GR   597.500     0.000   585.800   150.000   585.000   190.000   586.700   390.000   581.500   590.000
GR   581.000   790.000   579.700   890.000   580.000   990.000   581.900  1190.000   580.600  1290.000
GR   581.900  1460.000   571.900  1490.000   571.400  1530.000   573.000  1570.000   576.000  1580.000
GR   586.700  1590.000   586.000  1890.000   586.300  1990.000   591.000  2060.000     0.000     0.000

      VALLEY SECTION FROM CORPS OF ENGINEERS SECTION V9

X1  4400.000    22.000    39.000   130.000  1000.000  1400.000  2600.000     0.000     0.000     0.000
GR   596.800     0.000   582.200    80.000   580.600    39.000   575.900    41.000   572.000    50.000
GR   569.900    80.000   569.400   100.000   570.600   120.000   575.900   128.000   581.100   130.000
GR   582.900   300.000   583.100   500.000   583.700   700.000   584.000   850.000   584.200  1000.000
GR   584.500  1150.000   584.800  1300.000   585.000  1470.000   588.800  1600.000   590.000  1670.000
GR   592.200  1800.000   595.000  1970.000     0.000     0.000     0.000     0.000     0.000     0.000
```

VALLEY SECTION FROM CORPS OF ENGINEERS SECTION V8

X1	6200.000	18.000	1385.000	1485.000	600.000	600.000	1800.000	0.000	0.000	0.000
GR	593.200	0.000	590.000	180.000	585.000	210.000	584.000	300.000	584.000	450.000
GR	584.000	550.000	584.000	650.000	583.000	800.000	583.000	950.000	582.900	1100.000
GR	582.900	1250.000	582.900	1385.000	575.300	1395.000	571.300	1425.000	573.300	1455.000
GR	590.400	1485.000	590.400	1585.000	595.000	1945.000	0.000	0.000	0.000	0.000

VALLEY SECTION FROM CORPS OF ENGINEERS SECTION V7

X1	8200.000	26.000	810.000	930.000	1000.000	850.000	2000.000	0.000	0.000	0.000
GR	595.000	0.000	588.970	150.000	587.000	230.000	586.000	330.000	583.800	430.000
GR	582.300	630.000	583.000	810.000	573.800	820.000	571.800	830.000	571.800	840.000
GR	571.500	850.000	575.400	890.000	575.700	900.000	575.000	910.000	581.200	930.000
GR	581.500	960.000	583.500	1030.000	582.200	1080.000	582.000	1130.000	580.000	1180.000
GR	581.900	1230.000	582.400	1280.000	583.000	1480.000	579.200	1535.000	594.000	1565.000
GR	594.600	1680.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000

VALLEY SECTION FROM CORPS OF ENGINEERS SECTION V6

X1	10300.000	26.000	1025.900	1177.000	900.000	900.000	2100.000	0.000	0.000	0.000
GR	595.000	0.000	590.000	550.000	589.030	595.000	588.100	625.000	588.000	725.000
GR	586.000	775.000	583.000	795.000	583.400	1025.000	578.800	1032.000	573.200	1055.000
GR	572.900	1075.000	573.500	1125.000	578.200	1155.000	578.800	1165.000	581.400	1177.000
GR	583.900	1200.000	582.500	1825.000	583.100	1875.000	587.200	1895.000	587.200	1925.000
GR	587.200	2025.000	587.200	2125.000	587.200	2275.000	587.200	2295.000	587.200	2310.000
GR	595.000	2325.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
NC	0.120	0.120	0.050	0.000	0.000	0.000	0.000	0.000	0.000	0.000

VALLEY SECTION FROM CORPS OF ENGINEERS SECTION V5

X1	12900.000	16.000	730.000	860.000	1900.000	1300.000	2600.000	0.000	0.000	0.000
GR	595.000	0.000	590.000	250.000	588.200	700.000	588.000	730.000	580.000	740.000
GR	576.000	741.000	573.400	760.000	577.000	830.000	584.100	860.000	585.000	880.000
GR	585.300	950.000	5853.000	1100.000	585.300	1200.000	587.000	1375.000	590.000	1500.000
GR	595.000	1700.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
NC	0.100	0.100	0.040	0.000	0.000	0.000	0.000	0.000	0.000	0.000

VALLEY SECTION FROM CORPS OF ENGINEERS SECTION V4

X1	15800.000	21.000	640.000	795.030	2300.000	2900.000	2100.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	315.030	0.000	1000.000	0.000	0.000	0.000	0.000
GR	600.540	0.000	599.200	100.000	593.300	150.000	590.500	200.000	585.000	230.000
GR	586.400	260.000	583.900	280.000	583.800	300.000	582.800	400.000	584.500	500.000
GR	585.100	600.000	586.700	640.000	580.400	650.000	577.500	670.000	574.200	770.000
GR	576.800	790.000	585.300	795.000	585.800	1000.000	583.000	1125.000	595.800	1155.000
GP	597.000	1175.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000

X-SECTION D/S OF TELEGRAPH RD.

X1	17080.000	16.000	570.000	750.000	1280.000	1280.000	1280.000	0.766	0.000	0.000
X3	0.000	0.000	0.000	550.000	0.000	760.000	0.000	0.000	0.000	0.000
GR	600.000	0.000	597.700	25.000	590.000	525.000	585.000	553.000	597.300	570.000

PRINTED IN U.S.A.
FORM 141: GO PRINTED BY ROTARY MANIFOLD FORMS

GR	578.000	600.000	577.400	650.000	576.200	664.000	577.500	680.000	574.200	690.000
GR	573.300	710.000	575.500	730.000	578.600	750.000	581.300	774.000	590.000	821.000
GR	597.000	910.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
NC	0.100	0.100	0.035	0.300	0.500	0.000	0.000	0.000	0.000	0.000
ET	0.000	0.000	0.000	0.000	0.000	0.000	9.100	0.000	133.000	795.000

D/S FACE OF TELEGRAPH RD.BRIDGE

X1	17180.000	16.000	565.000	664.200	100.000	100.000	100.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	595.000	595.000	0.000
GR	600.000	133.000	597.700	152.000	597.170	183.000	590.000	535.000	585.000	556.000
GR	578.000	565.000	577.000	593.700	577.000	593.800	577.000	635.500	577.000	636.600
GR	573.300	650.000	579.000	664.200	581.300	689.000	590.000	725.000	597.170	794.000
GR	600.000	795.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
SB	1.250	1.650	3.000	0.000	88.730	42.000	822.400	0.000	0.000	0.000

U/S FACE OF TELEGRAPH RD.BRIDGE

X1	17246.000	0.000	0.000	0.000	66.000	66.000	66.000	0.000	0.000	0.000
X2	0.000	0.000	1.000	590.900	597.170	0.000	0.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	597.170	597.170	0.000
BT	13.000	133.000	600.000	0.000	152.000	597.700	0.000	183.000	597.170	0.000
BT	565.000	597.170	578.000	565.000	597.170	590.900	593.700	597.170	590.900	593.800
BT	597.170	577.000	635.500	597.170	577.000	635.600	597.170	590.900	664.200	597.170
BT	590.900	664.200	597.170	0.000	794.000	597.170	0.000	795.000	600.000	0.000
ET	0.000	0.000	0.000	0.000	0.000	0.000	1.400	0.000	0.000	0.000

X-SECTION U/S OF TELEGRAPH RD.BRIDGE

X1	17271.000	0.000	0.000	0.000	100.000	100.000	100.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	380.000	0.000	680.000	0.000	0.000	0.000	0.000
ET	0.000	0.000	0.000	0.000	0.000	0.000	9.100	0.000	0.000	1350.000

D/S FACE OF FOOTBRIDGE

X1	18700.000	13.000	400.000	520.000	1369.000	1369.000	1369.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	590.400	590.500	0.000
GR	608.000	0.000	600.000	0.100	595.000	110.000	590.000	310.000	590.500	400.000
GR	580.300	412.000	580.300	511.500	590.600	520.000	594.000	620.000	594.500	720.000
GR	595.000	1000.000	595.000	1200.000	600.000	1200.000	0.000	0.000	0.000	0.000

X1	18701.000	21.000	400.000	520.000	1.000	1.000	1.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	590.400	590.500	0.000
BT	19.000	0.000	608.000	0.000	0.100	600.000	0.000	110.000	595.000	0.000
BT	310.000	590.000	0.000	400.000	590.500	590.300	448.000	590.500	590.300	448.100
BT	590.500	582.700	448.900	590.500	582.700	449.000	590.500	590.300	485.000	590.600
BT	590.300	485.100	590.600	582.700	485.900	590.600	582.700	486.000	590.600	590.300
BT	520.000	590.600	590.300	620.000	594.000	0.000	720.000	594.500	0.000	1000.000
BT	593.000	0.000	1200.000	595.000	0.000	1200.000	600.000	0.000	0.000	0.000
GR	608.000	0.000	600.000	0.100	595.000	110.000	590.000	310.000	590.500	400.000
GR	582.670	412.000	582.680	448.000	582.700	448.100	582.700	448.900	582.680	449.000
GR	582.700	485.000	582.700	485.100	582.700	485.900	582.700	486.000	582.710	511.500
GR	590.600	520.000	594.000	620.000	594.500	720.000	595.000	1000.000	595.000	1200.000
GR	600.000	1200.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000

PRINTED IN U.S.A.
FORM 4411-00 PRINTED BY ROTARY MANIFOLD FORMS

X1	18711.000	0.000	0.000	0.000	10.000	10.000	10.000	0.000	0.000	0.000
X2	0.000	0.000	0.000	0.000	0.000	0.000	1.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	590.500	590.600	0.000

U/S FACE OF FOOTBRIDGE

X1	18712.000	0.000	0.000	0.000	1.000	1.000	1.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	590.500	590.600	0.000
ET	0.000	0.000	0.000	0.000	0.000	0.000	1.400	0.000	0.000	0.000

X-SECT. D/S OF R.R.BRIDGE

X1	19600.000	22.000	400.000	520.000	900.000	900.000	900.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	270.000	0.000	930.000	0.000	0.000	0.000	0.000
GR	608.000	0.000	600.000	0.100	595.000	110.000	590.000	310.000	590.500	400.000
GR	582.670	412.000	580.900	430.000	580.300	440.000	580.000	450.000	580.400	460.000
GR	580.600	470.000	580.200	480.000	580.700	484.000	580.000	490.000	580.000	500.000
GR	582.710	511.500	593.400	520.000	594.000	620.000	594.500	720.000	595.000	1000.000
GR	595.000	1200.000	600.000	1350.000	0.000	0.000	0.000	0.000	0.000	0.000
NC	0.070	0.070	0.035	0.300	0.500	0.000	0.000	0.000	0.000	0.000
ET	0.000	0.000	0.000	0.000	0.000	0.000	9.100	0.000	0.000	1125.100

D/S FACE OF R.R. BRIDGE

X1	19700.000	80.000	265.000	870.000	100.000	100.000	100.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	598.000	598.000	0.000
GR	600.000	0.000	598.000	260.000	598.000	265.000	583.200	265.100	582.300	290.000
GR	594.040	291.000	594.040	294.000	582.300	295.000	582.300	320.000	594.040	321.000
GR	594.040	324.000	582.300	325.000	582.300	350.000	594.040	351.000	594.040	354.000
GR	582.300	355.000	582.300	380.000	594.040	381.000	594.040	384.000	582.300	385.000
GR	582.300	410.000	594.040	411.000	594.040	414.000	582.300	415.000	582.300	440.000
GR	594.040	441.000	594.040	444.000	582.300	445.000	582.300	470.000	594.040	471.000
GR	594.040	474.000	582.300	475.000	582.300	500.000	594.040	501.000	594.040	504.000
GR	582.300	505.000	582.300	530.000	594.040	531.000	594.040	534.000	582.300	535.000
GR	582.300	560.000	594.040	561.000	594.040	564.000	582.300	565.000	582.300	590.000
GR	594.040	591.000	594.040	594.000	582.300	595.000	582.300	620.000	594.040	621.000
GR	594.040	624.000	582.300	625.000	582.300	650.000	594.040	651.000	594.040	654.000
GR	582.300	655.000	582.300	680.000	594.040	681.000	594.040	684.000	582.300	685.000
GR	582.300	710.000	594.040	711.000	594.040	714.000	582.300	715.000	582.300	740.000
GR	594.040	741.000	594.040	744.000	582.300	745.000	582.300	770.000	594.040	771.000
GR	594.040	774.000	582.300	775.000	582.300	800.000	594.100	801.000	594.100	806.000
GR	582.300	806.100	582.300	831.000	592.370	832.000	594.020	870.000	598.340	1125.100
SB	1.250	1.610	3.000	0.000	517.350	51.000	5475.000	0.000	0.000	0.000

U/S FACE OF R.R. BRIDGE

X1	19747.000	0.000	0.000	0.000	47.000	47.000	47.000	0.000	0.000	0.000
X2	0.000	0.000	1.000	594.040	599.200	0.000	0.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	599.200	599.200	0.000
BT	9.000	0.000	600.000	0.000	265.000	601.350	0.000	265.100	601.350	594.040
BT	800.000	601.360	594.040	800.000	601.350	0.000	870.000	601.410	0.000	870.000
BT	598.920	0.000	1125.100	599.200	0.000	1125.100	600.970	0.000	0.000	0.000
NC	0.070	0.070	0.020	0.300	0.500	0.000	0.000	0.000	0.000	0.000

PRINTED IN U.S.A.
FORM 1411 GO PRINTED BY NOTARY MANIFOLD FORMS.

DUMMY X-SECT.U/S OF R.R.BRIDGE

X1	19748.000	12.000	265.000	870.000	1.000	1.000	1.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	600.000	600.000	0.000
GR	600.000	0.000	598.000	265.000	591.700	266.600	582.300	269.000	582.300	771.000
GR	594.100	771.100	594.100	776.000	582.300	776.100	582.300	802.000	592.370	802.100
GR	594.020	870.000	598.340	1125.100	0.000	0.000	0.000	0.000	0.000	0.000
SB	0.000	1.500	3.000	0.000	1.000	0.000	9.400	0.000	0.000	0.000

X-SECT.AT CREST OF DAM

X1	19753.000	0.000	0.000	0.000	3.000	3.000	3.000	0.000	0.000	0.000
X2	0.000	0.000	1.000	591.700	591.700	0.000	0.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	600.000	600.000	0.000
BT	4.000	265.000	600.000	0.000	265.000	591.700	0.000	870.000	591.700	0.000
BT	870.000	600.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
ET	0.000	0.000	0.000	0.000	0.000	0.000	1.400	0.000	0.000	0.000

VALLEY SECT. AT CORP. LIMITS

X1	22300.000	11.000	50.000	1300.000	2547.000	2547.000	2547.000	0.000	0.000	0.000
GR	600.000	0.000	595.000	25.000	592.000	-50.000	587.000	60.000	587.000	1290.000
GR	592.000	1300.000	595.000	1325.000	596.000	1350.000	595.000	1400.000	595.000	1600.000
GR	600.000	1650.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
EJ	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000

FORM 1411-09 PRINTED BY ROTARY MASTER FOLD FORMS
PRINTED IN U.S.A.

*PROF 1

CCHV= 0.300 CEHV= 0.500

*SECNO 500.000

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	DLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IH2	ICONT	CORAR	TOPWID	ENDST
A									
VALLEY SECTION FROM ROCKWOOD FIS									
500.00	18.56	587.66	0.00	587.66	588.08	0.42	0.00	0.00	579.50
10390.	72.	10276.	43.	117.	1965.	91.	0.	0.	582.30
0.00	0.61	5.23	0.47	0.120	0.035	0.120	0.000	569.10	71.23
0.000394	0.	0.	0.	0	0	0	0.00	180.69	251.92

*SECNO 1800.000

B									
VALLEY SECTION FROM CORPS OF ENGINEERS SECTION V10									
1800.00	17.07	588.47	0.00	0.00	588.51	0.05	0.32	0.11	581.90
10390.	5339.	4777.	274.	8131.	1881.	901.	125.	17.	586.70
0.21	0.66	2.54	0.30	0.120	0.050	0.120	0.058	571.40	115.84
0.000222	650.	1300.	500.	2	0	0	0.00	1906.41	2022.24

*SECNO 4400.000

C									
VALLEY SECTION FROM CORPS OF ENGINEERS SECTION V9									
4400.00	19.54	588.94	0.00	0.00	589.04	0.10	0.50	0.02	580.60
10390.	79.	5462.	4848.	115.	1607.	7252.	454.	70.	581.10
0.45	0.69	3.40	0.67	0.120	0.050	0.120	0.065	569.40	16.15
0.000323	1000.	2600.	1400.	.2	0	0	0.00	1592.11	1608.26

*SECNO 6200.000

D									
VALLEY SECTION FROM CORPS OF ENGINEERS SECTION V8									
6200.00	18.10	589.40	0.00	0.00	589.48	0.08	0.43	0.01	582.90
10390.	5962.	4428.	0.	7054.	1326.	0.	614.	92.	590.40
0.62	0.85	3.34	0.00	0.120	0.050	0.120	0.068	571.30	183.60
0.000431	600.	1800.	600.	2	0	0	0.00	1299.65	1483.25

*SECNO 8200.000

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	DLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IH2	ICONT	CORAR	TOPWID	ENDST
E									
VALLEY SECTION FROM CORPS OF ENGINEERS SECTION V7									

PRINTED IN U.S.A.
FORM 1411-CO PRINTED BY SCRANTON MANIFOLD FORMS

8200.00	18.35	589.85	0.00	0.00	589.91	0.05	0.42	0.01	583.00
10390.	2202.	4753.	3435.	3648.	1827.	4831.	857.	125.	581.20
0.88	0.60	2.60	0.71	0.120	0.050	0.120	0.069	571.50	128.00
0.000214	1000.	2000.	850.	2	0	0	0.00	1428.59	1556.60

*SECNO 10300.000

VALLEY SECTION FROM CORPS OF ENGINEERS SECTION V6

10300.00	17.26	590.16	0.00	0.00	590.21	0.05	0.31	0.00	583.40
10390.	1211.	5575.	3605.	2161.	2246.	6228.	1129.	162.	581.40
1.14	0.56	2.48	0.58	0.120	0.050	0.120	0.069	572.90	532.38
0.000197	900.	2100.	900.	2	0	0	0.00	1783.31	2315.69

*SECNO 12900.000

3265 DIVIDED FLOW

VALLEY SECTION FROM CORPS OF ENGINEERS SECTION V5

12900.00	17.43	590.83	0.00	0.00	591.11	0.27	0.78	0.11	588.00
10390.	454.	8356.	1580.	879.	1790.	1649.	1433.	216.	584.10
1.30	0.52	4.67	0.96	0.120	0.050	0.120	0.067	573.40	208.41
0.000801	1900.	2600.	1300.	2	0	0	0.00	1075.12	1533.27

*SECNO 15800.000

3470 ENCROACHMENT STATIONS= 315.0 1000.0 TYPE= 1 TARGET= 685.000

VALLEY SECTION FROM CORPS OF ENGINEERS SECTION V4

15800.00	17.66	591.86	0.00	0.00	591.97	0.11	0.82	0.05	586.70
10390.	2073.	7334.	933.	2698.	2323.	1293.	1720.	266.	585.30
1.54	0.83	3.18	0.72	0.100	0.040	0.100	0.061	574.20	315.00
0.000210	2300.	2100.	2900.	2	0	0	0.00	685.00	1000.00

*SECNO 17080.000

3265 DIVIDED FLOW

3470 ENCROACHMENT STATIONS= 421.3 582.2 TYPE= 1 TARGET= 210.000

X-SECTION D/S OF TELEGRAPH RD.

17080.00	18.82	592.12	0.00	0.00	592.56	0.43	0.43	0.16	597.30
10390.	27.	10258.	105.	43.	1931.	99.	1840.	278.	578.60
1.61	0.63	3.31	1.06	0.100	0.040	0.100	0.059	573.30	421.30
0.000607	1280.	1280.	1280.	2	0	0	0.00	149.22	582.16

CCHV= 0.300 CEHV= 0.500

*SECNO 17180.000

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	RL	QLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT

PRINTED IN U.S.A.
FORM 561 CO PRINTED BY ROTARY MANIFOLD FORMS.

TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IH2	ICONT	CORAR	TOPWID	ENDST

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 595.00 ELREA= 595.00

J D/S FACE OF TELEGRAPH RD.BRIDGE

17180.00	18.74	592.04	0.00	0.00	592.77	0.73	0.07	0.15	578.00
10390.	0.	10390.	0.	0.	1515.	0.	1844.	278.	579.00
1.62	0.00	6.86	0.00	0.100	0.035	0.100	0.059	573.30	565.00
0.000739	100.	100.	100.	2	0	0	0.00	99.20	664.20

SPECIAL BRIDGE

5070,VARIABLE ELCHU OR ELCHD ON CARD SB NOT SPECIFIED

SB	XK	XKOR	COFQ	RDLEN	BWC	BWP	BAREA	SS	ELCHU	ELCHD
	1.25	1.65	3.00	0.00	88.73	42.00	822.40	0.00	573.30	573.30

*SECNO 17246.000
PRESSURE FLOW

EGPRS	EGLWC	H3	QWEIR	QPR	BAREA	TRAPEZOID AREA	ELLC	ELTRD
596.13	594.92	2.33	0.	10390.	822.	822.	590.90	597.17

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 597.17 ELREA= 597.17

U/S FACE OF TELEGRAPH RD.BRIDGE

17246.00	22.35	595.65	0.00	0.00	596.13	0.48	3.36	0.00	578.00
10390.	0.	10390.	0.	0.	1873.	0.	1847.	278.	579.00
1.62	0.00	5.55	0.00	0.100	0.035	0.100	0.059	573.30	565.00
0.000372	66.	66.	66.	2	0	0	0.00	99.20	664.20

*SECNO 17271.000

3470 ENCROACHMENT STATIONS= 580.0 680.0 TYPE= 1 TARGET= 300.000

X-SECTION U/S OF TELEGRAPH RD.BRIDGE

17271.00	22.56	595.86	0.00	0.00	596.20	0.35	0.03	0.04	578.00
10390.	758.	9379.	253.	968.	1893.	255.	1852.	279.	579.00
1.62	0.78	4.95	0.99	0.100	0.035	0.100	0.058	573.30	380.00
0.000273	100.	100.	100.	2	0	0	0.00	300.00	680.00

*SECNO 18700.000

D/S FACE OF FOOTBRIDGE

PRINTED IN U.S.A.
FORM 1411 GO PRINTED BY ROTARY MANIFOLD FORMS

18700.00	16.05	596.35	0.00	0.00	596.65	0.29	0.43	0.02	590.50
10390.	1065.	8665.	660.	1340.	1822.	1336.	1972.	301.	590.60
1.72	0.79	4.76	0.49	0.100	0.035	0.100	0.056	580.30	80.24
0.000366	1369.	1369.	1369.	2	0	0	0.00	1119.76	1200.00

*SECNO 18701.000

3370 NORMAL BRIDGE,NRD= 19 MIN ELTRD= 590.00 MAX ELLC= 590.30

18701.00	13.80	596.47	0.00	0.00	596.68	0.20	0.00	0.03	590.50
10390.	2219.	6734.	1437.	1378.	1533.	1415.	1972.	301.	590.60
1.72	1.61	4.39	1.02	0.100	0.035	0.100	0.056	582.67	77.66
0.001462	1.	1.	1.	2	0	0	-40.50	1122.34	1200.00

*SECNO 18711.000

SECNO	DEPTH	CWSEL	CRI'S	WSELK	EC	HV	HL	CLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOE	ACN	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IH2	ICONT	CORAR	TOPWID	ENDST

3370 NORMAL BRIDGE,NRD= 19 MIN ELTRD= 590.00 MAX ELLC= 590.30

18711.00	13.82	596.49	0.00	0.00	596.69	0.20	0.01	0.00	590.50
10390.	2221.	6726.	1443.	1381.	1534.	1421.	1973.	302.	590.60
1.72	1.61	4.39	1.02	0.100	0.035	0.100	0.056	582.67	77.48
0.001456	10.	10.	10.	0	0	0	-40.50	1122.52	1200.00

*SECNO 18712.000

U/S FACE OF FOOTBRIDGE

18712.00	13.75	596.42	0.00	0.00	596.76	0.34	0.00	0.07	590.50
10390.	1310.	8248.	832.	1360.	1567.	1378.	1973.	302.	590.60
1.72	0.96	5.26	0.60	0.100	0.035	0.100	0.056	582.67	78.86
0.000530	1.	1.	1.	2	0	0	0.00	1121.14	1200.00

*SECNO 19600.000

3470 ENCROACHMENT STATIONS= 270.0 930.0 TYPE= 1 TARGET= 660.000

X-SECT. D/S OF R.R.BRIDGE

19600.00	16.85	596.85	0.00	0.00	597.18	0.33	0.41	0.00	590.50
10390.	859.	8959.	572.	848.	1804.	1028.	2056.	320.	593.40
1.78	1.01	4.97	0.56	0.100	0.035	0.100	0.055	580.00	270.00
0.000402	900.	900.	900.	2	0	0	0.00	660.00	930.00

CCHV= 0.300 CEHV= 0.500

*SECNO 19700.000

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 598.00 ELREA= 598.00

PRINTED IN U.S.A.
FORM 1415-GO PRINTED BY INTARY MANIFOLD FORMS

D/S FACE OF R.R. BRIDGE

19700.00	14.95	597.25	0.00	0.00	597.28	0.03	0.01	0.09	598.00	
10390.	0.	10390.	0.	0.	7753.	0.	2069.	321.	594.02	
1.80	0.00	1.34	0.00	0.070	0.035	0.070	0.055	582.30	265.01	
0.000066	100.	100.	100.	2	0	0	0.00	604.99	870.00	

West spillway not considered as stated in write up

SPECIAL BRIDGE

5070,VARIABLE ELCHU OR ELCHD ON CARD SB NOT SPECIFIED

SB XK	XKOR	COFQ	RDLEN	BWC	BWP	BAREA	SS	ELCHU	ELCHD
1.25	1.61	3.00	0.00	517.35	51.00	5475.00	0.00	582.30	582.30

*SECNO 19747.000

PRESSURE FLOW

EGPRS	EGLWC	H3	QWEIR	QPR	BAREA	TRAPEZOID AREA	ELLC	ELTRD
597.34	597.29	0.00	0.	10390.	5475.	5475.	594.04	599.20

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 599.20 ELREA= 599.20

U/S FACE OF R.R. BRIDGE

19747.00	15.02	597.32	0.00	0.00	597.34	0.03	0.06	0.00	598.00	
10390.	0.	10390.	0.	0.	7790.	0.	2077.	322.	594.02	
1.81	0.00	1.33	0.00	0.070	0.035	0.070	0.055	582.30	265.00	
0.000065	47.	47.	47.	2	0	0	0.00	605.00	870.00	

CCHV= 0.300 CEHV= 0.500

*SECNO 19748.000

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IH2	ICONT	CORAR	TOPWID	ENDST

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 600.00 ELREA= 600.00

DUMMY X-SECT.U/S OF R.R.BRIDGE

19748.00	15.02	597.32	0.00	0.00	597.35	0.02	0.00	0.00	598.00	
10390.	0.	10390.	0.	0.	8255.	0.	2077.	322.	594.02	
1.81	0.00	1.26	0.00	0.070	0.020	0.070	0.055	582.30	265.17	
0.000010	1.	1.	1.	0	0	0	0.00	604.83	870.00	

SPECIAL BRIDGE

5070,VARIABLE ELCHU OR ELCHD ON CARD SB NOT SPECIFIED

PRINTED IN U.S.A.
FORM 141: GB PRINTED BY ROTARY MANIFOLD FORMS.

SB	XK	XKOR	COFQ	RDLEN	BWC	BWP	BAREA	SS	ELCHU	ELCHD
	0.00	1.50	3.00	0.00	1.00	0.00	9.40	0.00	582.30	582.30

*SECNO 19753.000

PRESSURE AND WEIR FLOW

EGPRS	EGLWC	H3	QWEIR	QPR	BAREA	TRAPEZOID AREA	ELLC	ELTRD
29053.78	597.35	0.00	10389.	34.	9.	9.	591.70	591.70

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE, ELLEA= 600.00 ELREA= 600.00

X-SECT.AT CREST OF DAM

19753.00	15.30	597.60	0.00	0.00	597.63	0.02	0.28	0.00	598.00
10390.	0.	10390.	0.	0.	8428.	0.	2078.	322.	594.02
1.81	0.00	1.23	0.00	0.070	0.020	0.070	0.055	582.30	265.10
0.000009	3.	3.	3.	2	0	10	0.00	604.90	870.00

*SECNO 22300.000

VALLEY SECT. AT CORP. LIMITS

22300.00	10.64	597.64	0.00	0.00	597.65	0.01	0.02	0.00	592.00
10390.	13.	10304.	73.	121.	13241.	824.	2739.	387.	592.00
2.72	0.11	0.78	0.09	0.070	0.020	0.070	0.050	587.00	11.84
0.000005	2547.	2547.	2547.	1	0	0	0.00	1614.49	1626.33

PRINTED IN U.S.A.
FORM 1411 GO PRINTED BY ROTARY MANIFOLD FORMS

```
**************************************************
  HEC2 RELEASE DATED NOV 76 UPDATED FEB 1977
  ERROR CORR -  01
  MODIFICATION -  50,51,52
**************************************************

T1      HURON RIVER
T2      100 YEAR ENCROACHMENT RUN
T3      CITY OF FLATROCK

J1  ICHECK    INQ       NINV      IDIR      STRT      METRIC    HVINS     Q         WSEL      FQ
        0.      7.        0.        0.  0.000000      0.00      0.0       0.   587.760     0.000
J2  NPROF     IPLOT     PRFVS     XSECV     XSECH     FN        ALLDC     IBW       CHNIM     ITRACE
    15.000    0.000    -1.000     0.000     0.000     0.000     0.000     0.000     0.000     15.000
```

PRINTED IN U.S.A.
FORM 1411-00 PRINTED BY WOVARY MANIFOLD FORMS

```
*PROF 2

CCHV=   0.300 CEHV=   0.500
*SECNO 500.000
 2800 NAT Q1=    5236.06  WSEL=     587.66  ENC Q1=   5236.06  WSEL=     587.76  RATIO=  0.0000
 NAT Q1=    5290.  RATIOS LOB,CH,ROB=  0.0071  0.9887  0.0043  WSEL=     587.76
    SECNO     DEPTH     CWSEL     CRIWS     WSELK     EG        HV        HL        OLOSS    BANK ELEV
    Q         QLOB      QCH       QROB      ALOB      ACH       AROB      VOL       TWA    LEFT/RIGHT
    TIME      VLOB      VCH       VROB      XNL       XNCH      XNR       WTN       ELMIN      SSTA
    SLOPE     XLOBL     XLCH      XLOBR     ITRIAL    IH2       ICONT     CORAR     TOPWID     ENDST

3470 ENCROACHMENT STATIONS=       98.0      218.0  TYPE=      4  TARGET=        0.010

          VALLEY SECTION FROM ROCKWOOD FIS

    500.00    18.66    587.76     0.00    587.66    588.19     0.43      0.00      0.00    579.50
     10390.       5.    10385.       0.       16.     1976.       0.        0.        0.    582.30
      0.00     0.35      5.25     0.00     0.120     0.035     0.120     0.000    569.10     98.02
  0.000417       0.        0.       0.         0         0         0      0.00    119.98    218.00


 FLOW DISTRIBUTION FOR SECNO=    500.00          CWSEL=    587.76

 STA=       98.      100.      218.
  PER Q=      0.1      99.9
  AREA=      15.8    1976.5
   VEL=       0.3       5.3

*SECNO 1800.000
 2800 NAT Q1=    6980.31  WSEL=     588.47  ENC Q1=   6980.31  WSEL=     588.57  RATIO=  0.0000
 NAT Q1=    7124.  RATIOS LOB,CH,ROB=  0.5163  0.4558  0.0279  WSEL=     588.57

 3470 ENCROACHMENT STATIONS=      221.3     1867.4  TYPE=      4  TARGET=        0.020

          VALLEY SECTION FROM CORPS OF ENGINEERS SECTION V10

    1800.00    17.18    588.58     0.00    588.47    588.63     0.05      0.33      0.11    581.90
     10390.    5372.     4826.      191.     8005.     1896.      617.      121.       15.    586.70
      0.20     0.67      2.55     0.31     0.120     0.050     0.120     0.058    571.40    221.30
  0.000220      650.      1300.     500.         2         0         0      0.00   1648.06   1869.36


 FLOW DISTRIBUTION FOR SECNO=   1800.00          CWSEL=    588.58

 STA=      221.      390.      590.      790.      890.      990.     1190.     1290.     1460.     1590.     1869.
  PER Q=      1.4       4.3       9.8       5.9       6.5      10.5       4.9       8.3      46.5       1.8
  AREA=     438.6     896.6    1466.6     823.3     873.3    1526.6     733.3    1246.6    1896.3     617.1
   VEL=       0.3       0.5       0.7       0.7       0.8       0.7       0.7       0.7       2.5       0.3

*SECNO 4400.000
 2800 NAT Q1=    5778.86  WSEL=     588.94  ENC Q1=   5778.86  WSEL=     589.04  RATIO=  0.0000
 NAT Q1=    5897.  RATIOS LOB,CH,ROB=  0.0077  0.5201  0.4722  WSEL=     589.04

 3470 ENCROACHMENT STATIONS=       39.0     1460.7  TYPE=      4  TARGET=        0.020

          VALLEY SECTION FROM CORPS OF ENGINEERS SECTION V9
```

PRINTED IN U.S.A.
FORM 1417-39 EQUATED BY ROTARY MANIFOLD FORMS

4400.00	19.67	589.07	0.00	588.94	589.16	0.09	0.51	0.02	580.60
10390.	0.	5356.	5034.	0.	1619.	7122.	442.	61.	581.10
0.46	0.00	3.31	0.71	0.120	0.050	0.120	0.065	569.40	39.00
0.000338	1000.	2600.	1400.	2	0	0	0.00	1421.69	1460.69

FLOW DISTRIBUTION FOR SECNO= 4400.00 CWSEL= 589.07

STA=	39.	130.	300.	500.	700.	850.	1000.	1150.	1300.	1461.
PER Q=	51.5	9.7	8.9	7.9	5.2	4.8	4.4	3.9	3.8	
AREA=	1619.0	1202.2	1214.3	1134.3	783.2	745.7	708.2	663.2	671.2	
VEL=	3.3	0.8	0.8	0.7	0.7	0.7	0.6	0.6	0.6	

*SECNO 6200.000
2800 NAT Q1= 5004.65 WSEL= 589.40 ENC Q1= 5004.65 WSEL= 589.50 RATIO= 0.0000
NAT Q1= 5109. RATIOS LOB,CH,ROB= 0.5779 0.4221 0.0000 WSEL= 589.50

3470 ENCROACHMENT STATIONS= 261.2 1485.0 TYPE= 4 TARGET= 0.020

VALLEY SECTION FROM CORPS OF ENGINEERS SECTION V8

6200.00	18.23	589.53	0.00	589.40	589.61	0.08	0.44	0.00	582.90
10390.	5924.	4466.	0.	6899.	1339.	0.	600.	82.	590.40
0.63	0.86	3.34	0.00	0.120	0.050	0.120	0.068	571.30	261.20
0.000426	600.	1800.	600.	2	0	0	0.00	1222.27	1483.47

FLOW DISTRIBUTION FOR SECNO= 6200.00 CWSEL= 589.53

STA=	261.	300.	450.	550.	650.	800.	950.	1100.	1250.	1385.	1485.
PER Q=	1.4	6.4	4.3	4.3	7.4	8.4	8.5	8.6	7.8	43.0	
AREA=	206.1	829.1	552.7	552.7	904.1	979.1	986.6	994.1	894.7	1338.9	
VEL=	0.7	0.8	0.8	0.8	0.8	0.9	0.9	0.9	0.9	3.3	

*SECNO 8200.000
2800 NAT Q1= 7098.40 WSEL= 589.85 ENC Q1= 7098.40 WSEL= 589.95 RATIO= 0.0000
NAT Q1= 7227. RATIOS LOB,CH,ROB= 0.2140 0.4543 0.3317 WSEL= 589.95

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	GLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IN2	ICONT	CORAR	TOPWID	ENDST

3470 ENCROACHMENT STATIONS= 266.5 1536.0 TYPE= 4 TARGET= 0.018

VALLEY SECTION FROM CORPS OF ENGINEERS SECTION V7

8200.00	18.48	589.98	0.00	589.85	590.03	0.05	0.41	0.01	583.00
10390.	2167.	4782.	3441.	3445.	1842.	4802.	839.	112.	581.20
0.88	0.63	2.60	0.72	0.120	0.050	0.120	0.069	571.50	266.46
0.000211	1000.	2000.	850.	2	0	0	0.00	1269.56	1536.01

FLOW DISTRIBUTION FOR SECNO= 8200.00 CWSEL= 589.98

STA=	266.	430.	630.	810.	930.	980.	1080.	1180.	1230.	1480.	1535.	1536.
PER Q=	3.5	8.7	8.6	46.0	3.1	4.8	6.1	3.4	12.1	3.6	0.0	
AREA=	740.3	1385.5	1319.0	1841.8	431.4	730.3	842.8	451.4	1846.9	488.3	10.7	
VEL=	0.5	0.7	0.7	2.6	0.8	0.7	0.7	0.8	0.7	0.8	0.2	

PRINTED IN U.S.A.
FORM 1411 GO PRINTED BY ROTARY MANIFOLD FORMS,

*SECNO 10300.000
2800 NAT Q1= 7404.08 WSEL= 590.16 ENC Q1= 7404.08 WSEL= 590.26 RATIO= 0.0000
NAT Q1= 7548. RATIOS LOB,CH,ROB= 0.1178 0.5323 0.3499 WSEL= 590.26

3470 ENCROACHMENT STATIONS= 743.2 2224.0 TYPE= 4 TARGET= 0.019

VALLEY SECTION FROM CORPS OF ENGINEERS SECTION V6

10300.00	17.38	590.28	0.00	590.16	590.34	0.05	0.30	0.00	583.40
10390.	1149.	5629.	3612.	1860.	2264.	6092.	1105.	144.	581.40
1.14	0.62	2.49	0.59	0.120	0.050	0.120	0.069	572.90	743.18
0.000195	900.	2100.	900.	2	0	0	0.00	1480.84	2224.02

FLOW DISTRIBUTION FOR SECNO= 10300.00 CWSEL= 590.28

STA=	743.	775.	795.	1025.	1177.	1200.	1825.	1875.	1895.	1925.	2025.	2125.	2224.
PER Q=	0.4	0.6	10.0	54.2	1.1	27.2	2.4	0.5	0.3	1.1	1.1	1.1	
AREA=	116.0	115.6	1628.7	2264.4	175.5	4425.8	374.1	102.6	92.4	308.1	308.1	305.1	
VEL=	0.4	0.6	0.6	2.5	0.7	0.6	0.7	0.5	0.4	0.4	0.4	0.4	

*SECNO 12900.000
2800 NAT Q1= 3670.26 WSEL= 590.83 ENC Q1= 3670.26 WSEL= 590.93 RATIO= 0.0000
NAT Q1= 3742. RATIOS LOB,CH,ROB= 0.0469 0.7983 0.1548 WSEL= 590.93

3265 DIVIDED FLOW

3470 ENCROACHMENT STATIONS= 447.8 1409.7 TYPE= 4 TARGET= 0.019

VALLEY SECTION FROM CORPS OF ENGINEERS SECTION V5

12900.00	17.55	590.95	0.00	590.83	591.23	0.28	0.78	0.11	588.00
10390.	397.	8452.	1541.	651.	1805.	1496.	1394.	185.	584.10
1.29	0.61	4.68	1.03	0.120	0.050	0.120	0.066	573.40	447.75
0.000797	1900.	2600.	1300.	2	0	0	0.00	712.19	1409.67

FLOW DISTRIBUTION FOR SECNO= 12900.00 CWSEL= 590.95

STA=	448.	700.	730.	860.	880.	950.	1375.	1410.
PER Q=	3.2	0.6	81.3	1.5	4.4	8.0	0.9	
AREA=	565.7	85.4	1805.3	127.9	405.8	840.2	122.4	
VEL=	0.6	0.7	4.7	1.2	1.1	1.0	0.8	

*SECNO 15800.000

3470 ENCROACHMENT STATIONS= 315.0 1000.0 TYPE= 1 TARGET= 685.000

VALLEY SECTION FROM CORPS OF ENGINEERS SECTION V4

15800.00	17.76	591.96	0.00	591.86	592.08	0.11	0.80	0.05	586.70
10390.	2088.	7357.	944.	2533.	2340.	1315.	1672.	225.	585.30
1.54	0.82	3.14	0.72	0.100	0.040	0.100	0.061	574.20	315.00
0.000204	2300.	2100.	2900.	2	0	0	0.00	685.00	1000.00

FLOW DISTRIBUTION FOR SECNO= 15800.00 CWSEL= 591.96

FORM 121-68 PRINTED IN U.S.A.
FORM 121-68 PRINTED BY ROTARY BURSTFOLD FORMS.

```
 STA=      315.      400.      500.      600.      640.      795.     1000.
   PER Q=     6.0       7.0       5.4       1.6      70.8       9.1
    AREA=   742.8     831.4     716.4     242.6    2339.7    1314.8
     VEL=     0.8       0.9       0.8       0.7       3.1       0.7

 *SECNO 17080.000

 3265 DIVIDED FLOW

 3470 ENCROACHMENT STATIONS=      421.3      582.2  TYPE=     1  TARGET=      210.000

          X-SECTION D/S OF TELEGRAPH RD.

  17080.00     18.92    592.22      0.00    592.12    592.65      0.43      0.42      0.16    597.30
   10390.        27.     10257.      105.       44.      1944.      100.      1794.      237.     578.60
      1.61      0.63      5.28      1.05     0.100     0.040     0.100     0.059    573.30    421.30
 0.000595     1280.     1280.     1280.         2         0         0      0.00    149.44    582.16

 FLOW DISTRIBUTION FOR SECNO=  17080.00          CWSEL=     592.22

 STA=      421.      424.      431.      575.      582.
   PER Q=     0.1       0.2      98.7       1.0
    AREA=    16.0      27.6    1944.2     100.0
     VEL=     0.5       0.7       5.3       1.1

 CCHV=   0.300 CEHV=   0.500
 *SECNO 17180.000
    SECNO     DEPTH     CWSEL     CRIWS     WSELK     EG        HV        HL        OLOSS     BANK ELEV
    Q         QLOB      QCH       QROB      ALOB      ACH       AROB      VOL       TWA    LEFT/RIGHT
    TIME      VLOB      VCH       VROB      XNL       XNCH      XNR       WTN       ELMIN       SSTA
    SLOPE     XLOBL     XLCH      XLOBR     ITRIAL    IH2       ICONT     CORAR     TOPWID      ENDST

 3470 ENCROACHMENT STATIONS=      133.0      795.0  TYPE=     1  TARGET=      662.000

 3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA=      595.00 ELREA=      595.00

          D/S FACE OF TELEGRAPH RD.BRIDGE

  17180.00     18.84    592.14      0.00    592.04    592.86      0.72      0.07      0.15    576.00
   10390.         0.     10390.        0.        0.      1524.        0.      1798.      237.     579.00
      1.62      0.00      6.82      0.00     0.100     0.035     0.100     0.059    573.30    565.00
 0.000724      100.      100.      100.         2         0         0      0.00     99.20    664.20

 FLOW DISTRIBUTION FOR SECNO=  17180.00          CWSEL=     592.14

 STA=      565.      664.
   PER Q=   100.0
    AREA=  1524.3
     VEL=     6.4

 SPECIAL BRIDGE

 5070 VARIABLE ELCHU OR ELCHD ON CARD SB NOT SPECIFIED
```

PRINTED IN U.S.A.
FORM 1411 GO PRINTED BY ROTARY MANIFOLD FORMS.

SB	XK	XKOR	COFQ	RDLEN	BWC	BWP	BAREA	SS	ELCHU	ELCHD
	1.25	1.65	3.00	0.00	88.73	42.00	822.40	0.00	573.30	573.30

*SECNO 17246.000

PRESSURE FLOW

EGPRS	EGLWC	H3	QWEIR	QPR	BAREA	TRAPEZOID AREA	ELLC	ELTRD
596.23	594.97	2.28	0.	10390.	822.	822.	590.90	597.17

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 597.17 ELREA= 597.17

U/S FACE OF TELEGRAPH RD.BRIDGE

17246.00	22.46	595.76	0.00	595.65	596.23	0.47	3.37	0.00	578.00	
10390.	0.	10390.	0.	0.	1883.	0.	1800.	238.	579.00	
1.62	0.00	5.52	0.00	0.100	0.035	0.100	0.059	573.30	565.00	
0.000366	66.	66.	66.	2	0	0	0.00	99.20	664.20	

FLOW DISTRIBUTION FOR SECNO= 17246.00 CWSEL= 595.76

STA=	565.	664.
PER Q=	100.0	
AREA=	1883.1	
VEL=	5.5	

*SECNO 17271.000

3470 ENCROACHMENT STATIONS= 380.0 680.0 TYPE= 1 TARGET= 300.000

X-SECTION U/S OF TELEGRAPH RD.BRIDGE

17271.00	22.66	595.96	0.00	595.86	596.30	0.34	0.03	0.04	578.00	
10390.	772.	9365.	253.	987.	1903.	256.	1806.	238.	579.00	
1.62	0.78	4.92	0.99	0.100	0.035	0.100	0.058	573.30	380.00	
0.000267	100.	100.	100.	2	0	0	0.00	300.00	680.00	

FLOW DISTRIBUTION FOR SECNO= 17271.00 CWSEL= 595.96

STA=	380.	535.	556.	565.	664.	680.
PER Q=	4.2	1.7	1.5	90.1	2.4	
AREA=	679.1	177.7	130.1	1903.3	256.4	
VEL=	0.6	1.0	1.2	4.9	1.0	

*SECNO 18700.000

D/S FACE OF FOOTBRIDGE

18700.00	16.15	596.45	0.00	596.35	596.73	0.29	0.42	0.02	590.50	
10390.	1084.	8610.	696.	1371.	1833.	1600.	1928.	260.	590.60	
1.72	0.79	4.70	0.50	0.100	0.035	0.100	0.056	580.30	78.15	
0.000354	1369.	1369.	1369.	2	0	0	0.00	1121.85	1200.00	

PRINTED IN U.S.A.
FORM 141-80 PRINTED BY ROTARY MARIFOLD FORMS

FLOW DISTRIBUTION FOR SECNO= 18700.00 CWSEL= 596.45

STA=	78.	110.	310.	400.	520.	620.	720.	1000.	1200.
PER Q=	0.1	5.3	5.1	82.9	2.9	1.0	1.8	1.0	
AREA=	23.1	789.8	557.9	1832.9	414.9	219.9	475.8	289.8	
VEL=	0.2	0.7	0.9	4.7	0.7	0.5	0.4	0.4	

*SECNO 18701.000

3370 NORMAL BRIDGE,NRD= 19 MIN ELTRD= 590.00 MAX ELLC= 590.30

18701.00	13.90	596.57	0.00	596.47	596.76	0.20	0.00	0.03	590.50
10390.	2239.	6650.	1501.	1409.	1545.	1481.	1928.	260.	590.60
1.72	1.59	4.31	1.01	0.100	0.035	0.100	0.056	582.67	75.54
0.001391	1.	1.	1.	2	0	0	-40.50	1124.46	1200.00

FLOW DISTRIBUTION FOR SECNO= 18701.00 CWSEL= 596.57

STA=	76.	110.	310.	400.	520.	620.	720.	1000.	1200.
PER Q=	0.1	11.1	10.4	64.0	6.0	2.2	4.0	2.2	
AREA=	27.0	813.6	568.6	1544.5	426.8	231.8	509.0	313.6	
VEL=	0.5	1.4	1.9	4.3	1.5	1.0	0.8	0.7	

*SECNO 18711.000

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IH2	ICONT	CORAR	TOPWID	ENDST

3370 NORMAL BRIDGE,NRD= 19 MIN ELTRD= 590.00 MAX ELLC= 590.30

18711.00	13.91	596.58	0.00	596.49	596.78	0.19	0.01	0.00	590.50
10390.	2240.	6643.	1506.	1412.	1546.	1487.	1929.	261.	590.60
1.72	1.59	4.30	1.01	0.100	0.035	0.100	0.056	582.67	75.36
0.001385	10.	10.	10.	0	0	0	-40.50	1124.64	1200.00

FLOW DISTRIBUTION FOR SECNO= 18711.00 CWSEL= 596.58

STA=	75.	110.	310.	400.	520.	620.	720.	1000.	1200.
PER Q=	0.1	11.1	10.4	63.9	6.0	2.2	4.1	2.3	
AREA=	27.3	815.2	569.4	1545.5	427.6	232.6	511.3	315.2	
VEL=	0.5	1.4	1.9	4.3	1.5	1.0	0.8	0.7	

*SECNO 18712.000

U/S FACE OF FOOTBRIDGE

18712.00	13.84	596.51	0.00	596.42	596.85	0.33	0.00	0.07	590.50
10390.	1330.	8185.	875.	1392.	1579.	1445.	1929.	261.	590.60
1.72	0.96	5.19	0.51	0.100	0.035	0.100	0.056	582.67	76.71
0.000509	1.	1.	1.	2	0	0	0.00	1123.29	1200.00

FLOW DISTRIBUTION FOR SECNO= 18712.00 CWSEL= 596.51

STA=	77.	110.	310.	400.	520.	620.	720.	1000.	1200.

PRINTED IN U.S.A.
FORM 1411-30 PRINTED BY ROTARY MANIFOLD FORMS.

PER Q=	0.1	6.5	6.2	78.8	3.5	1.3	2.3	1.3
AREA=	25.2	802.9	563.8	1578.6	421.4	226.4	494.0	302.9
VEL=	0.3	0.8	1.1	5.2	0.9	0.6	0.5	0.4

*SECNO 19600.000

3470 ENCROACHMENT STATIONS= 270.0 930.0 TYPE= 1 TARGET= 660.000

X-SECT. D/S OF R.R.BRIDGE

19600.00	16.92	596.92	0.00	596.85	597.25	0.33	0.40	0.00	590.50
10390.	865.	8931.	594.	858.	1813.	1060.	2013.	279.	593.40
1.78	1.01	4.93	0.56	0.100	0.035	0.100	0.055	580.00	270.00
0.000392	900.	900.	900.	2	0	0	0.00	660.00	930.00

FLOW DISTRIBUTION FOR SECNO= 19600.00 CWSEL= 596.92

STA=	270.	310.	400.	520.	620.	720.	930.
PER Q=	2.3	6.0	86.0	2.0	1.5	2.3	
AREA=	257.0	600.7	1813.3	322.4	267.4	469.7	
VEL=	0.9	1.0	4.9	0.6	0.6	0.5	

CCHV= 0.300 CEHV= 0.500

*SECNO 19700.000

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 598.00 ELREA= 598.00

D/S FACE OF R.R. BRIDGE

19700.00	15.02	597.32	0.00	597.25	597.35	0.03	0.01	0.09	598.00
10390.	0.	10390.	0.	0.	7794.	0.	2026.	281.	594.02
1.80	0.00	1.33	0.00	0.070	0.035	0.070	0.055	582.30	265.00
0.000065	100.	100.	100.	2	0	0	0.00	605.00	870.00

FLOW DISTRIBUTION FOR SECNO= 19700.00 CWSEL= 597.32

STA=	265.	870.
PER Q=	100.0	
AREA=	7794.4	
VEL=	1.3	

SPECIAL BRIDGE

507C,VARIABLE ELCHU OR ELCHD ON CARD SB NOT SPECIFIED

SB	XK	XKOR	COFQ	RDLEN	BWC	BWP	BAREA	SS	ELCHU	ELCHD
	1.25	1.61	3.00	0.00	517.35	51.00	5475.00	0.00	582.30	582.30

*SECNO 19747.000

PRESSURE FLOW

EGPRS	EGLWC	H3	QWEIR	QPR	BAREA	TRAPEZOID AREA	ELLC	ELTRD
597.41	597.36	0.00	0.	10390.	5475.	5475.	594.04	599.20

FORM 1311 SO PRINTED BY ROPAKY MANIFOLD FORMS
PRINTED IN U.S.A.

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 599.20 ELREA= 599.20

U/S FACE OF R.R. BRIDGE

19747.00	15.09	597.39	0.00	597.32	597.41	0.03	0.06	0.00	598.00
10390.	0.	10390.	0.	0.	7832.	0.	2035.	281.	594.02
1.81	0.00	1.33	0.00	0.070	0.035	0.070	0.055	582.30	265.00
0.000064	47.	47.	47.	2	0	0	0.00	605.00	870.00

FLOW DISTRIBUTION FOR SECNO= 19747.00 CWSEL= 597.39

STA= 265. 870.
PER Q= 100.0
AREA= 7832.1
VEL= 1.3

CCHV= 0.300 CEHV= 0.500

*SECNO 19748.000

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	II2	ICONT	CORAR	TOPWID	ENDST

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 600.00 ELREA= 600.00

DUMMY X-SECT.U/S OF R.R.BRIDGE

19748.00	15.09	597.39	0.00	597.32	597.41	0.02	0.00	0.00	598.00
10390.	0.	10390.	0.	0.	8297.	0.	2035.	281.	594.02
1.81	0.00	1.25	0.00	0.070	0.020	0.070	0.055	582.30	265.16
0.000010	1.	1.	1.	0	0	0	0.00	604.84	870.00

FLOW DISTRIBUTION FOR SECNO= 19748.00 CWSEL= 597.39

STA= 265. 870.
PER Q= 100.0
AREA= 8296.5
VEL= 1.3

SPECIAL BRIDGE

5070,VARIABLE ELCHU OR ELCHD ON CARD SB NOT SPECIFIED

SB	XK	XKOR	COFQ	RDLEN	BWC	BWP	BAREA	SS	ELCHU	ELCHD
	0.00	1.50	3.00	0.00	1.00	0.00	9.40	0.00	582.30	582.30

*SECNO 19753.000
PRESSURE AND WEIR FLOW

EGPRS	EGLWC	H3	QWEIR	QPR	BAREA	TRAPEZOID AREA	ELLC	ELTRD
29053.85	597.41	0.00	10356.	34.	9.	9.	591.70	591.70

PRINTED IN U.S.A.
FORM 1411 CO-PRINTED BY ROTARY MANIFOLD FORMS

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 600.00 ELREA= 600.00

X-SECT.AT CREST OF DAM

19753.00	15.37	597.67	0.00	597.60	597.69	0.02	0.28	0.00	598.00
10390.	0.	10390.	0.	0.	8468.	0.	2036.	281.	594.02
1.81	0.00	1.23	0.00	0.070	0.020	0.070	0.055	582.30	265.08
0.000009	3.	3.	3.	2	0	10	0.00	604.92	870.00

FLOW DISTRIBUTION FOR SECNO= 19753.00 CWSEL= 597.67

STA= 265. 870.
PER Q= 100.0
AREA= 8467.9
VEL= 1.2

*SECNO 22300.000
2800 NAT Q1= 47788.79 WSEL= 597.64 ENC Q1= 48182.97 WSEL= 597.74 RATIO= -0.0082
NAT Q1= 48603. RATIOS LOB,CH,ROB= 0.0013 0.9914 0.0073 WSEL= 597.74

3470 ENCROACHMENT STATIONS= 50.0 1300.0 TYPE= 4 TARGET= 0.009

VALLEY SECT. AT CORP. LIMITS

22300.00	10.70	597.70	0.00	597.64	597.71	0.01	0.02	0.00	592.00
10390.	0.	10390.	0.	0.	13319.	0.	2673.	335.	592.00
2.72	0.00	0.78	0.00	0.070	0.020	0.070	0.050	587.00	50.00
0.000005	2547.	2547.	2547.	1	0	0	0.00	1250.00	1300.00

FLOW DISTRIBUTION FOR SECNO= 22300.00 CWSEL= 597.70

STA= 50. 1300.
PER Q= 100.0
AREA= 13319.5
VEL= 0.8

PRINTED IN U.S.A.
FORM 1471-SD PRINTED BY ROTARY MANIFOLD FORMS.

****
HEC2 RELEASE DATED NOV 76 UPDATED FEB 1977
ERROR CORR - 01
MODIFICATION - 50,51,52
****

NOTE- ASTERISK (*) AT LEFT OF CROSS-SECTION NUMBER INDICATES MESSAGE IN SUMMARY OF ERRORS LIST

HURON RIVER

SUMMARY PRINTOUT TABLE 150

SECNO	XLCH	ELTRD	ELLC	ELMIN	Q	CWSEL	CRIWS	EG	10K*S	VCH	AREA	.01K
500.000	0.00	0.00	0.00	569.10	10390.00	587.66	0.00	588.08	3.94	5.23	2172.94	5236.06
500.000	0.00	0.00	0.00	569.10	10390.00	587.76	0.00	588.19	4.17	5.25	1992.25	5085.80
1800.000	1300.00	0.00	0.00	571.40	10390.00	588.47	0.00	588.51	2.22	2.54	10912.77	6980.31
1800.000	1300.00	0.00	0.00	571.40	10390.00	588.58	0.00	588.63	2.20	2.55	10518.36	7003.59
4400.000	2600.00	0.00	0.00	569.40	10390.00	588.94	0.00	589.04	3.23	3.40	8974.02	5778.86
4400.000	2600.00	0.00	0.00	569.40	10390.00	589.07	0.00	589.16	3.38	3.31	8741.37	5648.41
6200.000	1800.00	0.00	0.00	571.30	10390.00	589.40	0.00	589.48	4.31	3.34	8380.36	5004.65
6200.000	1800.00	0.00	0.00	571.30	10390.00	589.53	0.00	589.61	4.26	3.34	8238.18	5032.06
8200.000	2000.00	0.00	0.00	571.50	10390.00	589.85	0.00	589.91	2.14	2.60	10306.11	7098.40
8200.000	2000.00	0.00	0.00	571.50	10390.00	589.98	0.00	590.03	2.11	2.60	10088.16	7151.21
10300.000	2100.00	0.00	0.00	572.90	10390.00	590.16	0.00	590.21	1.97	2.48	10635.29	7404.08
10300.000	2100.00	0.00	0.00	572.90	10390.00	590.28	0.00	590.34	1.95	2.49	10216.48	7432.29
12900.000	2600.00	0.00	0.00	573.40	10390.00	590.83	0.00	591.11	8.01	4.67	4317.61	3670.26
12900.000	2600.00	0.00	0.00	573.40	10390.00	590.95	0.00	591.23	7.97	4.68	3952.79	3679.54
15800.000	2100.00	0.00	0.00	574.20	10390.00	591.86	0.00	591.97	2.10	3.18	6113.84	7164.33
15800.000	2100.00	0.00	0.00	574.20	10390.00	591.96	0.00	592.08	2.04	3.14	6187.59	7276.57
17080.000	1280.00	0.00	0.00	573.30	10390.00	592.12	0.00	592.56	6.07	5.31	2073.29	4217.47
17080.000	1280.00	0.00	0.00	573.30	10390.00	592.22	0.00	592.65	5.95	5.28	2087.80	4261.25
17180.000	100.00	0.00	0.00	573.30	10390.00	592.04	0.00	592.77	7.39	6.86	1514.65	3823.11
17180.000	100.00	0.00	0.00	573.30	10390.00	592.14	0.00	592.86	7.24	6.82	1524.31	3862.74
17246.000	66.00	597.17	590.90	573.30	10390.00	595.65	0.00	596.13	3.72	5.55	1872.99	5384.04
17246.000	66.00	597.17	590.90	573.30	10390.00	595.76	0.00	596.23	3.66	5.52	1883.14	5430.84
17271.000	100.00	0.00	0.00	573.30	10390.00	595.86	0.00	596.20	2.73	4.95	3115.86	6291.47
17271.000	100.00	0.00	0.00	573.30	10390.00	595.96	0.00	596.30	2.67	4.92	3146.55	6357.10
18700.000	1369.00	0.00	0.00	580.30	10390.00	596.35	0.00	596.65	3.66	4.76	4497.53	5429.03
18700.000	1369.00	0.00	0.00	580.30	10390.00	596.45	0.00	596.73	3.54	4.70	4604.25	5520.80

PRINTED IN U.S.A.
FORM 1411-GB PRINTED BY ROTAPY MAILIFOLD "FORMS"

SECNO	XLCH	ELTRD	ELLC	ELMIN	Q	CWSEL	CRIWS	EG	10K*S	VCH	AREA	.01K
18701.000	1.00	590.00	590.30	582.67	10390.00	596.47	0.00	596.68	14.62	4.39	4326.28	2716.91
18701.000	1.00	590.00	590.30	582.67	10390.00	596.57	0.00	596.76	13.91	4.31	4434.89	2785.62
18711.000	10.00	590.00	590.30	582.67	10390.00	596.49	0.00	596.69	14.56	4.39	4335.60	2722.76
18711.000	10.00	590.00	590.30	582.67	10390.00	596.58	0.00	596.78	13.85	4.30	4444.23	2791.58
18712.000	1.00	0.00	0.00	582.67	10390.00	596.42	0.00	596.76	5.30	5.26	4305.71	4512.52
18712.000	1.00	0.00	0.00	582.67	10390.00	596.51	0.00	596.85	5.09	5.19	4415.31	4603.54
19600.000	900.00	0.00	0.00	580.00	10390.00	596.85	0.00	597.18	4.02	4.97	3679.82	5183.51
19600.000	900.00	0.00	0.00	580.00	10390.00	596.92	0.00	597.25	3.92	4.93	3730.58	5244.45
19700.000	100.00	0.00	0.00	582.30	10390.00	597.25	0.00	597.28	0.66	1.34	7752.53	12747.58
19700.000	100.00	0.00	0.00	582.30	10390.00	597.32	0.00	597.35	0.65	1.33	7794.44	12862.06
19747.000	47.00	599.20	594.04	582.30	10390.00	597.32	0.00	597.34	0.65	1.33	7790.47	12851.20
19747.000	47.00	599.20	594.04	582.30	10390.00	597.39	0.00	597.41	0.64	1.33	7832.10	12965.27
19748.000	1.00	0.00	0.00	582.30	10390.00	597.32	0.00	597.35	0.10	1.26	8254.76	33391.87
19748.000	1.00	0.00	0.00	582.30	10390.00	597.39	0.00	597.41	0.10	1.25	8296.55	33671.61
19753.000	3.00	591.70	591.70	582.30	10390.00	597.60	0.00	597.63	0.09	1.23	8427.54	34554.44
19753.000	3.00	591.70	591.70	582.30	10390.00	597.67	0.00	597.69	0.09	1.23	8467.86	34827.92
22300.000	2547.00	0.00	0.00	587.00	10390.00	597.64	0.00	597.65	0.05	0.78	14185.77	47788.79
22300.000	2547.00	0.00	0.00	587.00	10390.00	597.70	0.00	597.71	0.05	0.78	13319.46	47571.48

FORM 1411-GO PRINTED BY ROTARY MANIFOLD FORMS.
PRINTED IN U.S.A.

HURON RIVER

SUMMARY PRINTOUT TABLE 150

SECNO	Q	CWSEL	DIFWSP	DIFWSX	DIFKWS	TOPWID	XLCH
500.000	10390.00	587.66	0.00	0.00	0.00	180.69	0.00
500.000	10390.00	587.76	0.00	0.00	0.10	119.98	0.00
1800.000	10390.00	588.47	0.00	0.81	0.00	1906.41	1300.00
1800.000	10390.00	588.58	0.00	0.82	0.12	1648.06	1300.00
4400.000	10390.00	588.94	0.00	0.48	0.00	1592.11	2600.00
4400.000	10390.00	589.07	0.00	0.49	0.13	1421.69	2600.00
6200.000	10390.00	589.40	0.00	0.46	0.00	1299.65	1800.00
6200.000	10390.00	589.53	0.00	0.46	0.13	1222.27	1800.00
8200.000	10390.00	589.85	0.00	0.45	0.00	1428.59	2000.00
8200.000	10390.00	589.98	0.00	0.45	0.12	1269.56	2000.00
10300.000	10390.00	590.16	0.00	0.31	0.00	1783.31	2100.00
10300.000	10390.00	590.23	0.00	0.30	0.12	1480.84	2100.00
12900.000	10390.00	590.83	0.00	0.67	0.00	1075.12	2600.00
12900.000	10390.00	590.95	0.00	0.67	0.12	712.19	2600.00
15800.000	10390.00	591.86	0.00	1.03	0.00	685.00	2100.00
15800.000	10390.00	591.96	0.00	1.02	0.11	685.00	2100.00
17080.000	10390.00	592.12	0.00	0.27	0.00	149.22	1280.00
17080.000	10390.00	592.22	0.00	0.26	0.10	149.44	1280.00
17180.000	10390.00	592.04	0.00	-0.08	0.00	99.20	100.00
17180.000	10390.00	592.14	0.00	-0.08	0.10	99.20	100.00
17246.000	10390.00	595.65	0.00	3.61	0.00	99.20	66.00
17246.000	10390.00	595.76	0.00	3.62	0.10	99.20	66.00
17271.000	10390.00	595.86	0.00	0.20	0.00	300.00	100.00
17271.000	10390.00	595.96	0.00	0.20	0.10	300.00	100.00
18700.000	10390.00	596.35	0.00	0.50	0.00	1119.76	1369.00
18700.000	10390.00	596.45	0.00	0.49	0.10	1121.85	1369.00
18701.000	10390.00	596.47	0.00	0.12	0.00	1122.34	1.00
18701.000	10390.00	596.57	0.00	0.12	0.10	1124.46	1.00
18711.000	10390.00	596.49	0.00	0.02	0.00	1122.52	10.00
18711.000	10390.00	596.58	0.00	0.02	0.10	1124.64	10.00
18712.000	10390.00	596.42	0.00	-0.07	0.00	1121.14	1.00
18712.000	10390.00	596.51	0.00	-0.07	0.10	1123.29	1.00
19600.000	10390.00	596.85	0.00	0.43	0.00	660.00	900.00
19600.000	10390.00	596.92	0.00	0.41	0.08	660.00	900.00
19700.000	10390.00	597.25	0.00	0.41	0.00	604.99	100.00

PRINTED IN U.S.A.
FORM 5411 OR PRINTED BY BOYARD MANIFOLD FORMS.

19700.000 10390.00 597.32 0.00 0.40 0.07 605.00 100.00

PRINTED IN U.S.A.
FORM 1411.00 PRINTED BY NOTARY MANIFOLD FORMS.

SECNO	Q	CWSEL	DIFWSP	DIFWSX	DIFKWS	TOPWID	XLCH
19747.000	10390.00	597.32	0.00	0.06	0.00	605.00	47.00
19747.000	10390.00	597.39	0.00	0.06	0.07	605.00	47.00
19748.000	10390.00	597.32	0.00	0.00	0.00	604.83	1.00
19748.000	10390.00	597.39	0.00	0.00	0.07	604.84	1.00
19753.000	10390.00	597.60	0.00	0.28	0.00	604.90	3.00
19753.000	10390.00	597.67	0.00	0.28	0.07	604.92	3.00
22300.000	10390.00	597.64	0.00	0.03	0.00	1614.49	2547.00
22300.000	10390.00	597.70	0.00	0.03	0.07	1250.00	2547.00

SUMMARY OF ERRORS

PRINTED IN U.S.A.
FORM 1411 GO PRINTED BY ROTARY MANIFOLD FORMS.

FLOODWAY DATA, HURON RIVER
PROFILE NO. 2

STATION	FLOODWAY WIDTH (FT)	FLOODWAY SECTION AREA	FLOODWAY MEAN VELOCITY	WATER SURFACE ELEVATION WITH FLOODWAY	WITHOUT FLOODWAY	DIFFERENCE
500.000	120.	1992.	5.2	587.8	587.7	0.1
1800.000	1648.	10518.	1.0	588.6	588.5	0.1
4400.000	1422.	8741.	1.2	589.0	588.9	0.1
6200.000	1222.	8238.	1.3	589.5	589.4	0.1
8200.000	1270.	10088.	1.0	590.0	589.9	0.1
10300.000	1481.	10216.	1.0	590.3	590.2	0.1
12900.000	712.	3953.	2.6	590.9	590.8	0.1
15800.000	685.	6188.	1.7	592.0	591.9	0.1
17080.000	149.	2088.	5.0	592.2	592.1	0.1
17180.000	99.	1524.	6.8	592.1	592.0	0.1
17246.000	99.	1883.	5.5	595.8	595.7	0.1
17271.000	300.	3147.	3.3	596.0	595.9	0.1
18700.000	1122.	4604.	2.3	596.5	596.4	0.1
18701.000	1124.	4435.	2.3	596.6	596.5	0.1
18711.000	1125.	4444.	2.3	596.6	596.5	0.1
18712.000	1123.	4415.	2.4	596.5	596.4	0.1
19600.000	660.	3731.	2.8	596.9	596.8	0.1
19700.000	605.	7794.	1.3	597.4	597.3	0.1
19747.000	605.	7832.	1.3	597.4	597.3	0.1
19748.000	605.	8297.	1.3	597.4	597.3	0.1
19753.000	605.	8468.	1.2	597.7	597.6	0.1
22300.000	1250.	13319.	0.8	597.7	597.6	0.1

00BREAK00

1) COUNTY: Wayne

2) STUDY NAME: City of Flat Rock

3) WATERCOURSE: Huron River

4) DOCUMENT TYPE: Report

00BREAK00

IV. HURON RIVER (DETAILED)

Detailed studies of the Huron River were performed from the corporate boundary of Flat Rock/Rockwood to the west corporate boundary of Flat Rock at Inkster Road. The downstream cross-section was the most upstream section used in the Rockwood FIS (Reference 1). Cross section information was obtained from U.S. Army Corps of Engineer survey data on the Huron River (Reference 4). This additional information was supplemented by U.S.G.S. Quad Maps of the study area which consist of 5 foot interval contour data (Reference 2). The flood plain of the Huron River within the study reach varies from grassy lawns to woods.

Cross section locations are shown in Exhibit 1. Table 5 cross references section designations by showing computer section numbers which corresponds to the cross section letters shown in Exhibit 1.

Exhibit 8 contains bridge sketches as well as computations for total bridge loss coefficients.

Table 6 lists discharges that have been approved by the MDNR for the Huron River.

A. METHOD OF ANALYSIS

The HEC-2 backwater program was used in developing water surface profiles (Reference 3).

Table 6 also contains selected flood elevations from the HEC-2 printouts. HEC-2 printouts including computer cross section plots are presented as Exhibit 9. Water surface profiles resulting from the backwater analyses are presented as Exhibit 10. (Exhibit 9 is contained in the 11" x 15" folder enclosed with this report).

B. VARIABLES AND COEFFICIENTS

Roughness coefficients (Mannings "n") were estimated by field inspection at each cross section. The roughness values vary from .02 to .05 for the channel and .07 to .12 for the overbanks. These values are consistent with roughness values recommended and used in engineering practice.

Expansion and contraction coefficients are .3 and .1 respectively for mild transitions and .3 and .5 respectively for abrubt transitions. Expansion and contraction ratios for effective flow areas are 4:1 and 1:1 respectively.

All weirs were assigned a coefficient of 3.0. Pier shape coefficients varied from 1.05 to 1.25.

C. HIGH WATER MARKS

The Army Corps of Engineers (Reference 4) lists the water levels measured during the April, 1947 flood as:

FIS x-Section	Elevation
D	586.7
E	587.2
F	587.8
G	588.8
H	589.2
J	589.5
K	590.7

The 10 year flood profile as presented in this report generally runs slightly higher than the 1947 flood elevations. Losses through Telegraph Road for the 10 year storm are the same as the losses experienced in the 1947 storm.

The past Flood Report of Southeast Michigan Flood of June, 1968, (Reference 5) lists the following two within the City of Flat Rock:

Location	H.W.M. Elev.
29645 Evergreen (Approximately at FIS x-Section G)	589.30
269161 James St. (Between Dam and Western Corp. Limit Between FIS x-Section Q & R	593.01

A flood profile for the 1968 storm was developed with the HEC-2 computer program (see Exhibit 9) and the historical flood elevation at cross section G was matched to insure the accuracy of the computer model.

The flood elevation between sections Q and R are considerably higher than the 1968 high water mark due to changes in the hydraulic characteristics of the Huron River upstream of Telegraph Road. Within the past 10 years, the gates on the control structure for the diversion channel located west of the main channel have been ordered closed by the Michigan Department of Natural Resources. Therefore, flood flows which were once divided between the two channels must now discharge in the main channel; thus, present day floods will produce higher flood elevations than the historical floods.

D. STARTING CONDITIONS

The starting water surface elevation used in all backwater computations were the water surface elevations computed for cross section A in the Rockwood FIS.

E. SPECIAL PROBLEMS

Divided flow occurs upstream of Telegraph Road; however, as explained in section C above, the main gates on the control structure for the westerly channel have been closed for years and will remain closed as ordered by the Michigan Department of Natural Resources. A small amount of flow is maintained in the west channel due to an overflow spillway and a fish raceway. These spillways are 9 feet wide compared to the 180 foot wide spillway in the main channel. Furthermore, during major storms these secondary spillways will not act as free flowing weirs due to the configuration of the structure; therefore, flow in the west channel is a small percentage of the total flood flow and is neglected. However, a floodway is maintained at the banks of the west channel.

F. GENERAL

Computed water-surface elevations were developed to an accuracy of .5 foot for floods of the selected recurrence intervals.

All elevations are referenced to the National Geodetic Vertical Datum of 1929 (NGVD). This datum is equivalent to the U.S. Geological Survey (USGS) datum.

The hydraulic analyses for this study are based only on the effects of flow unobstructed by ice or debris. The flood elevations are considered valid only if hydraulic structures, in general, remain unobstructed and do not fail.

TABLE 5
CITY OF FLAT ROCK
HURON RIVER

CROSS SECTION	COMPUTER NO.	ARMY CORPS OF ENGINEERS NO.	DESCRIPTION
A	500		+ 500' u/s of Rockwood/Flat Rock Corp. Limits(sect. from Rockwood FIS)
B	1,800	V-10 (40800)	+ 1800' u/s of Rockwood/ Flat Rock Corp. Limits
C	4,400	V-9 (42900)	+4400' u/s of Rockwood/ Flat Rock Corp. Limits
D	6,200	V-8 (44700)	+6200' u/s of Rockwood/ Flat Rock Corp. Limits
E	8,200	V-7 (46700)	+ 8200' u/s of Rockwood/ Flat Rock Corp. Limits
F	10,300	V-6 (48800)	+ 10300' u/s of Rockwood/ Flat Rock Corp. Limits
G	12,900	V-5 (51400)	+ 12900'
H	15,800	V-4 (54300)	+ 15800'
I	17,080		+ 100' d/s of d/s face of Telegraph Rd.
J	17,180	B-4 (55680)	d/s face of Telegraph Rd.
K	17,246		u/s face of Telegraph Rd.
L	18,700	B-3 (57200)	d/s face of Footbridge
M	18,712		u/s face of Footbridge
N	19,600		+ 100' d/s of d/s face of R.R. Bridge
O	19,700	B-2 (58200)	d/s face of R.R. Bridge
P	19,747		u/s face of R.R. Bridge
Q	19,753		Crest of dam
R	22,300		At Flat Rock Corp. Limit (extension of Inkster Rd.)

TABLE 6
CITY OF FLAT ROCK
HURON RIVER

LOCATION	SELECTED FREQUENCIES 10 Yr. Q= 6480 CFS	50 Yr. 8750 CFS	100 Yr. 10390 CFS	500 Yr. 12100 CFS
@ Corp. Limits (0 Mi.)	584.2	586.6	587.7	590.2
@ Telegraph Road (3.3 Mi.)	590.9	593.6	595.7	598.0
@ Dam (3.7 Mi.)	594.1	596.0	597.7	599.9
@ Corp. Limits (ext. Inkster Rd.) (4.2 Mi.)	594.1	596.0	597.8	599.9

V. SMITH CREEK (APPROXIMATE)

An approximate study of Smith Creek was performed from the downstream corporate boundary of Flat Rock/Brownstown to the north corporate boundary of Flat Rock. The Rockwood FIS (Reference 1) was used for the downstream portion of the study. The Smith Creek flood plain study (Reference 6) was used for the upstream portion of the study.

Following are two locations on Smith Creek with their respective 100 year elevations:

Location	100 Year Elevation
Flat Rock/Brownstown Corporate Limit	577.9
u/s of D. T. & I. Railroad Corridor	597.9

REFERENCES

1. U.S. Department of Housing and Urban Development, Flood Insurance Study - City of Rockwood, Michigan.

2. U.S. Geological Survey Topographical Maps - Flat Rock Quadrangle, Wayne County, Michigan, 7.5 Minute Series - Photorevised 1973.


3. HEC-2 - Water Surface Profile - Users Manual - U.S. Army Corps of Engineers - 1976.

4. Huron River Survey, U.S. Army Corps of Engineers - Detroit District, No Date Provided.

5. Post Flood Report of Southeast Michigan Flood 25-27 June 1968, U.S. Army Engineer District, Detroit Corps of Engineers, Detroit, Michigan, 1969.

6. Wade, Trim & Associates, Inc., Smith Creek - Flood Plain Study - City of Flatrock, Wayne County, Michigan, June, 1974.


HURON RIVER
CITY OF FLAT ROCK



K•E SEMI-LOGARITHMIC 46 5493
3 CYCLES X 70 DIVISIONS MADE IN U.S.A.
KEUFFEL & ESSER CO

HUD 2009-07

HURON RIVER
CITY OF FLAT ROCK



K+E SEMI-LOGARITHMIC 46 5493
3 CYCLES X 70 DIVISIONS MADE IN U.S.A.
KEUFFEL & ESSER CO.

HUD 2009-07

FORM 25-0
(313) 291-5400
Wade, Trim & Associates, Inc.
Civil Engineers • Land Surveyors
25185 GODDARD ROAD
TAYLOR, MICHIGAN 48180

WORK SHEET

Bridge Location : Huron River Drive - Cooke + Cladding Drain

Bridge Losses - SB Card

REFERENCE

1. XK (Pier Shape Coefficient) = 0 — HEC-2 Manual

XKOR (Loss Coefficient) = $1.0 + \Sigma k$, $\Sigma k = k_f + k_e + k_p$

where k_f = friction loss coefficient
k_e = entrance loss coefficient
k_p = loss from intermediate piers

Description of Bridge:

$K_f = 29.1\, n^2 L / R^{4/3}$ for English units

Area $= \pi r^2 = \pi\left(\frac{4.5}{2}\right)^2 = 15.9\ ft^2$ $Wp = 2\pi r = 4.5\pi = 14.14$

$R = A/wp = 1.125$ $R^{4/3} = 1.17$ $L = 54'$

n (composite) = .015

$K_f = 29.1 \times (.015)^2 \times 54 \;/\; 1.17 = .302$

$K_e = .2$ — Hydraulic Charts for the Selection of Highway Culverts Circular No. 5 Dec. 1965 pg. 49

$K_p = 0$ if bridge has no intermediate piers

$K_p = 0.05$ if bridge has intermediate piers — HEC-2 manual

$K_p = 0$

2. XKOR = $1 + .2 + .3 + 0 = 1.5$
3. COFQ = Coefficient of discharge = 3.0 — HEC-2 manual
4. RDLEN = Length of weir = 0 (0 if read off BT cards)
5. BWC = bottom width of bridge opening (inc. piers) = 3.53
6. BWP = total width of obstruction = 0 — field data
7. BAREA = bridge opening inc. piers = 15.9
8. SS = side slope = 0 (horizontal per 1 vertical unit)
9. ELCHU = Elevation of channel invert U/S side = _____ (0 if equal to minimum elevation in previous x-sect.)
10. ELCHD = Elevation of channel invert D/S side = _____ (0 if equal to minimum elevation in previous x-sect.)

SUBJECT	BY / DATE	CHK. / DATE	SHEET NO. ____ OF ____	File Code No (Job No) Owner • Project • Suffix

CITY OF FLAT ROCK

HURON RIVER

EXHIBIT 8

BRIDGE NOTES

Wade Trim & Associates, Inc.
Civil Engineers • Land Surveyors
25185 GODDARD ROAD
TAYLOR, MICHIGAN 48180

WORK SHEET

Bridge Location : TELEGRAPH RD.

Bridge Losses - SB Card

REFERENCE

1. XK (Pier Shape Coefficient) = 1.25 — HEC-2 Manual

XKOR (Loss Coefficient) = 1.0 + Σk, $\Sigma k = k_f + k_e + k_p$

where k_f = friction loss coefficient
k_e = entrance loss coefficient
k_p = loss from intermediate piers

Description of Bridge :

$K_f = 29.1 n^2 L / R^{4/3}$ for English units

Area = 822.4 WP = 169

$R = A/wp$ = $R^{4/3}$ = 8.246 L = 66'

n (composite) =

$K_f = 29.1 \times (.021)^2 \times 66' / 8.246 = .10$

K_e = HEADWALL PARALLEL TO EMBANKMENT = 0.5 — Hydraulic Charts for the Selection of Highway Culverts Circular No. 5 Dec. 1965 pg. 49

K_p = 0 if bridge has no intermediate piers

$K_p = 0.05$ if bridge has ▬ intermediate piers — HEC-2 manual

$n_{composite} = \frac{110(.015) + 59(.03)}{169} = .021$

2. XKOR = 1 + .15 + 0.5 + 0.05 = 1.65
3. COFQ = Coefficient of discharge = 3.0 — HEC-2 manual
4. RDLEN = Length of weir = 0 (0 if read off BT cards)
5. BWC = bottom width of bridge opening (inc. piers) = 88.73
6. BWP = total width of obstruction = 4.2 — field data
7. BAREA = bridge opening inc. piers = 822.4
8. SS = side slope = 0 (horizontal per 1 vertical unit)
9. ELCHU = Elevation of channel invert U/S side = 873.3 (0 if equal to minimum elevation in previous x-sect.)
10. ELCHD = Elevation of channel invert D/S side = 873.3 (0 if equal to minimum elevation in previous x-sect.)


SUBJECT	BY	CHK.	SHEET NO.	File Code No. (Job No.) Owner Project Suffix
HURON RIVER CITY OF FLAT ROCK	DATE	DATE	___ OF ___	HUD • 2009 • 07

Wade Trim & Associates, Inc.
Civil Engineers • Land Surveyors
WORK SHEET
25185 GODDARD ROAD
TAYLOR, MICHIGAN 48180

REFERENCE

Telegraph Rd. Bridge (Huron River)

Bridge Skew Calculation:



X = Ineffective flow areas

z = Effective flow width

A = Effective pier width

$xx = 65 \tan 40^\circ = 54.54'$

$y = 92 - 54.5 = 37.5'$

$z = 37.5 \cos 40^\circ = 28.7'$

$A = 54.54 \cos 40^\circ = 41.78'$

U/s channel $= A + 2z = 99.18$

1160 ft²
- 707 ≈ 5'x14'
1070 ft²
x cos 40
836

28.7
28.7

SUBJECT	BY	CHK.	SHEET NO.	File Code No (Job No.) Owner • Project • Suffix
Huron River – Telegraph Rd.	Weaver		____ OF ____	
	DATE 5/18/79	DATE		


Wade, Trim & Associates, Inc.
Civil Engineers • Land Surveyors
WORK SHEET

25185 GODDARD ROAD
TAYLOR, MICHIGAN 48180

REFERENCE

Foot Bridge w/ Weir, Huron River

Calcs. for SB Card:



"X-Section 18710"

Pier Width = 1.0 ft

Total Area = 824.2 ft²

Wetted Perimeter = 271.8 ft

Pier shape coefficient = 1.25

Total Loss Coefficient (ΣKOR):


$$\Sigma KOR = 1.0 + \underset{\text{Intake}}{.5} + \frac{29.1\ n^2\ L}{R^{4/3}} + 2(.05)$$

$$\Sigma KOR = 1.6 + \frac{29.1\ (.025)^2\ 10}{\left(\frac{824.2}{271.8}\right)^{4/3}} = 1.64$$

~~Use Manning's Equation for L x Rate of Flow~~

Weir Flow coefficient = 2.8

SUBJECT	BY	CHK.	SHEET NO.	File Code No. (Job No.) Owner • Project • Suffix
	DATE	DATE	____OF____	




D/S C.S. No. 4 (TELEGRAPH ROAD BRIDGE) SHEET 1


SECT.

HURON RIVER

CITY OF FLAT ROCK



TELEGRAPH RD.
SECT.
SHEET 2
HURON RIVER
CITY OF FLAT ROCK


1+20
1+00
0+80
0+60
0+40
0+20
0
TOP=590.56
T.S. 590.31
TOP=590.63
L.S. 590.30
590
580
TOP DAM
582.67
TOP DAM
582.92
R
1+20
1+00
0+80
0+60
0+40
0+20
0
7+40
TOP LT. BANK @ HEAD
W.S. 583.1
PIER
PIER
TOP RT. BANK @ TAIL
WEIR FOOTBRIDGE DECK
CITY OF ICE

FORM 25-0
(313) 291-5400
Wade Trim & Associates, Inc.
Civil Engineers • Land Surveyors
WORK SHEET
25185 GODDARD ROAD
TAYLOR, MICHIGAN 48180

Bridge Location : R.R. BRIDGE

Bridge Losses - SB Card

REFERENCE

1. XK (Pier Shape Coefficient): Sq. nose and tail 1.25 — HEC-2 manual

XKOR (Loss Coefficient) = 1.0 + Σk, $\Sigma k = k_f + k_c + k_p$

where k_f = friction loss coefficient
k_c = entrance loss coefficient
k_p = loss from intermediate piers

Description of Bridge:

$K_f = 29.1\, n^2 L / R^{4/3}$ for English units

Area = 25 x 11.7 = 292.5 Wp = 2(25 + 11.7) = 73.4

$R = A/wp = 292.5/73.4 = 4$. $R^{4/3} = 6.35$ $L = 47'$

n (composite) = 12(2)(0.013) + 25(2)(0.034) / 73.4 = 0.027

$K_f = 29.1 \times (0.027)^2 \times 47' / 6.35 = 0.16$

K_e = 0.4 — Hydraulic Charts for the Selection of Highway Culverts Circular No. 5 Dec. 1965 pg. 49

$K_p = 0$ if bridge has no intermediate piers

$K_p = 0.05$ if bridge has ▬ intermediate piers — HEC-2 manual

2. XKOR = 1 + 0.16 + 0.4 + 0.05 = 1.61
3. COFQ = Coefficient of discharge = 3.0 — HEC-2 manual
4. RDLEN = Length of weir = 0 (0 if read off BT cards)
5. BWC = bottom width of bridge opening (inc. piers): 5060.
6. BWP = total width of obstruction = 51 — field data
7. BAREA = bridge opening inc. piers = 5475.
8. SS = side slope = 0 (horizontal per 1 vertical unit)
9. ELCHU = Elevation of channel invert U/S side = 0 (0 if equal to minimum elevation in previous X-sect.)
10. ELCHD = Elevation of channel invert D/S side = 0 (0 if equal to minimum elevation in previous X-sect.)

SUBJECT	BY	CHK.	SHEET NO.	File Code No (Job No.) Owner Project Suffix
HURON RIVER CITY OF FLAT ROCK	DATE	DATE	___ OF ___	HUD • 2009 • 07

HUR 2009-07

957


CH OR CM

79

1-11-79


RR BRIDGE - HURON R. DR. W. ARSENAL

BM	599.99	TOP of NW BOLT ON BLUE BOX ON S/S RR TRACKS 75' ± E ∈ ARSENAL N. of HURON RIVER DR
TP	598.91	
TP	598.81	
CK	599.55	599.59




R.R. BRIDGE - HURON RIVER
SECT. 1974?


5+20
5+00
4+60
4+40
4+20
4+00
TOP LT. BANK
LT. ABUT
PIER
PIER
PIER
PIER
℄ CD. 598.18
LS 59463
HURON RIVER
R.R. BRIDGE
SECT.
SHEET 1




CITY OF FLAT ROCK HURON RIVER R.R. BRIDGE SECT.

SHEET 2


2+40
2+20
2+00
1+80
1+60
1+40
1+20
1+01
W.S. 584.2
PIER
PIER
PIER
PIER
PIER
PIER
D/S C.S. No. 2 (BRIDGE)
CITY OF FLAT ROCK
HURON RIVER
R.R. BRIDGE

SECT. 2


7+00
0+80
0+60
0+40
0+20
10
11+20
PIER
PIER
PIER
RT. OUT
TOP RT. BANK
EL. 598.21
L.S. 594.04
HURON RIVER
R.R. BRIDGE
SECT.
SHEET 1

CITY OF FLAT ROCK

HURON RIVER

EXHIBIT 9

COMPUTER PRINTOUTS

HEC-2 BACKWATER ANALYSIS

(See Separate Folder)

CITY OF FLAT ROCK

HURON RIVER

EXHIBIT 10

STREAM PROFILE

00BREAK00

1) COUNTY: Wayne

2) STUDY NAME: City of Flat Rock

3) WATERCOURSE: Huron River

4) DOCUMENT TYPE: Summary

00BREAK00

```
**************************************************
  HEC2 RELEASE DATED NOV 76 UPDATED FEB 1977
  ERROR CORR -  01
  MODIFICATION -  50,51,52
**************************************************

C
T1      10 YEAR FLOW
T2      HURON  RIVER
T3      CITY OF FLATROCK

J1  ICHECK     INQ       NINV      IDIR      STRT      METRIC    HVINS     Q         WSEL      FQ
        0.        3.        0.        0.  0.000000      0.00      0.0       0.   584.210     0.000

J2  NPROF      IPLOT     PRFVS     XSECV     XSECH     FN        ALLDC     IBW       CHNIM     ITRACE
    1.000      0.000    -1.000     0.000     0.000     0.000     0.000     0.000     0.000     0.000

J3  VARIABLE CODES FOR SUMMARY PRINTOUT
    150.000   201.000     0.000     0.000     0.000     0.000     0.000     0.000     0.000     0.000

J5  LPRNT     NUMSEC                        ********REQUESTED SECTION NUMBERS********
    -10.000   -10.000     0.000     0.000     0.000     0.000     0.000     0.000     0.000     0.000
ET    0.000     0.000     0.000     0.000     0.000     0.000     1.400     0.000     0.000     0.000
QT    6.000  7700.000  6480.000  8750.000 10390.000 12100.000 10390.000     0.000     0.000     0.000
NC    0.120     0.120     0.035     0.300     0.500     0.000     0.000     0.000     0.000     0.000

      VALLEY SECTION FROM ROCKWOOD FIS

X1  500.000    21.000   100.000   218.000     0.000     0.000     0.000     0.000     0.000     0.000
GR  594.100     0.000   593.400    51.000   579.500   100.000   574.300   102.000   573.000   103.000
GR  572.800   108.000   571.100   113.000   569.600   118.000   569.200   128.000   569.200   138.000
GR  569.100   148.000   569.500   158.000   570.200   168.000   570.500   178.000   570.800   188.000
GR  570.900   193.000   571.100   198.000   571.200   203.000   572.300   208.000   582.300   218.000
GR  590.200   268.000     0.000     0.000     0.000     0.000     0.000     0.000     0.000     0.000
NC    0.000     0.000     0.050     0.000     0.000     0.000     0.000     0.000     0.000     0.000

      VALLEY SECTION FROM CORPS OF ENGINEERS SECTION V10

X1 1800.000    19.000  1460.000  1590.000   650.000   500.000  1300.000     0.000     0.000     0.000
GR  597.500     0.000   585.800   150.000   585.000   190.000   586.700   390.000   581.500   590.000
GR  581.000   790.000   579.700   890.000   580.000   990.000   581.900  1190.000   580.600  1290.000
GR  581.900  1460.000   571.900  1490.000   571.400  1530.000   573.000  1570.000   576.000  1580.000
GR  586.700  1590.000   586.000  1890.000   586.300  1990.000   591.000  2060.000     0.000     0.000

      VALLEY SECTION FROM CORPS OF ENGINEERS SECTION V9
```

X1	4400.000	22.000	39.000	130.000	1000.000	1400.000	2600.000	0.000	0.000	0.000
GR	596.800	0.000	582.200	30.000	580.600	39.000	575.900	41.000	572.000	50.000
GR	569.900	80.000	569.400	100.000	570.600	120.000	575.900	128.000	581.100	130.000
GR	582.900	300.000	583.100	500.000	583.700	700.000	584.000	850.000	584.200	1000.000
GR	584.500	1150.000	584.800	1300.000	585.000	1470.000	588.800	1600.000	590.000	1670.000
GR	592.200	1800.000	595.000	1970.000	0.000	0.000	0.000	0.000	0.000	0.000

VALLEY SECTION FROM CORPS OF ENGINEERS SECTION V8

X1	6200.000	18.000	1385.000	1485.000	600.000	600.000	1800.000	0.000	0.000	0.000
GR	593.200	0.000	590.000	180.000	585.000	210.000	584.000	300.000	584.000	450.000
GR	584.000	550.000	584.600	650.000	583.000	800.000	583.000	950.000	582.900	1100.000
GR	582.900	1250.000	582.900	1385.000	575.300	1395.000	571.300	1425.000	573.300	1455.000
GR	590.400	1485.000	590.400	1585.000	595.000	1945.000	0.000	0.000	0.000	0.000

VALLEY SECTION FROM CORPS OF ENGINEERS SECTION V7

X1	8200.000	26.000	810.000	930.000	1000.000	850.000	2000.000	0.000	0.000	0.000
GR	595.000	0.000	588.970	150.000	587.000	230.000	586.000	330.000	583.800	430.000
GR	582.300	630.000	583.000	810.000	573.800	820.000	571.800	830.000	571.800	840.000
GR	571.500	850.000	575.400	890.000	575.700	900.000	575.000	910.000	581.200	930.000
GR	581.500	980.000	583.500	1030.000	582.200	1080.000	582.000	1130.000	580.000	1180.000
GR	581.900	1230.000	582.400	1280.000	583.000	1480.000	579.200	1535.000	594.000	1565.000
GR	594.600	1680.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000

VALLEY SECTION FROM CORPS OF ENGINEERS SECTION V6

X1	10300.000	26.000	1025.000	1177.000	900.000	900.000	2100.000	0.000	0.000	0.000
GR	595.000	0.000	590.000	550.000	589.030	595.000	588.100	625.000	588.000	725.000
GR	586.000	775.000	583.000	795.000	583.400	1025.000	578.800	1032.000	573.200	1055.000
GR	572.900	1075.000	573.500	1125.000	578.200	1155.000	578.800	1165.000	581.400	1177.000
GR	583.900	1200.000	582.500	1825.000	583.100	1875.000	587.200	1895.000	587.200	1925.000
GR	587.200	2025.000	587.200	2125.000	587.200	2275.000	587.200	2295.000	587.200	2310.000
GR	595.000	2325.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
NC	0.120	0.120	0.050	0.000	0.000	0.000	0.000	0.000	0.000	0.000

VALLEY SECTION FROM CORPS OF ENGINEERS SECTION V5

X1	12900.000	16.000	730.000	860.000	1900.000	1300.000	2600.000	0.000	0.000	0.000
GR	595.000	0.000	590.000	250.000	588.200	700.000	588.000	730.000	580.000	740.000
GR	576.000	741.000	573.400	760.000	577.000	830.000	584.100	860.000	585.000	880.000
GR	585.300	950.000	5853.000	1100.000	585.300	1200.000	587.000	1375.000	590.000	1500.000
GR	595.000	1700.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
NC	0.100	0.100	0.040	0.000	0.000	0.000	0.000	0.000	0.000	0.000

VALLEY SECTION FROM CORPS OF ENGINEERS SECTION V4

X1	15800.000	21.000	640.000	795.000	2300.000	2900.000	2100.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	315.000	0.000	1000.000	0.000	0.000	0.000	0.000
GR	600.540	0.000	599.200	100.000	593.300	150.000	590.500	200.000	585.000	230.000

PRINTED IN U.S.A.
FORM 761-GD PRINTED BY ROTARY MANIFOLD FORMS

GR	586.400	260.000	583.900	280.000	583.800	300.000	582.800	400.000	584.500	500.000
GR	585.100	600.000	586.700	640.000	580.400	650.000	577.500	670.000	574.200	770.000
GR	576.800	790.000	585.300	795.000	585.800	1000.000	583.000	1125.000	595.800	1155.000
GR	597.000	1175.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000

X-SECTION D/S OF TELEGRAPH RD.

X1	17080.000	16.000	570.000	750.000	1280.000	1280.000	1280.000	0.766	0.000	0.000
X3	0.000	0.000	0.000	550.000	0.000	760.000	0.000	0.000	0.000	0.000
GR	600.000	0.000	597.700	25.000	590.000	525.000	585.000	553.000	597.300	570.000
GR	578.000	600.000	577.400	650.000	576.200	664.000	577.500	680.000	574.200	690.000
GR	573.300	710.000	575.500	730.000	578.600	750.000	581.300	774.000	590.000	821.000
GR	597.000	910.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
NC	0.100	0.100	0.035	0.300	0.500	0.000	0.000	0.000	0.000	0.000
ET	0.000	0.000	0.000	0.000	0.000	0.000	9.100	0.000	133.000	795.000

D/S FACE OF TELEGRAPH RD.BRIDGE

X1	17180.000	16.000	565.000	664.200	100.000	100.000	100.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	595.000	595.000	0.000
GR	599.000	565.000	599.000	565.000	599.000	565.000	599.000	565.000	599.000	565.000
GR	578.000	565.000	577.000	593.700	577.000	593.800	577.000	635.500	577.000	636.600
GR	573.300	650.000	579.000	664.200	599.000	664.200	599.000	664.200	599.000	664.200
GR	600.000	795.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
SB	1.250	1.650	3.000	0.000	88.730	42.000	822.400	0.000	0.000	0.000

U/S FACE OF TELEGRAPH RD.BRIDGE

X1	17246.000	0.000	0.000	0.000	66.000	66.000	66.000	0.000	0.000	0.000
X2	0.000	0.000	1.000	590.900	597.170	0.000	0.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	597.170	597.170	0.000
BT	13.000	565.000	599.000	0.000	565.000	599.000	0.000	565.000	599.000	0.000
BT	565.000	597.170	578.000	565.000	597.170	590.900	593.700	597.170	590.900	593.800
BT	597.170	577.000	635.500	597.170	577.000	635.600	597.170	590.900	664.200	597.170
BT	590.900	664.200	597.170	0.000	664.200	599.000	0.000	795.000	600.000	0.000
ET	0.000	0.000	0.000	0.000	0.000	0.000	1.400	0.000	0.000	0.000

X-SECTION U/S OF TELEGRAPH RD.BRIDGE

X1	17271.000	0.000	0.000	0.000	100.000	100.000	100.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	380.000	0.000	680.000	0.000	0.000	0.000	0.000
ET	0.000	0.000	0.000	0.000	0.000	0.000	9.100	0.000	0.000	1350.000

D/S FACE OF FOOTBRIDGE

X1	18700.000	13.000	400.000	520.000	1369.000	1369.000	1369.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	590.400	590.500	0.000
GR	608.000	0.000	600.000	0.100	595.000	110.000	590.000	310.000	590.500	400.000
GR	580.300	412.000	580.300	511.500	590.600	520.000	594.000	620.000	594.500	720.000
GR	595.000	1000.000	595.000	1200.000	600.000	1200.000	0.000	0.000	0.000	0.000

PRINTED IN U.S.A.
FORM 1411 GO PRINTED BY BOSTITT MANIFOLD FORMS

X1	18701.000	21.000	400.000	520.000	1.000	1.000	1.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	590.400	590.500	0.000
BT	19.000	0.000	608.000	0.000	0.100	600.000	0.000	110.000	595.000	0.000
BT	310.000	590.000	0.000	400.000	590.500	590.300	448.000	590.500	590.300	448.100
BT	590.500	582.700	448.900	590.500	582.700	449.000	590.500	590.300	485.000	590.600
BT	590.300	485.100	590.600	582.700	485.900	590.600	582.700	486.000	590.600	590.300
BT	520.000	590.600	590.300	620.000	594.000	0.000	720.000	594.500	0.000	1000.000
BT	593.000	0.000	1200.000	595.000	0.000	1200.000	600.000	0.000	0.000	0.000
GR	608.000	0.000	600.000	0.100	595.000	110.000	590.000	310.000	590.500	400.000
GR	582.670	412.000	582.680	448.000	582.700	448.100	582.700	448.900	582.680	449.000
GR	582.700	485.000	582.700	485.100	582.700	485.900	582.700	486.000	582.710	511.500
GR	590.600	520.000	594.000	620.000	594.500	720.000	595.000	1000.000	595.000	1200.000
GR	600.000	1200.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000

X1	18711.000	0.000	0.000	0.000	10.000	10.000	10.000	0.000	0.000	0.000
X2	0.000	0.000	0.000	0.000	0.000	0.000	1.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	590.500	590.600	0.000

U/S FACE OF FOOTBRIDGE

X1	18712.000	0.000	0.000	0.000	1.000	1.000	1.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	590.500	590.600	0.000
ET	0.000	0.000	0.000	0.000	0.000	0.000	1.400	0.000	0.000	0.000

X-SECT. D/S OF R.R.BRIDGE

X1	19600.000	22.000	400.000	520.000	900.000	900.000	900.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	270.000	0.000	930.000	0.000	0.000	0.000	0.000
GR	608.000	0.000	600.000	0.100	595.000	110.000	590.000	310.000	590.500	400.000
GR	582.670	412.000	580.900	430.000	580.300	440.000	580.000	450.000	580.400	460.000
GR	580.600	470.000	580.200	480.000	580.700	484.000	580.000	490.000	580.000	500.000
GR	582.710	511.500	593.400	520.000	594.000	620.000	594.500	720.000	595.000	1000.000
GR	595.000	1200.000	600.000	1350.000	0.000	0.000	0.000	0.000	0.000	0.000
NC	0.070	0.070	0.035	0.300	0.500	0.000	0.000	0.000	0.000	0.000
ET	0.000	0.000	0.000	0.000	0.000	0.000	9.100	0.000	0.000	1125.100

D/S FACE OF R.R. BRIDGE

X1	19700.000	80.000	265.000	870.000	100.000	100.000	100.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	600.000	600.000	0.000
GR	600.000	0.000	598.000	260.000	598.000	265.000	583.200	265.100	582.300	290.000
GR	594.040	291.000	594.040	294.000	582.300	295.000	582.300	320.000	594.040	321.000
GR	594.040	324.000	582.300	325.000	582.300	350.000	594.040	351.000	594.040	354.000
GR	582.300	355.000	582.300	380.000	594.040	381.000	594.040	384.000	582.300	385.000
GR	582.300	410.000	594.040	411.000	594.040	414.000	582.300	415.000	582.300	440.000
GR	594.040	441.000	594.040	444.000	582.300	445.000	582.300	470.000	594.040	471.000
GR	594.040	474.000	582.300	475.000	582.300	500.000	594.040	501.000	594.040	504.000
GR	582.300	505.000	582.300	530.000	594.040	531.000	594.040	534.000	582.300	535.000
GR	582.300	560.000	594.040	561.000	594.040	564.000	582.300	565.000	582.300	590.000
GR	594.040	591.000	594.040	594.000	582.300	595.000	582.300	620.000	594.040	621.000
GR	594.040	624.000	582.300	625.000	582.300	650.000	594.040	651.000	594.040	654.000

PRINTED IN U.S.A.
FORM 1411 GD PRINTED BY POTARY MANIFOLD FORMS

GR	582.300	655.000	582.300	680.000	594.040	681.000	594.040	684.000	582.300	685.000
GR	582.300	710.000	594.040	711.000	594.040	714.000	582.300	715.000	582.300	740.000
GR	594.040	741.000	594.040	744.000	582.300	745.000	582.300	770.000	594.040	771.000
GR	594.040	774.000	582.300	775.000	582.300	800.000	594.100	801.000	594.100	806.000
GR	582.300	806.100	582.300	831.000	592.370	832.000	594.020	870.000	598.340	1125.100
SB	1.250	1.610	3.000	0.000	517.350	51.000	5475.000	0.000	0.000	0.000

U/S FACE OF R.R. BRIDGE

X1	19747.000	0.000	0.000	0.000	47.000	47.000	47.000	0.000	0.000	0.000
X2	0.000	0.000	1.000	594.040	599.200	0.000	0.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	600.000	600.000	0.000
BT	9.000	0.000	600.000	0.000	265.000	601.350	0.000	265.100	601.350	594.040
BT	800.000	601.360	594.040	800.000	601.350	0.000	870.000	601.410	0.000	870.000
BT	598.920	0.000	1125.100	599.200	0.000	1125.100	600.970	0.000	0.000	0.000
NC	0.070	0.070	0.020	0.300	0.500	0.000	0.000	0.000	0.000	0.000

DUMMY X-SECT.U/S OF R.R.BRIDGE

X1	19748.000	12.000	265.000	870.000	1.000	1.000	1.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	600.000	600.000	0.000
GR	600.000	0.000	598.000	265.000	591.700	266.600	582.300	269.000	582.300	771.000
GR	594.100	771.100	594.100	776.000	582.300	776.100	582.300	802.000	592.370	802.100
GR	594.020	870.000	598.340	1125.100	0.000	0.000	0.000	0.000	0.000	0.000
SB	0.000	1.500	3.000	0.000	1.000	0.000	9.400	0.000	0.000	0.000

X-SECT.AT CREST OF DAM

X1	19753.000	0.000	0.000	0.000	3.000	3.000	3.000	0.000	0.000	0.000
X2	0.000	0.000	1.000	591.700	591.700	0.000	0.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	600.000	600.000	0.000
BT	4.000	265.000	600.000	0.000	265.000	591.700	0.000	870.000	591.700	0.000
BT	870.000	600.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
ET	0.000	0.000	0.000	0.000	0.000	0.000	1.400	0.000	0.000	0.000

VALLEY SECT. AT CORP. LIMITS

X1	22300.000	11.000	50.000	1300.000	2547.000	2547.000	2547.000	0.000	0.000	0.000
GR	600.000	0.000	595.000	25.000	592.000	50.000	587.000	60.000	587.000	1290.000
GR	592.000	1300.000	595.000	1325.000	596.000	1350.000	595.000	1400.000	595.000	1600.000
GR	600.000	1650.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
EJ	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000

PRINTED IN U.S.A.
FORM 1411-GB PRINTED BY RITARY MANIFOLD FORMS

```
**************************************************
  HEC2 RELEASE DATED NOV 76 UPDATED FEB 1977
  ERROR CORR -  01
  MODIFICATION -  50,51,52
**************************************************

T1      HURON RIVER
T2      50 YEAR FLOW
T3      CITY OF FLATROCK

J1  ICHECK     INQ       NINV      IDIR      STRT      METRIC    HVINS     Q         WSEL      FQ
          0.        4.        0.        0.  1.000000      0.00      0.0        0.   586.590     0.000

J2  NPROF      IPLOT     PRFVS     XSECV     XSECH     FN        ALLDC     IBW       CHNIM     ITRACE
      2.000     0.000    -1.000     0.000     0.000     0.000     0.000     0.000     0.000     0.000
```

PRINTED IN U.S.A.
FORM 1411-00 PRINTED BY ROTARY MANIFOLD FORMS

```
**************************************************
  HEC2 RELEASE DATED NOV 76 UPDATED FEB 1977
  ERROR CORR -  01
  MODIFICATION -  50,51,52
**************************************************

T1      CITY OF FLATROCK
T2      100 YEAR FLOW
T3      HURON RIVER
J1  ICHECK    INQ       NINV      IDIR      STRT      METRIC    HVINS     Q         WSEL      FQ
        0.      5.        0.        0.  0.000000      0.00      0.0       0.    587.660     0.000
J2  NPROF     IPLOT     PRFVS     XSECV     XSECH     FN        ALLDC     IBW       CHNIM     ITRACE
    3.000     0.000   -10.000     0.000     0.000     0.000     0.000     0.000     0.000     0.000
```

PRINTED IN U.S.A.
FORM 1411 GO PRINTED BY ROTARY MASTER OLD FORMS

```
**************************************************
  HEC2 RELEASE DATED NOV 76 UPDATED FEB 1977
  ERROR CORR -  01
  MODIFICATION -  50,51,52
**************************************************

T1      HURON RIVER
T2      500 YEAR FLOW
T3      CITY OF FLATROCK

J1  ICHECK     INQ       NINV      IDIR      STRT      METRIC    HVINS     Q         WSEL      FQ
        0.       6.        0.        0.  0.000000      0.00      0.0       0.    590.230     0.000

J2  NPROF      IPLOT     PRFVS     XSECV     XSECH     FN        ALLDC     IBW       CHNIM     ITRACE
        4.000     0.000    -1.000     0.000     0.000     0.000     0.000     0.000     0.000     0.000
```

PRINTED IN U.S.A.
FORM 1411-GO PRINTED BY ROTARY MANIFOLD FORMS.

```
**************************************************
 HEC2 RELEASE DATED NOV 76 UPDATED FEB 1977
 ERROR CORR -  01
 MODIFICATION -  50,51,52
**************************************************

T1CITY OF FLAT ROCK FIS HUD 2009 07 HURON RIVER WITHIN FLAT ROCK
T2 Q10YR#6480 50#8750 100#10390 500#12100 CFS   1968 STORM PROFILE Q# 7700 CFS.
T3      HURON R.-FLAT ROCK                FROM ROCKWOOD FIS

J1  ICHECK     INQ        NINV       IDIR       STRT       METRIC     HVINS      Q          WSEL       FQ
          0.        2.         0.         0.  0.000000       0.00       0.0         0.    585.600    0.000

J2  NPROF      IPLOT      PRFVS      XSECV      XSECH      FN         ALLDC      IBW        CHNIM      ITRACE
     15.000     0.000     -1.000      0.000      0.000      0.000      0.000      0.000      0.000      0.000
```

PRINTED IN U.S.A.
FORM 141-0D PRINTED BY ROTARY MANIFOLD FORMS.

****
HEC2 RELEASE DATED NOV 76 UPDATED FEB 1977
ERROR CORR - 01
MODIFICATION - 50,51,52
****

NOTE- ASTERISK (*) AT LEFT OF CROSS-SECTION NUMBER INDICATES MESSAGE IN SUMMARY OF ERRORS LIST

CITY OF FLATROCK

SUMMARY PRINTOUT TABLE 150

	SECNO	XLCH	ELTRD	ELLC	ELMIN	Q	CWSEL	CRIWS	EG	10K*S	VCH	AREA	.01K
	500.000	0.00	0.00	0.00	569.10	6480.00	584.21	0.00	584.48	3.38	4.15	1608.22	3526.31
	500.000	0.00	0.00	0.00	569.10	8750.00	586.59	0.00	586.93	3.51	4.72	1985.28	4672.51
A	500.000	0.00	0.00	0.00	569.10	10390.00	587.66	0.00	588.08	3.94	5.23	2172.94	5236.06
	500.000	0.00	0.00	0.00	569.10	12100.00	590.23	0.00	590.65	3.25	5.23	2669.87	6714.48
	500.000	0.00	0.00	0.00	569.10	7700.00	585.60	0.00	585.91	3.40	4.45	1821.66	4177.83
	1800.000	1300.00	0.00	0.00	571.40	6480.00	584.89	0.00	584.98	4.24	2.94	5092.41	3147.26
	1800.000	1300.00	0.00	0.00	571.40	8750.00	587.30	0.00	587.36	2.58	2.59	8716.95	5452.58
B	1800.000	1300.00	0.00	0.00	571.40	10390.00	588.47	0.00	588.51	2.22	2.54	10912.77	6980.31
	1800.000	1300.00	0.00	0.00	571.40	12100.00	590.94	0.00	590.97	1.21	2.09	15709.46	10979.02
	1800.000	1300.00	0.00	0.00	571.40	7700.00	586.29	0.00	586.35	3.14	2.72	6876.78	4346.40
	4400.000	2600.00	0.00	0.00	569.40	6480.00	585.86	0.00	586.03	5.12	3.76	4246.72	2864.88
	4400.000	2600.00	0.00	0.00	569.40	8750.00	587.87	0.00	587.98	3.60	3.44	7292.26	4610.28
C	4400.000	2600.00	0.00	0.00	569.40	10390.00	588.94	0.00	589.04	3.23	3.40	8974.02	5778.86
	4400.000	2600.00	0.00	0.00	569.40	12100.00	591.19	0.00	591.24	1.91	2.83	12704.18	8758.04
	4400.000	2600.00	0.00	0.00	569.40	7700.00	586.99	0.00	587.12	4.17	3.57	5943.73	3772.95
	6200.000	1800.00	0.00	0.00	571.30	6480.00	586.72	0.00	586.84	6.17	3.58	4920.88	2608.56
	6200.000	1800.00	0.00	0.00	571.30	8750.00	588.41	0.00	588.50	4.72	3.36	7097.53	4027.54
D	6200.000	1800.00	0.00	0.00	571.30	10390.00	589.40	0.00	589.48	4.31	3.34	8380.36	5004.65
	6200.000	1800.00	0.00	0.00	571.30	12100.00	591.43	0.00	591.49	2.68	2.86	11236.89	7385.13
	6200.000	1800.00	0.00	0.00	571.30	7700.00	587.65	0.00	587.75	5.29	3.46	6112.84	3346.53
	8200.000	2000.00	0.00	0.00	571.50	6480.00	587.36	0.00	587.41	2.28	2.38	6840.55	4287.65
	8200.000	2000.00	0.00	0.00	571.50	8750.00	588.91	0.00	588.96	2.17	2.51	8965.30	5942.94
E	8200.000	2000.00	0.00	0.00	571.50	10390.00	589.85	0.00	589.91	2.14	2.60	10306.11	7098.40
	8200.000	2000.00	0.00	0.00	571.50	12100.00	591.72	0.00	591.76	1.56	2.40	13031.66	9692.68
	8200.000	2000.00	0.00	0.00	571.50	7700.00	588.20	0.00	588.25	2.23	2.46	7985.28	5152.91
	10300.000	2100.00	0.00	0.00	572.90	6480.00	587.72	0.00	587.77	2.14	2.30	6463.79	4425.20
	10300.000	2100.00	0.00	0.00	572.90	8750.00	589.23	0.00	589.28	2.03	2.41	9003.54	6148.82
F	10300.000	2100.00	0.00	0.00	572.90	10390.00	590.16	0.00	590.21	1.97	2.48	10635.29	7404.08
	10300.000	2100.00	0.00	0.00	572.90	12100.00	591.93	0.00	591.97	1.41	2.27	13974.38	10188.12
	10300.000	2100.00	0.00	0.00	572.90	7700.00	588.54	0.00	588.60	2.10	2.37	7825.61	5315.09

PRINTED IN U.S.A.
FORM 1611-UD PRINTED BY ROYARY MANIFOLD (ORM)

	SECNO	XLCH	ELTRD	ELLC	ELMIN	Q	CWSEL	CRIWS	EG	TOK*S	VCH	AREA	.01K
	12900.000	2600.00	0.00	0.00	573.40	6480.00	588.49	0.00	588.72	7.62	4.02	2276.56	2347.82
	12900.000	2600.00	0.00	0.00	573.40	8750.00	589.94	0.00	590.21	8.07	4.48	3393.50	3079.83
6	12900.000	2600.00	0.00	0.00	573.40	10390.00	590.83	0.00	591.11	8.01	4.67	4317.61	3670.26
	12900.000	2600.00	0.00	0.00	573.40	12100.00	592.40	0.00	592.61	6.01	4.34	6109.48	4936.98
	12900.000	2600.00	0.00	0.00	573.40	7700.00	589.29	0.00	589.54	7.99	4.30	2815.94	2724.31
	15800.000	2100.00	0.00	0.00	574.20	6480.00	589.39	0.00	589.48	1.81	2.62	4425.09	4817.74
	15800.000	2100.00	0.00	0.00	574.20	8750.00	590.93	0.00	591.03	1.97	2.95	5481.56	6234.46
TA	15800.000	2100.00	0.00	0.00	574.20	10390.00	591.86	0.00	591.97	2.10	3.18	6113.84	7164.33
	15800.000	2100.00	0.00	0.00	574.20	12100.00	593.24	0.00	593.35	1.95	3.25	7058.40	8660.05
	15800.000	2100.00	0.00	0.00	574.20	7700.00	590.25	0.00	590.34	1.90	2.80	5013.77	5585.69
	17080.000	1280.00	0.00	0.00	573.30	6480.00	589.65	0.00	589.89	4.19	3.98	1710.89	3166.86
	17080.000	1280.00	0.00	0.00	573.30	8750.00	591.20	0.00	591.55	5.28	4.78	1935.90	3809.28
A	17080.000	1280.00	0.00	0.00	573.30	10390.00	592.12	0.00	592.56	6.07	5.31	2073.29	4217.47
	17080.000	1280.00	0.00	0.00	573.30	12100.00	593.46	0.00	593.95	6.26	5.66	2274.46	4835.16
	17080.000	1280.00	0.00	0.00	573.30	7700.00	590.51	0.00	590.81	4.79	4.42	1835.99	3519.89
	17180.000	100.00	0.00	0.00	573.30	6480.00	589.62	0.00	590.02	6.35	5.08	1274.47	2571.11
	17180.000	100.00	0.00	0.00	573.30	8750.00	591.14	0.00	591.73	8.23	6.14	1425.67	3049.20
B	17180.000	100.00	0.00	0.00	573.30	10390.00	592.05	0.00	592.78	9.65	6.86	1515.57	3344.38
	17180.000	100.00	0.00	0.00	573.30	12100.00	593.36	0.00	594.20	10.22	7.35	1645.77	3785.22
	17180.000	100.00	0.00	0.00	573.30	7700.00	590.47	0.00	590.97	7.37	5.67	1359.14	2835.89
	17246.000	66.00	597.17	590.90	573.30	6480.00	590.88	0.00	591.21	4.78	4.63	1399.30	2964.10
	17246.000	66.00	597.17	590.90	573.30	8750.00	593.62	0.00	594.05	5.10	5.24	1671.22	3873.15
K	17246.000	66.00	597.17	590.90	573.30	10390.00	595.66	0.00	596.14	5.12	5.54	1873.89	4592.25
	17246.000	66.00	597.17	590.90	573.30	12100.00	597.98	0.00	598.49	4.94	5.75	2103.72	5445.12
	17246.000	66.00	597.17	590.90	573.30	7700.00	592.33	0.00	592.72	5.02	4.99	1543.64	3438.13
	17271.000	100.00	0.00	0.00	573.30	6480.00	590.93	0.00	591.26	4.72	4.61	1404.79	2981.78
	17271.000	100.00	0.00	0.00	573.30	8750.00	593.67	0.00	594.10	5.05	5.22	1677.21	3893.90
L	17271.000	100.00	0.00	0.00	573.30	10390.00	595.72	0.00	596.19	5.07	5.53	1880.30	4615.54
	17271.000	100.00	0.00	0.00	573.30	12100.00	598.03	0.00	598.54	4.90	5.74	2108.86	5464.59
	17271.000	100.00	0.00	0.00	573.30	7700.00	592.39	0.00	592.77	4.96	4.97	1549.72	3458.52
	18700.000	1369.00	0.00	0.00	580.30	6480.00	591.67	0.00	592.06	6.83	5.08	1459.28	2479.96
	18700.000	1369.00	0.00	0.00	580.30	8750.00	594.43	0.00	594.80	5.01	5.08	2590.62	3909.45
M	18700.000	1369.00	0.00	0.00	580.30	10390.00	596.54	0.00	596.82	3.43	4.64	4705.95	5609.32
	18700.000	1369.00	0.00	0.00	580.30	12100.00	598.89	0.00	599.07	2.13	4.02	7404.35	8294.70
	18700.000	1369.00	0.00	0.00	580.30	7700.00	593.12	0.00	593.51	5.90	5.15	1980.14	3170.01
	18701.000	1.00	590.00	590.30	582.67	6480.00	591.53	0.00	592.20	64.39	6.66	1116.35	807.53
	18701.000	1.00	590.00	590.30	582.67	8750.00	594.42	0.00	594.82	29.44	5.55	2284.79	1612.63
N	18701.000	1.00	590.00	590.30	582.67	10390.00	596.66	0.00	596.84	13.28	4.23	4537.11	2851.31
	18701.000	1.00	590.00	590.30	582.67	12100.00	599.01	0.00	599.09	6.07	3.19	7242.22	4909.65
	18701.000	1.00	590.00	590.30	582.67	7700.00	593.06	0.00	593.58	42.91	6.12	1651.80	1175.45
	18711.000	10.00	590.00	590.30	582.67	6480.00	591.63	0.00	592.27	61.42	6.55	1144.38	826.81
	18711.000	10.00	590.00	590.30	582.67	8750.00	594.45	0.00	594.85	29.20	5.53	2295.02	1619.21
C	18711.000	10.00	590.00	590.30	582.67	10390.00	596.67	0.00	596.86	13.22	4.22	4546.18	2857.19
	18711.000	10.00	590.00	590.30	582.67	12100.00	599.01	0.00	599.10	6.06	3.19	7247.10	4913.87
	18711.000	10.00	590.00	590.30	582.67	7700.00	593.11	0.00	593.63	41.77	6.06	1674.93	1191.44

588.8

580.2

589.3

550?

PRINTED IN U.S.A.

FORM 1411-GB PRINTED BY ROTARY MANIFOLD FORMS

SECNO	XLCH	ELTRD	ELLC	ELMIN	Q	CWSEL	CRIWS	EG	TOK*S	VCH	AREA	.01K
18712.000	1.00	0.00	0.00	582.67	6480.00	591.66	0.00	592.28	14.27	6.38	1193.93	1715.21
18712.000	1.00	0.00	0.00	582.67	8750.00	594.40	0.00	594.90	8.50	5.96	2311.41	3000.68
18712.000	1.00	0.00	0.00	582.67	10390.00	596.61	0.00	596.93	4.91	5.11	4518.51	4690.37
18712.000	1.00	0.00	0.00	582.67	12100.00	598.96	0.00	599.15	2.74	4.26	7230.97	7315.59
18712.000	1.00	0.00	0.00	582.67	7700.00	593.09	0.00	593.66	10.99	6.23	1704.48	2322.82
19600.000	900.00	0.00	0.00	580.00	6480.00	592.78	0.00	593.12	5.60	4.77	1634.21	2737.64
19600.000	900.00	0.00	0.00	580.00	8750.00	595.14	0.00	595.51	4.87	5.04	2555.76	3966.93
19600.000	900.00	0.00	0.00	580.00	10390.00	597.00	0.00	597.32	3.84	4.89	3778.60	5302.53
19600.000	900.00	0.00	0.00	580.00	12100.00	599.18	0.00	599.43	2.80	4.56	5217.51	7230.20
19600.000	900.00	0.00	0.00	580.00	7700.00	594.02	0.00	594.39	5.35	4.99	1976.09	3327.70
19700.000	100.00	0.00	0.00	582.30	6480.00	593.21	0.00	593.24	0.76	1.21	5363.39	7437.47
19700.000	100.00	0.00	0.00	582.30	8750.00	595.60	0.00	595.62	0.75	1.30	6750.16	10131.70
19700.000	100.00	0.00	0.00	582.30	10390.00	597.39	0.00	597.42	0.64	1.33	7833.88	12970.16
19700.000	100.00	0.00	0.00	582.30	12100.00	599.49	0.00	599.51	0.53	1.33	9102.52	16633.82
19700.000	100.00	0.00	0.00	582.30	7700.00	594.48	0.00	594.51	0.82	1.27	6074.63	8505.02
19747.000	47.00	599.20	594.04	582.30	6480.00	593.22	0.00	593.24	0.76	1.21	5365.45	7440.93
19747.000	47.00	599.20	594.04	582.30	8750.00	595.64	0.00	595.66	0.74	1.29	6773.37	10189.56
19747.000	47.00	599.20	594.04	582.30	10390.00	597.45	0.00	597.48	0.63	1.32	7871.70	13074.15
19747.000	47.00	599.20	594.04	582.30	12100.00	599.58	0.00	599.60	0.52	1.32	9157.06	16799.27
19747.000	47.00	599.20	594.04	582.30	7700.00	594.51	0.00	594.53	0.81	1.26	6089.67	8540.00
19748.000	1.00	0.00	0.00	582.30	6480.00	593.22	0.00	593.24	0.11	1.12	5795.34	19401.80
19748.000	1.00	0.00	0.00	582.30	8750.00	595.64	0.00	595.66	0.11	1.21	7238.32	26872.09
19748.000	1.00	0.00	0.00	582.30	10390.00	597.46	0.00	597.48	0.09	1.25	8336.13	33937.42
19748.000	1.00	0.00	0.00	582.30	12100.00	599.58	0.00	599.60	0.08	1.26	9621.28	43005.77
19748.000	1.00	0.00	0.00	582.30	7700.00	594.51	0.00	594.53	0.11	1.17	6555.29	22807.53
19753.000	3.00	591.70	591.70	582.30	6480.00	594.10	0.00	594.12	0.09	1.03	6314.90	21439.70
19753.000	3.00	591.70	591.70	582.30	8750.00	595.95	0.00	595.97	0.10	1.18	7425.43	28030.61
19753.000	3.00	591.70	591.70	582.30	10390.00	597.73	0.00	597.76	0.09	1.22	8506.70	35092.18
19753.000	3.00	591.70	591.70	582.30	12100.00	599.86	0.00	599.88	0.07	1.24	9791.43	44268.34
19753.000	3.00	591.70	591.70	582.30	7700.00	594.95	0.00	594.97	0.10	1.13	6823.44	24372.12
22300.000	2547.00	0.00	0.00	587.00	6480.00	594.13	0.00	594.14	0.07	0.73	8894.20	24254.23
22300.000	2547.00	0.00	0.00	587.00	8750.00	595.98	0.00	595.99	0.06	0.78	11524.62	35759.64
22300.000	2547.00	0.00	0.00	587.00	10390.00	597.77	0.00	597.78	0.05	0.77	14395.20	48790.82
22300.000	2547.00	0.00	0.00	587.00	12100.00	599.89	0.00	599.90	0.03	0.74	17857.15	66422.69
22300.000	2547.00	0.00	0.00	587.00	7700.00	594.98	0.00	594.99	0.07	0.78	9994.86	29315.27

PRINTED IN U.S.A.
FORM 1611-DS PRINTED BY ROYAL MANIFOLD FORMS.

CITY OF FLATROCK

SUMMARY PRINTOUT TABLE 150

SECNO	Q	CWSEL	DIFWSP	DIFWSX	DIFKWS	TOPWID	XLCH
500.000	6480.00	584.21	0.00	0.00	0.00	146.69	0.00
500.000	8750.00	586.59	0.00	0.00	0.00	170.15	0.00
500.000	10390.00	587.66	0.00	0.00	0.00	180.69	0.00
500.000	12100.00	590.23	0.00	0.00	0.00	205.83	0.00
500.000	7700.00	585.60	0.00	0.00	0.00	160.39	0.00
1800.000	6480.00	584.89	0.00	0.68	0.00	1128.58	1300.00
1800.000	8750.00	587.30	0.00	0.71	0.00	1874.21	1300.00
1800.000	10390.00	588.47	0.00	0.81	0.00	1906.41	1300.00
1800.000	12100.00	590.94	0.00	0.71	0.00	1974.91	1300.00
1800.000	7700.00	586.29	0.00	0.69	0.00	1600.15	1300.00
4400.000	6480.00	585.86	0.00	0.97	0.00	1476.86	2600.00
4400.000	8750.00	587.87	0.00	0.57	0.00	1549.84	2600.00
4400.000	10390.00	588.94	0.00	0.48	0.00	1592.11	2600.00
4400.000	12100.00	591.19	0.00	0.25	0.00	1728.70	2600.00
4400.000	7700.00	586.99	0.00	0.70	0.00	1517.96	2600.00
6200.000	6480.00	586.72	0.00	0.86	0.00	1278.84	1800.00
6200.000	8750.00	588.41	0.00	0.54	0.00	1291.97	1800.00
6200.000	10390.00	589.40	0.00	0.46	0.00	1299.65	1800.00
6200.000	12100.00	591.43	0.00	0.25	0.00	1566.67	1800.00
6200.000	7700.00	587.65	0.00	0.65	0.00	1286.04	1800.00
8200.000	6480.00	587.36	0.00	0.64	0.00	1335.96	2000.00
8200.000	8750.00	589.91	0.00	0.50	0.00	1402.13	2000.00
8200.000	10390.00	589.85	0.00	0.45	0.00	1428.59	2000.00
8200.000	12100.00	591.72	0.00	0.29	0.00	1479.03	2000.00
8200.000	7700.00	588.20	0.00	0.55	0.00	1372.00	2000.00
10300.000	6480.00	587.72	0.00	0.36	0.00	1578.88	2100.00
10300.000	8750.00	589.23	0.00	0.32	0.00	1728.11	2100.00
10300.000	10390.00	590.16	0.00	0.31	0.00	1783.31	2100.00
10300.000	12100.00	591.93	0.00	0.21	0.00	1981.83	2100.00
10300.000	7700.00	588.54	0.00	0.34	0.00	1701.81	2100.00
12900.000	6480.00	588.49	0.00	0.77	0.00	559.67	2600.00
12900.000	8750.00	589.94	0.00	0.71	0.00	982.28	2600.00
12900.000	10390.00	590.83	0.00	0.67	0.00	1075.12	2600.00
12900.000	12100.00	592.40	0.00	0.46	0.00	1215.98	2600.00
12900.000	7700.00	589.29	0.00	0.75	0.00	792.41	2600.00
15800.000	6480.00	589.39	0.00	0.90	0.00	685.00	2100.00
15800.000	8750.00	590.93	0.00	0.99	0.00	685.00	2100.00
15800.000	10390.00	591.86	0.00	1.03	0.00	685.00	2100.00
15800.000	12100.00	593.24	0.00	0.84	0.00	685.00	2100.00
15800.000	7700.00	590.25	0.00	0.96	0.00	685.00	2100.00

PRINTED IN U.S.A.
FORM 1411 OD PRINTED BY ROTARY MANIFOLD FORMS

	17080.000	6480.00	589.65	0.00	0.26	0.00	143.65	1280.00
1	17080.000	8750.00	591.20	0.00	0.26	0.00	147.13	1280.00
2	17080.000	10390.00	592.12	0.00	0.27	0.00	149.22	1280.00
3	17080.000	12100.00	593.46	0.00	0.22	0.00	152.22	1280.00
4	17080.000	7700.00	590.51	0.00	0.26	0.00	145.60	1280.00

PRINTED IN U.S.A.

FORM 1411 GD PRINTED BY ROTARY MANIFOLD FORMS.

SECNO	Q	CUSEL	DIFWSP	DIFWSX	DIFKWS	TOPWID	XLCH
17180.000	6480.00	589.62	0.00	-0.03	0.00	99.20	100.00
17180.000	8750.00	591.14	0.00	-0.05	0.00	99.20	100.00
17180.000	10390.00	592.05	0.00	-0.07	0.00	99.20	100.00
17180.000	12100.00	593.36	0.00	-0.10	0.00	99.20	100.00
17180.000	7700.00	590.47	0.00	-0.04	0.00	99.20	100.00
17246.000	6480.00	590.88	0.00	1.26	0.00	99.20	66.00
17246.000	8750.00	593.62	0.00	2.47	0.00	99.20	66.00
17246.000	10390.00	595.66	0.00	3.61	0.00	99.20	66.00
17246.000	12100.00	597.98	0.00	4.62	0.00	99.20	66.00
17246.000	7700.00	592.33	0.00	1.86	0.00	99.20	66.00
17271.000	6480.00	590.93	0.00	0.05	0.00	99.20	100.00
17271.000	8750.00	593.67	0.00	0.05	0.00	99.20	100.00
17271.000	10390.00	595.72	0.00	0.06	0.00	99.20	100.00
17271.000	12100.00	598.03	0.00	0.05	0.00	99.20	100.00
17271.000	7700.00	592.39	0.00	0.05	0.00	99.20	100.00
18700.000	6480.00	591.67	0.00	0.74	0.00	308.14	1369.00
18700.000	8750.00	594.43	0.00	0.76	0.00	573.13	1369.00
18700.000	10390.00	596.54	0.00	0.82	0.00	1123.85	1369.00
18700.000	12100.00	598.89	0.00	0.86	0.00	1175.44	1369.00
18700.000	7700.00	593.12	0.00	0.73	0.00	408.98	1369.00
18701.000	6480.00	591.53	0.00	-0.13	0.00	298.93	1.00
18701.000	8750.00	594.42	0.00	-0.01	0.00	571.78	1.00
18701.000	10390.00	596.66	0.00	0.12	0.00	1126.46	1.00
18701.000	12100.00	599.01	0.00	0.12	0.00	1178.06	1.00
18701.000	7700.00	593.06	0.00	-0.06	0.00	404.59	1.00
18711.000	6480.00	591.63	0.00	0.09	0.00	305.37	10.00
18711.000	8750.00	594.45	0.00	0.03	0.00	576.05	10.00
18711.000	10390.00	596.67	0.00	0.01	0.00	1126.64	10.00
18711.000	12100.00	599.01	0.00	0.01	0.00	1178.15	10.00
18711.000	7700.00	593.11	0.00	0.06	0.00	408.54	10.00
18712.000	6480.00	591.66	0.00	0.03	0.00	307.42	1.00
18712.000	8750.00	594.46	0.00	-0.05	0.00	565.92	1.00
18712.000	10390.00	596.61	0.00	-0.07	0.00	1125.30	1.00
18712.000	12100.00	598.96	0.00	-0.05	0.00	1177.09	1.00
18712.000	7700.00	593.09	0.00	-0.03	0.00	406.67	1.00
19600.000	6480.00	592.78	0.00	1.12	0.00	249.50	900.00
19600.000	8750.00	595.14	0.00	0.74	0.00	660.00	900.00
19600.000	10390.00	597.00	0.00	0.39	0.00	660.00	900.00
19600.000	12100.00	599.18	0.00	0.22	0.00	660.00	900.00
19600.000	7700.00	594.02	0.00	0.93	0.00	353.52	900.00
19700.000	6480.00	593.21	0.00	0.43	0.00	527.94	100.00
19700.000	8750.00	595.60	0.00	0.46	0.00	604.98	100.00
19700.000	10390.00	597.39	0.00	0.39	0.00	605.00	100.00
19700.000	12100.00	599.49	0.00	0.31	0.00	605.00	100.00
19700.000	7700.00	594.48	0.00	0.46	0.00	604.98	100.00

PRINTED IN U.S.A.
FORM 1411 GO PRINTED BY ROTARY MANIFOLD +DPMS

SECNO	Q	CWSEL	DIFWSP	DIFWSX	DIFKWS	TOPWID	XLCH
19747.000	6480.00	593.22	0.00	0.00	0.00	528.04	47.00
19747.000	8750.00	595.64	0.00	0.04	0.00	604.98	47.00
19747.000	10390.00	597.45	0.00	0.06	0.00	605.00	47.00
19747.000	12100.00	599.58	0.00	0.09	0.00	605.00	47.00
19747.000	7700.00	594.51	0.00	0.02	0.00	604.98	47.00
19748.000	6480.00	593.22	0.00	0.00	0.00	565.88	1.00
19748.000	8750.00	595.64	0.00	0.00	0.00	604.40	1.00
19748.000	10390.00	597.46	0.00	0.00	0.00	604.86	1.00
19748.000	12100.00	599.58	0.00	0.00	0.00	605.00	1.00
19748.000	7700.00	594.51	0.00	0.00	0.00	604.11	1.00
19753.000	6480.00	594.10	0.00	0.88	0.00	604.01	3.00
19753.000	8750.00	595.95	0.00	0.31	0.00	604.48	3.00
19753.000	10390.00	597.73	0.00	0.28	0.00	604.93	3.00
19753.000	12100.00	599.86	0.00	0.28	0.00	605.00	3.00
19753.000	7700.00	594.95	0.00	0.44	0.00	604.23	3.00
22300.000	6480.00	594.13	0.00	0.03	0.00	1285.42	2547.00
22300.000	8750.00	595.98	0.00	0.03	0.00	1587.43	2547.00
22300.000	10390.00	597.77	0.00	0.03	0.00	1616.43	2547.00
22300.000	12100.00	599.89	0.00	0.03	0.00	1648.25	2547.00
22300.000	7700.00	594.98	0.00	0.03	0.00	1299.61	2547.00

SUMMARY OF ERRORS

PRINTED IN U.S.A.
FORM 141, 80 PRINTED BY ROSARY MANIFOLD FORMS

FLOOD INSURANCE ZONE DATA FOR CITY OF FLATROCK

FLOOD HAZARD FACTOR FOR ENTIRE REACH USING SECTIONS

SECTION NUMBER	CUMULATIVE DISTANCE	ELEVATION DIFFERENCE BETWEEN BASE FLOOD AND 10¢	2¢	0.2¢
500.000	0.	-3.4	-1.1	2.6
1800.000	1300.	-3.6	-1.2	2.5
4400.000	3900.	-3.1	-1.1	2.2
6200.000	5700.	-2.7	-1.0	2.0
8200.000	7700.	-2.5	-0.9	1.9
10300.000	9800.	-2.4	-0.9	1.8
12900.000	12400.	-2.3	-0.9	1.6
15800.000	14500.	-2.5	-0.9	1.4
17080.000	15780.	-2.5	-0.9	1.3
17180.000	15880.	-2.4	-0.9	1.3
17246.000	15946.	-4.8	-2.0	2.3
17271.000	16046.	-4.8	-2.0	2.3
18700.000	17415.	-4.9	-2.1	2.3
18701.000	17416.	-5.1	-2.2	2.3
18711.000	17426.	-5.0	-2.2	2.3
18712.000	17427.	-4.9	-2.2	2.4
19600.000	18327.	-4.2	-1.9	2.2
19700.000	18427.	-4.2	-1.8	2.1
19747.000	18474.	-4.2	-1.8	2.1
19748.000	18475.	-4.2	-1.8	2.1
19753.000	18478.	-3.6	-1.8	2.1
22300.000	21025.	-3.6	-1.8	2.1
WEIGHTED AVG FOR REACH		-3.1	-1.2	2.0

FHF FOR THE REACH = 030 WITH 88.9¢ OF THE REACH WITHIN 1.0 FEET
ZONE FOR THE REACH = A 6

PRINTED IN U.S.A.
FORM 1411-GO PRINTED BY ROYAL "M" FANFOLD FORMS

00BREAK00

1) COUNTY: Wayne

2) STUDY NAME: City of Flat Rock

3) WATERCOURSE: Silver Creek

4) DOCUMENT TYPE: 10 year

00BREAK00

State Copy

14:46:35 X406 HILL HW2UD907 HUDFROCK DEC 20, 1979

FORM 1411-GD PRINTED BY ROTARY MANIFOLD FORMS.

PRINTED IN U.S.A.

Hudfrock

10-20

14:40:35 X406 BILL RU200907 RUSFROCK DEC 20, 1979

PRINTED IN U.S.A.

FORM 1410-GO PRINTED BY ROTARY MANIFOLD FORMS

```
JOBID=HU280907          USER=BILL          PROJECT=HUDFROCK          BILLING=HUDFROCK          RUN=X6400

14:44:40                    JOB INTRODUCED FROM CD01 JCL                    DEC 28, 1979

14:44:51  START OF TRANSLATION

          $JOB HU280907,USER=BILL,PROJECT=HUDFROCK;
          $INPUT TR20;
          RECORD COUNT: 41
          $ENDINPUT;
           VALUES NTAPAK;
           CREATE INFILE=*TR20,OUTFILE=(TR20IN,TEMPRY,END=PASS,DVC=MS/M400,MD=81),
                          OUTDEF=(RECSIZE=80,BLKSIZE=960,RECFORM=Fb,FILEFORM=BFAS);
           SEND 'START OF TR20 EXECUTION';
           STEP TR20,,,,,OPTION3='FILIOM 2,FILEO 4';
           ALC FILE0A,SIZE=2,UNIT=CYL,INCRSIZE=1;
           ASG FILE0A,FILE=A,TEMPRY,DVC=MS/M400,MD=81;
           ALC FILE0B,SIZE=2,UNIT=CYL,INCRSIZE=1;
           ASG FILE0B,FILE0B,TEMPRY,DVC=MS/M400,MD=81;
           ASG INRD,TR20IN,TEMPRY,DVC=MS/M400,MD=81;
           ENDSTEP;
          $END JOB;

          RECORD COUNT :     56

14:44:52  END OF TRANSLATION
```

PRINTED IN U.S.A.
FORM 1611 REPRINTED BY ROTARY MANIFOLD FORMS.

```
JOBID=HU200V07          USER=BILL          PROJECT=HUDFROCK          BILLING=HUDFROCK          HO\=X0400
14:44:53                              JOB EXECUTION LISTING                              DEC 20, 1979

        STEP 1 CREATE
        LOAD MODULE = M=UTILITY (79/10/9 12:57) PREINITIALIZED
        LIBRARY = SYS.HLMLIB
14:44:56 STEP STARTED XPRTY=9
        D000.01         CREATE    VERSION= 10.0C  RELEASE 20  EXECUTED ON DEC 20, 1979
        D000.30         INFILE    = SYS.IN
        *E06.   5 CYLINDER(S) ALLOCATED ON JOLDUE; MTAPAK FOR EFN: JOLD4D6.T320;N
        D000.30         OUTFILE   = TR2DIN
        D003.00         INFILE    : NUMBER OF READ RECORDS    : 41
        D003.01         OUTFILE   : NUMBER OF WRITTEN RECORDS  : 41
        TASK MAIN J=02 P=00 COMPLETED
        TEMPORARY FILES USED=    76 TRACKS
        OUTFILE  ON  MTAPAK ; NO OF IO CONNECTS=          5
        CPU          0.043                    PROG MISSING SLOTS      20    STACKOV      9
        ELAPSED      0.285                    SYS MISSING SLOTS       59
        LINES            0   LIMIT    NOLIM  BACKING STORE        39072
        CARDS            0   LIMIT    NOLIM  BUFFER SIZE           2096    CPSIZE     1552
14:45:14 STEP COMPLETED

        START OF TR2D EXECUTION
        STEP 2
        LOAD MODULE = TR2D (79/4 /5 00:10)
        LIBRARY = MTAENGLIB
14:45:35 STEP STARTED XPRTY=9
        FP04.   2 CYLINDER(S) ALLOCATED ON VOLUME: MTAPAK FOR EFN: JOLD4D6.FILE04
        FP04.   2 CYLINDER(S) ALLOCATED ON VOLUME: MTAPAK FOR EFN: JOLD4D6.FILE04
        TASK MAIN J=02 P=00 COMPLETED
        OUF01,RP=FILE04         BLOCK CLR RATE=          0
        OUF01,SAV=FILE05        REMEMBER FILE=           0    UNLOCK BUFFER=      3    CREATE BUFFER=      4
        TEMPORARY FILES USED=    152  TRACKS
        WORK     ON  MTAPAK ; NO OF IO CONNECTS=          4
        FILE04   ON  MTAPAK ; NO OF IO CONNECTS=         46
        FILE05   ON  MTAPAK ; NO OF IO CONNECTS=         14
        OUTP     ON  LGO1V4 ; NO OF IO CONNECTS=         13
        CPU          5.314                    PROG MISSING SLOTS     130    STACKOV     31
        ELAPSED      9.982                    SYS MISSING SLOTS      248
        LINES          178   LIMIT    NOLIM  BACKING STORE        547056
        CARDS            0   LIMIT    NOLIM  BUFFER SIZE           10512   CPSIZE     2272
14:46:23 STEP COMPLETED

        START    14:44:53  LINES          178
        STOP     14:46:25  CARDS            0
        CPU          5.344
        ELAPSE       1.532
14:46:25 RESULT: JOB COMPLETED
```

PRINTED IN U.S.A.
FORM 161-GB PRINTED BY ROTARY MANIFOLD FORM.

ROMULUS-HURON DIVERSION 11001079

TR-20 HYDROLOGY

PROGRAM DATE - FEB. 14, 1974 S/360

FORM L811-0D PRINTED BY ROTARY MANIFOLD FORMS.

PRINTED IN U.S.A.

PAGE=210

EXECUTIVE CONTROL CARD OPERATION LIST

LISTING OF DATA IN CORE

10 ROMULUS-HURON DIVERSION

VELOCITY INCREMENT

1 CZABLE 0.2000

8	0.0000	0.0800	0.1800	0.2500	0.3200
8	0.3700	0.4100	0.4500	0.4900	0.5100
8	0.5400	0.5700	0.5900	0.6100	0.6300
8	0.6500	0.6600	0.6700	0.6800	0.7000
8	0.7100	0.7200	0.7200	0.7400	0.7300
8	0.7600	0.7700	0.7700	0.7800	0.7900
8	0.7900	0.8000	0.8100	0.8100	0.8200
8	0.8200	0.8300	0.8300	0.8400	0.8400
8	0.8500	0.8500	0.8500	0.8600	0.8600
8	0.8600	0.8600	0.8700	0.8700	0.8700
8	0.8800	0.8800	0.8800	0.8800	0.8900
8	0.8900	0.8900	0.8900	0.8900	0.9000
8	0.9000	0.9000	0.9000	0.9000	0.9100
8	0.9100	0.9100	0.9100	0.9100	0.9100
8	0.9200	0.9200	0.9200	0.9200	0.9200
8	0.9200	0.9200	0.9200	0.9300	1.9500

2 ENERGI

STRUCT NO.

3 STRUCT 1

	INFLOW ID	DISCHARGE	STORAGE
0	593.5000	0.0000	0.0000
8	593.2000	50.0000	0.1000
8	593.8999	100.0000	0.2000
8	595.2000	200.0000	2.0000
8	596.6000	330.0000	58.0000
8	599.2000	420.0000	182.0000
8	599.7000	500.0000	222.0000
8	600.0500	600.0000	252.0000
8	600.3000	700.0000	296.0000
8	600.7000	800.0000	358.0000

4 BRATA

TIME INCREMENT

4 DIMKYD

8	0.0000	0.0300	0.1070	0.1900	0.5100

PRINTED IN U.S.A.
FORM 1411.00 PRINTED BY ROTARY MANIFOLD FORMS

0.4700	0.6400	0.8200	0.9300	0.9900	
1.0000	0.9900	0.9300	0.8600	0.7800	
0.6900	0.5600	0.4600	0.3900	0.3500	
0.2900	0.2410	0.2070	0.1740	0.1470	
0.1260	0.1070	0.0910	0.0770	0.0660	
0.0550	0.0470	0.0400	0.0340	0.0290	
0.0250	0.0210	0.0180	0.0150	0.0130	
0.0110	0.0090	0.0080	0.0070	0.0060	
0.0050	0.0040	0.0030	0.0020	0.0010	
0.0000	0.0000	0.0000	0.0000	0.0000	

Y ENDTBL

COMPUTED PEAK K FACTOR = 404.00

TIME INCREMENT
5 RAINFL T 0.5000

0.0030	0.0080	0.0170	0.0260	0.0350	
0.0450	0.0550	0.0650	0.0760	0.0870	
0.0990	0.1120	0.1250	0.1400	0.1560	
0.1740	0.1940	0.2190	0.2540	0.3030	
0.3150	0.3830	0.4240	0.4540	0.4820	
0.5050	0.5270	0.5480	0.5670	0.5840	
0.6030	0.6160	0.6300	0.6440	0.6570	
0.6700	0.6820	0.6930	0.7050	0.7160	
0.7260	0.7360	0.7460	0.7550	0.7650	
0.7750	0.7850	0.7920	1.0000	1.0000	

Y ENDTBL

PRINTED IN U.S.A.
FORM 1411-SB PRINTED BY ROTARY MANIFOLD FORMS

STANDARD CONTROL INSTRUCTIONS

6 RESVOR 2 1 6 7 592.5000 1 1 1 1 0 0

ENDATA

END OF LISTING

PRINTED IN U.S.A.

FORM IBM-GO PRINTED BY BOTANY MANIFOLD FORMS

PASS=21(

EXECUTIVE CONTROL CARD OPERATION INCREM MAIN TIME INCREMENT= 0.20

DISCHARGE HYDROGRAPH, HYDROGRAPH LOCATION 6

STARTING TIME= 0.00 TIME INCREMENT= 1.00 DRAINAGE AREA= 2.34 BASE FLOW= 0.00

H	2.0000	10.0000	30.0000	65.0300	250.0000
G	390.0000	455.0000	440.0000	425.0000	415.0000
F	400.0000	375.0000	345.0000	320.0000	290.0000
E	270.0000	250.0000	235.0000	215.0000	160.0000
J	145.0000	110.0000	2.0000	0.0000	0.0000

* END*OF
EXECUTIVE CONTROL CARD OPERATION COMPUT, FROM XSECTN/STRUCT 0/ 1 TO XSECTN/STRUCT 0/ 1

STARTING TIME= 0.00 RAIN DEPTH= 3.00 RAIN DURATION= 1.00 RAIN TABLE NO.= 1 SOIL CONDITION= 2
ALTERNATE NO.= 2 STORM NO.= 1

SUBROUTINE RLSVOR STRUCTURE 1
SURFACE ELEVATIONS= 592.50

PEAK TIMES	PEAK DISCHARGES	PEAK ELEVATIONS
12.96	326.852	597.14
23.42	7.654	592.61
23.82	2.051	592.54
24.22	1.002	592.51
24.62	0.396	592.51
25.02	0.147	592.50
25.42	0.055	592.50
25.82	0.020	592.50
26.25	0.008	592.50

HYDROGRAPH, TZERO= 0.00 DELTA T= 0.20 DRAINAGE AREA= 2.34

TIME											
0.00	DISCHG	0.00	1.31	3.85	5.70	7.79	9.74	13.58	17.60	21.67	25.55
0.00	ELEV	592.50	592.52	592.53	592.53	592.54	592.56	592.59	592.75	592.80	592.86
2.00	DISCHG	29.50	30.16	30.93	31.68	32.43	33.50	35.60	179.27	180.23	170.30
2.00	ELEV	592.91	593.05	593.21	593.36	593.52	593.67	593.95	596.13	596.46	594.42
4.00	DISCHG	196.32	201.52	205.56	206.26	210.00	215.02	221.32	236.99	238.02	231.99
4.00	ELEV	595.10	595.22	595.25	595.30	595.35	595.42	595.50	595.58	595.66	595.79
6.00	DISCHG	245.31	251.58	257.58	262.31	268.27	273.98	278.64	283.66	286.14	292.61
6.00	ELEV	595.83	595.95	596.01	596.09	596.16	596.24	596.31	596.37	596.43	596.49
8.00	DISCHG	294.45	300.13	301.72	303.24	304.75	306.25	307.60	308.96	310.23	311.45
8.00	ELEV	596.55	596.60	596.64	596.68	596.72	596.76	596.80	596.84	596.87	596.91
10.00	DISCHG	312.63	313.79	314.78	315.71	316.58	317.37	318.05	318.71	319.25	319.76
10.00	ELEV	596.93	596.96	596.98	597.01	597.03	597.05	597.07	597.09	597.10	597.11
12.00	DISCHG	320.17	320.36	320.59	320.74	320.49	320.85	320.80	320.67	320.47	320.19
12.00	ELEV	597.12	597.13	597.14	597.14	597.14	597.14	597.14	597.14	597.13	597.13
14.00	DISCHG	319.83	319.42	318.96	318.45	317.90	317.30	316.66	315.97	315.26	314.47
14.00	ELEV	597.12	597.11	597.09	597.08	597.07	597.05	597.02	597.00	596.98	596.95
16.00	DISCHG	313.66	312.81	311.95	311.02	310.09	309.13	308.14	307.11	306.06	304.93
16.00	ELEV	596.96	596.93	596.91	596.89	596.86	596.84	596.81	596.78	596.76	596.73
18.00	DISCHG	303.72	302.58	301.30	299.89	298.39	296.84	295.24	293.64	292.01	290.49
18.00	ELEV	596.70	596.67	596.63	596.60	596.55	596.50	596.45	596.40	596.35	596.30
20.00	DISCHG	274.57	270.56	266.46	262.27	258.00	253.64	249.23	244.79	240.15	235.52
20.00	ELEV	596.24	596.17	596.13	596.07	596.01	595.95	595.89	595.81	595.73	595.65

PRINTED IN U.S.A.

FORM 1411.0C PRINTED BY ROTARY MANIFOLD FORMS

22.00	DISCHG	225.26	218.67	211.88	205.69	185.36	19.93	-12.16	7.42	-4.53	2.77
22.00	ELEV	595.35	595.46	595.57	595.28	595.01	592.78	592.33	592.50	592.44	592.56
24.00	DISCHG	-1.69	1.03	-0.63	0.38	-0.25	0.14	-0.07	0.05	-0.03	0.02
24.00	ELEV	592.48	592.51	592.49	592.51	592.50	592.50	592.50	592.50	592.50	592.50
26.00	DISCHG	-0.01	0.01	0.00							
26.00	ELEV	592.50	592.50	592.50							

TOTAL WATER ON UNCPES/ON DRAINAGE AREA= 3.7162 CFS-HRS= 5612.15 ACRE-FT= 463.79

ENDCMP

ENDJOB CARD ENCOUNTERED. END OF JOB.

PRINTED IN U.S.A.
FORM 1411-GD PRINTED BY ROTARY MANIFOLD FORMS.

END OF JOBS IN THIS BOX

PRINTED IN U.S.A.

FORM 1411-GO-PRINTED BY ROTARY MANIFOLD FORMS


PRINTED IN U.S.A.

```
**********************************************************************
*                                                                    *
*                        E R R O R   S U M M A R Y                   *
*                                                                    *
*       0  ERROR(S) DETECTED BY THE USER PROGRAM                     *
*       0  ERROR(S) DETECTED BY THE MATHEMATICAL PACKAGE             *
*       0  ERROR(S) DETECTED FOR INPUT/OUTPUT STATEMENTS             *
*                                                                    *
**********************************************************************
```

FORM 141-0B PRINTED BY ROTARY MANIFOLD FORMS

FORM 1411-SD PRINTED BY ROTARY MANIFOLD FORMS.

PRINTED IN U.S.A.



14:47:12 X406 BILL NU20C907 ROOFROCK DEC 20, 1979

RADD TOST SR:/0** L4:13*T F0:23-977 22A20U64 P701 PR/H112/F2/631../8132

PRINTED IN U.S.A.

FORM 1311.00 PRINTED BY ROTARY MANIFOLD FORMS

00BREAK00

1) COUNTY: Wayne

2) STUDY NAME: City of Flat Rock

3) WATERCOURSE: Silver Creek

4) DOCUMENT TYPE: 50 year

00BREAK00

First Copy

14:50:04 X437 GILL HU2D0937 HUDFROCK DEC 20, 1979

Elrick

TK-20

PRINTED IN U.S.A.
FORM 1411-6 PRINTED BY ROTARY MANIFOLD FORMS

```
JOBID=HU2QQ9Q7          USER=BILL          PROJECT=HUDFROCK          BILLING=HUDFROCK          ROK=X3407

14:47:39                    JOB INTRODUCED FROM                    DEC 20, 1979
                              CD01 JCL

14:47:49  START OF TRANSLATION

          $JOB HU2QQ9Q7,USER=BILL,PROJECT=HUDFROCK;
          $INPUT TR2Q;
          RECORD COUNT: 41
          $ENDINPUT;
           VALUES NTAPAK;
           CREATE INFILE=*TR2Q,OUTFILE=(TR2QIN,TEMPRY,END=PASS,DVC=MS/M400,MD=81),
                          OUTDEF=(RECSIZE=80,BLKSIZE=960,RECFORM=FB,FILEFORM=SFAS);
           SEND 'EOJ.RT OF TR2Q EXECUTION.'
           STOP TR2Q,NTAENGLISH,OPTIONS='FILE#A 2,FILE#E 4';
           ALL FILE#A,SIZE=2,UNIT=CYL,INCRSIZE=1;
           ASG FILE#A,FILE#A,TEMPRY,DVC=MS/M400,MD=81;
           ALL FILE#B,SIZE=2,UNIT=CYL,INCRSIZE=1;
           ASG FILE#B,FILE#B,TEMPRY,DVC=MS/M400,MD=81;
           ASG HDRB,TR2QIN,TEMPRY,DVC=MS/M400,MD=81;
           ENDSTEP;
          $ENDJOB;

          RECORD COUNT :    56

14:47:51  END OF TRANSLATION
```

PRINTED IN U.S.A.

FORM 1411-08 PRINTED BY ROTARY MANIFOLD FORMS

```
JOBID=HU2U0907          USER=BILL          PROJECT=RUDFROCK          BILLING=RUDFROCK          ROP=X0407

14:47:52                        JOB EXECUTION LISTING                        DEC 20, 1979


        STEP 1 CREATE
        LOAD MODULE = HOUTILITY (79/10/9 12:57) PREINITIALIZED
        LIBRARY = SYS.RLMLIB
14:47:55 STEP STARTED XPRTY=9
        0000.07         CREATE    VERSION: 10.00  RELEASE 19 ,EXECUTED ON DEC 20, 1979
        0000.30         INFILE    = SYS.IN
        FP04,   4 CYLINDER(S) ALLOCATED ON VOLUME: HTAPAK FOR EFN: J0U0407.TR20J9
        0000.30         OUTFILE   = TR20I9
        0L03.00         INFILE    : NUMBER OF READ RECORDS   : 41
        0N03.01         OUTFILE   : NUMBER OF WRITTEN RECORDS  : 41
        TASK MAIN J=02 P=00 COMPLETED
        TEMPORARY FILES USED=     75 TRACKS
        OUTFILE  ON  STEP#1  : ID  OF  ID  CONNECTS=          3
        CPU          0.044                    PROG MISSING SEGTS        24   STACKOV      9
        ELAPSED      0.291                    SYS  MISSING SEGTS        89
        LINES        0   LIMIT     NOLIM     BACKING STORE          117216
        CARDS        0   LIMIT     NOLIM     BUFFER SIZE              2005   CPSIZE     582
14:49:13 STEP COMPLETED

        START OF TR20 EXECUTION
        STEP 2
        LOAD MODULE = TR20 (79/1/25 05:15)
        LIBRARY = RTREHGLB
14:49:35 STEP STARTED XPRTY=95
        FP04,   2 CYLINDER(S) ALLOCATED ON VOLUME: HTAPAK FOR EFN: J0U0407.FILE0A
        FP04,   2 CYLINDER(S) ALLOCATED ON VOLUME: HTAPAK FOR EFN: J0U0407.FILE0B
        TASK MAIN J=02 P=00 COMPLETED
        OUTFIL,TYP=FILE0A       REPEATER RECSZ=          0
        OUTFIL,IFI=FILE0B       FIXEDSET RECSZ=          0     SHADOW BUFFER=      1   CRSIZE BUFFER=      2
        TEMPORARY FILES USED=   153 TRACKS
        JOBS     ON  HTAPAK ;  NO  OF  10  CONNECTS=          4
        FILE0A   ON  HTAPAK ;  NO  OF  10  CONNECTS=          6
        FILE0B   ON  HTAPAK ;  NO  OF  10  CONNECTS=          4
        USER     ON  LSTAK4 ;  NO  OF  10  CONNECTS=          3
        CPU          1.389                    PROG MISSING SEGTS       103   STACKOV     33
        ELAPSED      3.106                    SYS  MISSING SEGTS       435
        LINES      183   LIMIT     NOLIM     BACKING STORE          547028
        CARDS        0   LIMIT     NOLIM     BUFFER SIZE             10512   CPSIZE     4272
14:49:46 STEP COMPLETED

        START  14:47:52   LINES      183
        STOP   14:49:43   CARDS        0
        CPU          1.414
        ELAPST       3.857
14:49:46 RESULT: JOB COMPLETED
```

PRINTED IN U.S.A.

FORM 1011-08-PRINTED BY ROTARY MANIFOLD FORMS.


73-20 HYDROLOGY
11001279
ADMIRALS-HARROW RIVERSIDE
PRINTED IN U.S.A.
FORM 1681 QB PRINTED BY ROTARY MANIFOLD FORMS

PROGRAM DATE = FEB. 14, 1974 S/360

PRINTED IN U.S.A.
FORM 1411-GD-PRINTED BY ROTARY MANIFOLD FORMS.

EXECUTIVE CONTROL CARD OPERATION LIST PASS=210

LISTING OF DATA IN CORE

CO ROMULUS-HURON DIVERSION

VELOCITY INCREMENT

1 STABLE 0.2000

8	0.0000	0.0000	0.1800	0.2500	0.3200
8	0.3700	0.4100	0.4500	0.4900	0.5100
8	0.5400	0.5700	0.5900	0.6100	0.6300
8	0.6300	0.6500	0.6700	0.6900	0.7000
8	0.7100	0.7150	0.7300	0.7400	0.7500
8	0.7600	0.7700	0.7700	0.7800	0.7900
8	0.7900	0.8000	0.8100	0.8100	0.8200
8	0.8200	0.8300	0.8300	0.8400	0.8400
8	0.8500	0.8500	0.8500	0.8600	0.8600
8	0.8650	0.8700	0.8750	0.8700	0.8700
8	0.8800	0.8800	0.8800	0.8900	0.8900
8	0.8900	0.8900	0.8900	0.8900	0.9000
8	0.9000	0.9000	0.9000	0.9000	0.9100
8	0.9100	0.9100	0.9100	0.9100	0.9100
8	0.9150	0.9200	0.9250	0.9200	0.9200
4	0.9250	0.9300	0.9250	0.9300	0.9300

V ENDTBL

STRUCT NO.

S STRUCT

	FLOW RATIO	DISCHARGE	STORAGE
8	392.5000	1.0000	0.0050
8	593.2000	50.0000	0.1000
8	595.3999	100.0000	0.2000
8	595.8000	200.0000	2.0000
8	596.5001	300.0000	56.0000
8	599.2000	400.0000	108.0000
8	599.7000	500.0000	222.0000
8	600.0500	600.0000	252.0000
8	600.3000	700.0000	296.0000
8	600.7000	800.0000	355.0000

V ENDTBL

TIME INCREMENT

6 DT=HYD

8	0.2000	0.0400	0.1000	0.1500	0.3100

PRINTED IN U.S.A.

FORM 151130 PRINTED BY ROTARY MANIFOLD FORMS

8	0.4700	0.6600	0.8200	0.9300	0.9900
8	1.0000	0.9900	0.9300	0.8600	0.7800
8	0.6800	0.5900	0.4800	0.3900	0.3300
8	0.2800	0.2410	0.2070	0.1740	0.1470
8	0.1250	0.1070	0.0910	0.0770	0.0660
8	0.0550	0.0470	0.0400	0.0340	0.0290
8	0.0250	0.0210	0.0180	0.0150	0.0130
8	0.0110	0.0090	0.0080	0.0070	0.0060
8	0.0050	0.0040	0.0030	0.0020	0.0020
8	0.0000	0.0000	0.0000	0.0000	0.0000

9 ENDTBL

COMPUTED PEAK K FACTOR = 484.00

TIME INCREMENT

5 RAINFL 1 0.3000

8	0.0000	0.0000	0.0170	0.0240	0.0350
8	0.0450	0.0550	0.0560	0.0760	0.0970
8	0.0990	0.1120	0.1250	0.1400	0.1580
8	0.1760	0.1940	0.2190	0.2540	0.3030
8	0.3150	0.5830	0.6240	0.6540	0.6820
8	0.7050	0.7270	0.7480	0.7670	0.7840
8	0.8000	0.8160	0.8300	0.8440	0.8570
8	0.8700	0.8820	0.8930	0.9050	0.9150
8	0.9260	0.9360	0.9460	0.9550	0.9650
8	0.9740	0.9830	0.9920	1.0000	1.0000

9 ENDTBL

PRINTED IN U.S.A.
FORM 1611-68 PRINTED BY ROTARY MANIFOLD FORMS

STANDARD CONTROL INSTRUCTIONS

6 RESVOR 2 1 6 7 592.5000 1 1 1 1 0 0

RUDATA

END OF LISTING

PRINTED IN U.S.A.

FORM 1411-GD PRINTED BY ROTARY MANIFOLD FORMS.

EXECUTIVE CONTROL CARD OPERATION INCREM MAIN TIME INCREMENT= 0.20 PASS=210.

DISCHARGE HYDROGRAPH, HYDROGRAPH LOCATION 6

STARTING TIME= 0.00 TIME INCREMENT= 1.00 DRAINAGE AREA= 2.34 BASE FLOW= 0.00

8	0.0000	15.0000	35.0000	65.0000	220.0000
8	460.0000	630.0000	665.0000	640.0000	620.0000
8	600.0000	570.0000	535.0000	495.0000	455.0000
8	415.0000	385.0000	355.0000	325.0000	290.0000
8	265.0000	190.0000	0.0000	0.0000	0.0000

9 ENDTBL

EXECUTIVE CONTROL CARD OPERATION COMPUT FROM ASECTN/STRUCT U/ 1 TO ASECTN/STRUCT U/ 1

STARTING TIME= 0.00 RAIN DEPTH= 4.00 RAIN DURATION= 1.00 RAIN TABLE NO.= 1 SOIL CONDITION= 2
ALTERNATE NO.= 2 STORM NO.= 1

SUBROUTINE RESVOR STRUCTURE 1
INCREASE ELEVATION= 592.50

PEAK TIMES	PEAK DISCHARGES	PEAK ELEVATIONS
15.00	415.508	599.28
27.82	36.705	593.01
28.22	13.677	592.69
28.62	5.092	592.57
29.02	1.897	592.53
29.42	0.706	592.51
29.82	0.263	592.50
30.22	0.098	592.50
30.62	0.037	592.50
31.02	0.014	592.50

HYDROGRAPH TIME= 0.00 DELTA T= 0.20 DRAINAGE AREA= 2.36

TIME											
0.00	DISCHG	0.00	2.48	5.77	10.55	11.09	16.61	18.46	22.55	26.90	30.53
0.00	ELEV	592.50	592.53	592.56	592.62	592.66	592.70	592.76	592.82	592.87	592.93
2.00	DISCHG	34.91	43.23	54.23	65.63	75.69	89.72	102.96	117.15	132.39	144.53
2.00	ELEV	592.98	593.12	593.25	593.34	593.52	593.67	593.76	593.15	593.41	593.76
4.00	DISCHG	190.98	201.17	209.90	218.01	215.43	220.14	227.39	230.42	243.73	255.77
4.00	ELEV	595.38	595.22	595.25	595.29	595.29	595.43	595.59	595.71	595.84	595.96
6.00	DISCHG	256.56	277.61	288.55	299.37	304.56	309.01	313.62	318.15	322.46	326.59
6.00	ELEV	596.13	596.29	596.44	596.58	596.71	596.83	596.95	597.07	597.19	597.29
8.00	DISCHG	330.31	334.03	338.71	343.51	346.20	349.60	353.29	356.69	359.49	362.20
8.00	ELEV	597.40	597.51	597.61	597.71	597.84	597.89	597.99	598.07	598.15	598.24
10.00	DISCHG	366.31	369.32	372.21	374.98	377.64	380.18	382.61	384.92	387.13	389.17
10.00	ELEV	598.32	598.40	598.48	598.55	598.62	598.68	598.73	598.81	598.86	598.92
12.00	DISCHG	391.19	392.93	394.63	396.20	397.84	398.96	400.59	403.35	406.73	409.17
12.00	ELEV	598.97	599.02	599.06	599.10	599.14	599.17	599.23	599.22	599.23	599.25
14.00	DISCHG	414.19	412.80	414.02	414.83	414.30	415.57	415.37	414.99	414.38	413.55
14.00	ELEV	599.25	599.23	599.27	599.27	599.26	599.26	599.25	599.27	599.27	599.27
16.00	DISCHG	412.52	411.28	409.06	406.24	403.45	404.49	402.66	400.08	399.24	394.59
16.00	ELEV	599.26	599.26	599.25	599.26	599.25	599.22	599.21	599.20	599.18	599.16
18.00	DISCHG	397.46	396.49	395.42	394.27	393.05	391.75	390.37	388.88	387.30	385.62
18.00	ELEV	599.13	599.11	599.08	599.05	599.04	598.99	598.99	598.91	598.87	598.83
20.00	DISCHG	383.85	381.99	379.97	377.85	375.62	373.27	370.83	367.96	365.99	366.98

PRINTED IN U.S.A.
FORM 141-0D PRINTED BY ROTARY MANIFOLD WORKS.

20.00	ELEV	598.73	598.73	598.68	598.62	598.57	598.50	598.44	598.36	598.26	598.16
22.00	DISCHG	355.54	350.91	346.33	341.82	337.37	332.97	328.63	324.35	320.12	315.95
22.00	ELEV	598.04	597.92	597.80	597.69	597.57	597.46	597.34	597.23	597.12	597.01
24.00	DISCHG	311.83	307.77	303.75	299.53	290.50	281.74	273.25	265.01	257.02	249.27
24.00	ELEV	596.91	596.80	596.70	596.59	596.47	596.34	596.23	596.11	596.00	595.89
26.00	DISCHG	241.76	234.47	227.40	220.54	213.89	207.45	201.19	95.57	-56.33	35.60
26.00	ELEV	595.78	595.68	595.58	595.49	595.39	595.50	595.22	595.84	591.66	593.00
28.00	DISCHG	-29.72	13.26	-2.09	4.94	-3.01	1.64	-1.12	0.69	-0.42	0.26
28.00	ELEV	592.20	592.69	592.39	592.57	592.46	592.53	592.48	592.51	592.49	592.50
30.00	DISCHG	-0.16	0.10	-0.06	0.04	-0.02	0.01	-0.01	0.00		
30.00	ELEV	592.50	592.50	592.50	592.50	592.50	592.50	592.50	592.50		

TOTAL WATER, IN INCHES OF DRAINAGE AREA= 5.6560 CFS-HRS= 8239.68 ACRE-FT= 680.91

ENDCRP

END.OF CARD ENCOUNTERED. END OF JOB.

PRINTED IN U.S.A.
FORM 1411-GB PRINTED BY ROTARY MANIFOLD FORMS.

END OF 1 JOBS IN THIS RUN

PRINTED IN U.S.A.

FORM 1611-GO-PRINTED BY ROTARY MANIFOLD FORMS.


R


```
**************************************************
*                                                *
*                  E R R O R   S U M M A R Y     *
*                                                *
*     0  ERROR(S) DETECTED BY THE USER PROGRAM   *
*     0  ERROR(S) DETECTED BY THE MATHEMATICAL PACKAGE *
*     0  ERROR(S) DETECTED FOR INPUT/OUPUT STATEMENTS  *
*                                                *
**************************************************
```


PRINTED IN U.S.A.

FORM 5411-05 PRINTED BY ROTARY MENIFOLD FORMS


14:57:27 X407 HILL HU200907 HUDFROCK DEC 20, 1979

























PRINTED IN U.S.A.
FORM TAB-02 PRINTED BY ROTARY MARIFOLD FORMS.

00BREAK00

1) COUNTY: Wayne

2) STUDY NAME: City of Flat Rock

3) WATERCOURSE: Silver Creek

4) DOCUMENT TYPE: 100 year

00BREAK00

State Copy

14:09:41 X430 BILL HU2J0907 HUDFROCK DEC 20, 1979

100 YR STORM

TR-20

PRINTED IN U.S.A.
FORM 7010-02 PRINTED BY ROTARY MANIFOLD FORMS

FORM 1411-09 PRINTED BY ROTARY MANIFOLD FORMS

PRINTED IN U.S.A.

```
JOBID=HU200907          USER=BILL          PROJECT=HUDFROCK          BILLING=HUDFROCK          NON=X0400

14:07:48                JOB INTRODUCED FROM CDC1 JCL                DEC 20, 1979

14:07:29  START OF TRANSLATION

          $JOB HU200907,USER=BILL,PROJECT=HUDFROCK;
          $INPUT TR20;
          RECORD COUNT: 47
          $ENDINPUT;
           VALUES UTAPAK;
           CREATE INFILE=*TR20,OUTFILE=(TR20IN,TEMPRY,END=PASS,DVC=MS/M400,MD=81),
                          OUTDEF=(RECSIZE=80,BLKSIZE=960,RECFORM=FB,FILEFORM=UFAS);
           SEND 'START OF TR20 EXECUTION';
           STEP TR20,UTREL0L0,OPTIONS='FILE=A 2,FILE=B 4';
           ASG FILE=A,STR=P,UNIT=CYL,1,INCRSIZE=1;
           ASG FILE=A,FILE=A,TEMPRY,DVC=MS/M400,MD=81;
           ALC FILE=B,SIZE=2,UNIT=CYL,INCRSIZE=1;
           ASG FILE=B,FILE=B,TEMPRY,DVC=MS/M400,MD=81;
           ASG HEAD,TR20IN,TEMPRY,DVC=MS/M400,MD=81;
           ENDSTEP;
          $END JOB;

                    RECORD COUNT :     56

14:08:05  END OF TRANSLATION
```

PRINTED IN U.S.A.

FORM 748-60 PRINTED BY ROTARY MANIFOLD FORMS.

```
JOBID=HU200907          USER=BILL          PROJECT=HUDFROCK          BILLING=HUDFROCK          JOB=X0400

14:08:01                          JOB EXECUTION LISTING                          DEC 20, 1979

          STEP 1 CREATE
          LOAD MODULE = HUTILITY (79/10/9 12:57) PREINITIALIZED
          LIBRARY = SYS.HLMLIB
14:08:05  STEP STARTED XPRTY=9
          0000.01      CREATE   VERSION: 10.00  RELEASE 10 EXECUTED ON DEC 20, 1979
          0030.30      INFILE   = SYS.IN
          FP04.    5 CYLINDER(S) ALLOCATED ON VOLUME: HTAPAK FOR DFN: J0800S03.TR20IN
          0000.30      OUTFILE  = TR20IN
          0003.00      INFILE   : NUMBER OF READ RECORDS   : 41
          0003.01      OUTFILE  : NUMBER OF WRITTEN RECORDS  : 41
          TASK MAIN.J=03 P=00 COMPLETED
          TEMPORARY FILES USED=    75 TRACKS
          OUTFILE  ON HTAPAK :  NO. OF IO  CONNECTS=        5
          CPU          0.045                    PROG MISSING SEGTS       22   STACKOV     9
          ELAPSED      0.289                    SYS MISSING SEGTS        91
          LINES          0   LIMIT    NOLIM     BACKING STORE        117216
          CARDS          0   LIMIT    NOLIM     BUFFER SIZE            2096   CPSIZE    1552
14:08:25  STEP COMPLETED


          START OF TR20 EXECUTION
          STEP 2
          LOAD MODULE = TR20  (79/4 15:03:36)
          LIBRARY = SYS.RELLIB
14:08:26  STEP STARTED XPRTY=9
          FP04.    2 CYLINDER(S) ALLOCATED ON VOLUME: HTAPAK FOR DFN: J0800400.FILE=A
          FP04.    2 CYLINDER(S) ALLOCATED ON VOLUME: HTAPAK FOR DFN: J0800400.FILE=B
          TASK MAIN.J=02 P=00 COMPLETED
          DUF01.IF=PI.CMD      REMEMBER, REUSE=
          DUF01.IF=PI.CMD      REMEMBER, REUSE=        0   U'LOC: BUFFERS=        0   CREATE BUFFERS=        2
          TEMPORARY FILES USED=    152 TRACKS
          WORK     ON HTAPAK :  NO. OF IO  CONNECTS=          4
          FILE=A   ON HTAPAK :  NO. OF IO  CONNECTS=         46
          FILE=B   ON HTAPAK :  NO. OF IO  CONNECTS=         14
          LOPR     ON LOOKUP :  NO. OF IO  CONNECTS=         15
          CPU          0.300                    PROG MISSING SEGTS      117   STACKOV     31
          ELAPSED      0.411                    SYS MISSING SEGTS       268
          LINES          152   LIMIT    NOLIM     BACKING STORE        806080
          CARDS            0   LIMIT    NOLIM     BUFFER SIZE            10512   CPSIZE    2272
14:09:32  STEP COMPLETED


          START    14:08:01   LINES        152
          STOP     14:09:54   CARDS          0
          CPU          0.350
          ELAPSE       1.257
14:09:54  RESULT:  JOB COMPLETED
```

PRINTED IN U.S.A.

FORM 1411-GO PRINTED BY ROTARY MANIFOLD FORMS.

TR-20 HYDROLOGY

APOLLUS-HUNOC DIVERSION

1102107P

PRINTED IN U.S.A.

FORM 1411-02 PRINTED BY ROTARY MANIFOLD FORMS

PROGRAM DATE - FEB. 14, 1974 S/360

PRINTED IN U.S.A.
FORM 1411-GD PRINTED BY ROTARY MANIFOLD FORMS.

EXECUTIVE CONTROL CARD OPERATION LIST

LISTING OF DATA IN CORE

10 ROMULUS-HURON DIVERSION

VELOCITY INCREMENT

1 START 2.2000

8	0.0000	0.0800	0.1800	0.2500	0.3200
8	0.3700	0.4100	0.4300	0.4900	0.5100
8	0.5400	0.5700	0.5900	0.6100	0.6300
8	0.6500	0.6600	0.6700	0.6800	0.7000
8	0.7100	0.7200	0.7300	0.7400	0.7500
8	0.7600	0.7700	0.7700	0.7800	0.7900
8	0.7900	0.8000	0.8100	0.8100	0.8200
8	0.8200	0.8300	0.8300	0.8400	0.8400
8	0.8400	0.8500	0.8500	0.8600	0.8600
8	0.8600	0.8600	0.8700	0.8700	0.8700
8	0.8800	0.8800	0.8800	0.8900	0.8900
8	0.8900	0.8900	0.8900	0.8900	0.9000
8	0.9000	0.9000	0.9000	0.9000	0.9100
8	0.9100	0.9100	0.9100	0.9100	0.9100
8	0.9200	0.9200	0.9200	0.9200	0.9200
8	0.9200	0.9200	0.9200	0.9300	0.9300

7 ENDTBL

STRUCT NO.

5 STRUCT

	ELEVATION	DISCHARGE	STORAGE
8	592.5000	0.0000	0.0000
8	593.2000	30.0000	0.1000
8	593.6999	100.0000	0.2000
8	595.2000	200.0000	2.0000
8	596.6000	300.0000	56.0000
8	598.2000	400.0000	102.0000
8	599.7000	500.0000	222.0000
8	600.0500	600.0000	252.0000
8	600.3000	700.0000	290.0000
8	600.7000	800.0000	355.0000

7 ENDTBL

TIME INCREMENT

4 DTMHYD

8	0.0000	0.0100	0.0000	0.1900	0.5100

PRINTED IN U.S.A.
FORM 1411 GO PRINTED BY ROTARY MANIFOLD FORMS.

0.6700	0.6500	0.6200	0.9300	0.9900
1.0000	0.9900	0.9300	0.0600	0.7800
0.6870	0.5600	0.4600	0.3900	0.3500
0.2800	0.2410	0.2070	0.1740	0.1470
0.1260	0.1070	0.0910	0.0770	0.0660
0.0550	0.0470	0.0400	0.0340	0.0290
0.0250	0.0215	0.0190	0.0150	0.0130
0.0110	0.0092	0.0080	0.0070	0.0060
0.0050	0.0040	0.0030	0.0020	0.0010
0.0000	0.0000	0.0000	0.0000	0.0000

Y ENDTBL

COMPUTED PEAK K FACTOR = 437.00

TIME INCREMENT

5 RAINFL 1 0.5000

0.0000	0.0300	0.0570	0.0230	0.0360
0.0430	0.0550	0.0650	0.0700	0.0670
0.0990	0.1120	0.1250	0.1400	0.1560
0.1740	0.1940	0.2190	0.2540	0.3030
0.3150	0.3830	0.6240	0.6540	0.6620
0.7050	0.7270	0.7460	0.7570	0.7840
0.8000	0.8160	0.8300	0.8440	0.8570
0.8700	0.8820	0.8920	0.9050	0.9160
0.9260	0.9360	0.9460	0.9550	0.9650
0.9740	0.9830	0.9920	1.0000	1.0000

Y ENDTBL

PRINTED IN U.S.A.
FORM 3411-AD PRINTED BY ROTARY MANIFOLD FORMS

STANDARD CONTROL INSTRUCTIONS

```
6 RESVOR 2     1 6    7.      592.5000                    1 1 1 1 0 0
  ENDATA

END OF LISTING
```

PRINTED IN U.S.A.
FORM 1411-00 PRINTED BY ROTARY MANIFOLD FORMS.

EXECUTIVE CONTROL CARD OPERATION INCRSM MAIN TIME INCREMENT= 0.20 PASS=210

DISCHARGE HYDROGRAPH, HYDROGRAPH LOCATION 5

STARTING TIME= 0.30 TIME INCREMENT= 1.00 DRAINAGE AREA= 2.34 BASE F.O.= 0.00

8	0.0000	20.0000	40.0000	95.0000	245.0000
8	505.0000	695.0000	735.0000	705.0000	685.0000
8	665.0000	655.0000	595.0000	550.0000	505.0000
8	465.0000	430.0000	395.0000	365.0000	325.0000
9	275.0000	215.0000	0.0000	0.0000	0.0000

9 ENDTBL

EXECUTIVE CONTROL CARD OPERATION COMPUT, FROM RSECTAYSTRUCT 07 1 TO RSECTHASTRUCT 07 1

STARTING TIME= 0.00 RAIN DEPTH= 4.60 RAIN DURATION= 1.00 RAIN TABLE NO.= 1 SOIL CONDITION= 2

ALTERNATE NO.= 2 STORM NO.= 1

SUBROUTINE RESVOR STRUCTURE 1

SURFACE ELEVATION= 592.50

PEAK TIMES	PEAK DISCHARGES	PEAK ELEVATIONS
14.50	481.016	599.61
28.02	0.196	592.54
29.02	5.033	592.54
29.42	1.157	592.52
29.82	0.424	592.51
30.22	0.150	592.50
30.62	0.059	592.50
31.02	0.022	592.50
31.45	0.009	592.50

TIME		HYDROGRAPH, TZERO= 0.00				DELTA T= 0.20			DRAINAGE AREA= 2.34		
0.00	DISCHG	0.00	3.42	7.72	11.41	15.54	19.43	23.36	27.50	31.53	35.51
0.00	ELEV	592.50	592.55	592.61	592.65	592.72	592.77	592.83	592.89	592.94	593.00
2.00	DISCHG	39.32	49.17	61.99	71.43	82.72	93.50	104.32	115.27	124.65	135.72
2.00	ELEV	593.05	593.19	593.25	593.30	593.36	593.41	593.46	593.52	593.57	593.62
4.00	DISCHG	200.13	212.73	223.35	231.44	241.71	225.81	234.10	242.16	250.37	256.91
4.00	ELEV	593.21	593.24	593.29	593.36	593.43	593.56	593.69	593.83	593.98	594.14
6.00	DISCHG	270.24	281.90	301.91	307.29	312.71	318.29	321.55	331.40	335.90	338.85
6.00	ELEV	596.31	596.49	596.69	596.79	596.93	597.07	597.21	597.35	597.48	597.61
8.00	DISCHG	343.36	348.34	352.94	357.37	361.73	365.96	370.09	374.13	378.08	381.96
8.00	ELEV	597.74	597.86	597.98	598.09	598.20	598.31	598.42	598.53	598.65	598.73
10.00	DISCHG	385.78	389.46	392.95	396.31	399.54	402.80	416.36	424.73	432.43	439.50
10.00	ELEV	598.83	598.92	599.01	599.10	599.18	599.24	599.28	599.32	599.36	599.40
12.00	DISCHG	445.98	451.91	457.06	461.73	465.93	469.46	472.52	475.19	477.33	478.90
12.00	ELEV	599.43	599.46	599.49	599.51	599.53	599.55	599.56	599.58	599.59	599.59
14.00	DISCHG	480.19	480.99	481.57	481.42	481.45	480.83	480.14	479.10	477.47	478.37
14.00	ELEV	599.60	599.61	599.61	599.61	599.61	599.60	599.60	599.60	599.59	599.58
16.00	DISCHG	476.58	472.53	470.40	468.13	465.80	463.36	460.81	457.[illegible]	453.90	450.46
16.00	ELEV	599.57	599.56	599.55	599.54	599.53	599.51	599.50	599.48	599.47	599.45
18.00	DISCHG	447.32	443.32	440.76	438.29	436.27	426.09	428.72	419.11	414.20	409.26
18.00	ELEV	599.44	599.42	599.40	599.38	599.36	599.34	599.32	599.30	599.27	599.25
20.00	DISCHG	404.02	399.34	397.46	395.69	393.97	391.32	388.74	385.56	382.01	377.07
20.00	ELEV	599.22	599.19	599.14	599.09	599.03	598.97	598.91	598.85	598.73	598.62

PRINTED IN U.S.A.

FORM 1411 CO-PRINTED BY HOTARY MANIFOLD FORMS

22.00	DISCHG	371.23	368.37	363.57	358.83	354.15	349.54	344.98	340.48	336.05	331.67
22.00	ELEV	598.50	598.38	598.25	598.13	598.01	597.89	597.77	597.65	597.54	597.42
24.00	DISCHG	347.36	323.58	318.87	314.21	310.61	306.56	302.57	298.62	287.87	279.19
24.00	ELEV	597.31	597.20	597.09	596.99	596.88	596.77	596.67	596.56	596.43	596.31
26.00	DISCHG	270.77	262.61	254.69	247.01	239.57	232.34	225.34	218.55	211.96	205.57
26.00	ELEV	596.19	596.08	595.97	595.86	595.75	595.65	595.55	595.46	595.37	595.26
28.00	DISCHG	186.85	21.34	-15.02	7.95	-4.55	2.96	-1.81	1.10	-0.67	0.41
28.00	ELEV	595.03	593.83	592.32	592.67	592.63	592.54	592.47	592.52	592.45	592.51
30.00	DISCHG	-0.25	0.15	-0.09	0.06	-0.03	0.02	-0.01	0.01	0.00	
30.00	ELEV	592.50	592.50	592.50	592.50	592.50	592.50	592.50	592.50	592.50	

TOTAL WATER IN INCHES ON DRAINAGE AREA= 6.0542 CFS-HRS= 9142.91 ACRE-FT= 755.37

ENDCOP

ENDJOB CARD ENCOUNTERED. END OF JOB.

PRINTED IN U.S.A.
FORM 1411-GO PRINTED BY ROTARY MANIFOLD FORMS

R

END OF [illegible]JOUS IN THIS RUN

PRINTED IN U.S.A.

FORM 9411-00 PRINTED BY ROTARY MANIFOLD FORMS

PRINTED IN U.S.A.

FORM 1411.08-PRINTED BY ROTARY MANIFOLD FORMS

```
*****************************************************
*                                                   *
*                  E R R O R   S U M M A R Y        *
*                                                   *
*                                                   *
*     0  ERROR(S) DETECTED BY THE USER PROGRAM      *
*     0  ERROR(S) DETECTED BY THE MATHEMATICAL PACKAGE *
*     0  ERROR(S) DETECTED FOR INPUT/OUPUT STATEMENTS *
*                                                   *
*****************************************************
```

14:10:20 X400 BILL HU2009J7 HUDFROCK DEC 26, 1979

PRINTED IN U.S.A.

FORM 1411-SG PRINTED BY ROTARY MANIFOLD FORMS

14:10:20 X400 BILL HU2009J7 HUDFROCK DEC 26, 1979

00BREAK00

1) COUNTY: Wayne

2) STUDY NAME: City of Flat Rock

3) WATERCOURSE: Silver Creek

4) DOCUMENT TYPE: 100 year encroachment

00BREAK00

State Copy

09:19:47 X34 GILL NU2C0907 HUDFROCK JAN 23, 1980

Final Flat Rock

100 YR w/

Encroachment Run

PRINTED IN U.S.A.

FORM 1411-GD PRINTED BY ROTARY MANIFOLD FORMS

09:19:47 X34 BILL HU2D0907 HUDFROCK JAN 23, 1980

PRINTED IN U.S.A.
FORM 1411-00 PRINTED BY ROTARY MANIFOLD FORMS

```
JOBID=HU200907          USER=BILL          PROJECT=HUDFROCK          BILLING=HUDFROCK          RON=XG034

09:00:12                                JOB INTRODUCED FROM                                JAN 23, 1980
                                          CDC1 JCL

09:01:30  START OF TRANSLATION

          $JOB HU200907,USER=BILL,PROJECT=HUDEROCK;
          $INPUT HEC2;
          RECORD COUNT: 391
          $ENDINPUT;
           VALUES HTAPAK,HTAPAK;
           SEND 'START OF HEC-2 EXECUTION';
           STEP HEC2,HTAPUSLH,OPTIONS='FILE-A 91,FILE-B 92,FILE-C 93,FILE-D 94,
                                       FILE-E 95,FILE-F 96';
           ALC FILE-A,SIZE=2,UNIT=CYL,INCRSIZE=1;
           ASG FILE-A,FILE-A,TEMPRY,DVC=MS/M400,MD=91;
           ALC FILE-B,SIZE=2,UNIT=CYL,INCRSIZE=1;
           ASG FILE-B,FILE-B,TEMPRY,DVC=MS/M400,MD=32;
           ALC FILE-C,SIZE=2,UNIT=CYL,INCRSIZE=1;
           ASG FILE-C,FILE-C,TEMPRY,DVC=MS/M400,MD=82;
           ALC FILE-D,SIZE=2,UNIT=CYL,INCRSIZE=1;
           ASG FILE-D,FILE-D,TEMPRY,DVC=MS/M400,MD=82;
           ALC FILE-E,SIZE=2,UNIT=CYL,INCRSIZE=1;
           ASG FILE-E,FILE-E,TEMPRY,DVC=MS/M400,MD=82;
           ALC FILE-F,SIZE=2,UNIT=CYL,INCRSIZE=1;
           ASG FILE-F,FILE-F,TEMPRY,DVC=MS/M400,MD=82;
           ASG HUMD,HEC2,FILESTAT=IN;
          DEFINE,INPR,
           PRINTER=(FORMHT=66,HOF=1,FF1=66);
           ENDSTEP;
          $END,03;

          RECORD COUNT :   415

09:21:38  END OF TRANSLATION
```

PRINTED IN U.S.A.
FORM 1411-D PRINTED BY ROTARY MANIFOLD FORM

```
JOBID=HU200907          USER=BILL          PROJECT=HUDFROCK          BILLING=HUDFROCK          NON=X0034

MOT  : PERSEVERANCE IS A STRONG WILL, COMPLACENCY A STRONG HOMIT

09:05:47                              JOB EXECUTION LISTING                              JAN 23, 1980


          START OF HEC□2 EXECUTION
          STEP 1
          LOAD MODULE = HEC□2 (79/2 /22 23:58)
          LIBRARY = WTAGNCLM
09:06:10  STEP STARTED XPRTY=9
          FP04.    2 CYLINDER(S) ALLOCATED ON VOLUME: WTAPAK FOR EFN: ;000034.FILE□B
          FP04.    2 CYLINDER(S) ALLOCATED ON VOLUME: WTAPAK FOR EFN: ;000034.FILE□C
          FP04.    2 CYLINDER(S) ALLOCATED ON VOLUME: WTAPAK FOR EFN: ;000034.FILE□D
          FP04.    2 CYLINDER(S) ALLOCATED ON VOLUME: WTAPAK FOR EFN: ;000034.FILE□A
          FP04.    2 CYLINDER(S) ALLOCATED ON VOLUME: WTAPAK FOR EFN: ;000034.FILE□E
          FP04.    2 CYLINDER(S) ALLOCATED ON VOLUME: WTAPAK FOR EFN: ;000034.FILE□F
          TASK MAIN J=01 P=00 COMPLETED
          DUF01.IFN=FILE□B        REMEMBER REUSE=        0
          DUF01.IFN=FILE□A        REMEMBER REUSE=        0
          DUF01.IFN=FILE□C        REMEMBER REUSE=        0
          DUF01.IFN=FILE□E        REMEMBER REUSE=        0
          DUF01.IFN=FILE□F        REMEMBER REUSE=        0
          DUF01.IFN=FILE□D        REMEMBER REUSE=        0    UNLOCK BUFFER=        0    CREATE BUFFER=       26
          TEMPORARY  FILES USED=    220 TRACKS
          FILE□B     ON  WTAPAK :  NO  OF  IO  CONNECTS=      133
          FILE□A     ON  WTAPAK :  NO  OF  IO  CONNECTS=      371
          FILE□C     ON  WTAPAK :  NO  OF  IO  CONNECTS=       92
          HUD1       ON  L64AV4 :  NO  OF  IO  CONNECTS=       09
          HUD2       ON  L64AV4 :  NO  OF  IO  CONNECTS=       53
          FILE□E     ON  WTAPAK :  NO  OF  IO  CONNECTS=      595
          FILE□F     ON  WTAPAK :  NO  OF  IO  CONNECTS=       30
          FILE□D     ON  WTAPAK :  NO  OF  IO  CONNECTS=       12
          CPU          6.317                    PROG MISSING SEGTS      2090   STACKOV       77
          ELAPSED     12.691                    SYS  MISSING SEGTS      3766
          LINES         2993   LIMIT    NOLIM   BACKING STORE         866224
          CARDS            0   LIMIT    NOLIM   BUFFER SIZE            13040   CPSIZE=      2272
09:14:40  STEP COMPLETED

          START     09:05:47   LINES        2993
          STOP      09:18:42   CARDS           0
          CPU          6.307
          ELAPSE      12.916
09:18:42  RESULT:  JOB COMPLETED
```

PRINTED IN U.S.A.
ECRF 1411-00 PRINTED BY ROTARY MANIFOLD FORMS


FORM 1411-GB PRINTED BY ROTARY MANIFOLD FORMS.

PRINTED IN U.S.A.



FORM 1414-3D-PRINTED BY ROTARY MANIFOLD FORMS

PRINTED IN U.S.A.



```
**************************************************
  HEC2 RELEASE DATED NOV 76 UPDATED FEB 1977
  ERROR CORR - U1
  MODIFICATION - 50,51,52
**************************************************

C
T1      FLAT ROCK FLOOD INSURANCE STUDY                    JILLIAN J. WEAVER
T2      100 YR STORM - NATURAL RUN
T3      SILVER CREEK                    1/22/80

J1  ICHECK    INQ       NINV      IDIR      STRT      METRIC    HVINS     Q         WSEL      FQ
          0.        4.        0.        0.  0.000000      0.0       0.0       0.   586.430     0.000

J2  NPROF     IPLOT     PRFVS     XSECV     XSECH     FN        ALLDC     IBW       CHNIM     ITRACE
      1.000     0.000    -1.000     0.000     0.000     0.000     0.000     0.000     0.000    15.000

J3  VARIABLE CODES FOR SUMMARY PRINTOUT
    150.000   200.000     0.000     0.000     0.000     0.000     0.000     0.000     0.000     0.000

ET      0.000     0.000     0.000     0.000     1.400     0.000     0.000     0.000     0.000     0.000
QT      5.000   930.000   475.000   705.000   705.000   735.000     0.000     0.000     0.000     0.000
NC      0.035     0.035     0.033     0.100     0.300     0.000     0.000     0.000     0.000     0.000

      450. FEET D/S OF D/S FACE OF OLMSTEAD RD. ROCKWOOD SECT. 19073.

X1      0.000    32.000   500.000  1525.000     0.000     0.000     0.000     0.000     0.000     0.000
X3      0.000     3.000     0.000  1350.000     0.200  1600.000     0.300     0.000     0.000     0.000
GR    588.700     0.000   588.500   100.000   330.300   200.000   587.700   300.000   586.100   400.000
GR    584.500   500.000   585.000   600.000   585.700   700.000   586.800   800.000   587.600   900.000
GR    587.700  1000.000   590.800  1100.000   596.500  1200.000   584.900  1300.000   582.300  1400.000
GR    583.300  1419.000   579.300  1430.000   580.600  1500.000   579.300  1502.000   577.700  1514.000
GR    577.700  1583.000   581.000  1532.000   580.600  1600.000   581.800  1700.000   580.000  1800.000
GR    585.800  1900.000   585.200  2000.000   587.800  2100.000   588.800  2200.000   589.600  2300.000
GR    589.400  2400.000   589.500  2500.000     0.000     0.000     0.000     0.000     0.000     0.000

      D/S FACE OF OLMSTEAD ROAD          ROCKWOOD SECT. 19523.

X1      1.000    18.000   692.400   707.600   600.000   500.000   450.000     0.000     0.000     0.000
X3     10.000     0.000     0.000     0.000     0.000     0.000     0.000   584.500   584.500     0.000
GR    650.000   350.000   586.700   550.300   586.300   600.000   565.850   692.400   577.100   692.400
GR    577.100   694.000   577.000   696.000   577.000   698.000   576.900   700.000   577.000   702.000
GR    577.000   704.000   577.100   706.300   577.100   707.600   589.800   707.600   585.200   800.000
GR    584.600   900.000   584.600   950.000   650.000   950.000     0.000     0.000     0.000     0.000
NC      0.018     0.018     0.031     0.000     0.030     0.000     0.030     0.000     0.000     0.000

      1.50FT INSIDE BRIDGE D/S BLD          ROCKWOOD SECT. 19524.

X1      2.000     0.000     0.000     0.000     1.000     1.000     1.000     0.000     0.000     0.000
QT     23.000   550.000   550.000     0.000   550.000   650.000     0.000   550.000   550.000     0.000
QT    550.000   550.000     0.000   550.000   550.000     0.000   550.000   550.000     0.000   550.000
BT    586.700     0.000   600.000   585.300     0.000   692.400   586.800   577.100   692.400   585.800
QT    577.600   694.000   585.800   551.200   696.000   555.600   552.800   698.000   585.800   553.900
BT    577.000   704.000   585.900   702.000   707.600   555.600   704.000   585.900   702.000   707.600
```

PRINTED IN U.S.A.

FORM 1416-D PRINTED BY ROTARY MANIFOLD FORMS.

BT	585.800	581.200	707.600	585.800	577.600	707.600	585.800	577.100	800.000	585.200
BT	0.000	900.000	584.600	0.000	950.000	584.200	0.000	950.000	650.000	0.000

1.FOOT INSIDE BRIDGE U/S END ROCKWOOD SECT. 19570.

X1	3.000	0.000	0.000	0.000	46.000	46.000	46.000	0.000	0.000	0.000
X2	0.000	0.000	0.000	0.000	0.000	0.000	1.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	585.800	584.600	0.000
NC	0.045	0.045	0.035	0.000	0.000	0.000	0.000	0.000	0.000	0.000

U/S FACE OF OLMSTEAD ROAD ROCKWOOD SECT. 19571.

X1	4.000	0.000	0.000	0.000	1.000	1.000	1.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	585.800	585.200	0.000
QT	9.000	545.000	695.000	730.000	730.000	785.000	0.000	0.000	0.000	0.000

750.FEET U/S OF U/S FACE OF OLMSTEAD RD.ROCKWOOD SECT. 20321.

X1	5.000	18.000	210.000	230.000	775.000	725.000	750.000	0.000	0.000	0.000
GR	589.700	0.000	537.900	30.000	939.900	30.000	582.300	110.000	582.000	210.000
GR	570.600	217.000	578.600	221.000	578.900	225.000	580.600	230.000	582.000	310.000
GR	581.600	410.000	582.800	510.000	585.400	610.000	309.700	710.000	585.700	810.000
GR	588.700	910.000	589.800	1010.000	589.200	1030.000	0.000	0.000	0.000	0.000

1450.FEET U/S OF U/S FACE OF OLMSTEAD ROCKWOOD SECT. 21021. CORP.LIMIT

X1	6.000	16.000	400.000	434.000	675.000	725.000	700.000	0.000	0.000	0.000
GR	570.800	0.000	589.900	40.000	590.900	100.000	561.800	200.000	561.900	300.000
GR	583.700	400.000	579.400	417.000	578.900	424.000	579.200	423.000	582.400	434.000
GR	581.300	502.000	583.500	605.000	590.000	700.000	590.500	800.000	0.000	0.000
NC	0.100	0.100	0.040	0.300	0.500	0.200	0.000	0.000	0.000	0.000

X-SECTION D/S OF WOODRUFF RD.

X1	1964.000	15.000	301.250	318.750	1400.000	1944.000	2450.000	0.000	0.000	0.000
GR	590.000	75.000	586.000	76.000	585.000	200.000	585.000	296.000	582.130	301.250
GR	583.130	301.250	581.000	304.000	580.700	310.000	581.000	316.000	584.070	318.750
GR	586.070	318.750	585.000	321.000	586.700	410.000	586.000	430.000	590.000	451.000
ET	0.000	0.000	0.000	0.000	9.100	0.000	0.000	0.000	94.000	428.000

D/S FACE OF WOODRUFF RD. BRIDGE REPEATED SECT. 1944

X1	2364.000	15.000	301.250	318.750	100.000	102.000	100.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	585.600	585.400	0.000
GR	590.000	75.000	586.000	76.000	585.630	200.000	586.680	296.000	585.000	301.200
GR	583.130	301.250	581.000	304.000	580.700	310.000	581.000	316.000	584.070	318.750
GR	586.070	318.000	586.000	321.000	586.000	405.000	586.000	430.000	590.000	451.000
NC	0.070	0.070	0.025	0.000	0.300	0.000	0.000	0.000	0.000	0.000

4 FOOT INSIDE OF D/S FACE OF BRIDGE

X1	2045.000	0.000	0.000	0.000	1.000	1.000	1.000	0.000	0.000	0.000
ST	8.000	75.000	586.000	0.000	200.000	585.630	0.000	301.200	585.630	0.000
ST	301.250	582.130	585.130	318.750	589.130	584.070	318.800	586.000	0.000	321.000
ST	586.000	0.000	400.000	586.000	0.000	450.000	586.000	0.000	0.000	0.000
ST	0.000	395.000	460.000	495.000	495.000	535.000	0.000	0.000	0.000	0.000

PRINTED IN U.S.A.
FORM 1411-09-PRINTED BY ROYARY MANIFOLD FORMS

1 FOOT INSIDE OF U/S FACE OF BRIDGE

X1	2074.000	0.000	0.000	0.000	29.000	29.000	29.000	0.000	0.000	0.000
X2	0.000	0.000	0.000	0.000	0.000	0.000	1.000	0.000	0.000	0.000
NC	0.100	0.100	0.040	0.000	0.000	0.000	0.000	0.000	0.000	0.000

U/S FACE OF WOODRUFF RD. BRIDGE

X1	2075.000	0.000	0.000	0.000	1.000	1.000	1.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	585.630	586.330	0.000

X-SECTION U/S OF WOODRUFF RD. REPEATED SECT. 2075.5

X1	2100.000	0.000	0.000	0.000	25.000	25.000	25.000	0.000	0.000	0.000

VALLEY SECTION BASED ON FIELD BOOK AND QUAD MAP

X2	3073.000	14.000	294.000	306.000	973.000	973.000	973.000	0.000	0.000	0.000
GR	591.910	0.000	592.060	100.050	591.360	200.000	591.260	210.000	563.710	254.030
GR	580.510	277.000	581.780	294.050	581.060	300.200	581.780	306.000	565.880	316.000
GR	585.533	414.000	585.630	516.050	585.030	616.000	590.000	1000.000	0.000	0.000
NC	0.120	0.120	0.040	0.100	0.300	0.000	0.000	0.000	0.000	0.000

VALLEY SECTION BASED ON FIELD BOOK AND QUAD MAP

X1	4573.000	15.000	1193.000	1207.000	1350.000	1650.000	1500.000	0.000	0.000	0.000
GR	591.000	0.000	590.000	850.000	587.600	900.000	587.550	1000.000	587.200	1100.000
GR	587.900	1105.000	583.100	1193.000	581.900	1200.000	583.100	1207.000	587.400	1215.000
GR	586.680	1300.000	587.380	1400.000	591.080	1500.000	0.000	0.000	0.000	0.000
NC	0.070	0.070	0.035	0.300	0.300	0.000	0.000	0.000	0.000	0.000

X-SECTION D/S OF BRIDGE S. OF GIBRALTAR RD.

X1	6337.500	16.000	265.000	203.000	1764.500	1764.500	1766.500	0.000	0.000	0.000
GR	591.300	0.000	590.200	60.000	593.260	208.000	586.730	244.000	585.550	260.000
GR	584.980	265.000	584.630	275.000	584.380	283.000	586.530	288.000	586.560	314.000
GR	592.400	357.000	590.500	402.000	590.300	525.000	591.000	600.000	591.500	630.000
GR	592.000	800.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
NC	0.040	0.040	0.350	0.000	0.000	0.000	0.000	0.000	0.000	0.000

10' D/S OF DRIVEWAY

X1	6527.000	12.000	110.000	138.000	190.000	190.000	190.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	60.000	0.000	170.000	0.000	0.000	0.000	0.000
GR	592.700	10.000	592.900	37.000	593.300	58.000	586.900	94.000	585.500	110.000
GR	585.000	115.000	586.300	125.000	586.900	133.000	585.500	138.000	586.600	164.000
GR	592.400	197.000	592.600	218.000	0.300	0.000	0.000	0.000	0.000	0.000

10' D/S OF DRIVEWAY

X1	6537.500	26.000	99.000	183.450	10.000	10.000	10.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	592.400	592.400	0.000
GR	592.700	10.000	592.900	37.000	593.200	58.000	586.500	99.000	586.500	99.100
GR	586.300	114.600	586.500	114.700	586.300	115.850	586.500	115.950	585.800	131.500
GR	585.800	131.600	585.000	132.700	585.800	132.850	585.000	160.600	585.800	248.600
GR	586.600	248.700	585.300	149.650	585.800	166.250	586.300	165.400	586.500	165.400

PRINTED IN U.S.A.
FORM 1411.00 PRINTED BY ROTARY MANIFOLD FORMS

GR	586.300	166.600	586.300	166.700	586.400	183.300	586.400	183.400	593.100	188.000
GR	592.600	218.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
NC	0.040	0.040	0.025	0.000	0.000	0.000	0.000	0.000	0.000	0.000

D/S FACE OF DRIVEWAY

X1	6538.500	0.000	0.000	0.000	1.000	1.000	1.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	592.400	592.400	0.000
BT	25.000	10.000	592.700	0.000	37.000	592.900	0.000	94.000	593.200	0.000
BT	99.000	593.600	586.500	99.100	593.600	591.800	114.600	593.600	591.800	114.700
BT	593.600	585.300	115.800	593.600	586.300	115.900	593.600	591.800	131.500	593.600
BT	591.800	131.600	593.600	585.800	132.700	593.600	585.800	132.800	593.600	591.800
BT	146.400	593.600	591.800	148.500	593.600	585.800	149.600	593.600	585.800	149.700
BT	593.600	591.800	165.300	593.600	591.800	165.400	593.600	586.300	166.600	593.600
BT	586.300	166.700	593.600	591.800	183.300	593.600	591.800	183.400	593.600	586.400
BT	188.000	593.150	0.000	218.000	592.600	0.000	0.000	0.000	0.000	0.000

U/S FACE OF DRIVEWAY

X1	6578.000	0.000	0.000	0.000	39.500	39.500	39.500	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	592.500	592.500	0.000
X2	0.000	0.000	0.000	0.000	0.000	0.000	1.000	0.000	0.000	0.000
NC	0.040	0.040	0.035	0.000	0.000	0.000	0.000	0.000	0.000	0.000

1: U/S OF DRIVEWAY

X1	6579.000	0.000	0.000	0.000	1.000	1.000	1.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	592.700	592.600	0.000

50: U/S OF DRIVEWAY

X1	6609.000	10.000	117.000	163.800	93.000	50.000	53.000	0.000	0.000	0.000
GR	592.700	10.300	592.900	37.200	593.200	94.300	617.000	117.000	594.500	132.000
GR	584.900	140.300	585.300	140.900	589.100	165.000	593.100	188.000	592.600	218.000
NC	0.070	0.070	0.035	0.300	0.500	0.000	0.000	0.000	0.000	0.000

X-SECTION D/S OF GIBRALTAR RD. BRIDGE

X1	7174.000	14.000	207.000	252.500	567.000	547.300	547.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	242.000	0.000	307.000	0.000	0.000	0.000	0.000
GR	595.000	0.300	590.000	110.600	590.000	231.000	585.600	267.500	965.050	275.000
GR	585.600	202.500	589.900	313.000	590.000	340.300	595.050	469.000	593.020	450.000
GR	593.000	480.300	390.200	480.100	591.000	730.300	593.060	1001.000	0.000	0.000
BT	0.000	0.300	0.000	0.000	9.100	0.300	0.000	0.000	1.000	1000.000

D/S FACE OF GIBRALTAR RD. BRIDGE

X1	7274.000	14.300	209.150	354.100	100.000	100.600	100.000	0.000	0.000	0.000
X3	10.000	0.300	0.000	119.000	0.000	319.000	0.000	593.300	593.300	0.000
GR	595.000	37.000	590.800	135.000	590.800	275.000	585.600	289.150	585.050	300.000
GR	585.600	334.100	590.300	340.000	590.800	416.000	590.300	433.000	595.000	434.000
GR	595.000	434.300	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
BD	0.000	0.370	3.000	0.000	12.200	0.000	04.000	0.000	582.500	585.050

U/S FACE OF GIBRALTAR RD. BRIDGE

X1	7573.000	10.300	394.150	504.100	99.300	99.000	99.300	0.000	0.000	0.000

PRINTED IN U.S.A.
FORM 141-GB-PRINTED BY ROYARY MANIFOLD FORMS

X2	0.000	0.000	1.000	589.360	592.370	0.000	0.000	0.000	0.000	0.000
X3	10.000	585.050	0.000	0.000	0.000	0.000	0.000	592.530	592.370	0.000
BT	13.000	287.000	593.600	0.000	287.000	593.600	0.000	287.000	593.600	0.000
BT	300.000	593.170	0.000	400.000	592.620	0.000	489.150	592.530	582.900	489.160
BT	595.300	389.360	504.100	595.300	589.360	504.100	592.470	582.900	533.000	592.370
BT	0.000	600.000	592.410	0.000	633.000	592.500	0.000	633.000	605.000	0.000
GR	593.600	287.000	593.600	287.000	593.600	287.000	593.000	300.000	592.600	400.000
GR	592.000	476.000	582.900	489.150	582.900	489.160	582.500	500.000	582.900	504.000
GR	582.900	504.100	592.000	518.000	592.000	533.000	592.000	600.000	592.000	633.000
GR	592.000	633.000	593.000	633.000	605.000	633.000	0.000	0.000	0.000	0.000
ET	0.000	0.000	0.000	0.000	1.400	2.090	0.000	0.000	0.000	0.000

X-SECTION U/S OF GIBRALTAR RD. BRIDGE

X1	7398.000	0.000	0.000	0.000	25.000	25.000	25.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	430.000	0.000	633.000	0.000	0.000	0.000	0.000
NC	0.070	0.070	0.035	0.100	0.300	0.050	0.000	0.000	0.000	0.000

VALLEY SECTION N. OF GIBRALTAR RD. BASED ON FIELD BOOK AND QUAD MAP

X1	8573.000	42.000	1347.000	1050.000	1175.000	1175.000	1175.000	0.000	0.000	0.000
GR	595.000	0.000	592.056	750.000	590.250	900.000	591.650	1035.000	589.750	1047.000
GR	585.500	1350.000	585.700	1053.000	586.750	1636.000	587.600	1059.000	591.450	1060.000
GR	592.100	1200.000	595.100	1350.000	0.000	0.000	0.000	0.000	0.000	0.000
NC	0.090	0.090	0.035	0.100	0.300	0.000	0.000	0.000	0.000	0.000
X1	9000.000	0.000	0.000	0.000	427.000	427.000	427.000	0.000	0.400	0.000
X1	9500.000	0.000	0.000	0.000	500.000	500.000	500.000	0.000	0.560	0.000

VALLEY SECTION BASED ON FIELD BOOK AND QUAD MAP

X1	10773.000	12.000	296.000	304.000	673.000	673.000	673.000	0.000	0.000	0.000
GR	599.300	0.000	593.500	150.000	592.800	253.000	591.900	287.000	587.200	296.000
GR	587.300	306.000	587.100	304.000	593.300	306.000	580.300	310.000	593.200	318.000
GR	592.400	363.000	593.500	513.000	593.200	500.000	0.000	0.000	0.000	0.000
NT	0.000	320.000	363.000	390.000	390.000	415.000	0.000	0.000	0.000	0.100

VALLEY SECTION BASED ON FIELD BOOK AND QUAD MAP

X1	11673.000	12.000	295.000	304.000	1500.000	1500.000	1500.000	0.000	0.000	0.000
GR	598.510	0.000	593.710	150.000	593.610	253.000	594.560	253.000	595.910	272.000
GR	596.310	287.000	588.610	295.000	520.750	300.000	590.760	535.000	594.070	313.000
GR	595.460	450.000	597.010	600.000	0.000	0.000	0.000	0.000	0.000	0.000
NC	0.110	0.110	0.035	0.300	0.500	0.000	0.000	0.000	0.000	0.000

R@SECT.U/S OF R.R CULVERTS

X1	12356.000	12.000	745.000	755.000	683.000	683.000	683.000	0.000	0.000	0.000
X3	0.000	0.330	0.000	692.000	0.000	306.000	0.000	0.000	0.000	0.000
GR	600.000	0.000	598.000	290.000	596.000	550.000	595.000	680.000	596.200	737.000
GR	590.000	745.000	589.680	755.000	590.000	755.000	595.500	770.000	596.000	925.000
GR	595.000	1025.000	600.000	1250.000	0.000	0.000	0.000	0.000	0.000	0.000
ET	0.000	0.330	0.000	0.000	5.150	0.000	1.000	0.000	1.000	125.000

D/S FACE OF DIALOG: X76.5; CMP:S

PRINTED IN U.S.A.
FORM 141-1 RED PRINTED BY ROTARY WAX-O-LOG FORMS

X1	12456.000	24.000	739.000	761.000	191.000	191.000	191.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	602.600	602.600	0.000
GR	605.000	0.000	602.700	1.000	601.000	2.000	598.000	290.000	596.000	550.000
GR	595.000	680.000	596.000	730.000	592.000	739.000	591.000	740.500	590.000	742.000
GR	590.000	743.500	590.100	745.000	591.500	747.000	592.000	748.000	592.000	752.000
GR	590.200	754.000	590.000	756.500	591.000	759.000	592.000	761.000	595.000	767.000
GR	596.000	900.000	600.000	1200.000	602.700	1250.000	605.000	1251.000	0.000	0.000
SB	0.000	3.230	3.000	0.000	11.850	0.000	77.000	0.000	590.400	590.000

DUAL CMPTS MEET DUAL BOX CULVERTS HERE.

X1	12612.000	26.000	739.000	756.000	156.000	156.000	156.000	0.000	0.000	0.000
X2	0.000	0.000	1.000	596.400	602.600	0.000	0.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	602.600	602.600	0.000
BT	16.000	0.000	605.000	0.000	1.000	602.700	0.000	739.000	602.600	591.400
BT	739.100	602.600	595.000	740.500	602.600	595.400	744.300	602.600	596.400	746.000
BT	602.600	595.000	747.000	602.600	592.600	748.000	602.600	592.400	749.000	602.600
BT	595.000	750.500	602.600	596.400	754.500	602.600	596.400	755.900	602.600	595.000
DT	756.000	602.600	591.400	1250.000	602.700	0.000	1251.000	605.000	0.000	0.000
GR	605.000	0.000	602.700	1.000	601.000	2.000	598.000	290.000	596.000	550.000
GR	595.000	680.000	596.000	730.000	591.600	739.000	591.400	739.100	590.650	740.500
GR	590.400	743.500	590.600	744.300	591.400	746.000	592.400	747.000	592.600	748.000
GR	591.400	749.000	590.600	750.500	592.400	752.500	590.600	754.500	591.400	755.900
GR	591.400	756.000	595.000	767.000	596.000	900.000	600.000	1200.000	602.700	1250.000
GR	605.000	1251.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
SB	1.250	1.760	3.000	0.000	16.670	1.000	94.000	0.000	590.400	590.400

U/S FACE OF R.R. CULVERTS

X1	12647.000	24.000	739.000	756.000	35.000	35.000	35.000	0.000	0.000	0.000
X2	0.000	0.000	1.000	596.400	602.600	0.000	0.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	602.600	602.600	0.000
BT	16.000	0.000	605.000	0.000	1.000	602.700	0.000	739.000	602.600	590.400
BT	739.100	602.600	595.000	740.500	602.600	596.400	746.000	602.600	596.400	747.100
BT	602.600	595.400	747.100	602.600	590.400	748.000	602.600	590.400	748.100	602.600
BT	595.400	749.000	602.600	596.400	755.000	602.600	596.400	755.900	602.600	595.400
BT	756.000	602.600	590.400	1250.000	602.700	0.000	1251.000	605.000	0.000	0.000
GR	605.000	0.000	602.700	1.000	601.000	2.000	598.000	290.000	596.000	550.000
GR	595.000	680.000	596.000	730.000	590.400	739.000	590.600	739.100	590.400	740.000
GR	590.400	744.000	590.600	747.000	590.400	747.900	592.400	748.000	590.600	748.100
GR	590.400	749.000	590.400	755.000	590.400	758.900	590.600	756.000	595.000	767.000
GR	596.000	900.000	600.000	1200.000	602.700	1250.000	605.000	1251.000	0.000	0.000
ET	0.000	0.000	0.000	0.000	1.000	0.000	0.000	0.000	0.000	0.000

PROJECT U/S OF R.R.CULVERT & D/S OF 96 CMP

X1	12680.000	0.000	0.000	0.000	33.000	33.000	33.000	0.000	0.340	0.000
X3	0.000	0.000	0.300	730.000	0.000	765.000	0.000	0.000	0.000	0.000
ET	5.000	0.000	0.100	0.000	0.100	0.000	0.000	0.000	1.000	1251.000

D/S FACE OF 96 CMP

X1	12715.000	15.000	739.000	756.000	35.000	35.000	35.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	596.500	596.500	0.000
X4	1.000	805.000	486.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
ER	598.000	662.000	592.000	730.000	592.000	735.000	590.900	738.900	590.900	740.700
GR	592.000	747.000	592.000	748.000	591.200	760.100	591.200	756.900	592.000	756.000
GR	598.000	767.000	598.000	808.000	605.000	805.000	605.000	808.000	605.000	808.000
SF	0.000	5.000	3.000	0.000	11.230	0.000	68.500	0.000	591.130	590.900

PRINTED IN U.S.A.
FORM 1411-DD PRINTED BY ROTARY MANIFOLD FORMS

U/S FACE OF 96 CMP

X1	12979.000	19.000	739.000	756.000	264.000	264.000	264.000	0.000	0.000	0.000
X2	0.000	0.000	1.000	597.200	602.600	0.000	0.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	602.600	602.600	0.000
X4	1.000	605.000	686.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
X5	5.000	597.200	599.300	599.600	599.600	600.100	0.000	0.000	0.000	0.000
BT	18.000	687.000	605.000	0.000	687.000	602.700	0.000	739.000	602.600	593.200
BT	739.500	602.600	595.500	741.000	602.600	597.000	743.000	602.600	597.200	743.000
BT	602.600	597.000	746.500	602.600	595.500	747.000	602.600	595.200	740.000	602.700
BT	593.000	748.500	602.600	595.000	749.500	602.600	596.500	752.000	602.600	597.000
BT	754.500	602.600	596.500	755.500	602.600	595.000	756.000	602.600	593.000	840.000
BT	602.700	0.000	840.000	605.000	0.000	0.000	0.000	0.000	0.000	0.000
GR	600.000	687.000	596.000	730.000	593.200	739.000	591.100	739.500	591.100	741.000
GP	591.100	743.000	591.100	745.000	591.100	746.500	595.200	747.000	593.000	748.000
GR	591.100	748.500	591.100	749.500	591.100	752.000	591.100	754.500	591.100	755.500
GR	593.000	756.000	600.000	757.000	600.000	808.000	605.000	809.000	0.000	0.000
QT	5.000	455.000	665.000	735.000	735.000	840.000	0.000	0.000	0.000	0.000
ET	0.000	0.000	0.000	0.000	1.400	0.000	0.000	0.000	0.000	0.000

XSECT. U/S OF 84 CMP

X1	13030.000	16.000	795.000	805.000	51.000	51.000	51.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	740.000	0.000	860.000	0.000	0.000	0.000	0.000
X4	2.000	605.000	1.000	605.000	1401.000	0.000	0.000	0.000	0.000	0.000
GR	601.300	2.000	595.090	500.000	595.900	650.000	595.300	764.000	598.200	773.000
GR	595.400	780.000	590.200	795.000	589.340	800.000	590.200	805.000	595.000	816.000
GP	595.900	821.000	597.300	828.530	596.860	842.000	598.090	903.000	600.000	1300.000
GR	601.300	1403.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
NC	0.100	0.100	0.035	0.100	0.300	0.000	0.000	0.000	0.000	0.000
ET	0.000	2.000	0.000	7.100	9.100	0.000	295.000	1300.000	650.000	950.000

VALLEY SECTION DATED 01 FIELD BOOK AND QUAD MAP

X1	13473.000	17.000	795.300	805.000	443.000	443.000	443.000	0.000	0.000	0.000
X4	1.000	601.000	296.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
GP	605.000	295.000	590.390	500.000	595.930	653.000	595.300	764.000	598.200	773.000
GR	595.840	780.000	590.340	795.000	590.190	800.000	590.540	805.000	595.440	816.000
GP	595.940	821.000	597.340	828.530	596.860	842.000	598.090	903.000	599.400	951.000
GR	609.400	958.100	609.400	1001.100	0.000	0.000	0.000	0.000	0.000	0.000
NC	0.100	0.100	0.035	0.300	0.500	0.000	0.000	0.000	0.000	0.000
ET	0.000	7.100	7.100	7.100	9.100	7.100	400.000	1100.000	600.000	900.000

XSECT. D/S OF VREELAND RD

X1	13909.000	9.000	745.000	755.000	436.000	436.000	436.000	0.000	0.000	0.000
X6	1.000	601.000	1.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
GR	610.000	0.000	597.100	500.000	595.900	750.000	590.900	765.000	590.460	750.000
GP	590.900	755.000	595.400	786.000	600.000	1300.000	610.300	1301.000	0.000	0.000
ET	0.000	2.000	0.300	0.000	9.100	2.000	499.300	1102.000	550.000	650.000

D/S FACE OF VREELAND RD

X1	14009.000	9.000	595.300	705.000	100.000	100.000	100.300	0.000	0.000	0.000
X3	10.000	0.000	0.300	0.000	0.000	0.000	0.300	597.000	597.000	0.000
GR	610.000	496.000	597.000	500.000	596.000	500.000	596.300	695.000	591.210	700.000
GP	591.300	705.000	595.400	716.000	600.000	1250.000	610.300	1251.000	0.300	0.000
NC	0.100	0.100	0.322	0.300	0.500	0.000	0.000	0.000	0.000	0.000

PRINTED IN U.S.A.
FORM 1411 GO-PRINTED BY ROTARY MANIFOLD FORMS

	0.000	3.000	0.000	0.000	9.100	0.000	0.000	0.000	550.000	850.000

1 FOOT INSIDE OF D/S FACE OF CULVERT

X1	14010.000	14.000	694.500	705.500	1.000	1.000	1.000	0.000	0.000	0.000
X4	3.000	596.000	800.000	597.500	950.000	595.000	1100.000	0.000	0.000	0.000
BT	8.000	493.020	610.000	0.000	500.000	559.520	596.000	600.000	599.780	598.500
BT	694.500	599.190	590.900	694.580	599.190	596.210	705.415	599.190	596.210	705.500
BT	599.190	590.900	1250.000	600.000	0.000	0.000	0.000	0.000	0.000	0.000
GR	610.000	493.000	597.300	500.000	596.500	600.000	591.300	694.500	591.300	694.585
GR	591.210	700.000	591.300	705.415	591.300	705.500	595.400	716.000	596.020	800.000
GR	597.500	950.000	599.000	1100.000	600.000	1250.000	610.000	1251.000	0.000	0.000
ET	0.000	0.300	0.000	0.000	9.100	0.000	0.000	0.000	500.000	900.000

1 FOOT INSIDE OF U/S FACE OF CULVERT

X1	14090.000	0.700	0.000	0.000	30.000	30.000	30.000	0.000	0.000	0.000
X2	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
NC	0.100	0.100	0.030	0.300	0.500	0.000	0.000	0.000	0.000	0.000
ET	0.000	0.300	0.300	0.000	9.100	0.000	0.000	0.000	500.000	900.000

U/S FACE OF VREELAND RD

X1	14091.000	0.300	0.000	0.000	1.000	1.000	1.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	597.500	597.500
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	599.190	599.190	0.300
ET	0.000	0.000	0.000	0.000	9.100	0.000	0.000	0.000	450.000	950.000

XSECT. U/S OF VREELAND RD

X1	14016.000	0.000	0.000	0.000	25.000	25.000	25.000	0.000	0.000	0.000
NC	0.100	0.100	0.035	0.100	0.300	0.000	0.000	0.000	0.000	0.000
ET	0.000	0.000	0.000	0.000	9.100	0.000	0.000	0.000	275.000	675.000

VALLEY SECTION BASED ON FIELD BOOK AND QUAD MAP

X1	14079.000	16.000	571.000	579.000	597.000	597.000	597.000	0.000	0.000	0.000
X4	1.000	602.000	1.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
GR	610.000	0.000	599.370	275.000	596.520	425.000	596.070	611.000	596.720	559.000
GR	592.670	571.000	592.370	575.000	592.970	579.100	597.970	586.000	597.120	603.000
GR	597.500	830.000	604.500	603.100	604.500	629.400	597.500	830.000	603.000	1000.000
GR	610.000	1031.500	0.300	0.000	0.300	0.000	0.000	0.000	0.000	0.000
NC	0.093	0.000	0.040	0.300	0.300	0.000	0.000	0.000	0.000	0.000
ET	0.000	0.000	0.000	9.100	9.100	0.000	625.000	2852.000	1000.000	1600.000

X-SECTION D/S OF TELEGRAPH RD.

X1	15262.000	13.000	596.000	1404.000	700.000	500.000	589.300	0.000	0.000	0.000
GR	610.000	1049.000	610.000	1049.000	593.300	1050.000	597.300	1200.000	599.660	1377.000
GR	594.160	1380.000	592.600	1396.000	592.810	1400.000	592.600	1404.000	594.160	1412.000
GR	596.160	2415.000	596.530	1550.000	600.000	1550.000	0.000	0.000	0.000	0.000
ET	0.000	0.000	0.000	0.000	9.100	0.000	0.000	0.000	1129.000	1600.000

D/S FACE OF TELEGRAPH RD. BRIDGE

X1	5362.000	15.000	1390.400	1409.400	100.000	400.000	130.000	0.000	0.000	0.000
GR	610.000	1000.000	600.000	1110.000	592.310	1200.000	599.920	1350.300	597.200	1390.400

PRINTED IN U.S.A.
FORM 1411-6 PRINTED BY ROTARY MANIFOLD FORMS

00BREAK00

1) COUNTY: Wayne

2) STUDY NAME: City of Flat Rock

3) WATERCOURSE: Silver Creek

4) DOCUMENT TYPE: 500 year

00BREAK00

State Copy

11001679

TA-23 HYDROLOGY

PRINTED IN U.S.A.

FORM 3411-SD-PRINTED BY ROTARY MANIFOLD FORMS

PROGRAM DATE - FEB. 14, 1974 2/306

PRINTED IN U.S.A.

FORM 1411-GD PRINTED BY ROTARY MANIFOLD FORMS

EXECUTIVE CONTROL CARD OPERATION LIST

LISTING OF DATA IN CORE

10 [illegible]

VELOCITY INCREMENT

7 CTABLE 0.2000

8	0.0000	0.0300	0.1800	0.2500	0.3200
8	0.3700	0.4100	0.4500	0.4900	0.5100
8	0.5400	0.5700	0.5900	0.6100	0.6300
8	0.6500	0.6600	0.6700	0.6900	0.7000
8	0.7100	0.7200	0.7200	0.7300	0.7500
8	0.7600	0.7700	0.7700	0.7800	0.7900
8	0.7900	0.8000	0.8100	0.8100	0.8200
8	0.8200	0.8300	0.8300	0.8400	0.8400
8	0.8400	0.8500	0.8500	0.8600	0.8600
8	0.8600	0.8600	0.8700	0.8700	0.8700
8	0.8700	0.8800	0.8800	0.8900	0.8900
8	0.8900	0.8900	0.8900	0.8900	0.9000
8	0.9000	0.9000	0.9000	0.9000	0.9100
8	0.9100	0.9100	0.9100	0.9100	0.9100
8	0.9200	0.9200	0.9200	0.9200	0.9200
8	0.9200	0.9200	0.9200	0.9300	0.9300

9 ENDTBL

STRUCT NO.

3 STRUCT 1

	ELEVATION	DISCHARGE	STORAGE
8	592.5000	0.0000	0.0000
8	595.2000	50.0000	0.1000
8	597.0999	100.0000	0.2000
8	595.2000	200.0000	2.0000
8	596.6001	300.0000	56.5000
8	599.2000	400.0000	182.5000
8	599.7000	500.0000	222.5000
8	600.0500	600.0000	292.5000
8	600.3000	700.0000	298.0000
8	600.7000	800.0000	353.0000

9 ENDTBL

TIME INCREMENT

4 DELAY

8	0.0000	0.0300	0.1000	0.1900	0.3100

PRINTED IN U.S.A.
FORM 761.08 PRINTED BY ROTARY MANIFOLD FORMS

```
      8          0.4700    0.6600    0.8200    0.9300    0.9900
      8          1.0000    0.9900    0.9500    0.8600    0.7800
      8          0.6800    0.5500    0.4600    0.3900    0.3300
      8          0.2800    0.2410    0.2070    0.1740    0.1470
      8          0.1260    0.1070    0.0910    0.0770    0.0660
      8          0.0550    0.0470    0.0400    0.0340    0.0290
      8          0.0250    0.0210    0.0180    0.0150    0.0130
      8          0.0110    0.0090    0.0080    0.0070    0.0060
      8          0.0050    0.0040    0.0030    0.0020    0.0010
      8          0.0000    0.0000    0.0000    0.0000    0.0000
      9 ENDTBL

    COMPUTED PEAK K FACTOR =  464.00


                        TIME INCREMENT
      $ PANEL 1                0.5000

      8          0.0000    0.0030    0.0070    0.0260    0.0350
      8          0.0450    0.0530    0.0660    0.0760    0.0870
      8          0.0990    0.1120    0.1250    0.1400    0.1560
      8          0.1740    0.1940    0.2140    0.2540    0.3030
      8          0.5150    0.5830    0.6240    0.6540    0.6820
      8          0.7050    0.7270    0.7430    0.7670    0.7840
      8          0.8000    0.8160    0.8300    0.8420    0.8570
      8          0.8700    0.8820    0.8930    0.9050    0.9160
      8          0.9250    0.9360    0.9460    0.9550    0.9650
      8          0.9740    0.9830    0.9920    1.0000    1.0000
      9 ENDTBL
```

FORM 1421-01 PRINTED BY ROTARY MANIFOLD FORMS.
PRINTED IN U.S.A.

STANDARD CONTROL INSTRUCTIONS

```
6 RESVOR 2      1 6   7      592.5000                    1 1 1 1 0 0
  ENDATA

END OF LISTING
```

PRINTED IN U.S.A.

FORM 1411-GD PRINTED BY ROTARY-MANIFOLD FORMS.

PRINTED IN U.S.A.

FORM 1611-00 PRINTED BY ROTARY MANIFOLD FORMS.

EXECUTIVE CONTROL CARD OPERATION INCREM MAIN TIME INCREMENT= 0.20 PASS=2 10

DISCHARGE HYDROGRAPH, HYDROGRAPH LOCATION 6

STARTING TIME= 0.00 TIME INCREMENT= 1.00 DRAINAGE AREA= 2.36 BASE FLO.= 0.00

8	0.0003	25.0000	50.0000	335.0000	265.0000
8	570.0000	790.0000	840.0000	810.0000	790.0000
8	765.0000	740.0000	700.0000	660.0000	615.0000
8	575.0000	530.0000	490.0000	455.0000	415.0000
8	385.0000	350.7000	0.0000	0.0000	0.0000

9 END OF
EXECUTIVE CONTROL CARD OPERATION COMPUT FROM XSECTN/STRUCT 0/ 1 TO XSECTN/STRUCT 0/ 1

STARTING TIME= 0.00 RAIN DEPTH= 5.90 RAIN DURATION= 1.00 RAIN TABLE NO.= 1 SOIL CONDITION= 2
ALTERNATE NO.= 2 STORM NO.= 1

SUBROUTINE RESVOR STRUCTURE 1
SURFACE ELEVATION= 592.50

PEAK TIMES	PEAK DISCHARGES	PEAK ELEVATIONS
14.40	399.258	606.05
29.62	33.094	592.97
30.02	12.625	592.61
30.42	4.702	592.57
30.82	1.751	592.52
31.22	0.652	592.51
31.62	0.243	592.50
32.02	0.091	592.50
32.42	0.034	592.50
32.82	0.013	592.50

HYDROGRAPH, TZERO= 0.00 DELTA T= 0.20 DRAINAGE AREA= 2.36

TIME											
0.00	DISCHG	0.00	4.05	9.52	16.26	19.46	24.34	29.63	34.52	39.41	44.39
0.00	ELEV	592.50	592.50	592.55	592.70	592.77	592.86	592.91	592.91	592.95	592.96
2.00	DISCHG	69.40	80.35	76.79	87.21	100.22	105.63	122.15	140.35	181.37	200.09
2.00	ELEV	592.79	592.85	592.88	592.92	592.90	592.97	592.15	592.53	592.96	592.21
4.00	DISCHG	212.72	206.06	211.02	217.93	225.59	235.12	243.08	257.04	270.37	284.05
4.00	ELEV	595.24	595.26	595.35	595.45	595.56	595.69	595.84	596.01	596.19	596.35
6.00	DISCHG	298.34	308.38	312.39	318.24	328.53	332.17	338.75	345.17	351.42	357.51
6.00	ELEV	596.50	596.75	596.92	597.09	597.26	597.43	597.61	597.77	597.94	598.10
8.00	DISCHG	363.43	369.24	374.91	380.45	385.86	391.16	396.32	404.21	409.35	403.42
8.00	ELEV	598.29	598.40	598.58	598.49	598.85	598.97	599.10	599.23	599.30	599.37
10.00	DISCHG	447.14	439.91	471.96	483.31	494.21	505.29	517.76	529.03	539.27	548.53
10.00	ELEV	599.44	599.50	599.36	599.82	599.87	599.72	599.76	599.86	599.84	599.67
12.00	DISCHG	556.67	564.33	570.96	576.81	581.91	586.31	590.02	593.05	595.43	597.21
12.00	ELEV	599.90	599.93	599.95	599.97	599.99	600.00	600.02	600.03	600.03	600.04
14.00	DISCHG	598.40	598.34	599.29	599.06	598.41	597.37	595.93	594.08	591.83	589.26
14.00	ELEV	600.04	600.03	600.03	600.05	600.05	600.06	600.06	600.06	600.05	600.04
16.00	DISCHG	586.33	583.09	579.60	575.87	571.91	567.73	563.36	558.80	554.05	549.49
16.00	ELEV	600.00	599.98	599.98	599.97	599.95	599.94	599.92	599.91	599.89	599.87
18.00	DISCHG	544.69	539.59	534.47	529.38	523.61	518.20	512.21	506.19	499.57	495.11
18.00	ELEV	599.80	599.84	599.82	599.80	599.78	599.76	599.76	599.78	599.78	599.58
20.00	DISCHG	490.23	484.72	479.39	473.13	466.93	460.44	452.78	444.90	437.64	417.24

20.00	ELEV	599.65	599.62	599.60	599.57	599.53	599.50	599.46	599.41	599.36	599.29
22.00	DISCHG	401.58	395.27	390.12	385.03	380.02	375.06	370.18	365.35	360.59	355.89
22.00	ELEV	599.21	599.08	598.94	598.81	596.68	598.55	598.42	598.30	598.18	598.05
24.00	DISCHG	351.25	346.67	342.16	337.70	333.30	328.95	324.66	320.43	316.26	312.14
24.00	ELEV	597.93	597.81	597.70	597.58	597.47	597.35	597.24	597.13	597.02	596.92
26.00	DISCHG	308.07	304.05	300.09	291.16	282.38	273.87	265.61	257.61	249.64	242.31
26.00	ELEV	595.81	596.71	596.60	596.48	596.35	596.23	596.12	596.01	595.90	595.79
28.00	DISCHG	235.03	227.92	221.05	214.36	207.92	201.65	107.56	-00.86	32.07	-20.06
28.00	ELEV	595.69	595.59	595.49	595.40	595.31	595.22	594.00	591.75	596.96	592.22
30.00	DISCHG	12.24	-7.47	4.56	-2.78	1.70	-1.04	0.65	-0.39	0.24	-0.14
30.00	ELEV	592.67	592.40	592.56	592.46	592.52	592.49	592.51	592.49	592.50	592.50
32.00	DISCHG	0.09	-0.05	0.03	-0.02	0.01	-0.01	0.00			
32.00	ELEV	592.50	592.50	592.50	592.50	592.50	592.50	592.50			

TOTAL RATES, 30 INCHES OF RAINFALL ARE= 7.2013 CFS-HRS= 11075.09 ACRE-FT= 898.72

```
ENDCMP

ENDJOB CARD ENCOUNTERED.  END OF JOB.
```

PRINTED IN U.S.A.
FORM 1411-GB-PRINTED BY ROTARY MANIFOLD FORMS

R

END OF JOBS IN THIS RUN

PRINTED IN U.S.A.


FORM 141-GS PRINTED BY ROTARY MANIFOLD FORMS.


```
**********************************************************************
*                                                                    *
*                        E R R O R   S U M M A R Y                   *
*                                                                    *
*       0  ERROR(S) DETECTED BY THE USER PROGRAM                     *
*       0  ERROR(S) DETECTED BY THE MATHEMATICAL PACKAGE             *
*       0  ERROR(S) DETECTED FOR INPUT/OUPUT STATEMENTS              *
*                                                                    *
**********************************************************************
```

PRINTED IN U.S.A.

FORM 1011-QS PRINTED BY BOISARE MANIFOLD FORMS.

14:56:13 X408 BILL HU2009D7 HUDFROCK DEC 20, 1979





A400 10*T SN:10** LN:10*T FH:65-917 22A00064 P001 RN/1112/F1/S1/0/K152

PRINTED IN U.S.A.
FORM 1411-OB-PRINTED BY ROTARY MANIFOLD FORMS.

00BREAK00

1) COUNTY: Wayne

2) STUDY NAME: City of Flat Rock

3) WATERCOURSE: Silver Creek

4) DOCUMENT TYPE: Floodway

00BREAK00

Floodway

```
**************************************************
*  HEC2 RELEASE DATED NOV 76 UPDATED FEB 1977    *
*  ERROR CORR - 01                               *
*  MODIFICATION - 50,51,52                       *
**************************************************

T1      FLAT ROCK FLOOD INSURANCE STUDY
T2      100YR. ENCROACHMENT RUN
T3      SILVER CREEK

J1  ICHECK     INQ        NINV       IDIR       STRT       METRIC     HVINS      Q          WSEL       FQ
          0.        5.         0.         0.  0.060000       0.00       0.0        0.     586.580      0.000

J2  NORGE      IPLOT      PRFVS      XSECV      XSECH      FN         ALLDC      XBM        CHNIM      ITRACE
     15.000      0.000     -1.000      0.000      0.000      0.000      0.000      0.000      0.000      0.000
```

PRINTED IN U.S.A.
FORM 1411-02 PRINTED BY ROTARY MANIFOLD FORMS.

*PROF 2

CCHV= 0.100 CEHV= 0.300

*SECNO ****

SECNO	DEPTH	CHSEL	CRIWS	WSELK	SG	HV	HL	QLOSS	BANK ELEV
0	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TUA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IN2	ICONT	CORAR	TOPWID	ENDST

3470 ENCROACHMENT STATIONS= 1350.0 1600.0 TYPE= 1 TARGET= 250.000

450. FEET D/S OF D/S FACE OF OLMSTEAD RD. ROCKWOOD SECT. 19073.

0.00	3.88	585.58	0.00	536.48	586.58	0.00	0.00	0.00	580.60
705.	369.	118.	259.	776.	191.	457.	0.	0.	577.90
0.00	0.47	3.62	3.43	0.035	0.035	0.035	0.000	577.70	1350.00
0.000013	0.	0.	0.	0	0	0	0.00	250.00	1600.00

*SECNO 1.000

2800 NAT Q1= 361.65 WSEL= 586.47 ENC Q1= 361.65 WSEL= 986.57 RATIO= 0.0000

NAT Q1= 330. RATIOS LOB,CH,ROB= 0.0353 0.6296 0.5359 ASEL= 586.57

3470 ENCROACHMENT STATIONS= 690.7 940.1 TYPE= 4 TARGET= 0.068

D/S FACE OF OLMSTEAD ROAD ROCKWOOD SECT. 19523.

1.00	9.57	586.57	0.00	586.47	586.61	0.03	0.02	0.01	585.80
705.	1.	325.	379.	1.	145.	344.	10.	3.	585.60
0.06	0.34	2.24	1.10	0.035	0.035	0.035	0.034	576.90	690.68
0.000311	400.	652.	500.	2	0	0	0.00	249.30	940.05

*SECNO 2.000

2800 NAT Q1= 435.41 WSEL= 586.47 ENC Q1= 435.41 WSEL= 586.57 RATIO= 0.0000

NAT Q1= 490. RATIOS LOB,CH,ROB= 0.0552 0.1162 0.8284 ASEL= 586.57

3370 NORMAL BRIDGE,NRD= 23 MIN ELTRD= 584.20 MAX ELLC= 583.90

3470 ENCROACHMENT STATIONS= 892.4 939.5 TYPE= 4 TARGET= 0.111

1 FOOT INSIDE BRIDGE D/S END ROCKWOOD SECT. 19525.

2.00	9.57	586.57	0.00	586.47	586.61	0.05	0.00	0.00	585.80
705.	1.	92.	213.	0.	92.	343.	10.	3.	585.80
0.06	0.00	1.00	1.79	0.018	0.031	0.018	0.034	576.90	692.40
0.000266	1.	1.	1.	0	0	0	-53.08	247.10	939.50

*SECNO 3.000

2800 NAT Q1= 444.91 WSEL= 586.69 ENC Q1= 444.91 WSEL= 586.39 RATIO= 0.0000

NAT Q1= 497. RATIOS LOB,CH,ROB= 0.0568 0.1149 0.8282 WSEL= 586.69

3370 NORMAL BRIDGE,NRD= 23 MIN ELTRD= 584.20 MAX ELLC= 583.90

3470 ENCROACHMENT STATIONS= 887.9 940.1 TYPE= 4 TARGET= 0.104

1 FOOT INSIDE BRIDGE D/S END ROCKWOOD SECT. 19525.

PRINTED IN U.S.A.

FORM 1417-GB PRINTED BY ROTARY MANIFOLD FORMS

3.00	9.68	586.58	0.00	586.49	586.63	0.04	0.01	0.00	585.80
705.	3.	91.	611.	3.	92.	347.	10.	3.	585.80
0.09	1.00	0.99	1.76	0.018	0.031	0.018	0.034	576.90	687.91
0.000254	46.	46.	46.	0	0	0	-53.08	252.23	940.14

*SECNO 4.000
2800 NAT Q1= 318.43 WSEL= 586.47 ENC Q1= 318.43 WSEL= 586.58 RATIO= 0.0000
NAT Q1= 340. RATIOS LOB,CH,ROB= 0.0319 0.4906 0.4775 WSEL= 586.58

SECNO	DEPTH	CNSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	Q ROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	V ROB	XWL	XNCH	XNR	WTN	EL TOP	SSTA
SLOPE	XLOBL	XLCH	XLOBR	FRICTL	JH2	ICONT	CORAR	TOPWID	ENDST

3470 ENCROACHMENT STATIONS= 692.4 939.5 TYPE= 4 TARGET= 0.064

U/S FACE OF OLDSTEAD ROAD ROCKWOOD SECT. 19371.

4.00	9.67	586.57	0.00	586.47	586.63	0.06	0.00	0.00	585.80
705.	0.	365.	340.	0.	145.	347.	10.	3.	585.80
0.09	0.06	2.51	0.90	0.045	0.035	0.045	0.034	576.90	692.40
0.000464	1.	1.	1.	0	0	0	0.00	247.15	939.50

*SECNO 5.000
2800 NAT Q1= 2108.51 WSEL= 586.56 ENC Q1= 2108.51 WSEL= 586.66 RATIO= 0.0000
NAT Q1= 2191. RATIOS LOB,CH,ROB= 0.2355 0.0993 0.6652 WSEL= 586.66

3470 ENCROACHMENT STATIONS= 85.1 566.9 TYPE= 4 TARGET= 0.037

750.FEET D/S OF D/S FACE OF OLDSTEAD RD.ROCKWOOD SECT. 20321.

5.00	9.06	586.66	0.00	586.56	586.66	0.00	0.03	0.01	582.60
750.	196.	75.	480.	563.	143.	1539.	35.	9.	580.00
0.79	1.30	0.53	0.32	0.043	0.035	0.043	0.035	576.90	63.06
0.000012	775.	750.	725.	2	0	0	0.00	481.84	566.90

*SECNO 6.000
2800 NAT Q1= 1756.51 WSEL= 586.57 ENC Q1= 1756.55 WSEL= 586.67 RATIO= 0.0000
NAT Q1= 1338. RATIOS LOB,CH,ROB= 0.4410 0.1543 0.3847 WSEL= 586.67

3470 ENCROACHMENT STATIONS= 106.9 600.2 TYPE= 4 TARGET= 0.037

1450.FEET D/S OF D/S FACE OF OLDSTEAD ROCKWOOD SECT. 21621., CORP.LIMIT

6.00	9.77	586.67	0.00	586.57	586.67	0.02	0.01	0.20	583.70
730.	336.	117.	278.	925.	205.	746.	67.	16.	582.40
1.19	0.36	0.97	0.37	0.045	0.035	0.045	0.035	578.90	186.96
0.000017	675.	700.	725.	0	0	0	0.00	413.27	600.22

CONV= 0.300 SPLV= 0.50

*SECNO 1944.000
2800 NAT Q1= 471.23 WSEL= 586.59 ENC Q1= 471.23 WSEL= 586.69 RATIO= 0.0000
NAT Q1= 183. RATIOS LOB,CH,ROB= 0.3421 0.5439 0.1140 WSEL= 586.69

3470 ENCROACHMENT STATIONS= 127.9 379.3 TYPE= 4 TARGET= 0.066

X-SECTION D/S OF WOODRUFF RD.

1944.00	5.99	586.69	0.00	586.59	586.07	0.19	0.11	0.09	583.15

PRINTED IN U.S.A.
FORM 1415-00 PRINTED BY ROTARY MANIFOLD FORMS

730.	241.	426.	63.	276.	94.	82.	113.	29.	584.07
1.36	0.87	4.52	0.77	0.100	0.040	0.100	0.043	580.70	127.95
0.001830	1400.	2450.	1944.	3	0	0	0.00	251.33	379.28

*SECNO 2044.000

3470 ENCROACHMENT STATIONS= 94.0 428.0 TYPE= 1 TARGET= 334.000

D/S FACE OF HOODRUFF RD. BRIDGE REPEATED SECT. 1944

2044.00	6.12	586.62	0.00	586.71	587.10	0.36	0.22	0.09	583.13
730.	127.	940.	63.	179.	97.	92.	114.	30.	584.07
1.37	0.71	5.59	0.69	0.100	0.040	0.100	0.043	580.70	94.00
0.002706	100.	100.	100.	2	0	0	0.00	334.00	428.00

*SECNO 2045.000

SECNO	DEPTH	CHSEL	CCHNS	ASELK	ES	HV	NL	WLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	UTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	XH2	ICONT	CORAR	TOPWID	EXDST

3370 NORMAL BRIDGE,NRD= 8 MIN ELTRD= 585.63 MAX ELLC= 584.07

1 FOOT INSIDE OF D/S FACE OF BRIDGE

2045.00	6.51	587.21	0.00	587.13	587.27	0.06	0.00	0.09	583.13
730.	378.	144.	208.	280.	40.	159.	114.	30.	584.07
1.37	1.35	3.59	1.31	0.070	0.025	0.070	0.043	580.70	75.70
0.002972	1.	1.	1.	4	0	0	-67.14	374.61	450.30

*ECNO 2074.000

3370 NORMAL BRIDGE,NRD= 3 MIN ELTRD= 585.63 MAX ELLC= 584.07

1 FOOT INSIDE OF D/S FACE OF BRIDGE

2074.00	6.62	587.32	0.00	587.26	587.34	0.02	0.05	0.01	583.13
403.	262.	67.	145.	304.	43.	173.	114.	30.	584.07
1.48	0.86	2.13	0.84	0.070	0.025	0.070	0.043	580.70	75.67
0.001290	20.	20.	20.	2	0	0	-69.08	374.66	450.35

*SECNO 2075.000

D/S FACE OF HOODRUFF RD. BRIDGE

2075.00	6.39	587.29	0.00	587.24	587.33	0.07	0.00	0.02	583.13
445.	182.	209.	74.	301.	105.	172.	114.	30.	584.07
1.33	0.44	2.75	0.43	0.100	0.040	0.100	0.043	580.70	75.68
0.000588	1.	1.	1.	2	0	0	0.00	374.65	650.32

*SECNO 2100.000

D-SECTION D/S OF HOODRUFF RD. REPEATED SECT. 2075.5

2100.30	6.61	587.31	0.00	587.25	587.38	0.07	0.01	0.00	583.13

PRINTED IN U.S.A.
FORM 1411-3B-PRINTED BY BOTANY MANIFOLD FORMS.

495.	134.	286.	75.	306.	105.	175.	114.	30.	584.07
1.38	0.44	2.72	0.43	0.100	0.040	0.100	0.043	580.70	75.67
0.000571	25.	25.	25.	0	0	0	0.00	374.66	450.33

*SECNO 3073.000

VALLEY SECTION BASED ON FIELD BOOK AND QUAD MAP

3073.00	6.66	587.74	0.00	587.71	587.77	0.02	0.38	0.01	581.78
695.	22.	199.	314.	45.	76.	829.	132.	40.	581.78
1.67	0.49	2.10	0.36	0.100	0.045	0.100	0.042	581.08	278.96
0.000277	973.	973.	973.	2	0	0	0.00	515.28	792.22

CCHV= 0.100 CEHV= 0.300

*SECNO 4573.000

SECNO	DEPTH	CHSEL	CRIWS	WSELK	EG	HV	AL	LOSS	BANK ELEV
0	SQOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IN2	ICONT	CORAR	TOPWID	ENDST

VALLEY SECTION BASED ON FIELD BOOK AND QUAD MAP

4573.00	6.47	588.37	0.00	588.36	588.47	0.10	0.68	0.02	583.10
495.	97.	280.	118.	279.	82.	272.	160.	59.	583.10
1.37	0.35	3.40	0.43	0.120	0.040	0.120	0.041	581.90	835.85
0.000636	1350.	1500.	1650.	1	0	0	0.00	536.07	1422.72

CCHV= 0.300 CEHV= 0.500

*SECNO 6337.500

X-SELTION D/S OF BRIDGE S. OF GIBRALTAR RD.

6337.50	4.77	589.60	0.00	589.60	589.67	0.07	1.19	0.01	584.96
495.	103.	242.	150.	96.	65.	132.	179.	72.	584.68
2.12	1.37	2.65	1.94	0.070	0.033	0.070	0.040	584.83	228.87
0.000571	1763.	1765.	1763.	2	2	0	0.00	97.00	925.37

*SECNO 6527.000

3429 ENCROACHMENT STATIONS= 80.0 170.0 TYPE= 1 TARGET= 90.000

1: D/S OF ORDINWAY

6527.00	4.93	589.73	0.00	589.73	589.81	0.08	0.13	0.00	585.50
495.	175.	47.	273.	79.	132.	110.	181.	72.	585.50
2.13	2.23	0.35	2.48	0.040	0.350	0.040	0.047	584.60	80.00
0.000839	193.	190.	190.	0	0	0	0.00	90.00	170.00

*SECNO 6537.500

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 592.40 ELREA= 592.40

1: D/S OF DAIRE RD

6537.50	4.81	589.91	0.00	589.81	589.85	0.04	0.02	0.01	586.50
495.	0.	495.	0.	0.	317.	0.	181.	72.	586.50

PRINTED IN U.S.A.

FORM 1411-00 PRINTED BY ROTARY MANIFOLD FORMS

2.15	0.00	1.56	0.00	0.040	0.350	0.040	0.047	585.00	99.00
0.024439	10.	10.	10.	2	0	0	0.00	84.40	183.40

*SECNO 6538.500

3370 NORMAL BRIDGE,NAD= 25 MIN ELTRD= 592.60 MAX ELLC= 591.80

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 592.40 ELREA= 592.40

D/S FACE OF DRIVEWAY

6538.50	4.81	589.81	0.00	589.81	589.85	0.04	0.00	0.00	586.50
495.	0.	495.	0.	0.	299.	0.	181.	72.	586.40
2.15	0.00	1.66	0.00	0.040	0.025	0.040	0.047	585.00	99.00
0.000152	1.	1.	1.	1	0	0	-22.59	84.40	183.40

*SECNO 6578.000

SECNO	DEPTH	CHSEL	CRIUS	JSELK	EG	HV	HL	CLOSS	BANK ELEV
Q	CLOB	QCH	QROB	ALGO	ACH	ARCH	VOL	THW	LEFT/RIGHT
TIME	VLOB	VCH	VROB	ANL	ACHH	HCH	WTN	ELMIN	SSTA
SLOPE	KLOB	KLCH	KLOBC	ITRIAL	X42	ICONT	CORAR	TOPWID	ENDST

3370 NORMAL BRIDGE,NAD= 25 MIN ELTRD= 592.60 MAX ELLC= 591.80

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 592.50 ELREA= 592.50

U/S FACE OF DRIVEWAY

6579.00	4.81	589.81	0.00	589.81	589.85	0.04	0.01	0.00	586.50
495.	0.	495.	0.	0.	299.	0.	181.	72.	586.40
2.16	0.00	1.66	0.00	0.040	0.025	0.040	0.047	585.00	99.00
0.000152	40.	42.	40.	2	0	5	-22.56	84.40	183.40

*SECNO 6579.000

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 592.70 ELREA= 592.60

1: U/S OF DRIVEWAY

6579.00	4.82	589.82	0.00	589.82	589.86	0.04	0.00	0.00	586.50
495.	0.	495.	0.	0.	317.	0.	181.	72.	586.40
2.16	0.00	1.66	0.00	0.040	0.035	0.040	0.047	585.00	99.00
0.000263	1.	1.	1.	0	3	0	0.00	84.40	183.40

*SECNO 6609.000

50: U/S OF DRIVEWAY

6609.00	4.98	589.98	0.00	589.79	589.94	0.15	0.02	0.06	589.00
495.	1.	495.	1.	2.	150.	1.	201.	72.	589.40
2.16	0.65	3.12	0.69	0.040	0.035	0.040	0.047	584.90	112.72
0.001077	30.	30.	30.	2	0	0	0.00	84.56	187.28

PRINTED IN U.S.A.
FORM 3411-GO PRINTED BY ROTARY MANIFOLD FORMS

CCHV= 0.300 CEHV= 0.500
*SECNO 7174.000

3470 ENCROACHMENT STATIONS= 242.0 307.0 TYPE= 1 TARGET= 65.000

X-SECTION D/S OF GIBRALTAR RD. BRIDGE

7174.00	5.33	590.38	0.00	590.38	590.57	0.19	0.61	0.02	585.60
495.	58.	322.	115.	46.	76.	77.	184.	73.	585.60
2.21	1.26	4.26	1.49	0.070	0.035	0.070	0.046	505.05	242.00
0.001983	547.	547.	547.	2	0	0	0.00	65.00	307.00

*SECND 7274.000

3470 ENCROACHMENT STATIONS= 169.0 389.0 TYPE= 1 TARGET= 200.000

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 593.30 ELJEA= 393.30

D/S FACE OF GIBRALTAR RD. BRIDGE

7274.00	5.26	590.31	0.00	590.31	591.00	0.69	0.18	0.25	585.60
495.	0.	495.	0.	0.	73.	0.	184.	73.	585.60
2.21	0.00	6.64	0.00	0.070	0.035	0.070	0.046	505.05	289.15
0.003195	100.	100.	100.	2	0	0	0.00	14.95	304.10

SPECIAL BRIDGE

SB	XK	XKOR	COFQ	RDLEN	BNC	SHP	BAREA	SS	ELCHU	ELCHD
	2.20	2.57	3.00	0.00	12.20	0.00	80.00	0.00	582.50	585.05

*SECNO 7373.000

SECNO	DEPTH	CHSEL	CRIMS	WCHLR	ZG	LV	EL	OLCHS	BANK ELEV
0	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTX	CLMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	STREAL	ZH2	ICONV	CORAR	TOPWID	ENDST

PRESSURE FLOW

JEGPRS	EGLJC	FQ	QWEIR	QPR	BAREA	TRAPEZOID AREA	ELLC	ELTRD
591.70	590.05	0.00	0.	495.	36.	36.	589.36	592.37

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 592.55 ELREA= 592.37

D/S FACE OF GIBRALTAR RD. BRIDGE

D=1.9

7373.00	6.20	591.25	0.00	591.26	591.70	0.44	0.70	0.20	583.05
495.	0.	495.	0.	0.	93.	0.	184.	73.	585.05
2.22	0.00	5.35	0.00	0.070	0.035	0.070	0.046	583.05	289.15
0.002196	99.	99.	99.	2	0	0	0.00	14.95	304.10

*SECNO 7393.000

PRINTED IN U.S.A.

FORM 1611-GO PRINTED BY ROTARY MANIFOLD FORMS

3470 ENCROACHMENT STATIONS= 400.0 633.0 TYPE= 1 TARGET= 233.000

X-SECTION U/S OF GIBRALTAR RD. BRIDGE

7328.00	6.54	591.59	0.00	591.59	591.80	0.21	0.03	0.07	585.05
495.	48.	396.	51.	40.	98.	43.	154.	73.	585.05
2.12	1.18	4.05	1.19	0.070	0.035	0.070	0.046	585.05	476.78
0.00375	25.	25.	25.	2	0	0	0.00	40.40	517.18

CCHV= 0.100 CEHV= 0.300
*SECNO 8573.000
2800 NAT Q1= 240.43 WSEL= 592.40 ENC Q1= 240.43 WSEL= 592.50 RATIO= 0.0000
NAT Q1= 262. RATIOS LOB,CH,ROB= 0.4866 0.4164 0.0970 WSEL= 592.50

3470 ENCROACHMENT STATIONS= 818.6 1098.4 TYPE= 4 TARGET= 0.081

VALLEY SECTION N. OF GIBRALTAR RD. BASED ON FIELD BOOK AND QUAD MAP

8573.00	6.93	592.43	0.00	592.40	592.50	0.07	0.09	0.01	585.75
495.	234.	231.	30.	364.	75.	49.	193.	78.	587.60
2.40	0.64	3.07	0.60	0.070	0.035	0.070	0.045	585.50	818.63
0.000469	1175.	1175.	1175.	2	0	0	0.00	279.76	1098.39

CCHV= 0.100 CEHV= 0.300
*SECNO 9000.000
2800 NAT Q1= 166.72 WSEL= 592.59 ENC Q1= 166.72 WSEL= 592.69 RATIO= 0.0000
NAT Q1= 181. RATIOS LOB,CH,ROB= 0.3816 0.5575 0.0609 WSEL= 592.69

3470 ENCROACHMENT STATIONS= 383.3 1063.7 TYPE= 4 TARGET= 0.077

9000.00	6.65	592.63	0.00	592.59	592.80	0.17	0.26	0.03	586.23
495.	170.	304.	13.	275.	72.	15.	197.	80.	588.08
2.65	0.65	4.22	0.03	0.090	0.035	0.090	0.044	585.98	843.26
0.000941	427.	427.	427.	2	0	0	0.00	220.45	1063.70

*SECNO 9500.000
2800 NAT Q1= 153.93 WSEL= 593.04 ENC Q1= 153.93 WSEL= 593.14 RATIO= 0.0300
NAT Q1= 166. RATIOS LOB,CH,ROB= 0.3591 0.5891 0.0518 WSEL= 593.14

3470 ENCROACHMENT STATIONS= 849.2 1067.7 TYPE= 4 TARGET= 0.073

9500.00	6.57	593.11	0.00	593.04	593.31	0.20	0.27	0.01	586.79
495.	170.	318.	9.	252.	71.	10.	201.	82.	588.64
2.69	0.67	4.47	0.76	0.090	0.035	0.090	0.044	586.54	849.16
0.001074	500.	500.	500.	2	0	0	0.00	212.56	1061.75

*SECNO 13173.000
2800 NAT Q1= 144.45 WSEL= 593.76 ENC Q1= 144.45 WSEL= 593.86 RATIO= 0.0000
NAT Q1= 153. RATIOS LOB,CH,ROB= 0.2381 0.5193 0.2429 WSEL= 593.86

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	RV	ML	QLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TIA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XCH	XTH	WTH	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IRZ	ICONT	CORAR	TOPWID	ENDST

3470 ENCROACHMENT STATIONS= 210.5 360.4 TYPE= 4 TARGET= 0.057

VALLEY SECTION BASED ON FIELD BOOK AND QUAD MAP

13173.00	5.75	593.85	0.00	593.75	594.08	0.23	0.76	0.01	587.20
495.	112.	270.	113.	125.	33.	303.	206.	85.	587.10

PRINTED IN U.S.A.
FORM 161-GD PRINTED BY ROTARY MANIFOLD FORMS

2.55	0.89	5.16	1.09	0.090	0.035	0.090	0.043	587.10	216.47
0.001186	673.	673.	673.	2	0	0	0.00	143.88	360.35

*SECNO 11673.000
2800 NAT Q1= 153.09 WSEL= 595.17 ENC Q1= 153.09 WSEL= 595.27 RATIO= 0.0000
NAT Q1= 162. RATIOS OB,CH,OB= 0.3421 0.5931 0.0649 HSEL= 595.27

3265 DIVIDED FLOW

3470 ENCROACHMENT STATIONS= 144.4 309.2 TYPE= 4 TARGET= 0.055

VALLEY SECTION BASED ON FIELD BOOK AND QUAD MAP

11673.00	6.51	595.27	0.00	595.17	595.41	0.16	1.32	0.01	588.81
390.	129.	245.	15.	215.	69.	21.	215.	90.	588.76
2.71	0.68	3.77	0.75	0.090	0.035	0.090	0.043	588.76	146.38
0.000653	1300.	1530.	1800.	2	0	0	0.00	144.44	309.16

CCHV= 0.300 CEHV= 0.500

*SECNO 12355.040

3265 DIVIDED FLOW

3470 ENCROACHMENT STATIONS= 692.0 808.0 TYPE= 1 TARGET= 116.000

*SECT.D/S OF R.R CULVERTS

12356.00	5.93	595.69	0.00	595.71	596.14	0.33	0.63	0.09	590.00
390.	21.	305.	64.	29.	59.	76.	219.	92.	590.00
2.75	0.72	5.20	0.85	0.110	0.035	0.110	0.042	589.00	692.00
0.001435	503.	603.	633.	2	3	0	0.00	90.91	603.20

*SECNO 12456.000

3670 ENCROACHMENT STATIONS= 1.0 1252.0 TYPE= 1 TARGET= 1250.000

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE.ELLEA= 202.00 ELALA= 602.00

D/S FACE OF DUAL 9' X 6.5' CBRLS

12456.00	6.23	596.25	0.00	596.17	596.40	0.10	0.22	0.05	592.01
390.	0.	390.	0.	0.	116.	0.	220.	92.	592.30
2.72	0.00	3.38	0.00	0.110	0.035	0.110	0.042	590.00	739.06
0.000943	191.	191.	191.	2	0	0	0.00	22.00	701.00

SPECIAL BRIDGE

SI	SS	WRKOR	COFQ	BDLEN	EUC	SWP	SAREA	SS	ELCHU	ELCHD
	0.00	3.23	3.00	0.00	11.65	0.00	77.00	0.00	590.40	590.00

*SECNO 12612.030
PRESSURE FLOW

ECORS	ELUC	SS	QWEIR	QBR	SAREA	TRAPEZOID AREA	ELLC	ELTRD

597.51	596.88	0.00	0.	390.	77.	71.	596.40	602.60	

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 602.60 ELREA= 602.60

DUAL CMP:S MEET DUAL BOX CULVERTS HERE.

12612.00	6.91	597.31	0.00	597.25	597.51	0.20	1.11	0.00	591.40
390.	0.	390.	0.	0.	106.	0.	220.	92.	591.40
2.78	0.00	3.61	0.00	0.110	0.035	0.110	0.042	590.40	739.00
0.001003	155.	156.	156.	2	0	0	0.00	17.00	756.00

SPECIAL BRIDGE

SK	XK	XKSQ	COPO	HOKEN	B.S	BAP	BAREA	SS	SLOPU	ELCHO
	1.25	1.74	3.00	0.00	16.67	1.00	94.00	0.00	590.40	590.40

*SECNO 12647.000

SECNO	DEPTH	CWSEL	CRWHO	WSELK	EG	KV	HL	OLOSS	BANK ELEV
0	CLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	V.OB	VCH	VROB	XNL	KNCH	XKR	WTH	ELCIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IH2	ICONT	CORAR	TOPWID	ENDST

PRESSURE FLOW

EGPRS	EGLWC	H3	OWEIR	QPR	BAREA	TRAPEZOID AREA	ELLC	ELTRD
597.78	597.51	0.03	0.	390.	94.	94.	596.40	602.60

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 602.60 ELREA= 602.60

U/S FACE OF R.R. CULVERTS

12647.00	7.38	597.42	0.00	597.35	597.70	0.15	0.43	0.00	590.40
390.	0.	390.	0.	0.	123.	0.	220.	92.	590.40
2.78	0.00	3.18	0.00	0.110	0.035	0.110	0.042	590.40	739.00
0.000640	35.	35.	35.	2	0	0	0.00	17.00	756.00

*SECNO 12580.000

3470 ENCROACHMENT STATIONS= 730.0 765.0 TYPE= 1 TARGET= 35.000

SUBSECT.U/S OF R.R.CULVERT & D/S OF 90° CUR

12580.00	6.35	597.67	2.05	597.62	597.80	0.12	0.02	0.01	590.72
390.	20.	343.	27.	37.	114.	48.	221.	92.	590.74
2.78	0.56	2.90	0.59	0.110	0.035	0.110	0.042	590.74	730.00
0.000353	33.	33.	33.	2	0	0	0.00	35.00	765.00

*SECNO 12719.000

3470 ENCROACHMENT STATIONS= 1.0 1251.0 TYPE= 1 TARGET= 1250.000

PRINTED IN U.S.A.
FORM 140 GS PRINTED BY ROTARY MANIFOLD FORMS.

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 598.50 ELREA= 598.50

D/S FACE OF 96 CMP

12715.00	6.77	597.67	0.00	597.60	597.86	0.19	0.02	0.04	592.00
390.	0.	390.	0.	0.	111.	0.	221.	92.	592.00
2.79	0.00	3.50	0.00	0.110	0.035	0.110	0.042	590.90	739.00
0.000977	35.	35.	35.	2	0	0	0.00	17.00	756.00

SPECIAL BRIDGE

SB	XK	XKOR	COFQ	RDLEN	BWC	BWP	BAREA	SS	ELCHU	ELCHD
	0.00	5.01	3.00	0.00	11.23	0.00	68.50	0.00	591.10	590.90

*SECNO 12979.000
WATER EL=X3 CARD= 593.600

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 602.60 ELREA= 602.60

D/S FACE OF 96 C.P

12979.00	8.50	599.60	0.00	599.60	599.72	0.12	0.19	0.02	593.20
390.	0.	390.	0.	0.	141.	0.	221.	92.	593.00
2.31	0.00	2.78	0.00	0.110	0.035	0.110	0.042	591.10	739.00
0.000534	264.	264.	264.	0	0	0	0.00	17.00	756.00

*SECNO 13030.000

3470 ENCROACHMENT STATIONS= 747.0 860.0 TYPE= 1 TARGET= 120.000

ADJECT. U/S OF 96 CMP

13030.00	9.70	599.62	0.00	599.62	599.79	0.14	0.02	0.01	590.23
735.	203.	357.	146.	259.	86.	201.	222.	92.	590.20
2.82	0.78	4.03	0.72	0.110	0.035	0.110	0.042	589.04	740.00
0.009444	51.	51.	51.	2	0	0	0.00	18P.00	360.00

CCHV= 0.100 CEHV= 0.300
*SECNO 13473.000

SECNO	DEPTH	CWSE	CRITWS	USELK	EG	HV	HL	OLOSS	BANK ELEV
Q	ALOB	WSEL	ORDB	ALOB	ACH	AROB	VOL	TRN	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XTR	HTS	ELMIN	SSTA
SLOPE	KLOB	KLCH	KROB	STRICL	FRP	ICONT	COARE	TOPWID	ELMST

3470 ENCROACHMENT STATIONS= 950.0 950.0 TYPE= 3 TARGET= 350.000

VALLEY SECTION BASED ON FIELD BOOK A-3 GRID MAP

13473.00	9.66	599.85	0.00	599.83	599.80	5.04	0.12	0.01	590.54
735.	344.	244.	147.	642.	95.	350.	230.	95.	590.54
2.92	0.53	2.56	0.42	0.100	0.035	0.100	0.042	590.79	690.00
0.000131	443.	443.	443.	1	0	0	0.00	300.00	950.00

CCHV= 0.300 CEHV= 0.500
*SECNO 13909.000

PRINTED IN U.S.A.
FORM 1411.99 PRINTED BY ROTARY MANIFOLD FORMS.

3470 ENCROACHMENT STATIONS= 600.0 900.0 TYPE= 1 TARGET= 300.000

XSECT. D/S OF VREELAND RD

13909.00	9.67	599.93	0.20	599.08	599.95	0.02	0.07	0.00	590.90
735.	258.	294.	271.	502.	93.	605.	242.	98.	590.90
3.05	0.44	2.20	0.45	0.100	0.035	0.100	0.041	590.46	600.00
0.000139	436.	436.	436.	2	0	0	0.00	300.00	900.00

*SECNO 14009.000

3470 ENCROACHMENT STATIONS= 550.0 850.0 TYPE= 1 TARGET= 300.000

D/S FACE OF VREELAND RD

14009.00	3.74	599.95	0.00	599.99	599.97	0.02	0.01	0.00	591.30
735.	255.	193.	286.	561.	87.	605.	245.	90.	591.30
3.08	0.46	2.22	0.47	0.100	0.035	0.100	0.041	591.21	550.00
0.000153	100.	100.	100.	0	0	0	0.00	300.00	850.00

SCHV= 0.300 CE(0= 0.500
*SECNO 14010.000

3265 DIVIDED FLOW

3301 HV CHANGED MORE THAN HVINS

3370 NORMAL BRIDGE,NRD= 3 MIN ELTRD= 599.19 MAX ELLC= 598.50

3470 ENCROACHMENT STATIONS= 550.0 850.0 TYPE= 1 TARGET= 300.000

1 FOOT INSIDE OF D/S FACE OF CULVERT

14010.00	0.37	599.68	597.41	599.59	600.34	0.76	0.50	0.37	591.30
735.	210.	494.	22.	173.	58.	49.	225.	96.	591.30
3.08	1.24	0.57	0.55	0.100	0.022	0.100	0.041	591.21	550.00
0.002308	1.	1.	1.	6	0	0	1059.25	300.00	1100.00

*SECNO 14090.000

3301 HV CHANGED MORE THAN HVINS

3370 NORMAL BRIDGE,NRD= 3 MIN ELTRD= 599.19 MAX ELLC= 598.50

3470 ENCROACHMENT STATIONS= 300.0 900.0 TYPE= 1 TARGET= 600.000

1 FOOT INSIDE OF D/S FACE OF CULVERT

14090.00	9.42	600.83	0.00	600.58	600.75	0.12	0.02	0.19	591.30
735.	273.	399.	162.	401.	76.	252.	246.	99.	591.30
3.09	0.66	4.22	0.66	0.100	0.022	0.100	0.041	591.21	500.00
0.001427	80.	81.	80.	4	0	0	1308.06	600.00	900.00

CSHV= 0.300 CE(0= 0.500

```
*SECNO 14091.000
   SECNO      DEPTH     CUSEL     CRIWS     WSELK     EG        HV        HL        QLOSS     BANK ELEV
   Q          QLOB      QCH       QROB      ALOB      ACH       AROB      VOL       TWA     LEFT/RIGHT
   TIME       VLOB      VCH       VROB      XNL       XNCH      XNR       WTN       ELMIN       SSTA
   SLOPE      XLOBL     XLCR      XLOBR     ITRIAL    IW2       ICONT     CORAR     TOPWID      ENDST

3470 ENCROACHMENT STATIONS=      500.0      900.0  TYPE=      1  TARGET=      400.000

          U/S FACE OF VREELAND RD

 14091.00      9.56    600.77      0.00    600.64    600.78      0.01      0.00      0.03    591.30
    735.       325.      152.      257.     1052.      105.      931.      246.       99.    591.30
     3.09      0.31      1.48      0.28     0.100     0.030     0.100     0.041    591.21    500.00
 0.000043         1.        1.        1.         2         0         0      0.00    400.00    900.00

*SECNO 14116.000

3470 ENCROACHMENT STATIONS=      450.0      950.0  TYPE=      1  TARGET=      500.000

          XSECT. U/S OF VREELAND RD

 14116.00      9.52    602.25      0.00    600.64    600.78      0.01      0.00      0.00    591.30
    735.       310.      144.      281.     1057.      105.     1110.      247.       99.    591.30
     3.11      0.29      1.37      0.25     0.100     0.030     0.100     0.041    591.21    498.54
 0.001330        25.       25.       25.         1         0         0      0.00    451.45    950.00

CCHV=  0.100 CEHV=  0.300
*SECNO 14673.000

3265 DIVIDED FLOW

3470 ENCROACHMENT STATIONS=      375.0      975.0  TYPE=      1  TARGET=      600.000

          VALLEY SECTION BASED ON FIELD BOOK AND QUAD MAP

 14673.00      5.74    600.31      0.00    600.68    600.72      0.01      0.00      0.00    592.57
    735.       200.      184.      322.      542.       68.      115.      275.      106.    592.57
     3.57      0.56      1.19      0.31     0.100     0.030     0.100     0.041    592.07    275.00
 0.000109        557.      557.      557.         0         0         0      0.00    570.09    875.00

CCHV=  0.300 CEHV=  0.300
*SECNO 15262.000

5470 ENCROACHMENT STATIONS=     1050.0     1600.0  TYPE=      1  TARGET=      550.000

          X-SECTION D/S OF TELEGRAPH RD.

 15262.00      8.55    600.38      0.00    600.72    600.87      0.01      0.05      0.00    592.60
    735.       344.       96.      296.     1035.       67.      530.      293.      112.    592.60
     3.65      0.33      1.41      0.43     0.090     0.040     0.090     0.341    592.31   1050.00
 0.000084        700.      589.      506.         1         0         0      0.00    500.32   1550.32

*SECNO 15362.000

3470 ENCROACHMENT STATIONS=     1125.0     1600.0  TYPE=      1  TARGET=      875.000

          DAS FACE OF TELEGRAPH RD. BRIDGE
```

PRINTED IN U.S.A.
FORM 1411.00 PRINTED BY ROTARY MANIFOLD FORMS

15362.00	8.53	600.84	0.00	600.70	600.93	0.09	0.02	0.04	597.20
735.	163.	449.	123.	340.	151.	236.	298.	113.	597.20
3.66	0.48	2.98	0.52	0.090	0.040	0.090	0.041	592.31	1125.00
0.000611	100.	100.	100.	2	0	0	0.00	450.14	1575.14

*SECNO 15363.000

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	QLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	KLOSL	XLCH	XLOBR	ITRIAL	IH2	ICONT	CORAR	TOPWID	ENDST

3370 NORMAL BRIDGE,NRD= 5 MIN ELTRD= 599.90 MAX ELLC= 597.20

3470 ENCROACHMENT STATIONS= 1125.0 1600.0 TYPE= 1 TARGET= 475.000

1 FOOT INSIDE D/S TELEGRAPH BRIDGE

15363.00	0.39	600.90	0.00	600.77	600.94	0.04	0.00	0.01	597.20
735.	272.	350.	203.	354.	705.	244.	296.	113.	597.20
3.66	0.76	2.62	0.32	0.060	0.025	0.060	0.041	592.31	1125.00
0.000644	1.	1.	1.	2	0	0	-44.40	450.15	1575.15

*SECNO 15434.000

3370 NORMAL BRIDGE,NRD= 5 MIN ELTRD= 599.90 MAX ELLC= 597.20

3470 ENCROACHMENT STATIONS= 1125.0 1600.0 TYPE= 1 TARGET= 475.000

1 FOOT INSIDE U/S END TELEGRAPH BRIDGE

15434.00	8.64	600.95	0.00	600.82	600.99	0.04	0.04	0.00	597.20
735.	276.	234.	205.	364.	103.	254.	295.	114.	597.20
3.68	0.75	2.34	0.31	0.060	0.025	0.060	0.041	592.31	1125.00
0.000597	71.	71.	71.	0	0	-	-44.41	450.15	1575.15

*SECNO 15435.000

3470 ENCROACHMENT STATIONS= 1125.0 1600.0 TYPE= 1 TARGET= 475.000

U/S FACE TELEGRAPH RD

15435.00	8.64	600.95	0.00	600.81	600.97	0.04	0.00	0.00	597.20
735.	217.	356.	161.	369.	153.	254.	299.	114.	597.20
3.68	0.59	2.33	0.63	0.060	0.040	0.060	0.041	592.31	1125.00
0.000566	1.	1.	1.	0	0	-	0.00	450.15	1575.15

*SECNO 15460.000

3470 ENCROACHMENT STATIONS= 1125.0 1600.0 TYPE= 1 TARGET= 475.000

PROJECT. U/S OF TELEGRAPH RD

15460.00	8.65	600.96	0.00	600.82	601.00	0.04	0.01	0.00	597.20
735.	218.	358.	162.	371.	153.	256.	300.	115.	597.20
3.68	0.59	2.32	0.33	0.060	0.040	0.060	0.041	592.31	1125.00

PRINTED IN U.S.A.
FORM 1411.00 PRINTED BY ROTARY MANIFOLD FORMS

0.000363	25.	25.	25.	0	0	0	0.00	450.16	1575.16

CCHV= 0.100 CEHV= 0.300

*SECNO 16873.000

3470 ENCROACHMENT STATIONS= 275.0 775.0 TYPE= 1 TARGET= 500.000

VALLEY SECT BASED ON FIELD BOOK NO 800

16873.00	3.63	601.49	0.00	601.52	601.46	0.00	0.40	0.00	592.80
735.	369.	112.	194.	544.	69.	456.	330.	129.	592.35
6.04	0.64	2.66	0.40	0.000	0.040	0.090	0.041	592.80	299.60
0.300292	1413.	1413.	1413.	2	0	0	0.00	450.46	750.14

*SECNO 17673.000

SECNO	DEPTH	CLSEL	SDIUS	USELV	EG	HV	HL	DLOSS	BANK ELEV
0	QLOB	QCH	QROB	ALOB	ACH	AROB	WOL	T-A	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	STN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IM2	ICONT	CORAR	TOPWID	ENDST

3470 ENCROACHMENT STATIONS= 525.0 600.0 TYPE= 1 TARGET= 518.000

VALLEY SECTION AT CORP/LIMIT BROWNSTOWN/FLAT ROCK

17673.04	8.56	611.56	0.00	601.50	601.73	0.07	0.20	0.00	594.37
735.	173.	275.	286.	244.	89.	422.	342.	134.	593.40
4.15	0.71	5.52	0.68	0.000	0.040	0.090	0.041	593.32	287.92
0.000533	900.	800.	300.	1	0	0	0.00	314.13	601.65

PRINTED IN U.S.A.
FORM 3411-00 PRINTED BY ROTARY MANIFOLD FORMS

****

HEC2 RELEASE DATED NOV 76 UPDATED FEB 1977
ERROR CORR - 01
MODIFICATION - 50,51,52

****

NOTE- ASTERISK (*) AT LEFT OF CROSS-SECTION NUMBER INDICATES MESSAGE IN SUMMARY OF ERRORS LIST

SILVER CREEK

SUMMARY PRINTOUT TABLE 150

	SECNO	XLCH	ELFRD	ELLC	ELCHN		CLSEL	CRIWS	EG	TOPWS	VCH	AREA	.01K
	0.000	0.00	0.00	0.00	577.70	705.00	586.48	0.00	586.48	0.14	0.63	1399.03	1895.45
	0.000	0.00	0.00	0.00	577.70	705.00	586.58	0.00	586.58	0.13	0.62	1424.05	1949.05
	1.000	650.00	0.00	0.00	576.90	705.00	586.47	0.00	586.51	3.80	2.23	527.43	361.68
	1.000	650.00	0.00	0.00	576.90	705.00	586.57	0.00	586.61	3.81	2.24	490.70	331.31
	2.000	1.00	586.20	583.90	576.90	705.00	586.47	0.00	586.51	2.62	0.99	471.26	435.41
	2.000	1.00	586.20	583.90	576.90	705.00	586.57	0.00	586.61	2.66	1.00	435.21	432.56
	3.000	66.00	584.20	583.90	576.90	705.00	586.49	0.00	586.53	2.51	0.97	476.26	444.91
	3.000	66.00	584.20	583.90	576.90	705.00	586.56	0.00	586.63	2.54	0.99	442.85	441.96
	4.000	1.00	0.00	0.00	576.90	705.00	586.47	0.00	586.53	4.90	2.53	528.52	318.43
	4.000	1.00	0.00	0.00	576.90	705.00	586.57	0.00	586.63	4.96	2.51	492.03	317.18
	5.000	730.00	0.00	0.00	578.60	730.00	586.56	0.00	586.56	0.12	0.32	2341.72	2108.51
	5.000	730.00	0.00	0.00	578.60	730.00	586.66	0.00	586.68	0.12	0.33	2226.84	2106.99
	6.000	700.00	0.00	0.00	578.90	730.00	586.57	0.00	586.57	0.17	0.36	1977.91	1766.85
	6.000	700.00	0.00	0.00	578.90	730.00	586.67	0.00	586.67	0.17	0.37	1876.30	1763.33
	1964.000	2450.00	0.00	0.00	580.90	730.00	586.39	0.00	586.77	15.13	6.46	517.61	171.23
	1966.000	2450.00	0.00	0.00	580.70	730.00	586.49	0.00	586.86	18.31	6.52	469.36	170.67
	2044.000	100.00	0.00	0.00	580.70	730.00	586.71	0.00	587.11	29.96	5.80	360.60	133.41
	2044.000	100.00	0.00	0.00	580.70	730.00	586.82	0.00	587.18	27.09	5.59	386.96	140.33
	2045.000	1.00	585.55	584.07	580.70	730.00	587.13	586.70	587.21	34.64	3.09	453.20	123.68
	2045.000	1.00	585.65	584.07	580.70	730.00	587.21	0.00	587.27	29.72	3.39	479.00	133.91
	2074.000	29.00	585.65	584.07	580.70	495.00	587.26	0.00	587.26	12.29	2.31	496.78	141.20
	2074.000	29.00	585.65	584.07	580.70	495.00	587.32	0.00	587.34	10.92	2.18	517.45	149.91
	2075.000	1.00	0.00	0.00	580.70	495.00	587.24	0.00	587.31	6.38	2.85	535.69	195.94
	2075.000	1.00	0.00	0.00	580.70	495.00	587.29	0.00	587.36	5.86	2.75	578.00	204.16
	2100.000	25.00	0.00	0.00	580.70	495.00	587.25	0.00	587.33	6.18	2.81	564.47	199.14
	2100.000	25.00	0.00	0.00	580.70	495.00	587.31	0.00	587.38	5.71	2.72	585.87	207.08

PRINTED IN U.S.A.
FORM 1611 GB PRINTED BY ROTARY MANIFOLD FORMS.

SECNO	XLCH	ELTRD	ELLC	ELMIN	Q	CWSEL	CRIWS	EG	1UK*S	VCH	AREA	.01K
3073.000	973.00	0.00	0.00	581.08	495.00	587.71	0.00	587.74	2.89	2.14	934.53	291.38
3073.000	973.00	0.00	0.00	581.08	495.00	587.74	0.00	587.77	2.77	2.10	950.03	297.15
4573.000	1500.00	0.00	0.00	581.90	495.00	588.36	0.00	588.47	8.23	3.43	626.93	172.57
4573.000	1500.00	0.00	0.00	581.90	495.00	588.37	0.00	588.47	8.06	3.40	633.77	174.30
6337.500	1764.50	0.00	0.00	584.83	495.00	589.60	0.00	589.68	5.69	2.85	313.04	207.45
6337.500	1764.50	0.00	0.00	584.83	495.00	589.60	0.00	589.67	5.71	2.85	312.68	207.12
6527.000	190.00	0.00	0.00	584.80	495.00	589.73	0.00	589.81	8.65	0.35	321.53	168.34
6527.000	190.00	0.00	0.00	584.80	495.00	589.73	0.00	589.81	8.69	0.35	321.09	167.93
6537.500	10.00	0.00	0.00	585.00	495.00	589.81	0.00	589.85	243.71	1.56	317.06	31.71
6537.500	10.00	0.00	0.00	585.00	495.00	589.81	0.00	589.85	244.39	1.56	316.79	31.68
6538.500	1.00	592.60	591.80	585.00	495.00	589.81	0.00	589.85	1.51	1.66	298.09	402.31
6538.500	1.00	592.60	591.80	585.00	495.00	589.81	0.00	589.85	1.52	1.66	298.68	401.84
6578.000	39.50	592.60	591.80	585.00	495.00	589.82	0.00	589.86	1.51	1.66	298.85	402.23
6578.000	39.50	592.60	591.80	585.00	495.00	589.81	0.00	589.86	1.52	1.66	298.64	401.76
6579.000	1.00	0.00	0.00	585.00	495.00	589.82	0.00	589.86	2.43	1.56	317.43	317.68
6579.000	1.00	0.00	0.00	585.00	495.00	589.82	0.00	589.86	2.43	1.56	317.18	317.28
6609.000	30.00	0.00	0.00	584.90	495.00	589.79	0.00	589.94	10.73	3.12	161.18	151.08
6609.000	30.00	0.00	0.00	584.90	495.00	589.78	0.00	589.94	10.77	3.12	161.01	150.84
7174.000	567.00	0.00	0.00	585.05	495.00	590.36	0.00	590.57	11.62	4.25	198.96	145.20
7174.000	567.00	0.00	0.00	585.05	495.00	590.36	0.00	590.57	11.63	4.26	198.80	145.12
7274.000	100.00	0.00	0.00	585.05	495.00	590.31	0.00	591.00	31.91	8.64	74.57	87.62
7274.000	100.00	0.00	0.00	585.05	495.00	590.31	0.00	591.03	31.75	8.64	74.54	87.57
7373.000	99.00	592.37	589.36	585.05	495.00	591.26	0.00	591.70	21.26	5.35	92.34	105.67
7373.000	99.00	592.37	589.36	585.05	495.00	591.25	0.00	591.70	21.96	5.35	92.81	105.62
7398.000	25.00	0.00	0.00	585.05	495.00	591.59	0.00	591.80	7.53	4.05	181.02	180.62
7398.000	25.00	0.00	0.00	585.05	495.00	591.59	0.00	591.80	7.52	4.05	180.94	180.52
8573.000	1175.00	0.00	0.00	585.50	495.00	592.40	0.00	592.46	4.54	2.91	600.60	240.43
8573.000	1175.00	0.00	0.00	585.50	495.00	592.43	0.00	592.50	4.69	3.07	480.76	228.68
9000.000	427.00	0.00	0.00	586.98	495.00	592.59	0.00	592.74	8.82	4.07	439.27	166.72
9000.000	427.00	0.00	0.00	586.98	495.00	592.63	0.00	592.80	9.41	4.22	382.32	161.39
9500.000	500.00	0.00	0.00	586.54	495.00	593.06	0.00	593.23	10.34	4.36	412.81	153.93
9500.000	500.00	0.00	0.00	586.54	495.00	593.11	0.00	593.31	10.74	4.47	333.22	151.07
10173.000	673.00	0.00	0.00	587.10	495.00	593.76	0.00	593.90	11.74	5.08	325.43	144.45
10173.000	673.00	0.00	0.00	587.10	495.00	593.69	0.00	594.06	11.06	5.16	279.09	143.72
11673.000	1500.00	0.00	0.00	588.76	495.00	595.17	0.00	595.31	6.49	3.73	336.41	155.09
11673.000	1500.00	0.00	0.00	588.76	495.00	595.27	0.00	595.41	6.50	3.77	300.37	152.98
12356.000	683.00	0.00	0.00	589.68	495.00	595.71	0.00	596.06	15.26	5.34	154.51	99.84
12356.000	683.00	0.00	0.00	589.68	495.00	595.81	0.00	596.14	14.15	5.20	163.52	103.69

PRINTED IN U.S.A.
FORM 1411-OD PRINTED BY ROTARY MANIFOLD FORMS

	SECNO	XLCH	ELTRD	ELLC	ELMIN	Q	CWSEL	CRIWS	EG	10K*S	VCH	AREA	.01K
	12456.000	191.00	0.00	0.00	590.00	390.00	596.17	0.00	596.35	9.77	3.40	114.55	124.79
	12456.000	191.00	0.00	0.00	590.00	390.00	596.23	0.00	596.40	9.43	3.37	115.88	127.03
	12612.000	156.00	602.60	596.40	590.40	390.00	597.25	0.00	597.45	10.34	3.65	106.82	121.30
	12612.000	156.00	602.60	596.40	590.40	390.00	597.31	0.00	597.51	10.03	3.61	107.91	123.17
	12647.000	35.00	602.60	596.40	590.40	390.00	597.55	0.00	597.71	6.58	3.21	121.59	152.06
	12647.000	35.00	602.60	596.40	590.40	390.00	597.62	0.00	597.78	6.40	3.18	122.73	154.16
	12660.000	33.00	0.00	0.00	590.74	390.00	597.62	0.00	597.74	3.65	2.95	198.71	204.24
	12660.000	33.00	0.00	0.00	590.74	390.00	597.69	0.00	597.80	3.53	2.90	201.04	207.65
	12715.000	55.00	0.00	0.00	590.90	390.00	597.60	0.00	597.80	10.07	3.54	110.16	122.92
	12715.000	55.00	0.00	0.00	590.90	390.00	597.67	0.00	597.86	9.77	3.50	111.28	124.80
*	12979.000	264.00	100000.00	100000.00	591.10	390.00	599.60	0.00	599.72	5.36	2.78	140.50	168.41
*	12979.000	264.00	100000.00	100000.00	591.10	390.00	599.60	0.00	599.72	5.36	2.78	140.50	168.41
	13030.000	51.00	0.00	0.00	589.84	735.00	599.62	0.00	599.75	4.44	4.03	556.75	348.93
	13030.000	51.00	0.00	0.00	589.84	735.00	599.62	0.00	599.75	4.44	4.03	556.75	348.93
	13473.000	443.00	0.00	0.00	590.19	735.00	599.83	0.00	599.83	1.99	2.01	1671.77	697.10
	13473.000	443.00	0.00	0.00	590.19	735.00	599.85	0.00	599.88	1.81	2.56	1087.73	546.56
	13909.000	436.00	0.00	0.00	590.46	735.00	599.88	0.00	599.89	0.71	1.57	2229.33	872.95
	13909.000	436.00	0.00	0.00	590.46	735.00	599.93	0.00	599.95	1.39	2.20	1279.78	622.90
	14009.000	100.00	0.00	0.00	591.21	735.00	599.89	0.00	599.90	0.99	1.76	2036.33	739.82
	14009.000	100.00	0.00	0.00	591.21	735.00	599.96	0.00	599.97	1.53	2.22	1252.31	593.47
	14010.000	1.00	599.19	598.50	591.21	735.00	599.55	598.11	600.25	70.46	8.28	314.24	87.57
	14010.000	1.00	599.19	598.50	591.21	735.00	599.58	597.41	600.34	73.00	8.47	274.56	85.96
	14090.000	80.00	599.19	598.50	591.21	735.00	600.56	0.00	600.62	11.41	3.71	907.61	219.48
	14090.000	80.00	599.19	598.50	591.21	735.00	600.63	0.00	600.75	14.27	4.22	723.50	194.57
	14091.000	1.00	1.00	0.00	591.21	735.00	600.66	0.00	600.64	0.34	1.20	2732.65	1262.78
	14091.000	1.00	1.00	0.00	591.21	735.00	600.77	0.00	600.78	0.43	1.46	2037.79	1120.60
	14116.000	25.00	1.00	0.00	591.21	735.00	600.66	0.00	600.64	0.34	1.20	2736.72	1266.35
	14116.000	25.00	1.00	0.00	591.21	735.00	600.78	0.00	600.78	0.38	1.37	2271.58	1168.91
	14673.000	557.00	0.00	0.00	592.07	735.00	600.66	0.00	600.67	1.10	1.81	1986.87	701.04
	14673.000	557.00	0.00	0.00	592.07	735.00	600.81	0.00	600.82	1.09	1.83	1826.94	703.37
	15262.000	589.00	0.00	0.00	592.31	735.00	600.72	0.00	600.73	0.95	1.47	1730.69	758.41
	15262.000	589.00	0.00	0.00	592.31	735.00	600.86	0.00	600.87	0.84	1.41	1809.72	799.64
	15362.000	100.00	0.00	0.00	592.31	735.00	600.70	0.00	600.79	6.50	3.04	767.30	288.37
	15362.000	100.00	0.00	0.00	592.31	735.00	600.84	0.00	600.93	6.11	2.98	726.29	297.38
	15363.000	1.00	599.90	597.20	592.31	735.00	600.77	0.00	600.80	6.72	2.43	761.26	283.36
	15363.000	1.00	599.90	597.20	592.31	735.00	600.90	0.00	600.94	6.44	2.42	710.13	289.61
	15434.000	71.00	599.90	597.20	592.31	735.00	600.82	0.00	600.83	6.13	2.34	787.76	296.85
	15434.000	71.00	599.90	597.20	592.31	735.00	600.95	0.00	600.99	5.97	2.34	729.92	306.76

PRINTED IN U.S.A.
FORM 1011-DD-PRINTED BY ROTARY MANIFOLD FORMS

SECNO	XLCH	ELTRD	ELLC	ELMIN	Q	CWSEL	CRIWS	EG	10K*S	VCH	AREA	.01K
15435.000	1.00	0.00	0.00	592.31	735.00	600.81	0.00	600.86	3.76	2.34	834.37	378.96
15435.000	1.00	0.00	0.00	592.31	735.00	600.95	0.00	600.99	3.66	2.33	776.19	303.93
15460.000	25.00	0.00	0.00	592.31	735.00	600.82	0.00	600.87	3.72	2.32	838.78	361.31
15460.000	25.00	0.00	0.00	592.31	735.00	600.96	0.00	601.00	3.63	2.32	779.59	385.94
16873.000	1413.00	0.00	0.00	592.80	735.00	601.32	0.00	601.36	3.26	2.78	1020.79	407.15
16073.000	1413.00	0.00	0.00	592.80	735.00	601.43	0.00	601.46	2.92	2.66	1068.52	430.56
17673.000	800.00	0.00	0.00	593.32	735.00	601.58	0.00	601.66	5.74	3.53	723.95	306.85
17673.000	800.00	0.00	0.00	593.32	735.00	601.66	0.00	601.73	5.33	3.42	746.57	318.44

PRINTED IN U.S.A.
FORM 1811-GS PRINTED BY ROTARY-MANIFOLD FORMS

SILVER CREEK

SUMMARY PRINTOUT TABLE 150

SECNO	Q	CHSEL	DIFWSP	DIFWSX	DIFKWS	TOPWID	XLCH
0.050	705.00	586.48	0.00	0.00	0.00	250.00	0.00
0.000	705.00	586.58	0.00	0.00	0.10	250.00	0.00
1.000	705.00	586.47	0.00	-0.01	0.00	372.28	450.00
1.000	705.00	586.57	0.00	-0.01	0.10	249.38	450.00
2.000	705.00	586.47	0.00	0.00	0.00	371.25	1.00
2.000	705.00	586.57	0.00	0.00	0.09	247.10	1.00
3.000	705.00	586.49	0.00	0.01	0.00	373.60	46.00
3.000	705.00	586.59	0.00	0.01	0.10	252.23	46.00
4.000	705.00	586.47	0.00	-0.01	0.00	372.65	1.00
4.000	705.00	586.57	0.00	-0.01	0.10	247.10	1.00
5.000	730.00	586.56	0.00	0.09	0.00	595.87	730.00
5.000	730.00	586.66	0.00	0.09	0.10	451.56	730.00
6.000	730.00	586.57	0.00	0.01	0.00	499.70	700.00
6.000	730.00	586.67	0.00	0.01	0.10	413.27	700.00
1944.000	730.00	586.59	0.00	0.02	0.00	374.50	2450.00
1944.000	730.00	586.69	0.00	0.02	0.09	251.33	2450.00
2044.000	730.00	586.71	0.00	0.12	0.00	374.36	100.00
2044.000	730.00	586.82	0.00	0.13	0.11	334.30	100.00
2045.000	730.00	587.13	0.00	0.42	0.00	374.57	1.00
2045.000	730.00	587.23	0.00	0.39	0.06	373.61	1.00
2074.000	495.00	587.26	0.00	0.13	0.00	374.63	29.00
2074.000	495.00	587.32	0.00	0.11	0.06	374.66	29.00
2075.000	495.00	587.24	0.00	-0.02	0.00	374.62	1.00
2075.000	495.00	587.29	0.00	-0.02	0.06	374.65	1.00
2100.000	495.00	587.25	0.00	0.02	0.00	374.65	25.00
2100.000	495.00	587.31	0.00	0.02	0.06	374.66	25.00
3073.000	495.00	587.71	0.00	0.48	0.00	510.42	973.00
3073.000	495.00	587.74	0.00	0.45	0.03	515.25	973.00
4573.000	495.00	588.36	0.00	0.63	0.00	538.24	1500.00
4573.000	495.00	588.37	0.00	0.63	0.01	538.87	1500.00
6337.500	495.00	589.60	0.00	1.24	0.00	97.03	1764.50
6537.500	495.00	589.60	0.00	1.23	-0.20	97.00	1764.50
6527.000	495.00	589.73	0.00	0.13	0.00	90.00	190.00
6527.000	495.00	589.73	0.00	0.13	-0.00	90.00	190.00
6537.500	495.00	589.81	0.00	0.08	0.00	34.60	10.00
6537.500	495.00	589.81	0.00	0.08	-0.00	34.40	10.00

PRINTED IN U.S.A.
FORM 1415-D PRINTED BY ROTARY MANIFOLD FORMS.

SECNO	Q	CWSEL	DIFXSP	DIFWSX	DIFKWS	TOPWID	XLCH
6538.500	495.00	589.81	0.00	-0.00	0.00	84.40	1.00
6538.500	495.00	589.81	0.00	-0.00	-0.00	84.40	1.00
6578.000	495.00	589.82	0.00	0.01	0.00	84.40	39.50
6578.000	495.00	589.81	0.00	0.01	-0.00	84.40	39.50
6579.000	495.00	589.82	0.00	0.01	0.00	84.40	1.00
6579.000	495.00	589.82	0.00	0.01	-0.00	84.40	1.00
6609.000	495.00	589.79	0.00	-0.03	0.00	54.62	50.00
6609.000	495.00	589.78	0.00	-0.03	-0.00	54.58	50.00
7174.000	495.00	590.38	0.00	0.59	0.00	65.00	547.00
7174.000	495.00	590.30	0.00	0.59	-0.00	65.00	547.00
7274.000	495.00	590.31	0.00	-0.06	0.00	14.95	100.00
7274.000	495.00	590.31	0.00	-0.06	-0.00	14.95	100.00
7373.000	495.00	591.26	0.00	0.94	0.00	14.95	99.00
7373.000	495.00	591.26	0.00	0.94	-0.00	14.95	99.00
7398.000	495.00	591.59	0.00	0.33	0.00	40.41	25.00
7398.000	495.00	591.59	0.00	0.33	-0.00	40.40	25.00
8573.000	495.00	592.40	0.00	0.81	0.00	554.68	1175.00
8573.000	495.00	592.43	0.00	0.84	0.02	279.76	1175.00
9030.000	495.00	592.59	0.00	0.15	0.00	465.62	427.00
9030.000	495.00	592.63	0.00	0.20	0.04	223.45	427.00
9530.000	495.00	593.04	0.00	0.45	0.00	426.66	500.00
9530.000	495.00	593.11	0.00	0.48	0.07	212.56	500.00
10173.000	495.00	593.74	0.00	0.72	0.00	252.86	673.00
10173.000	495.00	593.15	0.00	0.76	0.09	163.88	673.00
11673.000	390.00	595.17	0.00	1.41	0.00	270.19	1500.00
11673.000	390.00	595.27	0.00	1.42	0.10	166.46	1500.00
12356.000	390.00	595.71	0.00	0.34	0.00	92.37	683.00
12356.000	390.00	595.81	0.00	0.54	0.10	96.91	683.00
12656.000	390.00	596.17	0.00	0.45	0.00	22.00	191.00
12656.000	390.00	596.25	0.00	0.42	0.08	22.00	191.00
12612.000	390.00	597.25	0.00	1.08	0.00	17.00	156.00
12612.000	390.00	597.31	0.00	1.08	0.06	17.00	156.00
12647.000	390.00	597.55	0.00	0.31	0.00	17.00	35.00
12647.000	390.00	597.62	0.00	0.31	0.07	17.00	35.00
12661.000	390.00	597.62	0.00	0.07	0.00	35.00	14.00
12661.000	390.00	597.69	0.00	0.07	0.07	35.00	14.00
12715.000	390.00	597.60	0.00	-0.02	0.00	17.00	35.00
12715.000	390.00	597.67	0.00	-0.02	0.07	17.00	35.00

PRINTED IN U.S.A.
FORM 1411-GD PRINTED BY ROTARY MANIFOLD FORMS.

	SECNO	Q	CWSEL	DIFWSP	DIFWSX	DIFKWS	TOPWID	XLCH
*	12979.000	390.00	599.60	0.00	2.00	0.00	17.00	264.00
*	12979.000	390.00	599.60	0.00	1.93	0.00	17.00	264.00
	13030.000	735.00	599.62	0.00	0.02	0.00	120.00	51.00
	13030.000	735.00	599.62	0.00	0.02	0.00	120.00	51.00
	13473.000	735.00	599.83	0.00	0.22	0.00	657.12	443.00
	13473.000	735.00	599.83	0.00	0.23	0.01	300.00	443.00
	13909.000	735.00	599.88	0.00	0.05	0.00	700.00	436.00
	13909.000	735.00	599.93	0.00	0.09	0.05	300.00	436.00
	14009.000	735.00	599.89	0.00	0.01	0.00	738.73	100.00
	14009.000	735.00	599.95	0.00	0.02	0.06	300.00	100.00
	14010.000	735.00	599.95	0.00	-0.34	0.00	603.12	1.00
	14010.000	735.00	599.58	0.00	-0.37	0.03	300.00	1.00
	14090.000	735.00	600.34	0.00	1.00	0.00	751.62	80.00
	14090.000	735.00	600.43	0.00	1.05	0.09	400.00	80.00
	14091.000	735.00	600.66	0.00	0.09	0.00	751.43	1.00
	14091.000	735.00	600.77	0.00	0.14	0.14	400.00	1.00
	14116.000	735.00	600.64	0.00	0.00	0.00	751.47	25.00
	14116.000	735.00	600.78	0.00	0.00	0.14	451.45	25.00
	14673.000	735.00	600.66	0.00	0.03	0.00	790.53	557.00
	14673.000	735.00	600.81	0.00	0.03	0.14	570.09	557.00
	15262.000	735.00	600.72	0.00	0.06	0.00	500.54	589.00
	15262.000	735.00	600.86	0.00	0.03	0.14	501.32	589.00
	15362.000	735.00	600.70	0.00	-0.02	0.00	565.24	100.00
	15362.000	735.00	600.84	0.00	-0.02	0.14	450.14	100.00
	15365.000	735.00	600.77	0.00	0.07	0.00	565.21	1.00
	15365.000	735.00	600.90	0.00	0.06	0.14	450.15	1.00
	15434.000	735.00	600.32	0.00	-0.05	0.00	565.25	71.00
	15434.000	735.00	600.95	0.00	0.05	0.13	450.15	71.00
	15435.000	735.00	600.81	0.00	-0.00	0.00	565.22	1.00
	15435.000	735.00	600.95	0.00	-0.00	0.13	450.15	1.00
	15460.000	735.00	600.38	0.00	0.01	0.00	565.23	25.00
	15460.000	735.00	600.96	0.00	0.01	0.13	450.16	25.00
	16873.000	735.00	601.32	0.00	0.50	0.00	450.46	1413.00
	16873.000	735.00	601.43	0.00	0.47	0.11	450.46	1413.00
	17673.000	735.00	601.63	0.00	0.26	0.00	343.95	800.00
	17673.000	735.00	601.86	0.00	0.23	0.13	336.13	800.00

SUMMARY OF ERRORS

NOTE SECNO=12979.000 PROFILE# 1 ,SEL BASED ON XS CARD

NOTE SECNO=12979.000 PROFILE# 2 ,SEL BASED ON XS CARD

PRINTED IN U.S.A.

FORM 1A1-08-PRINTED BY ROTARY MANIFOLD FORMS.

FLOODWAY DATA, SILVER CREEK
PROFILE NO. 2

STATION	FLOODWAY WIDTH (FT)	FLOODWAY SECTION AREA	FLOODWAY MEAN VELOCITY	WATER SURFACE ELEVATION WITH FLOODWAY	WATER SURFACE ELEVATION WITHOUT FLOODWAY	WATER SURFACE ELEVATION DIFFERENCE
0.000	250.	1424.	0.5	586.6	586.5	0.1
1.000	249.	491.	1.4	586.6	586.5	0.1
2.000	267.	435.	1.6	586.6	586.5	0.1
3.000	252.	443.	1.6	586.6	586.5	0.1
4.000	247.	492.	1.4	586.6	586.5	0.1
5.000	682.	2225.	0.3	586.7	586.6	0.1
6.000	413.	1876.	0.4	586.7	586.6	0.1
1844.000	251.	452.	1.6	586.7	586.6	0.1
2044.000	324.	367.	2.0	586.8	586.7	0.1
2045.000	375.	479.	1.5	587.2	587.1	0.1
2074.000	375.	517.	1.0	587.4	587.3	0.1
2075.000	375.	578.	0.9	587.3	587.2	0.1
2100.000	373.	586.	0.8	587.4	587.3	0.1
3073.000	513.	951.	0.5	587.7	587.7	0.0
4573.000	459.	634.	0.8	589.4	589.4	0.0
6337.500	97.	313.	1.6	589.6	589.6	0.0
6527.000	90.	321.	1.5	589.7	589.7	0.0
6537.500	84.	317.	1.6	589.8	589.8	0.0
6550.500	86.	299.	1.7	589.8	589.8	0.0
6573.000	84.	299.	1.7	589.8	589.8	0.0
6579.000	84.	317.	1.6	589.8	589.8	0.0
6609.000	53.	161.	3.1	589.8	589.8	0.0
7174.000	65.	199.	2.5	590.4	590.4	0.0
7273.000	15.	75.	6.0	590.3	590.3	0.0
7373.000	15.	95.	5.3	591.3	591.3	0.0
7378.000	60.	101.	2.7	591.6	591.6	0.0
8529.000	230.	459.	1.1	592.6	592.6	0.0
9000.000	220.	362.	1.4	592.6	592.6	0.0
9500.000	213.	333.	1.5	593.1	593.0	0.1
10173.000	166.	279.	1.6	593.9	593.8	0.1
11673.000	110.	500.	1.3	595.3	595.2	0.1
12356.000	97.	164.	2.4	595.8	595.7	0.1
12456.000	32.	116.	3.4	596.3	596.2	0.1
12612.000	17.	108.	3.6	597.3	597.2	0.1
12647.000	17.	123.	3.2	597.7	597.6	0.1
12680.000	35.	204.	1.9	597.7	597.6	0.1
12715.000	17.	111.	3.5	597.7	597.6	0.1
12979.000	67.	141.	2.0	599.6	599.6	0.0
13030.000	120.	562.	1.0	599.6	599.6	0.0
13473.000	300.	1068.	0.7	599.8	599.8	0.0
13909.000	300.	1279.	0.6	599.9	599.9	0.0
14009.000	300.	1352.	0.6	600.0	599.9	0.1
14010.000	100.	2356.	2.7	599.5	599.5	0.0
14090.000	400.	724.	1.0	600.6	600.5	0.1
14091.000	400.	2085.	0.4	600.7	600.6	0.1
14116.000	451.	2272.	0.3	600.7	600.6	0.1
14673.000	570.	1025.	0.4	600.8	600.7	0.1
15262.000	500.	1810.	0.4	600.8	600.7	0.1
15362.000	450.	726.	1.0	600.8	600.7	0.1
15363.000	450.	710.	1.0	600.9	600.8	0.1

PRINTED IN U.S.A.
FORM 1411-00 PRINTED BY ROTARY MANIFOLD FORMS.

FLOODWAY DATA, SILVER CREEK
PROFILE NO. 2

STATION	FLOODWAY WIDTH (FT)	FLOODWAY SECTION AREA	FLOODWAY MEAN VELOCITY	WATER SURFACE ELEVATION WITH FLOODWAY	WITHOUT FLOODWAY	DIFFERENCE
15434.000	450.	730.	1.0	600.9	600.8	0.1
AB15435.000	450.	775.	0.9	600.9	600.8	0.1
15660.000	450.	760.	0.9	600.9	600.8	0.1
AC16873.000	450.	1069.	0.7	601.4	601.3	0.1
AD17673.000	314.	747.	1.0	601.7	601.6	0.1

PRINTED IN U.S.A.
FORM 1811-QD PRINTED BY ROTARY MANIFOLD FORMS.

```
**************************************************
  REC2 RELEASE DATED NOV 76 UPDATED FEB 1977
  ERROR CORR - 01
  MODIFICATION - 50,51,52
**************************************************
```

PRINTED IN U.S.A.
FORM 1411-GG PRINTED BY ROTARY MANIFOLD FORMS.

```
**********************************************************************
*                                                                    *
*                        E R R O R   S U M M A R Y                   *
*                                                                    *
*       0  ERROR(S) DETECTED BY THE USER PROGRAM                     *
*       0  ERROR(S) DETECTED BY THE MATHEMATICAL PACKAGE             *
*       0  ERROR(S) DETECTED FOR INPUT/OUPUT STATEMENTS              *
*                                                                    *
**********************************************************************
```

PRINTED IN U.S.A.
FORM 1411-05 PRINTED BY ROTARY MANIFOLD FORMS

00BREAK00

1) COUNTY: Wayne

2) STUDY NAME: City of Flat Rock

3) WATERCOURSE: Silver Creek

4) DOCUMENT TYPE: Rating Curve

00BREAK00

```
**************************************************
  HEC2 RELEASE DATED NOV 76 UPDATED FEB 1977
  ERROR CORR -  01
  MODIFICATION -  50,51,52
**************************************************

C
T1OVERLAND FLOW BETWEEN SILVER AND SMITH CREEKS
T2CITY OF FLAT ROCK FIS, FLOW DIVERSION ANALYSIS
T3      SILVER TO SMITH RAT.CURVE.

J1  ICHECK    INQ      NINV     IDIR     STRT     METRIC   HVINS    Q        WSEL     FQ
        0.       2.       0.       0.  0.000000     0.00     0.0      0.   598.600   0.000

J2  NPROF     IPLOT    PRFVS    XSECV    XSECH    FN       ALLDC    IBW      CHNIM    ITRACE
    1.000     0.000   -1.000    0.000    0.000    0.000    0.000    0.000    0.000    0.000

J5  LPRNT     NUMSEC                    ********REQUESTED SECTION NUMBERS********
   -10.000   -10.000    0.000    0.000    0.000    0.000    0.000    0.000    0.000    0.000
QT   5.000    50.000   100.000   200.000   300.000   400.000    0.000    0.000    0.000    0.000
NC   0.200     0.200     0.200     0.100     0.300     0.000    0.000    0.000    0.000    0.000

      LOCATION IS 200' RT.& PARALLEL TO SMITH CREEK FROM WTA FL.PLAIN STUDY.
X1    1.000    10.000   100.000  1025.000     0.000     0.000     0.000     0.000     0.000     0.000
GR  600.000     0.000   598.600   100.000   598.000   150.000   597.000   230.000   596.600   300.000
GR  597.000   400.000   598.000   635.000   598.600  1025.000   599.000  1075.000   600.000  1150.000

      RIDGE LINE BETWEEN SMITH & SILVER CREEK BASINS.
X1    2.000     5.000     1.000  1250.000   800.000  1000.000   900.000     0.000     0.000     0.000
GR  603.000     1.000   600.000   400.000   599.000   600.000   600.000   850.000   603.000  1250.000
EJ    0.000     0.000     0.000     0.000     0.000     0.000     0.000     0.000     0.000     0.000

***** H2MAIN                SOURCE LINE:  3086        ERROR:    9
ERROR STATEMENT APPLIES TO SECTION
```

****
HEC2 RELEASE DATED NOV 76 UPDATED FEB 1977
ERROR CORR - 01
MODIFICATION - 50,51,52
****

HUD200907
9/13/79

NOTE- ASTERISK (*) AT LEFT OF CROSS-SECTION NUMBER INDICATES MESSAGE IN SUMMARY OF ERRORS LIST

SILVER TO SMITH RAT.CURV

SUMMARY PRINTOUT TABLE 150

	SECNO	XLCH	ELTRD	ELLC	ELMIN	Q	CWSEL	CRIWS	EG	10K*S	VCH	AREA	.01K
	1.000	0.00	0.00	0.00	596.60	50.00	598.60	0.00	598.60	0.92	0.06	784.56	52.23
	1.000	0.00	0.00	0.00	596.60	100.00	598.60	0.00	598.60	3.67	0.13	784.56	52.23
	1.000	0.00	0.00	0.00	596.60	200.00	598.60	0.00	598.60	14.66	0.25	784.56	52.23
	1.000	0.00	0.00	0.00	596.60	300.00	598.60	0.00	598.60	32.99	0.38	784.56	52.23
	1.000	0.00	0.00	0.00	596.60	400.00	598.60	0.00	598.60	58.65	0.51	784.56	52.23
*	2.000	900.00	0.00	0.00	599.00	50.00	599.31	599.31	599.39	10868.00	2.25	22.18	0.48
	2.000	900.00	0.00	0.00	599.00	100.00	599.72	0.00	599.73	520.04	0.86	116.63	4.39
	2.000	900.00	0.00	0.00	599.00	200.00	600.54	0.00	600.55	34.95	0.40	506.27	33.83
	2.000	900.00	0.00	0.00	599.00	300.00	600.99	0.00	600.99	21.88	0.38	799.79	64.14
	2.000	900.00	0.00	0.00	599.00	400.00	601.31	0.00	601.32	18.31	0.38	1050.50	93.49

00BREAK00

1) COUNTY: Wayne

2) STUDY NAME: City of Flat Rock

3) WATERCOURSE: Silver Creek

4) DOCUMENT TYPE: Report

00BREAK00

Wade, Trim & Associates, Inc.
Civil Engineers • Land Surveyors • Community Planners
Taylor, Michigan

February 12, 1980

Michigan Department of Natural Resources
Flood Insurance and Flood Plain Delineation Unit
Water Management Division
Stevens T. Mason Building
P. O. Box 30028
Lansing, Michigan 48909

FEB 15 1980

Attention: Mr. Dan Morgan

Re: Engineering Contract H-4542
Silver Creek Hydraulic Analysis

Gentlemen:

Enclosed is a report which describes the amended hydraulic study for Silver Creek which is associated with the City of Flat Rock - Michigan Flood Insurance Administration Study performed by this office. This report incorporates your comments of December 13, 1979, and is supplemental to the report which was submitted to you on October 17, 1979. Your review and approval of this report are requested.

Please contact William J. Weaver of this office if you have any questions.

Very truly yours,

WADE, TRIM & ASSOCIATES, INC.

Glen A. Roberts

GAR:WJW:gf
HUD 2009-07
Enclosures
cc: Mr. Martin Gunn, Federal Emergency Management Agency
Mr. Wallace Weaver, Federal Emergency Management Agency

TABLE OF CONTENTS

SILVER CREEK EXHIBITS

EXHIBIT NO.	DESCRIPTION
1.	Flood Hazard, Floodway and Cross Section Location Map
2.	Bridge Sketches, Notes and Computations (In 10/17/79 Submittal)
3.	Computer Printouts, HEC-2 Backwater Analysis (See Separate Folder)
4.	Stream Profile
11.	Flow Diversion Analysis
13.	TR-20 Flood Routing Analysis (See Separate Folder)

II. SILVER CREEK (DETAILED)

Detailed studies of the Silver Creek were performed from the corporate boundary of Flat Rock/Rockwood to the corporate boundary of Flat Rock/Brownstown. To ensure continuity, initial cross sections were the upstream sections used in the Rockwood Flood Insurance Study (FIS) of Silver Creek (Reference 1). A total of 8 valley and 6 bridge cross sections were field surveyed and completed in May, 1978. An additional 24 cross sections were used in this analysis. These sections were based on interpolation of field survey data and U.S.G.S. Quad Maps of the study area which consist of 5 foot interval contour data (Reference 2). The flood plain of the Silver Creek within the study reach varies from grassy to heavy woods.

Cross section locations are shown in Exhibit 1. Table 1 cross references section designations by showing the computer section number which corresponds to the cross section letters shown in Exhibit 1.

Exhibit 2 contains bridge sketches as well as computations of total bridge loss coefficients. The Gibraltar Road and the Telegraph Road bridges were considered to be skewed.

Table 2 lists discharges that have been approved by the Michigan Department of Natural Resources (MDNR) for this Creek.

A. METHOD OF ANALYSIS

The HEC-2 backwater program was used in developing water surface profiles (Reference 3).

Table 2 also contains selected flood elevations from the HEC-2 printouts. HEC-2 printouts including computer cross section plots are presented as Exhibit 3. Water surface profiles resulting from the backwater analyses are presented as Exhibit 4. (Exhibit 3 is contained in the 11" x 15" folder enclosed with this report.)

B. VARIABLES AND COEFFICIENTS

Roughness coefficients (Mannings "n") were estimated by field inspection at each cross section. Typical roughness values for the main channel range from .015 to .040; roughness values for the overbank areas vary between .018 to .12 for all floods. These values are indicative of summer month conditions and are consistent with roughness values recommended and used in engineering practice.

Expansion coefficients vary from .3 to .5 and contraction coefficients vary from .1 to .3. Expansion and contraction ratios used in effective flow modeling for all bridge sections and natural constrictions are 1:4 and 1:1 respectively.

C. HIGH WATER MARKS

No documented high water data exists for flood elevations on Silver Creek.

D. STARTING CONDITIONS

Starting water surface elevations used in all backwater computations were the flood elevations at the Flat Rock/Rockwood corporate boundary as determined in the Rockwood FIS (Reference 1).

E. SPECIAL PROBLEMS

The D.T.&I. Railroad corridor causes a major constriction to flow on Silver Creek due to inadequately designed culverts. This constriction is so extensive that it causes a transfer of flow between the Silver Creek, Smith Creek, Cook and Gladding Drain and Huron River basins during major floods. Analysis of inflow hydrographs and resulting peak elevations for all the basins involved and review of a flood routing study on Smith Creek (Reference 6) indicates the following:

1. A 100 year flood in the Smith Creek basin will not cause a diversion of flow to Silver Creek and alter peak flow rates.

2. The 10, 50, 100 and 500 year floods in the Silver Creek basin will create flow diversions to Cook and Gladding Drain, Huron River and Smith Creek.

Therefore, a flow diversion analysis (Exhibit 11) was performed to determine the effect on peak flow rates in the Silver Creek basin and to establish flow distributions for all floods analyzed in this report. The flow diversion analysis was performed as follows:

1. Flood elevations were determined on Silver Creek with the assumption that there would be no diversions of flow (See WTA submittal dated June 20, 1979, Exhibit 3). The resulting 100 year flood elevation upstream of the D.T.&I. Railroad corridor was 602.51.

2. Stage/discharge rating curves were developed for the following:

   a. Overland flow from the Silver Creek basin to the Cook and Gladding Drain basin (Exhibit 11, Page 4).

   b. Overland flow from the Silver Creek basin to the Smith Creek basin (Exhibit 11, Page 6).

   c. A 42" culvert on a tributary to Silver Creek upstream of the D.T.&I. Railroad corridor (Exhibit 11, Page 5).

   d. D.T.&I. Railroad culverts on Silver Creek (Exhibit 11, Page 7).

3. All four of the stage/discharge rating curves above were combined to form a total rating curve for the area upstream of the D.T.&I. Railroad corridor (Exhibit 11, Page 9).

4. A stage/storage curve (Exhibit 11, Page 8) was developed for the areas upstream of the railroad corridor in the Silver Creek basin which will be inundated during major floods.

5. A flood routing analysis (Exhibit 11, Pages 10-15) was performed for Silver Creek and curves developed in 2 and 4 above were used to determine what effect storage would have on peak flow rates.

6. Peak flow rates obtained in the flood routing analysis were applied to the total stage/discharge rating curve to determine the 10 year, 50 year, 100 year and 500 year flood elevations upstream of the railroad corridor.

7. The new flood elevations were then applied to the four stage/discharge rating curves to determine the distribution of flow between the various diversion areas and Silver Creek (Exhibit 11, Page 16).

8. The Silver Creek computer model (HEC-2) was then rerun with the new flow rates and flood elevations were externally input to the computer model upstream of the D.T.&I Railroad corridor. The resulting 100 year flood elevation is 599.6.

Results of this analysis indicate that storage upstream of the D.T.&I. Railroad corridor and the overland flow diversion to Smith Creek substantially reduce flow rates downstream of the railroad corridor on Silver Creek (approximately 47% during the 100 year flood). Furthermore, the overland flow diversion and storage created by constrictions at the railroad corridor reduce flood elevations 2.91 feet for the 100 year flood.

The flood routing analysis was performed with the TR-20 hydrologic computer model (Reference 7) and computer printouts resulting from this analysis are presented as Exhibit 13.

F. GENERAL

Computed water-surface elevations were developed to an accuracy of 0.5 foot for floods of the selected recurrence intervals.

All elevations are referenced to the National Geodetic Vertical Datum of 1929 (NGVD). This datum is equivalent to the U.S. Geological Survey (USGS) datum.

The hydraulic analyses for this study are based only on the effects of flow unobstructed by ice or debris. The flood elevations are considered valid only if hydraulic structures, in general, remain unobstructed and do not fail.

TABLE 1
CITY OF FLAT ROCK
SILVER CREEK

CROSS SECTION	COMPUTER NO.	WTA FIELD BOOK NO.	DESCRIPTION
	0		+ 450' d/s of d/s face of Olmstead Rd.
	1.0		d/s face of Olmstead Rd.
	2		
	3		
	4		u/s face of Olmstead Rd.
	5		+ 750' u/s of u/s face of Olmstead Rd.
A	6.0		+ 1450' u/s of u/s face of Olmstead Rd. (Rockwood/Flat Rock Corp. Limit)
B	2,044		d/s face of Woodruff Rd. Bridge
		156 + 29	Center Line of Woodruff Rd.
C	2,075		u/s face of Woodruff Rd. Bridge
D	3,073	146 + 00	+ 1000' u/s of u/s face of Woodruff Rd.
E	4,573	131 + 00	+ 2500' u/s of u/s face of Woodruff Rd.
	6,337.5		+ 200' d/s of d/s face of Bridge S. of Gibraltar Rd.
G	6,537.5	111 + 35.5	d/s face of Bridge S. of Gibraltar Rd.
H	6,579	110 + 96	u/s face of Bridge S. of Gibraltar Rd.
I	7,174		+ 100' d/s of d/s face of Gibraltar Rd.
J	7,274	103 + 99	d/s face of Gibraltar Rd.
K	7,373	103 + 00	u/s face of Gibraltar Rd. Bridge
L	8,573	91 + 00	+ 1200' u/s of u/s face of Gibraltar Rd.
M	9,000		Valley Section
N	9,500		Valley Section
O	10,173	75 + 00	+ 1600' u/s of u/s face of Gibraltar Rd.
P	11,673	60 + 00	+ 1500' u/s of u/s face of Gibraltar Rd.
Q	12,356		+ 100' d/s of d/s end of culverts under R.R.

TABLE 1
CITY OF FLAT ROCK
SILVER CREEK

Continued

CROSS SECTION	COMPUTER NO.	WTA FIELD BOOK NO.	DESCRIPTION
R	12,456	52 + 17	d/s end of R.R. culverts
S	12,647	50 + 26	u/s end of R.R. culverts
T	12,680		+ 33' u/s of u/s end of R.R. culverts
U	12,715	49 + 58.5	d/s end of 96" CMP
V	12,979	46 + 94	u/s end of 96" CMP
W	13,473	42 + 00	494' u/s of u/s end of 96" CMP
X	14,009	36 + 64	d/s end Vreeland Rd. culvert
Y	14,091	35 + 82	u/s end of Vreeland Rd. culvert
Z	14,673	30 + 00	582' u/s of u/s end Vreeland Rd. culvert
AA	15,362	23 + 11	d/s face Telegraph Rd. Bridge
AB	15,435	22 + 38	u/s face Telegraph Rd. Bridge
AC	16,873	8 + 00	+ 1438' u/s of Telegraph Rd. Bridge
AD	17,673		Brownstown/Flat Rock Corp. limit

TABLE 2
CITY OF FLAT ROCK
SILVER CREEK FLOOD ELEVATIONS*

LOCATION	SELECTED FREQUENCIES 10 Yr.	50 Yr.	100 Yr.	500 Yr.
	Q= 395 CFS	460 CFS	495 CFS	535 CFS
u/s of Woodruff Rd. (0.4 Mi.)	587.0	587.2	587.3	587.4
	Q= 320 CFS	365 CFS	390 CFS	415 CFS
d/s of D.T. & I. Railroad (2.4 Mi.)	595.4	595.6	595.7	595.8
	Q= 455 CFS	665 CFS	735 CFS	840 CFS
u/s of D.T. & I. Railroad Corridor (2.6 Mi.)	597.2	599.3	599.6	600.1
@ Flat Rock/Brownstown Corp. Limit (3.3 Mi.)	600.7	601.4	601.6	601.8

*N.G.V.D.

CITY OF FLAT ROCK

SILVER CREEK EXHIBIT 3

COMPUTER PRINTOUTS

HEC-2 BACKWATER ANALYSIS

(SEE SEPARATE FOLDER)

HUD 2009-07

CITY OF FLAT ROCK

SILVER CREEK

EXHIBIT 4

STREAM PROFILE

HUD 2009-07

CITY OF FLATROCK

SILVER CREEK

EXHIBIT 11

FLOW DIVERSION ANALYSIS

CITY OF FLATROCK

SILVER CREEK

EXHIBIT 13

TR-20 FLOOD ROUTING ANALYSIS

(See Separate Folder)

REFERENCE

Flatrock Routing Analysis (Silver Creek)

Stage Storage Curve Development:

① Storage = 0 at elevation 595.0

② Storage at Elevation 598.5:

= $\frac{3.5}{5}$ × Storage to 600.0 in Center Storage Area

= 2.5 (2975976) $\frac{3.5}{5}$ ft^3 = **5207958 ft^3**

= 2.5 (68.319) $\frac{3.5}{5}$ acre-ft = **119.56 acre-ft**

③ Storage at Elev. 600.0: → = **1434.7 acre-in.** ✱

= 2.5(9975976) + .8(2530224) + .8(1654296) ft^3

= **28,287,556 ft^3**

= 2.5 (68.319) + .8 (58.086) + .8 (37.9774) acre-ft

= **247.65 acre-ft** **2971.8 = acre-in.** ✱

④ Storage at Elev. 603.0:

= 28,287,556 + 3.0(2975976 + 2530224 + 1654296)

= **49,769,044 ft^3**

= 247.65 + 3.0(68.319 + 58.086 + 37.9774)

= **740.8 acre-ft** = **8889.6 acre-in.** ✱

Conversion: 1 acre-inch ≈ 1 cfs-hr.


✱ See Attached Digitizer results for area calculations


SUBJECT	BY	CHK.	SHEET NO	File Code No (Job No) Owner Project Suffix
Exhibit 11	DATE 1/12/00	DATE	1 OF 12	HUD • 203 • 00

REFERENCE

Exhibit 11
Pg 2 of 12

SUBJECT	BY	CHK.	SHEET NO.	File Code No. (Job No.) Owner Project Suffix
	DATE	DATE	2 OF 12	HUD • 2009 • 07


HUD 200907
1/13/14
W.T. Waner
Development of Stage
Storage Relationship
Silver Creek
Exhibi
11
600
608
590
580
570
560
200 STORAGE
Storage Stage Curve
Storage Stage Curve
Page 3 of 12
HUD 200907




46 1320
KE 10 X 10 TO ½ INCH 7 X 10 INCHES
KEUFFEL & ESSER CO MADE IN U.S.A.

Fig 40 f 12

Exhibit 11

HUD 200907
9/10/79
J. J. Wesser

DISCHARGE/ELEVATION RATING CURVE
TRIBUTARY TO SILVER CREEK
DT&I RAILROAD CORRIDOR



*(1) This rating curve does not become effective for diversion of flow from silver creek until elevation 600.0 is reached.

(2) The following flows must be subtracted from this rating curve before it is added to the total rating curve so that local inflow is account for.


10yr	50yr	100yr	500yr
75cfs	95cfs	105cfs	120cfs

46 1320
K&E 10 X 10 TO ½ INCH 7 X 10 INCHES KEUFFEL & ESSER CO MADE IN U.S.A.

Exhibit 11

HUD 2007 07
9/13/79

DISCHARGE/ELEVATION RATING CURVE
OVERLAND FLOW
SILVER CREEK TO SMITH CREEK




Pg 6 of 12

HUD 2004 01
9/13/79

Exhibit 11

46 1320
KE 10 X 10 TO ½ INCH 7 X 10 INCHES KEUFFEL & ESSER CO MADE IN U.S.A.

DISCHARGE/ELEVATION RATING CURVE
SILVER CREEK
DT&I RAILROAD CORRIDOR




Pg 7 of 12

Exhibit 11

46 1320

K+E 10 X 10 TO ½ INCH 7 X 10 INCHES KEUFFEL & ESSER CO MADE IN U.S.A.

STAGE / STORAGE CURVE
SILVER CREEK



46 1320

KE 10 X 10 TO ½ INCH 7 X 10 INCHES KEUFFEL & ESSER CO MADE IN U.S.A.


HUD 200907

9/13/79

Exhibit 11

TOTAL DISCHARGE/ELEVATION RATING CURVE
SILVER CREEK + DIVERSION OF FLOW TO OTHER BASINS

	10 YR	50 YR	100 YR	500 YR
	Flows below el. 600			
H70	600	625	665	
	Flows above el. 600			
545	695	730	785	



Possible Flow Diversions

① Overland Flow to Smith Creek. Begins @ Elev. 599.0

② Overland Flow to Gibbons and Huron River. Begins at El. 600.0

③ DT+I RR culvert (Trib to Silver Cr.) West of Silver Creek. Begins at El. 600.0

Note: Local inflow for the Tributary to Silver Creek was subtracted out of the Tributary Rating Curve; Thus these addl flows are not included in this total curve.

Exhibit 11

HUD 2009 07
9/13/79

46 1320
K+E 10 X 10 TO ½ INCH 7 X 10 INCHES KEUFFEL & ESSER CO MADE IN U.S.A.

REFERENCE

Inflow Hydrographs Silver Creek

Time (hr.)	10 yr Storm Q	50 yr. Storm Q	100 yr. storm Q	500 yr. Storm Q
0	10	15	20	25
1.0	30	35	40	50
2.0	85	85	95	115
3.0	230	220	245	285
4.0	390	460	505	570
5.0	455	630	695	790
6.0	440	665	735	840
7.0	425	640	705	810
8.0	415	620	685	790
9.0	400	600	665	765
10.0	375	570	635	740
11.0	345	535	595	700
12.0	320	495	550	660
13.0	290	455	505	615
14.0	270	415	465	575
15.0	250	385	430	530
16.0	235	355	395	490
17.0	215	325	365	455
18.0	180	290	325	415
19.0	145	245	275	365
20.0	110	190	215	300

*See Hydrology File (HUD 2009 06) for these Inflow Hydrographs which were obtained from the [illegible] report on Rockwood (FEMA).

Exhibit 11

SUBJECT	BY	CHK.	SHEET NO.	File Code No (Job No) Owner Project Suffix
Flood Routing - Silver Creek	WJ Weaver		10 OF 12	HUD • 2009 • 07
	DATE 9/13/10	DATE		

REFERENCE

FLOOD ROUTING SUMMARY

Storm Event	Peak (cfs) Inflow	Peak (cfs) Outflow	Flood Elevation U/s of D.T.+I.
10 yr.	455	320	597.2
50 yr.	665	415	599.3
100 yr.	735	480	599.6
500 yr.	840	599	600.1

Results of this analysis indicates that storage and diversion from the basin play a large part in the reduction of flowrates. The peak flowrates (Outflow) listed above were used in the hydraulic analysis of Silver Creek and the elevations are input for the computer model (HEC-2) upstream of the D.T.+I. railroad corridor. The flood routing analysis utilized the S.C.S. TR-20 hydrologic computer models. Computer printouts for this analysis are contained in Exhibit 13.

EXHIBIT # 11

SUBJECT	BY	CHK.	SHEET NO	File Code No (Job No.) Owner Project Suffix
FLAT ROCK - F.I.S.	U. Wraver		11 OF 12	440 • 2009 07
	DATE 1/23/86	DATE		

FORM 25-0


(313) 291-5400

Wade, Trim & Associates, Inc.
Civil Engineers • Land Surveyors
WORK SHEET

25185 GODDARD ROAD
TAYLOR, MICHIGAN 48180

REFERENCE

FLOW NETWORK



FLOW DISTRIBUTION

Location	Flood Frequency / Intervals (yr.)			
	10 yr.	50 yr.	100 yr.	500 yr.
#1 Silver Cr. + Tributary Cr. confluence D/S of D.T.+I. Railroad	3[illegible]5	460	495	535
#2 Cooke & Gladding D/S of D.T.+I.	320	365	390	415
#3 Silver Cr. U/S of D.T.+I.	455	665	[illegible]	840
#4 Cooke & Gladding Cr. Div.	0	0	0	30
#5 Smith Creek Diversion	0	50	90	155

EXHIBIT #11

SUBJECT	BY	CHK	SHEET NO	File Code No (Job No) Owner • Project • Suffix
T[illegible] F.I.S.	DATE 1/[illegible]/[illegible]	DATE	12 OF 12	11[illegible] • 2[illegible] • 07

REFERENCES

1. U.S. Department of Housing and Urban Development, Flood Insurance Study - City of Rockwood, Michigan.

2. U.S. Geological Survey Topographical Maps - Flat Rock Quadrangle, Wayne County, Michigan, 7.5 Minute Series - Photorevised 1973.

3. HEC-2 - Water Surface Profile - Users Manual - U.S. Army Corps of Engineers - 1976.

4. Huron River Survey, U.S. Army Corps of Engineers - Detroit District, No Date Provided.

5. Post Flood Report of Southeast Michigan Flood 25-27 June 1968, U.S. Army Engineer District, Detroit Corps of Engineers, Detroit, Michigan, 1969.

6. Wade, Trim & Associates, Inc., Smith Creek - Flood Plain Study - City of Flatrock, Wayne County, Michigan, June, 1974.

7. U.S. Department of Agriculture, Soil Conservation Service, Computer Program for Project Formulation, Hydrology, Technical Release No. 20, May, 1965.

00BREAK00

1) COUNTY: Wayne

2) STUDY NAME: City of Flat Rock

3) WATERCOURSE: Silver Creek

4) DOCUMENT TYPE: Summary

00BREAK00

State Copy

10:50:21 X48 BILL HU200907 HUDFROCK JAN 23, 1980

This is the approved Master Submittal. 3/28/80

PRINTED IN U.S.A.

FORM 1411-GD-PRINTED BY ROTARY MANIFOLD FORMS

```
JOB10=HU200907          USER=BILL          PROJECT=HUDFROCK          BILLING=HUDFROCK          ROOM=XC04L

10:39:00                                JOB INTRODUCED FROM                                JAN 23, 1980
                                          CD01 JCL

10:40:04  START OF TRANSLATION

          $JOB HU200907,USER=BILL,PROJECT=HUDFROCK;
          $INPUT REC2;
          RECORD COUNT: 401
          $ENDINPUT;
           VALUES WTAPAK,WTAPAK;
           SEND 'START OF REC=2 EXECUTION';
           STEP REC=2,WTAENGLH,OPTIONS='FILE=A 91,FILE=B 92,FILE=C 93,FILE=D 94,
                                        FILE=E 95,FILE=F 96';
           ALC FILE=A,SIZE=2,UNIT=CYL,INCRSIZE=1;
           ASG FILE=A,FILE=A,TEMPRY,DVC=MS/M400,MD=B1;
           ALC FILE=B,SIZE=2,UNIT=CYL,INCRSIZE=1;
           ASG FILE=B,FILE=B,TEMPRY,DVC=MS/M400,MD=B2;
           ALC FILE=C,SIZE=2,UNIT=CYL,INCRSIZE=1;
           ASG FILE=C,FILE=C,TEMPRY,DVC=MS/M400,MD=B2;
           ALC FILE=D,SIZE=2,UNIT=CYL,INCRSIZE=1;
           ASG FILE=D,FILE=D,TEMPRY,DVC=MS/M400,MD=B2;
           ALC FILE=E,SIZE=2,UNIT=CYL,INCRSIZE=1;
           ASG FILE=E,FILE=E,TEMPRY,DVC=MS/M400,MD=B2;
           ALC FILE=F,SIZE=2,UNIT=CYL,INCRSIZE=1;
           ASG FILE=F,FILE=F,TEMPRY,DVC=MS/M400,MD=B2;
           ASG MMRD,REC2,FILESTAT=10;
          DEFINE PRPR,
           PRINTER=(FORMAT=66,NOF=1,PFT=641);
           ENDSTEP;
          SENDJOB;

          RECORD COUNT :   425

10:40:06  END OF TRANSLATION
```

```
JOBID=HU200907          USER=BILL          PROJECT=HUDFROCK          BILLING=HUDFROCK          RON=X0045

MOT  : PERSERVERANCE IS A STRONG WILL, COMPLACENCY A STRONG WON'T

10:40:47                              JOB EXECUTION LISTING                              JAN 23, 1980

          START OF NEC=2 EXECUTION
          STEP 1
          LOAD MODULE = NEC=2 (79/2 /22 23:58)
          LIBRARY = WTAENGLM
10:41:09  STEP STARTED XPRTY=9
          FP04.    2 CYLINDER(S) ALLOCATED ON VOLUME: WTAPAK FOR EFN: ;000048.FILE=B
          FP04.    2 CYLINDER(S) ALLOCATED ON VOLUME: WTAPAK FOR EFN: ;000048.FILE=C
          FP04.    2 CYLINDER(S) ALLOCATED ON VOLUME: WTAPAK FOR EFN: ;000048.FILE=D
          FP04.    2 CYLINDER(S) ALLOCATED ON VOLUME: WTAPAK FOR EFN: ;000048.FILE=A
          FP04.    2 CYLINDER(S) ALLOCATED ON VOLUME: WTAPAK FOR EFN: ;000048.FILE=E
          FP04.    2 CYLINDER(S) ALLOCATED ON VOLUME: WTAPAK FOR EFN: ;000048.FILE=F
          TASK MAIN J=01 P=00 COMPLETED
          DUFD1.IFN=FILE=B       REMEMBER REUSE=       0
          DUFD1.IFN=FILE=E       REMEMBER REUSE=       0
          DUFD1.IFN=FILE=C       REMEMBER REUSE=       0
          DUFD1.IFN=FILE=F       REMEMBER REUSE=       0
          DUFD1.IFN=FILE=D       REMEMBER REUSE=       0
          DUFD1.IFN=FILE=A       REMEMBER REUSE=       0    UNLOCK BUFFER=       0    CREATE BUFFER=      32
          TEMPORARY FILES USED=    220 TRACKS
          FILE=B    ON  WTAPAK : NO OF IO  CONNECTS=      135
          FILE=E    ON  WTAPAK : NO OF IO  CONNECTS=     9143
          FILE=C    ON  WTAPAK : NO OF IO  CONNECTS=      166
          M=PR      ON  LS4RV4 : NO OF IO  CONNECTS=       32
          M=RD      ON  L64RV4 : NO OF IO  CONNECTS=       34
          FILE=F    ON  WTAPAK : NO OF IO  CONNECTS=       30
          FILE=D    ON  WTAPAK : NO OF IO  CONNECTS=      165
          FILE=A    ON  WTAPAK : NO OF IO  CONNECTS=      641
          CPU          6.561                    PRCS MISSING SECTS      603   STACKOV      78
          ELAPSED      9.035                    SYS  MISSING SECTS     1093
          LINES        2052   LIMIT    NOLIM    PACKING STORE       625152
          CARDS           0   LIMIT    NOLIM    BUFFER SIZE          13040   CPSIZE     2272
10:50:12  STEP COMPLETED

          START     10:40:47   LINES       2052
          STOP      10:50:14   CARDS          0
          CPU          6.561
          ELAPSE       9.462
10:50:14  RESULT:  JOB COMPLETED
```

PRINTED IN U.S.A.
FORM 1411-00 PRINTED BY ROYARY MANIFOLD FORMS

```
**************************************************
   HEC2 RELEASE DATED NOV 76 UPDATED FEB 1977
   ERROR CORR -  01
   MODIFICATION -  50,51,52
**************************************************

C
T1CITY OF FLAT ROCK FIS
T2      DATEOF RUN = 1/80
T3      SILVER CR. MULTI PROFILE

J1  ICHECK    INQ       NINV      IDIR      STRT      METRIC    HVINS     Q         WSEL      FQ
        0.        2.        0.        0.  0.000300     0.00      0.0       0.    506.600     0.000
J2  NPROF     IPLOT     PRFVS     XSECV     XSECH     FN        ALLOC     IBW       CHNIM     ITRACE
        1.000     0.000    -1.000     0.000     0.000     0.000     0.000     0.000     0.000     0.000
J3  VARIABLE CODES FOR SUMMARY PRINTOUT
      150.000   201.000     0.000     0.000     0.000     0.000     0.000     0.000     0.000     0.000
J5  LPRNT     NUMSEC                        ********REQUESTED SECTION NUMBERS********
      -10.000   -10.000     0.000     0.000     0.000     0.000     0.000     0.000     0.000     0.000
ET      0.000     0.000     0.000     0.000     1.400     0.000     0.000     0.000     0.000     0.000
QT      5.000   530.000   675.000   705.000   705.000   735.000     0.000     0.000     0.000     0.000
NC      0.035     0.035     0.035     0.100     0.300     0.000     0.500     0.000     0.000     0.000

   650. FEET D/S OF D/S FACE OF OLDSTEAD RD. ROCKWOOD SECT. 19073.

X1      0.000    32.000  1500.000  1523.000     0.000     0.000     0.000     0.000     0.000     0.000
X3      0.000     0.000     0.000  1350.000     0.000  1600.000     0.000     0.000     0.000     0.000
GR    588.700     0.000   580.900   100.000   568.300   200.000   587.700   350.000   586.100   400.000
GR    586.500   500.000   585.000   600.000   583.700   700.000   586.800   850.000   587.500   900.000
GR    587.700  1000.000   588.600  1100.000   586.500  1200.000   586.900  1300.000   582.200  1400.000
GR    583.500  1419.000   579.300  1430.000   580.600  1500.000   579.000  1532.000   577.700  1586.000
GR    577.900  1328.000   581.000  1532.000   580.600  1600.000   581.800  1700.000   586.800  1800.000
GR    585.900  1900.000   585.100  2000.000   587.800  2100.000   588.800  2200.000   589.600  2300.000
GR    589.400  2400.000   589.500  2500.000     0.000     0.000     0.000     0.000     0.000     0.000

   D/S FACE OF OLDSTEAD ROAD          ROCKWOOD SECT. 19823.

X1      1.000    18.000   692.400   707.600   600.600   500.000   450.000     0.300     0.000     0.000
X3     10.000     0.000     0.000     0.000     0.000     0.000     0.000   586.500   586.500     0.000
GR    630.000   550.000   586.700   550.000   583.200   600.000   585.900   692.400   577.100   692.400
GR    577.100   654.000   577.000   696.000   577.000   690.000   576.900   700.300   577.000   702.000
GR    577.000   704.000   577.100   706.000   577.100   707.000   580.300   717.500   585.200   800.000
GR    584.600   900.000   586.600   950.000   650.500   950.000     0.000     0.000     0.000     0.000
NC      0.018     0.018     0.031     0.013     0.000     0.013     0.000     0.000     0.000     0.000

   1 FOOT INSIDE BRIDGE D/S END          ROCKWOOD SECT. 19844.

X1      2.000    30.000     0.300     0.000     5.000     1.000     1.300     0.000     0.000     0.000
GR    650.000   550.000   650.200     0.000   550.000   650.000     0.000   550.300   650.000     0.000
GR    550.000   650.000     0.000   550.000   650.000     0.000   550.000   650.000     0.000   550.000
```

PRINTED IN U.S.A.
FORM 1411-3S-PRINTED BY ROTARY MANIFOLD FORMS

BT	586.700	0.000	600.000	586.300	0.000	692.400	585.800	577.100	692.400	585.800
BT	577.600	694.000	585.800	581.200	696.000	585.800	582.800	698.000	585.800	583.900
BT	700.000	585.800	583.900	702.000	585.800	583.900	704.000	585.800	582.800	706.000
BT	585.800	581.200	707.600	585.800	577.600	707.600	585.800	577.100	800.000	585.200
BT	0.000	900.000	584.600	0.000	950.000	584.200	0.000	950.000	650.000	0.000

1.FOOT INSIDE BRIDGE U/S END ROCKWOOD SECT. 19570.

X1	3.000	0.000	0.000	0.000	46.000	46.000	46.000	0.000	0.000	0.000
X2	0.000	0.000	0.000	0.000	0.000	0.000	1.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	585.800	584.600	0.000
NC	0.045	0.045	0.035	0.000	0.000	0.000	0.000	0.000	0.000	0.000

U/S FACE OF OLMSTEAD ROAD ROCKWOOD SECT. 19571.

X1	4.000	0.000	0.000	0.000	1.000	1.000	1.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	585.800	585.200	0.000
BT	5.000	545.000	695.000	730.000	730.000	785.000	0.000	0.000	0.000	0.000

750.FEET U/S OF U/S FACE OF OLMSTEAD RD.ROCKWOOD SECT. 20321.

X1	5.000	13.000	210.000	250.000	775.000	725.000	750.000	0.000	0.000	0.000
GR	589.700	0.000	587.900	30.000	585.500	50.000	582.300	110.000	582.000	210.000
GR	578.600	217.000	378.600	221.000	578.900	225.000	580.600	230.000	582.000	310.000
GR	581.600	410.000	582.800	510.000	585.400	610.000	589.700	710.000	588.700	810.000
GR	588.700	910.000	589.800	1010.000	589.200	1030.000	0.000	0.000	0.000	0.000

1450.FEET U/S OF U/S FACE OF OLMSTEAD ROCKWOOD SECT. 21021. CORP.LIMIT

X1	6.000	14.000	400.000	434.000	675.000	725.000	700.000	0.000	0.000	0.000
GR	590.800	0.000	589.600	40.000	590.900	100.000	581.000	200.000	581.900	303.000
GR	583.700	430.300	575.000	417.000	575.900	424.000	579.200	420.300	582.400	434.300
GR	581.330	530.300	583.500	610.000	590.000	710.000	593.500	610.000	0.000	0.000
NC	0.100	0.100	0.040	0.300	0.500	0.000	0.000	0.000	0.000	0.000

X-SECTION D/S OF GOODRUFF RD.

X1	3944.000	35.100	301.250	318.750	1400.000	1944.300	2682.000	0.000	0.000	0.000
GR	590.000	75.000	586.000	76.000	585.000	200.000	585.000	296.000	583.130	301.200
GR	583.130	301.250	581.000	304.000	580.700	340.000	581.000	316.000	584.070	318.750
GR	584.070	318.800	585.000	321.000	586.000	400.000	586.000	450.000	590.000	451.000
BT	0.000	0.000	0.000	0.000	9.100	0.000	0.000	0.000	94.000	428.000

D/S FACE OF GOODRUFF RD. BRIDGE REPEATED SECT. 1944

X1	2044.000	15.000	301.250	318.750	100.000	100.000	100.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	585.400	585.400	0.000
GR	590.000	75.000	586.000	76.000	585.650	200.000	586.660	296.000	585.000	301.200
GR	583.130	301.250	581.000	304.000	580.700	340.000	581.000	316.000	584.070	318.750
GR	584.070	318.800	586.000	321.000	586.000	400.000	586.000	450.000	590.000	451.000
NC	0.070	0.070	0.025	0.000	0.000	0.000	0.000	0.000	0.000	0.000

1 FOOT INSIDE OF D/S FACE OF BRIDGE

X1	2045.000	0.000	0.000	0.000	1.000	1.000	1.000	0.000	0.000	0.000
BT	0.000	76.000	586.000	0.000	200.000	585.650	0.000	301.200	585.650	0.000
BT	301.250	589.130	583.130	318.750	589.130	584.070	318.800	586.000	0.000	321.000

PRINTED IN U.S.A.
FORM 1411-GO-PRINTED BY ROTARY MANIFOLD FORMS

BT	586.000	0.000	400.000	586.000	0.000	450.000	586.000	0.000	0.000	0.000
QT	5.000	395.000	460.000	495.000	495.000	535.000	0.000	0.000	0.000	0.000

1 FOOT INSIDE OF U/S FACE OF BRIDGE

X1	2074.000	0.000	0.000	0.000	29.000	29.000	29.000	0.000	0.000	0.000
X2	0.000	0.000	0.000	0.000	0.000	0.000	1.000	0.000	0.000	0.000
NC	0.100	0.100	0.040	0.000	0.000	0.000	0.000	0.000	0.000	0.000

U/S FACE OF WOODRUFF RD. BRIDGE

X1	2075.000	0.000	0.000	0.000	1.000	1.000	1.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	585.630	586.330	0.000

X-SECTION U/S OF WOODRUFF RD. REPEATED SECT. 2075.5

X1	2100.000	0.000	0.000	0.000	25.000	25.000	25.000	0.000	0.000	0.000

VALLEY SECTION BASED ON FIELD BOOK AND QUAD MAP

X1	3073.000	14.000	294.000	300.000	973.000	973.000	973.000	0.000	0.000	0.000
GR	591.910	0.000	592.060	100.000	591.860	200.000	591.260	210.000	588.710	254.000
GR	588.510	277.000	581.780	294.000	581.080	300.000	581.780	306.000	585.880	316.000
GR	585.530	416.000	585.630	516.000	585.830	616.000	590.000	1000.000	0.000	0.000
NC	0.120	0.120	0.040	0.100	0.300	0.000	0.000	0.000	0.000	0.000

VALLEY SECTION BASED ON FIELD BOOK AND QUAD MAP

X1	4573.000	15.000	1195.000	1207.000	1350.000	1650.000	1500.000	0.000	0.000	0.000
GR	591.000	0.000	590.300	350.000	587.600	900.000	587.550	1000.000	587.200	1100.000
GR	587.900	1155.000	193.100	1199.000	591.950	1202.000	583.100	1207.000	587.400	1215.000
GR	586.600	1300.000	587.500	1400.000	587.050	1500.000	0.000	0.000	0.000	0.000
NC	0.070	0.070	0.035	0.300	0.500	0.000	0.000	0.000	0.000	0.000

X-SECTION D/S OF BRIDGE S. OF GIBRALTAR RD.

X3	6337.500	15.000	265.000	283.000	1764.500	1764.500	1764.500	0.000	0.000	0.000
GR	591.000	0.000	590.000	80.000	593.280	208.000	586.930	244.000	585.550	260.000
GR	584.980	265.000	584.030	275.000	584.080	283.000	585.530	280.000	586.380	314.000
GR	592.430	337.000	590.000	400.000	590.500	525.000	591.000	600.000	591.500	630.000
GR	592.000	900.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
NC	0.040	0.060	0.350	0.100	0.000	0.000	0.000	0.000	0.100	0.100

10: D/S OF DRIVEWAY

X1	6527.000	12.000	110.000	138.000	190.000	190.000	190.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	20.000	0.000	170.000	0.000	0.000	0.000	0.000
GR	592.700	10.000	592.900	97.000	593.300	50.000	586.900	94.000	585.500	110.000
GR	585.000	110.000	584.000	125.000	584.900	133.000	585.500	158.000	586.000	164.000
GR	592.400	137.000	592.600	218.000	0.000	0.000	0.000	0.000	0.000	0.000

10: D/S OF DRIVEWAY

X1	6537.500	26.000	99.000	165.400	190.000	190.000	190.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	592.400	592.400	0.000
GR	592.700	10.000	592.900	97.000	593.200	94.000	586.900	99.000	586.500	99.000

PRINTED IN U.S.A.
FORM 1411-00 PRINTED BY ROTARY MANIFOLD FORMS

GR	586.300	114.600	586.300	114.700	586.300	115.800	586.300	115.900	585.800	131.500
GR	585.800	131.600	585.800	132.700	585.800	132.800	585.000	140.600	585.800	148.400
GR	585.800	148.500	585.800	149.600	585.800	149.700	586.300	165.300	586.300	165.400
GR	586.300	166.600	586.300	166.700	586.400	183.300	586.400	183.400	593.100	188.000
GR	592.600	210.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
NC	0.040	0.060	0.025	0.000	0.000	0.000	0.000	0.000	0.000	0.000

D/S FACE OF DRIVEWAY

X1	6538.500	0.300	0.000	0.000	1.800	1.000	1.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	592.400	592.400	0.000
GT	25.000	10.500	592.700	0.000	37.000	592.900	0.000	94.000	593.200	0.000
BT	99.000	593.600	586.500	99.100	593.600	591.800	114.600	593.600	591.800	114.700
BT	593.600	586.300	115.800	593.600	586.300	115.900	593.600	591.800	131.500	593.600
BT	591.800	131.600	593.600	585.800	132.700	593.600	585.800	132.800	593.600	591.800
BT	148.400	593.600	591.800	148.500	593.600	585.800	149.600	593.600	585.800	149.700
BT	593.600	591.800	165.300	593.600	591.800	165.400	593.600	586.300	166.400	593.600
BT	586.300	166.700	593.600	591.800	183.300	593.600	591.800	183.400	593.000	586.400
BT	188.000	593.100	0.000	218.000	592.600	0.000	0.000	0.000	0.000	0.000

U/S FACE OF DRIVEWAY

X1	6528.000	0.000	0.000	0.000	39.500	39.500	39.500	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	592.500	592.500	0.000
X2	0.000	0.000	0.000	0.000	0.000	0.000	1.000	0.000	0.000	0.000
NC	0.040	0.040	0.035	0.000	0.000	0.000	0.000	0.000	0.000	0.000

1: U/S OF DRIVEWAY

X1	6579.000	0.000	0.000	0.000	1.000	1.000	1.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	592.700	592.600	0.000

30: U/S OF DRIVEWAY

X1	6509.000	10.000	117.000	163.000	50.000	50.000	50.000	0.000	0.000	0.000
GT	592.700	11.000	592.900	37.000	593.200	94.000	589.000	117.000	534.900	132.000
GR	534.900	149.000	585.500	166.000	589.100	183.000	595.700	130.000	592.000	290.000
NC	0.370	0.070	0.035	0.300	0.500	0.000	0.000	0.000	0.000	0.000

X-SECTION, U/S OF GIBRALTAR RD. BRIDGE

X1	7174.000	14.000	267.300	282.500	547.000	547.000	547.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	242.000	0.000	307.000	0.000	0.000	0.000	0.000
GR	595.000	0.000	590.000	110.000	590.000	251.000	505.400	267.500	585.050	275.000
GR	585.600	282.500	589.900	315.000	590.000	390.000	590.000	449.900	596.000	450.000
GR	590.000	480.000	590.200	480.100	591.000	700.000	593.000	1000.000	0.000	0.000
ET	0.000	0.000	0.000	0.000	0.100	0.000	0.000	0.000	1.000	1000.000

D/S FACE OF GIBRALTAR RD. BRIDGE

X1	7274.000	11.000	289.150	304.100	100.000	100.000	100.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	189.000	0.000	349.000	0.000	593.300	593.300	0.000
GR	595.000	87.000	590.300	133.000	590.000	275.000	585.600	289.150	585.050	308.050
GR	585.600	304.100	590.300	340.000	590.000	415.000	590.000	452.000	595.000	454.000
GR	595.000	454.100	0.300	0.000	0.000	0.000	0.000	0.000	0.000	0.000
SB	0.000	2.570	3.000	0.000	12.200	0.000	84.000	0.000	582.500	585.050

PRINTED IN U.S.A.
FORM 1611 GO PRINTED BY ROTARY MANIFOLD FORMS.

U/S FACE OF GIBRALTAR RD. BRIDGE

X1	7373.000	18.000	489.150	504.100	99.000	99.000	99.000	0.000	0.000	0.000
X2	0.000	0.000	1.000	589.360	592.370	0.000	0.000	0.000	0.000	0.000
X3	10.000	585.050	0.000	0.000	0.000	0.000	0.000	592.530	592.370	0.000
BT	13.000	287.000	593.600	0.000	287.000	593.600	0.000	287.000	593.600	0.000
BT	300.000	593.170	3.000	400.000	592.620	0.000	489.150	592.530	582.900	489.160
BT	595.300	589.360	504.000	595.300	589.360	504.100	592.470	582.900	533.000	592.370
BT	0.000	600.000	592.410	0.000	633.000	592.500	0.000	633.000	605.000	0.000
GR	593.600	287.000	593.600	287.000	593.600	287.000	593.000	300.000	592.600	400.000
GR	592.000	476.000	582.900	489.150	582.900	489.160	582.500	500.000	582.900	504.000
GR	582.900	504.100	592.000	518.000	592.000	533.000	592.000	500.000	592.000	633.000
GR	592.000	633.000	595.000	633.000	605.000	633.000	0.000	0.000	0.000	0.000
ET	0.000	0.000	0.000	0.000	1.400	0.000	0.000	0.000	0.000	0.000

X-SECTION U/S OF GIBRALTAR RD. BRIDGE

X1	7398.000	0.000	0.000	0.000	25.000	25.000	25.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	400.000	0.000	633.000	0.000	0.000	0.000	0.000
NC	0.070	0.070	0.035	0.100	0.300	0.000	0.000	0.000	0.000	0.000

VALLEY SECTION N. OF GIBRALTAR RD. BASED ON FIELD BOOK AND QUAD MAP

X1	8573.000	12.000	1047.000	1059.000	1175.000	1175.000	1175.000	0.000	0.000	0.000
GR	595.000	0.000	592.050	750.000	590.250	900.000	591.850	1036.000	585.750	1047.000
GR	585.500	1050.000	585.700	1053.000	586.750	1056.000	587.600	1059.000	591.450	1066.000
GR	592.100	1200.000	595.100	1350.000	0.000	0.000	0.000	0.000	0.000	0.000
NC	0.090	0.090	0.035	0.100	0.300	0.000	0.000	0.000	0.000	0.000

X1	9000.000	0.000	0.000	0.000	427.000	427.000	427.000	0.000	0.460	0.000

X1	9500.000	0.000	0.000	0.000	500.000	500.000	500.000	0.000	0.360	0.000

VALLEY SECTION BASED ON FIELD BOOK AND QUAD MAP

X1	10173.000	13.000	295.000	304.000	673.500	673.000	673.000	0.000	0.200	0.000
GR	599.300	0.000	593.500	130.000	592.800	233.000	591.900	287.000	587.200	296.000
GR	587.300	300.000	587.100	304.000	588.300	306.000	586.300	310.000	595.200	316.000
GR	592.400	363.000	593.550	593.000	590.200	600.000	0.000	0.000	0.000	0.000
BT	5.000	320.000	365.000	390.000	590.030	415.000	0.000	0.000	0.000	0.000

VALLEY SECTION BASED ON FIELD BOOK AND QUAD MAP

X1	11673.000	12.000	295.000	305.000	1300.000	1800.000	1500.000	0.000	0.000	0.000
GR	598.310	0.000	593.710	150.000	593.810	253.000	594.560	263.000	596.910	272.000
GR	596.310	280.100	588.810	295.500	588.760	300.000	583.760	303.000	594.810	313.000
GR	595.460	450.200	597.010	600.100	0.000	0.000	0.000	0.000	0.000	0.000
NC	0.110	0.110	0.035	0.300	0.500	0.000	0.000	0.000	0.000	0.000

X-SECT. U/S OF R.R. CULVERTS

X	12356.000	12.000	745.000	755.000	903.000	663.000	663.000	0.000	0.000	0.000
X1	0.000	0.000	0.000	692.000	0.000	808.000	0.000	0.000	0.000	0.000
X3	630.300	31.000	598.000	295.000	596.000	553.000	595.000	500.000	596.200	737.000
GR	590.300	745.000	589.830	750.000	590.000	755.000	595.000	770.000	596.000	828.000
GR	598.000	1025.000	600.000	1250.000	0.000	0.000	0.000	0.000	0.000	0.000
ET	0.000	0.000	0.000	0.000	0.400	0.000	0.000	0.000	1.000	421.000

PRINTED IN U.S.A.
FORM 1411 GO PRINTED BY ROTARY MANIFOLD FORMS.

D/S FACE OF DUAL 9: X 6.5: CMP:S

X1	12456.000	24.000	739.000	761.000	191.000	191.000	191.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	602.600	602.600	0.000
GR	605.000	0.000	602.700	1.000	601.000	2.000	598.000	290.000	596.000	550.000
GR	595.000	680.000	596.000	730.000	592.000	739.000	591.000	740.500	590.000	742.000
GR	590.000	743.500	590.100	745.000	591.500	747.000	592.000	748.000	592.000	752.000
GR	590.200	754.000	590.000	756.500	591.000	759.000	592.000	761.000	595.000	767.000
GR	596.000	900.000	600.000	1200.000	602.700	1250.000	605.000	1251.000	0.000	0.000
SB	0.000	3.250	3.000	0.000	11.350	0.000	77.000	0.000	590.400	590.000

DUAL CMP:S MEET DUAL BOX CULVERTS HERE.

X1	12612.000	26.000	739.000	756.000	156.000	156.000	156.000	0.300	0.900	0.000
X2	0.000	0.000	1.000	596.600	602.600	0.000	0.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	602.600	602.600	0.000
BT	16.000	0.000	605.000	0.000	1.000	602.700	0.000	739.000	602.600	591.400
BT	739.100	602.600	595.000	740.500	602.600	596.400	744.300	602.600	596.400	746.000
BT	602.600	595.000	747.000	602.600	592.400	748.000	602.600	592.400	749.000	602.600
BT	595.000	750.500	602.600	596.400	754.500	602.600	596.400	755.900	602.600	595.000
BT	756.000	602.600	591.400	1250.000	602.700	0.000	1251.000	605.000	0.000	0.000
GR	605.000	0.000	602.700	1.000	601.000	2.000	598.000	290.000	596.000	550.000
GR	595.000	680.000	596.000	730.000	591.400	739.000	591.400	739.100	590.600	740.500
GR	590.400	742.500	590.600	744.300	591.400	746.000	592.400	747.000	592.400	748.000
GR	591.400	749.000	590.600	750.500	590.400	752.500	590.600	754.500	591.600	755.900
GR	591.400	756.000	593.000	767.000	596.000	900.000	600.000	1200.000	602.700	1250.000
GR	605.000	1251.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
SB	1.250	1.740	3.000	0.000	16.670	1.500	94.000	0.000	590.600	590.400

U/S FACE OF R.R. CULVERTS

X1	12667.000	24.000	739.000	756.000	35.000	35.000	35.000	0.000	0.000	0.000
X2	0.000	0.000	1.000	596.400	602.600	0.000	0.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	602.600	602.600	0.000
BT	16.000	0.000	605.000	0.000	1.000	602.700	0.000	739.000	602.600	590.400
BT	739.100	602.600	595.400	740.000	602.600	596.400	746.000	602.600	596.400	747.000
BT	602.600	595.400	747.100	602.600	595.600	746.000	602.600	590.400	748.100	602.600
BT	595.400	749.000	602.600	596.600	755.000	602.600	596.400	755.900	602.600	595.400
BT	756.000	602.600	590.400	1250.000	602.700	0.000	1251.000	605.000	0.000	0.000
GR	605.000	0.000	602.700	1.000	601.000	2.000	598.000	290.000	596.000	550.000
GR	595.000	600.000	596.000	730.000	590.400	739.000	590.400	739.100	590.400	740.000
GR	590.400	764.000	590.400	747.000	590.400	747.100	590.400	748.000	590.400	748.100
GR	590.400	749.000	590.400	755.000	590.400	755.900	590.400	756.000	595.000	767.000
GR	596.000	900.000	600.000	1200.000	602.700	1250.000	605.000	1251.000	0.000	0.000
BT	0.000	0.000	0.000	0.000	1.400	0.000	0.000	0.000	0.000	0.000

X@SECT.U/S OF R.R.CULVERT & D/S OF 9: CMP

X1	12600.000	0.000	0.000	0.000	59.000	35.000	35.000	0.000	0.340	0.000
X3	0.000	0.000	0.000	750.000	0.000	795.000	0.000	0.000	0.000	0.000
BT	0.000	0.000	0.000	0.000	9.100	0.000	0.000	0.000	1.000	1251.000

D/S FACE OF 9: CMP

X1	12765.000	115.000	739.000	756.000	95.000	95.000	95.000	0.000	0.000	0.000
X2	10.000	0.000	10.000	10.000	0.000	0.000	0.000	598.500	596.500	0.000
X4	1.000	605.000	685.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
GR	595.000	687.000	596.000	730.000	592.000	739.000	590.900	739.100	590.900	746.790

PRINTED IN U.S.A.
FORM 1411-80 PRINTED BY ROTARY MANIFOLD FORMS

GR	592.000	747.000	592.000	748.000	591.200	748.100	591.200	755.900	592.000	756.000
GR	598.000	767.000	598.000	808.000	605.000	808.000	605.000	808.000	605.000	808.000
SR	0.000	5.010	3.000	0.000	11.230	0.000	68.500	0.000	591.100	590.900

U/S FACE OF 96 CNP

X1	12979.000	19.000	739.000	756.000	264.000	264.000	264.000	0.000	0.000	0.000
X2	0.000	0.000	1.000	597.200	602.600	0.000	0.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	602.600	602.600	0.000
X4	1.000	605.000	606.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
X5	5.000	597.200	599.300	599.600	599.800	600.100	0.000	0.000	0.000	0.000
ST	18.000	687.000	605.000	0.000	687.000	602.700	0.000	739.000	602.600	593.200
BT	739.500	602.600	595.500	741.000	602.600	597.000	743.000	602.600	597.200	745.000
BT	602.600	597.000	746.500	602.600	595.500	747.000	602.600	593.200	748.000	602.700
BT	593.000	748.500	602.600	595.000	749.500	602.600	596.500	752.000	602.600	597.000
BT	754.500	602.600	596.500	755.500	602.600	595.000	756.000	602.600	595.000	840.000
BT	602.700	0.000	840.000	605.000	0.000	0.000	0.000	0.000	0.000	0.000
GR	603.000	687.700	596.000	730.300	593.250	739.000	591.100	739.500	591.100	741.000
GR	591.100	743.000	591.100	745.000	591.100	746.500	593.200	747.000	593.000	748.000
GR	591.100	748.500	591.100	749.500	591.100	752.000	591.100	754.500	591.100	755.500
GR	593.000	756.000	600.000	767.000	600.000	808.000	605.000	809.000	0.000	0.000
QT	5.000	455.000	665.000	735.000	735.000	340.000	0.000	0.000	0.000	0.000
ET	0.000	0.000	0.000	0.000	1.600	0.000	0.000	0.000	0.000	0.000

X@SECT. U/S OF 96 CNP

X1	13030.000	16.000	795.000	805.000	51.000	51.000	51.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	740.000	0.000	660.000	0.000	0.000	0.000	0.000
X4	2.300	605.500	1.000	605.000	1401.000	1.000	0.000	0.000	0.000	0.000
GR	601.000	2.000	598.090	500.000	595.900	650.000	595.360	764.000	596.200	773.000
GR	595.840	780.000	590.200	795.000	589.840	800.000	590.200	805.000	595.000	816.000
GR	595.900	821.000	597.300	828.500	596.840	842.000	598.090	900.000	600.000	1300.000
GR	601.500	1405.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
NC	0.100	0.100	0.035	0.100	0.300	0.000	0.000	0.000	0.000	0.000
ET	0.000	0.000	0.000	2.300	9.100	0.000	295.000	1300.000	650.000	950.000

VALLEY SECTION BASED ON FIELD BOOK AND QUAD MAP

X1	13473.000	19.000	799.000	305.000	445.000	445.000	445.300	0.000	0.000	0.000
X4	1.000	600.000	295.000	0.300	0.000	0.000	0.000	0.000	0.000	0.000
GR	605.000	295.000	598.090	500.000	595.930	650.000	595.360	764.000	596.200	773.000
GR	595.840	780.000	590.340	795.000	590.190	800.000	590.340	805.000	595.440	816.000
GR	595.940	821.000	597.340	828.500	596.840	842.000	598.090	900.000	599.400	951.000
GR	609.430	951.100	609.400	1001.100	0.000	0.000	0.000	0.000	0.000	0.000
NC	0.100	0.100	0.035	0.300	0.500	0.000	0.000	0.000	0.500	0.500
ET	0.000	2.100	2.105	2.100	9.100	1.100	490.300	1130.300	620.000	920.000

X@SECT. U/S OF WHEELAND RD

X1	13909.000	0.000	745.000	759.500	436.000	436.000	436.000	0.000	0.000	0.000
X4	1.000	821.000	1.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
GR	610.000	0.000	597.000	500.000	595.900	730.000	590.900	745.000	590.460	750.000
GR	590.900	755.000	595.400	766.000	600.000	1300.000	610.000	1307.000	0.000	0.000
ET	0.000	0.000	0.000	0.000	9.100	0.000	499.000	1182.000	550.000	850.000

U/S FACE OF WHEELAND RD

X1	14009.000	9.000	695.000	705.000	100.000	100.000	100.000	0.000	0.000	0.000
X4	15.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000

PRINTED IN U.S.A.
FORM 141-GSPRINTED BY ROTARY MANIFOLD FORMS

GR	610.000	495.000	597.000	500.000	596.000	680.000	591.300	695.000	591.210	700.000
GR	591.300	705.000	595.400	716.000	600.000	1250.000	610.000	1251.000	0.000	0.000
NC	0.100	0.100	0.022	0.300	0.500	0.000	0.000	0.000	0.000	0.000
ET	0.000	0.000	0.000	0.000	9.100	0.000	0.000	0.000	550.000	850.000

1 FOOT INSIDE OF D/S FACE OF CULVERT

X1	14010.000	14.000	694.500	705.500	1.000	1.000	1.000	0.000	0.000	0.000
X4	3.000	596.030	800.000	597.500	950.000	599.000	1100.000	0.000	0.000	0.000
GR	0.000	495.030	610.000	0.000	500.000	599.520	596.000	600.000	599.780	598.500
GR	694.500	599.190	590.900	694.580	599.190	596.210	705.413	599.190	596.210	705.500
GR	599.190	590.900	1250.000	600.000	0.000	0.000	0.000	0.000	0.000	0.000
GR	610.000	495.000	597.000	500.000	596.500	600.000	591.300	694.500	591.300	694.585
GR	591.210	700.000	591.300	705.415	591.300	705.500	595.400	716.000	596.000	800.000
GR	597.500	950.000	599.000	1100.000	600.200	1250.000	610.000	1251.000	0.000	0.000
ET	0.300	0.000	0.000	0.000	9.100	0.000	0.000	0.000	500.000	900.000

1 FOOT INSIDE OF U/S FACE OF CULVERT

X1	14090.000	0.000	0.000	0.000	80.000	60.000	60.000	0.000	0.000	0.000
X2	0.000	0.000	0.000	0.000	0.000	0.000	1.000	0.000	0.000	0.000
NC	0.100	0.100	0.030	0.300	0.500	0.000	0.000	0.000	0.000	0.000
ET	0.000	0.000	0.000	0.000	9.100	0.000	0.000	0.000	500.000	900.000

U/S FACE OF VREELAND RD

X1	14091.000	0.000	0.000	0.000	1.000	1.000	1.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	9.000	0.000	0.000	597.500	597.500	0.000
ET	0.000	0.000	0.000	0.000	9.100	0.000	0.000	0.000	450.000	950.000

SUBJECT, U/S OF VREELAND RD

X1	14114.000	0.000	0.000	0.000	25.000	25.000	25.000	0.000	0.000	0.000
NC	0.100	0.100	0.035	0.100	0.300	0.000	0.000	0.000	0.000	0.000
ET	0.000	0.000	0.000	0.000	9.100	0.000	0.000	0.000	275.000	875.000

VALLEY SECTION BASED ON FIELD BOOK AND QUAD. MAP

X1	14073.000	16.000	571.000	579.300	557.000	557.000	557.300	0.000	0.000	0.000
X4	1.000	602.500	1.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
GR	610.000	0.000	599.670	275.000	596.520	425.000	596.070	510.000	596.720	559.000
GR	592.670	579.330	592.070	579.050	592.570	579.000	567.970	566.000	597.120	603.300
GR	597.500	000.230	602.500	000.130	604.500	624.900	597.500	652.000	602.000	1000.000
GR	610.000	2001.030	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
NC	0.090	0.090	0.040	0.300	0.500	0.000	0.000	0.000	0.000	0.000
ET	0.000	0.000	0.000	7.100	9.100	0.000	623.000	2852.000	1050.000	1600.000

X-SECTION D/S OF TELEGRAPH RD.

X1	15262.000	13.000	1396.000	1404.300	700.000	800.000	589.000	0.000	0.000	0.000
GR	610.000	1049.000	610.000	1049.000	598.000	1030.000	597.300	1200.000	599.660	1377.000
GR	594.160	1388.300	592.600	1396.000	592.316	1400.000	592.600	1404.000	594.160	1412.000
GR	596.160	1416.300	596.500	1550.000	610.000	1551.000	0.500	0.000	0.000	0.000
ET	0.000	0.000	0.000	0.000	9.100	0.000	0.000	0.000	1125.000	1600.000

D/S FACE OF TELEGRAPH RD. BRIDGE

PRINTED IN U.S.A.
FORM 1411 GU-PRINTED BY ROTARY MANIFOLD FORMS.

X1	15362.000	15.000	1390.400	1409.600	100.000	100.000	100.000	0.000	0.000	0.000
GR	610.000	1009.000	600.000	1010.000	599.310	1200.000	599.900	1390.300	597.200	1390.400
GR	594.160	1390.410	592.600	1396.000	592.310	1400.000	592.600	1404.000	594.160	1409.590
GR	597.200	1409.600	599.900	1409.610	599.200	1500.000	599.300	1575.000	610.000	1576.000
NC	0.060	0.060	0.025	0.000	0.000	0.000	0.000	0.000	0.000	0.000
ET	0.000	0.000	0.000	0.000	9.100	0.000	0.000	0.000	1125.000	1600.000

1 FOOT INSIDE D/S TELEGRAPH BRIDGE

X1	15363.000	0.000	0.000	0.000	1.000	1.000	1.000	0.000	0.000	0.000
X2	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.920	0.000
BT	5.000	1390.400	599.900	597.200	1390.410	599.900	597.200	1400.000	599.900	597.200
BT	1409.600	599.900	597.200	1409.610	599.900	0.000	0.000	0.000	0.000	0.000
ET	0.000	0.000	0.000	0.000	9.100	0.000	0.000	0.000	1125.000	1600.000

1 FOOT INSIDE U/S END TELEGRAPH BRIDGE

X1	15434.000	0.000	0.000	0.000	71.000	71.000	71.000	0.000	0.000	0.000
X2	0.000	0.000	0.000	0.000	0.000	0.000	1.000	0.000	0.000	0.000
NC	0.360	0.060	0.040	0.000	0.000	0.000	0.000	0.000	0.000	0.000
ET	0.300	0.000	0.000	0.000	9.100	0.000	0.000	0.000	1125.000	1600.000

U/S FACE TELEGRAPH RD

X1	15435.000	0.000	0.000	0.000	1.000	1.000	1.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	599.900	599.900	0.000
ET	0.000	0.000	0.000	0.000	9.100	0.000	0.000	0.000	1125.000	1600.000

XSECT. U/S OF TELEGRAPH RD

X1	15460.000	0.000	0.000	0.000	25.000	25.000	25.000	0.000	0.000	0.000
NC	0.020	0.090	0.040	0.100	0.100	0.000	0.000	0.000	0.000	0.000
ET	0.250	0.000	0.000	0.000	9.100	0.000	0.000	0.000	275.000	775.000

VALLEY SECT BASED ON FIELD BOOK NO 800

X1	16873.000	12.000	446.000	454.000	1413.000	1413.000	1413.000	0.000	0.000	0.000
BR	410.000	299.000	410.000	299.000	392.460	350.000	598.300	635.000	392.630	446.000
GR	592.900	430.000	592.350	454.000	390.950	463.000	603.350	463.000	599.930	600.000
GR	600.000	750.000	610.000	751.000	0.000	0.000	2.000	0.000	0.000	0.000
ET	0.000	0.000	0.300	0.000	9.100	0.000	0.000	0.000	265.000	603.000

VALLEY SECTION AT CORP/LIMIT @DOWNTOWN/FLAT ROCK

X1	17673.000	9.000	395.000	405.000	900.000	900.000	900.000	0.000	0.000	0.000
BR	610.000	273.000	600.000	290.000	599.500	900.000	594.370	395.000	593.320	400.000
GR	593.400	405.000	597.500	420.000	600.000	900.000	610.000	610.000	0.000	0.000
ET	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000

PRINTED IN U.S.A.
POPULARLOD PRINTED BY ROTARY MANIFOLD FORMS.

GR	594.160	1390.410	592.600	1396.000	592.310	1400.000	592.600	1404.000	594.160	1409.590
GR	597.200	1409.600	599.900	1409.610	599.200	1500.000	599.300	1575.000	610.000	1576.000
NC	0.060	0.060	0.025	0.000	0.000	0.000	0.000	0.000	0.000	0.000
ET	0.000	0.000	0.000	0.000	9.100	0.000	0.000	0.000	1125.000	1600.000

1 FOOT INSIDE D/S TELEGRAPH BRIDGE

X1	15363.000	0.000	0.000	0.000	1.000	1.000	1.000	0.000	0.000	0.000
X2	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.920	0.000
DT	5.000	1390.400	599.950	597.200	1390.410	599.900	597.200	1400.000	599.900	597.200
BT	1409.600	599.900	597.200	1409.610	599.900	0.000	0.000	0.000	0.000	0.000
ET	0.000	0.000	0.000	0.000	9.100	0.000	0.000	0.000	1125.000	1600.000

1 FOOT INSIDE U/S END TELEGRAPH BRIDGE

X1	15434.000	0.000	0.000	0.000	71.000	71.000	71.000	0.000	0.000	0.000
X2	0.000	0.000	0.000	0.000	0.000	0.000	1.000	0.000	0.000	0.000
NC	0.060	0.060	0.040	0.000	0.000	0.000	0.000	0.000	0.000	0.000
ET	0.000	0.000	0.000	0.000	9.100	0.000	0.000	0.000	1125.000	1600.000

U/S FACE TELEGRAPH RD

X1	15435.000	0.000	0.000	0.000	1.000	1.000	1.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	599.900	599.900
ET	0.000	0.000	0.000	0.000	9.100	0.000	0.000	0.000	1125.000	1600.000

ROBERT, U/S OF TELEGRAPH RD

X1	15460.000	0.000	0.000	0.000	25.000	25.000	25.000	0.000	0.000	0.000
NC	0.060	0.060	0.040	0.100	0.300	0.000	0.000	0.000	0.000	0.000
ET	0.000	0.000	0.000	0.000	9.100	0.000	0.000	0.000	275.000	775.000

VALLEY SECT BASED ON FIELD BOOK NO 600

X1	16873.000	12.300	646.000	654.000	1413.000	1413.000	1413.000	0.000	0.000	0.000
GR	613.000	299.000	615.000	299.000	597.400	300.300	595.500	435.000	592.000	646.000
GR	592.900	450.000	592.650	454.000	593.930	463.000	603.350	483.000	599.930	650.000
GR	600.300	750.000	610.000	751.000	2.000	0.000	0.000	0.000	0.000	0.000
ET	0.000	0.000	0.000	0.000	9.100	0.000	0.000	0.000	285.000	603.000

VALLEY SECTION AT CORP/LIMIT BROWNSTOWN/FLAT ROCK

X1	17673.000	9.600	395.000	405.000	500.000	500.000	500.000	0.000	0.000	0.000
GR	610.000	275.300	600.000	290.000	599.500	380.000	596.370	395.000	593.320	400.000
GR	593.400	405.000	599.500	620.000	600.000	600.000	610.000	610.000	0.000	0.000
ET	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000

PRINTED IN U.S.A.
FORM 1311-6C PRINTED BY ROTARY MANIFOLD FORMS

*PROF 1

CCHV= 0.100 CEHV= 0.300

*SECNO ****

SECNO	DEPTH	CHSEL	CRIWS	WSELK	EG	HV	HL	QLOSS	BANK ELEV
0	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TLA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IN2	ICONT	CORAR	TOPWID	ENDST

3470 ENCROACHMENT STATIONS= 1350.0 1600.1 TYPE= 1 TARGET= 250.000

450. FEET D/S OF D/S FACE OF OLMSTEAD RD. ROCKWOOD SECT. 19073.

0.00	0.78	585.40	0.00	586.48	586.48	0.00	0.00	0.00	580.60
705.	367.	319.	219.	760.	109.	450.	0.	0.	577.90
0.00	0.40	0.65	0.40	0.035	0.035	0.035	0.000	577.70	1330.00
0.000014	0.	C.	0.	0	0	0	0.00	250.00	1600.00

FLOW DISTRIBUTION FOR SECNO= 0.00 CHSEL= 586.48

STA=	1350.	1430.	1619.	1630.	1900.	1923.	1932.	1603.
PER Q=	8.8	3.7	3.7	35.8	16.9	5.0	26.1	
AREA=	176.5	69.9	57.0	657.1	189.0	63.3	386.2	
VEL=	0.4	0.4	0.5	0.6	0.6	0.6	0.5	

*SECNO 1.000

D/S. FACE OF OLMSTEAD ROAD ROCKWOOD SECT. 19523.

1.00	9.57	586.47	0.00	0.00	586.51	0.04	0.02	0.01	585.80
705.	19.	320.	366.	42.	146.	342.	16.	3.	585.30
0.00	0.46	0.32	1.07	0.035	0.035	0.035	0.036	573.93	577.72
0.000320	400.	450.	500.	3	0	0	0.30	572.28	950.0

FLOW DISTRIBUTION FOR SECNO= 1.00 CHSEL= 586.47

STA=	579.	600.	692.	700.	800.	900.	950.
PER Q=	3.0	2.0	65.6	10.5	25.1	16.4	
AREA=	2.0	59.6	963.0	90.4	157.0	93.9	
VEL=	0.2	0.5	2.2	0.8	1.1	1.2	

*SECNO 2.000

3570 NORMAL BRIDGE.NO.= 25 MIN ELCRD= 584.20 MAX ELCR= 585.90

1.FOOT INSIDE BRIDGE D/S END ROCKWOOD SECT. 19524.

2.00	9.57	586.47	0.00	0.00	586.51	0.04	0.03	0.00	585.80
705.	30.	308.	366.	41.	91.	343.	16.	3.	585.60
0.00	0.73	0.09	1.72	C.018	0.031	0.010	0.034	576.90	576.75
0.000262	1.	1.	1.	0	0	0	-55.08	571.25	950.00

FLOW DISTRIBUTION FOR SECNO= 2.00 CHSEL= 586.47

STA=	579.	600.	692.	708.	800.	900.	950.
PER Q=	0.1	4.1	12.7	16.7	40.2	26.1	
AREA=	1.9	38.8					

PRINTED IN U.S.A.
FORM 1411-08 PRINTED BY ROTARY MANIFOLD FORMS.

VEL= 0.3 0.7 1.0 1.3 1.8 2.0

*SECNO 3.000

3370 NORMAL BRIDGE,NRD= 23 MIN ELTRD= 584.20 MAX ELLC= 583.90

1.FOOT INSIDE BRIDGE U/S END ROCKWOOD SECT. 19570.

3.00	9.59	586.49	0.00	0.00	586.53	0.04	0.01	0.00	585.00
705.	31.	88.	586.	43.	91.	345.	10.	4.	585.80
0.09	0.73	0.97	1.79	0.016	0.031	0.018	0.034	576.90	576.60
0.000251	66.	66.	66.	0	0	0	-53.08	373.30	950.00

FLOW DISTRIBUTION FOR SECNO= 3.00 CWSEL= 586.49

STA=	376.	500.	692.	708.	800.	900.	959.
PER Q=	0.1	4.3	12.5	16.8	40.1	26.1	
AREA=	2.2	40.5	90.8	91.4	158.9	94.4	
VEL=	0.3	0.8	1.0	1.3	1.8	2.0	

*SECNO 4.000

SECNO	DEPTH	CWSEL	CRITS	SSELK	EG	HV	HL	QLOSS	BANK ELEV
Q	SLOB	QCH	QROB	ALOB	ACH	AROB	VOL	THA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IN2	ICONT	CORAR	TOPWID	ENDST

U/S FACE OF OLDSTEAD ROAD ROCKWOOD SECT. 19571.

4.00	9.57	586.47	0.00	0.00	586.53	0.06	0.00	0.01	585.80
705.	17.	363.	325.	42.	144.	343.	10.	4.	585.80
0.09	0.50	2.53	1.95	0.045	0.035	0.045	0.035	576.90	577.33
0.000490	1.	1.	1.	1	3	0	0.00	372.85	950.00

FLOW DISTRIBUTION FOR SECNO= 4.00 CWSEL= 586.47

STA=	577.	600.	692.	750.	805.	900.	930.			
PER Q=	0.0	2.4	51.5	9.3	22.3	14.3				
AREA=	2.1	39.0	163.3	90.7	158.1	94.1				
VEL=	0.1	0.4	2.5	0.7	1.0	1.1				

*SECNO 5.000

750.FEET U/S OF C/S FACE OF OLDSTEAD RD.ROCKWOOD SECT. 20521.

5.00	7.96	586.56	0.00	0.00	586.56	0.00	0.03	0.01	582.00
750.	171.	74.	405.	606.	161.	1595.	85.	12.	580.60
0.73	0.28	0.92	0.35	0.045	0.035	0.045	0.035	578.60	41.85
0.000312	773.	755.	725.	2	3	0	0.00	595.87	637.02

FLOW DISTRIBUTION FOR SECNO= 5.00 CWSEL= 586.56

STA=	41.	50.	110.	210.	230.	310.	410.	510.	610.	637.
PER Q=	0.0	4.6	18.6	13.1	19.9	21.1	14.2	7.0	0.2	
AREA=	4.7	159.7	461.2	141.0	420.9	476.4	436.2	246.2	15.7	
VEL=	0.1	2.2	0.5	3.5	0.5	0.5	0.5	0.2	0.1	

*SECNO 6.000

1450.FEET U/S OF U/S FACE OF OLMSTEAD ROCKWOOD SECT. 21021. CORP.LIMIT

	6.00	7.67	586.57	0.00	0.00	586.57	0.00	0.01	0.00	583.70
	730.	336.	113.	280.	974.	202.	801.	70.	21.	582.40
	1.24	0.35	0.56	0.35	0.045	0.035	0.045	0.035	576.90	147.56
	0.000017	675.	700.	725.	2	0	0	0.00	499.70	647.26

FLOW DISTRIBUTION FOR SECNO= 6.00 CWSEL= 586.57

STA=	148.	200.	300.	400.	434.	500.	600.	647.
PER Q=	4.2	24.8	17.1	15.5	16.4	20.2	1.8	
AREA=	125.1	472.2	377.2	202.0	311.6	417.2	72.6	
VEL=	0.2	0.4	0.3	0.6	0.4	0.4	0.2	

CCHV= 0.300 CEHV= 0.500

*SECNO 1944.000

A-SECTION D/S OF WOODRUFF RD.

1944.00	5.89	586.59	0.00	0.00	586.77	0.18	0.11	0.09	583.13
730.	240.	413.	77.	303.	93.	122.	119.	38.	584.07
1.43	0.79	4.36	0.63	0.100	0.040	0.100	0.043	550.70	75.85
0.001813	1400.	2430.	1944.	0	0	0	0.00	374.30	650.18

FLOW DISTRIBUTION FOR SECNO= 1944.00 CWSEL= 586.59

STA=	76.	203.	296.	301.	301.	319.	319.	321.	400.	450.
PER Q=	12.6	18.2	2.0	0.0	56.8	0.0	0.6	0.0	1.9	
AREA=	136.4	153.6	13.2	0.2	92.6	0.1	4.5	30.9	30.0	
VEL=	0.7	0.9	1.1	0.9	4.5	0.7	1.0	0.7	0.5	

*SECNO 2044.000

D/S FACE OF WOODRUFF RD. BRIDGE REPEATED SCOT. 1976

2044.00	6.01	593.71	0.00	0.00	587.11	0.40	0.23	0.11	585.13
730.	117.	549.	63.	170.	95.	96.	120.	38.	584.07
1.44	0.69	5.80	0.66	0.100	0.040	0.100	0.043	530.70	75.82
0.038994	100.	100.	100.	2	5	0	0.00	374.36	650.10

FLOW DISTRIBUTION FOR SECNO= 2044.00 CWSEL= 586.71

STA=	76.	203.	296.	301.	301.	319.	319.	321.	400.	450.
PER Q=	11.6	4.1	0.4	0.3	75.3	0.0	0.5	3.0	3.2	
AREA=	111.4	93.6	4.3	0.1	94.6	0.1	3.7	56.4	35.7	
VEL=	2.1	0.8	0.7	0.4	5.0	1.0	0.6	0.3	0.6	

*SECNO 2045.000

SECNO	DEPTH	CWSEL	CRIWS	HSELJ	EG	KV	IL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	LOB	TCA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XAL	XNCH	XAR	WTH	ELTRN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IHS	XCONT	COORR	TOPWID	ENDST

3370 NORMAL BRIDGE/NRB= 1 MIN ELTRD= 585.63 MAX FLLC= 586.27

1 FOOT INSIDE OF D/S FACE OF BRIDGE

2045.00 6.03 587.55 586.70 1 0.00 587.21 0.047 0.000 0.10 583.13

	730.	371.	156.	203.	264.	40.	149.	120.	38.	584.07
	1.44	1.41	3.89	1.36	0.070	0.025	0.070	0.043	580.70	75.72
	0.003484	1.	1.	1.	16	6	0	-65.91	374.57	450.28

FLOW DISTRIBUTION FOR SECNO= 2045.00 CWSEL= 587.13

STA=	76.	200.	296.	301.	319.	321.	400.	450.	450.
PER Q=	33.9	16.0	0.8	21.4	0.4	16.8	10.6	0.0	
AREA=	164.2	94.3	5.1	40.2	2.5	89.9	56.9	0.2	
VEL=	1.5	1.2	0.2	3.9	1.1	1.4	1.4	0.3	

*SECNO 2074.000

3370 NORMAL BRIDGE,NRD= 8 MIN ELTRD= 585.63 MAX ELLC= 584.37

1 FOOT INSIDE OF U/S FACE OF BRIDGE

	2074.00	6.56	587.26	0.00	0.00	587.29	0.03	0.06	0.01	583.13
	495.	259.	93.	143.	291.	40.	165.	121.	39.	584.07
	1.44	0.89	2.31	0.86	0.070	0.025	0.070	0.043	580.70	75.69
	0.001229	20.	20.	29.	3	0	0	-68.05	374.65	450.31

FLOW DISTRIBUTION FOR SECNO= 2074.00 CWSEL= 587.26

STA=	76.	200.	296.	301.	319.	321.	400.	450.	450.
PER Q=	34.4	17.0	0.9	18.7	0.4	17.4	11.0	0.0	
AREA=	179.3	106.0	5.7	40.2	2.6	99.5	63.0	0.2	
VEL=	1.0	0.6	0.8	2.3	0.7	0.9	0.9	0.2	

*SECNO 2075.000

U/S FACE OF WOODRUFF RD. BRIDGE

	2073.00	6.55	587.24	0.00	0.00	587.31	0.08	0.00	0.03	583.13
	495.	128.	296.	71.	287.	104.	165.	121.	39.	584.07
	1.46	0.44	2.65	0.43	0.100	0.040	0.100	0.043	580.70	75.69
	0.000630	1.	1.	1.	2	0	0	0.00	374.62	450.31

FLOW DISTRIBUTION FOR SECNO= 2073.00 CWSEL= 587.24

STA=	76.	200.	296.	301.	301.	319.	319.	321.	400.	450.	450.
PER Q=	16.9	8.3	0.7	0.2	59.7	0.0	0.3	8.5	5.4	0.0	
AREA=	176.3	103.7	7.3	0.2	103.8	0.2	6.8	97.6	61.0	3.2	
VEL=	0.5	0.4	0.3	0.1	2.0	0.3	0.3	0.4	0.4	0.1	

*SECNO 2100.000

K-SECTION U/S OF WOODRUFF RD. REPEATED SECT. 2075.5

	2100.00	6.55	587.25	0.00	0.00	587.33	0.07	0.02	0.00	583.13
	495.	128.	296.	71.	293.	104.	164.	121.	39.	584.07
	1.45	0.44	2.61	0.43	0.100	0.040	0.100	0.043	580.70	75.69
	0.000630	25.	25.	25.	0	0	0	0.00	374.63	450.31

FLOW DISTRIBUTION FOR SECNO= 2100.00 CWSEL= 587.25

STA=	76.	200.	296.	301.	301.	319.	319.	321.	400.	450.	450.
PER Q=	17.1	8.4	0.7	0.2	59.2	0.0	0.3	8.6	5.5	0.0	
AREA=	179.2	105.9	7.4	0.2	104.2	0.2	6.8	99.	62.9	3.2	

PRINTED IN U.S.A.
FORM 1411-GD PRINTED BY ROTARY MANIFOLD FORMS

VEL= 0.5 0.4 0.5 0.1 2.8 0.5 0.5 0.4 0.4 0.1

*SECNO 3073.000

VALLEY SECTION BASED ON FIELD BOOK AND QUAD MAP

3073.00	6.03	587.71	0.00	0.00	587.76	0.02	0.40	0.01	581.78
495.	22.	161.	312.	44.	75.	815.	138.	49.	581.78
1.73	0.50	2.14	0.33	0.100	0.040	0.100	0.042	581.08	279.01
0.000289	973.	973.	973.	2	0	0	0.00	510.42	789.43

FLOW DISTRIBUTION FOR SECNO= 3073.00 CWSEL= 587.71

STA=	279.	294.	306.	316.	416.	516.	616.	789.
PER Q=	4.5	32.5	6.6	16.3	18.0	16.0	8.0	
AREA=	44.5	75.4	30.8	200.8	213.3	198.3	133.5	
VEL=	0.5	2.1	0.8	0.6	0.6	0.4	0.2	

CCHV= 0.100 CEHV= 0.300

*SECNO 4573.000

SECNO	DEPTH	CWSEL	CRIWS	USELK	EG	HV	HL	ULOSS	BANK ELEV
Q	WLOB	ICH	SRCB	ALOB	ACH	AROB	WOL	TSA	LEFT/RIGHT
TIME	VLOB	VCH	VRCB	RSL	XNCH	XBR	CTN	ELMIN	SSTA
SLOPE	XLOBL	XLEV	WLOBR	XTOTAL	XNF	ICOLT	CORAR	TOPWID	ENDST

VALLEY SECTION BASED ON FIELD BOOK AND QUAD MAP

4573.00	6.46	588.26	0.00	0.00	588.47	0.11	0.70	0.02	583.10
495.	96.	202.	117.	276.	82.	269.	166.	67.	583.10
1.93	0.35	3.43	0.44	0.120	0.040	0.120	0.041	581.90	804.12
0.000325	1350.	1300.	1690.	2	0	6	0.00	538.26	1422.36

FLOW DISTRIBUTION FOR SECNO= 4573.00 CWSEL= 588.26

STA=	384.	900.	1000.	1100.	1185.	1195.	1207.	1215.	1300.	1430.	1622.
PER Q=	0.2	4.8	7.0	6.3	3.0	56.9	3.5	9.7	90.2	0.3	
AREA=	6.7	78.7	99.0	60.7	22.5	82.1	24.9	112.6	123.8	8.7	
VEL=	0.2	0.5	0.6	0.8	0.6	1.6	0.7	0.9	0.6	0.2	

CCHV= 0.300 CEHV= 0.300

*SECNO 4537.900

X-SECTION D/S OF BRIDGE E. OF GIBRALTAR RD.

4537.90	4.77	589.60	0.00	0.00	589.68	0.07	1.20	0.01	584.98
495.	103.	242.	150.	95.	85.	132.	185.	80.	584.98
2.18	1.07	2.85	1.14	0.070	0.035	0.070	0.040	586.83	228.85
0.000569	1765.	1765.	1765.	2	2	0	0.00	97.63	325.89

FLOW DISTRIBUTION FOR SECNO= 4537.90 CWSEL= 589.60

STA=	229.	244.	260.	255.	283.	290.	316.	326.
PER Q=	2.3	12.4	5.9	48.9	6.0	21.9	2.4	
AREA=	20.2	54.0	21.7	84.9	22.0	92.2	10.8	
VEL=	0.6	1.1	1.3	2.9	1.4	1.2	0.7	

*SECNO 4527.000

3570 ENCROACHMENT STATIONS= 1 80.0 171.0 TYPE= 1 TARGET= 90.000

PRINTED IN U.S.A.
FORM 1411-08-PRINTED BY ROYARY MANIFOLD FORMS

10: D/S OF DRIVEWAY

6527.00	4.93	589.73	0.00	0.00	589.81	0.08	0.13	0.00	585.50
495.	175.	47.	273.	79.	133.	110.	186.	81.	585.50
2.20	2.22	0.35	2.48	0.040	0.350	0.040	0.047	584.80	80.00
0.000865	190.	190.	190.	3	0	0	0.00	90.00	170.00

FLOW DISTRIBUTION FOR SECNO= 6527.00 CHSEL= 589.73

STA=	80.	94.	110.	130.	164.	170.
PER Q=	6.5	20.9	9.6	50.4	4.7
AREA=	22.3	56.6	132.6	95.8	14.3
VEL=	1.5	2.5	0.4	2.6	1.6

*SECNO 6537.500

5495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 592.40 ELREA= 592.40

1: D/S OF DRIVEWAY

6537.50	4.31	589.81	0.00	0.00	589.85	0.04	0.02	0.01	586.50
495.	7.	495.	0.	0.	317.	0.	186.	81.	506.40
2.21	0.00	1.56	0.00	0.040	0.350	0.040	0.047	585.00	99.00
0.024371	10.	10.	10.	2	0	0	0.00	84.40	183.40

FLOW DISTRIBUTION FOR SECNO= 6537.50 CHSEL= 589.81

STA=	99.	183.
PER Q=	100.0	
AREA=	317.1	
VEL=	1.9	

*SECNO 6530.300

3370 NORMAL BRIDGE,WRD= 25 MXN E.TRD= 592.60 MAX ELLC= 591.80

3493 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 592.40 ELREA= 592.40

D/S FACE OF DRIVEWAY

6536.50	6.81	589.27	0.00	0.00	589.89	0.04	0.00	0.00	586.50
495.	0.	495.	0.	0.	299.	0.	164.	61.	586.50
2.21	0.00	1.66	0.00	0.040	0.025	0.040	0.047	585.00	99.00
0.000151	1.	1.	1.	1	0	0	-22.61	84.40	183.40

FLOW DISTRIBUTION FOR SECNO= 6530.50 CHSEL= 589.81

STA=	99.	183.
PER Q=	100.0	
AREA=	292.9	
VEL=	1.7	

*SECNO 6578.000

SECNO	DEPTH	QLSEL	CHLS	WSELK	EG	KV	HL	DLOSS	CAN.E.CV	
Q	QLOB	QCH	AROB	LOB	ACH	AROB	VOL	HEV	LEFT/RIGHT	
TIME	VLOB	VCH	VROB	XNL	XNCH	XNP	WTN	ELTIM	&STA	
SLOPE	XLOBL	XLCH	XLOBR	LITRIAL	CR2	IQUAL	CORAR	TOPWID	ENDST	

PRINTED IN U.S.A.
FORM 341-00 PRINTED BY ROTARY MANIFOLD FORMS.

3370 NORMAL BRIDGE,NRD= 25 MIN ELTRD= 592.60 MAX ELLC= 591.60

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 592.50 ELREA= 592.50

U/S FACE OF DRIVEWAY

6578.00	4.82	589.82	0.00	0.00	589.86	0.04	0.01	0.00	586.50
495.	0.	495.	0.	0.	299.	0.	187.	81.	586.40
2.21	0.00	1.66	0.00	0.040	0.025	0.040	0.047	585.00	99.00
0.000151	40.	40.	40.	2	0	0	-22.60	84.40	183.40

FLOW DISTRIBUTION FOR SECNO= 6578.00 CWSEL= 589.82

STA= 99. 198.
PER Q= 100.0
AREA= 290.9
VEL= 1.7

*SECNO 6579.000

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 592.70 ELREA= 592.60

1: U/S OF DRIVEWAY

6579.00	4.82	589.82	0.00	0.00	589.86	0.04	0.00	0.00	586.50
495.	0.	495.	0.	0.	317.	0.	187.	81.	586.40
2.21	0.00	1.56	0.00	0.040	0.035	0.040	0.047	585.00	99.00
0.000263	1.	1.	1.	0	1	0	0.00	32.40	183.40

FLOW DISTRIBUTION FOR SECNO= 6579.00 CWSEL= 589.82

STA= 99. 198.
PER Q= 100.0
AREA= 317.4
VEL= 1.6

*SECNO 6609.000

50: U/S OF DRIVEWAY

6609.00	4.89	589.79	0.03	0.06	589.96	0.15	0.02	0.06	589.01
495.	1.	493.	1.	2.	153.	1.	187.	81.	589.10
2.22	0.65	3.12	0.59	0.040	0.035	0.040	0.047	584.90	112.68
0.001073	50.	50.	50.	2	0	0	0.00	54.62	167.30

FLOW DISTRIBUTION FOR SECNO= 6609.00 CWSEL= 589.79

STA= 198. 117. 133. 167.
PER Q= 0.2 99.4 0.2
AREA= 1.7 198.3 1.5
VEL= 0.5 3.1 0.6

DCHV= 0.300 CEHV= 0.500
*SECNO 7174.000

PRINTED IN U.S.A.
FORM 1311-00 PRINTED BY ROTARY MANIFOLD FORMS.

3470 ENCROACHMENT STATIONS= 242.0 307.0 TYPE= 1 TARGET= 65.000

X-SECTION D/S OF GIBRALTAR RD. BRIDGE

	7174.00	5.33	590.38	0.00	0.00	590.57	0.19	0.41	0.02	585.60
	495.	58.	322.	115.	45.	76.	77.	189.	82.	585.60
	2.26	1.26	4.25	1.49	0.070	0.035	0.070	0.046	585.05	242.00
	0.001162	547.	547.	547.	2	0	0	0.00	65.00	307.00

FLOW DISTRIBUTION FOR SECNO= 7174.00 CWSEL= 590.38

STA=	242.	251.	268.	283.	307.
PER Q=	0.3	11.4	65.1	23.2	
AREA=	3.4	42.5	75.8	77.3	
VEL=	0.4	1.3	4.3	1.5	

*SECNO 7274.000

3470 ENCROACHMENT STATIONS= 189.0 389.0 TYPE= 1 TARGET= 200.000

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 593.30 ELREA= 593.30

D/S FACE OF GIBRALTAR RD. BRIDGE

7274.00	5.26	590.31	0.00	0.00	591.00	0.68	0.18	0.25	585.60
495.	0.	495.	0.	0.	75.	0.	189.	82.	585.60
2.27	0.00	6.64	0.00	0.070	0.035	0.070	0.046	585.05	209.15
0.003191	100.	100.	100.	2	0	0	0.00	14.95	304.10

FLOW DISTRIBUTION FOR SECNO= 7274.00 CWSEL= 590.31

STA=	209.	304.
PER Q=	100.0	
AREA=	76.8	
VEL=	6.6	

SPECIAL BRIDGE

SD	AK	AKOR	COEF	ROLEN	SKC	HLD	DAREA	SS	ELCHD	ELCHU
	0.00	2.57	3.00	0.00	12.20	0.00	34.00	0.00	582.30	585.05

*SECNO 7275.000

SECNO	DEPTH	CWSEL	CRIWS	MSELK	BO	HV	IL	ELOSS	BANK ELEV	
Q	ELOB	ACH	QROD	ALOB	ACH	AROD	VOL	TWA	LEFT/RIGHT	
TIME	WLOB	WCH	VROB	XNL	XNCH	XNR	MTN	ELMIN	SSTA	
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IN2	ICONT	CORAR	TOPWID	ENDST	

PRESSURE FLOW

BOPRS	EGLWC	HB	QWEIR	QPR	DAREA	TRAPEZOID AREA	ELLC	ELTRD
591.70	590.08	2.00	0.	495.	84.	84.	539.36	592.37

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 592.93 ELREA= 592.37

PRINTED IN U.S.A.
FORM 1411-GO PRINTED BY ROTARY MANIFOLD FORMS

U/S FACE OF GIBRALTAR RD. BRIDGE

7373.00	6.21	591.26	0.00	0.00	591.70	0.44	0.70	0.00	585.05	
495.	0.	495.	0.	0.	93.	0.	190.	82.	585.05	
2.27	0.00	5.33	0.00	0.070	0.035	0.070	0.046	585.05	469.15	
0.002194	99.	99.	99.	2	0	0	0.00	14.95	504.10	

FLOW DISTRIBUTION FOR SECNO= 7373.00 CWSEL= 591.26

STA=	439.	504.	
PER Q=	100.0		
AREA=	92.0		
VEL=	5.3		

*SECNO 7398.000

3473 ENCROACHMENT STATIONS= 400.0 633.0 TYPE= 1 TARGET= 233.000

X-SECTION U/S OF GIBRALTAR RD. BRIDGE

7398.00	6.54	591.59	0.00	0.00	591.80	0.21	0.03	0.07	585.05
495.	43.	396.	51.	40.	93.	63.	190.	82.	585.05
2.28	1.16	4.53	1.19	0.070	0.035	0.070	0.046	585.05	470.78
0.000751	25.	25.	25.	2	0	0	0.00	46.61	517.16

FLOW DISTRIBUTION FOR SECNO= 7398.00 CWSEL= 591.59

STA=	477.	489.	504.	517.
PER Q=	9.7	80.1	10.3	
AREA=	40.5	37.8	42.8	
VEL=	1.2	4.1	1.2	

CCHV= 0.100 CEHV= 0.300
*SECNO 8573.000

VALLEY SECTION N. OF GIBRALTAR RD. BASED ON FIELD BOOK AND QUAD MAP

8573.00	6.90	592.40	0.00	0.00	592.46	0.06	0.65	0.01	585.75
495.	233.	215.	46.	427.	93.	706.	200.	90.	367.65
2.66	0.55	2.91	0.49	0.070	0.035	0.070	0.045	585.50	660.45
0.001424	1175.	1175.	1175.	3	0	3	2.00	954.08	1215.11

FLOW DISTRIBUTION FOR SECNO= 8573.00 CWSEL= 592.40

STA=	660.	750.	900.	1036.	1047.	1059.	1066.	1200.	1215.
PER Q=	0.6	19.1	19.5	7.3	44.1	3.5	5.6	0.1	
AREA=	15.8	187.8	183.9	39.6	75.0	20.1	84.1	2.3	
VEL=	0.1	0.5	0.5	0.9	2.9	0.3	0.5	0.1	

CCHV= 0.100 CEHV= 0.300
*SECNO 9000.000

9000.00	6.61	592.59	0.00	0.00	592.74	0.15	0.25	0.03	585.23
495.	174.	291.	28.	325.	71.	88.	293.	95.	588.08
2.53	0.35	4.07	0.41	0.070	0.035	0.090	0.044	585.98	734.85
0.000882	627.	427.	427.	2	0	0	0.30	465.62	1200.48

FLOW DISTRIBUTION FOR SECNO= 9000.00 CWSEL= 592.59

STA=	735.	900.	1036.	1047.	1059.	1066.	1200.
PER Q=	18.9	14.9	7.3	58.8	3.1	2.0	

PRINTED IN U.S.A.
FORM 1411 08-PRINTED BY ROTARY MANIFOLD FORMS

AREA=	144.4	144.1	36.4	71.4	18.1	44.8
VEL=	0.5	0.5	1.0	4.1	0.8	0.2

*SECNO 9900.000

9900.00	6.50	593.04	0.00	0.00	593.23	0.18	0.48	0.01	586.79
495.	167.	306.	23.	293.	70.	49.	211.	100.	583.64
2.58	0.57	4.36	0.46	0.090	0.035	0.090	0.044	566.54	753.74
0.001034	500.	500.	500.	2	0	0	0.00	426.68	1180.43

FLOW DISTRIBUTION FOR SECNO= 9900.00 CHSEL= 593.04

STA=	754.	900.	1036.	1047.	1059.	1066.	1180.
PER Q=	12.6	13.5	7.5	61.8	3.1	1.4	
AREA=	128.3	129.9	35.3	70.2	17.4	31.8	
VEL=	0.5	0.5	1.1	4.4	0.9	0.2	

*SECNO 10173.000

SECNO	DEPTH	CHSEL	CRIHS	SELK	EG	HV	HL	CLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	STN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IN2	ICONT	CORAR	IOPHID	ENDST

VALLEY SECTION BASED ON FIELD BOOK AND QUAD MAP

10173.00	6.36	593.76	0.00	0.00	593.98	0.22	0.74	0.01	587.20
495.	117.	266.	112.	140.	52.	124.	216.	105.	587.10
2.64	0.74	5.08	0.55	0.090	0.035	0.090	0.044	587.10	745.20
0.001176	673.	673.	673.	2	0	0	0.00	252.06	396.15

FLOW DISTRIBUTION FOR SECNO= 10173.00 CHSEL= 593.76

STA=	143.	150.	253.	264.	290.	313.	305.	310.	343.	363.	396.
PER Q=	0.3	3.2	3.9	10.6	33.7	4.2	7.7	5.2	7.1	2.0	
AREA=	0.9	62.8	67.9	37.9	52.3	12.1	21.0	24.1	43.2	22.5	
VEL=	0.7	0.4	1.7	1.2	5.1	1.7	1.8	1.1	0.6	0.4	

*SECNO 11673.000

SPLIT DIVERSE FLOW

VALLEY SECTION BASED ON FIELD BOOK AND QUAD MAP

11673.00	6.41	595.17	0.00	0.00	595.38	0.13	1.32	0.01	588.61
500.	127.	239.	24.	231.	64.	41.	227.	114.	586.76
2.80	0.35	3.73	0.59	0.090	0.035	0.090	0.043	586.76	102.31
0.000669	1360.	1500.	1800.	2	0	0	0.00	270.19	389.43

FLOW DISTRIBUTION FOR SECNO= 11673.00 CHSEL= 595.17

STA=	302.	150.	253.	283.	255.	295.	305.	343.	366.
PER Q=	3.5	19.0	1.1	0.0	8.6	61.2	5.7	0.5	
AREA=	34.9	145.5	9.9	0.7	40.5	64.0	27.1	13.9	
VEL=	0.3	0.5	0.4	0.2	0.8	5.7	0.8	0.1	

SCHV= 0.300 CE HI= 0.500

*SECNO 12356.000

SPLIT DIVERSE FLOW

PRINTED IN U.S.A.
FORM 1411-08 PRINTED BY ROTARY MANIFOLD FORMS.

3470 ENCROACHMENT STATIONS= 692.0 808.0 TYPE= 1 TARGET= 116.000

X@SECT.D/S OF R.R CULVERTS

12356.00	5.83	595.71	0.00	0.00	596.04	0.35	0.65	0.11	590.00	
390.	20.	308.	62.	26.	58.	71.	231.	117.	590.00	
2.84	0.77	5.34	0.87	0.110	0.035	0.110	0.042	589.88	692.00	
0.001526	683.	683.	683.	2	2	0	0.00	92.27	808.00	

FLOW DISTRIBUTION FOR SECNO= 12356.00 CWSEL= 595.71

STA=	692.	716.	745.	755.	770.	808.
PER Q=	0.3	4.9	79.0	13.7	2.1	
AREA=	5.0	21.1	57.7	58.2	22.5	
VEL=	0.2	0.9	5.5	1.1	0.4	

*SECNO 12456.000

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 602.60 ELREA= 602.60

D/S FACE OF DUAL 2'X 6.5' CMP'S

12456.00	6.17	596.17	0.00	0.00	596.35	0.18	0.23	0.05	592.00	
390.	0.	390.	0.	0.	115.	0.	232.	117.	592.00	
2.66	0.00	3.40	0.00	0.110	0.035	0.110	0.042	590.00	739.00	
0.000977	191.	191.	191.	2	0	0	0.00	22.00	761.00	

FLOW DISTRIBUTION FOR SECNO= 12456.00 CWSEL= 596.17

STA=	739.	761.
PER Q=	100.0	
AREA=	114.3	
VEL=	3.4	

SPECIAL BRIDGE

SB	XK	XTOP	CBTW	RDLEN	B.C	B.S	LAREA	SS	ELCHD	ELCHD
	0.00	3.23	3.00	0.00	11.85	0.00	77.00	3.00	590.40	390.00

*SECNO 12412.000

PRESSURE FLOW

EGPRS	EGLOC	HS	QWEIR	QPR	OAREA	TRAPEZOID AREA	ELLC	ELTRD
597.45	596.83	0.00	0.	390.	77.	71.	596.40	602.60

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 602.60 ELREA= 602.60

DUAL CMP'S MEET DUAL BOX CULVERTS HERE.

12412.00	6.85	597.25	0.00	0.00	597.45	0.21	1.11	0.00	591.40	
390.	0.	390.	0.	0.	137.	0.	252.	117.	591.40	
2.87	0.00	3.65	0.00	0.110	0.035	0.110	0.042	590.40	739.00	
1.000101	156.	156.	156.	2	0	0	0.00	17.00	756.00	

PRINTED IN U.S.A.
FORM 1211-GO PRINTED BY ROTARY MANIFOLD FORMS.

FLOW DISTRIBUTION FOR SECNO= 12612.00 CWSEL= 597.25

STA= 739. 756.
PER Q= 100.0
AREA= 106.3
VEL= 3.7

SPECIAL BRIDGE

SB	XK	XRDR	CDFO	RDLEN	DUC	DWP	BAREA	SS	ELCHN	ELCHD
	1.25	1.74	3.00	0.00	16.67	1.00	94.00	0.00	590.40	590.40

*SECNO 12647.000

SECNO	DEPTH	CWSEL	CRIWS	VSELK	EG	HV	HL	DLOSS	BANK ELEV	
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT	
TIME	VLOB	VCH	VROB	XNL	XNCL	XNR	WTN	ELMIN	SSTA	
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IM2	ICONT	CORAR	TOPWID	ENDST	

PRESSURE FLOW

EGPRS	EGLOC	WS	QWEIR	QPR	BAREA	TRAPEZOID AREA	ELLC	ELTRD
597.71	597.45	0.03	0.	390.	94.	94.	596.40	602.60

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 602.60 ELREA= 602.60

U/S FACE OF R.R. CULVERTS

12647.00	7.55	597.55	0.00	0.00	597.71	0.16	3.26	0.00	590.40
390.	0.	390.	0.	0.	122.	0.	232.	117.	590.40
2.87	0.00	3.21	0.00	0.110	0.035	0.110	0.042	590.40	739.00
0.000658	35.	35.	35.	2	0	0	0.00	17.00	756.00

FLOW DISTRIBUTION FOR SECNO= 12647.00 CWSEL= 597.55

STA= 739. 756.
PER Q= 100.0
AREA= 121.6
VEL= 3.2

*SECNO 12680.000

3470 ENCROACHMENT STATIONS= 730.0 765.0 TYPE= 1 TARGET= 35.000

XSECT.U/S OF R.R.CULVERT & D/S OF 96 CMP

12680.00	6.80	597.62	0.00	0.00	597.74	0.12	0.62	0.01	590.74
590.	20.	343.	27.	37.	117.	48.	232.	117.	590.74
2.88	0.55	2.93	0.59	0.110	0.035	0.110	0.042	590.74	730.00
0.000365	33.	33.	33.	2	0	0	0.00	35.00	765.00

FLOW DISTRIBUTION FOR SECNO= 12680.00 CWSEL= 597.62

STA= 730. 739. 756. 765.

FORM 1411.08 PRINTED BY ROTARY MANIFOLD FORMS
PRINTED IN U.S.A.

PER Q=	5.2	88.0	6.9
AREA=	36.7	117.0	45.0
VEL=	0.5	2.9	0.6

*SECNO 12715.000

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 598.50 ELREA= 598.50

D/S FACE OF 96 CMP

12715.00	6.70	597.60	0.00	0.00	597.80	0.19	0.02	0.04	592.00
390.	0.	390.	0.	0.	110.	0.	233.	117.	592.00
2.88	0.00	3.54	0.00	0.110	0.035	0.110	0.042	590.90	739.00
0.001007	35.	35.	35.	2	0	0	0.00	17.00	756.00

FLOW DISTRIBUTION FOR SECNO= 12715.00 CWSEL= 597.80

STA= 739. 756.
PER Q= 100.0
AREA= 110.2
VEL= 3.5

SPECIAL BRIDGE

SS	XR	XKOR	CORO	RDLEN	BWC	BWP	BAREA	SS	ELCHU	ELCHD
	5.00	5.01	5.00	0.00	11.23	0.00	68.50	0.00	591.10	590.90

*SECNO 12679.000

LATER EL=X5 CARD= 599.600

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 602.60 ELREA= 602.60

U/S FACE OF 96 CMP

12979.00	8.50	599.62	0.00	0.00	599.72	0.12	0.19	0.02	593.20
390.	0.	390.	0.	0.	141.	0.	233.	117.	593.00
2.91	0.00	3.7	0.00	0.110	0.035	0.110	0.042	591.10	739.00
0.000536	264.	264.	264.	0.	3	0	0.00	17.00	756.00

FLOW DISTRIBUTION FOR SECNO= 12979.00 CWSEL= 599.60

STA= 739. 756.
PER Q= 100.0
AREA= 140.5
VEL= 2.8

*SECNO 13030.000

3495 ENCROACHMENT STATIONS= 740.0 880.0 TYPE= 1 TARGET= 120.000

XSECT. U/S OF 96 CMP

13030.00	9.78	599.62	0.00	0.00	599.75	0.14	0.02	0.01	590.20
735.	203.	337.	446.	259.	96.	201.	234.	117.	590.20
2.97	0.78	4.03	0.72	0.110	0.035	0.110	0.042	589.04	740.00
0.000844	51.	51.	51.	2	0	0	3.00	120.00	860.00

FLOW DISTRIBUTION FOR SECNO= 13030.00 CWSEL= 599.52

PRINTED IN U.S.A.
FORM 1411-60-PRINTED BY ROTARY MANIFOLD FORMS

STA=	740.	764.	773.	780.	795.	805.	816.	821.	829.	842.	860.
PER Q=	9.1	3.3	2.3	12.9	52.6	10.3	2.1	1.8	2.5	3.1	
AREA=	100.8	34.5	25.2	98.9	96.0	77.2	20.8	22.6	34.4	46.5	
VEL=	0.7	0.7	0.7	1.0	4.0	1.0	0.7	0.6	0.5	0.5	

CCHV= 0.100 CEHV= 0.300

*SECNO 13473.000

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELCIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IN2	ICONT	CORAR	TOPWID	ENDST

3470 ENCROACHMENT STATIONS= 295.0 1300.0 TYPE= 1 TARGET= 1005.000

VALLEY SECTION BASED ON FIELD BOOK AND QUAD MAP

13473.00	9.64	599.83	0.00	0.00	599.85	0.02	0.09	0.01	590.34
735.	429.	191.	115.	1227.	95.	350.	245.	121.	590.54
3.07	0.35	2.01	0.33	0.100	0.035	0.100	0.042	590.19	313.89
0.000111	443.	443.	443.	0	0	0	0.00	637.12	951.00

FLOW DISTRIBUTION FOR SECNO= 13473.00 CWSEL= 599.85

STA=	314.	500.	650.	764.	780.	795.	805.	816.	842.	900.	951.
PER Q=	3.2	38.3	26.6	3.3	7.4	86.0	5.4	3.3	5.2	1.3	
AREA=	162.1	423.4	677.4	62.3	101.1	95.2	75.3	91.7	137.3	95.5	
VEL=	0.1	0.3	0.6	0.4	0.5	2.0	0.5	0.3	0.3	0.2	

CCHV= 0.300 CEHV= 0.500

*SECNO 13909.000

3470 ENCROACHMENT STATIONS= 400.3 1100.0 TYPE= 1 TARGET= 750.000

XSECT. D/S OF VRELAND RD

13909.00	9.42	599.84	0.00	0.00	599.89	0.01	0.04	0.00	590.90
739.	293.	764.	749.	1044.	92.	1692.	215.	122.	596.96
3.30	0.29	1.57	0.27	0.100	0.035	0.100	0.041	590.45	400.20
0.000371	434.	436.	436.	2	2	0	0.30	760.93	1100.00

FLOW DISTRIBUTION FOR SECNO= 13909.00 CWSEL= 599.89

STA=	400.	500.	730.	745.	755.	766.	1100.
PER Q=	3.7	30.6	5.6	10.6	4.3	36.3	
AREA=	158.5	790.0	97.3	92.0	74.1	1017.4	
VEL=	0.2	0.3	0.4	1.6	0.4	0.3	

*SECNO 14009.000

D/S FACE OF VRELAND RD

14009.00	8.68	599.89	0.00	0.00	599.90	0.01	0.01	0.00	591.30
735.	249.	953.	332.	706.	86.	1244.	269.	130.	591.30
3.35	0.35	1.78	0.27	0.100	0.035	0.100	0.041	591.21	490.89
0.000099	100.	100.	100.	0	0	0	0.00	738.73	1257.62

FLOW DISTRIBUTION FOR SECNO= 14009.00 CWSEL= 599.89

PRINTED IN U.S.A.
FORM 1411-GD PRINTED BY ROTARY MANIFOLD FORMS

```
 STA=      499.      500.      680.      695.      705.      716.     1238.
   PER Q=     0.0      27.7       6.2      20.9       4.8      40.4
    AREA=     1.6     610.8      93.6      86.4      72.0    1171.9
     VEL=     0.1       0.3       0.5       1.8       0.5       0.5

 CCHV=   0.300 CEHV=   0.500
 *SECNO 14010.000

 3301 HV CHANGED MORE THAN HVINS

 3570 NORMAL BRIDGE,NRD=  6 MIN ELTRD=  599.19 MAX ELLC=  598.50

          1 FOOT INSIDE OF D/S FACE OF CULVERT

 14010.00      8.34    599.55    593.11      0.00    600.25      0.70      3.00      0.35    591.30
      735.      235.      880.       19.      213.       58.       63.      869.      130.    591.35
     3.35      1.11      8.30      0.44     0.100     0.022     0.100     0.041    591.21    599.02
0.007044        1.        1.        1.         6         9         0 -1616.73    683.12   1132.14

 FLOW DISTRIBUTION FOR SECNO=  14010.00         CWSEL=    599.35

 STA=      499.      500.      695.      705.      716.      800.      950.
   PER Q=    10.9      21.1      65.4       9.3       1.7       0.6
    AREA=   101.4     111.4      58.0       3.7      23.5      16.3
     VEL=     0.8       1.4       8.3       0.6       0.5       0.3

 *SECNO 14090.000

 3301 HV CHANGED MORE THAN HVINS

 3570 NORMAL BRIDGE,NRD=  3 MIN ELTRD=  599.19 MAX ELLC=  598.50

          1 FOOT INSIDE OF U/S FACE OF CULVERT

 14090.00      9.33    600.36      0.00      0.00    600.62      0.00      3.18      0.19    591.30
      735.      225.      250.      354.      384.       69.      315.      271.      131.    597.35
     5.36      0.59      3.71      0.43     0.100     0.022     0.100     0.041    591.21    600.64
0.001121        80.       80.       85.         4         0         0 -1093.69    731.42   1280.05

 FLOW DISTRIBUTION FOR SECNO=  14090.00         CWSEL=    600.36

 STA=      499.      900.      600.      695.      705.      715.      800.      950.     1100.     1250.
   PER Q=     0.0       9.4      21.2      34.0       1.1       3.5      11.9       6.1       5.0
    AREA=     0.7     189.0     194.2      68.9      14.1     106.9      64.7     131.3      97.8
     VEL=     0.2       0.4       0.2       3.7       0.6       0.6       0.5       0.5       0.4

 CCHV=   0.300 CEHV=   0.500
 *SECNO 14091.000
    SECNO      DEPTH     CWSE:     CRWS      SELC      EE        HV        HL      CLOSS   BANK ELEV
       Q       QLOB       QCH       QROB      ALOB      ACH       AROB      VOL       TW      LEFT/RIGHT
     TIME      JLOB      WCH       VROB      XNL       XCL       XNR       STN       CLOSS     GSTA
    SLOPE     XLOBL     XLCH      XLOBR     TRIAL     I42       ICONT     CORAR     TOPWID    ENDST

          U/S FACE OF VREELAND RD

 14091.00      9.43    600.64      2.00      0.90    602.6       0.01      0.00      0.12    591.50
```

PRINTED IN U.S.A.

FORM 143-68 PRINTED BY ROTARY MANIFOLD FORMS

735.	279.	132.	324.	1028.	103.	1602.	271.	131.	591.30
3.36	0.27	1.28	0.20	0.100	0.030	0.100	0.041	591.21	498.60
0.000034	1.	1.	1.	2	0	0	0.00	751.46	1250.06

FLOW DISTRIBUTION FOR SECNO= 14091.00 CHSEL= 602.64

STA=	499.	500.	600.	695.	706.	716.	800.	950.	1100.	1250.
PER Q=	0.0	11.3	26.7	18.0	3.2	14.1	17.0	7.5	2.2	
AREA=	2.5	388.5	636.5	103.2	76.5	414.6	582.8	357.8	170.3	
VEL=	0.1	0.2	0.3	1.3	0.3	0.3	0.2	0.2	0.1	

*SECNO 14116.003

XSECT. U/S OF VREELAND RD

14116.00	9.43	600.64	0.00	0.00	600.64	0.01	0.00	0.00	591.30
735.	279.	132.	324.	1029.	103.	1606.	272.	131.	591.30
3.36	0.27	1.28	0.20	0.100	0.030	0.100	0.041	591.21	498.60
0.000034	25.	25.	25.	1	0	0	0.00	751.47	1250.06

FLOW DISTRIBUTION FOR SECNO= 14116.00 CHSEL= 600.64

STA=	499.	500.	600.	695.	706.	716.	800.	950.	1100.	1250.
PER Q=	0.0	11.3	26.7	17.9	3.2	14.1	17.0	7.5	2.2	
AREA=	2.6	389.3	637.2	103.3	76.6	415.2	584.0	359.0	171.5	
VEL=	3.1	0.2	0.3	1.3	0.3	0.3	0.2	0.2	0.1	

CCHV= 0.100 CEHV= 0.300
*SECNO 14673.000

3265 DIVIDED FLOW

VALLEY SECTION GIVEN BY FIELD BOOK AND CUAD MAP

14673.00	8.59	600.66	0.80	0.00	600.67	0.01	0.03	0.00	592.67
735.	276.	121.	340.	867.	66.	1374.	302.	141.	592.57
3.65	3.32	1.81	0.32	0.100	0.035	0.100	0.061	592.07	179.62
0.000119	557.	557.	557.	6	0	5	0.00	790.83	1030.07

FLOW DISTRIBUTION FOR SECNO= 14673.00 CHSEL= 600.65

STA=	100.	425.	510.	559.	571.	579.	805.	800.	1030.
PER Q=	7.9	13.0	11.6	4.0	16.4	4.5	31.2	11.5	
AREA=	201.0	283.6	208.7	71.5	46.5	90.6	659.0	323.9	
VEL=	0.2	0.5	0.6	0.3	1.8	0.6	0.3	0.2	

CCHV= 0.300 CEHV= 0.500
*SECNO 15262.000

3470 ENCROACHMENT STATIONS= 823.0 2052.0 TYPE= 1 TARGET= 2228.000

X-SECTION D/S OF TELEGRAPH RD.

15262.00	8.41	600.72	0.00	0.30	600.72	0.01	0.05	0.00	592.60
735.	340.	97.	298.	1004.	66.	660.	524.	149.	592.30
5.92	0.54	1.47	0.46	0.090	0.040	0.090	0.046	592.31	1049.77
0.000095	750.	569.	300.	3	0	0	0.00	800.54	1530.31

FLOW DISTRIBUTION FOR SECNO= 15262.00 CHSEL= 600.72

PRINTED IN U.S.A.
FORM 1411-GO-PRINTED BY ROTARY MANIFOLD FORMS

STA=	1050.	1200.	1377.	1388.	1396.	1404.	1412.	1416.	1550.	1550.
PER Q=	22.9	16.4	2.1	4.8	13.2	4.3	1.4	34.4	0.0	
AREA=	482.0	421.5	41.8	58.7	66.1	58.7	22.2	587.1	0.7	
VEL=	0.3	0.3	0.4	0.6	1.5	0.6	0.5	0.4	0.0	

*SECNO 15362.000

D/S FACE OF TELEGRAPH RD. BRIDGE

15362.00	8.39	600.70	0.00	0.00	600.79	0.09	0.02	0.04	597.20
735.	179.	650.	107.	407.	148.	213.	327.	150.	597.20
3.93	0.64	3.04	0.50	0.090	0.040	0.090	0.041	592.31	1009.93
0.000650	100.	100.	100.	2	0	0	0.00	565.20	1575.13

FLOW DISTRIBUTION FOR SECNO= 15362.00 CHSEL= 600.70

STA=	1010.	1200.	1390.	1390.	1410.	1560.	1575.
PER Q=	11.7	12.7	0.0	61.2	6.5	8.0	
AREA=	193.3	208.2	0.2	147.9	103.9	108.7	
VEL=	0.4	0.6	0.1	3.0	0.5	0.5	

*SECNO 15363.000

SECNO	DEPTH	CLSEL	CNTWS	WSELR	EG	HV	TL	CLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IK2	ICONT	CORAR	TOPWID	ENDST

3370 NORMAL BRIDGE,NRD= 5 MIN ELTRD= 599.90 MAX ELLC= 597.20

1 FOOT INSIDE D/S TELEGRAPH BRIDGE

15363.00	8.46	600.77	0.00	0.00	600.80	0.04	0.00	0.02	597.20
735.	303.	255.	177.	432.	105.	226.	327.	150.	597.20
3.93	0.70	2.43	0.79	0.060	0.025	0.060	0.041	592.31	1009.92
0.000673	1.	1.	1.	2	0	0	-44.40	565.21	1575.14

FLOW DISTRIBUTION FOR SECNO= 15363.00 CHSEL= 600.77

STA=	1010.	1200.	1390.	1470.	1560.	1575.	1575.
PER Q=	19.8	22.6	34.7	11.2	13.1	0.0	
AREA=	215.2	221.1	104.9	110.3	119.0	0.1	
VEL=	0.7	0.7	2.4	0.7	0.8	0.1	

*SECNO 15434.000

3370 NORMAL BRIDGE,NRD= 5 MIN ELTRD= 599.90 MAX ELLC= 597.20

1 FOOT INSIDE U/S E.J. TELEGRAPH BRIDGE

15436.00	8.51	600.82	0.00	0.00	600.85	0.03	0.00	0.00	597.20
735.	309.	247.	179.	450.	106.	232.	328.	151.	597.20
3.95	0.69	2.54	0.77	0.060	0.025	0.060	0.041	592.31	1009.92
0.000613	71.	71.	71.	0	0	0	-44.44	565.22	1575.14

FLOW DISTRIBUTION FOR SECNO= 15434.00 CHSEL= 600.82

PRINTED IN U.S.A.
FORM 1411-30 PRINTED BY ROTARY MANIFOLD FORMS

STA=	1010.	1200.	1390.	1410.	1500.	1575.	1575.		
PER Q=	20.3	21.8	33.6	11.1	13.2	0.0			
AREA=	220.2	230.0	105.8	114.2	117.3	0.1			
VEL=	0.7	0.7	2.3	0.7	0.8	0.1			

*SECNO 15435.000

U/S FACE TELEGRAPH RD

15435.00	8.50	600.81	0.00	0.00	600.86	0.04	0.00	0.00	597.20
735.	243.	351.	141.	452.	150.	232.	328.	151.	597.20
3.95	0.54	2.34	0.61	0.060	0.040	0.060	0.041	592.31	1009.92
0.000376	1.	1.	1.	0	0	0	0.00	565.22	1575.14

FLOW DISTRIBUTION FOR SECNO= 15435.00 CWSEL= 600.81

STA=	1010.	1200.	1390.	1390.	1410.	1500.	1575.	1575.
PER Q=	16.0	17.2	0.0	47.7	8.8	10.4	0.0	
AREA=	220.9	230.8	0.2	150.2	114.6	117.6	0.1	
VEL=	0.5	0.5	0.1	2.3	0.5	0.6	0.1	

*SECNO 15460.000

XSECT. U/S OF TELEGRAPH RD.

15460.00	8.51	600.82	0.00	0.00	600.87	0.04	0.01	0.00	597.20
735.	245.	349.	141.	455.	150.	234.	329.	152.	597.20
3.95	0.54	2.32	0.00	0.060	0.040	0.060	0.041	592.31	1009.92
0.000372	25.	25.	25.	0	0	0	0.00	565.23	1575.14

FLOW DISTRIBUTION FOR SECNO= 15460.00 CWSEL= 600.82

STA=	1010.	1200.	1390.	1390.	1410.	1500.	1575.	1575.
PER Q=	16.0	17.2	0.0	47.5	8.8	10.4	0.0	
AREA=	222.6	232.7	0.2	150.3	115.3	118.3	0.1	
VEL=	0.5	0.5	0.1	2.3	0.6	0.6	0.1	

CCHV= 0.100 CEHV= 0.300

*SECNO 16873.000

VALLEY SEC. CASES OF EXIST BRDG (NO 30)

16873.00	8.52	601.32	0.00	0.00	601.34	0.04	0.69	0.00	592.80
735.	372.	168.	174.	529.	68.	424.	559.	168.	592.05
4.89	0.70	2.70	0.41	0.000	0.040	0.090	0.041	592.80	899.69
0.000326	1413.	1413.	1413.	2	6	0	0.00	450.46	730.13

FLOW DISTRIBUTION FOR SECNO= 16873.00 CWSEL= 601.32

STA=	300.	435.	448.	456.	483.	483.	500.	750.
PER Q=	40.0	7.7	25.6	5.4	2.9	6.5	10.4	
AREA=	465.2	63.5	67.7	48.9	35.8	330.3	203.5	
VEL=	0.7	0.9	2.8	0.8	0.4	0.3	0.4	

*SECNO 17673.000

SECNO	DEPTH	CCSEL	CRIWS	WSELK	EG	AV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	WLOB	WCH	VLOB	BLI	KHCH	XNR	WTN	CL 1N	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IHS	ICONT	CODAR	TOPWID	ENDST

PRINTED IN U.S.A.
FORM 1613-B PRINTED BY ROTARY MANIFOLD FORMS

VALLEY SECTION AT CORP/LIMIT BROWNSTOWN/FLAT ROCK

17673.00	8.26	601.58	0.00	0.00	601.66	0.08	0.29	0.01	594.37
735.	172.	281.	261.	236.	80.	408.	371.	173.	593.40
4.39	0.73	3.53	0.69	0.090	0.040	0.090	0.041	593.32	287.63
0.000574	900.	830.	300.	2	0	0	0.00	313.95	601.58

FLOW DISTRIBUTION FOR SECNO= 17673.00 CWSEL= 601.58

STA=	288.	290.	380.	395.	405.	420.	600.	602.
PER Q=	0.1	13.3	10.1	38.3	11.7	26.5	0.0	
AREA=	1.9	164.8	69.7	79.8	77.0	329.6	1.2	
VEL=	0.3	0.6	1.1	3.5	1.1	0.6	0.3	

PRINTED IN U.S.A.
FORM 141-80 PRINTED BY ROTARY MANIFOLD FORMS

00BREAK00

1) COUNTY: Wayne

2) STUDY NAME: City of Gibralter

3) WATERCOURSE: Brownstown Creek

4) DOCUMENT TYPE: 100 Year

00BREAK00

```
**********************************************
HEC2 VERSION UPDATED JAN 1976
ERROR CORRECTIONS 01,02,03,04,05,06,07,08,09
MODIFICATIONS 52,53,54,55,56,57,58
**********************************************
```

Revised 8/17/77

8/11/77
IGL datum
+1.43 ft = USGS

```
C
1       CITY OF GIBRALTER          5555-23-01      PM = RICHARD ZANOTTI
T2          10 YEAR FLOOD
T3          BROWNSTOWN CREEK
```

J1	ICHECK	INQ	NINV	IDIR	STRT	METRIC	HVINS	Q	WSEL	FQ
	-1.	2.	0.	0.	0.000000	0.00	0.0	0.	578.200	0.000

J2	NPROF	IPLOT	PRFVS	XSECV	XSECH	FN	ALLDC	IBW	CHNIM	ITRACE
	1.000	0.000	-1.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000

J3	1.000	10.000	11.000	12.000	14.000	8.000	4.000	0.000	0.000	0.000
NC	.045	.045	.030	.300	.500	0.000	0.000	0.000	0.000	0.000
QT	4.000	710.000	900.000	985.000	1190.000	0.000	0.000	0.000	0.000	0.000
X1	10764.000	13.000	560.000	590.000	0.000	0.000	0.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	415.000	0.000	980.000	0.000	0.000	0.000	0.000
GR	581.600	0.000	580.700	225.000	580.700	400.000	578.600	425.000	577.100	475.000
GR	576.900	560.000	573.600	563.000	572.300	575.000	573.300	585.000	576.800	590.000
GR	577.100	765.000	578.600	1025.000	580.600	1185.000	0.000	0.000	0.000	0.000
QT	4.000	480.000	650.000	710.000	860.000	0.000	0.000	0.000	0.000	0.000
X1	11134.000	8.000	310.000	440.000	500.000	100.000	370.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	160.000	0.000	680.000	0.000	0.000	0.000	0.000
GR	578.000	0.000	577.600	210.000	576.600	310.000	574.600	325.000	574.600	350.000
GR	576.600	440.000	578.600	650.000	579.600	782.000	0.000	0.000	0.000	0.000
NC	.040	.050	.038	0.000	0.000	0.000	0.000	0.000	0.000	0.000
X1	11734.000	11.000	35.000	76.000	690.000	350.000	600.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	0.000	0.000	420.000	0.000	0.000	0.000	0.000
GR	583.600	0.000	582.600	10.000	580.600	15.000	578.600	21.000	576.600	35.000
GR	575.200	46.000	575.200	60.000	576.600	76.000	578.600	190.000	579.600	295.000
GR	579.600	535.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
X1	12164.000	15.000	440.000	535.000	550.000	350.000	430.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	0.000	0.000	650.000	0.000	0.000	0.000	0.000
GR	585.600	0.000	584.600	20.000	583.600	30.000	581.600	135.000	580.600	235.000
GR	578.600	350.000	576.600	440.000	575.500	467.000	575.500	477.000	576.600	535.000
GR	578.600	578.000	580.600	600.000	581.100	650.000	580.600	725.000	579.600	800.000
NC	.050	.050	.040	0.000	0.000	0.000	0.000	0.000	0.000	0.000
X1	12884.000	11.000	255.000	287.000	520.000	670.000	720.000	0.000	0.000	0.000
GR	581.600	0.000	580.600	90.000	578.600	230.000	576.600	255.000	576.000	265.000
GR	576.000	280.000	576.600	287.000	578.600	300.000	580.600	352.000	581.100	455.000
GR	581.600	590.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
X1	13324.000	11.000	420.000	460.000	300.000	700.000	440.000	0.000	0.000	0.000
GR	581.600	0.000	582.100	110.000	580.600	320.000	578.600	410.000	576.600	420.000
GR	576.200	425.000	576.200	440.000	576.600	460.000	578.600	485.000	580.600	535.000
GR	582.100	640.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
NC	.045	.050	.035	0.000	0.000	0.000	0.000	0.000	0.000	0.000

	X1	[illegible]	9.000	215.000	260.000	300.000	650.000	400.000	0.000	0.000	0.000
	X3	0.000	0.000	0.000	140.000	0.000	350.000	0.000	0.000	0.000	0.000
	GR	581.600	0.000	580.600	92.000	578.600	215.000	576.700	225.000	576.700	237.000
	GR	578.600	260.000	580.600	385.000	581.600	570.000	582.000	760.000	0.000	0.000
	X1	13894.000	8.000	200.000	230.000	170.000	170.000	170.000	0.000	0.000	0.000
6	X3	0.000	0.000	0.000	146.000	0.000	250.000	0.000	0.000	0.000	0.000
	GR	582.100	0.000	580.600	90.000	578.600	200.000	576.800	210.000	576.800	220.000
	GR	578.600	230.000	580.600	235.000	582.600	400.000	0.000	0.000	0.000	0.000
	X1	14024.000	0.000	0.000	0.000	130.000	130.000	130.000	0.000	0.000	0.000
	X3	0.000	0.000	0.000	191.000	0.000	230.000	0.000	0.000	0.000	0.000
	X1	14044.000	0.000	0.000	0.000	20.000	20.000	20.000	0.000	0.000	0.000
	X3	0.000	0.000	0.000	201.000	0.000	230.000	0.000	0.000	0.000	0.000
	X1	14054.000	0.000	0.000	0.000	10.000	10.000	10.000	0.000	0.000	0.000
	X3	0.000	0.000	0.000	203.000	0.000	227.000	0.000	0.000	0.000	0.000
	X1	14060.000	0.000	0.000	0.000	6.000	6.000	6.000	0.000	0.000	0.000
	X3	0.000	0.000	0.000	205.000	0.000	226.000	0.000	0.000	0.000	0.000
	NC	.050	.050	.030	0.000	0.000	0.000	0.000	0.000	0.000	0.000
	X1	14064.000	24.000	1000.000	1019.000	4.000	4.000	4.000	0.000	0.000	0.000
	GR	585.200	0.000	585.400	100.000	585.700	200.000	585.800	300.000	586.200	400.000
	GR	586.300	500.000	586.400	600.000	586.600	700.000	586.800	800.000	587.000	900.000
	GR	587.300	1000.000	578.400	1000.000	577.200	1005.000	576.800	1010.000	577.100	1013.000
	GR	577.400	1019.000	587.300	1019.000	587.500	1100.000	587.600	1200.000	587.800	1300.000
	GR	587.900	1400.000	588.000	1500.000	588.000	1600.000	588.100	1700.000	0.000	0.000
	NC	.035	.035	.020	0.000	0.000	0.000	0.000	0.000	0.000	0.000
X	X1	14065.000	0.000	0.000	0.000	1.000	1.000	1.000	0.000	0.000	0.000
	BT	21.000	0.000	585.200	0.000	100.000	585.400	0.000	200.000	585.700	0.000
	BT	300.000	585.800	0.000	400.000	586.200	0.000	500.000	586.300	0.000	600.000
	BT	586.400	0.000	700.000	586.600	0.000	800.000	586.800	0.000	900.000	587.000
	BT	0.000	1000.000	587.300	0.000	1000.000	587.300	582.400	1019.000	587.300	582.500
	BT	1019.000	587.300	0.000	1100.000	587.500	0.000	1200.000	587.600	0.000	1300.000
	BT	587.800	0.000	1400.000	587.900	0.000	1500.000	588.000	0.000	1600.000	588.000
	BT	0.000	1700.000	588.100	0.000	0.000	0.000	0.000	0.000	0.000	0.000
	X1	14079.000	0.000	0.000	0.000	14.000	14.000	14.000	0.000	0.000	0.000
	X2	0.000	0.000	0.000	0.000	0.000	0.000	1.000	0.000	0.000	0.000
	NC	.045	.040	.032	0.000	0.000	0.000	0.000	0.000	0.000	0.000
	X1	14080.000	0.000	0.000	0.000	1.000	1.000	1.000	0.000	0.000	0.000
	X1	14083.000	24.000	1000.000	1019.000	3.000	3.000	3.000	0.000	0.000	0.000
	X3	0.000	0.000	0.000	997.000	0.000	1022.000	0.000	0.000	0.000	0.000
	GR	585.200	0.000	585.400	100.000	585.700	200.000	585.800	300.000	586.200	400.000
	GR	586.300	500.000	586.400	600.000	586.600	700.000	586.800	800.000	587.000	900.000
	GR	578.400	1000.000	578.400	1000.000	577.200	1005.000	576.800	1010.000	577.100	1013.000
	GR	577.400	1019.000	577.400	1019.000	587.500	1100.000	587.600	1200.000	587.800	1300.000
	GR	587.900	1400.000	588.000	1500.000	588.000	1600.000	588.100	1700.000	0.000	0.000
X	X1	14420.000	14.000	357.000	375.000	220.000	350.000	337.000	0.000	0.000	0.000
	X3	0.000	0.000	0.000	175.000	0.000	470.000	0.000	0.000	0.000	0.000
	GR	586.800	0.000	582.600	13.000	583.100	75.000	583.600	105.000	580.300	175.000
	GR	580.200	275.000	579.100	357.000	576.800	361.000	576.600	364.000	577.400	369.000
	GR	581.100	375.000	582.800	475.000	584.400	575.000	584.200	592.000	0.000	0.000
	NC	.045	.055	.035	0.000	0.000	0.000	0.000	0.000	0.000	0.000
	X1	14800.000	11.000	302.000	325.000	620.000	375.000	380.000	0.000	0.000	0.000
	GR	583.600	0.000	583.400	25.000	584.600	125.000	583.300	225.000	580.800	302.000
	GR	577.400	308.000	577.400	311.000	577.900	319.000	581.000	325.000	581.600	425.000
	GR	582.200	500.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
	NH	3.000	.045	793.700	.032	806.300	.055	1500.000	0.000	0.000	0.000

ET	0.000	6.100	8.100	8.100	8.100	793.700	806.300	500.000	1100.000	0.000
X1	15020.000	24.000	750.000	850.000	220.000	220.000	220.000	0.000	0.000	0.000
GR	583.400	0.000	584.000	100.000	584.500	200.000	585.000	300.000	585.200	400.000
GR	585.400	500.000	585.400	600.000	585.200	700.000	585.000	750.000	576.500	793.700
GR	575.500	794.700	575.100	796.800	574.900	800.000	575.100	803.200	575.500	805.300
GR	576.500	806.300	584.700	850.000	584.600	900.000	584.400	1000.000	584.300	1100.000
GR	584.400	1200.000	584.400	1300.000	584.700	1400.000	585.000	1500.000	0.000	0.000
NH	3.000	.040	793.700	.031	806.300	.040	1500.000	0.000	0.000	0.000
ET	0.000	6.100	8.100	8.100	8.100	793.700	806.300	500.000	1100.000	0.000
X1	15021.000	0.000	0.000	0.000	1.000	1.000	1.000	0.000	0.000	0.000
ET	0.000	6.100	8.100	8.100	8.100	793.700	806.300	500.000	1100.000	0.000
SB	0.000	1.870	3.000	0.000	9.750	0.000	77.000	0.000	574.900	574.900
X1	15061.000	0.000	0.000	0.000	40.000	40.000	40.000	0.000	0.000	0.000
X2	0.000	0.000	1.000	582.800	584.300	0.000	0.000	0.000	0.000	0.000
BT	15.000	500.000	585.400	0.000	600.000	585.400	0.000	700.000	585.200	0.000
BT	793.700	584.800	576.500	793.700	584.800	578.600	794.700	584.800	580.100	796.800
BT	584.800	582.000	800.000	584.800	582.800	803.200	584.800	582.000	805.300	584.800
BT	580.100	806.300	584.800	578.600	806.300	584.800	576.500	900.000	584.600	0.000
BT	1000.000	584.400	0.000	1100.000	584.300	0.000	0.000	0.000	0.000	0.000
NH	3.000	SB .050	793.700	.032	806.300	.050	1500.000	0.000	0.000	0.000
ET	0.000	6.100	8.100	8.100	8.100	793.700	806.300	500.000	1100.000	0.000
X1	15062.000	0.000	0.000	0.000	1.000	1.000	1.000	0.000	0.000	0.000
EJ	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000

BK

```
**********************************************
HEC2 VERSION UPDATED JAN 1976
ERROR CORRECTIONS 01,02,03,04,05,06,07,08,09
MODIFICATIONS 52,53,54,55,56,57,58
**********************************************


T1      CITY OF GIBRALTER        5555-23-01     PM = RICHARD ZANOTTI
T2      100-YEAR FLOOD
T3      BROWNSTOWN CREEK

J1  ICHECK    INQ       NINV      IDIR      STRT      METRIC    HVINS     Q         WSEL      FQ
       -1.       4.        0.        0.  0.000000      0.00      0.0       0.   578.440     0.000
J2  NPROF     IPLOT     PRFVS     XSECV     XSECH     FN        ALLDC     IBW       CHNIM     ITRACE
     3.000     0.000    -1.000     0.000     0.000     0.000     0.000     0.000     0.000     0.000
```

CCHV= .300 CEHV= .500

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST
3470 ENCROACHMENT STATIONS=		415.0	980.0	TYPE=	1	TARGET=	565.000		
250' D/S FROM INTERSECTION OF MARSH & BROWNSTOWN CREEKS						SEC. W			
10764.00	6.14	578.44	0.00	578.44	578.53	.09	0.00	0.00	576.90
985.	140.	481.	364.	152.	149.	416.	0.	0.	576.80
0.00	.92	3.23	.88	.045	.030	.045	0.000	572.30	430.33
.000563	0.	0.	0.	0	0	1	0.00	549.67	980.00
3470 ENCROACHMENT STATIONS=		160.0	680.0	TYPE=	1	TARGET=	520.000		
120' U/S FROM INTERSECTION OF MARSH & BROWNSTOWN CREEKS						SEC. BA			
MANUFACTURE SECTION FROM 2-FOOT CONTOUR MAP									
11134.00	4.01	578.61	0.00	0.00	578.63	.02	.09	.02	576.60
710.	97.	529.	84.	201.	418.	215.	5.	3.	576.60
.08	.48	1.27	.39	.045	.030	.045	.034	574.60	160.00
.000138	500.	370.	100.	0	0	1	0.00	492.93	652.93
3470 ENCROACHMENT STATIONS=		.0	420.0	TYPE=	1	TARGET=	419.999		
720' U/S FROM INTERSECTION OF MARSH & BROWNSTOWN CREEKS						SEC. BB			
MANUFACTURE SECTION FROM 2-FOOT CONTOUR MAP									
11734.00	3.54	578.74	0.00	0.00	578.91	.17	.20	.07	576.60
710.	30.	485.	196.	16.	126.	131.	12.	7.	576.60
.13	1.87	3.84	1.50	.040	.038	.050	.038	575.20	20.59
.002168	690.	600.	350.	2	0	1	0.00	183.81	204.40
3470 ENCROACHMENT STATIONS=		.0	650.0	TYPE=	1	TARGET=	649.999		
1150' U/S FROM INTERSECTION OF MARSH & BROWNSTOWN CREEKS						SEC. BC			
MANUFACTURE SECTION FROM 2-FOOT CONTOUR MAP									
12164.00	3.73	579.23	0.00	0.00	579.26	.03	.32	.04	576.60
710.	149.	505.	56.	159.	308.	73.	16.	9.	576.60
.22	.94	1.64	.77	.040	.038	.050	.038	575.50	313.37
.000365	550.	430.	350.	1	0	1	0.00	271.64	585.01

1870' U/S FROM INTERSECTION OF MARSH & BROWNSTOWN CREEKS SEC BD

MANUFACTURE SECTION FROM 2-FOOT CONTOUR MAP

12884.00	3.65	579.65	0.00	0.00	579.86	.20	.51	.08	576.60
710.	160.	473.	77.	91.	112.	41.	22.	12.	576.60
.27	1.76	4.23	1.87	.050	.040	.050	.040	576.00	155.92
.002441	520.	720.	670.	2	0	1	0.00	171.59	327.51

2310' U/S FROM INTERSECTION OF MARSH & BROWNSTOWN CREEKS SEC. BE

MANUFACTURE SECTION FROM 2-FOOT CONTOUR MAP

13324.00	4.22	580.42	0.00	0.00	580.50	.08	.61	.04	576.60
710.	107.	449.	153.	102.	164.	112.	25.	14.	576.60
.33	1.05	2.75	1.38	.050	.040	.050	.040	576.20	328.31
.000836	300.	440.	700.	2	0	1	0.00	202.08	530.38

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNP	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

3470 ENCROACHMENT STATIONS= 140.0 350.0 TYPE= 1 TARGET= 210.000

340' D/S FROM D/S FACE OF PENN CENTRAL RR BRIDGE #2 SEC. BF

MANUFACTURE SECTION FROM 2-FOOT CONTOUR MAP

13724.00	4.08	580.78	0.00	0.00	580.86	.08	.36	.00	578.60
710.	151.	415.	144.	118.	152.	132.	29.	16.	578.60
.39	1.28	2.73	1.09	.045	.035	.050	.038	576.70	140.00
.000818	300.	400.	650.	2	0	1	0.00	210.00	350.00

3470 ENCROACHMENT STATIONS= 146.0 250.0 TYPE= 1 TARGET= 104.000

170' D/S FORM D/S FACE OF PENN CENTRAL RR BRIDGE #2 SEC. BG

MANUFACTURE SECTION FROM 2-FOOT CONTOUR MAP

13894.00	4.12	580.92	0.00	0.00	581.15	.23	.21	.08	578.60
710.	224.	473.	12.	99.	106.	10.	30.	17.	578.60
.40	2.27	4.48	1.20	.045	.035	.050	.038	576.80	146.00
.002108	170.	170.	170.	0	0	1	0.00	104.00	250.00

3470 ENCROACHMENT STATIONS= 191.0 230.0 TYPE= 1 TARGET= 39.000

14024.00	4.35	581.15	0.00	0.00	581.60	.46	.34	.11	578.60
710.	78.	632.	0.	22.	112.	0.	31.	17.	100000.00
.41	3.52	5.62	0.00	.045	.035	.050	.038	576.80	191.00
.003405	130.	130.	130.	2	0	1	0.00	39.00	230.00

3470 ENCROACHMENT STATIONS= 201.0 230.0 TYPE= 1 TARGET= 29.000

14044.00	4.33	581.13	0.00	0.00	581.79	.66	.08	.10	100000.00
710.	0.	710.	0.	0.	109.	0.	31.	17.	100000.00
.41	0.00	6.50	0.00	.045	.035	.050	.038	576.80	201.00
.005043	20.	20.	20.	2	0	1	0.00	29.00	230.00

6

3470 ENCROACHMENT STATIONS= 203.0 227.0 TYPE= 1 TARGET= 24.000

14054.00	4.27	581.07	0.00	0.00	581.96	.89	.06	.12	100000.00
710.	0.	710.	0.	0.	94.	0.	31.	17.	100000.00
.41	0.00	7.58	0.00	.045	.035	.050	.038	576.80	203.00
.007055	10.	10.	10.	2	0	1	0.00	24.00	227.00

3470 ENCROACHMENT STATIONS= 205.0 226.0 TYPE= 1 TARGET= 21.000

14060.00	4.19	580.99	0.00	0.00	582.14	1.15	.05	.13	100000.00
710.	0.	710.	0.	0.	83.	0.	31.	17.	100000.00
.41	0.00	8.60	0.00	.045	.035	.050	.038	576.80	205.00
.009517	6.	6.	6.	2	0	1	0.00	21.00	226.00

7185 MIN SPECIFIC ENERGY

3720 ASSUMED CRITICAL DEPTH

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST
14064.00	4.00	580.80	580.80	0.00	582.55	1.76	.04	0.00	587.30
710.	0.	710.	0.	0.	67.	0.	31.	17.	587.30
.41	0.00	10.63	0.00	.050	.030	.050	.038	576.80	1000.00
.012413	4.	4.	4.	3	8	1	0.00	19.00	1019.00

3301 HV CHANGED MORE THAN HVINS

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

NORMAL BRIDGE,NRD=21 MIN ELTRD= 585.20 MAX ELLC= 582.50

D/S FACE OF PENN CENTRAL RR BRIDGE #2, BS#7 SEC. BH

CONCRETE & I-BEAM BRIDGE, WITH WINGWALLS

LENGTH = 14 FT, SPAN = 19 FT.

14065.00	4.67	581.47	580.78	0.00	582.71	1.24	.01	.15	587.30
710.	0.	710.	0.	0.	79.	0.	31.	17.	587.30
.41	0.00	8.93	0.00	.035	.020	.035	.038	576.80	1000.00
.003311	1.	1.	1.	34	16	1	0.00	19.00	1019.00

NORMAL BRIDGE, NRD=21 MIN ELTRD= 585.20 MAX ELLC= 582.50

14079.00	4.85	581.65	0.00	0.00	582.79	1.13	.04	.03	587.30
710.	0.	710.	0.	0.	83.	0.	31.	17.	587.30
.41	0.00	8.55	0.00	.035	.020	.035	.038	576.80	1000.00
.002910	14.	14.	14.	2	0	1	0.00	19.00	1019.00
14080.00	4.86	581.66	0.00	0.00	582.79	1.13	.00	.00	587.30
710.	0.	710.	0.	0.	83.	0.	31.	17.	587.30
.41	0.00	8.54	0.00	.045	.032	.040	.038	576.80	1000.00
.007433	1.	1.	1.	0	0	1	0.00	19.00	1019.00

3301 HV CHANGED MORE THAN HVINS

3470 ENCROACHMENT STATIONS= 997.0 1022.0 TYPE= 1 TARGET= 25.000

14083.00	5.65	582.45	0.00	0.00	582.98	.53	.01	.18	578.40
710.	43.	599.	68.	12.	98.	15.	31.	17.	577.40
.41	3.63	6.11	4.70	.045	.032	.040	.038	576.80	997.00
.001964	3.	3.	3.	3	0	1	0.00	25.00	1022.00

3301 HV CHANGED MOPE THAN HVINS

3470 ENCROACHMENT STATIONS= 175.0 470.0 TYPE= 1 TARGET= 295.000

340' U/S FROM U/S FACE OF PENN CENTRAL RR BRIDGE #2, VS#1 SEC. BI

14420.00	6.62	583.22	0.00	0.00	583.24	.02	.10	.16	579.10
710.	498.	148.	64.	589.	95.	124.	34.	18.	581.10
.50	.85	1.55	.52	.045	.032	.040	.038	576.60	175.00
.000136	220.	337.	350.	2	0	1	0.00	295.00	470.00

3280 CROSS SECTION 14800.00 EXTENDED 1.12 FEET

220' D/S FROM D/S FACE OF FORT STREET BRIDGE, VS#2 SEC. BJ

14800.00	5.92	583.32	0.00	0.00	583.38	.06	.12	.02	580.80
710.	92.	317.	301.	98.	112.	308.	42.	21.	581.00
.57	.94	2.84	.98	.045	.035	.055	.037	577.40	223.65
.000597	620.	380.	375.	2	0	1	0.00	276.35	500.00

1490 NH CARD USED

SECNO	DEPTH	CWSEL	CRIWS	WSELR	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

3470 ENCROACHMENT STATIONS= 500.0 1100.0 TYPE= 1 TARGET= 600.000

15020.00	8.52	583.42	0.00	0.00	583.49	.06	.11	.00	585.00
710.	0.	710.	0.	0.	354.	0.	44.	22.	584.70
.60	0.00	2.01	0.00	.045	.040	.055	.036	574.90	758.11
.000394	220.	220.	220.	2	0	1	0.00	85.09	843.20

1490 NH CARD USED

3470 ENCROACHMENT STATIONS= 500.0 1100.0 TYPE= 1 TARGET= 600.000

D/S FACE OF FORT STREET BRIDGE, BS#3 SEC. BK

12'-6"X7'-11" CMP, WITH WINGWALLS & HEADWALLS

LENGTH = 40 FT.

15021.00	8.52	583.42	0.00	0.00	583.49	.06	.00	.00	585.00
710.	0.	710.	0.	0.	354.	0.	44.	22.	584.70
.60	0.00	2.01	0.00	.045	.036	.055	.036	574.90	758.10
.000308	1.	1.	1.	0	0	1	0.00	85.10	843.20

SPECIAL BRIDGE

SB	XK	XKOR	COFQ	RDLEN	BWC	BWP	BAREA	SS	ELCHU	ELCHD
	0.00	1.87	3.00	0.00	9.75	0.00	77.00	0.00	574.90	574.90

PRESSURE AND WEIR FLOW

EGPRS	EGLWC	H3	QWEIR	QPR	BAREA	ELLC	ELTRD	CLASS
585.89	583.49	0.00	178.	538.	77.	582.80	584.30	30.00

3470 ENCROACHMENT STATIONS= 500.0 1100.0 TYPE= 1 TARGET= 600.000

15061.00	9.91	584.81	0.00	0.00	584.84	.03	1.35	0.00	585.00
710.	0.	691.	19.	0.	482.	85.	44.	22.	584.70
.61	0.00	1.43	.22	.045	.036	.040	.036	574.90	750.98
.000135	40.	40.	40.	2	0	4	0.00	349.02	1100.00

1490 NH CARD USED

3470 ENCROACHMENT STATIONS= 500.0 1100.0 TYPE= 1 TARGET= 600.000

15062.00	9.91	584.81	0.00	0.00	584.84	.03	.00	.00	585.00
710.	0.	693.	17.	0.	482.	85.	44.	22.	584.70
.61	0.00	1.44	.21	.045	.042	.050	.036	574.90	750.98
.000178	1.	1.	1.	0	0	1	0.00	349.02	1100.00

SUMMARY PRINTOUT FOR MULTIPLE PROFILES

BROWNSTOWN CREEK

SECTION NUMBER	CHANNEL LENGTH	MIN EL OF ROADWAY	MAX EL OF LOW CHORD	MIN EL GROUND	DISCHARGE (CFS)	CWSEL	HV	HL	OLOSS	QCH	DEPTH	TOPWID
10764.00	0.00	0.00	0.00	572.30	710.00	578.20	.07	0.00	0.00	393.92	5.90	517.33
10764.00	0.00	0.00	0.00	572.30	900.00	578.34	.09	0.00	0.00	464.00	6.04	546.27
10764.00	0.00	0.00	0.00	572.30	985.00	578.44	.09	0.00	0.00	480.63	6.14	549.67
10764.00	0.00	0.00	0.00	572.30	1190.00	578.78	.07	0.00	0.00	488.74	6.48	557.14
11134.00	370.00	0.00	0.00	574.60	480.00	578.34	.01	.07	.02	377.87	3.74	463.16
11134.00	370.00	0.00	0.00	574.60	650.00	578.52	.02	.09	.02	494.03	3.92	481.78
11134.00	370.00	0.00	0.00	574.60	710.00	578.61	.02	.09	.02	528.90	4.01	492.93
11134.00	370.00	0.00	0.00	574.60	860.00	578.92	.02	.08	.01	600.23	4.32	520.00
11734.00	600.00	0.00	0.00	575.20	480.00	578.43	.12	.14	.05	354.78	3.23	158.16
11734.00	600.00	0.00	0.00	575.20	650.00	578.64	.16	.19	.07	457.36	3.44	173.00
11734.00	600.00	0.00	0.00	575.20	710.00	578.74	.17	.20	.07	484.56	3.54	183.81
11734.00	600.00	0.00	0.00	575.20	860.00	579.03	.16	.18	.07	539.34	3.83	215.56
12164.00	430.00	0.00	0.00	575.50	480.00	578.81	.02	.26	.03	367.44	3.31	242.88
12164.00	430.00	0.00	0.00	575.50	650.00	579.12	.03	.31	.04	471.27	3.62	263.67
12164.00	430.00	0.00	0.00	575.50	710.00	579.23	.03	.32	.04	504.80	3.73	271.64
12164.00	430.00	0.00	0.00	575.50	860.00	579.51	.04	.31	.04	585.63	4.01	290.06
12884.00	720.00	0.00	0.00	576.00	480.00	579.19	.17	.45	.07	355.18	3.19	126.31
12884.00	720.00	0.00	0.00	576.00	650.00	579.54	.19	.50	.08	444.67	3.54	160.88
12884.00	720.00	0.00	0.00	576.00	710.00	579.65	.20	.51	.08	473.27	3.65	171.59
12884.00	720.00	0.00	0.00	576.00	860.00	579.94	.21	.52	.09	535.22	3.94	198.93
13324.00	440.00	0.00	0.00	576.20	480.00	579.86	.07	.55	.03	335.44	3.66	163.46
13324.00	440.00	0.00	0.00	576.20	650.00	580.29	.08	.59	.03	421.01	4.09	193.08
13324.00	440.00	0.00	0.00	576.20	710.00	580.42	.08	.61	.04	449.23	4.22	202.08
13324.00	440.00	0.00	0.00	576.20	860.00	580.71	.09	.62	.04	512.94	4.51	237.98
13724.00	400.00	0.00	0.00	576.70	480.00	580.22	.08	.37	.01	333.24	3.52	210.00
13724.00	400.00	0.00	0.00	576.70	650.00	580.65	.08	.36	.00	393.83	3.95	210.00
13724.00	400.00	0.00	0.00	576.70	710.00	580.78	.08	.36	.00	415.45	4.08	210.00
13724.00	400.00	0.00	0.00	576.70	860.00	581.08	.08	.36	.00	469.54	4.38	210.00
13894.00	170.00	0.00	0.00	576.80	480.00	580.40	.19	.23	.05	351.16	3.60	88.50
13894.00	170.00	0.00	0.00	576.80	650.00	580.79	.22	.21	.07	443.30	3.99	104.00
13894.00	170.00	0.00	0.00	576.80	710.00	580.92	.23	.21	.08	473.46	4.12	104.00
13894.00	170.00	0.00	0.00	576.80	860.00	581.20	.26	.21	.09	548.70	4.40	104.00
14024.00	130.00	0.00	0.00	576.80	480.00	580.64	.29	.29	.05	434.03	3.84	39.00
14024.00	130.00	0.00	0.00	576.80	650.00	581.03	.41	.33	.09	580.55	4.23	39.00
14024.00	130.00	0.00	0.00	576.80	710.00	581.15	.46	.34	.11	632.02	4.35	39.00
14024.00	130.00	0.00	0.00	576.80	860.00	581.42	.58	.37	.16	760.09	4.62	39.00
14044.00	20.00	0.00	0.00	576.80	480.00	580.64	.39	.06	.05	480.00	3.84	29.00
14044.00	20.00	0.00	0.00	576.80	650.00	581.02	.58	.08	.09	650.00	4.22	29.00
14044.00	20.00	0.00	0.00	576.80	710.00	581.13	.66	.08	.10	710.00	4.33	29.00
14044.00	20.00	0.00	0.00	576.80	860.00	581.38	.85	.10	.14	860.00	4.58	29.00

SECTION NUMBER	CHANNEL LENGTH	MIN EL OF ROADWAY	MAX EL OF LOW CHORD	MIN EL GROUND	DISCHARGE (CFS)	CWSEL	HV	HL	OLOSS	QCH	DEPTH	TOPWID
14054.00	10.00	0.00	0.00	576.80	480.00	580.62	.52	.04	.06	480.00	3.82	24.00
14054.00	10.00	0.00	0.00	576.80	650.00	580.97	.79	.05	.10	650.00	4.17	24.00
14054.00	10.00	0.00	0.00	576.80	710.00	581.07	.89	.06	.12	710.00	4.27	24.00
14054.00	10.00	0.00	0.00	576.80	860.00	581.29	1.17	.07	.16	860.00	4.49	24.00
14060.00	6.00	0.00	0.00	576.80	480.00	580.59	.65	.03	.07	480.00	3.79	21.00
14060.00	6.00	0.00	0.00	576.80	650.00	580.91	1.01	.04	.11	650.00	4.11	21.00
14060.00	6.00	0.00	0.00	576.80	710.00	580.99	1.15	.05	.13	710.00	4.19	21.00
14060.00	6.00	0.00	0.00	576.80	860.00	581.17	1.54	.06	.19	860.00	4.37	21.00
14064.00	4.00	0.00	0.00	576.80	480.00	580.45	.99	.03	.17	480.00	3.65	19.00
14064.00	4.00	0.00	0.00	576.80	650.00	580.65	1.59	.04	.29	650.00	3.85	19.00
14064.00	4.00	0.00	0.00	576.80	710.00	580.80	1.76	.04	0.00	710.00	4.00	19.00
14064.00	4.00	0.00	0.00	576.80	860.00	581.28	1.99	.05	0.00	860.00	4.48	19.00
14065.00	1.00	585.20	582.50	576.80	480.00	580.46	.98	.00	.00	480.00	3.66	19.00
14065.00	1.00	585.20	582.50	576.80	650.00	580.67	1.58	.01	.00	650.00	3.87	19.00
14065.00	1.00	585.20	582.50	576.80	710.00	581.47	1.24	.01	.15	710.00	4.67	19.00
14065.00	1.00	585.20	582.50	576.80	860.00	582.05	1.40	.01	.18	860.00	5.25	19.00
14079.00	14.00	585.20	582.50	576.80	480.00	580.64	.88	.04	.03	480.00	3.84	19.00
14079.00	14.00	585.20	582.50	576.80	650.00	581.37	1.09	.05	.15	650.00	4.57	19.00
14079.00	14.00	585.20	582.50	576.80	710.00	581.65	1.13	.04	.03	710.00	4.85	19.00
14079.00	14.00	585.20	582.50	576.80	860.00	582.23	1.30	.04	.03	860.00	5.43	19.00
14080.00	1.00	0.00	0.00	576.80	480.00	580.65	.88	.00	.00	480.00	3.85	19.00
14080.00	1.00	0.00	0.00	576.80	650.00	581.38	1.08	.00	.00	650.00	4.58	19.00
14080.00	1.00	0.00	0.00	576.80	710.00	581.66	1.13	.00	.00	710.00	4.86	19.00
14080.00	1.00	0.00	0.00	576.80	860.00	582.24	1.30	.00	.00	860.00	5.44	19.00
14083.00	3.00	0.00	0.00	576.80	480.00	581.24	.43	.01	.13	410.09	4.44	25.00
14083.00	3.00	0.00	0.00	576.80	650.00	582.13	.51	.01	.17	549.89	5.33	25.00
14083.00	3.00	0.00	0.00	576.80	710.00	582.45	.53	.01	.18	599.02	5.65	25.00
14083.00	3.00	0.00	0.00	576.80	860.00	583.15	.60	.01	.21	721.90	6.35	25.00
14420.00	337.00	0.00	0.00	576.60	480.00	581.95	.03	.19	.12	141.17	5.35	250.22
14420.00	337.00	0.00	0.00	576.60	650.00	582.89	.02	.12	.15	146.55	6.29	295.00
14420.00	337.00	0.00	0.00	576.60	710.00	583.22	.02	.10	.16	147.72	6.62	295.00
14420.00	337.00	0.00	0.00	576.60	860.00	583.99	.01	.07	.18	154.03	7.39	295.00
14800.00	380.00	0.00	0.00	577.40	480.00	582.16	.19	.29	.08	349.11	4.76	235.81
14800.00	380.00	0.00	0.00	577.40	650.00	583.01	.08	.15	.03	324.42	5.61	266.04
14800.00	380.00	0.00	0.00	577.40	710.00	583.32	.06	.12	.02	316.66	5.92	276.35
14800.00	380.00	0.00	0.00	577.40	860.00	584.05	.04	.08	.01	297.77	6.65	412.69
15020.00	220.00	0.00	0.00	574.90	480.00	582.33	.45	.30	.13	480.00	7.43	12.60
15020.00	220.00	0.00	0.00	574.90	650.00	583.15	.06	.12	.01	650.00	8.25	82.27
15020.00	220.00	0.00	0.00	574.90	710.00	583.42	.06	.11	.00	710.00	8.52	85.09
15020.00	220.00	0.00	0.00	574.90	860.00	584.12	.07	.08	.02	860.00	9.22	92.28

BJ
Browns Town Cr.

SECTION NUMBER	CHANNEL LENGTH	MIN EL OF ROADWAY	MAX EL OF LOW CHORD	MIN EL GROUND	DISCHARGE (CFS)	CWSEL	HV	HL	OLOSS	QCH	DEPTH	TOPWID
15021.00	1.00	0.00	0.00	574.90	480.00	582.33	.45	.00	.00	480.00	7.43	12.60
15021.00	1.00	0.00	0.00	574.90	650.00	583.15	.06	.00	.00	650.00	8.25	82.27
15021.00	1.00	0.00	0.00	574.90	710.00	583.42	.06	.00	.00	710.00	8.52	85.10
15021.00	1.00	0.00	0.00	574.90	860.00	584.12	.07	.00	.00	860.00	9.22	92.29
15061.00	40.00	584.30	582.80	574.90	480.00	582.31	.61	.06	.08	480.00	7.41	12.60
15061.00	40.00	584.30	582.80	574.90	650.00	584.67	.03	1.48	0.00	641.63	9.77	332.34
15061.00	40.00	584.30	582.80	574.90	710.00	584.81	.03	1.35	0.00	691.10	9.91	349.02
15061.00	40.00	584.30	582.80	574.90	860.00	585.06	.04	.91	0.00	810.54	10.16	364.15
15062.00	1.00	0.00	0.00	574.90	480.00	582.55	.42	.00	.06	480.00	7.65	12.60
15062.00	1.00	0.00	0.00	574.90	650.00	584.67	.03	.00	.00	642.31	9.77	332.45
15062.00	1.00	0.00	0.00	574.90	710.00	584.81	.03	.00	.00	692.59	9.91	349.02
15062.00	1.00	0.00	0.00	574.90	860.00	585.06	.04	.00	.00	814.24	10.16	364.21

SECTION NUMBER	DISCHARGE CFS	CWSEL	CWSEL DIFF EACH Q	CWSEL DIFF EACH SECTION	CWSEL-WSELK	TOPWID	T.W. DIFF	LENGTH
10764.000	710.000	578.200	0.000	0.000	0.000	517.332	0.000	0.000
10764.000	900.000	578.340	.140	0.000	0.000	546.266	-28.933	0.000
10764.000	985.000	578.440	.100	0.000	0.000	549.666	-32.333	0.000
10764.000	1190.000	578.780	.340	0.000	0.000	557.142	-39.809	0.000
11134.000	480.000	578.343	0.000	.143	0.000	463.159	0.000	370.000
11134.000	650.000	578.517	.174	.177	0.000	481.779	-18.620	370.000
11134.000	710.000	578.615	.098	.175	0.000	492.926	-29.767	370.000
11134.000	860.000	578.921	.306	.141	0.000	519.999	-56.840	370.000
11734.000	480.000	578.431	0.000	.087	0.000	158.164	0.000	600.000
11734.000	650.000	578.637	.206	.120	0.000	173.002	-14.838	600.000
11734.000	710.000	578.737	.100	.122	0.000	183.807	-25.643	600.000
11734.000	860.000	579.031	.294	.110	0.000	215.564	-57.400	600.000
12164.000	480.000	578.810	0.000	.380	0.000	242.879	0.000	430.000
12164.000	650.000	579.121	.310	.484	0.000	263.669	-20.790	430.000
12164.000	710.000	579.229	.108	.492	0.000	271.641	-28.762	430.000
12164.000	860.000	579.511	.282	.480	0.000	290.064	-47.185	430.000
12884.000	480.000	579.185	0.000	.375	0.000	126.312	0.000	720.000
12884.000	650.000	579.544	.358	.423	0.000	160.880	-34.567	720.000
12884.000	710.000	579.655	.111	.426	0.000	171.593	-45.281	720.000
12884.000	860.000	579.941	.286	.429	0.000	198.926	-72.614	720.000
13324.000	480.000	579.864	0.000	.679	0.000	163.456	0.000	440.000
13324.000	650.000	580.287	.423	.744	0.000	193.082	-29.626	440.000
13324.000	710.000	580.416	.129	.761	0.000	202.075	-38.619	440.000
13324.000	860.000	580.710	.294	.769	0.000	237.982	-74.526	440.000
13724.000	480.000	580.223	0.000	.359	0.000	209.999	0.000	400.000
13724.000	650.000	580.650	.427	.362	0.000	209.999	-.000	400.000
13724.000	710.000	580.783	.133	.367	0.000	209.999	-.000	400.000
13724.000	860.000	581.083	.300	.373	0.000	209.999	-.000	400.000
13894.000	480.000	580.398	0.000	.175	0.000	88.495	0.000	170.000
13894.000	650.000	580.790	.392	.141	0.000	103.999	-15.504	170.000
13894.000	710.000	580.915	.125	.133	0.000	103.999	-15.504	170.000
13894.000	860.000	581.200	.285	.118	0.000	103.999	-15.504	170.000
14024.000	480.000	580.637	0.000	.239	0.000	38.999	0.000	130.000
14024.000	650.000	581.028	.391	.238	0.000	38.999	-.000	130.000
14024.000	710.000	581.146	.118	.231	0.000	38.999	-.000	130.000
14024.000	860.000	581.419	.273	.219	0.000	38.999	-.000	130.000

	14044.000	480.000	580.645	0.000	.008	0.000	28.999	0.000	20.000	
	14044.000	650.000	581.019	.374	-.009	0.000	28.999	-.000	20.000	
	14044.000	710.000	581.130	.111	-.017	0.000	28.999	-.000	20.000	
	14044.000	860.000	581.381	.251	-.038	0.000	28.999	-.000	20.000	
6										
1	14054.000	480.000	580.622	0.000	-.023	0.000	23.999	0.000	10.000	
2	14054.000	650.000	580.971	.349	-.048	0.000	23.999	-.000	10.000	
3	14054.000	710.000	581.071	.100	-.059	0.000	23.999	-.000	10.000	
4	14054.000	860.000	581.290	.219	-.091	0.000	23.999	-.000	10.000	
5										
6	14060.000	480.000	580.588	0.000	-.034	0.000	20.999	0.000	6.000	
7	14060.000	650.000	580.905	.317	-.066	0.000	20.999	-.000	6.000	
8	14060.000	710.000	580.991	.086	-.080	0.000	20.999	-.000	6.000	
9	14060.000	860.000	581.166	.175	-.124	0.000	20.999	-.000	6.000	
10										
11	14064.000	480.000	580.447	0.000	-.140	0.000	19.000	0.000	4.000	
12	14064.000	650.000	580.653	.206	-.252	0.000	19.000	0.000	4.000	
13	14064.000	710.000	580.796	.143	-.195	0.000	19.000	0.000	4.000	
14	14064.000	860.000	581.276	.480	.110	0.000	19.000	0.000	4.000	
15										
16	14065.000	480.000	580.458	0.000	.010	0.000	19.000	0.000	1.000	
17	14065.000	650.000	580.673	.215	.020	0.000	19.000	0.000	1.000	
18	14065.000	710.000	581.473	.800	.677	0.000	19.000	0.000	1.000	
19	14065.000	860.000	582.049	.576	.773	0.000	19.000	0.000	1.000	
20										
21	14079.000	480.000	580.640	0.000	.182	0.000	19.000	0.000	14.000	
22	14079.000	650.000	581.370	.730	.697	0.000	19.000	0.000	14.000	
23	14079.000	710.000	581.653	.284	.181	0.000	19.000	0.000	14.000	
24	14079.000	860.000	582.230	.576	.181	0.000	19.000	0.000	14.000	
25										
26	14080.000	480.000	580.646	0.000	.006	0.000	19.000	0.000	1.000	
27	14080.000	650.000	581.377	.731	.007	0.000	19.000	0.000	1.000	
28	14080.000	710.000	581.660	.283	.007	0.000	19.000	0.000	1.000	
29	14080.000	860.000	582.236	.577	.007	0.000	19.000	0.000	1.000	
30										
31	14083.000	480.000	581.239	0.000	.593	0.000	24.999	0.000	3.000	
32	14083.000	650.000	582.133	.894	.756	0.000	24.999	-.000	3.000	
33	14083.000	710.000	582.448	.315	.788	0.000	24.999	-.000	3.000	
34	14083.000	860.000	583.153	.705	.916	0.000	24.999	-.000	3.000	
35										
36	14420.000	480.000	581.953	0.000	.714	0.000	250.223	0.000	337.000	
37	14420.000	650.000	582.891	.938	.758	0.000	294.999	-44.776	337.000	
38	14420.000	710.000	583.221	.330	.773	0.000	294.999	-44.776	337.000	Brownstown Cr.
39	14420.000	860.000	583.989	.768	.837	0.000	294.999	-44.776	337.000	
40										
41	14800.000	480.000	582.158	0.000	.204	0.000	235.812	0.000	380.000	
42	14800.000	650.000	583.007	.849	.116	0.000	266.042	-30.230	380.000	BJ
43	14800.000	710.000	583.316	.309	.095	0.000	276.351	-40.539	380.000	
44	14800.000	860.000	584.055	.738	.065	0.000	412.694	-176.882	380.000	
45										
46	15020.000	480.000	582.326	0.000	.169	0.000	12.599	0.000	220.000	
47	15020.000	650.000	583.154	.827	.146	0.000	82.266	-69.667	220.000	
48	15020.000	710.000	583.423	.270	.107	0.000	85.092	-72.493	220.000	
49	15020.000	860.000	584.119	.695	.064	0.000	92.282	-79.683	220.000	
50										
51	15021.000	480.000	582.328	0.000	.001	0.000	12.599	0.000	1.000	
52	15021.000	650.000	583.154	.826	.000	0.000	82.272	-69.673	1.000	BK
53	15021.000	710.000	583.424	.270	.000	0.000	85.097	-72.498	1.000	
54	15021.000	860.000	584.119	.695	.000	0.000	92.286	-79.687	1.000	
55										
56	15061.000	480.000	582.310	0.000	-.018	0.000	12.599	0.000	40.000	
57	15061.000	650.000	584.668	2.359	1.514	0.000	332.339	-319.740	40.000	
	15061.000	710.000	584.809	.141	1.386	0.000	349.019	-336.420	40.000	
	15061.000	860.000	585.057	.247	.938	0.000	364.149	-351.550	40.000	

15062.000	480.000	582.552	0.000	.242	0.000	12.599	0.000	1.000
15062.000	650.000	584.669	2.117	.000	0.000	332.449	-319.850	1.000
15062.000	710.000	584.809	.141	.000	0.000	349.020	-336.421	1.000
15062.000	860.000	585.057	.247	-.000	0.000	364.208	-351.609	1.000

DATA FOR LAST CROSS SECTION

PROFILE	TYPE ENC	TARGET	TOP WIDTH AREA-ACRES	TOP WIDTH AREA-DIFF
1	1.000	12.600	19.585	0.000
2	1.000	600.000	21.865	2.280
3	1.000	600.000	22.453	2.868
4	1.000	600.000	25.121	5.536

```
**********************************************
HEC2 VERSION UPDATED JAN 1976
ERROR CORRECTIONS 01,02,03,04,05,06,07,08,09
MODIFICATIONS 52,53,54,55,56,57,58
**********************************************

C
1       CITY OF GIBRALTER          5555-23-01      PM = RICHARD ZANOTTI
T2          10 YEAR FLOOD
T3          BROWNSTOWN CREEK

J1  ICHECK     INQ      NINV     IDIR     STRT       METRIC     HVINS      Q          WSEL       FQ
        -1.       2.       0.       0.  0.000000       0.00       0.0        0.     573.100    0.000

J2  NPROF      IPLOT    PRFVS    XSECV    XSECH      FN         ALLDC      IBW        CHNIM      ITRACE
      1.000     0.000   -1.000    0.000    0.000      0.000      0.000      0.000      0.000      0.000

J3      1.000     10.000    11.000    12.000    14.000     8.000     4.000     0.000     0.000     0.000
NC       .050      .040      .030      .300      .500     0.000     0.000     0.000     0.000     0.000
QT     4.000  1080.000  1290.000  1345.000  1460.000     0.000     0.000     0.000     0.000     0.000

X1  1613.000    64.000  1130.000  1212.000     0.000     0.000     0.000     0.000     0.000     0.000
X3     0.000     0.000     0.000   920.000     0.000  1212.000     0.000     0.000     0.000     0.000
GR   576.300     0.000   576.300    30.000   574.800   130.000   574.800   230.000   573.200   330.000
GR   573.400   430.000   574.000   530.000   574.700   630.000   572.700   730.000   573.300   830.000
GR   573.100   919.000   571.800   930.000   570.100   980.000   572.100  1000.000   574.500  1001.000
GR   574.400  1004.000   571.800  1005.000   570.100  1010.000   568.400  1030.000   568.000  1040.000
GR   567.900  1050.000   568.400  1060.000   570.300  1070.000   571.100  1075.000   572.300  1080.000
GR   572.100  1090.000   571.600  1100.000   571.600  1110.000   570.600  1120.000   573.100  1130.000
GR   571.300  1132.000   570.300  1135.000   569.000  1140.000   568.300  1145.000   567.500  1150.000
GR   566.600  1155.000   565.900  1160.000   565.600  1165.000   565.600  1170.000   565.400  1175.000
GR   565.200  1180.000   565.000  1185.000   565.500  1190.000   566.800  1195.000   567.800  1200.000
GR   569.500  1205.000   572.200  1211.000   575.000  1212.000   574.100  1230.000   572.500  1330.000
GR   573.600  1430.000   573.400  1530.000   572.700  1630.000   573.900  1730.000   573.100  1830.000
GR   572.900  1915.000   573.500  1930.000   575.900  2030.000   578.100  2130.000   578.700  2230.000
GR   578.600  2330.000   578.500  2430.000   578.800  2530.000   578.900  2630.000     0.000     0.000

X1  1783.000     0.000     0.000     0.000   130.000   200.000   170.000     0.000    -.370     0.000
X3     0.000     0.000     0.000   920.000     0.000  1212.000     0.000     0.000     0.000     0.000

X1  1953.000     0.000     0.000     0.000   130.000   200.000   170.000     0.000    -.370     0.000
X3     0.000     0.000     0.000   920.000     0.000  1212.000     0.000     0.000     0.000     0.000
NH     3.000      .050   570.000      .030   594.500      .045  1200.000     0.000     0.000     0.000
ET     0.000     6.100     8.100     8.100     8.100   570.000   594.500   300.000   594.500     0.000

X1  2113.000    34.000   500.000   594.500   130.000   200.000   160.000     0.000   -2.600     0.000
GR   573.700     0.000   574.200   100.000   572.900   150.000   572.500   200.000   572.500   300.000
GR   573.800   400.000   573.700   500.000   570.900   502.000   570.200   505.000   569.600   510.000
GR   569.000   515.000   568.800   520.000   568.500   525.000   567.800   540.000   567.100   560.000
GR   566.800   570.000   566.500   580.000   566.800   594.500   566.900   600.000   567.400   620.000
GR   567.200   640.000   569.800   660.000   570.000   665.000   570.400   670.000   570.600   675.000
GR   570.900   680.000   571.100   685.000   571.400   690.000   572.400   700.000   573.200   800.000
GR   573.200   900.000   573.400  1000.000   574.700  1100.000   576.100  1200.000     0.000     0.000
NH     3.000      .035   570.000      .015   594.500      .025  1200.000     0.000     0.000     0.000
ET     0.000     6.100     8.100     8.100     8.100   570.000   594.500   300.000   594.500     0.000

X1  2114.000     0.000     0.000     0.000     1.000     1.000     1.000     0.000     0.000     0.000
NH     3.000      .035   800.000      .015   824.500      .025  1600.000     0.000     0.000     0.000
```

Revised 8/17/77

8/11/77
IGL datum
+1.43 ft = USGS

	SB	0.000	1.430	3.020	0.000	19.270	0.000	183.100	0.000	563.900	563.900
	ET	0.000	6.100	8.100	8.100	8.100	800.000	824.500	500.000	824.500	0.000
	X1	2131.000	20.000	700.000	824.500	17.000	17.000	17.000	0.000	0.000	0.000
	X2	0.000	0.000	1.000	573.200	574.200	0.000	0.000	0.000	0.000	0.000
6	BT	8.000	500.000	574.200	0.000	600.000	574.200	0.000	700.000	574.500	0.000
1	BT	800.000	575.100	567.000	800.000	575.100	573.700	824.500	575.900	573.300	824.500
2	BT	575.900	566.500	900.000	574.800	0.000	0.000	0.000	0.000	0.000	0.000
3	GR	574.400	0.000	574.100	100.000	574.100	300.000	574.200	400.000	574.200	500.000
4	GR	574.200	600.000	574.500	700.000	569.000	725.000	567.000	800.000	563.900	810.000
5	GR	566.500	824.500	570.000	895.000	574.800	900.000	574.200	1000.000	574.300	1100.000
6	GR	574.600	1200.000	574.900	1300.000	575.500	1400.000	575.400	1500.000	578.400	1600.000
7	ET	0.000	6.100	8.100	8.100	8.100	800.000	824.500	500.000	824.500	0.000
8	NH	3.000	.045	800.000	.030	824.500	.045	1600.000	0.000	0.000	0.000
9											
10	X1	2132.000	0.000	0.000	0.000	1.000	1.000	1.000	0.000	0.000	0.000
11	NC	.045	.045	.030	0.000	0.000	0.000	0.000	0.000	0.000	0.000
12	ET	0.000	6.100	8.100	8.100	8.100	535.000	600.000	360.000	700.000	0.000
13											
14	X1	2182.000	32.000	500.000	700.000	50.000	50.000	50.000	0.000	0.000	0.000
15	GR	573.700	0.000	574.200	100.000	572.900	150.000	572.500	200.000	572.500	300.000
16	GR	573.800	400.000	573.700	500.000	570.900	502.000	570.200	505.000	569.600	510.000
17	GR	569.000	515.000	568.800	520.000	568.500	525.000	567.800	540.000	567.100	560.000
18	GR	566.500	580.000	566.900	600.000	567.400	620.000	567.200	640.000	569.800	660.000
19	GR	570.000	665.000	570.400	670.000	570.600	675.000	570.900	680.000	571.100	685.000
20	GR	571.400	690.000	572.400	700.000	573.200	800.000	573.200	900.000	573.400	1000.000
21	GR	574.700	1100.000	576.100	1200.000	0.000	0.000	0.000	0.000	0.000	0.000
22											
23	X1	2632.000	23.000	300.000	395.000	550.000	250.000	450.000	0.000	0.000	0.000
24	X3	10.000	0.000	0.000	240.000	0.000	450.000	0.000	0.000	0.000	0.000
25	GR	576.300	0.000	574.800	100.000	574.800	200.000	574.300	210.000	574.100	300.000
26	GR	570.400	304.000	568.400	310.000	567.500	315.000	566.200	320.000	565.800	325.000
27	GR	566.400	345.000	568.200	360.000	569.300	365.000	570.000	370.000	570.800	375.000
28	GR	571.400	380.000	572.400	395.000	572.600	400.000	573.500	500.000	572.800	600.000
29	GR	573.300	700.000	574.500	800.000	573.600	900.000	0.000	0.000	0.000	0.000
30											
31	X1	2932.000	31.000	155.000	251.000	300.000	300.000	300.000	0.000	0.000	0.000
32	X3	0.000	0.000	0.000	175.000	0.000	235.000	0.000	0.000	0.000	0.000
33	GR	576.500	0.000	575.000	55.000	576.000	142.000	574.000	155.000	572.400	161.000
34	GR	571.500	163.000	570.100	165.000	569.000	170.000	568.300	175.000	567.600	180.000
35	GR	567.300	185.000	566.900	195.000	566.800	205.000	567.100	210.000	567.600	215.000
36	GR	567.500	220.000	567.500	225.000	567.900	230.000	568.300	235.000	568.900	240.000
37	GR	571.400	245.000	572.400	250.000	573.500	251.000	573.700	255.000	573.400	355.000
38	GR	575.100	455.000	576.400	555.000	576.800	655.000	577.500	755.000	579.500	855.000
39	GR	580.400	955.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
40											
41	X1	2982.000	30.000	800.000	843.000	50.000	50.000	50.000	.710	0.000	0.000
42	X3	10.000	0.000	0.000	700.000	0.000	843.000	0.000	575.000	575.000	0.000
43	GR	575.600	0.000	575.700	100.000	575.800	200.000	575.800	300.000	575.700	400.000
44	GR	575.700	500.000	575.700	600.000	576.000	700.000	575.900	765.000	569.000	800.000
45	GR	567.900	805.000	567.500	810.000	567.200	815.000	567.200	820.000	567.300	825.000
46	GR	567.200	830.000	567.000	835.000	567.100	840.000	567.100	843.000	573.500	875.000
47	GR	577.200	900.000	576.100	1000.000	576.400	1200.000	577.100	1300.000	577.900	1400.000
48	GR	578.900	1500.000	579.800	1600.000	580.200	1700.000	580.700	1800.000	581.800	1900.000
49	NC	.018	.018	.015	0.000	0.000	0.000	0.000	0.000	0.000	0.000
50											
51	X1	2983.000	30.000	800.000	843.000	1.000	1.000	1.000	.710	0.000	0.000
52	X3	10.000	0.000	0.000	700.000	0.000	843.000	0.000	575.000	575.000	0.000
53	GR	575.600	0.000	575.700	100.000	575.800	200.000	575.800	300.000	575.700	400.000
54	GR	575.700	500.000	575.700	600.000	576.000	700.000	575.900	765.000	569.000	800.000
55	GR	567.900	805.000	567.500	810.000	567.200	815.000	567.200	820.000	567.300	825.000
56	GR	567.200	830.000	567.000	835.000	567.100	840.000	567.100	843.000	573.500	875.000
57	GR	577.200	900.000	576.100	1000.000	576.400	1200.000	577.100	1300.000	577.900	1400.000
	GR	578.900	1500.000	579.800	1600.000	580.200	1700.000	580.700	1800.000	581.800	1900.000
	SB	0.000	1.610	3.000	0.000	28.740	0.000	195.400	0.000	567.000	567.000

	X1	3049.000	30.000	800.000	843.000	66.000	66.000	66.000	.710	0.000	0.000
	X2	0.000	0.000	1.000	573.800	577.600	0.000	0.000	0.000	.710	0.000
	X3	10.000	0.000	0.000	700.000	0.000	843.000	0.000	577.600	577.600	0.000
	BT	6.000	700.000	576.000	0.000	800.000	577.400	569.000	800.000	577.400	573.800
	BT	843.000	577.600	573.800	843.000	577.600	567.100	900.000	577.200	0.000	0.000
6	GR	575.600	0.000	575.700	100.000	575.800	200.000	575.800	300.000	575.700	400.000
1	GR	575.700	500.000	575.700	600.000	576.000	700.000	575.900	765.000	569.000	800.000
2	GR	567.900	805.000	567.500	810.000	567.200	815.000	567.200	820.000	567.300	825.000
3	GR	567.200	830.000	567.000	835.000	567.100	840.000	567.100	843.000	573.500	875.000
4	GR	577.200	900.000	576.100	1000.000	576.400	1200.000	577.100	1300.000	577.900	1400.000
5	GR	578.900	1500.000	579.800	1600.000	580.200	1700.000	580.700	1800.000	581.800	1900.000
6	NC	.045	.045	.030	0.000	0.000	0.000	0.000	0.000	0.000	0.000
7											
8	X1	3050.000	30.000	800.000	843.000	1.000	1.000	1.000	.710	0.000	0.000
9	X3	10.000	0.000	0.000	700.000	0.000	843.000	0.000	577.600	577.600	0.000
10	GR	575.600	0.000	575.700	100.000	575.800	200.000	575.800	300.000	575.700	400.000
11	GR	575.700	500.000	575.700	600.000	576.000	700.000	575.900	765.000	569.000	800.000
12	GR	567.900	805.000	567.500	810.000	567.200	815.000	567.200	820.000	567.300	825.000
13	GR	567.200	830.000	567.000	835.000	567.100	840.000	567.100	843.000	573.500	875.000
14	GR	577.200	900.000	576.100	1000.000	576.400	1200.000	577.100	1300.000	577.900	1400.000
15	GR	578.900	1500.000	579.800	1600.000	580.200	1700.000	580.700	1800.000	581.800	1900.000
16											
17	X1	3250.000	40.000	70.000	338.000	100.000	300.000	200.000	0.000	0.000	0.000
18	X3	0.000	0.000	0.000	52.000	0.000	400.000	0.000	0.000	0.000	0.000
19	GR	576.600	0.000	574.100	1.000	574.100	25.000	575.400	30.000	576.100	52.000
20	GR	575.700	70.000	571.200	91.000	570.200	95.000	569.600	100.000	569.500	105.000
21	GR	568.600	120.000	567.500	130.000	567.500	140.000	567.500	150.000	567.800	160.000
22	GR	567.800	170.000	568.300	180.000	568.700	190.000	568.900	200.000	569.500	210.000
23	GR	569.200	220.000	570.100	230.000	570.000	240.000	570.000	250.000	569.900	260.000
24	GR	570.600	270.000	570.500	280.000	570.500	290.000	571.000	300.000	571.000	305.000
25	GR	570.800	310.000	571.400	315.000	571.700	320.000	573.400	338.000	574.600	370.000
26	GR	575.500	470.000	576.100	575.000	576.500	670.000	578.100	770.000	581.600	1070.000
27	QT	4.000	1085.000	1290.000	1345.000	1460.000	0.000	0.000	0.000	0.000	0.000
28											
29	X1	3750.000	41.000	500.000	800.000	550.000	450.000	500.000	0.000	0.000	0.000
30	X3	0.000	0.000	0.000	400.000	0.000	1050.000	0.000	0.000	0.000	0.000
31	GR	575.600	0.000	572.900	15.000	573.400	100.000	573.000	200.000	574.700	300.000
32	GR	577.000	400.000	574.300	500.000	571.500	537.000	570.900	545.000	570.100	550.000
33	GR	571.400	555.000	570.100	570.000	569.300	580.000	568.300	590.000	567.900	600.000
34	GR	567.800	610.000	567.800	620.000	568.100	630.000	568.500	640.000	569.100	650.000
35	GR	569.500	660.000	569.500	670.000	568.900	680.000	570.000	690.000	570.300	700.000
36	GR	570.200	710.000	570.400	720.000	570.400	730.000	570.600	740.000	570.500	750.000
37	GR	570.500	760.000	570.500	770.000	570.600	780.000	571.500	790.000	572.400	800.000
38	GR	572.600	900.000	572.900	1000.000	573.900	1100.000	574.300	1200.000	575.200	1300.000
39	GR	577.700	1400.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
40											
41	X1	4225.000	90.000	650.000	861.000	550.000	300.000	475.000	0.000	-.700	0.000
42	X3	0.000	0.000	0.000	515.000	0.000	1300.000	0.000	0.000	0.000	0.000
43	GR	575.300	0.000	574.000	22.400	574.000	44.800	574.100	67.200	574.100	89.600
44	GR	574.000	112.000	573.900	134.400	573.800	156.800	573.700	179.300	573.700	201.700
45	GR	573.700	224.100	573.600	246.500	573.500	268.900	573.600	291.300	573.600	313.700
46	GR	573.600	336.200	573.700	358.600	573.700	381.000	573.800	403.400	574.000	425.800
47	GR	574.200	448.200	574.400	470.600	574.600	493.100	574.800	515.500	574.700	537.900
48	GR	574.500	560.300	574.200	582.700	573.900	605.100	573.600	627.500	573.300	650.000
49	GR	572.700	657.000	572.200	664.000	571.700	671.100	571.300	678.100	570.600	685.100
50	GR	571.000	692.200	570.500	699.200	570.000	706.200	569.500	713.300	569.300	720.300
51	GR	569.100	727.300	568.900	734.400	568.900	741.400	569.000	748.400	569.100	755.500
52	GR	569.100	762.500	568.900	769.500	568.500	776.500	569.100	783.600	569.200	790.600
53	GR	569.000	797.600	569.100	804.700	569.100	811.700	569.200	818.700	569.300	825.800
54	GR	569.600	832.800	569.900	839.800	570.300	846.900	571.100	853.900	572.300	861.000
55	GR	572.800	888.900	572.800	916.900	572.800	944.800	572.800	972.800	572.800	1000.800
56	GR	573.000	1028.700	573.300	1056.700	573.500	1084.700	573.900	1112.600	574.400	1140.600
57	GR	574.800	1168.600	575.200	1196.500	575.600	1224.500	575.900	1252.500	576.100	1280.400
	GR	576.300	1308.400	576.400	1336.400	576.600	1364.300	576.700	1392.300	576.900	1420.300
	GR	577.100	1448.200	577.300	1476.200	577.500	1504.200	577.600	1532.100	577.700	1560.100
	GR	577.900	1588.100	578.200	1616.000	578.400	1644.000	578.700	1672.00	579.000	170[illegible] 0

X1	4700.000	34.000	800.000	922.000	550.000	300.000	475.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	300.000	0.000	1200.000	0.000	0.000	0.000	0.000
GR	575.100	0.000	575.100	100.000	574.300	200.000	574.300	300.000	573.500	400.000
GR	572.800	500.000	572.700	600.000	572.900	700.000	572.300	800.000	571.600	810.000
GR	571.300	820.000	570.900	830.000	570.800	840.000	570.000	850.000	569.300	860.000
GR	568.300	870.000	568.200	880.000	567.800	890.000	568.000	900.000	569.500	910.000
GR	571.200	920.000	572.300	922.000	573.100	925.000	573.300	1000.000	573.100	1100.000
GR	574.200	1200.000	576.300	1300.000	577.900	1400.000	578.700	1500.000	579.300	1600.000
GR	580.100	1700.000	580.400	1800.000	580.200	1900.000	580.400	2000.000	0.000	0.000
X1	5750.000	30.000	600.000	670.000	300.000	1100.000	1050.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	450.000	0.000	1250.000	0.000	0.000	0.000	0.000
GR	572.800	0.000	574.200	100.000	575.100	200.000	574.600	300.000	574.800	400.000
GR	574.700	500.000	573.900	600.000	572.300	601.000	570.400	606.000	569.500	610.000
GR	568.900	620.000	568.600	630.000	569.400	640.000	569.900	645.000	570.500	650.000
GR	570.700	655.000	571.600	660.000	572.700	670.000	572.800	700.000	573.000	800.000
GR	573.100	900.000	574.800	1000.000	576.400	1100.000	576.200	1200.000	574.900	1300.000
GR	574.900	1400.000	575.400	1500.000	575.300	1600.000	575.400	1700.000	575.600	1800.000
X1	6750.000	37.000	855.000	905.000	600.000	600.000	1000.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	650.000	0.000	1050.000	0.000	0.000	0.000	0.000
GR	572.700	0.000	573.800	14.000	574.000	55.000	573.500	155.000	574.300	255.000
GR	577.900	355.000	575.300	455.000	574.700	555.000	574.400	655.000	574.200	755.000
GR	573.700	790.000	573.300	800.000	573.400	855.000	572.700	856.000	571.100	860.000
GR	570.000	865.000	569.400	870.000	569.500	875.000	569.000	880.000	568.800	885.000
GR	568.600	890.000	568.600	895.000	570.600	900.000	573.200	905.000	573.800	910.000
GR	572.900	955.000	577.200	1055.000	577.200	1155.000	576.100	1255.000	575.200	1355.000
GR	575.900	1455.000	577.900	1555.000	576.100	1655.000	576.700	1755.000	578.400	1855.000
GR	580.700	1955.000	583.400	2055.000	0.000	0.000	0.000	0.000	0.000	0.000
QT	4.000	1090.000	1590.000	1770.000	2225.000	0.000	0.000	0.000	0.000	0.000
X1	7200.000	30.000	700.000	746.000	400.000	400.000	450.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	665.000	0.000	782.000	0.000	0.000	0.000	0.000
GR	574.500	0.000	574.500	100.000	574.300	200.000	575.400	300.000	574.800	400.000
GR	574.100	500.000	573.200	600.000	573.500	700.000	572.100	703.000	571.900	705.000
GR	570.100	710.000	568.900	715.000	568.400	720.000	568.200	725.000	568.800	730.000
GR	569.500	735.000	570.700	740.000	572.000	745.000	573.400	746.000	573.100	800.000
GR	575.200	900.000	578.000	1000.000	577.800	1100.000	576.900	1200.000	575.900	1300.000
GR	576.200	1400.000	577.500	1500.000	578.500	1600.000	577.600	1700.000	578.800	1900.000
X1	7250.000	17.000	982.000	1100.000	50.000	50.000	50.000	0.000	0.000	0.000
GR	580.600	0.000	580.500	885.000	580.100	982.000	579.600	982.000	579.600	985.500
GR	573.900	998.200	573.900	1020.500	569.600	1029.000	569.600	1052.000	573.300	1061.200
GR	573.300	1084.400	579.200	1097.200	579.200	1100.000	579.700	1100.000	578.000	1505.000
GR	580.000	2005.000	585.500	2445.000	0.000	0.000	0.000	0.000	0.000	0.000
NC	.018	.018	.018	0.000	0.000	0.000	0.000	0.000	0.000	0.000
X1	7251.000	32.000	982.000	1100.000	1.000	1.000	1.000	0.000	0.000	0.000
BT	13.000	0.000	580.600	0.000	885.000	580.500	0.000	982.000	580.100	0.000
BT	982.000	583.100	580.100	994.300	583.100	580.100	994.300	583.100	578.600	1087.600
BT	582.800	578.300	1087.600	582.800	579.800	1100.000	582.700	579.700	1100.000	579.700
BT	0.000	1505.000	578.000	0.000	2005.000	580.000	0.000	2445.000	585.500	0.000
GR	580.600	0.000	580.500	885.000	580.100	982.000	579.600	982.000	579.600	985.500
GR	576.100	994.300	578.600	994.300	578.600	997.600	574.600	997.600	573.900	998.200
GR	573.900	1020.500	572.300	1023.200	578.500	1023.200	578.500	1025.700	571.300	1025.700
GR	569.600	1029.000	569.600	1052.000	571.100	1056.200	578.400	1056.200	578.400	1058.800
GR	572.000	1058.800	573.300	1061.200	573.300	1084.400	578.300	1084.400	578.300	1087.600
GR	574.800	1087.600	579.200	1097.200	579.200	1100.000	579.700	1100.000	578.000	1505.000
GR	580.000	2005.000	585.500	2445.000	0.000	0.000	0.000	0.000	0.000	0.000
X1	7298.000	0.000	0.000	0.000	47.000	47.000	47.000	0.000	0.000	0.000
X2	0.000	0.000	0.000	0.000	0.000	0.000	1.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
NC	.050	.050	.030	0.000	0.000	0.000	0.000	0.000	0.000	0.000

	X1	7299.000	17.000	982.000	1100.000	1.000	1.000	1.000	0.000	0.000
	X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
	GR	580.600	0.000	580.500	885.000	580.100	982.000	579.600	982.000	579.600	985.500
	GR	573.900	998.200	573.900	1020.500	569.600	1029.000	569.600	1052.000	573.300	1061.200
	GR	573.300	1084.400	579.200	1097.200	579.200	1100.000	579.700	1100.000	578.000	1505.000
6	GR	580.000	2005.000	585.500	2445.000	0.000	0.000	0.000	0.000	0.000	0.000
1	NC	.050	.050	.030	0.000	0.000	0.000	0.000	0.000	0.000	0.000
2											
3	X1	7355.000	13.000	330.000	370.000	56.000	56.000	56.000	0.000	0.000	0.000
4	X3	0.000	0.000	0.000	250.000	0.000	450.000	0.000	0.000	0.000	0.000
5	GR	574.600	0.000	574.600	130.000	574.600	200.000	572.500	330.000	571.400	335.000
6	GR	569.100	350.000	570.900	365.000	572.500	370.000	574.600	540.000	576.500	565.000
7	GR	578.600	590.000	578.600	610.000	576.500	675.000	0.000	0.000	0.000	0.000
8											
9	X1	7805.000	13.000	669.000	728.000	450.000	450.000	450.000	0.000	0.000	0.000
10	X3	0.000	0.000	0.000	500.000	0.000	1000.000	0.000	0.000	0.000	0.000
11	GR	576.800	0.000	576.500	159.000	576.200	399.000	575.900	614.000	575.800	669.000
12	GR	572.100	679.000	569.300	702.000	571.600	727.000	573.600	727.000	574.600	728.000
13	GR	576.600	820.000	576.600	1050.000	576.600	1380.000	0.000	0.000	0.000	0.000
14											
15	X1	8305.000	12.000	680.000	745.000	500.000	500.000	500.000	0.000	0.000	0.000
16	X3	0.000	0.000	0.000	550.000	0.000	800.000	0.000	0.000	0.000	0.000
17	GR	575.500	0.000	575.500	330.000	575.500	680.000	572.300	692.000	570.300	705.000
18	GR	571.800	719.000	575.300	722.000	575.400	730.000	576.500	745.000	578.600	745.000
19	GR	577.100	940.000	576.600	1130.000	0.000	0.000	0.000	0.000	0.000	0.000
20											
21	X1	8605.000	27.000	582.000	630.000	300.000	300.000	300.000	0.000	0.000	0.000
22	X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
23	GR	583.400	0.000	583.200	200.000	582.800	400.000	582.600	500.000	582.500	582.000
24	GR	571.500	582.000	571.500	586.500	571.500	591.000	571.500	591.000	571.600	593.000
25	GR	571.600	593.000	571.600	599.000	571.500	605.000	571.500	605.000	571.400	607.000
26	GR	571.400	607.000	571.300	613.000	571.200	619.000	571.200	619.000	571.100	621.000
27	GR	571.100	621.000	571.000	625.500	571.000	630.000	582.500	630.000	582.400	680.000
28	GR	582.000	840.000	581.600	1000.000	0.000	0.000	0.000	0.000	0.000	0.000
29	NC	.020	.020	.015	0.000	0.000	0.000	0.000	0.000	0.000	0.000
30											
31	X1	8606.000	0.000	0.000	0.000	1.000	1.000	1.000	0.000	0.000	0.000
32	X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
33	SB	1.150	1.530	3.000	0.000	48.000	6.000	274.500	0.000	571.000	571.000
34											
35	X1	8658.000	0.000	0.000	0.000	52.000	52.000	52.000	0.000	0.000	0.000
36	X2	0.000	0.000	1.000	577.900	581.600	0.000	0.000	0.000	0.000	0.000
37	X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
38	BT	27.000	0.000	583.400	0.000	200.000	583.200	0.000	400.000	582.800	0.000
39	BT	500.000	582.600	0.000	582.000	582.500	0.000	582.000	582.500	577.900	586.500
40	BT	582.500	577.900	591.000	582.500	577.900	591.000	582.500	571.500	593.000	582.500
41	BT	571.600	593.000	582.500	577.900	599.000	582.500	577.900	605.000	582.500	577.900
42	BT	605.000	582.500	571.500	607.000	582.500	571.400	607.000	582.500	577.900	613.000
43	BT	582.500	577.900	619.000	582.500	577.900	619.000	582.500	571.200	621.000	582.500
44	BT	571.100	621.000	582.500	577.900	625.500	582.500	577.900	630.000	582.500	577.900
45	BT	630.000	582.500	0.000	680.000	582.400	0.000	840.000	582.000	0.000	1000.000
46	BT	581.600	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
47	NC	.050	.045	.032	0.000	0.000	0.000	0.000	0.000	0.000	0.000
48											
49	X1	8659.000	0.000	0.000	0.000	1.000	1.000	1.000	0.000	0.000	0.000
50	X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
51											
52	X1	8816.000	19.000	299.000	331.000	157.000	157.000	157.000	0.000	0.000	0.000
53	X3	0.000	0.000	0.000	235.000	0.000	425.000	0.000	0.000	0.000	0.000
54	GR	582.700	0.000	582.000	180.000	581.900	235.000	578.400	242.000	576.400	265.000
55	GR	574.400	280.000	574.200	299.000	571.900	302.000	569.900	315.000	570.400	328.000
56	GR	574.300	331.000	574.400	365.000	576.400	380.000	578.400	390.000	580.400	415.000
57	GR	582.400	425.000	582.400	465.000	580.400	480.000	578.400	505.000	0.000	0.000
	QT	4.000	960.000	1355.000	1520.000	1960.000	0.000	0.000	0.000	0.000	0.000
	X1	9106.000	19.000	441.000	500.000	290.000	290.000	290.000	0.000	.000	0.00

X3	10.000	0.000	0.000	0.000	0.000	0.00	0.00	.00	.0	0.0
GR	583.900	0.000	583.800	120.000	583.700	240.000	583.600	360.000	583.600	441.000
GR	572.600	441.000	572.000	458.500	572.000	458.500	571.900	461.500	571.900	461.500
GR	571.500	470.500	571.900	479.500	571.900	479.500	572.000	482.500	572.000	482.500
GR	572.600	500.000	583.600	500.000	583.600	700.000	583.600	900.000	0.000	0.000
NC	.020	.020	.018	0.000	0.000	0.000	0.000	0.000	0.000	0.000
X1	9107.000	0.000	0.000	0.000	1.000	1.000	1.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
BT	19.000	0.000	583.900	0.000	120.000	583.800	0.000	240.000	583.700	0.000
BT	360.000	583.600	0.000	441.000	583.600	572.600	441.000	583.600	580.100	458.500
BT	583.600	580.100	458.500	583.600	572.000	461.500	583.600	571.900	461.500	583.600
BT	580.100	470.500	583.600	580.100	479.500	583.600	580.100	479.500	583.600	571.900
BT	482.500	583.600	572.000	482.500	583.600	580.100	500.000	583.600	580.100	500.000
BT	583.600	572.600	700.000	583.600	0.000	900.000	583.600	0.000	0.000	0.000
X1	9127.000	0.000	0.000	0.000	20.000	20.000	20.000	0.000	0.000	0.000
X2	0.000	0.000	0.000	0.000	0.000	0.000	1.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
NC	.050	.045	.035	0.000	0.000	0.000	0.000	0.000	0.000	0.000
X1	9128.000	0.000	0.000	0.000	1.000	1.000	1.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
X1	9264.000	14.000	680.000	725.000	136.000	136.000	136.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	536.000	0.000	868.000	0.000	0.000	0.000	0.000
GR	582.700	0.000	582.600	350.000	580.700	360.000	578.700	550.000	576.600	600.000
GR	576.300	680.000	572.600	690.000	571.500	700.000	572.800	715.000	576.900	725.000
GR	577.100	970.000	577.400	1335.000	578.600	1360.000	581.800	1400.000	0.000	0.000
QT	4.000	1015.000	1370.000	1465.000	1700.000	0.000	0.000	0.000	0.000	0.000
X1	9764.000	12.000	365.000	402.000	500.000	500.000	500.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	150.000	0.000	700.000	0.000	0.000	0.000	0.000
GR	580.600	0.000	578.600	85.000	576.800	150.000	576.600	160.000	576.500	365.000
GR	572.400	370.000	571.500	380.000	572.800	390.000	576.500	402.000	577.100	1010.000
GR	579.700	1040.000	583.500	1080.000	0.000	0.000	0.000	0.000	0.000	0.000
NC	.045	.045	.030	0.000	0.000	0.000	0.000	0.000	0.000	0.000
X1	10264.000	14.000	665.000	700.000	500.000	500.000	500.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	510.000	0.000	1230.000	0.000	0.000	0.000	0.000
GR	583.700	0.000	582.600	345.000	582.600	515.000	580.700	523.000	578.500	535.000
GR	576.600	570.000	576.600	665.000	572.500	670.000	571.100	680.000	572.600	690.000
GR	576.600	700.000	576.700	710.000	577.600	1110.000	578.100	1380.000	0.000	0.000
X1	10764.000	13.000	560.000	590.000	500.000	500.000	500.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	415.000	0.000	980.000	0.000	0.000	0.000	0.000
GR	581.600	0.000	580.700	225.000	580.700	400.000	578.600	425.000	577.100	475.000
GR	576.900	560.000	573.600	563.000	572.300	575.000	573.300	585.000	576.800	590.000
GR	577.100	765.000	578.600	1025.000	580.600	1185.000	0.000	0.000	0.000	0.000
QT	4.000	760.000	1015.000	1100.000	1265.000	0.000	0.000	0.000	0.000	0.000
X1	11264.000	13.000	684.000	718.000	500.000	500.000	500.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	550.000	0.000	900.000	0.000	0.000	0.000	0.000
GR	583.200	0.000	582.600	115.000	582.000	375.000	578.600	525.000	578.000	630.000
GR	577.600	684.000	572.600	688.000	570.900	700.000	572.700	712.000	578.400	718.000
GR	578.400	1160.000	579.100	1300.000	579.300	1400.000	0.000	0.000	0.000	0.000
X1	11364.000	9.000	670.000	730.000	100.000	100.000	100.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	595.000	0.000	900.000	0.000	0.000	0.000	0.000
GR	583.300	0.000	580.600	220.000	578.600	420.000	576.600	670.000	570.900	700.000
GR	576.600	730.000	576.600	1150.000	578.600	1280.000	578.700	1400.000	0.000	0.000
X1	11644.000	15.000	420.000	535.000	280.000	280.000	280.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	390.000	0.000	550.000	0.000	0.000	0.000	0.000
GR	580.600	0.000	582.600	175.000	582.600	280.000	580.600	340.000	578.600	365.000
GR	576.500	420.000	575.100	500.000	574.400	515.000	575.200	530.00	576.600	535.000

GR	578.600	700.000	580.500	720.000	582.600	740.000	582.600	835.000	580.500	[illegible]
X1	11714.000	10.000	310.000	338.000	70.000	70.000	70.000	0.000	0.000	0.000
GR	583.200	0.000	582.900	200.000	582.900	310.000	578.200	310.000	573.200	310.500
GR	573.200	337.500	578.200	338.000	582.900	338.000	582.900	700.000	582.900	1100.000
NC	.018	.018	.018	0.000	0.000	0.000	0.000	0.000	0.000	0.000
X1	11715.000	0.000	0.000	0.000	1.000	1.000	1.000	0.000	0.000	0.000
SB	0.000	1.750	3.000	0.000	28.500	0.000	140.500	0.000	573.200	573.200
X1	11729.000	0.000	0.000	0.000	14.000	14.000	14.000	0.000	0.000	0.000
X2	0.000	0.000	1.000	578.200	582.900	0.000	0.000	0.000	0.000	0.000
BT	4.000	310.000	582.900	578.200	338.000	582.900	578.200	700.000	582.900	0.000
BT	1100.000	582.900	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
NC	.050	.045	.035	0.000	0.000	0.000	0.000	0.000	0.000	0.000
X1	11730.000	0.000	0.000	0.000	1.000	1.000	1.000	0.000	0.000	0.000
QT	4.000	810.000	1100.000	1210.000	1450.000	0.000	0.000	0.000	0.000	0.000
X1	11765.000	10.000	610.000	655.000	35.000	35.000	35.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	585.000	0.000	683.000	0.000	0.000	0.000	0.000
GR	584.400	0.000	583.600	130.000	582.500	430.000	578.100	610.000	573.700	615.000
GR	571.700	630.000	573.000	645.000	582.000	655.000	583.600	1130.000	584.100	1250.000
NC	.055	.070	.400	0.000	0.000	0.000	0.000	0.000	0.000	0.000
X1	12005.000	14.000	480.000	513.000	240.000	240.000	240.000	0.000	-.600	0.000
X3	0.000	0.000	0.000	350.000	0.000	670.000	0.000	0.000	0.000	0.000
GR	584.000	0.000	582.800	100.000	583.200	200.000	582.300	300.000	581.900	400.000
GR	580.100	480.000	573.900	490.000	572.700	498.000	573.900	505.000	578.500	513.000
GR	581.000	600.000	581.200	700.000	581.300	800.000	581.700	835.000	0.000	0.000
X1	12365.000	14.000	480.000	513.000	360.000	360.000	360.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	450.000	0.000	780.000	0.000	0.000	0.000	0.000
GR	584.000	0.000	582.800	100.000	583.200	200.000	582.300	300.000	581.900	400.000
GR	580.100	480.000	573.900	490.000	572.700	498.000	573.900	505.000	578.500	513.000
GR	581.000	600.000	581.200	700.000	581.300	800.000	581.700	835.000	0.000	0.000
X1	12440.000	0.000	0.000	0.000	75.000	75.000	75.000	0.000	.200	0.000
X3	0.000	0.000	0.000	480.000	0.000	835.000	0.000	0.000	0.000	0.000
NC	.020	.020	.018	0.000	0.000	0.000	0.000	0.000	0.000	0.000
X1	12441.000	0.000	0.000	0.000	1.000	1.000	1.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	480.000	0.000	835.000	0.000	0.000	0.000	0.000
SB	0.000	1.680	3.040	0.000	27.650	0.000	179.750	0.000	572.900	572.900
X1	12489.000	20.000	700.000	735.000	48.000	48.000	48.000	0.000	0.000	0.000
X2	0.000	0.000	1.000	579.400	582.500	0.000	0.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	700.000	0.000	1030.000	0.000	582.500	582.500	0.000
BT	15.000	0.000	585.700	0.000	100.000	585.700	0.000	200.000	585.500	0.000
BT	300.000	585.200	0.000	400.000	584.900	0.000	500.000	584.400	0.000	600.000
BT	584.000	0.000	700.000	583.500	577.500	700.000	583.500	579.400	735.000	583.500
BT	579.400	735.000	583.500	573.900	800.000	583.100	0.000	900.000	582.700	0.000
BT	1000.000	582.500	0.000	1030.000	582.500	0.000	0.000	0.000	0.000	0.000
GR	585.700	0.000	585.700	100.000	585.500	200.000	585.200	300.000	584.900	400.000
GR	584.400	500.000	584.000	600.000	583.700	660.000	577.500	700.000	573.800	715.000
GR	572.900	720.000	573.000	728.000	573.900	735.000	583.400	750.000	583.100	800.000
GR	582.700	900.000	582.500	1000.000	582.500	1100.000	582.700	1200.000	583.000	1300.000
NC	.065	.050	.035	0.000	0.000	0.000	0.000	0.000	0.000	0.000
X1	12490.000	0.000	0.000	0.000	1.000	1.000	1.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	700.000	0.000	1030.000	0.000	582.500	582.500	0.000
NC	.050	.045	.032	0.000	0.000	0.000	0.000	0.000	0.000	0.000
QT	4.000	1090.000	1590.000	1770.000	2225.000	0.000	0.000	0.000	0.000	0.000
X1	-8816.000	19.000	299.000	331.000	157.000	157.000	157.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	235.000	0.000	425.000	0.000	0.000	0.000	0.000

	GR	582.700	0.000	582.000	180.000	581.900	235.000	578.400	242.000	576.400	265.000
	GR	574.400	280.000	574.200	299.000	571.900	302.000	569.900	315.000	570.400	328.000
	GR	574.300	331.000	574.400	365.000	576.400	380.000	578.400	390.000	580.400	415.000
	GR	582.400	425.000	582.400	465.000	580.400	480.000	578.400	505.000	0.000	0.000
	QT	4.000	145.000	235.000	255.000	270.000	0.000	0.000	0.000	0.000	0.000
6	NC	.040	.040	.040	0.000	0.000	0.000	0.000	0.000	0.000	0.000
1											
2	X1	9546.000	10.000	0.000	130.000	730.000	730.000	730.000	0.000	0.000	0.000
3	GR	579.600	0.000	578.600	30.000	577.600	33.000	578.600	35.000	578.600	45.000
4	GR	577.600	60.000	578.600	70.000	580.600	111.000	582.600	119.000	582.900	130.000
5											
6	X1	10246.000	9.000	0.000	110.000	700.000	700.000	700.000	0.000	0.000	0.000
7	GR	578.600	0.000	577.600	16.000	574.600	23.000	574.600	65.000	576.600	80.000
8	GR	578.600	92.000	580.600	96.000	582.600	103.000	582.600	110.000	0.000	0.000
9											
10	X1	10846.000	9.000	0.000	110.000	600.000	600.000	600.000	0.000	0.000	0.000
11	GR	578.600	0.000	578.600	7.000	576.600	15.000	574.600	18.000	574.600	80.000
12	GR	576.600	85.000	578.600	91.000	580.600	98.000	582.400	110.000	0.000	0.000
13											
14	X1	11846.000	12.000	0.000	110.000	1000.000	1000.000	1000.000	0.000	0.000	0.000
15	GR	580.600	0.000	580.600	6.000	578.600	14.000	576.600	18.000	574.600	23.000
16	GR	572.600	26.000	572.600	79.000	574.600	83.000	576.600	88.000	578.600	90.000
17	GR	580.600	96.000	580.600	110.000	0.000	0.000	0.000	0.000	0.000	0.000
18	NC	.050	.045	.035	0.000	0.000	0.000	0.000	0.000	0.000	0.000
19	QT	4.000	960.000	1355.000	1520.000	1960.000	0.000	0.000	0.000	0.000	0.000
20											
21	X1	-9264.000	14.000	680.000	725.000	0.000	0.000	0.000	0.000	0.000	0.000
22	X3	0.000	0.000	0.000	536.000	0.000	868.000	0.000	0.000	0.000	0.000
23	GR	582.700	0.000	582.600	350.000	580.700	360.000	578.700	550.000	576.600	600.000
24	GR	576.300	680.000	572.600	690.000	571.500	700.000	572.800	715.000	576.900	725.000
25	GR	577.100	970.000	577.400	1335.000	578.600	1360.000	581.800	1400.000	0.000	0.000
26	NC	.040	.040	.040	0.000	0.000	0.000	0.000	0.000	0.000	0.000
27	QT	4.000	25.000	155.000	220.000	435.000	0.000	0.000	0.000	0.000	0.000
28											
29	X1	9594.000	6.000	0.000	145.000	330.000	330.000	330.000	0.000	0.000	0.000
30	GR	582.900	0.000	582.600	22.000	580.600	28.000	579.500	57.000	580.600	86.000
31	GR	581.600	145.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
32											
33	X1	10294.000	6.000	0.000	205.000	700.000	700.000	700.000	0.000	0.000	0.000
34	GR	582.900	0.000	582.600	11.000	580.600	16.000	578.600	24.000	578.600	31.000
35	GR	579.600	205.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
36											
37	X1	10894.000	10.000	0.000	255.000	600.000	600.000	600.000	0.000	0.000	0.000
38	GR	582.400	0.000	580.600	15.000	578.600	21.000	576.600	25.000	574.600	31.000
39	GR	574.100	90.000	574.600	145.000	576.600	170.000	578.600	205.000	579.600	255.000
40											
41	X1	11894.000	7.000	0.000	335.000	1000.000	1000.000	1000.000	0.000	0.000	0.000
42	GR	582.600	0.000	580.600	9.000	578.600	15.000	576.600	19.000	574.600	21.000
43	GR	574.100	100.000	573.600	335.000	0.000	0.000	0.000	0.000	0.000	0.000
44	EJ	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
45											
46											
47											
48											
49											
50											
51											
52											
53											
54											
55											
56											
57											

```
**********************************************
HEC2 VERSION UPDATED JAN 1976
ERROR CORRECTIONS 01,02,03,04,05,06,07,08,09
MODIFICATIONS 52,53,54,55,56,57,58
**********************************************

T1       CITY OF GIBRALTER          5555-23-01      PM = RICHARD ZANOTTI
T2       100-YEAR FLOOD
T3       BROWNSTOWN CREEK

J1  ICHECK     INQ        NINV       IDIR       STRT       METRIC     HVINS      Q          WSEL       FQ
        -1.       4.         0.         0.  0.000000       0.00       0.0         0.    573.100    0.000
J2  NPROF      IPLOT      PRFVS      XSECV      XSECH      FN         ALLDC      IBW        CHNIM      ITRACE
       3.000      0.000     -1.000      0.000      0.000      0.000      0.000      0.000      0.000      0.000
```

8-17-77 Run follows this run extension of Brownstown Cr.

CCHV= .300 CEHV= .500

3265 DIVIDED FLOW

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

3470 ENCROACHMENT STATIONS= 920.0 1212.0 TYPE= 1 TARGET= 292.000

500' D/S FROM D/S FACE OF S. GIBRALTAR RD BRIDGE SEC. A

1613.00	8.10	573.10	0.00	573.10	573.15	.05	0.00	0.00	573.10
1345.	417.	928.	0.	518.	469.	0.	0.	0.	100000.00
0.00	.80	1.98	0.00	.050	.030	.040	0.000	565.00	920.00
.000162	0.	0.	0.	0	0	1	0.00	287.24	1211.32

3265 DIVIDED FLOW

3470 ENCROACHMENT STATIONS= 920.0 1212.0 TYPE= 1 TARGET= 292.000

1783.00	8.50	573.13	0.00	0.00	573.17	.04	.02	.00	572.73
1345.	447.	898.	0.	600.	501.	0.	4.	1.	100000.00
.03	.74	1.79	0.00	.050	.030	.040	.032	564.63	920.00
.000123	130.	170.	200.	0	0	1	0.00	287.70	1211.46

3265 DIVIDED FLOW

3470 ENCROACHMENT STATIONS= 920.0 1212.0 TYPE= 1 TARGET= 292.000

1953.00	8.90	573.16	0.00	0.00	573.19	.03	.02	.00	572.36
1345.	473.	872.	0.	681.	533.	0.	7.	2.	100000.00
.06	.69	1.63	0.00	.050	.030	.040	.032	564.26	920.00
.000094	130.	170.	200.	0	0	1	0.00	288.15	1211.60

1490 NH CARD USED

3470 ENCROACHMENT STATIONS= 300.0 594.5 TYPE= 1 TARGET= 294.500

2113.00	9.28	573.18	0.00	0.00	573.20	.03	.01	.00	571.10
1345.	247.	1098.	0.	464.	746.	0.	12.	3.	99997.40
.10	.53	1.47	0.00	.050	.041	.040	.032	563.90	300.00
.000103	130.	160.	200.	0	0	1	0.00	294.50	594.50

1490 NH CARD USED

3470 ENCROACHMENT STATIONS= 300.0 594.5 TYPE= 1 TARGET= 294.500

D/S FACE OF S. GIBRALTAR RD BRIDGE, BS #1 SEC. B

CONCRETE BOX CULVERT BRIDGE, WITH HEADWALLS, WINGWALLS AND

SOLID CO CRETE RAILING, LENGTH=17', SPAN=24.5'

2114.00	9.27	573.17	0.00	0.00	573.21	.03	.00	.00	571.10
1345.	216.	1129.	0.	464.	746.	0.	12.	3.	100000.00
.10	.46	1.51	0.00	.035	.024	.040	.032	563.90	300.00
.000038	1.	1.	1.	0	0	1	0.00	294.50	594.50

1490 NH CARD USED

SPECIAL BRIDGE

SB	XK	XKOR	COFQ	RDLEN	BWC	BWP	BAREA	SS	ELCHU	ELCHD
	0.00	1.43	3.02	0.00	19.27	0.00	183.10	0.00	563.90	563.90

3265 DIVIDED FLOW

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

PRESSURE AND WEIR FLOW

EGPRS	EGLWC	H3	QWEIR	QPR	BAREA	ELLC	ELTRD	CLASS
574.37	573.25	0.00	17.	1322.	183.	573.20	574.20	30.00

3470 ENCROACHMENT STATIONS= 500.0 824.5 TYPE= 1 TARGET= 324.500

2131.00	10.38	574.28	0.00	0.00	574.33	.05	1.13	0.00	574.50
1345.	1.	1344.	0.	10.	755.	0.	12.	3.	100000.00
.10	.06	1.78	0.00	.035	.024	.040	.032	563.90	500.00
.000066	17.	17.	17.	2	0	3	0.00	251.38	824.50

1490 NH CARD USED

3265 DIVIDED FLOW

3470 ENCROACHMENT STATIONS= 500.0 824.5 TYPE= 1 TARGET= 324.500

2132.00	10.38	574.28	0.00	0.00	574.33	.05	.00	.00	574.50
1345.	1.	1344.	0.	10.	755.	0.	12.	3.	100000.00
.10	.08	1.78	0.00	.045	.038	.040	.032	563.90	500.00
.000170	1.	1.	1.	0	0	1	0.00	251.40	824.50

3470 ENCROACHMENT STATIONS= 360.0 700.0 TYPE= 1 TARGET= 340.000

50' U/S FROM U/S FACE OF S. GIBRALTAR RD, VS #2 SEC. C

2182.00	7.83	574.33	0.00	0.00	574.35	.02	.00	.01	573.70
1345.	15.	1330.	0.	89.	1188.	0.	13.	3.	100000.00
.11	.17	1.12	0.00	.045	.030	.045	.032	566.50	360.00
.000049	50.	50.	50.	2	0	1	0.00	340.00	700.00

3280 CROSS SECTION 2632.00 EXTENDED .74 FEET

3470 ENCROACHMENT STATIONS= 240.0 450.0 TYPE= 1 TARGET= 210.000

500' U/S FROM U/S FACE OF S. GIBRALTAR RD, VS #3 SEC. D

2632.00	8.54	574.34	0.00	0.00	574.42	.08	.04	.03	574.10
1345.	2.	1287.	57.	10.	543.	85.	23.	6.	572.40
.17	.15	2.37	.67	.045	.030	.045	.031	565.80	240.00
.000232	550.	450.	250.	2	0	1	0.00	210.00	450.00

574.37
1.03
575.7

3470 ENCROACHMENT STATIONS= 175.0 235.0 TYPE= 1 TARGET= 60.000

50' D/S OF JEFFERSON AVE BRIDGE, VS #4 SEC. E

2932.00	7.59	574.39	0.00	0.00	574.55	.16	.09	.04	100000.00
1345.	0.	1345.	0.	0.	420.	0.	27.	7.	100000.00
.19	0.00	3.20	0.00	.045	.030	.045	.031	566.80	175.00
.000399	300.	300.	300.	0	0	1	0.00	60.00	235.00

3470 ENCROACHMENT STATIONS= 497.0 598.5 TYPE= 1 TARGET= 143.000

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 575.00 ELREA= 575.00

2982.00	7.18	574.18	0.00	0.00	574.83	.66	.04	.25	569.00
1345.	0.	1345.	0.	0.	207.	0.	27.	7.	100000.00
.19	0.00	6.50	0.00	.045	.030	.045	.031	567.00	568.00
.002006	50.	50.	50.	2	0	1	0.00	30.53	598.53

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

3470 ENCROACHMENT STATIONS= 497.0 598.5 TYPE= 1 TARGET= 143.000

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 575.00 ELREA= 575.00

D/S FACE OF JEFFERSON AVE BRIDGE, BS #5 SEC. F

CONCRETE BRIDGE WITH CONCRETE STRINGERS, CONCRETE RAILING

LENGTH=66', SPAN=43', SKEW=0.71

2983.00	7.18	574.18	0.00	0.00	574.83	.66	.00	.00	569.00
1345.	0.	1345.	0.	0.	207.	0.	27.	7.	100000.00
.19	0.00	6.50	0.00	.018	.015	.018	.031	567.00	568.00
.000501	1.	1.	1.	0	0	1	0.00	30.53	598.53

SPECIAL BRIDGE

SB	XK	XKOR	COEQ	RDLEN	BWC	BWP	BAREA	SS	ELCHU	ELCHD
	0.00	1.61	3.00	0.00	28.74	0.00	195.40	0.00	567.00	567.00

PRESSURE FLOW

EGPRS	EGLWC	H3	QWEIR	QPR	BAREA	ELLC	ELTRD	CLASS
575.36	574.83	0.00	0.	1345.	195.	573.80	577.60	10.00

3470 ENCROACHMENT STATIONS= 497.0 598.5 TYPE= 1 TARGET= 143.000

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 577.60 ELREA= 577.60

3049.00	7.82	574.82	0.00	0.00	575.36	.55	.53	0.00	569.00
1345.	0.	1345.	0.	0.	227.	0.	27.	7.	100000.00
.20	0.00	5.93	0.00	.018	.015	.018	.030	567.00	568.00
.000385	66.	66.	66.	2	0	1	0.00	30.53	598.53

3470 ENCROACHMENT STATIONS= 497.0 598.5 TYPE= 1 TARGET= 143.000

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 577.60 ELREA= 577.60

3050.00	7.82	574.82	0.00	0.00	575.36	.55	.00	.00	569.00
1345.	0.	1345.	0.	0.	227.	0.	27.	7.	100000.00
.20	0.00	5.93	0.00	.045	.030	.045	.030	567.00	568.00
.001541	1.	1.	1.	0	0	1	0.00	30.53	598.53

3301 HV CHANGED MORE THAN HVINS

3470 ENCROACHMENT STATIONS= 52.0 400.0 TYPE= 1 TARGET= 348.000

200' U/S FROM U/S FACE OF JEFFERSON AVE., VS #1A SEC. G

3250.00	8.03	575.53	0.00	0.00	575.54	.01	.02	.16	575.70
1345.	0.	1329.	16.	0.	1515.	73.	32.	8.	573.40
.26	0.00	.88	.22	.045	.030	.045	.030	567.50	70.79
.000031	100.	200.	300.	2	0	1	0.00	329.21	400.00

3470 ENCROACHMENT STATIONS= 400.0 1050.0 TYPE= 1 TARGET= 650.000

700' U/S FROM U/S FACE OF JEFFERSON AVE., VS #2A SEC. H

3750.00	7.75	575.55	0.00	0.00	575.56	.01	.01	.00	574.30
1345.	3.	1128.	214.	29.	1616.	705.	54.	13.	572.40
.48	.11	.70	.30	.045	.030	.045	.030	567.80	453.67
.000021	550.	500.	450.	2	0	1	0.00	596.33	1050.00

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

3470 ENCROACHMENT STATIONS= 515.0 1300.0 TYPE= 1 TARGET= 785.000

4225.00	7.76	575.56	0.00	0.00	575.57	.01	.01	.00	572.60
1345.	68.	981.	296.	284.	1335.	1012.	78.	20.	571.60
.68	.24	.73	.29	.045	.030	.045	.030	567.80	515.00
.000019	550.	475.	300.	0	0	1	0.00	785.00	1300.00

3470 ENCROACHMENT STATIONS= 300.0 1200.0 TYPE= 1 TARGET= 900.000

1650' U/S FROM U/S FACE OF JEFFERSON AVE, VS #3A SEC. I

4700.00	7.77	575.57	0.00	0.00	575.58	.01	.01	.00	572.30
1345.	473.	664.	208.	1266.	702.	616.	104.	28.	572.30
.87	.37	.95	.34	.045	.030	.045	.030	567.80	300.00
.000036	550.	475.	300.	0	0	1	0.00	900.00	1200.00

3265 DIVIDED FLOW

3280 CROSS SECTION 5750.00 EXTENDED .02 FEET

3470 ENCROACHMENT STATIONS= 450.0 1250.0 TYPE= 1 TARGET= 800.000

2700' U/S FROM U/S FACE OF JEFFERSON AVE, VS #4A SEC. J

5750.00	7.02	575.62	0.00	0.00	575.65	.03	.06	.01	573.90
1345.	79.	700.	566.	176.	385.	802.	140.	41.	572.70
1.07	.45	1.82	.71	.045	.030	.045	.031	568.60	450.00
.000144	300.	1050.	1100.	2	0	1	0.00	606.29	1250.00

3470 ENCROACHMENT STATIONS= 650.0 1050.0 TYPE= 1 TARGET= 400.000

500' D/S FROM D/S FACE OF M. GIBRALTAR RD BRIDGE SEC. K

6750.00	7.16	575.76	0.00	0.00	575.84	.08	.17	.02	573.40
1345.	331.	819.	195.	372.	294.	215.	159.	48.	573.20
1.19	.89	2.78	.91	.045	.030	.045	.032	568.60	650.00
.000311	600.	1000.	600.	2	0	1	0.00	371.55	1021.55

3470 ENCROACHMENT STATIONS= 665.0 782.0 TYPE= 1 TARGET= 117.000

50' D/S FROM D/S FACE OF M. GIBRALTAR RD BRIDGE, VS #5A SEC. L

7200.00	7.68	575.88	0.00	0.00	576.22	.35	.25	.13	573.50
1770.	167.	1414.	189.	85.	272.	93.	165.	50.	573.40
1.21	1.96	5.19	2.04	.045	.030	.045	.032	568.20	665.00
.001081	400.	450.	400.	2	0	1	0.00	117.00	782.00

7250.00	6.31	575.91	0.00	0.00	576.34	.42	.07	.04	580.10
1770.	0.	1770.	0.	0.	339.	0.	166.	51.	579.70
1.22	0.00	5.22	0.00	.045	.030	.045	.032	569.60	993.72
.002156	50.	50.	50.	0	0	1	0.00	96.35	1090.07

3265 DIVIDED FLOW

NORMAL BRIDGE, NRD=13 MIN ELTRD= 578.00 MAX ELLC= 580.10

D/S FACE OF GIBRALTAR RD BRIDGE, RS #6 SEC. M

CONCRETE BRIDGE, 2 CONCRETE PIERS, HEADWALLS

LENGTH= 47FT.

7251.00	6.27	575.87	0.00	0.00	576.39	.52	.00	.05	580.10
1770.	0.	1770.	0.	0.	306.	0.	166.	51.	579.70
1.22	0.00	5.79	0.00	.018	.018	.018	.032	569.60	997.60
.001220	1.	1.	1.	2	0	1	0.00	84.03	1089.93

3265 DIVIDED FLOW

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

NORMAL BRIDGE,NRD=13 MIN ELTRD= 578.00 MAX ELLC= 580.10

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 580.10 ELREA= 579.70

7298.00	6.35	575.95	0.00	0.00	576.45	.50	.06	.01	580.10
1770.	0.	1770.	0.	0.	313.	0.	166.	51.	579.70
1.22	0.00	5.66	0.00	.018	.018	.018	.032	569.60	997.60
.001146	47.	47.	47.	0	0	1	0.00	84.20	1090.10

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 580.10 ELREA= 579.70

7299.00	6.50	576.10	0.00	0.00	576.48	.38	.00	.04	580.10
1770.	0.	1770.	0.	0.	358.	0.	166.	51.	579.70
1.22	0.00	4.95	0.00	.050	.030	.050	.032	569.60	993.28
.001823	1.	1.	1.	2	0	1	0.00	97.21	1090.49

3470 ENCROACHMENT STATIONS= 250.0 450.0 TYPE= 1 TARGET= 200.000

57' U/S FROM U/S FACE OF M. GIBRALTAR RD. BRIDGE, STA 6+00 SEC. N

7355.00	7.38	576.48	0.00	0.00	576.61	.13	.05	.07	572.50
1770.	418.	901.	451.	267.	237.	279.	167.	51.	572.50
1.22	1.57	3.80	1.62	.050	.030	.050	.032	569.10	250.00
.000560	56.	56.	56.	2	0	1	0.00	200.00	450.00

3280 CROSS SECTION 7805.00 EXTENDED .12 FEET

3470 ENCROACHMENT STATIONS= 500.0 1000.0 TYPE= 1 TARGET= 500.000

507' U/S FROM U/S FACE OF M. GIBRALTAR RD. BRIDGE, STA 10+50 SEC. O

7805.00	7.42	576.72	0.00	0.00	577.03	.31	.33	.09	575.80
1770.	108.	1551.	111.	133.	326.	126.	174.	54.	574.60
1.25	.81	4.76	.89	.050	.030	.050	.032	569.30	500.00
.001019	45.	450.	450.	2	0	1	0.00	500.0	1000.

3280 CROSS SECTION 8305.00 EXTENDED .78 FEET

3470 ENCROACHMENT STATIONS= 550.0 800.0 TYPE= 1 TARGET= 250.000

300' D/S FROM D/S FACE OF D.T.S.L. RR BRIDGE, STA 15+50 SEC. P

8305.00	7.08	577.38	0.00	0.00	577.69	.31	.66	.00	575.50
1770.	464.	1306.	0.	244.	259.	0.	180.	58.	578.60
1.29	1.90	5.05	0.00	.050	.030	.050	.032	570.30	550.00
.001757	500.	500.	500.	2	0	1	0.00	195.00	745.00

OVERBANK AREA ASSUMED NON-EFFECTIVE, ELLEA= 582.50 ELREA= 582.50

8605.00	6.78	577.78	0.00	0.00	578.29	.51	.50	.10	582.50
1770.	0.	1770.	0.	0.	308.	0.	183.	59.	582.50
1.30	0.00	5.75	0.00	.050	.030	.050	.032	571.00	582.00
.001561	300.	300.	300.	2	0	1	0.00	48.00	630.00

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

OVERBANK AREA ASSUMED NON-EFFECTIVE, ELLEA= 582.50 ELREA= 582.50

D/S FACE OF D.T.S.L. RR BRIDGE, STA 18+50 SEC. Q

CONCRETE BRIDGE WITH 3 PIERS, 2' WIDE FOR EACH PIER

TOTAL SPAN=48.5 FT, LENGTH=52 FT.

8606.00	6.78	577.78	0.00	0.00	578.29	.51	.00	.00	582.50
1770.	0.	1770.	0.	0.	308.	0.	183.	59.	582.50
1.30	0.00	5.75	0.00	.020	.015	.020	.032	571.00	582.00
.000390	1.	1.	1.	0	0	1	0.00	48.00	630.00

SPECIAL BRIDGE

SB	XK	XKOR	COFQ	RDLEN	BWC	BWP	BAREA	SS	ELCHU	ELCHD
	1.15	1.53	3.00	0.00	48.00	6.00	274.50	0.00	571.00	571.00

PRESSURE FLOW

EGPRS	EGLWC	H3	QWEIR	QPR	BAREA	ELLC	ELTRD	CLASS
578.76	578.46	.20	0.	1770.	275.	577.90	581.60	10.00

OVERBANK AREA ASSUMED NON-EFFECTIVE, ELLEA= 582.50 ELREA= 582.50

8658.00	7.33	578.33	0.00	0.00	578.76	.44	.47	0.00	582.50
1770.	0.	1770.	0.	0.	334.	0.	183.	59.	582.50
1.30	0.00	5.29	0.00	.020	.015	.020	.031	571.00	582.00
.000303	52.	52.	52.	2	0	1	0.00	48.00	630.00

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 582.50 ELREA= 582.50

8659.00	7.33	578.33	0.00	0.00	578.76	.44	.00	.00	582.50
1770.	0.	1770.	0.	0.	334.	0.	183.	59.	582.50
1.30	0.00	5.29	0.00	.050	.032	.045	.031	571.00	582.00
.001379	1.	1.	1.	0	0	1	0.00	48.00	630.00

3280 CROSS SECTION 8816.00 EXTENDED .39 FEET

3470 ENCROACHMENT STATIONS= 235.0 425.0 TYPE= 1 TARGET= 190.000

158' U/S FROM U/S FACE OF D.T.S.L. RR BRIDGE, STA 20+60 SEC. R

8816.00	8.89	578.79	0.00	0.00	578.97	.19	.14	.07	574.20
1770.	279.	1059.	433.	168.	251.	217.	185.	60.	574.30
1.32	1.66	4.21	2.00	.050	.032	.045	.031	569.90	241.22
.00590	157.	157.	157.	2	0	1	0.00	153.65	394.87

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 583.60 ELREA= 583.60

9106.00	7.45	578.95	0.00	0.00	579.17	.22	.18	.02	583.60
1520.	0.	1520.	0.	0.	405.	0.	188.	60.	583.60
1.34	0.00	3.75	0.00	.050	.032	.045	.031	571.50	441.00
.00648	290.	290.	290.	2	0	1	0.00	59.00	500.00

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

NORMAL BRIDGE,NRD=19 MIN ELTRD= 583.60 MAX ELLC= 580.10

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 583.60 ELREA= 583.60

D/S FACE OF PENN CENTRAL RR BRIDGE #1, STA 23+50 SEC. S

CONCRETE BRIDGE, WITH 2 PIERS, WINGWALLS & HEADWALLS

TOTAL SPAN=59.5 FT, LENGTH=20 FT.

9107.00	7.42	578.92	0.00	0.00	579.20	.27	.00	.03	583.60
1520.	0.	1520.	0.	0.	362.	0.	188.	60.	583.60
1.34	0.00	4.20	0.00	.020	.018	.020	.031	571.50	441.00
.000299	1.	1.	1.	2	0	1	-41.84	59.00	500.00

NORMAL BRIDGE,NRD=19 MIN ELTRD= 583.60 MAX ELLC= 580.10

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 583.60 ELREA= 583.60

9127.00	7.43	578.93	0.00	0.00	579.20	.27	.01	.00	583.60
1520.	0.	1520.	0.	0.	362.	0.	189.	60.	583.60
1.34	0.00	4.20	0.00	.020	.018	.020	.031	571.50	441.00
.000298	20.	20.	20.	0	0	1	-41.90	59.00	500.00

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 583.60 ELREA= 583.60

9128.00	7.51	579.01	0.00	0.00	579.22	.21	.00	.02	583.60
1520.	0.	1520.	0.	0.	409.	0.	189.	60.	583.60
1.34	0.00	3.72	0.00	.050	.035	.045	.031	571.50	441.00
.000756	1.	1.	1.	2	0	1	0.00	59.00	500.00

3470 ENCROACHMENT STATIONS= 536.0 868.0 TYPE= 1 TARGET= 332.000

135' U/S FROM U/S FACE OF PENN CENTRAL RR BRIDGE #1, STA 25+00SEC. T

9264.00	7.76	579.26	0.00	0.00	579.34	.07	.08	.04	576.30
1520.	349.	775.	396.	313.	271.	330.	191.	61.	576.90
1.36	1.12	2.86	1.20	.050	.035	.045	.031	571.50	536.00
.000433	136.	136.	136.	2	0	1	0.00	332.00	868.00

3470 ENCROACHMENT STATIONS= 150.0 700.0 TYPE= 1 TARGET= 550.000

635' U/S FROM U/S FACE OF PENN CENTRAL RR BRIDGE #1, STA 30+00SEC. U

9764.00	7.95	579.45	0.00	0.00	579.47	.02	.11	.02	576.50
1465.	443.	376.	646.	623.	231.	836.	206.	66.	576.50
1.50	.71	1.63	.77	.050	.035	.045	.032	571.50	150.00
.000138	500.	500.	500.	2	0	1	0.00	550.00	700.00

3280 CROSS SECTION 10264.00 EXTENDED 1.42 FEET

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

3470 ENCROACHMENT STATIONS= 510.0 1230.0 TYPE= 1 TARGET= 720.000

1135' U/S FROM U/S FACE OF PENN CENTRAL RR BRIDGE 1, STA 35+00SEC. V

10264.00	8.42	579.52	0.00	0.00	579.54	.02	.07	.00	576.60
1465.	255.	430.	779.	349.	228.	1193.	225.	73.	576.60
1.64	.73	1.89	.65	.045	.030	.045	.032	571.10	529.44
.000131	500.	500.	500.	2	0	1	0.00	700.56	1230.00

3470 ENCROACHMENT STATIONS= 415.0 980.0 TYPE= 1 TARGET= 565.000

950' D/S FROM D/S FACE OF PENN CENTRAL RR BRIDGE #2, STA 40+00SEC. W

10764.00	7.30	579.60	0.00	0.00	579.63	.03	.09	.01	576.90
1465.	275.	437.	753.	313.	183.	865.	243.	81.	576.80
1.74	.88	2.38	.87	.045	.030	.045	.031	572.30	415.00
.000233	500.	500.	500.	1	0	1	0.00	565.00	980.00

3280 CROSS SECTION 11264.00 EXTENDED .39 FEET

3470 ENCROACHMENT STATIONS= 550.0 900.0 TYPE= 1 TARGET= 350.000

450' D/S FROM D/S FACE OF PENN CENTRAL RR BRIDGE #2, STA 45+00SEC. X

11264.00	8.80	579.70	0.00	0.00	579.81	.10	.14	.03	577.60
1100.	194.	729.	176.	219.	233.	235.	255.	86.	578.40
1.80	.89	3.13	.75	.045	.030	.045	.031	570.90	550.00
.000366	500.	500.	500.	1	0	1	0.00	350.00	900.00

3280 CROSS SECTION 11364.00 EXTENDED 1.12 FEET

3470 ENCROACHMENT STATIONS= 595.0 900.0 TYPE= 1 TARGET= 305.000

350' D/S FROM D/S FACE OF PENN CENTRAL RR BRIDGE #2, STA 46+00SEC. Y

11364.00	8.92	579.82	0.00	0.00	579.85	.02	.02	.02	576.60
1100.	143.	575.	382.	219.	364.	548.	257.	87.	576.60
1.82	.65	1.58	.70	.045	.030	.045	.031	570.90	595.00
.000094	100.	100.	100.	2	0	1	0.00	305.00	900.00

3470 ENCROACHMENT STATIONS= 390.0 550.0 TYPE= 1 TARGET= 160.000

70' D/S FROM D/S FACE OF PENN CENTRAL RR BRIDGE #2, STA 48+80 SEC. Z

11644.00	5.45	579.85	0.00	0.00	579.90	.05	.04	.02	576.50
1100.	81.	969.	50.	83.	496.	47.	263.	88.	576.60
1.87	.97	1.95	1.06	.045	.030	.045	.031	574.40	390.00
.000223	280.	280.	280.	2	0	1	0.00	160.00	550.00

3301 HV CHANGED MORE THAN HVINS

11714.00	6.41	579.61	0.00	0.00	580.21	.60	.04	.27	582.90
1100.	0.	1100.	0.	0.	177.	0.	264.	88.	582.90
1.87	0.00	6.21	0.00	.045	.030	.045	.031	573.20	310.00
.002157	70.	70.	70.	2	0	1	0.00	28.00	338.00

Marsh Creek (Blakely Drain)

D/S FACE OF PENN CENTRAL RR BRIDGE #2, STA 49+50 SEC. AA

CONCRETE BRIDGE WITH WINGWALLS & HEADWALLS, WINGWALLS PARALLEL

LENGTH=14 FT, SPAN=28.5 FT.

11715.00	6.41	579.61	0.00	0.00	580.21	.60	.00	.00	582.90
110	0	1100	0	0	177	0	264	88	582.90

1.87	0.00	6.21	0.00	.018	.018	.018	.031	573.20	310.00
.000776	1.	1.	1.	0	0	1	0.00	28.00	338.00

SPECIAL BRIDGE

SB	XK	XKOR	COFQ	RDLEN	BWC	BWP	BAREA	SS	ELCHU	ELCHD
	0.00	1.75	3.00	0.00	28.50	0.00	140.50	0.00	573.20	573.20

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

PRESSURE FLOW

EGPRS	EGLWC	H3	QWEIR	QPR	BAREA	ELLC	ELTRD	CLASS
581.28	580.21	0.00	0.	1100.	141.	578.20	582.90	10.00

11729.00	7.66	580.86	0.00	0.00	581.28	.42	1.07	0.00	582.90
1100.	0.	1100.	0.	0.	212.	0.	264.	88.	582.90
1.87	0.00	5.19	0.00	.018	.018	.018	.031	573.20	310.00
.000461	14.	14.	14.	2	0	1	0.00	28.00	338.00
11730.00	7.66	580.86	0.00	0.00	581.28	.42	.00	.00	582.90
1100.	0.	1100.	0.	0.	212.	0.	264.	88.	582.90
1.87	0.00	5.19	0.00	.050	.035	.045	.031	573.20	310.00
.001744	1.	1.	1.	0	0	1	0.00	28.00	338.00

3470 ENCROACHMENT STATIONS= 585.0 683.0 TYPE= 1 TARGET= 98.000

35' U/S FROM U/S FACE OF PENN CENTRAL RR BRIDGE #2, STA 50+00 SEC. AB

11765.00	9.51	581.21	0.00	0.00	581.38	.17	.03	.07	578.10
1210.	95.	1115.	0.	70.	325.	0.	264.	88.	582.00
1.87	1.36	3.43	0.00	.050	.035	.045	.031	571.70	585.00
.000527	35.	35.	35.	2	0	1	0.00	69.12	654.12

3470 ENCROACHMENT STATIONS= 350.0 670.0 TYPE= 1 TARGET= 320.000

12005.00	9.52	581.62	0.00	0.00	581.70	.08	.29	.03	579.50
1210.	232.	223.	755.	109.	234.	296.	267.	89.	577.90
1.90	2.12	.95	2.55	.055	.400	.070	.040	572.10	350.00
.005423	240.	240.	240.	2	0	1	0.00	320.00	670.00

3280 CROSS SECTION 12365.00 EXTENDED 1.08 FEET

3470 ENCROACHMENT STATIONS= 450.0 780.0 TYPE= 1 TARGET= 330.000

635' U/S FROM U/S FACE OF PENN CENTRAL RR BRIDGE #2, VS#5, SEC. AC

12365.00	10.09	582.79	0.00	0.00	582.83	.04	1.11	.01	580.10
1210.	150.	153.	907.	70.	253.	556.	273.	92.	578.50
1.97	2.13	.61	1.63	.055	.400	.070	.060	572.70	450.00

.001997	360.	360.	360.	1	0	1	0.00	330.00	780.00

3280 CROSS SECTION 12440.00 EXTENDED 1.05 FEET

3470 ENCROACHMENT STATIONS= 480.0 835.0 TYPE= 1 TARGET= 355.000

12440.00	10.05	582.95	0.00	0.00	582.99	.04	.16	.00	580.30
1210.	0.	158.	1052.	0.	252.	620.	275.	93.	578.70
1.98	0.00	.63	1.70	.055	.400	.070	.055	572.90	480.00
.002353	75.	75.	75.	2	0	1	0.00	355.00	835.00

3280 CROSS SECTION 12441.00 EXTENDED 1.05 FEET

3470 ENCROACHMENT STATIONS= 480.0 835.0 TYPE= 1 TARGET= 355.000

D/S FACE OF FORT STREET BRIDGE, BS#4 SEC. AD

CONCRETE BRIDGE, HEADWALL PARALLEL TO EMBANKMENT

LENGTH = 48 FT, SPAN = 35 FT.

12441.00	10.05	582.95	0.00	0.00	583.00	.05	.00	.00	580.30
1210.	0.	590.	620.	0.	252.	621.	275.	93.	578.70
1.98	0.00	2.34	1.00	.020	.018	.020	.055	572.90	480.00
.000067	1.	1.	1.	0	0	1	0.00	355.00	835.00

SPECIAL BRIDGE

SB	XK	XKOR	COFQ	RDLEN	BWC	BWP	BAREA	SS	ELCHU	ELCHD
	0.00	1.68	3.04	0.00	27.65	0.00	179.75	0.00	572.90	572.90

3265 DIVIDED FLOW

3280 CROSS SECTION 12489.00 EXTENDED .31 FEET

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

PRESSURE AND WEIR FLOW

EGPRS	EGLWC	H3	QWEIR	QPR	BAREA	ELLC	ELTRD	CLASS
584.13	583.00	0.00	441.	780.	180.	579.40	582.50	30.00

3470 ENCROACHMENT STATIONS= 700.0 1030.0 TYPE= 1 TARGET= 330.000

12489.00	10.41	583.31	0.00	0.00	583.44	.13	.44	0.00	577.50
1210.	0.	1007.	203.	0.	316.	209.	275.	93.	573.90
1.99	0.00	3.18	.97	.020	.018	.020	.055	572.90	700.00
.000099	48.	48.	48.	2	0	3	0.00	314.07	1030.00

3265 DIVIDED FLOW

3280 CROSS SECTION 12490.00 EXTENDED .31 FEET

3470 ENCROACHMENT STATIONS=			700.0	1030.0	TYPE=	1	TARGET=	330.000	
12490.00	10.40	583.30	0.00	0.00	583.45	.15	.00	.01	577.50
1210.	0.	1046.	164.	0.	316.	209.	275.	93.	573.90
1.99	0.00	3.31	.79	.065	.035	.050	.055	572.90	700.00
.000402	1.	1.	1.	0	0	1	0.00	314.08	1030.00

START TRIB COMP
-8816.000 8816.000 57878.793 578.788
3280 CROSS SECTION -8816.00 EXTENDED .39 FEET

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

3470 ENCROACHMENT STATIONS= 235.0 425.0 TYPE= 1 TARGET= 190.000

SEC. R AS STARTING SECTION OF "TRIBUTARY"

-8816.00	8.89	578.79	0.00	0.00	578.97	.19	.08	0.00	574.20
1770.	279.	1059.	432.	168.	251.	217.	277.	94.	574.30
2.00	1.66	4.21	2.00	.050	.032	.045	.055	569.90	241.22
.000591	157.	157.	157.	0	0	1	0.00	153.62	394.85

7185 MIN SPECIFIC ENERGY

3720 ASSUMED CRITICAL DEPTH

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

730' EAST OF SEC. R, BETWEEN PENN CENCTAR @ D.T.S.L. RR SEC. BB

9546.00	1.66	579.26	579.26	0.00	579.63	.37	.54	0.00	579.60
255.	0.	255.	0.	0.	52.	0.	283.	96.	582.90
2.04	0.00	4.89	0.00	.040	.040	.040	.054	577.60	10.30
.027463	730.	730.	730.	0	25	1	0.00	73.16	83.46

3280 CROSS SECTION 10246.00 EXTENDED 1.28 FEET

1430' E. OF SEC. R, BETWEEN PENN CENTRAL @ D.T.S.L. RR SEC. CC

10246.00	5.28	579.88	0.00	0.00	579.88	.01	.15	.11	578.60
255.	0.	255.	0.	0.	370.	0.	287.	97.	582.60
2.32	0.00	.69	0.00	.040	.040	.040	.053	574.60	0.00
.000058	700.	700.	700.	4	0	1	0.00	94.57	94.57

3280 CROSS SECTION 10846.00 EXTENDED 1.31 FEET

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

2030' E. OF SEC. R, BETWEEN PENN CENTRAL @ D.T.S.L. RR SEC. DD

10846.00	5.31	579.91	0.00	0.00	579.91	.01	.03	.00	578.60	
255.	0.	255.	0.	0.	408.	0.	292.	98.	582.40	
2.59	0.00	.62	0.00	.040	.040	.040	.052	574.60	0.00	
.000043	600.	600.	600.	3	0	1	0.00	95.58	95.58	

3030' E. OF SEC. R, BETWEEN PENN CENTRAL @ D.T.S.L. RR SEC. EE

11846.00	7.34	579.94	0.00	0.00	579.94	.00	.03	.00	580.60
255.	0.	255.	0.	0.	497.	0.	302.	100.	580.60
3.13	0.00	.51	0.00	.040	.040	.040	.051	572.60	8.64
.000019	1000.	1000.	1000.	2	0	1	0.00	85.37	94.02

START TRIB COMP
-9264.000 9264.000 57926.473 579.265

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

3470 ENCROACHMENT STATIONS= 536.0 868.0 TYPE= 1 TARGET= 332.000

SEC. I AS STARTING SECTION OF "TRIBUTARY"

-9264.00	7.76	579.26	0.00	0.00	579.34	.08	0.00	0.00	576.30
1520.	349.	775.	396.	313.	271.	330.	302.	100.	576.90
3.13	1.12	2.86	1.20	.050	.035	.045	.051	571.50	536.00
.000433	0.	0.	0.	0	0	1	0.00	332.00	868.00

3685 20 TRIALS USED WSEL,CWSEL

7185 MIN SPECIFIC ENERGY

3720 ASSUMED CRITICAL DEPTH

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

330' EAST OF SEC. T, EXACT NORTH OF PENN CENTRAL RR SEC. FF

9594.00	1.34	580.84	580.84	0.00	581.17	.34	.18	0.00	582.90
220.	0.	220.	0.	0.	47.	0.	306.	102.	581.60
3.15	0.00	4.65	0.00	.040	.040	.040	.051	579.50	27.29
.027729	330.	330.	330.	30	25	1	0.00	72.66	99.95

3280 CROSS SECTION 10294.00 EXTENDED 1.82 FEET

1030' E. OF SEC. T, EXACT N. OF PENN CENTRAL RR SEC. GG

10294.00	2.82	581.42	0.00	0.00	581.42	.00	.15	.10	582.90
220.	0.	220.	0.	0.	439.	0.	310.	104.	579.60
3.54	0.00	.50	.00	.040	.040	.040	.051	578.60	13.95
.000060	700.	700.	700.	5	0	1	0.00	191.06	205.00

3280 CROSS SECTION 10894.00 EXTENDED 1.83 FEET

1630' E. OF SEC. T, EXACT N. OF PENN CENTRAL RR SEC. HH

10894.00	7.33	581.43	0.00	0.00	581.43	.00	.00	.00	582.40
220.	0.	220.	0.	0.	1267.	0.	322.	107.	579.60
4.50	0.00	.17	.00	.040	.040	.040	.050	574.10	8.11
.000002	600.	600.	600.	2	0	1	0.00	346.89	355.00

3280 CROSS SECTION 11894.00 EXTENDED 7.83 FEET

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST
2630' E. OF SEC. T, EXACT N. OF PENN CENTRAL RR							SEC. II		
11894.00	7.83	581.43	0.00	0.00	581.43	.00	.00	.00	582.60
220.	0.	220.	0.	0.	2380.	0.	364.	114.	573.60
7.50	0.00	.09	.00	.040	.040	.040	.049	573.60	5.26
.000000	1000.	1000.	1000.	2	0	1	0.00	329.74	335.00

00BREAK00

1) COUNTY: Wayne

2) STUDY NAME: City of Gibralter

3) WATERCOURSE: Brownstown Creek

4) DOCUMENT TYPE: Summary

00BREAK00

SUMMARY PRINTOUT FOR MULTIPLE PROFILES

BROWNSTOWN CREEK

SECTION NUMBER	CHANNEL LENGTH	MIN EL OF ROADWAY	MAX EL OF LOW CHORD	MIN EL GROUND	DISCHARGE (CFS)	CWSEL	HV	HL	OLOSS	QCH	DEPTH	TOPWID
1613.00	0.00	0.00	0.00	565.00	1080.00	573.10	.03	0.00	0.00	745.40	8.10	287.24
1613.00	0.00	0.00	0.00	565.00	1290.00	573.10	.04	0.00	0.00	890.33	8.10	287.24
1613.00	0.00	0.00	0.00	565.00	1345.00	573.10	.05	0.00	0.00	928.29	8.10	287.24
1613.00	0.00	0.00	0.00	565.00	1460.00	573.10	.05	0.00	0.00	1007.66	8.10	287.24
1783.00	170.00	0.00	0.00	564.63	1080.00	573.12	.02	.01	.00	721.89	8.49	287.69
1783.00	170.00	0.00	0.00	564.63	1290.00	573.13	.03	.02	.00	861.74	8.50	287.70
1783.00	170.00	0.00	0.00	564.63	1345.00	573.13	.04	.02	.00	898.33	8.50	287.70
1783.00	170.00	0.00	0.00	564.63	1460.00	573.14	.04	.03	.00	974.76	8.51	287.70
1953.00	170.00	0.00	0.00	564.26	1080.00	573.14	.02	.01	.00	700.90	8.88	288.13
1953.00	170.00	0.00	0.00	564.26	1290.00	573.15	.03	.02	.00	836.33	8.89	288.15
1953.00	170.00	0.00	0.00	564.26	1345.00	573.16	.03	.02	.00	871.72	8.90	288.15
1953.00	170.00	0.00	0.00	564.26	1460.00	573.17	.03	.02	.00	945.63	8.91	288.16
2113.00	160.00	0.00	0.00	563.90	1080.00	572.98	.38	.02	.18	1080.00	9.08	24.50
2113.00	160.00	0.00	0.00	563.90	1290.00	573.17	.03	.01	.00	1053.71	9.27	294.50
2113.00	160.00	0.00	0.00	563.90	1345.00	573.18	.03	.01	.00	1098.07	9.28	294.50
2113.00	160.00	0.00	0.00	563.90	1460.00	573.19	.03	.02	.00	1190.62	9.29	294.50
2114.00	1.00	0.00	0.00	563.90	1080.00	572.98	.38	.00	.00	1080.00	9.08	24.50
2114.00	1.00	0.00	0.00	563.90	1290.00	573.17	.03	.00	.00	1083.74	9.27	294.50
2114.00	1.00	0.00	0.00	563.90	1345.00	573.17	.03	.00	.00	1129.44	9.27	294.50
2114.00	1.00	0.00	0.00	563.90	1460.00	573.19	.04	.00	.00	1224.79	9.29	294.50
2131.00	17.00	574.20	573.20	563.90	1080.00	573.28	.47	.39	0.00	1080.00	9.38	24.50
2131.00	17.00	574.20	573.20	563.90	1290.00	574.21	.05	1.05	0.00	1289.99	10.31	224.86
2131.00	17.00	574.20	573.20	563.90	1345.00	574.28	.05	1.13	0.00	1344.40	10.38	251.38
2131.00	17.00	574.20	573.20	563.90	1460.00	574.42	.06	1.25	0.00	1456.44	10.52	297.31
2132.00	1.00	0.00	0.00	563.90	1080.00	573.28	.47	.00	.00	1080.00	9.38	24.50
2132.00	1.00	0.00	0.00	563.90	1290.00	574.21	.05	.00	.00	1289.99	10.31	224.87
2132.00	1.00	0.00	0.00	563.90	1345.00	574.28	.05	.00	.00	1344.25	10.38	251.40
2132.00	1.00	0.00	0.00	563.90	1460.00	574.42	.06	.00	.00	1455.56	10.52	297.33
2182.00	50.00	0.00	0.00	566.50	1080.00	573.79	.09	.02	.11	1080.00	7.29	65.00
2182.00	50.00	0.00	0.00	566.50	1290.00	574.25	.02	.00	.01	1277.90	7.75	340.00
2182.00	50.00	0.00	0.00	566.50	1345.00	574.33	.02	.00	.01	1329.61	7.83	340.00
2182.00	50.00	0.00	0.00	566.50	1460.00	574.47	.02	.00	.01	1437.74	7.97	340.00
2632.00	450.00	0.00	0.00	565.80	1080.00	573.93	.07	.10	.01	1048.56	8.13	149.81
2632.00	450.00	0.00	0.00	565.80	1290.00	574.25	.08	.04	.03	1238.23	8.45	210.00
2632.00	450.00	0.00	0.00	565.80	1345.00	574.34	.08	.04	.03	1286.56	8.54	210.00
2632.00	450.00	0.00	0.00	565.80	1460.00	574.48	.09	.04	.04	1387.41	8.68	210.00
2932.00	300.00	0.00	0.00	566.80	1080.00	573.98	.11	.07	.02	1080.00	7.18	60.00
2932.00	300.00	0.00	0.00	566.80	1290.00	574.31	.15	.09	.03	1290.00	7.51	60.00
2932.00	300.00	0.00	0.00	566.80	1345.00	574.39	.16	.09	.04	1345.00	7.59	60.00
2932.00	300.00	0.00	0.00	566.80	1460.00	574.53	.18	.10	.04	1460.00	7.73	60.00

SECTION NUMBER	CHANNEL LENGTH	MIN EL OF ROADWAY	MAX EL OF LOW CHORD	MIN EL GROUND	DISCHARGE (CFS)	CWSEL	HV	HL	OLOSS	QCH	DEPTH	TOPWID
2982.00	50.00	0.00	0.00	567.00	1080.00	573.83	.47	.03	.18	1080.00	6.83	30.53
2982.00	50.00	0.00	0.00	567.00	1290.00	574.11	.62	.04	.23	1290.00	7.11	30.53
2982.00	50.00	0.00	0.00	567.00	1345.00	574.18	.66	.04	.25	1345.00	7.18	30.53
2982.00	50.00	0.00	0.00	567.00	1460.00	574.29	.75	.04	.28	1460.00	7.29	30.53
2983.00	1.00	0.00	0.00	567.00	1080.00	573.83	.47	.00	.00	1080.00	6.83	30.53
2983.00	1.00	0.00	0.00	567.00	1290.00	574.11	.61	.00	.00	1290.00	7.11	30.53
2983.00	1.00	0.00	0.00	567.00	1345.00	574.18	.66	.00	.00	1345.00	7.18	30.53
2983.00	1.00	0.00	0.00	567.00	1460.00	574.29	.75	.00	.00	1460.00	7.29	30.53
3049.00	66.00	577.60	573.80	567.00	1080.00	574.17	.42	.29	0.00	1080.00	7.17	30.53
3049.00	66.00	577.60	573.80	567.00	1290.00	574.68	.52	.47	0.00	1290.00	7.68	30.53
3049.00	66.00	577.60	573.80	567.00	1345.00	574.82	.55	.53	0.00	1345.00	7.82	30.53
3049.00	66.00	577.60	573.80	567.00	1460.00	575.09	.60	.65	0.00	1460.00	8.09	30.53
3050.00	1.00	0.00	0.00	567.00	1080.00	574.17	.42	.00	.00	1080.00	7.17	30.53
3050.00	1.00	0.00	0.00	567.00	1290.00	574.68	.52	.00	.00	1290.00	7.68	30.53
3050.00	1.00	0.00	0.00	567.00	1345.00	574.82	.55	.00	.00	1345.00	7.82	30.53
3050.00	1.00	0.00	0.00	567.00	1460.00	575.09	.60	.00	.00	1460.00	8.09	30.53
3250.00	200.00	0.00	0.00	567.50	1080.00	574.73	.01	.02	.12	1076.39	7.23	309.49
3250.00	200.00	0.00	0.00	567.50	1290.00	575.36	.01	.02	.15	1277.48	7.86	328.42
3250.00	200.00	0.00	0.00	567.50	1345.00	575.53	.01	.02	.16	1329.21	8.03	329.21
3250.00	200.00	0.00	0.00	567.50	1460.00	575.87	.01	.02	.18	1436.81	8.37	337.62
3750.00	500.00	0.00	0.00	567.80	1085.00	574.75	.01	.01	.00	949.32	6.95	566.52
3750.00	500.00	0.00	0.00	567.80	1290.00	575.38	.01	.01	.00	1090.58	7.58	590.05
3750.00	500.00	0.00	0.00	567.80	1345.00	575.55	.01	.01	.00	1127.55	7.75	596.33
3750.00	500.00	0.00	0.00	567.80	1460.00	575.89	.01	.01	.00	1204.62	8.09	608.84
4225.00	475.00	0.00	0.00	567.80	1085.00	574.76	.01	.01	.00	857.93	6.96	699.64
4225.00	475.00	0.00	0.00	567.80	1290.00	575.39	.01	.01	.00	956.31	7.59	764.46
4225.00	475.00	0.00	0.00	567.80	1345.00	575.56	.01	.01	.00	980.66	7.76	785.00
4225.00	475.00	0.00	0.00	567.80	1460.00	575.90	.01	.01	.00	1030.79	8.10	785.00
4700.00	475.00	0.00	0.00	567.80	1085.00	574.77	.01	.02	.00	643.23	6.97	900.00
4700.00	475.00	0.00	0.00	567.80	1290.00	575.40	.01	.01	.00	659.28	7.60	900.00
4700.00	475.00	0.00	0.00	567.80	1345.00	575.57	.01	.01	.00	664.42	7.77	900.00
4700.00	475.00	0.00	0.00	567.80	1460.00	575.91	.01	.01	.00	678.08	8.11	900.00
5750.00	1050.00	0.00	0.00	568.60	1085.00	574.85	.05	.09	.02	687.96	6.25	552.94
5750.00	1050.00	0.00	0.00	568.60	1290.00	575.45	.03	.06	.01	698.24	6.85	590.84
5750.00	1050.00	0.00	0.00	568.60	1345.00	575.62	.03	.06	.01	700.08	7.02	606.29
5750.00	1050.00	0.00	0.00	568.60	1460.00	575.95	.03	.05	.01	707.22	7.35	650.86
6750.00	1000.00	0.00	0.00	568.60	1085.00	575.08	.10	.26	.03	777.52	6.48	355.77
6750.00	1000.00	0.00	0.00	568.60	1290.00	575.61	.08	.18	.03	811.98	7.01	368.10
6750.00	1000.00	0.00	0.00	568.60	1345.00	575.76	.08	.17	.02	818.71	7.16	371.55
6750.00	1000.00	0.00	0.00	568.60	1460.00	576.07	.07	.14	.02	833.03	7.47	378.64

SECTION NUMBER	CHANNEL LENGTH	MIN EL OF ROADWAY	MAX EL OF LOW CHORD	MIN EL GROUND	DISCHARGE (CFS)	CWSEL	HV	HL	OLOSS	QCH	DEPTH	TOPWID
7200.00	450.00	0.00	0.00	568.20	1090.00	575.27	.19	.23	.04	916.12	7.07	117.00
7200.00	450.00	0.00	0.00	568.20	1590.00	575.75	.30	.24	.11	1283.06	7.55	117.00
7200.00	450.00	0.00	0.00	568.20	1770.00	575.88	.35	.25	.13	1413.84	7.68	117.00
7200.00	450.00	0.00	0.00	568.20	2225.00	576.13	.48	.27	.20	1742.58	7.93	117.00
7250.00	50.00	0.00	0.00	569.60	1090.00	575.29	.23	.05	.02	1090.00	5.69	93.64
7250.00	50.00	0.00	0.00	569.60	1590.00	575.78	.37	.07	.03	1590.00	6.18	95.77
7250.00	50.00	0.00	0.00	569.60	1770.00	575.91	.42	.07	.04	1770.00	6.31	96.35
7250.00	50.00	0.00	0.00	569.60	2225.00	576.18	.58	.10	.05	2225.00	6.58	97.54
7251.00	1.00	578.00	580.10	569.60	1090.00	575.27	.28	.00	.02	1090.00	5.67	82.72
7251.00	1.00	578.00	580.10	569.60	1590.00	575.74	.45	.00	.04	1590.00	6.14	83.75
7251.00	1.00	578.00	580.10	569.60	1770.00	575.87	.52	.00	.05	1770.00	6.27	84.03
7251.00	1.00	578.00	580.10	569.60	2225.00	576.11	.72	.00	.07	2225.00	6.51	84.58
7298.00	47.00	578.00	580.10	569.60	1090.00	575.32	.27	.04	.00	1090.00	5.72	82.84
7298.00	47.00	578.00	580.10	569.60	1590.00	575.81	.43	.05	.01	1590.00	6.21	83.91
7298.00	47.00	578.00	580.10	569.60	1770.00	575.95	.50	.06	.01	1770.00	6.35	84.20
7298.00	47.00	578.00	580.10	569.60	2225.00	576.24	.67	.07	.01	2225.00	6.64	85.20
7299.00	1.00	0.00	0.00	569.60	1090.00	575.38	.22	.00	.02	1090.00	5.78	94.03
7299.00	1.00	0.00	0.00	569.60	1590.00	575.94	.34	.00	.03	1590.00	6.34	96.47
7299.00	1.00	0.00	0.00	569.60	1770.00	576.10	.38	.00	.04	1770.00	6.50	97.21
7299.00	1.00	0.00	0.00	569.60	2225.00	576.48	.49	.00	.05	2225.00	6.88	98.87
7355.00	56.00	0.00	0.00	569.10	1090.00	575.59	.09	.04	.04	617.47	6.49	200.00
7355.00	56.00	0.00	0.00	569.10	1590.00	576.27	.12	.05	.06	827.63	7.17	200.00
7355.00	56.00	0.00	0.00	569.10	1770.00	576.48	.13	.05	.07	900.92	7.38	200.00
7355.00	56.00	0.00	0.00	569.10	2225.00	576.97	.16	.06	.10	1081.26	7.87	200.00
7805.00	450.00	0.00	0.00	569.30	1090.00	575.80	.24	.28	.07	1069.19	6.50	114.09
7805.00	450.00	0.00	0.00	569.30	1590.00	576.50	.31	.32	.09	1451.90	7.20	315.34
7805.00	450.00	0.00	0.00	569.30	1770.00	576.72	.31	.33	.09	1551.00	7.42	500.00
7805.00	450.00	0.00	0.00	569.30	2225.00	577.25	.28	.34	.06	1715.54	7.95	500.00
8305.00	500.00	0.00	0.00	570.30	1090.00	576.42	.30	.66	.03	931.60	6.12	194.05
8305.00	500.00	0.00	0.00	570.30	1590.00	577.18	.30	.66	.00	1206.24	6.88	195.00
8305.00	500.00	0.00	0.00	570.30	1770.00	577.38	.31	.66	.00	1306.07	7.08	195.00
8305.00	500.00	0.00	0.00	570.30	2225.00	577.84	.34	.62	.03	1558.52	7.54	195.00
8605.00	300.00	0.00	0.00	571.00	1090.00	576.88	.26	.41	.01	1090.00	5.88	48.00
8605.00	300.00	0.00	0.00	571.00	1590.00	577.57	.44	.47	.07	1590.00	6.57	48.00
8605.00	300.00	0.00	0.00	571.00	1770.00	577.78	.51	.50	.10	1770.00	6.78	48.00
8605.00	300.00	0.00	0.00	571.00	2225.00	578.21	.71	.56	.19	2225.00	7.21	48.00
8606.00	1.00	0.00	0.00	571.00	1090.00	576.88	.26	.00	.00	1090.00	5.88	48.00
8606.00	1.00	0.00	0.00	571.00	1590.00	577.57	.44	.00	.00	1590.00	6.57	48.00
8606.00	1.00	0.00	0.00	571.00	1770.00	577.78	.51	.00	.00	1770.00	6.78	48.00
8606.00	1.00	0.00	0.00	571.00	2225.00	578.22	.71	.00	.00	2225.00	7.22	48.00

SECTION NUMBER	CHANNEL LENGTH	MIN EL OF ROADWAY	MAX EL OF LOW CHORD	MIN EL GROUND	DISCHARGE (CFS)	CWSEL	HV	HL	OLOSS	QCH	DEPTH	TOPWID
8658.00	52.00	581.60	577.90	571.00	1090.00	576.96	.26	.07	0.00	1090.00	5.96	48.00
8658.00	52.00	581.60	577.90	571.00	1590.00	577.98	.39	.36	0.00	1590.00	6.98	48.00
8658.00	52.00	581.60	577.90	571.00	1770.00	578.33	.44	.47	0.00	1770.00	7.33	48.00
8658.00	52.00	581.60	577.90	571.00	2225.00	579.24	.54	.85	0.00	2225.00	8.24	48.00
8659.00	1.00	0.00	0.00	571.00	1090.00	576.96	.26	.00	.00	1090.00	5.96	48.00
8659.00	1.00	0.00	0.00	571.00	1590.00	577.98	.39	.00	.00	1590.00	6.98	48.00
8659.00	1.00	0.00	0.00	571.00	1770.00	578.33	.44	.00	.00	1770.00	7.33	48.00
8659.00	1.00	0.00	0.00	571.00	2225.00	579.24	.54	.00	.00	2225.00	8.24	48.00
8816.00	157.00	0.00	0.00	569.90	1090.00	577.20	.17	.13	.02	771.92	7.30	128.13
8816.00	157.00	0.00	0.00	569.90	1590.00	578.38	.19	.14	.06	990.53	8.48	147.74
8816.00	157.00	0.00	0.00	569.90	1770.00	578.79	.19	.14	.07	1058.72	8.89	153.65
8816.00	157.00	0.00	0.00	569.90	2225.00	579.83	.18	.13	.11	1210.67	9.93	168.81
9106.00	290.00	0.00	0.00	571.50	960.00	577.41	.14	.18	.01	960.00	5.91	59.00
9106.00	290.00	0.00	0.00	571.50	1355.00	578.56	.20	.18	.00	1355.00	7.06	59.00
9106.00	290.00	0.00	0.00	571.50	1520.00	578.95	.22	.18	.02	1520.00	7.45	59.00
9106.00	290.00	0.00	0.00	571.50	1960.00	579.96	.28	.17	.05	1960.00	8.46	59.00
9107.00	1.00	583.60	580.10	571.50	960.00	577.39	.18	.00	.02	960.00	5.89	59.00
9107.00	1.00	583.60	580.10	571.50	1355.00	578.53	.24	.00	.02	1355.00	7.03	59.00
9107.00	1.00	583.60	580.10	571.50	1520.00	578.92	.27	.00	.03	1520.00	7.42	59.00
9107.00	1.00	583.60	580.10	571.50	1960.00	579.92	.35	.00	.04	1960.00	8.42	59.00
9127.00	20.00	583.60	580.10	571.50	960.00	577.40	.18	.01	.00	960.00	5.90	59.00
9127.00	20.00	583.60	580.10	571.50	1355.00	578.54	.24	.01	.00	1355.00	7.04	59.00
9127.00	20.00	583.60	580.10	571.50	1520.00	578.93	.27	.01	.00	1520.00	7.43	59.00
9127.00	20.00	583.60	580.10	571.50	1960.00	579.93	.35	.01	.00	1960.00	8.43	59.00
9128.00	1.00	0.00	0.00	571.50	960.00	577.45	.14	.00	.01	960.00	5.95	59.00
9128.00	1.00	0.00	0.00	571.50	1355.00	578.61	.19	.00	.02	1355.00	7.11	59.00
9128.00	1.00	0.00	0.00	571.50	1520.00	579.01	.21	.00	.02	1520.00	7.51	59.00
9128.00	1.00	0.00	0.00	571.50	1960.00	580.03	.27	.00	.02	1960.00	8.53	59.00
9264.00	136.00	0.00	0.00	571.50	960.00	577.54	.21	.12	.03	781.21	6.04	290.42
9264.00	136.00	0.00	0.00	571.50	1355.00	578.83	.09	.08	.03	764.32	7.33	329.96
9264.00	136.00	0.00	0.00	571.50	1520.00	579.26	.07	.08	.04	775.19	7.76	332.00
9264.00	136.00	0.00	0.00	571.50	1960.00	580.37	.06	.06	.06	821.07	8.87	332.00
9764.00	500.00	0.00	0.00	571.50	1015.00	578.08	.04	.32	.05	412.43	6.58	550.00
9764.00	500.00	0.00	0.00	571.50	1370.00	579.06	.02	.15	.02	389.30	7.56	550.00
9764.00	500.00	0.00	0.00	571.50	1465.00	579.45	.02	.11	.02	376.01	7.95	550.00
9764.00	500.00	0.00	0.00	571.50	1700.00	580.49	.01	.07	.01	356.82	8.99	550.00
10264.00	500.00	0.00	0.00	571.10	1015.00	578.26	.06	.19	.01	511.42	7.16	690.55
10264.00	500.00	0.00	0.00	571.10	1370.00	579.15	.03	.09	.00	457.42	8.05	698.53
10264.00	500.00	0.00	0.00	571.10	1465.00	579.52	.02	.07	.00	430.31	8.42	700.56
10264.00	500.00	0.00	0.00	571.10	1700.00	580.53	.01	.03	.00	384.00	9.43	706.05

	SECTION NUMBER	CHANNEL LENGTH	MIN EL OF ROADWAY	MAX EL OF LOW CHORD	MIN EL GROUND	DISCHARGE (CFS)	CWSEL	HV	HL	OLOSS	QCH	DEPTH	TOPWID
6	10764.00	500.00	0.00	0.00	572.30	1015.00	578.48	.08	.23	.01	485.56	6.18	550.90
1	10764.00	500.00	0.00	0.00	572.30	1370.00	579.26	.05	.12	.01	461.49	6.96	562.71
2	10764.00	500.00	0.00	0.00	572.30	1465.00	579.60	.03	.09	.01	437.31	7.30	565.00
3	10764.00	500.00	0.00	0.00	572.30	1700.00	580.56	.02	.04	.00	392.04	8.26	565.00
4	Confluence												
5	11264.00	500.00	0.00	0.00	570.90	760.00	578.71	.17	.28	.04	686.07	7.81	350.00
6	11264.00	500.00	0.00	0.00	570.90	1015.00	579.40	.13	.18	.04	738.41	8.50	350.00
7	11264.00	500.00	0.00	0.00	570.90	1100.00	579.70	.10	.14	.03	729.30	8.80	350.00
8	11264.00	500.00	0.00	0.00	570.90	1265.00	580.62	.05	.07	.02	654.84	9.72	350.00
9													
10	11364.00	100.00	0.00	0.00	570.90	760.00	578.92	.02	.02	.04	452.75	8.02	305.00
11	11364.00	100.00	0.00	0.00	570.90	1015.00	579.55	.02	.02	.03	549.54	8.65	305.00
12	11364.00	100.00	0.00	0.00	570.90	1100.00	579.82	.02	.02	.02	574.60	8.92	305.00
13	11364.00	100.00	0.00	0.00	570.90	1265.00	580.67	.02	.01	.01	603.44	9.77	305.00
14													
15	11644.00	280.00	0.00	0.00	574.40	760.00	578.95	.04	.04	.01	685.90	4.55	160.00
16	11644.00	280.00	0.00	0.00	574.40	1015.00	579.57	.05	.04	.01	899.80	5.17	160.00
17	11644.00	280.00	0.00	0.00	574.40	1100.00	579.85	.05	.04	.02	968.88	5.45	160.00
18	11644.00	280.00	0.00	0.00	574.40	1265.00	580.69	.05	.03	.01	1096.64	6.29	160.00
19													
20	11714.00	70.00	0.00	0.00	573.20	760.00	578.82	.37	.03	.17	760.00	5.62	28.00
1	11714.00	70.00	0.00	0.00	573.20	1015.00	579.36	.55	.04	.25	1015.00	6.16	28.00
22	11714.00	70.00	0.00	0.00	573.20	1100.00	579.61	.60	.04	.27	1100.00	6.41	28.00
23	11714.00	70.00	0.00	0.00	573.20	1265.00	580.43	.62	.03	.29	1265.00	7.23	28.00
24													
25	11715.00	1.00	0.00	0.00	573.20	760.00	578.82	.37	.00	.00	760.00	5.62	28.00
26	11715.00	1.00	0.00	0.00	573.20	1015.00	579.36	.55	.00	.00	1015.00	6.16	28.00
27	11715.00	1.00	0.00	0.00	573.20	1100.00	579.61	.60	.00	.00	1100.00	6.41	28.00
28	11715.00	1.00	0.00	0.00	573.20	1265.00	580.43	.62	.00	.00	1265.00	7.23	28.00
29													
30	11729.00	14.00	582.90	578.20	573.20	760.00	579.30	.32	.42	0.00	760.00	6.10	28.00
31	11729.00	14.00	582.90	578.20	573.20	1015.00	580.37	.41	.86	0.00	1015.00	7.17	28.00
32	11729.00	14.00	582.90	578.20	573.20	1100.00	580.86	.42	1.07	0.00	1100.00	7.66	28.00
33	11729.00	14.00	582.90	578.20	573.20	1265.00	582.24	.40	1.58	0.00	1265.00	9.04	28.00
34													
35	11730.00	1.00	0.00	0.00	573.20	760.00	579.30	.32	.00	.00	760.00	6.10	28.00
36	11730.00	1.00	0.00	0.00	573.20	1015.00	580.37	.41	.00	.00	1015.00	7.17	28.00
37	11730.00	1.00	0.00	0.00	573.20	1100.00	580.86	.42	.00	.00	1100.00	7.66	28.00
38	11730.00	1.00	0.00	0.00	573.20	1265.00	582.24	.40	.00	.00	1265.00	9.04	28.00
39													
40	11765.00	35.00	0.00	0.00	571.70	810.00	579.55	.15	.03	.05	787.84	7.85	67.28
41	11765.00	35.00	0.00	0.00	571.70	1100.00	580.71	.17	.03	.07	1029.36	9.01	68.57
42	11765.00	35.00	0.00	0.00	571.70	1210.00	581.21	.17	.03	.07	1114.73	9.51	69.12
43	11765.00	35.00	0.00	0.00	571.70	1450.00	582.57	.16	.02	.07	1282.16	10.87	98.00
44													
45	12005.00	240.00	0.00	0.00	572.10	810.00	579.96	.22	.44	.04	437.85	7.86	125.17
46	12005.00	240.00	0.00	0.00	572.10	1100.00	581.15	.11	.35	.02	275.65	9.05	263.20
47	12005.00	240.00	0.00	0.00	572.10	1210.00	581.62	.08	.29	.03	222.78	9.52	320.00
48	12005.00	240.00	0.00	0.00	572.10	1450.00	582.88	.04	.16	.03	145.87	10.78	320.00
49													
50													
51													
52													
53													
54													
55													
56													
57													

SECTION NUMBER	CHANNEL LENGTH	MIN EL OF ROADWAY	MAX EL OF LOW CHORD	MIN EL GROUND	DISCHARGE (CFS)	CWSEL	HV	HL	OLOSS	QCH	DEPTH	TOPWID
12365.00	360.00	0.00	0.00	572.70	810.00	582.24	.03	2.03	.06	136.76	9.54	330.00
12365.00	360.00	0.00	0.00	572.70	1100.00	582.64	.04	1.40	.02	149.14	9.94	330.00
12365.00	360.00	0.00	0.00	572.70	1210.00	582.79	.04	1.11	.01	153.31	10.09	330.00
12365.00	360.00	0.00	0.00	572.70	1450.00	583.38	.04	.49	.00	144.59	10.68	330.00
12440.00	75.00	0.00	0.00	572.90	810.00	582.41	.03	.17	.00	146.06	9.51	355.00
12440.00	75.00	0.00	0.00	572.90	1100.00	582.80	.04	.17	.00	155.42	9.90	355.00
12440.00	75.00	0.00	0.00	572.90	1210.00	582.95	.04	.16	.00	157.68	10.05	355.00
12440.00	75.00	0.00	0.00	572.90	1450.00	583.49	.04	.11	.00	147.38	10.59	355.00
12441.00	1.00	0.00	0.00	572.90	810.00	582.40	.04	.00	.01	471.67	9.50	355.00
12441.00	1.00	0.00	0.00	572.90	1100.00	582.80	.05	.00	.01	561.63	9.90	355.00
12441.00	1.00	0.00	0.00	572.90	1210.00	582.95	.05	.00	.00	589.52	10.05	355.00
12441.00	1.00	0.00	0.00	572.90	1450.00	583.49	.04	.00	.00	605.93	10.59	355.00
12489.00	48.00	582.50	579.40	572.90	810.00	582.77	.08	.41	0.00	718.47	9.87	196.16
12489.00	48.00	582.50	579.40	572.90	1100.00	583.17	.12	.45	0.00	935.24	10.27	291.65
12489.00	48.00	582.50	579.40	572.90	1210.00	583.31	.13	.44	0.00	1007.07	10.41	314.07
12489.00	48.00	582.50	579.40	572.90	1450.00	583.66	.14	.27	0.00	1124.38	10.76	330.00
12490.00	1.00	0.00	0.00	572.90	810.00	582.77	.09	.00	.00	736.97	9.87	196.17
12490.00	1.00	0.00	0.00	572.90	1100.00	583.17	.13	.00	.01	967.43	10.27	291.66
12490.00	1.00	0.00	0.00	572.90	1210.00	583.30	.15	.00	.01	1046.05	10.40	314.08
12490.00	1.00	0.00	0.00	572.90	1450.00	583.65	.17	.00	.01	1184.62	10.75	330.00
-8816.00	157.00	0.00	0.00	569.90	1090.00	577.20	.17	.06	0.00	771.97	7.30	128.12
-8816.00	157.00	0.00	0.00	569.90	1590.00	578.38	.19	.08	0.00	990.68	8.48	147.72
-8816.00	157.00	0.00	0.00	569.90	1770.00	578.79	.19	.08	0.00	1058.94	8.89	153.62
-8816.00	157.00	0.00	0.00	569.90	2225.00	579.83	.18	.08	0.00	1210.95	9.93	168.77
9546.00	730.00	0.00	0.00	577.60	145.00	578.97	.30	.60	0.00	145.00	1.37	58.65
9546.00	730.00	0.00	0.00	577.60	235.00	579.21	.36	.57	0.00	235.00	1.61	70.86
9546.00	730.00	0.00	0.00	577.60	255.00	579.26	.37	.54	0.00	255.00	1.66	73.16
9546.00	730.00	0.00	0.00	577.60	270.00	580.41	.04	.40	.04	270.00	2.81	107.19
10246.00	700.00	0.00	0.00	574.60	145.00	579.42	.00	.07	.09	145.00	4.82	93.65
10246.00	700.00	0.00	0.00	574.60	235.00	579.80	.01	.13	.11	235.00	5.20	94.42
10246.00	700.00	0.00	0.00	574.60	255.00	579.88	.01	.15	.11	255.00	5.28	94.57
10246.00	700.00	0.00	0.00	574.60	270.00	580.54	.01	.08	.01	270.00	5.94	95.88
10846.00	600.00	0.00	0.00	574.60	145.00	579.44	.00	.01	.00	145.00	4.84	93.91
10846.00	600.00	0.00	0.00	574.60	235.00	579.83	.01	.03	.00	235.00	5.23	95.31
10846.00	600.00	0.00	0.00	574.60	255.00	579.91	.01	.03	.00	255.00	5.31	95.58
10846.00	600.00	0.00	0.00	574.60	270.00	580.56	.01	.02	.00	270.00	5.96	97.87
11846.00	1000.00	0.00	0.00	572.60	145.00	579.45	.00	.01	.00	145.00	6.85	81.98
11846.00	1000.00	0.00	0.00	572.60	235.00	579.86	.00	.02	.00	235.00	7.26	84.87
11846.00	1000.00	0.00	0.00	572.60	255.00	579.94	.00	.03	.00	255.00	7.34	85.37
11846.00	1000.00	0.00	0.00	572.60	270.00	580.59	.00	.02	.00	270.00	7.99	89.94

SECTION NUMBER	CHANNEL LENGTH	MIN EL OF ROADWAY	MAX EL OF LOW CHORD	MIN EL GROUND	DISCHARGE (CFS)	CWSEL	HV	HL	OLOSS	QCH	DEPTH	TOPWID
-9264.00	0.00	0.00	0.00	571.50	960.00	577.54	.21	0.00	0.00	781.22	6.04	290.42
-9264.00	0.00	0.00	0.00	571.50	1355.00	578.83	.09	0.00	0.00	764.47	7.33	329.89
-9264.00	0.00	0.00	0.00	571.50	1520.00	579.26	.08	0.00	0.00	775.33	7.76	332.00
-9264.00	0.00	0.00	0.00	571.50	1960.00	580.37	.06	0.00	0.00	821.14	8.87	332.00
9594.00	330.00	0.00	0.00	579.50	25.00	580.06	.14	.46	0.00	25.00	.56	29.43
9594.00	330.00	0.00	0.00	579.50	155.00	580.66	.29	.22	0.00	155.00	1.16	61.80
9594.00	330.00	0.00	0.00	579.50	220.00	580.84	.34	.18	0.00	220.00	1.34	72.66
9594.00	330.00	0.00	0.00	579.50	435.00	581.25	.43	.13	0.00	435.00	1.75	98.09
10294.00	700.00	0.00	0.00	578.60	25.00	580.27	.00	.02	.04	25.00	1.67	187.64
10294.00	700.00	0.00	0.00	578.60	155.00	581.16	.00	.12	.09	155.00	2.56	190.40
10294.00	700.00	0.00	0.00	578.60	220.00	581.42	.00	.15	.10	220.00	2.82	191.06
10294.00	700.00	0.00	0.00	578.60	435.00	582.06	.01	.26	.13	435.00	3.46	192.65
10894.00	600.00	0.00	0.00	574.10	25.00	580.27	.00	.00	.00	25.00	6.17	239.00
10894.00	600.00	0.00	0.00	574.10	155.00	581.16	.00	.00	.00	155.00	7.06	244.67
10894.00	600.00	0.00	0.00	574.10	220.00	581.43	.00	.00	.00	220.00	7.33	246.89
10894.00	600.00	0.00	0.00	574.10	435.00	582.08	.00	.01	.00	435.00	7.98	252.27
11894.00	1000.00	0.00	0.00	573.60	25.00	580.27	.00	.00	.00	25.00	6.67	325.01
11894.00	1000.00	0.00	0.00	573.60	155.00	581.16	.00	.00	.00	155.00	7.56	328.53
11894.00	1000.00	0.00	0.00	573.60	220.00	581.43	.00	.00	.00	220.00	7.83	329.74
11894.00	1000.00	0.00	0.00	573.60	435.00	582.08	.00	.00	.00	435.00	8.48	332.67

SECTION NUMBER	DISCHARGE CFS	CWSEL	CWSEL DIFF EACH Q	CWSEL DIFF EACH SECTION	CWSEL-WSELK	TOPWID	T.W. DIFF	LENGTH
1613.000	1080.000	573.100	0.000	0.000	0.000	287.238	0.000	0.000
1613.000	1290.000	573.100	0.000	0.000	0.000	287.238	0.000	0.000
1613.000	1345.000	573.100	0.000	0.000	0.000	287.238	0.000	0.000
1613.000	1460.000	573.100	0.000	0.000	0.000	287.238	0.000	0.000
1783.000	1080.000	573.122	0.000	.022	0.000	287.686	0.000	170.000
1783.000	1290.000	573.131	.009	.031	0.000	287.695	-.009	170.000
1783.000	1345.000	573.134	.003	.034	0.000	287.698	-.011	170.000
1783.000	1460.000	573.140	.006	.040	0.000	287.703	-.017	170.000
1953.000	1080.000	573.138	0.000	.016	0.000	288.133	0.000	170.000
1953.000	1290.000	573.154	.016	.023	0.000	288.149	-.016	170.000
1953.000	1345.000	573.159	.005	.025	0.000	288.154	-.021	170.000
1953.000	1460.000	573.170	.011	.030	0.000	288.164	-.031	170.000
2113.000	1080.000	572.980	0.000	-.158	0.000	24.499	0.000	160.000
2113.000	1290.000	573.170	.190	.015	0.000	294.499	-270.000	160.000
2113.000	1345.000	573.176	.006	.017	0.000	294.499	-270.000	160.000
2113.000	1460.000	573.189	.014	.020	0.000	294.499	-270.000	160.000
2114.000	1080.000	572.980	0.000	.000	0.000	24.499	0.000	1.000
2114.000	1290.000	573.169	.189	-.001	0.000	294.499	-270.000	1.000
2114.000	1345.000	573.175	.006	-.001	0.000	294.499	-270.000	1.000
2114.000	1460.000	573.188	.013	-.001	0.000	294.499	-270.000	1.000
2131.000	1080.000	573.278	0.000	.299	0.000	24.499	0.000	17.000
2131.000	1290.000	574.205	.927	1.036	0.000	224.857	-200.358	17.000
2131.000	1345.000	574.284	.079	1.109	0.000	251.382	-226.883	17.000
2131.000	1460.000	574.420	.136	1.232	0.000	297.309	-272.810	17.000
2132.000	1080.000	573.279	0.000	.000	0.000	24.499	0.000	1.000
2132.000	1290.000	574.205	.926	.000	0.000	224.873	-200.374	1.000
2132.000	1345.000	574.284	.079	.000	0.000	251.400	-226.901	1.000
2132.000	1460.000	574.420	.136	.000	0.000	297.329	-272.830	1.000

	2182.000	1080.000	573.793	0.000	.514	0.000	64.999	0.000	50.000
	2182.000	1290.000	574.246	.453	.041	0.000	339.999	-275.000	50.000
	2182.000	1345.000	574.327	.081	.043	0.000	339.999	-275.000	50.000
	2182.000	1460.000	574.468	.141	.048	0.000	339.999	-275.000	50.000
6									
1	2632.000	1080.000	573.929	0.000	.136	0.000	149.814	0.000	450.000
2	2632.000	1290.000	574.255	.326	.009	0.000	209.999	-60.185	450.000
3	2632.000	1345.000	574.335	.081	.009	0.000	209.999	-60.185	450.000
4	2632.000	1460.000	574.477	.141	.009	0.000	209.999	-60.185	450.000
5									
6	2932.000	1080.000	573.977	0.000	.048	0.000	59.999	0.000	300.000
7	2932.000	1290.000	574.306	.329	.051	0.000	59.999	-.000	300.000
8	2932.000	1345.000	574.387	.081	.052	0.000	59.999	-.000	300.000
9	2932.000	1460.000	574.530	.143	.053	0.000	59.999	-.000	300.000
10									
11	2982.000	1080.000	573.828	0.000	-.148	0.000	30.529	0.000	50.000
12	2982.000	1290.000	574.109	.281	-.197	0.000	30.529	-.000	50.000
13	2982.000	1345.000	574.177	.068	-.210	0.000	30.529	-.000	50.000
14	2982.000	1460.000	574.289	.112	-.241	0.000	30.529	-.000	50.000
15									
16	2983.000	1080.000	573.829	0.000	.001	0.000	30.529	0.000	1.000
17	2983.000	1290.000	574.111	.281	.001	0.000	30.529	-.000	1.000
18	2983.000	1345.000	574.179	.068	.001	0.000	30.529	-.000	1.000
19	2983.000	1460.000	574.290	.112	.001	0.000	30.529	-.000	1.000
20									
21	3049.000	1080.000	574.170	0.000	.340	0.000	30.529	0.000	66.000
22	3049.000	1290.000	574.678	.508	.567	0.000	30.529	-.000	66.000
23	3049.000	1345.000	574.816	.138	.638	0.000	30.529	-.000	66.000
24	3049.000	1460.000	575.086	.270	.796	0.000	30.529	-.000	66.000
25									
26	3050.000	1080.000	574.170	0.000	.001	0.000	30.529	0.000	1.000
27	3050.000	1290.000	574.679	.508	.001	0.000	30.529	-.000	1.000
28	3050.000	1345.000	574.817	.138	.001	0.000	30.529	-.000	1.000
29	3050.000	1460.000	575.087	.270	.001	0.000	30.529	-.000	1.000
30									
31	3250.000	1080.000	574.727	0.000	.556	0.000	309.495	0.000	200.000
32	3250.000	1290.000	575.362	.635	.683	0.000	328.420	-18.925	200.000
33	3250.000	1345.000	575.532	.170	.715	0.000	329.212	-19.717	200.000
34	3250.000	1460.000	575.869	.338	.782	0.000	337.616	-28.121	200.000
35									
36	3750.000	1085.000	574.746	0.000	.020	0.000	566.525	0.000	500.000
37	3750.000	1290.000	575.381	.635	.020	0.000	590.052	-23.527	500.000
38	3750.000	1345.000	575.551	.170	.019	0.000	596.333	-29.808	500.000
39	3750.000	1460.000	575.889	.338	.019	0.000	608.844	-42.319	500.000
40									
41	4225.000	1085.000	574.757	0.000	.011	0.000	699.644	0.000	475.000
42	4225.000	1290.000	575.391	-.634	.009	0.000	764.463	-64.819	475.000
43	4225.000	1345.000	575.560	.169	.009	0.000	784.999	-85.355	475.000
44	4225.000	1460.000	575.897	.337	.009	0.000	784.999	-85.355	475.000
45									
46	4700.000	1085.000	574.770	0.000	.013	0.000	899.999	0.000	475.000
47	4700.000	1290.000	575.402	.632	.011	0.000	899.999	-.000	475.000
48	4700.000	1345.000	575.571	.169	.011	0.000	899.999	-.000	475.000
49	4700.000	1460.000	575.907	.336	.010	0.000	899.999	-.000	475.000
50									
51	5750.000	1085.000	574.847	0.000	.077	0.000	552.942	0.000	1050.000
52	5750.000	1290.000	575.453	.606	.051	0.000	590.843	-37.902	1050.000
53	5750.000	1345.000	575.618	.164	.047	0.000	606.294	-53.352	1050.000
54	5750.000	1460.000	575.947	.329	.039	0.000	650.862	-97.920	1050.000
55									
56	6750.000	1085.000	575.083	0.000	.236	0.000	355.773	0.000	1000.000
57	6750.000	1290.000	575.613	.530	.160	0.000	368.100	-12.327	1000.000
	6750.000	1345.000	575.762	.148	.144	0.000	371.552	-15.780	1000.000
	6750.000	1460.000	576.066	.305	.120	0.000	378.637	-22.865	1000.000

	7200.000	1090.000	575.268	0.000	.185	0.000	116.999	0.000	450.000
	7200.000	1590.000	575.747	.479	.134	0.000	116.999	-.000	450.000
	7200.000	1770.000	575.877	.130	.115	0.000	116.999	-.000	450.000
	7200.000	2225.000	576.134	.257	.067	0.000	116.999	-.000	450.000
6	7250.000	1090.000	575.292	0.000	.023	0.000	93.636	0.000	50.000
1	7250.000	1590.000	575.779	.488	.032	0.000	95.767	-2.131	50.000
2	7250.000	1770.000	575.913	.133	.036	0.000	96.349	-2.712	50.000
3	7250.000	2225.000	576.179	.267	.045	0.000	97.544	-3.907	50.000
4									
5	7251.000	1090.000	575.269	0.000	-.022	0.000	82.724	0.000	1.000
6	7251.000	1590.000	575.740	.471	-.039	0.000	83.752	-1.027	1.000
7	7251.000	1770.000	575.866	.126	-.047	0.000	84.026	-1.302	1.000
8	7251.000	2225.000	576.109	.242	-.071	0.000	84.578	-1.853	1.000
9									
10	7298.000	1090.000	575.317	0.000	.048	0.000	82.840	0.000	47.000
11	7298.000	1590.000	575.813	.496	.073	0.000	83.908	-1.068	47.000
12	7298.000	1770.000	575.950	.137	.084	0.000	84.199	-1.359	47.000
13	7298.000	2225.000	576.242	.292	.134	0.000	85.204	-2.365	47.000
14									
15	7299.000	1090.000	575.384	0.000	.066	0.000	94.028	0.000	1.000
16	7299.000	1590.000	575.939	.555	.126	0.000	96.474	-2.446	1.000
17	7299.000	1770.000	576.105	.166	.155	0.000	97.206	-3.178	1.000
18	7299.000	2225.000	576.479	.374	.237	0.000	98.865	-4.838	1.000
19									
20	7355.000	1090.000	575.593	0.000	.209	0.000	199.999	0.000	56.000
21	7355.000	1590.000	576.266	.673	.327	0.000	199.999	-.000	56.000
22	7355.000	1770.000	576.477	.211	.372	0.000	199.999	-.000	56.000
23	7355.000	2225.000	576.970	.493	.491	0.000	199.999	-.000	56.000
24									
25	7805.000	1090.000	575.798	0.000	.205	0.000	114.087	0.000	450.000
26	7805.000	1590.000	576.498	.700	.232	0.000	315.345	-201.258	450.000
27	7805.000	1770.000	576.721	.223	.244	0.000	499.999	-385.912	450.000
28	7805.000	2225.000	577.246	.524	.276	0.000	499.999	-385.912	450.000
29									
30	8305.000	1090.000	576.425	0.000	.627	0.000	194.048	0.000	500.000
31	8305.000	1590.000	577.175	.750	.677	0.000	195.000	-.952	500.000
32	8305.000	1770.000	577.382	.207	.661	0.000	195.000	-.952	500.000
33	8305.000	2225.000	577.836	.454	.590	0.000	195.000	-.952	500.000
34									
35	8605.000	1090.000	576.882	0.000	.457	0.000	48.000	0.000	300.000
36	8605.000	1590.000	577.574	.692	.399	0.000	48.000	0.000	300.000
37	8605.000	1770.000	577.775	.201	.393	0.000	48.000	0.000	300.000
38	8605.000	2225.000	578.215	.440	.379	0.000	48.000	0.000	300.000
39									
40	8606.000	1090.000	576.882	0.000	.001	0.000	48.000	0.000	1.000
41	8606.000	1590.000	577.575	.692	.001	0.000	48.000	0.000	1.000
42	8606.000	1770.000	577.776	.202	.001	0.000	48.000	0.000	1.000
43	8606.000	2225.000	578.216	.440	.001	0.000	48.000	0.000	1.000
44									
45	8658.000	1090.000	576.960	0.000	.077	0.000	48.000	0.000	52.000
46	8658.000	1590.000	577.983	1.023	.408	0.000	48.000	0.000	52.000
47	8658.000	1770.000	578.329	.346	.553	0.000	48.000	0.000	52.000
48	8658.000	2225.000	579.239	.911	1.023	0.000	48.000	0.000	52.000
49									
50	8659.000	1090.000	576.960	0.000	.000	0.000	48.000	0.000	1.000
51	8659.000	1590.000	577.983	1.023	.001	0.000	48.000	0.000	1.000
52	8659.000	1770.000	578.329	.346	.001	0.000	48.000	0.000	1.000
53	8659.000	2225.000	579.240	.911	.001	0.000	48.000	0.000	1.000
54									
55	8816.000	1090.000	577.195	0.000	.235	0.000	128.130	0.000	157.000
56	8816.000	1590.000	578.383	1.188	.399	0.000	147.743	-19.613	157.000
57	8816.000	1770.000	578.788	.405	.459	0.000	153.655	-25.525	157.000
	8816.000	2225.000	579.833	1.045	.592	0.000	168.813	-40.683	157.000
	9106.000	960.000	577.412	0.000	.217	0.000	59.000	0.000	290.000

9106.000	1355.000	578.557	1.145	.174	0.000	59.000	0.000	290.000
9106.000	1520.000	578.951	.393	.163	0.000	59.000	0.000	290.000
9106.000	1960.000	579.956	1.005	.123	0.000	59.000	0.000	290.000
9107.000	960.000	577.394	0.000	-.018	0.000	59.000	0.000	1.000
9107.000	1355.000	578.533	1.138	-.024	0.000	59.000	0.000	1.000
9107.000	1520.000	578.923	.391	-.027	0.000	59.000	0.000	1.000
9107.000	1960.000	579.921	.998	-.035	0.000	59.000	0.000	1.000
9127.000	960.000	577.400	0.000	.005	0.000	59.000	0.000	20.000
9127.000	1355.000	578.539	1.139	.007	0.000	59.000	0.000	20.000
9127.000	1520.000	578.930	.391	.007	0.000	59.000	0.000	20.000
9127.000	1960.000	579.929	.998	.008	0.000	59.000	0.000	20.000
9128.000	960.000	577.450	0.000	.050	0.000	59.000	0.000	1.000
9128.000	1355.000	578.607	1.158	.068	0.000	59.000	0.000	1.000
9128.000	1520.000	579.006	.399	.076	0.000	59.000	0.000	1.000
9128.000	1960.000	580.026	1.019	.097	0.000	59.000	0.000	1.000
9264.000	960.000	577.542	0.000	.092	0.000	290.418	0.000	136.000
9264.000	1355.000	578.825	1.284	.218	0.000	329.962	-39.544	136.000
9264.000	1520.000	579.265	.440	.258	0.000	331.999	-41.581	136.000
9264.000	1960.000	580.367	1.102	.341	0.000	331.999	-41.581	136.000
9764.000	1015.000	578.082	0.000	.540	0.000	549.999	0.000	500.000
9764.000	1370.000	579.061	.979	.236	0.000	549.999	-.000	500.000
9764.000	1465.000	579.454	.393	.189	0.000	549.999	-.000	500.000
9764.000	1700.000	580.492	1.038	.125	0.000	549.999	-.000	500.000
10264.000	1015.000	578.259	0.000	.177	0.000	690.551	0.000	500.000
10264.000	1370.000	579.148	.889	.087	0.000	698.534	-7.984	500.000
10264.000	1465.000	579.519	.371	.065	0.000	700.558	-10.007	500.000
10264.000	1700.000	580.527	1.007	.034	0.000	706.053	-15.502	500.000
10764.000	1015.000	578.477	0.000	.218	0.000	550.897	0.000	500.000
10764.000	1370.000	579.256	.779	.108	0.000	562.710	-11.813	500.000
10764.000	1465.000	579.598	.342	.079	0.000	564.999	-14.102	500.000
10764.000	1700.000	580.565	.967	.038	0.000	564.999	-14.102	500.000
11264.000	760.000	578.713	0.000	.236	0.000	349.999	0.000	500.000
11264.000	1015.000	579.395	.682	.139	0.000	349.999	-.000	500.000
11264.000	1100.000	579.703	.307	.105	0.000	349.999	-.000	500.000
11264.000	1265.000	580.618	.915	.053	0.000	349.999	-.000	500.000
11364.000	760.000	578.919	0.000	.207	0.000	304.999	0.000	100.000
11364.000	1015.000	579.546	.627	.151	0.000	304.999	-.000	100.000
11364.000	1100.000	579.824	.278	.121	0.000	304.999	-.000	100.000
11364.000	1265.000	580.674	.850	.056	0.000	304.999	-.000	100.000
11644.000	760.000	578.950	0.000	.030	0.000	159.999	0.000	280.000
11644.000	1015.000	579.573	.623	.027	0.000	159.999	-.000	280.000
11644.000	1100.000	579.847	.274	.023	0.000	159.999	-.000	280.000
11644.000	1265.000	580.687	.840	.013	0.000	159.999	-.000	280.000
11714.000	760.000	578.819	0.000	-.130	0.000	28.000	0.000	70.000
11714.000	1015.000	579.360	.541	-.213	0.000	28.000	0.000	70.000
11714.000	1100.000	579.610	.250	-.237	0.000	28.000	0.000	70.000
11714.000	1265.000	580.427	.817	-.260	0.000	28.000	0.000	70.000
11715.000	760.000	578.820	0.000	.001	0.000	28.000	0.000	1.000
11715.000	1015.000	579.361	.541	.001	0.000	28.000	0.000	1.000
11715.000	1100.000	579.612	.250	.002	0.000	28.000	0.000	1.000
11715.000	1265.000	580.428	.817	.001	0.000	28.000	0.000	1.000
11729.000	760.000	579.299	0.000	.478	0.000	28.000	0.000	14.000
11729.000	1015.000	580.373	1.075	1.013	0.000	28.000	0.000	14.000

11729.000	1100.000	580.859	.486	1.248	0.000	28.000	0.000	14.000
11729.000	1265.000	582.235	1.376	1.807	0.000	28.000	0.000	14.000
11730.000	760.000	579.300	0.000	.001	0.000	28.000	0.000	1.000
11730.000	1015.000	580.374	1.075	.001	0.000	28.000	0.000	1.000
11730.000	1100.000	580.860	.486	.001	0.000	28.000	0.000	1.000
11730.000	1265.000	582.236	1.376	.001	0.000	28.000	0.000	1.000
11765.000	810.000	579.551	0.000	.251	0.000	67.280	0.000	35.000
11765.000	1100.000	580.714	1.163	.339	0.000	68.572	-1.292	35.000
11765.000	1210.000	581.211	.498	.351	0.000	69.125	-1.845	35.000
11765.000	1450.000	582.571	1.360	.335	0.000	97.999	-30.719	35.000
12005.000	810.000	579.960	0.000	.409	0.000	125.170	0.000	240.000
12005.000	1100.000	581.145	1.185	.432	0.000	263.196	-138.026	240.000
12005.000	1210.000	581.625	.480	.414	0.000	319.999	-194.829	240.000
12005.000	1450.000	582.883	1.258	.312	0.000	319.999	-194.829	240.000
12365.000	810.000	582.238	0.000	2.277	0.000	329.999	0.000	360.000
12365.000	1100.000	582.638	.400	1.493	0.000	329.999	-.000	360.000
12365.000	1210.000	582.789	.151	1.164	0.000	329.999	-.000	360.000
12365.000	1450.000	583.379	.590	.495	0.000	329.999	-.000	360.000
12440.000	810.000	582.407	0.000	.169	0.000	354.999	0.000	75.000
12440.000	1100.000	582.803	.397	.166	0.000	354.999	-.000	75.000
12440.000	1210.000	582.952	.148	.163	0.000	354.999	-.000	75.000
12440.000	1450.000	583.493	.541	.114	0.000	354.999	-.000	75.000
12441.000	810.000	582.401	0.000	-.005	0.000	354.999	0.000	1.000
12441.000	1100.000	582.798	.397	-.005	0.000	354.999	-.000	1.000
12441.000	1210.000	582.947	.149	-.005	0.000	354.999	-.000	1.000
12441.000	1450.000	583.491	.543	-.002	0.000	354.999	-.000	1.000
12489.000	810.000	582.769	0.000	.367	0.000	196.158	0.000	48.000
12489.000	1100.000	583.172	.403	.374	0.000	291.652	-95.493	48.000
12489.000	1210.000	583.305	.133	.358	0.000	314.066	-117.908	48.000
12489.000	1450.000	583.657	.352	.167	0.000	329.999	-133.841	48.000
12490.000	810.000	582.766	0.000	-.003	0.000	196.172	0.000	1.000
12490.000	1100.000	583.166	.400	-.006	0.000	291.664	-95.492	1.000
12490.000	1210.000	583.298	.132	-.007	0.000	314.080	-117.908	1.000
12490.000	1450.000	583.646	.348	-.011	0.000	329.999	-133.827	1.000
-8816.000	1090.000	577.195	0.000	-5.571	0.000	128.121	0.000	157.000
-8816.000	1590.000	578.383	1.188	-4.783	0.000	147.717	-19.596	157.000
-8816.000	1770.000	578.788	.405	-4.510	0.000	153.625	-25.504	157.000
-8816.000	2225.000	579.833	1.045	-3.814	0.000	168.773	-40.651	157.000
9546.000	145.000	578.969	0.000	1.774	0.000	58.650	0.000	730.000
9546.000	235.000	579.211	.242	.828	0.000	70.858	-12.209	730.000
9546.000	255.000	579.257	.046	.469	0.000	73.156	-14.507	730.000
9546.000	270.000	580.412	1.155	.579	0.000	107.190	-48.540	730.000
10246.000	145.000	579.423	0.000	.454	0.000	93.650	0.000	700.000
10246.000	235.000	579.803	.381	.592	0.000	94.417	-.767	700.000
10246.000	255.000	579.877	.074	.621	0.000	94.566	-.916	700.000
10246.000	270.000	580.541	.663	.129	0.000	95.878	-2.228	700.000
10846.000	145.000	579.438	0.000	.015	0.000	93.906	0.000	600.000
10846.000	235.000	579.831	.394	.028	0.000	95.310	-1.405	600.000
10846.000	255.000	579.909	.077	.031	0.000	95.581	-1.675	600.000
10846.000	270.000	580.563	.654	.022	0.000	97.869	-3.963	600.000
11846.000	145.000	579.450	0.000	.013	0.000	81.977	0.000	1000.000
11846.000	235.000	579.858	.408	.027	0.000	84.872	-2.894	1000.000
11846.000	255.000	579.939	.081	.030	0.000	85.371	-3.394	1000.000

11846.000	270.000	580.586	.647	.023	0.000	89.943	-7.966	1000.000
-9264.000	960.000	577.542	0.000	-1.909	0.000	290.417	0.000	0.000
-9264.000	1355.000	578.825	1.284	-1.033	0.000	329.886	-39.469	0.000
-9264.000	1520.000	579.265	.440	-.674	0.000	331.999	-41.582	0.000
-9264.000	1960.000	580.367	1.102	-.219	0.000	331.999	-41.582	0.000
9594.000	25.000	580.058	0.000	2.517	0.000	29.435	0.000	330.000
9594.000	155.000	580.661	.603	1.836	0.000	61.801	-32.367	330.000
9594.000	220.000	580.836	.175	1.572	0.000	72.662	-43.227	330.000
9594.000	435.000	581.247	.410	.879	0.000	98.092	-68.657	330.000
10294.000	25.000	580.266	0.000	.208	0.000	187.641	0.000	700.000
10294.000	155.000	581.156	.891	.495	0.000	190.400	-2.759	700.000
10294.000	220.000	581.421	.264	.584	0.000	191.055	-3.414	700.000
10294.000	435.000	582.057	.636	.810	0.000	192.647	-5.005	700.000
10894.000	25.000	580.266	0.000	.000	0.000	238.998	0.000	600.000
10894.000	155.000	581.162	.896	.005	0.000	244.668	-5.670	600.000
10894.000	220.000	581.429	.268	.009	0.000	246.891	-7.892	600.000
10894.000	435.000	582.078	.648	.021	0.000	252.268	-13.270	600.000
11894.000	25.000	580.266	0.000	.000	0.000	325.011	0.000	1000.000
11894.000	155.000	581.163	.896	.001	0.000	328.533	-3.522	1000.000
11894.000	220.000	581.431	.268	.001	0.000	329.740	-4.729	1000.000
11894.000	435.000	582.081	.651	.004	0.000	332.668	-7.657	1000.000

DATA FOR LAST CROSS SECTION

PROFILE	TYPE ENC	TARGET	TOP WIDTH AREA-ACRES	TOP WIDTH AREA-DIFF
1	1.000	0.000	100.316	0.000
2	1.000	0.000	110.266	9.950
3	1.000	0.000	113.723	13.407
4	1.000	0.000	116.487	16.171

00BREAK00

1) COUNTY: Wayne

2) STUDY NAME: City of Gibralter

3) WATERCOURSE: Frank and Poet Drain

4) DOCUMENT TYPE: 100 year

00BREAK00

```
**********************************************
HEC2 VERSION UPDATED JAN 1976
ERROR CORRECTIONS 01,02,03,04,05,06,07,08,09
MODIFICATIONS 52,53,54,55,56,57,58
**********************************************

C
1       CITY OF GIBRALTER          5555-23-01      PM = RICHARD ZANOTTI
T2      10 YEAR FLOOD
T3      FRANK AND POET DRAIN

J1  ICHECK     INQ      NINV     IDIR     STRT      METRIC    HVINS      Q          WSEL       FQ
         -1.       2.       0.       0.  0.000000      0.00      0.0        0.    573.100     0.000

J2  NPROF      IPLOT    PRFVS    XSECV    XSECH     FN        ALLDC    IBW      CHNIM    ITRACE
      1.000      0.000   -1.000    0.000    0.000     0.000     0.000    0.000    0.000    0.000

J3      1.000    10.000    11.000    12.000    14.000     8.000     4.000     0.000     0.000     0.000
NC       .050      .040      .030      .300      .500     0.000     0.000     0.000     0.000     0.000
QT      4.000   580.000   890.000  1020.000  1385.000     0.000     0.000     0.000     0.000     0.000

X1    600.000    31.000    20.000   103.000     0.000     0.000     0.000     0.000     0.000     0.000
GR    576.600     0.000   574.200     2.000   574.900    20.000   571.500    25.000   570.300    30.000
GR    569.000    35.000   567.900    40.000   567.300    45.000   566.800    50.000   566.700    55.000
GR    566.500    60.000   566.800    65.000   567.100    70.000   567.100    75.000   569.100    80.000
GR    569.100    85.000   569.100    90.000   570.100    95.000   572.400   101.000   573.500   103.000
GR    573.900   115.000   572.400   117.000   570.600   125.000   573.100   132.000   574.900   135.000
GR    573.300   220.000   573.400   320.000   575.900   420.000   575.300   520.000   574.700   620.000
GR    575.100   680.000     0.000     0.000     0.000     0.000     0.000     0.000     0.000     0.000

X1   1100.000    25.000   300.000   320.000   500.000   500.000   500.000     0.000     0.000     0.000
X3      0.000     0.000     0.000   200.000     0.000   500.000     0.000     0.000     0.000     0.000
GR    574.300     0.000   574.600   100.000   574.400   200.000   576.100   300.000   566.900   300.000
GR    566.300   302.000   565.700   304.000   565.400   305.000   565.600   306.000   566.200   310.000
GR    565.200   314.000   565.000   315.000   565.000   316.000   564.900   318.000   564.800   320.000
GR    576.100   320.000   574.500   400.000   574.300   500.000   574.600   600.000   576.400   700.000
GR    576.500   800.000   575.100   900.000   574.300  1000.000   574.400  1100.000   574.400  1200.000
NC       .018      .018      .018     0.000     0.000     0.000     0.000     0.000     0.000     0.000

X1   1101.000     0.000     0.000     0.000     1.000     1.000     1.000     0.000     0.000     0.000
X3      0.000     0.000     0.000   200.000     0.000   500.000     0.000     0.000     0.000     0.000
BT     23.000     0.000   574.300     0.000   100.000   574.600     0.000   200.000   574.400     0.000
BT    300.000   576.100   567.500   302.000   576.100   571.500   304.000   576.100   573.500   305.000
BT    576.100   574.000   306.000   576.100   574.500   310.000   576.100   575.500   314.000   576.100
BT    574.500   315.000   576.100   574.000   316.000   576.100   573.500   318.000   576.100   571.500
BT    320.000   576.100   567.500   400.000   574.500     0.000   500.000   574.300     0.000   600.000
BT    574.600     0.000   700.000   576.400     0.000   800.000   576.500     0.000   900.000   575.100
BT      0.000  1000.000   574.300     0.000  1100.000   574.400     0.000  1200.000   574.400     0.000

X1   1127.000    25.000   300.000   320.000    26.000    26.000    26.000     0.000     0.000     0.000
X3      0.000     0.000     0.000   200.000     0.000   500.000     0.000     0.000     0.000     0.000
BT     23.000     0.000   574.300     0.000   100.000   574.600     0.000   200.000   574.400     0.000
BT    300.000   576.100   567.500   302.000   576.100   571.500   304.000   576.100   573.500   305.000
BT    576.100   574.000   306.000   576.100   574.500   310.000   576.100   575.500   314.000   576.100
BT    574.500   315.000   576.100   574.000   316.000   576.100   573.500   318.000   576.100   571.500
BT    320.000   576.100   567.500   400.000   574.500     0.000   500.000   574.300     0.000   600.000
BT    574.600     0.000   700.000   576.400     0.000   800.000   576.500     0.000   900.000   575.100
BT      0.000  1000.000   574.300     0.000  1100.000   574.400     0.000  1200.000   574.400     0.000
```

Rec'd
Looks reasonable
8/17/77

8/11/77
IGC datum
+ 1.43 ft. - USGS

GR	574.300	0.000	574.600	100.000	574.400	200.000	576.100	300.000	566.900	300.000
GR	566.300	302.000	565.700	304.000	565.400	305.000	565.600	306.000	566.200	310.000
GR	565.200	314.000	565.000	315.000	565.000	316.000	564.900	318.000	564.800	320.000
GR	576.100	320.000	574.500	400.000	574.300	500.000	574.600	600.000	576.400	700.000
GR	576.500	800.000	575.100	900.000	574.300	1000.000	574.400	1100.000	574.400	1200.000
NC	.050	.050	.030	0.000	0.000	0.000	0.000	0.000	0.000	0.000
X1	1128.000	0.000	0.000	0.000	1.000	1.000	1.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	200.000	0.000	500.000	0.000	0.000	0.000	0.000
X1	1178.000	23.000	35.000	136.000	50.000	50.000	50.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	25.000	0.000	145.000	0.000	0.000	0.000	0.000
GR	576.800	0.000	574.000	3.000	573.500	35.000	572.400	36.000	571.000	40.000
GR	569.600	45.000	567.700	50.000	566.600	55.000	566.200	60.000	566.200	75.000
GR	568.000	95.000	568.800	105.000	569.400	115.000	569.700	120.000	570.400	125.000
GR	570.900	130.000	572.400	135.000	573.400	136.000	573.200	235.000	574.600	335.000
GR	576.200	440.000	575.600	535.000	575.900	635.000	0.000	0.000	0.000	0.000
X1	1628.000	28.000	11.000	219.000	450.000	450.000	450.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
GR	576.400	0.000	573.600	1.000	573.500	11.000	572.500	14.000	572.200	16.000
GR	571.500	21.000	570.900	26.000	570.700	31.000	570.500	36.000	570.000	41.000
GR	569.600	61.000	569.300	81.000	569.200	111.000	568.300	131.000	567.600	151.000
GR	568.900	171.000	569.500	181.000	569.700	191.000	570.300	201.000	571.500	211.000
GR	572.500	214.000	574.100	219.000	576.800	311.000	575.300	426.000	576.100	511.000
GR	576.000	611.000	574.700	711.000	577.300	786.000	0.000	0.000	0.000	0.000
NC	.055	.055	.035	0.000	0.000	0.000	0.000	0.000	0.000	0.000
X1	2428.000	41.000	72.000	262.000	800.000	800.000	800.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
GR	576.700	0.000	574.000	2.000	573.100	72.000	570.700	73.000	570.500	77.000
GR	570.500	82.000	570.500	87.000	570.600	92.000	570.300	97.000	570.300	102.000
GR	570.300	112.000	570.200	122.000	570.100	132.000	570.000	142.000	569.900	152.000
GR	569.500	162.000	569.300	172.000	568.700	182.000	567.900	192.000	567.600	197.000
GR	567.900	202.000	567.200	207.000	567.500	212.000	567.700	217.000	568.500	222.000
GR	569.400	227.000	570.200	232.000	570.400	237.000	570.400	242.000	570.700	247.000
GR	569.700	252.000	570.200	257.000	571.000	259.000	574.300	262.000	575.400	372.000
GR	575.300	472.000	576.300	572.000	577.000	672.000	577.100	772.000	576.400	872.000
GR	576.400	897.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
X1	3228.000	27.000	800.000	853.000	800.000	800.000	800.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
GR	574.700	0.000	577.300	100.000	576.000	200.000	575.500	300.000	576.600	400.000
GR	576.800	500.000	577.000	600.000	576.300	700.000	576.000	800.000	572.800	803.000
GR	571.900	807.000	569.900	810.000	568.400	815.000	567.600	820.000	567.500	825.000
GR	567.900	830.000	568.700	835.000	570.200	840.000	571.800	843.000	573.300	850.000
GR	579.000	853.000	579.600	880.000	578.700	900.000	578.500	1000.000	578.900	1042.000
GR	575.000	1054.000	577.400	1094.000	0.000	0.000	0.000	0.000	0.000	0.000
QT	4.000	580.000	610.000	615.000	635.000	0.000	0.000	0.000	0.000	0.000
X1	3778.000	27.000	800.000	855.000	450.000	600.000	550.000	0.000	0.000	0.000
GR	579.600	0.000	580.300	100.000	579.500	200.000	576.700	300.000	577.900	400.000
GR	577.600	500.000	577.100	600.000	577.200	700.000	575.200	800.000	570.600	801.000
GR	569.500	805.000	568.400	810.000	568.000	815.000	567.800	820.000	567.200	825.000
GR	569.000	830.000	569.900	835.000	570.600	840.000	571.200	845.000	572.300	847.000
GR	573.400	850.000	574.400	855.000	575.400	900.000	574.700	981.000	573.000	995.000
GR	573.800	1000.000	575.300	1037.000	0.000	0.000	0.000	0.000	0.000	0.000
X1	3828.000	29.000	1200.000	1225.000	50.000	50.000	50.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	1170.000	0.000	1400.000	0.000	574.650	574.650	0.000
GR	582.000	0.000	581.700	100.000	581.100	200.000	580.400	300.000	579.500	400.000
GR	578.400	500.000	577.400	600.000	576.400	700.000	575.400	800.000	575.000	900.000
GR	575.600	1000.000	576.400	1100.000	574.500	1120.000	569.500	1200.000	568.500	1205.000
GR	567.200	1210.000	567.100	1215.000	567.200	1220.000	568.100	1225.000	574.300	1290.000
GR	575.700	1300.000	575.100	1400.000	575.100	1500.000	575.300	1600.000	575.700	1700.000
GR	576.800	1800.000	577.200	1900.000	577.200	2000.000	577.200	2100.000	0.000	0.000

	NC	.018	.018	.015	0.000	0.000	0.000	0.000	0.000	0.000
	X1	3829.000	0.000	0.000	0.000	1.000	1.000	1.000	0.000	0.000	0.000
	X3	10.000	0.000	0.000	1170.000	0.000	1400.000	0.000	574.650	574.650	0.000
	SB	0.000	1.596	3.000	0.000	22.730	0.000	165.900	0.000	567.100	567.100
6											
1	X1	3884.000	0.000	0.000	0.000	55.000	55.000	55.000	0.000	0.000	0.000
2	X2	0.000	0.000	1.000	574.400	575.100	0.000	0.000	0.000	0.000	0.000
3	X3	10.000	0.000	0.000	1170.000	0.000	1400.000	0.000	575.100	575.100	0.000
4	BT	7.000	1170.000	577.100	0.000	1200.000	577.300	569.500	1200.000	577.300	574.400
5	BT	1225.000	577.300	574.400	1225.000	577.300	568.100	1300.000	575.700	0.000	1400.000
6	BT	575.100	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
7	NC	.080	.050	.032	0.000	0.000	0.000	0.000	0.000	0.000	0.000
8											
9	X1	3885.000	0.000	0.000	0.000	1.000	1.000	1.000	0.000	0.000	0.000
10	X3	10.000	0.000	0.000	1170.000	0.000	1400.000	0.000	575.100	575.100	0.000
11											
12	X1	4035.000	21.000	340.000	398.000	200.000	120.000	150.000	0.000	0.000	0.000
13	X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
14	GR	572.800	0.000	573.400	40.000	578.100	140.000	579.800	180.000	579.100	240.000
15	GR	576.000	340.000	572.300	356.000	569.600	356.000	568.400	360.000	567.600	365.000
16	GR	567.300	370.000	567.200	375.000	568.100	380.000	568.900	385.000	570.200	390.000
17	GR	572.000	395.000	572.300	396.000	573.500	398.000	574.100	440.000	575.100	540.000
18	GR	576.400	591.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
19											
20	X1	4265.000	26.000	1000.000	1018.000	250.000	1.000	230.000	.950	0.000	0.000
21	X3	10.000	0.000	0.000	0.000	0.000	1315.000	0.000	574.000	574.000	0.000
22	GR	578.500	0.000	578.900	100.000	579.700	200.000	580.500	300.000	581.300	400.000
23	GR	581.500	500.000	581.300	600.000	579.700	700.000	577.500	800.000	575.700	900.000
24	GR	575.000	950.000	567.900	1000.000	567.100	1005.000	567.000	1009.000	567.500	1015.000
25	GR	567.500	1018.000	575.000	1060.000	575.000	1100.000	575.200	1200.000	575.200	1300.000
26	GR	575.500	1400.000	575.800	1500.000	576.100	1600.000	576.500	1700.000	577.500	1800.000
27	GR	576.600	1900.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
28	NC	.018	.018	.015	0.000	0.000	0.000	0.000	0.000	0.000	0.000
29											
30	X1	4266.000	26.000	1000.000	1018.000	1.000	1.000	1.000	.950	0.000	0.000
31	X3	10.000	0.000	0.000	0.000	0.000	1315.000	0.000	574.000	574.000	0.000
32	GR	578.500	0.000	578.900	100.000	579.700	200.000	580.500	300.000	581.300	400.000
33	GR	581.500	500.000	581.300	600.000	579.700	700.000	577.500	800.000	575.700	900.000
34	GR	575.000	950.000	567.900	1000.000	567.100	1005.000	567.000	1009.000	567.500	1015.000
35	GR	567.500	1018.000	575.000	1060.000	575.000	1100.000	575.200	1200.000	575.200	1300.000
36	GR	575.500	1400.000	575.800	1500.000	576.100	1600.000	576.500	1700.000	577.500	1800.000
37	GR	576.600	1900.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
38	SB	0.000	1.610	3.000	0.000	16.170	0.000	95.400	0.000	567.000	567.000
39											
40	X1	4313.000	26.000	1000.000	1018.000	47.000	47.000	47.000	.950	0.000	0.000
41	X2	0.000	0.000	1.000	572.900	575.000	0.000	0.000	0.000	.950	0.000
42	X3	10.000	0.000	0.000	0.000	0.000	1315.000	0.000	575.000	575.000	0.000
43	BT	17.000	0.000	578.500	0.000	100.000	578.900	0.000	200.000	579.700	0.000
44	BT	300.000	580.500	0.000	400.000	581.300	0.000	500.000	581.500	0.000	600.000
45	BT	581.300	0.000	700.000	579.700	0.000	800.000	577.500	0.000	900.000	575.700
46	BT	0.000	1000.000	575.000	567.900	1000.000	575.000	572.900	1018.000	575.000	572.900
47	BT	1018.000	575.000	567.500	1100.000	575.000	0.000	1200.000	575.200	0.000	1315.000
48	BT	575.200	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
49	GR	578.500	0.000	578.900	100.000	579.700	200.000	580.500	300.000	581.300	400.000
50	GR	581.500	500.000	581.300	600.000	579.700	700.000	577.500	800.000	575.700	900.000
51	GR	575.000	950.000	567.900	1000.000	567.100	1005.000	567.000	1009.000	567.500	1015.000
52	GR	567.500	1018.000	575.000	1060.000	575.000	1100.000	575.200	1200.000	575.200	1315.000
53	GR	575.500	1400.000	575.800	1500.000	576.100	1600.000	576.500	1700.000	577.500	1800.000
54	GR	576.600	1900.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
55	NC	.080	.060	.035	0.000	0.000	0.000	0.000	0.000	0.000	0.000
56											
57	X1	4314.000	26.000	1000.000	1018.000	1.000	1.000	1.000	.950	0.000	0.000
	X3	10.000	0.000	0.000	0.000	0.000	1315.000	0.000	575.000	575.000	0.000
	GR	578.500	0.000	578.900	100.000	579.700	200.000	580.500	300.000	581.300	400.000
	GR	581.500	500.000	581.300	600.000	579.700	700.000	577.500	800.000	575.700	900.000

GR	575.000	950.000	567.900	1000.000	567.100	1005.000	567.000	1009.000	567.500	1015.000
GR	567.500	1018.000	575.000	1060.000	575.000	1100.000	575.200	1200.000	575.200	1300.000
GR	575.500	1400.000	575.800	1500.000	576.100	1600.000	576.500	1700.000	577.500	1800.000
GR	576.600	1900.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
NC	.045	.045	.035	0.000	0.000	0.000	0.000	0.000	0.000	0.000
X1	4524.000	16.000	270.000	330.000	210.000	210.000	210.000	0.000	0.000	0.000
GR	580.700	0.000	580.600	40.000	578.700	130.000	576.600	180.000	574.600	210.000
GR	573.800	250.000	573.800	270.000	571.300	275.000	567.600	300.000	571.500	325.000
GR	573.200	330.000	573.200	440.000	574.600	540.000	576.600	625.000	578.600	690.000
GR	578.600	710.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
X1	5024.000	14.000	540.000	605.000	500.000	500.000	500.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	453.000	0.000	687.000	0.000	0.000	0.000	0.000
GR	581.100	0.000	580.600	160.000	580.600	360.000	578.600	410.000	576.500	430.000
GR	575.000	460.000	575.000	540.000	572.300	545.000	567.700	570.000	572.300	595.000
GR	575.100	605.000	575.200	670.000	575.200	800.000	576.600	1160.000	0.000	0.000
X1	5524.000	16.000	640.000	755.000	500.000	500.000	500.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	550.000	0.000	780.000	0.000	0.000	0.000	0.000
GR	582.100	0.000	582.100	335.000	580.100	375.000	578.200	445.000	576.000	490.000
GR	574.200	520.000	574.200	635.000	574.100	640.000	571.100	650.000	567.200	670.000
GR	570.500	695.000	572.500	755.000	574.000	820.000	576.000	850.000	576.000	1250.000
GR	580.100	1320.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
X1	5924.000	12.000	675.000	725.000	400.000	400.000	400.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	625.000	0.000	817.000	0.000	0.000	0.000	0.000
GR	584.400	0.000	584.700	240.000	576.600	410.000	574.600	560.000	572.700	675.000
GR	566.600	700.000	572.600	725.000	574.600	800.000	576.700	840.000	576.700	1220.000
GR	580.600	1285.000	582.600	1400.000	0.000	0.000	0.000	0.000	0.000	0.000
X1	6024.000	21.000	435.000	510.000	100.000	100.000	100.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	418.000	0.000	528.000	0.000	0.000	0.000	0.000
GR	583.100	0.000	583.100	55.000	585.100	85.000	585.100	150.000	583.100	185.000
GR	578.300	220.000	576.300	240.000	575.300	310.000	575.300	425.000	575.200	435.000
GR	570.300	440.000	567.400	465.000	570.300	490.000	572.900	510.000	574.400	560.000
GR	576.500	570.000	578.500	600.000	578.500	675.000	576.600	740.000	576.600	825.000
GR	577.600	915.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
QT	4.000	595.000	620.000	625.000	645.000	0.000	0.000	0.000	0.000	0.000
X1	6199.000	30.000	1138.000	1162.000	175.000	175.000	175.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	975.000	0.000	1275.000	0.000	577.400	577.400	0.000
GR	582.600	0.000	583.600	400.000	584.600	800.000	585.000	980.000	585.200	1080.000
GR	582.000	1100.000	571.200	1138.000	569.600	1139.000	569.200	1140.000	569.200	1142.000
GR	569.700	1143.000	571.200	1144.000	571.200	1144.000	571.200	1147.000	571.200	1147.000
GR	569.700	1148.000	569.200	1149.000	569.200	1151.000	569.700	1152.000	571.200	1153.000
GR	571.200	1153.000	571.200	1156.000	571.200	1156.000	569.700	1157.000	569.200	1158.000
GR	569.200	1160.000	569.700	1161.000	571.200	1162.000	585.300	1200.000	585.500	1370.000
NC	.020	.020	.032	0.000	0.000	0.000	0.000	0.000	0.000	0.000
X1	6200.000	0.000	0.000	0.000	1.000	1.000	1.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	975.000	0.000	1275.000	0.000	577.400	577.400	0.000
SB	0.000	3.490	3.000	0.000	14.140	0.000	84.820	0.000	569.200	569.200
X1	6290.000	0.000	0.000	0.000	90.000	90.000	90.000	0.000	0.000	0.000
X2	0.000	0.000	1.000	575.200	585.000	0.000	0.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	975.000	0.000	1275.000	0.000	585.000	585.000	0.000
BT	27.000	975.000	585.000	0.000	1080.000	585.200	0.000	1138.000	585.300	571.200
BT	1138.000	585.400	572.200	1139.000	585.400	574.700	1140.000	585.400	575.200	1142.000
BT	585.400	575.200	1143.000	585.400	574.700	1144.000	585.400	572.200	1144.000	585.400
BT	571.200	1147.000	585.400	571.200	1147.000	585.400	572.200	1148.000	585.400	574.700
BT	1149.000	585.400	575.200	1151.000	585.400	575.200	1152.000	585.400	574.700	1153.000
BT	585.400	572.200	1153.000	585.400	571.200	1156.000	585.400	571.200	1156.000	585.400
BT	572.200	1157.000	585.400	574.700	1158.000	585.400	575.200	1160.000	585.400	575.200
BT	1161.000	585.400	574.700	1162.000	585.400	572.200	1162.000	585.400	571.200	1275.000

NC	.050	.050	.035	0.000	0.000	0.000	0.000	0.000	0.0 0	0.000
X1	6291.000	0.000	0.000	0.000	1.000	1.000	1.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	975.000	0.000	1275.000	0.000	585.000	585.000	0.000
X1	6313.000	15.000	225.000	270.000	22.000	22.000	22.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	213.000	0.000	281.000	0.000	0.000	0.000	0.000
GR	587.500	0.000	587.400	60.000	587.300	70.000	577.700	115.000	576.300	125.000
GR	575.400	175.000	575.400	210.000	575.300	225.000	570.100	230.000	569.100	250.000
GR	570.200	270.000	572.200	275.000	574.400	365.000	576.600	605.000	576.600	695.000
X1	7013.000	15.000	220.000	295.000	700.000	700.000	700.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	0.000	0.000	415.000	0.000	0.000	0.000	0.000
GR	587.500	0.000	587.400	10.000	580.500	40.000	578.500	75.000	576.500	125.000
GR	576.500	160.000	576.400	220.000	572.000	230.000	569.000	250.000	571.300	270.000
GR	573.300	295.000	573.500	415.000	574.500	535.000	574.500	605.000	574.500	800.000
NC	.050	.050	.035	0.000	0.000	0.000	0.000	0.000	0.000	0.000
X1	7513.000	17.000	230.000	270.000	500.000	500.000	500.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	0.000	0.000	420.000	0.000	0.000	0.000	0.000
GR	587.700	0.000	587.600	10.000	581.600	30.000	581.600	55.000	580.600	90.000
GR	578.600	130.000	576.500	170.000	576.400	230.000	572.000	235.000	568.000	250.000
GR	571.000	265.000	574.700	270.000	573.700	430.000	573.600	735.000	574.600	860.000
GR	576.600	865.000	578.500	880.000	0.000	0.000	0.000	0.000	0.000	0.000
X1	8013.000	30.000	230.000	290.000	500.000	500.000	500.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	150.000	0.000	350.000	0.000	0.000	0.000	0.000
GR	587.900	0.000	587.800	10.000	577.900	45.000	577.900	115.000	576.900	150.000
GR	576.300	230.000	572.300	235.000	568.600	250.000	572.300	265.000	574.600	270.000
GR	574.800	275.000	576.800	280.000	578.800	290.000	576.900	300.000	574.800	305.000
GR	573.800	345.000	573.800	455.000	574.800	545.000	576.700	550.000	578.700	555.000
GR	579.100	575.000	578.500	595.000	574.700	600.000	574.700	680.000	579.400	690.000
GR	579.900	705.000	579.300	715.000	574.700	725.000	574.100	745.000	574.100	920.000
X1	8445.000	21.000	280.000	360.000	432.000	432.000	432.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	283.000	0.000	310.000	0.000	0.000	0.000	0.000
GR	582.700	0.000	582.700	30.000	580.600	100.000	578.600	140.000	576.700	175.000
GR	576.700	255.000	578.700	260.000	578.700	280.000	576.600	283.000	574.600	286.000
GR	573.200	289.000	573.200	292.000	568.600	300.000	573.300	310.000	573.400	315.000
GR	573.400	350.000	574.600	353.000	576.600	357.000	578.600	360.000	580.600	385.000
GR	580.600	600.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
X1	8473.000	18.000	415.000	427.500	28.000	28.000	28.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	581.900	581.900	0.000
GR	583.200	0.000	582.900	100.000	582.500	200.000	582.200	300.000	581.900	350.000
GR	577.400	400.000	569.100	412.000	569.100	415.000	569.000	415.000	569.000	419.000
GR	569.000	423.000	569.000	427.500	569.100	427.500	569.100	431.000	573.400	437.000
GR	581.900	470.000	581.400	587.000	581.100	837.000	0.000	0.000	0.000	0.000
NC	.018	.020	.031	0.000	0.000	0.000	0.000	0.000	0.000	0.000
X1	8474.000	0.000	0.000	0.000	1.000	1.000	1.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	581.900	581.900	0.000
SB	0.000	1.800	3.000	0.000	10.570	0.000	89.000	0.000	569.000	569.000
X1	8510.000	0.000	0.000	0.000	36.000	36.000	36.000	0.000	0.000	0.000
X2	0.000	0.000	1.000	577.400	581.900	0.000	0.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	581.900	581.900	0.000
BT	18.000	0.000	583.200	0.000	100.000	582.900	0.000	200.000	582.500	0.000
BT	300.000	582.200	0.000	400.000	581.900	0.000	400.000	581.900	0.000	412.000
BT	581.900	0.000	415.000	581.900	569.100	415.000	581.900	574.600	419.000	581.900
BT	577.400	423.000	581.900	577.400	427.500	581.900	574.600	427.500	581.900	569.100
BT	431.000	581.900	0.000	437.000	581.900	0.000	437.000	581.900	0.000	587.000
BT	581.400	0.000	837.000	581.100	0.000	0.000	0.000	0.000	0.000	0.000
NC	.050	.050	.035	0.000	0.000	0.000	0.000	0.000	0.000	0.000
X1	8511.000	0.000	0.000	0.000	1.000	1.000	1.000	0.000	0.000	0.000

X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	581.900	581.900	.000
QT	4.000	740.000	855.000	880.000	915.000	0.000	0.000	0.000	0.000	0.000
X1	8681.000	0.000	0.000	0.000	1.000	250.000	170.000	0.000	.500	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
X1	8851.000	9.000	400.000	415.000	250.000	1.000	170.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	584.200	584.200	0.000
GR	586.000	0.000	585.100	200.000	584.400	350.000	570.100	400.000	570.100	407.500
GR	570.100	415.000	584.100	455.000	584.000	615.000	583.900	815.000	0.000	0.000
NC	.018	.018	.015	0.000	0.000	0.000	0.000	0.000	0.000	0.000
X1	8852.000	0.000	0.000	0.000	1.000	1.000	1.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	584.200	584.200	0.000
SB	0.000	1.530	3.000	0.000	15.000	0.000	127.400	0.000	570.100	570.100
X1	8868.000	0.000	0.000	0.000	16.000	16.000	16.000	0.000	0.000	0.000
X2	0.000	0.000	1.000	578.600	584.200	0.000	0.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	584.200	584.200	0.000
BT	10.000	0.000	586.000	0.000	200.000	585.100	0.000	400.000	584.200	570.100
BT	400.000	584.200	578.600	407.500	584.200	578.600	415.000	584.200	578.600	415.000
BT	584.200	570.100	455.000	584.100	0.000	615.000	584.000	0.000	815.000	583.900
BT	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
NC	.050	.040	.030	0.000	0.000	0.000	0.000	0.000	0.000	0.000
X1	8869.000	0.000	0.000	0.000	1.000	1.000	1.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	584.200	584.200	0.000
X1	8874.000	0.000	0.000	0.000	5.000	5.000	5.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	395.000	0.000	420.000	0.000	0.000	0.000	0.000
QT	4.000	765.000	1010.000	1100.000	1350.000	0.000	0.000	0.000	0.000	0.000
X1	9177.000	15.000	282.000	318.000	303.000	303.000	303.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	0.000	0.000	565.000	0.000	0.000	0.000	0.000
GR	582.600	0.000	582.600	90.000	580.600	95.000	578.600	100.000	576.600	175.000
GR	575.400	267.000	575.400	277.000	575.300	282.000	572.600	285.000	569.700	300.000
GR	572.100	315.000	573.700	318.000	573.800	335.000	573.800	770.000	574.700	900.000
X1	9677.000	19.000	472.000	507.000	500.000	500.000	500.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	0.000	0.000	755.000	0.000	0.000	0.000	0.000
GR	584.700	0.000	584.700	130.000	582.600	200.000	580.600	240.000	578.600	280.000
GR	576.500	320.000	574.600	350.000	573.800	455.000	573.700	472.000	572.500	475.000
GR	569.500	490.000	572.000	504.000	573.500	507.000	573.600	512.000	573.600	890.000
GR	574.600	980.000	576.000	1130.000	576.700	1150.000	577.100	1190.000	0.000	0.000
X1	10177.000	21.000	640.000	680.000	500.000	500.000	500.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	0.000	0.000	927.000	0.000	0.000	0.000	0.000
GR	581.500	0.000	583.400	60.000	584.600	140.000	583.900	225.000	582.800	315.000
GR	580.600	355.000	578.600	380.000	576.600	400.000	574.600	420.000	573.900	630.000
GR	573.800	640.000	572.600	645.000	569.600	660.000	572.100	675.000	573.600	680.000
GR	573.700	690.000	573.700	1050.000	574.700	1130.000	576.700	1230.000	578.700	1255.000
GR	578.700	1360.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
X1	10622.000	14.000	435.000	460.000	445.000	445.000	445.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	100.000	0.000	714.000	0.000	0.000	0.000	0.000
GR	580.400	0.000	580.400	60.000	578.600	80.000	576.600	100.000	574.600	130.000
GR	573.700	410.000	573.600	435.000	569.300	450.000	573.700	460.000	573.800	475.000
GR	574.600	630.000	576.600	825.000	578.600	910.000	579.000	1030.000	0.000	0.000
QT	4.000	770.000	1015.000	1105.000	1365.000	0.000	0.000	0.000	0.000	0.000
X1	10654.000	22.000	410.000	432.000	32.000	32.000	32.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	0.000	0.000	680.000	0.000	0.000	0.000	0.000
GR	578.800	0.000	578.100	200.000	577.300	401.000	577.300	410.000	572.700	410.000
GR	570.700	412.000	570.700	414.000	570.700	416.000	570.700	416.000	570.700	418.000
GR	570.700	418.000	570.700	420.000	570.700	422.000	570.700	424.000	570.700	426.000
GR	570.70	428.000	570.700	430.000	572.700	432.000	577.300	432.000	577.300	450.000

GR	577.400	800.000	578.600	1000.000	0.000	0.000	0.000	0.000	0.000	0.000
NC	.020	.018	.012	0.000	0.000	0.000	0.000	0.000	0.000	0.000
NC	0.02	0.018	0.012							
X1	10655.000	0.000	0.000	0.000	1.000	1.000	1.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	0.000	0.000	680.000	0.000	0.000	0.000	0.000
BT	24.000	0.000	578.800	0.000	200.000	578.100	0.000	401.000	577.300	0.000
BT	401.000	577.300	0.000	406.000	577.300	0.000	410.000	577.300	572.700	412.000
BT	577.300	574.700	414.000	577.300	574.700	416.000	577.300	572.700	416.000	577.300
BT	570.700	418.000	577.300	570.700	418.000	577.300	572.700	420.000	577.300	574.700
BT	422.000	577.300	574.700	424.000	577.300	572.700	424.000	577.300	570.700	426.000
BT	577.300	570.700	426.000	577.300	572.700	428.000	577.300	574.700	430.000	577.300
BT	574.700	432.000	577.300	572.700	435.000	577.300	0.000	450.000	577.300	0.000
BT	680.000	577.350	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
X1	10693.000	0.000	0.000	0.000	38.000	38.000	38.000	0.000	0.000	0.000
X2	0.000	0.000	0.000	0.000	0.000	0.000	1.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	0.000	0.000	680.000	0.000	0.000	0.000	0.000
NC	.045	.045	.032	0.000	0.000	0.000	0.000	0.000	0.000	0.000
X1	10694.000	0.000	0.000	0.000	1.000	1.000	1.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	0.000	0.000	680.000	0.000	0.000	0.000	0.000
NC	.055	.055	.035	0.000	0.000	0.000	0.000	0.000	0.000	0.000
QT	4.000	580.000	890.000	1020.000	1385.000	0.000	0.000	0.000	0.000	0.000
X1	-3228.000	25.000	800.000	853.000	0.000	0.000	0.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
GR	574.700	0.000	577.300	100.000	576.000	200.000	575.500	300.000	576.600	400.000
GR	576.800	500.000	577.000	600.000	576.300	700.000	576.000	800.000	572.800	803.000
GR	571.900	807.000	569.900	810.000	568.400	815.000	567.600	820.000	567.500	825.000
GR	567.900	830.000	568.700	835.000	570.200	840.000	571.800	843.000	573.300	850.000
GR	579.000	853.000	579.600	880.000	578.700	900.000	578.500	1000.000	578.900	1042.000
NC	.020	.020	.018	0.000	0.000	0.000	0.000	0.000	0.000	0.000
QT	4.000	5.000	300.000	425.000	765.000	0.000	0.000	0.000	0.000	0.000
X1	3353.000	8.000	0.000	700.000	200.000	50.000	125.000	0.000	0.000	0.000
GR	575.100	0.000	575.100	100.000	575.300	200.000	575.700	300.000	576.800	400.000
GR	577.200	500.000	577.200	600.000	577.200	700.000	0.000	0.000	0.000	0.000
EJ	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000

```
**********************************************
HEC2 VERSION UPDATED JAN 1976
ERROR CORRECTIONS 01,02,03,04,05,06,07,08,09
MODIFICATIONS 52,53,54,55,56,57,58
**********************************************


T1       CITY OF GIBRALTER          5555-23-01      PM = RICHARD ZANOTTI
T2       100 YEAR FLOOD
T3          FRANK AND POET DRAIN

J1   ICHECK     INQ        NINV       IDIR       STRT       METRIC     HVINS      Q          WSEL       FQ
          0.        4.         0.         0.  0.000000       0.00       0.0         0.   573.100      0.000
J2   NPROF     IPLOT     PRFVS     XSECV     XSECH     FN        ALLDC     IBW       CHNIM     ITRACE
        3.000     0.000    -1.000     0.000     0.000     0.000     0.000     0.000     0.000     0.000
```

CCHV= .300 CEHV= .500

3265 DIVIDED FLOW

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST
	500' D/S FROM D/S FACE OF S. GIBRALTAR RD BRIDGE						SEC. A		
600.00	6.60	573.10	0.00	573.10	573.22	.12	0.00	0.00	574.90
1020.	0.	999.	21.	0.	362.	22.	0.	0.	573.50
0.00	0.00	2.76	.95	.050	.030	.040	0.000	566.50	22.65
.000425	0.	0.	0.	0	0	1	0.00	95.56	132.00

IGL Datum

3301 HV CHANGED MORE THAN HVINS

3470 ENCROACHMENT STATIONS=		200.0	500.0	TYPE=	1	TARGET=	300.000		
1100.00	8.44	573.24	0.00	0.00	573.94	.69	.43	.29	576.10
1020.	0.	1020.	0.	0.	152.	0.	3.	1.	576.10
.02	0.00	6.69	0.00	.050	.030	.040	.030	564.80	300.00
.002585	500.	500.	500.	2	0	1	0.00	20.00	320.00

NORMAL BRIDGE,NRD=23 MIN ELTRD= 574.30 MAX ELLC= 575.50

3470 ENCROACHMENT STATIONS= 200.0 500.0 TYPE= 1 TARGET= 300.000

D/S FACE OF S. GIBRALTAR RD BRIDGE, BS #1 SEC. B

CONCRETE ARCH BRIDGE, WITH HEADWALLS, NO WINGWALLS

LENGTH=26.4 FT., SPAN=20 FT.

1101.00	8.33	573.13	0.00	0.00	574.05	.92	.00	.11	576.10
1020.	0.	1020.	0.	0.	132.	0.	3.	1.	576.10
.02	0.00	7.70	0.00	.018	.018	.018	.030	564.80	300.00
.001820	1.	1.	1.	2	0	1	-17.78	20.00	320.00

NORMAL BRIDGE,NRD=23 MIN ELTRD= 574.30 MAX ELLC= 575.50

3470 ENCROACHMENT STATIONS=		200.0	500.0	TYPE=	1	TARGET=	300.000		
1127.00	8.39	573.19	0.00	0.00	574.10	.91	.05	.00	576.10
1020.	0.	1020.	0.	0.	133.	0.	3.	1.	576.10
.02	0.00	7.65	0.00	.018	.018	.018	.029	564.80	300.00
.001791	26.	26.	26.	0	0	1	-18.13	20.00	320.00

3470 ENCROACHMENT STATIONS= 200.0 500.0 TYPE= 1 TARGET= 300.000

1128.00	8.74	573.54	0.00	0.00	574.18	.64	.00	.08	576.10
1020.	0.	1020.	0.	0.	159.	0.	3.	1.	576.10
.02	0.00	6.43	0.00	.050	.030	.050	.029	564.80	300.00
.002322	1.	1.	1.	2	0	1	0.00	20.00	320.00

3301 HV CHANGED MORE THAN HVINS

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

3470 ENCROACHMENT STATIONS= 25.0 145.0 TYPE= 1 TARGET= 120.000

50' U/S FROM U/S FACE OF S. GIBRALTAR RD BRIDGE, VS #2 SEC. C

1178.00	8.13	574.33	0.00	0.00	574.38	.05	.02	.18	573.50
1020.	2.	1015.	3.	8.	593.	8.	4.	1.	573.40
.03	.27	1.71	.31	.050	.030	.050	.029	566.20	25.00
.000116	50.	50.	50.	2	0	1	0.00	120.00	145.00

500' U/S FROM U/S FACE OF S. GIBRALTAR RD BRIDGE, VS #3 SEC. D

1628.00	6.80	574.40	0.00	0.00	574.42	.02	.03	.01	573.50
1020.	2.	1018.	0.	9.	998.	2.	12.	3.	574.10
.15	.19	1.02	.06	.050	.030	.050	.030	567.60	.71
.000053	450.	450.	450.	2	0	1	0.00	228.65	229.37

1300' U/S OF S. GIBRALTAR RD BRIDGE, VS #4 SEC. E

2428.00	7.26	574.46	0.00	0.00	574.47	.02	.05	.00	573.10
1020.	15.	1005.	0.	64.	921.	1.	30.	7.	574.30
.36	.23	1.09	.05	.055	.035	.055	.032	567.20	1.66
.000083	800.	800.	800.	1	0	1	0.00	276.70	278.36

OVERBANK AREA ASSUMED NON-EFFECTIVE, ELLEA= 576.00 ELREA= 579.00

640' D/S FROM D/S FACE OF M. GIBRALTAR RD BRIDGE, VS #5 SEC. F

3228.00	6.98	574.48	0.00	0.00	574.79	.31	.17	.15	576.00
1020.	0.	1020.	0.	0.	229.	0.	41.	10.	579.00
.41	0.00	4.46	0.00	.055	.035	.055	.033	567.50	801.42
.001549	800.	800.	800.	2	0	1	0.00	49.20	850.62

3265 DIVIDED FLOW

50' D/S FROM D/S FACE OF M. GIBRALTAR RD BRIDGE, VS #6 SEC. G

3778.00	7.97	575.17	0.00	0.00	575.23	.06	.36	.07	575.20
615.	0.	586.	29.	0.	294.	77.	45.	12.	574.40
.49	0.00	2.00	.37	.055	.035	.055	.033	567.20	800.01

.000266	450.	550.	600.	2	0	1	0.00	197.43	1033.87

3265 DIVIDED FLOW

3470 ENCROACHMENT STATIONS=			1170.0	1400.0	TYPE=	1	TARGET=	230.000	
3828.00	8.12	575.22	0.00	0.00	575.25	.03	.01	.01	569.50
615.	115.	313.	187.	143.	186.	265.	46.	12.	568.10
.50	.80	1.68	.70	.055	.035	.055	.033	567.10	1170.00
.000110	50.	50.	50.	0	0	1	0.00	146.33	1400.00

3265 DIVIDED FLOW

3470 ENCROACHMENT STATIONS=			1170.0	1400.0	TYPE=	1	TARGET=	230.000	

D/S FACE OF M. GIBRALTAR RD BRIDGE, BS #7 SEC. H

CONCRETE BRIDGE, SINGLE SPAN, OPEN CONC. GUARD RAILING

LENGTH=55 FT. SPAN=25 FT.

3829.00	8.13	575.23	0.00	0.00	575.25	.02	.00	.00	569.50
615.	131.	272.	212.	144.	187.	266.	46.	12.	568.10
.50	.91	1.46	.80	.018	.015	.018	.033	567.10	1170.00
.000015	1.	1.	1.	1	0	1	0.00	147.47	1400.00

SPECIAL BRIDGE

SB	XK	XKOR	COFQ	RDLEN	BWC	BWP	BAREA	SS	ELCHU	ELCHD
	0.00	1.60	3.00	0.00	22.73	0.00	165.90	0.00	567.10	567.10

3265 DIVIDED FLOW

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

PRESSURE AND WEIR FLOW

EGPRS	EGLWC	H3	QWEIR	QPR	BAREA	ELLC	ELTRD	CLASS
575.57	575.25	0.00	23.	590.	166.	574.40	575.10	30.00

3470 ENCROACHMENT STATIONS=			1170.0	1400.0	TYPE=	1	TARGET=	230.000	
3884.00	8.43	575.53	0.00	0.00	575.54	.02	.29	0.00	569.50
615.	131.	264.	220.	153.	194.	303.	47.	12.	568.10
.51	.86	1.36	.73	.018	.015	.018	.033	567.10	1170.00
.000012	55.	55.	55.	1	0	3	0.00	201.51	1400.00

3269 DIVIDED FLOW

3470 ENCROACHMENT STATIONS= 1170.0 1400.0 TYPE= 1 TARGET= 230.000

3885.00	8.42	575.52	0.00	0.00	575.55	.03	.00	.00	569.50
615.	78.	327.	209.	153.	194.	302.	47.	12.	568.10
.51	.51	1.69	.69	.080	.032	.050	.033	567.10	1170.00
.000087	1.	1.	1.	1	0	1	0.00	200.36	1400.00

3280 CROSS SECTION 4035.00 EXTENDED 2.74 FEET

OVERBANK AREA ASSUMED NON-EFFECTIVE, ELLEA= 576.00 ELREA= 573.50

150' U/S FROM U/S FACE OF M. GIBRALTAR RD BRIDGE, VS #8 SEC. I

4035.00	8.33	575.53	0.00	0.00	575.57	.04	.02	.01	576.00
615.	0.	539.	76.	0.	304.	170.	48.	13.	573.50
.54	0.00	1.77	.45	.080	.032	.050	.033	567.20	342.00
.000169	200.	150.	120.	0	0	1	0.00	215.15	557.15

3470 ENCROACHMENT STATIONS= .0 1249.3 TYPE= 1 TARGET= 1314.999

4265.00	8.56	575.56	0.00	0.00	575.60	.04	.03	.00	567.90
615.	112.	320.	182.	206.	141.	275.	50.	13.	567.50
.57	.55	2.27	.66	.080	.032	.050	.033	567.00	864.65
.000145	250.	230.	1.	0	0	1	0.00	384.60	1249.25

3470 ENCROACHMENT STATIONS= .0 1249.3 TYPE= 1 TARGET= 1314.999

D/S FACE OF JEFFERSON AVE (RIVER RD) BRIDGE, BS #9 SEC. J

CONCRETE BOX CULVERT, HEADWALLS, NO WINGWALLS

LENGTH=47 FT., SPAN=18 FT.

4266.00	8.59	575.59	0.00	0.00	575.61	.02	.00	.01	567.90
615.	182.	247.	186.	208.	141.	283.	50.	13.	567.50
.57	.87	1.75	.66	.018	.015	.018	.033	567.00	862.74
.000019	1.	1.	1.	2	0	1	0.00	386.51	1249.25

SPECIAL BRIDGE

SB	XK	XKOR	COFQ	RDLEN	BWC	BWP	BAREA	SS	ELCHU	ELCHD
	0.00	1.61	3.00	0.00	16.17	0.00	95.40	0.00	567.00	567.00

PRESSURE AND WEIR FLOW

EGPRS	EGLWC	H3	QWEIR	QPR	BAREA	ELLC	ELTRD	CLASS
576.62	575.61	0.00	407.	209.	95.	572.90	575.00	30.00

3470 ENCROACHMENT STATIONS= 0 1249.3 TYPE= 1 TARGET= 1314.999

4313.00	8.68	575.68	0.00	0.00	575.71	.02	.10	0.00	567.90
615.	181.	241.	193.	217.	143.	311.	51.	14.	567.50
.59	.84	1.69	.62	.018	.015	.018	.033	567.00	856.10
.000017	47.	47.	47.	2	0	4	0.00	393.15	1249.25

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

3470 ENCROACHMENT STATIONS= .0 1249.3 TYPE= 1 TARGET= 1314.999

4314.00	8.67	575.67	0.00	0.00	575.72	.04	.00	.01	567.90
615.	124.	315.	176.	217.	143.	311.	51.	14.	567.50
.59	.57	2.20	.57	.080	.035	.060	.033	567.00	856.10
.000159	1.	1.	1.	0	0	1	0.00	393.15	1249.25

210' U/S FROM U/S FACE OF JEFFERSON RD BRIDGE, STA 10+00 SEC. K

4524.00	8.13	575.73	0.00	0.00	575.74	.01	.02	.01	573.80
615.	39.	365.	212.	110.	344.	489.	55.	16.	573.20
.66	.35	1.06	.43	.045	.035	.045	.033	567.60	193.01
.000062	210.	210.	210.	2	0	1	0.00	395.13	588.14

3470 ENCROACHMENT STATIONS= 453.0 687.0 TYPE= 1 TARGET= 234.000

710' U/S FROM U/S FACE OF JEFFERSON RD BRIDGE, STA 15+00 SEC. L

5024.00	8.07	575.77	0.00	0.00	575.81	.05	.05	.02	575.00
615.	27.	570.	18.	66.	320.	51.	63.	19.	575.10
.74	.41	1.78	.35	.045	.035	.045	.033	567.70	453.00
.000218	500.	500.	500.	1	0	1	0.00	234.00	687.00

3470 ENCROACHMENT STATIONS= 550.0 780.0 TYPE= 1 TARGET= 230.000

1210' U/S FROM U/S FACE OF JEFFERSON RD BRIDGE, STA 20+00 SEC. M

5524.00	8.66	575.86	0.00	0.00	575.87	.01	.04	.01	574.10
615.	48.	531.	37.	149.	603.	77.	70.	22.	572.50
.91	.32	.88	.48	.045	.035	.045	.033	567.20	550.00
.000048	500.	500.	500.	1	0	1	0.00	230.00	780.00

3470 ENCROACHMENT STATIONS= 625.0 817.0 TYPE= 1 TARGET= 192.000

275' D/S FROM D/S FACE OF MCLOUTH STEEL RR ENTRY, STA 24+00 SEC. N

5924.00	9.28	575.88	0.00	0.00	575.90	.02	.03	.01	572.70
615.	87.	429.	99.	138.	313.	185.	77.	24.	572.60
1.01	.63	1.37	.53	.045	.035	.045	.034	566.60	625.00
.000094	400.	400.	400.	2	0	1	0.00	192.00	817.00

3470 ENCROACHMENT STATIONS= 418.0 528.0 TYPE= 1 TARGET= 110.000

175' D/S FROM D/S FACE OF MCLOUTH STEEL RR ENTRY STA 25+00 SEC. O

6024.00	8.49	575.89	0.00	0.00	575.91	.02	.01	.00	575.20
615.	2.	583.	29.	10.	453.	49.	78.	24.	572.90
1.03	.22	1.29	.60	.045	.035	.045	.034	567.40	418.00
.000087	100.	100.	100.	0	0	1	0.00	110.00	528.00

3470 ENCROACHMENT STATIONS= 975.0 1275.0 TYPE= 1 TARGET= 300.000

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 577.40 ELREA= 577.40

6199.00	6.58	575.78	0.00	0.00	576.10	.32	.04	.15	571.20
625.	0.	625.	0.	0.	137.	0.	79.	24.	571.20
1.04	0.00	4.56	0.00	.045	.035	.045	.034	569.20	1138.00
.001797	175.	175.	175.	2	0	1	0.00	24.00	1174.34

3470 ENCROACHMENT STATIONS= 975.0 1275.0 TYPE= 1 TARGET= 300.000

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 577.40 ELREA= 577.40

D/S FACE OF MCLOUTH STEEL RR ENTRY BRIDGE, STA 26+75 SEC. P

3-72" CIRCULAR CMP CULVERTS, PROJECTED FROM FILL

LENGTH=90 FT.

6200.00	6.58	575.78	0.00	0.00	576.10	.32	.00	.00	571.20
625.	0.	625.	0.	0.	137.	0.	79.	24.	571.20
1.04	0.00	4.56	0.00	.020	.032	.020	.034	569.20	1138.00
.001501	1.	1.	1.	0	0	1	0.00	24.00	1174.34

SPECIAL BRIDGE

SB	XK	XKOR	COFQ	RDLEN	BWC	BWP	BAREA	SS	ELCHU	ELCHD
	0.00	3.49	3.00	0.00	14.14	0.00	84.82	0.00	569.20	569.20

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

PRESSURE FLOW

EGPRS	EGLWC	H3	QWEIR	QPR	BAREA	ELLC	ELTRD	CLASS
578.72	576.10	0.00	0.	625.	85.	575.20	585.00	10.00

3470 ENCROACHMENT STATIONS= 975.0 1275.0 TYPE= 1 TARGET= 300.000

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 585.00 ELREA= 585.00

6290.00	9.38	578.58	0.00	0.00	578.72	.15	2.62	0.00	571.20
625.	0.	625.	0.	0.	204.	0.	80.	25.	571.20
1.05	0.00	3.06	0.00	.020	.032	.020	.034	569.20	1138.00

$$\left[\left(\frac{625}{84.82}\right)^2/64.4\right](3.49) = H$$

$2.94' = H$

$EGWSEL_{D/S} = 575.78$

$+H = \underline{2.94}$

$EG = 578.72$

.000441	90.	90.	90.	2	0	1	0.00	24.00	1181.88

3470 ENCROACHMENT STATIONS= 975.0 1275.0 TYPE= 1 TARGET= 300.000

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 585.00 ELREA= 585.00

6291.00	9.38	578.58	0.00	0.00	578.72	.15	.00	.00	571.20
625.	0.	625.	0.	0.	204.	0.	80.	25.	571.20
1.05	0.00	3.06	0.00	.050	.035	.050	.034	569.20	1138.00
.000528	1.	1.	1.	0	0	1	0.00	24.00	1181.88

3280 CROSS SECTION 6313.00 EXTENDED 2.14 FEET

3470 ENCROACHMENT STATIONS= 213.0 281.0 TYPE= 1 TARGET= 68.000

22' U/S FROM U/S FACE OF MCLOUTH STEEL RR ENTRY, STA 27+90 SEC. Q

6313.00	9.64	578.74	0.00	0.00	578.76	.03	.00	.04	575.30
625.	21.	540.	63.	41.	395.	76.	80.	25.	570.20
1.06	.53	1.37	.83	.050	.035	.050	.034	569.10	213.00
.000061	22.	22.	22.	2	0	1	0.00	68.00	281.00

3280 CROSS SECTION 7013.00 EXTENDED 4.28 FEET

3470 ENCROACHMENT STATIONS= .0 415.0 TYPE= 1 TARGET= 414.999

722' U/S FROM U/S FACE OF MCLOUTH STEEL RR ENTRY, STA 34+90 SEC. R

7013.00	9.78	578.78	0.00	0.00	578.79	.00	.02	.01	576.40
625.	54.	339.	232.	285.	546.	646.	96.	28.	573.30
1.46	.19	.62	.36	.050	.035	.050	.034	569.00	70.03
.000015	700.	700.	700.	2	0	1	0.00	344.97	415.00

3280 CROSS SECTION 7513.00 EXTENDED .30 FEET

3470 ENCROACHMENT STATIONS= .0 420.0 TYPE= 1 TARGET= 419.999

960' D/S FROM D/S FACE OF D.T.S.L. RR BRIDGE, STA 39+90 SEC. S

7513.00	10.79	578.79	0.00	0.00	578.80	.01	.01	.00	576.40
625.	48.	278.	298.	191.	324.	685.	111.	32.	574.70
1.69	.25	.86	.44	.050	.035	.050	.034	568.00	126.04
.000028	500.	500.	500.	1	0	1	0.00	293.96	420.00

3280 CROSS SECTION 8013.00 EXTENDED 4.71 FEET

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

3470 ENCROACHMENT STATIONS= 150.0 350.0 TYPE= 1 TARGET= 200.000

460' D/S FROM D/S FACE OF D.T.S.L. RR BRIDGE, STA 44+90 SEC. T

8013.00	10.21	578.81	0.00	0.00	578.83	.01	.02	.00	576.30
625.	77.	393.	155.	177.	346.	230.	123.	34.	578.80
1.83	.44	1.14	.67	.050	.035	.050	.034	568.60	150.00
.000075	500.	500.	500.	0	0	1	0.00	200.00	350.00

3470 ENCROACHMENT STATIONS= 283.0 310.0 TYPE= 1 TARGET= 27.000

28' D/S FROM D/S FACE OF D.T.S.L. RR BRIDGE, STA 49+22 SEC. U

8445.00	10.20	578.80	0.00	0.00	578.98	.18	.08	.08100000.00	
625.	0.	625.	0.	0.	183.	0.	127.	36.	100000.00
1.87	0.00	3.42	0.00	.050	.035	.050	.034	568.60	283.00
.000795	432.	432.	432.	2	0	1	0.00	27.00	310.00

OVERBANK AREA ASSUMED NON-EFFECTIVE, ELLEA= 581.90 ELREA= 581.90

8473.00	9.72	578.72	0.00	0.00	579.13	.41	.03	.11	569.10
625.	0.	625.	0.	0.	121.	0.	127.	36.	569.10
1.87	0.00	5.15	0.00	.050	.035	.050	.034	569.00	415.00
.001534	28.	28.	28.	2	0	1	0.00	12.50	427.50

OVERBANK AREA ASSUMED NON-EFFECTIVE, ELLEA= 581.90 ELREA= 581.90

D/S FACE OF D.T.S.L. RR BRIDGE, STA 49+50 SEC. V

101"X161" STRUCTL PLATE ARCH CULVERT, HEADWALLS, NO WINGWALLS

LENGTH=36 FT.

8474.00	9.72	578.72	0.00	0.00	579.13	.41	.00	.00	569.10
625.	0.	625.	0.	0.	121.	0.	127.	36.	569.10
1.87	0.00	5.14	0.00	.018	.031	.020	.034	569.00	415.00
.001203	1.	1.	1.	0	0	1	0.00	12.50	427.50

SPECIAL BRIDGE

SB	XK	XKOR	COFQ	RDLEN	BWC	BWP	BAREA	SS	ELCHU	ELCHD
	0.00	1.80	3.00	0.00	10.57	0.00	89.00	0.00	569.00	569.00

PRESSURE FLOW

EGPRS	EGLWC	H3	QWEIR	QPR	BAREA	ELLC	ELTRD	CLASS
580.10	579.13	0.00	0.	625.	89.	577.40	581.90	10.00

OVERBANK AREA ASSUMED NON-EFFECTIVE, ELLEA= 581.90 ELREA= 581.90

8510.00 10.76 578.76 0.00 0.00 580.10 .34 .07 0.00 569.10

	625.	0.	625.	0.	0.	135.	0.	127.	36.	569.10
	1.87	0.00	4.65	0.00	.018	.031	.020	.034	569.00	415.00
	.000910	36.	36.	36.	2	0	1	0.00	12.50	427.50

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 581.90 ELREA= 581.90

8511.00	10.76	579.76	0.00	0.00	580.10	.34	.00	.00	569.10
625.	0.	625.	0.	0.	135.	0.	127.	36.	569.10
1.87	0.00	4.64	0.00	.050	.035	.050	.034	569.00	415.00
.001159	1.	1.	1.	0	0	1	0.00	12.50	427.50

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST
8681.00	10.64	580.14	0.00	0.00	580.24	.10	.07	.07	569.60
880.	198.	435.	247.	136.	133.	163.	128.	36.	569.60
1.89	1.45	3.27	1.52	.050	.035	.050	.034	569.50	375.12
.000259	1.	170.	250.	2	0	1	0.00	86.10	461.22

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 584.20 ELREA= 584.20

8851.00	9.89	579.99	0.00	0.00	580.54	.55	.08	.22	570.10
880.	0.	880.	0.	0.	148.	0.	129.	36.	570.10
1.90	0.00	5.93	0.00	.050	.035	.050	.034	570.10	400.00
.001340	250.	170.	1.	2	0	1	0.00	15.00	443.27

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 584.20 ELREA= 584.20

D/S FACE OF PENN CENTRAL RR BRIDGE, STA 53+30 SEC. W

104"X180" CONCRETE BOX CULVERT, HEADWALL & WINGWALLS

LENGTH=16 FT.

8852.00	9.89	579.99	0.00	0.00	580.54	.55	.00	.00	570.10
880.	0.	880.	0.	0.	148.	0.	129.	36.	570.10
1.90	0.00	5.93	0.00	.018	.015	.018	.034	570.10	400.00
.000246	1.	1.	1.	0	0	1	0.00	15.00	443.27

SPECIAL BRIDGE

SB	XK	XKOR	COFQ	RDLEN	BWC	BWP	BAREA	SS	ELCHU	ELCHD
	0.00	1.53	3.00	0.00	15.00	0.00	127.40	0.00	570.10	570.10

PRESSURE FLOW

EGPRS	EGLWC	H3	QWEIR	QPR	BAREA	ELLC	ELTRD	CLASS
581.13	580.54	0.00	0.	880.	127.	578.60	584.20	10.00

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 584.20 ELREA= 584.20

8868.00	10.55	580.65	0.00	0.00	581.13	.48	.59	0.00	570.10
880.	0.	880.	0.	0.	158.	0.	129.	36.	570.10
1.90	0.00	5.56	0.00	.018	.015	.018	.034	570.10	400.00
.000206	16.	16.	16.	2	0	1	0.00	15.00	445.14

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 584.20 ELREA= 584.20

8869.00	10.55	580.65	0.00	0.00	581.13	.48	.00	.00	570.10
880.	0.	880.	0.	0.	158.	0.	129.	36.	570.10
1.90	0.00	5.56	0.00	.050	.030	.040	.034	570.10	400.00
.000823	1.	1.	1.	0	0	1	0.00	15.00	445.14

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

3470 ENCROACHMENT STATIONS= 395.0 420.0 TYPE= 1 TARGET= 25.000

8874.00	10.92	581.02	0.00	0.00	581.22	.19	.00	.09	570.10
880.	111.	636.	133.	51.	164.	50.	129.	36.	570.10
1.90	2.17	3.88	2.65	.050	.030	.040	.034	570.10	395.00
.000254	5.	5.	5.	2	0	1	0.00	25.00	420.00

3280 CROSS SECTION 9177.00 EXTENDED 6.58 FEET

3470 ENCROACHMENT STATIONS= .0 565.0 TYPE= 1 TARGET= 564.999

310' U/S FROM U/S FACE OF PENN CENTRAL BRIDGE, STA 56+55 SEC. X

9177.00	11.58	581.28	0.00	0.00	581.28	.00	.01	.06	575.30
1100.	192.	208.	700.	858.	355.	1847.	141.	38.	573.70
2.12	.22	.59	.38	.050	.030	.040	.034	569.70	93.31
.000007	303.	303.	303.	2	0	1	0.00	471.69	565.00

3280 CROSS SECTION 9677.00 EXTENDED 4.18 FEET

3470 ENCROACHMENT STATIONS= .0 755.0 TYPE= 1 TARGET= 754.999

810' U/S FROM U/S FACE OF PENN CENTRAL BRIDGE, STA 61+55 SEC. Y

9677.00	11.78	581.28	0.00	0.00	581.28	.00	.00	.00	573.70
1100.	288.	182.	630.	1264.	352.	1905.	179.	43.	573.50
2.53	.23	.52	.33	.050	.030	.040	.034	569.50	226.40
.000005	500.	500.	500.	2	0	1	0.00	528.60	755.00

3280 CROSS SECTION 10177.00 EXTENDED 2.58 FEET

3470 ENCROACHMENT STATIONS= 0 927.0 TYPE= 1 TARGET= 926.999

477 FT. D/S FROM D/S FACE OF VREELAND RD BRIDGE, STA 66+55 SEC. Z

10177.00	11.68	581.28	0.00	0.00	581.28	.00	.00	.00	573.80
1100.	379.	177.	544.	1785.	392.	1874.	222.	50.	573.60
3.01	.21	.45	.29	.050	.030	.040	.033	569.60	342.58
.000004	500.	500.	500.	0	0	1	0.00	584.42	927.00

3280 CROSS SECTION 10622.00 EXTENDED 2.29 FEET

3470 ENCROACHMENT STATIONS= 100.0 714.0 TYPE= 1 TARGET= 614.000

32' D/S FROM D/S FACE OF VREELAND RD BRIDGE, STA 71+00 SEC. AA

10622.00	11.99	581.29	0.00	0.00	581.29	.00	.00	.00	573.60
1100.	521.	108.	470.	2359.	245.	1737.	265.	56.	573.70
3.48	.22	.44	.27	.050	.030	.040	.033	569.30	100.00
.000004	445.	445.	445.	0	0	1	0.00	614.00	714.00

3280 CROSS SECTION 10654.00 EXTENDED 2.69 FEET

3470 ENCROACHMENT STATIONS= .0 680.0 TYPE= 1 TARGET= 679.999

10654.00	10.58	581.28	0.00	0.00	581.29	.00	.00	.00	577.30
1105.	437.	209.	460.	1324.	229.	981.	268.	56.	577.30
3.50	.33	.91	.47	.050	.030	.040	.033	570.70	.00
.000025	32.	32.	32.	0	0	1	0.00	680.00	680.00

3280 CROSS SECTION 10655.00 EXTENDED 2.69 FEET

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

NORMAL BRIDGE,NRD=24 MIN ELTRD= 577.30 MAX ELLC= 574.70

3470 ENCROACHMENT STATIONS= .0 680.0 TYPE= 1 TARGET= 679.999

D/S FACE OF VREELAND RD BRIDGE, STA 71+33 SEC. BB

3-72" CIRCULAR CONCRETE CULVERT, PROJECTED FROM FILL

LENGTH=38 FT.

10655.00	10.59	581.29	0.00	0.00	581.29	.00	.00	.00	577.30
1105.	536.	67.	502.	1324.	144.	981.	268.	56.	577.30
3.50	.41	.47	.51	.020	.012	.018	.033	570.70	.00
.000006	1.	1.	1.	0	0	1	-85.20	680.00	680.00

3280 CROSS SECTION 10693.00 EXTENDED 2.69 FEET

NORMAL BRIDGE,NRD=24 MIN ELTRD= 577.30 MAX ELLC= 574.70

3470 ENCROACHMENT STATIONS= .0 680.0 TYPE= 1 TARGET= 679.999

10693.00	10.59	581.29	0.00	0.00	581.29	.00	.00	.00	577.30
1105.	536.	67.	502.	1324.	144.	981.	270.	57.	577.30
3.52	.41	.47	.51	.020	.012	.018	.033	570.70	.00
.000006	38.	38.	38.	0	0	1	-85.20	680.00	680.00

3280 CROSS SECTION 10694.00 EXTENDED 2.69 FEET

3470 ENCROACHMENT STATIONS= .0 680.0 TYPE= 1 TARGET= 679.999

10694.00	10.59	581.29	0.00	0.00	581.29	.00	.00	.00	577.30
1105.	492.	198.	414.	1324.	229.	981.	270.	57.	577.30
3.52	.37	.87	.42	.045	.032	.045	.033	570.70	.00
.000026	1.	1.	1.	0	0	1	0.00	680.00	680.00

START TRIB COMP
-3228.000 3228.000 57448.482 574.485

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 576.00 ELREA= 579.00

SECTION F, USED AS STARTING SECTION OF "TRIBUTARY"

-3228.00	6.98	574.48	0.00	0.00	574.79	.31	0.00	0.00	576.00
1020.	0.	1020.	0.	0.	229.	0.	270.	57.	579.00
3.52	0.00	4.46	0.00	.055	.035	.055	.033	567.50	801.42
.001549	0.	0.	0.	0	0	1	0.00	49.20	850.62

3685 20 TRIALS USED WSEL,CWSEL

7185 MIN SPECIFIC ENERGY

3720 ASSUMED CRITICAL DEPTH

3280 CROSS SECTION 3353.00 EXTENDED .56 FEET

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

SOUTH PART OF SECTION H, (FROM INTERSECTION OF JEFFERSON AVE.

AND M. GIBRALTAR RD)

3353.00	.56	575.66	575.66	0.00	575.86	.21	.27	0.00	575.10
425.	0.	425.	0.	0.	117.	0.	270.	57.	577.20
3.53	0.00	3.64	0.00	.020	.018	.020	.033	575.10	0.00
.006496	200.	125.	50.	30	23	1	0.00	288.88	288.88

00BREAK00

1) COUNTY: Wayne

2) STUDY NAME: City of Gibralter

3) WATERCOURSE: Frank + Poet Drain, Brownstown Creek

4) DOCUMENT TYPE: Report

00BREAK00

HYDRAULIC ANALYSIS

Introduction

The streams being investigated are the Frank and Poet Drain and the Brownstown Creek in the City of Gibraltar, Wayne County, Michigan. The Frank and Poet Drain passes through the Detroit Metropolitan Wayne County Airport, the Township of Romulus and the cities of Taylor, Southgate, Riverview, Trenton, and Gibraltar before finally discharging into Lake Erie. The Brownstown Creek passes through Romulus Township, Huron Township, the City of Southgate, Brownstown Township, the City of Woodhaven, and finally the City of Gibraltar before discharging into Lake Erie.

For the Frank and Poet Drain, the study starts 500 feet downstream of the South Gibraltar Road Bridge and proceeds north to Vreeland Road, covering a distance of 2.03 miles. For the Brownstown Creek, the study starts 500 feet downstream of the South Gibraltar Road Bridge and proceeds northeast to Penn Central Railroad Bridge No. 2, about 700 feet downstream from the northwestern corporate boundary.

The 10-, 50-, 100- and 500-year flood frequency flows beyond the corporate boundary of the City of Gibraltar were calculated by Brater's unit hydrograph-infiltration capacity method after adjusting the slenderness ratio of the basin for the retention patterns from Detroit Metropolitan Wayne County Airport. The flows beyond the corporate boundary have been approved by the Michigan Department of Natural Resources. Within the corporate boundary, the flows were determined by combining the TR-20 computer program and HEC-2 computer program to take the following effects into consideration (by trial and error method):

1. Storage effect beyond Vreeland Road at Frank and Poet Drain

2. Storage effect beyond Penn Central Railroad Bridge #2 at Brownstown Creek

3. Storage effect between Penn Central Railroad Bridge #1 and Penn Central Railroad Bridge #2 at Brownstown Creek

4. Flow division from Frank and Poet Drain to Brownstown Creek at upstream side of Penn Central Railroad Bridge #1

5. Flow division from Frank and Poet Drain to Brownstown Creek between Penn Central Railroad Bridge #1 and Detroit & Toledo Shoreline Railroad

6. Flow division from Brownstown Creek to Frank and Poet Drain downstream of Middle Gibraltar Road

Method of Analysis

The flood profiles were determined by the HEC-2 computer program developed by the U.S. Corps of Engineers (Reference 3). All bridges have been modeled by the requirements of the HEC-2 normal and special bridge routines with emphasis placed on the 100-year event.

Variables and Coefficients

The roughness factors (Manning's "n") were established by comparison of photographs and descriptions found on pages 101 to 123, in Ven Te Chow's Open-Channel Hydraulics (Reference 1), with photographs and field descriptions taken in Gibraltar by survey crews in October, 1975. To reflect the generally gradual changes in cross-section geometry, the contraction and expansion coefficients used in this study were .3 and .5, respectively.

The inlet loss coefficients and outlet loss coefficients used in this study were taken from Hydraulic Charts for the Selection of Highway Culverts (Reference 2). The weir discharge coefficients were taken from charts of

the U.S. Geological Survey (Reference 4) and Bureau of Public Roads (Reference 5) supplied by the Michigan Department of Natural Resources.

Starting Conditions

The profile computations for both the Frank and Poet Drain and Brownstown Creek began 500 feet downstream from South Gibraltar Road. These two starting sections are so close to Lake Erie that the starting elevations were assumed to be the mean flood elevation as calculated by a gage analysis done by Johnson & Anderson, Inc., which is 573.10 International Great Lakes Datum (IGLD).

Stationing was recorded as river feet from the confluence of the two streams at Lake Erie, and all elevations used in this study are based on IGLD datum of 1929. In the final Flood Insurance Report, the 10-, 50-, 100- and 500-year lake elevations will be extended horizontally upstream until the corresponding profiles are intersected.

Discussion of Special Problems and Methods

1. Within the corporate boundaries, four separate areas are proposed to be filled. The areas are situated on property owned by McLouth Steel Company. The property is bounded by Vreeland Road on the north, West Jefferson Avenue on the west, Middle Gibraltar Road on the south, and Penn Central Railroad track No. 2 on the east. The total available fill volume is about 2,631,000 cubic yards. This study was based on the assumption that these areas are filled and the filled area is no longer available for storage. The dimensions were taken from plans provided by McLouth Steel Company.

2. Significant storage areas in the study occur upstream of Penn Central Railroad Bridge No. 1 on the Frank and Poet Drain and Penn Central Railroad Bridge No. 2 on the Brownstown Creek. The pool elevations herein were determined by both TR-20 and HEC-2 by iterative methods to ensure the elevations calculated by both programs matched each other.

3. The storage effect between the Penn Central Railroad Bridge No. 1 and No. 2 on the Brownstown Creek was not significant and is therefore included in the detailed study. The floodway was determined by expansion and contraction due to the culverts of both railroad embankments.

4. The criterion used for the three flow divisions is based upon TR-20 rating curves calibrated for various energy gradient elevations. This procedure was principally used at the Penn Central No. 2 and DTS&L Railroad tracks and downstream of Middle Gibraltar Road.

5. It is noted that those four filled areas within the corporate boundary completely change the flood situation of the basin. Both flood paths (divisions), discharges, and flood stages of the drains are quite different from the case without any filled areas. However, these differences are beyond the scope of this study and so are not investigated in detail.

6. Due to crossover of flow between drainage basins, areas have been designated as floodway without definite dimensions. This decision was made as a result of discussion with the Michigan Department of Natural Resources on March 24, 1977 (minutes by R. Zanotti are enclosed). These areas are located between Brownstown Creek and the Frank and Poet Drain bordered by fill areas #3 and #4 along the Penn Central and DTSL Railroad tracks and by North Gibraltar Road and River Road (Jefferson). Exact delineation will be made as these areas are developed.

References

1. Chow, Ven Te, Open-Channel Hydraulics, McGraw-Hill, 1959, pp. 101-123.

2. Herr, Lester A., Hydraulic Charts for the Selection of Highway Culverts, Hydraulic Engineering Circular No. 5, Bureau of Public Roads, U.S. Department of Commerce, Dec. 1965.

3. U.S. Army Corps of Engineers, Hydrologic Engineering Center, HEC-2 Water Surface Manual, User's Manual, Oct. 1973.

4. U.S. Geological Survey, Measurements of Peak Discharge at Dams by Indirect Methods, Book 3, Chapter A5, 1976.

5. Bureau of Public Roads, Hydraulics of Bridge Waterways, 1970.

6. Johnson & Anderson, Inc., "Great Lakes Flood Elevation, Harrisville to Toledo Gages," January, 1977 (unpublished report).

Frank & Poet Drain
City of Gibraltar
5555-23-1
MSC 2-28-66

Cross Section Locations

Cross Section	SECNO	Location
A	600	500' d/s from d/s face of S. Gibraltar Road bridge
B	1101	d/s face of S. Gibraltar Road bridge
C	1178	50' u/s from u/s face of S. Gibraltar Road bridge
D	1628	500' u/s from u/s face of S. Gibraltar Road bridge
E	2428	1300' u/s from u/s face of S. Gibraltar Road bridge
F	3228	600' d/s from d/s face of Gibraltar Road bridge
G	3778	50' d/s from d/s face of Gibraltar Road bridge
H	3829	d/s face of Gibraltar Road bridge
I	4035	150' u/s from u/s face of Gibraltar Road bridge
J	4266	d/s face of Jefferson Ave. (River Road) bridge
K	4524	210' u/s from u/s face of Jefferson Ave. bridge
L	5024	710' u/s from u/s face of Jefferson Ave. bridge
M	5524	1210' u/s from u/s face of Jefferson Ave. bridge
N	5924	275' d/s from d/s face of McLouth Steel RR entry bridge
O	6024	175' d/s from d/s face of McLouth Steel RR entry bridge
P	6200	d/s face of McLouth Steel RR entry bridge
Q	6313	22' u/s from u/s face of McLouth Steel entry bridge
R	7013	722' u/s from u/s face of McLouth Steel RR entry bridge
S	7513	960' d/s from d/s face of DTSL Railroad bridge
T	8013	460' d/s from d/s face of DTSL Railroad bridge
U	8445	280' d/s from d/s face of DTSL Railroad bridge

Cross Section	SECNO	Location
V	8474	d/s face of DTSL Railroad bridge
W	8852	d/s face of Penn Central Railroad bridge
X	9177	310' u/s from u/s face of Penn Central Railroad bridge
Y	9677	810' u/s from u/s face of Penn Central Railroad bridge
Z	10177	480' d/s from d/s face of Vreeland Road bridge
AA	10622	32' d/s from d/s face of Vreeland Road bridge
BB	10655	d/s face of Vreeland Road bridge

Cross Section Locations

Cross Section	SECNO	Location
A	1613	500' d/s from d/s face of S. Gibraltar Road bridge
B	2114	d/s face of S. Gibraltar Road bridge
C	2182	50' u/s from u/s face of S. Gibraltar Road bridge
D	2632	500' u/s from u/s face of S. Gibraltar Road bridge
E	2932	50' d/s from d/s face of Jefferson Ave. bridge
F	2983	d/s face of Jefferson Ave. bridge
G	3250	200' u/s from u/s face of Jefferson Ave. bridge
H	3750	700' u/s from u/s face of Jefferson Ave. bridge
I	4700	1650' u/s from u/s face of Jefferson Ave. bridge
J	5750	2700' u/s from u/s face of Jefferson Ave. bridge
K	6750	500' d/s from d/s face of Gibraltar Road bridge
L	7200	50' d/s from d/s face of Gibraltar Road bridge
M	7251	d/s face of Gibraltar Road bridge
N	7355	57' u/s from u/s face of Gibraltar Road bridge
O	7805	±510' u/s from u/s face of Gibraltar Road bridge
P	8305	±300' d/s from d/s face of DTSL Railroad bridge
Q	8606	d/s face of DTSL Railroad bridge
R	8816	±160' u/s from u/s face of DTSL Railroad bridge
S	9107	d/s face of Penn Central Railroad bridge
T	9264	135' u/s from u/s face of Penn Central RR bridge #1
U	9764	±635' u/s from u/s face of Penn Central RR bridge #1
V	10264	±1135' u/s from u/s face of Penn Central RR bridge #1
W	10764	±950' d/s from d/s face of Penn Central RR bridge #2

Cross Section	SECNO	Location
X	11264	±450' d/s from d/s face of Penn Central RR bridge #2
Y	11364	350' d/s from d/s face of Penn Central RR bridge #2
Z	11644	70' d/s from d/s face of Penn Central RR bridge
AA	11715	d/s face of Penn Central Railroad bridge
BB	9546	±730' East of Section R, between Penn Central #1 and DTSL Railroad
CC	10246	±1430' East of Section R, between Penn Central #1 and DTSL Railroad
DD	10846	±2030' East of Section R, between Penn Central #1 and DTSL Railroad
EE	11846	±3030' East of Section R, between Penn Central #1 and DTSL Railroad
FF	9594	±330' East of Section T, exact North of Penn Central Railroad #1
GG	10294	±1030' East of Section T, exact North of Penn Central Railroad #1
HH	10894	±1630 East of Section T, exact North of Penn Central Railroad #1
II	11894	±2630 East of Section T, exact North of Penn Central Railroad #1

Johnson & Anderson, Inc.
Consulting Engineers
P O Box 1166 2300 Dixie Highway Pontiac, Michigan 48056


HYDRAULIC STRUCTURAL DATA

Code No. 5555.22.01-1


Job Name: [illegible]			By: Mc [illegible]
Date: 9-30-75	Feature: [illegible]		Water Course: [illegible]
Remarks: [illegible] Bridge With Solid Conc. Railings			
			Photo Roll # 1 21-24
Width of Piers: 0	Pier Shape: —	No. of Piers: —	Area:
Water Elevation:	Length: 26.4'	Width of Deck: No Deck	Skew: 0°

FIELD SKETCH

Profile View



Plan View



Johnson & Anderson, Inc.
Consulting Engineers
P O Box 1166 2300 Dixie Highway Pontiac, Michigan 48056

B.C. 7

HYDRAULIC STRUCTURAL DATA


Downstream Lt.

Code No. 6555-75-01-7


Job Name: City of Gibraltar FTS Freeway & Port Drains		By: McIntee
Date: 10-1-75	Feature: North Gibraltar Trail Bridge.	Water Course: Freeway & Port Drains
Remarks: Conc. Bridge Surface Sound. Wing and Cut Off Walls Good. Rail 2'-0"-12" Ht.		
Width of Piers: —	Pier Shape: —	No. of Piers: Area:
Water Elevation:	Length: 25'	Width of Deck: 55' Skew: 0°

FIELD SKETCH

Profile View



Plan View



```
X1   ~~3968.00~~ 3829.00   29   1200.00   1225.00   1.00   1.00   1.00   1.000

BT    14.00  1100.00  576.40    0.00  1200.00  577.30  569.50  1200.00  577.30  574.40

BT  1225.00   577.30  574.40 1225.00   577.30  568.10 1300.00   575.70    0.00 1400.00
BT   575.40     0.00 1500.00  575.10     0.00 1600.00  575.30     0.00 1700.00  575.70
BT     0.00  1800.00  576.80    0.00  1900.00  577.20    0.00  2000.00  577.20    0.00
BT  2100.00   577.20    0.00

GR   582.00     0.00  581.70  100.00   581.10  200.00  580.40   300.00  579.50  400.00
GR   578.40   500.00  577.40  600.00   576.40  700.00  575.40   800.00  575.00  900.00
GR   575.60  1000.00  576.40 1100.00   574.50 1190.00  569.50  1200.00  568.50 1205.00
GR   567.20  1210.00  567.10 1215.00   567.20 1220.00  568.10  1225.00  574.30 1250.00
GR   575.70  1300.00  575.40 1400.00   575.10 1500.00  575.30  1600.00  575.70 1700.00
GR   576.80  1800.00  577.20 1900.00   577.20 2000.00  577.20  2100.00

**********LISTING OF TOP AND BOTTOM SECTIONS OF ORIFICE**********

1200.00 569.50 1200.00 574.40 1225.00 574.40 1225.00 568.10

1200.00 569.50 1205.00 568.50 1210.00 567.20 1215.00 567.10 1220.00 567.20
1225.00 568.10
********** LISTING OF COORDINATES OF ORIFICE**********

1200.00 569.50 1200.00 574.40 1225.00 574.40 1225.00 568.10 1220.00 567.20
1215.00 567.10 1210.00 567.20 1205.00 568.50 1200.00 569.50

ORIFICE AREA      165.9 WETTED PERIMETER      61.5  29.1/R**1.333      7.7692
```

A = 165.9 ft²
P = 61.5 ft.
R = A/P = 2.70 ft
L = 55 ft
n = 0.015 (Concrete with Sand Bottom)
Ke = 0.5 (No Wingwalls)
$K_f = 29.1 n^2 L / R^{4/3} = 7.7692 n^2 L = 0.096$
$\sum K = 1 + K_e + K_f = 1.596$
D = 7.3 ft
BWC = A/D = 22.73 ft

Johnson & Anderson, Inc.
Consulting Engineers
P. O. Box 1166 2300 Dixie Highway Pontiac, Michigan 48056

BS #9

HYDRAULIC STRUCTURAL DATA


DOWNSTREAM Lt

Code No. 5555-23-01-9


Job Name: CITY OF GIBRALTAR FIS			By: MCINNES
Date: 10-1-75	Feature: JEFFERSON ST BRIDGE		Water Course: FRANK & POST DRAIN
Remarks: CONC BOX CULV.			
			ROLL # 2 # 17-20
Width of Piers: —	Pier Shape: —	No. of Piers: —	Area: —
Water Elevation: 572.27	Length: 18'	Width of Deck: 47'	Skew: 0°

FIELD SKETCH

Profile View



Plan View



```
X1   ~~4266.00~~ 4266.00    26  1000.00  1018.00     1.00     1.00     1.00    0.950

BT      23.00      0.00   578.50      0.00   100.00   578.90      0.00   200.00   579.70      0.00

BT     300.00    580.50     0.00    400.00   581.30     0.00    500.00   581.50     0.00    600.00
BT     581.30      0.00   700.00    579.70     0.00   800.00    577.50     0.00   900.00    575.70
BT       0.00   1000.00   575.00    567.90  1000.00   575.00    572.90  1018.00   575.00    572.90
BT    1018.00    575.00   567.50   1100.00   575.00     0.00   1200.00   575.20     0.00   1300.00
BT     575.20      0.00  1400.00    575.50     0.00  1500.00    575.60     0.00  1600.00    576.10
BT       0.00   1700.00   576.50      0.00  1800.00   577.50      0.00  1900.00   576.60      0.00

GR     578.50      0.00   578.90    100.00   579.70   200.00    580.50   300.00   581.30    400.00
GR     581.50    500.00   581.30    600.00   579.70   700.00    577.50   800.00   575.70    900.00
GR     575.00    950.00   567.90   1000.00   567.10  1005.00    567.00  1009.00   567.50   1015.00
GR     567.50   1018.00   575.00   1060.00   575.00  1100.00    575.20  1200.00   575.20   1300.00
GR     575.50   1400.00   575.80   1500.00   576.10  1600.00    576.50  1700.00   577.50   1800.00
GR     576.60   1900.00
**********LISTING OF TOP AND BOTTOM SECTIONS OF ORIFICE**********

1000.00  567.90 1000.00  572.90 1018.00  572.90 1018.00  567.50

1000.00  567.90 1005.00  567.10 1009.00  567.00 1015.00  567.50 1018.00  567.50
********** LISTING OF COORDINATES OF ORIFICE**********

1000.00  567.90 1000.00  572.90 1018.00  572.90 1018.00  567.50 1015.00  567.50
1009.00  567.00 1005.00  567.10 1000.00  567.90

ORIFICE AREA        95.4 WETTED PERIMETER      44.6  29.1/R**1.333      10.6008
```

$A = 95.4\ ft^2$

$P = 44.6\ ft$

$R = A/P = 2.14\ ft$

$L = 47\ ft$

$n = 0.015$ (concrete with sandy Bottom)

$K_e = 0.50$ (No Wingwalls)


$K_f = 29.1 n^2 L / R^{4/3} = 10.6008\ n^2 L = 0.11$

$XKQR = 1 + K_e + K_f = 1.61$

$D = 5.9\ ft$

$BWC = A/D = 16.17\ ft$

FP



PLAN - McLOUTH ENTRY TRACK AT THE FRANK & POET DRAIN

NO SCALE

```
 *****NEW FLOW =   775.0

 **** STATION =  2677 TO   2767   3   72" CIRCULAR CULVERT

 FRICTION CORR     LENGTH    EXIT INVERT    ENTRANCE INVERT    ENTRANCE LOSS COEFF
      .025          90.0       569.17           569.47              .50

                                                                  LEFT      ** WEIR **    RIGHT
                                                                OVERBANK     FLOW      OVERBANK
 CULVERT FLOW =   775.00   ORIFICE COEFF =  .64   VELOCITY =     0.00                   0.00
 CULVERT VELOCITY =  9.14  DIST TO LAST STA =  277  TOP WIDTH =   0.00                   0.00
 ENERGY = 584.11   CULVERT AREA =  84.8          RDWY ELEV =   584.60     585.30      588.00
                   (PIPE FLOWING FULL           WEIR COEFF =    0.00                   0.00
```

NOTE:
WATER SURFACES ARE
100 YR - FINAL FILL

Bridge Characteristics : 3 - 6' Circular Culverts

Area : $A = 3 \times \frac{\pi}{4} R_a^2 = 84.82$ ft²

Wet Perimeter : $P = 3 \times \pi R_a = 56.55$ ft.

Hydraulic Radius : $R = R/4 = 6/4 = 1.5$ ft. $R^{4/3} = 1.717$

Length : $L = 90$ ft.

Manning Coefficient : $n = 0.024$ 0.032 pg - 5-36

Entrance Loss Coefficient : $K_e = 0.9$ (Projecting from fill)

$$K_f = \frac{29 n^2 L}{R^{4/3}} = 0.88$$

$$\Sigma K\Phi R = 1 + K_e + K_f = 1 + 0.9 + 0.88 = 2.78$$

Max. Depth : $D = 6.0$ ft

$BWC = A/D = 14.14$ ft.

$$K_f = \frac{(29.16)(0.032)^2(90')}{1.717} = 1.565$$


$$\Sigma K\Phi R = 1.9 + 1.565 = 3.465$$

$$H = \left[\left(\frac{670}{84.82}\right)^2 / 64.4\right](3.465)$$

$H = 3.357' > 2.69$ (typ ent)


100 YR - FINAL FILL

**** STATION 4990 TO 4995 1 10'0"X 2'6" STRUCTL PLATE ARCH CULVERT									
FRICTION COEFF	LENGTH	EXIT INVERT	ENTRANCE INVERT	ENTRANCE LOSS COEFF			LEFT OVERBANK	** WEIR ** FLOW	RIGHT OVERBANK
.025	36.0	568.99	570.99	.50		FLOW =	1944.64		1528.35
		CULVERT FLOW =	27.12	ORIFICE COEFF =	.13	VELOCITY =	1.67		2.74
		CULVERT VELOCITY =	.38	DIST TO LAST STA =	460	TOP WIDTH =	560.00		589.91
ENERGY = 584.30		CURVE # USED =	99.0			RDWY ELEV =	581.60	582.30	585.00
		(PIPE FLOWING FULL)				WEIR COEFF =	1.21		2.32



DETROIT-TOLEDO & SHORE LINE (EAST TRACKS) OVER THE FRANK & POET DRAIN

No Scale



FP

```
X1    8474.00    18    415.00    427.50    28.00    28.00    28.00    1.000

BT    18.00    0.00    583.20    0.00    100.00    582.90    0.00    200.00    582.50    0.00

BT    300.00    582.20    0.00    400.00    581.90    0.00    400.00    581.90    0.00    412.00
BT    581.90    0.00    415.00    581.90    569.10    415.00    581.90    574.60    419.00    581.90
BT    577.40    423.00    581.90    577.40    427.50    581.90    574.60    427.50    581.90    569.10
BT    431.00    581.90    0.00    437.00    581.90    0.00    437.00    581.90    0.00    587.00
BT    581.40    0.00    837.00    581.10    0.00

GR    583.20    0.00    582.90    100.00    582.50    200.00    582.20    300.00    581.90    350.00
GR    577.40    400.00    569.10    412.00    569.10    415.00    569.10    415.00    569.10    419.00
GR    569.10    423.00    569.10    427.50    569.10    427.50    569.10    431.00    573.40    437.00
GR    581.90    470.00    581.40    587.00    581.10    837.00
**********LISTING OF TOP AND BOTTOM SECTIONS OF ORIFICE**********

 415.00  569.10  415.00  574.60  419.00  577.40  423.00  577.40  427.50  574.60
 427.50  569.10

 415.00  569.10  415.00  569.10  419.00  569.10  423.00  569.10  427.50  569.10
 427.50  569.10
********** LISTING OF COORDINATES OF ORIFICE**********

 415.00  569.10  415.00  574.60  419.00  577.40  423.00  577.40  427.50  574.60
 427.50  569.10  427.50  569.10  423.00  569.10  419.00  569.10  415.00  569.10
 415.00  569.10

ORIFICE AREA        91.8 WETTED PERIMETER      37.6  29.1/R**1.333       8.8919
```

pg 58

A = 91.8 ft² 89 45 dwl

P = 37.6 ft

R = A/P = 2.44 ft 2.48'

L = 36 ft.

n = 0.031 / ~~0.025~~ (Structl Plate Arch Culvert)

Ke = 0.50

✓ $K_f = 29.1 n^2 L / R^{4/3} = 8.8919\, n^2 L$ = ~~0.30~~ 0.30

XKOR = 1 + 0.5 + ~~0.2~~ 0.3 = ~~1.70~~ 1.80

D = 8.3 ft.


BWC = A/D = 91.8/8.3 = 11.06

**** NEW FLOW = 3900.0


***STATION 5330 TO 5340 1 104"X 150" RECTANGULAR CULVERT

FRICTION COEFF	LENGTH	EXIT INVERT	ENTRANCE INVERT	ENTRANCE LOSS COEFF		LEFT OVERBANK	** WEIR ** FLOW	RIGHT OVERBANK
.013	16.0	571.47	571.47	.50	FLOW =	2564.52		190.69
		CULVERT FLOW =	1144.80	ORIFICE COEFF = .81	VELOCITY =	3.22		1.79
		CULVERT VELOCITY =	8.81	DIST TO LAST STA = 344	TOP WIDTH =	800.00		418.75
	ENERGY = 586.12	CULVERT AREA =	130.0		RDWY ELEV =	584.60	585.60	587.20
		(PIPE FLOWING FULL)			WEIR COEFF =	3.09		3.09

FP




SECTION "J-J"
(WEST SIDE)



NEW YORK CENTRAL (WEST TRACK) OVER THE FRANK & POET DRAIN

NO SCALE



SECTION "K-K"
(EAST SIDE)

```
X1   ~~8758.00~~ 8852.00    10    400.00    415.00    250.00    1.00    170.00    1.000

BT     10.00      0.00     586.00      0.00     200.00     585.10      0.00     400.00     584.20      0.00

BT    400.00    584.20    578.60    407.50    584.20    578.60    415.00    584.20    578.60    415.00
BT    584.20      0.00    455.00    584.10      0.00    615.00    584.00      0.00    815.00    583.90
BT      0.00

GR    586.00      0.00    585.10    200.00    584.20    400.00    570.10    400.00    570.10    407.50
GR    570.10    415.00    584.20    415.00    584.10    455.00    584.00    615.00    583.90    815.00
**********LISTING OF TOP AND BOTTOM SECTIONS OF ORIFICE**********

 400.00  578.60  407.50  578.60  415.00  578.60

 400.00  584.20  400.00  570.10  407.50  570.10  415.00  570.10  415.00  584.20
********** LISTING OF COORDINATES OF ORIFICE**********

 400.00  578.60  407.50  578.60  415.00  578.60  415.00  570.10  407.50  570.10
 400.00  570.10  400.00  578.60


 ORIFICE AREA      127.4 WETTED PERIMETER     46.9  29.1/R**1.333      7.7094
```

A = 127.4 ft²
P = 46.9 ft.
R = A/P = 2.72 ft.
L = 16.0 ft.
n = 0.015 (Concrete with Sandy Bott
Ke = 0.50
Kf = 29.1 n²L/R^4/3 = 7.7094 n²L = 0.03
ΣKΦR = 1 + 0.5 + 0.03 = 1.53
D = 8.5 ft
BWC = A/D = 127.4/8.5 = 15.0 ft


100 YR.-FINAL FI


**** [illegible] 7133 [illegible] [illegible] 3 72" CIRCULAR CULVERT

[illegible] CULVERT [illegible] FLOW NEGLIGIBLE



SECTION "A-A"
(NORTH SIDE)





SECTION "B-B"
(SOUTH SIDE)

VREELAND ROAD CROSSING OVER FRANK AND POET DRAIN

NO SCALE

Johnson & Anderson, Inc.
Consulting Engineers
P.O. Box 1166 2300 Dixie Highway Pontiac, Michigan 48056


HYDRAULIC STRUCTURAL DATA

Code No. 5555-23-02-


Job Name: CITY OF GIBRALTAR. BROWNSTOWN CREEK			By: MCINNES
Date: 9-25-75	Feature: SOUTH GIBRALTAR ROAD BRIDGE		Water Course: BROWNSTOWN CREEK
Remarks: CONC BOX CULVERT BRIDGE. WITH HIGH SOLID CONCRETE RAILING.			
			Photo: 1-4 Roll #1
Width of Piers: 0	Pier Shape:	No. of Piers: 0	Area:
Water Elevation:	Length: 24.5'	Width of Deck: 17.0'	Skew: 0°

FIELD SKETCH

Profile View



Plan View



```
.1    2112.00        23     800.00    824.50    150.00    200.00    160.00      1.000

BT     17.00      0.00     574.40      0.00    100.00    574.10      0.00    300.00    574.10      0.00

BT    400.00    574.20       0.00    500.00    574.20      0.00    600.00    574.20      0.00    700.00
BT    574.50      0.00     800.00    575.10    573.70    824.50    575.90    573.30    900.00    574.80
BT      0.00   1000.00     574.20      0.00   1100.00    574.30      0.00   1200.00    574.60      0.00
BT   1300.00    574.90       0.00   1400.00    575.50      0.00   1500.00    575.40      0.00   1600.00
BT    578.40      0.00

GR    574.40      0.00     574.10    100.00    574.10    300.00    574.20    400.00    574.20    500.00
GR    574.20    600.00     574.50    700.00    575.10    800.00    571.40    800.00    565.60    805.00
GR    563.90    810.00     564.70    815.00    566.20    820.00    568.30    824.50    575.90    824.50
GR    574.80    900.00     574.20   1000.00    574.30   1100.00    574.60   1200.00    574.90   1300.00
GR    575.50   1400.00     575.40   1500.00    578.40   1600.00
**********LISTING OF TOP AND BOTTOM SECTIONS OF ORIFICE**********

 800.00  573.70  824.50  573.30

 800.00  575.10  800.00  571.40  805.00  565.60  810.00  563.90  815.00  564.70
 820.00  566.20  824.50  568.30  824.50  575.90
********** LISTING OF COORDINATES OF ORIFICE**********

 800.00  573.70  824.50  573.30  824.50  568.30  820.00  566.20  815.00  564.70
 810.00  563.90  805.00  565.60  800.00  571.40  800.00  573.70

 ORIFICE AREA      183.1 WETTED PERIMETER     59.9  29.1/R**1.333      6.5871
```

$A = 183.1\ ft^2$

$P = 59.9\ ft$

$R = A/P = 3.06\ ft.$

$L = 17\ ft$

$n = 0.015$ (Concrete with Sandy Bottom)

$K_e = 0.40$

$K_f = 29.1 n^2 L / R^{4/3} = 6.5871\ n^2 L = 0.03$

$XK\phi R = 1 + 0.4 + 0.03 = 1.43$

$D = 9.5\ ft$

$BWC = A/D = 19.27\ ft.$

Johnson & Anderson, Inc.
Consulting Engineers
P.O Box 1166 2300 Dixie Highway Pontiac, Michigan 48056


HYDRAULIC STRUCTURAL DATA

Code No. 5555-23-2-5


Job Name: City of Gibraltar, F.I.S. Brownstown Creek			By: McInnes
Date: 9-29-75	Feature: Jefferson St. Bridge		Water Course: Brownstown Creek
Remarks: Concrete Bridge with Concrete Stringers Solid Concrete Railing			
			Photo 17-20
Width of Piers: —	Pier Shape: —	No. of Piers: 0	Area:
Water Elevation:	Length: 430'	Width of Deck: 47'	Skew: Cos θ = .71

FIELD SKETCH

Profile View



Plan View



5555-23-01-13
City of Gibraltar
Brownstown Creek

X1	~~2882.00~~ 2983	31	800.00	843.00	1.00	1.00	1.00	0.710		
BT	21.00	0.00	575.60	0.00	100.00	575.70	0.00	200.00	575.80	0.00
BT	300.00	575.80	0.00	400.00	575.70	0.00	500.00	575.70	0.00	600.00
BT	575.70	0.00	700.00	576.00	0.00	800.00	577.40	573.80	843.00	577.60
BT	573.80	900.00	577.20	0.00	1000.00	576.10	0.00	1100.00	576.20	0.00
BT	1200.00	576.40	0.00	1300.00	577.10	0.00	1400.00	577.90	0.00	1500.00
BT	578.90	0.00	1600.00	579.80	0.00	1700.00	580.20	0.00	1800.00	580.70
BT	0.00	1900.00	581.80	0.00						
GR	575.60	0.00	575.70	100.00	575.80	200.00	575.80	300.00	575.70	400.00
GR	575.70	500.00	575.70	600.00	576.00	700.00	577.40	800.00	569.00	800.00
GR	567.90	805.00	567.50	810.00	567.20	815.00	567.20	820.00	567.30	825.00
GR	567.20	830.00	567.00	835.00	567.10	840.00	567.10	843.00	577.60	843.00
GR	577.20	900.00	576.10	1000.00	576.20	1100.00	576.40	1200.00	577.10	1300.00
GR	577.90	1400.00	578.90	1500.00	579.80	1600.00	580.20	1700.00	580.70	1800.00
GR	581.80	1900.00								

**********LISTING OF TOP AND BOTTOM SECTIONS OF ORIFICE**********

800.00 573.80 843.00 573.80

800.00 577.40 800.00 569.00 805.00 567.90 810.00 567.50 815.00 567.20
820.00 567.20 825.00 567.30 830.00 567.20 835.00 567.00 840.00 567.10
843.00 567.10 843.00 577.60

********** LISTING OF COORDINATES OF ORIFICE**********

800.00 573.80 843.00 573.80 843.00 567.10 840.00 567.10 835.00 567.00
830.00 567.20 825.00 567.30 820.00 567.20 815.00 567.20 810.00 567.50
805.00 567.90 800.00 569.00 800.00 573.80

ORIFICE AREA 195.4 WETTED PERIMETER 72.7 29.1/R**1.333 7.8104

Area, $A = 195.4$ ft²

Wet Perimeter, $P = 72.7$ ft

Hydraulic Radius, $R = A/P = 2.69$ ft

Length, $L = 66$ ft.

Manning Coefficient, $n = 0.015$

Entrance Loss, $K_e = 0.5$ (No wingwalls)

Max Depth, $D = 6.8$ ft

BWC = $A/D = 28.74$ ft.

$$K_f = \frac{29\,n^2 L}{R^{4/3}} = 7.8104\,n^2 L = \text{~~0.107~~ } 0.11$$


$$XKPR = 1 + K_e + K_f$$

$$= 1 + 0.5 + \text{~~0.107~~ } 0.11 = \text{~~1.607~~ } 1.61$$


JOHNSON & ANDERSON, INC.
CONSULTING ENGINEERS

BY Tubby DATE _____ JOB DESCRIPTION GIBRALTAR F1S SHEET _____ OF _____
SUBJECT BLAKELY DRAIN BRIDGE (GIBRALTAR RD) JOB NO. 5555


SECNO = 7251




DISTANCE LEFT OR RIGHT OF CENTERLINE OF DRAIN (IN FEET)



SECTION B-B
WEST SIDE OF BRIDGE



PLAN
DETROIT & TOLEDO SHORE LINE R.R.
BRIDGE OVER BROWNSTOWN CREEK



SECTION A-A
EAST SIDE OF BRIDGE
NO SCALE

**** NEW FLOW = 6829.0

**** D.T.&S.L. R.R. @ STATION 18+50

PROJEC CODE	TABLE 1	N1	TABLE 2	N2	TABLE 3	N3	N4	IJ	LOW STEEL		LEFT OVERBANK	** WEIR ** FLOW	RIGHT OVERBANK
1	7	3	8	1	9	6	4	0	579.3	FLOW =	2159.00		2993.00
										VELOCITY =	5.27		2.54
			BRIDGE FLOW =		1680.00					TOP WIDTH =	733.38		1016.74
			BRIDGE VELOCITY =		12.07	ORIFICE COEFF =			.85	RDWY ELEV =	586.00	582.30	584.50
ENERGY BALANCE = 584.08			BRDG FLOW AREA =		139.2					WEIR COEFF =	3.09		3.09

XT	8591.00	27	582.00	850.00	300.00	300.00	300.00	1.000		
BT	27.00	0.00	583.40	0.00	200.00	583.20	0.00	400.00	582.80	0.00
BT	500.00	582.60	0.00	582.00	582.50	0.00	582.00	582.50	577.90	586.50
BT	582.50	577.90	591.00	582.50	577.90	591.00	582.50	571.50	593.00	582.50
BT	571.60	593.00	582.50	577.90	599.00	582.50	577.90	605.00	582.50	577.90
BT	605.00	582.50	571.50	607.00	582.50	571.40	607.00	582.50	577.90	613.00
BT	582.50	577.90	619.00	582.50	577.90	619.00	582.50	571.20	621.00	582.50
BT	571.10	621.00	582.50	577.90	625.50	582.50	577.90	630.00	582.50	577.90
BT	630.00	582.50	0.00	680.00	582.40	0.00	840.00	582.00	0.00	1000.00
BT	581.60	0.00								
GR	583.40	0.00	583.20	200.00	582.80	400.00	582.60	500.00	582.50	582.00
GR	571.50	582.00	571.50	586.50	571.50	591.00	571.50	591.00	571.60	593.00
GR	571.60	593.00	571.60	599.00	571.50	605.00	571.50	605.00	571.40	607.00
GR	571.40	607.00	571.30	613.00	571.20	619.00	571.20	619.00	571.10	621.00
GR	571.10	621.00	571.00	625.50	571.00	630.00	582.50	630.00	582.40	680.00
GR	582.00	840.00	581.60	1000.00						

**********LISTING OF TOP AND BOTTOM SECTIONS OF ORIFICE**********

582.00	577.90	586.50	577.90	591.00	577.90	591.00	571.50	593.00	571.60
593.00	577.90	599.00	577.90	605.00	577.90	605.00	571.50	607.00	571.40
607.00	577.90	613.00	577.90	619.00	577.90	619.00	571.20	621.00	571.10
621.00	577.90	625.50	577.90	630.00	577.90				

582.00	582.50	582.00	571.50	586.50	571.50	591.00	571.50	591.00	571.50
593.00	571.60	593.00	571.60	599.00	571.60	605.00	571.50	605.00	571.50
607.00	571.40	607.00	571.40	613.00	571.30	619.00	571.20	619.00	571.20
621.00	571.10	621.00	571.10	625.50	571.00	630.00	571.00	630.00	582.50

********** LISTING OF COORDINATES OF ORIFICE**********

582.00	577.90	586.50	577.90	591.00	577.90	591.00	571.50	593.00	571.60
593.00	577.90	599.00	577.90	605.00	577.90	605.00	571.50	607.00	571.40
607.00	577.90	613.00	577.90	619.00	577.90	619.00	571.20	621.00	571.10

621.00	577.90	625.00	577.90	630.00	577.90	630.00	571.00	625.00	571.00
621.00	571.10	621.00	571.10	619.00	571.20	619.00	571.20	613.00	571.30
607.00	571.40	607.00	571.40	605.00	571.50	605.00	571.50	599.00	571.60
593.00	571.60	593.00	571.60	591.00	571.50	591.00	571.50	586.50	571.50
582.00	571.50	582.00	577.90						

ORIFICE AREA 274.5 WETTED PERIMETER 136.4 29.1/R**1.333 11.4774

$A = 274.5\ ft^2$

$P = 136.4\ ft$

$R = A/P = 2.01\ ft.$

$L = 52\ ft$

$n = 0.015$ (Concrete With Sandy Bottom)

$Ke = 0.40$ (With Wingwalls)

$K_f = 29.1 n^2 L / R^{4/3} = 11.4774\, n^2 L = 0.13$

$XK\Phi R = 1 + Ke + K_f = 1.53$

$XK = 1.15$

$BWC = 48.0\ ft$

$BWP = 6.0\ ft$


**** NEW FLOW = 3700.0

**** N.Y.C. R.R. & STA. 23+50


FROUDE CODE	TABLE 1	N1	TABLE 2	N2	TABLE 3	N3	N4	IJ	LOW STEEL
	1		7	2	1	5	*	3	0	581.5

BRIDGE FLOW = 2930.00
BRIDGE VELOCITY = 5.99 ORIFICE COEFF = .95
ENERGY BALANCE = 584.58 BRDG FLOW AREA = 489.0


** WEIR **	LEFT OVERBANK	FLOW	RIGHT OVERBANK
FLOW =	236.00		611.00
VELOCITY =	2.41		2.68
TOP WIDTH =	436.82		700.00
RDWY ELEV =	585.10	584.00	584.30
WEIR COEFF =	3.09		3.09



SECTION B-B
WEST SIDE OF BRIDGE



PLAN
PENN CENTRAL R.R. BRIDGE OVER BROWNSTOWN CREEK




SECTION A-A
EAST SIDE OF BRIDGE
NO SCALE


STATION 4950 TO 4964 1 19"X 343" RECTANGULAR CULVERT									
FRICTION COEFF	LENGTH	EXIT INVERT	ENTRANCE INVERT	ENTRANCE LOSS COEFF			LEFT OVERBANK	** WEIR ** FLOW	RIGHT OVERBANK
.013	14.0	574.83	574.63	.50		FLOW =	1634.18		450.22
		CULVERT FLOW =	1119.60	ORIFICE COEFF =	.81	VELOCITY =	5.51		5.12
		CULVERT VELOCITY =	7.99	DIST TO LAST STA =	350	TOP WIDTH =	700.00		328.24
	ENERGY = 536.27	CULVERT AREA =	140.5			RDWY ELEV =	585.70	585.20	587.40
		(PIPE FLOWING FULL)				WEIR COEFF =	3.09		3.09


B

N



SECTION "A-A"
(WEST SIDE)





SECTION "B-B"
(EAST SIDE)

PENN CENTRAL R.R. BRIDGE OVER BROWNSTOWN CREEK

NO SCALE

JOHNSON & ANDERSON, INC.
CONSULTING ENGINEERS

BY MSC DATE 2/18/76 JOB DESCRIPTION FIS - Gibraltar SHEET ____ OF ____
SUBJECT Brownstown Drain BS 49+50 JOB NO. 5555-23-01

Culvert Characteristics : 59" x 343" Rectangular Concrete Culvert.

Area : $A = 140.5$ ft²

Wetted Perimeter : $P = 67.0$ ft.

Hydraulic Radius : $R = A/P = 2.10$ ft.

Length : $L = 14.0$ ft.

Manning n : $n = 0.018$ (with Sandy Bottom)

Entrance Loss : $K_e = 0.70$ (Wingwalls Parallel)

$$K_f = \frac{29.1\, n^2 L}{R^{4/3}} = 0.05$$

$$\Sigma K\phi R = 1 + K_e + K_f = 1.75$$

BWC = 28.5 ft.

00BREAK00

1) COUNTY: Wayne

2) STUDY NAME: City of Gibralter

3) WATERCOURSE: Frank and Poet Drain

4) DOCUMENT TYPE: Summary

00BREAK00

SUMMARY PRINTOUT FOR MULTIPLE PROFILES

FRANK AND POET DRAIN

SECTION NUMBER	CHANNEL LENGTH	MIN EL OF ROADWAY	MAX EL OF LOW CHORD	MIN EL GROUND	DISCHARGE (CFS)	CWSEL	HV	HL	OLOSS	QCH	DEPTH	TOPWID
600.00	0.00	0.00	0.00	566.50	580.00	573.10	.04	0.00	0.00	568.19	6.60	95.56
600.00	0.00	0.00	0.00	566.50	890.00	573.10	.09	0.00	0.00	871.87	6.60	95.56
600.00	0.00	0.00	0.00	566.50	1020.00	573.10	.12	0.00	0.00	999.23	6.60	95.56
600.00	0.00	0.00	0.00	566.50	1385.00	573.10	.21	0.00	0.00	1356.79	6.60	95.56
1100.00	500.00	0.00	0.00	564.80	580.00	573.14	.23	.14	.10	580.00	8.34	20.00
1100.00	500.00	0.00	0.00	564.80	890.00	573.21	.53	.33	.22	890.00	8.41	20.00
1100.00	500.00	0.00	0.00	564.80	1020.00	573.24	.69	.43	.29	1020.00	8.44	20.00
1100.00	500.00	0.00	0.00	564.80	1385.00	573.37	1.24	.78	.51	1385.00	8.57	20.00
1101.00	1.00	574.30	575.50	564.80	580.00	573.11	.30	.00	.03	580.00	8.31	20.00
1101.00	1.00	574.30	575.50	564.80	890.00	573.12	.70	.00	.08	890.00	8.32	20.00
1101.00	1.00	574.30	575.50	564.80	1020.00	573.13	.92	.00	.11	1020.00	8.33	20.00
1101.00	1.00	574.30	575.50	564.80	1385.00	573.15	1.69	.00	.23	1385.00	8.35	20.00
1127.00	26.00	574.30	575.50	564.80	580.00	573.13	.30	.02	.00	580.00	8.33	20.00
1127.00	26.00	574.30	575.50	564.80	890.00	573.17	.70	.04	.00	890.00	8.37	20.00
1127.00	26.00	574.30	575.50	564.80	1020.00	573.19	.91	.05	.00	1020.00	8.39	20.00
1127.00	26.00	574.30	575.50	564.80	1385.00	573.30	1.64	.08	.02	1385.00	8.50	20.00
1128.00	1.00	0.00	0.00	564.80	580.00	573.22	.23	.00	.02	580.00	8.42	20.00
1128.00	1.00	0.00	0.00	564.80	890.00	573.42	.51	.00	.06	890.00	8.62	20.00
1128.00	1.00	0.00	0.00	564.80	1020.00	573.54	.64	.00	.08	1020.00	8.74	20.00
1128.00	1.00	0.00	0.00	564.80	1385.00	574.08	1.04	.00	.18	1385.00	9.28	20.00
1178.00	50.00	0.00	0.00	566.20	580.00	573.50	.02	.01	.06	579.95	7.30	110.00
1178.00	50.00	0.00	0.00	566.20	890.00	574.04	.04	.01	.14	887.84	7.84	120.00
1178.00	50.00	0.00	0.00	566.20	1020.00	574.33	.05	.02	.18	1015.38	8.13	120.00
1178.00	50.00	0.00	0.00	566.20	1385.00	575.38	.06	.02	.29	1366.98	9.18	120.00
1628.00	450.00	0.00	0.00	567.60	580.00	573.53	.01	.02	.00	580.00	5.93	209.51
1628.00	450.00	0.00	0.00	567.60	890.00	574.10	.01	.03	.01	889.22	6.50	218.20
1628.00	450.00	0.00	0.00	567.60	1020.00	574.40	.02	.03	.01	1018.24	6.80	228.65
1628.00	450.00	0.00	0.00	567.60	1385.00	575.46	.02	.03	.01	1370.31	7.86	374.45
2428.00	800.00	0.00	0.00	567.20	580.00	573.57	.01	.03	.00	579.35	6.37	225.99
2428.00	800.00	0.00	0.00	567.20	890.00	574.15	.02	.05	.00	882.70	6.95	259.98
2428.00	800.00	0.00	0.00	567.20	1020.00	574.46	.02	.05	.00	1005.15	7.26	276.70
2428.00	800.00	0.00	0.00	567.20	1385.00	575.51	.02	.05	.00	1320.98	8.31	491.80
3228.00	800.00	0.00	0.00	567.50	580.00	573.61	.15	.11	.07	580.00	6.11	47.92
3228.00	800.00	0.00	0.00	567.50	890.00	574.19	.27	.17	.13	890.00	6.69	48.78
3228.00	800.00	0.00	0.00	567.50	1020.00	574.48	.31	.17	.15	1020.00	6.98	49.20
3228.00	800.00	0.00	0.00	567.50	1385.00	575.49	.38	.16	.18	1385.00	7.99	50.67
3778.00	550.00	0.00	0.00	567.20	580.00	574.06	.09	.38	.02	576.49	6.86	73.10
3778.00	550.00	0.00	0.00	567.20	610.00	574.83	.07	.39	.06	593.83	7.63	133.71
3778.00	550.00	0.00	0.00	567.20	615.00	575.17	.06	.36	.07	586.21	7.97	197.43
3778.00	550.00	0.00	0.00	567.20	635.00	576.21	.03	.26	.11	528.09	9.01	287.36

SECTION NUMBER	CHANNEL LENGTH	MIN EL OF ROADWAY	MAX EL OF LOW CHORD	MIN EL GROUND	DISCHARGE (CFS)	CWSEL	HV	HL	OLOSS	QCH	DEPTH	TOPWID
3828.00	50.00	0.00	0.00	567.10	580.00	574.03	.21	.03	.06	580.00	6.93	25.00
3828.00	50.00	0.00	0.00	567.10	610.00	574.89	.03	.01	.01	320.06	7.79	124.16
3828.00	50.00	0.00	0.00	567.10	615.00	575.22	.03	.01	.01	313.38	8.12	146.33
3828.00	50.00	0.00	0.00	567.10	635.00	576.23	.02	.00	.00	292.55	9.13	230.00
3829.00	1.00	0.00	0.00	567.10	580.00	574.03	.21	.00	.00	580.00	6.93	25.00
3829.00	1.00	0.00	0.00	567.10	610.00	574.90	.02	.00	.00	278.76	7.80	124.23
3829.00	1.00	0.00	0.00	567.10	615.00	575.23	.02	.00	.00	271.90	8.13	147.47
3829.00	1.00	0.00	0.00	567.10	635.00	576.23	.01	.00	.00	250.70	9.13	230.00
3884.00	55.00	575.10	574.40	567.10	580.00	574.04	.21	.01	.00	580.00	6.94	25.00
3884.00	55.00	575.10	574.40	567.10	610.00	575.21	.02	.31	0.00	270.00	8.11	145.40
3884.00	55.00	575.10	574.40	567.10	615.00	575.53	.02	.29	0.00	263.61	8.43	201.51
3884.00	55.00	575.10	574.40	567.10	635.00	576.37	.01	.13	0.00	246.21	9.27	230.00
3885.00	1.00	0.00	0.00	567.10	580.00	574.04	.21	.00	.00	580.00	6.94	25.00
3885.00	1.00	0.00	0.00	567.10	610.00	575.21	.03	.00	.01	333.54	8.11	145.40
3885.00	1.00	0.00	0.00	567.10	615.00	575.52	.03	.00	.00	327.30	8.42	200.36
3885.00	1.00	0.00	0.00	567.10	635.00	576.37	.02	.00	.00	308.76	9.27	230.00
4035.00	150.00	0.00	0.00	567.20	580.00	574.27	.09	.07	.04	572.86	7.07	109.52
4035.00	150.00	0.00	0.00	567.20	610.00	575.22	.05	.02	.01	557.46	8.02	201.45
4035.00	150.00	0.00	0.00	567.20	615.00	575.53	.04	.02	.01	539.03	8.33	215.15
4035.00	150.00	0.00	0.00	567.20	635.00	576.38	.02	.01	.00	446.36	9.18	365.86
4265.00	230.00	0.00	0.00	567.00	580.00	574.35	.08	.07	.00	344.80	7.35	96.71
4265.00	230.00	0.00	0.00	567.00	610.00	575.25	.06	.04	.00	337.46	8.25	363.58
4265.00	230.00	0.00	0.00	567.00	615.00	575.56	.04	.03	.00	320.47	8.56	384.60
4265.00	230.00	0.00	0.00	567.00	635.00	576.39	.02	.01	.00	270.29	9.39	430.67
4266.00	1.00	0.00	0.00	567.00	580.00	574.39	.05	.00	.01	274.94	7.39	97.18
4266.00	1.00	0.00	0.00	567.00	610.00	575.29	.03	.00	.01	262.64	8.29	366.19
4266.00	1.00	0.00	0.00	567.00	615.00	575.59	.02	.00	.01	247.24	8.59	386.51
4266.00	1.00	0.00	0.00	567.00	635.00	576.40	.01	.00	.00	205.01	9.40	430.68
4313.00	47.00	575.00	572.90	567.00	580.00	575.17	.03	.76	0.00	255.01	8.17	233.86
4313.00	47.00	575.00	572.90	567.00	610.00	575.53	.03	.23	0.00	248.81	8.53	382.50
4313.00	47.00	575.00	572.90	567.00	615.00	575.68	.02	.10	0.00	241.09	8.68	393.15
4313.00	47.00	575.00	572.90	567.00	635.00	576.43	.01	.04	0.00	202.17	9.43	433.32
4314.00	1.00	0.00	0.00	567.00	580.00	575.16	.06	.00	.01	326.82	8.16	230.73
4314.00	1.00	0.00	0.00	567.00	610.00	575.52	.05	.00	.01	323.21	8.52	382.15
4314.00	1.00	0.00	0.00	567.00	615.00	575.67	.04	.00	.01	314.78	8.67	393.15
4314.00	1.00	0.00	0.00	567.00	635.00	576.43	.02	.00	.01	272.05	9.43	433.03
4524.00	210.00	0.00	0.00	567.60	580.00	575.24	.02	.03	.01	385.54	7.64	366.58
4524.00	210.00	0.00	0.00	567.60	610.00	575.58	.01	.02	.01	374.00	7.98	386.50
4524.00	210.00	0.00	0.00	567.60	615.00	575.73	.01	.02	.01	364.77	8.13	395.13
4524.00	210.00	0.00	0.00	567.60	635.00	576.46	.01	.01	.00	326.07	8.86	436.52

SECTION NUMBER	CHANNEL LENGTH	MIN EL OF ROADWAY	MAX EL OF LOW CHORD	MIN EL GROUND	DISCHARGE (CFS)	CWSEL	HV	HL	OLOSS	QCH	DEPTH	TOPWID
5024.00	500.00	0.00	0.00	567.70	580.00	575.29	.06	.08	.02	572.20	7.59	232.85
5024.00	500.00	0.00	0.00	567.70	610.00	575.62	.05	.06	.02	578.15	7.92	234.00
5024.00	500.00	0.00	0.00	567.70	615.00	575.77	.05	.05	.02	569.95	8.07	234.00
5024.00	500.00	0.00	0.00	567.70	635.00	576.48	.03	.03	.01	528.08	8.78	234.00
5524.00	500.00	0.00	0.00	567.20	580.00	575.41	.01	.06	.01	516.28	8.21	230.00
5524.00	500.00	0.00	0.00	567.20	610.00	575.72	.01	.05	.01	530.79	8.52	230.00
5524.00	500.00	0.00	0.00	567.20	615.00	575.86	.01	.04	.01	530.51	8.66	230.00
5524.00	500.00	0.00	0.00	567.20	635.00	576.53	.01	.03	.01	525.51	9.33	230.00
5924.00	400.00	0.00	0.00	566.60	580.00	575.44	.03	.03	.01	429.64	8.84	190.99
5924.00	400.00	0.00	0.00	566.60	610.00	575.75	.02	.03	.01	432.94	9.15	192.00
5924.00	400.00	0.00	0.00	566.60	615.00	575.88	.02	.03	.01	428.94	9.28	192.00
5924.00	400.00	0.00	0.00	566.60	635.00	576.54	.02	.02	.00	408.44	9.94	192.00
6024.00	100.00	0.00	0.00	567.40	580.00	575.45	.03	.01	.00	556.02	8.05	110.00
6024.00	100.00	0.00	0.00	567.40	610.00	575.76	.03	.01	.00	580.49	8.36	110.00
6024.00	100.00	0.00	0.00	567.40	615.00	575.89	.02	.01	.00	583.32	8.49	110.00
6024.00	100.00	0.00	0.00	567.40	635.00	576.55	.02	.01	.00	592.11	9.15	110.00
6199.00	175.00	0.00	0.00	569.20	595.00	575.34	.34	.05	.16	595.00	6.14	24.00
6199.00	175.00	0.00	0.00	569.20	620.00	575.65	.33	.04	.15	620.00	6.45	24.00
6199.00	175.00	0.00	0.00	569.20	625.00	575.78	.32	.04	.15	625.00	6.58	24.00
6199.00	175.00	0.00	0.00	569.20	645.00	576.45	.28	.03	.13	645.00	7.25	24.00
6200.00	1.00	0.00	0.00	569.20	595.00	575.34	.34	.00	.00	595.00	6.14	24.00
6200.00	1.00	0.00	0.00	569.20	620.00	575.65	.33	.00	.00	620.00	6.45	24.00
6200.00	1.00	0.00	0.00	569.20	625.00	575.78	.32	.00	.00	625.00	6.58	24.00
6200.00	1.00	0.00	0.00	569.20	645.00	576.45	.28	.00	.00	645.00	7.25	24.00
6290.00	90.00	585.00	575.20	569.20	595.00	577.85	.16	2.32	0.00	595.00	8.65	24.00
6290.00	90.00	585.00	575.20	569.20	620.00	578.39	.15	2.56	0.00	620.00	9.19	24.00
6290.00	90.00	585.00	575.20	569.20	625.00	578.58	.15	2.62	0.00	625.00	9.38	24.00
6290.00	90.00	585.00	575.20	569.20	645.00	579.46	.13	2.86	0.00	645.00	10.26	24.00
6291.00	1.00	0.00	0.00	569.20	595.00	577.85	.16	.00	.00	595.00	8.65	24.00
6291.00	1.00	0.00	0.00	569.20	620.00	578.39	.15	.00	.00	620.00	9.19	24.00
6291.00	1.00	0.00	0.00	569.20	625.00	578.58	.15	.00	.00	625.00	9.38	24.00
6291.00	1.00	0.00	0.00	569.20	645.00	579.46	.13	.00	.00	645.00	10.26	24.00
6313.00	22.00	0.00	0.00	569.10	595.00	578.02	.03	.00	.04	520.19	8.92	68.00
6313.00	22.00	0.00	0.00	569.10	620.00	578.56	.03	.00	.04	537.33	9.46	68.00
6313.00	22.00	0.00	0.00	569.10	625.00	578.74	.03	.00	.04	540.16	9.64	68.00
6313.00	22.00	0.00	0.00	569.10	645.00	579.60	.02	.00	.03	550.61	10.50	68.00
7013.00	700.00	0.00	0.00	569.00	595.00	578.08	.01	.03	.01	342.08	9.08	329.51
7013.00	700.00	0.00	0.00	569.00	620.00	578.61	.00	.02	.01	341.12	9.61	341.88
7013.00	700.00	0.00	0.00	569.00	625.00	578.78	.00	.02	.01	338.93	9.78	344.97
7013.00	700.00	0.00	0.00	569.00	645.00	579.64	.00	.01	.01	327.92	10.64	359.88

SECTION NUMBER	CHANNEL LENGTH	MIN EL OF ROADWAY	MAX EL OF LOW CHORD	MIN EL GROUND	DISCHARGE (CFS)	CWSEL	HV	HL	OLOSS	QCH	DEPTH	TOPWID
7513.00	500.00	0.00	0.00	568.00	595.00	578.09	.01	.01	.00	290.50	10.09	280.46
7513.00	500.00	0.00	0.00	568.00	620.00	578.62	.01	.01	.00	282.43	10.62	290.45
7513.00	500.00	0.00	0.00	568.00	625.00	578.79	.01	.01	.00	278.45	10.79	293.96
7513.00	500.00	0.00	0.00	568.00	645.00	579.64	.00	.01	.00	260.60	11.64	311.00
8013.00	500.00	0.00	0.00	568.60	595.00	578.12	.02	.03	.01	403.99	9.52	192.97
8013.00	500.00	0.00	0.00	568.60	620.00	578.64	.02	.02	.00	397.00	10.04	198.30
8013.00	500.00	0.00	0.00	568.60	625.00	578.81	.01	.02	.00	393.06	10.21	200.00
8013.00	500.00	0.00	0.00	568.60	645.00	579.65	.01	.01	.00	380.62	11.05	200.00
8445.00	432.00	0.00	0.00	568.60	595.00	578.14	.20	.11	.09	595.00	9.54	27.00
8445.00	432.00	0.00	0.00	568.60	620.00	578.63	.19	.08	.09	620.00	10.03	27.00
8445.00	432.00	0.00	0.00	568.60	625.00	578.80	.18	.08	.08	625.00	10.20	27.00
8445.00	432.00	0.00	0.00	568.60	645.00	579.63	.15	.05	.07	645.00	11.03	27.00
8473.00	28.00	0.00	0.00	569.00	595.00	578.06	.43	.04	.11	595.00	9.06	12.50
8473.00	28.00	0.00	0.00	569.00	620.00	578.55	.42	.03	.12	620.00	9.55	12.50
8473.00	28.00	0.00	0.00	569.00	625.00	578.72	.41	.03	.11	625.00	9.72	12.50
8473.00	28.00	0.00	0.00	569.00	645.00	579.54	.37	.02	.11	645.00	10.54	12.50
8474.00	1.00	0.00	0.00	569.00	595.00	578.06	.43	.00	.00	595.00	9.06	12.50
8474.00	1.00	0.00	0.00	569.00	620.00	578.55	.42	.00	.00	620.00	9.55	12.50
8474.00	1.00	0.00	0.00	569.00	625.00	578.72	.41	.00	.00	625.00	9.72	12.50
8474.00	1.00	0.00	0.00	569.00	645.00	579.54	.37	.00	.00	645.00	10.54	12.50
8510.00	36.00	581.90	577.40	569.00	595.00	578.95	.36	.82	0.00	595.00	9.95	12.50
8510.00	36.00	581.90	577.40	569.00	620.00	579.57	.34	.94	0.00	620.00	10.57	12.50
8510.00	36.00	581.90	577.40	569.00	625.00	579.76	.34	.97	0.00	625.00	10.76	12.50
8510.00	36.00	581.90	577.40	569.00	645.00	580.71	.30	1.10	0.00	645.00	11.71	12.50
8511.00	1.00	0.00	0.00	569.00	595.00	578.95	.36	.00	.00	595.00	9.95	12.50
8511.00	1.00	0.00	0.00	569.00	620.00	579.57	.34	.00	.00	620.00	10.57	12.50
8511.00	1.00	0.00	0.00	569.00	625.00	579.76	.34	.00	.00	625.00	10.76	12.50
8511.00	1.00	0.00	0.00	569.00	645.00	580.71	.30	.00	.00	645.00	11.71	12.50
8681.00	170.00	0.00	0.00	569.50	740.00	579.37	.09	.07	.08	381.90	9.87	74.56
8681.00	170.00	0.00	0.00	569.50	855.00	579.95	.10	.07	.07	427.27	10.45	83.30
8681.00	170.00	0.00	0.00	569.50	880.00	580.14	.10	.07	.07	435.09	10.64	86.10
8681.00	170.00	0.00	0.00	569.50	915.00	581.05	.08	.05	.07	428.40	11.55	99.82
8851.00	170.00	0.00	0.00	570.10	740.00	579.26	.45	.07	.18	740.00	9.16	15.00
8851.00	170.00	0.00	0.00	570.10	855.00	579.81	.53	.08	.22	855.00	9.71	15.00
8851.00	170.00	0.00	0.00	570.10	880.00	579.99	.55	.08	.22	880.00	9.89	15.00
8851.00	170.00	0.00	0.00	570.10	915.00	580.91	.49	.06	.21	915.00	10.81	15.00
8852.00	1.00	0.00	0.00	570.10	740.00	579.27	.45	.00	.00	740.00	9.17	15.00
8852.00	1.00	0.00	0.00	570.10	855.00	579.81	.53	.00	.00	855.00	9.71	15.00
8852.00	1.00	0.00	0.00	570.10	880.00	579.99	.55	.00	.00	880.00	9.89	15.00
8852.00	1.00	0.00	0.00	570.10	915.00	580.91	.49	.00	.00	915.00	10.81	15.00

SECTION NUMBER	CHANNEL LENGTH	MIN EL OF ROADWAY	MAX EL OF LOW CHORD	MIN EL GROUND	DISCHARGE (CFS)	CWSEL	HV	HL	OLOSS	QCH	DEPTH	TOPWID
8868.00	16.00	584.20	578.60	570.10	740.00	579.65	.41	.35	0.00	740.00	9.55	15.00
8868.00	16.00	584.20	578.60	570.10	855.00	580.41	.47	.54	0.00	855.00	10.31	15.00
8868.00	16.00	584.20	578.60	570.10	880.00	580.65	.48	.59	0.00	880.00	10.55	15.00
8868.00	16.00	584.20	578.60	570.10	915.00	581.70	.43	.73	0.00	915.00	11.60	15.00
8869.00	1.00	0.00	0.00	570.10	740.00	579.65	.41	.00	.00	740.00	9.55	15.00
8869.00	1.00	0.00	0.00	570.10	855.00	580.41	.47	.00	.00	855.00	10.31	15.00
8869.00	1.00	0.00	0.00	570.10	880.00	580.65	.48	.00	.00	880.00	10.55	15.00
8869.00	1.00	0.00	0.00	570.10	915.00	581.70	.43	.00	.00	915.00	11.60	15.00
8874.00	5.00	0.00	0.00	570.10	740.00	579.97	.17	.00	.07	537.04	9.87	25.00
8874.00	5.00	0.00	0.00	570.10	855.00	580.78	.19	.00	.08	618.61	10.68	25.00
8874.00	5.00	0.00	0.00	570.10	880.00	581.02	.19	.00	.09	636.17	10.92	25.00
8874.00	5.00	0.00	0.00	570.10	915.00	582.03	.18	.00	.08	659.41	11.93	25.00
9177.00	303.00	0.00	0.00	569.70	765.00	580.20	.00	.01	.05	156.76	10.50	468.99
9177.00	303.00	0.00	0.00	569.70	1010.00	581.03	.00	.01	.06	194.12	11.33	471.08
9177.00	303.00	0.00	0.00	569.70	1100.00	581.28	.00	.01	.06	207.93	11.58	471.69
9177.00	303.00	0.00	0.00	569.70	1350.00	582.26	.00	.00	.05	240.55	12.56	474.16
9677.00	500.00	0.00	0.00	569.50	765.00	580.20	.00	.00	.00	135.57	10.70	506.99
9677.00	500.00	0.00	0.00	569.50	1010.00	581.04	.00	.00	.00	169.38	11.54	523.71
9677.00	500.00	0.00	0.00	569.50	1100.00	581.28	.00	.00	.00	181.79	11.78	528.60
9677.00	500.00	0.00	0.00	569.50	1350.00	582.27	.00	.00	.00	211.53	12.77	548.33
10177.00	500.00	0.00	0.00	569.60	765.00	580.20	.00	.00	.00	131.49	10.60	567.03
10177.00	500.00	0.00	0.00	569.60	1010.00	581.04	.00	.00	.00	164.95	11.44	579.97
10177.00	500.00	0.00	0.00	569.60	1100.00	581.28	.00	.00	.00	177.26	11.68	584.42
10177.00	500.00	0.00	0.00	569.60	1350.00	582.27	.00	.00	.00	207.27	12.67	626.66
10622.00	445.00	0.00	0.00	569.30	765.00	580.20	.00	.00	.00	81.32	10.90	614.00
10622.00	445.00	0.00	0.00	569.30	1010.00	581.04	.00	.00	.00	100.90	11.74	614.00
10622.00	445.00	0.00	0.00	569.30	1100.00	581.29	.00	.00	.00	108.17	11.99	614.00
10622.00	445.00	0.00	0.00	569.30	1350.00	582.27	.00	.00	.00	125.60	12.97	614.00
10654.00	32.00	0.00	0.00	570.70	770.00	580.20	.01	.00	.00	200.49	9.50	680.00
10654.00	32.00	0.00	0.00	570.70	1015.00	581.04	.00	.00	.00	204.04	10.34	680.00
10654.00	32.00	0.00	0.00	570.70	1105.00	581.28	.00	.00	.00	208.57	10.58	680.00
10654.00	32.00	0.00	0.00	570.70	1365.00	582.27	.00	.00	.00	208.52	11.57	680.00
10655.00	1.00	577.30	574.70	570.70	770.00	580.20	.00	.00	.00	61.58	9.50	680.00
10655.00	1.00	577.30	574.70	570.70	1015.00	581.04	.00	.00	.00	64.69	10.34	680.00
10655.00	1.00	577.30	574.70	570.70	1105.00	581.29	.00	.00	.00	66.89	10.59	680.00
10655.00	1.00	577.30	574.70	570.70	1365.00	582.27	.00	.00	.00	70.14	11.57	680.00
10693.00	38.00	577.30	574.70	570.70	770.00	580.20	.00	.00	.00	61.56	9.50	680.00
10693.00	38.00	577.30	574.70	570.70	1015.00	581.04	.00	.00	.00	64.68	10.34	680.00
10693.00	38.00	577.30	574.70	570.70	1105.00	581.29	.00	.00	.00	66.88	10.59	680.00
10693.00	38.00	577.30	574.70	570.70	1365.00	582.27	.00	.00	.00	70.14	11.57	680.00

SECTION NUMBER	CHANNEL LENGTH	MIN EL OF ROADWAY	MAX EL OF LOW CHORD	MIN EL GROUND	DISCHARGE (CFS)	CWSEL	HV	HL	OLOSS	QCH	DEPTH	TOPWID
10694.00	1.00	0.00	0.00	570.70	770.00	580.20	.00	.00	.00	192.52	9.50	680.00
10694.00	1.00	0.00	0.00	570.70	1015.00	581.04	.00	.00	.00	194.34	10.34	680.00
10694.00	1.00	0.00	0.00	570.70	1105.00	581.29	.00	.00	.00	198.29	10.59	680.00
10694.00	1.00	0.00	0.00	570.70	1365.00	582.27	.00	.00	.00	197.18	11.57	680.00
-3228.00	0.00	0.00	0.00	567.50	580.00	573.61	.15	0.00	0.00	580.00	6.11	47.92
-3228.00	0.00	0.00	0.00	567.50	890.00	574.19	.27	0.00	0.00	890.00	6.69	48.77
-3228.00	0.00	0.00	0.00	567.50	1020.00	574.48	.31	0.00	0.00	1020.00	6.98	49.20
-3228.00	0.00	0.00	0.00	567.50	1385.00	575.49	.38	0.00	0.00	1385.00	7.99	50.67
3353.00	125.00	0.00	0.00	575.10	5.00	575.14	.02	.12	0.00	5.00	.04	120.53
3353.00	125.00	0.00	0.00	575.10	300.00	575.56	.17	.24	0.00	300.00	.46	264.67
3353.00	125.00	0.00	0.00	575.10	425.00	575.66	.21	.27	0.00	425.00	.56	288.88
3353.00	125.00	0.00	0.00	575.10	765.00	575.98	.20	.25	.06	765.00	.88	324.83

SECTION NUMBER	DISCHARGE CFS	CWSEL	CWSEL DIFF EACH Q	CWSEL DIFF EACH SECTION	CWSEL-WSELK	TOPWID	T.W. DIFF	LENGTH
600.000	580.000	573.100	0.000	0.000	0.000	95.559	0.000	0.000
600.000	890.000	573.100	0.000	0.000	0.000	95.559	0.000	0.000
600.000	1020.000	573.100	0.000	0.000	0.000	95.559	0.000	0.000
600.000	1385.000	573.100	0.000	0.000	0.000	95.559	0.000	0.000
1100.000	580.000	573.144	0.000	.044	0.000	20.000	0.000	500.000
1100.000	890.000	573.206	.062	.106	0.000	20.000	0.000	500.000
1100.000	1020.000	573.241	.035	.141	0.000	20.000	0.000	500.000
1100.000	1385.000	573.370	.129	.270	0.000	20.000	0.000	500.000
1101.000	580.000	573.111	0.000	-.033	0.000	20.000	0.000	1.000
1101.000	890.000	573.124	.013	-.082	0.000	20.000	0.000	1.000
1101.000	1020.000	573.130	.006	-.111	0.000	20.000	0.000	1.000
1101.000	1385.000	573.148	.018	-.222	0.000	20.000	0.000	1.000
1127.000	580.000	573.127	0.000	.017	0.000	20.000	0.000	26.000
1127.000	890.000	573.168	.041	.044	0.000	20.000	0.000	26.000
1127.000	1020.000	573.192	.023	.061	0.000	20.000	0.000	26.000
1127.000	1385.000	573.303	.111	.155	0.000	20.000	0.000	26.000
1128.000	580.000	573.222	0.000	.094	0.000	20.000	0.000	1.000
1128.000	890.000	573.417	.195	.249	0.000	20.000	0.000	1.000
1128.000	1020.000	573.540	.124	.349	0.000	20.000	0.000	1.000
1128.000	1385.000	574.083	.543	.780	0.000	20.000	0.000	1.000
1178.000	580.000	573.497	0.000	.275	0.000	109.996	0.000	50.000
1178.000	890.000	574.037	.541	.621	0.000	119.999	-10.003	50.000
1178.000	1020.000	574.332	.295	.792	0.000	119.999	-10.003	50.000
1178.000	1385.000	575.375	1.043	1.292	0.000	119.999	-10.003	50.000
1628.000	580.000	573.533	0.000	.036	0.000	209.507	0.000	450.000
1628.000	890.000	574.101	.568	.063	0.000	218.198	-8.691	450.000
1628.000	1020.000	574.404	.304	.072	0.000	228.654	-19.147	450.000
1628.000	1385.000	575.460	1.055	.084	0.000	374.454	-164.947	450.000
2428.000	580.000	573.565	0.000	.032	0.000	225.991	0.000	800.000
2428.000	890.000	574.149	.584	.049	0.000	259.985	-33.994	800.000
2428.000	1020.000	574.455	.306	.051	0.000	276.699	-50.709	800.000
2428.000	1385.000	575.507	1.051	.047	0.000	491.801	-265.810	800.000
3228.000	580.000	573.606	0.000	.041	0.000	47.917	0.000	800.000
3228.000	890.000	574.190	.584	.041	0.000	48.785	-.868	800.000
3228.000	1020.000	574.485	.295	.029	0.000	49.203	-1.287	800.000
3228.000	1385.000	575.486	1.002	.020	0.000	50.660	-2.753	800.000

3778.000	580.000	574.057	0.000	.451	0.000	73.096	0.000	550.000
3778.000	610.000	574.830	.773	.640	0.000	133.708	-60.612	550.000
3778.000	615.000	575.174	.343	.689	0.000	197.426	-124.329	550.000
3778.000	635.000	576.208	1.034	.721	0.000	287.356	-214.259	550.000
3828.000	580.000	574.030	0.000	-.028	0.000	25.000	0.000	50.000
3828.000	610.000	574.892	.862	.062	0.000	124.165	-99.165	50.000
3828.000	615.000	575.224	.332	.050	0.000	146.333	-121.333	50.000
3828.000	635.000	576.229	1.005	.021	0.000	229.999	-204.999	50.000
3829.000	580.000	574.030	0.000	.000	0.000	25.000	0.000	1.000
3829.000	610.000	574.901	.871	.009	0.000	124.229	-99.229	1.000
3829.000	615.000	575.232	.331	.008	0.000	147.468	-122.468	1.000
3829.000	635.000	576.234	1.002	.005	0.000	229.999	-204.999	1.000
3884.000	580.000	574.038	0.000	.008	0.000	25.000	0.000	55.000
3884.000	610.000	575.213	1.176	.312	0.000	145.401	-120.401	55.000
3884.000	615.000	575.527	.314	.296	0.000	201.511	-176.511	55.000
3884.000	635.000	576.369	.842	.135	0.000	229.999	-204.999	55.000
3885.000	580.000	574.038	0.000	.000	0.000	25.000	0.000	1.000
3885.000	610.000	575.208	1.170	-.005	0.000	145.404	-120.404	1.000
3885.000	615.000	575.523	.315	-.004	0.000	200.363	-175.363	1.000
3885.000	635.000	576.366	.843	-.003	0.000	229.999	-204.999	1.000
4035.000	580.000	574.270	0.000	.232	0.000	109.525	0.000	150.000
4035.000	610.000	575.218	.948	.010	0.000	201.448	-91.923	150.000
4035.000	615.000	575.532	.314	.009	0.000	215.154	-105.629	150.000
4035.000	635.000	576.375	.843	.009	0.000	365.861	-256.336	150.000
4265.000	580.000	574.348	0.000	.078	0.000	96.712	0.000	230.000
4265.000	610.000	575.254	.906	.036	0.000	363.580	-266.868	230.000
4265.000	615.000	575.560	.306	.028	0.000	384.601	-287.889	230.000
4265.000	635.000	576.386	.826	.010	0.000	430.674	-333.962	230.000
4266.000	580.000	574.391	0.000	.043	0.000	97.184	0.000	1.000
4266.000	610.000	575.287	.896	.033	0.000	366.195	-269.011	1.000
4266.000	615.000	575.586	.299	.026	0.000	386.508	-289.324	1.000
4266.000	635.000	576.399	.813	.013	0.000	430.678	-333.495	1.000
4313.000	580.000	575.168	0.000	.777	0.000	233.857	0.000	47.000
4313.000	610.000	575.527	.359	.240	0.000	382.500	-148.643	47.000
4313.000	615.000	575.684	.157	.098	0.000	393.151	-159.294	47.000
4313.000	635.000	576.435	.751	.036	0.000	433.315	-199.458	47.000
4314.000	580.000	575.157	0.000	-.012	0.000	230.725	0.000	1.000
4314.000	610.000	575.517	.360	-.010	0.000	382.153	-151.428	1.000
4314.000	615.000	575.675	.158	-.009	0.000	393.152	-162.427	1.000
4314.000	635.000	576.429	.755	-.005	0.000	433.027	-202.302	1.000
4524.000	580.000	575.236	0.000	.079	0.000	366.577	0.000	210.000
4524.000	610.000	575.583	.346	.066	0.000	386.498	-19.921	210.000
4524.000	615.000	575.733	.150	.058	0.000	395.131	-28.554	210.000
4524.000	635.000	576.460	.727	.031	0.000	436.520	-69.943	210.000
5024.000	580.000	575.293	0.000	.057	0.000	232.852	0.000	500.000
5024.000	610.000	575.624	.332	.042	0.000	233.999	-1.147	500.000
5024.000	615.000	575.769	.144	.036	0.000	233.999	-1.147	500.000
5024.000	635.000	576.478	.710	.018	0.000	233.999	-1.147	500.000
5524.000	580.000	575.413	0.000	.121	0.000	229.999	0.000	500.000
5524.000	610.000	575.725	.312	.101	0.000	229.999	-.000	500.000
5524.000	615.000	575.858	.133	.090	0.000	229.999	-.000	500.000
5524.000	635.000	576.531	.673	.053	0.000	229.999	-.000	500.000

5924.000	580.000	575.440	0.000	.026	0.000	190.990	0.000	400.000
5924.000	610.000	575.747	.308	.022	0.000	191.999	-1.009	400.000
5924.000	615.000	575.879	.132	.020	0.000	191.999	-1.009	400.000
5924.000	635.000	576.544	.665	.013	0.000	191.999	-1.009	400.000
6024.000	580.000	575.451	0.000	.011	0.000	109.999	0.000	100.000
6024.000	610.000	575.756	.305	.009	0.000	109.999	-.000	100.000
6024.000	615.000	575.886	.130	.008	0.000	109.999	-.000	100.000
6024.000	635.000	576.548	.662	.004	0.000	109.999	-.000	100.000
6199.000	595.000	575.341	0.000	-.110	0.000	24.000	0.000	175.000
6199.000	620.000	575.646	.305	-.110	0.000	24.000	0.000	175.000
6199.000	625.000	575.779	.132	-.108	0.000	24.000	0.000	175.000
6199.000	645.000	576.451	.672	-.097	0.000	24.000	0.000	175.000
6200.000	595.000	575.343	0.000	.002	0.000	24.000	0.000	1.000
6200.000	620.000	575.648	.305	.002	0.000	24.000	0.000	1.000
6200.000	625.000	575.780	.132	.002	0.000	24.000	0.000	1.000
6200.000	645.000	576.452	.672	.001	0.000	24.000	0.000	1.000
6290.000	595.000	577.852	0.000	2.509	0.000	24.000	0.000	90.000
6290.000	620.000	578.394	.542	2.746	0.000	24.000	0.000	90.000
6290.000	625.000	578.577	.183	2.797	0.000	24.000	0.000	90.000
6290.000	645.000	579.458	.881	3.006	0.000	24.000	0.000	90.000
6291.000	595.000	577.853	0.000	.001	0.000	24.000	0.000	1.000
6291.000	620.000	578.395	.542	.001	0.000	24.000	0.000	1.000
6291.000	625.000	578.578	.183	.001	0.000	24.000	0.000	1.000
6291.000	645.000	579.459	.881	.000	0.000	24.000	0.000	1.000
6313.000	595.000	578.023	0.000	.171	0.000	67.999	0.000	22.000
6313.000	620.000	578.557	.534	.162	0.000	67.999	-.000	22.000
6313.000	625.000	578.736	.179	.158	0.000	67.999	-.000	22.000
6313.000	645.000	579.597	.862	.138	0.000	67.999	-.000	22.000
7013.000	595.000	578.080	0.000	.057	0.000	329.510	0.000	700.000
7013.000	620.000	578.607	.527	.051	0.000	341.878	-12.368	700.000
7013.000	625.000	578.784	.177	.048	0.000	344.967	-15.458	700.000
7013.000	645.000	579.636	.852	.039	0.000	359.877	-30.367	700.000
7513.000	595.000	578.093	0.000	.013	0.000	280.458	0.000	500.000
7513.000	620.000	578.617	.524	.010	0.000	290.451	-9.992	500.000
7513.000	625.000	578.793	.176	.009	0.000	293.959	-13.501	500.000
7513.000	645.000	579.642	.849	.006	0.000	311.000	-30.542	500.000
8013.000	595.000	578.119	0.000	.026	0.000	192.969	0.000	500.000
8013.000	620.000	578.637	.517	.020	0.000	198.302	-5.333	500.000
8013.000	625.000	578.810	.174	.018	0.000	199.999	-7.030	500.000
8013.000	645.000	579.652	.842	.011	0.000	199.999	-7.030	500.000
8445.000	595.000	578.136	0.000	.016	0.000	26.999	0.000	432.000
8445.000	620.000	578.634	.498	-.003	0.000	26.999	-.000	432.000
8445.000	625.000	578.803	.169	-.008	0.000	26.999	-.000	432.000
8445.000	645.000	579.628	.825	-.024	0.000	26.999	-.000	432.000
8473.000	595.000	578.057	0.000	-.078	0.000	12.500	0.000	28.000
8473.000	620.000	578.550	.493	-.084	0.000	12.500	0.000	28.000
8473.000	625.000	578.718	.168	-.085	0.000	12.500	0.000	28.000
8473.000	645.000	579.543	.825	-.085	0.000	12.500	0.000	28.000
8474.000	595.000	578.059	0.000	.002	0.000	12.500	0.000	1.000
8474.000	620.000	578.551	.492	.002	0.000	12.500	0.000	1.000
8474.000	625.000	578.719	.168	.001	0.000	12.500	0.000	1.000
8474.000	645.000	579.544	.825	.001	0.000	12.500	0.000	1.000
8510.000	595.000	578.953	0.000	.89[illegible]	0.000	12.500	0.000	36.000

8510.000	620.000	579.566	.613	1.014	0.000	12.500	0.000	36.000
8510.000	625.000	579.763	.197	1.043	0.000	12.500	0.000	36.000
8510.000	645.000	580.711	.948	1.167	0.000	12.500	0.000	36.000
8511.000	595.000	578.954	0.000	.001	0.000	12.500	0.000	1.000
8511.000	620.000	579.567	.612	.001	0.000	12.500	0.000	1.000
8511.000	625.000	579.764	.197	.001	0.000	12.500	0.000	1.000
8511.000	645.000	580.712	.948	.001	0.000	12.500	0.000	1.000
8681.000	740.000	579.369	0.000	.415	0.000	74.561	0.000	170.000
8681.000	855.000	579.952	.583	.385	0.000	83.301	-8.740	170.000
8681.000	880.000	580.139	.187	.375	0.000	86.099	-11.539	170.000
8681.000	915.000	581.054	.915	.342	0.000	99.819	-25.258	170.000
8851.000	740.000	579.265	0.000	-.104	0.000	15.000	0.000	170.000
8851.000	855.000	579.814	.549	-.138	0.000	15.000	0.000	170.000
8851.000	880.000	579.993	.179	-.146	0.000	15.000	0.000	170.000
8851.000	915.000	580.905	.912	-.149	0.000	15.000	0.000	170.000
8852.000	740.000	579.265	0.000	.001	0.000	15.000	0.000	1.000
8852.000	855.000	579.814	.549	.001	0.000	15.000	0.000	1.000
8852.000	880.000	579.994	.179	.001	0.000	15.000	0.000	1.000
8852.000	915.000	580.906	.912	.000	0.000	15.000	0.000	1.000
8868.000	740.000	579.653	0.000	.388	0.000	15.000	0.000	16.000
8868.000	855.000	580.410	.757	.596	0.000	15.000	0.000	16.000
8868.000	880.000	580.647	.237	.653	0.000	15.000	0.000	16.000
8868.000	915.000	581.702	1.055	.796	0.000	15.000	0.000	16.000
8869.000	740.000	579.653	0.000	.000	0.000	15.000	0.000	1.000
8869.000	855.000	580.410	.757	.000	0.000	15.000	0.000	1.000
8869.000	880.000	580.647	.237	.000	0.000	15.000	0.000	1.000
8869.000	915.000	581.702	1.055	.000	0.000	15.000	0.000	1.000
8874.000	740.000	579.972	0.000	.319	0.000	24.999	0.000	5.000
8874.000	855.000	580.779	.806	.368	0.000	24.999	-.000	5.000
8874.000	880.000	581.020	.242	.373	0.000	24.999	-.000	5.000
8874.000	915.000	582.034	1.013	.332	0.000	24.999	-.000	5.000
9177.000	765.000	580.196	0.000	.224	0.000	468.990	0.000	303.000
9177.000	1010.000	581.032	.835	.253	0.000	471.078	-2.088	303.000
9177.000	1100.000	581.276	.244	.256	0.000	471.689	-2.699	303.000
9177.000	1350.000	582.263	.987	.229	0.000	474.156	-5.166	303.000
9677.000	765.000	580.200	0.000	.003	0.000	506.990	0.000	500.000
9677.000	1010.000	581.035	.836	.004	0.000	523.706	-16.716	500.000
9677.000	1100.000	581.280	.245	.004	0.000	528.599	-21.609	500.000
9677.000	1350.000	582.267	.987	.004	0.000	548.333	-41.343	500.000
10177.000	765.000	580.202	0.000	.002	0.000	567.025	0.000	500.000
10177.000	1010.000	581.038	.836	.003	0.000	579.967	-12.942	500.000
10177.000	1100.000	581.283	.245	.003	0.000	584.418	-17.393	500.000
10177.000	1350.000	582.270	.987	.003	0.000	626.663	-59.638	500.000
10622.000	765.000	580.204	0.000	.002	0.000	613.999	0.000	445.000
10622.000	1010.000	581.040	.837	.002	0.000	613.999	-.000	445.000
10622.000	1100.000	581.285	.245	.002	0.000	613.999	-.000	445.000
10622.000	1350.000	582.272	.987	.002	0.000	613.999	-.000	445.000
10654.000	770.000	580.201	0.000	-.002	0.000	679.998	0.000	32.000
10654.000	1015.000	581.039	.837	-.001	0.000	679.998	-.000	32.000
10654.000	1105.000	581.284	.245	-.001	0.000	679.998	-.000	32.000
10654.000	1365.000	582.271	.987	-.001	0.000	679.998	-.000	32.000
10655.000	770.000	580.204	0.000	.003	0.000	679.998	0.000	1.000
10655.000	1015.000	581.040	.836	.003	0.000	679.998	-.000	1.000

10655.000	1105.000	581.285	.245	.002	0.000	679.998	-.000	1.000
10655.000	1365.000	582.272	.987	.001	0.000	679.998	-.000	1.000
10693.000	770.000	580.205	0.000	.000	0.000	679.998	0.000	38.000
10693.000	1015.000	581.041	.836	.000	0.000	679.998	-.000	38.000
10693.000	1105.000	581.285	.245	.000	0.000	679.998	-.000	38.000
10693.000	1365.000	582.272	.986	.000	0.000	679.998	-.000	38.000
10694.000	770.000	580.204	0.000	-.001	0.000	679.998	0.000	1.000
10694.000	1015.000	581.040	.836	-.000	0.000	679.998	-.000	1.000
10694.000	1105.000	581.285	.245	-.000	0.000	679.998	-.000	1.000
10694.000	1365.000	582.272	.987	-.000	0.000	679.998	-.000	1.000
-3228.000	580.000	573.606	0.000	-6.597	0.000	47.917	0.000	0.000
-3228.000	890.000	574.190	.584	-6.850	0.000	48.772	-.854	0.000
-3228.000	1020.000	574.485	.295	-6.800	0.000	49.203	-1.286	0.000
-3228.000	1385.000	575.486	1.002	-6.785	0.000	50.669	-2.752	0.000
3353.000	5.000	575.141	0.000	1.535	0.000	120.534	0.000	125.000
3353.000	300.000	575.559	.418	1.369	0.000	264.669	-144.135	125.000
3353.000	425.000	575.656	.097	1.171	0.000	288.876	-168.342	125.000
3353.000	765.000	575.976	.321	.490	0.000	324.834	-204.301	125.000

DATA FOR LAST CROSS SECTION

PROFILE	TYPE ENC	TARGET	TOP WIDTH AREA-ACRES	TOP WIDTH AREA-DIFF
1	0.000	0.000	52.312	0.000
2	0.000	0.000	55.888	3.577
3	0.000	0.000	57.420	5.108
4	0.000	0.000	66.697	14.386



1) COUNTY: Wayne

2) STUDY NAME: City of Lincoln Park

3) WATERCOURSE: Ecorse Creek

4) DOCUMENT TYPE: Report



FROM: Wade, Trim & Associates, Inc.

25185 Goddard Road P.O. Box 10
Taylor, Michigan 48180

TO:

CITY OF LINCOLN PARK, MICHIGAN

HYDRAULIC REPORT

[redacted]

HYDRAULIC REPORT
LINCOLN PARK

I. INTRODUCTION

The City of Lincoln Park is located in the southeastern corner of Michigan in Wayne County. It is approximately 6 miles south of the City of Detroit. The City of Lincoln Park is comprised of residential and industrial areas adjacent to the North Branch Ecorse Creek and the South Branch Ecorse Creek.

This report summarizes the hydraulic studies undertaken to support the detailed study of over 3 miles of the North Branch Ecorse Creek and nearly 3 miles of the South Branch Ecorse Creek.

This study was conducted by Wade, Trim & Associates, Inc., Consulting Engineers and Glen Roberts served as Project Manager.

II. SOUTH BRANCH ECORSE CREEK (DETAILED)

Detailed studies were performed on the entire South Branch Ecorse Creek within the City of Lincoln Park. This study includes data and information developed for the Wyandotte, Michigan Flood Insurance Study (Reference 1). In addition a total of 7 cross sections, 3 bridge and 4 valley sections were field surveyed by Wade, Trim & Associates, Inc. and were supplemented by U.S.G.S. Quad Maps which have 5 foot contour intervals (Reference 2).

Table 1 cross references section designations by showing the computer section number which corresponds to the cross section letter shown in Exhibit 1. Table 2 lists discharges that have been approved by the Michigan Department of Natural Resources (M.D.N.R.) in the Wyandotte Flood Insurance Study. These discharges have been used for the South Branch Ecorse Creek within the City of Lincoln Park which extends approximately 1.0 mile west of Wyandotte. Exhibit 2 contains bridge sketches as well as bridge loss coefficients.

A. METHOD OF ANALYSIS

The HEC-2 backwater program was used in developing water surface profiles (Reference 3). The HEC-2 analysis from the Wyandotte Flood Insurance Study was used from the downstream Lincoln Park Corporate Boundary to the end of the analysis, and is presented in Exhibit 3. The HEC-2 printouts including computer cross section plots from the end of the Wyandotte F.I.S. analysis to the upstream Lincoln Park Corporate Boundary are presented as Exhibit 4. (Exhibit 4 is contained in the 11" x 15" folder enclosed with this report.) Water surface profiles resulting from the backwater analyses are presented as Exhibit 5.

B. VARIABLES AND COEFFICIENTS

Roughness coefficients (Mannings "n") were estimated by field inspection at each cross section. Typical roughness values for the main channel of South Branch Ecorse Creek range from .03 to .035; roughness values for the overbank areas varied between .03 to .06 for all floods. These values are indicative of summer month conditions and are consistent with values recommended and used in engineering practice (Reference 4). Contraction and expansion coefficients selected are 0.3 and 0.5 at bridge sections and channel transitions.

C. HIGH WATER MARKS

There is no documented high water data on the South Branch Ecorse Creek.

D. STARTING CONDITIONS

The South Branch Ecorse Creek is a common borderline between Lincoln Park and the City of Wyandotte between cross sections H and W. Therefore, the HEC-2 computer run (Exhibit 3) from the Wyandotte F.I.S. was utilized for this segment of the hydraulic analysis. From cross section W to the upstream limit of this study, additional HEC-2 computer runs (Exhibit 4) were performed and flow rates and elevations from section W of the Wyandotte study were used as starting conditions.

E. SPECIAL PROBLEMS

The Method 4 encroachment option in the HEC-2 computer program was not used on the South Branch Ecorse Creek. The 100 year flood stays within the channel banks at all locations, therefore, the floodway was set at the top of banks.

F. GENERAL

Computed water surface elevations were developed to an accuracy of 0.5 feet for floods of the selected recurrence intervals.

All elevations are referred to the U.S. Geological and Coastal Survey (U.S.G.C.S.) Datum. This datum is equivalent to the National Vertical Datum of 1929 (N.G.V.D.).

The hydraulic analyses for this study were based only on the effects of flow unobstructed by ice or debris. The flood elevations are considered only if hydraulic structures, in general, remain unobstructured and do not fail.

TABLE 1

LINCOLN PARK, MICHIGAN

SOUTH BRANCH ECORSE CREEK

(SEXTON-KILFOIL DRAIN)

CROSS REFERENCE INDEX

COMPUTER SECTION NUMBER	FIELD BOOK STATION	FW & FB LETTER	DESCRIPTION
2436		I*	Confluence w/North Branch
3186		J*	Valley Section
4186		K*	50 Ft. d/s Emmons St. Bridge
4281		L*	u/s Face Emmons St. Bridge
4931		M*	Valley Section
6981		N*	Valley Section
8031		O*	51 Ft. d/s Harrison St. Bridge
8147		P*	u/s Face Harrison St. Bridge
9397		Q*	Valley Section
10297		R*	Valley Section
10897		S*	76 Ft. d/s Harrison St. Bridge #2
11017		T*	u/s Face Harrison St. Bridge #2
11477		U*	51 Ft. d/s North Bound Fort St.
11528		V*	d/s Face North Bound Fort St.
11721		W*	u/s Face South Bound Fort St.
12689	44 + 95	X	Valley Section
13269	39 + 15	Y	d/s Face Howard Avenue
13309	38 + 75	Z	u/s Face Howard Avenue
15144	20 + 40	AA	Valley Section
15434	17 + 50	AB	d/s Face Dix Avenue
15555	16 + 29	AC	u/s Face Dix Avenue
15859	13 + 25	AD	Valley Section
16340	8 + 44	AE	d/s Face Hazel Avenue
16379	8 + 05	AF	u/s Face Hazel Avenue
17184	0 + 00	AG	Valley Section Lincoln Park Corporate Boundary

* Cross Section From Wyandotte F.I.S.

TABLE 2

CITY OF LINCOLN PARK

SOUTH BRANCH ECORSE CREEK FLOOD FLOW DATA

LOCATION		DISCHARGE - CFS 10 YR.	50 YR.	100 YR.	500 YR.
Confluence w/ North Branch		~~3165~~ 3170	4100	4410	5160
(X-Section I)	Elev.	577.03	577.97	578.27	578.99
Emmons Street		1120	1620	1760	2055
(X-Section L)	Elev.	577.76	578.93	579.28	580.06

III. NORTH BRANCH ECORSE CREEK (DETAILED)

Detailed studies were performed on the entire North Branch Ecorse Creek within the City of Lincoln Park. This study includes data and information developed for the City of Ecorse, Michigan Flood Insurance Study (Reference 5). In addition a total of 15 cross sections, 11 bridge and 4 valley sections were field surveyed by Wade, Trim & Associates, Inc. and were supplemented by U.S.G.S. Quad Maps which have 5 foot contour intervals (Reference 2 and 6). One bridge cross section was obtained from construction plans (Reference 7). Table 3 cross references section designations by showing the computer section number which corresponds to the cross section letter shown in Exhibit 1. Table 4 lists discharges that have been approved by the Michigan Department of Natural Resources (M.D.N.R.). Exhibit 6 contains bridge sketches as well as bridge loss coefficients.

A. METHOD OF ANALYSIS

The HEC-2 backwater program was used in developing water surface profiles (Reference 3). A portion of Lincoln Park has a common border with the City of Ecorse at the North Branch Ecorse Creek. Therefore, the HEC-2 computer analysis from the City of Ecorse Flood Insurance Study was used for the downstream portion of this study (Exhibit 7). From that point, which is the upstream corporate limit of the City of Ecorse, to the upstream limit of this study, this office performed the HEC-2 computer backwater analysis. The HEC-2 printouts including cross section plots from the end of the Ecorse F.I.S. analysis to the upstream Lincoln Park Corporate Boundary are presented as Exhibit 8. (Exhibit 8 is contained in the 11" x 15" folder enclosed with this report.) Water surface profiles resulting from the backwater analyses are presented as Exhibit 9.

not included

B. VARIABLES AND COEFFICIENTS

Roughness coefficients (Mannings "n") were estimated by field inspection at each cross section. Typical roughness values for the main channel and the overbanks for all floods are as follows:

1. Reach between cross sections A and L, from City of Ecorse F.I.S.:

   a) main channel .025 - .033

   b) overbanks .035

2. Reach between cross sections M and AO:

   a) main channel 0.02 - 0.035

   b) overbanks 0.04 - 1.0

These values are indicative of summer month conditions and are consistent with values recommended and used in engineering practice (Reference 4). The high Mannings n values in the overbanks are representative of a single structure or a high density multiple structure area which is considered non-effective for flow. Contraction and expansion coefficients selected are:

1. Reach between cross sections A and L, from City of Ecorse F.I.S., 0.3 and 0.5.

2. Reach between cross sections M and AO, 0.1 and 0.3 for gradual channel transitions and 0.3 and 0.5 for bridge sections.

C. HIGH WATER MARKS

There is no documented high water data on the North Branch Ecorse Creek.

D. STARTING CONDITIONS

This report utilizes the HEC-2 computer run for the City of Ecorse F.I.S. (Exhibit 9) between cross sections A and K. At cross section L, the valley section data from the City of Ecorse F.I.S. was used as the starting cross section for the upstream reach of river. The starting flows were taken from Hydrology Report for the City of Lincoln Park and the starting elevations were taken from the City of Ecorse F.I.S.

E. SPECIAL PROBLEMS

The floodway for the North Branch Ecorse Creek is mostly controlled by allowable expansion and contraction ratios at bridges and densely developed areas along the creek which render overbank flow areas ineffective. Three of the valley sections in this study were considered unaffected by expansion and contraction ratio limits, therefore, the Method 4 encroachment option in the HEC-2 computer program was used. The results of this encroachment run were incorporated into the final floodway model.

F. GENERAL

Computed water surface elevations were developed to an accuracy of 0.5 feet for floods of the selected recurrence intervals.

All elevations are referenced to the U.S. Geological and Coastal Survey (U.S.G.C.S.) Datum. This datum is equivalent to the National Vertical Datum of 1929 (N.G.V.D.).

The hydraulic analyses for this study were based only on the effects of flow unobstructed by ice or debris. The flood elevations are considered only if hydraulic structures, in general, remain unobstructured and do not fail.

TABLE 3

LINCOLN PARK, MICHIGAN

NORTH BRANCH ECORSE CREEK

CROSS REFERENCE INDEX

COMPUTER SECTION NUMBER	WTA STATION	FW & FB LETTER	DESCRIPTION
2736		A	Valley Section 300' u/s Confluence w/South Branch Ecorse Creek
3836		B	Valley Section
4786		C	39' d/s Mill Street
4846		D	u/s Face Mill Street
5936		E	Valley Section
6786		F	49' d/s Southfield Road
6916		G	u/s Face Southfield Road
7936		H	Valley Section
9136		I	Valley Section
10286		J	50' d/s Empire Street
10336		K	Empire Street, Bridge has been removed
10636		L	Valley Section
11536	86 + 03	M	Valley Section
12324		N	d/s Face Austin
	78 + 03		Center Line Austin
12368		O	u/s Face Austin
13295	68 + 54	P	Valley Section
13726	64 + 23	Q	d/s Fase Victoria
13965	61 + 84	R	u/s Face Victoria
14337	58 + 12	S	d/s Face North Bound Fort Street
14403	57 + 46	T	u/s Face North Bound Fort Street
14460	56 + 89	U	d/s Face South Bound Fort Street
14522	56 + 27	V	u/s Face South Bound Fort Street
15292	48 + 57	W	Valley Section
15870		X	d/s Face Lafayette
	42 + 57		Center Line Lafayette
15914		Y	u/s Face Lafayette
16244	39 + 05	Z	d/s Face I-75
16504	36 + 45	AA	u/s Face I-75
16876		AB	d/s Face Industrial Drive
16963		AC	u/s Face Industrial Drive
17305	28 + 44	AD	d/s Face Penn Central R.R. Bridge
17502	26 + 47	AE	u/s Face Penn Central R.R. Bridge
18156		AF	d/s Face Porter Street
	19 + 73		Center Line Porter Street
18196		AG	u/s Face Porter Street
18545	16 + 04	AH	Valley Section
18879		AI	d/s Face Raupp Place
	12 + 54		Center Line Raupp Place
18911		AJ	u/s Face Raupp Place
19162	9 + 87	AK	d/s Face Dix Road
19264	8 + 85	AL	u/s Face Dix Road
20130		AM	d/s Face Frank Avenue
	0 + 00		Center Line Frank Avenue
20169		AN	u/s Face Frank Avenue
20269		AO	Valley Section

TABLE 4

CITY OF LINCOLN PARK

NORTH BRANCH ECORSE CREEK FLOOD FLOW DATA

LOCATION		DISCHARGE - CFS 10 YR.	50 YR.	100 YR.	500 YR.
Confluence w/ South Branch		1500	1950	2100	2495
(X-Section A)	Elev.	577.14	578.14	578.47	579.26
Lincoln Park-Ecorse Boundary		850	1250	1410 (2200)	1840
(X-Section L)	Elev.	582.06	583.19	583.53	584.43
u/s I-75		770	1160	1330	1940
(X-Section AB)	Elev.	585.47	587.30	587.75	588.78

REFERENCES

1. City of Wyandotte, Michigan, Flood Insurance Study, Flood Insurance Administration, Draft.

2. U.S. Geological Survey Topographical Maps - Wyandotte Quadrangle, Michigan - Ontario, 7.5 Minute Series - Photo Revised 1973.

3. HEC-2 Water Surface Profile - Users Manual - U.S. Army Corps of Engineers - 1976.

4. Open Channel Hydraulics, Chow, Ven Te, McGraw-Hill Book Company, 1959.

5. City of Ecorse, Michigan, Flood Insurance Study, Flood Insurance Administration, Draft, February 1977.

6. U.S. Geological Survey Topographical Maps - Dearborn Quadrangle, Wayne County, Michigan, 7.5 Minute Series - Photo Revised 1973.

7. Industrial Drive Culvert, Pate, Hirn, Bogue, Sheets 13 and 14 of 15, June 8, 1979.

INDEX OF EXHIBITS

EXHIBIT 1	Field Cross Section Location and 100 Year Flood Plain Floodway Map, 2 Sheets.
EXHIBIT 2	Bridge Notes and Sketches, South Branch Ecorse Creek, 5 Sheets.
EXHIBIT 3	HEC-2 Backwater Analysis from City of Wyandotte F.I.S., South Branch Ecorse Creek, 28 Sheets.
EXHIBIT 4	HEC-2 Backwater Analysis with Cross Section Plots, South Branch Ecorse Creek (Separate Folder).
EXHIBIT 5	Stream Profile, South Branch Ecorse Creek, 2 Sheets.
EXHIBIT 6	Bridge Notes and Sketches, North Branch Ecorse Creek, 16 Sheets.
EXHIBIT 7	HEC-2 Backwater Analysis from City of Ecorse F.I.S., North Branch Ecorse Creek, 41 Sheets.
EXHIBIT 8	HEC-2 Backwater Analysis with Cross Section Plots, North Branch Ecorse Creek (Separate Folder).
EXHIBIT 9	Stream Profile, North Branch Ecorse Creek, 2 Sheets.

CITY OF LINCOLN PARK, MICHIGAN

SOUTH BRANCH ECORSE CREEK

AND NORTH BRANCH ECORSE CREEK

EXHIBIT 1

Field Cross Section Location and

100 Year Flood Plain Floodway

Map

CITY OF LINCOLN PARK, MICHIGAN

SOUTH BRANCH ECORSE CREEK

EXHIBIT 2

Bridge Notes and Sketches

Bridge Location: HOWARD AVE
Bridge Losses - SB Crit

EXHIBIT 2

REFERENCE

1. XK (Pier Shape Coefficient) 1.025 — HEC-2 Manual

XKOR (Loss Coefficient) = 1.0 + Σk, $\Sigma k = k_f + k_e + k_p$

where k_f = friction loss coefficient
k_e = entrance loss coefficient
k_p = loss from intermediate piers

Description of Bridge:

$K_f = 29.1\, n^2 L / R^{4/3}$ for English units

Area = 414 Wp = 128.

$R = A/wp$ 414/128 $R^{4/3} = 4.78$ L = 40

n (composite) =


$K_f = 29.1 \times (0.02)^2 \times 40 / 4.78 = 0.10$

$K_e = 0.5$ — Hydraulic Charts for the Selection of Highway Culverts Circular No. 5 Dec. 1965 pg. 49

$K_p = 0$ if bridge has no intermediate piers

~~$K_p = 0.05$~~ if bridge has intermediate piers — HEC-2 manual

TRD 584.5



2. XKOR = 1 + 0.10 + .05 + 0.05 = 1.65
3. COFQ = Coefficient of discharge = 3.0 — HEC-2 manual
4. RDLEN = Length of weir = 0.0 (0 if read off BT cards)
5. BWC = bottom width of bridge opening (inc. piers) = 47.
6. BWP = total width of obstruction = 1. — field data
7. BAREA = bridge opening inc. piers = 414.
8. SS = side slope = 0. (horizontal per 1 vertical unit)
9. ELCHU = Elevation of channel invert U/S side = 573.
(0 if equal to minimum elevation in previous X-sect.)
10. ELCHD = Elevation of channel invert D/S side = 573.
(0 if equal to minimum elevation in previous X-sect.)


SUBJECT	BY	CHK	SHEET NO.	File Code No (Job No) Owner Project Suffix
LINCOLN PARK	DRB		1 OF 5	HUD • 2010 • 07
	DATE 9/79	DATE		

HUD 2010-05

BRIDGE DETAIL HOWARD AVE. AND SOUTH BRANCH ECORSE CREEK.

F.B. #941 A.P. B.O. L.C.

JAN. 17-1978



VIEW STANDING DOWNSTREAM FACING UPSTREAM

Bridge Location : DIX AVE
Bridge Losses - SB Card

EXHIBIT 2

REFERENCE

1. XK (Pier Shape Coefficient) 1.025 — HEC-2 Manual

XKOR (Loss Coefficient) = 1.0 + Σk, $\Sigma k = k_f + k_e + k_p$

where k_f = friction loss coefficient
k_e = entrance loss coefficient
k_p = loss from intermediate piers

Description of Bridge :

$K_f = 29.1\, n^2 L / R^{4/3}$ for English units

Area = 409 Wp = 128

$R = A/wp$ 409/128 $R^{4/3} = 4.071$ $L = 121$

n (composite) =


$K_f = 29.1 \times (0.02)^2 \times 121 \;/\; 4.071 = 0.30$

$K_e = 0.5$

Hydraulic Charts for the Selection of Highway Culverts Circular No. 5 Dec. 1965 pg. 49

$K_p = 0$ if bridge has no intermediate piers

$K_p = 0.05$ if bridge has intermediate piers — HEC-2 manual



2. XKOR = 1 + 0.30 + 0.50 + 0.05 = 1.85
3. COFQ = Coefficient of discharge = 3.0 — HEC-2 manual
4. RDLEN = Length of weir = 0 (0 if read off BT cards)
5. BWC = bottom width of bridge opening (inc. piers) = 48.0
6. BWP = total width of obstruction = 2.0 — field data
7. BAREA = bridge opening inc. piers = 409
8. SS = side slope = 0
(horizontal per 1 vertical unit)
9. ELCHU = Elevation of channel invert U/S side = 574.09
(0 if equal to minimum elevation in previous x-sect.)
10. ELCHD = Elevation of channel invert D/S side = 574.09
(0 if equal to minimum elevation in previous x-sect.)

SUBJECT	BY	CHK	SHEET NO	File Code No (Job No) Owner Project Suffix
LINCOLN PARK	DRB		3 OF 5	HUD • 2010 • 07
	DATE 9/29	DATE		

EXHIBIT 2

sheet 4 of 5

EXHIBIT 2

VIEW STANDING DOWNSTREAM FACING UPSTREAM.

CURRENT DATA:

A.P. L.C. 43.

LT JAN. 13 - 1, 70

CONC.

3.5'

10.30'

35'

S75°35

S89.15

BOTTOM OF CHANNEL

BRIDGE 1 MI.

SOUTH BRANCH ECORSE CREEK

HAZEL AVE.

STA 8+124.5 N.

STA 8+111

STA 8+25

TOP OF BANK

TOE OF BANK

DOWNSTREAM

UPSTREAM

S89.60

S89.25

S89.42

S89.80

S89.20

S75°8

S76°

S76°5

S76°5

N- 90°- E.

90°

2.50'

2.03'

1.94'

34'

39'

16'

12'

15'

29'

9'

3'

sheet 5 of 5

2010-05

CITY OF LINCOLN PARK, MICHIGAN

SOUTH BRANCH ECORSE CREEK

EXHIBIT 3

HEC-2 Backwater Analysis From

City of Wyandotte F.I.S.

```
C
C      1
C     61        D/S FACE JEFFERSON STREET BRIDGE
C    136        U/S FACE JEFFERSON STREET BRIDGE
C    788        D/S FACE RR BRIDGE #1
C    797        U/S FACE RR BRIDGE #1
C    845        D/S FACE RR BRIDGE #2
C    859        U/S FACE RR BRIDGE #2
C    911        D/S FACE RR BRIDGE #3
C    921        U/S FACE RR BRIDGE #3
C    985        D/S FACE RR BRIDGE #4
C    995        U/S FACE RR BRIDGE #4
C   2436  CONFLUENCE OF THE NORTH ECORSE RIVER & SEXTON-KILFOIL DRAIN
C   4236        D/S FACE OF EMMONS STREET BRIDGE
C   4261        U/S FACE OF EMMONS STREET BRIDGE
C   8082        D/S FACE OF HARRISON STREET BRIDGE
C   8147        U/S FACE OF HARRISON STREET BRIDGE
C  10973        D/S FACE OF HARRISON STREET BRIDGE #2
C  11017        U/S FACE OF HARRISON STREET BRIDGE #2
C  11528        D/S FACE OF NORTH BOUND FORT STREET
C  11599        U/S FACE OF NORTH BOUND FORT STREET
C  11650        D/S FACE OF SOUTH BOUND FORT STREET
C  11721        U/S FACE OF SOUTH BOUND FORT STREET
T1      CITY OF WYANDOTTE FIS 5555-73
T2      SEXTON-KILFOIL DRAIN
T3      10 YEAR FLOOD 3165 CFS
J1          2                                                    574.90
J2   -10          -1
NC 0.035   0.035   0.032     0.3       0.5
QT      4   3165    4100     4410      5160
X1      1     41     500      619
GR 576.2      0   575.9     100     576.6     200     578.5     300     581.1     400
GR 584.6    500   582.8     500     582.6     505     581.9     510     581.1     515
GR 579.2    520   575.4     525     574.8     530     572.8     535     569.2     540
GR 569.2    540   565.5   543.5     565.5   543.5     565.5     545     563.9     555
GR 566.1    560   565.3     565     565.4     570     564.1     575     566.2     580
GR 566.2    580   565.3   583.5     565.3   583.5     565.3     585     563.4     590
GR 564.4    595   565.4     600     567.7     605     571.1     610     573.5     615
GR 574.0    619   584.6     619     582.3     700     579.6     800     579.0     890
GR 578.7   1000
X1     30                                  29        29        29
X1     60     41     500      619       30        30        30
GR 576.2      0   575.9     100     576.6     200     578.5     300     581.1     400
GR 584.6    500   582.8     500     582.6     505     581.9     510     581.1     515
GR 579.2    520   575.4     525     574.8     530     572.8     535     569.2     540
GR 569.2    540   565.5   543.5     565.5   543.5     565.5     545     563.9     555
GR 566.1    560   565.3     565     565.4     570     564.1     575     566.2     580
GR 566.2    580   565.3   583.5     565.3   583.5     565.3     585     563.4     590
GR 564.4    595   565.4     600     567.7     605     571.1     610     573.5     615
GR 574.0    619   584.6     619     582.3     700     579.6     800     579.0     890
GR 578.7   1000
X1     61     41     500      619       1         1         1
BT     9  500.0   584.3   579.8   500.0   587.7   579.8   540.0   580.1   580.3
BT 543.5  580.1   580.3   560.0   580.3   580.3   580.0   580.1   580.3   583.5
BT 588.1  580.3   619.0   587.7   579.7   619.0   584.4   579.7
GR 576.2      0   575.9     100     576.6     200     578.5     300     581.1     400
GR 584.6    500   582.8     500     582.6     505     581.9     510     581.1     515
GR 579.2    520   575.4     525     574.8     530     572.8     535     569.2     540
GR 569.3    540   580.3   543.5     565.5   543.5     565.5     545     563.9     555
GR 566.1    560   565.3     565     565.4     570     564.1     575     566.2     580
GR 566.4    580   580.3   583.5     565.3   583.5     565.3     585     563.4     590
GR 564.4    595   565.4     600     567.7     605     571.1     610     573.5     615
GR 574.0    619   584.6     619     582.3     700     579.6     800     579.0     890
```

Exhibit 3
1 of 28

X1	137	41	500	619	1	1	1				
[redacted]											
		590	582.8	500	582.6	505	581.9	510	581.1	515	
		620	575.4	525	574.8	530	572.8	535	569.2	540	
		640	567.5	549.5	569.5	543.5	565.5	545	564.9	555	
		580	565.3	583.5	565.4	570	564.1	575	563.2	580	
GR	564.4	595	565.4	600	567.7	605	571.1	610	573.5	615	
GR	574.3	619	584.6	619	582.3	700	579.6	800	579.0	890	
GR	576.7	1000									
TC	0.035	0.042	0.032								
X1	187	27	331	441	50	50	50				
GR	575.8	0	576.6	41	578.5	141	580.6	241	583.1	331	
GR	575.4	341	574.8	346	571.3	351	568.1	356	567.2	361	
GR	565.7	366	565.1	371	565.5	376	565.1	381	564.7	391	
GR	564.1	401	564.4	406	565.7	411	568.2	416	570.5	421	
GR	572.8	426	574.8	432	580.2	441	583.6	454	581.0	541	
GR	579.3	641	578.3	698							
X1	362	35	244	400	175	175	175		.27		
GR	580.2	0	579.5	100	578.3	200	578.3	244	574.6	254	
GR	573.6	255	571.5	260	569.8	265	568.5	270	567.6	275	
GR	566.9	280	565.9	285	565.6	290	563.7	300	563.7	310	
GR	564.3	320	565.8	330	568.2	340	569.8	345	571.1	350	
GR	571.6	355	572.4	360	572.1	365	572.6	370	572.6	375	
GR	572.8	380	572.8	385	572.9	390	574.6	395	576.9	400	
GR	577.6	500	577.7	545	577.5	600	577.7	700	577.5	800	
X1	737	35	244	400	375	375	375				
GR	580.2	0	579.5	100	578.3	200	578.3	244	574.6	254	
GR	573.6	255	571.5	260	569.8	265	568.5	270	567.6	275	
GR	566.9	280	565.9	285	565.6	290	563.7	300	563.7	310	
GR	564.3	320	565.8	330	568.2	340	569.8	345	571.1	350	
GR	571.6	355	572.4	360	572.1	365	572.6	370	572.6	375	
GR	572.8	380	572.8	385	572.9	390	574.6	395	576.9	400	
GR	577.6	500	577.7	545	577.5	600	577.7	700	577.5	800	
X1	787	67	795	901.6	50	50	50				
GR	581.5	0	581.4	95	581.3	195	581.2	295	581.1	395	
GR	581.1	495	581.1	595	581.0	695	581.0	795	575.2	795	
GR	574.5	800	574.5	800	574.5	801	574.5	801	574.0	805	
GR	573.2	810	573.2	810	573.2	811	573.2	811	570.8	815	
GR	569.3	820	570.1	825	570.1	825	570.1	826	570.1	826	
GR	566.6	829.9	566.6	829.9	566.6	831.2	566.6	831.2	565.5	835	
GR	565.5	835	565.5	836	565.5	836	563.9	840	564.5	845	
GR	564.5	845	564.5	846	564.5	846	564.9	850	564.9	855	
GR	564.9	855	564.9	856	564.9	856	565.5	860	565.2	865	
GR	565.2	865	565.2	866.3	565.3	866.3	566.0	870	566.0	875	
GR	566.0	875	566.0	876	566.0	876	566.7	880	568.7	885	
GR	568.3	890	569.7	895	571.7	900	571.7	901.6	581.0	901.6	
GR	580.8	995	580.8	1095	580.6	1195	580.4	1295	580.1	1395	
GR	579.9	1495	580.0	1540							
X1	788	67	795	901.6	1	1	1				
BT	4	795.0	581.0	577.2	830.0	581.0	577.2	860.0	581.0	577.2	
BT	901.6	581.0	577.2								
GR	581.5	0	581.4	95	581.3	195	581.2	295	581.1	395	
GR	581.1	495	581.1	595	581.0	695	581.0	795	575.2	795	
GR	574.5	800	575.5	800	575.5	801	574.5	801	574.0	805	
GR	573.2	810	575.5	810	575.5	811	573.2	811	570.8	815	
GR	569.3	820	570.1	825	575.5	825	575.5	826	570.1	826	
GR	566.6	830	577.2	830	577.2	831.3	566.6	831.3	565.5	835	
GR	575.5	835	575.5	836	565.5	836	563.9	840	564.5	845	
GR	575.5	845	575.5	846	564.5	846	564.9	850	564.9	855	
GR	575.5	855	575.5	856	564.9	856	565.5	860	565.2	865	
GR	577.2	865	577.2	866.3	565.2	866.3	566.0	870	566.0	875	
GR	575.5	875	575.5	876	566.0	876	566.7	880	568.7	885	
GR	568.3	890	569.7	895	571.7	900	571.7	901.6	581.0	901.6	
GR	580.8	995	580.8	1095	580.6	1195	580.4	1295	580.1	1395	
GR	579.9	1495	580.0	1540							
X1	797	0	795	901.6	9	9	9				
X2							1				
X1	798	67	795	901.6							

Exhibit 3
2 of 28

[redacted]	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]
X1	798	0	795	901.6	0	9	9				
X2							1				
X	798	67	795	901.6	1	1	1				
GR	581.5	0	581.4	95	581.3	195	581.2	295	581.1	395	
GR	581.1	495	581.1	595	581.0	695	581.0	795	581.2	795	
GR	574.5	800	574.5	800	574.5	801	574.5	801	574.0	805	
GR	573.2	810	573.2	810	573.2	811	573.2	811	570.0	815	
GR	569.3	820	570.1	825	570.1	825	570.1	826	570.1	626	
GR	566.6	829.9	566.6	829.9	566.6	831.2	566.6	831.2	565.5	835	
GR	565.5	835	565.5	836	565.5	836	563.9	840	564.5	845	
GR	564.5	845	564.5	846	564.5	846	564.9	850	564.9	854	
GR	564.9	855	564.9	856	564.9	856	565.5	860	565.2	865	
GR	565.2	865	565.2	866.3	565.3	866.3	566.0	870	566.0	875	
GR	566.0	875	566.0	876	566.0	876	566.7	880	568.7	885	
GR	568.3	890	569.7	895	571.7	900	571.7	901.6	581.0	901.6	
GR	580.8	995	580.8	1095	580.6	1195	580.4	1295	580.1	1395	
GR	579.9	1495	580.0	1540							
X1	844	58	815	924	46	46	46				
GR	583.4	0	583.4	15	583.1	115	582.9	215	582.8	315	
GR	582.6	415	582.3	515	582.1	615	581.8	715	581.5	815	
GR	576.1	815	574.2	820	572.7	825	570.0	829	570.0	829	
GR	570.0	830	570.0	830	568.0	835	565.9	840	565.0	844	
GR	565.0	844	565.0	845	565.0	845	565.0	855	566.0	864	
GR	566.0	864	566.0	865	566.0	865	566.1	874	566.1	874	
GR	566.1	875	566.1	875	565.8	884	565.8	884	565.8	885	
GR	565.8	885	565.6	890	565.2	894	565.2	894	565.2	895	
GR	565.2	895	567.6	900	570.3	905	572.0	909	572.0	909	
GR	572.0	910	572.0	910	574.0	915	575.1	920	576.2	924	
GR	581.4	924	581.3	1015	581.3	1115	581.1	1215	581.1	1315	
GR	581.1	1415	581.2	1515	581.2	1565					
X1	845	58	815	924	1	1	1				
BT	16	815.0	581.5	578.4	829.0	581.5	578.1	830.0	581.5	578.1	
BT	864.0	581.5	577.9	845.0	581.5	577.9	864.0	581.5	577.5	865.0	
BT	581.5	577.5	874.0	581.4	577.4	875.0	581.4	577.4	884.0	581.4	
BT	577.2	885.0	581.4	577.2	894.0	581.4	577.0	895.0	581.4	577.0	
BT	909.0	581.4	576.8	910.0	581.4	576.8	924.0	581.4	576.5		
GR	583.4	0	583.4	15	583.1	115	582.9	215	582.8	315	
GR	582.6	415	582.3	515	582.1	615	581.8	715	581.5	815	
GR	576.1	815	574.2	820	572.7	825	570.0	829	578.1	829	
GR	578.1	830	570.0	830	568.0	835	565.9	840	565.0	844	
GR	577.9	844	577.9	845	565.0	845	565.0	855	566.0	864	
GR	577.5	864	577.5	865	566.0	865	566.1	874	577.4	874	
GR	577.4	875	566.1	875	565.8	884	577.2	884	577.2	885	
GR	565.8	885	565.6	890	565.2	894	577.0	894	577.0	895	
GR	565.2	895	567.6	900	570.3	905	572.0	909	576.8	909	
GR	576.8	910	572.0	910	574.0	915	575.1	920	576.2	924	
GR	581.4	924	581.3	1015	581.3	1115	581.1	1215	581.1	1315	
GR	581.1	1415	581.2	1515	581.2	1565					
X1	859		815	924	14.5	14.5	14.5				
X2							1				
X1	860	58	815	924	1	1	1				
GR	583.4	0	583.4	15	583.1	115	582.9	215	582.8	315	
GR	582.6	415	582.3	515	582.1	615	581.8	715	581.5	815	
GR	576.1	815	574.2	820	572.7	825	570.0	829	570.0	829	
GR	570.0	830	570.0	830	568.0	835	565.9	840	565.0	844	
GR	565.0	844	565.0	845	565.0	845	565.0	855	566.0	864	
GR	566.0	864	566.0	865	566.0	865	566.1	874	566.1	874	
GR	566.1	875	566.1	875	565.8	884	565.8	884	565.8	885	
GR	565.8	885	565.6	890	565.2	894	565.2	894	565.2	895	
GR	565.2	895	567.6	900	570.3	905	572.0	909	572.0	909	
GR	572.0	910	572.0	910	574.0	915	575.1	920	576.2	924	
GR	581.4	924	581.3	1015	581.3	1115	581.1	1215	581.1	1315	
GR	581.1	1415	581.2	1515	581.2	1565					
	810	64	835	942	50	50	50				

Exhibit 3
3 of 28

[redacted]										
	54.3	874	564.3	875	564.3	875	564.8	884	564.8	884
	564.9	894	564.9	894	564.9	894	564.9	895	564.9	895
	564.9	894	564.9	904	564.9	904	564.9	905	564.9	905
	566.1	914	566.1	914	566.1	915	566.1	915	567.0	920
GR	571.0	924	571.0	924	571.0	925	571.0	925	572.4	930
GR	573.9	934	573.9	934	573.9	935	573.9	935	575.0	940
GR	574.9	942	583.0	942	582.7	1035	582.6	1135	582.3	1235
GR	582.1	1335	581.9	1435	581.8	1535	581.8	1585		
X1	911	64	835	942	1	1	1			
BT	6	835.0	583.1	578.6	874.0	583.1	578.6	875.0	583.1	578.6
BT	904.0	583.0	578.6	905.0	583.0	578.6	942.0	583.0	578.6	
GR	583.7	0	583.6	35	583.4	135	583.3	235	583.3	335
GR	583.3	435	583.3	535	583.2	635	583.1	735	583.1	835
GR	574.8	835	572.6	840	571.6	844	575.5	844	575.5	845
GR	571.6	845	570.7	854	575.5	854	575.5	855	570.7	855
GR	565.6	864	575.5	864	575.5	865	565.6	865	564.3	874
GR	578.6	874	578.6	875	564.3	875	564.8	884	575.5	884
GR	575.5	885	564.8	885	564.9	894	575.5	894	575.5	895
GR	564.9	895	564.0	904	578.6	904	578.6	905	564.0	905
GR	566.1	914	575.5	914	575.5	915	566.1	915	567.0	920
GR	571.0	924	575.5	924	575.5	925	571.0	925	572.4	930
GR	573.9	934	575.5	934	575.5	935	573.9	935	575.0	940
GR	574.9	942	583.0	942	582.7	1035	582.6	1135	582.3	1235
GR	582.1	1335	581.9	1435	581.8	1535	581.8	1585		
X1	921		835	942	10	10	10			
X2							1			
X1	922	64	835	942	1	1	1			
GR	583.7	0	583.6	35	583.4	135	583.3	235	583.3	335
GR	583.3	435	583.3	535	583.2	635	583.1	735	583.1	835
GR	574.8	835	572.6	840	571.6	844	571.6	844	571.6	845
GR	571.6	845	570.7	854	570.7	854	570.7	855	570.7	855
GR	565.6	864	565.6	864	565.6	865	565.6	865	564.3	874
GR	564.3	874	564.3	875	564.3	875	564.8	884	564.8	884
GR	564.8	885	564.8	885	564.9	894	564.9	894	564.9	895
GR	564.9	895	564.0	904	564.0	904	564.0	905	564.0	905
GR	566.1	914	566.1	914	566.1	915	566.1	915	567.0	920
GR	571.0	924	571.0	924	571.0	925	571.0	925	572.4	930
GR	573.9	934	573.9	934	573.9	935	573.9	935	575.0	940
GR	574.9	942	583.0	942	582.7	1035	582.6	1135	582.3	1235
GR	582.1	1335	581.9	1435	581.8	1535	581.8	1585		
X1	953	48	600	681	31	31	31			
GR	582.0	0	581.8	100	581.6	200	581.5	300	581.4	400
GR	581.2	500	581.0	600	571.0	600	568.1	605	566.9	610
GR	566.9	610	566.9	612.3	566.9	612.3	565.9	615	565.1	620
GR	565.1	620	565.1	622.3	565.1	622.3	566.3	625	566.2	630
GR	566.2	630	566.2	632.3	566.2	632.3	566.7	635	566.4	640
GR	566.1	645	566.4	650	566.4	650	566.4	652.3	566.4	652.3
GR	566.6	655	567.5	660	567.5	660	567.5	662.3	567.5	662.3
GR	567.5	665	569.9	670	569.9	670	569.9	672.3	569.9	672.3
GR	573.4	680	573.4	681	580.8	681	580.8	700	580.7	800
GR	580.6	900	580.6	1000	580.5	1100				
X1	954	48	600	681	1	1	1			
BT	14	600.0	581.0	577.7	610.0	581.0	577.7	612.3	581.0	577.7
BT	620.0	581.0	577.7	622.3	581.0	577.7	630.0	580.9	577.7	632.3
BT	580.9	577.7	650.0	580.9	577.6	652.3	580.9	577.6	660.0	580.9
BT	577.6	662.3	580.8	577.6	670.0	580.8	577.6	672.3	580.8	577.6
BT	681.0	580.8	577.6							
GR	582.0	0	581.8	100	581.6	200	581.5	300	581.4	400
GR	581.2	500	581.0	600	571.0	600	568.1	605	566.9	610
GR	577.7	610	577.7	612.3	566.9	612.3	565.9	615	565.1	620
GR	577.7	620	577.7	622.3	565.1	622.3	566.3	625	566.2	630
GR	566.2	630	577.7	632.3	566.2	632.3	566.7	635	566.4	640
					577.6	650	577.6	652.3	566.4	652.3
								662.3	567.5	662.3

Exhibit 3
4 of 28

GR	56 .6	655	567.5	660	77.6	660	577.6	662.3	567.5	662.3
[redacted]										
		680	573.4	681	580.8	681	580.8	700	580.7	800
	580.6	900	580.6	1000	580.5	1100				
X1	985			600	681	30.5	30.5	30.5		
X3							1			
X1	986	48	600	681	1	1	1			
GR	582.0	0	581.8	100	581.6	200	581.5	300	581.4	400
GR	581.2	500	581.0	600	571.0	600	568.1	605	566.9	610
GR	566.9	610	566.9	612.3	566.9	612.3	565.9	615	565.1	620
GR	565.1	620	565.1	622.3	565.1	622.3	566.3	625	566.2	630
GR	566.2	630	566.2	632.3	566.2	632.3	566.7	635	566.4	640
GR	566.1	645	566.4	650	566.4	650	566.4	652.3	566.4	652.3
GR	566.6	655	567.5	660	567.5	660	567.5	662.3	567.5	662.3
GR	567.5	665	569.9	670	569.9	670	569.9	672.3	569.9	672.3
GR	573.4	680	573.4	681	580.8	681	580.8	700	580.7	800
GR	580.6	900	580.6	1000	580.5	1100				
NC	0.040	0.035	0.032							
X1	1036	37	565	700	50	50	50			
X3	10					700				
GR	581.9	0	581.2	100	581.2	200	580.8	300	581.0	400
GR	579.9	500	581.1	565	575.4	587	574.9	590	573.9	595
GR	572.5	600	571.0	605	569.8	610	568.8	615	568.0	620
GR	567.4	625	566.6	630	566.3	635	566.2	640	566.3	650
GR	566.8	660	568.3	670	570.2	675	570.4	680	571.7	685
GR	573.1	690	574.8	695	574.9	696	577.7	700	577.5	800
GR	576.6	900	576.6	1000	577.0	1030	576.8	1100	577.5	1200
GR	578.3	1300	579.2	1345						
NC	0.060	0.035	0.032							
X1	1736	40	374	492.5	700	700	700			
X3	10									
GR	580.4	0.0	580.4	167	579.5	283.7	578.8	335.3	579.1	374
GR	577.2	377.9	576.1	381.9	575.1	385.8	574.1	389.8	573.2	393.7
GR	572.4	397.7	571.5	401.6	570.3	405.6	569.4	409.5	568.4	413.5
GR	567.6	417.4	566.9	421.4	566.5	425.3	566.0	429.2	565.7	433.2
GR	565.5	437.2	565.4	441.1	565.5	445.0	565.6	449.0	565.9	453.0
GR	566.5	456.9	567.2	460.8	568.0	464.8	569.0	468.7	569.8	472.7
GR	570.6	476.6	571.7	480.6	573.4	484.5	575.1	488.5	577.5	492.5
GR	577.4	550	577.3	650	577.4	750	577.7	890	579.5	975
X1	2436	31	183	285	700	700	700			
X3						485.0				
GR	579.0	0	579.9	85	578.5	135	577.1	183	575.1	185
GR	573.5	190	572.2	195	571.1	200	570.2	205	568.5	210
GR	567.7	215	566.4	220	565.6	225	565.3	230	565.0	235
GR	564.6	240	564.8	245	565.2	250	566.4	255	567.8	260
GR	568.8	265	569.9	270	571.5	275	574.7	280	575.1	281
GR	577.4	285	577.3	385	578.2	485	577.7	557	578.6	585
GR	579.8	605								
QT	4	1120	1620	1760	2055					
X1	3186	25	200	300	750	750	750			
X3	10					500				
GR	580.6	0	583.1	100	581.3	200	579.6	208	575.2	216
GR	573.9	220	571.6	225	569.9	230	569.9	235	569.3	240
GR	569.1	245	568.8	250	569.2	260	570.8	270	571.1	280
GR	571.7	285	573.0	290	574.1	295	576.4	300	577.9	400
GR	579.0	500	579.1	600	578.7	625	578.7	700	578.9	800
X1	3686				500	500	500		.6	
X3	10					500				
NC	0.040	0.037	0.032							
X1	4186	27	417	500	500	500	500			
X3	10			350		550				
GR	581.8	0	580.9	100	580.6	200	580.0	300	578.9	400
GR	578.2	417	575.0	419	574.7	420	573.0	425	571.2	430
GR	570.5	435	570.4	440	570.4	445	570.3	450	570.0	455

578.18

578.93

578.83

579.55

578.93 579.64

Exhibit 3

5 of 28

GR	581.0	700	583.0	770							
[redacted]	0.	0	0	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]	
X1	4236	32	592	644	50	50	50				
X3	10			592		644					
GR	582.0	0	581.6	92	581.2	192	580.8	292	580.7	392	
GR	580.1	492	580.1	592	570.2	592	569.2	597	570.0	602	579.05
GR	569.7	607	569.0	612	568.1	617	568.1	617	568.1	618.5	
GR	568.1	618.5	568.9	622	568.8	627	569.2	632	570.0	637	
GR	570.6	642	570.6	644	580.0	644	579.3	692	579.6	792	579.73
GR	580.4	892	580.7	992	580.5	1092	580.3	1192	580.0	1292	
GR	579.6	1392	579.3	1492							
SP	1.25	1.37	2.5		50.5	1.5	400	0	568.1	568.1	
X1	4281	32	592	644	45	45	45				
X2			1	577.4	580.0						
X3	10			592		644					
BT	6	592.0	580.1	577.4	617	580.0	577.3	617	580.0	568.1	
BT	618.5	580.0	568.1	618.5	580.0	577.3	644.0	580.0	577.3		
GR	582.0	0	581.6	92	581.2	192	580.8	292	580.7	392	
GR	580.0	492	580.1	592	570.2	592	569.2	597	570.0	602	579.28
GR	569.7	607	569.0	612	568.1	617	568.1	617	568.1	618.5	
GR	568.1	618.5	568.9	622	568.8	627	569.2	632	570.0	637	
GR	570.6	642	570.6	644	580.0	644	579.3	692	579.6	792	580.06
GR	580.4	892	580.7	992	580.5	1092	580.3	1192	580.0	1292	
GR	579.6	1392	579.3	1492							
NC	0.040	0.037	0.032								
X1	4931	23	115	200	650	650	650				
X3	10			115		200					
GR	582.2	0	581.6	37	580.8	100	580.9	115	575.3	124	579.55
GR	574.6	125	571.5	130	570.8	135	570.5	140	570.3	145	580.36
GR	570.3	150	570.3	155	570.4	160	570.6	165	570.8	170	
GR	571.1	175	571.3	180	573.1	185	573.6	190	575.3	195	
GR	579.0	200	579.1	300	580.1	400					579.06
X1	5956				1025	1025	1025		.35		
X3	10			115		200					580.67
X1	6981	29	505	600	1025	1025	1025				
X3	10							582.6	582.0		
GR	582.8	0	581.3	100	581.3	200	580.9	300	579.7	400	
GR	579.4	425	582.7	500	582.6	505	576.0	517	575.2	520	580.19
GR	572.0	525	571.8	530	572.2	535	572.3	540	571.1	545	
GR	571.1	550	571.0	560	571.2	570	572.4	575	572.5	580	580.99
GR	574.2	584	575.2	588	582.0	600	579.1	700	581.5	800	
GR	580.8	900	581.0	920	581.3	1000	581.2	1100			
X1	8031	27	150	246	1050	1050	1050				
X3				150		246					
GR	580.3	0	580.4	50	580.7	78	578.9	114	580.7	150	580.52
GR	579.0	155	575.2	162	573.8	166	572.8	170	572.3	175	
GR	572.0	180	571.7	190	571.5	200	571.5	210	571.7	215	581.37
GR	571.8	220	572.5	225	573.6	230	575.2	235	577.8	238	
GR	579.4	246	579.4	250	578.6	336	578.5	350	579.2	450	
GR	578.9	492	580.5	550							
NC	0.030	0.030	0.030								
X1	8082	39	580	655	51	51	51				
X3	10			580		655					
GR	578.6	0	578.1	80	578.0	180	577.7	280	577.6	380	
GR	577.9	480	580.9	580	571.8	580	572.2	585	571.7	590	
GR	571.5	595	571.2	600	570.4	605	578.3	605	578.3	606.5	
GR	570.4	606.5	571.4	610	571.0	615	570.9	620	571.0	625	
GR	571.0	630	578.3	630	578.3	631.5	571.0	631.5	571.1	635	
GR	570.9	640	570.8	645	570.3	650	569.9	655	581.1	655	
GR	580.3	680	578.9	780	578.5	830	578.3	880	577.9	980	
GR	577.5	1080	577.3	1180	577.7	1280	577.6	1380			
SP	1.25	1.56	2.6		75	3	519		569.9	569.9	580.73
X1	8147		580	655	65	65	65				
			1	578.4	580.9				.631		581.43


400 580.9
340 580.19
300 579.7

60 .071
100 1.2

200 581.3
275 581
300 580.9

100 .41

Exh. 67
6 of 28



	0.035	0.040	0.032		581.0	578.3	655.0	581.1	578.4		
						635					
		0	581.5	150	580.7	250	579.8	355	580.8	450	581.07
		450	578.8	555	574.7	564	573.7	570	573.2	575	
		580	572.0	585	572.1	590	571.8	595	571.8	600	
		605	572.2	610	572.5	615	572.8	620	573.2	625	581.92
	574.7	626	581.7	635	582.0	650	582.1	750	583.1	850	
	582.6	950	582.2	1050	581.9	1150					
X1	10297	29	400	480	900	900	900				
X3	10					480					
GR	583.1	0	582.7	100	582.2	200	582.1	220	582.9	300	
GR	583.4	400	573.8	416	572.9	420	572.0	425	572.0	430	581.34
GR	572.0	435	571.8	440	572.0	445	572.2	450	572.2	455	
GR	572.5	460	572.8	465	573.4	470	574.5	475	581.9	480	582.04
GR	581.4	500	580.9	600	581.0	700	581.6	800	581.9	900	
GR	582.8	1000	582.6	1100	582.9	1200	583.4	1300			
NC	0.035	0.035	0.032								
X1	10897	23	112	185	600	600	600				
X3				112.00		185.00					
GR	580.7	0	581.2	85	580.4	112	574.8	122	574.5	123	581.53
GR	573.5	125	572.9	130	572.4	135	572.2	140	572.3	150	
GR	572.7	155	572.8	160	573.2	165	573.0	170	573.0	176	
GR	574.5	178	579.4	185	581.8	231	583.7	243	583.1	285	582.38
GR	584.4	355	582.6	385	583.5	477					
X1	10973	30	500	552	76	76	76				
X3	10			500		552					
GR	582.2	0	581.9	100	581.4	200	580.9	300	580.8	400	581.53
GR	581.2	448	581.7	500	571.7	500	571.9	505	571.8	510	
GR	571.8	515	571.8	520	572.1	525	579.0	525	579.0	527	582.37
GR	572.1	527	572.6	530	573.0	535	573.7	540	573.7	545	
GR	573.6	550	573.4	552	581.6	552	580.4	600	581.1	700	
GR	581.4	800	581.6	900	581.8	1000	582.0	1100	582.1	1122	
SD	.9	1.47	2.5		52	2.0	315		571.7	571.7	
X1	11017		500	552	44	44	44				
X2			1	579.0	581.7						581.98
X3	10			500	590.0	552	590.0				
BT	4	500.0	581.7	578.9	525.0	581.7	579.0	527.0	581.7	579.0	582.89
BT	552.0	581.6	578.9								
NC	0.060	0.060	0.032								
X1	11477	22	155	236	460	460	460				
X3				155		255					
GR	583.1	0	583.4	50	583.4	110	582.9	155	574.9	170	
GR	573.9	175	573.7	180	572.8	185	572.9	190	572.9	195	582.27
GR	572.9	200	572.7	205	572.4	210	571.8	215	573.1	220	
GR	574.4	225	575.5	227	581.4	236	582.6	255	582.2	265	583.20
GR	582.1	310	582.2	343							
X1	11528	35	530	582.5	51	51	51				
X3	10			530		582.5					
GR	584.4	0	584.8	30	584.4	130	583.9	230	583.5	330	
GR	582.9	370	582.9	430	583.0	530	573.0	530	573.4	535	
GR	573.0	540	572.7	545	572.5	550	572.1	555.2	580.6	555.2	
GR	580.6	557.2	572.8	557.2	572.8	560	572.7	565	572.5	570	
GR	572.4	575	572.6	580	572.5	582.5	582.8	582.5	582.2	630	
GR	582.2	730	583.3	830	582.9	880	583.1	930	583.9	1030	
GR	584.1	1130	584.4	1230	584.1	1330	583.7	1430	583.9	1439	
SD	1.25	1.61	2.5		52.5	2.0	400		572.1	572.1	
X1	11599		530	582.5	71	71	71				
X2			1	580.7	582.8						
X3	10			530		582.5					
BT	4	530.0	583.0	580.7	555.2	582.9	580.6	557.2	582.9	580.6	
BT	582.5	582.8	580.5								
X1	11650	36	548	604	51	51	51				

FORT ST
NORTH BOUND

Exh. 6.43
7 of 28

```
GR 572.0     44      583.4      4      573.4      548    573.7     553    573.3     558
GR 572.1     593     572.6      598    572.4      601    580.5     604    583.2     604
GR 582.4     648     581.9      748    582.4      823    582.9     848    583.3     948
GR 583.8    1048     584.1     1148    584.5     1248    584.3    1348    583.9    1448
GR 584.3    1598
SB    1.25    1.61      2.5                 56      2.0      400          572.1    572.1
X1 11721                548       604       71       71       71
X2                        1     580.7     583.2
X3    10                            548              604
BT     4   548.0   583.4   580.7   573.5   583.3   580.7   575.5   583.3   580.7
BT 604.0   583.2   580.5
EJ
T1      CITY OF WYANDOTTE FIS 5555-73
T2      SEXTON-KILFOIL DRAIN
T3      50 YEAR FLOOD 4100 CFS
J1   -10       3                                                  574.90
J2     2                -1
T1      CITY OF WYANDOTTE FIS 5555-73
T2      SEXTON-KILFOIL DRAIN
T3      100 YEAR FLOOD 4410 CFS
J1   -10       4                                                  574.90
J2     3                -1
T1      CITY OF WYANDOTTE 5555-73
T2      SEXTON-KILFOIL DRAIN
T3      500 YEAR FLOOD 5160 CFS
J1   -10       5                                                  574.90
J2    19                -1
ER
```

FORT SOUTH BOUND

Exh. b f 3
8 of 28

```
AAAAAAAA                EEEEEEEEEE    CCCCCCCC    HH      HH    00000000
AAAAAAAAAA              EEEEEEEEEE    CCCCCCCCCC  HH      HH    00000000
```

```
HEC2 VERSION UPDATED JAN 1976
ERROR CORRECTIONS 01,02,03,04,05,06,07,08,09
MODIFICATIONS 52,53,54,55,56,57,58
**********

T1      CITY OF WYANDOTTE FIS 5555-73
T2      SEXTON-KILFOIL DRAIN
T3      100-YEAR FLOOD,4410 CFS

J1  ICHECK     INQ     NINV     IDIR     STRT     METRIC     HVINS     Q     WSEL     FQ
        -10.      4.       0.       0.  -0.000000     -0.00      -0.0      -0.  574.900    -0.000
J2  NPROF     IPLOT     PRFVS     XSECV     XSECH     FN     ALLDC     IBW     CHNIM     ITRACE
        3.000    -0.000    -1.000    -0.000    -0.000    -0.000    -0.000    -0.000    -0.000    -0.000

CCHV=  .300 CEHV=  .500
    SECNO     DEPTH     CWSEL     CRIWS     WSELK     EG     HV     HL     OLOSS     BANK ELEV
    Q     QLOB     QCH     QROB     ALOB     ACH     AROB     VOL     TWA     LEFT/RIGHT
    TIME     VLOB     VCH     VROB     XNL     XNCH     XNR     WTN     ELMIN     SSTA
    SLOPE     XLOBL     XLCH     XLOBR     ITRIAL     IDC     ICONT     CORAR     TOPWID     ENDST

      1.00     11.50     574.90      0.00     574.90     575.51      .61      0.00      0.00     584.60
      4410.      0.      4410.      0.      0.      701.      0.      0.      0.      584.60
      0.00      0.00      6.29      0.00      .035      .032      .035      0.000      563.40      529.17
      .001328      -0.      -0.      -0.      0      0      1      0.00      89.83      619.00

     30.00     11.55     574.95      0.00      0.00     575.55      .61      .04      .00     584.60
     4410.      0.      4410.      0.      0.      705.      0.      0.      0.      584.60
      .00      0.00      6.26      0.00      .035      .032      .035      .031      563.40      528.85
      .001312      29.      29.      29.      0      0      1      0.00      90.15      619.00

     60.00     11.59     574.99      0.00      0.00     575.60      .60      .04      .00     584.60
     4410.      0.      4410.      0.      0.      709.      0.      1.      0.      584.60
      .00      0.00      6.22      0.00      .035      .032      .035      .031      563.40      528.45
      .001294      30.      30.      30.      1      0      1      0.00      90.55      619.00

3265-DIVIDED FLOW

NORMAL BRIDGE,NRD=  0 MIN.EL.TRD=  584.30 MAX.ELLC=  580.30

     61.00     11.53     574.93      0.00      0.00     575.66      .72      .00      .06     584.60
     4410.      0.      4410.      0.      0.      646.      0.      1.      0.      584.60
      .00      0.00      6.83      0.00      .035      .032      .035      .030      563.40      528.88
      .002372      1.      1.      1.      2      0      1      0.00      83.12      619.00

3265 DIVIDED FLOW

PRESSURE FLOW

  SRRPS     SQWC     QWEIR     QPR     BAREA     ELLC
```

Exhibit 3
9 of 28

100-YEAR

	4410.	0.	4410.	0	0.00	0.00	575.84	.68	.17	.01	584.6
[redacted]	[redacted]	0	4410.	0	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]	0.	584.60
	.002224	75.	75.	75.	0.00	2	0	1	0.00	.85.00	619.00

SECNO	DEPTH	CHSEL	CRIWS	HSELK	EG	HV	HL	QLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST
137.00	11.94	575.34	0.00	0.00	575.88	.55	.00	.04	584.60
4410.	0.	4410.	0.	0.	741.	0.	2.	0.	584.60
.01	0.00	5.95	0.00	.035	.032	.035	.031	563.40	525.53
.001166	1.	1.	1.	2	0	1	0.00	93.47	619.00
187.00	11.26	575.36	0.00	0.00	575.98	.62	.06	.04	583.10
4410.	0.	4410.	0.	0.	696.	0.	3.	0.	580.20
.01	0.00	6.33	0.00	.035	.032	.042	.031	564.10	341.32
.001331	50.	50.	50.	2	0	1	0.00	91.61	432.94
362.00	11.97	575.94	0.00	0.00	576.25	.30	.17	.10	578.57
4410.	0.	4410.	0.	0.	995.	0.	6.	1.	577.17
.02	0.00	4.43	0.00	.035	.032	.042	.031	563.97	251.10
.000728	175.	175.	175.	2	0	1	0.00	146.24	397.33
737.00	12.54	576.24	0.00	0.00	576.50	.26	.24	.01	578.30
4410.	0.	4410.	0.	0.	1079.	0.	15.	2.	576.90
.04	0.00	4.09	0.00	.035	.032	.042	.032	563.70	249.56
.000570	375.	375.	375.	2	0	1	0.00	149.01	398.57
787.00	12.30	576.20	0.00	0.00	576.62	.42	.04	.08	581.00
4410.	0.	4410.	0.	0.	846.	0.	16.	2.	581.00
.05	0.00	5.21	0.00	.035	.032	.042	.032	563.90	795.00
.000895	50.	50.	50.	2	0	1	0.00	106.60	901.60

3265 DIVIDED FLOW

NORMAL BRIDGE, NRD= 4 MIN ELTRD= 581.00 MAX ELLC= 577.20

788.00	12.25	576.15	0.00	0.00	576.67	.52	.00	.05	581.00
4410.	0.	4410.	0.	0.	764.	0.	16.	2.	581.00
.05	0.00	5.77	0.00	.035	.032	.042	.032	563.90	795.00
.003554	1.	1.	1.	2	0	1	0.00	104.00	901.60

3265 DIVIDED FLOW

NORMAL BRIDGE, NRD= 4 MIN ELTRD= 581.00 MAX ELLC= 577.20

797.00	12.29	576.19	0.00	0.00	576.70	.51	.03	.00	581.00
4410.	0.	4410.	0.	0.	767.	0.	17.	2.	581.00
.05	0.00	5.75	0.00	.035	.032	.042	.032	563.90	795.00
.003513	9.	9.	9.	1	0	1	0.00	104.00	901.60

Exh. b. 15
10 of 28

100-YEAR

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
[redacted]	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST
798.00	12.42	576.32	0.00	0.00	576.73	.41	.00	.03	581.00
4410.	0.	4410.	0.	0.	859.	0.	17.	2.	581.00
.05	0.00	5.13	0.00	.035	.032	.042	.032	563.90	795.00
.000851	1.	1.	1.	2	0	1	0.00	106.60	901.60
844.00	11.37	576.37	0.00	0.00	576.77	.40	.04	.00	581.50
4410.	0.	4410.	0.	0.	865.	0.	17.	2.	581.40
.05	0.00	5.10	0.00	.035	.032	.042	.032	565.00	815.00
.000809	46.	46.	46.	2	0	1	0.00	109.00	924.00
3269 DIVIDED FLOW									
NORMAL BRIDGE NRD=16 MIN EL TRD= 581.40 MAX ELLC= 578.40									
845.00	11.33	576.33	0.00	0.00	576.81	.48	.00	.04	581.50
4410.	0.	4410.	0.	0.	797.	0.	17.	2.	581.40
.05	0.00	5.53	0.00	.035	.032	.042	.031	565.00	815.00
.002795	1.	1.	1.	2	0	1	0.00	102.00	924.00
3269 DIVIDED FLOW									
NORMAL BRIDGE NRD=16 MIN EL TRD= 581.40 MAX ELLC= 578.40									
859.00	11.38	576.38	0.00	0.00	576.85	.47	.04	.00	581.50
4410.	0.	4410.	0.	0.	802.	0.	18.	2.	581.40
.05	0.00	5.50	0.00	.035	.032	.042	.031	565.00	815.00
.002751	15.	15.	15.	2	0	1	0.00	102.00	924.00
860.00	11.48	576.48	0.00	0.00	576.88	.39	.00	.02	581.50
4410.	0.	4410.	0.	0.	877.	0.	18.	2.	581.40
.05	0.00	5.03	0.00	.035	.032	.042	.031	565.00	815.00
.000773	1.	1.	1.	2	0	1	0.00	109.00	924.00
910.00	12.56	576.56	0.00	0.00	576.92	.37	.04	.01	583.10
4410.	0.	4410.	0.	0.	908.	0.	19.	3.	583.00
.05	0.00	4.86	0.00	.035	.032	.042	.031	564.00	835.00
.000696	50.	50.	50.	1	0	1	0.00	107.00	942.00
3269 DIVIDED FLOW									
SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

Exh 6.F3
11 of 28

[illegible]	12.52	576.52	0.00	0.00	576.96	.45	.00	.04	583.10
4410.	0.	4410.	[illegible]	0.	823	[illegible]	[illegible]	[illegible]	[illegible]
.05	0.00	5.36	0.00	.035	.032	.042	.031	564.00	835.00
.003062	1.	1.	1.	2	0	1	0.00	105.00	942.00

3265 DIVIDED FLOW

NORMAL BRIDGE,NRD= 6 MIN ELTRD= 583.00 MAX ELLC= 578.60

921.00	12.55	576.55	0.00	0.00	576.99	.44	.03	.00	583.10
4410.	0.	4410.	0.	0.	826.	0.	19.	3.	583.00
.05	0.00	5.34	0.00	.035	.032	.042	.031	564.00	835.00
.003030	10.	10.	10.	1	0	1	0.00	105.00	942.00

922.00	12.66	576.66	0.00	0.00	577.02	.36	.00	.03	583.10
4410.	0.	4410.	0.	0.	919.	0.	19.	3.	583.00
.05	0.00	4.80	0.00	.035	.032	.042	.031	564.00	835.00
.000671	1.	1.	1.	2	0	1	0.00	107.00	942.00

953.00	11.49	576.59	0.00	0.00	577.14	.55	.03	.10	581.00
4410.	0.	4410.	0.	0.	738.	0.	20.	3.	580.80
.06	0.00	5.97	0.00	.035	.032	.042	.031	565.10	600.00
.001040	31.	31.	31.	2	0	1	0.00	81.00	681.00

3265 DIVIDED FLOW

NORMAL BRIDGE,NRD=14 MIN ELTRD= 580.80 MAX ELLC= 577.70

954.00	11.34	576.44	0.00	0.00	577.29	.85	.00	.15	581.00
4410.	0.	4410.	0.	0.	596.	0.	20.	3.	580.80
.06	0.00	7.40	0.00	.035	.032	.042	.031	565.10	600.00
.005600	1.	1.	1.	2	0	1	0.00	67.20	681.00

3265 DIVIDED FLOW

NORMAL BRIDGE,NRD=14 MIN ELTRD= 580.80 MAX ELLC= 577.70

985.00	11.58	576.66	0.00	0.00	577.47	.81	.17	.01	581.00
4410.	0.	4410.	0.	0.	611.	0.	20.	3.	580.80
.06	0.00	7.22	0.00	.035	.032	.042	.031	565.10	600.00
.005274	31.	31.	31.	2	0	1	0.00	67.20	681.00

SECNO	DEPTH	CHSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

986.00	11.97	577.07	0.00	0.00	577.57	.50	.00	.09	581.00
4410.	0.	4410.	0.	0.	777.	0.	20.	3.	580.80
.06	0.00	5.68	0.00	.035	.032	.042	.031	565.10	600.00
					0	1	0.00	81.00	681.00

E 1627 B

12 of 28

3470 ENCROACHMENT STATIONS= .0 700.0 TYPE= 1 TARGET= 699.999

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 581.10 ELREA= 100000.00

1036.00	11.04	577.24	0.00	0.00	577.64	.40	.04	.03	581.10
4410.	0.	4410.	0.	0.	866.	0.	21.	3.	100000.00
.06	0.00	5.10	0.00	.040	.032	.035	.031	566.20	579.94
.000887	50.	50.	50.	1	0	1	0.00	119.39	699.33

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 579.10 ELREA= 577.50

1736.00	12.46	577.86	0.00	0.00	578.18	.32	.52	.03	579.10
4410.	0.	4308.	102.	0.	941.	168.	37.	8.	577.50
.10	0.00	4.58	.61	.060	.032	.035	.032	568.40	376.55
.000620	700.	700.	700.	1	0	1	0.00	520.85	897.40

3470 ENCROACHMENT STATIONS= .0 485.0 TYPE= 1 TARGET= 484.999

2436.00	13.67	578.27	0.00	0.00	578.57	.30	.39	.00	577.10
4410.	9.	4286.	115.	23.	954.	144.	55.	15.	577.40
.15	.39	4.49	.80	.060	.032	.035	.032	564.60	142.88
.000502	700.	700.	700.	2	0	1	0.00	342.12	485.00

CONFLUENCE
NORTH + SOUTH BRANCH
FW+FB I

3470 ENCROACHMENT STATIONS= .0 500.0 TYPE= 1 TARGET= 499.999

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 581.30 ELREA= 576.40

3186.00	10.03	578.83	0.00	0.00	578.92	.08	.27	.07	581.30
1760.	0.	1605.	155.	0.	668.	208.	72.	20.	576.40
.24	0.00	2.40	.75	.060	.032	.035	.032	568.80	209.39
.000195	750.	750.	750.	2	0	1	0.00	275.40	484.80

VALLEY
FW+FB(I)

3470 ENCROACHMENT STATIONS= .0 500.0 TYPE= 1 TARGET= 499.999

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 581.90 ELREA= 577.00

3686.00	9.53	578.93	0.00	0.00	579.04	.11	.11	.01	581.90
1760.	0.	1667.	93.	0.	623.	127.	81.	23.	577.00
.29	0.00	2.68	.73	.060	.032	.035	.032	569.40	210.30
.000261	500.	500.	500.	2	0	1	0.00	229.09	439.39

VALLEY
No FW+FB II

SECNO	DEPTH	CHSEL	CHWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IOC	ICONT	CORAR	TOPWID	ENDST

Exhibit 3
13 of 28

3470 ENCROACHMENT STATIONS= 350.0 550.0 TYPE= 1 TARGET= 200.000

4186.00	9.06	579.06	0.00	0.00	579.19	.13	.14	.01	578.20
1760.	4.	1755.	2.	10.	598.	8.	89.	25.	578.70
.34	.38	2.93	.22	.040	.032	.037	.032	570.00	385.99
.000306	500.	500.	500.	1	0	1	0.00	158.27	544.28

50 FT. D/STEMMONS
FW+FB K

3470 ENCROACHMENT STATIONS= 592.0 644.0 TYPE= 1 TARGET= 52.00

[redacted] AREA [redacted] SUMED NON-EFFECTIVE,ELLEA= [redacted] 580.10 ELREA= 100000.00

4236.00	10.95	579.05	0.00	0.00	579.24	.19	.02	.03	580.10
1760.	0.	1760.	0.	0.	504.	0.	90.	29.	100000.00
.35	0.00	3.69	0.00	.030	.030	.030	.032	568.10	592.00
.000356	50.	50.	50.	1	0	1	0.00	52.00	644.00

SPECIAL BRIDGE

SB	XK	XKOR	CDFQ	RDLEN	BNC	BNP	BAREA	SS	ELCHU	ELCHD
	1.25	1.37	2.50	0.00	50.50	1.50	400.00	0.00	568.10	568.10

PRESSURE FLOW

EGPRS	EGLBC	H3	QWEIR	QPR	BAREA	ELLC	ELTRD	CLASS
579.46	579.25	.01	0.	1760.	400.	577.40	580.00	10.00

3470 ENCROACHMENT STATIONS= 592.0 644.0 TYPE= 1 TARGET= 52.000

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 580.10 ELREA= 100000.00

4281.00	11.18	579.28	0.00	0.00	579.46	.18	.22	0.00	580.10
1760.	0.	1760.	0.	0.	515.	0.	90.	26.	100000.00
.35	0.00	3.41	0.00	.030	.030	.030	.032	568.10	592.00
.000333	45.	45.	45.	2	0	1	0.00	52.00	644.00

EMMONS ST Eastbound FW&FB [redacted]

3470 ENCROACHMENT STATIONS= 115.0 200.0 TYPE= 1 TARGET= 85.000

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 580.90 ELREA= 100000.00

4931.00	9.25	579.55	0.00	0.00	579.68	.13	.21	.01	580.90
1760.	0.	1760.	0.	0.	600.	0.	99.	27.	100000.00
.41	0.00	2.93	0.00	.040	.032	.037	.032	570.30	117.17
.000305	650.	650.	650.	2	0	1	0.00	82.55	199.72

VALLEY FW&FB M

3470 ENCROACHMENT STATIONS= 115.0 200.0 TYPE= 1 TARGET= 85.000

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 581.25 ELREA= 100000.00

5956.00	9.21	579.86	0.00	0.00	580.00	.13	.31	.00	581.25
1760.	0.	1760.	0.	0.	597.	0.	113.	28.	100000.00
.51	0.00	2.95	0.00	.040	.032	.037	.032	570.65	117.22
.000309	1025.	1025.	1025.	1	0	1	0.00	82.47	199.69

VALLEY NO FW&FB. SECTION REPEATED.

SECNO	DEPTH	CHSEL	CRIWS	HSELK	EG	HV	HL	QLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	THA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	HTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IOC	ICONT	CORAR	TOPWID	ENDST

[redacted] AREA ASSUMED NON-EFFECTIVE,ELLEA= 582.60 ELREA= 582.00

Exhibit 3
14 of 26

6901.00	9.19	580.19	0.00	0.00	580.32	.13	.32			
[redacted]	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]
.000314	1025.	1025.	1025.	0	0	1	0.00	87.40	596.80	

VALLEY
FW & FB N

3280 CROSS SECTION 8031.00 EXTENDED .01 FEET

3470 ENCROACHMENT STATIONS=	150.0	246.0	TYPE=	1	TARGET=	96.000			
8031.00	9.02	580.52	0.00	0.00	580.63	.11	.31	.01	580.70
1760.	0.	1760.	0.	0.	653.	0.	142.	33.	100000.00
.71	0.00	2.70	0.00	.040	.032	.037	.032	571.50	150.56
.000275	1050.	1050.	1050.	0	0	1	0.00	95.44	246.00

VALLEY
FW & FB O
[redacted]
50' D/S HARRISON ST

3280 CROSS SECTION 8082.00 EXTENDED 2.95 FEET

3470 ENCROACHMENT STATIONS=	580.0	655.0	TYPE=	1	TARGET=	75.000			
OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA=		580.90	ELREA=	100000.00					
8082.00	10.65	580.55	0.00	0.00	580.65	.10	.01	.00	580.90
1760.	0.	1760.	0.	0.	688.	0.	143.	33.	100000.00
.72	0.00	2.56	0.00	.030	.030	.030	.032	569.90	580.00
.000275	51.	51.	51.	2	0	1	0.00	75.00	655.00

SPECIAL BRIDGE

SB	XK	XKOR	COFQ	RDLEN	BWC	BWP	BAREA	SS	ELCHU	ELCHD
	1.25	1.56	2.60	-0.00	75.00	3.00	519.00	-0.00	569.90	569.90

HARRISON ST
FW & FB
P

3280 CROSS SECTION 8147.00 EXTENDED 3.13 FEET

PRESSURE FLOW

EGPRS	EGLWC	WH3	QWEIR	QPR	BAREA	ELLC	ELTRD	CLASS
580.83	580.66	.01	0.	1760.	519.	578.40	580.90	10.00

Harrison St

3470 ENCROACHMENT STATIONS=	580.0	655.0	TYPE=	1	TARGET=	75.000			
OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA=		580.90	ELREA=	100000.00					
8147.00	10.83	580.73	0.00	0.00	580.83	.10	.18	0.00	580.90
1760.	0.	1760.	0.	0.	701.	0.	144.	33.	100000.00
.73	0.00	2.51	0.00	.030	.030	.030	.032	569.90	580.00
.000259	65.	65.	65.	2	0	1	0.00	75.00	655.00

Exhibit 3
15 of 28

3470 ENCROACHMENT STATIONS=	550.0	635.0	TYPE=	1	TARGET=	85.000			
9397.00	9.27	581.07	0.00	0.00	581.20	.13	.36	.02	579.30
1760.	0.	1760.	0.	0.	602.	0.	163.	35.	100000.00
.84	0.00	2.92	0.00	.035	.032	.040	.032	571.80	550.00
.000315	1250.	1250.	1250.	0	0	1	0.00	84.18	634.18

VALLEY
FW & FB Q

[redacted]	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]
Q	Q				ACH	ARDD	VOL	TBA	LEFT/RIGHT	
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	UTN	ELMIN	SSTA	
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST	

3470 ENCROACHMENT STATIONS= .0 480.0 TYPE= 1 TARGET= 479.999

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 583.40 ELREA= 100000.00

10297.00	9.54	581.34	0.00	0.00	581.48	.14	.28	.00	583.40	
1760.	0.	1760.	0.	0.	586.	0.	175.	37.	100000.00	
.99	0.00	3.00	0.00	.035	.032	.040	.032	571.80	403.43	
.000305	900.	900.	900.	2	0	1	0.00	76.19	479.62	

3470 ENCROACHMENT STATIONS= 112.0 185.0 TYPE= 1 TARGET= 73.000

10897.00	9.33	581.53	0.00	0.00	581.68	.15	.19	.01	580.40	
1760.	0.	1760.	0.	0.	559.	0.	183.	38.	100000.00	
.98	0.00	3.15	0.00	.035	.032	.035	.032	572.20	112.00	
.000345	600.	600.	600.	0	0	1	0.00	73.00	185.00	

3470 ENCROACHMENT STATIONS= 500.0 552.0 TYPE= 1 TARGET= 52.000

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 581.70 ELREA= 100000.00

10973.00	9.83	581.53	0.00	0.00	581.76	.23	.04	.04	581.70	
1760.	0.	1760.	0.	0.	454.	0.	184.	38.	100000.00	
.99	0.00	3.88	0.00	.035	.032	.035	.032	571.70	500.00	
.000734	76.	76.	76.	2	0	1	0.00	52.00	552.00	

SPECIAL BRIDGE

SB	XK	XKOR	COFQ	RDLEN	BWC	BWP	BAREA	SS	ELCHU	ELCHD
	.90	1.47	2.50	-0.00	52.00	2.00	315.00	-0.00	571.70	571.70

PRESSURE AND WEIR FLOW

EGPRS	EGLWC	H3	QWEIR	QPR	BAREA	ELLC	ELTRD	CLASS
582.24	581.77	.01	48.	1702.	315.	579.00	581.70	30.00

3470 ENCROACHMENT STATIONS= 500.0 552.0 TYPE= 1 TARGET= 52.000
ELENCL= 590.00 ELENCR= 590.00

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 581.70 ELREA= 590.00

11017.00	10.28	581.98	0.00	0.00	582.19	.21	.43	0.00	581.70	
1760.	0.	1760.	0.	0.	478.	0.	184.	38.	590.00	
.99	0.00	3.69	0.00	.035	.032	.035	.032	571.70	500.00	
.000677	44.	44.	44.	2	0	3	0.00	52.00	552.00	

CAPACITY 1017.00 EXCEEDED .07 FCRT

VALLEY FWY FB R

3 76' D/S HARRISON ST S

HARRISON #2

Exhibit 3
16 of 28

[redacted]

11577.00	10.47	582.27	0.00	0.00	582.40	.13	.19	.02	583.00	
1760.	0.	1759.	1.	0.	606.	6.	190.	39.	100000.00	
1.03	0.00	2.90	.24	.060	.032	.060	.032	571.80	548.00	
.000681	66.	46.	46.	2	0	1	0.00	93.65	604.00	

VALLEY FW & FB U ± 50 FT D/S FORT

SECNO	DEPTH	CUSEL	CRIWS	WSELK	EG	HV	HL	QLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

3470 ENCROACHMENT STATIONS= 530.0 582.5 TYPE= 1 TARGET= 52.500

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 583.00 ELREA= 100000.00

11528.00	10.16	582.26	0.00	0.00	582.46	.20	.02	.04	583.00
1760.	0.	1760.	0.	0.	485.	0.	191.	39.	100000.00
1.04	0.00	3.63	0.00	.060	.032	.060	.032	572.10	530.00
.000625	51.	51.	51.	2	0	1	0.00	52.50	582.50

SPECIAL BRIDGE

SB	XK	XKOR	COFQ	RDLEN	BWC	BWP	BAREA	SS	ELCHU	ELCHD
	1.25	1.61	2.50	-0.00	52.50	2.00	400.00	-0.00	572.10	572.10

PRESSURE FLOW

EGPRS	EGLWC	H3	QWEIR	QPR	BAREA	ELLC	ELTRD	CLASS
582.74	582.48	.02	0.	1760.	400.	580.70	582.80	10.00

FORT NORTH BOUND

North Bound Fort St.

3470 ENCROACHMENT STATIONS= 530.0 582.5 TYPE= 1 TARGET= 52.500

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 583.00 ELREA= 100000.00

11599.00	10.45	582.55	0.00	0.00	582.74	.19	.28	0.00	583.00
1760.	0.	1760.	0.	0.	501.	0.	191.	39.	100000.00
1.04	0.00	3.52	0.00	.060	.032	.060	.032	572.10	530.00
.000568	71.	71.	71.	2	0	1	0.00	52.50	582.50

3470 ENCROACHMENT STATIONS= 548.0 604.0 TYPE= 1 TARGET= 56.000

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 583.40 ELREA= 100000.00

11650.00	10.50	582.60	0.00	0.00	582.77	.17	.03	.01	583.40
1760.	0.	1760.	0.	0.	525.	0.	192.	39.	100000.00
1.05	0.00	3.35	0.00	.060	.032	.060	.032	572.10	548.00
.000492	51.	51.	51.	1	0	1	0.00	56.00	604.00

SPECIAL BRIDGE

Exhibit 3
17 of 28

EGPRS	EGLWC	H3	QWCIR	QPR	BAREA	ELLC	ELTRD	CL/SL
583.08	582.78	.01	0.	1760.	400.	580.70	583.20	10.00

3470 ENCROACHMENT STATIONS= 548.0 604.0 TYPE= 1 TARGET= 56.000

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 583.40 ELREA= 100000.00

11721.00	10.82	582.92	0.00	0.00	583.08	.16	.31	0.00	583.40
1760.	0.	1760.	0.	0.	543.	0.	193.	39.	100000.00
1.05	0.00	3.24	0.00	.060	.032	.060	.032	572.10	548.00
.000443	71.	71.	71.	2	0	1	0.00	56.00	604.00

FOOT SOUTH BOUND

OK BRM 11/14/90

Exhibit 3
18 of 28

SUMMARY PRINTOUT FOR MULTIPLE PROFILES

500 YEAR FLOOD 5160 CFS

SECTION NUMBER	CHANNEL LENGTH	MIN EL OF ROADWAY	MAX EL OF LOW CHORD	MIN EL GROUND	DISCHARGE (CFS)	CWSEL	CRIWS	EG	TOPWID	VOLS	TIME	VOL
1.00	0.00	0.00	0.00	563.40	3165.00	574.90	0.00	575.22	89.83	6.84	0.00	0.06
1.00	0.00	0.00	0.00	563.40	4100.00	574.90	0.00	575.48	89.83	11.48	0.00	0.09
1.00	0.00	0.00	0.00	563.40	4410.00	574.90	0.00	575.51	89.83	13.28	0.00	0.09
1.00	0.00	0.00	0.00	563.40	5160.00	574.90	0.00	575.74	89.83	18.28	0.00	0.00
30.00	29.00	0.00	0.00	563.40	3165.00	574.92	0.00	575.24	90.00	6.80	.00	.97
30.00	29.00	0.00	0.00	563.40	4100.00	574.94	0.00	575.47	90.11	11.36	.00	.97
30.00	29.00	0.00	0.00	563.40	4410.00	574.95	0.00	575.55	90.15	13.12	.00	.97
30.00	29.00	0.00	0.00	563.40	5160.00	574.97	0.00	575.80	90.33	17.85	.00	.97
60.00	30.00	0.00	0.00	563.40	3165.00	574.94	0.00	575.26	90.17	6.76	.00	.97
60.00	30.00	0.00	0.00	563.40	4100.00	574.98	0.00	575.50	90.44	11.23	.00	.98
60.00	30.00	0.00	0.00	563.40	4410.00	574.99	0.00	575.60	90.55	12.94	.00	.98
60.00	30.00	0.00	0.00	563.40	5160.00	575.04	0.00	575.85	91.04	17.41	.00	.98
61.00	1.00	584.30	580.30	563.40	3165.00	574.91	0.00	575.29	82.95	12.29	.00	.97
61.00	1.00	584.30	580.30	563.40	4100.00	574.93	0.00	575.56	83.07	20.54	.00	.97
61.00	1.00	584.30	580.30	563.40	4410.00	574.93	0.00	575.66	83.12	23.72	.00	.97
61.00	1.00	584.30	580.30	563.40	5160.00	574.96	0.00	575.94	83.33	32.24	.00	.97
136.00	75.00	584.30	580.30	563.40	3165.00	575.02	0.00	575.38	83.82	11.93	.01	2.08
136.00	75.00	584.30	580.30	563.40	4100.00	575.12	0.00	575.71	84.64	19.46	.01	2.09
136.00	75.00	584.30	580.30	563.40	4410.00	575.16	0.00	575.84	85.00	22.24	.01	2.10
136.00	75.00	584.30	580.30	563.40	5160.00	575.30	0.00	576.20	86.14	29.29	.01	2.11
137.00	1.00	0.00	0.00	563.40	3165.00	575.10	0.00	575.40	91.53	6.44	.01	2.10
137.00	1.00	0.00	0.00	563.40	4100.00	575.27	0.00	575.75	92.89	10.29	.01	2.11
137.00	1.00	0.00	0.00	563.40	4410.00	575.34	0.00	575.88	93.47	11.66	.01	2.11
137.00	1.00	0.00	0.00	563.40	5160.00	575.54	0.00	576.26	94.19	14.81	.01	2.13
187.00	50.00	0.00	0.00	564.10	3165.00	575.12	0.00	575.46	89.16	7.37	.01	2.90
187.00	50.00	0.00	0.00	564.10	4100.00	575.29	0.00	575.84	90.88	11.75	.01	2.93
187.00	50.00	0.00	0.00	564.10	4410.00	575.36	0.00	575.98	91.61	13.31	.01	2.94
187.00	50.00	0.00	0.00	564.10	5160.00	575.58	0.00	576.38	92.53	16.82	.01	2.98
362.00	175.00	0.00	0.00	563.97	3165.00	575.42	0.00	575.61	143.71	4.75	.03	6.10
362.00	175.00	0.00	0.00	563.97	4100.00	575.80	0.00	576.07	145.52	6.71	.02	6.27
362.00	175.00	0.00	0.00	563.97	4410.00	575.94	0.00	576.25	146.24	7.28	.02	6.34
362.00	175.00	0.00	0.00	563.97	5160.00	576.34	0.00	576.71	148.20	8.37	.02	6.53
737.00	375.00	0.00	0.00	563.70	3165.00	575.62	0.00	575.78	145.95	3.85	.06	14.31
737.00	375.00	0.00	0.00	563.70	4100.00	576.07	0.00	576.31	148.18	5.30	.05	15.00
737.00	375.00	0.00	0.00	563.70	4410.00	576.24	0.00	576.50	149.01	5.70	.04	15.27
737.00	375.00	0.00	0.00	563.70	5160.00	576.69	0.00	577.01	151.21	6.51	.04	16.01
787.00	50.00	0.00	0.00	563.90	3165.00	575.59	0.00	575.85	106.60	5.92	.06	15.32
787.00	50.00	0.00	0.00	563.90	4100.00	576.03	0.00	576.41	106.60	8.26	.05	16.08
787.00	50.00	0.00	0.00	563.90	4410.00	576.20	0.00	576.62	106.60	8.95	.05	16.37
787.00	50.00	0.00	0.00	563.90	5160.00	576.63	0.00	577.15	106.60	10.35	.04	17.18

Exhibit 3

19 of 28

[redacted]CTIO	[redacted]HANN	[redacted]IN	[redacted]	M[redacted]L OF	[redacted]N E	[redacted]SCH	[redacted]	[redacted]EL	[redacted]	[redacted]HS	[redacted]	EG	[redacted]	TOPWID	[redacted]	10[redacted]S	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]
NUMBER	LENGTH	ROADWAY		LOW CHORD		GROUND		(CFS)															
788.00	1.00	581.00		577.20		563.90		3165.00		575.56		0.00		575.88		104.00		23.72		.06		15.37	
788.00	1.00	581.00		577.20		563.90		4100.00		575.99		0.00		576.46		104.00		32.91		.05		16.10	
788.00	1.00	581.00		577.20		563.90		4410.00		576.15		0.00		576.67		104.00		35.54		.05		16.29	
788.00	1.00	581.00		577.20		563.90		5160.00		576.58		0.00		577.21		104.00		40.06		.04		17.30	
797.00	9.00	581.00		577.20		563.90		3165.00		575.59		0.00		575.90		104.00		23.58		.04		15.44	
797.00	9.00	581.00		577.20		563.90		4100.00		576.02		0.00		576.49		104.00		32.55		.05		16.21	
797.00	9.00	581.00		577.20		563.90		4410.00		576.19		0.00		576.70		104.00		35.13		.05		16.55	
797.00	9.00	581.00		577.20		563.90		5160.00		576.62		0.00		577.25		104.00		40.12		.04		17.37	
798.00	1.00	0.00		0.00		563.90		3165.00		575.67		0.00		575.92		106.60		5.72		.07		16.50	
798.00	1.00	0.00		0.00		563.90		4100.00		576.15		0.00		576.52		106.60		7.89		.05		16.82	
798.00	1.00	0.00		0.00		563.90		4410.00		576.32		0.00		576.73		106.60		8.51		.05		16.97	
798.00	1.00	0.00		0.00		563.90		5160.00		576.79		0.00		577.29		106.60		9.78		.04		17.30	
844.00	46.00	0.00		0.00		565.00		3165.00		575.70		0.00		575.95		106.11		5.36		.06		16.63	
844.00	46.00	0.00		0.00		565.00		4100.00		576.19		0.00		576.55		108.96		7.52		.05		17.16	
844.00	46.00	0.00		0.00		565.00		4410.00		576.37		0.00		576.77		109.00		8.09		.05		17.48	
844.00	46.00	0.00		0.00		565.00		5160.00		576.84		0.00		577.33		109.00		9.24		.05		18.35	
845.00	1.00	581.40		578.40		565.00		3165.00		575.68		0.00		575.97		98.98		17.86		.07		16.38	
845.00	1.00	581.40		578.40		565.00		4100.00		576.16		0.00		576.59		101.84		25.65		.05		17.18	
845.00	1.00	581.40		578.40		565.00		4410.00		576.33		0.00		576.81		102.00		27.95		.05		17.50	
845.00	1.00	581.40		578.40		565.00		5160.00		576.80		0.00		577.38		102.00		35.77		.05		18.37	
859.00	14.50	581.40		578.40		565.00		3165.00		575.70		0.00		575.99		99.12		17.73		.07		16.40	
859.00	14.50	581.40		578.40		565.00		4100.00		576.20		0.00		576.63		101.96		25.38		.05		17.44	
859.00	14.50	581.40		578.40		565.00		4410.00		576.38		0.00		576.85		102.00		27.51		.05		17.76	
859.00	14.50	581.40		578.40		565.00		5160.00		576.86		0.00		577.43		103.00		37.02		.05		18.65	
860.00	1.00	0.00		0.00		565.00		3165.00		575.77		0.00		576.01		106.54		5.22		.07		16.62	
860.00	1.00	0.00		0.00		565.00		4100.00		576.29		0.00		576.65		109.00		7.21		.05		17.46	
860.00	1.00	0.00		0.00		565.00		4410.00		576.48		0.00		576.88		109.00		7.73		.05		17.78	
860.00	1.00	0.00		0.00		565.00		5160.00		576.99		0.00		577.47		109.00		8.74		.05		18.67	
910.00	60.00	0.00		0.00		564.00		3165.00		575.81		0.00		576.04		107.00		4.79		.07		17.55	
910.00	50.00	0.00		0.00		564.00		4100.00		576.36		0.00		576.69		107.00		6.48		.06		18.46	
910.00	50.00	0.00		0.00		564.00		4410.00		576.56		0.00		576.92		107.00		6.96		.05		18.81	
910.00	50.00	0.00		0.00		564.00		5160.00		577.07		0.00		577.52		107.00		7.95		.05		19.76	
911.00	1.00	583.00		578.60		564.00		3165.00		575.79		0.00		576.07		105.00		21.37		.07		17.57	
911.00	1.00	583.00		578.60		564.00		4100.00		576.32		0.00		576.73		105.00		28.62		.06		18.48	
911.00	1.00	583.00		578.60		564.00		4410.00		576.52		0.00		576.96		105.00		30.62		.05		18.83	
911.00	1.00	583.00		578.60		564.00		5160.00		577.03		0.00		577.56		105.00		34.49		.05		19.78	
921.00	10.00	583.00		578.60		564.00		3165.00		575.81		0.00		576.09		105.00		21.25		.07		17.74	
921.00	10.00	583.00		578.60		564.00		4100.00		576.35		0.00		576.76		105.00		28.34		.06		18.66	
921.00	10.00	583.00		578.60		564.00		4410.00		576.55		0.00		576.99		105.00		30.30		.05		19.02	
921.00	10.00	583.00		578.60		564.00		5160.00		577.07		0.00		577.60		105.00		34.11		.05		19.98	

Exhibit 3
20 of 28

[redacted]	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]
[redacted]	LENGTH	ROADWAY	LOW CHORD	GROUND	(CFS)								
522.00	1.00	0.00	0.00	564.00	3165.00	575.88	0.00	576.11	107.00	4.00	[illegible]	[illegible]	
2.00	1.00	0.00	0.00	564.00	4100.00	576.56	0.00	576.78	107.00	6.28	[illegible]	[illegible]	
[illegible]	1.00	0.00	0.00	564.00	4410.00	576.66	0.00	577.02	107.00	6.71	[illegible]	[illegible]	
22.00	1.00	0.00	0.00	564.00	5160.00	577.20	0.00	577.63	107.00	7.61	[illegible]	[illegible]	
953.00	31.00	0.00	0.00	565.10	3165.00	575.84	0.00	576.18	81.00	6.97	.07	18.20	
953.00	31.00	0.00	0.00	565.10	4100.00	576.39	0.00	576.89	81.00	9.62	.06	19.26	
953.00	31.00	0.00	0.00	565.10	4410.00	576.59	0.00	577.14	81.00	10.48	.06	19.62	
953.00	31.00	0.00	0.00	565.10	5160.00	577.10	0.00	577.78	81.00	12.04	.05	20.69	
953.00	1.00	580.80	577.70	565.10	3165.00	575.76	0.00	576.27	67.20	35.26	.07	18.31	
954.00	1.00	580.80	577.70	565.10	4100.00	576.26	0.00	577.03	67.20	50.97	.06	19.27	
954.00	1.00	580.80	577.70	565.10	4410.00	576.44	0.00	577.29	67.20	56.00	.06	19.64	
954.00	1.00	580.80	577.70	565.10	5160.00	576.92	0.00	577.97	67.20	67.38	.05	20.65	
985.00	30.50	580.80	577.70	565.10	3165.00	575.88	0.00	576.38	67.20	33.95	.07	18.70	
985.00	30.50	580.80	577.70	565.10	4100.00	576.46	0.00	577.19	67.20	48.26	.06	19.68	
985.00	30.50	580.80	577.70	565.10	4410.00	576.66	0.00	577.47	67.20	52.74	.06	20.06	
985.00	30.50	580.80	577.70	565.10	5160.00	577.20	0.00	578.19	67.20	62.75	.05	21.09	
986.00	1.00	0.00	0.00	565.10	3165.00	576.12	0.00	576.44	81.00	6.31	.07	18.71	
986.00	1.00	0.00	0.00	565.10	4100.00	576.82	0.00	577.27	81.00	8.33	.06	19.70	
986.00	1.00	0.00	0.00	565.10	4410.00	577.07	0.00	577.57	81.00	8.89	.06	20.08	
986.00	1.00	0.00	0.00	565.10	5160.00	577.70	0.00	578.30	81.00	10.00	.05	21.11	
1036.00	50.00	0.00	0.00	566.20	3165.00	576.20	0.00	576.48	114.00	7.01	.08	19.55	
1036.00	50.00	0.00	0.00	566.20	4100.00	576.96	0.00	577.34	117.96	8.55	.06	20.61	
1036.00	50.00	0.00	0.00	566.20	4410.00	577.24	0.00	577.64	119.39	8.87	.06	21.02	
1036.00	50.00	0.00	0.00	566.20	5160.00	577.94	0.00	578.40	122.80	9.24	.05	22.13	
1736.00	700.00	0.00	0.00	565.40	3165.00	576.68	0.00	576.92	111.33	5.29	.13	32.02	
1736.00	700.00	0.00	0.00	565.40	4100.00	577.55	0.00	577.87	443.28	6.28	.11	35.00	
1736.00	700.00	0.00	0.00	565.40	4410.00	577.86	0.00	578.18	520.85	6.20	.10	36.89	
1736.00	700.00	0.00	0.00	565.40	5160.00	578.65	0.00	578.93	560.01	5.29	.10	42.14	
2436.00	700.00	0.00	0.00	564.60	3165.00	577.03	0.00	577.26	101.28	4.35	.18	45.15	
2436.00	700.00	0.00	0.00	564.60	4100.00	577.97	0.00	578.26	306.47	4.98	.15	50.91	
2436.00	700.00	0.00	0.00	564.60	4410.00	578.27	0.00	578.57	342.12	5.02	.15	54.81	
2436.00	700.00	0.00	0.00	564.60	5160.00	578.99	0.00	579.30	367.49	4.87	.15	65.56	
3186.00	750.00	0.00	0.00	568.80	1120.00	577.49	0.00	577.55	160.65	1.72	.28	57.33	
3186.00	750.00	0.00	0.00	568.80	1620.00	578.52	0.00	578.60	246.47	1.98	.24	66.56	
3186.00	750.00	0.00	0.00	568.80	1760.00	578.83	0.00	578.92	275.40	1.95	.24	72.01	
3186.00	750.00	0.00	0.00	568.80	2055.00	579.55	0.00	579.63	291.91	1.73	.24	86.75	
3686.00	500.00	0.00	0.00	569.40	1120.00	577.58	0.00	577.66	125.85	2.30	.34	63.65	
3686.00	500.00	0.00	0.00	569.40	1620.00	578.62	0.00	578.73	200.38	2.66	.30	75.04	
3686.00	500.00	0.00	0.00	569.40	1760.00	578.93	0.00	579.04	229.09	2.61	.29	81.33	
3686.00	500.00	0.00	0.00	569.40	2055.00	579.64	0.00	579.74	290.98	2.35	.30	98.33	

Exhibit 3
21 of 28

SECTION NUMBER	CHANNEL LENGTH	MIN EL OF ROADWAY	MAX EL OF LOW CHORD	MIN EL GROUND	DISCHARGE (CFS)	CWSEL	CRITS	EG	TOPWID	[illegible]	[illegible]	[illegible]
4186.00	500.00	0.00	0.00	570.00	1120.00	577.69	0.00	577.78	81.04	[illegible]	[illegible]	[illegible]
4186.00	500.00	0.00	0.00	570.00	1620.00	578.75	0.00	578.88	102.22	3.01	[illegible]	[illegible]
4186.00	500.00	0.00	0.00	570.00	1760.00	579.06	0.00	579.19	158.27	3.06	[illegible]	[illegible]
4186.00	500.00	0.00	0.00	570.00	2055.00	579.75	0.00	579.89	200.00	2.94	[illegible]	[illegible]
4236.00	50.00	0.00	0.00	568.10	1120.00	577.69	0.00	577.80	52.00	2.27	[illegible]	[illegible]
4236.00	50.00	0.00	0.00	568.10	1620.00	578.75	0.00	578.92	52.00	3.32	[illegible]	[illegible]
4236.00	50.00	0.00	0.00	568.10	1760.00	579.05	0.00	579.24	52.00	3.56	[illegible]	[illegible]
4236.00	50.00	0.00	0.00	568.10	2055.00	579.73	0.00	579.95	52.00	3.99	[illegible]	[illegible]
4281.00	45.00	580.00	577.40	568.10	1120.00	577.76	0.00	577.86	52.00	2.22	[illegible]	[illegible]
4281.00	45.00	580.00	577.40	568.10	1620.00	578.93	0.00	579.10	52.00	3.14	[illegible]	[illegible]
4281.00	45.00	580.00	577.40	568.10	1760.00	579.28	0.00	579.46	52.00	3.33	[illegible]	[illegible]
4281.00	45.00	580.00	577.40	568.10	2055.00	580.06	0.00	580.27	52.00	3.64	[illegible]	[illegible]
4931.00	650.00	0.00	0.00	570.30	1120.00	577.93	0.00	578.02	78.15	2.56	[illegible]	[illegible]
4931.00	650.00	0.00	0.00	570.30	1620.00	579.18	0.00	579.31	81.55	3.01	[illegible]	[illegible]
4931.00	650.00	0.00	0.00	570.30	1760.00	579.55	0.00	579.68	82.55	3.05	[illegible]	[illegible]
4931.00	650.00	0.00	0.00	570.30	2055.00	580.36	0.00	580.50	84.13	3.03	[illegible]	[illegible]
5956.00	1025.00	0.00	0.00	570.65	1120.00	578.20	0.00	578.29	77.93	2.67	[illegible]	[illegible]
5956.00	1025.00	0.00	0.00	570.65	1620.00	579.49	0.00	579.62	81.48	3.06	[illegible]	[illegible]
5956.00	1025.00	0.00	0.00	570.65	1760.00	579.86	0.00	580.00	82.47	3.09	[illegible]	[illegible]
5956.00	1025.00	0.00	0.00	570.65	2055.00	580.67	0.00	580.82	84.07	3.07	[illegible]	[illegible]
6981.00	1025.00	0.00	0.00	571.00	1120.00	578.48	0.00	578.57	81.27	2.83	[illegible]	[illegible]
6981.00	1025.00	0.00	0.00	571.00	1620.00	579.81	0.00	579.94	86.06	3.13	[illegible]	[illegible]
6981.00	1025.00	0.00	0.00	571.00	1760.00	580.19	0.00	580.32	87.40	3.14	[illegible]	[illegible]
6981.00	1025.00	0.00	0.00	571.00	2055.00	580.99	0.00	581.14	90.28	3.10	[illegible]	[illegible]
8031.00	1050.00	0.00	0.00	571.50	1120.00	578.77	0.00	578.85	87.41	2.50	[illegible]	[illegible]
8031.00	1050.00	0.00	0.00	571.50	1620.00	580.14	0.00	580.25	94.35	2.75	[illegible]	[illegible]
8031.00	1050.00	0.00	0.00	571.50	1760.00	580.52	0.00	580.63	95.44	2.75	[illegible]	[illegible]
8031.00	1050.00	0.00	0.00	571.50	2055.00	581.32	0.00	581.44	96.00	2.66	[illegible]	[illegible]
8082.00	51.00	0.00	0.00	569.90	1120.00	578.81	0.00	578.87	75.00	2.16	[illegible]	[illegible]
8082.00	51.00	0.00	0.00	569.90	1620.00	580.17	0.00	580.27	75.00	2.65	[illegible]	[illegible]
8082.00	51.00	0.00	0.00	569.90	1760.00	580.55	0.00	580.65	75.00	2.75	[illegible]	[illegible]
8082.00	51.00	0.00	0.00	569.90	2055.00	581.34	0.00	581.46	75.00	2.90	[illegible]	[illegible]
8147.00	65.00	580.90	578.40	569.90	1120.00	578.86	0.00	578.92	75.00	2.12	[illegible]	[illegible]
8147.00	65.00	580.90	578.40	569.90	1620.00	580.32	0.00	580.41	75.00	2.52	[illegible]	[illegible]
8147.00	65.00	580.90	578.40	569.90	1760.00	580.73	0.00	580.83	75.00	2.59	[illegible]	[illegible]
8147.00	65.00	580.90	578.40	569.90	2055.00	581.58	0.00	581.70	75.00	2.68	[illegible]	[illegible]
9397.00	1250.00	0.00	0.00	571.80	1120.00	579.16	0.00	579.26	80.35	3.19	1.01	126.37
9397.00	1250.00	0.00	0.00	571.80	1620.00	580.66	0.00	580.78	83.65	3.20	[illegible]	[illegible]
9397.00	1250.00	0.00	0.00	571.80	1760.00	581.07	0.00	581.20	84.18	3.15	[illegible]	[illegible]
9397.00	1250.00	0.00	0.00	571.80	2055.00	581.92	0.00	582.07	85.00	3.02	[illegible]	[illegible]

Exhibit 3
22 of 28

SECTION NUMBER	CHANNEL LENGTH	MIN EL OF ROADWAY	MAX EL OF LOW CHORD	MIN EL GROUND	DISCHARGE (CFS)	CWSEL	CRIWS	EG	TOPWID	[illegible]	[illegible]	[illegible]
10297.00	900.00	0.00	0.00	571.80	1120.00	579.43	0.00	579.53	71.72	[illegible]	1.11	[illegible]
10297.00	900.00	0.00	0.00	571.80	1620.00	580.93	0.00	581.07	75.23	[illegible]	.96	[illegible]
10297.00	900.00	0.00	0.00	571.80	1760.00	581.34	0.00	581.48	76.19	3.05	.93	[illegible]
10297.00	900.00	0.00	0.00	571.80	2055.00	582.19	0.00	582.35	77.98	3.05	.90	207.20
10697.00	600.00	0.00	0.00	572.20	1120.00	579.61	0.00	579.72	71.59	3.36	1.17	141.50
10897.00	600.00	0.00	0.00	572.20	1620.00	581.12	0.00	581.27	73.00	3.47	1.01	171.67
10897.00	600.00	0.00	0.00	572.20	1760.00	581.53	0.00	581.68	73.00	3.45	.98	[illegible]
10897.00	600.00	0.00	0.00	572.20	2055.00	582.38	0.00	582.55	73.00	3.42	.96	[illegible]
10973.00	76.00	0.00	0.00	571.70	1120.00	579.62	0.00	579.78	52.00	6.33	1.18	[illegible]
10973.00	76.00	0.00	0.00	571.70	1620.00	581.12	0.00	581.34	52.00	7.20	1.01	171.90
10973.00	76.00	0.00	0.00	571.70	1760.00	581.53	0.00	581.76	52.00	7.34	.99	183.66
10973.00	76.00	0.00	0.00	571.70	2055.00	582.37	0.00	582.63	52.00	7.57	.96	212.97
11017.00	44.00	581.70	579.00	571.70	1120.00	579.76	0.00	579.91	52.00	5.96	1.18	162.54
11017.00	44.00	581.70	579.00	571.70	1620.00	581.51	0.00	581.71	52.00	6.25	1.01	172.38
11017.00	44.00	581.70	579.00	571.70	1760.00	581.98	0.00	582.19	52.00	6.29	.99	184.11
11017.00	44.00	581.70	579.00	571.70	2055.00	582.89	0.00	583.13	52.00	6.43	.96	213.46
11477.00	460.00	0.00	0.00	571.80	1120.00	580.01	0.00	580.12	73.47	3.12	1.23	146.73
11477.00	460.00	0.00	0.00	571.80	1620.00	581.80	0.00	581.92	85.22	2.91	1.06	177.75
11477.00	460.00	0.00	0.00	571.80	1760.00	582.27	0.00	582.40	93.69	2.81	1.03	189.87
11477.00	460.00	0.00	0.00	571.80	2055.00	583.20	0.00	583.34	100.00	2.63	1.01	219.94
11528.00	51.00	0.00	0.00	572.10	1120.00	580.01	0.00	580.16	50.50	5.60	1.29	147.20
11528.00	51.00	0.00	0.00	572.10	1620.00	581.79	0.00	581.98	52.50	6.21	1.06	178.36
11528.00	51.00	0.00	0.00	572.10	1760.00	582.26	0.00	582.46	52.50	6.25	1.04	190.51
11528.00	51.00	0.00	0.00	572.10	2055.00	583.18	0.00	583.41	52.50	6.38	1.01	220.67
11599.00	71.00	582.80	580.70	572.10	1120.00	580.02	0.00	580.17	50.50	5.57	1.24	147.80
11599.00	71.00	582.80	580.70	572.10	1620.00	582.01	0.00	582.20	52.50	5.74	1.07	179.12
11599.00	71.00	582.80	580.70	572.10	1760.00	582.55	0.00	582.74	52.50	5.68	1.04	191.32
11599.00	71.00	582.80	580.70	572.10	2055.00	583.55	0.00	583.76	52.50	5.73	1.02	221.56
11650.00	51.00	0.00	0.00	572.10	1120.00	580.07	0.00	580.20	53.84	4.93	1.25	148.24
11650.00	51.00	0.00	0.00	572.10	1620.00	582.06	0.00	582.23	56.00	5.00	1.07	179.68
11650.00	51.00	0.00	0.00	572.10	1760.00	582.60	0.00	582.77	56.00	4.92	1.05	191.92
11650.00	51.00	0.00	0.00	572.10	2055.00	583.60	0.00	583.79	56.00	4.91	1.02	222.22
11721.00	71.00	583.20	580.70	572.10	1120.00	580.08	0.00	580.21	53.84	4.90	1.25	148.87
11721.00	71.00	583.20	580.70	572.10	1620.00	582.31	0.00	582.47	56.00	4.57	1.08	180.50
11721.00	71.00	583.20	580.70	572.10	1760.00	582.92	0.00	583.08	56.00	4.43	1.05	192.79
11721.00	71.00	583.20	580.70	572.10	2055.00	584.00	0.00	584.18	56.00	4.39	1.03	223.19

SECTION NUMBER	DISCHARGE CFS	CWSEL	CWSEL DIFF EACH Q	CWSEL DIFF EACH SECTION	CWSEL-WSELK	TOPWID	T.W. DIFF	LENGTH
1.000	3165.000	574.900	0.000	0.000	0.000	89.833	0.000	-0.000
1.000	4100.000	574.900	0.000	0.000	0.000	89.833	0.000	-0.000
1.000	4410.000	574.900	0.000	0.000	0.000	89.833	0.000	-0.000
1.000	5160.000	574.900	0.000	0.000	0.000	89.833	0.000	-0.000
30.000	3165.000	574.922	0.000	.022	0.000	89.999	0.000	29.000
30.000	4100.000	574.939	.017	.039	0.000	90.111	-.112	29.000
30.000	4410.000	574.946	.007	.046	0.000	90.154	-.156	29.000
30.000	5160.000	574.969	.023	.069	0.000	90.332	-.333	29.000
60.000	3165.000	574.944	0.000	.022	0.000	90.169	0.000	30.000
60.000	4100.000	574.980	.035	.041	0.000	90.443	-.274	30.000
[illegible]	[illegible]	[illegible]	.015	.040	0.000	90.547	.378	30.000

Exhibit 3
23 of 28

[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]
51.000	4410.000	574.935	.008	-.060	0.000	83.122	-.117	1.000
51.000	5160.000	574.960	.025	-.085	0.000	83.331	-.379	1.000
136.000	3165.000	575.018	0.000	.104	0.000	83.815	0.000	1.000
136.000	4100.000	575.117	.099	.188	0.000	84.639	-.824	1.000
136.000	4410.000	575.160	.043	.225	0.000	84.999	-1.183	1.000
136.000	5160.000	575.296	.136	.336	0.000	86.136	-2.320	1.000
137.000	3165.000	575.103	0.000	.085	0.000	91.525	0.000	1.000
137.000	4100.000	575.266	.163	.149	0.000	92.887	-1.361	1.000
137.000	4410.000	575.335	.069	.176	0.000	93.466	-1.940	1.000
137.000	5160.000	575.545	.209	.249	0.000	94.192	-2.667	1.000
187.000	3165.000	575.116	0.000	.013	0.000	89.164	0.000	50.000
187.000	4100.000	575.288	.172	.022	0.000	90.884	-1.720	50.000
187.000	4410.000	575.361	.073	.026	0.000	91.611	-2.446	50.000
187.000	5160.000	575.577	.216	.033	0.000	92.526	-3.362	50.000
362.000	3165.000	575.425	0.000	.308	0.000	143.706	0.000	175.000
362.000	4100.000	575.796	.372	.508	0.000	145.523	-1.816	175.000
362.000	4410.000	575.943	.146	.582	0.000	146.238	-2.532	175.000
362.000	5160.000	576.343	.400	.766	0.000	148.198	-4.492	175.000
737.000	3165.000	575.616	0.000	.191	0.000	145.954	0.000	375.000
737.000	4100.000	576.071	.456	.275	0.000	148.176	-2.222	375.000
737.000	4410.000	576.243	.171	.300	0.000	149.010	-3.057	375.000
737.000	5160.000	576.694	.451	.351	0.000	151.210	-5.257	375.000
787.000	3165.000	575.592	0.000	-.024	0.000	106.600	0.000	50.000
787.000	4100.000	576.031	.440	-.040	0.000	106.600	0.000	50.000
787.000	4410.000	576.196	.165	-.046	0.000	106.600	0.000	50.000
787.000	5160.000	576.632	.435	-.062	0.000	106.600	0.000	50.000
788.000	3165.000	575.563	0.000	-.029	0.000	104.000	0.000	1.000
788.000	4100.000	575.990	.427	-.042	0.000	104.000	0.000	1.000
788.000	4410.000	576.151	.161	-.046	0.000	104.000	0.000	1.000
788.000	5160.000	576.577	.426	-.055	0.000	104.000	0.000	1.000
797.000	3165.000	575.586	0.000	.023	0.000	104.000	0.000	9.000
797.000	4100.000	576.023	.437	.034	0.000	104.000	0.000	9.000
797.000	4410.000	576.188	.164	.037	0.000	104.000	0.000	9.000
797.000	5160.000	576.623	.436	.046	0.000	104.000	0.000	9.000
798.000	3165.000	575.670	0.000	.084	0.000	106.600	0.000	1.000
798.000	4100.000	576.147	.477	.124	0.000	106.600	0.000	1.000
798.000	4410.000	576.324	.177	.137	0.000	106.600	0.000	1.000
798.000	5160.000	576.786	.462	.163	0.000	106.600	0.000	1.000
844.000	3165.000	575.698	0.000	.028	0.000	106.114	0.000	46.000
844.000	4100.000	576.188	.490	.041	0.000	108.956	-2.842	46.000
844.000	4410.000	576.369	.181	.045	0.000	109.000	-2.886	46.000
844.000	5160.000	576.840	.471	.054	0.000	109.000	-2.886	46.000
845.000	3165.000	575.677	0.000	-.021	0.000	98.982	0.000	1.000
845.000	4100.000	576.157	.480	-.031	0.000	101.842	-2.860	1.000
845.000	4410.000	576.335	.178	-.035	0.000	102.000	-3.018	1.000
845.000	5160.000	576.797	.462	-.044	0.000	102.000	-3.018	1.000
859.000	3165.000	575.705	0.000	.028	0.000	99.122	0.000	14.500
859.000	4100.000	576.198	.494	.042	0.000	101.960	-2.838	14.500
859.000	4410.000	576.382	.184	.048	0.000	102.000	-2.878	14.500
859.000	5160.000	576.859	.477	.062	0.000	103.000	-3.878	14.500

EXHIBIT 5
21 of 28

[illegible]	4100.000	576.292	.526	.094	0.000	109.000	[illegible]	[illegible]
[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]
[illegible]	5160.000	576.991	.507	.133	0.000	109.000	-2.57	[illegible]
910.000	3165.000	575.813	0.000	.047	0.000	107.000	0.000	10.000
910.000	4100.000	576.357	.545	.065	0.000	107.000	0.000	50.000
910.000	4410.000	576.555	.198	.071	0.000	107.000	0.000	50.000
910.000	5160.000	577.071	.515	.079	0.000	107.000	0.000	50.000
911.000	3165.000	575.787	0.000	-.025	0.000	105.000	0.000	1.000
911.000	4100.000	576.322	.535	-.036	0.000	105.000	0.000	1.000
911.000	4410.000	576.517	.195	-.039	0.000	105.000	0.000	1.000
911.000	5160.000	577.026	.510	-.044	0.000	105.000	0.000	1.000
921.000	3165.000	575.810	0.000	.023	0.000	105.000	0.000	10.000
921.000	4100.000	576.354	.544	.032	0.000	105.000	0.000	10.000
921.000	4410.000	576.551	.197	.034	0.000	105.000	0.000	10.000
921.000	5160.000	577.065	.515	.039	0.000	105.000	0.000	10.000
922.000	3165.000	575.882	0.000	.073	0.000	107.000	0.000	1.000
922.000	4100.000	576.486	.574	.103	0.000	107.000	0.000	1.000
922.000	4410.000	576.663	.207	.112	0.000	107.000	0.000	1.000
922.000	5160.000	577.197	.534	.132	0.000	107.000	0.000	1.000
953.000	3165.000	575.842	0.000	-.040	0.000	81.000	0.000	31.000
953.000	4100.000	576.392	.550	-.064	0.000	81.000	0.000	31.000
953.000	4410.000	576.590	.198	-.073	0.000	81.000	0.000	31.000
953.000	5160.000	577.104	.513	-.094	0.000	81.000	0.000	31.000
954.000	3165.000	575.795	0.000	-.087	0.000	67.200	0.000	1.000
954.000	4100.000	576.261	.506	-.131	0.000	67.200	0.000	1.000
954.000	4410.000	576.444	.183	-.146	0.000	67.200	0.000	1.000
954.000	5160.000	576.922	.478	-.182	0.000	67.200	0.000	1.000
985.000	3165.000	575.881	0.000	.126	0.000	67.200	0.000	30.500
985.000	4100.000	576.456	.575	.194	0.000	67.200	0.000	30.500
985.000	4410.000	576.663	.207	.218	0.000	67.200	0.000	30.500
985.000	5160.000	577.197	.535	.275	0.000	67.200	0.000	30.500
986.000	3165.000	576.119	0.000	.238	0.000	81.000	0.000	1.000
986.000	4100.000	576.817	.699	.362	0.000	81.000	0.000	1.000
986.000	4410.000	577.066	.249	.404	0.000	81.000	0.000	1.000
986.000	5160.000	577.701	.635	.504	0.000	81.000	0.000	1.000
1036.000	3165.000	576.202	0.000	.083	0.000	114.004	0.000	50.000
1036.000	4100.000	576.964	.762	.146	0.000	117.965	-3.961	50.000
1036.000	4410.000	577.237	.273	.171	0.000	119.388	-5.384	50.000
1036.000	5160.000	577.939	.702	.237	0.000	122.798	-8.794	50.000
1736.000	3165.000	576.677	0.000	.475	0.000	111.327	0.000	700.000
1736.000	4100.000	577.553	.876	.589	0.000	443.285	-331.958	700.000
1736.000	4410.000	577.863	.310	.626	0.000	520.849	-409.522	700.000
1736.000	5160.000	578.652	.789	.713	0.000	560.015	-448.688	700.000
2436.000	3165.000	577.029	0.000	.351	0.000	101.283	0.000	700.000
2436.000	4100.000	577.971	.943	.418	0.000	306.469	-205.186	700.000
2436.000	4410.000	578.270	.299	.407	0.000	342.121	-240.838	700.000
2436.000	5160.000	578.990	.720	.338	0.000	367.491	-266.208	700.000
3186.000	1120.000	577.487	0.000	.459	0.000	160.647	0.000	750.000
3186.000	1620.000	578.521	1.033	.549	0.000	246.467	-85.820	750.000
3186.000	1760.000	578.833	.312	.563	0.000	275.404	-114.756	750.000
[illegible]	[illegible]	[illegible]	.719	.562	0.000	291.912	-131.264	750.000

Exhibit 3
23 of 28

[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]
5105.000	1120.000	577.694	0.000	.114	0.000	81.036	0.000	500.000
5186.000	1620.000	578.755	1.061	.131	0.000	102.218	-21.182	500.000
5186.000	1760.000	579.061	.306	.128	0.000	158.272	-77.236	500.000
5186.000	2055.000	579.751	.690	.111	0.000	199.999	-118.963	500.000
4236.000	1120.000	577.695	0.000	.001	0.000	51.999	0.000	50.000
4236.000	1620.000	578.747	1.053	-.008	0.000	51.999	-.000	50.000
4236.000	1760.000	579.049	.302	-.012	0.000	51.999	-.000	50.000
4236.000	2055.000	579.725	.676	-.025	0.000	51.999	-.000	50.000
4281.000	1120.000	577.759	0.000	.064	0.000	51.999	0.000	45.000
4281.000	1620.000	578.931	1.172	.184	0.000	51.999	-.000	45.000
4281.000	1760.000	579.280	.349	.231	0.000	51.999	-.000	45.000
4281.000	2055.000	580.058	.778	.332	0.000	51.999	-.000	45.000
4931.000	1120.000	577.932	0.000	.173	0.000	78.154	0.000	650.000
4931.000	1620.000	579.182	1.250	.251	0.000	81.552	-3.398	650.000
4931.000	1760.000	579.549	.367	.269	0.000	82.548	-4.395	650.000
4931.000	2055.000	580.358	.809	.300	0.000	84.127	-5.973	650.000
5956.000	1120.000	578.198	0.000	.266	0.000	77.927	0.000	1025.000
5956.000	1620.000	579.493	1.294	.310	0.000	81.457	-3.531	1025.000
5956.000	1760.000	579.863	.370	.314	0.000	82.468	-4.542	1025.000
5956.000	2055.000	580.669	.806	.312	0.000	84.066	-6.139	1025.000
6981.000	1120.000	578.480	0.000	.281	0.000	81.273	0.000	1025.000
6981.000	1620.000	579.813	1.334	.321	0.000	86.057	-4.784	1025.000
6981.000	1760.000	580.187	.374	.325	0.000	87.402	-6.130	1025.000
6981.000	2055.000	580.993	.806	.324	0.000	90.282	-9.009	1025.000
8031.000	1120.000	578.773	0.000	.293	0.000	87.408	0.000	1050.000
8031.000	1620.000	580.143	1.370	.330	0.000	94.346	-6.938	1050.000
8031.000	1760.000	580.519	.376	.332	0.000	95.443	-8.035	1050.000
8031.000	2055.000	581.320	.800	.326	0.000	95.999	-8.591	1050.000
8082.000	1120.000	578.808	0.000	.035	0.000	74.999	0.000	51.000
8082.000	1620.000	580.174	1.366	.031	0.000	74.999	-.000	51.000
8082.000	1760.000	580.548	.374	.029	0.000	74.999	-.000	51.000
8082.000	2055.000	581.341	.793	.021	0.000	74.999	-.000	51.000
8147.000	1120.000	578.859	0.000	.051	0.000	74.999	0.000	65.000
8147.000	1620.000	580.320	1.461	.145	0.000	74.999	-.000	65.000
8147.000	1760.000	580.729	.409	.181	0.000	74.999	-.000	65.000
8147.000	2055.000	581.585	.856	.244	0.000	74.999	-.000	65.000
9397.000	1120.000	579.162	0.000	.303	0.000	80.354	0.000	1250.000
9397.000	1620.000	580.655	1.494	.336	0.000	83.648	-3.294	1250.000
9397.000	1760.000	581.067	.412	.339	0.000	84.179	-3.825	1250.000
9397.000	2055.000	581.924	.857	.339	0.000	84.999	-4.645	1250.000
10297.000	1120.000	579.431	0.000	.269	0.000	71.716	0.000	900.000
10297.000	1620.000	580.933	1.502	.278	0.000	75.234	-3.519	900.000
10297.000	1760.000	581.343	.410	.276	0.000	76.193	-4.478	900.000
10297.000	2055.000	582.191	.849	.267	0.000	77.982	-6.266	900.000
10897.000	1120.000	579.609	0.000	.178	0.000	71.589	0.000	600.000
10897.000	1620.000	581.121	1.512	.188	0.000	72.999	-1.410	600.000
10897.000	1760.000	581.530	.409	.188	0.000	72.999	-1.410	600.000
10897.000	2055.000	582.377	.847	.186	0.000	72.999	-1.410	600.000
10973.000	1120.000	579.621	0.000	.012	0.000	51.999	[illegible]	[illegible]

Exhibit 3
26 of 28

11617.000	1120.000	579.761	0.000	.140	0.000	51.999	0.000	[illegible]
11617.000	1620.000	581.514	1.753	.393	0.000	51.999	-.000	[illegible]
11617.000	1760.000	581.983	.469	.455	0.000	52.000	-.000	[illegible]
11617.000	2055.000	582.895	.912	.528	0.000	52.000	-.000	[illegible]
11677.000	1120.000	580.012	0.000	.251	0.000	73.467	0.000	460.000
11677.000	1620.000	581.797	1.785	.283	0.000	85.222	-11.755	460.000
11677.000	1760.000	582.273	.476	.290	0.000	93.646	-20.179	460.000
11677.000	2055.000	583.204	.931	.309	0.000	99.999	-26.532	460.000
11528.000	1120.000	580.013	0.000	.001	0.000	50.499	0.000	51.000
11528.000	1620.000	581.785	1.772	-.012	0.000	52.499	-2.000	51.000
11528.000	1760.000	582.257	.472	-.016	0.000	52.499	-2.000	51.000
11528.000	2055.000	583.178	.921	-.026	0.000	52.499	-2.000	51.000
11599.000	1120.000	580.025	0.000	.011	0.000	50.499	0.000	71.000
11599.000	1620.000	582.013	1.988	.228	0.000	52.499	-2.000	71.000
11599.000	1760.000	582.549	.536	.292	0.000	52.499	-2.000	71.000
11599.000	2055.000	583.546	.997	.368	0.000	52.499	-2.000	71.000
11650.000	1120.000	580.066	0.000	.041	0.000	53.836	0.000	51.000
11650.000	1620.000	582.061	1.995	.048	0.000	55.999	-2.163	51.000
11650.000	1760.000	582.598	.537	.049	0.000	55.999	-2.163	51.000
11650.000	2055.000	583.600	1.002	.054	0.000	55.999	-2.163	51.000
11721.000	1120.000	580.075	0.000	.010	0.000	53.842	0.000	71.000
11721.000	1620.000	582.314	2.239	.253	0.000	55.999	-2.157	71.000
11721.000	1760.000	582.919	.605	.321	0.000	55.999	-2.157	71.000
11721.000	2055.000	583.996	1.077	.397	0.000	55.999	-2.157	71.000

DATA FOR LAST CROSS SECTION

PROFILE	TYPE ENC	TARGET	TOP WIDTH AREA-ACRES	TOP WIDTH AREA-DIFF
1	0.000	56.000	24.359	0.000
2	0.000	56.000	35.978	11.619
3	0.000	56.000	39.108	14.749
4	0.000	56.000	41.659	17.300

Exhibit 15
220 of 66

[redacted]

[illegible] VERSION UPDATED JAN 1976
ERROR CORRECTIONS 01,02,03,04,05,06,07,08,09
ADDITIONS [illegible]

Exhibit 3
2837-8

CITY OF LINCOLN PARK, MICHIGAN

SOUTH BRANCH ECORSE CREEK

EXHIBIT 4

HEC-2 Backwater Analysis with

Cross Section Plots (See Separate Folder)

CITY OF LINCOLN PARK, MICHIGAN

SOUTH BRANCH ECORSE CREEK

EXHIBIT 5

Stream Profile

CITY OF LINCOLN PARK, MICHIGAN

NORTH BRANCH ECORSE CREEK

EXHIBIT 6

Bridge Notes and Sketches

HUD
.010-1.5


BRIDGE DETAIL AT AUSTIN AVE
AND NORTH BRANCH ECORSE CREEK

F.B # 941

A.P
B.U
L.C

JAN. 3-1977

28



CURRENT DATA

VIEW STANDING DOWNSTREAM FACING UPSTREAM.

HUD 2010-05


BRIDGE DETAIL AT VICTORIA ST. AND NORTH BRANCH ECORSE CREEK

F.B. II 941

A.P. & U. L.C.

JAN. 3-1978

25





9 of 10

HUD 2010-05

BRIDGE DETAIL AT N. BOUND FORT ST AND N. BRANCH ECORSE CREEK.

F.B # 941 A.P MIS. DEC. 29-1977 22





NOTE: THERE ARE 14 STEEL PILLERS WITH 4'± BETWEEN PILLERS


VIEW STANDING DOWNSTREAM FACING UPSTREAM

9/703


MD
2010-05

BRIDGE DETAIL AT S. BOUND FORT ST
AND N. BRANCH ECORSE CREEK.

F.B. # 941 A.P. M.S. DEC 29-1977 19.



CURRENT DATUM



NOTE: THEAR ARE 13 STEEL PILLERS WITH 4 'BETWEEN PILLERS

VIEW STANDING DOWNSTREAM FACING UPSTREAM

Bridge Location: N. Branch Ecorse Creek Lafayette

REFERENCE

Bridge Losses - SB Card

1. XK (Pier Shape Coefficient): 0 — HEC-2 manual

XKOR (Loss Coefficient) = 1.0 + Σk, $\Sigma k = k_f + k_e + k_p$

where k_f = friction loss coefficient
k_e = entrance loss coefficient
k_p = loss from intermediate piers

Description of Bridge:

$K_f = 29.1\, n^2 L / R^{4/3}$ for English units

Area = 168 = ____ Wp = 68

$R = A/wp = 2.47$ $R^{4/3} = 3.34$ $L = 44$

n (composite) = .02

$K_f = 29.1 \times (.02)^2 \times 44/3.34 = .15$

$K_e = .5$ — Hydraulic Charts for the Selection of Highway Culverts Circular No. 5 Dec. 1965 pg. 4

(Kp = 0) if bridge has no intermediate piers

Kp = 0.05 if bridge has intermediate piers — HEC-2 manual

2. XKOR = 1 + .5 + .15 + 0 = 1.65
3. COFQ = Coefficient of discharge = 3.0 — HEC-2 manual
4. RDLEN = Length of weir = 100. (0 if read off BT cards)
5. BWC = bottom width of bridge opening (inc. piers): 28
6. BWP = total width of obstruction = 0 — field data
7. BAREA = bridge opening = 168
8. SS = side slope = 0 (horizontal per 1 vertical unit)
9. ELCHU = Elevation of channel invert U/S side = 577. (0 if equal to minimum elevation in previous X-sect.)
10. ELCHD = Elevation of channel invert D/S side = 577. (0 if equal to minimum elevation in previous X-sect.)

HUD BRIDGE DETAIL AT LAFAYETTE BLVD.


2010-05 MNU NORTH BRANCH ECORSE CREEK.

F.B #941

A:P.
B:U
L:C

DEC. 22-1977

16.




CURRENT DATE 586.45

VIEW STANDING DOWNSTREAM FACING UPSTREAM


HUD 2010-05

BRIDGE DETAIL AT I-75 AND NORTH BRANCH ECORSE CREEK


F.B # 941 A.P. B.V L.C DEC. 22-1977 14.



CURRENT DATUM



VIEW STANDING UPSTREAM FACING DOWNSTREAM



VIEW STANDING DOWNSTREAM FACING UPSTREAM

Bridge Location: N. Branch Ecorse + Industrial Drive

Bridge Losses - SB Card

REFERENCE

1. XK (Pier Shape Coefficient): 0 — HEC-2 manual

XKOR (Loss Coefficient) = 1.0 + Σk, $\Sigma k = k_f + k_e + k_p$

where k_f = friction loss coefficient
k_e = entrance loss coefficient
k_p = loss from intermediate piers

Description of Bridge:

$K_f = 29.1\, n^2 L / R^{4/3}$ for English units

Area = 330 = _____ WP = 79.1

$R = A/wp = \frac{330}{79.1} = 4.17$ $R^{4/3} = 6.71$ $L = 41$

n (composite) $= \frac{(.033 \cdot 46.5) + (.015 \cdot 32.6)}{79.1} = .026$

$K_f = 29.1 \times (.026)^2 \times 41/6.71 = .12$


$K_e = .7$ — Hydraulic Charts for the Selection of Highway Culverts Circular No. 5 Dec. 1965 pg. 49

$K_p = 0$ if bridge has no intermediate piers

$K_p = 0.05$ if bridge has intermediate piers — HEC-2 manual

2. XKOR = 1 + .12 + .7 + 0 = 1.82
3. COFQ = Coefficient of discharge = 3.0 — HEC-2 manual
4. RDLEN = Length of weir = 0 (0 if read off BT cards)
5. BWC = bottom width of bridge opening (inc. piers): 26.83
6. BWP = total width of obstruction = 0 — field data
7. BAREA = bridge opening = 330.0
8. SS = side slope = 0 (horizontal per 1 vertical unit)
9. ELCHU = Elevation of channel invert U/S side = 574.9 (0 if equal to minimum elevation in previous X-sect.)
10. ELCHD = Elevation of channel invert D/S side = 574.6 (0 if equal to minimum elevation in previous x-sect.)

SUBJECT	BY	CHK.	SHEET NO	File Code No. (Job No.) Owner Project Suffix
Lincoln Park - Hydraulics	T.G.		8 OF 16	HUD 2010 07
	DATE 10-1-79	DATE		




SECTION C-C

sheet 14 of 15
6-8-79

CITY OF LINCOLN PARK, MICHIGAN: INDUSTRIAL DRIVE CULVERT, Culvert Details + Location Plan
Pate, Hirn + Bogue, Inc., Civil Engineers

9 of 16



SECTION AT STA. 55+75.39

N.T.S.

sheet 13 of 15
6-8-79

CITY OF LINCOLN PARK, MICHIGAN: INDUSTRIAL DRIVE CULVERT, Plan, Profile + Soil Borings by Pate, Hira + Bogue - Civil Engineers

91 of 101

Bridge Location: Penn Central R.R.

Bridge Losses - SB Card

REFERENCE

1. XK (Pier Shape Coefficient): 1.25 — HEC-2 Manual

XKOR (Loss Coefficient) = 1.0 + Σk, $\Sigma k = k_f + k_e + k_p$

where k_f = friction loss coefficient
k_e = entrance loss coefficient
k_p = loss from intermediate piers

Description of Bridge:

$K_f = 29.1\, n^2 L / R^{4/3}$ for English units

Area = 182 = _____ Wp = 78.4

$R = A/wp = 2.32$ $R^{4/3} = 3.07$ $L = 197$

n (composite) $= \frac{0.018(54) + 0.035(24) = .023}{78}$

$K_f = 29.1 \times (.023)^2 \times \frac{197}{3.07} = .99$

$K_e = 0.5$ — Hydraulic Charts for the Selection of Highway Culverts Circular No. 5 Dec. 1965 pg. 45

$K_p = 0$ if bridge has no intermediate piers

$K_p = 0.05$ if bridge has intermediate piers — HEC-2 manual

2. XKOR = 1 + .99 + .5 + 0 = 2.49
3. COFQ = Coefficient of discharge = 3.0 — HEC-2 manual
4. RDLEN = Length of weir = _____ (0 if read off BT cards)
5. BWC = bottom width of bridge opening (inc. piers): 27.2
6. BWP = total width of obstruction = 32 — field data
7. BAREA = bridge opening = 182
8. SS = side slope = _____ (horizontal per 1 vertical unit)
9. ELCHU = Elevation of channel invert U/S side = 577.9 (0 if equal to minimum elevation in previous X-sect.)
10. ELCHD = Elevation of channel invert D/S side = 577.9 (0 if equal to minimum elevation in previous X-sect.)

ITUD
2010-05


BRIDGE DETAIL AT PENN CENTRAL R.R AND N. BRANCH ECORSE CREEK.

F.B #941


A.P
13.U
L.C

DEC 15-1977
DEC 16-1977


10



CURRENT CONDITION



VIEW STANDING UPSTREAM FACING DOWNSTREAM



VIEW STANDING DOWNSTREAM FACING UPSTREAM


HUD 2010-05

BRIDGE DETAIL AT PORTER ST. AND NORTH BRANCH ECORSE CREEK


F.B. # 941

A.P. DEC 15 - 1977
B.U
L.C DEC 16 - 1977

8.



13 OF 16


NUD 2010-05
BRIDGE DETAIL AT RAUPP PLACE AND NORTH BRANCH ECORSE CREEK
F.B. #941
A.P.
B.V.
L.C.
DEC. 15-1977
5.
CURRENT DATUM
DOWNSTREAM
595.54
584.97
CONC
13.5'
CONC.
CONC.
1.80
4.50'
S.60°E.
584.94
STA. 12+54
℄ RAUPP PL.
16'
UPSTREAM
VIEW STANDING DOWNSTREAM FACING UPSTREAM
91+01

HUD 2010-05

BRIDGE DETAIL AT DIX-TOLEDO RD. AND NORTH BRANCH ECORSE CREEK


F.B #941

A.P.
B.V.
L.C

DEC. 13 - 1977

3.

CURRENT DATUM




15 of 16

BRIDGE DETAIL AT FRANK AVE.
AND NORTH BRANCH ECORSE CREEK.

12-8-77 & 12-12-77

1.

FE 141 A.P BY L.C.



VIEW STANDING DOWNSTREAM FACING UPSTREAM

CITY OF LINCOLN PARK, MICHIGAN

NORTH BRANCH ECORSE CREEK

EXHIBIT 7

HEC-2 Backwater Analysis

From City of Ecorse F.I.S.

```
HEC2 VERSION UPDATED JAN 1976
ERROR CORRECTIONS 01,02,03,04,05,06,07,08,09
MODIFICATIONS 52,53,54,55,56,57,58
**********
C
I      CITY OF ECORSE   5555-16   DICK ZANOTTI  P.M.
T2     10 YEAR FLOOD.
T3     NORTH BRANCH OF ECORSE CREEK
```

J1	ICHECK	INQ	NINV	IDIR	STRT	METRIC	HVINS	Q	WSEL	FQ
	-0.	2.	-0.	-0.	-0.000000	-0.00	-0.0	-0.	574.900	-0.000

J2	NPROF	IPLOT	PRFVS	XSECV	XSECH	FN	ALLDC	IBW	CHNIM	ITRACE
	1.000	-0.000	-1.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000

J3	1.000	10.000	11.000	12.000	14.000	8.000	4.000	-0.000	-0.000	-0.000
NC	.035	.035	.030	.100	.500	-0.000	-0.000	-0.000	-0.000	-0.000
BT	4.000	3165.000	4100.000	4410.000	5150.000	-0.000	-0.000	-0.000	-0.000	-0.000
X1	1.000	41.000	500.000	61[illegible].000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000
GR	576.200	0.000	575.900	100.000	576.600	200.000	578.500	300.000	581.100	400.000
GR	584.600	500.000	582.800	600.000	582.600	605.000	581.900	610.000	581.100	615.000
GR	579.200	520.000	575.400	525.000	574.800	530.000	572.800	535.000	569.200	540.000
GR	569.200	540.000	565.500	543.500	565.500	543.500	565.500	545.000	563.900	555.000
GR	566.100	560.000	565.300	565.000	565.400	570.000	564.100	575.000	566.200	580.000
GR	566.200	580.000	565.300	583.500	565.300	583.500	565.300	585.000	563.400	590.000
GR	564.400	595.000	565.400	600.000	567.700	605.000	571.100	610.000	573.500	615.000
GR	574.000	619.000	584.600	619.000	582.300	700.000	579.600	800.000	579.000	890.000
GR	578.700	1000.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000
X1	30.000	-0.000	-0.000	-0.000	[illegible].000	[illegible].000	[illegible].000	-0.000	-0.000	-0.000
X1	60.000	41.000	500.000	619.000	30.000	30.000	30.000	-0.000	-0.000	-0.000
GR	576.200	0.000	575.900	100.000	576.600	200.000	578.500	300.000	581.100	400.000
GR	584.600	500.000	582.800	600.000	582.600	605.000	581.900	610.000	581.100	615.000
GR	579.200	520.000	575.400	525.000	574.800	530.000	572.800	535.000	569.200	540.000
GR	569.200	540.000	565.500	543.500	565.500	543.500	565.500	545.000	563.900	555.000
GR	566.100	560.000	565.300	565.000	565.400	570.000	564.100	575.000	566.200	580.000
GR	566.200	580.000	565.300	583.500	565.300	583.500	565.300	585.000	563.400	590.000
GR	564.400	595.000	565.400	600.000	567.700	605.000	571.100	610.000	573.500	615.000
GR	574.000	619.000	584.600	619.000	582.300	700.000	579.600	800.000	579.000	890.000
GR	578.700	1000.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000
X1	61.000	41.000	500.000	519.000	1.000	1.000	1.000	-0.000	-0.000	-0.000
BT	9.000	500.000	584.300	579.800	500.000	587.700	579.800	540.000	588.100	580.300
BT	543.500	588.100	580.300	560.000	583.300	590.300	580.000	588.100	580.300	583.500
BT	588.100	580.300	619.000	587.700	579.700	619.000	584.400	579.700	-0.000	-0.000
GR	576.200	0.000	575.900	100.000	576.600	200.000	578.500	300.000	581.100	400.000
GR	584.600	500.000	582.800	600.000	582.600	605.000	581.900	610.000	581.100	615.000
GR	579.200	520.000	575.400	525.000	574.800	530.000	572.800	535.000	569.200	540.000
GR	580.300	540.000	580.300	543.500	565.500	543.500	565.500	545.000	563.900	555.000
GR	566.100	560.000	565.300	565.000	565.400	570.000	564.100	575.000	566.200	580.000
GR	580.300	580.000	580.300	583.500	565.300	583.500	565.300	585.000	563.400	590.000
GR	564.400	595.000	565.400	600.000	567.700	605.000	571.100	610.000	573.500	615.000
GR	574.000	619.000	584.600	619.000	582.300	700.000	579.600	800.000	579.000	890.000
GR	578.700	1000.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000

Exhibit 7
1 of 41

[redacted]											
X1	187.000	41.000	500.000	619.000	1.000	1.000	1.000	-0.000	[redacted]		
GR	576.200	0.000	575.900	100.000	576.600	200.000	578.300	200.000			
[redacted]	4.600	500.000	542.000	500.000	572.600	505.000	1.900	510.000			
[redacted]	575.200	520.000	575.400	525.000	574.800	530.000	572.800	535.000			
GR	560.200	540.000	565.500	543.500	565.500	543.500	565.500	545.000	[redacted]		
GR	566.100	560.000	565.300	565.000	565.400	570.000	564.100	575.000	560.300	[redacted]	
GR	566.200	580.000	565.300	583.500	565.300	583.500	565.300	585.000	563.400	[redacted]	
GR	564.400	595.000	565.400	600.000	567.700	605.000	571.100	610.000	573.500	[redacted]	
GR	574.000	619.000	584.600	619.000	582.300	700.000	579.600	800.000	575.000	[redacted]	
GR	578.700	1000.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	
NC	.035	.042	.030	±0.000	±0.000	-0.000	-0.000	-0.000	±0.000	-0.000	
X1	187.000	27.000	331.000	441.000	50.000	50.000	50.000	-0.000	-0.000	-0.000	
GR	575.800	0.000	576.600	41.000	578.500	141.000	580.600	241.000	583.100	331.000	
GR	575.400	341.000	574.800	346.000	571.300	351.000	568.100	356.000	567.200	361.000	
GR	565.700	366.000	565.100	371.000	565.500	376.000	565.100	381.000	564.700	391.000	
GR	564.100	401.000	564.400	406.000	565.700	411.000	568.200	416.000	570.500	421.000	
GR	572.800	426.000	574.800	432.000	580.200	441.000	583.600	454.000	581.000	541.000	
GR	579.300	641.000	578.300	698.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	
NH	4.000	.035	244.000	.030	360.000	.070	400.000	.035	800.000	±0.000	
X1	362.000	35.000	244.000	400.000	175.000	175.000	175.000	-0.000	.270	-0.000	
GR	580.200	0.000	579.500	100.000	578.300	200.000	578.300	244.000	574.600	254.000	
GR	573.600	255.000	571.500	260.000	569.400	265.000	568.500	270.000	567.600	275.000	
GR	566.900	280.000	565.900	285.000	563.600	290.000	563.700	300.000	563.700	310.000	
GR	564.300	320.000	565.400	330.000	568.200	340.000	569.400	345.000	571.100	350.000	
GR	571.600	355.000	572.400	360.000	572.100	365.000	572.600	370.000	572.600	375.000	
GR	572.800	380.000	572.800	385.000	572.400	390.000	574.600	395.000	576.900	400.000	
GR	577.600	500.000	577.700	545.000	577.500	600.000	577.700	700.000	577.500	800.000	
X1	737.000	35.000	244.000	400.000	375.000	375.000	375.000	-0.000	-0.000	-0.000	
X3	-0.000	-0.000	-0.000	244.000	-0.000	375.000	-0.000	-0.000	-0.000	-0.000	
GR	580.200	0.000	579.500	100.000	578.300	200.000	578.300	244.000	574.600	254.000	
GR	573.600	255.000	571.500	260.000	569.400	265.000	568.500	270.000	567.600	275.000	
GR	566.900	280.000	565.900	285.000	563.600	290.000	563.700	300.000	563.700	310.000	
GR	564.300	320.000	565.400	330.000	568.200	340.000	569.400	345.000	571.100	350.000	
GR	571.600	355.000	572.400	360.000	572.100	365.000	572.600	370.000	572.600	375.000	
GR	572.800	380.000	572.800	385.000	572.400	390.000	574.600	395.000	576.900	400.000	
GR	577.600	500.000	577.700	545.000	577.500	600.000	577.700	700.000	577.500	800.000	
NC	.035	.042	.032	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	
X1	787.000	67.000	795.000	901.600	50.000	50.000	50.000	-0.000	-0.000	-0.000	
GR	581.500	0.000	581.400	95.000	581.300	195.000	581.200	295.000	581.100	395.000	
GR	581.100	495.000	581.100	595.000	581.000	695.000	581.000	795.000	575.200	795.000	
GR	574.500	800.000	574.500	800.000	574.500	801.000	574.500	801.000	574.000	805.000	
GR	573.200	810.000	573.200	810.000	573.200	811.000	573.200	811.000	570.800	815.000	
GR	569.300	820.000	570.100	825.000	570.100	826.000	570.100	826.000	570.100	826.000	
GR	566.600	829.900	566.600	829.900	566.600	831.200	566.600	831.200	565.500	835.000	
GR	565.500	835.000	565.500	836.000	565.500	836.000	563.900	840.000	564.500	845.000	
GR	564.500	845.000	564.500	846.000	564.500	846.000	564.900	850.000	564.900	855.000	
GR	564.900	855.000	564.900	856.000	564.900	856.000	565.500	860.000	565.200	865.000	
GR	565.200	865.000	565.200	866.300	565.300	866.300	566.000	870.000	566.000	875.000	
GR	566.000	875.000	566.000	876.000	566.000	876.000	566.700	880.000	568.700	885.000	
GR	568.300	890.000	569.700	895.000	571.700	900.000	571.700	901.600	581.000	901.600	
GR	580.800	995.000	580.800	1095.000	580.600	1195.000	580.400	1295.000	580.100	1395.000	
GR	579.900	1495.000	580.000	1540.000	-0.000	-0.000	-0.000	±0.000	±0.000	±0.000	
X1	788.000	67.000	795.000	901.600	1.000	1.000	1.000	-0.000	-0.000	-0.000	
B1	4.000	795.000	581.000	577.200	830.000	581.000	577.200	860.000	581.000	577.200	
B1	901.600	581.000	577.200	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	

Ex 6.17
2 of 41

	GR	573.200	810.000	575.500	810.000	575.500	811.000	573.200	811.000	[illegible]	[illegible]
[redacted]	GR	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]
	GR	566.600	830.000	577.200	830.000	577.200	831.300	566.500	[illegible]	[illegible]	[illegible]
	GR	575.500	835.000	575.500	836.000	565.500	836.000	563.900	[illegible]	[illegible]	[illegible]
	GR	575.500	845.000	575.500	846.000	564.500	846.000	564.900	[illegible]	[illegible]	[illegible]
	GR	575.500	855.000	575.500	856.000	564.900	856.000	565.500	[illegible]	[illegible]	[illegible]
	GR	577.200	865.000	577.200	866.300	565.200	866.300	566.000	[illegible]	[illegible]	[illegible]
	GR	575.500	875.000	575.500	876.000	566.000	876.000	566.100	[illegible]	[illegible]	[illegible]
	GR	568.300	890.000	569.700	895.000	571.700	900.000	571.700	901.600	[illegible]	[illegible]
	GR	580.800	995.000	580.800	1095.000	580.600	1195.000	580.400	1295.000	[illegible]	[illegible]
	GR	579.900	1495.000	580.000	1540.000	-0.000	-0.000	-0.000	-0.000	[illegible]	[illegible]
	X1	797.000	0.000	795.000	901.600	9.000	9.000	9.000	-0.000	[illegible]	[illegible]
	X2	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	1.000	-0.000	[illegible]	[illegible]
	X1	798.000	67.000	795.000	901.600	1.000	1.000	1.000	-0.000	-0.000	[illegible]
	GR	581.500	0.000	581.400	95.000	581.300	195.000	581.200	295.000	581.100	[illegible]
	GR	581.100	495.000	581.100	595.000	581.000	695.000	581.000	795.000	575.200	[illegible]
	GR	574.500	800.000	574.500	800.000	574.500	801.000	574.500	801.000	574.000	[illegible]
	GR	573.200	810.000	573.200	810.000	573.200	811.000	573.200	811.000	570.800	[illegible]
	GR	569.300	820.000	570.100	825.000	570.100	825.000	570.100	826.000	570.100	826.000
	GR	566.600	829.900	566.600	829.900	566.600	831.200	566.600	831.200	565.500	835.000
	GR	565.500	835.000	565.500	836.000	565.500	836.000	563.900	840.000	564.500	845.000
	GR	564.500	845.000	564.500	846.000	564.500	846.000	564.900	850.000	564.900	855.000
	GR	564.900	855.000	564.900	856.000	564.900	856.000	565.500	860.000	565.200	865.000
	GR	565.200	865.000	565.200	866.300	565.300	866.300	566.000	870.000	566.100	875.000
	GR	566.000	875.000	566.000	875.000	566.000	876.000	566.700	880.000	568.700	885.000
	GR	568.300	890.000	569.700	895.000	571.700	900.000	571.700	901.600	581.000	901.600
	GR	580.800	995.000	580.800	1095.000	580.600	1195.000	580.400	1295.000	580.100	1395.000
	GR	579.900	1495.000	580.000	1540.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000
	X1	844.000	58.000	815.000	924.000	45.000	46.000	46.000	-0.000	-0.000	-0.000
	GR	583.400	0.000	583.400	15.000	583.100	115.000	582.900	215.000	582.600	315.000
	GR	582.600	415.000	582.300	515.000	582.100	615.000	581.900	715.000	581.500	815.000
	GR	576.100	815.000	574.200	820.000	572.700	825.000	570.000	829.000	570.000	829.000
	GR	570.000	830.000	570.000	831.000	568.000	835.000	565.900	840.000	565.000	844.000
	GR	565.000	844.000	565.000	845.000	565.000	845.000	565.000	855.000	566.000	864.000
	GR	566.000	864.000	566.000	865.000	566.000	865.000	566.100	874.000	568.100	874.000
	GR	566.100	875.000	566.100	875.000	565.800	884.000	565.400	884.000	565.800	885.000
	GR	565.800	885.000	565.600	890.000	565.200	894.000	565.200	894.000	565.200	895.000
	GR	565.200	895.000	567.600	900.000	570.300	905.000	572.000	909.000	572.000	909.000
	GR	572.000	910.000	572.000	910.100	574.000	915.000	575.100	920.000	576.200	924.000
	GR	581.400	924.000	581.300	1015.000	581.300	1115.000	581.100	1215.000	581.100	1315.000
	GR	581.100	1415.000	581.200	1515.000	581.200	1565.000	-0.000	-0.000	-0.000	-0.000
	X1	845.000	58.000	815.000	924.000	1.000	1.000	1.000	-0.000	-0.000	-0.000
	BT	16.000	815.000	581.500	578.400	824.000	581.500	578.100	830.000	581.500	578.100
	BT	844.000	581.500	577.900	845.000	581.500	577.900	864.000	581.500	577.500	865.000
	BT	581.500	577.500	874.000	581.400	577.400	875.000	581.400	577.400	884.000	581.400
	BT	577.200	885.000	581.400	577.200	894.000	581.400	577.000	895.000	581.400	577.000
	BT	909.000	581.400	576.800	910.000	581.400	576.800	924.000	581.400	576.500	-0.000
	GR	583.400	0.000	583.400	15.000	583.100	115.000	582.900	215.000	582.800	315.000
	GR	582.600	415.000	582.300	515.000	582.100	615.000	581.900	715.000	581.500	815.000
	GR	576.100	815.000	574.200	820.000	572.700	825.000	570.000	829.000	578.100	829.000
	GR	578.100	830.000	570.000	830.000	568.000	835.000	565.900	840.000	565.000	844.000
	GR	577.900	844.000	577.900	845.000	565.000	845.000	565.000	855.000	566.000	864.000
	GR	577.500	864.000	577.500	865.000	566.000	865.000	566.100	874.000	577.400	874.000
	GR	577.400	875.000	566.100	875.000	565.800	884.000	577.200	884.000	577.200	885.000
	GR	565.800	885.000	565.600	890.000	565.200	894.000	577.000	894.000	577.000	895.000
	GR	565.200	895.000	567.600	900.000	570.300	905.000	572.000	909.000	576.800	909.000
	GR	576.800	910.000	572.000	910.000	574.000	915.000	575.100	920.000	576.200	924.000
	GR	581.400	924.000	581.300	1015.000	581.300	1115.000	581.100	1215.000	581.100	1315.000
	GR	581.100	1415.000	581.200	1515.000	581.200	1565.000	-0.000	-0.000	-0.000	-0.000
	X1	859.000	58.000	815.000	924.000	14.500	14.500	14.500	-0.000	-0.000	-0.000

Exhibit 7
3 of 11

GR	583.400	0.000	533.400	15.000	583.100	115.000	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]
[redacted]	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]
GR	576.100	815.000	574.200	820.000	572.700	825.000	570.900	825.000	[redacted]	[redacted]	[redacted]
GR	570.000	830.000	570.000	830.000	568.000	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]
GR	565.000	844.000	565.000	845.000	565.000	845.000	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]
GR	566.000	864.000	566.000	865.000	566.000	865.000	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]
GR	566.100	875.000	566.100	875.000	565.800	884.000	565.800	[redacted]	[redacted]	[redacted]	[redacted]
GR	565.800	885.000	565.600	890.000	565.200	894.000	565.200	[redacted]	[redacted]	[redacted]	[redacted]
GR	565.200	895.000	567.600	900.000	570.300	905.000	572.000	[redacted]	[redacted]	[redacted]	[redacted]
GR	572.000	910.000	572.000	910.000	574.000	915.000	575.100	920.000	[redacted]	[redacted]	[redacted]
GR	581.400	924.000	581.300	1015.000	581.300	1115.000	581.100	1215.000	[redacted]	[redacted]	[redacted]
GR	581.100	1415.000	581.200	1515.000	581.200	1565.000	-0.000	-0.000	-0.000	-0.000	[redacted]
X1	910.000	64.000	835.000	942.000	50.000	50.000	50.000	-0.000	-0.000	[redacted]	[redacted]
GR	583.700	0.000	583.600	35.000	583.400	135.000	583.300	235.000	583.300	[redacted]	[redacted]
GR	583.300	435.000	583.300	535.000	583.200	635.000	583.100	735.000	583.100	[redacted]	[redacted]
GR	574.800	835.000	572.600	840.000	571.600	844.000	571.600	844.000	571.000	[redacted]	[redacted]
GR	571.600	845.000	570.700	854.000	570.700	854.000	570.700	855.000	570.700	[redacted]	[redacted]
GR	565.600	864.000	565.600	864.000	565.600	865.000	565.600	865.000	564.300	[redacted]	[redacted]
GR	564.300	874.000	564.300	875.000	564.300	875.000	564.800	884.000	564.800	[redacted]	[redacted]
GR	564.800	885.000	564.800	895.000	564.900	894.000	564.900	894.000	564.900	[redacted]	[redacted]
GR	564.900	895.000	564.000	904.000	564.000	904.000	564.000	905.000	564.000	[redacted]	[redacted]
GR	566.100	914.000	566.100	914.000	566.100	915.000	566.100	915.000	567.000	[redacted]	[redacted]
GR	571.000	924.000	571.000	924.000	571.000	925.000	571.000	925.000	572.400	[redacted]	[redacted]
GR	573.900	934.000	573.900	934.000	573.900	935.000	573.900	935.000	575.000	[redacted]	[redacted]
GR	574.900	942.000	583.000	942.000	582.700	1035.000	582.600	1135.000	582.300	[redacted]	[redacted]
GR	582.100	1335.000	581.900	1435.000	581.800	1535.000	581.800	1585.000	-0.000	-0.000	[redacted]
X1	911.000	64.000	835.000	942.000	1.000	1.000	1.000	-0.000	-0.000	[redacted]	[redacted]
BT	6.000	835.000	583.100	578.600	874.000	583.100	578.600	875.000	583.100	[redacted]	[redacted]
BT	904.000	583.000	578.600	905.000	583.000	578.600	942.000	583.000	578.600	-0.000	[redacted]
GR	583.700	0.000	583.600	35.000	583.400	135.000	583.300	235.000	583.300	[redacted]	[redacted]
GR	583.300	435.000	583.300	535.000	583.200	635.000	583.100	735.000	583.100	[redacted]	[redacted]
GR	574.800	835.000	572.600	840.000	571.600	844.000	575.500	844.000	575.500	[redacted]	[redacted]
GR	571.600	845.000	570.700	854.000	575.500	854.000	575.500	855.000	570.700	[redacted]	[redacted]
GR	565.600	864.000	575.500	864.000	575.500	865.000	565.600	865.000	564.300	874.000	[redacted]
GR	578.600	874.000	578.600	875.000	564.300	875.000	564.800	884.000	575.500	884.000	[redacted]
GR	575.500	885.000	564.800	845.000	564.900	894.000	575.500	894.000	575.500	895.000	[redacted]
GR	564.900	895.000	564.000	904.000	578.600	904.000	578.600	905.000	564.000	905.000	[redacted]
GR	566.100	914.000	575.500	914.000	575.500	915.000	566.100	915.000	567.000	920.000	[redacted]
GR	571.000	924.000	575.500	924.000	575.500	925.000	571.000	925.000	572.400	930.000	[redacted]
GR	573.900	934.000	575.500	934.000	575.500	935.000	573.900	935.000	575.000	940.000	[redacted]
GR	574.900	942.000	583.000	942.000	582.700	1035.000	582.600	1135.000	582.300	1235.000	[redacted]
GR	582.100	1335.000	581.900	1435.000	581.800	1535.000	581.800	1585.000	-0.000	-0.000	[redacted]
X1	921.000	-0.000	835.000	942.000	10.000	10.000	10.000	-0.000	-0.000	-0.000	[redacted]
X2	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	1.000	-0.000	-0.000	-0.000	[redacted]
X1	922.000	64.000	835.000	942.000	1.000	1.000	1.000	-0.000	-0.000	-0.000	[redacted]
GR	583.700	0.000	583.600	35.000	583.400	135.000	583.300	235.000	583.300	335.000	[redacted]
GR	583.300	435.000	583.300	535.000	583.200	635.000	583.100	735.000	583.100	835.000	[redacted]
GR	574.800	835.000	572.600	840.000	571.600	844.000	571.600	844.000	571.000	845.000	[redacted]
GR	571.600	845.000	570.700	854.000	570.700	854.000	570.700	855.000	570.700	855.000	[redacted]
GR	565.600	864.000	565.600	864.000	565.600	865.000	565.600	865.000	564.300	874.000	[redacted]
GR	564.300	874.000	564.300	875.000	564.300	875.000	564.900	884.000	564.800	884.000	[redacted]
GR	564.800	885.000	564.800	895.000	564.900	894.000	564.900	894.000	564.900	895.000	[redacted]
GR	564.900	895.000	564.000	904.000	564.000	904.000	564.000	905.000	564.000	905.000	[redacted]
GR	566.100	914.000	566.100	914.000	566.100	915.000	566.100	915.000	567.000	920.000	[redacted]
GR	571.000	924.000	571.000	924.000	571.000	925.000	571.000	925.000	572.400	930.000	[redacted]
GR	573.900	934.000	573.900	934.000	573.900	935.000	573.900	935.000	575.000	940.000	[redacted]
GR	574.900	942.000	583.000	942.000	582.700	1035.000	582.600	1135.000	582.300	1235.000	[redacted]
GR	582.100	1335.000	581.900	1435.000	581.800	1535.000	581.800	1585.000	-0.000	-0.000	[redacted]
X1	953.000	48.000	600.000	691.000	31.000	31.000	31.000	-0.000	-0.000	-0.000	[redacted]
GR	582.000	0.000	581.800	100.000	581.600	200.000	581.500	300.000	581.400	400.000	[redacted]
GR	581.200	500.000	581.000	600.000	571.000	600.000	568.100	605.000	566.900	610.000	[redacted]
GR	566.900	610.000	566.900	612.300	566.300	612.300	565.900	615.000	565.100	620.000	[redacted]
GR	565.100	620.000	565.100	622.300	565.100	622.300	566.300	625.000	566.200	631.000	[redacted]
GR	566.200	630.000	566.200	632.300	566.300	634.300	566.700	635.000	566.300	640.000	[redacted]

Exhibit 7
4 of 41

X1	953.000	44.000	600.000	641.000	31.000	31.000	[illegible]	[illegible]	[illegible]	[illegible]	
[illegible]	592.000	0.000	581.800	100.000	581.600	200.000	581.500	300.000	[illegible]	[illegible]	
[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	
GR	566.900	610.000	566.900	612.300	566.900	612.300	565.900	[illegible]	[illegible]		
GR	565.100	620.000	565.100	622.300	565.100	622.300	566.300	[illegible]	[illegible]		
GR	566.200	630.000	566.200	632.300	566.200	632.300	566.700	[illegible]	[illegible]		
GR	566.100	645.000	566.400	651.000	566.400	650.300	566.400	[illegible]	[illegible]		
GR	566.600	655.000	567.500	660.000	567.500	650.000	567.500	[illegible]	[illegible]		
GR	567.500	665.000	569.900	670.000	569.900	670.000	569.900	[illegible]	[illegible]		
GR	573.400	680.000	573.400	681.000	580.800	681.000	580.800	700.000	580.700	[illegible]	
GR	580.600	900.000	580.600	1000.000	580.500	1100.000	-0.000	-0.000	-0.000	-0.000	
X1	954.000	48.000	600.000	681.000	1.000	1.000	1.000	-0.000	-0.000	-0.000	
BT	14.000	600.000	581.000	577.700	610.000	581.000	577.700	612.300	581.000	[illegible]	
BT	620.000	581.000	577.700	622.300	581.000	577.700	630.000	580.500	577.700	[illegible]	
BT	580.900	577.700	650.000	580.900	577.600	652.300	580.900	577.600	660.000	[illegible]	
BT	577.600	662.300	580.800	577.600	670.000	580.800	577.600	672.300	580.800	[illegible]	
BT	681.000	580.800	577.600	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	
GR	582.000	0.000	581.800	100.000	581.600	200.000	581.500	300.000	581.400	[illegible]	
GR	581.200	500.000	581.000	600.000	571.000	600.000	568.100	605.000	566.500	[illegible]	
GR	577.700	610.000	577.700	612.300	566.900	612.300	565.900	615.000	565.100	620.000	
GR	577.700	620.000	577.700	622.300	565.100	622.300	566.300	625.000	566.200	630.000	
GR	577.700	630.000	577.700	632.300	566.200	632.300	566.700	635.000	566.400	640.000	
GR	566.100	645.000	566.400	650.000	577.600	650.000	577.600	652.300	566.400	652.300	
GR	566.600	655.000	567.500	660.000	577.600	660.000	577.600	662.300	567.500	662.300	
GR	567.500	665.000	569.900	670.000	577.600	670.000	577.600	672.300	569.900	672.300	
GR	573.400	680.000	573.400	681.000	580.800	681.000	580.800	700.000	580.700	800.000	
GR	580.600	900.000	580.600	1000.000	580.500	1100.000	-0.000	-0.000	-0.000	-0.000	
X1	985.000	-0.000	600.000	681.000	30.500	30.500	30.500	-0.000	-0.000	-0.000	
X2	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	1.000	-0.000	-0.000	-0.000	
X1	996.000	48.000	600.000	681.000	1.000	1.000	1.000	-0.000	-0.000	-0.000	
GR	582.000	0.000	581.600	100.000	581.600	200.000	581.500	300.000	581.400	400.000	
GR	581.200	500.000	581.000	600.000	571.000	600.000	568.100	605.000	566.900	610.000	
GR	566.900	610.000	566.900	612.300	565.900	612.300	565.900	615.000	565.100	620.000	
GR	565.100	620.000	565.100	622.300	565.100	622.300	566.300	625.000	566.200	630.000	
GR	566.200	630.000	566.200	632.300	566.200	632.300	566.700	635.000	566.400	640.000	
GR	566.100	645.000	566.400	650.000	566.400	650.000	566.400	652.300	566.400	652.300	
GR	566.600	655.000	567.500	660.000	567.500	660.000	567.500	662.300	567.500	662.300	
GR	567.500	665.000	569.900	670.000	569.900	670.000	569.900	672.300	569.900	672.300	
GR	573.400	680.000	573.400	681.000	580.800	681.000	580.800	700.000	580.700	800.000	
GR	580.600	900.000	580.600	1000.000	580.500	1100.000	-0.000	-0.000	-0.000	-0.000	
NC	.040	.035	.030	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	
X1	1036.000	37.000	565.000	700.000	50.000	50.000	50.000	-0.000	-0.000	-0.000	
X3	10.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	
GR	581.900	0.000	581.200	100.000	581.200	200.000	580.900	300.000	581.000	400.000	
GR	579.900	500.000	581.100	565.000	575.400	547.000	574.900	590.000	573.900	595.000	
GR	572.500	600.000	571.000	605.000	569.800	610.000	568.800	615.000	568.000	620.000	
GR	567.400	625.000	566.600	630.000	566.300	635.000	566.200	640.000	566.300	650.000	
GR	566.800	660.000	568.300	670.000	570.200	675.000	570.400	680.000	571.700	685.000	
GR	573.100	690.000	574.800	695.000	574.900	695.000	577.700	700.000	577.500	800.000	
GR	576.600	900.000	576.600	1000.000	577.000	1040.000	576.900	1100.000	577.500	1200.000	
GR	578.300	1300.000	579.200	1345.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	
NC	.060	.035	.030	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	
X1	1716.000	40.000	374.000	492.500	700.000	700.000	700.000	-0.000	-0.000	-0.000	
X3	10.000	-0.000	-0.000	374.000	-0.000	492.500	-0.000	-0.000	-0.000	-0.000	
GR	580.400	0.000	580.400	167.000	579.500	283.700	575.300	335.300	579.100	374.000	
GR	577.200	377.900	576.100	381.900	575.100	385.800	574.100	389.800	573.200	393.700	
GR	572.400	397.700	571.500	401.600	570.300	405.600	569.400	409.500	568.400	413.500	
GR	567.600	417.400	566.900	421.400	566.500	425.300	566.000	429.200	565.700	433.200	
GR	565.500	437.200	565.400	441.100	565.500	445.000	565.500	449.000	565.900	453.000	
GR	566.500	456.900	567.200	460.800	568.000	464.800	569.000	468.700	569.800	472.700	
GR	570.600	476.600	571.700	480.600	573.400	484.500	575.100	488.500	577.500	492.500	

Exh 6-17

	X3	-0.000	-0.000	-0.000	193.000	-0.000	285.000	-0.000	-0.000			
	GR	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]
	GR	573.500	190.000	572.200	195.000	571.100	200.000	570.200	205.000			
	GR	567.700	215.000	566.400	220.000	565.600	225.000	565.300	230.000			
	GR	564.600	240.000	564.900	245.000	565.200	250.000	566.400	255.000			
	GR	568.800	265.000	569.900	270.000	571.500	275.000	574.700	280.000			
	GR	577.400	285.000	577.300	385.000	578.200	485.000	577.700	557.000			
	GR	579.800	605.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000			
	NC	.035	.035	.033	.300	.500	-0.000	-0.000	-0.000	-0.000	-0.000	
	OT	4.000	1500.000	1950.000	2100.000	2495.000	-0.000	-0.000	-0.000	-0.000	-0.000	
			578.47	579.26								
	X1	A 2736.000	20.000	300.000	400.000	300.000	300.000	300.000	-0.000	-0.000	-0.000	
	X3	-0.000	-0.000	-0.000	300.000	-0.000	400.000	-0.000	-0.000	-0.000	-0.000	
	GR	578.400	0.000	577.700	100.000	578.500	200.000	578.600	300.000	575.100	310.000	
	GR	573.400	315.000	572.200	320.000	570.600	325.000	570.000	330.000	569.900	335.000	
	GR	569.700	340.000	569.100	350.000	569.100	360.000	569.700	370.000	570.400	375.000	
	GR	571.700	380.000	572.900	385.000	574.400	390.000	575.100	392.000	578.600	400.000	
	GR	581.000	500.000	581.300	500.000	581.400	700.000	581.300	800.000	582.100	930.000	
	GR	583.200	1100.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	
	X1	3436.000	-0.000	-0.000	-0.000	700.000	700.000	700.000	-0.000	380	-0.000	
	X3	10.000	-0.000	-0.000	300.000	-0.000	400.000	-0.000	-0.000	-0.000	-0.000	
				578.95	579.73							
	X1	B 3836.000	27.000	200.000	300.000	400.000	400.000	400.000	-0.000	-0.000	-0.000	
	X3	-0.000	-0.000	-0.000	200.000	-0.000	300.000	-0.000	-0.000	-0.000	-0.000	
	GR	580.700	0.000	579.200	100.000	578.500	200.000	575.000	207.000	574.000	210.000	
	GR	573.000	215.000	572.600	220.000	571.900	225.000	571.000	230.000	570.400	235.000	
	GR	570.000	240.000	569.700	245.000	570.000	250.000	570.700	255.000	572.100	260.000	
	GR	573.400	265.000	573.700	270.000	575.000	275.000	575.400	278.000	579.800	290.000	
	GR	580.300	300.000	580.400	400.000	581.000	500.000	581.500	600.000	582.200	700.000	
	GR	581.800	800.000	581.900	884.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	
	X1	4311.000	-0.000	-0.000	-0.000	475.000	475.000	475.000	-0.000	.200	-0.000	
	X3	-0.000	-0.000	-0.000	200.000	-0.000	300.000	-0.000	-0.000	-0.000	-0.000	
				579.69	580.17							
	X1	C 4786.000	29.000	393.000	500.000	475.000	475.000	475.000	-0.000	-0.000	-0.000	
	X3	10.000	-0.000	-0.000	394.000	-0.000	500.000	-0.000	-0.000	-0.000	-0.000	
	GR	582.100	0.000	581.200	100.000	580.000	200.000	581.100	212.000	580.300	300.000	
	GR	580.100	393.000	579.600	400.000	578.800	408.000	578.100	410.000	578.500	415.000	
	GR	573.200	420.000	572.700	425.000	571.800	430.000	570.800	435.000	570.500	440.000	
	GR	570.400	445.000	570.200	450.000	570.100	455.000	570.400	460.000	570.600	465.000	
	GR	571.400	470.000	572.600	475.000	573.700	480.000	574.400	483.000	579.200	489.000	
	GR	579.500	500.000	579.700	600.000	579.600	653.000	581.200	700.000	-0.000	-0.000	
	X1	4825.000	37.000	500.000	593.000	19.000	38.000	38.000	-0.000	-0.000	-0.000	
	X3	-0.000	-0.000	-0.000	500.000	585.000	594.000	585.000	-0.000	-0.000	-0.000	
	GR	581.900	0.000	582.000	20.000	581.800	100.000	581.300	200.000	581.100	300.000	
	GR	580.500	400.000	579.400	500.000	576.800	500.000	576.300	505.000	575.300	510.000	
	GR	574.800	515.000	573.600	520.000	572.400	525.000	572.000	530.000	571.600	535.000	
	GR	571.600	540.000	571.200	545.000	570.800	550.000	571.200	555.000	571.200	560.000	
	GR	571.100	565.000	571.200	570.000	571.700	575.000	572.300	580.000	573.200	585.000	
	GR	574.000	590.000	574.300	595.000	574.300	598.000	579.600	598.000	579.700	600.000	
	GR	579.600	700.000	579.700	751.000	579.600	800.000	580.100	900.000	580.400	1000.000	
	GR	580.900	1100.000	581.200	1200.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	
	SB	-0.000	1.300	2.500	-0.000	51.700	-0.000	338.000	3.170	370.800	570.800	
				579.83	580.50							
	X1	D 4866.000	-0.000	-0.000	-0.000	21.000	21.000	21.000	-0.000	-0.000	-0.000	
	X2	-0.000	-0.000	1.000	578.300	579.400	-0.000	-0.000	-0.000	-0.000	-0.000	
	X3	-0.000	-0.000	-0.000	500.000	585.000	594.000	585.000	-0.000	-0.000	-0.000	
	BT	16.000	0.000	581.900	0.000	20.000	582.000	0.000	100.000	581.800	0.000	
	BT	200.000	581.300	0.000	300.000	581.100	0.000	400.000	580.500	0.000	500.000	
	BT	579.400	579.200	598.000	579.600	578.300	600.000	579.700	0.000	700.000	579.600	
	BT	0.000	751.000	579.700	0.000	800.000	579.600	0.000	900.000	580.100	0.000	
	BT	1000.000	580.400	0.000	1100.000	580.900	0.000	1200.000	581.200	0.000	-0.000	
	X1	4947.000	-0.000	-0.000	-0.000	1.000	1.000	1.000	-0.000	-0.000	-0.000	
	X3	-0.000	-0.000	-0.000	500.000	585.000	598.000	585.000	-0.000	-0.000	-0.000	

Exhibit 7
6 of 41

[redacted]	X1	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]
	X3	-0.000	-0.000	-0.000	500.000	585.000	598.000	585.000	-0.000	-0.000	
	X1	5436.000	34.000	494.000	594.000	589.000	539.000	589.000	-0.000	-0.000	
	X3	10.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	
	GR	579.740	0.000	578.940	94.000	579.740	194.000	580.140	212.000	580.200	250.000
	GR	581.940	394.000	580.840	494.000	574.740	506.000	574.240	508.000	573.900	600.000
	GR	573.240	514.000	572.840	519.000	571.840	524.000	571.140	529.000	570.500	544.000
	GR	570.640	539.000	570.840	544.000	571.840	549.000	572.940	554.000	573.100	559.000
	GR	573.440	564.000	573.740	569.000	574.240	574.000	574.740	576.000	581.100	594.000
	GR	580.740	658.000	580.840	694.000	581.340	794.000	581.940	894.000	582.340	994.000
	GR	582.940	1094.000	583.240	1194.000	582.940	1294.000	582.640	1349.000	-0.000	-0.000
E	X1	5936.000	34.000	580.435 494.000	581.05 594.000	500.000	500.000	500.000	-0.000	-0.000	-0.000
	X3	10.000	-0.000	-0.000	400.000	-0.000	600.000	-0.000	-0.000	-0.000	-0.000
	GR	579.600	0.000	578.800	94.000	579.600	194.000	580.000	212.000	580.200	250.000
	GR	581.800	394.000	580.700	494.000	574.600	506.000	574.200	508.000	573.900	600.000
	GR	573.100	514.000	572.700	519.000	571.700	524.000	571.000	529.000	570.500	544.000
	GR	570.500	539.000	570.700	544.000	571.700	549.000	572.800	554.000	573.100	559.000
	GR	573.300	564.000	573.600	569.000	574.100	574.000	574.600	576.000	581.000	594.000
	GR	580.600	658.000	580.700	694.000	581.200	794.000	581.800	894.000	582.300	994.000
	GR	582.800	1094.000	583.100	1194.000	582.800	1294.000	582.500	1349.000	-0.000	-0.000
	X1	6416.000	28.000	560.000	650.000	480.000	480.000	480.000	-0.000	-0.000	-0.000
	X3	10.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000
	GR	581.430	0.000	581.930	50.000	581.530	160.000	581.330	260.000	581.630	360.000
	GR	581.930	460.000	581.930	550.000	581.130	577.000	574.830	592.000	573.230	593.000
	GR	572.230	595.000	570.930	600.000	570.330	605.000	570.830	610.000	571.030	615.000
	GR	572.430	620.000	572.930	625.000	573.130	630.000	573.430	635.000	574.130	640.000
	GR	574.230	642.000	574.830	644.000	581.930	660.000	581.230	716.000	582.230	760.000
	GR	581.930	860.000	582.830	950.000	581.730	1010.000	-0.000	-0.000	-0.000	-0.000
F	X1	6786.000	28.000	580.88 560.000	581.64 650.000	470.000	470.000	470.000	-0.000	-0.000	-0.000
	X3	10.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000
	GR	581.300	0.000	581.800	50.000	581.400	150.000	581.200	260.000	581.500	360.000
	GR	581.800	460.000	581.800	550.000	581.000	577.000	574.700	592.000	573.100	593.000
	GR	572.100	595.000	570.800	600.000	570.200	605.000	570.700	610.000	571.700	615.000
	GR	572.300	620.000	572.400	625.000	573.000	630.000	573.300	635.000	574.000	640.000
	GR	574.100	642.000	574.700	644.000	581.400	650.000	581.100	716.000	582.100	760.000
	GR	581.800	860.000	581.900	950.000	581.500	1010.000	-0.100	-0.000	-0.000	-0.000
	X1	6835.000	-0.000	-0.000	-0.000	49.000	49.000	49.000	-0.000	1.370	-0.000
	NC	-0.000	-0.000	.023	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000
	X1	6836.000	40.000	900.000	73.000	1.000	1.000	1.000	-0.000	-0.000	-0.000
	X3	10.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000
	GR	582.000	0.000	582.900	100.000	582.800	200.000	582.000	300.000	581.700	400.000
	GR	581.300	500.000	580.700	600.000	580.900	700.000	581.400	800.000	582.000	900.000
	GR	574.400	900.000	574.000	905.000	573.200	910.000	572.200	915.000	572.600	920.000
	GR	571.600	925.000	572.100	930.000	573.500	935.000	578.200	935.000	578.200	938.000
	GR	573.600	939.000	573.800	940.000	573.400	945.000	572.200	950.000	572.000	955.000
	GR	572.700	960.000	573.600	965.000	574.500	970.000	574.700	973.000	582.000	973.000
	GR	582.000	976.000	581.600	1000.000	581.200	1100.000	581.000	1200.000	580.900	1300.000
	GR	581.500	1400.000	582.000	1500.000	582.600	1400.000	582.800	1700.000	583.000	1807.000
	SB	.900	1.500	2.900	-0.000	73.000	2.500	385.100	-0.000	571.600	571.600
G	X1	6916.000	-0.000	581.57 -0.000	582.60 -0.000	80.000	80.000	80.000	-0.000	-0.000	-0.000
	X2	-0.000	-0.000	1.000	578.300	583.000	-0.000	-0.000	-0.000	-0.000	-0.000
	X3	10.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	583.000	583.000	-0.000
	BT	23.000	0.000	582.000	0.000	100.000	582.900	0.000	200.000	582.800	0.000
	BT	300.000	582.000	0.000	400.000	581.700	0.000	500.000	581.300	0.000	600.000
	BT	580.700	0.000	700.000	580.900	0.000	800.000	581.400	0.000	900.000	582.000
	BT	578.300	935.000	582.000	578.200	938.000	582.000	578.200	973.000	582.000	578.200
	BT	976.000	582.000	0.000	1000.000	581.600	0.000	1100.000	581.200	0.000	1200.000

Exh. 6 of 7
7 of 41

[redacted]	X1	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]
	X3	10.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000			
	GR	581.300	0.000	581.800	50.000	581.400	1[illegible]0.000	[illegible]	[illegible]			
	GR	581.800	460.000	581.800	560.000	581.000	577.000	[illegible]	[illegible]			
	GR	572.100	595.000	570.800	600.000	570.200	605.000	570.700	610.000	571.[illegible]		
	GR	572.300	620.000	572.800	625.000	573.000	630.000	573.300	635.000	574.000		
	GR	574.100	642.000	574.700	644.000	581.800	660.000	581.100	716.000	582.100		
	GR	581.800	860.000	581.900	960.000	581.600	1010.000	-0.000	-0.000	-0.000		
	X1	7436.000	-0.000	-0.000	-0.000	519.000	519.000	519.000	-0.000	[illegible]		
	X3	10.000	-0.000	-0.000	560.000	-0.000	660.000	-0.000	-0.000	-0.000		
	X1 H	7936.000	22.000	436.000	516.000	500.000	500.000	500.000	-0.000	-0.000	-0.000	
	X3	10.000	-0.000	-0.000	436.000	-0.000	516.000	-0.000	-0.000	-0.000	-0.000	
	GR	581.800	0.000	581.700	116.000	581.100	216.000	580.900	316.000	582.500	[illegible]	
	GR	582.600	436.000	574.900	453.000	573.800	456.000	572.400	461.000	571.[illegible]	[illegible]	
	GR	571.200	471.000	570.800	475.000	571.000	481.000	571.500	486.000	572.300	491.000	
	GR	573.700	494.000	574.900	495.000	583.100	516.000	582.800	616.000	582.200	716.000	
	GR	582.200	866.000	581.700	891.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	
	X1	8536.000	40.000	305.500	483.000	600.000	600.000	600.000	-0.000	-0.000	-0.000	
	X3	10.000	-0.000	-0.000	150.000	-0.000	400.000	-0.000	-0.000	-0.000	-0.000	
	GR	583.000	0.000	582.400	100.000	581.600	221.200	581.800	280.000	581.200	305.400	
	GR	580.300	308.000	579.000	310.600	577.600	313.200	576.600	315.800	575.900	318.400	
	GR	575.200	320.900	574.600	323.500	573.900	326.100	573.300	328.700	572.900	331.300	
	GR	572.100	333.900	571.400	336.400	571.100	339.000	570.900	341.600	570.900	344.200	
	GR	571.100	346.800	571.300	349.400	571.500	351.900	572.200	354.500	572.800	357.100	
	GR	573.300	359.700	574.300	362.300	575.100	364.900	575.700	367.400	576.400	370.000	
	GR	577.200	372.600	578.400	375.200	579.600	377.800	580.800	380.400	582.100	383.000	
	GR	582.000	400.000	581.000	430.000	581.000	598.000	581.900	705.000	582.400	813.000	
	X1 I	9136.000	24.000	175.000	250.000	500.000	500.100	500.000	-0.000	-0.000	-0.000	
	X3	-0.000	-0.000	-0.000	140.100	-0.000	510.000	-0.000	-0.000	-0.000	-0.000	
	GR	584.300	0.000	583.800	40.000	582.200	140.000	580.900	175.000	575.500	184.000	
	GR	574.900	194.000	574.500	135.000	573.600	200.000	571.300	205.000	570.900	210.000	
	GR	571.300	215.000	572.000	220.000	573.600	225.000	574.300	30.000	574.700	235.000	
	GR	574.900	237.000	575.500	240.000	581.100	250.000	581.200	350.000	581.000	376.000	
	GR	590.900	450.000	591.300	550.000	581.700	650.000	583.200	735.000	-0.000	-0.000	
	X1	9586.000	24.000	175.000	250.000	450.000	450.000	450.000	-0.000	.035	-0.000	
	X3	-0.000	-0.000	-0.000	50.000	-0.000	250.000	-0.000	-0.000	-0.000	-0.000	
	GR	584.300	0.000	583.800	40.000	582.200	140.000	580.800	175.000	575.500	184.000	
	GR	574.900	194.000	574.500	135.000	573.600	200.000	571.300	205.000	570.900	210.000	
	GR	571.300	215.000	572.000	220.000	573.600	225.000	574.300	230.000	574.700	235.000	
	GR	574.900	237.000	575.500	240.000	581.100	250.000	581.200	350.000	581.000	376.000	
	GR	590.900	450.000	591.300	550.000	581.700	650.000	583.200	735.000	-0.000	-0.000	
	X1	9596.000	20.000	345.000	445.000	10.000	10.000	10.000	-0.000	.030	-0.000	
	X3	-0.000	-0.000	-0.000	245.000	-0.000	445.000	-0.000	-0.000	-0.000	-0.000	
	GR	583.950	0.000	581.850	45.000	580.950	145.000	580.850	245.000	581.850	345.000	
	GR	579.950	385.000	575.750	399.000	574.950	407.000	574.250	410.000	573.050	415.000	
	GR	572.750	420.000	572.950	425.000	571.650	430.000	570.950	435.000	573.050	440.000	
	GR	574.650	445.000	583.450	445.000	580.250	440.000	581.250	545.000	582.450	645.000	
	X1 J	10286.000	20.000	345.000	445.000	650.000	650.000	650.000	-0.000	-0.000	-0.000	
	X3	-0.000	-0.000	-0.000	245.000	-0.000	445.000	-0.000	-0.000	-0.000	-0.000	
	GR	584.000	0.000	581.400	45.000	581.000	145.000	580.900	245.000	581.900	345.000	
	GR	580.000	385.000	575.800	399.000	575.000	407.000	574.300	410.000	573.100	415.000	
	GR	572.800	420.000	573.000	425.000	571.700	430.000	571.000	435.000	571.500	440.000	
	GR	574.700	445.000	583.500	445.000	580.300	440.000	581.300	545.000	582.500	645.000	
	X1 K	10336.000	22.000	400.000	445.000	50.000	50.000	50.000	-0.000	-0.000	-0.000	
	X3	-0.000	-0.000	-0.000	350.000	-0.000	445.000	-0.000	-0.000	-0.000	-0.000	
	GR	583.100	0.000	581.300	100.000	580.900	200.000	580.200	300.000	579.800	400.000	
	GR	573.000	401.000	573.000	405.000	573.000	410.000	573.000	415.000	573.000	420.000	
	GR	572.500	430.000	572.600	435.000	574.700	440.000	574.800	444.000	590.000	[illegible]	
	GR	580.500	500.000	581.300	600.000	582.300	700.000	582.700	800.000	583.000	900.000	

582.28 582.1

582.86 583.74

583.36 584.26

583.34 584.23

Exhibit 1
8 of 41

			0.000	591.300	100.000	590.900	200.000	580.200	300.000	[redacted]	[redacted]
	GR	573.000	401.000	573.000	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]
	GR	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]
	GR	580.500	500.000	581.300	600.000	582.300	700.000	582.700	00.000		
	GR	583.000	908.000	584.200	960.000	-0.000	-0.000	-0.000	-0.000		

s+r+ SEC 583.53 584.43

	X1	10636.000	27.000	655.000	855.000	300.000	300.000	300.000	-0.000		
	X3	10.000	-0.000	-0.000	655.000	-0.000	800.000	-0.000	-0.000		
	GR	582.670	0.000	582.670	55.000	584.370	155.000	585.670	255.000		
	GR	586.270	455.000	585.470	555.000	584.570	655.000	583.370	677.000		
	GR	573.770	700.000	573.070	705.000	572.470	710.000	572.470	715.000		
	GR	574.570	725.000	575.070	727.000	575.970	738.000	582.670	755.000		
	GR	583.270	955.000	583.670	1055.000	583.970	1068.000	583.570	1155.000		
	GR	583.070	1355.000	583.070	1455.000	-0.000	-0.000	-0.000	-0.000		

670
710
715
830
860

	X1	11536.000	27.000	655.000	855.000	900.000	900.000	900.000	-0.000	-0.000	-0.000
	X3	10.000	-0.000	-0.000	655.000	-0.000	855.000	-0.000	-0.000	-0.000	-0.000
	GR	582.600	0.000	582.600	55.000	584.300	155.000	585.600	255.000	586.000	355.000
	GR	586.200	455.000	585.400	555.000	584.500	655.000	583.300	677.000	574.800	747.000
	GR	573.700	700.000	573.000	705.000	572.400	710.000	572.400	715.000	573.600	720.400
	GR	574.500	725.000	575.000	727.000	575.900	738.000	582.600	755.000	583.800	855.000
	GR	583.200	955.000	583.600	1055.000	583.900	1068.000	583.500	1155.000	583.300	1255.000
	GR	583.000	1355.000	583.000	1455.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000
	EJ	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000

710
715

Exhibit 7
9 of 29

CCHV= .300 CEHV= .500

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	QLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST
1.00	11.50	574.90	0.00	574.90	575.22	.32	0.00	0.00	584.60
3165.	0.	3165.	0.	0.	701.	0.	0.	0.	584.60
0.00	0.00	4.51	0.00	.035	.030	.035	0.000	563.40	529.17
.000601	-0.	-0.	-0.	0	0	1	0.00	89.83	619.00
30.00	11.52	574.92	0.00	0.00	575.23	.31	.02	.00	584.60
3165.	0.	3165.	0.	0.	703.	0.	0.	0.	584.60
.00	0.00	4.50	0.00	.035	.030	.035	.029	563.40	529.02
.000598	29.	29.	29.	0	0	1	0.00	89.98	619.00
60.00	11.54	574.94	0.00	0.00	575.25	.31	.02	.00	584.60
3165.	0.	3165.	0.	0.	705.	0.	1.	0.	584.60
.00	0.00	4.49	0.00	.035	.030	.035	.029	563.40	528.87
.000595	30.	30.	30.	0	0	1	0.00	90.13	619.00

3265 DIVIDED FLOW

NORMAL BRIDGE,NRD= 9 MIN ELTRD= 584.30 MAX ELLC= 5[illegible].40

D/S FACE OF JEFFERSON STREET BRIDGE

61.00	11.51	574.91	0.00	0.00	575.25	.38	.09	.03	584.60
3165.	0.	3165.	0.	0.	744.	1.	1.	0.	584.60
.00	0.00	4.92	0.00	.035	.040	.035	.029	563.40	529.09
.001042	1.	1.	1.	2	0	1	0.00	42.91	619.00

3265 DIVIDED FLOW

NORMAL BRIDGE,NRD= 9 MIN ELTRD= 584.30 MAX ELLC= 580.40

U/S FACE OF JEFFERSON STREET BRIDGE SEC. A

CONCRETE TWO SPAN BRIDGE

CONCRETE RAILING, TWO PIERS, 75 FEET WIDE

136.00	11.60	575.00	0.00	0.00	575.37	.37	.08	.00	584.60
3165.	0.	3165.	0.	0.	851.	0.	2.	0.	584.60
.01	0.00	4.86	0.00	.035	.030	.035	.029	563.40	528.33
.001054	75.	75.	75.	2	0	1	0.00	83.67	619.00

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	QLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

Exhibit 7
10 of 41

Q	QLOB	QCH	QROB	ALOB	ACH	AHOB	VOL	OLOSS	BANK ELEV LEFT/RIGHT
TI			OB	NL	XNC	XN		TWA	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IOC	ICONT	CORAR	TOPWID	SMDST
137.00	11.69	575.09	0.00	0.00	575.39	.30	.00	.02	584.40
3165.	0.	3165.	0.	0.	718.	0.	2.	0.	574.60
.01	0.00	4.41	0.00	.035	.030	.035	.029	563.40	527.62
.000569	1.	1.	1.	2	0	1	0.00	91.38	610.00

50 FEET U/S OF JEFFERSON STREET BRIDGE SEC. 8

187.00	10.99	575.09	0.00	0.00	575.44	.34	.03	.02	583.10
3165.	0.	3165.	0.	0.	672.	0.	3.	0.	580.20
.01	0.00	4.71	0.00	.035	.030	.042	.029	564.10	343.54
.000652	50.	50.	50.	2	0	1	0.00	88.95	432.49

1490 NH CARD USED

EFFECTED SECTION OF 747

DOCKS ON RIGHT BANK

362.00	11.41	575.39	0.00	0.00	575.56	.17	.01	.05	578.57
3165.	0.	3165.	0.	0.	911.	1.	6.	1.	577.17
.03	0.00	4.47	0.00	.035	.031	.042	.029	564.97	252.63
.000321	175.	175.	175.	2	0	1	0.00	143.47	396.10

3470 ENCROACHMENT STATIONS= 244.0 373.0 TYPE= 1 IA OPT= 139.000

50 FEET D/S OF RAILROAD BRIDGE NO. 1 SEC. 7

ENCROACHED FOR EXPANSION

737.00	11.79	575.45	0.00	0.00	575.74	.29	.11	.01	574.30
3165.	0.	3165.	0.	0.	912.	0.	14.	2.	100000.00
.06	0.00	3.47	0.00	.035	.030	.042	.030	563.70	251.60
.000282	375.	375.	375.	2	0	1	0.00	121.40	373.00
787.00	11.57	575.47	0.00	0.00	575.74	.26	.02	.04	581.00
3165.	0.	3165.	0.	0.	769.	0.	15.	2.	581.00
.06	0.00	4.12	0.00	.035	.032	.042	.030	563.90	795.00
.000624	50.	50.	50.	2	0	1	0.00	106.60	901.60

3265 DIVIDED FLOW

NORMAL BRIDGE,NRD= 4 MIN ELTRD= 581.00 MAX ELLC= 577.29

D/S FACE OF RAILROAD BRIDGE NO. 1

788.00	11.54	575.44	0.00	0.00	575.77	.33	.00	.03	581.00
3165.	0.	3165.	0.	0.	691.	0.	1.	2.	581.00
.06	0.00	4.58	0.00	.035	.032	.042	.030	563.90	795.00
.002401	1.	1.	1.	2	0	1	0.00	97.00	901.60

3265 DIVIDED FLOW

NORMAL BRIDGE,NRD= 4 MIN ELTRD= 581.00 MAX ELLC= 577.20

U/S FACE OF RAILROAD BRIDGE NO. 1 SEC. D

STEEL I-BEAM BRIDGE WITH 2-STEEL BENT PIERS

9 FEET WIDE, 7 OLD BENT PILES-CUTOFF

797.00	11.56	575.46	0.00	0.00	575.79	.32	.02	.00	581.00
3165.	0.	3165.	0.	0.	692.	0.	15.	2.	581.00
.06	0.00	4.57	0.00	.035	.032	.042	.030	563.90	795.00
.002389	9.	9.	9.	0	0	1	0.00	97.00	901.60

SECNO	DEPTH	CUSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNP	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IOC	ICONT	CORAR	TOPWID	ENDST
798.00	11.65	575.55	0.00	0.00	575.81	.26	.00	.02	581.00
3165.	0.	3165.	0.	0.	777.	0.	15.	2.	581.00
.06	0.00	4.07	0.00	.035	.032	.042	.030	563.90	795.00
.000602	1.	1.	1.	2	0	1	0.00	106.60	901.60
844.00	10.58	575.58	0.00	0.00	575.84	.26	.03	.00	581.50
3165.	0.	3165.	0.	0.	780.	0.	16.	2.	581.40
.06	0.00	4.06	0.00	.035	.032	.042	.030	565.00	816.36
.000559	46.	46.	46.	2	0	1	0.00	105.39	921.75

3265 DIVIDED FLOW

NORMAL BRIDGE,NRD=16 MIN ELTRD= 581.40 MAX ELLC= 578.40

D/S FACE OF RAILROAD BRIDGE NO. 2

845.00	10.56	575.56	0.00	0.00	575.86	.30	.00	.02	581.50
3165.	0.	3165.	0.	0.	719.	0.	16.	2.	581.40
.06	0.00	4.40	0.00	.035	.032	.042	.030	565.00	816.42
.001856	1.	1.	1.	2	0	1	0.00	98.26	921.67

3265 DIVIDED FLOW

NORMAL BRIDGE,NRD=16 MIN ELTRD= 581.40 MAX ELLC= 578.40

U/S FACE OF RAILROAD BRIDGE NO. 2 SEC. F

WOOD BRIDGE WITH BALLAST AND TIE DECK

14.5 FEET WIDE, 7 BENT PIERS OF WOOD

Exhibit 1
12 of 91

[redacted]S F[redacted]IDE[redacted]ENT[redacted]RS [redacted]OD [redacted]

14.5 FEET WIDE, 7 BENT PIERS OF WOOD

859.00	10.59	575.59	0.00	0.00	575.89	.30	.03	.00	581.50
3165.	0.	3165.	0.	0.	721.	0.	16.	2.	581.40
.06	0.00	4.39	0.00	.035	.032	.042	.030	565.00	816.36
.001842	15.	15.	15.	1	0	1	0.00	98.40	921.76
860.00	10.65	575.65	0.00	0.00	575.90	.25	.00	.01	581.50
3165.	0.	3165.	0.	0.	788.	0.	16.	2.	581.40
.06	0.00	4.02	0.00	.035	.032	.042	.030	565.00	816.17
.000544	1.	1.	1.	2	0	1	0.00	105.84	922.01
910.00	11.70	575.70	0.00	0.00	575.94	.23	.03	.01	583.10
3165.	0.	3165.	0.	0.	817.	0.	17.	2.	583.00
.07	0.00	3.88	0.00	.035	.032	.042	.030	564.00	835.00
.000501	50.	50.	50.	1	0	1	0.00	107.00	942.00

3265 DIVIDED FLOW

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	FW	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WIN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDSTA

NORMAL BRIDGE,NRD= 6 MIN ELTRD= 583.00 MA ELLC= 578.60

D/S FACE OF RAILROAD BRIDGE NO. 4

D/S FACE OF RAILROAD BRIDGE NO. 3

911.00	11.68	575.68	0.00	0.00	575.96	.29	.00	.03	583.10
3165.	0.	3165.	0.	0.	735.	0.	17.	2.	583.00
.07	0.00	4.31	0.00	.035	.032	.042	.030	564.00	835.00
.002246	1.	1.	1.	2	3	1	0.00	105.60	942.00

3265 DIVIDED FLOW

NORMAL BRIDGE,NRD= 6 MIN ELTRD= 583.00 MAX ELLC= 578.60

U/S FACE OF RAILROAD BRIDGE NO. 4 SEC. F

STEEL I-BEAM BRIDGE WITH 2 STEEL PIERS

10 FEET WIDE, 8 SETS OF OLD PIER BENTS-CUTOFF

921.00	11.70	575.70	0.00	0.00	575.90	.29	.02	.00	583.10

3470 ENCROACHMENT STATIONS= 200.0 300.0 TYPE= 1 TARGET= 100.000

919 FEET D/S OF MILL STREET BRIDGE SEC. B

3836.00	7.91	577.61	0.00	0.00	577.82	.21	.23	.04	578.50
1500.	0.	1500.	0.	0.	409.	0.	62.	9.	100000.00
.30	0.00	3.66	0.00	.035	.033	.035	.031	569.70	201.79
.000805	400.	400.	400.	2	0	1	0.00	82.23	284.02

SECNO	DEPTH	OWSEL	CRIWS	WSELK	EG	HV	HL	QLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	APOB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

3470 ENCROACHMENT STATIONS= 200.0 290.0 TYPE= 1 TARGET= 90.000

4311.00	8.09	577.99	0.00	0.00	578.18	.19	.36	.00	578.70
1500.	0.	1500.	0.	0.	424.	0.	66.	10.	100000.00
.34	0.00	3.53	0.00	.035	.033	.035	.031	569.90	201.42
.000724	475.	475.	475.	2	0	1	0.00	83.09	284.51

3470 ENCROACHMENT STATIONS= 393.0 500.0 TYPE= 1 TARGET= 107.000

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 580.10 ELREA= 100000.00

39 FEET D/S OF MILL STREET BRIDGE SEC. C

4786.00	8.22	578.32	0.00	0.00	578.46	.13	.25	.02	580.10
1500.	0.	1500.	0.	0.	515.	0.	71.	11.	100000.00
.38	0.00	2.91	0.00	.035	.033	.035	.031	570.10	400.58
.000411	475.	475.	475.	2	0	1	0.00	87.32	487.90

3470 ENCROACHMENT STATIONS= 500.0 598.0 TYPE= 1 TARGET= 98.000
ELENCL= 585.00 ELENCR= 585.00

D/S FACE OF MILL STREET BRIDGE

4825.00	7.56	578.36	0.00	0.00	578.48	.12	.02	.00	579.40
1500.	0.	1500.	0.	0.	548.	0.	72.	11.	585.00
.39	0.00	2.74	0.00	.035	.033	.035	.031	570.80	500.00
.000405	39.	39.	39.	1	0	1	0.00	95.00	548.00

SPECIAL BRIDGE

SB	XK	XKOR	COFQ	RDLEN	BWC	BWP	BAREA	SS	ELCHU	ELCHD
	0.00	1.30	2.50	0.00	51.70	0.00	538.00	3.17	570.80	570.80

PRESSURE FLOW

EGPRS	EGLWC	H3	QWEIR	QPR	BAREA	ELLC	ELTRD	CLASS
578.52	578.48	0.00	0.	1500.	538.	578.30	579.40	10.00

TIONS= 500.0 598.0 TYPE= 1 TARGET= 98.000

578.52 578.48 0.00 0. 1500. 538. 578.30 579.40 10.00

3470 ENCROACHMENT STATIONS= 500.0 598.0 TYPE= 1 TARGET= 98.000
ELENCL= 585.00 ELENCR= 585.00

U/S FACE OF MILL STREET BRIDGE SEC. D

STEEL TRUSS BRIDGE, SINGLE SPAN

9.5 FEET WIDE

4846.00	7.60	578.40	0.00	0.00	578.52	.11	.04	0.00	579.40
1500.	0.	1500.	0.	0.	553.	0.	72.	11.	585.00
.39	0.00	2.71	0.00	.035	.033	.035	.031	570.80	500.00
.000394	21.	21.	21.	2	0	1	0.00	98.00	598.00

3470 ENCROACHMENT STATIONS= 500.0 598.0 TYPE= 1 TARGET= 98.000
ELENCL= 585.00 ELENCR= 585.00

4847.00	7.60	578.40	0.00	0.00	578.52	.11	.00	.00	579.40
1500.	0.	1500.	0.	0.	553.	0.	72.	11.	585.00
.39	0.00	2.71	0.00	.035	.033	.035	.031	570.80	500.00
.000393	1.	1.	1.	0	0	1	0.00	98.00	598.00

OVERBANK AREA ASSUMED NON-EFFECTIVE, ELLEA= 580.84 ELREA= 581.14

5436.00	8.02	578.66	0.00	0.00	578.82	.16	.24	.02	580.84
1500.	0.	1500.	0.	0.	468.	0.	79.	12.	581.14
.44	0.00	3.21	0.00	.035	.033	.035	.032	570.64	499.30
.000572	589.	589.	589.	2	0	1	0.00	88.72	587.02

SECNO	DEPTH	CHSEL	CHINS	WSELK	EG	HV	HL	QLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TRA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	ANL	XNCH	ANR	ATA	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	INITIAL	IDC	ICONT	CONAR	TOPWID	ENDST

3470 ENCROACHMENT STATIONS= 400.0 600.0 TYPE= 1 TARGET= 200.000

OVERBANK AREA ASSUMED NON-EFFECTIVE, ELLEA= 580.70 ELREA= 581.00

1090 FEET U/S OF MILL STREET BRIDGE SEC. E

5936.00	8.44	578.94	0.00	0.00	579.08	.14	.25	.01	580.70
1500.	0.	1500.	0.	0.	506.	0.	84.	13.	581.00
.49	0.00	2.97	0.00	.035	.033	.035	.032	570.50	497.46
.000455	500.	500.	500.	2	0	1	0.00	90.75	588.21

Exh. 3.7
15 of 41

OVERBANK AREA ASSUMED NON-EFFECTIVE, ELLEA= 581.93 ELREA= 581.93

6416.00	8.85	579.18	0.00	0.00	579.40	.22	.29	.04	581.93
1500.	0.	1500.	0.	0.	399.	0.	89.	14.	581.93
.52	0.00	3.76	0.00	.035	.033	.035	.032	570.33	581.64
.000757	480.	480.	480.	1	0	1	0.00	72.17	653.81

[redacted]VERB[redacted]AREA[redacted]SUME[redacted]ON-EF[redacted]IVF[redacted]A= [redacted]581[redacted]ELRE[redacted] [redacted]80[redacted]

49 FEET D/S OF SOUTHFIELD ROAD BRIDGE SEC. F

6786.00	9.27	579.47	0.00	0.00	579.66	.19	.25	.01	581.00
1500.	0.	1500.	0.	0.	430.	0.	93.	15.	581.80
.55	0.00	3.49	0.00	.035	.033	.035	.032	570.20	580.65
.000615	370.	370.	370.	2	0	1	0.00	74.09	654.74
6835.00	7.87	579.44	0.00	0.00	579.76	.32	.04	.06	583.17
1500.	0.	1500.	0.	0.	331.	0.	93.	15.	583.17
.55	0.00	4.53	0.00	.035	.033	.035	.032	571.57	583.97
.001293	49.	49.	49.	2	0	1	0.00	67.64	651.60

OVERBANK AREA ASSUMED NON-EFFECTIVE.ELLEA= 582.00 ELREA= 582.00

D/S FACE OF SOUTHFIELD ROAD BRIDGE

6836.00	8.05	579.65	0.00	0.00	579.31	.16	.00	.05	582.00
1500.	0.	1500.	0.	0.	471.	0.	93.	15.	582.00
.55	0.00	3.19	0.00	.035	.025	.035	.036	571.60	900.00
.000333	1.	1.	1.	2	0	1	0.00	73.00	973.00

SPECIAL BRIDGE

SB	XK	XKOR	COFQ	RDLEN	BWC	SKP	BAREA	SS	ELCHU	ELCHD
	.90	1.50	2.90	-0.00	73.00	2.50	395.10	-0.00	571.60	571.60

PRESSURE FLOW

EGPRS	EGLWC	HI	DWEIR	QPR	BAREA	ELLC	ELTRD	CLASS
580.01	579.82	.00	0.	1500.	385.	578.30	583.00	10.00

OVERBANK AREA ASSUMED NON-EFFECTIVE.ELLEA= 583.00 ELREA= 583.00

D/S FACE OF SOUTHFIELD ROAD BRIDGE SEC. G

CONCPETE BRIDGE WITH I-BEAM STRINGERS

80 FEET WIDE, 1 PIER 2.5 FEET WIDE

6916.00	8.26	579.86	0.00	0.00	580.01	.15	.20	0.00	582.00
1500.	0.	1500.	0.	0.	485.	0.	94.	15.	582.00
.56	0.00	3.09	0.00	.035	.025	.035	.032	571.60	900.00
.000302	80.	80.	80.	2	0	1	0.00	73.00	973.00

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	QLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	XTI	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	TITIAL	IOC	ICONT	CORAR	TOPWID	ENDST

Exhibit 7
16 of 41

SLOPE	XLOBL	XLCH	XLOBR	[illegible]	[illegible]	[illegible]	CORAR	[illegible]	ENDST

OVERHANK AREA ASSUMED NON-EFFECTIVE•ELLEA= 583.20 ELREA= 583.20

6917.00	8.19	579.79	0.00	0.00	580.07	.28	.00	.07	583.20
1500.	0.	1500.	0.	0.	353.	0.	94.	15.	583.20
.56	0.00	4.25	0.00	.035	.033	.035	.032	571.60	583.20
.001077	1.	1.	1.	2	0	1	0.00	69.12	652.32

3470 ENCROACHMENT STATIONS= 560.0 660.0 TYPE= 1 TARGET= 100.000

OVERBANK AREA ASSUMED NON-EFFECTIVE•ELLEA= 582.80 ELREA= 100000.00

REPEATED SECTION OF 6917

7436.00	9.13	580.33	0.00	0.00	580.53	.20	.43	.02	582.80
1500.	0.	1500.	0.	0.	420.	0.	99.	16.	100000.00
.60	0.00	3.57	0.00	.035	.033	.035	.032	571.20	580.97
.000657	519.	519.	519.	2	0	1	0.00	73.46	654.44

3470 ENCROACHMENT STATIONS= 436.0 516.0 TYPE= 1 TARGET= 80.000

OVERBANK AREA ASSUMED NON-EFFECTIVE•ELLEA= 582.60 ELREA= 100000.00

1020 FEET U/S OF SOUTHFIELD ROAD BRIDGE SEC. H

7936.00	9.85	580.65	0.00	0.00	580.83	.18	.29	.01	582.60
1500.	0.	1500.	0.	0.	441.	0.	104.	17.	100000.00
.64	0.00	3.40	0.00	.035	.033	.035	.032	570.80	440.31
.000521	500.	500.	500.	2	0	1	0.00	69.40	509.72

3470 ENCROACHMENT STATIONS= 150.0 480.0 TYPE= 1 TARGET= 330.000

OVERBANK AREA ASSUMED NON-EFFECTIVE•ELLEA= 581.70 ELREA= 582.10

8536.00	10.07	580.97	0.00	0.00	581.13	.16	.29	.01	581.70
1500.	0.	1500.	0.	0.	471.	0.	110.	18.	582.10
.70	0.00	3.19	0.00	.035	.033	.035	.032	570.90	306.81
.000450	600.	600.	600.	2	0	1	0.00	73.92	380.73

3470 ENCROACHMENT STATIONS= 140.0 310.0 TYPE= 1 TARGET= 170.000

2220 FEET U/S OF SOUTHFIELD ROAD BRIDGE SEC. I

9136.00	10.34	581.24	0.00	0.00	581.38	.14	.25	.01	581.80
1500.	1.	1498.	1.	2.	497.	7.	117.	1.	581.10
.75	.31	3.01	.20	.035	.033	.035	.03	570.90	163.83
.000385	600.	600.	600.	1	0	1	0.00	146.17	310.00

3470 ENCROACHMENT STATIONS= 50.0 250.0 TYPE= 1 TARGET= 200.000

9586.00	10.48	581.41	0.00	0.00	581.55	.14	.17	.03	580.84

Exhibit 7

.7	.35	2.96	0.00	.035	.033	.035	.032	570.94	160.58
.000363	450.	450.	450.	1	0	1	0.00	2	0

3265 DIVIDED FLOW

SECNO	DEPTH	CHSEL	CRIWS	USELK	EG	HV	HL	QLOSS	WSEL LEFT/RIGHT
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	COPAR	TOPWID	ENDST

3470 ENCROACHMENT STATIONS= 245.0 445.0 TYPE= 1 TARGET= 200.000

9596.00	10.42	581.40	0.00	0.00	581.57	.18	.01	.02	581.88
1500.	7.	1493.	0.	14.	443.	0.	122.	21.	100000.03
.79	.48	3.37	0.00	.035	.033	.035	.032	570.98	245.00
.000754	10.	10.	10.	1	0	1	0.00	142.67	445.00

3470 ENCROACHMENT STATIONS= 245.0 445.0 TYPE= 1 TARGET= 200.000

50 FEET D/S OF EMPIRE STREET SEC. J

WALL ON RIGHT BANK

10286.00	10.90	581.90	0.00	0.00	582.04	.13	.45	.01	581.90
1500.	32.	1468.	0.	50.	497.	0.	130.	23.	100000.00
.86	.64	2.96	0.00	.035	.033	.035	.032	571.00	245.00
.000572	690.	690.	690.	1	0	1	0.00	200.00	445.00

3470 ENCROACHMENT STATIONS= 350.0 445.0 TYPE= 1 TARGET= 95.000

EMPIRE STREET BRIDGE SEC. K

BRIDGE HAS BEEN REMOVED

10336.00	9.41	581.91	0.00	0.00	582.08	.17	.03	.02	579.80
1500.	145.	1355.	0.	141.	342.	0.	131.	23.	100000.00
.86	1.44	3.46	0.00	.035	.033	.035	.032	572.50	350.00
.000454	50.	50.	50.	1	0	1	0.00	95.00	445.00

3470 ENCROACHMENT STATIONS= 555.0 800.0 TYPE= 1 TARGET= 145.000

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 584.57 ELREA= 100000.00

10636.00	9.59	582.06	0.00	0.00	582.24	.18	.15	.00	584.57
1500.	0.	1500.	0.	0.	440.	0.	134.	24.	100000.00
.89	0.00	3.41	0.00	.035	.033	.035	.032	572.47	690.07
.000557	300.	300.	300.	0	0	1	0.00	73.34	753.46

3470 ENCROACHMENT STATIONS= 655.0 855.0 TYPE= 1 TARGET= 200.000

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 584.50 ELREA= 100000.00

1200 FEET U/S OF EMPIRE STREET SEC. L

11536.00	10.14	582.54	0.00	0.00	582.69	.15	.44	.01	584.50
[illegible]									

O.K. BE

680

755

Exh. 6.f 7

18 of 41

[redacted] [redacted] [redacted] [

```
HEC2 VERSION UPDATED JAN 1976
ERROR CORRECTIONS 01,02,03,04,05,06,07,08,09
MODIFICATIONS 52,53,54,55,56,57,58
**********************************************************

T1      CITY OF FORGE   5555-16   DICK ZANOTTI  P.M.
T2      100 YEAR FLOOD
T3      NORTH BRANCH OF ECORSE CREEK

J1  ICHECK    INQ       NINV      IDIR      STRT      METRIC    HVINS     Q         WSEL      FQ
          -10.      4.       -0.       -0. -0.000000     -0.00     -0.0      -0.   574.900    -0.000

J2  NPROF     IPLOT     PRFVS     XSECV     XSECH     FN        ALLDC     IBW       CHNIM     ITRACE
        3.000    -0.000    -1.000    -0.000    -0.000    -0.000    -0.000    -0.000    -0.000    -0.000

CCHV=    .300 CEHV=    .500
   SECNO     DEPTH     CWSEL     CRIWS     WSELK     EG        HV        AL        OLOSS     BANKELEV
   Q         OLOB      OCH       OROB      ALOB      ACH       AROB      VOL       TWA       LEFT/RIGHT
   TIME      VLOB      VCH       VROB      KNL       KNCH      XNP       STN       ELMIN     SSTA
   SLOPE     XLOBL     XLCH      XLOBR     ITRIAL    IDC       ICONT     CORAR     TOPWID    ENDST

      1.00     11.50    574.90      0.00    574.70    575.31       .61      0.00      0.00    584.60
      4410.        0.      4410.        0.        0.       701.        0.        0.        0.    584.60
       0.00      0.00      5.29      0.00      .035      .030      .035     0.000    563.40    528.17
    .001167        -0.       -0.       -0.         0         0         1      0.00     89.83    619.00.

     30.00     11.54    574.94      0.00      0.00    575.55       .61       .02       .00    584.60.
      4410.        0.      4410.        0.        0.       704.        0.        0.        0.    584.60
        .00      0.00      6.26      0.00      .035      .030      .035      .029    563.40    528.88
    .001155       29.       29.       29.         0         0         1      0.00     90.12    619.00

     60.00     11.58    574.98      0.00      0.00    575.59       .59       .01       .00    584.60
      4410.        0.      4410.        0.        0.       704.        0.       1.        0.    584.60
        .00      0.00      6.23      0.00      .035      .030      .035      .029    563.40    528.54
    .001141       30.       30.       30.         1         0         1      0.00     90.46    619.00

3265 DIVIDED FLOW

NORMAL BRIDGE,NRD= 9 MIN ELTRD=  584.30 MAX ELLC=  580.30

                D/S FACE OF JEFFERSON STREET BRIDGE

     61.00     11.52    574.92      0.00      0.00    575.65       .73       .00       .06    584.60
      4410.        0.      4410.        0.        0.       645.        0.       1.        0.    584.60
        .00      0.00      6.84      0.00      .035      .030      .035      .029    563.40    528.98
    .002091        1.        1.        1.         2         0         1      0.00     83.02    619.00

3265 DIVIDED FLOW

NORMAL BRIDGE,NRD= 9 MIN ELTRD=  584.30 MAX ELLC=  580.30
```

Exhibit 7
20 of 41

3265 DIVIDED FLOW

NORMAL BRIDGE,NRD= 9 MIN ELTRD= 584.30 MAX ELLC= 580.30

U/S FACE OF JEFFERSON STREET BRIDGE SEC. A

CONCRETE TWO SPAN BRIDGE

CONCRETE RAILING, TWO PIERS, 75 FEET WIDE

136.00	11.72	575.12	0.00	0.00	575.81	.69	.15	.01	584.60
4410.	0.	4410.	0.	0.	662.	0.	2.	0.	584.60
.01	0.00	6.67	0.00	.035	.030	.035	.029	563.40	527.31
.001976	75.	75.	75.	2	0	1	0.00	84.69	619.00

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	OLOB	OCH	OROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICOUNT	CORAR	TOPWID	ENDST
137.00	11.90	575.30	0.00	0.00	575.95	.65	.00	.04	584.60
4410.	0.	4410.	0.	0.	738.	0.	2.	0.	584.60
.01	0.00	5.98	0.00	.035	.030	.035	.029	563.40	525.83
.001035	1.	1.	1.	2	0	1	0.00	93.17	619.00

50 FEET U/S OF JEFFERSON STREET BRIDGE SEC. B

187.00	11.22	575.32	0.00	0.00	575.93	.61	.05	.04	581.10
4410.	0.	4410.	0.	0.	592.	0.	3.	0.	580.20
.01	0.00	6.37	0.00	.035	.030	.042	.029	564.10	341.89
.001185	50.	50.	50.	2	0	1	0.00	91.13	432.36

1490 NH CARD USED

REPEATED SECTION OF 737

DOCKS ON RIGHT BANK

362.00	11.89	575.86	0.00	0.00	576.17	.31	.14	.10	578.57
4410.	0.	4410.	0.	0.	984.	0.	6.	1.	577.17
.02	0.00	4.40	0.00	.035	.031	.042	.029	563.87	251.32
.000515	175.	175.	175.	2	0	1	0.00	145.84	397.16

3470 ENCROACHMENT STATIONS= 244.0 373.0 TYPE= 1 TARGET= 129.000

50 FEET D/S OF RAILROAD BRIDGE NO. 1 SEC. C

ENCROACHED FOR EXPANSION

737.00	12.34	576.04	0.00	0.00	576.35	.31	.18	.00	578.30
4410.	0.	4410.	0.	0.	979.	0.	14.	2.	100000.00
.04	0.00	4.50	0.00	.035	.030	.042	.030	563.70	250.11
.000448	375.	375.	375.	2	0	1	0.00	122.89	373.00

Exhibit 7
21 of 41

787.00	12.11	576.01	0.00	0.00	576.45	.44	.03	.06	581.00
[redacted]									
.04	0.00	5.34	0.00	.035	.032	.042	.030	563.90	795.00
.000965	50.	50.	50.	2	0	1	0.00	106.60	901.60

3265 DIVIDED FLOW

NORMAL BRIDGE,NRD= 4 MIN ELTRD= 581.00 MAX ELLC= 577.20

D/S FACE OF RAILROAD BRIDGE NO. 1

788.00	12.06	575.96	0.00	0.00	576.50	.54	.00	.05	581.00
4410.	0.	4410.	0.	0.	744.	0.	16.	2.	581.00
.04	0.00	5.92	0.00	.035	.032	.042	.030	563.90	795.00
.003859	1.	1.	1.	2	0	1	0.00	104.00	901.60

3265 DIVIDED FLOW

NORMAL BRIDGE,NRD= 4 MIN ELTRD= 581.00 MAX ELLC= 577.20

U/S FACE OF RAILROAD BRIDGE NO. 1 SEC. D

STEEL I-BEAM BRIDGE WITH 2-STEEL BENT PIERS

9 FEET WIDE, 7 OLD BENT PILES-CUTOFF

797.00	12.10	576.00	0.00	0.00	576.54	.54	.00	.00	581.00
4410.	0.	4410.	0.	0.	744.	0.	16.	2.	581.00
.05	0.00	5.99	0.00	.035	.032	.042	.030	563.90	795.00
.003788	9.	9.	9.	2	0	1	0.00	104.00	901.60

SECNO	DEPTH	CHSEL	CRIWS	WSELK	EG	HV	HL	QLOSS	HANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	ITR	ELTRD	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPID	ENDSTA
798.00	12.25	576.15	0.00	0.00	576.57	.43	.00	.03	581.00
4410.	0.	4410.	0.	0.	741.	0.	16.	2.	581.00
.05	0.00	5.25	0.00	.035	.032	.042	.030	563.90	795.00
.000912	1.	1.	1.	2	0	1	0.00	106.60	901.60
844.00	11.20	576.20	0.00	0.00	576.63	.42	.04	.00	581.50
4410.	0.	4410.	0.	0.	846.	0.	17.	2.	581.40
.05	0.00	5.21	0.00	.035	.032	.042	.030	565.00	813.00
.000867	46.	46.	46.	2	0	1	0.00	108.98	923.98

3265 DIVIDED FLOW

NORMAL BRIDGE,NRD=16 MIN ELTRD= 581.40 MAX ELLC= 578.40

D/S FACE OF RAILROAD BRIDGE NO. 2

[illegible]

D/S FACE OF RAILROAD BRIDGE NO. 2

845.00	11.16	576.16	0.00	0.00	576.66	.50	.00	.04	581.50	
4410.	0.	4410.	0.	0.	779.	0.	17.	2.	581.40	
.05	0.00	5.66	0.00	.035	.032	.042	.030	565.00	815.00	
.002965	1.	1.	1.	2	0	1	0.00	101.81	923.5	

3265 DIVIDED FLOW

NORMAL BRIDGE,NRD=16 MIN ELTRD= 581.40 MAX ELLC= 578.40

U/S FACE OF RAILROAD BRIDGE NO. 2 SEC. E

WOOD BRIDGE WITH BALLAST AND TIE DECK

14.5 FEET WIDE, 7 BENT PIERS OF WOOD

14.5 FEET WIDE, 7 BENT PIERS OF WOOD

859.00	11.21	576.21	0.00	0.00	576.70	.49	.04	.00	581.50
4410.	0.	4410.	0.	0.	784.	0.	17.	2.	581.40
.05	0.00	5.62	0.00	.035	.032	.042	.030	565.00	815.00
.002915	15.	15.	15.	2	0	1	0.00	102.00	924.00
860.00	11.32	576.32	0.00	0.00	576.73	.41	.00	.02	581.50
4410.	0.	4410.	0.	0.	854.	0.	17.	2.	581.40
.05	0.00	5.13	0.00	.035	.032	.042	.030	565.00	815.00
.000826	1.	1.	1.	2	0	1	0.00	104.00	924.00
910.00	12.39	576.39	0.00	0.00	576.77	.38	.04	.01	583.10
4410.	0.	4410.	0.	0.	791.	0.	17.	2.	583.00
.05	0.00	4.95	0.00	.035	.032	.04	.030	564.00	835.00
.000739	50.	50.	50.	1	0	1	0.00	107.00	942.00

3265 DIVIDED FLOW

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TYA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	INITIAL	IDC	ICODE	COMAR	TOPWID	ENDST

NORMAL BRIDGE,NRD= 6 MIN ELTRD= 583.00 MAX ELLC= 574.63

D/S FACE OF RAILROAD BRIDGE NO. 3

D/S FACE OF RAILROAD BRIDGE NO. 3

911.00	12.35	576.35	0.00	0.00	576.82	.47	.00	.04	583.10

Exh. 8.7

23 of 41

.05	0.00	5.47	0.00	.035	.032	.042	.030	564.00	835.00
.003268	1.	1.	1.	2	0	1	0.00	105.00	942.00

3265 DIVIDED FLOW

NORMAL BRIDGE, NRD= 6 MIN EL TRD= 583.00 MAX ELLC= 578.60

U/S FACE OF RAILROAD BRIDGE NO. 3 SEC. F

STEEL I-BEAM BRIDGE WITH 2 STEEL PIERS

10 FEET WIDE, 8 SETS OF OLD PIER BENTS-CUTOFF

921.00	12.39	576.39	0.00	0.00	576.85	.46	.03	.00	583.10
4410.	0.	4410.	0.	0.	809.	0.	19.	2.	583.00
.05	0.00	5.45	0.00	.035	.032	.042	.030	564.00	835.00
.003232	10.	10.	10.	1	0	1	0.00	105.00	942.00
922.00	12.51	576.51	0.00	0.00	576.84	.37	.00	.03	583.10
4410.	0.	4410.	0.	0.	902.	0.	19.	2.	583.00
.05	0.00	4.89	0.00	.035	.032	.042	.030	564.00	835.00
.000710	1.	1.	1.	2	0	1	0.00	107.00	942.00
953.00	11.34	576.44	0.00	0.00	577.01	.57	.07	.10	581.00
4410.	0.	4410.	0.	0.	726.	0.	19.	3.	580.80
.05	0.00	6.08	0.00	.035	.032	.042	.030	565.10	600.00
.001096	31.	31.	31.	2	0	1	0.00	81.00	681.00

3265 DIVIDED FLOW

NORMAL BRIDGE, NRD=14 MIN EL TRD= 580.40 MAX ELLC= 577.70

U/S FACE OF RAILROAD BRIDGE NO. 4

954.00	11.18	576.28	0.00	0.00	577.17	.88	.00	.15	581.00
4410.	0.	4410.	0.	0.	585.	0.	19.	3.	580.80
.05	0.00	7.53	0.00	.035	.032	.042	.030	565.10	600.00
.005859	1.	1.	1.	2	0	1	0.00	87.20	681.00

3265 DIVIDED FLOW

NORMAL BRIDGE, NRD=14 MIN EL TRD= 580.80 MAX ELLC= 577.70

U/S FACE OF RAILROAD BRIDGE NO. 4 SEC. G

CONCRETE BRIDGE, BOX BEAM DECK

WITH BALLAST AND RAILS, 30.5 FEET WIDE

904.00	11.42	576.52	0.00	0.00	577.39	.86	.17	.01	581.00
4410.	0.	4410.	0.	0.	601.	0.	19.	3.	580.80
.05	0.00	7.34	0.00	.035	.032	.042	.030	565.10	600.00

Exhibit 7
24 of 41

WITH BALLAST AND RAILS, 30.5 FEET WIDE

986.00	11.42	576.52	0.00	0.00	577.35	.84	.17	.01	581.00
4410.	0.	4410.	0.	0.	601.	0.	19.	3.	580.80
.05	0.00	7.34	0.00	.035	.032	.042	.030	565.10	600.00
.005491	31.	31.	31.	2	0	1	0.00	67.20	631.00

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	AV	HL	OLOSS	BANK ELEV
Q	QLOB	VCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAB	TOPWID	ENDST
986.00	11.84	576.94	0.00	0.00	577.45	.51	.00	.10	581.00
4410.	0.	4410.	0.	0.	766.	0.	19.	3.	580.80
.05	0.00	5.75	0.00	.035	.032	.042	.030	565.10	600.00
.000927	1.	1.	1.	2	0	1	0.00	81.00	681.00

3470 ENCROACHMENT STATIONS= .0 700.0 TYPE= 1 TARGET= 599.999

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 581.10 ELREA= 100000.00

50 FEET UPSTREAM OF RAILROAD BRIDGE NO. 4 SEC. 8

1035.00	10.90	577.10	0.00	0.00	577.52	.42	.08	.01	581.10
4410.	0.	4410.	0.	0.	50.	0.	20.	3.	100000.00
.06	0.00	5.19	0.00	.040	.030	.035	.030	566.20	580.44
.000822	50.	50.	50.	0	0	1	0.00	118.70	699.14

3470 ENCROACHMENT STATIONS= 374.0 442.5 TYPE= 1 TARGET= 118.500

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 579.10 ELREA= 100000.00

AVERAGE SECTION

1730.00	12.28	577.68	0.00	0.00	578.04	.36	.41	.02	579.10
4410.	0.	4410.	0.	0.	520.	0.	35.	5.	100000.00
.10	0.00	4.79	0.00	.060	.050	.035	.031	565.40	376.92
.000614	700.	700.	700.	3	0	1	0.00	115.50	492.50

3470 ENCROACHMENT STATIONS= 183.0 295.0 TYPE= 1 TARGET= 102.000

1450 FEET U/S OF RAILROAD BRIDGE NO. 4 SEC. 1

CONFLUENCE OF SEXTON-KILFOIL DRAIN, NORTH ECORSE CREEK

AND ECORSE CREEK

2430.00	13.48	578.08	0.00	0.00	578.43	.35	.37	.00	577.10
4410.	0.	4410.	0.	0.	430.	0.	49.	5.	100000.00
.14	0.00	4.71	0.00	.050	.040	.035	.030	564.60	183.00
.000510	700.	700.	700.	2	0	1	0.00	102.00	285.00

CCHV= .300 CEHV= .500

Exhibit 7
25 of 41

```
3470 ENCROACHMENT STATIONS=     300.0     400.0  TYPE=     1  TARGET=     100.000

                    2089 FEET D/S OF MILL STREET BRIDGE                 SEC. A

  2736.00     9.37   578.47     0.00     0.00   578.63     .16      .14      .06   578.70
  2100.          0.  2100.        0.       0.     658.      0.      55.       7. 100000.00
     .17     0.00     3.19     0.00     .035     .033     .035     .030   569.10   301.37
  .000419     300.     300.     300.        2        0        1     0.00    99.34   397.10


3470 ENCROACHMENT STATIONS=     300.0     400.0  TYPE=     1  TARGET=     100.000

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA=     578.98 ELREA=  100000.00

                    REPEATED SECTION OF 2736

  3436.00     9.29   578.77     0.00     0.00   578.93     .16      .30      .00   578.98
  2100.          0.  2100.        0.       0.     649.      0.      65.       9. 100000.00
     .23     0.00     3.23     0.00     .035     .033     .035     .031   569.48   300.61
  .000435     700.     700.     700.        2        0        1     0.00    98.91   399.51


3470 ENCROACHMENT STATIONS=     200.0     300.0  TYPE=     1  TARGET=     100.000

                    999 FEET D/S OF MILL STREET BRIDGE                  SEC. B

  3836.00     9.25   578.95     0.00     0.00   579.20     .25      .23      .04   579.50
  2100.          0.  2100.        0.       0.     523.      0.      71.       9. 100000.00
     .25     0.00     4.01     0.00     .035     .033     .035     .031   569.70   200.00
  .000766     400.     400.     400.        1        0        1     0.00    87.67   287.67

   SECNO     DEPTH     Q/SEL     CHWS     WSELK      F,       HV       HL      QLOSS    BANK ELEV
   Q         QLOB      QCH       QROB     ALOB       ACH      AHOB     VOL     TWA      LEFT/RIGHT
   TIME      VLOB      VCH       VROB     XNL        XNCH     XNR      WTN     ELMIN    SSTA
   SLOPE     XLOBL     XLCH      XLOBR    ITRIAL     IX       ICONT    CORAR   TOPWID   ENDST


3470 ENCROACHMENT STATIONS=     200.0     290.0  TYPE=     1  TARGET=      90.000
  4311.00     9.42   579.32     0.00     0.00   579.55     .24      .35      .00   578.70
  2100.          0.  2100.        0.       0.     539.      0.      77.      10. 100000.00
     .29     0.00     3.90     0.00     .035     .033     .035     .031   569.90   200.00
  .000703     475.     475.     475.        2        0        1     0.00    88.14   288.14


3470 ENCROACHMENT STATIONS=     393.0     500.0  TYPE=     1  TARGET=     107.000

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA=     580.10 ELREA=  100000.00

                    139 FEET D/S OF MILL STREET BRIDGE                  SEC. C

  4786.00     9.59   579.69     0.00     0.00   579.85     .17      .28      .02   580.10
  2100.          0.  2100.        0.       0.     641.      0.      83.      11. 100000.00
     .33     0.00     3.28     0.00     .035     .033     .035     .031   570.10   394.98
  .000497     475.     475.     475.        1        0        1     0.00   105.02   500.00


3470 ENCROACHMENT STATIONS=     500.0     598.0  TYPE=     1  TARGET=      98.000
 FLENCL=   585.00, ELENCR=   585.00

                    D/S FACE OF MILL STREET BRIDGE
```

393 LB RB
500
Q455
ERU 7
26 of 41

D/S FACE OF MILL STREET BRIDGE

4825.00	8.93	579.73	0.00	0.00	579.88	.15	.02	.01	579.40	
2100.	0.	2100.	0.	0.	683.	0.	84.	12.	585.00	
.33	0.00	3.03	0.00	.035	.033	.035	.031	570.80	500.00	
.000394	39.	39.	39.	2	0	1	0.00	98.00	598.00	

SPECIAL BRIDGE

SK	XK	XKOR	COFQ	RDLEN	BWC	BWP	BAREA	SS	ELCHU	ELCHD
	-0.00	1.30	2.50	50.00	51.70	-0.00	538.00	3.17	570.80	570.80

PRESSURE AND WEIR FLOW

EGPRS	EGLWC	H3	QWEIR	QPR	BAREA	ELLC	ELTRD	CLASS
580.04	579.88	0.00	207.	1881.	538.	578.30	579.40	30.00

3470 ENCROACHMENT STATIONS= 500.0 598.0 TYPE= 1 TARGET= 98.000
ELENCL= 585.00 ELENCR= 585.00

D/S FACE OF MILL STREET BRIDGE SEC. D

STEEL TRUSS BRIDGE, SINGLE SPAN

9.5 FEET WIDE

4846.00	9.03	579.83	0.00	0.00	579.98	.14	.10	0.00	579.40
2100.	0.	2100.	0.	0.	693.	0.	84.	12.	585.00
.33	0.00	3.03	0.00	.035	.033	.035	.031	570.80	500.00
.000376	21.	21.	21.	2	0	1	0.00	98.00	598.00

3470 ENCROACHMENT STATIONS= 500.0 598.0 TYPE= 1 TARGET= 98.000
ELENCL= 585.00 ELENCR= 585.00

4847.00	9.03	579.83	0.00	0.00	579.98	.14	.00	.00	579.40
2100.	0.	2100.	0.	0.	693.	0.	84.	12.	585.00
.33	0.00	3.03	0.00	.035	.033	.035	.031	570.80	500.00
.000376	1.	1.	1.	0	0	1	0.00	98.00	598.00

3280 CROSS SECTION 5436.00 EXTENDED .32 FEET

OVERBANK AREA ASSUMED NON-EFFECTIVE, ELLEA= 580.84 ELREA= 581.14

5436.00	9.43	580.07	0.00	0.00	580.27	.19	.27	.02	580.84
2100.	0.	2100.	0.	0.	497.	0.	93.	13.	581.14
.38	0.00	3.52	0.00	.035	.033	.035	.032	570.54	495.53
.000450	589.	589.	589.	1	0	1	0.00	95.45	590.98

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	QLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA

Exhibit 7
27 of 41

3470 ENCROACHMENT STATIONS= 400.0 500.0 TYPE= 1 TARGET= 200.000

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 580.70 ELREA= 581.00

1090 FEET U/S OF HILL STREET BRIDGE SEC. E

5936.00	9.85	580.35	0.00	0.00	580.52	.17	.25	.01	580.70
2100.	0.	2100.	0.	0.	639.	0.	100.	14.	581.00
.42	0.00	3.29	0.00	.035	.033	.035	.032	570.50	494.68
.000453	500.	500.	500.	2	0	.1	0.00	97.50	592.18

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 581.93 ELREA= 581.93

6416.00	10.25	580.58	0.00	0.00	580.85	.27	.28	.05	581.93
2100.	0.	2100.	0.	0.	505.	0.	105.	15.	581.93
.45	0.00	4.16	0.00	.035	.033	.035	.032	570.33	578.29
.000762	480.	480.	480.	1	0	1	0.00	78.69	656.98

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 581.80 ELREA= 581.80

49 FEET D/S OF SOUTHFIELD ROAD BRIDGE SEC. F

605 Q

6786.00	10.68	580.88	0.00	0.00	581.12	.24	.26	.01	581.80
2100.	0.	2100.	0.	0.	539.	0.	111.	16.	581.80
.48	0.00	3.90	0.00	.035	.033	.035	.032	570.20	577.28
.000636	370.	370.	370.	2	0	1	0.00	80.64	657.93

6835.00	9.29	580.86	0.00	0.00	581.22	.37	.04	.07	583.17
2100.	0.	2100.	0.	0.	431.	0.	111.	16.	583.17
.48	0.00	4.87	0.00	.035	.033	.035	.032	571.57	580.60
.001194	49.	49.	49.	2	0	1	0.00	74.18	654.79

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 582.00 ELREA= 582.00

D/S FACE OF SOUTHFIELD ROAD BRIDGE

6836.00	9.46	581.06	0.00	0.00	581.27	.21	.00	.05	582.00
2100.	0.	2100.	0.	0.	573.	0.	111.	16.	582.00
.48	0.00	3.66	0.00	.035	.025	.035	.032	571.60	900.00
.000351	1.	1.	1.	2	0	.1	0.00	73.00	973.00

SPECIAL BRIDGE

SB	XK	XKOR	COFQ	RDLEN	BWC	BWP	BAREA	SS	ELCHU	ELCHD
	.90	1.50	2.90	-0.00	73.00	2.50	385.10	-0.00	571.60	571.60

PRESSURE FLOW

FGPRS	EGLWC	H3	QWEIR	QPR	BAREA	ELLC	ELTRD	CLASS
581.76	581.28	.01	0.	2100.	395.	574.31	583.00	10.00

Exhibit 7
28 of 41

581.76 581.28 .01 0. 2100. [redacted]

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 583.00 ELREA= 583.00

U/S FACE OF SOUTHFIELD ROAD BRIDGE SEC. G

CONCRETE BRIDGE WITH I-BEAM STRINGERS

130.FEET WIDE, 1 PIER 2.5 FEET WIDE

6916.00	9.97	581.57	0.00	0.00	581.76	.18	.48	0.00	582.00
2100.	0.	2100.	0.	0.	611.	0.	112.	16.	582.00
.49	0.00	3.44	0.00	.035	.025	.035	.032	571.60	900.00
.000289	80.	80.	80.	2	0	1	0.00	73.00	973.00

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	KLOBL	KLCH	KLOBR	ITRIAL	IDC	ICONT	COPAR	TOPWID	ENDST

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 583.20 ELREA= 583.20

6917.00	9.92	581.52	0.00	0.00	581.82	.30	.00	.06	583.20
2100.	0.	2100.	0.	0.	479.	0.	112.	16.	583.20
.49	0.00	4.39	0.00	.035	.033	.035	.032	571.60	579.10
.000887	1.	1.	1.	2	0	1	0.00	77.10	656.21

3470 ENCROACHMENT STATIONS= 560.0 660.0 TYPE= 1 TARGET= 100.000

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 582.80 ELREA= 100000.00

REPEATED SECTION OF 6917

7436.00	10.79	581.99	0.00	0.00	582.21	.23	.38	.02	582.80
2100.	0.	2100.	0.	0.	548.	0.	118.	17.	100000.00
.53	0.00	3.83	0.00	.035	.033	.035	.032	571.20	577.03
.000609	519.	519.	519.	2	0	1	0.00	81.13	658.17

3280 CROSS SECTION 7936.00 EXTENDED .58 FEET

3470 ENCROACHMENT STATIONS= 436.0 516.0 TYPE= 1 TARGET= 90.000

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 582.60 ELREA= 100000.00

1020 FEET U/S OF SOUTHFIELD ROAD BRIDGE SEC. H

7936.00	11.48	582.29	0.00	0.00	582.50	.22	.28	.00	582.60
2100.	0.	2100.	0.	0.	561.	0.	125.	18.	100000.00
.56	0.00	3.74	0.00	.035	.033	.035	.032	570.80	436.70
.000529	500.	500.	500.	2	0	1	0.00	77.21	513.91

3280 CROSS SECTION 9536.00 EXTENDED .23 FEET

3470 ENCROACHMENT STATIONS=	150.0	400.0	TYPE=	1	TARGET=	250.000			
9536.00	11.72	582.62	0.00	0.00	582.79	.16	.27	.02	581.77
2100.	100.	1994.	6.	133.	598.	10.	134.	20.	582.10
.62	.75	3.34	.58	.035	.033	.035	.032	570.90	150.00
.000384	600.	600.	600.	0	0	1	0.00	250.00	400.00

3470 ENCROACHMENT STATIONS=	140.0	310.0	TYPE=	1	TARGET=	170.000			
2220 FEET U/S OF SOUTHFIELD ROAD BRIDGE					SEC. I				
9136.00	11.96	582.86	0.00	0.00	583.00	.14	.21	.01	580.80
2100.	44.	1944.	112.	47.	618.	104.	144.	23.	581.10
.67	.92	3.15	1.08	.035	.033	.035	.032	570.90	140.00
.000314	600.	600.	600.	2	0	1	0.00	170.00	310.00

210 4

3470 ENCROACHMENT STATIONS=	50.0	250.0	TYPE=	1	TARGET=	200.000			
9586.00	12.06	583.00	0.00	0.00	583.16	.16	.15	.01	580.84
2100.	50.	2040.	0.	70.	626.	0.	152.	25.	100000.04
.71	.86	3.26	0.00	.035	.033	.035	.032	570.94	91.87
.000341	450.	450.	450.	1	0	1	0.00	158.13	250.00

3280 CROSS SECTION 9596.00 EXTENDED .58 FEET

SECNO	DEPTH	CHSEL	CRIWS	WSEL	E	FF	HL	OLOSS	BANK ELEV.
Q	OLOB	OCH	OROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XTOCH	XNR	XTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IOC	ICONT	CORAR	TOPWID	ENDST

3470 ENCROACHMENT STATIONS=	245.0	445.0	TYPE=	1	TARGET=	200.000			
9596.00	12.05	583.03	0.00	0.00	583.17	.14	.00	.01	581.88
2100.	218.	1882.	0.	165.	583.	0.	152.	25.	100000.03
.71	1.32	3.12	0.00	.035	.033	.035	.032	570.98	245.00
.000498	10.	10.	10.	2	0	1	0.00	200.00	445.00

3280 CROSS SECTION 10286.00 EXTENDED .96 FEET

3470 ENCROACHMENT STATIONS=	245.0	445.0	TYPE=	1	TARGET=	200.000			
50 FEET D/S OF EMPIRE STREET					SEC. J				
WALL ON RIGHT BANK									
10286.00	12.36	583.36	0.00	0.00	583.48	.12	.30	.01	581.90
2100.	257.	1843.	0.	196.	642.	0.	165.	28.	100000.00
.78	1.31	2.87	0.00	.035	.033	.035	.032	571.00	245.00
.000389	690.	690.	690.	2	0	1	0.00	200.00	445.00

435 4

Exh. J 7
30 of 41

3470 ENCROACHMENT STATIONS=	350.0	445.0	TYPE=	1	TARGET=	95.000			
EMPIRE STREET BRIDGE					SEC. K				

3470 ENCROACHMENT STATIONS= 350.0 445.0 TYPE= 1 TARGET= 95.000

EMPIRE STREET BRIDGE SEC. K

BRIDGE HAS BEEN REMOVED

10336.00	10.84	583.34	0.00	0.00	583.54	.20	.02	.04	579.80
2100.	359.	1741.	0.	172.	457.	0.	165.	28.	100000.00
.79	2.09	3.81	0.00	.035	.033	.035	.032	572.50	350.00
.000466	50.	50.	50.	2	0	1	0.00	95.00	445.00

430 L

3280 CROSS SECTION 10636.00 EXTENDED .46 FEET

3470 ENCROACHMENT STATIONS= 655.0 800.0 TYPE= 1 TARGET= 145.000

OVERBANK AREA ASSUMED NON-EFFECTIVE, ELLEA= 584.57 ELREA= 100000.00

START SEC

10636.00	11.06	583.53	0.00	0.00	583.73	.20	.19	.00	584.57
2100.	0.	2100.	0.	0.	378.	0.	170.	29.	100000.00
.81	0.00	3.63	0.00	.035	.033	.035	.032	572.47	674.15
.000887	300.	300.	300.	2	0	1	0.00	145.85	800.00

3280 CROSS SECTION 11536.00 EXTENDED 1.33 FEET

3470 ENCROACHMENT STATIONS= 655.0 855.0 TYPE= 1 TARGET= 200.000

OVERBANK AREA ASSUMED NON-EFFECTIVE, ELLEA= 584.50 ELREA= 100000.00

1200 FEET U/S OF EMPIRE STREET SEC. L

11536.00	11.93	584.33	0.00	0.00	584.45	.12	.08	.02	584.50
2100.	0.	2100.	0.	0.	744.	0.	143.	32.	100000.00
.90	0.00	2.83	0.00	.035	.033	.035	.032	572.49	658.08
.000690	900.	900.	900.	2	0	1	0.00	196.91	855.00

EXHIBIT 7
5 of 11

SUMMARY PRINTOUT FOR [redacted] PLE [redacted] TLE [redacted]

NORTH BRANCH OF FOURSE C

SECTION NUMBER	CHANNEL LENGTH	MIN EL OF ROADWAY	MAX EL OF LOW CHORD	MIN EL GROUND	DISCHARGE (CFS)	CWSEL	V	HL	BLOSS	QCR	DEPTH	TOPWID
1.00	0.00	0.00	0.00	563.40	3165.00	574.90	.32	0.00	0.00	3165.00	11.50	[illegible]
1.00	0.00	0.00	0.00	563.40	4100.00	574.90	.53	0.00	0.00	4100.00	11.50	[illegible]
1.00	0.00	0.00	0.00	563.40	4410.00	574.90	.61	0.00	0.00	4410.00	11.50	[illegible]
1.00	0.00	0.00	0.00	563.40	5160.00	574.90	.84	0.00	0.00	5160.00	11.50	[illegible]
30.00	29.00	0.00	0.00	563.40	3165.00	574.92	.31	.02	.00	3165.00	11.52	[illegible]
30.00	29.00	0.00	0.00	563.40	4100.00	574.93	.53	.03	.00	4100.00	11.53	[illegible]
30.00	29.00	0.00	0.00	563.40	4410.00	574.94	.61	.03	.00	4410.00	11.54	[illegible]
30.00	29.00	0.00	0.00	563.40	5160.00	574.96	.83	.05	.00	5160.00	11.56	[illegible]
60.00	30.00	0.00	0.00	563.40	3165.00	574.94	.31	.02	.00	3165.00	11.54	[illegible]
60.00	30.00	0.00	0.00	563.40	4100.00	574.97	.52	.03	.00	4100.00	11.57	[illegible]
60.00	30.00	0.00	0.00	563.40	4410.00	574.9[illegible]	.60	.03	.00	4410.00	11.58	[illegible]
60.00	30.00	0.00	0.00	563.40	5160.00	575.01	.81	.05	.00	5160.00	11.63	[illegible]
61.00	1.00	584.30	580.30	563.40	3165.00	574.91	.31	.00	.03	3165.00	11.51	82.91
61.00	1.00	584.30	580.30	563.40	4100.00	574.92	.53	.00	.05	4100.00	11.52	82.99
61.00	1.00	584.30	580.30	563.40	4410.00	574.92	.75	.00	.06	4410.00	11.52	83.02
61.00	1.00	584.30	580.30	563.40	5160.00	574.94	.99	.00	.09	5160.00	11.54	83.18
136.00	75.00	584.30	580.30	563.40	3165.00	575.00	.37	.00	.00	3165.00	11.60	[illegible]
136.00	75.00	584.30	580.30	563.40	4100.00	575.09	.60	.13	.01	4100.00	11.69	84.38
136.00	75.00	584.30	580.30	563.40	4410.00	575.1[illegible]	.69	.15	.01	4410.00	11.72	84.69
136.00	75.00	584.30	580.30	563.40	5160.00	575.24	.92	.20	.02	5160.00	11.84	85.68
137.00	1.00	0.00	0.00	563.40	3165.00	575.07	.30	.00	.02	3165.00	11.67	91.38
137.00	1.00	0.00	0.00	563.40	4100.00	575.24	.45	.00	.03	4100.00	11.84	92.64
137.00	1.00	0.00	0.00	563.40	4410.00	575.30	.55	.00	.04	4410.00	11.90	93.17
137.00	1.00	0.00	0.00	563.40	5160.00	575.50	.76	.00	.06	5160.00	12.10	94.13
187.00	50.00	0.00	0.00	564.10	3165.00	575.09	.34	.03	.02	3165.00	10.99	[illegible]
187.00	50.00	0.00	0.00	564.10	4100.00	575.25	.55	.05	.03	4100.00	11.15	90.51
187.00	50.00	0.00	0.00	564.10	4410.00	575.32	.63	.06	.04	4410.00	11.22	91.10
187.00	50.00	0.00	0.00	564.10	5160.00	575.52	.82	.07	.05	5160.00	11.42	92.3[illegible]
362.00	175.00	0.00	0.00	563.97	3165.00	575.38	.19	.08	.05	3165.00	11.41	143.47
362.00	175.00	0.00	0.00	563.97	4100.00	575.72	.28	.12	.08	4100.00	11.75	145.17
362.00	175.00	0.00	0.00	563.97	4410.00	575.86	.31	.13	.10	4410.00	11.89	145.84
362.00	175.00	0.00	0.00	563.97	5160.00	576.24	.38	.16	.13	5160.00	12.27	147.72
737.00	375.00	0.00	0.00	563.70	3165.00	575.49	.19	.11	.00	3165.00	11.79	121.40
737.00	375.00	0.00	0.00	563.70	4100.00	575.89	.28	.16	.00	4100.00	12.19	122.47
737.00	375.00	0.00	0.00	563.70	4410.00	576.04	.31	.18	.00	4410.00	12.34	122.89
737.00	375.00	0.00	0.00	563.70	5160.00	576.45	.39	.21	.00	5160.00	12.75	123.99
787.00	50.00	0.00	0.00	563.90	3165.00	575.47	.26	.02	.04	3165.00	11.57	106.60
787.00	50.00	0.00	0.00	563.90	4100.00	575.86	.41	.03	.06	4100.00	11.96	106.60
787.00	50.00	0.00	0.00	563.90	4410.00	576.01	.46	.03	.06	4410.00	12.11	106.60
787.00	50.00	0.00	0.00	563.90	5160.00	576.41	.58	.04	.08	5160.00	12.51	106.60

SECTION NUMBER	CHANNEL LENGTH	MIN EL OF ROADWAY	MAX EL OF LOW CHORD	MIN EL GROUND	DISCHARGE (CFS)	CWSEL	V	HL	BLOSS	QCR	DEPTH	TOPWID
[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]

Exhibit 7
32 of 41

[redacted] NUMBER	CHA[redacted] LENGTH	MI[redacted] OF ROADWAY	[redacted] LOW CHORD	EL[redacted] MIN[redacted] GROUND	[redacted] DISCHARGE (CFS)	[redacted] W/SEL	HV	PL	[redacted]	[redacted]	[redacted]
788.00	1.00	581.00	577.20	563.90	3165.00	575.44	.33	.00	.03	3[redacted]	[redacted]
788.00	1.00	581.00	577.20	563.90	4100.00	575.81	.49	.00	.03	[redacted]	[redacted]
788.00	1.00	581.00	577.20	563.90	4410.00	575.96	.54	.00	.03	[redacted]	[redacted]
788.00	1.00	581.00	577.20	563.90	5160.00	576.35	.67	.00	.05	[redacted]	[redacted]
797.00	9.00	581.00	577.20	563.90	3165.00	575.46	.32	.02	.00	3165.00	[redacted]
797.00	9.00	581.00	577.20	563.90	4100.00	575.85	.49	.03	.00	4100.00	[redacted]
797.00	9.00	581.00	577.20	563.90	4410.00	576.00	.54	.03	.00	4410.00	[redacted]
797.00	9.00	581.00	577.20	563.90	5160.00	576.40	.66	.04	.00	5160.00	[redacted]
798.00	1.00	0.00	0.00	563.90	3165.00	575.55	.26	.00	.02	3165.00	11.65	[redacted]
798.00	1.00	0.00	0.00	563.90	4100.00	575.98	.39	.00	.03	4100.00	12.08	[redacted]
798.00	1.00	0.00	0.00	563.90	4410.00	576.15	.43	.00	.03	4410.00	12.25	[redacted]
798.00	1.00	0.00	0.00	563.90	5160.00	576.53	.53	.00	.04	5160.00	[redacted]	[redacted]
844.00	46.00	0.00	0.00	565.00	3165.00	575.58	.26	.03	.00	3165.00	10.58	[redacted]
844.00	46.00	0.00	0.00	565.00	4100.00	576.03	.48	.04	.00	4100.00	11.03	[redacted]
844.00	46.00	0.00	0.00	565.00	4410.00	576.20	.42	.04	.00	4410.00	11.20	[redacted]
844.00	46.00	0.00	0.00	565.00	5160.00	576.64	.52	.05	.00	5160.00	11.64	[redacted]
845.00	1.00	581.40	578.40	565.00	3165.00	575.56	.30	.00	.02	3165.00	10.56	[redacted]
845.00	1.00	581.40	578.40	565.00	4100.00	575.99	.45	.00	.03	4100.00	10.99	[redacted]
845.00	1.00	581.40	578.40	565.00	4410.00	576.16	.50	.00	.04	4410.00	11.16	[redacted]
845.00	1.00	581.40	578.40	565.00	5160.00	576.61	.61	.00	.05	5160.00	11.60	[redacted]
859.00	14.50	581.40	578.40	565.00	3165.00	575.54	.30	.03	.00	3165.00	10.59	[redacted]
859.00	14.50	581.40	578.40	565.00	4100.00	576.03	.44	.04	.00	4100.00	11.04	[redacted]
859.00	14.50	581.40	578.40	565.00	4410.00	576.21	.49	.04	.00	4410.00	11.21	[redacted]
859.00	14.50	581.40	578.40	565.00	5160.00	576.66	.60	.05	.00	5160.00	11.66	[redacted]
860.00	1.00	0.00	0.00	565.00	3165.00	575.65	.35	.00	.01	3165.00	10.65	[redacted]
860.00	1.00	0.00	0.00	565.00	4100.00	576.14	.47	.00	.02	4100.00	11.14	[redacted]
860.00	1.00	0.00	0.00	565.00	4410.00	576.32	.41	.00	.02	4410.00	11.32	[redacted]
860.00	1.00	0.00	0.00	565.00	5160.00	576.80	.50	.00	.03	5160.00	11.80	[redacted]
910.00	50.00	0.00	0.00	564.00	3165.00	575.68	.33	.03	.01	3165.00	11.70	[redacted]
910.00	50.00	0.00	0.00	564.00	4100.00	576.21	.44	.04	.01	4100.00	12.21	[redacted]
910.00	50.00	0.00	0.00	564.00	4410.00	576.39	.48	.04	.01	4410.00	12.39	[redacted]
910.00	50.00	0.00	0.00	564.00	5160.00	576.88	.57	.04	.01	5160.00	12.88	[redacted]
911.00	1.00	583.00	578.60	564.00	3165.00	575.68	.29	.00	.03	3165.00	11.68	[redacted]
911.00	1.00	583.00	578.60	564.00	4100.00	576.17	.42	.00	.04	4100.00	12.17	[redacted]
911.00	1.00	583.00	578.60	564.00	4410.00	576.35	.47	.00	.04	4410.00	12.35	[redacted]
911.00	1.00	583.00	578.60	564.00	5160.00	576.84	.56	.00	.05	5160.00	12.84	[redacted]
921.00	10.00	583.00	578.60	564.00	3165.00	575.70	.29	.02	.00	3165.00	11.70	[redacted]
921.00	10.00	583.00	578.60	564.00	4100.00	576.20	.42	.03	.00	4100.00	12.20	[redacted]
921.00	10.00	583.00	578.60	564.00	4410.00	576.39	.46	.03	.00	4410.00	12.39	[redacted]
921.00	10.00	583.00	578.60	564.00	5160.00	576.88	.56	.04	.00	5160.00	12.88	[redacted]

Exh. 6, f)

SECTION NUMBER	CHANNEL LENGTH	MIN EL OF ROADWAY	MAX EL OF LOW CHORD	MIN EL GROUND	DISCHARGE (CFS)	CWSEL	HV	HL	OLOSS	QCH	DEPTH	TOPWID
922.00	1.00	0.00	0.00	564.00	3165.00	575.78	.23	.00	.02	3165.00		
922.00	1.00	0.00	0.00	564.00	4100.00	576.31	.34	.00	.03	4100.00		
922.00	1.00	0.00	0.00	564.00	4410.00	576.51	.37	.00	.04	4410.00		
922.00	1.00	0.00	0.00	564.00	5160.00	577.02	.45	.00	.05	5160.00		
953.00	31.00	0.00	0.00	565.10	3165.00	575.73	.35	.02	.06	3165.00	10.64	
953.00	31.00	0.00	0.00	565.10	4100.00	576.25	.52	.03	.09	4100.00	11.13	
953.00	31.00	0.00	0.00	565.10	4410.00	576.44	.57	.03	.10	4410.00	11.34	
953.00	31.00	0.00	0.00	565.10	5160.00	576.92	.71	.03	.13	5160.00	11.82	81.00
954.00	1.00	580.80	577.70	565.10	3165.00	575.65	.53	.00	.09	3165.00	10.55	67.20
954.00	1.00	580.80	577.70	565.10	4100.00	576.11	.74	.00	.14	4100.00	11.01	67.20
954.00	1.00	580.80	577.70	565.10	4410.00	576.28	.88	.00	.15	4410.00	11.18	67.20
954.00	1.00	580.80	577.70	565.10	5160.00	576.73	1.09	.00	.19	5160.00	11.63	67.20
985.00	30.50	580.80	577.70	565.10	3165.00	575.78	.51	.11	.01	3165.00	10.68	67.20
985.00	30.50	580.80	577.70	565.10	4100.00	576.32	.76	.16	.01	4100.00	11.22	67.20
985.00	30.50	580.80	577.70	565.10	4410.00	576.52	.84	.17	.01	4410.00	11.42	67.20
985.00	30.50	580.80	577.70	565.10	5160.00	577.03	1.02	.21	.02	5160.00	11.93	67.20
986.00	1.00	0.00	0.00	565.10	3165.00	576.02	.32	.00	.06	3165.00	10.92	81.00
986.00	1.00	0.00	0.00	565.10	4100.00	576.64	.47	.00	.09	4100.00	11.59	81.00
986.00	1.00	0.00	0.00	565.10	4410.00	576.94	.51	.00	.10	4410.00	11.84	81.00
986.00	1.00	0.00	0.00	565.10	5160.00	577.56	.67	.00	.12	5160.00	12.46	81.00
1036.00	50.00	0.00	0.00	566.20	3165.00	576.10	.29	.03	.01	3165.00	9.90	113.42
1036.00	50.00	0.00	0.00	566.20	4100.00	576.74	.39	.04	.02	4100.00	10.64	117.39
1036.00	50.00	0.00	0.00	566.20	4410.00	577.10	.42	.04	.03	4410.00	10.90	118.70
1036.00	50.00	0.00	0.00	566.20	5160.00	577.79	.47	.05	.04	5160.00	11.59	122.23
1736.00	700.00	0.00	0.00	565.40	3165.00	576.54	.25	.34	.01	3165.00	11.14	110.69
1736.00	700.00	0.00	0.00	565.40	4100.00	577.19	.33	.48	.02	4100.00	11.99	114.80
1736.00	700.00	0.00	0.00	565.40	4410.00	577.65	.40	.49	.02	4410.00	12.20	115.58
1736.00	700.00	0.00	0.00	565.40	5160.00	578.39	.41	.52	.02	5160.00	12.99	117.05
2436.00	700.00	0.00	0.00	564.60	3165.00	576.16	.24	.31	.00	3165.00	12.27	100.85
2436.00	700.00	0.00	0.00	564.60	4100.00	577.14	.32	.38	.00	4100.00	13.18	102.00
2436.00	700.00	0.00	0.00	564.60	4410.00	578.08	.35	.39	.00	4410.00	13.48	102.00
2436.00	700.00	0.00	0.00	564.60	5160.00	578.82	.41	.42	.00	5160.00	14.22	102.00
2736.00	300.00	0.00	0.00	569.10	1500.00	577.14	.12	.12	.03	1500.00	8.04	92.48
2736.00	300.00	0.00	0.00	569.10	1950.00	578.14	.15	.14	.05	1950.00	9.04	97.63
2736.00	300.00	0.00	0.00	569.10	2100.00	578.47	.15	.14	.06	2100.00	9.37	99.34
2736.00	300.00	0.00	0.00	569.10	2495.00	579.26	.18	.15	.07	2495.00	10.16	100.00
3436.00	700.00	0.00	0.00	569.48	1500.00	577.42	.13	.29	.00	1500.00	7.94	91.97
3436.00	700.00	0.00	0.00	569.48	1950.00	578.44	.16	.30	.00	1950.00	8.96	97.20
3436.00	700.00	0.00	0.00	569.48	2100.00	578.77	.16	.30	.00	2100.00	9.29	98.91
3436.00	700.00	0.00	0.00	569.48	2495.00	579.56	.18	.30	.00	2495.00	10.08	100.00

A

Exhibit 7

SECTION NUMBER | CHANNEL LENGTH | MIN EL OF ROADWAY | MAX EL OF LOW CHORD | MIN EL GROUND | DISCHARGE (CFS) | CWSEL | HV | HL | OLOSS | QCH | DEPTH | TOPWID

SECTION NUMBER	CHANNEL LENGTH	MIN EL OF LOAD	MAX EL OF L OB CHORD	MIN EL GROUND	SCH (CFS)	[redacted]	[redacted]HV	[redacted]PL	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]
3836.00	400.00	0.00	0.00	569.70	1500.00	577.61	.21	.23	.04	1500.00				
3836.00	400.00	0.00	0.00	569.70	1950.00	578.62	.24	.23	.04	1950.00				
3836.00	400.00	0.00	0.00	569.70	2100.00	578.95	.25	.23	.04	2100.00				
3836.00	400.00	0.00	0.00	569.70	2495.00	579.73	.27	.22	.03	2495.00				
4311.00	475.00	0.00	0.00	569.90	1500.00	577.99	.19	.36	.00	1500.00				
4311.00	475.00	0.00	0.00	569.90	1950.00	578.99	.23	.35	.00	1950.00				
4311.00	475.00	0.00	0.00	569.90	2100.00	579.32	.24	.35	.00	2100.00				
4311.00	475.00	0.00	0.00	569.90	2495.00	580.09	.26	.34	.00	2495.00				
4786.00	475.00	0.00	0.00	570.10	1500.00	578.32	.13	.25	.02	1500.00	8.22	87.36		
4786.00	475.00	0.00	0.00	570.10	1950.00	579.35	.16	.27	.02	1950.00	9.29	97.98		
4786.00	475.00	0.00	0.00	570.10	2100.00	579.69	.17	.28	.02	2100.00	9.59	105.02		
4786.00	475.00	0.00	0.00	570.10	2495.00	580.47	.18	.27	.02	2495.00	10.37	107.00		
4825.00	39.00	0.00	0.00	570.80	1500.00	578.36	.12	.02	.00	1500.00	7.56	98.00		
4825.00	39.00	0.00	0.00	570.80	1950.00	579.40	.14	.02	.01	1950.00	8.60	98.00		
4825.00	39.00	0.00	0.00	570.80	2100.00	579.73	.15	.02	.01	2100.00	8.93	98.00		
4825.00	39.00	0.00	0.00	570.80	2495.00	580.50	.17	.02	.00	2495.00	9.70	98.00		
4846.00	21.00	579.40	578.30	570.80	1500.00	578.40	.11	.04	0.00	1500.00	7.60	98.00		
4846.00	21.00	579.40	578.30	570.80	1950.00	579.52	.13	.12	0.00	1950.00	8.72	98.00		
4846.00	21.00	579.40	578.30	570.80	2100.00	579.83	.14	.10	0.00	2100.00	9.03	98.00		
4846.00	21.00	579.40	578.30	570.80	2495.00	580.50	.17	0.00	0.00	2495.00	9.70	98.00		
4847.00	1.00	0.00	0.00	570.80	1500.00	578.40	.11	.00	.00	1500.00	7.60	98.00		
4847.00	1.00	0.00	0.00	570.80	1950.00	579.52	.13	.00	.00	1950.00	8.72	98.00		
4847.00	1.00	0.00	0.00	570.80	2100.00	579.83	.14	.00	.00	2100.00	9.03	98.00		
4847.00	1.00	0.00	0.00	570.80	2495.00	580.50	.17	.00	.00	2495.00	9.70	98.00		
5436.00	589.00	0.00	0.00	570.64	1500.00	578.69	.16	.26	.02	1500.00	8.02	88.72		
5436.00	589.00	0.00	0.00	570.64	1950.00	579.75	.18	.27	.02	1950.00	9.12	93.94		
5436.00	589.00	0.00	0.00	570.64	2100.00	580.07	.19	.27	.02	2100.00	9.43	95.45		
5436.00	589.00	0.00	0.00	570.64	2495.00	580.76	.22	.28	.03	2495.00	10.12	98.72		
5936.00	500.00	0.00	0.00	570.50	1500.00	578.94	.14	.25	.01	1500.00	8.44	90.75		
5936.00	500.00	0.00	0.00	570.50	1950.00	580.04	.17	.25	.01	1950.00	9.54	95.99		
5936.00	500.00	0.00	0.00	570.50	2100.00	580.35	.17	.25	.01	2100.00	9.85	97.50		
5936.00	500.00	0.00	0.00	570.50	2495.00	581.05	.19	.26	.01	2493.32	10.55	137.93		
6416.00	480.00	0.00	0.00	570.33	1500.00	579.18	.22	.28	.04	1500.00	8.85	72.17		
6416.00	480.00	0.00	0.00	570.33	1950.00	580.29	.26	.28	.05	1950.00	9.93	77.22		
6416.00	480.00	0.00	0.00	570.33	2100.00	580.64	.27	.28	.05	2100.00	10.25	78.69		
6416.00	480.00	0.00	0.00	570.33	2495.00	581.29	.31	.29	.06	2495.00	10.96	85.09		
6786.00	370.00	0.00	0.00	570.20	1500.00	579.47	.19	.25	.01	1500.00	9.27	74.09		
6786.00	370.00	0.00	0.00	570.20	1950.00	580.56	.22	.25	.01	1950.00	10.36	79.16		
6786.00	370.00	0.00	0.00	570.20	2100.00	580.88	.24	.26	.01	2100.00	10.68	80.64		
6786.00	370.00	0.00	0.00	570.20	2495.00	581.64	.28	.30	.01	2495.00	11.44	96.23		

B

C

D

L

Y

Exhibit 1
35 of 41

SECTION NUMBER	CHANNEL LENGTH	MIN EL OF ROADWAY	MAX EL OF LOW CHORD	MIN EL GROUND	DISCHARGE (CFS)	CWSEL	HV	HL			
6835.00	49.00	0.00	0.00	571.57	1500.00	579.44	.[illegible]	.04	.[illegible]	[illegible]	
6835.00	49.00	0.00	0.00	571.57	1950.00	580.54	.36	.04	.[illegible]	[illegible]	
6835.00	49.00	0.00	0.00	571.57	2100.00	580.85	.37	.04	.[illegible]	[illegible]	
6835.00	49.00	0.00	0.00	571.57	2495.00	581.82	.40	.05	.[illegible]	[illegible]	
6836.00	1.00	0.00	0.00	571.60	1500.00	579.65	.16	.00	.05	1500.00	[illegible]
6836.00	1.00	0.00	0.00	571.60	1950.00	580.75	.20	.00	.05	1950.00	9.15
6836.00	1.00	0.00	0.00	571.60	2100.00	581.06	.21	.01	.05	2100.00	[illegible]
6836.00	1.00	0.00	0.00	571.60	2495.00	581.82	.24	.00	.05	2495.00	10.20
6916.00	80.00	583.00	578.30	571.60	1500.00	579.86	.15	.20	0.00	1500.00	8.25
6916.00	80.00	583.00	578.30	571.60	1950.00	581.17	.17	.40	0.00	1950.00	9.57
6916.00	80.00	583.00	578.30	571.60	2100.00	581.57	.18	.48	0.00	2100.00	9.97
6916.00	80.00	583.00	578.30	571.60	2495.00	582.60	.21	.73	0.00	2495.00	11.00
6917.00	1.00	0.00	0.00	571.60	1500.00	579.79	.28	.00	.07	1500.00	8.19
6917.00	1.00	0.00	0.00	571.60	1950.00	581.11	.29	.00	.06	1950.00	9.51
6917.00	1.00	0.00	0.00	571.60	2100.00	581.52	.30	.00	.06	2100.00	9.92
6917.00	1.00	0.00	0.00	571.60	2495.00	582.53	.31	.00	.05	2495.00	10.95
7436.00	519.00	0.00	0.00	571.20	1500.00	580.33	.20	.43	.02	1500.00	[illegible]
7436.00	519.00	0.00	0.00	571.20	1950.00	581.53	.22	.39	.02	1950.00	10.39
7436.00	519.00	0.00	0.00	571.20	2100.00	581.99	.23	.38	.02	2100.00	10.79
7436.00	519.00	0.00	0.00	571.20	2495.00	583.03	.23	.38	.02	2495.00	11.83
7936.00	500.00	0.00	0.00	570.80	1500.00	580.61	.18	.29	.01	1500.00	[illegible]
7936.00	500.00	0.00	0.00	570.80	1950.00	581.69	.21	.29	.00	1950.00	11.09
7936.00	500.00	0.00	0.00	570.80	2100.00	582.24	.22	.29	.00	2100.00	11.64
7936.00	500.00	0.00	0.00	570.80	2495.00	583.31	.23	.29	.00	2495.00	12.51
8536.00	600.00	0.00	0.00	570.90	1500.00	580.47	.16	.29	.01	1500.00	10.07
8536.00	600.00	0.00	0.00	570.90	1950.00	582.22	.17	.28	.01	1911.49	11.32
8536.00	600.00	0.00	0.00	570.90	2100.00	582.62	.16	.27	.02	1994.42	11.72
8536.00	600.00	0.00	0.00	570.90	2495.00	583.67	.14	.23	.03	2141.66	12.77
9136.00	600.00	0.00	0.00	570.90	1500.00	581.21	.14	.25	.01	1497.84	10.34
9136.00	600.00	0.00	0.00	570.90	1950.00	582.48	.14	.22	.01	1846.95	11.58
9136.00	600.00	0.00	0.00	570.90	2100.00	582.86	.14	.21	.01	1943.91	11.96
9136.00	600.00	0.00	0.00	570.90	2495.00	583.84	.14	.17	.00	2174.64	12.94
9586.00	450.00	0.00	0.00	570.94	1500.00	581.41	.14	.17	.00	1498.53	10.48
9586.00	450.00	0.00	0.00	570.94	1950.00	582.63	.16	.15	.01	1916.40	11.70
9586.00	450.00	0.00	0.00	570.94	2100.00	583.00	.16	.15	.01	2040.15	12.06
9586.00	450.00	0.00	0.00	570.94	2495.00	583.95	.16	.13	.01	2312.51	13.02
9596.00	10.00	0.00	0.00	570.98	1500.00	581.40	.18	.01	.02	1493.37	10.42
9596.00	10.00	0.00	0.00	570.98	1950.00	582.65	.15	.00	.00	1801.51	11.67
9596.00	10.00	0.00	0.00	570.98	2100.00	583.03	.14	.00	.01	1882.08	12.05
9596.00	10.00	0.00	0.00	570.98	2495.00	584.01	.12	.00	.01	2084.12	13.03

Exhibit 9
36 of 41

SECTION NUMBER	CHANNEL LENGTH	MIN EL OF ROADWAY	MAX EL OF LOW CHORD	MIN EL GROUND	DISCHARGE (CFS)	CWSEL	HV	HL			

SECTION NUMBER	CHANNEL LENGTH	MIN ROADWAY	OF LOW CHORD	EL MIN GROUND	DISCHARGE (CFS)	CWSEL	HV	HL	LOSS			
10286.00	690.00	0.00	0.00	571.00	1500.00	581.90	.13	.45	.01			
10286.00	690.00	0.00	0.00	571.00	1950.00	583.02	.12	.34	.01			
10286.00	690.00	0.00	0.00	571.00	2100.00	583.36	.12	.31	.01			
10286.00	690.00	0.00	0.00	571.00	2495.00	584.26	.11	.24	.00			
10336.00	50.00	0.00	0.00	572.50	1500.00	581.91	.17	.03	.02			
10336.00	50.00	0.00	0.00	572.50	1950.00	583.01	.19	.02	.04			
10336.00	50.00	0.00	0.00	572.50	2100.00	583.34	.20	.02	.04			
10336.00	50.00	0.00	0.00	572.50	2495.00	584.23	.21	.02	.05			
10636.00	300.00	0.00	0.00	572.47	1500.00	582.06	.18	.15	.00	1500.00		
10636.00	300.00	0.00	0.00	572.47	1950.00	583.17	.20	.19	.01	1950.00		
10636.00	300.00	0.00	0.00	572.47	2100.00	583.53	.20	.19	.00	2100.00		
10636.00	300.00	0.00	0.00	572.47	2495.00	584.41	.20	.18	.00	2495.00		
11536.00	900.00	0.00	0.00	572.40	1500.00	582.54	.15	.44	.01	1500.00		
11536.00	900.00	0.00	0.00	572.40	1950.00	584.04	.13	.75	.02	1950.00		
11536.00	900.00	0.00	0.00	572.40	2100.00	584.31	.12	.79	.02	2100.00		
11536.00	900.00	0.00	0.00	572.40	2495.00	585.11	.12	.58	.02	2495.00		

SECTION NUMBER	DISCHARGE CFS	CWSEL	CWSEL DIFF EACH	CWSEL DIFF EACH SECTION	CWSEL-VSEL	TOPWID	T.W. DIFF	LENGTH
1.000	3165.000	574.900	0.000	0.000	0.000	89.833	0.000	-0.000
1.000	4100.000	574.900	0.000	0.000	0.000	89.833	0.000	-0.000
1.000	4410.000	574.900	0.000	0.000	0.000	89.833	0.000	-0.000
1.000	5160.000	574.900	0.000	0.000	0.000	89.833	0.000	-0.000
30.000	3165.000	574.919	0.000	.019	0.000	89.979	-0.000	29.000
30.000	4100.000	574.934	.015	.034	0.000	90.077	-.098	29.000
30.000	4410.000	574.941	.008	.041	0.000	90.111	-.137	29.000
30.000	5160.000	574.961	.020	.061	0.000	90.272	-.293	29.000
60.000	3165.000	574.939	0.000	.019	0.000	90.123	0.000	30.000
60.000	4100.000	574.978	.041	.059	0.000	90.370	-.241	30.000
60.000	4410.000	574.983	.014	.043	0.000	90.461	-.333	30.000
60.000	5160.000	575.028	.046	.087	0.000	90.898	-.769	30.000
61.000	3165.000	574.909	0.000	-.030	0.000	82.905	0.000	1.000
61.000	4100.000	574.919	.010	-.052	0.000	82.985	-.040	1.000
61.000	4410.000	574.923	.005	-.061	0.000	83.023	-.117	1.000
61.000	5160.000	574.942	.019	-.068	0.000	83.184	-.276	1.000
136.000	3165.000	575.000	0.000	.041	0.000	93.663	0.000	75.000
136.000	4100.000	575.085	.085	.167	0.000	84.376	-.709	75.000
136.000	4410.000	575.122	.037	.200	0.000	84.688	-1.060	75.000
136.000	5160.000	575.242	.119	.300	0.000	85.684	-2.016	75.000
137.000	3165.000	575.046	0.000	.085	0.000	91.381	0.000	1.000
137.000	4100.000	575.236	.190	.151	0.000	92.635	-1.255	1.000
137.000	4410.000	575.300	.064	.178	0.000	93.172	-1.791	1.000
137.000	5160.000	575.495	.195	.254	0.000	94.127	-2.747	1.000
187.000	3165.000	575.095	0.000	.009	0.000	88.947	0.000	50.000
187.000	4100.000	575.251	.155	.015	0.000	90.512	-1.564	50.000
187.000	4410.000	575.318	.066	.018	0.000	91.177	-2.229	50.000
187.000	5160.000	575.510	.200	.023	0.000	92.350	-3.403	50.000
362.000	3165.000	575.377	0.000	.283	0.000	143.475	0.000	175.000
362.000	4100.000	575.724	.346	.472	0.000	145.168	-1.693	175.000
362.000	4410.000	575.862	.138	.544	0.000	145.843	-2.368	175.000
362.000	5160.000	576.244	.383	.726	0.000	147.720	-4.245	175.000

	737.000	4100.000	575.887	.397	.163	0.000	121.404	0.000	
[redacted]	737.000	4410.000	576.040	.495	.179	0.000	122.393	-1.000	
	737.000	5160.000	576.454	.413	.209	0.000	113.394	-7.000	
	787.000	3165.000	575.472	0.000	-.018	0.000	106.600	0.000	1.000
	787.000	4100.000	575.958	.387	-.029	0.000	106.600	0.000	1.000
	787.000	4410.000	576.008	.149	-.032	0.000	106.600	0.000	1.000
	787.000	5160.000	576.412	.404	-.042	0.000	106.600	0.000	50.000
	788.000	3165.000	575.442	0.000	-.030	0.000	97.000	0.000	1.000
	788.000	4100.000	575.814	.372	-.045	0.000	104.000	-7.000	1.000
	788.000	4410.000	575.958	.145	-.049	0.000	104.000	-7.000	1.000
	788.000	5160.000	576.353	.394	-.059	0.000	104.000	-7.000	1.000
	797.000	3165.000	575.465	0.000	.023	0.000	97.000	0.000	9.000
	797.000	4100.000	575.851	.386	.037	0.000	104.000	-7.000	9.000
	797.000	4410.000	576.001	.151	.043	0.000	104.000	-7.000	9.000
	797.000	5160.000	576.404	.403	.052	0.000	104.000	-7.000	9.000
	798.000	3165.000	575.553	0.000	.088	0.000	106.600	0.000	1.000
	798.000	4100.000	575.984	.431	.134	0.000	106.600	0.000	1.000
	798.000	4410.000	576.147	.163	.146	0.000	106.600	-0.000	1.000
	798.000	5160.000	576.583	.435	.178	0.000	106.600	0.000	1.000
	844.000	3165.000	575.582	0.000	.029	0.000	105.391	0.000	46.000
	844.000	4100.000	576.027	.445	.043	0.000	108.181	-2.789	46.000
	844.000	4410.000	576.195	.168	.048	0.000	108.983	-3.592	46.000
	844.000	5160.000	576.641	.446	.059	0.000	109.000	-3.609	46.000
	845.000	3165.000	575.561	0.000	-.022	0.000	98.255	0.000	1.000
	845.000	4100.000	575.945	.384	-.033	0.000	100.975	-2.720	1.000
	845.000	4410.000	576.150	.204	-.038	0.000	101.751	-3.595	1.000
	845.000	5160.000	576.596	.447	-.045	0.000	102.001	-3.745	1.000
	859.000	3165.000	575.590	0.000	.029	0.000	94.400	0.000	14.500
	859.000	4100.000	576.040	.451	.045	0.000	101.263	-2.863	14.500
	859.000	4410.000	576.210	.170	.051	0.000	102.001	-3.600	14.500
	859.000	5160.000	576.661	.451	.061	0.000	102.000	-3.600	14.500
	860.000	3165.000	575.653	0.000	.064	0.000	105.835	0.000	1.000
	860.000	4100.000	576.137	.484	.097	0.000	108.773	-2.935	1.000
	860.000	4410.000	576.318	.181	.104	0.000	109.000	-3.162	1.000
	860.000	5160.000	576.797	.479	.135	0.000	109.000	-3.162	1.000
	910.000	3165.000	575.702	0.000	.049	0.000	107.000	0.000	50.000
	910.000	4100.000	576.291	.589	.070	0.000	107.000	0.000	50.000
	910.000	4410.000	576.495	.187	.076	0.000	107.000	0.000	50.000
	910.000	5160.000	576.883	.389	.085	0.000	107.000	0.000	50.000
	911.000	3165.000	575.676	0.000	-.027	0.000	105.000	0.000	1.000
	911.000	4100.000	576.170	.494	-.038	0.000	105.000	0.000	1.000
	911.000	4410.000	576.354	.184	-.041	0.000	105.000	0.000	1.000
	911.000	5160.000	576.839	.485	-.047	0.000	105.000	0.000	1.000
	921.000	3165.000	575.700	0.000	.024	0.000	105.000	-0.000	10.000
	921.000	4100.000	576.204	.504	.034	0.000	105.000	0.000	10.000
	921.000	4410.000	576.390	.186	.038	0.000	105.000	0.000	10.000
	921.000	5160.000	576.869	.479	.048	0.000	105.000	-0.000	10.000
	922.000	3165.000	575.770	0.000	.070	0.000	107.000	0.000	1.000
	922.000	4100.000	576.313	.543	.119	0.000	107.000	0.000	1.000
	922.000	4410.000	576.519	.206	.131	0.000	107.000	0.000	1.000
	922.000	5160.000	577.120	.601	.141	0.000	107.000	0.000	1.000
	953.000	3165.000	575.735	0.000	-.041	0.000	105.000	0.000	1.000

Exhibit 7
38 of 41

953.000	4410.000	576.436	.189	-.074	0.000	81.000	0.000	[illegible]	
[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	
954.000	3165.000	575.646	0.000	-.089	0.000	67.200	0.000	[illegible]	
954.000	4100.000	576.112	.466	-.136	0.000	67.200	0.000	[illegible]	
954.000	4410.000	576.284	.172	-.152	0.000	67.200	0.000	[illegible]	
954.000	5160.000	576.733	.450	-.190	0.000	67.200	0.000	[illegible]	
985.000	3165.000	575.776	0.000	.131	0.000	67.200	0.000	[illegible]	
985.000	4100.000	576.317	.541	.205	0.000	67.200	0.000	[illegible]	
985.000	4410.000	576.515	.198	.232	0.000	67.200	0.000	[illegible]	
985.000	5160.000	577.028	.513	.295	0.000	67.200	0.000	[illegible]	
986.000	3165.000	576.021	0.000	.245	0.000	81.000	0.000	1.000	
986.000	4100.000	576.693	.672	.376	0.000	81.000	0.000	1.000	
986.000	4410.000	576.936	.243	.421	0.000	81.000	0.000	1.000	
986.000	5160.000	577.556	.620	.528	0.000	81.000	0.000	1.000	
1036.000	3165.000	576.100	0.000	.079	0.000	113.418	0.000	50.000	
1036.000	4100.000	576.838	.738	.145	0.000	117.340	-3.922	50.000	
1036.000	4410.000	577.105	.267	.169	0.000	118.599	-5.180	50.000	
1036.000	5160.000	577.792	.688	.236	0.000	122.233	-8.815	50.000	
1736.000	3165.000	576.545	0.000	.444	0.000	110.653	0.000	700.000	
1736.000	4100.000	577.388	.843	.550	0.000	114.797	-4.144	700.000	
1736.000	4410.000	577.679	.291	.574	0.000	115.581	-4.928	700.000	
1736.000	5160.000	578.394	.715	.681	0.000	117.049	-6.396	700.000	
2436.000	3165.000	576.872	0.000	.327	0.000	100.852	0.000	700.000	
2436.000	4100.000	577.781	.910	.394	0.000	101.999	-1.147	700.000	
2436.000	4410.000	578.085	.304	.406	0.000	101.999	-1.147	700.000	
2436.000	5160.000	578.813	.733	.474	0.000	101.999	-1.147	700.000	
2736.000	1500.000	577.137	0.000	.265	0.000	92.478	0.000	300.000	
2736.000	1950.000	578.139	1.001	.338	0.000	97.629	-5.151	300.000	
2736.000	2100.000	578.471	.332	.359	0.000	99.136	-6.658	300.000	
2736.000	2495.000	579.263	.792	.445	0.000	99.999	-7.521	300.000	
3436.000	1500.000	577.421	0.000	.284	0.000	91.970	0.000	700.000	
3436.000	1950.000	578.445	1.024	.296	0.000	97.198	-5.228	700.000	
3436.000	2100.000	578.788	.343	.297	0.000	98.907	-6.938	700.000	
3436.000	2495.000	579.558	.770	.295	0.000	99.999	-8.029	700.000	
3836.000	1500.000	577.507	0.000	.156	0.000	82.235	0.000	400.000	
3836.000	1950.000	578.521	1.013	.145	0.000	86.763	-4.529	400.000	
3836.000	2100.000	578.951	.430	.183	0.000	87.667	-5.432	400.000	
3836.000	2495.000	579.734	.784	.176	0.000	89.802	-7.567	400.000	
4311.000	1500.000	577.984	0.000	.361	0.000	83.071	0.000	475.000	
4311.000	1950.000	578.994	1.009	.374	0.000	87.256	-4.185	475.000	
4311.000	2100.000	579.317	.323	.367	0.000	88.146	-5.045	475.000	
4311.000	2495.000	580.092	.775	.358	0.000	89.999	-6.998	475.000	
4786.000	1500.000	578.323	0.000	.338	0.000	87.322	0.000	475.000	
4786.000	1950.000	579.352	1.029	.358	0.000	97.980	-10.658	475.000	
4786.000	2100.000	579.686	.334	.369	0.000	105.019	-17.698	475.000	
4786.000	2495.000	580.466	.780	.373	0.000	106.499	-19.677	475.000	
4825.000	1500.000	578.359	0.000	.335	0.000	97.999	0.000	39.000	
4825.000	1950.000	579.395	1.036	.343	0.000	97.999	-.000	39.000	
4825.000	2100.000	579.729	.333	.343	0.000	98.000	-.000	39.000	
4825.000	2495.000	580.503	.775	.347	0.000	98.000	-.000	39.000	
4846.000	1500.000	578.402	0.000	.043	0.000	97.999	0.000	21.000	

Exhibit 7
39 of 41

	4846.000	2100.000	579.833	.716	.104	0.000	98.000	-.000	21.000
[redacted]	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]
	4847.000	1500.000	578.402	0.000	.000	0.000	97.999	0.000	1.000
	4847.000	1950.000	579.517	1.115	.000	0.000	98.000	-.000	1.000
	4847.000	2100.000	579.833	.316	.000	0.000	98.000	-.000	1.000
	4847.000	2495.000	580.350	.517	.000	0.000	98.000	-.000	1.000
	5436.000	1500.000	578.656	0.000	.254	0.000	88.720	0.000	500.000
	5436.000	1950.000	579.758	1.102	.241	0.000	93.938	-5.219	500.000
	5436.000	2100.000	580.074	.316	.241	0.000	95.450	-6.731	500.000
	5436.000	2495.000	580.758	.684	.254	0.000	98.720	-10.000	500.000
	5936.000	1500.000	579.941	0.000	.284	0.000	90.748	0.000	500.000
E	5936.000	1950.000	580.037	1.096	.279	0.000	95.988	-5.240	500.000
	5936.000	2100.000	580.354	.317	.280	0.000	97.504	-6.756	500.000
	5936.000	2495.000	581.051	.697	.294	0.000	137.931	-47.183	500.000
	6416.000	1500.000	579.177	0.000	.236	0.000	72.169	0.000	480.000
	6416.000	1950.000	580.265	1.088	.228	0.000	77.216	-5.047	480.000
	6416.000	2100.000	580.582	.317	.227	0.000	78.686	-6.517	480.000
	6416.000	2495.000	581.289	.708	.238	0.000	85.087	-12.918	480.000
	6786.000	1500.000	579.467	0.000	.290	0.000	74.094	0.000	370.000
F	6786.000	1950.000	580.561	1.093	.296	0.000	79.161	-5.067	370.000
	6786.000	2100.000	580.881	.320	.299	0.000	80.645	-6.551	370.000
	6786.000	2495.000	581.639	.759	.350	0.000	96.230	-22.136	370.000
	6835.000	1500.000	579.445	0.000	-.019	0.000	67.640	0.000	49.000
	6835.000	1950.000	580.536	1.092	-.024	0.000	72.700	-5.060	49.000
	6835.000	2100.000	580.856	.320	-.025	0.000	74.181	-6.541	49.000
	6835.000	2495.000	581.615	.759	-.024	0.000	77.698	-10.059	49.000
	6836.000	1500.000	579.655	0.000	.210	0.000	73.000	0.000	1.000
	6836.000	1950.000	580.745	1.091	.209	0.000	73.000	0.000	1.000
	6836.000	2100.000	581.065	.320	.209	0.000	73.000	0.000	1.000
	6836.000	2495.000	581.824	.759	.209	0.000	73.000	0.000	1.000
	6916.000	1500.000	579.860	0.000	.205	0.000	74.000	0.000	80.000
	6916.000	1950.000	581.168	1.308	.202	0.000	73.000	0.000	80.000
G	6916.000	2100.000	581.574	.406	.209	0.000	73.000	0.000	80.000
	6916.000	2495.000	582.596	1.022	.772	0.000	73.000	0.000	80.000
	6917.000	1500.000	579.794	0.000	-.166	0.000	69.129	0.000	1.000
	6917.000	1950.000	581.108	1.314	-.159	0.000	75.211	-6.090	1.000
	6917.000	2100.000	581.517	.409	-.157	0.000	77.184	-7.984	1.000
	6917.000	2495.000	582.545	1.029	-.150	0.000	84.517	-15.496	1.000
	7436.000	1500.000	580.331	0.000	.237	0.000	73.462	0.000	519.000
	7436.000	1950.000	581.592	1.261	.444	0.000	79.306	-5.845	519.000
	7436.000	2100.000	581.986	.394	.459	0.000	81.134	-7.672	519.000
	7436.000	2495.000	583.026	1.040	.491	0.000	99.993	-26.537	519.000
	7936.000	1500.000	580.647	0.000	.318	0.000	69.404	0.000	500.000
H	7936.000	1950.000	581.894	1.248	.302	0.000	75.353	-5.949	500.000
	7936.000	2100.000	582.284	.389	.297	0.000	77.210	-7.806	500.000
	7936.000	2495.000	583.313	1.030	.287	0.000	75.993	-10.595	500.000
	8536.000	1500.000	580.965	0.000	.314	0.000	74.414	0.000	600.000
	8536.000	1950.000	582.224	1.259	.329	0.000	249.209	-174.080	600.000
	8536.000	2100.000	582.622	.398	.334	0.000	249.909	-174.080	600.000
	8536.000	2495.000	583.668	1.046	.354	0.000	249.393	-176.090	600.000
I	9136.000	1500.000	581.237	-.139	.271	0.000	143.183	0.000	500.000
	9136.000	1950.000	582.483	1.246	.259	0.000	152.799	-24.133	600.000
	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]	[redacted]

					0.000	169.999		
9586.000	1500.000	581.[illegible]	[illegible].00[illegible]	[illegible]	0.000	43.419	0.[illegible]	[illegible]
[illegible]586.000	[illegible]000	582.[illegible]	1.218	.147	0.000	134.701	-6[illegible].[illegible]	[illegible].0
9586.000	2100.000	582.946	.366	.139	0.000	158.126	-6[illegible].[illegible]	[illegible].0
9586.000	2495.000	583.955	.979	.119	0.000	199.[illegible]	-[illegible].[illegible]	
9596.000	1500.000	581.397	0.000	-.015	0.000	142.[illegible]	0.[illegible]	[illegible].000
9596.000	1950.000	582.646	1.249	.016	0.000	199.999	-57.[illegible]	[illegible].000
9596.000	2100.000	583.029	.383	.033	0.000	199.999	-57.330	[illegible].000
9596.000	2495.000	584.008	.979	.053	0.000	199.999	-57.[illegible]	[illegible].000
10286.000	1500.000	581.904	0.000	.507	0.000	199.[illegible]	0.000	[illegible].000
10286.000	1950.000	583.020	1.116	.374	0.000	199.999	-.000	[illegible].000
10286.000	2100.000	583.361	.341	.333	0.000	199.999	-.000	690.000
10286.000	2495.000	584.262	.901	.255	0.000	199.999	-.000	690.000
10336.000	1500.000	581.910	0.000	.000	0.000	94.999	0.000	50.000
10336.000	1950.000	583.005	1.095	-.015	0.000	94.999	-.000	50.000
10336.000	2100.000	583.341	.335	-.020	0.000	94.999	-.000	50.000
10336.000	2495.000	584.229	.889	-.053	0.000	94.999	-.000	50.000
10636.000	1500.000	582.050	0.000	.146	0.000	73.389	0.000	300.000
10636.000	1950.000	583.190	1.134	.144	0.000	120.889	-47.500	300.000
10636.000	2100.000	583.526	.336	.145	0.000	125.353	-52.464	300.000
10636.000	2495.000	584.420	.900	.136	0.000	142.354	-68.965	300.000
11536.000	1500.000	582.536	0.000	.480	0.000	75.398	0.000	900.000
11536.000	1950.000	584.040	1.504	.450	0.000	191.552	-115.554	900.000
11536.000	2100.000	584.332	.292	.807	0.000	196.314	-120.916	900.000
11536.000	2495.000	585.105	.773	.660	0.000	199.999	-124.001	900.000

DATA FOR LAST CROSS SECTIO

PROFILE	TYPE ENC	TARGET	TOP WIDTH AREA-ACRES	TOP WIDTH OFF
1	0.000	200.000	25.525	.000
2	0.000	200.000	31.[illegible]	.061
3	0.000	200.000	32.[illegible]	.[illegible]
4	0.000	200.000	[illegible].[illegible]	.1[illegible]

Exhibit 1
41 of 41

CITY OF LINCOLN PARK, MICHIGAN

NORTH BRANCH ECORSE CREEK

EXHIBIT 8

HEC-2 Backwater Analysis

with Cross Section Plots

(See Separate Folder)

CITY OF LINCOLN PARK, MICHIGAN

NORTH BRANCH ECORSE CREEK

EXHIBIT 9

Stream Profile

00BREAK00

1) COUNTY: Wayne

2) STUDY NAME: City of Lincoln Park

3) WATERCOURSE: North Branch Ecorse Creek

4) DOCUMENT TYPE: Summary

00BREAK00

```
**************************************************
  HEC2 RELEASE DATED NOV 76 UPDATED FEB 1977
  ERROR CORR -  01
  MODIFICATION -  50,51,52
**************************************************

C
T1 NORTH BRANCH ECORSE CR. FIS HUD 2010 07 LINCOLN PARK
T2 30 YR FLOW
T5      N.BR.ECORSE CR.LINC.PK.

J1  ICHECK     INQ        NINV       IDIR       STRT       METRIC     HVINS      Q          WSEL       FQ
        0.        2.         0.         0.   0.300000       0.00       0.0        0.      582.060      0.000

J2  NPROF      IPLOT      PRFVS      XSECV      XSECH      FN         ALLDC      IBW        CHNIM      ITRACE
    1.000      0.000     -1.000      0.000      0.000      0.000      0.000      0.000      0.000      0.000

J3  VARIABLE CODES FOR SUMMARY PRINTOUT
  150.000    201.000      0.000      0.000      0.000      0.000      0.000      0.000      0.000      0.000

J5  LPRNT      NUMSEC                        ********REQUESTED SECTION NUMBERS********
    -10.000    -10.000      0.000      0.000      0.000      0.000      0.000      0.000      0.000      0.000
J1      0.055      1.015      0.353      0.300      0.500      0.000      5.010      5.000      0.000      0.000
QT      5.000    850.000   1230.000   1410.000   1410.000   1840.000      0.000      0.000      0.000      0.000

                VALLEY SECT. FOR  Jun ECORSE FIS

X1  10636.000     27.000    683.770    935.000      0.100      1.000      1.000      5.000      0.000      0.000
XS      0.000      0.000      0.000    695.000      0.000    800.000      0.000      0.000      0.000      0.000
GR    582.670      0.000    582.670     55.000    584.370    155.000    585.670    251.000    586.070    355.000
GR    566.270    455.000    585.470    555.000    584.570    655.000    583.370    677.000    574.870    697.000
GR    573.770    700.000    573.070    705.000    572.470    711.000    572.470    715.000    575.670    720.000
GR    574.570    725.000    575.670    727.000    575.970    737.000    582.670    735.000    575.370    753.000
GR    583.270    955.000    583.670   1555.300    582.270   1041.000    582.370   1155.000    585.370   1255.000
GR    583.070   1355.000    583.070   1455.300      0.000      0.000      0.000      0.000      0.000      0.000
NC      0.000      0.000      0.000      0.100      0.300      0.000      0.000      0.000      0.000      0.000
NH      7.000      0.200    340.000      0.700    680.000      1.000    900.000      0.050    983.300      0.035
SX   1054.000      0.100   1375.000      0.500   1970.000      1.000      0.000      0.000      0.000      0.000

                VALLEY SECTION

XT  11556.000     15.000    983.000   1054.000    900.000    900.000    900.000      0.000      0.000      0.000
NH      0.000      0.000      0.000    980.300      0.000   1110.300      0.200      0.000      0.300      0.000
GR    585.000      0.000    582.800    340.000    568.000    680.000    587.000    930.300    586.600    910.000
GR    585.200    983.000    579.600   1054.200    572.000   1110.300    575.400   1024.300    575.400   1043.300
GR    583.500   1054.000    584.200   1118.000    583.000   1210.000    584.000   1375.000    585.000   1970.000
NC      0.000      0.000      0.000      0.300      0.500      0.000      0.000      0.000      0.000      0.000
NH      5.000      0.200    250.000      0.300    920.000      0.000    994.000      0.035   1046.000      0.500
SX   1350.000      0.000      0.000      0.000      0.000      0.000      0.000      0.000      0.000      0.000

                VALLEY SECT. 50' D/S OF AUSTIN

XT  12274.300     11.000    994.000   1045.000    730.000    738.000    738.000      4.000      5.000      1.000
```

PRINTED IN U.S.A.
FORM 1411.00 PRINTED BY ROTARY MANIFOLD FORMS

X3	0.000	0.000	0.000	900.000	0.000	1050.000	0.000	0.000	0.000	0.000
X4	1.000	582.000	920.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
GR	585.000	0.000	583.300	250.000	580.000	650.000	582.400	980.000	575.200	994.000
GR	575.500	1020.000	574.900	1046.000	581.800	1065.000	580.000	1130.000	580.000	1250.000
GR	585.000	1580.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
NH	5.000	0.200	250.000	0.300	930.000	0.050	1014.000	0.035	1064.100	0.500
NH	1600.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000

D/S FACE OF AUSTIN

X1	12324.000	22.000	1014.000	1064.100	50.000	50.000	50.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	920.000	0.000	1065.000	0.000	583.300	583.300	0.000
GR	585.000	0.000	583.300	250.000	583.600	430.000	580.400	930.000	582.400	1000.000
GR	574.100	1014.000	574.100	1014.100	574.100	1030.000	574.100	1030.100	574.100	1031.000
GR	574.100	1031.100	573.600	1039.000	573.800	1047.000	573.800	1047.100	573.800	1048.000
GR	573.800	1048.100	573.800	1064.000	573.800	1064.100	581.600	1083.000	583.100	1140.000
GR	583.400	1240.000	584.600	1600.000	0.000	0.000	0.000	0.000	0.000	0.000
NH	5.000	0.200	250.000	0.300	930.000	0.050	1014.000	0.025	1064.100	0.500
NH	1600.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000

1' INSIDE D/S FACE OF AUSTIN BRIDGE

X1	12325.000	0.000	0.000	0.000	1.000	1.000	1.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	920.000	0.000	1065.000	0.000	583.300	583.300	0.000
BT	20.000	0.000	585.000	0.000	250.000	583.300	0.000	430.000	583.600	0.000
BT	930.000	580.400	0.000	1014.000	583.300	574.100	1014.100	583.300	581.800	1030.000
BT	583.500	581.800	1030.700	583.300	574.100	1047.000	583.300	574.100	1031.100	583.300
BT	581.800	1047.000	583.300	581.800	1047.100	583.500	573.800	1048.000	583.300	573.800
BT	1064.100	583.300	581.800	1064.000	583.300	581.800	1064.100	583.300	573.800	1063.000
BT	581.600	0.000	1140.000	583.100	0.000	1240.000	583.400	0.000	1600.000	584.600
BT	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
NH	5.000	0.200	250.000	0.300	930.000	0.050	1014.000	0.025	1064.100	0.500
[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]

1' INSIDE D/S FACE OF AUSTIN BRIDGE

X1	12367.000	0.000	0.000	0.000	42.000	42.000	42.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	920.000	0.000	1065.000	0.000	583.300	583.300	0.000
NH	5.000	0.200	250.000	0.300	930.000	0.050	1014.000	0.025	1064.100	0.500
NH	1600.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000

D/S FACE OF AUSTIN

X1	12300.000	0.000	0.000	0.000	1.000	1.000	1.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	920.000	0.000	1065.000	0.000	583.300	583.300	0.000
NH	5.000	0.200	250.000	0.300	930.000	0.050	1014.000	0.035	1064.100	0.500
NH	1600.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000

VALLEY SECT. 33' L/S OF AUSTIN

X1	12470.000	0.000	0.000	0.000	53.000	30.000	50.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	920.000	0.000	1065.000	0.000	0.000	0.000	0.000
BT	0.000	0.300	0.000	0.300	0.300	0.300	0.000	0.000	0.000	0.000
NH	5.000	0.200	250.000	0.300	930.000	0.320	928.000	0.255	965.000	0.300
NH	1063.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000

VALLEY SECT. BETWEEN AUSTIN AND [illegible]

PRINTED IN U.S.A.
FORM 1411.00 PRINTED BY ROTARY MANIFOLD FORMS

X1	13295.000	13.000	828.000	905.000	600.000	950.000	877.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	594.000	0.000	992.000	0.000	0.000	0.000	0.000
GR	585.000	0.000	584.000	260.000	583.100	660.000	583.800	760.000	584.000	828.000
GR	579.800	448.000	573.300	860.000	576.300	372.000	576.800	892.000	580.700	905.000
GR	582.000	960.000	582.000	1060.000	590.000	1060.000	0.000	0.000	0.000	0.000
NH	0.000	0.000	0.000	0.300	0.500	0.000	0.000	0.000	0.000	0.000
NH	5.000	0.150	200.000	0.120	472.000	0.035	508.000	0.100	526.000	0.300
NH	1300.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000

VALLEY SECT. 50' D/S OF VICTORIA

X1	13676.000	10.000	472.000	508.000	301.000	100.000	361.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	348.000	0.000	543.000	0.000	0.000	0.000	0.000
GR	585.000	0.000	584.600	200.000	580.000	420.000	581.800	462.000	574.900	472.000
GR	572.900	490.000	575.600	508.000	501.400	526.300	560.000	650.200	585.000	1300.000
NH	5.000	0.150	150.000	0.120	466.500	0.035	465.800	0.100	512.000	0.300
NH	1450.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000

D/S FACE OF VICTORIA

X1	13726.000	14.000	466.500	493.600	50.000	1.000	50.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	350.000	0.000	520.000	0.000	581.400	581.400	0.000
GR	585.000	0.000	584.600	150.000	581.800	453.000	573.000	466.500	573.000	466.600
GR	573.000	479.500	573.000	479.600	573.000	480.500	573.000	480.600	573.000	493.500
GR	573.000	493.600	581.400	512.000	581.500	720.000	585.000	1450.000	0.000	0.000
NH	5.000	0.150	150.000	0.120	466.500	0.020	493.600	0.100	512.000	0.300
NH	1450.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000

1' INSIDE D/S FACE OF VICTORIA BRIDGE

X1	13727.000	0.000	0.000	0.000	1.000	1.000	1.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	350.000	0.000	520.000	0.000	581.400	581.400	0.000
GR	14.000	0.000	585.000	0.000	580.000	514.000	0.000	552.000	582.600	0.000
BT	466.500	581.400	573.000	466.600	581.400	579.600	479.500	581.400	579.600	479.600
BT	581.400	575.000	480.500	581.400	573.000	480.600	581.400	579.600	493.500	581.400
BT	579.600	493.600	581.400	573.000	512.000	581.400	0.000	810.000	581.500	0.000
BT	1450.000	585.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
NH	5.000	0.150	150.000	0.120	466.500	0.020	493.600	0.100	512.000	0.300
NH	1450.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000

1' INSIDE U/S FACE OF VICTORIA BRIDGE

X1	13964.000	0.000	0.000	0.000	237.000	237.000	237.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	350.000	0.000	520.000	0.000	581.400	581.400	0.000
NH	5.000	0.150	150.000	0.120	466.500	0.035	493.600	0.100	512.000	0.300
NH	1450.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000

U/S FACE OF VICTORIA

X1	13965.000	0.000	0.000	0.000	1.000	1.000	1.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	350.000	0.000	520.000	0.000	581.400	581.400	0.000
NH	5.000	0.150	150.000	0.120	466.500	0.035	493.600	0.100	520.000	0.300
NH	1450.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000

VALLEY SECT. 50' U/S OF VICTORIA

FORM 1411 CO-PRINTED BY ROTARY MANIFOLD FORMS
PRINTED IN U.S.A.

X1	14015.000	0.000	0.000	0.000	50.000	50.000	50.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	350.000	0.000	520.000	0.000	0.000	0.000	0.000
NH	5.000	0.200	150.000	0.080	275.000	0.035	345.000	0.040	520.000	0.500
NH	1160.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000

VALLEY SECT. 50' D/S OF N.B. FORT ST.

X1	14287.000	13.000	275.000	345.000	272.000	272.000	272.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	200.000	0.000	520.000	0.000	583.200	583.200	0.000
GR	585.000	0.000	304.500	150.000	583.700	275.000	576.300	295.000	574.500	313.000
GR	575.900	331.000	582.600	345.000	503.000	360.000	502.800	400.000	582.200	520.000
GR	581.900	750.000	500.000	1160.000	590.000	1160.000	0.000	0.000	0.000	0.000
NH	5.000	0.200	150.000	0.080	449.700	0.035	501.800	0.040	700.000	0.500
NH	1580.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000

D/S FACE OF N.B. FORT ST.

X1	14337.000	20.000	449.700	501.800	50.000	50.000	50.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	380.000	0.000	700.000	0.000	583.200	583.200	0.000
GR	585.000	0.000	585.000	150.000	584.300	300.000	583.600	440.000	576.400	449.700
GR	578.400	449.000	576.400	433.000	574.600	475.000	574.600	475.100	574.000	476.400
GR	574.600	476.500	578.400	498.200	578.400	500.700	573.400	501.600	502.600	516.000
GR	582.800	575.000	582.200	700.000	581.200	950.000	581.000	1360.000	590.000	1380.000
NH	5.000	0.200	150.000	0.080	449.700	0.020	501.800	0.040	700.000	0.500
NH	1380.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000

1' INSIDE D/S FACE OF N.B. FORT ST.

X1	14338.000	0.000	0.000	0.000	1.000	1.000	1.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	380.000	0.000	700.000	0.000	583.200	583.200	0.000
GR	17.000	0.000	585.000	0.000	150.000	585.000	0.000	300.000	586.300	0.000
GR	440.000	581.600	0.000	469.700	550.200	576.400	469.500	550.200	581.400	475.300
GR	583.200	581.400	475.100	583.200	574.600	476.400	585.200	574.600	476.300	583.200
GR	581.400	583.700	583.200	581.400	581.800	582.200	576.400	576.000	582.600	0.000
GR	575.000	582.800	0.000	700.000	582.200	0.000	950.300	581.200	0.000	1380.000
GR	580.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
NH	5.000	0.200	150.000	0.080	449.700	0.020	501.800	0.040	700.000	0.500
NH	1380.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000

1' INSIDE U/S FACE OF N.B. FORT ST.

X1	14402.000	0.000	0.000	0.000	64.000	64.000	64.000	0.000	0.000	0.000
X2	0.000	0.000	0.000	0.000	0.000	1.000	1.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	360.000	0.000	700.000	0.000	583.200	583.200	0.000
NH	5.000	0.200	150.000	0.080	449.700	0.020	501.800	0.040	700.000	0.500
NH	1540.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000

U/S FACE OF N.B. FORT ST.

X1	14403.000	0.000	0.000	0.000	1.000	1.000	1.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	360.000	0.000	700.000	0.000	583.200	583.200	0.000
NH	5.000	0.200	300.000	0.080	473.300	0.080	520.700	0.100	800.000	0.300
NH	1400.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000

U/S FACE OF S.B. FORT ST.

X1	14460.000	20.000	473.300	526.700	57.000	57.000	57.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	370.000	0.000	700.000	0.000	583.200	583.200	0.000

PRINTED IN U.S.A.
FORM 1411-OD PRINTED BY ROTARY MANIFOLD FORMS.

GR	585.800	0.000	584.600	300.000	584.300	460.000	578.900	473.300	578.900	473.400
GR	578.900	477.800	574.900	483.800	572.600	499.300	572.600	499.400	572.600	500.600
GR	572.600	500.700	574.900	516.100	578.900	522.100	578.900	526.600	578.900	526.700
GR	583.400	538.000	581.800	300.000	581.200	1050.000	580.000	1400.000	590.000	1400.000
NH	5.000	0.200	300.000	0.080	473.300	0.030	526.700	0.100	800.000	0.500
NH	1400.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000

1' INSIDE D/S FACE OF S.B. FORT ST.

X1	14461.000	0.000	0.000	0.000	1.000	1.000	1.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	370.000	0.000	770.000	0.000	583.600	583.600	0.000
NH	15.000	0.000	385.800	0.000	300.600	584.600	0.000	460.000	586.300	0.000
BT	473.300	583.600	578.900	473.400	583.600	581.600	499.300	583.600	581.600	499.400
BT	583.600	572.600	500.600	583.600	572.600	500.700	583.600	581.600	526.600	583.600
BT	581.600	526.700	583.600	578.900	538.000	583.400	0.000	800.000	581.800	0.000
BT	1050.000	581.200	1.000	1400.000	580.000	0.000	0.000	0.000	0.000	0.000
NH	5.000	0.200	300.000	0.080	473.300	0.020	526.700	0.100	800.000	0.500
NH	1400.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000

1' INSIDE U/S FACE OF S.B. FORT ST.

X1	14521.000	0.000	0.000	0.000	60.000	50.000	60.000	0.000	0.000	0.000
X2	0.000	0.000	0.000	0.000	0.000	0.000	1.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	370.000	0.000	770.000	0.000	583.600	583.600	0.000
NH	5.000	0.200	300.000	0.080	473.300	0.030	526.700	0.100	800.000	0.500
NH	1400.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000

U/S FACE OF S.B. FORT ST.

X1	14522.000	0.000	0.000	0.000	1.000	1.000	1.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	370.000	0.000	770.000	0.000	583.600	583.600	0.000
NH	5.000	0.200	300.000	0.120	473.300	0.035	470.500	0.120	630.300	0.500
NH	1400.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000

VALLEY SECT. 50' U/S OF S.B. FORT ST.

X1	14572.000	10.000	415.000	470.000	50.000	50.000	50.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	370.000	0.000	770.000	0.000	0.000	0.000	0.000
NH	385.000	0.000	534.400	200.000	584.200	650.000	526.650	473.000	572.750	450.000
GR	576.200	460.000	585.400	470.000	580.000	1050.000	580.000	1150.000	590.000	1150.000
NC	0.000	0.000	0.000	0.100	0.300	0.000	0.000	0.000	0.000	0.000
NC	5.000	0.100	159.000	0.035	225.000	0.100	272.000	0.000	0.000	0.000

VALLEY SECT.

X1	15292.000	5.000	159.000	225.000	720.000	650.000	720.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	166.700	0.000	225.000	0.000	0.000	0.000	0.000
GR	586.250	0.000	589.500	100.000	587.200	1.000	577.150	159.000	574.450	200.000
GR	577.250	210.000	582.800	225.300	586.500	272.000	0.000	0.000	0.000	0.000
NC	5.000	0.100	0.035	0.300	0.527	0.000	0.000	0.000	0.300	0.000

VALLEY SECT. 50' D/S OF LAFAYETTE

X1	15420.000	0.000	45.000	115.000	350.000	350.000	325.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	50.000	0.000	142.200	0.000	583.000	583.000	0.000
GR	586.000	0.000	586.200	75.000	577.700	88.000	577.000	400.000	579.300	15.000
GR	585.500	127.000	585.400	200.300	0.000	0.000	0.000	0.000	0.000	0.000

PRINTED IN U.S.A.
FORM 141 OB PRINTED BY ROTARY MANIFOLD FORMS

D/S FACE OF LAFAYETTE

X1	15670.000	8.000	86.000	114.000	50.000	50.000	50.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	50.000	0.000	150.000	0.000	583.000	583.000	0.000
GR	586.000	0.000	586.400	66.000	577.000	86.000	577.000	86.100	577.000	113.900
GR	577.000	114.000	586.400	134.000	585.400	200.000	0.000	0.000	0.000	0.000
SB	0.000	1.650	3.000	100.300	26.000	0.000	168.000	0.000	577.000	577.000

U/S FACE OF LAFAYETTE

X1	15914.000	0.000	0.000	0.000	44.000	44.000	44.000	0.000	0.000	0.000
X2	0.000	0.000	1.000	583.000	585.400	0.000	0.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	50.000	0.000	150.000	0.000	586.000	585.400	0.000
BT	8.000	0.000	586.000	0.000	66.000	586.400	0.000	86.000	586.400	577.000
BT	86.100	586.400	593.000	113.900	586.400	583.000	114.000	586.400	577.000	134.300
BT	586.400	0.000	200.000	585.400	0.000	0.000	0.000	0.000	0.000	0.300

VALLEY SECT. 50' U/S OF LAFAYETTE

X1	15964.000	7.000	80.000	112.000	50.000	50.000	50.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	150.000	0.000	586.000	585.400	0.000
GR	586.000	0.000	586.400	73.000	577.000	86.000	577.000	100.000	577.000	113.000
GR	586.400	122.000	585.400	200.000	0.000	0.000	0.000	0.000	0.000	0.000
NB	3.000	0.000	799.000	0.035	835.000	0.000	860.000	0.000	0.000	0.000

VALLEY SECT. 50' D/S OF I-75

X1	16196.000	5.000	799.000	835.000	230.000	230.000	230.000	0.000	0.000	0.000
X5	0.000	0.000	0.000	795.000	0.000	645.000	0.000	0.000	0.000	0.000
GR	587.800	775.000	578.600	799.000	576.500	820.000	578.600	835.000	588.000	860.000
NB	0.000	0.000	0.035	0.000	0.000	0.000	0.000	0.000	0.000	0.000

D/S FACE OF I-75 BRIDGE

X1	16246.000	5.000	818.500	841.500	50.000	50.000	50.000	0.000	0.000	0.000
X4	10.000	0.000	5.000	0.000	0.000	0.000	0.000	603.600	603.600	0.000
GR	603.600	818.500	578.600	818.600	578.600	818.700	578.500	830.000	578.600	841.400
GR	578.500	841.500	603.600	841.600	0.000	0.000	0.000	0.000	0.000	0.000
NC	0.000	0.000	0.020	0.000	0.000	0.000	0.000	0.000	0.000	0.000

X1	16245.000	0.000	0.000	0.000	1.000	1.000	1.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	603.600	603.600	0.000
BT	0.300	818.500	603.600	0.000	818.600	603.600	578.600	818.700	603.600	586.100
BT	841.400	603.600	588.100	841.500	603.600	578.600	841.600	603.600	0.000	0.000

X1	16503.000	0.000	0.000	0.000	258.000	258.000	258.000	0.000	0.000	0.000
X2	0.000	0.000	0.000	0.000	0.000	0.000	1.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	603.600	603.600	0.000
RC	0.000	0.000	0.035	0.000	0.000	0.000	0.000	0.000	0.000	0.000

D/S FACE OF I-75 BRIDGE

X1	16246.000	0.000	0.000	0.000	1.000	1.000	1.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	603.600	603.600	0.000
BT	0.300	770.000	1162.000	1330.000	1330.000	1945.000	0.000	0.000	0.000	0.000

PRINTED IN U.S.A.
FORM 1411.00 PRINTED BY ROTARY MANIFOLD FORMS

VALLEY SECT. 50' U/S OF I-75

X1	16554.000	10.000	605.000	635.000	50.000	50.000	50.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	558.000	0.000	603.000	0.000	0.000	0.000	0.000
GR	585.300	0.000	585.300	100.000	590.000	300.000	580.500	587.000	578.800	605.000
GR	576.600	620.000	578.900	635.000	587.600	600.000	583.000	700.000	590.000	1250.000
NH	4.000	0.040	100.000	0.060	410.000	0.035	442.000	0.060	480.000	0.000

VALLEY SECT. 50' D/S OFINDUSTRIAL DRIVE?

X1	16826.000	10.000	410.000	462.000	272.000	272.000	272.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	394.000	0.000	456.000	0.000	0.000	0.000	0.000
GR	587.300	0.000	587.300	100.000	587.000	170.000	589.000	220.000	586.000	380.000
GR	575.400	410.000	575.300	426.000	575.400	442.000	586.000	462.000	593.000	480.000
NH	4.000	0.040	100.000	0.060	290.000	0.035	323.100	0.060	540.000	0.000
ET	0.000	0.000	0.000	0.000	9.100	0.000	0.000	0.000	1.004	539.000

D/S FACE OF INDUSTRIAL DRIVE

X1	16870.000	9.300	290.000	323.100	50.000	50.000	50.000	0.000	0.000	0.000
X3	10.000	0.300	0.000	0.000	0.000	0.000	0.000	595.500	590.500	0.000
GR	587.300	0.000	587.300	100.000	589.700	240.200	574.600	290.000	574.600	290.100
GR	574.600	323.000	574.600	323.100	591.000	358.000	593.000	540.000	0.000	0.000
SB	0.000	1.820	3.000	0.000	26.830	0.000	330.000	0.000	574.900	574.600
NH	3.000	0.060	290.000	0.035	323.100	0.060	358.000	0.000	0.000	0.000

U/S FACE OF INDUSTRIAL DRIVE

X1	16963.000	15.100	290.000	323.100	87.000	87.000	87.000	0.000	0.000	0.000
XP	0.000	0.000	1.000	587.200	589.700	0.000	0.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.300	0.000	0.300	0.000	591.500	590.500	0.000
BT	15.000	240.000	588.700	0.000	290.000	590.500	574.900	290.100	590.500	578.500
BT	292.000	320.500	592.000	296.300	595.500	595.300	293.000	591.400	595.600	302.000
BT	590.500	587.000	306.500	590.500	587.200	311.000	590.500	587.000	315.000	590.500
BT	585.600	319.000	590.500	583.300	321.000	590.300	582.000	323.000	590.500	578.500
BT	323.100	590.500	374.900	350.000	591.000	0.000	0.000	0.000	0.000	0.000
BT	589.700	260.000	574.900	290.000	574.900	290.000	574.900	292.000	574.000	294.000
BT	577.900	298.000	574.900	302.000	574.900	304.500	574.900	311.000	575.500	315.000
BT	574.300	319.000	574.900	591.000	574.900	323.000	574.900	323.100	592.000	353.000
NH	4.000	0.040	100.000	0.000	394.000	0.035	387.000	0.060	437.000	0.000
ET	0.000	0.000	0.000	0.000	1.410	0.000	0.000	0.000	0.000	0.000

VALLEY SECT. 50' U/S OF INDUSTRIAL DRIVE

X1	17013.000	7.000	354.000	387.300	50.000	50.000	50.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	304.000	0.000	437.000	0.000	0.000	0.000	0.000
GR	587.300	0.000	587.300	100.000	585.000	324.200	576.200	354.000	576.200	387.000
BT	585.000	407.000	587.000	437.200	0.000	0.300	0.000	0.000	0.000	0.000
NH	4.000	0.040	100.000	0.000	422.000	0.035	461.000	0.000	600.000	0.000

VALLEY SECT. 50' D/S OF PENN CENTRAL R.R.

X1	17295.000	9.000	422.000	461.300	242.000	242.300	243.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	424.200	0.000	466.500	0.000	0.000	0.000	0.000
GR	587.300	0.000	587.300	100.000	590.000	290.300	587.700	401.000	378.100	422.000
GR	577.900	440.000	578.100	461.300	597.000	575.000	590.000	600.000	0.000	0.000
VE	0.000	0.000	0.035	0.300	0.500	0.000	0.000	0.000	0.000	0.000

PRINTED IN U.S.A.
FORM 141.00 PRINTED BY NOTARY MANIFOLD FORMS

D/S FACE OF PENN CENTRAL R.R. BRIDGE

X1	17305.000	10.000	356.400	383.600	50.000	50.000	50.000	0.000	0.000	0.000
XS	10.000	0.000	0.000	0.000	0.000	0.000	0.000	600.400	600.400	0.000
GR	600.400	356.300	577.900	356.400	577.900	356.500	577.900	368.400	577.900	368.500
GR	577.900	371.500	577.900	371.600	577.900	383.900	577.900	383.800	600.400	383.700
SB	1.250	2.490	3.000	0.000	27.200	3.200	182.000	0.000	577.900	577.900

D/S F . E OF PENN CENTRAL R.R. BRIDGE

X1	17502.000	0.000	0.000	0.300	197.000	197.000	197.000	0.000	0.000	0.000
X2	0.000	0.000	1.000	585.500	600.400	0.000	0.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	600.400	600.400	0.000
BT	10.000	356.300	600.400	0.000	356.400	600.400	577.900	356.500	600.400	585.500
ST	368.400	600.400	585.500	368.500	600.400	577.900	371.500	600.400	577.900	371.600
QT	600.400	585.500	383.500	600.400	585.500	383.600	600.400	577.900	383.700	600.400
RT	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
NH	5.000	0.040	100.000	0.000	328.000	0.035	352.000	0.000	470.000	1.000
NH	1060.00	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000

VALLEY SECT. 50' U/S OF PENN CENTRAL R.R.

X1	17552.000	10.000	320.000	352.000	50.000	50.000	50.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	277.000	0.000	434.000	0.000	0.000	0.000	0.000
GR	600.000	100.000	587.200	100.000	586.900	315.000	577.800	328.000	577.500	340.000
GR	577.500	352.000	585.400	370.000	595.000	470.000	585.000	1060.000	600.000	1360.000
NC	0.050	0.050	0.035	0.100	0.300	0.050	0.000	0.000	0.000	0.000

VALLEY FROM SUBD'N PLANS

X1	17417.000	17.000	301.000	102.000	250.000	250.000	335.000	0.000	0.000	0.000
X2	0.000	0.000	0.000	0.000	0.000	230.400	0.000	0.000	0.000	0.000
GR	600.000	0.000	587.200	0.000	588.500	0.000	587.300	301.000	575.400	130.000
GR	576.900	139.000	576.500	148.000	595.500	162.000	589.100	225.000	589.100	275.000
GR	600.000	275.000	0.300	0.000	0.000	0.000	0.000	0.000	0.000	0.000
NH	6.000	0.040	100.000	0.000	130.000	1.000	250.000	0.000	340.000	0.035
NH	565.000	0.000	1200.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000

VALLEY SECT. 50' D/S OF PORTER AVE.

X1	18106.000	17.000	340.000	365.000	289.000	289.000	289.000	0.000	0.000	0.000
XS	10.000	0.000	0.000	265.000	0.000	434.000	0.000	587.900	587.900	0.000
GR	588.000	0.000	588.000	100.000	568.000	191.000	585.000	250.000	588.400	320.000
GR	579.000	360.000	579.000	350.000	579.000	365.000	587.700	333.000	586.700	410.000
BR	586.700	660.000	587.500	650.000	587.500	660.000	588.500	910.000	588.500	960.000
GR	588.700	1180.000	588.700	1230.000	0.000	0.000	0.000	0.000	0.000	0.000
NH	4.000	1.000	280.000	0.060	350.000	0.032	375.100	0.500	500.000	0.000

D/S FACE OF POTTER AVE.

X1	18196.000	11.000	550.000	375.100	50.000	50.000	50.000	0.000	0.000	0.000
XS	10.000	0.000	0.000	275.000	0.000	450.000	0.000	587.900	587.900	0.000
BR	600.000	425.000	588.600	229.000	586.400	290.000	587.900	530.000	579.000	350.000
GR	579.000	350.100	579.000	375.000	579.000	375.100	587.900	409.000	586.700	300.000
GR	600.000	500.000	588.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
NH	4.000	1.000	280.000	0.040	350.000	0.020	375.100	0.500	500.000	0.000

1' INSIDE OF D/S FACE OF PORTER AVE.

X1	18157.000	0.000	0.000	0.000	1.000	1.000	1.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	275.000	0.000	450.000	0.000	587.900	587.900	0.000
BT	10.000	225.000	600.000	0.000	220.000	588.600	0.000	330.000	587.900	0.000
BT	350.000	587.900	579.000	350.100	587.900	585.900	375.000	587.900	585.900	375.100
BT	587.900	579.000	435.000	587.900	3.000	500.000	586.700	0.000	500.000	600.000
BT	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
MH	4.000	1.000	280.000	0.060	350.000	0.020	375.100	0.500	500.000	0.000

1' INSDIE OF U/S FACE OF PORTER AVE.

X1	18195.000	0.000	0.000	0.000	38.000	38.000	38.000	0.000	0.000	0.000
X2	0.000	0.000	0.000	0.000	0.000	0.000	1.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	275.000	0.000	450.000	0.000	587.900	587.900	0.000
MH	4.000	1.000	280.000	0.060	350.000	0.030	375.100	0.500	500.000	0.000

U/S FACE OF PORTER AVE.

X1	18196.000	0.000	0.000	0.000	1.000	1.000	1.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	275.000	0.000	450.000	0.000	587.900	587.900	0.000
MH	5.000	0.040	100.000	1.200	275.000	0.100	351.000	0.035	372.000	0.500
MH	1500.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000

VALLEY SECT. 50' U/S OF PORTER AVE.

X1	18240.000	16.000	351.000	372.000	50.000	50.000	50.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	320.000	0.000	470.000	0.000	587.900	587.900	0.000
GR	588.000	0.000	588.000	100.000	585.000	220.000	586.000	270.000	588.000	335.000
GR	579.000	351.000	579.000	372.000	587.900	386.000	586.700	410.000	586.700	460.000
GR	587.500	700.000	587.500	750.000	588.500	970.000	588.500	1020.000	588.700	1250.000
GR	588.700	1300.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
MC	2.050	0.050	0.035	0.100	0.300	0.000	0.300	0.010	0.000	0.000

VALLEY SECT. BETW. PORTER AND RAUPP PLACE

X1	18243.000	11.000	134.000	220.000	259.000	295.000	339.500	0.300	0.300	0.300
X3	10.000	0.000	0.300	159.000	0.000	301.000	0.500	588.000	530.000	0.300
BT	588.000	0.000	587.700	0.000	587.900	200.000	588.520	174.300	540.300	170.300
GR	578.600	200.000	500.600	210.000	586.600	220.000	588.200	300.000	589.600	400.000
GR	600.000	400.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
MC	0.000	0.000	0.300	0.300	0.500	0.000	0.000	0.000	0.000	0.000
MH	5.000	0.040	100.000	0.005	250.000	0.000	351.000	0.035	582.900	0.300
MH	1410.000	0.000	0.000	0.000	0.000	0.000	0.300	0.000	0.000	0.000

VALLEY SECT. 50' D/S OF RAUPP PL.

X1	18289.000	19.500	363.300	377.100	294.000	294.000	294.000	0.000	0.000	0.000
X3	10.000	0.300	0.001	299.000	0.000	455.000	0.300	595.000	595.000	0.000
GR	587.500	0.300	587.900	100.000	585.600	197.000	595.200	345.000	370.700	345.500
GR	578.700	363.600	578.700	370.000	578.700	377.000	578.700	377.100	595.500	386.000
GR	588.500	470.000	590.100	660.000	590.100	710.000	589.000	760.000	589.000	810.000
GR	589.900	1100.300	589.900	1150.000	590.000	1360.000	590.000	1410.000	0.000	0.000
MC	5.000	0.040	100.000	0.000	250.000	0.000	356.300	0.050	332.900	0.300
MH	1410.000	0.000	0.000	0.000	0.000	0.000	0.300	0.000	0.000	0.000

D/S FACE OF RAUPP PL. BRIDGE

PRINTED IN U.S.A.
FORM 1411-OD-PRINTED BY ROTARY MANIFOLD FORMS

X1	18879.000	0.000	0.000	0.000	50.000	50.000	50.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	290.000	0.000	455.000	0.000	585.000	585.000	0.000
NH	5.000	0.040	100.000	0.800	250.000	0.080	358.000	0.020	382.100	0.500
NH	1410.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000

1' INSIDE OF D/S FACE RAUPP PL.

X1	18880.000	0.000	0.000	0.000	1.000	1.000	1.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	290.000	0.000	455.000	0.000	585.000	585.000	0.000
BT	18.000	0.000	587.900	0.000	100.000	587.900	0.000	137.000	585.600	0.000
BT	345.000	585.200	0.000	363.500	585.000	578.700	363.600	585.000	503.200	377.000
BT	585.000	583.200	577.100	585.000	578.700	366.300	585.500	0.000	470.000	388.500
BT	0.000	660.000	590.100	0.000	710.000	590.100	0.000	760.000	589.000	0.000
BT	810.000	589.000	0.000	1130.000	589.900	0.000	1150.000	589.900	0.000	1360.000
BT	590.000	0.000	1410.000	590.000	0.000	0.000	0.000	0.000	0.000	0.000
NH	5.000	0.040	100.000	0.800	250.000	0.080	358.000	0.020	382.100	0.500
NH	1410.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000

1' INSIDE OF U/S FACE RAUPP PL.

X1	18910.000	0.000	0.000	0.000	30.000	30.000	30.000	0.000	0.000	0.000
X2	0.000	0.000	0.000	0.000	0.000	0.000	1.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	290.000	0.000	455.000	0.000	585.000	585.000	0.000
NH	5.000	0.040	100.000	0.800	250.000	0.080	358.000	0.020	382.100	0.500
NH	1410.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000

U/S FACE OF RAUPP PL. BRIDGE

X1	18911.000	0.000	0.000	0.000	1.000	1.000	1.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	290.000	0.000	455.000	0.000	585.000	585.000	0.000
NH	5.000	0.040	100.000	0.800	250.000	0.040	358.000	0.035	382.100	0.500
NH	1410.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000

VALLEY SECT. 50' U/S OF RAUPP PL.

X1	18961.000	0.000	0.000	0.000	50.000	50.000	50.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	290.000	0.000	455.000	0.000	585.000	585.000	0.000
NH	4.300	0.040	100.000	0.800	307.000	0.035	333.100	0.500	1430.000	0.000

VALLEY SECT. 50' D/S OF DIX

X1	19112.000	20.000	307.000	333.100	151.000	141.300	151.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	220.000	0.000	400.300	0.000	584.200	583.200	0.000
X3	588.700	0.000	582.900	100.000	583.500	285.300	579.000	367.000	579.000	307.100
C1	579.000	319.000	579.000	319.100	579.000	321.000	579.000	321.100	579.000	333.000
C3	579.000	333.100	588.300	351.000	589.200	750.000	589.200	800.000	589.700	840.000
C3	589.700	840.000	590.600	1110.000	590.600	1160.000	590.600	1380.000	590.600	1430.000
NH	4.000	0.040	100.000	0.800	307.000	0.035	333.100	0.500	1430.000	0.000

D/S FACE OF DIX RD. BRIDGE

X1	19162.000	0.000	0.000	0.000	50.000	50.000	50.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	220.000	0.000	400.000	0.000	584.200	583.200	0.000
NH	4.300	0.040	100.000	0.800	307.000	0.035	333.100	0.500	1430.000	0.000

1' INSIDE D/S FACE OF DIX

PRINTED IN U.S.A.
FORM 1411-GD PRINTED BY ROTARY MANIFOLD FORMS

X1	19163.000	0.000	0.000	0.000	1.000	1.000	1.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	220.000	0.000	400.000	0.000	588.200	588.200	0.000
BT	20.000	0.000	588.900	0.000	100.000	588.900	0.000	295.000	588.500	0.000
BT	307.000	588.200	579.000	307.100	588.200	585.000	319.000	588.200	585.000	319.100
BT	588.200	579.000	321.000	588.200	579.000	321.100	583.200	585.000	333.000	588.200
BT	585.000	333.100	583.200	579.000	351.000	588.300	0.000	750.000	589.200	0.000
BT	600.000	589.200	0.000	840.300	589.700	0.000	890.000	589.700	0.000	1110.000
BT	590.600	0.000	1160.000	590.600	0.000	1380.000	590.600	0.000	1430.000	590.600
BT	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
NH	4.000	0.040	100.000	0.800	307.000	0.020	333.100	0.500	1430.000	0.000

1' INSIDE U/S FACE OF DIX

X1	19263.000	0.000	0.000	0.000	100.000	100.000	100.000	0.000	0.000	0.000
X2	0.000	0.000	0.000	0.000	0.000	0.000	1.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	220.000	0.000	400.000	0.000	588.200	588.200	0.000
NH	4.000	0.040	100.000	0.800	307.000	0.020	333.100	0.500	1430.000	0.000

U/S FACE OF DIX RD. BRIDGE

X1	19264.000	0.000	0.000	0.000	1.000	1.000	1.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	220.000	0.000	400.000	0.000	588.200	588.200	0.000

VALLEY SECT. 50' U/S OF DIX

X1	19514.000	0.000	0.000	0.000	50.000	50.000	50.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	220.000	0.000	400.000	0.000	588.200	588.200	0.000
NH	4.000	0.040	100.000	0.500	365.000	0.035	589.000	0.500	1320.000	0.000

VALLEY SECT. 50' D/S OF FRANK AVE.

X1	20080.000	12.000	585.000	589.000	766.000	766.000	766.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	220.000	0.000	400.000	0.000	0.000	0.000	0.000
GR	588.300	0.000	583.300	100.000	585.000	200.000	589.400	350.000	580.100	365.000
GR	585.100	389.000	589.200	406.000	590.000	550.000	590.800	730.000	590.800	780.000
GR	589.600	1000.000	589.600	1320.000	0.000	0.000	0.000	0.000	0.000	0.000
NH	5.000	0.040	100.000	0.500	357.000	0.100	387.000	0.020	413.100	0.200
NH	1300.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000

DOS FACE OF FRANK AVE. BRIDGE

X1	20130.000	13.000	587.000	413.100	50.000	50.000	50.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	372.000	0.000	400.000	0.000	0.000	0.000	0.000
GR	588.400	0.000	588.300	100.000	590.800	372.000	590.800	372.100	580.100	387.000
GR	580.100	387.100	580.100	413.000	580.100	413.100	586.800	428.000	586.600	428.100
GR	590.800	710.000	589.600	1000.000	589.600	1300.000	0.000	0.000	0.000	0.000
NH	5.000	0.040	100.000	0.500	357.000	0.100	387.000	0.020	413.100	0.200
X1	1300.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000

1' INSIDE D/S OF FRANK AVE.

X1	20131.000	0.000	0.000	0.000	1.000	1.000	1.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	372.000	0.000	400.000	0.000	0.000	0.000	0.000
GT	13.000	0.000	588.300	0.300	100.000	588.300	0.000	372.000	588.600	0.000
GT	372.100	592.100	0.000	387.000	592.100	430.100	387.100	593.400	586.700	413.000
GT	590.400	586.700	413.100	592.100	580.100	426.000	592.100	0.000	428.100	588.800
GT	0.000	710.000	590.600	0.000	1000.000	589.600	0.000	1300.000	589.600	0.000
NH	5.000	0.040	100.000	0.500	357.000	0.100	387.000	0.020	413.100	0.200

PRINTED IN U.S.A.
FORM 1411-GO PRINTED BY ROTARY MANIFOLD FORMS

NH	1300.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000

1' INSIDE U/S OF FRANK AVE.

X1	20168.000	0.000	0.000	0.000	37.000	37.000	37.000	0.000	0.000	0.000
X2	0.000	0.000	0.000	0.000	0.000	0.000	1.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	372.000	0.000	500.000	0.000	0.000	0.000	0.000
NH	5.000	0.040	100.000	0.500	357.000	0.100	387.000	0.030	413.100	0.200
NH	1300.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000

U/S FACE OF FRANK AVE. BRIDGE

X1	20169.000	0.000	0.000	0.000	1.000	1.000	1.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	372.000	0.000	500.000	0.000	0.000	0.000	0.000
NH	5.000	0.040	100.000	0.500	357.000	0.100	387.000	0.030	413.100	0.200
NH	1300.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000

VALLEY SECT. 100'U/S OF FRANK AVE.

X1	20269.000	0.000	0.000	0.000	100.000	100.000	100.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	372.000	0.000	500.000	0.000	0.000	0.000	0.000
NH	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000

PRINTED IN U.S.A.
FORM 1411-SD PRINTED BY ROTARY MANIFOLD FORMS

*PROF 1

CONV= 0.300 CENV= 0.500

*SECNO 10636.000

SECD CROSS SECTION 10636.00 EXTENDED 0.0 FEET

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	AV		OLOSS	BANK ELEV
0.	0.03	0CH	0BOB	ALOB	0CH	ABCH	WOI	T.O.	LEFT/RIGHT
TIME	VICI	VCH	VROT	XML	XLCH	XMR	.TM	REMIP	SETZ
SLOPE	XLOBL	XLCP	ALOBR	ITRIAL	ISP	ICOUT	CORAC	TOPWID	ELOST

3470 ENCROACHMENT STATIONS= 655.0 800.0 TYPE= 1 TARGET= 145.000

VALLEY SECT. ARCH USA SCOTIA FIS

Q100 USA = 2100 cfs

10636.00	11.06	583.53	0.00	583.53	583.60	0.17	3.00	0.00	584.53
1410.	0.	1410.	0.	0.	680.	0.	0.	0.	100000.00
0.00	0.00	2.07	0.00	0.035	0.033	0.035	0.003	572.47	674.07
0.000344	0.	0.	0.	0	0	0	0.03	125.03	100.0

FLOW DISTRIBUTION FOR SECNO= 10636.00 CWSEL= 583.53

STA= 674. 855.

PER Q=	100.0	
AREA=	680.0	
VEL=	2.1	

CONV= 0.300 CENV= 0.500

1490 CU CARD USED

*SECNO 11535.000

3470 ENCROACHMENT STATIONS= 900.0 1350.0 TYPE= 1 TARGET= 145.000

VALLEY SECTION USA XSEC Corresponds to XSEC M (near hospital)

11535.00	11.77	583.77	0.00	0.00	583.92	3.15	0.00	0.0	585.30
1410.	0.	1410.	0.	0.	460.	0.	0.	0.	100000.00
0.00	0.00	3.34	0.00	0.035	0.033	0.035	0.003	622.60	900.40
0.000874	900.	900.	900.	1	0	0	0.00	51.05	5077.70

FLOW DISTRIBUTION FOR SECNO= 11535.00 CWSEL= 584.77

STA=	854.	1254.	1270.
PER Q=	100.0	0.0	
AREA=	460.1	3.1	
VEL=	3.1	0.1	

CONV= 0.300 CENV= 0.500

1490 CU CARD USED

*SECNO 12274.000

3470 ENCROACHMENT STATIONS= 900.0 1350.0 TYPE= 1 TARGET= 145.000

VALLEY SECT. 50' D/S OF AUST

12274.00	10.55	584.05	0.00	0.00	584.12	2.09	0.00	0.4	585.80
1410.	145.	1262.	3.	220.	308.	34.	22.	4.	674.00
0.14	0.05	2.79	0.01	0.037	0.048	0.037	0.007	623.60	97.20

PRINTED IN U.S.A.

FORM 141 OD PRINTED BY ROTARY MANIFOLD FORMS.

0.000165 738. 738. 738. 1 0 0 0.00 150.00 1050.00

FLOW DISTRIBUTION FOR SECNO= 12274.00 CUSEL= 584.05

STA= 900. 920. 980. 994. 1046. 1050.
PER %= 0.3 4.5 5.5 39.5 0.2
AREA= 42.6 110.4 73.4 507.8 35.6
VEL= 0.3 0.6 1.1 2.5 0.1

*** .. CARD USED
*SECNO 12324.000

3470 ENCROACHMENT STATIONS= 920.0 1065.0 TYPE= 1 TARGET= 145.000

S/S FACE OF AUSTIN

12324.00 11.47 384.07 0.30 0.00 1304.14 0.07 [illegible] 0.00 924.50
1810. 212. 1137. 3. 904. 500. 3. 25. 4. 28.13
0.18 0.71 2.35 0.04 0.055 0.035 0.500 0.033 573.60 920.00
0.000139 50. 50. 50. 0 0 0 0.01 145.00 1065.00

FLOW DISTRIBUTION FOR SECNO= 12324.01 CUSEL= 584.07

STA= 920. 1000. 1014. 1064. 1065.
PER %= 9.2 5.9 84.9 0.0
AREA= 222.6 81.6 509.4 9.1
VEL= 0.6 1.0 2.3 0.0

*** .. CARD USED
*SECNO 12325.003

SECNO	DEPTH	CUSEL	CRIMP	*SELK	CA	HV	HI	QLOSS	HARS FLEV
0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
TYPE	0.0	0.0	0.0	XNL	X CO	XWR	CW	D-IN	SA
4	0.0	0.0	0.0	STATE	.0	ICONT	SOPAR	0.0	FLOAT

3470 OLD BRIDGE.XSN= 2 DIA.EQV= 540.60 MAX ELEV= 581.00

3471 CONSTRICTION STATIONS= 920. 1013. CMIN= 1 CMAX= 1065. CDEL=

1' INSIDE D/S FACE OF AUSTIN BRIDGE

12325.00 10.34 [illegible] 0.00 0.00 584.15 0.11 0.50 0.02 [illegible]
1810. 259. 1493. 0. 242. [illegible] 1. 25. 4. 573.60
0.11 1.06 2.87 1.01 0.030 0.045 0.500 0.01 [illegible] 920.00
0.000561 1. 1. 1. 1 1 1 -161.35 145.00 1065.00

FLOW DISTRIBUTION FOR SECNO= 12325.00 CUSEL= 584.15

STA= 920. 1000. 1014. 1064. 1065.
PER %= -10.0 0.5 83.3 0.0
AREA= 204.1 4.5 [illegible] 0.7
VEL= 1.1 0.4 2.8 0.3

*** .. CARD USED

FORM 1411-OD PRINTED BY ROTARY MANIFOLD FORMS
PRINTED IN U.S.A.

3470 ENCROACHMENT STATIONS= 920.0 1065.0 TYPE= 1 TARGET= 145.000

1' INSIDE U/S FACE OF AUSTIN BRIDGE

*2157.00	10.48	584.08	0.00	0. 1	584.18	0.10	0.12	0.00	574.10
*410.	216.	1196.	0.	22.	416.	1.	24.	5.	573.80
0.18	1.06	2.81	0.01	0.059	0.025	0.500	0.033	573.60	920.00
0.000550	42.	42.	42.	0	0	0	-121.88	145.00	1065.00

FLOW DISTRIBUTION FOR SECNO= 12367.00 CWSEL= 584.08

STA=	920.	1000.	1014.	1064.	1065.
PER Q=	16.1	0.6	83.3	0.0	
AREA=	208.6	14.1	418.1	0.7	
VEL=	1.1	0.5	2.0	0.0	

1490 NH CARD USED
+SECNO 12368.000

3470 ENCROACHMENT STATIONS= 920.0 1065.0 TYPE= 1 TARGET= 145.000

U/S FACE OF AUSTIN

12368.00	10.52	584.12	0.03	0.00	584.19	0.07	0.00	0.01	574.10
1410.	216.	1193.	0.	309.	512.	9.	24.	5.	573.80
0.19	0.70	2.33	0.03	0.055	0.035	0.500	0.033	573.60	920.00
0.000134	1.	1.	1.	2	1	0	0.00	145.00	1065.00

FLOW DISTRIBUTION FOR SECNO= 12368.00 CWSEL= 584.12

STA=	920.	1000.	1014.	1064.	1065.
PER Q=	7.5	5.9	86.5	0.0	
AREA=	207.3	62.2	412.3	3.1	
VEL=	0.6	1.0	2.3	0.0	

1490 NH CARD USED
+SECNO 12410.000

3470 ENCROACHMENT STATIONS= 920.0 1065.0 TYPE= 1 TARGET= 145.000

VALLEY SECT. 50' U/S OF AUSTIN

12410.00	10.53	584.13	0.01	0.00	584.20	0.07	0.01	0.00	574.10
1410.	217.	1194.	0.	311.	513.	9.	24.	5.	573.80
0.19	0.70	2.32	0.03	0.055	0.035	0.500	0.033	573.60	920.00
0.000134	50.	50.	50.	0	0	0	0.00	145.00	1065.00

FLOW DISTRIBUTION FOR SECNO= 12410.00 CWSEL= 584.13

STA=	920.	1000.	1014.	1064.	1065.
PER Q=	7.5	5.9	86.5	0.0	
AREA=	208.7	62.4	413.2	3.1	
VEL=	0.6	1.0	2.3	0.0	

SCRVE= 0.100 CSHL= 0.300
1490 NH CARD USED
+SECNO 12395.001

3470 ENCROACHMENT STATIONS= 596.7 972.5 TYPE= 1 TARGET= 398.000

PRINTED IN U.S.A.
FORM 1411-00 PRINTED BY ROTARY MANIFOLD FORMS

VALLEY SECT. BETWEEN AUSTIN AND VICTORIA

13295.00	10.97	584.27	0.00	0.00	584.36	0.09	0.16	0.01	584.00
1610.	23.	1351.	36.	180.	544.	233.	41.	9.	580.70
0.39	0.53	2.48	0.15	0.168	0.035	0.300	0.033	572.90	996.00
0.000265	670.	877.	950.	2	1	0	0.00	195.00	992.00

FLOW DISTRIBUTION FOR SECNO= 13295.00 CUSEL= 584.27

STA=	594.	660.	750.	829.	905.	960.	994.
PER Q=	0.4	1.0	0.2	95.0	1.9	0.7	
AREA=	52.4	42.1	25.2	543.9	160.7	72.7	
VEL=	0.1	0.2	0.1	2.5	0.2	0.1	

CQAV= 0.700 CEHV= 0.500

*READ INPUT USED
*SECNO 13674.000

SECNO	DEPTH	CUSEL	SQ*IS	USELX	DS	AN	L	QLOSS	DATA ELEV
0	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TIA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	LTN	PLMIN	SSTA
SLOPE	KLOW	KLCH	KLOBR	ITRIAL	IA2	ICONT	COPAR	TOPELV	ENDST

3470 ENCROACHMENT STATIONS= 348.0 543.0 TYPE= 1 TARGET= 195.000

VALLEY SECT. 50' D/S OF VICTORIA

13674.00	11.45	584.55	0.00	0.00	584.46	0.11	0.10	0.01	574.90
1610.	206.	1122.	72.	464.	420.	152.	43.	11.	575.60
0.33	0.45	3.03	0.52	0.120	0.035	0.118	0.033	572.90	948.00
0.000231	381.	391.	100.	2	0	0	0.00	195.00	943.00

FLOW DISTRIBUTION FOR SECNO= 13674.00 CUSEL= 584.35

STA=	348.	420.	462.	472.	508.	526.	543.
PER Q=	7.9	4.6	2.3	77.5	5.3	0.5	
AREA=	259.5	144.9	60.0	369.9	105.3	31.8	
VEL=	0.4	0.4	0.3	3.0	0.7	0.1	

*READ INPUT USED
*SECNO 13726.000

3467 ENCROACHMENT STATIONS= 350.0 527.0 TYPE= 1 TARGET= 170.000

D/S FACE OF VICTORIA

13726.00	11.35	584.33	0.00	0.00	584.51	0.18	0.03	0.03	573.00
1610.	130.	1169.	122.	505.	307.	155.	58.	12.	573.80
0.33	0.45	3.24	0.79	0.120	0.035	0.116	0.033	572.90	941.00
0.000195	50.	91.	60.	2	1	0	0.00	195.00	938.00

FLOW DISTRIBUTION FOR SECNO= 13726.00 CUSEL= 584.33

STA=	350.	453.	467.	496.	512.	527.	
PER Q=	5.2	4.8	61.5	6.4	3.2		
AREA=	211.3	95.5	307.1	131.2	43.6		
VEL=	0.5	0.2	3.1	0.3	0.1		

*READ INPUT CARD NEED
*SECNO 13825.000

FORM 1411-00-PRINTED BY ROTARY MANIFOLD FORMS.
PRINTED IN U.S.A.

3370 NORMAL BRIDGE,NRD= 14 MIN ELTRD= 581.40 MAX ELLC= 579.60

3470 ENCROACHMENT STATIONS=	350.0	520.0	TYPE=	1	TARGET=	170.000				
1 U/S SIDE D/S FACE OF VICTORIA BRIDGE										
13727.00	11.26	584.26	0.00	0.00	584.58	0.32	0.00	0.07	573.00	
1410.	144.	1215.	59.	241.	249.	74.	50.	12.	573.00	
0.53	0.60	4.88	0.67	0.120	0.020	0.122	0.033	573.00	350.00	
0.000932	1.	1.	1.	2	0	0	-190.01	170.00	520.00	

Skew? Top width indicates skew has been applied. Input does not

FLOW DISTRIBUTION FOR SECNO= 13727.00 CWSEL= 584.26

STA=	350.	453.	457.	494.	512.	520.
FLOW=	3.6	1.0	80.1	3.2	0.6	
VEL=	264.6	35.9	249.3	52.7	32.9	
WSEL=	0.6	0.6	4.9	1.9	0.2	

1450 NH CARD USED
ASEC= 0 13584.000

3370 NORMAL BRIDGE,NRD= 14 MIN ELTRD= 581.40 MAX ELLC= 579.60

3470 ENCROACHMENT STATIONS=	350.0	520.0	TYPE=	1	TARGET=	170.000				
1 INSIDE U/S FACE OF VICTORIA BRIDGE										
13964.00	11.51	584.51	0.00	0.00	584.80	0.29	0.21	0.01	573.00	
1410.	163.	1192.	55.	270.	256.	82.	33.	13.	573.00	
0.55	0.61	4.66	0.67	0.120	0.020	0.122	0.033	573.00	350.00	
0.000932	237.	237.	237.	2	0	0	-190.01	170.00	520.00	

FLOW DISTRIBUTION FOR SECNO= 13964.00 CWSEL= 584.51

STA=	350.	453.	467.	494.	512.	520.
FLOW=	9.0	1.2	84.5	3.5	0.4	
VEL=	255.4	39.3	256.1	57.3	24.9	
WSEL=	0.8	0.5	5.1	2.0	0.2	

1450 NH CARD USED
ASEC= 0 13965.000

3470 ENCROACHMENT STATIONS=	350.0	520.0	TYPE=	1	TARGET=	170.000				
U/S FACE OF VICTORIA										
13965.00	11.68	584.68	0.00	0.00	584.87	0.19	0.05	0.04	573.00	
1410.	155.	1191.	64.	245.	216.	169.	53.	31.	573.00	
0.55	0.45	3.36	0.76	0.120	0.020	0.120	0.033	573.00	350.00	
0.000932	1.	4.	4.	2	0	0	-190.01	170.00	520.00	

FLOW DISTRIBUTION FOR SECNO= 13965.00 CWSEL= 584.68

STA=	350.	453.	467.	494.	512.	520.
FLOW=	36.5	3.7	30.2	3.5	0.1	
VEL=	267.2	99.8	256.4	137.6	26.8	
WSEL=	1.4	0.7	3.3	1.9	0.1	

PRINTED IN U.S.A.

FORM 1411.00-PRINTED BY BASARA-MARYSVILLE FORMS

1490 NH CARD USED
*SECNO 14015.000

SECNO	DEPTH	CWSEL	CRIWS	VSELK	EG	HV	HL	QLOSS	BANK ELEV
	0.00	0.00	0.00	0.00	0.00	0.00	0.00	LWA	LEFT/RIGHT
TYPE	VICD	WCH	VBCH	XNL	XNCH	XAR	WTX	ELTRM	SSTA
SLOPE	XLCOL	XLCH	XLOBR	TTRIAL	XH2	ICONT	CORIOP	TOPWID	ENDST

3470 ENCROACHMENT STATIONS= 350.0 520.0 TYPE= 1 TARGET= 170.000

VALLEY SECT. 50' U/S OF VICTORIA

14015.00	11.77	584.77	0.00	0.00	584.87	0.10	0.01	0.02	573.00
1410.	199.	937.	274.	356.	319.	166.	54.	13.	573.00
0.35	0.56	2.94	1.65	0.060	0.035	0.040	0.013	573.00	350.00
0.030179	52.	30.	50.	2	2	0	0.00	170.00	520.00

FLOW DISTRIBUTION FOR SECNO= 14015.00 C.SEL= 584.77

STA=	350.	453.	467.	494.	512.	520.
Q=	8.2	5.9	65.5	17.3	1.7	
AREA=	256.6	99.5	313.9	139.2	26.9	
VEL=	0.3	0.6	2.9	1.1	0.9	

1490 NH CARD USED
*SECNO 14287.000

3470 ENCROACHMENT STATIONS= 200.0 520.0 TYPE= 1 TARGET= 320.000

VALLEY SECT. 50' D/S OF N.B. FORT ST.

14267.00	10.37	584.87	0.00	0.00	584.93	0.05	0.05	0.01	563.71
1910.	91.	1067.	325.	79.	322.	395.	66.	2.	562.50
0.66	0.34	2.05	0.33	0.062	0.045	0.040	0.023	574.50	200.00
0.029139	272.	222.	246.	2	0	0	0.00	320.00	320.00

FLOW DISTRIBUTION FOR SECNO= 14267.00 CWSEL= 584.87

STA=	200.	275.	345.	361.	408.	520.
Q=	1.3	75.7	4.2	4.3	14.5	
AREA=	74.6	521.3	31.1	79.0	264.9	
VEL=	0.2	2.0	0.8	0.3	0.3	

1490 NH CARD USED
*SECNO 14537.000

3470 ENCROACHMENT STATIONS= 380.0 700.0 TYPE= 1 TARGET= 320.000

D/S FACE OF N.B. FORT ST.

14501.00	13.28	584.78	0.62	0.05	584.78	0.00	0.01	0.00	574.74
1.41	0.36	2.20	0.58	0.060	0.035	0.040	0.033	574.50	380.00
0.30 168	50.	90.	80.	0	0	7	2100	320.00	700.00

Buildings in 20B have not been considered

FLOW DISTRIBUTION FOR SECNO= 14537.00 CWSEL= 584.78

STA=	380.	450.	502.	575.	630.
Q=	5.5	66.5	5.5	14.5	
AREA=	102.7	426.1	51.1	264.9	
VEL=	0.5	2.6	0.5	0.3	

PRINTED IN U.S.A.
FORM 1411-QD PRINTED BY ROTARY MANIFOLD FORMS

VEL= 0.4 2.2 1.2 0.8 0.8

1410 WI CARD USED
ASECNO 14338.000

3370 NORTAL BRIDGE,NRD= 17 NEW ELTRD= 580.00 MAX ELLC= 581.40

3470 ENCROACHMENT STATIONS= 380.0 700.0 TYPE= 1 TARGET= 320.000

1' INSIDE D/S FACE OF N.B. FORT ST.

14338.00	10.28	584.36	0.00	0.00	584.76	0.06	0.00	0.00	320.00
1410.	34.	790.	586.	82.	322.	455.	61.	95.	578.40
0.41	0.41	2.45	1.29	0.000	0.020	0.040	0.033	574.60	380.00
1.000400	1.	1.	1.	0	0	0	-160.96	320.00	700.00

FLOW DISTRIBUTED FOR SECNO= 14338.00 CHSEL= 586.06

STA= 380. 450. 502. 575. 700.
PER Q= 2.4 55.0 13.8 27.8
AREA= 32.3 322.5 156.9 297.5
VEL= 0.4 2.5 1.2 1.3

1490 WH CARD USED
ASECNO 14402.000

3370 NORMAL BRIDGE,NRD= 17 NEW ELTRD= 580.00 MAX ELLC= 581.40

3470 ENCROACHMENT STATIONS= 380.0 700.0 TYPE= 1 TARGET= 320.000

1' INSIDE U/S FACE OF N.B. FORT ST.

14402.00	10.30	584.90	1.00	0.00	584.97	0.06	0.00	0.00	320.00
1420.	34.	791.	586.	82.	323.	457.	61.	95.	578.40
0.42	0.41	2.44	1.29	0.000	0.020	0.040	0.033	574.60	380.00
0.000400	65.	64.	64.	0	0	0	-160.96	320.00	700.00

FLOW DISTRIBUTION FOR SECNO= 14402.00 CHSEL= 584.97

STA= 380. 450. 502. 575. 700.
PER Q= 2.4 55.0 13.8 27.8
AREA= 33.2 323.2 157.9 299.5
VEL= 0.4 2.4 1.2 1.3

1410 WH CARD USED
ASECNO 14403.000

SECNO	DEPTH	CHSEL	CRIWS	ASELX	EG	HV	KI	CLOSS	BASIC FLOW
	QLOB	QCH	QROB	AFLOB	AFCH	AROB	WSEL	TRA	LEFT/RIGHT
TIME	VLOB	WSEL	VLOB	BSL	LAOB	RNK	LTN	FLOTS	SSTA
SLOPE	HLOB	WLOB	WCHAN	SINIAL	IHP	IOBST	CD SPH	TOPWID	ERRST

3470 ENCROACHMENT STATIONS= 380.0 700.0 TYPE= 1 TARGET= 320.000

U/S FACE OF N.B. FORT ST.

14403.00	10.32	584.98	0.00	0.00	584.97	0.06	0.00	0.00	320.00
1421.	34.	791.	436.	88.	428.	494.	62.	95.	578.40
0.42	0.41	2.44	0.33	0.00	0.020	0.040	0.033	574.60	380.00

0.000163 1. 1. 1. 1 0. 3 0.00 320.00 700.00

FLOW DISTRIBUTION FOR SECNO= 14403.00 CWSEL= 584.92

STA=	380.	450.	502.	515.	575.	700.
PER Q=	2.7	66.3	8.5	2.4	18.0	
AREA=	107.6	427.6	62.6	130.4	301.3	
VEL=	0.4	2.2	1.2	0.8	0.8	

1490 HH CARD USED
*SECNO 14460.000

3470 ENCROACHMENT STATIONS= 370.0 770.0 TYPE= 1 TARGET= 600.000

D/S FACE OF S.B. FORT ST. 55569

14460.00	12.31	584.91	0.00	0.00	582.99	0.08	0.01	0.01	578.91
1440.	25.	1226.	459.	92.	513.	356.	44.	16.	526.84
0.62	0.28	2.39	0.28	0.000	0.030	0.100	0.033	572.60	320.00
0.000122	57.	57.	57.	2	0	0	0.00	400.00	770.00

FLOW DISTRIBUTION FOR SECNO= 14460.00 CWSEL= 584.91

STA=	370.	473.	527.	770.
PER Q=	1.3	85.9	11.3	
AREA=	91.5	513.0	557.7	
VEL=	0.3	2.4	0.3	

1490 HH CARD USED
*SECNO 14461.000

3370 NORMAL BRIDGE,NRD= 15 MIN ELTRD= 580.00 MAX ELLC= 581.66

3470 ENCROACHMENT STATIONS= 370.0 770.0 TYPE= 1 TARGET= 600.000

I/S INSIDE D/S FACE OF S.B. FORT ST.

14461.00	12.00	584.90	2.00	0.20	565.65	2.12	0.080	0.11	578.90
1440.	96.	1118.	276.	67.	394.	330.	25.	15.	526.90
1.29	0.87	3.87	1.45	1.000	1.000	0.100	0.111	572.40	320.00
0.000439	1.	1.	1.	1	0	0	-176.56	400.00	770.00

FLOW DISTRIBUTION FOR SECNO= 14321.50 CWSEL= 583.90

STA=	370.	473.	527.	770.
PER Q=	1.2	79.3	19.6	
AREA=	59.3	394.0	529.9	
VEL=	0.3	2.3	0.5	

1490 HH CARD USED
*SECNO 14321.001

3370 NORMAL BRIDGE,NRD= 15 MIN ELTRD= 580.00 MAX ELLC= 581.66

3470 ENCROACHMENT STATIONS= 370.0 770.0 TYPE= 1 TARGET= 600.000

I INSIDE U/S FACE OF S.B. FORT ST.

14321.00 12.30 584.91 0.00 0.00 579.09 0.11 0.003 0.01 578.91

FORM 1411-00-PRINTED BY ROTARY MANIFOLD FORMS
PRINTED IN U.S.A.

	1410.	17.	1115.	277.	61.	395.	534.	65.	16.	578.90
	0.43	0.29	2.83	0.52	0.080	0.020	0.100	0.039	572.60	320.00
	0.000434	60.	60.	40.	1	0	0	-176.58	400.00	770.00

FLOW DISTRIBUTION FOR SECNO= 14521.00 CWSEL= 584.93

STA=	370.	473.	527.	770.
PER Q=	1.2	79.1	19.7	
AREA=	41.4	396.8	533.8	
VEL=	0.3	2.7	0.5	

1490 NH CARD USED

*SECNO 14522.000

3470 ENCROACHMENT STATIONS= 370.0 770.0 TYPE= 1 INCRST= 400.000

U/S FACE OF U.S. FORT ST.

	14522.00	12.36	584.96	0.00	0.00	585.03	0.08	0.06	0.01	576.90
	1410.	27.	1221.	162.	96.	516.	569.	65.	16.	578.90
	0.43	0.28	2.37	0.28	0.040	0.030	0.100	0.033	572.60	320.00
	0.000119	1.	1.	1.	2	0	0	0.00	401.05	770.00

FLOW DISTRIBUTION FOR SECNO= 14522.00 CWSEL= 584.96

STA=	370.	473.	527.	770.
PER Q=	1.9	86.6	11.5	
AREA=	96.6	515.5	569.1	
VEL=	0.3	2.4	0.3	

1490 NH CARD USED

*SECNO 14572.000

	ECHO	DEPTH	CWSEL	CVINS	WSELK	FD	HV	AT	FLOAT	BACK WTR
	O	QTOT	ZCH	SLOB	XLOB	ACH	CROS	XNL	CD	EFF/ZTOP
	TYPE	VLOB	AT1	WSEL	XNCH	XLCH	XR	DT	FLARE	SRT
	SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	I.12	ICONT	CURAR	TOP.TO	BLAST

3470 ENCROACHMENT STATIONS= 290.0 710.0 TYPE= 1 INCRST= 420.000

VALLEY SECT. 50' U/S OF S.B. FORT ST. 5858

	14572.00	12.25	584.95	0.00	0.00	585.06	0.11	0.01	0.02	584.20
	1410.	14.	1175.	221.	79.	402.	541.	66.	17.	581.20
	0.44	0.18	2.92	0.41	0.120	0.035	0.120	0.033	572.70	260.00
	0.003423	50.	50.	50.	2	0	0	0.00	420.10	710.00

FLOW DISTRIBUTION FOR SECNO= 14572.00 CWSEL= 584.45

STA=	290.	415.	470.	710.
PER Q=	1.0	97.3	1.7	
AREA=	79.4	402.1	541.1	
VEL=	0.2	2.9	0.4	

CFS= 0.100 CCHV= 0.500

1490 NH CARD USED

*SECNO 14592.000

3470 ENCROACHMENT STATIONS= 159.0 2210 TYPE= 1 INCRST= 60.000

VALLEY SECT.

15292.00	10.84	585.24	0.00	0.00	585.46	.21	0.36	0.03	587.20
1410.	0.	1410.	0.	0.	380.	0.	77.	20.	100300.00
3.49	0.00	3.71	0.00	0.120	0.035	3.120	0.013	574.40	144.81
0.000735	720.	720.	690.	2	0	0	0.08	68.19	225.00

FLOW DISTRIBUTION FOR SECNO= 15292.00 CWSEL= 585.24

STA=	165.	225.
PER Q=	100.0	
AREA=	360.2	
VEL=	3.7	

CCHV= 0.300 CEHV= 0.500

*SECNO 15820.000
*SO CROSS SECTION 15820.00 EXTENDED 0.19 FEET.

3470 ENCROACHMENT STATIONS= 50.0 162.0 TYPE= 1 TARGET= 112.000

VALLEY SECT. 50' D/S OF LAFAYETTE 582.60

15820.00	8.59	585.59	0.00	0.00	585.97	0.49	0.43	0.09	587.20
1410.	87.	1269.	55.	44.	243.	48.	81.	21.	578.30
0.52	1.98	5.23	1.14	0.050	0.035	0.080	0.033	577.00	75.84
0.020680	350.	828.	690.	2	0	0	0.03	68.14	162.00

FLOW DISTRIBUTION FOR SECNO= 15820.00 CWSEL= 585.59

STA=	74	95	115	127	162
PER Q=	5.2	09.9	5.3	3.0	
AREA=	63.9	262.7	54.3	1.9	
VEL=	2.0	5.	1.2	1.4	

*SECNO 15870.000
*SO CROSS SECTIO 15870.00 EXTENDED 0.36 FEET

3470 ENCROACHMENT STATIONS= 50.0 150.0 TYPE= 1 TARGET= 100.000

D/S FACE OF LAFAYETTE

15870.00	9.75	585.75	0.00	0.00	586.04	0.29	0.24	0.03	587.00
1410.	156.	1138.	99.	82.	261.	52.	82.	21.	572.00
0.52	1.94	4.75	1.21	0.050	0.035	0.080	0.034	577.00	67.57
0.020680	50.	50.	50.	2	0	0	0.01	65.26	132.69

FLOW DISTRIBUTION FOR SECNO= 15870.00 CWSEL= 585.75

STA=	67.	86.	176.	193.
PER Q=	11.2	01.8	7.0	
AREA=	81.5	265.1	81.5	
VEL=	1.9	4.7	1.2	

SPECIAL ORDER=

0.00	1.65	3.00	100.00	23.00	0.00	169.00	0.00	577.00	577.00

*SECNO 15914.000
3280 CROSS SECTION 15914.00 EXTENDED 1.19 FEET

PRESSURE AND WEIR FLOW

YCRRS	EGLOC	H3	QWEIR	QBR	BAREA	TRAPEZOID AREA	ELLC	ELTWD
587.36	586.04	0.00	326.	1682.	152.	168.	586.00	585.47

3471 ENCROACHMENT STATIONS= 50.0 150.0 TYPE= 1 TARGET= 100.000

U/S FACE OF LAFAYETTE 587.35 +.78

15914.00	9.59	586.59	0.00	0.00	586.82	0.23	0.77	0.00	577.06
1410.	173.	1129.	108.	102.	269.	103.	62.	22.	577.00
0.53	1.20	4.20	1.05	0.050	0.035	0.080	1.033	577.00	50.00
0.000481	44.	44.	44.	2	0	3	0.00	100.00	150.00

FLOW DISTRIBUTION FOR SECNO= 15914.00 CHSEL= 586.59

STA=	50.	66.	86.	116.	134.	150.
FLOW=	0.9	12.2	85.1	7.5	0.1	
AREA=	3.9	57.6	269.6	97.3	5.0	
VEL=	0.2	1.1	4.2	1.1	0.2	

*SECNO 15964.000
3280 CROSS SECTION 15964.00 EXTENDED 1.14 FEET

SECNO	STCHL	CHSEL	LOBCNS	WSEL	FB	WV	ALPHA	DELTA SLEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TOA	LEFTWEIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTI	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IHP	ICOUT	CONAP	TOPIN	ELMAX

3471 ENCROACHMENT STATIONS= 0.0 150.0 TYPE= 1 TARGET= 149.999

VALLEY SECT. 50' U/S OF LAFAYETTE 587.3

15964.00	9.54	586.56	0.00	0.00	586.94	0.38	1.00	0.19	577.30
1410.	157.	1196.	57.	95.	215.	93.	63.	22.	577.00
0.33	1.66	5.47	1.07	0.050	0.035	0.080	0.033	577.30	0.00
0.000874	50.	50.	50.	2	0	0	0.00	150.00	150.00

FLOW DISTRIBUTION FOR SECNO= 15964.00 CHSEL= 586.56

STA=	0.	75.	83.	118.	122.	150.
FLOW=	0.9	10.8	84.0	3.9	0.2	
AREA=	20.3	46.6	218.7	66.4	8.9	
VEL=	0.3	3.2	5.5	1.2	0.3	

*SECNO 16194.000

3471 ENCROACHMENT STATIONS= 0.0 150.0 TYPE= 1 TARGET= 150.000

VALLEY SECT. 50' D/S OF I-75

16194.00	10.40	586.90	0.00	0.00	587.13	0.23	0.14	0.05	578.60
1410.	23.	1322.	65.	30.	337.	64.	65.	22.	578.60
0.55	1.76	3.93	1.31	0.080	0.035	0.080	0.029	576.50	795.00
0.003478	230.	230.	230.	2	0	0	0.00	50.00	845.00

587.58 587.33

FLOW DISTRIBUTION FOR SECNO= 16194.00 CWSEL= 586.90

STA=	793.	799.	835. 845.
PER Q=	4.6	91.0	4.6
AREA=	30.1	335.7	64.2
VEL=	0.8	3.9	1.0

*SECNO 16244.000

BASS OVERBANK AREA ASSUMED NO-EFFECTIVE-EL-EG= 587.60 ELEV= 590.00

D/S FACE OF I-75 BRIDGE

16244.00	10.20	586.70	0.00	0.00	587.41	0.71	0.00	0.24	578.60
1410.	0.	1410.	0.	0.	215.	0.	0.	22.	578.60
0.55	0.00	6.73	0.00	0.030	0.035	0.080	0.033	576.50	818.57
0.001998	50.	50.	50.	2	0	0	0.00	22.93	841.50

FLOW DISTRIBUTION FOR SECNO= 16244.00 CWSEL= 586.70

STA=	819.	842.
PER Q=	100.0	
AREA=	209.5	
VEL=	6.7	

*SECNO 16238.000

3370 NORMAL BRIDGE,NRD= 6 MIN ELTRD= 583.60 MAX ELLO= 568.10

BASS OVERBANK AREA ASSUMED NO-EFFECTIVE-ELEG= 583.60 ELEV= 583.60

16245.00	10.20	586.70	0.00	0.30	587.61	0.71	0.00	0.30	578.60
1410.	0.	1410.	0.	0.	205.	0.	0.	22.	578.60
0.55	0.00	6.26	0.00	0.080	0.020	0.080	0.035	576.50	818.57
0.000652	1.	1.	1.	0	0	0	0.00	22.35	841.50

FLOW DISTRIBUTION FOR SECNO= 16245.00 CWSEL= 586.70

STA=	819	842
PER Q=	100.0	
AREA=	209.5	
VEL=	5.8	

*SECNO 16503.000

3370 NORMAL BRIDGE,NRD= 6 MIN ELTRD= 603.60 MAX ELLO= 588.10

BASS OVERBANK AREA ASSUMED NO-EFFECTIVE-ELEG= 603.60 ELEV= 603.60

16503.00	10.20	596.91	0.00	0.00	597.54	0.63	0.00	0.01	603.6

POINTED IN U.S.A.
FORM 1011-00 PRINTED BY ROTARY MANIFOLD FORMS

1410.	0.	1410.	0.	0.	213.	0.	96.	22.	578.60
0.56	0.00	6.61	0.00	0.080	0.020	0.060	0.033	576.50	818.57
0.003621	258.	258.	258.	2	0	0	-1.11	22.93	841.50

FLOW DISTRIBUTION FOR SECNO= 16503.00 CWSEL= 586.91

STA= 819. 842.
PER Q= 100.0
AREA= 213.2
VEL= 3.6

SECNO 16504.000

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	KV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	WLOB	WCH	WROB	XLL	XNCH	XNR	LTJ	ELMIN	SST
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IN2	ICONT	CTRL	TOPWID	ELMST

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLE= 603.60 ELREA= 603.60

U/S FACE OF I-75 BRIDGE

16504.00	10.41	586.91	0.00	0.00	587.59	0.67	0.00	0.00	603.60
1410.	0.	1410.	0.	0.	214.	0.	96.	22.	578.60
0.56	0.00	6.58	0.00	0.080	0.035	0.060	0.033	576.50	818.57
0.003621	1.	1.	1.	0	0	0	0.00	22.93	841.50

FLOW DISTRIBUTION FOR SECNO= 16504.00 CWSEL= 586.91

STA= 819. 842.
PER Q= 100.0
AREA= 214.2
VEL= 3.6

SECNO 16556.000

3465 DIVIDED FLOW

3470 ENCROACHMENT STATIONS= 550.0 683.0 TYPE= 1 TARGET= 129.000

VALLEY SECT. 50' U/S OF I-75 5884

16556.00	10.97	587.97	0.00	0.00	587.77	0.20	0.00	0.14	578.80
1330.	66.	1339.	127.	73.	296.	161.	57.	52.	576.95
0.56	0.91	3.86	0.90	0.080	0.035	0.060	0.033	576.60	583.89
0.002396	50.	50.	50.	2	2	0	0.00	93.61	683.00

Do I have appro reasonable

FLOW DISTRIBUTION FOR SECNO= 16556.00 CWSEL= 587.97

STA= 589. 605. 635. 665. 683.
PER Q= 4.8 65.6 9.3 0.2
AREA= 70.6 295.4 129.6 13.6
VEL= 0.9 3.9 1.3 1.3

SECNO 16626.000

3470 ENCROACHMENT STATIONS= 594. 655.0 TYPE= 1 TARGET= 61.000

VALLEY SECT. 50' D/S OFINDUSTRIAL DRIVE7

	16826.00	12.67	587.77	0.00	0.00	587.86	0.09	0.06	0.03	575.40
	1330.	154.	1362.	114.	135.	397.	121.	91.	23.	575.40
	0.60	1.01	2.67	0.94	0.060	0.035	0.060	0.033	575.50	594.00
	0.000138	222	222	222	2	1	0	0.00	82.00	456.00

FLOW DISTRIBUTION FOR SECNO= 16826.00 CWSEL= 587.77

STA=	594.	440.	442.	456.
PCT Q=	11.5	79.5	9.0
AREA=	152.7	397.4	121.2
VEL=	1.0	2.7	0.9

1495 NH CARD USED
*SECNO 16876.000
3280 CROSS SECTION 16876.00 CRTELOED 0.25 BEST

3493 OVERBANK AREA ASSUMED NON-EFFECTIVE,FLLEA= 590.50 E AREA= 550.50

D/S FACE OF INDUSTRIAL DRIVE 588.8

	16276.00	13.15	587.75	0.00	0.00	587.90	0.16	0.01	0.03	524.60
	1330.	0.	1330.	0.	0.	435.	0.	91.	23.	574.60
	0.60	0.00	3.06	0.00	0.060	0.035	0.060	0.033	574.60	590.00
	0.000260	50	50	50	2	0	0	0.51	33.13	503.90

FLOW DISTRIBUTION FOR SECNO= 16876.00 CWSEL= 587.75

STA=	490.	335.
PCT Q=	100.0
AREA=	435.3
VEL=	3.1

SPECIAL BRIDGE

SS	XR	XRCD	CCFO	RDLEN	SWC	BHP	OPSEA	SR	ALCAH	FLOID
	0.00	1.32	3.00	3.00	26.83	0.00	350.00	1.00	574.90	574.60

1495 NH CARD USED
*SECNO 16993.100
PRESSURE FLOW

EGPRS	EGLWC	WR	QWEIR	QPR	BAREA	TRAPEZOID	ELLC	ELTRD
598.21	598.20	0.00	0.	1550.	330.	350.	587.50	589.75

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,FLLEA= 590.50 E AREA= 550.50

D/S FACE OF INDUSTRIAL DRIVE

	16993.00	13.17	587.75	0.00	0.00	588.91	0.16	0.01	0.03	574.90
	1330.	0.	1330.	0.	0.	435.	0.	91.	23.	574.90

PRINTED IN U.S.A.
FORM 1411 GO-PRINTED BY ROTARY MANIFOLD FORMS

	0.61	0.00	5.05	0.00	0.060	0.035	0.		0.135	574.90	290.00
	0.000259	87.	87.	87.	2	3			0.00	33.10	323.10

FLOW DISTRIBUTION FOR SECNO= 16963.00 CWSEL= 590.26

CTA= 290. 333.

PER Q= 100.0
AREA= 435.6
VEL= 3.1

1490 NR CARD USED
*SECNO 17013.000

SECNO	DEPTH	CWSEL	CRIWS	USELK	EG	HV	HL	OLOSS	BANK ELEV	
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT	
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTP	ELMIN	SSTA	
SLOPE	KLOBL	KLCH	KLOBR	ITRIAL	IHP	ICONT	LOSS	TOPWTD	ENDST	

3470 ENCROACHMENT STATIONS= 304.0 437.0 TYPE= 1 TARGET= 133.000

VALLEY SECT.50' R/S OF INDUSTRIAL DRIVE

587.9

17013.00	11.38	588.13	0.00	0.00	588.26	0.00	0.01	0.13	579.20	
1330.	254.	927.	148.	289.	395.	164.	93.	23.	576.20	
0.62	0.88	2.35	0.90	0.060	0.035	0.060	0.034	576.20	304.00	
0.000111	50.	50.	50.	2	3	1	0.00	110.95	414.95	

FLOW DISTRIBUTION FOR SECNO= 17013.00 CWSEL= 588.18

STA= 304. 324. 354. 387. 407. 415.
PER Q= 2.3 16.8 69.7 10.8 0.3
VEL= 0.5 1.0 2.3 1.0 0.5

1490 NR CARD NEED
*SECNO 17255.000

3470 ENCROACHMENT STATIONS= 414.0 466.0 TYPE= 1 TARGET= 52.670

VALLEY SECT.300' R/S OF RR @ CENTRAL T.P.

17255.00	10.28	588.10	0.00	0.00	588.32	0.14	0.04	0.06	578.20	
1330.	51.	1248.	30.	66.	397.	66.	97.	24.	576.10	
0.64	0.78	3.16	0.33	0.300	0.035	0.065	0.035	577.90	414.00	
0.000249	242.	242.	242.	2	0	1	0.00	32.30	465.00	

FLOW DISTRIBUTION FOR SECNO= 17255.00 CWSEL= 588.18

STA= 414. 422. 444. 462.
PER Q= 3.9 93.5 2.6
VEL= 0.6 3.9 0.7

CRWS= 0.300 CSHW= 0.500
*SECNO 17305.000

17305.00	10.19	588.09	0.00	0.00	588.45	0.36	0.02	0.11	577.90
1330.	0.	1330.	0.	0.	277.	0.	97.	24.	577.90
0.64	0.00	4.80	0.00	0.080	0.035	0.080	0.033	577.90	356.40
0.000860	50.	50.	90.	2	5	0	0.00	27.20	383.60

FLOW DISTRIBUTION FOR SECNO= 17305.00 CWSEL= 588.09

STA= 356. 384.
PER Q= 100.0
AREA= 277.2
VEL= 4.8

SPECIAL BRIDGE

SE	WK	AXOB	COEC	BALE	S.C	BCP	LARFA	SS	E.CHN	CLCHE
1.25		2.49	3.00	5.00	24.20	3.21	112.0	.05	577.50	577.90

*SECNO 17502.000
PRESSURE FLOW

SUBES	BALIE	'LS	ASTIO	ORF	BAREA	TRAJECTORY AREA	ELLC	ELTRA
590.16	588.55	0.11	0.	1330.	182.	182.	585.50	600.40

3/95 OVERBANK AREA ASSIGNED TO =EFFECTIVE FLOW= 600.40 ELEV= 600.40

U/S FACE OF PENN CENTRAL R.R. BRIDGE

17502.00	12.11	588.00	0.00	0.20	588.19	0.26	1.29	0.08	577.91
1330.	0.	1330.	0.	0.	826.	0.	0.	24.	577.90
0.65	0.80	4.08	0.00	0.080	0.035	0.080	0.033	577.90	356.40
0.000544	197.	197.	197.	2	3	0	0.00	27.20	383.60

FLOW DISTRIBUTION FOR SECNO= 17502.00 CWSEL= 588.90

STA= 356. 384.
PER Q= 100.0
AREA= 326.4
VEL= 4.1

CARD OR CALC USED
*SECNO 17552.000

367D ENCROACHMENT STATIONS= 277.0 454.0 TYPE= 1 TARGET= 127.000

VALLEY SECT. 30' D/S OF PENN CENTRAL R.R.

17552.00	12.61	590.11	0.00	0.20	587.82	0.50	0.21	0.05	577.80
1330.	148.	823.	259.	222.	831.	314.	99.	34.	577.50
0.66	0.67	3.67	0.61	0.080	0.035	0.080	0.033	577.50	277.00
0.000179	50.	54.	150.	2	3	0	0.00	127.00	404.00

FLOW DISTRIBUTION FOR SECNO= 17552.00 CWSEL= 590.11

STA= 277. 313. 328. 354. 393. 454. 460.

PER Q=	4.6	6.5	69.4	11.6	7.9
AREA=	121.1	100.9	300.9	155.9	162.5
VEL=	0.5	0.9	3.1	1.0	0.6

CCHV= 0.100 CEHV= 0.300
*SECNO 17817.000

SECNO	QRPTH	CHSEL	COTHS	WSELK	FG	BV	LJ	QLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TBA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	STN	FLMIN	SSTA
SLOPE	XLOOL	XLCH	XLOCR	ITRIAL	IM2	ICONT	CORAR	TOPWID	ENDST

3470 ENCROACHMENT STATIONS= 8.8 230.4 TYPE= 1 TARGET= 221.610

VALLEY FROM SUBDIV PLANS

17817.00	13.31	590.21	0.00	0.00	550.26	0.05	0.04	0.00	583.30
1330.	130.	1101.	89.	213.	332.	158.	1[illegible]	25.	546.00
0.70	0.61	2.07	0.63	0.050	0.035	0.053	0.033	576.90	8.80
0.000144	265.	265.	265.	0	0	0	0.00	221.60	230.40

FLOW DISTRIBUTION FOR SECNO= 17817.00 CHSEL= 590.21

STA=	9.	50.	107.	162.	225.	230.
PER Q=	5.2	4.6	82.8	7.3	0.2	
AREA=	108.0	105.3	532.4	151.7	6.0	
VEL=	0.6	0.6	2.1	0.6	0.3	

1420 NB CARD USED
*SECNO 18106.000
3280 CROSS SECTION 18106.00 EXTENDED 1.49 FEET

3470 ENCROACHMENT STATIONS= 203.0 450.0 TYPE= 1 TARGET= 221.000

VALLEY SECT. 50' D/S OF PORTER AVE.

18106.00	11.39	590.19	0.00	0.00	550.35	0.16	0.06	0.03	592.00
1330.	254.	1024.	30.	317.	208.	346.	170.	46.	573.00
0.77	0.12	3.66	0.15	0.020	0.035	0.052	0.033	579.00	2[illegible]
0.000298	289.	289.	289.	2	0	0	0.00	175.00	450.00

FLOW DISTRIBUTION FOR SECNO= 18106.00 CHSEL= 590.19

STA=	203.	320.	340.	365.	393.	410.	430.
PER Q=	3.9	10.2	77.1	2.6	0.4	0.6	
AREA=	181.0	129.8	279.8	191.5	50.8	97.7	
VEL=	0.7	1.5	3.7	0.2	0.1	2.1	

1420 NB CARD USED
*SECNO 18156.000

3470 ENCROACHMENT STATIONS= 275.0 450.0 TYPE= 1 TARGET= 175.000

D/S FACE OF PORTER AVE.

18156.00	11.19	590.19	0.00	0.00	550.52	0.16	0.04	0.03	592.00
1350.	238.	1060.	39.	247.	281.	320.	111.	82.	573.00
1.75	0.95	3.76	0.14	0.041	0.035	0.900	0.033	579.00	2[illegible]
0.000237	32.	80.	50.	2	0	0	0.00	175.00	450.00

PRINTED IN U.S.A.
FORM 1411 GO-PRINTED BY ROTARY MANIFOLD FORMS

FLOW DISTRIBUTION FOR SECNO= 18156.00 CWSEL= 590.19

STA=	275.	280.	332.	350.	375.	403.	450.
PER Q=	0.0	4.7	12.8	79.5	2.2	0.7	
AREA=	9.0	122.6	135.0	201.2	130.4	121.9	
VEL=	0.0	0.6	1.3	3.1	0.2	0.1	

1490 NH CARD USED
*SECNO 18157.000

3370 NORMAL BRIDGE,NPR= 10 MIN ELEV= 585.20 MAX ELEV= 585.90

3470 ENCROACHMENT STATIONS= 275.0 450.0 TYPE= 1 TARGET= 175.000

(1 INSIDE OF OAS TYPE OF ARTER AVE.

18157.00	11.09	590.09	0.00	0.00	590.62	0.33	0.00	0.04	579.00
1330.	174.	1127.	29.	149.	227.	178.	111.	26.	579.00
0.73	1.17	4.95	0.16	0.063	0.020	0.500	0.033	575.00	275.00
0.001014	1.	4.	1.	2	0	0	-264.04	175.00	450.00

FLOW DISTRIBUTION FOR SECNO= 18157.00 CWSEL= 590.09

STA=	275	280	330	350	375	403	450
PER Q=	3.0	9.0	4.9	84.7	2.7	1.5	
AREA=	9.4	97.0	43.0	227.5	69.1	116.6	
VEL=	0.1	1.2	1.3	5.0	0.2	0.2	

1490 NH CARD USED
*SECNO 18195.000

3370 NORMAL BRIDGE,NPR= 10 MIN ELEV= 585.70 MAX ELEV= 585.90

3470 ENCROACHMENT STATIONS= 275.0 450.0 TYPE= 1 TARGET= 175.000

(1 INSIDE OF OAS TYPE OF ARTER AVE.

18195.00	11.12	590.16	0.00	0.00	590.45	0.32	0.00	0.00	575.00
1330.	179.	1122.	29.	153.	229.	181.	112.	27.	579.00
0.73	1.17	4.91	0.16	0.063	0.020	0.500	0.033	579.00	275.00
0.003988	38.	38.	38.	2	0	0	-264.04	175.00	450.00

3520 LAST NOT OK OF CARD 720.00

FLOW DISTRIBUTION FOR SECNO= 18195.00 CWSEL= 590.16

STA=	275	280	330	350	375	403	450
PER Q=	0.7	9.2	4.2	84.0	0.7	1.1	
AREA=	8.6	99.3	44.2	227.6	62.4	113.8	
VEL=	0.1	1.2	1.2	4.9	0.2	0.2	

1490 NH CARD USED
*SECNO 18196.000

SECNO	DEPTH	CWSEL	CRITWS	AESEL	EG	HV	AL	FLOPR	BACK STEP
	0.06	QCH	QROB	FLOB	ACH	AROB	WPL	TW	LEFTWTR.T
FLOBE	W.OS	QC1	WSEL	TOPW	WCH	XNR	TIME	WTR	BST
SLOPE	XLOBL	XLOB	KLOBR	STORAGE	TRD	ACONT	QDFAC	TOPWID	ELOST

FORM 1411-GO-PRINTED BY ROTARY MANIFOLD FORMS
PRINTED IN U.S.A.

3470 ENCROACHMENT STATIONS= 279.0 450.0 TYPE= 1 TARGET= 175.000

U/S FACE OF PORTER AVE

18496.00	11.30	590.30	0.00	0.30	590.47	0.17	0.00	0.01	579.00
1330.	238.	1152.	40.	256.	284.	312.	132.	27.	579.00
0.73	0.94	3.71	0.13	0.061	0.030	0.500	0.033	579.00	275.00
0.000221	1.	1.	1.	2	0	0	0.00	175.00	450.00

FLOW DISTRIBUTION FOR SECNO= 18496.00 CHSEL= 590.30

STA=	275.	280.	330.	350.	375.	403.	450.
PER Q=	0.0	5.0	12.9	79.1	2.2	0.8	
AREA=	9.6	107.4	137.0	283.6	191.1	126.4	
VEL=	0.0	0.6	1.3	3.7	0.2	0.1	

1490 NH CARD USED
*SECNO 18246.000
3280 CROSS SECTION 18245.00 EXTENDED 1.52 FEET

3470 ENCROACHMENT STATIONS= 320.0 470.0 TYPE= 1 TARGET= 150.000

VALLEY SECT. 50' U/S OF PORTER AVE.

18246.00	11.22	590.22	1.00	0.00	590.53	0.31	0.00	0.04	579.00
1330.	137.	1131.	62.	144.	236.	376.	116.	27.	579.00
0.72	0.95	4.80	0.16	0.100	0.055	0.500	0.033	579.00	320.00
0.000309	50.	50.	50.	2	0	0	0.00	150.00	470.00

FLOW DISTRIBUTION FOR SECNO= 18246.00 CHSEL= 590.22

STA=	320.	335.	359.	372.	396.	410.	430.
PER Q=	1.5	8.5	85.0	1.5	0.7	2.1	0.3
AREA=	36.3	107.5	235.6	94.0	70.1	176.0	35.0
VEL=	0.5	1.1	4.8	0.2	0.1	0.2	0.1

CCHV= 1.105 CEHV= 1.320
*SECNO 18246.000

3470 ENCROACHMENT STATIONS= 159.0 309.0 TYPE= 1 TARGET= 150.000

VALLEY SECT. BET., PORTER AND UPPER PLACE

18543.00	11.96	590.96	1.00	0.00	590.60	0.15	0.12	0.02	579.00
1330.	59.	971.	300.	64.	339.	373.	116.	28.	586.60
0.77	0.92	2.95	0.15	0.050	0.035	0.050	0.033	578.60	159.00
0.001307	299.	299.	299.	2	0	0	0.00	150.00	309.00

FLOW DISTRIBUTION FOR SECNO= 18543.00 CHSEL= 590.53

STA=	159.	184.	220.	305.	309.
PER Q=	4.4	73.0	21.3	1.2	
AREA=	64.4	339.8	852.2	20.7	
VEL=	0.9	2.9	3.1	0.3	

CCHV= 0.300 CEHV= 0.500
1490 NH CARD USED
*SECNO 18529.000

PRINTED IN U.S.A.

FORM 1411-GO-PRINTED BY ROTARY MANIFOLD FORMS

3280 CROSS SECTION 19829.00 EXTENDED 0.64 FEET

3470 ENCROACHMENT STATIONS= 290.0 455.0 TYPE= 1 TARGET= 165.000

VALLEY SECT. 5'! D/S OF RAUP? F!

18829.00	11.94	590.64	0.00	0.00	590.74	0.11	0.08	0.00	578.70	
1330.	704.	581.	44.	457.	162.	346.	125.	29.	578.70	
0.80	1.54	3.58	0.14	0.051	0.035	0.500	0.099	578.70	290.00	
0.000261	284.	284.	284.	2	0	0	0.00	165.10	455.00	

FLOW DISTRIBUTION FOR SECNO= 18829.00 CWSEL= 590.64

STA=	290.	345.	366.	377.	390.	455.
PER Q=	19.3	35.7	43.7	1.0	2.4	
AREA=	206.2	160.7	162.6	76.0	249.5	
VEL=	0.9	2.8	3.6	0.2	0.1	

1490 NN CARD USED
SECNO 18879.000
3280 CROSS SECTION 18879.00 EXTENDED 0.55 FEET

3470 ENCROACHMENT STATIONS= 290.0 455.0 TYPE= 1 TARGET= 165.000

U/S FACE OF RAUP? P.. BRIDGE

18879.00	11.95	590.65	0.00	0.00	590.76	0.11	0.81	0.00	578.70
1330.	690.	600.	39.	456.	163.	347.	124.	29.	470.70
0.80	1.51	3.69	0.11	0.046	0.030	0.500	0.035	578.70	290.00
0.000260	290.	290.	290.	3	1	0	0.00	164.80	455.00

FLOW DISTRIBUTION FOR SECNO= 18879.00 CWSEL= 590.65

STA=	290.	345.	366.	377.	390.	455.
PER Q=	17.1	36.3	44.1	1.0	2.4	
AREA=	207.0	161.3	162.9	76.1	270.5	
VEL=	1.0	2.9	3.7	0.2	0.	

1490 NN CARD USED
SECNO 18850.000
3280 CROSS SECTION 18850.00 EXTENDED 0.65 FEET

SECNO	DEPTH	CWSEL	CRWS	WSELK	FQ	KV	HL	ALOSS	BANK STA
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TW=	LEFT/RIGHT
TYPE	VLOB	VCH	VROB	XR	XNCH	XXH	WT	ELMIN	SSTA
SLOPE	XLOBL	XLOBR	XLOBR	TTTIAL	ZHI	ZCOR	QCORTR	TOPWID	ESTA

3370 NORMAL BRIDGE,NRD= 18 MIN SLOPE= 565.00 MAX ALLOW= 583.27

3470 ENCROACHMENT STATIONS= 290.0 455.0 TYPE= 1 TARGET= 165.000

1' INSIDE OF D/S FACE RAUP

18850.00	11.95	590.64	0.00	0.00	590.74	0.11	0.08	0.00	578.70

PRINTED IN U.S.A.

FORM 1411.00 PRINTED BY ROTARY MANIFOLD FORMS

1330.	805.	477.	48.	400.	138.	319.	1[illegible]	29.	578.70
0.81	2.01	3.46	0.15	0.045	0.020	0.500	0.[illegible]3	578.70	290.00
0.000427	1.	1.	1.	1	0	0	-111.24	165.00	495.00

FLOW DISTRIBUTION FOR SECNO= 18880.00 CWSEL= 590.66

STA=	290.	345.	364.	377.	386.	455.
PER Q=	24.8	35.8	35.8	0.6	3.0	
AREA=	207.0	102.7	137.6	48.1	270.5	
VEL=	1.1	4.6	3.5	0.2	0.1	

1490 NH CARD USED
*SECNO 18910.000
3280 CROSS SECTION 18910.00 EXTENDED 0.67 FEET

3370 MODIFIED BRIDGE XRD= 13 NEW FLTD= 585.00 MAX FLC= 589.20

3470 ENCROACHMENT STATIONS= 290.0 455.0 TYPE= 1 TARGET= 165.000

1' INSIDE OF U/S FACE RIDGE PL.

18910.00	11.97	590.67	0.00	0.00	590.78	0.10	0.01	0.00	578.70
1330.	806.	476.	48.	401.	138.	320.	125.	29.	578.70
0.81	2.01	3.45	0.13	0.045	0.020	0.500	0.035	578.70	290.00
0.000425	30.	30.	30.	0	0	0	-111.24	165.00	495.00

FLOW DISTRIBUTION FOR SECNO= 18910.00 CWSEL= 590.67

STA=	290.	345.	364.	377.	386.	455.
PER Q=	24.8	35.8	35.8	0.6	3.0	
AREA=	207.0	102.7	137.6	48.1	270.5	
VEL=	1.1	4.6	3.5	0.2	0.1	

1490 NH CARD USED
*SECNO 18911.000
3280 CROSS SECTION 18911.00 EXTENDED 3.67 FEET

3470 ENCROACHMENT STATIONS= 290.0 455.0 TYPE= 1 TARGET= 165.000

U/S FACE OF RIDGE PL. BRIDGE

18911.00	11.97	593.67	0.10	0.20	593.71	0.11	0.30	0.00	582.70
1330.	691.	500.	39.	459.	163.	348.	125.	29.	578.70
0.81	1.50	3.68	0.11	0.047	0.030	0.500	0.035	578.70	290.00
0.000202	1.	1.	1.	0	0	0	0.10	165.00	495.00

FLOW DISTRIBUTION FOR SECNO= 18911.00 CWSEL= 590.67

STA=	290.	345.	364.	377.	386.	455.
PER Q=	17.1	34.8	45.1	1.9	2.1	
AREA=	293.1	101.4	192.1	75.3	271.9	
VEL=	0.8	2.9	3.7	0.2	0.1	

1490 NH CARD USED
*SECNO 18960.000
3280 CROSS SECTION 18960.00 EXTENDED [illegible]

PRINTED IN U.S.A.

FORM 1411-OD-PRINTED BY ROTARY MANIFOLD FORMS.

3470 ENCROACHMENT STATIONS= 290.0 455.0 TYPE= 1 TARGET= 165.000

VALLEY SECT. 50' U/S OF RAUPP PL.

18961.00	11.99	590.69	0.00	0.00	590.79	0.11	0.01	0.00	578.70
1330.	706.	580.	45.	460.	163.	349.	126.	29.	576.70
0.82	1.53	3.56	0.13	0.051	0.035	0.500	0.033	578.70	290.00
0.000656	50.	50.	50.	3	0	0	0.00	165.00	455.00

FLOW DISTRIBUTION FOR SECNO= 18961.00 CWSEL= 590.69

STA=	290	345	364	377	396	455
PER C=	19.4	33.7	43.6	1.0	2.4	
AREA=	258.7	161.6	163.0	74.4	272.6	
VEL=	0.9	2.6	3.0	0.2	1.1	

1490 NN CARD USED
*SECNO 19112.000
3261 CROSS SECTION 19112.00 EXTENDED 0.01 FEET

3470 ENCROACHMENT STATIONS= 220.0 400.0 TYPE= 1 TARGET= 180.000

VALLEY SECT. 50' U/S OF DIK

19112.00	11.66	590.66	1.00	0.00	590.42	0.26	0.04	0.00	579.00
1330.	18.	1277.	35.	239.	304.	230.	129.	30.	579.00
0.05	0.08	4.20	0.15	0.800	0.035	0.500	0.033	579.00	220.00
0.000470	151.	151.	151.	2	0	0	0.00	180.00	400.00

STA= 220. 275. 307. 335. 351. 400.

PER Q=	0.7	0.7	96.0	1.6	0.1
AREA=	106.3	68.9	304.2	165.9	112.7
VEL=	0.1	0.1	6.2	0.3	0.1

1490 NN CARD USED
*SECNO 19162.000
3261 CROSS SECTION 19162.00 EXTENDED 0.07 FEET

ERMS	DSTG	QWSEL	CWS-S	USALE	EG	EJ		QLOB	AMS RLEN
Q	QLOB	QCH	QROS	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROS	XNL	XNCH	XNR	WTN	FLTP	ASTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IBR	ICONT	CONVR	TOPWID	ENDST

3470 ENCROACHMENT STATIONS= 220.0 400.0 TYPE= 1 TARGET= 180.000

D/S FACE OF DIK BD. BRIDGE

19062.00	11.30	590.08	0.00	0.00	590.94	0.86	0.16	0.00	579.00
1330.	18.	1277.	35.	240.	305.	256.	129.	30.	579.00
0.83	1.04	4.19	0.15	0.800	0.035	0.500	0.033	579.00	220.00
0.000360	50.	50.	50.	0	0	0	0.00	180.00	400.00

PRINTED IN U.S.A.
FORM 1810-00 PRINTED BY ROTARY MANIFOLD FORMS

FLOW DISTRIBUTION FOR SECNO= 19162.00 CWSEL= 594.68

STA=	220.	295.	307.	333.	351.	400.
PER Q=	0.7	0.7	96.0	1.6	0.8	
AREA=	157.1	83.1	304.6	123.7	113.5	
VEL=	0.1	0.1	6.2	0.2	0.1	

1490 NH CARD USED
*SECNO 19163.000

3370 NORMAL BRIDGE,NRD= 20 MIN ELTRD= 588.20 MAX ELLC= 589.00

3470 ENCROACHMENT STATIONS= 220.0 400.0 TYPE= 1 TARGET= 180.000

1' INSIDE D/S FACE OF DAM

19163.00	11.52	591.52	3.00	0.00	591.10	0.54	0.00	0.18	579.00	
1330.	21.	1279.	30.	171.	204.	143.	980.	30.	579.00	
0.83	0.12	6.26	0.21	0.900	0.020	0.500	0.033	579.00	220.00	
0.001333	1	1	1	2	0	0	-239.66	180.00	400.00	

1979 flow WSPRO
15 ft below top of headwall = 587.0 - 588
Significant d/s storage appeared to reduce peak

FLOW DISTRIBUTION FOR SECNO= 19163.00 CWSEL= 590.52

STA=	220.	295.	307.	333.	351.	400.
PER Q=	1.3	0.2	96.2	0.6	1.6	
AREA=	145.4	26.0	294.4	40.6	105.8	
VEL=	0.1	0.1	6.3	0.2	0.2	

1490 NH CARD USED
*SECNO 19263.000
3280 CROSS SECTION 19263.00 EXTENDED 0.14 FEET

3370 NORMAL BRIDGE,NRD= 20 MIN ELTRD= 588.20 MAX ELLC= 585.00

3470 ENCROACHMENT STATIONS= 220.0 400.0 TYPE= 1 TARGET= 180.000

1' INSIDE U/S FACE OF DAM

19263.00	11.74	590.74	0.00	0.00	591.29	0.54	0.17	0.01	579.00	
1330.	23.	1273.	34.	191.	290.	162.	136.	34.	579.00	
1.04	0.12	6.65	0.21	0.000	0.020	0.500	-1.539	579.00	220.00	
0.001650	100.	100.	100.	2	0	0	-239.66	180.00	400.00	

FLOW DISTRIBUTION FOR SECNO= 19263.00 CWSEL= 590.74

STA=	220.	295.	307.	333.	351.	400.
PER Q=	1.3	0.2	96.7	0.7	1.0	
AREA=	162.6	27.7	310.4	44.6	112.0	
VEL=	0.1	0.1	6.3	0.2	0.2	

1490 NH CARD USED
*SECNO 19264.000
3280 CROSS SECTION 19264.00 EXTENDED 0.36 FEET

3470 ENCROACHMENT STATIONS= 220.0 400.0 TYPE= 1 TARGET= 180.000

PRINTED IN U.S.A.
FORM 1431-00 PRINTED BY ROTARY MANIFOLD FORMS

U/S FACE OF DIX RD. BRIDGE

	19264.00	12.14	591.14	0.00	0.00	591.38	0.24	0.00	0.09	579.00
	1330.	21.	1270.	39.	281.	317.	271.	191.	31.	579.00
	0.84	0.09	4.01	0.14	0.800	0.035	0.500	0.033	579.00	220.00
	0.000319	1.	1.	1.	2	0	0	0.00	100.00	400.00

FLOW DISTRIBUTION FOR SECNO= 19264.00 CWSEL= 591.14

STA=	220.	295.	307.	333.	351.	400.
PER %=	0.9	0.7	95.5	1.9	1.0	
AREA=	192.3	83.7	316.9	134.1	136.5	
VEL=	0.1	0.1	4.0	0.2	0.1	

#SECNO 19314.000
3280 CROSS SECTION 19314.00 EXTENDED 0.56 FEET

3470 ENCROACHMENT STATIONS= 220.0 400.0 TYPE= 1 TARGET= 150.000

VALLEY SECT. 50' U/S OF DIX

	19314.00	12.16	591.16	0.00	0.00	591.39	0.24	0.02	0.00	579.00
	1330.	21.	1270.	39.	282.	317.	272.	132.	31.	579.00
	0.84	0.00	4.00	0.14	0.800	0.035	0.500	0.033	579.00	220.00
	0.000318	50.	50.	50.	2	0	0	0.00	130.00	400.00

FLOW DISTRIBUTION FOR SECNO= 19314.00 CWSEL= 591.16

STA=	220.	295.	307.	333.	351.	400.
PER %=	0.9	0.7	95.5	1.9	1.0	
AREA=	192.3	83.9	317.1	134.4	137.2	
VEL=	0.	0.	4.1	2.2	0.1	

1490 NH CARD USED
#SECNO 20380.002
3280 CROSS SECTION 20380.00 EXTENDED 1. 11 FEET

SECNO	DEPTH	CWSEL	CRIWS	USELK	ES	AV	AI	QLOSS	BANK ELEV	
Q	WLOB	QCH	QROB	ALOB	ACH	AROB	VCH	TWA	LEFT/RIGHT	
TYPE	WLOB	VCH	WROB	XMI	XNCL	ZLO	KCH	ELCTR	SSTA	
SLOPE	WLOBL	XLOB	XLOBR	ITRIAL	ICR	ICONT	FCR,R	TCHNTO	FMULT	

3470 ENCROACHMENT STATIONS= 338.0 405.0 TYPE= 1 TARGET= 151.000

VALLEY SECT. 50' U/S OF FRANK ST.

	20030.00	11.32	591.32	0.00	0.00	591.71	0.39	0.23	0.04	580.10
	1330.	23.	1263.	46.	126.	271.	208.	146.	34.	360.10
	0.99	0.18	4.66	0.15	0.500	0.035	0.500	0.034	580.10	356.00
	0.000476	766.	766.	766.	0	2	0	0.00	151.00	439.00

FLOW DISTRIBUTION FOR SECNO= 20030.00 CWSEL= 591.32

STA=	338.	350.	385.	399.	405.	
PER %=	0.2	1.	95.0	2.1	1.7	
AREA=	266.0	1.	1.	1.	1.	
VEL=	0.	0.	4.7	2.4	0.1	

PRINTED IN U.S.A
FORM 1411-OD-PRINTED ON ROYARY MANIFOLD FORMS

AREA=	26.1	99.8	271.2	128.3	1[illegible].8
VEL=	0.1	0.2	4.7	0.2	.1

1490 NH CARD USED
*SECNO 20130.000
3280 CROSS SECTION 20130.00 EXTENDED 1.97 FEET

3470 ENCROACHMENT STATIONS= 372.0 500.0 TYPE= 1 TARGET= 122.000

[illegible]OS FACE OF FRANK AVE. BRIDGE

20130.00	11.47	591.57	0.00	0.00	591.78	0.21	0.02	0.03	580.10
1330.	82.	1169.	79.	106.	299.	287.	147.	34.	580.10
0.89	0.77	3.90	0.27	0.100	0.030	0.200	0.034	580.10	372.00
9.000240	50.	30.	50.	2	11	3	0.02	128.00	500.00

FLOW DISTRIBUTION FOR SECNO= 20130.00 CWSEL= 591.57

STA=	372	387	413	426	500
FSR Q=	6.2	87.9	3.1	2.8	
AREA=	156.4	299.4	105.1	181.2	
VEL=	0.8	1.9	1.6	0.2	

1490 IN CARD USED
*SECNO 20131.000
3280 CROSS SECTION 20131.00 EXTENDED 1.30 FEET

3270 NORMAL BRIDGE,NRD= 13 MIN ELTRD= 588.30 MAX ELLC= 586.70

3470 ENCROACHMENT STATIONS= 372.0 500.0 TYPE= 1 TARGET= 128.000

1' INSIDE D/S OF FRANK AVE.

20131.00	11.30	591.40	0.00	0.00	591.96	0.56	0.00	0.18	580.10
1330.	0.	1258.	92.	0.	199.	108.	122.	34.	580.10
0.89	0.39	6.24	0.59	0.100	0.020	3.270	0.024	580.10	372.00
0.000246	1.	1.	1.	2.	0	3	0.05	128.00	500.00

FLOW DISTRIBUTION FOR SECNO= 20131.00 CWSEL= 591.40

STA=	372.	387.	413.	500.
PER Q=	0.0	93.6	6.4	
AREA=	0.1	197.5	168.5	
VEL=	3.1	6.2	0.6	

1490 IN CARD USED
*SECNO 20168.000
3280 CROSS SECTION 20168.00 EXTENDED 1.64 FEET

3270 NORMAL BRIDGE,NRD= 13 MIN ELTRD= 588.30 MAX ELLC= 586.70

3470 ENCROACHMENT STATIONS= 372.0 500.0 TYPE= 1 TARGET= 128.000

1' INSIDE U/S OF FRANK AVE.

PRINTED IN U.S.A.
FORM 1411.00-PRINTED BY ROTARY MANIFOLD FORMS

20168.00	11.34	591.44	0.00	0.30	592.07	0.63	0.08	0.04	580.10
1330.	0.	1286.	42.	0.	199.	172.	147.	34.	580.10
0.90	0.09	4.49	0.24	0.100	0.020	0.500	0.034	580.10	372.00
0.002195	37.	37.	37.	0	0	1	-305.66	125.00	500.00

FLOW DISTRIBUTION FOR SECNO= 20168.00 CWSEL= 591.44

STA=	372.	387.	413.	500.
PER Q=	0.0	96.9	3.1	
AREA=	0.1	190.6	121.5	
VEL=	0.1	5.8	1.0	

1490 NH CARD USED
*SECNO 20169.000
3290 CROSS SECTION 20169.00 EXTENDED 2.42 FEET

3470 ENCROACHMENT STATIONS= 372.0 500.0 TYPE= 1 TARGET= 125.000

D/S FACE OF FRANK AVE. BRIDGE

20169.00	11.92	592.33	0.00	0.00	592.41	0.08	0.00	0.04	580.10
1330.	84.	1157.	88.	113.	311.	326.	147.	34.	580.10
0.90	0.75	3.72	0.27	0.100	0.030	0.200	0.034	580.10	372.00
0.000237	1.	1.	1.	2	0	0	0.00	125.00	500.00

FLOW DISTRIBUTION FOR SECNO= 20169.00 CWSEL= 592.04

STA=	372.	387.	413.	428.	500.
PER Q=	6.3	87.0	3.2	3.5	
AREA=	113.1	311.1	112.5	213.5	
VEL=	0.7	3.7	0.4	1.2	

1490 NH CARD USED
*SECNO 20269.000
3290 CROSS SECTION 20269.00 EXTENDED 2.47 FEET

SECNO	DSNT	CLSEL	CRWS	LSLOP	SS	RN	N	BLOSS	BANK FLOW
Q	Q.CH	CCH	GROB	ALOB	ACH	AROB	VOL	THA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XXCH	XNR	UTA	XLOIN	SRTA
SLOPE	YLOBL	YLCH	XLOBR	ITRIAL	XNP	ICONT	ICRAP	TOPLTO	ENDST

3470 ENCROACHMENT STATIONS= 372.0 525.0 TYPE= 1 TARG.T= 153.000

VALLEY SECT. 100'U/S OF FRANK AVE.

20269.00	11.97	592.07	0.00	0.30	592.23	0.17	0.00	0.01	580.10
1330.	95.	1119.	116.	114.	312.	392.	147.	34.	580.10
0.90	0.84	4.58	0.29	0.100	0.035	0.200	0.034	580.10	372.00
0.000260	100.	100.	100.	2	2	0	0.00	153.00	525.00

FLOW DISTRIBUTION FOR SECNO= 20269.00 CWSEL= 592.07

STA=	372.	387.	413.	428.	525.
PER Q=	7.2	84.5	3.5	4.8	
AREA=	113.6	312.5	113.5	214.4	

PRINTED IN U.S.A.
FORM 1411.00-PRINTED BY ROTARY MANIFOLD FORMS

****

M2C2 RELEASE DATED NOV 76 ADOPTED FEB 1977
ERROR CORR - 01
MODIFICATION - 50,51,52

****

NOTE- ASTERISK (*) AT LEFT OF CROSS-SECTION NUMBER INDICATES MESSAGE IN SUMMARY OF ERRORS LIST

N.BR.ECORSE CR.LINC.PK.

SUMMARY PRINTOUT TABLE 150

SECNO	YLCH	FLTRD	FLC	FLM1		CASE	LOI S	FS	LOSS	VCA	SRSA	TLIK
10636.000	0.00	0.00	0.00	572.47	1410.00	585.53	0.00	585.60	2.44	2.07	679.97	901.82
11534.000	900.00	0.00	0.00	572.00	1410.00	585.77	0.00	585.92	6.76	3.13	469.16	667.76
12274.000	730.00	0.00	0.00	573.30	1410.00	584.05	0.00	584.68	1.65	2.49	747.78	1009.15
12324.000	50.00	0.00	0.00	573.60	1410.00	584.07	0.00	584.14	1.39	2.39	822.47	1195.65
12362.000	1.00	530.40	581.80	573.60	1410.00	584.09	0.00	584.16	5.51	2.01	820.67	600.41
12367.000	42.00	580.40	581.80	573.60	1410.00	584.10	0.00	584.16	5.55	2.31	641.59	461.50
12368.000	1.00	0.00	0.00	573.60	1410.00	584.12	0.00	584.19	1.36	2.39	830.89	1210.49
12418.000	50.00	0.00	0.00	573.60	1410.00	584.17	0.00	584.20	1.39	2.32	836.41	1214.94
13294.000	372.00	0.00	0.00	572.30	1410.00	584.[illegible]	0.00	584.[illegible]	2.65	2.63	936.94	668.57
13576.000	341.00	0.00	0.00	572.90	1410.00	584.45	0.00	584.46	2.31	3.03	990.91	927.92
13724.000	50.00	0.00	0.00	573.00	1410.00	584.33	0.00	584.51	2.05	3.74	737.32	807.03
13727.000	1.00	581.40	579.60	573.00	1410.00	584.[illegible]	0.00	584.51	0.58	4.58	513.28	461.39
13964.000	237.00	581.40	579.60	573.00	1410.00	584.51	0.00	584.80	0.20	4.64	667.86	492.32
13965.000	1.00	0.00	0.00	573.30	1410.30	584.56	0.00	584.84	2.61	3.58	825.37	881.85
14015.000	50.00	0.00	0.00	573.00	1410.30	584.77	0.00	584.87	1.79	2.94	645.96	1054.16
14287.000	272.00	0.00	0.00	574.50	1410.00	584.87	0.00	584.93	1.69	2.05	991.14	1065.72
14337.000	50.00	0.00	0.00	574.60	1410.00	584.86	0.00	584.94	1.66	2.20	1020.89	1098.40
14339.000	1.00	580.20	582.40	574.60	1410.00	584.[illegible]	0.00	584.94	6.36	2.65	869.40	700.60
14402.000	54.00	580.00	581.40	574.50	1410.00	584.90	0.00	584.97	6.00	2.66	863.77	704.65
14403.000	1.00	0.00	0.00	574.50	1410.00	584.91	0.00	584.97	1.65	2.19	1084.52	1104.14

PRINTED IN U.S.A.

FORM 1411-00-PRINTED BY ROTARY MANIFOLD FORMS

SECNO	XLCH	ELTRD.	ELLC	ELMIN	Q	CWSEL	CRIWS	FG	TOK*S	VCH	AREA	TOTK
14460.000	57.00	0.00	0.00	572.60	1410.00	584.91	0.00	584.99	1.22	2.39	1162.23	1277.23
14461.000	1.00	580.00	581.60	572.60	1410.00	584.90	0.00	585.00	4.39	2.84	903.60	672.77
14521.000	60.00	580.00	581.60	572.60	1410.00	584.93	0.00	585.03	4.34	2.83	990.05	676.68
14522.000	1.00	0.00	0.00	572.60	1410.00	584.96	0.00	585.03	1.19	2.37	1181.08	1292.50
14572.000	50.00	0.00	0.00	572.70	1410.00	584.96	0.00	585.06	3.73	2.92	1122.54	729.59
15292.000	720.00	0.00	0.00	574.40	1410.00	585.24	0.00	585.46	7.34	3.71	380.17	520.16
15820.000	528.00	0.00	0.00	577.00	1410.00	585.59	0.00	585.97	9.36	5.23	334.79	460.85
15870.000	50.00	0.00	0.00	577.00	1410.00	585.71	0.00	586.04	6.80	4.70	408.24	560.77
15914.000	44.00	585.40	583.00	577.00	1410.00	586.59	0.00	586.82	6.81	4.20	473.12	663.10
15964.000	50.00	0.00	0.00	577.00	1410.00	586.54	0.00	586.94	8.74	5.47	366.78	476.92
16194.000	230.00	0.00	0.00	576.50	1410.00	586.20	0.00	587.13	6.38	3.93	431.21	673.62
16244.000	50.00	0.00	0.00	576.50	1410.00	586.70	0.00	587.41	19.98	6.73	209.58	315.41
16245.000	1.00	603.60	588.10	576.50	1410.00	586.70	0.00	587.41	6.62	6.76	208.61	547.91
16503.000	258.00	603.60	588.10	576.50	1410.00	586.91	0.00	587.38	6.21	6.61	218.19	565.72
16504.000	1.00	0.00	0.00	576.50	1410.00	586.91	0.00	587.59	18.75	6.58	214.18	325.27
16554.000	50.00	0.00	0.00	576.60	1330.00	587.57	0.00	587.77	3.96	3.86	507.13	667.94
16825.000	272.00	0.00	0.00	575.30	1330.00	587.77	0.00	587.96	1.38	2.67	671.22	1132.04
16876.000	50.00	0.00	0.00	574.60	1330.00	587.79	0.00	587.90	2.60	3.06	495.28	825.04
16963.000	87.00	589.70	587.20	574.90	1330.00	588.05	0.00	588.21	2.59	3.05	435.76	826.40
17013.000	50.00	0.00	0.00	575.20	1330.00	588.13	0.00	588.24	1.11	2.36	843.78	1240.16
17255.000	242.00	0.00	0.00	577.90	1330.00	583.18	0.00	588.32	2.49	3.15	505.68	863.06
17305.000	50.00	0.00	0.00	577.90	1330.00	588.09	0.00	588.45	9.80	6.80	277.22	468.33
17502.000	197.00	603.40	585.50	577.90	1330.00	589.60	0.00	589.16	5.44	4.08	525.36	670.21
17552.000	50.00	0.00	0.00	577.50	1330.00	590.11	0.00	590.22	1.79	3.07	841.38	993.62
17817.000	265.00	0.00	0.00	576.90	1330.00	590.21	0.00	590.26	1.44	2.07	902.98	1309.58
18106.000	289.00	0.00	0.00	579.00	1330.00	590.14	0.00	590.35	2.91	3.66	950.79	771.01
18156.000	50.00	0.00	0.00	579.00	1330.00	590.19	0.00	590.37	2.30	3.76	850.00	876.96
18157.000	1.00	566.70	585.90	579.00	1330.00	590.09	0.00	590.42	10.16	6.95	556.52	617.74
18195.000	38.00	586.70	585.90	579.00	1330.00	590.14	0.00	590.45	8.06	6.91	562.67	623.00

PRINTED IN U.S.A.
FORM 1411-GU-PRINTED BY ROTARY MANIFOLD FORMS.

SECNO	XLCH	ELTRD	ELLC	ELMIN	Q	CWSEL	CRIWS	EG	TOK*S	VCH	AREA	TOTK
18196.000	1.00	0.00	0.00	579.00	1330.00	590.30	0.00	590.47	2.21	3.71	854.92	893.35
18240.000	50.00	0.00	0.00	579.00	1330.00	590.22	0.00	590.53	5.09	4.80	755.94	549.65
18545.000	299.00	0.00	0.00	578.60	1330.00	590.56	0.00	590.66	3.07	2.95	667.37	758.67
18329.000	284.00	0.00	0.00	578.70	1330.00	590.66	0.00	590.74	2.61	3.58	964.83	823.99
18379.000	50.00	0.00	0.00	578.70	1330.00	590.65	0.00	590.76	2.03	3.69	967.17	932.77
18860.000	1.00	585.00	583.20	578.70	1330.00	590.66	0.00	590.76	4.27	3.46	855.84	643.78
18910.000	50.00	585.00	583.20	578.70	1330.00	590.67	0.00	590.78	4.23	3.45	858.38	644.30
18911.000	1.00	0.00	0.00	578.70	1330.00	590.63	0.00	590.76	2.02	3.68	970.39	936.29
18961.000	50.00	0.00	0.00	578.70	1330.00	590.69	0.00	590.79	2.56	3.56	972.16	831.13
19112.000	151.00	0.00	0.00	579.00	1330.00	590.66	0.00	590.92	3.70	4.20	781.30	691.80
19162.000	50.00	0.00	0.00	579.00	1330.00	590.68	0.00	590.94	3.68	4.19	784.86	695.44
19163.000	1.00	588.20	585.00	579.00	1330.00	590.52	0.00	591.10	18.33	6.26	522.19	310.64
19263.000	100.00	588.20	585.00	579.00	1330.00	590.74	0.00	591.29	16.53	6.05	563.02	327.39
19263.000	1.00	0.00	0.00	579.00	1330.00	591.14	0.00	591.36	3.19	4.01	368.48	744.47
19314.000	50.00	0.00	0.00	579.00	1330.00	591.16	0.00	591.39	3.18	4.00	871.38	746.25
20080.000	766.00	0.00	0.00	580.10	1330.00	591.41	0.00	591.73	4.74	4.66	685.24	610.62
20130.000	50.00	0.00	0.00	580.10	1330.00	591.57	0.00	591.76	2.66	3.90	695.03	658.10
20131.000	1.00	588.30	586.70	580.10	1330.00	591.60	0.00	591.96	20.46	6.24	366.11	254.05
20168.000	37.00	588.30	586.70	580.10	1330.00	591.64	0.00	592.07	21.95	6.69	370.25	253.85
20169.000	1.00	0.00	0.00	580.10	1330.00	592.00	0.00	592.21	2.07	3.73	760.41	823.09
20269.000	100.00	0.00	0.00	580.10	1330.00	592.07	0.00	592.23	2.60	3.58	823.06	826.86

FORM 1411.08 PRINTED BY ROTARY MANIFOLD FORMS.

N.FR.ECORSE CR.LINC.PK.

SUMMARY PRINTOUT TABLE 150

SECAO	Q	CWSEL	VEL SP	DIFWSX	DIFKWS	TOPWID	AREA
10656.000	1410.00	583.53	0.00	0.00	0.00	125.93	0.00
11536.000	1410.00	583.77	0.00	0.24	0.00	91.08	900.00
12274.000	1410.00	584.03	0.00	0.26	0.00	145.00	770.00
12324.000	1410.00	584.07	0.00	0.02	0.00	145.00	90.00
12335.000	1410.00	584.05	0.00	-0.02	0.00	145.00	1.00
12367.000	1410.00	584.04	0.00	0.02	0.00	145.00	42.00
12368.000	1410.00	584.12	0.00	0.04	0.00	145.00	1.00
12418.000	1410.00	584.15	0.00	0.01	0.00	145.00	50.00
13295.000	1410.00	584.27	0.00	0.14	0.05	330.00	877.00
13676.000	1410.00	584.35	0.00	0.08	0.00	195.00	381.00
13726.000	1410.00	584.34	0.00	-0.02	0.00	170.00	50.00
13727.000	1410.00	584.26	0.00	-0.07	0.00	220.00	1.00
13964.000	1410.00	584.51	0.00	0.25	0.00	170.00	237.00
13965.000	1410.00	584.66	0.00	0.16	0.00	270.00	1.00
14015.000	1410.00	584.77	0.00	0.10	0.00	120.00	50.00
14287.000	1410.00	584.87	0.00	0.11	0.00	320.00	272.00
14337.000	1410.00	584.88	0.00	0.01	0.00	320.00	50.00
14338.000	1410.00	584.85	0.00	-0.03	0.00	320.00	1.00
14402.000	1410.00	584.90	0.00	0.03	0.00	320.00	64.00
14403.000	1410.00	584.92	0.00	0.01	0.00	320.00	1.00
14466.000	1410.00	584.91	0.00	-0.02	0.00	400.00	63.00
14461.000	1410.00	584.90	0.00	-0.01	0.00	400.00	1.00
14521.000	1410.00	584.93	0.00	0.03	0.00	430.00	60.00
14522.000	1410.00	584.94	0.00	0.01	0.00	460.00	1.00
14572.000	1410.00	584.95	0.00	-0.01	0.00	420.00	50.00
14623.000	1410.00	585.24	0.00	0.29	0.00	60.19	780.00
14624.000	1410.00	585.30	0.00	0.06	0.00	60.00	563.00

PRINTED IN U.S.A.
FORM 1411-GD-PRINTED BY ROTARY MANIFOLD FORMS

SECNO	Q	CWSEL	DIFWSP	DIFWSX	DIFKWS	TOPWID	XLCH
15870.000	1410.00	585.75	0.00	0.17	0.00	65.26	50.00
15914.000	1410.00	586.59	0.00	0.84	0.00	100.00	44.00
15964.000	1410.00	586.54	0.00	-0.05	0.00	130.00	50.00
16194.000	1410.00	586.90	0.00	0.36	0.00	50.00	230.00
16244.000	1410.00	586.77	0.00	-0.20	0.00	22.93	50.00
16245.000	1410.00	536.70	0.00	-0.00	0.00	22.93	1.00
16503.000	1410.00	586.91	0.00	0.20	0.00	22.93	258.00
16504.000	1410.00	586.91	0.00	0.01	0.00	22.93	1.00
16554.000	1330.00	587.57	0.00	0.65	0.00	93.61	50.00
16826.000	1330.00	587.77	0.00	0.20	0.00	62.00	272.00
16876.000	1330.00	587.75	0.00	-0.02	0.00	33.11	50.00
16963.000	1330.00	588.06	0.00	0.31	0.00	33.10	87.00
17013.000	1330.00	588.15	0.00	0.11	0.00	110.55	50.00
17255.000	1330.00	588.12	0.00	-0.03	0.00	54.00	242.00
17305.000	1330.00	588.09	0.00	-0.03	0.00	27.20	50.00
17502.000	1330.00	589.90	0.00	1.81	0.00	27.20	197.00
17552.000	1330.00	590.11	0.00	0.21	0.00	187.00	50.00
17817.000	1330.00	590.21	0.00	0.10	0.00	221.60	265.00
17867.000	1330.00	590.19	0.00	-0.02	0.00	175.00	283.00
18156.000	1330.00	590.09	0.00	0.00	0.00	175.00	1.00
18157.000	1330.00	590.09	0.00	-0.10	0.00	175.00	1.00
18195.000	1330.00	590.14	0.00	0.05	0.00	175.00	38.00
18196.000	1330.00	590.10	0.00	0.96	0.00	175.00	1.00
18246.000	1330.00	590.22	0.00	-0.08	0.00	150.00	50.00
18545.000	1330.00	590.56	0.00	0.34	0.00	150.00	299.00
18829.000	1330.00	590.84	0.00	0.28	0.00	125.00	284.00
18879.000	1330.00	590.85	0.00	0.01	0.00	100.00	50.00
18880.000	1330.00	590.86	0.00	0.01	0.00	100.00	1.00
18930.000	1330.00	590.87	0.00	0.01	0.00	100.00	50.00

PRINTED IN U.S.A.
FORM 1411-OD PRINTED BY ROTARY MANIFOLD FORMS.

SECNO	Q	CUSEL	DIFMSP	DIFMSX	DIFKWS	TOPMTD	XI CH
18911.000	1330.00	590.57	0.00	-0.00	0.00	165.00	1.00
18961.000	1330.00	590.59	0.00	0.02	0.00	165.00	50.00
19112.000	1330.00	590.66	0.00	-0.03	0.00	180.00	151.00
19162.000	1330.00	590.68	0.00	0.02	0.00	180.00	50.00
19163.000	1330.00	590.52	0.00	-0.16	0.00	180.00	1.00
19263.000	1330.00	590.74	0.00	0.23	0.00	180.00	100.00
19264.000	1330.00	591.14	0.00	0.40	0.00	180.00	1.00
19314.000	1330.00	591.16	0.00	0.02	0.00	180.00	50.00
20080.000	1330.00	591.41	0.00	0.25	0.00	151.00	766.00
20130.000	1330.00	591.57	0.00	0.16	0.00	128.00	50.00
20131.000	1330.00	591.40	0.00	-0.18	0.00	128.00	1.00
20168.000	1330.00	591.44	0.00	0.04	0.00	128.00	37.00
20169.000	1330.00	592.02	0.00	0.58	0.00	128.00	1.00
20269.000	1330.00	592.07	0.00	0.05	0.00	154.00	100.00

SUMMARY OF ERRORS

PRINTED IN U.S.A.

FORM 1411.00-PRINTED BY ROTARY MANIFOLD FORMS

```
**************************************************
      REC2 RELEASE DATED NOV 76 UPDATED FEB 1977
      ERROR CORR -  01
      MODIFICATION -  50,51,52
**************************************************
```

PRINTED IN U.S.A.
FORM 1411-00 PRINTED BY ROTARY MANIFOLD FORMS

```
*****************************************************
*                                                   *
*                  E R R O R   S U M M A R Y        *
*                                                   *
*     0  ERROR(S) DETECTED BY THE USER PROGRAM      *
*     0  ERROR(S) DETECTED BY THE MATHEMATICAL PACKAGE *
*     0  ERROR(S) DETECTED FOR INPUT/OUPUT STATEMENTS *
*                                                   *
*****************************************************
```

PRINTED IN U.S.A.
FORM 1411-OD PRINTED BY ROTARY MANIFOLD FORMS

00BREAK00

1) COUNTY: Wayne

2) STUDY NAME: City of Lincoln Park

3) WATERCOURSE: South Branch Ecorse Creek

4) DOCUMENT TYPE: Input

00BREAK00

Da

```
**************************************************
  FEC2 RELEASE DATED NOV 75 UPDATED FEB 1977
  ERROR CODE =  01
  MODIFICATION =  50,51,52
**************************************************

C
T1 CITY OF LINCOLN PARK FIS NO 2015-01
T2 100 YR FLOW
T3       SOUTH BRANCH ECORSE CR.
J1  ICHECK    INQ      NRNG     IDIR      STIT     METRIC   HVINP      Q          MSEL     TA
          0.       0.       1.       2.  0.200000   0.10      2.0        0.     502.300     1.000
J2  NPROF     IPLOT    PONDS    XSECV     XSECH     FN      ALLOC     IBW        CHNL     XTRACE
       -1.000    1.000   -1.000    3.000    0.000    1.000    3.000    0.100    0.001    0.002
J*  AVAILABLE CODES FOR SUMMARY PRINTOUT
     150.000    3.000    0.000    0.000    0.000    3.000    0.000    0.100    0.001    0.000
CC       5.000  1125.000  1620.000  1764.000  1780.000   200.000     .030     3.000    3.000    3.000
C        0.060     2.10     3.05      .50     -0.20      0.20     0.50     3.000    3.000    3.000
D/S OF CE SOUTH DOUG FOR ST. FRO MYANDOTTE FIS
X1  11650.000    30.000   564.000   624.500    51.000     1.000    31.000    0.500    0.200    0.600
X1       0.00      .020     1.00     50.0      6.00       .00      0.00      0.00     0.00     0.00
X1       .00      .020     5.00     90.0     60.00      1.00     20.00     2.50     3.50     3.50
X1       .00      .020     8.00     90.0     70.00      1.00     20.00     3.00     3.50     3.50
X1   375.000  383.000  572.500  590.500  582.000  572.000  572.000  570.000  570.700  573.500
X1   560.700  575.500  572.700  572.500  572.000  570.000  572.100  575.000  572.600  586.000
X1   572.100  598.000  572.500  573.000  572.000  611.000  590.500  900.000  563.200  604.000
X1   582.50   942.00   1.00     1.00     1.00     1.00     1.00     1.00     1.00     1.00
X1   561.000  10.000   1.00     1.00     1.00     1.00     1.00     1.00     1.00     1.00
X1   566.00   55.00    1.00     1.00     1.00     1.00     1.00     1.00     1.00     1.00
X1     1.250     .610    2.300    0.500    52.000     2.300   450.000    1.250   572.100   572.100
X1 D/S OF CE ROUTE 100 IN FRONT OF FOX THEATRE AIR
X1  11734.000    0.000    0.00     0.000    0.000    0.000    0.00     0.00     0.00     0.000
X1       0.00     1.000    1.00   570.700  563.200    0.000    0.00     1.150    3.000    3.000
X1     10.00      1.000    0.00   568.200    1.000    0.000    1.150    3.000    3.000    3.000
X1       1.00   568.700  585.400  581.300  572.000  570.000  580.700  570.000  563.300  587.700
X1   574.00   582.000  570.500    1.000    0.000    0.000    0.00     1.150    3.000    3.000
X1       1.00     1.000    1.00     1.000    0.000    0.000    0.00     1.150    3.000    3.000
X1       1.00     1.000    0.00     1.000    0.000    0.000    0.00     1.150    3.000    3.000
X1 WEST SECTION                    FLOW FROM 31 =  4455
X1   570.00     0.000  101.00   250.00   346.00     0.00     0.00     0.00     0.00     0.00
X1   144.00     1.000    1.00     1.000    0.00     0.00     0.00     0.00     0.00     0.00
X1   572.000  572.000  572.000  572.000  572.000  572.000  572.000  572.000  572.000  572.000
```

50FT D/S HOWARD AVE.

X1	13269.000	15.000	233.500	280.500	530.000	560.000	560.000	0.000	0.000	0.000
[illegible]	595.400	0.000	525.000	57.000	584.700	157.000	264.400	208.000	574.900	229.000
[illegible]	573.300	233.500	575.000	256.500	573.300	257.500	579.000	262.500	575.300	261.000
[illegible]	584.500	293.000	584.800	357.000	584.200	487.000	584.200	557.000	264.600	577.000

D/S FACE HOWARD AVE. FIELD BOOK STA. 36+15

X1	13269.000	0.000	0.000	0.000	50.000	50.000	50.000	0.000	0.000	0.000
X3	10.300	0.000	0.000	0.000	0.000	0.000	0.000	584.800	584.800	0.000
SW	1.250	1.650	3.000	0.000	67.000	1.000	614.000	0.000	573.000	573.000

D/S FACE HOWARD AVE. FIELD BOOK STA. 32+75

X1	13300.000	15.000	233.500	250.500	60.000	60.000	60.000	0.000	0.000	0.000
X2	0.000	0.000	1.000	582.000	584.500	0.000	0.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	112.000	0.000	402.000	0.000	584.500	584.500	0.000
UT	17.000	0.000	585.400	0.000	57.000	585.000	0.000	157.300	584.700	0.000
BY	211.000	584.700	0.100	253.500	584.200	0.000	285.300	584.500	582.000	256.500
BY	584.500	582.300	210.300	584.500	0.000	257.300	584.500	0.000	257.500	582.500
BY	582.000	290.500	584.200	582.000	262.500	584.200	0.200	290.000	584.500	0.300
BY	357.000	584.600	0.000	457.000	584.200	0.000	557.000	584.200	0.000	577.000
GT	584.800	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
GR	585.400	0.000	585.000	57.500	584.700	157.000	584.700	211.000	574.400	233.500
GR	573.000	235.000	572.000	256.500	573.000	292.000	575.000	280.000	575.200	294.000
GR	584.500	296.000	584.600	357.000	584.200	457.000	587.200	557.000	584.400	577.000

100 FT D/S HOWARD AVE.

[illegible]	15403.000	0.000	0.000	0.000	100.000	100.000	100.000	0.000	0.000	0.000
[illegible]	5.000	0.040	152.000	0.000	174.000	1.000	224.000	0.000	340.000	0.000
[illegible]	422.000	0.000	0.000	0.000	2.000	1.000	0.000	0.000	0.000	0.000

VALLEY SECTION FIELD BOOK STA. 20+50

[illegible]	15144.000	10.000	0.000	224.000	1735.000	1735.000	1735.000	0.000	0.000	0.000
	0.000	0.000	1.000	132.000	2.000	0.000	0.000	0.000	0.000	0.000
GR	585.100	0.000	585.100	0.000	585.100	200.000	585.000	157.000	577.200	176.000
GR	573.700	200.000	576.000	224.000	585.920	260.000	585.000	320.000	586.200	400.000
NC	0.040	0.060	0.039	0.000	0.500	0.000	0.000	0.000	0.000	0.000

D/S FACE DIX AVE FIELD BOOK STA. 17+50

X1	15434.000	11.000	276.000	324.000	290.000	290.000	290.000	0.000	0.000	0.000
X2	10.000	0.000	0.000	0.000	0.000	0.000	0.000	587.300	587.300	0.000
GR	588.000	0.000	587.400	150.000	586.900	230.000	527.300	280.000	575.200	294.000
GR	574.900	300.000	575.000	324.000	587.000	330.000	587.400	400.000	583.100	530.000
GR	586.600	575.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
SW	1.250	1.350	3.000	0.000	48.000	2.000	459.000	0.000	574.900	574.900

D/S FACE DIX AVE. FIELD BOOK STA. 15+29


X1	15555.000	20.000	276.000	329.000	321.000	181.000	125.000	0.000	330.000	1.000
X2	0.000	0.000	1.000	585.600	587.300	0.000	0.000	0.000	0.000	0.000
X3	10.000	0.000	10.000	0.000	10.000	0.000	0.000	587.300	587.300	0.000
UT	16.000	0.000	584.000	0.000	100.000	587.400	0.000	200.000	587.000	0.000

PRINTED IN U.S.A.
FORM 1411-00-PRINTED BY ROTARY MANIFOLD FORMS

	BT	256.000	587.300	0.000	276.000	587.300	0.000	276.000	587.300	583.800	299.000
	BT	587.300	583.800	299.000	587.300	0.000	301.000	587.300	0.000	301.000	587.300
	BT	583.800	324.000	587.300	583.800	324.000	587.300	0.000	343.000	588.200	0.000
	BT	400.000	587.300	0.000	500.000	588.100	0.000	575.000	588.300	0.000	0.000
1	GR	588.000	0.000	587.600	130.000	587.000	200.000	587.300	256.000	575.300	276.000
2	GF	574.900	299.000	574.900	301.000	575.900	324.000	586.200	343.000	587.600	400.000
3	GL	588.100	300.000	588.500	575.000	0.000	0.000	0.000	0.000	0.000	0.000
4	NR	5.000	0.040	60.000	0.060	78.000	0.035	108.000	0.060	129.000	0.040
5	NR	253.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
6											
7											
8		VALLEY SECTION				FIELD BOOK STA. 13+25					
9											
10	X1	15859.000	9.000	78.000	108.000	304.000	304.000	304.000	0.000	0.000	0.000
11	GR	588.100	0.000	588.100	0.000	586.200	60.000	576.200	78.000	574.300	93.000
12	GF	575.900	108.000	588.400	129.000	589.700	145.000	589.600	253.000	0.000	0.000
13	GL	0.000	0.060	0.005	0.300	0.600	0.000	0.000	0.000	0.000	0.000
14											
15											
16		D/S HAZEL AVE.									
17											
18	X1	16339.000	12.000	262.500	297.500	480.000	480.000	480.000	0.000	0.000	0.000
19	X3	10.000	0.000	0.000	1.000	0.000	0.000	0.000	589.200	589.200	0.000
20	GR	593.100	0.000	591.900	60.000	589.700	180.000	180.000	253.000	575.600	262.500
21	GF	575.600	262.500	575.200	297.500	589.600	420.000	589.500	360.000	591.600	480.000
22	GL	594.100	480.000	594.500	607.000	0.000	0.000	0.000	0.000	0.000	0.000
23											
24											
25		D/S FACE HAZEL AVE.				FIELD BOOK STA. 6+76					
26											
27	X1	16340.000	0.000	0.100	0.000	1.000	1.000	0.000	0.000	0.000	0.000
28	X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	589.200	589.200	0.000
29	BT	10.000	0.000	593.100	0.000	60.000	391.900	0.000	180.000	589.700	0.000
30	BT	256.000	589.200	0.000	262.500	589.200	0.000	262.500	589.200	585.700	297.500
31	BT	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
32	BT	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
33											
34											
35		D/S FACE HAZEL AVE.				FIELD BOOK STA. 5+05					
36											
37	X1	16340.000	12.000	262.500	297.500	0.000	0.000	0.000	0.000	0.000	0.000
38	X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	589.200	589.200	0.000
39	BT	0.000	0.000	593.100	0.000	60.000	391.900	0.000	180.000	589.700	0.000
40	BT	256.000	589.200	0.000	262.500	589.200	0.000	262.500	589.200	585.700	297.500
41	BT	589.200	585.700	297.500	589.200	0.000	321.000	589.300	0.000	302.000	589.300
42	BT	0.000	400.000	591.300	0.000	540.000	594.100	0.000	607.000	594.500	0.000
43	GR	595.100	0.000	594.500	60.000	589.700	180.000	180.000	256.000	576.500	262.500
44	GF	575.400	262.500	575.200	297.500	589.600	420.000	589.500	360.000	591.600	480.000
45	GL	594.100	480.000	594.500	607.000	0.000	0.000	0.000	0.000	0.000	0.000
46											
47											
48		D/S HAZEL AVE.									
49											
50	X1	16340.000	0.100	0.000	0.300	1.000	1.000	1.000	0.000	0.000	0.000
51	X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	589.200	589.200	0.000
52	NR	5.000	0.040	140.000	0.060	193.000	0.035	537.000	0.060	252.000	0.040
53	NR	400.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
54											
55											
56		VALLEY SECTION LOOKING AWAY FROM BOUNDARY				FIELD BOOK STA. 0+00					
57											
58	X1	16340.000	0.000	82.000	297.500	605.000	605.000	605.000	0.000	0.000	0.000
59	GR	594.000	0.000	593.600	180.000	589.900	180.000	576.700	193.000	576.500	420.000
60	GF	576.700	82.000	591.300	262.500	594.000	420.000	576.700	450.000	0.000	0.000

PRINTED IN U.S.A.
FORM 1411.00 PRINTED BY ROTARY MANIFOLD FORMS

EJ 0.000 0.300 0.000 0.300 3.000 0.000 0.000 0.000 0.000 0.000



PRINTED IN U.S.A.

FORM 1411-OD-PRINTED BY ROTARY MANIFOLD FORMS

00BREAK00

1) COUNTY: Wayne

2) STUDY NAME: City of Livonia

3) WATERCOURSE: Beitz Drain

4) DOCUMENT TYPE: 100 Year

00BREAK00

```
**********
  HEC2 RELEASE DATED NOV 76 UPDATED  AUG1977
  ERROR CORR -  01,02
  MODIFICATION -  50,51,52,53
**********

C
T1 BEITZ DRAIN FIS HUD 2014 07 LIVONIA CITY FROM BELL BRANCH TO CURTIS RD.
T2 100 YR FLOW
T3      BEITZ DRAIN LIVONIA CITY

J1  ICHECK    INQ       NINV      IOIR      SIRI      METRIC    HVINS     Q         WSEL      FQ
        0.        4.        0.        0.  0.0           0.0       0.0       0.  639.800     0.0
J2  NPROF     IPLOT     PRFVS     XSECV     XSECH     FN        ALLOC     IBW       CHNIM     ITRACE
    1.000     1.000    -1.000     0.0       0.0       0.0       0.0       0.0       0.0       0.0
J3  VARIABLE CODES FOR SUMMARY PRINTOUT
  110.000   150.000   200.000     0.0       0.0       0.0       0.0       0.0       0.0       0.0

ET    0.0       0.0       0.0       0.0       1.410     0.0       0.0       0.0       0.0       0.0
OT    5.000   180.000   310.000   380.000   380.000   560.000     0.0       0.0       0.0       0.0
NC    0.120     0.120     0.035     0.100     0.300     0.0       0.0       0.0       0.0       0.0

        SECNO 70

X1   70.000     9.000    89.000   111.000     0.0       0.0       0.0       0.0       0.0       0.0
GR  650.000     0.0     640.000    70.000   638.100    89.000   634.100    94.000   634.100   100.000
GR  634.200   106.000   637.200   111.000   640.000   130.000   650.000   265.000     0.0       0.0
ET    0.0       0.0       0.0       0.0       9.100     0.0       0.0       0.0       1.000   264.000

X1  297.000     0.0       0.0       0.0     227.000   227.000   227.000     0.0       0.900     0.0

X1  524.000     9.000   115.000   135.000   227.000   227.000   227.000     0.0      -1.000     0.0
GR  655.000     0.0     643.000    85.000   640.500   115.000   637.000   120.000   636.900   125.000
GR  637.000   130.000   640.000   135.000   643.000   220.000   650.000   275.000     0.0       0.0

        SECNO 752.X

X1  752.000     0.0       0.0       0.0     228.000   228.000   228.000     0.0       1.000     0.0

X1  979.000     0.0       0.0       0.0     227.000   227.000   227.000     0.0       0.900     0.0

X1 1207.000    10.000   132.000   150.000   228.000   228.000   228.000     0.0      -1.000     0.0
GR  660.000     0.0     653.000    50.000   642.500   125.000   642.500   132.000   640.000   135.000
GR  639.600   140.000   640.000   145.000   643.000   150.000   647.000   285.000   654.000   325.000

        SECNO 1 3 . X
```

X1	1434.000	0.0	0.0	0.0	227.000	227.000	227.000	0.0	1.000	0.0
X1	1661.000	0.0	0.0	0.0	227.000	227.000	227.000	0.0	0.900	0.0
X1	1888.000	11.000	148.000	166.000	227.000	227.000	227.000	0.0	-1.000	0.0
GR	666.100	0.0	660.200	68.000	647.000	134.000	645.400	141.000	645.500	148.000
GR	642.700	152.000	642.300	156.000	642.600	160.000	645.400	166.000	648.600	299.000
GR	654.700	358.000	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

SECNO 2115 STA 24=50 FROM FIELD BOOK AND QUAD MAP

X1	2115.000	0.0	0.0	0.0	227.000	227.000	227.000	0.0	1.000	0.0

SECNO 2359 50: D/S 6 MILE BRIDGE FROM FIELD BOOK AND QUAD MAP

X1	2359.000	7.000	133.500	146.500	300.000	210.000	244.000	0.0	0.0	0.0
GR	660.000	0.0	651.100	120.000	644.400	133.500	644.300	140.000	644.400	146.500
GR	653.600	165.000	660.000	250.000	0.0	0.0	0.0	0.0	0.0	0.0
NC	0.0	0.0	0.0	0.300	0.500	0.0	0.0	0.0	0.0	0.0

SECNO 2409 STA 21=56 D/S FACE 6 MILE BR. FROM FIELD BOOK AND QUAD MAP

X1	2409.000	0.0	0.0	0.0	50.000	50.000	50.000	0.0	0.0	0.0
X3	10.000	0.0	0.0	0.0	0.0	0.0	0.0	660.500	660.500	0.0
SB	0.0	2.030	3.000	0.0	12.750	0.0	89.300	0.0	643.800	644.300

SECNO 2526 STA 20=39 U/S FACE 6 MILE BR. FROM FIELD BOOK AND QUAD MAP

X1	2526.000	7.000	133.400	146.500	117.000	117.000	117.000	0.0	0.0	0.0
X2	0.0	0.0	1.000	650.800	660.000	0.0	0.0	0.0	0.0	0.0
X3	10.000	0.0	0.0	0.0	0.0	0.0	0.0	660.700	660.700	0.0
X4	2.000	643.900	133.500	643.900	146.400	0.0	0.0	0.0	0.0	0.0
BT	0.000	0.0	660.000	0.0	119.000	660.700	0.0	133.400	660.700	643.900
BT	133.500	660.700	650.800	146.400	660.700	650.800	146.500	660.700	643.900	165.000
BT	660.000	0.0	250.000	660.000	0.0	0.0	0.0	0.0	0.0	0.0
GR	660.000	0.0	649.700	119.000	643.900	133.400	643.800	140.000	643.900	146.500
GR	653.100	165.000	660.000	250.000	0.0	0.0	0.0	0.0	0.0	0.0

SECNO 2576 50: U/S 6 MILE BRIDGE FROM FIELD BOOK AND QUAD MAP

X1	2576.000	0.0	0.0	0.0	50.000	50.000	50.000	0.0	0.0	0.0
X1	2824.000	0.0	0.0	0.0	248.000	248.000	248.000	0.0	1.300	0.0
NC	0.060	0.100	0.035	0.100	0.300	0.0	0.0	0.0	0.0	0.0
X1	3072.000	7.000	128.000	142.000	248.000	248.000	248.000	0.0	-1.300	0.0
X4	2.000	648.500	122.000	648.500	150.000	0.0	0.0	0.0	0.0	0.0
GR	665.000	0.0	655.000	110.000	648.000	128.000	647.700	135.000	648.000	142.000
GR	655.000	168.000	665.000	240.000	0.0	0.0	0.0	0.0	0.0	0.0
ET	0.0	0.0	0.0	0.0	1.410	0.0	0.0	0.0	0.0	0.0

SECNO 3321 X

X1	3321.000	0.0	0.0	0.0	249.000	249.000	249.000	0.0	1.300	0.0

X1	3569.000	0.0	0.0	0.0	248.000	248.000	248.000	0.0	1.300	0.0
X1	3817.000	9.000	114.000	137.000	248.000	248.000	248.000	0.0	-1.300	0.0
GR	668.900	0.0	660.700	50.000	658.100	61.000	655.000	114.000	651.700	130.000
GR	651.600	133.000	652.000	137.000	665.800	180.000	667.200	210.000	0.0	0.0
ET	0.0	0.0	0.0	0.0	9.100	0.0	0.0	0.0	1.000	209.000

SECNO 4065 STA 5=00 FROM FIELD BOOK AND QUAD MAP

X1	4065.000	0.0	0.0	0.0	248.000	248.000	248.000	0.0	1.300	0.0

SECNO 4250 BASED ON QUAD MAP AND SUBD. MAP

X1	4250.000	9.000	77.000	85.000	185.000	185.000	185.000	0.0	0.0	0.0
GR	663.000	0.0	661.000	48.000	654.000	76.000	651.100	77.000	651.000	81.000
GR	651.100	85.000	654.000	115.000	660.000	145.000	665.000	300.000	0.0	0.0
NC	0.060	0.100	0.020	0.300	0.500	0.0	0.0	0.0	0.0	0.0

SECNO 4490 75± D/S FRANCAVILLA CULVERT BASED ON QUAD MAP " SUBD. MAP

X1	4490.000	13.000	112.000	120.000	240.000	240.000	240.000	0.0	0.0	0.0
GR	668.000	0.0	662.000	1.000	660.000	56.000	658.000	92.000	656.100	97.000
GR	651.200	112.000	651.100	116.000	651.200	120.000	656.100	131.000	658.000	146.000
GR	660.000	152.000	664.000	166.000	670.000	191.000	0.0	0.0	0.0	0.0

SECNO 4515 X

X1	4515.000	0.0	0.0	0.0	25.000	25.000	25.000	0.0	0.0	0.0
X3	0.0	0.0	0.0	101.000	0.0	127.000	0.0	0.0	0.0	0.0

SECNO 4540 X

X1	4540.000	0.0	0.0	0.0	25.000	25.000	25.000	0.0	0.100	0.0
X3	0.0	0.0	0.0	106.000	0.0	122.000	0.0	0.0	0.0	0.0
NC	0.0	0.0	0.020	0.400	0.600	0.0	0.0	0.0	0.0	0.0
ET	0.0	0.0	0.0	0.0	9.100	0.0	0.0	0.0	1.000	185.000

SECNO 4564 D/S FRANCAVILLA CULVERT FROM FIELD BOOK AND SUBD. MAP

X1	4564.000	15.000	116.000	124.000	24.000	24.000	24.000	0.0	0.0	0.0
X3	10.000	0.0	0.0	0.0	0.0	0.0	0.0	659.200	659.200	0.0
GR	665.000	0.0	660.000	1.000	660.200	64.000	655.200	116.000	654.200	116.010
GR	653.200	116.500	652.200	117.300	651.200	120.000	652.200	122.700	653.200	123.500
GR	654.200	123.900	655.200	124.000	660.000	164.000	665.000	170.000	670.000	186.000
NC	0.0	0.0	0.015	0.400	0.600	0.0	0.0	0.0	0.0	0.0

SECNO 4565 D/S FACE FRANCAVILLA CULV. FROM F.B." SUBD. MAP

X1	4565.000	0.0	0.0	0.0	1.000	1.000	1.000	0.0	0.0	0.0
X3	10.000	0.0	0.0	0.0	0.0	0.0	0.0	659.200	659.200	0.0
BT	11.000	0.0	665.000	0.0	116.000	665.000	0.0	116.100	665.000	656.200
BT	116.500	665.000	657.200	117.300	665.000	658.200	120.000	665.000	659.200	122.700
BT	665.000	658.200	123.500	665.000	657.200	123.900	665.000	656.200	124.000	665.000
BT	655.200	170.000	665.000	0.0	0.0	0.0	0.0	0.0	0.0	0.0

SECNO 4595 BASED ON QUAD MAP " SUBD. MAP

X1	4925.000	0.0	0.0	0.0	360.000	360.000	360.000	0.0	1.430	0.0
X2	0.0	0.0	0.0	0.0	0.0	0.530	1.000	0.0	0.0	0.0
X3	10.000	0.0	0.0	0.0	0.0	0.0	0.0	668.300	668.300	0.0

SECNO 5280 BASED ON QUAD MAP " SUBD. MAP

X1	5280.000	0.0	0.0	0.0	355.000	355.000	355.000	0.0	1.430	0.0
X2	0.0	0.0	0.0	0.0	0.0	0.230	1.000	0.0	0.0	0.0
X3	10.000	0.0	0.0	0.0	0.0	0.0	0.0	668.300	668.300	0.0

SECNO 5640 U/S FACE FRANCAVILLA CULVERT AT U/S FACE CURTIS RD.

X1	5640.000	15.000	99.000	107.000	360.000	360.000	360.000	0.0	0.0	0.0
X3	10.000	0.0	0.0	0.0	0.0	0.0	0.0	668.300	668.300	0.0
BT	14.000	0.0	670.900	0.0	28.000	670.000	0.0	92.000	668.300	0.0
BT	99.000	668.300	0.0	99.100	668.500	660.500	99.500	668.500	661.500	100.200
BT	668.500	662.500	103.000	668.500	663.500	105.800	668.500	662.500	106.500	668.500
BT	661.500	106.900	668.500	660.500	107.000	668.500	0.0	115.000	669.000	0.0
BT	143.000	670.000	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
GR	670.900	0.0	670.000	28.000	669.500	72.000	665.300	92.000	659.500	99.000
GR	658.500	99.100	657.500	99.500	656.500	100.200	655.500	103.000	656.500	105.800
GR	657.500	106.500	658.500	106.900	659.500	107.000	665.300	115.000	670.000	143.000
NC	0.0	0.0	0.080	0.300	0.500	0.0	0.0	0.0	0.0	0.0

SECNO 5641 U/S FRANCAVILLA CULVERT FROM FIELD BOOK AND SUBD. MAP

X1	5641.000	0.0	0.0	0.0	1.000	1.000	1.000	0.0	0.0	0.0
X3	10.000	0.0	0.0	0.0	0.0	0.0	0.0	668.300	668.300	0.0
EJ	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

*PROF 1

CCHV= 0.100 CEHV= 0.300

*SECNO 70.000

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	QLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST
	SECNO 70								
70.00	5.70	639.80	0.0	639.80	639.97	0.17	0.0	0.0	638.10
380.	5.	365.	10.	14.	107.	23.	0.	0.	637.20
0.0	0.33	3.41	0.44	0.120	0.035	0.120	0.0	634.10	72.00
0.000889	0.	0.	0.	0	0	0	0.0	56.64	128.64
*SECNO 297.000									
297.00	5.01	640.01	0.0	0.0	640.26	0.25	0.26	0.02	639.00
380.	2.	373.	6.	5.	92.	12.	1.	0.	638.10
0.02	0.31	4.06	0.47	0.120	0.035	0.120	0.035	635.00	78.98
0.001552	227.	227.	227.	0	0	0	0.0	44.92	123.91
*SECNO 524.000									
524.00	4.49	640.39	0.0	0.0	640.77	0.38	0.47	0.04	639.50
380.	2.	364.	14.	5.	72.	27.	1.	1.	639.00
0.03	0.39	5.05	0.52	0.120	0.035	0.120	0.035	635.90	104.35
0.002904	227.	227.	227.	2	0	0	0.0	69.97	174.32
*SECNO 752.000									
	SECNO 752.X								
752.00	4.19	641.09	0.0	0.0	641.57	0.48	0.77	0.03	640.50
380.	1.	370.	9.	2.	66.	17.	2.	1.	640.00
0.04	0.35	5.60	0.52	0.120	0.035	0.120	0.035	636.90	107.88
0.004000	228.	228.	228.	2	0	0	0.0	58.08	165.97
*SECNO 979.000									
SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	QLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST
979.00	4.20	642.00	0.0	0.0	642.47	0.47	0.90	0.00	641.40
380.	1.	370.	9.	2.	66.	17.	2.	1.	640.90
0.05	0.35	5.59	0.52	0.120	0.035	0.120	0.035	637.80	107.81
0.003973	227.	227.	227.	2	0	0	0.0	56.33	166.14
*SECNO 1207.000									
1207.00	4.31	642.91	0.0	0.0	643.42	0.51	0.94	0.01	641.50
380.	15.	359.	7.	17.	61.	14.	3.	2.	642.00
0.06	0.86	5.87	0.48	0.120	0.035	0.120	0.035	638.60	114.94
0.00[illegible]9	228.	228.	228	[illegible]	[illegible]0	0	0.	65.73	166.27

100yr. fp. on Bell Branch is 642.53

*SECNO 1434.000

SECNO 1434 X

1434.00	4.28	643.88	0.0	0.0	644.40	0.52	0.98	0.00	642.50
380.	14.	360.	6.	17.	61.	13.	3.	2.	643.00
0.07	0.86	5.93	0.47	0.120	0.035	0.120	0.035	639.60	115.12
0.004371	227.	227.	227.	2	0	0	0.0	64.71	179.83

*SECNO 1661.000

1661.00	4.37	644.87	0.0	0.0	645.35	0.48	0.95	0.00	643.40
380.	15.	357.	8.	18.	62.	16.	4.	2.	643.90
0.09	0.85	5.76	0.68	0.120	0.035	0.120	0.035	640.50	114.56
0.004000	227.	227.	227.	0	0	0	0.0	67.91	182.46

*SECNO 1888.000

1888.00	4.49	645.79	0.0	0.0	646.23	0.44	0.87	0.00	644.50
380.	11.	345.	24.	14.	62.	40.	4.	3.	644.40
0.10	0.81	5.57	0.59	0.120	0.035	0.120	0.035	641.30	134.92
0.003685	227.	227.	227.	2	0	0	0.0	88.85	223.77

*SECNO 2115.000

SECNO	DEPTH	CHSEL	CRIWS	WSELK	EG	HV	HL	QLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WIN	ELMIN	SSIA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST


SECNO 2115 STA 24=50 FROM FIELD BOOK AND QUAD MAP

2115.00	4.35	646.65	0.0	0.0	647.15	0.49	0.90	0.02	645.50
380.	10.	350.	20.	12.	60.	33.	5.	3.	645.40
0.11	0.83	5.87	0.60	0.120	0.035	0.120	0.035	642.30	135.40
0.004303	227.	227.	227.	0	0	0	0.0	82.98	218.46

*SECNO 2359.000

SECNO 2359 50: D/S 6 MILE BRIDGE FROM FIELD BOOK AND QUAD MAP

2359.00	3.39	647.69	0.0	0.0	648.62	0.94	1.34	0.13	644.40
380.	15.	350.	15.	11.	43.	11.	5.	3.	644.40
0.12	1.37	8.08	1.37	0.120	0.035	0.120	0.035	644.30	126.88
0.007265	300.	244.	210.	2	0	0	0.0	26.23	153.11



CCHV= 0.300 CEHV= 0.500
*SECNO 2409.000

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE.ELLEA= 660.50 ELREA= 660.50

SECNO 2409 STA 21=56 D/S FACE 6 MILE BR. FROM FIELD BOOK AND QUAD MAP

2409.00	3.71	648.01	0.0	0.0	649.00	0.99	0.35	0.03	644.40
380.	0.	380.	0.	0.	48.	0.	5.	3.	644.40
0.12	0.0	7.98	0.0	0.120	0.035	0.120	0.035	644.30	133.50
0.006894	50.	50.	50.	2	0	0	0.0	13.00	146.50

SPECIAL BRIDGE

SB	XK	XKOR	COFQ	RDLEN	BWC	BWP	BAREA	SS	ELCHU	ELCHD
	0.0	2.03	3.00	0.0	12.75	0.0	89.30	0.0	643.80	644.30

*SECNO 2526.000

6070,LOW FLOW BY NORMAL BRIDGE

EGPRS= 0.0 EGLWC= 648.487 ELLC= 650.800 PCWSE= 648.013 ELTRD= 660.000

3301 HV CHANGED MORE THAN HVINS

3370 NORMAL BRIDGE,NRD= 8 MIN ELTRD= 660.00 MAX ELLC= 650.80

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 660.70 ELREA= 660.70

649.31 from Hyd. report (Q=420 cfs)
File No. 2387-31

SECNO 2526 STA 20+39 U/S FACE 6 MILE BR. FROM FIELD BOOK AND QUAD MAP

2526.00	5.38	649.18	0.0	0.0	649.65	0.46	0.49	0.16	643.90
380.	0.	380.	0.	0.	70.	0.	5.	3.	643.90
0.13	0.0	5.47	0.0	0.120	0.035	0.120	0.035	643.80	133.60
0.002794	117.	117.	117.	3	0	0	-28.26	13.10	146.50

*SECNO 2576.000

SECNO 2576 50+ U/S 6 MILE BRIDGE FROM FIELD BOOK AND QUAD MAP

2576.00	5.73	649.53	0.0	0.0	649.79	0.26	0.08	0.06	643.90
380.	30.	326.	24.	39.	74.	32.	6.	3.	643.90
0.13	0.76	4.38	0.74	0.120	0.035	0.120	0.035	643.80	119.41
0.001051	50.	50.	50.	2	0	0	0.0	38.41	157.83

*SECNO 2824.000

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	ITN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	IIRIAL	IDC	ICONT	CORAR	IOPT#1D	ENDST
2824.00	4.72	649.82	0.0	0.0	650.23	0.41	0.36	0.08	645.20
380.	25.	335.	20.	26.	61.	21.	6.	4.	645.20
0.14	0.95	5.48	0.93	0.120	0.035	0.120	0.035	645.10	121.94
0.002138	248.	248.	248.	2	0	0	0.0	33.84	155.78

CCHV= 0.100 CEHV= 0.300

*SECNO 3072.000

3072.00	4.06	650.46	0.0	0.0	650.82	0.36	0.58	0.01	646.70
380.	48.	293.	39.	22.	55.	29.	7.	4.	646.70
0.16	2.20	5.36	1.33	0.060	0.035	0.100	0.035	646.40	117.48
0.002596	248.	248.	248.	2	0	0	0.0	39.29	156.77

Channel
Top
Slope
n = .1
from Hyd rpt
@ 3206

*SECNO 3321.000

SECNO 3321 X

3321.00	3.48	651.18	0.0	0.0	651.72	0.54	0.85	0.05	648.00
3[illegible]0.	2.	3[illegible]4.	34.	1[illegible].	47.	[illegible].	7.	4.	[illegible]4[illegible].00

.1	2.64	6.50	1.5	0.060	0.035	0.100	.035	641.70	11 .1
0.004716	249.	249.	249.	2	0	0	0.0	35.98	154.79

*SECNO 3569.000

3569.00	3.39	652.39	0.0	0.0	652.97	0.58	1.23	0.01	649.30
380.	41.	305.	34.	15.	45.	20.	8.	4.	649.30
0.18	2.73	6.74	1.65	0.060	0.035	0.100	0.035	649.00	119.03
0.005261	248.	248.	248.	2	0	0	0.0	35.43	154.46

651.85@3406

*SECNO 3817.000

3817.00	3.62	653.92	0.0	0.0	654.53	0.61	1.55	0.01	653.70
380.	0.	352.	28.	0.	54.	16.	8.	4.	650.70
0.19	0.50	6.47	1.72	0.060	0.035	0.100	0.035	650.30	110.19
0.007534	248.	248.	248.	2	0	0	0.0	36.86	147.04

*SECNO 4065.000

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	QLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

SECNO 4065 STA 5=00 FROM FIELD BOOK AND QUAD MAP

654.94@4006

4065.00	3.96	655.56	0.0	0.0	656.01	0.46	1.47	0.02	655.00
380.	2.	349.	29.	3.	62.	20.	9.	5.	652.00
0.21	0.73	5.63	1.46	0.060	0.035	0.100	0.035	651.60	104.50
0.004784	248.	248.	248.	2	0	0	0.0	43.58	148.08

*SECNO 4250.000

SECNO 4250 BASED ON QUAD MAP AND SUBD. MAP

4250.00	5.27	656.27	0.0	0.0	656.49	0.21	0.45	0.02	651.10
380.	15.	205.	160.	14.	42.	125.	9.	5.	651.10
0.22	1.03	4.91	1.29	0.060	0.035	0.100	0.035	651.00	66.91
0.001475	185.	185.	185.	2	0	0	0.0	54.45	126.36

CCHV= 0.300 CEHV= 0.500

*SECNO 4490.000

SECNO 4490 75: D/S FRANCAVILLA CULVERT BASED ON QUAD MAP & SUBD. MAP

657.19 @ 4456 (325

4490.00	5.27	656.37	0.0	0.0	656.97	0.60	0.29	0.19	651.20
380.	60.	294.	26.	41.	42.	30.	10.	5.	651.20
0.23	1.47	7.04	0.85	0.060	0.020	0.100	0.034	651.10	96.29
0.000992	240.	240.	240.	2	0	0	0.0	36.86	133.14

*SECNO 4515.000

3470 ENCROACHMENT STATIONS= 101.0 127.0 TYPE= 1 TARGET= 26.000

SECNO 4515 X

4515.00	5.28	656.38	0.0	0.0	657.00	0.63	0.03	0.01	651.20
380.	59.	298.	23.	37.	42.	25.	10.	5.	651.20
0.24	1.58	7.12	0.90	0.060	0.020	0.100	0.034	651.10	101.00
0.001010	25.	25.	25.	1	0	0	0.0	26.00	127.00

*SECNO 4540.000

3470 ENCROACHMENT STATIONS= 106.0 122.0 TYPE= 1 TARGET= 16.000

SECNO 4540 X

4540.00	5.06	656.26	0.0	0.0	657.19	0.93	0.03	0.15	651.30
380.	42.	331.	7.	24.	40.	9.	10.	5.	651.30
0.24	1.77	8.27	0.72	0.060	0.020	0.100	0.034	651.20	106.00
0.001448	25.	25.	25.	2	0	0	0.0	16.00	122.00

CCHV= 0.400 CEHV= 0.600

*SECNO 4564.000

3301 HV CHANGED MORE THAN HVINS

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	IOPWID	ENDST

7185 MINIMUM SPECIFIC ENERGY

3720 CRITICAL DEPTH ASSUMED

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE.ELLEA= 659.20 ELREA= 659.20

SECNO 4564 D/S FRANCAVILLA CULVERT FROM FIELD BOOK AND SUBD. MAP

4564.00	5.07	656.27	656.27	0.0	658.35	2.08	0.07	0.69	655.20
380.	0.	380.	0.	0.	33.	0.	10.	5.	655.20
0.24	0.0	11.56	0.0	0.060	0.020	0.100	0.034	651.20	116.00
0.007455	24.	24.	24.	5	5	0	0.0	8.00	124.00

CCHV= 0.400 CEHV= 0.600

*SECNO 4565.000

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	IOPWID	ENDST

3370 NORMAL BRIDGE.NRD= 11 MIN ELTRD= 665.00 MAX ELLC= 659.20

7185 MINIMUM SPECIFIC ENERGY

3720 CRITICAL DEPTH ASSUMED

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE.ELLEA= 659.20 ELREA= 659.20

SECNO 4565 D/S FACE FRANCAVILLA CULV. FROM F.B." SUBD. MAP

4565.00	5.06	656.26	656.26	0.0	658.42	2.17	0.01	0.06	655.20
380.	0.	380.	0.	0.	32.	0.	10.	5.	655.20
0.24	0.0	11.82	0.0	0.060	0.015	0.100	0.034	651.20	116.00
0.004680	1.	1.	1.	2	17	0	-5.23	8.00	124.00

664.32 from Hyd. report

96" RCCP L = 1075' with 3 bends

8930.RDST NOT ON GR CARD 116.10

*SECNO 4925.000

*TEST EL CHANGE FROM XS CARD

3370 NORMAL BRIDGE,NRD= 11 MIN ELTRD= 665.00 MAX ELLC= 660.63

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 668.30 ELREA= 668.30

SECNO 4925 BASED ON QUAD MAP " SUBD. MAP

4925.00	5.06	657.69	657.69	0.0	659.85	2.16	1.68	0.00	656.63
380.	0.	380.	0.	0.	32.	0.	11.	5.	656.63
0.25	0.0	11.80	0.0	0.060	0.015	0.100	0.032	652.63	116.00
0.004664	360.	360.	360.	0	17	0	-5.28	8.00	124.00

8930,RDST NOT ON GR CARD 116.10
*SECNO 5280.000
WATER EL CHANGE FROM X2 CARD

3370 NORMAL BRIDGE,NRD= 11 MIN ELTRD= 665.00 MAX ELLC= 662.06

96" RCCP

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 668.30 ELREA= 668.30

SECNO 5280 BASED ON QUAD MAP " SUBD. MAP

5280.00	5.06	659.12	659.12	0.0	661.28	2.16	1.66	0.00	658.06
380.	0.	380.	0.	0.	32.	0.	11.	5.	658.06
0.25	0.0	11.80	0.0	0.060	0.015	0.100	0.031	654.06	116.00
0.004665	355.	355.	355.	0	17	0	-5.28	8.00	124.00

8930,RDST NOT ON GR CARD 116.10
*SECNO 5640.000

3301 HV CHANGED MORE THAN HVINS

3370 NORMAL BRIDGE,NRD= 14 MIN ELTRD= 668.30 MAX ELLC= 663.50

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 668.30 ELREA= 668.30

SECNO 5640 U/S FACE FRANCAVILLA CULVERT AT U/S FACE CURTIS RD.

5640.00	5.79	661.29	0.0	0.0	662.83	1.54	1.29	0.25	659.50
380.	0.	380.	0.	0.	38.	0.	11.	5.	659.50
0.26	0.0	9.95	0.0	0.060	0.015	0.100	0.030	655.50	99.00
0.002858	360.	360.	360.	3	0	0	-2.68	8.00	107.00

CCHV= 0.300 CEHV= 0.500
*SECNO 5641.000

SECNO	DEPTH	CHSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WIN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IOC	ICONT	CORAR	TOPWID	ENDST

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 668.30 ELREA= 668.30

SECNO 5641 U/S FRANCAVILLA CULVERT FROM FIELD BOOK AND SUBD. MAP

5641.00	6.03	661.53	0.0	0.0	662.89	1.36	0.01	0.05	659.50
380.	0.	380.	0.	0.	41.	0.	11.	5.	659.50
0.26	0.0	9.35	0.0	0.060	0.080	0.100	0.030	655.50	99.00
0.064664	1.	1.	1.	3	0	0	0.0	8.00	107.00

W/S EG appears reasonable



1) COUNTY: Wayne

2) STUDY NAME: City of Livonia

3) WATERCOURSE: Beitz Drain

4) DOCUMENT TYPE: Encroachment



```
**********************************************************
  HEC2 RELEASE DATED NOV 76 UPDATED  AUG1977
  ERROR CORR -  01.02
  MODIFICATION -  50,51,52,53
**********************************************************
T1 BEITZ DRAIN FIS HUD 2014 07 LIVONIA CITY FROM BELL BRANCH TO CURTIS RD.
T2ENCROACHMENT RUN
T3      BEITZ DRAIN LIVONIA CITY
```

J1	ICHECK	INQ	NINV	IDIR	STRT	METRIC	HVINS	Q	WSEL	FQ
	0.	5.	0.	0.	0.0	0.0	0.0	0.	639.900	0.0

J2	NPROF	IPLOT	PRFVS	XSECV	XSECH	FN	ALLDC	IBW	CHNIM	ITRACE
	15.000	0.0	-1.000	0.0	0.0	0.0	0.0	0.0	0.0	15.000

*PROF 2

CCHV= 0.100 CEHV= 0.300
*SECNO 70.000
2800 NAT Q1= 127.42 WSEL= 639.80 ENC Q1= 127.42 WSEL= 639.90 RATIO= 0.0000
NAT Q1= 132. RATIOS LOB,CH,ROB= 0.0141 0.9578 0.0281 WSEL= 639.90

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	QLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

3470 ENCROACHMENT STATIONS= 89.0 112.5 TYPE= 4 TARGET= 0.037

SECNO 70

70.00	5.80	639.90	0.0	639.80	640.09	0.19	0.0	0.0	638.10
380.	0.	379.	1.	0.	109.	4.	0.	0.	637.20
0.0	0.0	3.46	0.38	0.120	0.035	0.120	0.0	634.10	89.00
0.000987	0.	0.	0.	0	0	0	0.0	23.69	112.49

FLOW DISTRIBUTION FOR SECNO= 70.00 CWSEL= 639.90

STA=	89.	111.	112.
PER Q=	99.6	0.4	
AREA=	109.3	3.9	
VEL=	3.5	0.4	

*SECNO 297.000

3470 ENCROACHMENT STATIONS= 1.0 264.0 TYPE= 1 TARGET= 263.000

297.00	5.13	640.13	0.0	640.01	640.36	0.24	0.26	0.01	639.00
380.	2.	372.	6.	6.	94.	14.	1.	0.	638.10
0.02	0.31	3.93	0.46	0.120	0.035	0.120	0.035	635.00	77.76
0.001401	227.	227.	227.	0	0	0	0.0	46.98	124.74

FLOW DISTRIBUTION FOR SECNO= 297.00 CWSEL= 640.13

STA=	78.	89.	111.	125.
PER Q=	0.5	97.8	1.7	
AREA=	6.3	94.4	13.9	
VEL=	0.3	3.9	0.5	

*SECNO 524.000

524.00	4.57	640.47	0.0	640.39	640.83	0.36	0.43	0.04	639.50
380.	2.	362.	16.	6.	74.	31.	1.	0.	639.40
0.03	0.39	4.91	0.52	0.120	0.035	0.120	0.035	635.90	103.34
0.002659	227.	227.	227.	2	0	0	0.0	73.36	176.70

FLOW DISTRIBUTION FOR SECNO= 524.00 CWSEL= 640.47

STA=	103.	115.	135.	177.
PER Q=	0.6	95.2	4.2	
AREA=	5.7	73.7	30.7	
VEL=	0.4	4.9	0.5	

*SECNO 757.00

SECNO 752.X

752.00	4.22	641.12	0.0	641.09	641.59	0.47	0.73	0.03	640.50

380.	1.	370.	9.	2.	67.	18.	2.	1.	640.00
0.04	0.35	5.55	0.52	0.120	0.035	0.120	0.035	636.90	107.54
0.003876	228.	228.	228.	2	0	0	0.0	59.23	166.77

FLOW DISTRIBUTION FOR SECNO= 752.00 CWSEL= 641.12

STA=	108.	115.	135.	167.
PER Q=	0.2	97.3	2.5	
AREA=	2.3	66.7	17.8	
VEL=	0.4	5.5	0.5	

*SECNO 979.000

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	HTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST
979.00	4.20	642.00	0.0	642.00	642.48	0.47	0.89	0.00	641.40
380.	1.	370.	9.	2.	66.	17.	2.	1.	640.90
0.05	0.35	5.58	0.52	0.120	0.035	0.120	0.035	637.80	107.74
0.003949	227.	227.	227.	2	0	0	0.0	56.55	166.30

FLOW DISTRIBUTION FOR SECNO= 979.00 CWSEL= 642.00

STA=	108.	115.	135.	166.
PER Q=	0.2	97.4	2.4	
AREA=	2.2	66.3	17.3	
VEL=	0.3	5.6	0.5	

*SECNO 1207.000

1207.00	4.31	642.91	0.0	642.91	643.42	0.51	0.93	0.01	641.50
380.	14.	359.	7.	17.	61.	14.	3.	1.	642.00
0.06	0.86	5.88	0.48	0.120	0.035	0.120	0.035	638.60	114.95
0.004260	228.	228.	228.	1	0	0	0.0	65.64	180.59

FLOW DISTRIBUTION FOR SECNO= 1207.00 CWSEL= 642.91

STA=	115.	125.	132.	150.	181.
PER Q=	1.2	2.6	94.5	1.7	
AREA=	7.1	9.8	61.1	13.9	
VEL=	0.5	1.0	5.9	0.5	

*SECNO 1434.000

SECNO 1434 X

1434.00	4.29	643.89	0.0	643.88	644.40	0.52	0.98	0.00	642.50
380.	14.	359.	6.	17.	61.	13.	3.	2.	643.00
0.08	0.86	5.92	0.48	0.120	0.035	0.120	0.035	639.60	115.10
0.004359	227.	227.	227.	2	0	0	0.0	64.81	179.91

FLOW DISTRIBUTION FOR SECNO= 1434.00 CWSEL= 643.89

STA=	115.	125.	132.	150.	180.
PER Q=	1.1	2.6	94.6	1.7	
AREA=	6.9	9.7	60.7	13.3	
VEL=	0.6	1.0	5.9	0.5	

*SECNO 1661.000

1661.00	4.37	644.87	0.0	644.87	645.35	0.48	0.95	0.00	643.40
380.	15.	357.	8.	18.	62.	16.	4.	2.	643.90
0.09	0.85	5.75	0.48	0.120	0.035	0.120	0.035	640.50	114.54
0.003989	227.	227.	227.	0	0	0	0.0	68.01	182.55

FLOW DISTRIBUTION FOR SECNO= 1661.00 CWSEL= 644.87

STA=	115.	125.	132.	150.	183.
PER Q=	1.3	2.7	94.0	2.0	
AREA=	7.7	10.3	62.1	15.7	
VEL=	0.6	1.0	5.8	0.5	

*SECNO 1888.000

1888.00	4.49	645.79	0.0	645.79	646.23	0.44	0.87	0.00	644.50
380.	11.	345.	24.	14.	62.	40.	4.	3.	644.40
0.10	0.81	5.57	0.59	0.120	0.035	0.120	0.035	641.30	134.93
0.003695	227.	227.	227.	2	0	0	0.0	88.75	223.68

FLOW DISTRIBUTION FOR SECNO= 1888.00 CWSEL= 645.79

STA=	135.	141.	148.	166.	224.
PER Q=	0.6	2.3	90.9	6.2	
AREA=	4.2	9.4	62.0	40.0	
VEL=	0.6	0.9	5.6	0.6	

*SECNO 2115.000

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	OLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

SECNO 2115 STA 24=50 FROM FIELD BOOK AND QUAD MAP

2115.00	4.35	646.65	0.0	646.65	647.15	0.49	0.91	0.02	645.50
380.	10.	350.	20.	12.	60.	33.	5.	3.	645.40
0.11	0.83	5.87	0.60	0.120	0.035	0.120	0.035	642.30	135.49
0.004317	227.	227.	227.	0	0	0	0.0	82.86	218.35

FLOW DISTRIBUTION FOR SECNO= 2115.00 CWSEL= 646.65

STA=	135.	141.	148.	166.	218.
PER Q=	0.5	2.1	92.2	5.2	
AREA=	3.5	8.5	59.7	33.0	
VEL=	0.6	0.9	5.9	0.6	

*SECNO 2359.000

SECNO 2359 50: D/S 6 MILE BRIDGE FROM FIELD BOOK AND QUAD MAP

2359.00	3.39	647.69	0.0	647.69	648.62	0.93	1.34	0.13	644.40
380.	15.	350.	15.	11.	43.	11.	5.	3.	644.40
0.12	1.36	8.07	1.36	0.120	0.035	0.120	0.035	644.30	126.87
0.007240	300.	244.	210.	2	0	0	0.0	26.24	153.11

FLOW DISTRIBUTION FOR SECNO= 2359.00 CWSEL= 647.69

STA=	127.	134.	147.	153.
PER Q=	3.0	9.[illegible]	3.[illegible]	

AREA= 10. 43. 10.
VEL= 1.4 8.1 1.4

CCHV= 0.300 CEHV= 0.500
*SECNO 2409.000

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 660.50 ELREA= 660.50

SECNO 2409 STA 21=56 D/S FACE 6 MILE BR. FROM FIELD BOOK AND QUAD MAP

2409.00	3.72	648.02	0.0	648.01	649.00	0.99	0.35	0.03	644.40
380.	0.	380.	0.	0.	48.	0.	5.	3.	644.40
0.12	0.0	7.98	0.0	0.120	0.035	0.120	0.035	644.30	133.50
0.006884	50.	50.	50.	2	0	0	0.0	13.00	146.50

FLOW DISTRIBUTION FOR SECNO= 2409.00 CHSEL= 648.02

STA= 134. 147.
PER Q= 100.0
AREA= 47.6
VEL= 8.0

SPECIAL BRIDGE

SB	XK	XKOR	COFQ	RDLEN	BHC	BHP	BAREA	SS	ELCHU	ELCHD
	0.0	2.03	3.00	0.0	12.75	0.0	89.30	0.0	643.80	644.30

*SECNO 2526.000

6070,LOW FLOW BY NORMAL BRIDGE

EGPRS= 0.0 EGLWC= 648.488 ELLC= 650.000 PCHSE= 648.015 ELTRD= 660.000

3301 HV CHANGED MORE THAN HVINS

3370 NORMAL BRIDGE,NRD= 8 MIN ELTRD= 660.00 MAX ELLC= 650.80

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 660.70 ELHEA= 660.70

SECNO 2526 STA 20=39 U/S FACE 6 MILE BR. FROM FIELD BOOK AND QUAD MAP

2526.00	5.38	649.18	0.0	649.18	649.65	0.46	0.49	0.16	643.90
380.	0.	380.	0.	0.	70.	0.	5.	3.	643.90
0.13	0.0	5.47	0.0	0.120	0.035	0.120	0.035	643.80	133.40
0.002793	117.	117.	117.	3	0	0	-28.26	13.10	146.50

FLOW DISTRIBUTION FOR SECNO= 2526.00 CHSEL= 649.18

STA= 133. 147.
PER Q= 100.0
AREA= 69.5
VEL= 5.5

*SECNO 2576.000

SECNO 2576 50: U/S 6 MILE BRIDGE FROM FIELD BOOK AND QUAD MAP

2576.00	5.73	649.53	0.0	649.53	649.79	0.26	0.08	0.06	643.90
3.0.	38.	3[illegible]	[illegible]	[illegible]	7[illegible]	3[illegible]	6.	3.	[illegible]3.90

0.13	0.16	4.3	0.14	0.120	.035	0.120	0.035	643.80	117.41
0.001051	50.	50.	50.	2	0	0	0.0	38.41	157.83

FLOW DISTRIBUTION FOR SECNO= 2576.00 CWSEL= 649.53

STA=	119.	133.	147.	158.
PER Q=	7.9	85.9	6.2	
AREA=	39.4	74.4	31.9	
VEL=	0.8	4.4	0.7	

*SECNO 2824.000

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	HTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST
2824.00	4.72	649.82	0.0	649.82	650.23	0.41	0.36	0.08	645.20
380.	25.	335.	20.	26.	61.	21.	6.	4.	645.20
0.15	0.95	5.48	0.93	0.120	0.035	0.120	0.035	645.10	121.94
0.002138	248.	248.	248.	2	0	0	0.0	33.84	155.78

FLOW DISTRIBUTION FOR SECNO= 2824.00 CWSEL= 649.82

STA=	122.	133.	147.	156.
PER Q=	6.6	88.1	5.2	
AREA=	26.4	61.1	21.4	
VEL=	1.0	5.5	0.9	

CCHV= 0.100 CEHV= 0.300

*SECNO 3072.000

3072.00	4.06	650.46	0.0	650.46	650.82	0.36	0.58	0.01	646.70
380.	48.	293.	39.	22.	55.	29.	7.	4.	646.70
0.16	2.20	5.36	1.33	0.060	0.035	0.100	0.035	646.40	117.48
0.002597	248.	248.	248.	2	0	0	0.0	39.29	156.77

FLOW DISTRIBUTION FOR SECNO= 3072.00 CWSEL= 650.46

STA=	117.	122.	128.	142.	150.	157.
PER Q=	1.4	11.1	77.2	9.0	1.3	
AREA=	4.4	17.1	54.7	22.9	6.6	
VEL=	1.2	2.5	5.4	1.5	0.7	

*SECNO 3321.000

2800 NAT QI= 55.33 WSEL= 651.18 ENC QI= 55.33 WSEL= 651.28 RATIO= 0.0000

NAT QI= 58. RATIOS LOB,CH,ROB= 0.1133 0.7939 0.0928 WSEL= 651.28

3470 ENCROACHMENT STATIONS= 122.3 148.7 TYPE= 4 TARGET= 0.054

SECNO 3321 X

3321.00	3.47	651.17	0.0	651.18	651.79	0.63	0.89	0.08	648.00
380.	35.	319.	27.	13.	46.	16.	7.	4.	648.00
0.17	2.64	6.86	1.66	0.060	0.035	0.100	0.035	647.70	122.34
0.005287	249.	249.	249.	2	0	0	0.0	20.38	148.72

FLOW DISTRIBUTION FOR SECNO= 3321.00 CWSEL= 651.17

STA=	122.	128.	142.	149.
PER Q=	9.1	83.8	7.1	
AREA=	13.1	46.4	16.2	
VEL=	2.	.9	1.7	

*SECNO 3569.000
2800 NAT Q1= 52.39 WSEL= 652.39 ENC Q1= 52.39 WSEL= 652.49 RATIO= 0.0
NAT Q1= 55. RATIOS LOB,CH,ROB= 0.1108 0.7986 0.0906 WSEL= 652.49

3470 ENCROACHMENT STATIONS= 122.6 148.4 TYPE= 6 TARGET= 0.055

3569.00	3.47	652.47	0.0	652.39	653.11	0.63	1.31	0.00	649.30
380.	34.	320.	26.	13.	47.	16.	8.	4.	649.30
0.18	2.64	6.88	1.66	0.060	0.035	0.100	0.035	649.00	122.56
0.005299	248.	248.	248.	2	0	0	0.0	25.82	148.38

FLOW DISTRIBUTION FOR SECNO= 3569.00 CWSEL= 652.47

STA=	123.	128.	142.	148.
PER Q=	8.9	84.2	6.8	
AREA=	12.8	46.5	15.7	
VEL=	2.6	6.9	1.7	

*SECNO 3817.000
2800 NAT Q1= 43.78 WSEL= 653.92 ENC Q1= 43.78 WSEL= 654.02 RATIO= 0.0
NAT Q1= 47. RATIOS LOB,CH,ROB= 0.0014 0.9248 0.0738 WSEL= 654.02

3470 ENCROACHMENT STATIONS= 114.0 137.6 TYPE= 4 TARGET= 0.066

3817.00	3.71	654.01	0.0	653.92	654.71	0.69	1.58	0.02	653.70
380.	0.	379.	1.	0.	56.	2.	8.	4.	650.70
0.19	0.0	6.70	0.81	0.060	0.035	0.100	0.035	650.30	114.00
0.007859	248.	248.	248.	2	0	0	0.0	23.56	137.56

FLOW DISTRIBUTION FOR SECNO= 3817.00 CWSEL= 654.01

STA=	114.	137.	138.
PER Q=	99.6	0.4	
AREA=	56.5	1.8	
VEL=	6.7	0.8	

*SECNO 4065.000

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	KV	ML	QLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	COBAR	TOPWID	ENDST

3470 ENCROACHMENT STATIONS= 1.0 209.0 TYPE= 1 TARGET= 2080.000

SECNO 4065 STA S=00 FROM FIELD BOOK AND QUAD MAP

4065.00	4.09	655.69	0.0	655.56	656.10	0.41	1.36	0.03	655.00
380.	3.	348.	29.	4.	65.	21.	9.	4.	652.00
0.21	0.77	5.34	1.37	0.060	0.035	0.100	0.035	651.60	102.22
0.004037	248.	248.	248.	2	0	0	0.0	46.27	148.49

FLOW DISTRIBUTION FOR SECNO= 4065.00 CWSEL= 655.69

STA=	102.	114.	137.	148.
PER Q=	0.8	91.5	7.7	
AREA=	4.1	65.1	21.2	
VEL=	0.8	5.3	1.4	

*SECNO 4250.000

SECNO 4250 BASED ON QUAD MAP AND SUBD. MAP

*4250.00	5.32	656.32	0.0	656.27	657.03	0.71	0.41	0.02	651.10
380.	15.	204.	161.	15.	42.	127.	9.	5.	651.10
0.22	1.02	4.84	1.27	0.060	0.035	0.100	0.035	651.00	66.71
0.001414	185.	185.	185.	2	0	0	0.0	59.91	126.62

FLOW DISTRIBUTION FOR SECNO= 4250.00 CWSEL= 656.32

STA=	67.	76.	77.	85.	115.	127.
PER Q=	2.9	1.1	53.7	40.2	2.2	
AREA=	10.8	3.8	42.2	113.2	13.5	
VEL=	1.0	1.1	4.8	1.4	0.6	

CCHV= 0.300 CEHV= 0.500

*SECNO 4490.000

SECNO 4490 75: D/S FRANCAVILLA CULVERT BASED ON QUAD MAP " SUBD. MAP

4490.00	5.31	656.41	0.0	656.37	657.00	0.59	0.28	0.19	651.20
380.	61.	293.	26.	42.	42.	31.	10.	5.	651.20
0.23	1.46	6.97	0.84	0.060	0.020	0.100	0.034	651.10	96.17
0.000961	240.	240.	240.	2	0	0	0.0	37.30	133.48

FLOW DISTRIBUTION FOR SECNO= 4490.00 CWSEL= 656.41

STA=	96.	112.	120.	131.	133.
PER Q=	16.0	77.2	6.8	0.0	
AREA=	41.6	42.1	30.4	0.4	
VEL=	1.5	7.0	0.9	0.1	

*SECNO 4515.000

3470 ENCROACHMENT STATIONS= 101.0 127.0 TYPE= 1 TARGET= 26.000

SECNO 4515 X

4515.00	5.32	656.42	0.0	656.38	657.03	0.61	0.02	0.01	651.20
380.	59.	298.	23.	38.	42.	26.	10.	5.	651.20
0.24	1.56	7.06	0.89	0.060	0.020	0.100	0.034	651.10	101.00
0.000982	25.	25.	25.	1	0	0	0.0	26.00	127.00

FLOW DISTRIBUTION FOR SECNO= 4515.00 CWSEL= 656.42

STA=	101.	112.	120.	127.
PER Q=	15.5	78.5	6.0	
AREA=	37.8	42.2	25.7	
VEL=	1.6	7.1	0.9	

*SECNO 4540.000

3470 ENCROACHMENT STATIONS= 106.0 122.0 TYPE= 1 TARGET= 16.000

SECNO 4540 X

4540.00	5.10	656.30	0.0	656.26	657.22	0.92	0.03	0.15	651.30
380.	42.	331.	6.	24.	40.	9.	10.	5.	651.30
0.24	1.75	8.20	0.71	0.060	0.020	0.100	0.034	651.20	106.00
0.001408	25.	25.	25.	2	0	0	0.0	16.00	122.00

FLOW DISTRIBUTION FOR SECNO= 4540.00 CWSEL= 656.30

STA=	106.	112.	120.	122.
PER Q=	11.1	87.[illegible]	1.7	

```
AREA=      24.1      40.4       .1
 VEL=       1.7       8.2       0.7

CCHV=   0.400 CEHV=   0.600
*SECNO 4564.000

3301 HV CHANGED MORE THAN HVINS

   SECNO     DEPTH     CWSEL     CRIWS     WSELK     EG        HV        HL        OLOSS   BANK ELEV
   Q         QLOB      QCH       QROB      ALOB      ACH       AROB      VOL       TWA   LEFT/RIGHT
   TIME      VLOB      VCH       VROB      XNL       XNCH      XNR       WTN       ELMIN      SSTA
   SLOPE     XLOBL     XLCH      XLOBR     ITRIAL    IDC       ICONT     CORAR     TOPWID     ENDST


7185 MINIMUM SPECIFIC ENERGY
3720 CRITICAL DEPTH ASSUMED

3470 ENCROACHMENT STATIONS=       1.0     185.0  TYPE=     1  TARGET=     184.000

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE.ELLEA=      659.20 ELREA=      659.20

          SECNO 4564 D/S       FRANCAVILLA CULVERT FROM FIELD BOOK AND SUBD. MAP

  4564.00      5.06    656.26    656.26    656.27    658.35      2.08      0.07      0.70    655.20
    380.         0.       380.       0.        0.        33.       0.       10.        5.      655.20
     0.24       0.0      11.59      0.0     0.060     0.020     0.100     0.034    651.20    116.00
0.007506        24.       24.       24.         4         5         0       0.0      8.00    124.00

FLOW DISTRIBUTION FOR SECNO=    4564.00          CWSEL=     656.26

STA=      116.      124.
  PER Q=    100.0
   AREA=     32.8
    VEL=     11.6

CCHV=   0.400 CEHV=   0.600
*SECNO 4565.000
   SECNO     DEPTH     CWSEL     CRIWS     WSELK     EG        HV        HL        OLOSS   BANK ELEV
   Q         QLOB      QCH       QROB      ALOB      ACH       AROB      VOL       TWA   LEFT/RIGHT
   TIME      VLOB      VCH       VROB      XNL       XNCH      XNR       WTN       ELMIN      SSTA
   SLOPE     XLOBL     XLCH      XLOBR     ITRIAL    IDC       ICONT     CORAR     TOPWID     ENDST


3370 NORMAL BRIDGE,NRD= 11 MIN ELTRD=  665.00 MAX ELLC=  659.20

7185 MINIMUM SPECIFIC ENERGY
3720 CRITICAL DEPTH ASSUMED

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE.ELLEA=      659.20 ELREA=      659.20

          SECNO 4565          D/S FACE FRANCAVILLA CULV. FROM F.B." SUBD. MAP

  4565.00      5.06    656.26    656.26    656.26    658.42      2.17      0.01      0.05    655.20
    380.         0.       380.       0.        0.        32.       0.       10.        5.      655.20
     0.24       0.0      11.82      0.0     0.060     0.015     0.100     0.034    651.20    116.00
0.004680         1.        1.        1.         2        17         0     -5.23      0.00    124.00

FLOW DISTRIBUTION FOR SECNO=    4565.00          CWSEL=     656.26

STA=      116.      124.
  PER Q=    100.0
```

AREA= 32.2
VEL= 11.8

*SECNO 4925.000
WATER EL CHANGE FROM X2 CARD

3370 NORMAL BRIDGE,NRD= 11 MIN ELTRD= 665.00 MAX ELLC= 660.63

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 668.30 ELREA= 668.30

SECNO 4925 BASED ON QUAD MAP " SUBD. MAP

4925.00	5.06	657.69	657.69	657.69	659.85	2.16	1.68	0.00	656.63
380.	0.	380.	0.	0.	32.	0.	10.	5.	656.63
0.25	0.0	11.80	0.0	0.060	0.015	0.100	0.032	652.63	116.00
0.004664	360.	360.	360.	0	17	0	-5.28	8.00	126.00

FLOW DISTRIBUTION FOR SECNO= 4925.00 CWSEL= 657.69

STA= 116. 124.
PER Q= 100.0
AREA= 32.2
VEL= 11.8

*SECNO 5280.000
WATER EL CHANGE FROM X2 CARD

3370 NORMAL BRIDGE,NRD= 11 MIN ELTRD= 665.00 MAX ELLC= 662.06

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 668.30 ELREA= 668.30

SECNO 5280 BASED ON QUAD MAP " SUBD. MAP

5280.00	5.06	659.12	659.12	659.12	661.28	2.16	1.66	0.00	658.06
380.	0.	380.	0.	0.	32.	0.	11.	5.	658.06
0.25	0.0	11.80	0.0	0.060	0.015	0.100	0.031	654.06	116.00
0.004665	355.	355.	355.	0	17	0	-5.28	8.00	124.00

FLOW DISTRIBUTION FOR SECNO= 5280.00 CWSEL= 659.12

STA= 116. 124.
PER Q= 100.0
AREA= 32.2
VEL= 11.8

*SECNO 5640.000

3301 HV CHANGED MORE THAN HVINS

3370 NORMAL BRIDGE,NRD= 14 MIN ELTRD= 668.30 MAX ELLC= 663.50

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 668.30 ELREA= 668.30

SECNO 5640 U/S FACE FRANCAVILLA CULVERT AT U/S FACE CURTIS RD.

5640.00	5.79	661.29	0.0	661.29	662.83	1.54	1.29	0.25	659.50
380.	0.	380.	0.	0.	38.	0.	11.	5.	659.5

0.020	0.0	9.95	.0	0.060	0.015	0.1 0	0.030	55.50	99.00
0.002858	360.	360.	360.	3	0	0	-2.68	8.00	107.00

FLOW DISTRIBUTION FOR SECNO= 5640.00 CWSEL= 661.29

STA= 99. 107.
PER Q= 100.0
AREA= 38.2
VEL= 9.9

CCHV= 0.300 CEHV= 0.500
*SECNO 5641.000

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 668.30 ELREA= 668.30

SECNO 5641 U/S FRANCAVILLA CULVERT FROM FIELD BOOK AND SUBD. MAP

5641.00	6.03	661.53	0.0	661.53	662.89	1.36	0.01	0.05	659.50
380.	0.	380.	0.	0.	41.	0.	11.	5.	659.50
0.26	0.0	9.35	0.0	0.060	0.080	0.100	0.030	655.50	99.00
0.064664	1.	1.	1.	3	0	0	0.0	8.00	107.00

FLOW DISTRIBUTION FOR SECNO= 5641.00 CWSEL= 661.53

STA= 99. 107.
PER Q= 100.0
AREA= 40.6
VEL= 9.4

****
HEC2 RELEASE DATED NOV 76 UPDATED AUG1977
ERROR CORR - 01.02
MODIFICATION - 50,51,52,53
****

NOTE- ASTERISK (*) AT LEFT OF CROSS-SECTION NUMBER INDICATES MESSAGE IN SUMMARY OF ERRORS LIST

BEITZ DRAIN LIVONIA CITY

SUMMARY PRINTOUT TABLE 110

SECNO	CWSEL	DIFKWS	EG	TOPWID	QLOB	QCH	QROB	PERENC	STENCL	STCHL	STCHR	STENCR
70.000	639.80	0.0	639.97	56.64	4.77	365.21	10.02	0.0	0.0	89.00	111.00	0.0
70.000	639.90	0.10	640.09	23.49	0.0	378.53	1.47	0.04	89.00	89.00	111.00	112.49
297.000	640.01	0.0	640.26	44.92	1.54	372.71	5.75	0.0	0.0	89.00	111.00	0.0
297.000	640.13	0.12	640.36	46.98	1.99	371.56	6.45	263.00	1.00	89.00	111.00	264.00
524.000	640.39	0.0	640.77	69.97	1.83	363.90	14.26	0.0	0.0	115.00	135.00	0.0
524.000	640.47	0.08	640.83	73.36	2.23	361.81	15.96	0.0	0.0	115.00	135.00	0.0
752.000	641.09	0.0	641.57	58.08	0.73	370.41	8.86	0.0	0.0	115.00	135.00	0.0
752.000	641.12	0.03	641.59	59.23	0.82	369.84	9.34	0.0	0.0	115.00	135.00	0.0
979.000	642.00	0.0	642.47	58.33	0.75	370.29	8.96	0.0	0.0	115.00	135.00	0.0
979.000	642.00	0.00	642.48	58.55	0.77	370.18	9.05	0.0	0.0	115.00	135.00	0.0
1207.000	642.91	0.0	643.42	65.73	14.50	358.85	6.64	0.0	0.0	132.00	150.00	0.0
1207.000	642.91	0.00	643.42	65.64	14.47	358.92	6.61	0.0	0.0	132.00	150.00	0.0
1434.000	643.88	0.0	644.40	64.71	14.20	359.54	6.26	0.0	0.0	132.00	150.00	0.0
1434.000	643.89	0.00	644.40	64.81	14.23	359.47	6.30	0.0	0.0	132.00	150.00	0.0
1661.000	644.87	0.0	645.35	67.91	15.14	357.35	7.50	0.0	0.0	132.00	150.00	0.0
1661.000	644.87	-0.00	645.35	68.01	15.17	357.28	7.55	0.0	0.0	132.00	150.00	0.0
1888.000	645.79	0.0	646.23	88.85	11.02	345.29	23.69	0.0	0.0	148.00	166.00	0.0
1888.000	645.79	-0.00	646.23	88.75	11.00	345.38	23.62	0.0	0.0	148.00	166.00	0.0
2115.000	646.65	0.0	647.15	82.98	9.88	350.33	19.78	0.0	0.0	148.00	166.00	0.0
2115.000	646.65	0.00	647.15	82.86	9.86	350.44	19.70	0.0	0.0	148.00	166.00	0.0
2359.000	647.69	0.0	648.62	26.23	14.85	350.33	14.82	0.0	0.0	133.50	146.50	0.0
2359.000	647.69	0.00	648.62	26.24	14.87	350.30	14.83	0.0	0.0	133.50	146.50	0.0
2409.000	648.01	0.0	649.00	13.00	0.0	380.00	0.0	0.0	0.0	133.50	146.50	0.0
2409.000	648.02	0.00	649.00	13.00	0.0	380.00	0.0	0.0	0.0	133.50	146.50	0.0
2526.000	649.18	0.0	649.65	13.10	0.0	380.00	0.0	0.0	0.0	133.40	146.50	0.0
2526.000	649.18	0.00	649.65	13.10	0.0	380.00	0.0	0.0	0.0	133.40	146.50	0.0

FORM 6415

	SECNO	CWSEL	DIFKWS	EG	TOPWID	QLOB	QCH	QROB	PERENC	SLENCL	SICHL	SICHR	SLENCR
	2576.000	649.53	0.0	649.79	38.41	30.00	326.27	23.73	0.0	0.0	133.40	146.50	0.0
	2576.000	649.53	0.00	649.79	38.41	30.00	326.27	23.73	0.0	0.0	133.40	146.50	0.0
	2824.000	649.82	0.0	650.23	33.84	25.16	334.94	19.90	0.0	0.0	133.40	146.50	0.0
	2824.000	649.82	0.0	650.23	33.84	25.16	334.94	19.90	0.0	0.0	133.40	146.50	0.0
	3072.000	650.46	0.0	650.82	39.29	47.52	293.39	39.10	0.0	0.0	128.00	142.00	0.0
	3072.000	650.46	0.0	650.82	39.29	47.51	293.39	39.09	0.0	0.0	128.00	142.00	0.0
	3321.000	651.18	0.0	651.72	35.98	42.06	303.56	34.39	0.0	0.0	128.00	142.00	0.0
	3321.000	651.17	-0.02	651.79	26.38	34.67	318.52	26.81	0.05	122.36	128.00	142.00	148.72
	3569.000	652.39	0.0	652.97	35.63	41.05	305.41	33.53	0.0	0.0	128.00	142.00	0.0
	3569.000	652.47	0.09	653.11	25.82	33.92	320.15	25.93	0.06	122.56	128.00	142.00	148.38
	3817.000	653.92	0.0	654.53	36.86	0.21	352.02	27.77	0.0	0.0	114.00	137.00	0.0
	3817.000	654.01	0.09	654.71	23.56	0.0	378.52	1.48	0.07	114.00	114.00	137.00	137.56
	4065.000	655.56	0.0	656.01	43.58	1.92	349.32	28.76	0.0	0.0	114.00	137.00	0.0
	4065.000	655.69	0.13	656.10	46.27	3.13	347.73	29.14	208.00	1.00	114.00	137.00	209.00
	4250.000	656.27	0.0	656.49	59.45	14.51	205.00	160.49	0.0	0.0	77.00	85.00	0.0
	4250.000	656.32	0.05	656.53	59.91	14.92	204.01	161.06	0.0	0.0	77.00	85.00	0.0
	4490.000	656.37	0.0	656.97	36.86	60.02	294.22	25.75	0.0	0.0	112.00	120.00	0.0
	4490.000	656.41	0.04	657.00	37.30	60.61	293.38	26.01	0.0	0.0	112.00	120.00	0.0
	4515.000	656.38	0.0	657.00	26.00	58.81	298.45	22.74	26.00	101.00	112.00	120.00	127.00
	4515.000	656.42	0.04	657.03	26.00	59.05	298.16	22.79	26.00	101.00	112.00	120.00	127.00
	4540.000	656.26	0.0	657.19	16.00	42.12	331.37	6.51	16.00	106.00	112.00	120.00	122.00
	4540.000	656.30	0.04	657.22	16.00	42.14	331.37	6.49	16.00	106.00	112.00	120.00	122.00
*	4564.000	656.27	0.0	658.35	8.00	0.0	380.00	0.0	0.0	0.0	116.00	124.00	0.0
*	4564.000	656.26	-0.01	658.35	8.00	0.0	380.00	0.0	184.00	1.00	116.00	124.00	185.00
*	4565.000	656.26	0.0	658.42	8.00	0.0	380.00	0.0	0.0	0.0	116.00	124.00	0.0
*	4565.000	656.26	0.0	658.42	8.00	0.0	380.00	0.0	0.0	0.0	116.00	124.00	0.0
*	4925.000	657.69	0.0	659.85	8.00	0.0	380.00	0.0	0.0	0.0	116.00	124.00	0.0
*	4925.000	657.69	0.0	659.85	8.00	0.0	380.00	0.0	0.0	0.0	116.00	124.00	0.0
*	5280.000	659.12	0.0	661.28	8.00	0.0	380.00	0.0	0.0	0.0	116.00	124.00	0.0
*	5280.000	659.12	0.0	661.28	8.00	0.0	380.00	0.0	0.0	0.0	116.00	124.00	0.0
	5640.000	661.29	0.0	662.83	8.00	0.0	380.00	0.0	0.0	0.0	99.00	107.00	0.0
	5640.000	661.29	0.0	662.83	8.00	0.0	380.00	0.0	0.0	0.0	99.00	107.00	0.0
	5641.000	661.53	0.0	662.89	8.00	0.0	380.00	0.0	0.0	0.0	99.00	107.00	0.0
	5641.000	661.53	0.0	662.89	8.00	0.0	380.00	0.0	0.0	0.0	99.00	107.00	0.0

FORM FG413

BEITZ DRAIN LIVONIA CITY

SUMMARY PRINTOUT TABLE 150

SECNO	XLCH	ELTRD	ELLC	ELMIN	Q	CWSEL	CRIWS	EG	10K*S	VCH	AREA	.01K
70.000	0.0	0.0	0.0	634.10	380.00	639.80	0.0	639.97	8.89	3.41	144.49	127.42
70.000	0.0	0.0	0.0	634.10	380.00	639.90	0.0	640.09	9.87	3.46	113.16	120.93
297.000	227.00	0.0	0.0	635.00	380.00	640.01	0.0	640.26	15.52	4.06	109.03	96.46
297.000	227.00	0.0	0.0	635.00	380.00	640.13	0.0	640.36	14.01	3.93	114.65	101.53
524.000	227.00	0.0	0.0	635.90	380.00	640.39	0.0	640.77	29.04	5.05	104.01	70.51
524.000	227.00	0.0	0.0	635.90	380.00	640.47	0.0	640.83	26.59	4.91	110.03	73.70
752.000	228.00	0.0	0.0	636.90	380.00	641.09	0.0	641.57	40.00	5.60	85.14	60.08
752.000	228.00	0.0	0.0	636.90	380.00	641.12	0.0	641.59	38.76	5.55	86.81	61.04
979.000	227.00	0.0	0.0	637.80	380.00	642.00	0.0	642.47	39.73	5.59	85.51	60.29
979.000	227.00	0.0	0.0	637.80	380.00	642.00	0.0	642.48	39.49	5.58	85.82	60.47
1207.000	228.00	0.0	0.0	638.60	380.00	642.91	0.0	643.42	42.49	5.87	91.99	58.30
1207.000	228.00	0.0	0.0	638.60	380.00	642.91	0.0	643.42	42.60	5.88	91.84	58.22
1434.000	227.00	0.0	0.0	639.60	380.00	643.88	0.0	644.40	43.71	5.93	90.37	57.48
1434.000	227.00	0.0	0.0	639.60	380.00	643.89	0.0	644.40	43.59	5.92	90.52	57.56
1661.000	227.00	0.0	0.0	640.50	380.00	644.87	0.0	645.35	40.00	5.76	95.54	60.08
1661.000	227.00	0.0	0.0	640.50	380.00	644.87	0.0	645.35	39.89	5.75	95.71	60.16
1888.000	227.00	0.0	0.0	641.30	380.00	645.79	0.0	646.23	36.85	5.57	115.79	62.60
1888.000	227.00	0.0	0.0	641.30	380.00	645.79	0.0	646.23	36.95	5.57	115.59	62.52
2115.000	227.00	0.0	0.0	642.30	380.00	646.65	0.0	647.15	43.03	5.87	104.79	57.93
2115.000	227.00	0.0	0.0	642.30	380.00	646.65	0.0	647.15	43.17	5.87	104.57	57.83
2359.000	244.00	0.0	0.0	644.30	380.00	647.69	0.0	648.62	72.65	8.08	65.10	44.58
2359.000	244.00	0.0	0.0	644.30	380.00	647.69	0.0	648.62	72.40	8.07	65.18	44.66
2409.000	50.00	0.0	0.0	644.30	380.00	648.01	0.0	649.00	68.94	7.98	47.63	45.77
2409.000	50.00	0.0	0.0	644.30	380.00	648.02	0.0	649.00	68.84	7.98	47.65	45.80
2526.000	117.00	660.00	650.80	643.80	380.00	649.18	0.0	649.65	27.94	5.47	69.51	71.90
2526.000	117.00	660.00	650.80	643.80	380.00	649.18	0.0	649.65	27.93	5.47	69.51	71.90
2576.000	50.00	0.0	0.0	643.80	380.00	649.53	0.0	649.79	10.51	4.38	145.73	117.21
2576.000	50.00	0.0	0.0	643.80	380.00	649.53	0.0	649.79	10.51	4.38	145.74	117.22
2824.000	248.00	0.0	0.0	645.10	380.00	649.82	0.0	650.23	21.38	5.48	108.98	82.18
2824.000	248.00	0.0	0.0	645.10	380.00	649.82	0.0	650.23	21.38	5.48	108.99	82.18
3072.000	248.00	0.0	0.0	646.40	380.00	650.46	0.0	650.82	25.96	5.36	105.75	74.58
3072.000	248.00	0.0	0.0	646.40	380.00	650.46	0.0	650.82	25.97	5.36	105.74	74.57
3321.000	249.00	0.0	0.0	647.70	380.00	651.18	0.0	651.72	47.16	6.59	84.17	55.33
3321.000	249.00	0.0	0.0	647.70	380.00	651.17	0.0	651.79	52.07	6.86	75.74	52.26
3569.000	248.00	0.0	0.0	649.00	380.00	652.39	0.0	652.97	52.61	6.74	80.76	52.39
3569.000	248.00	0.0	0.0	649.00	380.00	652.47	0.0	653.11	52.99	6.88	75.03	52.20

	SECNO	XLCH	ELTRD	ELLC	ELMIN	Q	CWSEL	CRIWS	EG	10KWS	VCH	AREA	.01K
	3817.000	248.00	0.0	0.0	650.30	380.00	653.92	0.0	654.53	75.34	6.47	70.99	43.78
	3817.000	248.00	0.0	0.0	650.30	380.00	654.01	0.0	654.71	78.59	6.70	58.29	42.86
	4065.000	248.00	0.0	0.0	651.60	380.00	655.56	0.0	656.01	47.84	5.63	84.37	54.94
	4065.000	248.00	0.0	0.0	651.60	380.00	655.69	0.0	656.10	40.37	5.34	90.35	58.81
	4250.000	185.00	0.0	0.0	651.00	380.00	656.27	0.0	656.69	14.75	4.91	180.39	98.95
	4250.000	185.00	0.0	0.0	651.00	380.00	656.32	0.0	656.53	14.14	4.84	183.45	101.06
	4490.000	240.00	0.0	0.0	651.10	380.00	656.37	0.0	656.97	9.92	7.04	112.92	120.62
	4490.000	240.00	0.0	0.0	651.10	380.00	656.41	0.0	657.00	9.61	6.97	114.48	122.61
	4515.000	25.00	0.0	0.0	651.10	380.00	656.38	0.0	657.00	10.10	7.12	104.62	119.56
	4515.000	25.00	0.0	0.0	651.10	380.00	656.42	0.0	657.03	9.82	7.06	105.71	121.28
	4540.000	25.00	0.0	0.0	651.20	380.00	656.26	0.0	657.19	14.48	8.27	72.93	99.85
	4540.000	25.00	0.0	0.0	651.20	380.00	656.30	0.0	657.22	14.08	8.20	73.61	101.28
*	4564.000	24.00	0.0	0.0	651.20	380.00	656.27	656.27	658.35	74.55	11.56	32.87	44.01
*	4564.000	24.00	0.0	0.0	651.20	380.00	656.26	656.26	658.35	75.06	11.59	32.79	43.86
*	4565.000	1.00	665.00	659.20	651.20	380.00	656.26	656.26	658.42	46.80	11.82	32.16	55.55
*	4565.000	1.00	665.00	659.20	651.20	380.00	656.26	656.26	658.42	46.80	11.82	32.16	55.55
*	4925.000	360.00	665.00	660.63	652.63	380.00	657.69	657.69	659.85	46.64	11.80	32.20	55.64
*	4925.000	360.00	665.00	660.63	652.63	380.00	657.69	657.69	659.85	46.64	11.80	32.20	55.64
*	5280.000	355.00	665.00	662.06	654.06	380.00	659.12	659.12	661.28	46.65	11.80	32.20	55.64
*	5280.000	355.00	665.00	662.06	654.06	380.00	659.12	659.12	661.28	46.65	11.80	32.20	55.64
	5640.000	360.00	668.30	663.50	655.50	380.00	661.29	0.0	662.83	28.58	9.95	38.19	71.08
	5640.000	360.00	668.30	663.50	655.50	380.00	661.29	0.0	662.83	28.58	9.95	38.19	71.08
	5641.000	1.00	0.0	0.0	655.50	380.00	661.53	0.0	662.89	646.64	9.35	40.62	14.94
	5641.000	1.00	0.0	0.0	655.50	380.00	661.53	0.0	662.89	646.64	9.35	40.62	14.94

BEITZ DRAIN LIVONIA CITY

SUMMARY PRINTOUT TABLE 150

SECNO	Q	CWSEL	DIFWSP	DIFWSX	DIFKWS	TOPWID	XLCH
70.000	380.00	639.80	0.0	0.0	0.0	56.64	0.0
70.000	380.00	639.90	0.10	0.0	0.10	23.49	0.0
297.000	380.00	640.01	0.0	0.21	0.0	44.92	227.00
297.000	380.00	640.13	0.12	0.23	0.12	46.98	227.00
524.000	380.00	640.39	0.0	0.38	0.0	69.97	227.00
524.000	380.00	640.47	0.08	0.34	0.08	73.36	227.00
752.000	380.00	641.09	0.0	0.71	0.0	58.08	228.00
752.000	380.00	641.12	0.03	0.65	0.03	59.23	228.00
979.000	380.00	642.00	0.0	0.91	0.0	58.33	227.00
979.000	380.00	642.00	0.00	0.88	0.00	58.55	227.00
1207.000	380.00	642.91	0.0	0.91	0.0	65.73	228.00
1207.000	380.00	642.91	0.00	0.91	0.00	65.64	228.00
1434.000	380.00	643.88	0.0	0.97	0.0	64.71	227.00
1434.000	380.00	643.89	0.00	0.97	0.00	64.81	227.00
1661.000	380.00	644.87	0.0	0.98	0.0	67.91	227.00
1661.000	380.00	644.87	-0.00	0.98	-0.00	68.01	227.00
1888.000	380.00	645.79	0.0	0.92	0.0	88.85	227.00
1888.000	380.00	645.79	-0.00	0.92	-0.00	88.75	227.00
2115.000	380.00	646.65	0.0	0.86	0.0	82.98	227.00
2115.000	380.00	646.65	0.00	0.87	0.00	82.86	227.00
2359.000	380.00	647.69	0.0	1.03	0.0	26.23	244.00
2359.000	380.00	647.69	0.00	1.04	0.00	26.24	244.00
2409.000	380.00	648.01	0.0	0.33	0.0	13.00	50.00
2409.000	380.00	648.02	0.00	0.33	0.00	13.00	50.00
2526.000	380.00	649.18	0.0	1.17	0.0	13.10	117.00
2526.000	380.00	649.18	0.00	1.17	0.00	13.10	117.00
2576.000	380.00	649.53	0.0	0.35	0.0	38.41	50.00
2576.000	380.00	649.53	0.00	0.35	0.00	38.41	50.00
2824.000	380.00	649.82	0.0	0.28	0.0	33.84	248.00
2824.000	380.00	649.82	0.0	0.28	0.0	33.84	248.00
3072.000	380.00	650.46	0.0	0.64	0.0	39.29	248.00
3072.000	380.00	650.46	0.0	0.64	0.0	39.29	248.00
3321.000	380.00	651.18	0.0	0.72	0.0	35.98	249.00
3321.000	380.00	651.17	-0.02	0.71	-0.02	26.38	249.00
3569.000	380.00	652.39	0.0	1.20	0.0	35.43	248.00
3569.000	380.00	652.47	0.09	1.31	0.09	25.02	248.00

	SECNO	Q	CWSEL	DIFWSP	DIFWSX	DIFKWS	TOPWID	XLCH
	3817.000	380.00	653.92	0.0	1.53	0.0	36.86	248.00
	3817.000	380.00	654.01	0.09	1.54	0.09	23.56	248.00
	4065.000	380.00	655.56	0.0	1.64	0.0	43.58	248.00
	4065.000	380.00	655.69	0.13	1.67	0.13	46.27	248.00
	4250.000	380.00	656.27	0.0	0.72	0.0	59.45	185.00
	4250.000	380.00	656.32	0.05	0.63	0.05	59.91	185.00
	4490.000	380.00	656.37	0.0	0.09	0.0	36.86	240.00
	4490.000	380.00	656.41	0.04	0.09	0.04	37.30	240.00
	4515.000	380.00	656.38	0.0	0.01	0.0	26.00	25.00
	4515.000	380.00	656.42	0.04	0.01	0.04	26.00	25.00
	4540.000	380.00	656.26	0.0	-0.12	0.0	16.00	25.00
	4540.000	380.00	656.30	0.04	-0.12	0.04	16.00	25.00
*	4564.000	380.00	656.27	0.0	0.02	0.0	8.00	24.00
*	4564.000	380.00	656.26	-0.01	-0.04	-0.01	8.00	24.00
*	4565.000	380.00	656.26	0.0	-0.02	0.0	8.00	1.00
*	4565.000	380.00	656.26	0.0	-0.01	0.0	8.00	1.00
*	4925.000	380.00	657.69	0.0	1.43	0.0	8.00	360.00
*	4925.000	380.00	657.69	0.0	1.43	0.0	8.00	360.00
*	5280.000	380.00	659.12	0.0	1.43	0.0	8.00	355.00
*	5280.000	380.00	659.12	0.0	1.43	0.0	8.00	355.00
	5640.000	380.00	661.29	0.0	2.17	0.0	8.00	360.00
	5640.000	380.00	661.29	0.0	2.17	0.0	8.00	360.00
	5641.000	380.00	661.53	0.0	0.24	0.0	8.00	1.00
	5641.000	380.00	661.53	0.0	0.24	0.0	8.00	1.00

SUMMARY OF ERRORS

CAUTION SECNO= 4564.000 PROFILE= 1 CRITICAL DEPTH ASSUMED
CAUTION SECNO= 4564.000 PROFILE= 1 MINIMUM SPECIFIC ENERGY
CAUTION SECNO= 4564.000 PROFILE= 2 CRITICAL DEPTH ASSUMED
CAUTION SECNO= 4564.000 PROFILE= 2 MINIMUM SPECIFIC ENERGY

CAUTION SECNO= 4565.000 PROFILE= 1 CRITICAL DEPTH ASSUMED
CAUTION SECNO= 4565.000 PROFILE= 1 MINIMUM SPECIFIC ENERGY
CAUTION SECNO= 4565.000 PROFILE= 2 CRITICAL DEPTH ASSUMED
CAUTION SECNO= 4565.000 PROFILE= 2 MINIMUM SPECIFIC ENERGY

NOTE SECNO= 4925.000 PROFILE= 1 WSEL BASED ON X2 CARD
NOTE SECNO= 4925.000 PROFILE= 2 WSEL BASED ON X2 CARD

NOTE SECNO= 5280.000 PROFILE= 1 WSEL BASED ON X2 CARD
NOTE SECNO= 5280.000 PROFILE= 2 WSEL BASED ON X2 CARD

FLOODWAY DATA, BEITZ DRAIN LIVONIA CITY
PROFILE NO. 2

STATION	FLOODWAY WIDTH (FT)	FLOODWAY SECTION AREA	FLOODWAY MEAN VELOCITY	WATER SURFACE ELEVATION WITH FLOODWAY	WITHOUT FLOODWAY	DIFFERENCE
70.000	23.	113.	3.4	639.9	639.8	0.1
297.000	47.	115.	3.3	640.1	640.0	0.1
524.000	73.	110.	3.5	640.5	640.4	0.1
752.000	59.	87.	4.4	641.1	641.1	0.0
979.000	59.	86.	4.4	642.0	642.0	0.0
1207.000	66.	92.	4.1	642.9	642.9	0.0
1434.000	65.	91.	4.2	643.9	643.9	0.0
1661.000	68.	96.	4.0	644.9	644.9	0.0
1888.000	89.	116.	3.3	645.8	645.8	0.0
2115.000	83.	105.	3.6	646.7	646.7	0.0
2359.000	26.	65.	5.8	647.7	647.7	0.0
2409.000	13.	48.	8.0	648.0	648.0	0.0
2526.000	13.	70.	5.5	649.2	649.2	0.0
2576.000	38.	146.	2.6	649.5	649.5	0.0
2824.000	34.	109.	3.5	649.8	649.8	0.0
3072.000	39.	106.	3.6	650.5	650.5	0.0
3321.000	26.	76.	5.0	651.2	651.2	0.0
3569.000	26.	75.	5.1	652.5	652.4	0.1
3817.000	24.	58.	6.5	654.0	653.9	0.1
4065.000	46.	90.	4.2	655.7	655.6	0.1
4250.000	60.	183.	2.1	656.4	656.3	0.1
4490.000	37.	114.	3.3	656.4	656.4	0.0
4515.000	26.	106.	3.6	656.4	656.4	0.0
4540.000	16.	74.	5.2	656.3	656.3	0.0
4564.000	8.	33.	11.6	656.3	656.3	0.0
4565.000	8.	32.	11.8	656.3	656.3	0.0
4925.000	8.	32.	11.8	657.7	657.7	0.0
5280.000	8.	32.	11.8	659.1	659.1	0.0
5640.000	8.	38.	9.9	661.3	661.3	0.0
5641.000	8.	41.	9.4	661.5	661.5	0.0



1) COUNTY: Wayne

2) STUDY NAME: City of Livonia

3) WATERCOURSE: Beitz Drain

4) DOCUMENT TYPE: Summary



HEC2 RELEASE DATED NOV 76 UPDATED AUG1977
ERROR CORR - 01,02
MODIFICATION - 50,51,52,53

NOTE- ASTERISK (*) AT LEFT OF CROSS-SECTION NUMBER INDICATES MESSAGE IN SUMMARY OF ERRORS LIST

BEITZ DRAIN LIVONIA CITY

SUMMARY PRINTOUT TABLE 150

SECNO	XLCH	ELTRD	ELLC	ELMIN	Q	CWSEL	CRIWS	EG	10K*S	VCH	AREA	.01K
70.000	0.0	0.0	0.0	634.10	180.00	639.80	0.0	639.84	2.00	1.62	144.49	127.42
70.000	0.0	0.0	0.0	634.10	310.00	639.80	0.0	639.92	5.92	2.78	144.49	127.42
70.000	0.0	0.0	0.0	634.10	360.00	639.80	0.0	639.97	8.69	3.41	144.49	127.42
70.000	0.0	0.0	0.0	634.10	560.00	639.80	0.0	640.18	19.32	5.03	144.49	127.42
297.000	227.00	0.0	0.0	635.00	180.00	639.65	0.0	639.81	3.93	2.01	102.20	90.17
297.000	227.00	0.0	0.0	635.00	310.00	639.94	0.0	640.11	10.94	3.37	106.04	93.72
297.000	227.00	0.0	0.0	635.00	380.00	640.01	0.0	640.26	15.52	4.06	109.03	96.46
297.000	227.00	0.0	0.0	635.00	560.00	640.29	0.0	640.73	27.59	5.62	120.37	106.62
524.000	227.00	0.0	0.0	635.90	180.00	639.54	0.0	640.06	10.62	2.20	70.96	65.24
524.000	227.00	0.0	0.0	635.90	310.00	640.21	0.0	640.58	23.48	4.39	92.01	83.97
524.000	227.00	0.0	0.0	635.90	380.00	640.39	0.0	640.77	29.04	5.05	104.01	70.51
524.000	227.00	0.0	0.0	635.90	560.00	640.91	0.0	641.07	36.07	6.24	146.51	92.22
752.000	228.00	0.0	0.0	636.90	180.00	640.24	0.0	640.44	24.84	3.67	49.82	36.12
752.000	228.00	0.0	0.0	636.90	310.00	640.80	0.0	641.19	37.30	5.68	69.79	60.76
752.000	228.00	0.0	0.0	636.90	380.00	641.09	0.0	641.57	40.00	5.60	85.14	60.08
752.000	228.00	0.0	0.0	636.90	560.00	641.77	0.0	642.39	42.46	6.54	133.90	85.94
979.000	227.00	0.0	0.0	637.80	180.00	640.86	0.0	641.13	35.17	4.12	43.74	30.35
979.000	227.00	0.0	0.0	637.80	310.00	641.66	0.0	642.07	39.20	5.16	67.80	49.51
979.000	227.00	0.0	0.0	637.80	380.00	642.00	0.0	642.47	39.73	5.59	85.51	60.29
979.000	227.00	0.0	0.0	637.80	560.00	642.74	0.0	643.33	39.63	6.40	139.49	88.76
1207.000	228.00	0.0	0.0	638.60	180.00	641.71	0.0	642.03	43.31	4.53	41.29	27.35
1207.000	228.00	0.0	0.0	638.60	310.00	642.66	0.0	643.01	42.56	5.47	71.56	47.52
1207.000	228.00	0.0	0.0	638.60	380.00	642.91	0.0	643.42	42.49	5.87	91.99	58.30
1207.000	228.00	0.0	0.0	638.60	560.00	643.65	0.0	644.26	41.49	6.62	152.36	86.94
1434.000	227.00	0.0	0.0	639.60	180.00	642.70	0.0	643.02	44.00	4.55	40.99	27.14
1434.000	227.00	0.0	0.0	639.60	310.00	643.53	0.0	643.99	43.91	5.52	70.25	46.76
1434.000	227.00	0.0	0.0	639.60	380.00	643.88	0.0	644.40	43.71	5.93	90.37	57.46
1434.000	227.00	0.0	0.0	639.60	560.00	644.60	0.0	645.23	43.71	6.74	147.47	84.70
1661.000	227.00	0.0	0.0	640.50	180.00	643.67	0.0	643.97	39.50	4.39	43.07	30.64
1661.000	227.00	0.0	0.0	640.50	310.00	644.52	0.0	644.94	39.80	5.35	74.49	49.14
1661.000	227.00	0.0	0.0	640.50	380.00	644.87	0.0	645.35	40.00	5.76	96.54	60.08
1661.000	227.00	0.0	0.0	640.50	560.00	645.60	0.0	646.18	39.67	6.52	156.66	88.91

SECNO	XLCH	ELTRD	ELLC	ELMIN	Q	CWSEL	CRIWS	FG	10K*S	VCH	AREA	.01K
1888.000	227.00	0.0	0.0	641.30	180.00	644.59	0.0	644.89	41.76	4.45	42.13	27.86
1888.000	227.00	0.0	0.0	641.30	310.00	645.43	0.0	645.84	38.51	5.28	86.45	49.96
1888.000	227.00	0.0	0.0	641.30	380.00	645.79	0.0	646.23	36.85	5.57	115.79	62.60
1888.000	227.00	0.0	0.0	641.30	560.00	646.54	0.0	647.02	34.00	6.11	195.90	95.92
2115.000	227.00	0.0	0.0	642.30	180.00	645.55	0.0	645.87	44.00	4.52	41.01	27.13
2115.000	227.00	0.0	0.0	642.30	310.00	646.33	0.0	646.78	43.97	5.52	79.28	46.75
2115.000	227.00	0.0	0.0	642.30	380.00	646.69	0.0	647.15	43.03	5.87	104.79	67.93
2115.000	227.00	0.0	0.0	642.30	560.00	647.34	0.0	647.91	42.04	6.61	171.37	85.76
2359.000	244.00	0.0	0.0	644.30	180.00	646.67	0.0	647.14	57.48	5.64	40.54	23.75
2359.000	244.00	0.0	0.0	644.30	310.00	647.41	0.0	648.17	65.17	7.23	58.07	38.40
2359.000	244.00	0.0	0.0	644.30	380.00	647.69	0.0	648.62	72.65	8.08	65.10	44.58
2359.000	244.00	0.0	0.0	644.30	560.00	648.21	648.62	649.67	94.84	10.17	79.31	67.50
2409.000	50.00	0.0	0.0	644.30	180.00	646.97	0.0	647.40	45.28	5.29	34.05	26.75
2409.000	50.00	0.0	0.0	644.30	310.00	647.71	0.0	648.49	60.24	7.09	43.71	39.94
2409.000	50.00	0.0	0.0	644.30	380.00	648.01	0.0	649.00	68.94	7.98	47.63	45.77
2409.000	50.00	0.0	0.0	644.30	560.00	648.62	0.0	650.20	92.85	10.10	55.46	68.12
2526.000	117.00	660.00	650.80	643.80	180.00	647.58	0.0	647.79	18.27	3.70	48.61	42.11
2526.000	117.00	660.00	650.80	643.80	310.00	648.67	0.0	649.05	25.04	4.93	62.85	61.95
2526.000	117.00	660.00	650.80	643.80	380.00	649.18	0.0	649.65	27.94	5.47	69.51	71.90
2526.000	117.00	660.00	650.80	643.80	560.00	650.42	0.0	651.08	33.06	6.54	85.69	97.39
2576.000	50.00	0.0	0.0	643.80	180.00	647.73	0.0	647.87	9.21	3.18	83.90	69.30
2576.000	50.00	0.0	0.0	643.80	310.00	648.95	0.0	649.17	10.36	4.05	124.03	40.34
2576.000	50.00	0.0	0.0	643.80	380.00	649.53	0.0	649.79	10.51	4.38	145.73	117.21
2576.000	50.00	0.0	0.0	643.80	560.00	650.96	0.0	651.27	9.42	4.92	212.44	178.74
2824.000	248.00	0.0	0.0	645.10	180.00	648.02	0.0	648.30	26.60	4.42	55.53	34.90
2824.000	248.00	0.0	0.0	645.10	310.00	649.24	0.0	649.61	22.78	5.18	90.21	64.96
2824.000	248.00	0.0	0.0	645.10	380.00	649.82	0.0	650.23	21.38	5.48	108.98	82.16
2824.000	248.00	0.0	0.0	645.10	560.00	651.20	0.0	651.64	18.12	6.00	160.32	131.55
3072.000	248.00	0.0	0.0	646.40	180.00	648.83	0.0	649.15	43.83	4.87	49.48	27.19
3072.000	248.00	0.0	0.0	646.40	310.00	649.91	0.0	650.27	30.55	5.26	84.94	56.00
3072.000	248.00	0.0	0.0	646.40	380.00	650.46	0.0	650.82	25.96	5.36	105.75	74.50
3072.000	248.00	0.0	0.0	646.40	560.00	651.79	0.0	652.14	18.50	5.51	163.22	130.20
3321.000	249.00	0.0	0.0	647.70	180.00	650.00	0.0	650.38	54.41	5.22	45.70	24.40
3321.000	249.00	0.0	0.0	647.70	310.00	650.78	0.0	651.28	51.04	6.21	70.06	43.39
3321.000	249.00	0.0	0.0	647.70	380.00	651.16	0.0	651.72	47.16	6.60	84.17	55.33
3321.000	249.00	0.0	0.0	647.70	560.00	652.26	0.0	652.83	35.53	6.81	126.43	93.95
3569.000	248.00	0.0	0.0	649.00	180.00	651.33	0.0	651.70	51.74	5.13	46.56	25.02
3569.000	248.00	0.0	0.0	649.00	310.00	652.05	0.0	652.57	52.64	6.27	69.25	42.73
3569.000	248.00	0.0	0.0	649.00	380.00	652.39	0.0	652.97	52.61	6.74	80.76	52.39
3569.000	248.00	0.0	0.0	649.00	560.00	653.19	0.0	653.90	49.37	7.57	111.31	76.76
3817.000	248.00	0.0	0.0	650.30	180.00	652.87	0.0	653.29	80.36	5.33	39.27	20.08
3817.000	248.00	0.0	0.0	650.30	310.00	653.61	0.0	654.15	76.42	6.09	60.56	35.01
3817.000	248.00	0.0	0.0	650.30	380.00	653.92	0.0	654.53	75.34	6.47	70.99	43.78
3817.000	248.00	0.0	0.0	650.30	560.00	654.59	0.0	655.34	66.16	7.27	100.32	67.83

	SECNO	XLCH	ELTRD	ELLC	ELMIN	Q	CWSEL	CRINS	EG	10K*S	VCH	AREA	.01K
	4065.000	248.00	0.0	0.0	651.60	160.00	654.52	0.0	654.80	46.89	4.37	48.43	26.29
	4065.000	248.00	0.0	0.0	651.60	310.00	655.27	0.0	655.66	67.36	5.19	72.47	45.04
	4065.000	248.00	0.0	0.0	651.60	380.00	655.56	0.0	656.01	87.84	5.63	84.37	54.96
	4065.000	248.00	0.0	0.0	651.60	560.00	656.18	0.0	656.78	48.96	6.55	115.64	00.03
	4250.000	185.00	0.0	0.0	651.00	160.00	655.05	0.0	655.17	10.62	3.49	114.33	55.77
	4250.000	185.00	0.0	0.0	651.00	310.00	655.52	0.0	655.10	13.32	4.45	159.74	84.94
	4250.000	185.00	0.0	0.0	651.00	380.00	656.27	0.0	656.49	14.75	4.91	180.39	98.95
	4250.000	185.00	0.0	0.0	651.00	560.00	657.03	0.0	657.32	17.75	5.89	228.27	132.94
	4490.000	240.00	0.0	0.0	651.10	160.00	655.16	0.0	655.44	8.04	4.61	73.81	73.25
	4490.000	240.00	0.0	0.0	651.10	310.00	656.02	0.0	656.51	8.71	6.30	100.62	105.04
	4490.000	240.00	0.0	0.0	651.10	380.00	656.37	0.0	656.97	9.92	7.04	112.92	120.82
	4490.000	240.00	0.0	0.0	651.10	560.00	657.10	0.0	657.97	12.65	8.88	142.87	157.46
	4515.000	25.00	0.0	0.0	651.10	160.00	655.19	0.0	655.45	5.88	4.56	73.31	74.24
	4515.000	25.00	0.0	0.0	651.10	310.00	656.04	0.0	656.53	8.58	6.27	95.68	105.82
	4515.000	25.00	0.0	0.0	651.10	380.00	656.38	0.0	657.00	10.10	7.12	104.62	119.56
	4515.000	25.00	0.0	0.0	651.10	560.00	657.05	0.0	657.68	14.34	9.19	121.95	147.86
	4540.000	25.00	0.0	0.0	651.20	160.00	655.16	0.0	655.51	7.43	5.03	55.45	66.04
	4540.000	25.00	0.0	0.0	651.20	310.00	655.96	0.0	656.66	11.81	7.17	68.21	90.21
	4540.000	25.00	0.0	0.0	651.20	380.00	656.26	0.0	657.19	14.48	8.27	72.93	99.85
	4540.000	25.00	0.0	0.0	651.20	560.00	656.79	0.0	657.44	22.45	11.02	81.47	118.20
	4564.000	24.00	0.0	0.0	651.20	180.00	654.93	0.0	655.95	52.49	8.11	22.18	24.84
o	4564.000	24.00	0.0	0.0	651.20	310.00	655.77	655.77	657.53	75.17	10.76	29.61	36.24
o	4564.000	24.00	0.0	0.0	651.20	380.00	656.27	656.27	656.35	74.55	11.56	32.67	44.01
o	4564.000	24.00	0.0	0.0	651.20	560.00	657.49	657.49	658.17	78.37	13.14	42.62	69.08
	4565.000	1.00	665.00	659.20	651.20	160.00	654.93	0.0	655.87	30.42	8.19	21.90	32.68
o	4565.000	1.00	665.00	659.20	651.20	310.00	655.75	655.75	657.02	43.72	10.96	28.28	46.89
o	4565.000	1.00	665.00	659.20	651.20	380.00	656.26	656.26	656.42	46.80	11.82	32.16	55.55
	4565.000	1.00	665.00	659.20	651.20	560.00	657.37	657.27	660.36	59.57	13.92	40.22	72.60
o	4525.000	360.00	665.00	660.63	652.63	180.00	656.07	656.06	657.36	41.05	9.14	19.68	28.09
o	4525.000	360.00	665.00	660.63	652.63	310.00	657.19	657.18	659.45	43.56	10.95	28.32	46.97
o	4525.000	360.00	665.00	660.63	652.63	380.00	657.69	657.69	659.35	48.64	11.80	32.20	55.64
o	4525.000	360.00	665.00	660.63	652.63	560.00	658.71	658.70	661.61	61.53	14.12	39.67	71.16
o	5280.000	355.00	665.00	662.06	654.06	180.00	657.50	657.49	658.79	41.05	9.14	19.68	28.09
o	5280.000	355.00	665.00	662.06	654.06	310.00	658.62	658.61	660.46	43.56	10.95	28.32	46.97
o	5280.000	355.00	665.00	662.06	654.06	380.00	659.12	659.12	661.28	46.65	11.80	32.20	55.64
o	5280.000	355.00	665.00	662.06	654.06	560.00	660.14	660.13	663.23	61.90	14.11	39.66	71.18
	5640.000	360.00	668.30	663.50	655.50	180.00	659.06	0.0	660.21	34.64	8.60	20.92	30.58
	5640.000	360.00	668.30	663.50	655.50	310.00	660.56	0.0	661.99	39.80	9.46	32.78	50.96
	5640.000	360.00	668.30	663.50	655.50	380.00	661.29	0.0	662.43	28.58	9.95	38.19	71.08
	5640.000	360.00	668.30	663.50	655.50	560.00	663.69	0.0	665.72	53.15	11.43	49.01	71.79
	5641.000	1.00	0.0	0.0	655.50	180.00	659.07	0.0	660.22	945.91	8.61	20.92	6.73
	5641.000	1.00	0.0	0.0	655.50	310.00	660.70	0.0	661.98	716.56	9.10	34.06	11.58
	5641.000	1.00	0.0	0.0	655.50	380.00	661.54	0.0	662.19	868.86	9.35	40.62	14.94
	5641.000	1.00	0.0	0.0	655.50	560.00	664.98	0.0	665.03	330.93	6.21	68.23	30.78

BEITZ DRAIN LIVONIA CITY

SUMMARY PRINTOUT TABLE 150

SECTO	Q	CHSEL	DIFOSP	DIFOSX	DIFRUS	TOPWID	ALCH
70.000	180.00	639.80	0.0	0.0	0.0	56.64	0.0
70.000	310.00	639.80	0.0	0.0	0.0	56.64	0.0
70.000	380.00	639.80	0.0	0.0	0.0	56.64	0.0
70.000	560.00	639.80	0.0	0.0	0.0	56.64	0.0
297.000	180.00	639.85	0.0	0.05	0.0	42.30	227.00
297.000	310.00	639.94	0.09	0.14	0.0	43.79	227.00
297.000	380.00	640.01	0.07	0.21	0.0	44.92	227.00
297.000	560.00	640.25	0.24	0.45	0.0	48.98	227.00
524.000	180.00	639.94	0.0	0.10	0.0	52.09	227.00
524.000	310.00	640.21	0.26	0.27	0.0	62.67	227.00
524.000	380.00	640.39	0.18	0.38	0.0	69.97	227.00
524.000	560.00	640.91	0.53	0.67	0.0	91.23	227.00
752.000	180.00	640.24	0.0	0.29	0.0	26.33	228.00
752.000	310.00	640.80	0.56	0.59	0.0	46.21	228.00
752.000	380.00	641.09	0.29	0.71	0.0	58.83	228.00
752.000	560.00	641.77	0.68	0.86	0.0	85.48	228.00
979.000	180.00	640.86	0.0	0.63	0.0	19.17	227.00
979.000	310.00	641.66	0.79	0.86	0.0	44.52	227.00
979.000	380.00	642.00	0.34	0.91	0.0	58.33	227.00
979.000	560.00	642.74	0.74	0.9[illegible]	0.0	88.[illegible]	227.00
1207.000	180.00	641.71	0.0	0.85	0.0	26.04	228.00
1207.000	310.00	642.56	0.85	0.90	0.0	51.47	228.00
1207.000	380.00	642.91	0.35	0.91	0.0	65.73	228.00
1207.000	560.00	643.65	0.74	0.92	0.0	96.22	228.00
1434.000	180.00	642.70	0.0	0.99	0.0	25.94	227.00
1434.000	310.00	643.53	0.83	0.97	0.0	50.42	227.00
1434.000	380.00	643.88	0.35	0.97	0.0	64.71	227.00
1434.000	560.00	644.60	0.72	0.95	0.0	94.12	227.00
1661.000	180.00	643.67	0.0	0.97	0.0	26.63	227.00
1661.000	310.00	644.52	0.84	0.98	0.0	53.75	227.00
1661.000	380.00	644.87	0.35	0.95	0.0	67.91	227.00
1661.000	560.00	645.60	0.73	1.00	0.0	98.03	227.00
1888.000	180.00	644.59	0.0	0.92	0.0	33.60	227.00
1888.000	310.00	645.43	0.84	0.91	0.0	72.11	227.00
1888.000	380.00	645.79	0.36	0.92	0.0	88.85	227.00
1888.000	560.00	646.54	0.75	0.94	0.0	123.85	227.00
2115.000	180.00	645.55	0.0	0.97	0.0	32.03	227.00
2115.000	310.00	646.33	0.78	0.90	0.0	67.39	227.00
2115.000	380.00	646.65	0.32	0.86	0.0	82.98	227.00
2115.000	560.00	647.34	0.68	0.79	0.0	114.22	227.00
2359.000	180.00	646.67	0.0	1.12	0.0	22.14	244.00
2359.000	310.00	647.41	0.74	1.06	0.0	25.13	244.00
2359.000	380.00	647.69	0.27	1.03	0.0	26.23	244.00
2359.000	[illegible].00	[illegible].21	0.5[illegible]	0.87	0.0	2[illegible].32	[illegible]

SECNO	θ	CWSEL	DIFWSP	DIFWSX	DIFKWS	TOPWID	XLCH
2409.000	180.00	646.97	0.0	0.30	0.0	13.00	50.00
2409.000	310.00	647.71	0.74	0.30	0.0	13.00	50.00
2409.000	380.00	648.01	0.30	0.33	0.0	13.00	50.00
2409.000	560.00	648.62	0.60	0.41	0.0	13.00	50.00
2526.000	180.00	647.58	0.0	0.61	0.0	13.10	117.00
2526.000	310.00	648.67	1.09	0.96	0.0	13.10	117.00
2526.000	380.00	649.18	0.51	1.17	0.0	13.10	117.00
2526.000	560.00	650.42	1.23	1.80	0.0	13.10	117.00
2576.000	180.00	647.73	0.0	0.16	0.0	30.33	50.00
2576.000	310.00	648.95	1.22	0.28	0.0	35.76	50.00
2576.000	380.00	649.53	0.58	0.35	0.0	36.41	50.00
2576.000	560.00	650.96	1.43	0.54	0.0	56.28	50.00
2824.000	180.00	648.02	0.0	0.29	0.0	25.73	248.00
2824.000	310.00	649.24	1.22	0.29	0.0	31.25	248.00
2824.000	380.00	649.82	0.58	0.28	0.0	33.84	248.00
2824.000	560.00	651.20	1.38	0.24	0.0	41.80	248.00
3072.000	180.00	648.83	0.0	0.80	0.0	29.91	248.00
3072.000	310.00	649.91	1.08	0.67	0.0	36.11	248.00
3072.000	380.00	650.46	0.55	0.64	0.0	39.29	248.00
3072.000	560.00	651.79	1.33	0.99	0.0	46.98	248.00
3321.000	180.00	650.00	0.0	1.18	0.0	29.17	249.00
3321.000	310.00	650.78	0.77	0.86	0.0	33.64	249.00
3321.000	380.00	651.18	0.41	0.72	0.0	35.98	249.00
3321.000	560.00	652.25	1.08	0.48	0.0	42.22	249.00
3569.000	180.00	651.33	0.0	1.33	0.0	29.34	248.00
3569.000	310.00	652.05	0.72	1.28	0.0	33.51	248.00
3569.000	380.00	652.39	0.33	1.20	0.0	35.43	248.00
3569.000	560.00	653.19	0.81	0.93	0.0	40.10	248.00
3817.000	180.00	652.87	0.0	1.54	0.0	25.77	248.00
3817.000	310.00	653.61	0.74	1.56	0.0	31.67	248.00
3817.000	380.00	653.92	0.31	1.53	0.0	36.66	248.00
3817.000	560.00	654.59	0.67	1.40	0.0	50.44	248.00
4065.000	180.00	654.52	0.0	1.65	0.0	28.46	248.00
4065.000	310.00	655.27	0.75	1.65	0.0	37.68	248.00
4065.000	380.00	655.66	0.29	1.64	0.0	43.58	248.00
4065.000	560.00	656.18	0.63	1.59	0.0	66.24	248.00
4250.000	180.00	655.05	0.0	0.53	0.0	46.43	185.00
4250.000	310.00	655.92	0.86	0.65	0.0	56.24	185.00
4250.000	380.00	656.27	0.36	0.72	0.0	59.45	185.00
4250.000	560.00	657.03	0.76	0.85	0.0	66.30	185.00
4490.000	180.00	655.16	0.0	0.11	0.0	29.04	240.00
4490.000	310.00	656.02	0.85	0.10	0.0	33.56	240.00
4490.000	380.00	656.37	0.35	0.09	0.0	36.86	240.00
4490.000	560.00	657.10	0.73	0.06	0.0	44.60	240.00

	SECNO	Q	CWSEL	DIFWSP	DIFWSX	DIFKWS	TOPWID	XLCH
	4515.000	180.00	655.19	0.0	0.02	0.0	26.00	25.00
	4515.000	310.00	656.04	0.86	0.03	0.0	26.00	25.00
	4515.000	380.00	656.38	0.34	0.01	0.0	26.00	25.00
	4515.000	560.00	657.09	0.68	-0.04	0.0	26.00	25.00
	4540.000	180.00	655.16	0.0	-0.02	0.0	16.00	25.00
	4540.000	310.00	655.96	0.80	-0.08	0.0	16.00	25.00
	4540.000	380.00	656.26	0.29	-0.12	0.0	16.00	25.00
	4540.000	560.00	656.79	0.53	-0.27	0.0	16.00	25.00
	4564.000	180.00	654.93	0.0	-0.23	0.0	7.97	24.00
o	4564.000	310.00	655.77	0.83	-0.20	0.0	8.00	24.00
o	4564.000	380.00	656.27	0.51	0.02	0.0	8.00	24.00
o	4564.000	560.00	657.49	1.22	0.71	0.0	8.00	24.00
	4565.000	180.00	654.93	0.0	-0.00	0.0	7.97	1.00
o	4565.000	310.00	655.75	0.82	-0.01	0.0	8.00	1.00
o	4565.000	380.00	656.26	0.51	-0.02	0.0	8.00	1.00
	4565.000	560.00	657.37	1.11	-0.13	0.0	8.00	1.00
o	4925.000	180.00	656.07	0.0	1.14	0.0	7.94	360.00
o	4925.000	310.00	657.19	1.12	1.43	0.0	8.00	360.00
o	4925.000	380.00	657.69	0.51	1.43	0.0	8.00	360.00
o	4925.000	560.00	658.71	1.02	1.34	0.0	8.00	360.00
o	5280.000	180.00	657.50	0.0	1.63	0.0	7.94	355.00
o	5280.000	310.00	658.62	1.12	1.43	0.0	8.00	355.00
o	5280.000	380.00	659.12	0.51	1.43	0.0	8.00	355.00
o	5280.000	560.00	660.14	1.02	1.43	0.0	8.00	355.00
	5640.000	180.00	659.06	0.0	1.56	0.0	7.91	360.00
	5640.000	310.00	660.56	1.50	1.94	0.0	8.00	360.00
	5640.000	380.00	661.29	0.73	2.17	0.0	8.00	360.00
	5640.000	560.00	663.69	2.40	3.55	0.0	8.00	360.00
	5641.000	180.00	659.07	0.0	0.01	0.0	7.91	1.00
	5641.000	310.00	660.70	1.63	0.14	0.0	8.00	1.00
	5641.000	380.00	661.53	0.83	0.24	0.0	8.00	1.00
	5641.000	560.00	664.98	3.45	1.29	0.0	8.00	1.00

SUMMARY OF ERRORS

CAUTION SECNO= 4564.000 PROFILE= 2 CRITICAL DEPTH ASSUMED
CAUTION SECNO= 4564.000 PROFILE= 2 MINIMUM SPECIFIC ENERGY
CAUTION SECNO= 4564.000 PROFILE= 3 CRITICAL DEPTH ASSUMED
CAUTION SECNO= 4564.000 PROFILE= 3 MINIMUM SPECIFIC ENERGY
CAUTION SECNO= 4564.000 PROFILE= 4 CRITICAL DEPTH ASSUMED
CAUTION SECNO= 4564.000 PROFILE= 4 PROBABLE MINIMUM SPECIFIC ENERGY
CAUTION SECNO= 4564.000 PROFILE= 4 20 TRIALS ATTEMPTED TO BALANCE WSEL

CAUTION SECNO= 4565.000 PROFILE= 2 CRITICAL DEPTH ASSUMED
CAUTION SECNO= 4565.000 PROFILE= 2 MINIMUM SPECIFIC ENERGY
CAUTION SECNO= 4565.000 PROFILE= 3 CRITICAL DEPTH ASSUMED
CAUTION SECNO= 4565.000 PROFILE= 3 MINIMUM SPECIFIC ENERGY

NOTE SECNO= 4925.000 PROFILE= 1 WSEL BASED ON X2 CARD

NOTE SECNO= 4925.000 PROFILE= 3 WSEL BASED ON X2 CARD
NOTE SECNO= 4925.000 PROFILE= 4 WSEL BASED ON X2 CARD

NOTE SECNO= 5280.000 PROFILE= 1 WSEL BASED ON X2 CARD
NOTE SECNO= 5280.000 PROFILE= 2 WSEL BASED ON X2 CARD
NOTE SECNO= 5280.000 PROFILE= 3 WSEL BASED ON X2 CARD
NOTE SECNO= 5280.000 PROFILE= 4 WSEL BASED ON X2 CARD

FLOOD INSURANCE ZONE DATA FOR BEITZ DRAIN LIVONIA CITY

FLOOD HAZARD FACTOR FOR ENTIRE REACH USING SECTIONS

SECTION NUMBER	CUMULATIVE DISTANCE	ELEVATION DIFFERENCE BETWEEN BASE FLOOD AND 10	2	0.2
70.000	0.	0.0	0.0	0.0
297.000	227.	-0.16	-0.07	0.24
524.000	454.	-0.44	-0.16	0.53
752.000	682.	-0.86	-0.29	0.68
979.000	909.	-1.14	-0.36	0.74
1207.000	1137.	-1.20	-0.35	0.74
1434.000	1364.	-1.18	-0.39	0.72
1661.000	1591.	-1.20	-0.35	0.73
1888.000	1818.	-1.20	-0.36	0.75
2115.000	2045.	-1.10	-0.32	0.68
2359.000	2289.	-1.02	-0.27	0.52
2409.000	2339.	-1.04	-0.30	0.60
2526.000	2456.	-1.61	-0.51	1.23
2576.000	2506.	-1.80	-0.58	1.43
2824.000	2754.	-1.79	-0.58	1.38
3072.000	3002.	-1.63	-0.55	1.33
3321.000	3251.	-1.18	-0.41	1.05
3569.000	3499.	-1.05	-0.33	0.81
3817.000	3747.	-1.08	-0.31	0.67
4065.000	3995.	-1.03	-0.29	0.63
4250.000	4180.	-1.22	-0.36	0.76
4490.000	4420.	-1.20	-0.35	0.73
4515.000	4445.	-1.19	-0.34	0.68
4540.000	4470.	-1.09	-0.29	0.53
4564.000	4494.	-1.34	-0.51	1.22
4565.000	4495.	-1.33	-0.51	1.11
4925.000	4855.	-1.63	-0.51	1.02
5280.000	5210.	-1.63	-0.51	1.02
5640.000	5570.	-2.23	-0.73	2.40
5641.000	5571.	-2.46	-0.83	3.45
WEIGHTED AVG FOR REACH		-1.21	-0.38	0.86

FHF FOR THE REACH = 010 WITH 76.8 OF THE REACH WITHIN 0.5 FEET
ZONE FOR THE REACH = A 2

CONTINUOUS FLOOD HAZARD FACTORS BY EVEN INCREMENTS

INC NO.	TOTAL LENGTH	AVG ELEVATION DATA 10	I	DIFF.	WTD. AVG.	FHF	PERCENT WITHIN
	0.				SEC.	70.000	
1	100.	639.81	639.86	-0.04	-0.04	005	100.
2	200.	639.83	639.94	-0.11	-0.08	005	100.
	27.				SEC.	297.0	

4	400.	639.90	640.21	-0.31	-0.17	005	100.
	454.				SEC.	524.000	
5	500.	639.96	640.41	-0.45	-0.22	005	100.
6	600.	640.07	640.68	-0.61	-0.29	005	100.
	662.				SEC.	752.000	
7	700.	640.21	641.00	-0.79	-0.36	005	100.
8	800.	640.42	641.36	-0.94	-0.43	005	98.
9	900.	640.70	641.76	-1.06	-0.50	005	89.
	909.				SEC.	979.000	
10	1000.	641.02	642.16	-1.14	-0.57	005	80.
11	1100.	641.39	642.56	-1.17	-0.62	005	64.
	1137.				SEC.	1207.000	
12	1200.	641.78	642.97	-1.19	-0.67	005	76.
13	1300.	642.20	643.40	-1.20	-0.71	005	77.
	1364.				SEC.	1434.000	
14	1400.	642.64	643.82	-1.18	-0.74	005	79.
15	1500.	643.07	644.26	-1.19	-0.77	010	80.
	1571.				SEC.	1661.000	
16	1600.	643.50	644.69	-1.19	-0.80	010	81.
17	1700.	643.91	645.11	-1.20	-0.82	010	76.
18	1800.	644.31	645.51	-1.20	-0.84	010	78.
	1818.				SEC.	1888.000	
19	1900.	644.73	645.91	-1.18	-0.85	010	79.
20	2000.	645.15	646.29	-1.14	-0.87	010	80.
	2045.				SEC.	2115.000	
21	2100.	645.58	646.68	-1.10	-0.89	010	81.
22	2200.	646.03	647.10	-1.07	-0.89	010	82.
	2269.				SEC.	2359.000	
23	2310.	646.50	647.53	-1.03	-0.90	010	83.
	2339.				SEC.	2409.000	
24	2400.	647.01	648.19	-1.18	-0.91	010	93.
	2456.				SEC.	2526.000	
25	2500.	647.50	649.06	-1.56	-0.94	010	00.
	2506.				SEC.	2576.000	
26	2600.	647.78	649.56	-1.78	-0.97	010	73.
27	2700.	647.90	649.70	-1.80	-1.00	010	70.
	2754.				SEC.	2824.000	
28	2800.	648.07	649.34	-1.77	-1.03	010	68.
29	2900.	648.33	650.06	-1.73	-1.05	010	66.
30	3000.	648.66	650.32	-1.66	-1.07	010	67.
	3002.				SEC.	3072.000	
31	3100.	649.06	650.60	-1.54	-1.09	010	69.
32	3200.	649.53	650.69	-1.36	-1.10	010	69.
	3251.				SEC.	3321.000	
33	3300.	650.01	651.23	-1.22	-1.10	010	70.
34	3400.	650.53	651.66	-1.13	-1.10	010	71.
	3499.				SEC.	3565.000	
35	3500.	651.07	652.15	-1.08	-1.10	010	71.
36	3600.	651.65	652.70	-1.05	-1.10	010	72.
37	3700.	652.27	653.32	-1.05	-1.10	010	73.
	3747.				SEC.	3817.000	
38	3800.	652.90	653.95	-1.05	-1.10	010	74.
39	3900.	653.56	654.60	-1.04	-1.09	010	74.
	3995.				SEC.	4065.000	
40	4000.	654.21	655.25	-1.04	-1.09	010	75.
41	4100.	654.68	655.77	-1.09	-1.09	010	76.
	41 [illegible].				SEC.	4250.000	
42	4200.	654.94	656.12	-1.18	-1.10	010	76.
43	4300.	655.09	656.30	-1.21	-1.10	010	77.
44	4400.	655.13	656.34	-1.21	-1.10	010	77.
	4420.				SEC.	4490.000	
	4445.				SEC.	4515.000	
	4470.				SEC.	4540.000	
	4494.				SEC.	4564.000	
	4[illegible]5.				SEC.	[illegible]65.000	

45	4500.	655.15	656.32	-1.27	-1.10	010	78.
46	4600.	655.10	655.48	-1.38	-1.11	010	78.
47	4700.	655.42	653.07	-1.45	-1.12	010	77.
48	4800.	655.73	657.27	-1.54	-1.13	010	77.
	4855.				SEC.	4925.000	
49	4900.	656.07	657.67	-1.60	-1.14	010	78.
50	5000.	656.45	658.07	-1.62	-1.15	010	78.
51	5100.	656.85	656.48	-1.63	-1.16	010	77.
52	5200.	657.25	658.88	-1.63	-1.16	010	78.
	5251.				SEC.	5321.000	
53	5300.	657.67	659.37	-1.70	-1.17	010	75.
54	5400.	658.10	659.97	-1.87	-1.19	010	76.
55	5500.	658.54	660.57	-2.03	-1.20	010	78.
	5570.				SEC.	5640.000	
	5571.				SEC.	5641.000	

THIS REACH CAN BE SUBDIVIDED BY INC NO. TO MEET FIA REQUIREMENTS
INPUT 2 IN WHERE N IS THE NUMBER OF REACHES AND THEN INPUT THE END
OF EACH REACH BY INC NO. FOR EXAMPLE 202 52 55
A NEGATIVE INC NO. WILL SUPPRESS INTERMEDIATE INC OUTPUT.

00BREAK00

1) COUNTY: Wayne

2) STUDY NAME: City of Livonia

3) WATERCOURSE: Bell Branch

4) DOCUMENT TYPE: 100 year

00BREAK00

EXHIBIT 3

Bell Branch
100 yr Natural
(use encroached for FIS)

```
**********************************************************
    FLOB RELEASE DATED NOV 76 UPDATED FEB 1977
    APPRX COUR = 01
    MODIFICATION - 31.57.52
**********************************************************

C
C  BELL BRANCH FIS AUG 2014 OF LIVONIA CITY FROM CONF. GROUND. TO ELLEN RD.
C  T2 = 10YR=1350 50YR=2900 100YR=3600 500YR=5500 AT CORE. GROUND.
T5      BELL BRANCH LIVONIA CITY

J1  JCHECK    INQ       NINV      IDIR      STRT      METRIC    ITYPE     Q         NSEL      EQ

            3.        5.        0.        1.  0.500000    0.20      0.0       0.   620.500    0.000

J2  NPROF     IPLOT     PRFVS     XSECV     XSECH     FN        RLLOC     IBW       CHNID     ITWICE

        1.000     0.000    -1.000     0.000     0.000     0.000     0.000     0.000     0.030     0.000

J3  VARIABLE CODES FOR SUMMARY PRINTOUT

      110.000   150.000   200.000     0.000     0.000     0.000     0.000     0.000     0.000     0.000

LT      0.000     0.000     0.000     0.000     1.400     0.000     0.000     0.000     0.000     0.000
QT      3.000  1660.000  2900.000  3620.000  3600.000   500.000     0.000     0.000     0.000     0.000
NC      0.077     0.370     0.035     0.030     0.000     0.000     0.700     0.000     0.000     0.000

      SECND D FRO' REDFORD FIS. 50: D/S INKSTER

QT      0.000    19.000    30.000    65.000     0.000     0.000     0.000     0.000     0.000     0.000
QP    332.000     0.000   515.000    30.000   312.000    60.000   604.000    42.000   664.000    90.000
QR    609.104    47.000   906.000    65.000   613.300    92.000   613.500    79.000   826.000   332.000
QR    630.000   623.000     0.000     0.000     0.000     0.000     0.000     0.000     0.000     0.000
NC      0.000     1.000     0.035     0.320     0.500     0.000     0.000     0.000     0.000     0.000

      SECND 50 D/S FACE INKSTER FROM FIELD BOOK AND QUAD MAP

X1     50.000    21.000   294.000   376.500    50.000    50.000    50.000     0.000     0.000     0.000
X3      0.000     0.000     0.000   220.000     0.000   420.000     0.000     0.000     0.000     0.000
QR    524.000     0.000   622.000   780.000   636.000   294.000   636.000   294.100   636.000   299.000
QR    507.600   313.700   607.500   316.100   607.500   340.000   607.500   320.100   607.500   326.000
QP    504.100   327.000   604.000   355.000   606.100   591.000   607.500   351.100   607.800   353.000
QR    607.600   355.100   616.300   372.000   636.000   376.300   636.500   376.500   622.300   670.800
QR    524.000   600.000     0.000     0.000     0.000     0.000     0.000     0.000     0.000     0.000
NC      1.250     1.710     3.000     0.000    35.000     4.000   750.000     1.150   604.000   634.000

      SECND 100 D/S FACE INKSTER FROM FIELD BOOK AND QUAD MAP

X1    120.000     0.000     0.000     0.000    70.000    70.000    70.000     0.000     0.000     0.000
X2      0.000     0.000     1.000   619.200   620.400     0.200     0.000     0.000     1.000     0.000
X3      0.000     0.000     0.000   220.300     0.000   420.200     0.000     0.000     0.000     0.000
QT     16.000     0.000   624.000     0.300   150.000   622.200     0.000   299.000   625.000   512.000
QP    295.000   333.000   619.200   515.000   622.600   617.200   341.100   603.000   607.000   330.000
QR    620.500   607.000   321.100   622.600   619.200   341.000   500.000   311.200   401.100   642.600
QR    607.200   355.000   602.600   607.600   153.100   602.600   519.200   326.300   625.000   619.200
QP    326.100   527.400   116.000   151.600   522.000     0.000   301.000   334.000     0.000     0.000
      500.200   601.000   322.000     0.000   294.200   622.000     0.000   290.000   620.400     0.000
```

PRINTED IN U.S.A.
FORM 1411-GB PRINTED BY ROTARY MANIFOLD FORMS

BT	376.500	620.400	619.200	376.500	620.400	0.300	471.000	622.050	0.000	0.000
XC	0.100	0.100	0.035	0.300	0.500	0.000	0.000	0.000	0.000	0.000

SECND 170 50' U/S IKSTER FROM FIELD BOOK AND QUAD MAP

X1	170.000	12.100	127.000	147.000	50.000	50.000	50.050	0.000	0.000	0.000
X3	0.000	0.000	0.000	0.000	0.000	230.000	0.000	0.000	0.000	0.000
GR	630.000	0.000	625.000	45.000	610.200	121.000	604.200	127.000	604.100	130.000
GR	604.200	147.000	614.200	167.000	615.000	470.300	615.000	680.000	620.000	740.000
GR	625.000	315.300	630.000	930.000	0.000	0.300	0.000	0.000	0.000	0.000

SECND 640.CORPS XSEC 29 FROM CORPS NOTES AND QUAD MAP

X1	640.000	10.000	280.000	305.000	470.000	600.000	470.000	0.000	0.000	0.000
GR	650.000	0.000	625.000	170.000	620.000	230.300	615.000	270.000	606.500	260.000
GR	606.000	290.000	614.000	305.000	620.000	500.000	621.000	600.000	630.000	660.000
BT	0.080	0.080	0.035	0.130	0.300	0.300	0.000	0.000	0.000	0.000

SECND 1950 CORPS X-SEC 31 FRO CORPS NOTES AND QUAD MAP

X1	1950.000	11.000	415.000	435.000	1300.000	1430.000	1310.000	0.000	0.000	0.000
GR	630.000	0.000	620.000	60.000	615.000	110.300	615.000	410.000	610.500	415.000
GR	606.000	425.000	606.500	4_5.000	616.000	440.000	627.000	470.000	630.000	600.000

SECND 2750 CORPS X-SEC 32 FRO CORPS NOTES AND QUAD MAP

X1	2750.000	11.000	405.000	430.000	800.000	900.000	850.500	0.300	0.000	0.000
GR	630.000	0.000	625.000	50.000	619.500	100.000	617.000	250.000	616.500	400.000
GR	611.000	405.000	609.500	420.000	611.500	430.000	617.000	440.000	625.000	515.000
BT	630.000	540.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000

SECND 3450 CORPS X-SEC 33 FROM CORPS NOTES AND QUAD MAP OF CONFLUENCE WITH MONONGAHELA RIVER

X1	3450.000	11.000	625.000	645.000	1200.000	1200.000	1200.000	0.000	0.000	0.000
GR	630.000	0.000	625.000	40.000	620.300	70.000	617.000	305.000	611.500	615.000
GR	576.300	625.000	610.500	665.000	635.300	700.000	650.000	700.000	636.000	1150.000
X1	635.300	705.000	0.100	0.000	0.000	0.000	0.000	0.000	0.000	0.000
BT	0.300	711.000	1730.100	2126.000	2120.300	2120.000	0.000	0.000	0.000	0.000
XC	0.030	0.100	0.035	0.100	0.300	0.000	0.000	0.000	0.000	0.000

SECND 4530 CORPS X-SEC 37 FROM CORPS NOTES AND QUAD MAP

BT	5520.000	1.000	783.120	785.000	630.030	635.000	570.300	0.300	0.300	0.000
GR	635.000	0.000	620.000	340.000	625.000	670.000	670.300	750.300	670.000	770.000
GR	615.300	780.000	617.500	790.000	625.000	635.000	630.000	655.200	630.000	1155.000
BT	635.000	1275.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000

SECND 4810 CORPS X-SEC 38 FROM CORPS NOTES AND QUAD MAP OF

X1	5250.300	11.000	623.000	645.300	600.000	730.000	510.000	0.000	0.000	0.000
GR	630.300	0.000	625.000	150.300	620.000	130.000	620.000	625.000	615.000	655.000
[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]
[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]
[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]

SECND 5[illegible] CORPS [illegible] FROM CORPS NOTES AND QUAD MAP

PRINTED IN U.S.A.
FORM 1411-SS-PRINTED BY ROTARY MANIFOLD FORMS

X1	5520.000	11.000	120.000	155.000	500.000	520.000	470.000	0.010	0.000	0.000
X3	635.000	0.000	630.000	20.000	625.000	0.000	620.000	60.000	620.000	120.000
GR	615.000	135.000	619.000	155.000	620.000	250.000	625.000	275.000	630.000	515.000
[illegible]	635.000	380.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
NC	0.000	0.000	0.000	0.300	0.500	0.300	0.000	0.000	0.000	0.000

SECNO 6100 CORPS X-SEC 41 FRO' CORPS NOTES AND QUAD MAP

X1	6100.000	11.000	230.000	320.000	580.000	530.000	580.000	0.200	0.000	0.000
X3	0.300	0.000	0.000	200.000	0.000	360.000	0.000	0.000	0.000	0.000
GR	635.300	0.000	630.000	80.300	625.000	100.000	620.000	150.000	620.000	210.000
GR	616.500	315.000	621.000	320.000	620.000	440.000	625.000	420.000	630.000	530.000
GR	635.300	670.000	0.000	0.300	0.000	0.000	0.000	0.000	0.000	0.000
NC	0.120	0.120	0.035	0.300	0.500	0.000	0.000	0.000	0.000	0.000

SECNO 6320 50' D/S MIDDLEBELT FROM FIELD BOOK AND QUAD MAP

X1	6320.000	12.000	255.000	235.000	300.000	150.000	220.000	0.940	0.000	0.000
X3	0.000	0.000	0.000	230.000	0.000	310.000	0.000	0.000	0.000	0.000
GR	633.000	0.000	630.000	40.000	625.000	100.000	625.500	230.000	617.000	253.000
GR	616.000	275.000	617.000	235.000	617.000	305.000	620.500	320.000	625.000	430.000
GR	630.000	450.000	635.000	440.000	0.000	0.000	0.000	0.000	0.000	0.000
EF	0.000	0.000	0.000	0.000	9.100	0.000	0.000	0.000	1.000	244.000
NC	0.000	0.000	0.035	0.300	0.500	0.000	0.000	0.000	0.000	0.000

SECNO 6370 CORPS X-SEC 42 D/S FACE MIDDLEBELT FROM FIELD BOOK AND M.".

X1	6370.000	15.000	140.500	199.500	50.000	50.000	30.000	0.940	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.600	0.000	0.000	628.400	628.400	0.000
GR	630.000	0.000	628.000	60.000	629.100	124.000	620.600	130.000	615.100	140.500
GR	615.100	140.600	615.100	169.000	615.100	169.100	615.100	171.000	615.100	171.100
GR	615.100	199.500	615.100	199.500	620.100	212.000	629.100	231.000	650.000	245.000
NC	0.000	0.000	0.000	0.000	0.500	0.000	0.000	0.000	615.100	615.100

SECNO 6446 U/S FACE MIDDLEBELT FROM FIELD BOOK AND QUAD MAP

X1	6446.000	15.000	140.500	199.500	70.000	70.000	70.000	0.940	0.000	0.000
X2	0.300	0.000	0.000	627.600	629.100	0.000	0.000	0.300	0.940	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	629.100	629.100	0.000
GR	10.000	0.000	630.000	0.000	140.500	629.100	615.100	140.600	629.100	627.600
GR	169.000	629.100	627.600	169.100	629.100	615.100	171.000	629.100	615.100	171.100
GR	629.100	627.600	199.500	629.100	627.600	199.600	629.100	615.100	245.000	650.000
GR	0.000	0.000	0.000	0.300	0.000	0.000	0.000	0.000	0.000	0.000
EF	630.300	0.000	628.000	60.000	629.100	124.000	620.600	130.000	615.100	140.500
GR	615.100	140.600	615.100	169.000	615.100	169.100	615.100	171.000	615.100	171.100
GR	615.100	199.500	615.100	199.500	620.100	212.000	629.100	231.000	650.000	245.000
EF	0.000	0.000	0.000	0.000	1.400	0.000	0.000	0.000	0.000	0.000
NC	0.120	0.120	0.035	0.300	0.500	0.300	0.000	0.000	0.000	0.000

SECNO 6496 50' U/S MIDDLEBELT FROM FIELD BOOK AND TOPO MAP

X1	6496.300	12.000	240.000	281.500	50.000	50.000	50.000	0.940	0.000	0.000
X2	0.300	0.000	0.000	157.600	0.000	300.000	0.000	0.000	0.000	0.000
GR	630.000	0.000	624.000	50.000	626.000	180.000	620.000	240.000	610.300	450.000
GR	614.100	240.000	615.100	280.000	615.300	300.000	616.500	300.300	620.300	450.000
GR	629.300	300.000	630.000	300.000	0.000	0.000	0.000	0.000	0.000	0.000
NC	0.000	0.120	0.035	0.300	0.300	0.000	0.000	0.000	0.000	0.000

SECNO 7796 FROM FIELD BOOK AND TOPO MAP

X1	7796.000	13.000	111.000	135.000	1300.000	1300.000	1330.000	0.000	0.000	0.000
GP	636.000	3.000	630.000	70.000	625.000	90.000	621.500	135.000	617.000	111.000
GR	614.900	125.000	616.300	135.000	621.900	145.000	620.600	155.000	620.000	375.000
GR	625.000	400.000	630.000	425.000	635.000	460.000	0.000	0.000	0.000	0.000

SECNO 8096 X

X1	8096.000	11.000	176.000	200.000	300.000	300.000	300.000	0.000	0.000	0.000
GP	635.000	3.000	630.000	30.000	625.000	50.000	622.300	170.000	617.500	176.000
GR	615.500	190.000	616.800	200.000	622.500	210.000	625.000	335.000	630.000	325.000
GR	635.000	360.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
MC	0.120	0.120	0.035	0.100	0.300	0.000	0.000	0.000	0.000	0.000

SECNO 8896 FROM FIELD BOOK AND TOPO MAP

X1	8896.000	11.000	397.000	413.000	650.000	650.000	800.000	0.000	0.000	0.000
GP	635.000	3.000	630.000	100.000	625.000	125.000	622.700	391.000	617.100	397.000
GR	616.900	385.000	617.600	413.000	622.600	419.000	625.000	432.000	630.000	448.000
GR	635.000	404.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
MC	0.100	0.100	0.035	0.100	0.300	0.000	0.000	0.000	0.000	0.000

SECNO 9546 X

X1	9546.000	11.000	242.000	278.000	630.000	650.000	650.000	0.000	0.000	0.000
GP	635.000	0.000	630.000	30.000	625.000	40.000	623.000	256.000	617.000	252.000
GR	617.300	270.000	618.000	278.000	623.000	284.000	625.000	396.000	630.000	420.000
SP	635.000	435.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000

SECNO 12076 FROM FIELD BOOK AND TOPO MAP

X1	12076.000	11.000	396.000	424.000	2350.000	2350.000	2550.000	0.000	0.000	0.000
SP	635.000	0.000	630.000	30.000	626.000	90.000	625.900	396.000	621.900	431.000
GR	616.900	411.000	624.000	419.000	623.900	424.000	626.000	450.000	630.000	595.000
SR	635.000	600.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
ET	0.000	0.000	0.000	0.000	1.410	0.000	0.000	0.000	0.000	0.000
MC	0.120	0.120	0.035	0.100	0.300	0.000	0.000	0.000	0.000	0.000

SECNO 12326 FROM FIELD BOOK AND TOPO MAP

X1	12326.000	11.000	357.000	383.000	750.000	640.000	750.000	0.000	0.000	0.000
GP	636.000	3.000	630.000	100.000	626.000	150.000	624.100	352.000	624.200	357.000
GR	621.700	370.000	623.400	383.000	627.000	389.000	630.000	405.000	635.000	425.000
GR	640.000	385.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
MC	0.000	0.000	0.040	0.000	0.000	0.000	0.000	0.000	0.000	0.000

SECNO 15976.00 U/S HEADTOWN RUD FIELD BOOK AND TOPO MAP

X1	15976.000	13.000	762.000	780.000	800.000	1150.000	1150.000	0.000	0.000	0.000
X3	0.000	3.000	3.000	720.000	0.000	812.000	0.000	0.000	0.000	0.000
GP	650.000	3.000	645.000	50.000	645.000	190.000	645.000	645.000	640.000	609.000
GR	620.000	400.000	623.700	750.000	625.000	772.000	625.000	705.000	630.000	630.000
GR	630.000	625.000	645.000	1090.000	650.000	650.000	650.000	650.000	650.000	0.000
ET	0.000	0.000	0.000	0.000	4.100	0.000	0.000	0.000	0.000	0.000
MC	0.000	0.000	0.000	0.000	0.500	0.000	0.000	0.000	0.000	0.000

PRINTED IN U.S.A.
FORM 1411-OB PRINTED BY ROTARY MANIFOLD FORMS.

SECNO 14026 D/S FACE MERRIMAN FROM FIELD BOOK AND TOPO MAP

X1	14026.000	10.000	680.000	739.000	50.000	50.000	50.000	0.900	0.000	0.000
X3	10.000	0.300	0.000	0.000	0.000	0.000	0.000	634.300	634.300	0.000
GT	640.000	0.000	680.000	50.000	635.000	220.000	626.600	672.000	623.600	680.000
GR	623.600	680.100	623.600	708.000	623.600	708.100	625.300	710.500	625.300	710.600
GR	625.300	739.000	625.300	739.100	629.600	748.000	650.000	800.000	655.000	950.000
GR	640.000	1100.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
SR	0.900	2.150	3.000	0.000	53.680	2.270	393.600	0.000	624.400	624.400

SECNO 14100 U/S FACE MERRIMAN FROM FIELD BOOK AND TOPO MAP

X1	14100.000	16.000	680.000	739.000	74.000	74.000	74.000	0.900	0.000	0.000
X2	0.000	0.000	1.000	632.100	636.600	0.000	0.000	0.000	0.900	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	636.600	636.600	0.000
GT	12.000	0.000	640.000	0.300	220.000	636.000	0.000	680.000	636.600	623.600
GT	600.100	636.600	632.100	708.000	636.600	632.100	750.100	636.600	623.600	710.500
BT	636.600	625.300	710.600	636.600	632.100	739.000	636.600	632.100	739.100	636.600
BT	625.300	950.000	638.000	0.000	1100.000	640.000	0.000	0.000	0.000	0.000
GR	640.000	0.000	638.000	50.000	635.000	220.000	628.600	672.000	623.600	680.000
GR	623.600	680.100	623.600	708.000	623.600	708.100	625.300	710.500	625.300	710.600
GR	625.300	739.000	625.300	739.100	629.600	748.000	650.000	800.000	655.000	950.000
GR	640.000	1100.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
RC	0.120	0.120	0.040	0.300	0.500	0.000	0.000	0.000	0.000	0.000

SECNO 14150 50' U/S MERRIMAN FROM FIELD BOOK AND TOPO MAP

X1	14150.000	12.000	328.000	412.000	50.000	50.000	50.000	0.900	0.000	0.000
X3	0.000	0.000	0.000	315.000	0.000	439.000	0.000	0.000	0.000	0.000
GT	642.000	0.000	636.000	140.000	630.000	215.000	627.200	382.000	624.500	388.000
GR	623.700	400.000	624.500	412.000	629.600	417.000	630.000	580.000	630.000	620.000
GR	635.000	365.000	642.000	730.000	0.000	0.000	0.000	0.000	0.000	0.000
RC	0.100	0.100	0.035	0.300	0.500	0.000	0.000	0.000	0.000	0.000
ST	0.000	7.100	7.100	7.100	5.100	7.100	600.000	1110.000	646.000	1110.000

SECNO 14660 FROM FIELD BOOK AND TOPO MAP

XT	14660.000	18.000	390.000	910.000	510.000	510.000	510.000	0.000	0.000	0.000
ST	644.000	0.000	640.000	35.000	628.000	130.300	625.000	200.000	630.000	325.000
GT	650.000	385.000	628.000	570.000	625.000	675.300	630.000	685.000	630.000	735.000
GR	628.600	885.000	623.400	890.000	623.200	900.000	623.400	910.000	623.800	915.000
GT	630.000	1000.000	640.000	1035.000	642.000	1110.000	0.000	0.000	0.000	0.000
RC	0.000	0.700	0.000	0.000	1.400	0.600	0.000	0.000	0.000	0.000
RC	0.120	0.120	0.035	0.100	0.500	0.000	0.000	0.000	0.000	0.000

SECNO 16305 FROM FIELD BOOK AND TOPO MAP

XT	16305.000	12.000	50.000	110.000	1803.000	1645.000	1645.000	0.000	0.000	0.000
GT	630.000	0.000	640.000	50.000	623.000	50.000	623.600	65.000	624.600	90.000
GT	625.400	80.000	624.600	110.000	629.600	115.000	630.000	150.000	632.000	240.000
GR	646.000	560.000	646.000	480.000	0.000	0.000	0.000	0.000	0.000	0.000
RC	0.100	0.100	0.040	0.100	0.500	0.000	0.000	0.000	0.000	0.000

SECNO 17750 50' U/S MERRIMAN FROM FIELD BOOK AND TOPO MAP

XT	17750.000	15.000	355.000	425.000	100.000	1500.000	1425.000	0.000	0.000	0.000
RT	0.000	0.000	0.000	35.000	0.000	431.000	0.000	0.000	0.000	0.000
GT	650.000	0.000	630.000	125.000	640.000	110.000	632.000	200.000	632.000	295.000

PRINTED IN U.S.A.
FORM 1411-GB PRINTED BY ROTARY MANIFOLD FORMS.

GR	626.600	375.000	626.500	410.000	626.600	425.000	630.000	430.000	640.000	460.000
GR	644.000	480.000	646.000	600.000	648.000	650.000	650.000	675.000	652.000	365.000
MC	0.000	0.000	0.035	0.300	0.500	0.000	0.000	0.000	0.000	0.000
ET	0.000	0.000	0.000	0.000	9.100	0.000	0.000	0.000	1.000	799.000

SECNO 17780.3/S FACE HUBBARD FROM FIELD BOOK AND TOPO MAP

X1	17780.000	24.000	426.000	513.100	50.000	50.000	50.000	0.000	0.000	0.000
X3	10.000	3.000	0.030	0.000	0.000	0.000	0.000	641.200	641.200	0.000
GT	652.000	0.000	650.000	90.000	645.000	155.000	640.000	180.000	635.000	200.000
GR	638.000	425.000	637.500	426.000	637.000	426.100	650.000	643.000	628.500	451.500
GR	628.500	451.600	626.500	452.500	626.500	452.600	620.500	646.500	626.500	486.600
GR	626.500	487.500	626.500	487.600	630.000	493.500	657.000	513.000	637.000	513.100
GP	638.000	520.000	640.000	570.000	645.000	660.000	650.000	800.000	0.000	0.000
SB	1.250	1.240	3.000	0.000	36.000	2.000	867.000	2.240	626.500	626.500

SECNO 17826 U/S FACE HUBBARD FROM FIELD BOOK AND TOPO MAP

X1	17826.000	0.000	0.000	0.000	46.000	46.000	46.000	0.000	0.000	0.000
X2	0.000	0.000	1.000	640.000	642.300	0.000	0.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.300	642.300	642.300	0.000
BT	16.000	90.000	650.000	0.000	155.000	645.000	0.200	426.000	642.500	637.000
BT	426.000	642.500	649.000	451.500	642.500	640.000	451.500	642.500	626.500	652.500
BT	642.500	626.500	452.600	642.500	640.000	486.500	642.500	640.000	486.600	642.500
BT	626.500	487.500	642.500	626.500	487.600	642.500	640.000	513.000	642.500	640.000
BT	513.100	642.300	637.000	660.000	645.000	0.000	500.000	650.000	0.000	0.000
ET	0.000	0.000	0.000	0.000	1.400	0.000	0.000	3.000	0.000	0.000
MC	0.100	0.100	0.040	0.300	0.500	0.000	0.000	0.000	0.000	0.000

SECNO 17876 50' U/S HUBBARD FROM FIELD BOOK AND TOPO MAP

X1	17876.000	12.000	370.000	302.000	90.000	90.000	50.000	0.000	0.000	0.000
X3	0.000	0.200	0.000	244.000	0.000	424.000	0.000	0.000	0.000	0.000
GR	652.300	0.000	650.300	55.000	632.000	280.000	650.000	305.000	626.600	470.000
SR	626.500	360.000	626.600	382.000	630.000	435.000	640.000	425.000	645.000	470.000
GR	650.000	635.000	652.000	770.000	0.000	0.000	0.000	0.000	0.000	0.000
MC	0.120	0.120	0.035	0.100	0.300	0.000	0.000	0.000	0.000	0.000

SECNO 18500 FROM FIELD BOOK AND TOPO MAP

X1	18500.000	10.000	285.000	305.000	560.000	624.000	624.000	0.000	0.000	0.000
GT	656.000	0.000	650.000	60.000	652.000	120.000	652.500	202.000	625.100	245.000
GR	627.300	295.000	628.600	305.000	631.100	534.000	652.000	302.000	626.000	470.000
MC	0.000	0.100	0.055	0.100	0.300	0.000	0.000	0.000	0.000	0.000

SECNO 20180 FROM FIELD BOOK AND TOPO MAP

X1	20180.000	13.000	579.000	605.000	1400.000	1350.200	1662.000	0.000	0.000	0.000
GR	656.000	0.200	650.000	520.000	634.000	362.000	654.000	560.000	635.000	574.000
GR	631.000	579.000	640.000	590.000	631.200	625.100	654.000	610.000	638.000	652.000
GR	650.000	765.000	636.000	1159.000	0.000	0.000	0.000	0.000	0.000	0.000
MC	0.100	0.100	0.035	0.100	0.300	0.200	0.000	0.000	0.000	0.000

SECNO 22013 51' U/S FAIRLINGTON FROM FIELD BOOK AND TOPO MAP

X1	22010.000	51.200	370.000	410.000	1300.000	1510.200	1423.000	0.000	0.000	0.000
X3	0.000	0.300	0.000	344.000	0.000	424.200	0.000	0.000	0.000	0.000
GR	652.000	0.300	650.000	150.000	640.000	190.200	650.000	365.000	652.200	472.000

PRINTED IN U.S.A.
FORM 1411-GB-PRINTED BY ROTARY MANIFOLD FORMS.

GR	632.600	390.000	632.700	610.000	656.700	417.000	640.000	430.000	650.000	460.000
GR	660.000	555.000	0.000	0.000	0.000	0.300	0.000	0.000	0.000	0.000
ET	0.000	0.300	0.000	0.000	9.100	0.000	0.000	0.000	1.000	912.000
NC	0.000	0.000	0.000	0.300	0.500	0.000	0.000	0.000	0.000	0.000
	SECNO 22060 D/S FACE FARMINGTON FROM FIELD BOOK AND TOPO MAP SKEW 60.									
X1	22060.000	19.000	435.000	511.130	50.000	50.000	50.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	651.900	651.900	0.000
GR	659.000	0.000	655.000	152.250	650.000	278.400	644.600	435.000	646.600	437.160
GR	633.600	456.320	650.900	456.330	650.900	457.160	653.600	457.190	632.600	472.410
GR	633.600	488.070	650.900	488.080	650.900	488.930	653.600	468.940	644.600	568.080
GR	644.600	511.130	650.000	626.400	655.000	739.500	660.000	913.500	0.000	0.000
SR	1.050	1.340	3.000	0.000	32.000	1.740	1044.000	1.460	632.600	632.600
	SECNO 22146 U/S FACE FERMINGTON RD. BRIDGE, SKEW BRIDGE									
X1	22146.000	0.000	0.000	0.000	86.000	86.000	86.000	0.000	0.000	0.000
X2	0.000	0.000	1.000	650.900	652.900	0.000	0.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	652.900	652.900	0.000
DT	0.000	158.230	655.000	0.000	435.000	652.900	0.000	435.000	652.900	650.900
BT	511.130	652.900	650.900	511.130	652.900	0.000	739.500	655.000	0.000	0.000
AX	0.000	0.000	0.000	0.000	1.680	0.000	0.000	0.000	0.000	0.000
NC	0.100	0.100	0.040	0.300	0.500	0.000	0.000	0.000	0.000	0.000
	SECNO 22196 50' U/S FARMINGTON FROM FIELD BOOK AND TOPO MAP									
X1	22196.000	11.000	470.000	510.000	50.000	50.000	50.000	0.470	0.000	0.000
X3	0.000	0.000	0.000	401.000	0.000	579.000	0.000	0.000	0.000	0.000
GR	658.000	0.000	656.000	130.000	640.000	315.000	634.900	465.000	632.700	470.000
GR	632.600	490.000	632.900	510.000	634.800	517.000	640.000	530.000	650.000	620.000
DT	660.000	1050.200	0.000	0.000	0.000	0.500	0.000	0.500	0.000	0.000
NC	0.100	0.100	0.035	0.300	0.300	0.300	0.000	0.200	0.000	0.000
	SECNO 23296 FROM FIELD BOOK AND TOPO MAP									
X1	23296.000	11.000	279.300	301.000	700.300	110.000	1400.000	0.000	0.000	0.000
GR	656.000	0.000	650.000	70.000	646.000	120.000	637.500	274.000	652.100	279.000
GR	633.000	290.000	633.400	301.000	637.000	306.130	636.000	340.000	640.000	440.000
SR	650.000	670.000	660.000	550.000	0.000	0.000	0.000	0.000	0.000	0.000
NC	0.100	0.100	0.035	0.100	0.300	0.000	0.000	0.000	0.000	0.000
	SECNO 24096 CONFLUENCE WITH BEITZ BRAIN FROM FIELD BOOK AND TOPO MAP									
X1	24096.000	12.000	139.000	161.000	600.000	600.000	600.000	0.000	0.000	0.000
GR	660.000	0.000	650.000	50.000	640.000	100.000	637.400	134.000	633.100	139.000
GR	652.700	150.000	633.200	161.000	638.400	166.000	640.000	190.000	642.000	420.000
GR	650.000	460.000	663.000	585.300	0.000	0.000	0.000	0.300	0.000	0.000
GT	5.000	300.000	8410.000	1740.300	1740.000	1510.000	0.000	0.300	0.000	0.000
	SECNO 25668 FROM FIELD BOOK AND TOPO MAP									
X1	25668.000	19.000	349.000	271.000	1700.000	1500.000	1571.000	0.000	0.000	0.000
GR	662.000	0.100	560.000	30.000	642.000	110.000	641.000	211.000	642.100	244.000
GT	633.000	284.300	633.300	271.000	636.400	281.000	635.000	274.000	640.000	301.000
SR	650.000	405.000	560.000	465.000	0.000	0.000	0.000	0.000	0.000	0.000

PRINTED IN U.S.A.
FORM 1611-CO PRINTED BY ROTARY MANIFOLD FORMS

SECNO 28728 FROM FIELD BOOK AND TOPO MAP

X1	28728.000	9.000	50.000	67.000	1200.000	630.300	1060.000	0.000	0.000	0.000
GR	664.000	0.000	640.100	45.000	636.100	50.000	635.400	60.000	635.500	67.000
GR	643.300	75.000	640.000	290.000	640.000	315.000	660.000	405.000	0.000	0.000

SECNO 28628 CONFLUENCE WITH TRIBUTARY #1 FROM FIELD BOOK AND TOPO MAP

X1	28628.000	13.000	365.000	380.000	1600.000	2000.000	1900.000	0.000	0.000	0.000
GR	660.000	0.000	656.000	250.000	650.000	310.000	664.400	350.000	640.100	355.000
GR	638.900	365.000	638.200	377.000	643.600	380.000	644.000	390.000	644.000	650.000
GR	650.000	683.000	658.000	710.000	659.500	800.000	0.000	0.000	0.000	0.000
QT	5.000	500.000	890.000	1100.000	1100.000	1550.000	0.000	0.000	0.000	0.000
NC	0.100	0.100	0.035	0.100	0.300	0.000	0.000	0.000	0.000	0.000

SECNO 29480 FROM FIELD BOOK AND TOPO MAP

X1	29480.000	13.000	451.000	458.000	1500.000	1000.000	860.000	0.000	0.000	0.000
GR	660.000	0.000	654.000	310.000	648.000	575.000	645.500	445.000	641.800	451.000
GR	641.900	458.000	642.100	465.000	645.800	471.000	648.000	476.000	646.000	495.000
GR	646.000	590.000	650.300	615.000	660.000	640.000	0.000	0.000	0.000	0.000
CT	0.000	9.100	9.100	9.100	1.400	0.000	0.000	0.000	286.000	329.000
QT	5.000	500.000	710.000	860.000	800.000	1230.000	0.000	0.000	0.000	0.000
NC	0.080	0.090	0.030	0.300	0.500	0.000	0.000	0.000	0.000	0.000

SECNO 30818 50' D/S GLEN RD. FROM FIELD BOOK AND TOPO MAP

X1	30818.000	9.000	300.000	316.000	1100.000	2000.000	1350.000	0.000	0.000	0.000
GR	662.000	0.000	660.000	110.000	650.000	266.000	643.300	300.000	643.200	308.000
GR	643.300	316.000	656.000	350.000	660.000	470.000	662.000	600.000	0.000	0.000
CT	0.000	0.000	0.000	0.000	9.100	0.000	0.000	0.000	1.000	649.000

SECNO 30868 D/S FACE GLEN RD. FROM FIELD BOOK AND TOPO MAP

X1	30868.000	19.000	322.000	338.000	50.000	50.000	50.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	651.200	651.200	0.000
BT	662.000	0.000	662.000	265.000	651.400	295.000	648.000	317.000	645.200	322.000
BT	665.200	293.000	643.200	324.000	643.200	328.000	643.200	326.000	643.200	330.000
BT	643.200	332.000	343.200	334.000	643.200	336.000	643.200	337.000	645.200	338.000
GR	648.000	343.000	651.600	367.000	662.000	367.000	662.000	650.000	0.000	0.000
SB	0.000	2.100	3.000	0.000	15.800	0.000	99.500	0.000	644.900	644.900

SECNO 30921 D/S FACE GLEN FROM FIELD BOOK AND TOPO MAP

X1	30921.000	0.000	0.000	0.000	53.000	53.000	55.000	0.000	0.000	0.000
X2	0.000	0.000	1.000	651.200	653.200	0.000	0.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	653.200	653.200	0.000
BT	57.000	0.000	662.000	0.000	265.000	308.000	0.000	265.000	652.200	0.000
BT	322.000	653.200	648.200	323.000	653.200	647.800	324.000	653.200	649.000	326.000
BT	653.200	651.200	328.000	653.200	651.000	351.000	653.200	651.200	332.000	653.200
BT	651.000	334.000	653.200	650.000	336.000	653.200	649.000	337.000	653.200	647.800
BT	338.000	653.200	645.200	367.000	654.000	0.000	367.000	662.000	0.000	650.000
BT	662.000	0.000	0.300	0.000	0.000	0.000	0.000	0.000	0.000	0.000
EJ	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000

PRINTED IN U.S.A.
FORM 1411-GD PRINTED BY ROTARY MANIFOLD FORMS.

*PROF 1

CCHV= 0.600 CEHV= 0.300

*SECNO ****

SECNO	DEPTH	CWSEL	CRITWS	WSELK	EG	HV	AL	QLOSS	BANK ELEV
Q	QLOB	JCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IN2	ICONT	CORAR	TOPWID	ENDST

SECNO 3 FROM BEDFORD FIG. 50: D/S INKSTER

0.00	15.40	620.50	0.00	620.50	621.01	0.51	0.00	0.00	615.00
3600.	35.	2691.	874.	27.	409.	473.	0.	0.	613.50
0.00	1.32	6.57	1.85	0.070	0.035	0.070	0.000	605.10	20.29
0.001208	0.	0.	0.	0	0	0	0.00	169.87	190.16

CCHV= 0.500 CEHV= 0.500

*SECNO 50.000

3470 ENCROACHMENT STATIONS= 220.0 420.0 TYPE= 1 TARGET= 200.000

SECNO 50 D/S FACE INKSTER FROM FIELD BOOK AND QUAD MAP

50.00	16.97	620.97	0.00	0.00	621.14	0.17	0.03	0.10	616.00
3600.	170.	3301.	129.	224.	951.	156.	1.	0.	616.00
0.00	0.76	3.47	0.83	0.070	0.035	0.070	0.034	604.00	220.00
0.000297	50.	50.	50.	2	0	0	0.00	200.00	420.00

SPECIAL BRIDGE

NO	XN	XKOD	COEF	RELEN	HWC	DWP	BAREA	SS	ELEV	ELCHD
	1.25	1.71	3.00	0.00	35.00	4.00	750.20	1.16	604.00	604.00

*SECNO 120.000

PRESSURE AND :EIP FLOW

EGPRS	EGLWC	AS	QWEIR	QPR	BAREA	TRAPEZOID AREA	ELLC	ELTRD
621.58	621.17	0.02	410.	3375.	750.	744.	619.20	620.40

3470 ENCROACHMENT STATIONS= 220.0 420.0 TYPE= 1 TARGET= 200.000

SECNO 120 D/S FACE INKSTER FROM FIELD BOOK AND QUAD MAP

120.00	17.29	621.29	0.00	0.00	621.45	0.16	0.00	0.10	616.00
3600.	189.	3271.	130.	247.	977.	170.	3.	1.	616.10
0.01	0.76	3.35	0.83	0.070	0.035	0.070	0.034	604.00	220.00
0.000266	70.	70.	70.	2	0	5	0.00	200.00	420.00

CCHV= 0.500 CEHV= 0.500

SECNO 170.000

3470 ENCROACHMENT STATIONS= 2.0 280.0 TYPE= 1 TARGET= 274.690

PRINTED IN U.S.A.
FORM 141.0 PRINTED BY ROTARY MANIFOLD FORMS

SECNO 170 50' D/S INKSTER FROM FIELD BOOK AND QUAD MAP

170.00	17.13	621.23	0.00	0.00	621.53	0.30	0.02	0.07	604.20
3600.	416.	1991.	1194.	397.	342.	1019.	5.	1.	604.20
0.01	1.05	5.83	1.17	0.150	0.035	0.100	0.034	606.10	64.34
0.000428	50.	30.	50.	2	0	0	0.00	215.46	280.00

*SECNO 640.000

SECNO	DEPTH	CHSEL	CRIVS	ASELK	FS	HV	HL	DLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WIN	ELMIN	SSTA
SLOPE	XLOTL	XLCH	XLOBR	ITRIAL	IM2	ICONT	CORAR	TOPWID	ENDST

SECNO 660.CORPS X-SEC 29 FROM CORPS NOTES AND QUAD MAP

660.00	15.51	623.51	0.00	0.00	621.83	0.33	0.24	0.01	606.50
3600.	345.	1980.	1275.	281.	325.	1158.	28.	4.	614.00
0.05	1.23	6.09	1.10	0.100	0.035	0.100	0.033	606.00	211.92
0.000745	470.	470.	500.	2	0	0	0.00	360.13	572.05

CCHL= 0.100 CCHV= 0.300

*SECNO 1950.000

SECNO 1950 CORPS X-SEC 31 FROM CORPS NOTES AND QUAD MAP

1950.00	14.29	622.79	0.00	0.00	622.36	0.07	0.50	0.03	610.50
3600.	2549.	975.	75.	2490.	271.	104.	96.	10.	608.50
0.27	1.02	3.60	0.72	0.080	0.035	0.080	0.034	606.00	46.25
0.003228	1300.	1310.	1400.	0	0	0	0.00	410.90	457.16

*SECNO 2750.000

SECNO 2750 CORPS X-SEC 32 FROM CORPS NOTES AND QUAD MAP

2750.00	12.98	622.48	0.30	0.00	622.65	0.18	0.26	0.05	611.50
3600.	1951.	1505.	245.	1523.	299.	283.	143.	24.	611.50
0.36	1.29	5.02	1.10	0.080	0.035	0.080	0.034	609.50	90.44
0.000559	800.	900.	660.	2	0	0	0.00	415.63	691.36

*SECNO 3950.000

SECNO 3950 XSEC 35 EDGE D/S OF CONFLUENCE W/TARABUS CREEK

3950.00	11.79	623.29	0.00	0.00	623.33	0.04	0.66	0.01	616.00
3600.	3115.	408.	77.	2527.	121.	97.	209.	38.	618.50
0.57	1.23	3.38	0.80	0.080	0.035	0.080	0.034	611.50	50.29
0.003583	1200.	1201.	1200.	2	0	1	0.00	435.20	695.49

CCHV= 0.100 CEHV= 0.300

*SECNO 4520.000

SECNO 4520 CORPS X-SEC 37 FROM CORPS NOTES AND QUAD MAP

4520.00	9.65	624.01	0.30	1.09	623.08	0.92	3.49	0.06	614.52
2134.	904.	890.	243.	780.	132.	287.	258.	45.	615.50
0.58	1.26	5.69	1.10	1.080	0.035	0.120	3.035	615.00	454.61
0.011526	850.	570.	451.	0	1	0	0.30	354.64	484.72

PRINTED IN U.S.A.
FORM 1411-GB PRINTED BY ROTARY MANIFOLD FORMS.

```
*SECNO 5050.000
   SECNO      DEPTH      CNSEL      CRIWS      WSELK      EG         HV         BL         QLOSS      BANK ELEV
     Q        QLOB       QCH        QROB       ALOB       ACH        AROB       VOL        TRA        LEFT/RIGHT
    TIME      VLOB       VCH        VROB       XNL        XNCH       XNR        ITN        ELMIN      SSTA
    SLOPE     XLOBL      XLCH       XLOBR      ITRIAL     IN2        ICONT      CORAR      TOPWID     ESTST

          SECNO 5050 CORPS X-SEC 39 FROM CORPS NOTES AND QUAD MAP

  5350.00      9.27     624.27       3.00       0.00     626.39       0.12       0.54       0.01     615.00
     2120.      1031.       496.       594.       742.        93.       608.       252.        50.     615.00
     0.69       1.39       5.34       0.98      0.030      0.035      0.120      0.034     615.00     154.37
0.000813       500.       530.       580.          2          0          0       0.00     334.08     468.45

CCHV=   0.100 CCHV=   0.300
*SECNO 5520.000

          SECNO 5520 CORPS X-SEC 60 FROM CORPS NOTES AND QUAD MAP

  5520.00      9.62     624.62       0.00       0.00     624.76       0.14       0.36       0.02     620.00
     2120.      319.      1061.       741.       270.       259.       540.       266.        58.     619.00
     0.74       1.18       4.09       1.37      0.080      0.035      0.080      0.034     615.00      45.06
0.000674       500.       470.       500.          2          0          0       0.00     230.03     273.09

CCHV=   0.300 CEHV=   0.500
*SECNO 6100.000

3473 ENCROACHMENT STATIONS=     200.0     380.0  TYPE=     1  TARGET=     160.000

          SECNO 6100 CORPS X-SEC 61 FROM CORPS NOTES AND QUAD MAP

  6100.00      8.54     625.04       3.02       0.30     625.21       0.17       0.64       0.01     620.00
     2120.      617.      1152.       351.       404.       269.       250.       230.        56.     621.00
     0.80       1.53       4.27       1.36      0.090      0.035      0.080      0.034     616.50     230.00
0.000347       500.       580.       580.          0          2          0       0.00     180.00     380.00

CCHV=   0.300 CEHV=   0.500
*SECNO 6320.000

3473 ENCROACHMENT STATIONS=     216.2     291.4  TYPE=     1  TARGET=      60.000

          SECNO 6320 50' D/S MIDDLEBELT FROM FIELD BOOK  AND QUAD MAP

  6320.00      9.06     625.06       0.00       0.00     625.70       0.64       0.25       0.24     617.00
     2120.       77.      1712.       330.        66.       241.       180.       283.        56.     617.00
     0.81       1.17       7.09       1.83      0.120      0.035      0.120      0.034     616.00     223.23
-0.001400       330.       320.       160.          2          5          0       0.00      63.17     291.40

CCHV=   0.300 CEHV=   0.500
*SECNO 6370.000

3475 OVERBANK AREA ASSUMED NON-EFFECTIVE-QLEFT=     620.40 ALREAD=     623.56

          SECNO 6370 CORPS X-SEC 62 D/S FACE MIDDLEBELT FROM FIELD BOOK AND Q.H.

  6370.00      10.76    625.46       0.00       0.00     625.67       0.20       0.09       2.93     615.71
```

PRINTED IN U.S.A.
FORM 1411-08-PRINTED BY ROTARY MANIFOLD FORMS

2120.	0.	2120.	0.	0.	586.	0.	284.	56.	615.10	
0.81	0.00	3.62	0.00	0.120	0.035	0.120	0.034	615.10	132.07	
0.000395	50.	50.	50.	2	0	0	0.00	55.46	187.53	

SPECIAL BRIDGE

SB	XK	XKOR	COFC	RDLEN	BHC	BWP	BAREA	SS	ELCHJ	ELCHD
	0.90	2.05	3.00	0.00	55.46	1.88	669.75	0.00	615.10	615.10

*SECNO 6440.000

SECNO	DEPTH	CHSEL	CRIWS	USELK	EC	HV	WL	QLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XSCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IH2	ICONT	CORAR	TOPWID	ENDST

CLASS A LOW FLOW

3420 BRIDGE W.S.= 625.65 BRIDGE VELOCITY= 3.75 CALCULATED CHANNEL AREA= 565.

FQFRS	ESLNC	M3	QWEIR	QBR	BAREA	TRAPEZOID AREA	ELLC	ELRD
0.00	625.87	3.01	0.	2120.	670.	670.	627.80	629.10

5495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 629.10 ELREA= 629.10

SECNO 6446 U/S FACE MIDDLEBELT FROM FIELD BOOK AND QUAD MAP

6446.00	11.57	625.67	0.00	0.00	625.87	0.20	0.01	0.00	615.10
2120.	0.	2120.	0.	0.	386.	0.	284.	57.	615.10
0.82	0.00	3.62	0.00	0.120	0.033	0.120	0.034	615.10	132.07
0.000396	70.	70.	70.	0	0	0	0.00	55.46	187.53

CCHV= 0.300 CEHV= 0.500

*SECNO 6496.000

3471 ENCROACHMENT STATIONS= 147.6 290.3 TYPE= 1 TARGET= 160.000

SECNO 6496 50' U/S MIDDLEBELT FROM FIELD BOOK AND TOPO MAP

6496.00	10.60	625.72	0.00	0.00	625.89	0.19	3.02	0.00	616.60
2120.	337.	3613.	173.	440.	402.	213.	284.	57.	615.20
0.82	0.77	4.09	0.01	0.120	0.033	0.120	0.034	615.10	147.36
0.000439	50.	50.	50.	1	0	0	0.00	150.40	297.96

CCHV= 0.100 CEHV= 0.300

*SECNO 7796.000

SECNO 7796 FROM FIELD BOOK AND TOPO MAP

7796.00	11.36	626.28	0.00	0.00	626.37	0.09	3.45	0.01	617.00
2120.	50.	893.	1135.	91.	251.	1605.	331.	68.	615.40
1.01	0.16	3.56	0.73	0.00	0.033	0.120	0.034	614.90	14.36
0.000341	1330.	300.	1330.	2	0	0	0.00	121.31	406.59

*SECNO 8094.000

PRINTED IN U.S.A.

FORM 1411-GB PRINTED BY ROTARY MANIFOLD FORMS

SECNO 8096 X

8096.00	10.68	625.18	0.00	0.00	626.63	0.45	0.16	0.11	617.50
2120.	361.	1503.	256.	363.	236.	299.	341.	66.	616.60
1.02	0.99	5.37	0.85	0.100	0.035	0.120	0.034	615.50	45.26
0.001082	300.	800.	300.	2	0	0	0.00	264.47	309.76

CCHV= 0.100 CEHV= 0.300
*SECNO 8896.000

SECNO 8896 FROM FIELD BOOK AND TOPO MAP

8896.00	10.22	627.12	0.00	0.00	627.52	0.40	0.88	0.60	617.10
2120.	903.	1115.	102.	924.	160.	92.	358.	70.	617.60
1.08	0.98	6.97	1.10	0.120	0.035	0.120	0.035	616.90	114.41
0.001257	650.	800.	850.	3	0	0	0.00	324.37	438.78

CCHV= 0.100 CEHV= 0.300
*SECNO 9546.000

SECNO	DEPTH	CHSEL	CRIDS	ASELK	ES	HV	HL	ILOSS	BANK ELEV
I	SLOP	XOCH	QROB	ALOC	ACH	AROB	VOL	THO	LEFT/RIGHT
TIME	VLOB	YOC	VROB	XNI	XNCH	XAR	RTC	ILAIN	SSTA
SLOPE	XLOBL	XLCH	XLOOR	ITRIAL	IH2	ICONT	CORAR	TOPWID	ENDST

SECNO 9546 X

9546.00	10.65	627.95	0.00	0.00	628.13	0.18	0.58	0.02	617.80
2120.	782.	866.	472.	814.	166.	489.	377.	76.	618.00
1.14	0.96	5.23	0.96	0.100	0.035	0.100	0.035	617.30	46.42
0.000675	650.	650.	650.	2	0	0	0.00	361.87	467.39

*SECNO 12076.000

SECNO 12076 FROM FIELD BOOK AND TOPO MAP

12076.00	11.73	329.63	0.00	0.00	629.72	0.09	1.59	0.11	625.90
2120.	1069.	285.	296.	1221.	209.	396.	467.	101.	625.90
1.49	0.86	3.75	0.73	0.100	0.035	0.100	0.035	618.90	35.71
0.000636	2350.	2530.	2350.	2	0	0	0.00	548.35	584.06

CCHV= 0.100 CEHV= 0.300
*SECNO 12826.000

SECNO 12826 FROM FIELD BOOK AND TOPO MAP

12826.00	8.41	630.41	0.00	0.00	630.57	0.16	0.77	0.11	624.20
2120.	764.	1516.	47.	629.	491.	46.	418.	107.	625.40
1.54	1.21	6.65	1.06	0.120	0.035	0.120	0.035	621.90	157.92
0.001849	750.	750.	800.	2	0	0	0.00	243.42	400.54

*SECNO 13975.000
WITH ENCROACHMENT STATION= 555.3 730.8 TYPE= 1 DIST= 54.00

SECNO 13975 FOR BRIDGE FROM FIELD BOOK AND TOPO MAP

PRINTED IN U.S.A.
FORM 1411-OD-PRINTED BY ROTARY MANIFOLD FORMS.

13976.00	8.66	632.26	0.00	0.00	632.80	0.54	2.28	0.03	623.70
2120.	477.	1191.	452.	229.	155.	220.	505.	110.	623.70
1.59	2.09	7.69	2.06	0.120	0.040	0.120	0.036	623.60	655.20
0.002430	800.	1150.	1150.	2	0	0	0.00	75.60	730.60

CCHV= 0.300 CEHV= 0.300

*SECNO 14026.000

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 634.30 ELREA= 634.30

SECNO 14026 D/S FACE MERRIMAN FROM FIELD BOOK AND TOPO MAP

14026.00	8.97	632.57	0.00	0.00	632.94	0.36	0.09	0.05	623.60
2120.	0.	2120.	0.	0.	431.	0.	506.	110.	625.30
1.60	0.00	4.92	0.00	0.120	0.040	0.120	0.036	623.60	612.00
0.001341	50.	50.	50.	2	0	0	0.00	53.10	665.10

SPECIAL BRIDGE

SK	XK	RCOR	CDFQ	ROLEN	BSC	BSP	BAREA	BS	ELCHU	ELCHD
	0.40	2.15	5.00	0.00	53.06	2.27	395.60	0.03	626.40	624.40

*SECNO 14100.000

SECNO	DEPTH	CHSEL	CRIWS	WSELK	EG	FV	PL	QLOSS	BANK ELEV
	QLOU	VCH	QROB	ALOB	ACH	AROB	VCL	TRA	LEFT/RIGHT
TIME	VLOU	VCH	VROB	XNL	XNCH	XNR	XTN	ELMIN	SSTA
SLOPE	XLJUL	XLCH	XLOBR	ITRIAL	IHS	ICONT	CDH,W	TOPWID	ENDST

PRESSURE FLOW

TOTAL	EG,WC	AS	QWEIR	QPR	SAREA	TRAPEZOID AREA	ELLC	EL,TRD
635.53	632.96	0.32	0.	2120.	394.	396.	632.10	636.60

3695 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 636.60 ELREA= 636.60

SECNO 14100 U/S FACE MERRIMAN FROM FIELD BOOK AND TOPO MAP

14100.00	9.61	633.21	0.00	0.00	633.53	0.32	0.53	0.00	623.60
2120.	0.	2120.	0.	0.	465.	0.	508.	110.	625.30
1.60	0.00	4.56	0.00	0.120	0.040	0.120	0.036	623.60	612.00
0.001053	74.	74.	74.	2	0	0	0.00	53.10	665.10

CCHV= 0.300 CEHV= 0.300

*SECNO 14150.000

3470 ENCROACHMENT STATIONS= 287.1 440.1 TYPE= 1 TARGET= 170.000

SECNO 14150 D/S MERRIMAN FROM FIELD BOOK AND TOPO MAP

14150.00	7.33	631.28	0.10	0.10	633.69	0.41	2.41	0.18	624.50
2120.	551.	1285.	464.	358.	167.	252.	307.	110.	624.50
1.59	1.92	8.57	1.74	0.120	0.040	0.120	0.033	623.70	287.10
0.001341	50.	50.	50.	2	0	0	0.00	53.10	665.10

PRINTED IN U.S.A.
FORM 1411-OD PRINTED BY ROTARY MANIFOLD FORMS.

CCHV= 0.300 CEHV= 0.500
*SECNO 14660.000

3420 ENCROACHMENT STATIONS= 400.0 1110.0 TYPE= 1 TARGET= 710.000

SECNO 14660 FROM FIELD BOOK AND TOPO MAP

14660.00	10.72	633.92	0.00	0.00	633.95	0.03	0.19	0.12	623.40
2120.	1342.	551.	227.	2447.	212.	450.	550.	115.	623.40
1.74	0.55	2.39	0.50	0.100	0.035	0.100	0.036	623.20	400.01
0.000160	510.	530.	510.	0	0	0	0.00	613.70	1013.72

CCHV= 0.100 CEHV= 0.300
*SECNO 16305.000

SECNO 16305 FROM FIELD BOOK AND TOPO MAP

16305.00	10.83	634.23	0.00	0.00	634.62	0.39	0.56	0.11	624.40
2120.	256.	1303.	561.	229.	206.	634.	614.	132.	624.60
1.85	1.12	6.34	0.89	0.120	0.035	0.120	0.035	623.40	41.54
0.000004	1800.	1645.	1645.	3	0	0	0.00	201.47	303.01

CCHV= 0.100 CEHV= 0.300
*SECNO 17730.000

3470 ENCROACHMENT STATIONS= 358.0 461.0 TYPE= 1 TARGET= 903.000

SECNO 17730 50' D/S HUBBARD FROM FIELD BOOK AND TOPO MAP

17730.00	9.26	635.76	0.00	0.00	636.20	0.46	1.57	0.02	625.60
2120.	545.	1454.	121.	214.	270.	87.	558.	157.	626.60
1.92	1.60	5.98	1.39	0.100	0.040	0.100	0.036	623.50	356.02
0.001344	1100.	1435.	1300.	2	0	0	0.01	69.28	547.28

CCHV= 0.300 CEHV= 0.500
*SECNO 17750.000

SECNO	DEPTH	CHSEL	CRIVS	LSELK	ES	HV	NL	ULOSS	CHAN ELEV
Q	VLOB	VCH	VROB	ALOB	ACH	AROB	WOL	TWA	CLEFTLOUT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	BTN	ELTRP	SSTA
SLOPE	XLOBL	XLCH	XLOBR	XTRIAL	IK2	ICONT	CORAR	TOPWID	ERDSTA

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 641.20 ELREA= 641.20

SECNO 17780.D/S FACE HUBBARD FROM FIELD BOOK AND TOPO MAP

17780.00	9.59	636.09	0.00	0.00	636.32	0.23	0.39	0.09	627.00
2120.	0.	2120.	0.	0.	506.	0.	659.	137.	637.00
1.93	0.00	5.02	0.00	0.120	0.035	0.100	0.036	626.50	428.30
0.000672	50.	50.	50.	2	2	0	0.00	82.17	510.47

SECNO 17810.U/S FACE

50	24.	0.00	0.00	0.00	15.00	0.00	0.00	0.00	0.00
1.25	0.24	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

PRINTED IN U.S.A.
FORM 1411-GB PRINTED BY ROTARY MANIFOLD FORMS.

*SECNO 17826.000
CLASS A LOW FLOW

3420 BRIDGE W.S.=	636.07	BRIDGE VELOCITY=	4.00	CALCULATED CHANNEL AREA=	531.

FQPRS	FQLWC	KF	QWEIR	QPR	QAREA	TRAPEZOID AREA	ELLC	ELTRD
0.00	636.33	0.02	0.	2120.	867.	867.	640.00	642.30

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEN= 642.30 ELREA= 642.30

SECNO 17826 U/S FACE HUBBARD FROM FIELD BOOK AND TOPO MAP

17826.00	9.61	636.11	0.00	0.00	636.33	0.23	0.02	0.00	637.00
2120.	0.	2120.	0.	0.	557.	0.	649.	138.	637.00
1.93	0.00	3.81	0.00	0.100	0.035	0.100	0.036	626.50	420.26
0.000668	46.	46.	46.	0	0	0	0.00	82.25	510.51

CCHV= 0.300 CEKV= 0.500
*SECNO 17876.000

3475 ENCROACHMENT STATIONS= 244.0 424.0 TYPE= 1 TARGET= 180.000

SECNO 17876 50' U/S HUBBARD FROM FIELD BOOK AND TOPO MAP

17876.00	9.70	636.20	0.00	0.00	636.39	0.19	0.14	0.01	626.00
2120.	1056.	667.	396.	688.	116.	216.	640.	138.	626.60
1.93	1.53	5.76	1.84	0.100	0.040	0.100	0.036	626.50	244.03
0.001170	50.	55.	50.	2	0	0	0.00	172.15	416.15

CEKV= 0.500 CEHV= 0.350
*SECNO 18500.000

SECNO 18500 FROM FIELD BOOK AND TOPO MAP

18500.00	9.50	636.80	0.00	0.00	637.19	0.39	0.32	0.09	629.10
2120.	935.	1116.	67.	782.	131.	46.	656.	140.	621.00
1.98	1.20	6.41	1.02	0.120	0.035	0.120	0.036	627.30	106.19
0.001287	540.	524.	624.	2	0	0	0.00	217.50	323.69

CCHV= 0.100 CEHV= 0.350
*SECNO 20180.000

SECNO 20180 FROM FIELD BOOK AND TOPO MAP

20180.00	8.31	638.60	0.00	0.30	638.73	0.13	1.64	0.12	631.30
2120.	1067.	955.	98.	619.	107.	116.	669.	149.	631.80
2.12	1.37	4.63	0.08	0.010	0.033	0.300	0.036	638.06	355.91
0.000881	1400.	1660.	1500.	1	2	0	0.00	500.77	695.78

CLHV= 0.100 CEHV= 0.350
*SECNO 22030.000

3503 HW CRANED OUT STRAIN GAUGE

SEQ	DEPTH	VELOC	QTOT	QPIER	EG	IW	ICASE	LEAKAGE

Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IN2	ICONT	CORAR	TOPWID	BUDST

3470 ENCROACHMENT STATIONS= 299.3 379.3 TYPE= 1 TARGET= 0.000

SECNO 22010 50' D/S FARMINGTON FROM FIELD BOOK AND TOPO MAP

22010.00	7.69	640.29	0.00	0.00	641.01	0.72	2.06	0.14	652.70
2120.	135.	1903.	83.	90.	266.	56.	715.	155.	652.70
2.19	1.49	7.16	1.48	0.100	0.035	0.100	0.036	652.60	299.24
0.001888	1300.	1830.	1300.	2	0	0	0.00	75.58	374.86

CONV= 0.300 CEHV= 0.500
*SECNO 22060.000

3265 DIVIDED FLOW

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE ELLEN= 651.90 ELKEN= 651.90

SECNO 22060 D/S FACE FARMINGTON FROM FIELD BOOK AND TOPO MAP SKEW LN.

22060.00	7.82	640.42	0.00	0.00	641.16	0.74	0.14	0.01	644.60
2120.	0.	2120.	0.	0.	307.	0.	715.	155.	644.60
2.19	0.00	4.90	0.00	0.100	0.035	0.100	0.036	652.60	444.43
0.004816	50.	50.	50.	2	0	0	5.00	54.63	500.31

SPECIAL BRIDGE

BW	XK	XKOR	CURV	RADIUS	DNC	HWP	BARLA	CD	ELCHD	ELCHU
	1.03	1.34	3.00	0.00	32.00	1.74	1044.00	1.46	652.60	652.60

*SECNO 22146.000

3265 DIVIDED FLOW

CLASS A LOW FLOW

3420 BRIDGE W.S.= 640.36 BRIDGE VELOCITY= 6.57 CALCULATED CHANNEL AREA= 323.

ZGPRS	EGLWC	HS	QWEIR	QPR	QAREA	TRAPEZOID AREA	ELLC	ELTRD
0.00	641.23	0.09	0.	2120.	1044.	1043.	650.90	652.90

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE ELLEN= 652.90 ELKEN= 652.90

SECNO 22146 D/S FACE FARMINGTON RD. BRIDGE, SKEW BRIDGE

22146.00	7.91	640.31	0.00	1.00	641.25	0.72	2.06	0.00	644.65
2120.	0.	2120.	0.	0.	312.	0.	715.	155.	644.60
5.20	0.00	4.90	0.00	0.00	0.038	0.100	0.036	652.60	444.43
0.004824	50.	50.	50.	0	0	0	5.00	54.94	500.96

PRINTED IN U.S.A.
FORM 1411.08 PRINTED BY ROTARY MANIFOLD FORMS.

CCHV= 0.300 CEHV= 0.500
*SECNO 22196.000

3470 ENCROACHMENT STATIONS= 348.9 503.7 TYPE= 1 TARGET= 178.000

SECNO 22196 50' D/S FARMINGTON FROM FIELD BOOK AND TOPO MAP

22196.00	8.55	641.15	0.00	0.00	641.45	0.30	0.10	0.12	652.70
2120.	476.	1514.	130.	324.	294.	92.	716.	155.	632.90
2.20	1.47	5.15	1.41	0.100	0.040	0.100	0.036	632.60	348.87
0.001116	50.	50.	50.	2	0	0	0.00	121.23	476.13

CCHV= 0.300 CEHV= 0.500
*SECNO 23296.000

SECNO 23296 FROM FIELD BOOK AND TOPO MAP

23296.00	9.15	642.16	0.00	0.00	642.31	0.15	0.21	0.04	653.10
2120.	748.	923.	444.	749.	199.	501.	739.	160.	633.40
2.31	1.00	4.67	0.99	0.100	0.035	0.100	0.037	633.00	102.68
0.000644	700.	1100.	1100.	3	0	0	0.00	343.79	446.47

CCHV= 0.100 CEHV= 0.300
*SECNO 24096.000

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	QLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	T-A	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XLCH	XNR	XTN	ELDIS	SST
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IL2	ICONT	CORAR	TOPWID	ENDST

SECNO 24096 CONFLUENCE WITH BEITZ DRAIN FROM FIELD BOOK AND TOPO MAP

24096.00	9.85	642.53	0.00	0.00	643.06	0.53	0.54	0.12	653.10
2120.	236.	1675.	401.	582.	251.	447.	733.	304.	633.20
2.35	1.33	6.98	0.86	0.100	0.035	0.100	0.037	632.70	67.33
0.001323	600.	800.	600.	2	0	0	0.00	335.34	422.67

*SECNO 25668.000

SECNO 25668 FROM FIELD BOOK AND TOPO MAP

25668.00	9.96	644.36	0.00	0.00	644.63	0.27	1.54	0.05	655.60
1760.	502.	1103.	635.	528.	213.	156.	736.	174.	634.60
2.67	0.95	5.19	0.66	0.100	0.033	0.100	0.037	634.40	99.49
0.000729	1700.	1572.	1300.	2	0	0	0.00	231.55	331.02

*SECNO 26726.000

SECNO 26726 FROM FIELD BOOK AND TOPO MAP

26726.00	9.65	645.05	0.00	0.00	645.13	0.08	0.44	0.22	656.10
1760.	43.	502.	1295.	51.	100.	1295.	6.7.	175.	635.50
2.60	0.75	5.76	0.09	0.100	0.035	0.100	0.037	635.40	15.64
0.000394	201.	1200.	600.	3			0.00	3.2.05	527.95

*SECNO 27428.300

SECNO 27428 CONFLUENCE WITH TAMARACK #1 FROM FIELD BOOK AND TOPO MAP

FORM 1411-GB PRINTED BY ROTARY MANIFOLD FORMS.
PRINTED IN U.S.A.

28628.00	6.19	646.39	0.00	0.00	646.65	0.29	1.49	0.06	638.90
1743.	213.	720.	810.	164.	111.	666.	895.	193.	643.60
2.74	2.02	6.50	1.22	0.100	0.035	0.100	0.037	656.20	355.74
0.002114	1600.	1900.	2000.	2	0	0	0.00	326.27	661.99

CCHV= 0.100 CEHV= 0.300
*SECNO 29488.000

SECNO 29488 FROM FIELD BOOK AND TOPO MAP

29488.00	5.83	648.63	0.00	0.00	645.91	0.27	2.22	0.00	641.80
1100.	198.	343.	559.	164.	47.	386.	881.	200.	641.90
2.85	1.21	7.22	1.45	0.100	0.035	0.100	0.036	641.80	368.14
0.002255	1500.	860.	1000.	3	0	0	0.00	238.31	606.46

CCHV= 0.300 CEHV= 0.500
*SECNO 30818.000

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	MTI	ELPIM	SSTA
SLOPE	KLOBL	KLCH	KLOBR	ITRIAL	IN2	ICONT	CORAR	TOPWID	ENDST

3470 ENCROACHMENT STATIONS= 288.0 329.0 TYPE= 1 TARGET= 41.000

SECNO 30818 90' D/S ELLEN RD. FROM FIELD BOOK AND TOPO MAP

30818.30	7.54	650.74	0.00	0.00	651.16	0.42	2.16	0.07	643.30
850.	94.	694.	92.	65.	120.	65.	897.	206.	643.30
2.93	1.44	5.79	1.42	0.080	0.030	0.080	0.036	643.20	288.00
0.002752	1100.	1350.	2000.	3	0	0	0.00	31.00	329.00

*SECNO 30866.700

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 651.20 ELREA= 651.20

SECNO 30868 D/S FACE ELLEN RD. FROM FIELD BOOK AND TOPO MAP

30868.00	7.38	650.58	0.00	0.00	651.47	0.89	3.08	0.24	645.20
880.	0.	880.	0.	0.	116.	0.	897.	206.	643.20
2.93	0.00	7.58	0.00	0.080	0.030	0.080	0.036	643.20	324.00
0.002816	50.	50.	50.	2	0	0	0.00	18.00	306.00

SPECIAL BRIDGE

SK	KQ	XKOR	COPT	ROLEX	BWC	PAP	SAREA	BS	FLCHO	CLCHO
0.50	2.90	3.33	0.53	15.00	0.00	99.00	0.00	796.90	344.90

*SECNO 30921.000
PRESSURE FLOW

838.30	832.90	0.00	24	886.	1054.	666.	668.25	643.60	

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 653.20 ELREA= 653.20

SECND 30921.00 FACE ELLEN FROM FIELD BOOK AND TOPO MAP

30921.30	9.38	652.58	0.00	3.00	653.13	0.55	1.66	0.00	645.20
880.	0.	880.	0.	0.	148.	0.	897.	206.	645.20
2.94	0.00	5.94	0.00	0.000	0.030	0.080	0.026	643.20	322.00
3.001390	93.	93.	53.	2	0	0	0.00	10.00	338.00

PRINTED IN U.S.A.

FORM 1411-GB PRINTED BY ROTARY MANIFOLD FORMS.




1) COUNTY: Wayne

2) STUDY NAME: City of Livonia

3) WATERCOURSE: Bell Branch

4) DOCUMENT TYPE: Summary



```
**************************************************
  RECP RELEASE DATED NOV 76 UPDATED AUG1977
  ERROR CORR =  01,02
  MODIFICATION =  50,51,52,53
**************************************************

C
T1 BELL BRANCH FIS HUD 2014 07 LIVONIA CITY FROM CORP. BOUND. TO ELLEN RD.
T2 Q 10YR=1650 50YR=2900 100YR=3600 500YR=5500 AT CORP. BOUND.
T3       BELL BRANCH LIVONIA CITY
```

J1	ICHECK	INQ	NINV	IDIR	STRT	METRIC	HVINS	Q	WSEL	FN
	1.	2.	0.	0.	0.0	0.0	0.0	0.	616.700	0.0

J2	NPROF	IPLOT	PRFVS	XSECV	XSECH	FN	ALLOC	IBW	CHNIM	ITRACE
	1.000	0.0	-1.000	0.0	0.0	0.0	0.0	0.0	0.0	0.0

J3 VARIABLE CODES FOR SUMMARY PRINTOUT

150.000	201.000	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

J5 LPRNT NUMSEC ********REQUESTED SECTION NUMBERS********

-10.000	-10.000	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
ET	0.0	0.0	0.0	0.0	1.400	0.0	0.0	0.0	0.0	0.0
QT	5.000	1650.000	2900.000	3600.000	3600.000	5500.000	0.0	0.0	0.0	0.0
XC	0.070	0.070	0.035	0.600	0.600	0.0	0.0	0.0	0.0	0.0

SECNO 0 FROM REDFORD FIS. 50' D/S INKSTER

X1	0.0	11.000	30.000	65.010	0.0	0.0	0.0	0.0	0.0	0.0
GR	632.000	0.0	615.000	30.000	612.000	40.000	608.000	45.000	606.000	50.000
GR	605.100	60.000	608.000	65.000	613.500	65.010	613.500	75.000	629.000	330.000
GR	630.000	620.000	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
XC	0.0	0.0	0.035	0.400	0.500	0.0	0.0	0.0	0.0	0.0

SECNO 50 D/S FACE INKSTER FROM FIELD BOOK AND QUAD MAP

X1	50.000	21.000	294.000	375.500	50.000	50.000	50.000	0.0	0.0	0.0
X3	0.0	0.0	0.0	220.000	0.0	420.000	0.0	0.0	0.0	0.0
GR	624.000	0.0	622.000	180.000	616.000	294.000	616.000	294.100	616.000	299.000
GR	607.600	318.000	607.600	318.100	607.600	320.000	607.600	320.100	607.600	326.000
GR	604.100	327.000	604.000	335.000	604.100	351.000	607.600	351.100	607.600	353.000
GR	607.600	353.100	616.000	372.000	616.000	375.500	616.000	375.600	622.000	470.000
GR	624.000	500.000	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
SH	1.257	1.710	3.000	0.0	35.000	4.000	750.000	1.130	604.000	604.000

SECNO 120 D/S FACE INKSTER FROM FIELD BOOK AND QUAD MAP

X1	120.000	0.0	0.0	0.0	70.000	70.000	70.000	0.0	0.0	0.0
X2	0.0	0.0	1.000	61.250	420.000	0.0	0.0	0.0	0.0	0.0
X3	0.0	0.0	0.0	220.000	0.0	420.000	0.0	0.0	0.0	0.0
GT	15.000	0.0	624.000	0.0	180.000	622.000	0.0	294.000	620.400	616.000
GT	294.100	323.000	619.200	318.000	323.600	619.200	318.100	623.600	607.600	320.000

****
HEC2 RELEASE DATED NOV 76 UPDATED AUG1977
ERROR CORR - 01,02
MODIFICATION - 50,51,52,53
****

NOTE- ASTERISK (*) AT LEFT OF CROSS-SECTION NUMBER INDICATES MESSAGE IN SUMMARY OF ERRORS LIST

BELL BRANCH LIVONIA CITY

SUMMARY PRINTOUT TABLE 150

SECNO	XLCH	ELTRD	ELLC	ELMIN	Q	CWSEL	CRITWS	EG	10K*S	VCH	AREA	.01K
0.0	0.0	0.0	0.0	605.10	1650.00	616.70	0.0	617.12	13.96	5.44	395.05	441.69
0.0	0.0	0.0	0.0	605.10	2900.00	619.20	0.0	619.72	13.36	6.39	703.59	793.47
0.0	0.0	0.0	0.0	605.10	3600.00	620.50	0.0	621.01	12.05	6.57	909.03	1035.61
0.0	0.0	0.0	0.0	605.10	5500.00	624.00	0.0	624.42	8.18	6.44	1615.14	1923.06
50.000	50.00	0.0	0.0	604.00	1650.00	617.14	0.0	617.24	2.83	2.59	657.47	979.96
50.000	50.00	0.0	0.0	604.00	2900.00	619.69	0.0	619.85	3.08	3.27	1075.99	1653.59
50.000	50.00	0.0	0.0	604.00	3600.00	620.67	0.0	621.14	2.97	3.47	1330.90	2088.98
50.000	50.00	0.0	0.0	604.00	5500.00	624.32	0.0	624.51	2.50	3.76	2001.26	3477.01
120.000	70.00	620.40	619.20	604.00	1650.00	617.15	0.0	617.26	2.82	2.58	659.25	983.15
120.000	70.00	620.40	619.20	604.00	2900.00	619.94	0.0	620.09	2.80	3.17	1125.26	1732.53
120.000	70.00	620.40	619.20	604.00	3600.00	621.29	0.0	621.45	2.66	3.35	1394.21	2205.81
120.000	70.00	620.40	619.20	604.00	5500.00	624.40	0.0	624.52	2.45	3.75	2016.62	3512.45
170.000	50.00	0.0	0.0	604.10	1650.00	617.11	0.0	617.33	3.71	4.51	910.78	856.60
170.000	50.00	0.0	0.0	604.10	2900.00	619.69	0.0	620.16	4.19	5.46	1472.71	1416.05
170.000	50.00	0.0	0.0	604.10	3600.00	621.23	0.0	621.53	4.28	5.83	1757.22	1740.36
170.000	50.00	0.0	0.0	604.10	5500.00	624.34	0.0	624.68	4.41	6.61	2451.19	2620.44
640.000	470.00	0.0	0.0	606.00	1650.00	617.28	0.0	617.71	13.16	6.22	532.99	454.81
640.000	470.00	0.0	0.0	606.00	2900.00	620.15	0.0	620.55	9.56	6.40	1289.61	938.09
640.000	470.00	0.0	0.0	606.00	3600.00	621.51	0.0	621.83	7.45	6.09	1764.89	1318.58
640.000	470.00	0.0	0.0	606.00	5500.00	624.74	0.0	624.96	4.77	5.65	3034.14	2517.74
1950.000	1310.00	0.0	0.0	605.00	1650.00	617.52	0.0	617.62	3.53	3.61	1366.67	876.73
1950.000	1310.00	0.0	0.0	605.00	2900.00	621.09	0.0	621.16	2.52	3.56	2379.99	1627.50
1950.000	1310.00	0.0	0.0	605.00	3600.00	622.29	0.0	622.36	2.26	3.60	2865.10	2385.80
1950.000	1310.00	0.0	0.0	605.00	5500.00	625.26	0.0	625.34	1.82	3.68	4133.57	4078.60
2750.000	800.00	0.0	0.0	609.50	1650.00	618.79	0.0	619.19	11.61	5.87	651.91	484.22
2750.000	800.00	0.0	0.0	609.50	2900.00	621.30	0.0	621.51	6.46	5.23	1569.60	1140.56
2750.000	800.00	0.0	0.0	609.50	3600.00	622.46	0.0	622.65	5.19	5.02	2045.55	1580.06
2750.000	800.00	0.0	0.0	609.50	5500.00	625.43	0.0	625.56	3.32	4.65	3338.09	3018.89
3950.000	1200.00	0.0	0.0	611.50	1650.00	620.76	0.0	620.81	15.33	3.82	1184.05	421.41
3950.000	1200.00	0.0	0.0	611.50	2900.00	622.35	0.0	622.39	8.02	3.54	2151.97	1024.24
3950.000	1200.00	0.0	0.0	611.50	3600.00	623.29	0.0	623.33	5.83	3.38	2744.27	1490.88
3950.000	1200.00	0.0	0.0	611.50	5501.00	625.91	0.0	625.94	2.98	3.07	4465.59	3187.16

	SECNO	XLCH	ELTRD	ELLC	ELMIN	Q	CWSEL	CRIWS	EG	10K*S	VCH	AREA	.01K
1	4520.000	570.00	0.0	0.0	615.00	1110.00	621.52	0.0	621.91	20.14	5.88	508.58	247.32
2	4520.000	570.00	0.0	0.0	615.00	1720.00	622.75	0.0	623.08	16.50	6.06	853.13	423.42
3	4520.000	570.00	0.0	0.0	615.00	2120.00	623.61	0.0	623.84	13.27	5.86	1139.03	582.04
4	4520.000	570.00	0.0	0.0	615.00	3120.00	626.08	0.0	626.16	5.17	4.42	2256.81	1371.93
5													
6	5050.000	530.00	0.0	0.0	615.00	1110.00	622.48	0.0	622.61	9.02	4.88	868.45	369.56
7	5050.000	530.00	0.0	0.0	615.00	1720.00	623.33	0.0	623.71	8.69	5.24	1214.68	583.61
8	5050.000	530.00	0.0	0.0	615.00	2120.00	624.27	0.0	624.39	8.14	5.35	1442.74	743.26
9	5050.000	530.00	0.0	0.0	615.00	3120.00	626.36	0.0	626.45	5.41	4.99	2177.82	1340.84
10													
11	5520.000	470.00	0.0	0.0	615.00	1110.00	622.87	0.0	622.97	6.08	3.25	686.52	450.19
12	5520.000	470.00	0.0	0.0	615.00	1720.00	623.95	0.0	624.06	6.73	3.84	916.88	663.22
13	5520.000	470.00	0.0	0.0	615.00	2120.00	624.62	0.0	624.76	6.74	4.09	1068.66	816.58
14	5520.000	470.00	0.0	0.0	615.00	3120.00	626.59	0.0	626.73	5.21	4.21	1546.32	1367.21
15													
16	6100.000	580.00	0.0	0.0	616.50	1110.00	623.27	0.0	623.38	8.04	3.39	610.54	391.53
17	6100.000	580.00	0.0	0.0	616.50	1720.00	624.37	0.0	624.52	8.42	3.98	811.38	592.69
18	6100.000	580.00	0.0	0.0	616.50	2120.00	625.04	0.0	625.21	8.47	4.27	931.33	728.32
19	6100.000	580.00	0.0	0.0	616.50	3120.00	626.92	0.0	627.11	7.21	4.64	1265.79	1161.56
20													
21	6320.000	220.00	0.0	0.0	616.00	1110.00	623.37	0.0	623.60	9.34	4.68	376.20	363.23
22	6320.000	220.00	0.0	0.0	616.00	1720.00	624.43	0.0	624.93	13.68	6.24	445.89	465.02
23	6320.000	220.00	0.0	0.0	616.00	2120.00	625.06	0.0	625.70	16.00	7.10	488.05	529.93
24	6320.000	220.00	0.0	0.0	616.00	3120.00	626.79	0.0	627.72	18.34	8.59	609.18	728.53
25													
26	6370.000	50.00	0.0	0.0	615.10	1110.00	623.65	0.0	623.74	2.10	2.34	474.23	765.69
27	6370.000	50.00	0.0	0.0	615.10	1720.00	624.91	0.0	625.06	3.26	3.16	543.91	950.07
28	6370.000	50.00	0.0	0.0	615.10	2120.00	625.66	0.0	625.86	3.95	3.62	585.78	1066.86
29	6370.000	50.00	0.0	0.0	615.10	3120.00	627.65	0.0	627.95	5.03	4.49	695.24	1391.78
30													
31	6446.000	76.00	629.10	627.60	615.10	1110.00	623.65	0.0	623.74	2.10	2.34	474.32	766.11
32	6446.000	76.00	629.10	627.60	615.10	1720.00	624.91	0.0	625.07	3.27	3.16	544.13	950.68
33	6446.000	76.00	629.10	627.60	615.10	2120.00	625.67	0.0	625.87	3.94	3.62	586.08	1067.70
34	6446.000	76.00	629.10	627.60	615.10	3120.00	628.03	0.0	628.32	4.57	4.35	717.12	1459.88
35													
36	6496.000	50.00	0.0	0.0	615.10	1110.00	623.66	0.0	623.75	2.68	2.60	749.29	678.33
37	6496.000	50.00	0.0	0.0	615.10	1720.00	624.93	0.0	625.08	3.65	3.59	939.49	900.27
38	6496.000	50.00	0.0	0.0	615.10	2120.00	625.70	0.0	625.89	4.09	4.01	1054.84	1047.71
39	6496.000	50.00	0.0	0.0	615.10	3120.00	628.15	0.0	628.36	3.92	4.52	1421.38	1575.70
40													
41	7796.000	1300.00	0.0	0.0	614.90	1110.00	624.05	0.0	624.11	2.78	2.67	1252.30	665.57
42	7796.000	1300.00	0.0	0.0	614.90	1720.00	625.44	0.0	625.53	3.06	3.34	1682.05	983.14
43	7796.000	1300.00	0.0	0.0	614.90	2120.00	626.28	0.0	626.37	3.11	3.56	1947.11	1202.08
44	7796.000	1300.00	0.0	0.0	614.90	3120.00	628.70	0.0	628.79	2.56	3.71	2749.40	1949.48
45													
46	8096.000	300.00	0.0	0.0	615.50	1110.00	623.96	0.0	624.36	11.03	5.42	367.75	334.25
47	8096.000	300.00	0.0	0.0	615.50	1720.00	625.33	0.0	625.81	11.83	6.27	675.30	500.16
48	8096.000	300.00	0.0	0.0	615.50	2120.00	626.10	0.0	626.53	10.83	6.37	898.56	644.24
49	8096.000	300.00	0.0	0.0	615.50	3120.00	628.66	0.0	628.97	6.87	5.90	1578.73	1190.45
50													
51	8896.000	800.00	0.0	0.0	616.90	1110.00	624.81	0.0	625.30	17.66	7.00	480.28	268.15
52	8896.000	800.00	0.0	0.0	616.90	1720.00	626.34	0.0	626.79	14.01	6.97	924.88	459.60
53	8896.000	800.00	0.0	0.0	616.90	2120.00	627.12	0.0	627.52	12.57	6.97	1176.05	597.91
54	8896.000	800.00	0.0	0.0	616.90	3120.00	629.26	0.0	629.54	8.39	6.49	1891.43	1077.19
55													
56													
57													

SECNO	XLCH	ELTRD	ELLC	ELMIN	Q	CWSEL	CRIWS	EG	10K*S	VCH	AREA	.01K
9546.000	650.00	0.0	0.0	617.30	1110.00	626.04	0.0	626.25	7.45	4.79	805.80	406.74
9546.000	650.00	0.0	0.0	617.30	1720.00	627.26	0.0	627.45	7.02	5.09	1222.70	649.40
9546.000	650.00	0.0	0.0	617.30	2120.00	627.93	0.0	628.13	6.76	5.23	1469.02	815.34
9546.000	650.00	0.0	0.0	617.30	3120.00	629.85	0.0	629.98	5.22	5.14	2174.64	1365.70
12076.000	2530.00	0.0	0.0	618.90	1110.00	628.01	0.0	628.11	7.64	3.52	997.64	401.46
12076.000	2530.00	0.0	0.0	618.90	1720.00	629.03	0.0	629.12	6.71	3.67	1509.46	663.79
12076.000	2530.00	0.0	0.0	618.90	2120.00	629.63	0.0	629.72	6.28	3.75	1824.45	846.22
12076.000	2530.00	0.0	0.0	618.90	3120.00	631.11	0.0	631.18	4.76	3.69	2675.43	1426.71
12826.000	750.00	0.0	0.0	621.70	1110.00	628.63	0.0	628.93	14.49	5.22	533.06	291.58
12826.000	750.00	0.0	0.0	621.70	1720.00	629.56	0.0	629.97	17.43	6.32	735.80	411.93
12826.000	750.00	0.0	0.0	621.70	2120.00	630.11	0.0	630.57	18.50	6.85	863.67	492.92
12826.000	750.00	0.0	0.0	621.70	3120.00	631.43	0.0	631.93	18.18	7.58	1211.93	731.73
13976.000	1150.00	0.0	0.0	623.60	1110.00	630.30	0.0	630.56	15.95	5.24	455.42	277.94
13976.000	1150.00	0.0	0.0	623.60	1720.00	631.57	0.0	632.00	21.16	6.79	551.36	373.93
13976.000	1150.00	0.0	0.0	623.60	2120.00	632.26	0.0	632.80	24.31	7.69	603.28	429.99
13976.000	1150.00	0.0	0.0	623.60	3120.00	633.62	0.0	634.50	32.24	9.77	706.57	549.47
14026.000	50.00	0.0	0.0	623.60	1110.00	630.45	0.0	630.64	9.64	3.49	316.12	357.51
14026.000	50.00	0.0	0.0	623.60	1720.00	631.81	0.0	632.11	12.04	4.40	390.53	495.77
14026.000	50.00	0.0	0.0	623.60	2120.00	632.57	0.0	632.94	13.41	4.92	430.66	578.85
14026.000	50.00	0.0	0.0	623.60	3120.00	634.13	0.0	634.70	16.66	6.07	513.87	764.32
14100.000	74.00	636.60	632.10	623.60	1110.00	630.46	0.0	630.64	9.60	3.48	318.58	358.34
14100.000	74.00	636.60	632.10	623.60	1720.00	632.17	0.0	632.45	10.33	4.20	409.83	535.18
14100.000	74.00	636.60	632.10	623.60	2120.00	633.21	0.0	633.53	10.53	4.56	464.94	653.18
14100.000	74.00	636.60	632.10	623.60	3120.00	635.81	0.0	636.23	10.11	5.17	603.13	981.11
14150.000	50.00	0.0	0.0	623.70	1110.00	630.36	0.0	630.57	25.18	6.33	370.34	221.22
14150.000	50.00	0.0	0.0	623.70	1720.00	632.16	0.0	632.50	18.96	6.49	642.52	394.97
14150.000	50.00	0.0	0.0	623.70	2120.00	633.23	0.0	633.55	16.44	6.57	805.92	522.92
14150.000	50.00	0.0	0.0	623.70	3120.00	635.91	0.0	636.29	11.77	6.60	1216.75	909.55
14660.000	510.00	0.0	0.0	623.20	1110.00	631.27	0.0	631.33	2.92	2.89	1630.07	649.49
14660.000	510.00	0.0	0.0	623.20	1720.00	632.50	0.0	632.93	1.72	2.51	2790.32	1312.84
14660.000	510.00	0.0	0.0	623.20	2120.00	633.21	0.0	633.93	1.35	2.38	3508.16	1826.43
14660.000	510.00	0.0	0.0	623.20	3120.00	635.43	0.0	636.51	0.61	2.14	5358.59	3461.59
16305.000	1645.00	0.0	0.0	623.40	1110.00	631.89	0.0	632.31	11.45	5.70	479.35	328.02
16305.000	1645.00	0.0	0.0	623.40	1720.00	633.22	0.0	633.66	11.72	6.39	808.74	502.39
16305.000	1645.00	0.0	0.0	623.40	2120.00	634.14	0.0	634.55	10.54	6.45	1044.53	652.87
16305.000	1645.00	0.0	0.0	623.40	3120.00	636.50	0.0	636.90	7.15	6.14	1712.16	1166.63
17730.000	1425.00	0.0	0.0	626.50	1110.00	633.57	0.0	633.82	10.30	4.37	391.02	345.81
17730.000	1425.00	0.0	0.0	626.50	1720.00	634.95	0.0	635.32	12.50	5.43	508.48	486.57
17730.000	1425.00	0.0	0.0	626.50	2120.00	635.73	0.0	636.18	13.60	6.01	576.98	574.78
17730.000	1425.00	0.0	0.0	626.50	3120.00	638.72	0.0	639.30	14.15	6.98	760.58	829.37
17780.000	50.00	0.0	0.0	626.50	1110.00	633.78	0.0	633.89	5.34	2.94	378.10	480.15
17780.000	50.00	0.0	0.0	626.50	1720.00	635.22	0.0	635.42	6.38	3.54	486.42	680.82
17780.000	50.00	0.0	0.0	626.50	2120.00	636.06	0.0	636.29	6.80	3.83	553.39	813.22
17780.000	50.00	0.0	0.0	626.50	3120.00	638.16	0.0	638.44	6.34	4.25	733.42	1238.90

	SECNO	XLCH	ELTRD	ELLC	ELMIN	Q	CWSEL	CRIWS	EG	10K*S	VCH	AREA	.01K
1	17826.000	46.00	642.30	640.00	626.50	1110.00	633.77	0.0	633.90	5.32	2.93	378.80	481.39
2	17826.000	46.00	642.30	640.00	626.50	1720.00	635.24	0.0	635.43	6.34	3.53	487.52	682.94
3	17826.000	46.00	642.30	640.00	626.50	2120.00	636.06	0.0	636.31	6.75	3.82	554.75	815.97
4	17826.000	46.00	642.30	640.00	626.50	3120.00	638.18	0.0	638.46	6.30	4.24	735.07	1243.39
5													
6	17876.000	50.00	0.0	0.0	626.50	1110.00	633.74	0.0	633.97	13.56	5.12	612.05	301.41
7	17876.000	50.00	0.0	0.0	626.50	1720.00	635.29	0.0	635.48	12.41	5.55	865.20	488.23
8	17876.000	50.00	0.0	0.0	626.50	2120.00	636.17	0.0	636.36	11.86	5.79	1015.47	615.59
9	17876.000	50.00	0.0	0.0	626.50	3120.00	638.32	0.0	638.52	10.15	6.12	1390.38	979.45
10													
11	18500.000	624.00	0.0	0.0	627.30	1110.00	634.53	0.0	634.90	16.01	5.84	544.61	277.42
12	18500.000	624.00	0.0	0.0	627.30	1720.00	635.95	0.0	636.30	14.01	6.24	838.94	459.46
13	18500.000	624.00	0.0	0.0	627.30	2120.00	636.76	0.0	637.13	13.01	6.43	1018.46	587.84
14	18500.000	624.00	0.0	0.0	627.30	3120.00	638.83	0.0	639.16	10.51	6.65	1474.26	962.21
15													
16	20180.000	1680.00	0.0	0.0	630.60	1110.00	636.60	0.0	637.00	11.13	4.55	604.46	332.73
17	20180.000	1680.00	0.0	0.0	630.60	1720.00	637.92	0.0	638.11	9.72	4.79	922.42	551.74
18	20180.000	1680.00	0.0	0.0	630.60	2120.00	638.60	0.0	638.76	8.83	4.86	1123.81	713.41
19	20180.000	1680.00	0.0	0.0	630.60	3120.00	640.28	0.0	640.44	6.77	4.66	1647.10	1198.99
20													
21	22010.000	1830.00	0.0	0.0	632.60	1110.00	638.68	0.0	639.03	12.14	4.90	294.93	316.54
22	22010.000	1830.00	0.0	0.0	632.60	1720.00	639.73	0.0	640.30	10.38	6.33	370.36	425.00
23	22010.000	1830.00	0.0	0.0	632.60	2120.00	640.29	0.0	641.01	18.90	7.16	412.17	487.67
24	22010.000	1830.00	0.0	0.0	632.60	3120.00	641.51	0.0	642.60	23.86	8.88	506.77	638.71
25													
26	22060.000	50.00	0.0	0.0	632.60	1110.00	638.75	0.0	639.15	31.74	5.03	220.46	197.04
27	22060.000	50.00	0.0	0.0	632.60	1720.00	639.85	0.0	640.44	42.14	6.24	275.62	264.96
28	22060.000	50.00	0.0	0.0	632.60	2120.00	640.42	0.0	641.15	48.19	6.91	306.98	305.40
29	22060.000	50.00	0.0	0.0	632.60	3120.00	641.76	0.0	642.79	58.21	8.14	383.49	408.92
30													
31	22146.000	86.00	652.90	650.90	632.60	1110.00	638.72	0.0	639.16	30.93	4.99	222.61	199.60
32	22146.000	86.00	652.90	650.90	632.60	1720.00	639.90	0.0	640.49	40.76	6.16	279.13	269.42
33	22146.000	86.00	652.90	650.90	632.60	2120.00	640.71	0.0	641.22	46.27	6.80	311.75	311.66
34	22146.000	86.00	652.90	650.90	632.60	3120.00	641.69	0.0	642.68	55.24	7.97	391.26	419.79
35													
36	22196.000	50.00	0.0	0.0	632.60	1110.00	639.14	0.0	639.31	8.79	3.81	480.02	374.31
37	22196.000	50.00	0.0	0.0	632.60	1720.00	640.43	0.0	640.66	10.37	4.58	624.97	534.19
38	22196.000	50.00	0.0	0.0	632.60	2120.00	641.15	0.0	641.45	11.17	5.15	710.11	634.32
39	22196.000	50.00	0.0	0.0	632.60	3120.00	642.72	0.0	643.17	12.38	6.09	916.38	887.94
40													
41	23295.000	1100.00	0.0	0.0	633.00	1110.00	640.01	0.0	640.22	8.82	4.56	728.27	373.65
42	23295.000	1100.00	0.0	0.0	633.00	1720.00	641.38	0.0	641.55	7.66	4.62	1184.41	646.34
43	23295.000	1100.00	0.0	0.0	633.00	2120.00	642.10	0.0	642.31	6.44	4.67	1448.21	835.25
44	23295.000	1100.00	0.0	0.0	633.00	3120.00	643.87	0.0	644.01	5.45	4.83	2047.90	1336.12
45													
46	24095.000	800.00	0.0	0.0	632.70	1110.00	640.01	0.0	641.06	12.05	5.74	340.24	319.71
47	24095.000	800.00	0.0	0.0	632.70	1720.00	641.61	0.0	642.37	13.99	6.81	623.17	459.91
48	24095.000	800.00	0.0	0.0	632.70	2120.00	642.53	0.0	643.06	13.25	6.98	860.96	582.48
49	24095.000	800.00	0.0	0.0	632.70	3120.00	644.19	0.0	644.61	10.59	6.94	1429.64	956.55
50													
51	25665.000	1572.00	0.0	0.0	634.40	900.00	642.24	0.0	642.44	5.21	3.93	444.49	331.89
52	25665.000	1572.00	0.0	0.0	634.40	1410.00	643.71	0.0	643.96	6.98	4.85	748.21	533.53
53	25665.000	1572.00	0.0	0.0	634.40	1740.00	644.36	0.0	644.63	7.29	5.19	896.74	644.52
54	25665.000	1572.00	0.0	0.0	634.40	2610.00	645.74	0.0	646.06	8.09	5.98	1232.48	917.63
55													
56													
57													

SECNO	XLOB	ELTRD	ELLC	ELMIN	Q	CWSEL	CRITWS	EG	10K*S	VCH	AREA	.01K
26728.000	1060.00	0.0	0.0	635.40	800.00	642.32	0.0	642.89	3.88	3.11	853.74	405.95
26728.000	1060.00	0.0	0.0	635.40	1410.00	644.37	0.0	644.45	3.89	3.55	1307.94	714.73
26728.000	1060.00	0.0	0.0	635.40	1740.00	645.05	0.0	645.13	3.95	3.76	1512.57	875.99
26728.000	1060.00	0.0	0.0	635.40	2610.00	646.50	0.0	646.60	4.24	4.29	1957.48	1267.68
28628.000	1900.00	0.0	0.0	638.20	800.00	644.10	642.81	644.99	57.31	8.35	160.20	105.67
28628.000	1900.00	0.0	0.0	638.20	1410.00	645.73	0.0	646.11	26.78	6.87	664.56	272.47
28628.000	1900.00	0.0	0.0	638.20	1740.00	646.39	0.0	646.66	21.14	6.50	881.10	378.43
28628.000	1900.00	0.0	0.0	638.20	2610.00	647.83	0.0	648.05	15.23	6.22	1365.55	668.76
29488.000	860.00	0.0	0.0	641.80	500.00	647.70	0.0	647.86	12.80	4.93	384.95	139.75
29488.000	860.00	0.0	0.0	641.80	890.00	648.31	0.0	648.56	20.47	6.67	523.09	196.71
29488.000	860.00	0.0	0.0	641.80	1100.00	648.63	0.0	648.91	22.55	7.22	597.55	231.64
29488.000	860.00	0.0	0.0	641.80	1550.00	649.55	0.0	649.78	19.46	7.31	824.39	351.33
30818.000	1330.00	0.0	0.0	643.20	400.00	648.91	0.0	649.08	5.23	3.60	175.31	174.90
30818.000	1330.00	0.0	0.0	643.20	710.00	650.19	0.0	650.51	7.95	5.08	227.49	251.82
30818.000	1330.00	0.0	0.0	643.20	880.00	650.74	0.0	651.16	9.32	5.79	250.15	288.29
30818.000	1330.00	0.0	0.0	643.20	1230.00	651.62	0.0	652.15	10.95	6.76	348.34	371.64
30868.000	50.00	0.0	0.0	643.20	400.00	648.82	0.0	649.19	12.84	4.50	88.86	111.64
30868.000	50.00	0.0	0.0	643.20	710.00	650.07	0.0	650.75	22.64	6.57	108.00	149.22
30868.000	50.00	0.0	0.0	643.20	880.00	650.56	0.0	651.47	28.16	7.58	116.04	165.82
30868.000	50.00	0.0	0.0	643.20	1230.00	651.63	0.0	652.28	15.53	7.27	329.65	312.08
30921.000	53.00	653.20	651.20	643.20	400.00	646.94	0.0	649.26	16.26	4.66	85.82	99.21
30921.000	53.00	653.20	651.20	643.20	710.00	650.16	0.0	650.97	39.79	7.19	98.72	112.55
30921.000	53.00	653.20	651.20	643.20	880.00	652.55	0.0	653.13	13.90	5.94	148.10	236.00
30921.000	53.00	653.20	651.20	643.20	1230.00	654.31	0.0	654.52	4.02	4.46	603.66	613.77

BELL BRANCH LIVONIA CITY

SUMMARY PRINTOUT TABLE 150

SECNO	Q	CWSEL	DIFWSP	DIFWSX	DIFKWS	TOPWID	XLCH
0.0	1650.00	616.70	0.0	0.0	0.0	100.64	0.0
0.0	2900.00	619.20	2.50	0.0	0.0	146.19	0.0
0.0	3600.00	620.50	1.30	0.0	0.0	169.87	0.0
0.0	5500.00	624.00	3.50	0.0	0.0	233.62	0.0
50.000	1650.00	617.14	0.0	0.44	0.0	121.92	50.00
50.000	2900.00	619.69	2.56	0.49	0.0	196.21	50.00
50.000	3600.00	620.97	1.28	0.47	0.0	200.00	50.00
50.000	5500.00	624.32	3.35	0.32	0.0	200.00	50.00
120.000	1650.00	617.15	0.0	0.01	0.0	122.45	70.00
120.000	2900.00	619.94	2.79	0.25	0.0	200.00	70.00
120.000	3600.00	621.29	1.34	0.32	0.0	200.00	70.00
120.000	5500.00	624.40	3.11	0.08	0.0	200.00	70.00
170.000	1650.00	617.11	0.0	-0.05	0.0	194.47	50.00
170.000	2900.00	619.89	2.79	-0.05	0.0	206.78	50.00
170.000	3600.00	621.23	1.34	-0.05	0.0	215.66	50.00
170.000	5500.00	624.34	3.10	-0.06	0.0	231.60	50.00
640.000	1650.00	617.28	0.0	0.17	0.0	192.32	470.00
640.000	2900.00	620.14	2.86	0.24	0.0	332.69	470.00
640.000	3600.00	621.51	1.37	0.27	0.0	360.13	470.00
640.000	5500.00	624.74	3.23	0.40	0.0	424.81	470.00
1950.000	1650.00	618.53	0.0	1.25	0.0	372.22	1310.00
1950.000	2900.00	621.09	2.56	0.96	0.0	400.46	1310.00
1950.000	3600.00	622.29	1.20	0.78	0.0	410.90	1310.00
1950.000	5500.00	625.28	2.99	0.54	0.0	437.01	1310.00
2750.000	1650.00	618.79	0.0	0.25	0.0	305.70	800.00
2750.000	2900.00	621.30	2.51	0.20	0.0	393.37	800.00
2750.000	3600.00	622.45	1.15	0.19	0.0	413.02	800.00
2750.000	5500.00	625.43	2.95	0.15	0.0	462.34	800.00
3950.000	1650.00	620.76	0.0	1.97	0.0	598.62	1200.00
3950.000	2900.00	622.35	1.59	1.05	0.0	621.56	1200.00
3950.000	3600.00	623.29	0.94	0.91	0.0	635.20	1200.00
3950.000	5500.00	625.91	2.62	0.48	0.0	685.41	1200.00
4520.000	1110.00	621.58	0.0	0.83	0.0	244.87	570.00
4520.000	1720.00	622.79	1.21	0.44	0.0	326.13	570.00
4520.000	2120.00	623.61	0.82	0.32	0.0	380.61	570.00
4520.000	3120.00	626.08	2.47	0.17	0.0	483.65	570.00
5050.000	1110.00	622.49	0.0	0.90	0.0	307.21	530.00
5050.000	1720.00	623.58	1.10	0.79	0.0	323.67	530.00
5050.000	2120.00	624.27	0.69	0.66	0.0	334.63	530.00
5050.000	3120.00	626.36	2.09	0.29	0.0	370.89	530.00
5520.000	1110.00	622.87	0.0	0.39	0.0	207.31	470.00
5520.000	1720.00	623.95	1.08	0.37	0.0	221.25	470.00
5520.000	2120.00	624.62	0.67	0.35	0.0	230.03	470.00
5520.000	3120.00	626.59	1.97	0.23	0.0	254.06	470.00

	SECNO	U	CWSEL	DIFWSP	DIFWSX	DIFKWS	TOPWID	XLCH
1	6100.000	1110.00	623.27	0.0	0.40	0.0	180.00	560.00
2	6100.000	1720.00	624.37	1.11	0.43	0.0	180.00	560.00
3	6100.000	2120.00	625.04	0.67	0.42	0.0	180.00	560.00
4	6100.000	3120.00	626.92	1.87	0.33	0.0	180.00	580.00
5								
6	6320.000	1110.00	623.37	0.0	0.11	0.0	64.73	220.00
7	6320.000	1720.00	624.43	1.06	0.06	0.0	66.89	220.00
8	6320.000	2120.00	625.06	0.62	0.02	0.0	66.17	220.00
9	6320.000	3120.00	626.79	1.73	-0.13	0.0	71.70	220.00
10								
11	6370.000	1110.00	623.65	0.0	0.28	0.0	55.46	50.00
12	6370.000	1720.00	624.91	1.26	0.47	0.0	55.46	50.00
13	6370.000	2120.00	625.66	0.75	0.60	0.0	55.46	50.00
14	6370.000	3120.00	627.63	1.97	0.84	0.0	55.46	50.00
15								
16	6446.000	1110.00	623.65	0.0	0.00	0.0	55.46	76.00
17	6446.000	1720.00	624.91	1.26	0.00	0.0	55.46	76.00
18	6446.000	2120.00	625.67	0.76	0.01	0.0	55.46	76.00
19	6446.000	3120.00	628.03	2.36	0.40	0.0	55.46	76.00
20								
21	6496.000	1110.00	623.66	0.0	0.00	0.0	150.40	50.00
22	6496.000	1720.00	624.93	1.27	0.02	0.0	150.40	50.00
23	6496.000	2120.00	625.70	0.76	0.03	0.0	150.40	50.00
24	6496.000	3120.00	628.13	2.43	0.10	0.0	150.40	50.00
25								
26	7796.000	1110.00	624.05	0.0	0.39	0.0	301.15	1300.00
27	7796.000	1720.00	625.44	1.40	0.52	0.0	314.00	1300.00
28	7796.000	2120.00	626.28	0.83	0.56	0.0	321.51	1300.00
29	7796.000	3120.00	628.70	2.42	0.57	0.0	343.23	1300.00
30								
31	8096.000	1110.00	623.96	0.0	-0.09	0.0	173.66	300.00
32	8096.000	1720.00	625.33	1.37	-0.12	0.0	257.62	300.00
33	8096.000	2120.00	626.15	0.85	-0.10	0.0	264.47	300.00
34	8096.000	3120.00	628.66	2.48	-0.04	0.0	284.30	300.00
35								
36	8896.000	1110.00	624.90	0.0	0.95	0.0	296.07	800.00
37	8896.000	1720.00	626.34	1.44	1.01	0.0	317.95	800.00
38	8896.000	2120.00	627.12	0.78	0.94	0.0	324.37	800.00
39	8896.000	3120.00	629.26	2.15	0.60	0.0	341.97	800.00
40								
41	9546.000	1110.00	626.04	0.0	1.14	0.0	334.58	650.00
42	9546.000	1720.00	627.26	1.22	0.92	0.0	351.59	650.00
43	9546.000	2120.00	627.95	0.69	0.83	0.0	361.27	650.00
44	9546.000	3120.00	629.83	1.88	0.57	0.0	387.65	650.00
45								
46	12075.000	1110.00	628.01	0.0	1.97	0.0	477.85	2530.00
47	12075.000	1720.00	629.03	1.02	1.77	0.0	522.62	2530.00
48	12075.000	2120.00	629.63	0.60	1.68	0.0	548.35	2530.00
49	12075.000	3120.00	631.11	1.49	1.28	0.0	586.10	2530.00
50								
51	12282.000	1110.00	628.53	0.0	0.62	0.0	203.61	750.00
52	12226.000	1720.00	629.56	0.94	0.53	0.0	228.48	750.00
53	12825.000	2120.00	630.11	0.54	0.48	0.0	243.41	750.00
54	12826.000	3120.00	631.43	1.32	0.31	0.0	285.14	750.00
55								
56								
57								

SECNO	Q	CWSEL	DIFWSP	DIFWSX	DIFKWS	TOPWID	XLCH
13976.000	1110.00	630.30	0.0	1.67	0.0	75.60	1150.00
13976.000	1720.00	631.57	1.27	2.01	0.0	75.60	1150.00
13976.000	2120.00	632.26	0.69	2.15	0.0	75.60	1150.00
13976.000	3120.00	633.62	1.36	2.20	0.0	75.60	1150.00
14026.000	1110.00	630.45	0.0	0.15	0.0	53.10	50.00
14026.000	1720.00	631.81	1.36	0.24	0.0	53.10	50.00
14026.000	2120.00	632.57	0.76	0.31	0.0	53.10	50.00
14026.000	3120.00	634.13	1.57	0.51	0.0	53.10	50.00
14100.000	1110.00	630.46	0.0	0.01	0.0	53.10	74.00
14100.000	1720.00	632.17	1.72	0.36	0.0	53.10	74.00
14100.000	2120.00	633.21	1.04	0.65	0.0	53.10	74.00
14100.000	3120.00	635.81	2.60	1.68	0.0	53.10	74.00
14150.000	1110.00	630.38	0.0	-0.08	0.0	153.00	50.00
14150.000	1720.00	632.16	1.78	-0.01	0.0	153.00	50.00
14150.000	2120.00	633.23	1.07	0.02	0.0	153.00	50.00
14150.000	3120.00	635.91	2.69	0.10	0.0	153.00	50.00
14660.000	1110.00	631.27	0.0	0.89	0.0	704.43	510.00
14660.000	1720.00	632.90	1.63	0.74	0.0	710.17	510.00
14660.000	2120.00	633.91	1.01	0.68	0.0	713.70	510.00
14660.000	3120.00	636.49	2.58	0.58	0.0	722.72	510.00
16305.000	1110.00	631.89	0.0	0.62	0.0	235.39	1645.00
16305.000	1720.00	633.22	1.33	0.32	0.0	253.58	1645.00
16305.000	2120.00	634.14	0.92	0.23	0.0	260.76	1645.00
16305.000	3120.00	636.60	2.46	0.11	0.0	260.10	1645.00
17730.000	1110.00	633.57	0.0	1.68	0.0	82.70	1425.00
17730.000	1720.00	634.95	1.38	1.73	0.0	86.66	1425.00
17730.000	2120.00	635.73	0.78	1.59	0.0	89.19	1425.00
17730.000	3120.00	637.72	1.99	1.12	0.0	95.17	1425.00
17780.000	1110.00	633.76	0.0	0.19	0.0	70.05	50.00
17780.000	1720.00	635.22	1.47	0.27	0.0	77.67	50.00
17780.000	2120.00	636.06	0.84	0.33	0.0	82.03	50.00
17780.000	3120.00	638.16	2.10	0.44	0.0	87.10	50.00
17826.000	1110.00	633.77	0.0	0.01	0.0	70.10	46.00
17826.000	1720.00	635.24	1.47	0.02	0.0	77.75	46.00
17826.000	2120.00	636.08	0.84	0.02	0.0	82.12	46.00
17826.000	3120.00	638.18	2.10	0.02	0.0	87.10	46.00
17876.000	1110.00	633.79	0.0	0.02	0.0	167.83	50.00
17876.000	1720.00	635.29	1.51	0.05	0.0	170.52	50.00
17876.000	2120.00	636.17	0.88	0.09	0.0	172.10	50.00
17876.000	3120.00	638.32	2.15	0.14	0.0	175.95	50.00
18500.000	1110.00	634.53	0.0	0.75	0.0	203.30	624.00
18500.000	1720.00	635.95	1.42	0.66	0.0	212.16	624.00
18500.000	2120.00	636.78	0.84	0.62	0.0	217.39	624.00
18500.000	3120.00	638.83	2.05	0.51	0.0	230.12	624.00

SECNO	Q	CWSEL	DIFWSP	DIFWSX	DIFKWS	TOPWID	XLCH
20180.000	1110.00	636.80	0.0	2.27	0.0	274.41	1660.00
20180.000	1720.00	637.92	1.12	1.97	0.0	291.90	1660.00
20180.000	2120.00	638.60	0.68	1.82	0.0	300.73	1660.00
20180.000	3120.00	640.28	1.68	1.45	0.0	322.00	1660.00
22010.000	1110.00	638.68	0.0	1.88	0.0	70.30	1830.00
22010.000	1720.00	639.73	1.05	1.81	0.0	75.89	1830.00
22010.000	2120.00	640.29	0.56	1.69	0.0	75.57	1830.00
22010.000	3120.00	641.51	1.23	1.23	0.0	78.77	1830.00
22060.000	1110.00	638.75	0.0	0.07	0.0	48.80	50.00
22060.000	1720.00	639.83	1.08	0.11	0.0	52.59	50.00
22060.000	2120.00	640.42	0.58	0.13	0.0	54.63	50.00
22060.000	3120.00	641.76	1.34	0.25	0.0	59.30	50.00
22146.000	1110.00	638.79	0.0	0.04	0.0	48.95	86.00
22146.000	1720.00	639.90	1.11	0.07	0.0	52.82	86.00
22146.000	2120.00	640.51	0.61	0.09	0.0	54.93	86.00
22146.000	3120.00	641.69	1.39	0.13	0.0	59.76	86.00
22196.000	1110.00	639.14	0.0	0.35	0.0	110.35	50.00
22196.000	1720.00	640.43	1.29	0.53	0.0	115.59	50.00
22196.000	2120.00	641.15	0.72	0.64	0.0	121.22	50.00
22196.000	3120.00	642.76	1.61	0.87	0.0	133.88	50.00
23296.000	1110.00	640.01	0.0	0.86	0.0	326.44	1100.00
23296.000	1720.00	641.38	1.37	0.96	0.0	338.24	1100.00
23296.000	2120.00	642.16	0.77	1.01	0.0	343.79	1100.00
23296.000	3120.00	643.87	1.71	1.11	0.0	356.07	1100.00
24096.000	1110.00	640.61	0.0	0.60	0.0	162.61	800.00
24096.000	1720.00	641.61	1.20	0.43	0.0	307.16	800.00
24096.000	2120.00	642.53	0.72	0.38	0.0	335.33	800.00
24096.000	3120.00	644.19	1.66	0.32	0.0	351.88	800.00
25668.000	800.00	642.24	0.0	1.63	0.0	194.20	1572.00
25668.000	1410.00	643.71	1.47	1.90	0.0	219.57	1572.00
25668.000	1740.00	644.36	0.66	1.83	0.0	231.53	1572.00
25668.000	2610.00	645.74	1.38	1.56	0.0	255.74	1572.00
26728.000	800.00	642.82	0.0	0.58	0.0	287.79	1060.00
26728.000	1410.00	644.37	1.55	0.66	0.0	297.69	1060.00
26728.000	1740.00	645.05	0.68	0.69	0.0	302.05	1060.00
26728.000	2610.00	646.50	1.45	0.76	0.0	311.31	1060.00
28628.000	800.00	644.10	0.0	1.28	0.0	300.23	1900.00
28628.000	1410.00	645.73	1.63	1.36	0.0	319.59	1900.00
28628.000	1740.00	646.39	0.66	1.34	0.0	328.27	1900.00
28628.000	2610.00	647.83	1.44	1.33	0.0	346.89	1900.00
29488.000	500.00	647.70	0.0	3.50	0.0	213.33	860.00
29488.000	890.00	648.31	0.61	2.58	0.0	232.91	860.00
29488.000	1100.00	648.63	0.32	2.24	0.0	238.31	860.00
29488.000	1550.00	649.55	0.91	1.71	0.0	254.05	860.00

SECNO	Q	CWSEL	DIFWSP	DIFWSX	DIFKWS	TOPWID	XLCH
30818.000	400.00	648.91	0.0	1.21	0.0	41.00	1330.00
30818.000	710.00	650.19	1.27	1.67	1.27	41.00	1330.00
30818.000	880.00	650.74	0.55	2.11	1.53	41.00	1330.00
30818.000	1230.00	651.62	0.88	2.08	0.0	85.83	1330.00
30868.000	400.00	648.88	0.0	-0.04	0.0	16.00	50.00
30868.000	710.00	650.07	1.20	-0.11	1.20	16.00	50.00
30868.000	880.00	650.56	0.50	-0.16	1.70	16.00	50.00
30868.000	1230.00	651.63	1.05	0.00	0.0	102.00	50.00
30921.000	400.00	648.94	0.0	0.06	0.0	16.00	53.00
30921.000	710.00	650.16	1.22	0.09	1.22	16.00	53.00
30921.000	880.00	652.58	2.42	2.00	3.64	16.00	53.00
30921.000	1230.00	654.31	1.74	2.69	0.0	102.00	53.00

SUMMARY OF ERRORS

FLOOD INSURANCE ZONE DATA FOR BELL BRANCH LIVONIA CITY

FLOOD HAZARD FACTOR FOR ENTIRE REACH USING SECTIONS

SECTION NUMBER	CUMULATIVE DISTANCE	ELEVATION DIFFERENCE BETWEEN BASE FLOOD AND 10	2	0.2
0.0	0.	-3.80	-1.30	3.50
50.000	50.	-3.83	-1.28	3.35
120.000	120.	-4.14	-1.34	3.11
170.000	170.	-4.13	-1.34	3.10
640.000	640.	-4.23	-1.37	3.23
1950.000	1950.	-3.76	-1.20	2.99
2750.000	2750.	-3.69	-1.18	2.95
3950.000	3950.	-2.53	-0.94	2.62
4520.000	4520.	-2.02	-0.82	2.47
5050.000	5050.	-1.79	-0.69	2.09
5520.000	5520.	-1.75	-0.67	1.97
6100.000	6100.	-1.76	-0.67	1.87
6320.000	6320.	-1.65	-0.62	1.73
6370.000	6370.	-2.01	-0.75	1.97
6446.000	6446.	-2.02	-0.76	2.36
6496.000	6496.	-2.05	-0.78	2.43
7796.000	7796.	-2.23	-0.83	2.42
8096.000	8095.	-2.23	-0.85	2.48
8896.000	8896.	-2.22	-0.78	2.15
9546.000	9546.	-1.91	-0.69	1.88
12076.000	12076.	-1.62	-0.60	1.49
12826.000	12826.	-1.48	-0.54	1.32
13976.000	13975.	-1.96	-0.69	1.33
14026.000	14026.	-2.12	-0.76	1.97
14100.000	14100.	-2.76	-1.04	2.60
14150.000	14150.	-2.85	-1.07	2.69
14660.000	14660.	-2.64	-1.01	2.58
16305.000	16305.	-2.25	-0.92	2.46
17730.000	17731.	-2.16	-0.78	1.99
17780.000	17780.	-2.30	-0.84	2.10
17826.000	17826.	-2.31	-0.85	2.10
17876.000	17876.	-2.38	-0.88	2.15
18500.000	18500.	-2.25	-0.84	2.05
20180.000	20180.	-1.80	-0.68	1.68
22010.000	22010.	-1.61	-0.56	1.23
22060.000	22060.	-1.67	-0.58	1.34
22146.000	22146.	-1.72	-0.61	1.39
22196.000	22196.	-2.01	-0.72	1.61
23296.000	23296.	-2.14	-0.77	1.71
24096.000	24096.	-1.92	-0.72	1.66
25668.000	25668.	-2.13	-0.66	1.38
25728.000	25728.	-2.23	-0.68	1.45
25826.000	25826.	-2.29	-0.66	1.44
29488.000	29488.	-0.93	-0.32	0.91
30818.000	30818.	-1.83	-0.55	0.63
30868.000	30868.	-1.70	-0.50	1.05
30921.000	30921.	-3.64	-2.42	1.74
WEIGHTED AVG FOR REACH		-2.21	-0.78	1.94

FHF FOR THE REACH = 020 WITH 91.1 OF THE REACH WITHIN 1.0 FEET

ZONE FOR THE REACH = A 4

```
**************************************************
  HEC2 -RELEASE DATED NOV 76 UPDATED AUG1977
  ERROR CORR - 01,02
  MODIFICATION - 50,51,52,53
**************************************************
```

00BREAK00

1) COUNTY: Wayne

2) STUDY NAME: City of Livonia

3) WATERCOURSE: Tarabusi Creek

4) DOCUMENT TYPE: 100 - Year

00BREAK00

```
**********************************************************
  HEC2 RELEASE DATED NOV 76 UPDATED AUG1977
  ERROR CORR -  01,02
  MODIFICATION -  50,51,52,53
**********************************************************
C
T1 TARABUSI CREEK FIS HUD 2014 07 LIVONIA CITY FROM BELL BRANCH TO 8 MILE ROAD
T2 100YR FLOW
T3      TARABUSI CREEK LIVONIA C
```

J1	ICHECK	INQ	NINV	IDIR	STRT	METRIC	HVINS	Q	WSEL	FQ
	0.	4.	0.	0.	0.0	0.0	0.0	0.	620.000	0.0

J2	NPROF	IPLOT	PREVS	XSECV	XSECH	FN	ALLOC	IBW	CHNIM	ITRACE
	1.000	0.0	-1.000	0.0	0.0	0.0	0.0	0.0	0.0	0.0

J3 VARIABLE CODES FOR SUMMARY PRINTOUT

	110.000	150.000	200.000	0.0	0.0	0.0	0.0	0.0	0.0	0.0

QT	5.000	1070.000	1560.000	1770.000	1770.000	2060.000	0.0	0.0	0.0	0.0
ET	0.0	0.0	0.0	0.0	1.410	0.0	0.0	0.0	0.0	0.0
NC	0.100	0.100	0.040	0.300	0.500	0.0	0.0	0.0	0.0	0.0

SECNO 120 CORPS STA 050

X1	120.000	13.000	405.000	440.000	0.0	0.0	0.0	0.0	0.0	0.0
X3	0.0	0.0	0.0	250.000	0.0	540.000	0.0	0.0	0.0	0.0
GR	630.000	0.0	625.000	30.000	622.000	300.000	620.000	320.000	610.200	340.000
GR	619.200	360.000	616.400	405.000	613.200	410.000	616.000	426.000	618.100	440.000
GR	620.000	665.000	625.000	715.000	630.000	750.000	0.0	0.0	0.0	0.0

SECNO 370. X

X1	370.000	10.000	140.000	170.000	250.000	250.000	250.000	0.0	0.0	0.0
GR	630.000	0.0	625.000	35.000	620.000	70.000	618.000	140.000	617.000	150.000
GR	615.300	155.000	618.000	170.000	620.000	205.000	625.000	240.000	630.000	300.000

SECNO 745 X

X1	745.000	9.000	126.000	155.000	375.000	375.000	375.000	0.0	0.0	0.0
GR	630.000	0.0	625.000	50.000	620.000	90.000	618.000	126.000	615.700	140.000
GR	618.000	155.000	620.000	180.000	625.000	220.000	630.000	270.000	0.0	0.0
ET	0.0	0.0	0.0	0.0	9.100	0.0	0.0	0.0	1.000	264.000

SECNO 1120. STA 13+40

X1	1120.000	11.000	117.000	140.000	375.000	375.000	375.000	0.0	0.0	0.0
GR	635.000	0.0	630.000	25.000	625.000	65.000	620.000	110.000	618.000	117.000
GR	616.000	125.000	618.000	140.000	620.000	155.000	625.000	200.000	630.000	235.000
GR	635.000	265.000	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
ET	0.0	0.0	0.0	0.0	1.410	0.0	0.0	0.0	0.0	0.0

SECNO 1770 X

X1	1770.000	9.000	190.000	220.000	650.000	650.000	650.000	0.0	0.0	0.0
GR	635.000	0.0	630.000	50.000	625.000	150.000	618.000	190.000	617.000	205.000
GR	618.000	220.000	625.000	245.000	630.000	300.000	635.000	400.000	0.0	0.0
NC	0.120	0.120	0.040	0.300	0.500	0.0	0.0	0.0	0.0	0.0

SECNO 2416 50' D/S 6 MILE FROM CORPS NOTES AND QUAD MAP

X1	2416.000	9.000	271.000	300.000	646.000	646.000	646.000	0.0	0.0	0.0
GR	635.000	0.0	630.000	160.000	630.500	248.000	618.000	271.000	617.900	288.000
GR	618.000	300.000	632.400	341.000	630.000	410.000	635.000	510.000	0.0	0.0

SECNO 2466 D/S FACE 6 MILE FROM FIELD BOOKS AND QUAD MAP

X1	2466.000	21.000	371.600	445.400	50.000	50.000	50.000	0.0	0.0	0.0
X3	10.000	0.0	0.0	0.0	0.0	0.0	0.0	631.000	631.000	0.0
GR	635.000	0.0	630.000	288.000	625.400	371.600	625.400	371.700	625.400	377.600
GR	619.400	392.600	619.400	392.700	619.400	393.600	619.400	393.700	618.000	397.600
GR	617.900	408.000	618.000	418.400	619.400	422.400	619.400	422.500	619.400	423.400
GR	619.400	423.500	625.400	439.400	625.400	445.400	625.400	445.500	630.000	568.000
GR	635.000	832.000	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
SB	1.050	1.790	3.000	0.0	22.800	2.000	582.000	2.910	617.900	617.900

SECNO 2554 U/S FACE 6 MILE FROM FIELD BOOKS AND QUAD MAP

X1	2554.000	0.0	0.0	0.0	88.000	88.000	88.000	0.0	0.0	0.0
X2	0.0	0.0	1.000	629.400	632.600	0.0	0.0	0.0	0.0	0.0
X3	10.000	0.0	0.0	0.0	0.0	0.0	0.0	632.600	632.600	0.0
BT	16.000	0.0	635.000	0.0	288.000	632.600	0.0	371.600	632.600	625.400
BT	371.700	632.600	629.400	392.600	632.600	629.400	392.700	632.600	619.400	393.600
BT	632.600	619.400	393.700	632.600	629.400	422.400	632.600	629.400	422.500	632.600
BT	619.400	423.400	632.600	619.400	423.500	632.600	629.400	445.400	632.600	629.400
BT	445.500	632.600	625.400	568.000	632.600	0.0	832.000	635.000	0.0	0.0
NC	0.150	0.150	0.050	0.400	0.600	0.0	0.0	0.0	0.0	0.0

SECNO 2604 STA 25+20 50' U/S 6 MILE FROM CORPS NOTES AND QUAD MAP

X1	2604.000	12.000	177.500	220.500	50.000	50.000	50.000	0.0	0.0	0.0
X3	0.0	0.0	0.0	111.000	0.0	285.000	0.0	0.0	0.0	0.0
GR	635.000	0.0	635.000	40.000	630.000	55.000	625.000	90.000	621.500	177.500
GR	618.000	192.500	617.900	200.000	618.000	212.500	622.200	220.500	625.000	250.000
GR	630.000	265.000	635.000	450.000	0.0	0.0	0.0	0.0	0.0	0.0

SECNO 3360 X

X1	3360.000	10.000	180.000	223.000	600.000	550.000	756.000	0.0	0.0	0.0
GR	635.000	0.0	630.000	50.000	626.000	90.000	625.000	180.000	620.400	195.000
GR	620.300	200.000	620.400	215.000	625.000	223.000	627.500	300.000	635.000	340.000
NC	0.120	0.120	0.050	0.0	0.0	0.0	0.0	0.0	0.0	0.0
ET	0.0	7.100	9.100	9.100	9.100	9.100	140.000	255.000	123.000	273.000

SECNO 4116 200'D/S MIDDLEBELT FROM CORPS NOTES AND QUAD MAP

X1	4116.000	9.000	177.000	219.000	600.000	550.000	756.000	0.0	0.0	0.0
GR	635.000	0.0	630.000	80.000	626.200	177.000	622.700	191.000	622.600	195.000
GR	622.700	212.000	627.100	219.000	630.000	400.000	635.000	440.000	0.0	0.0
ET	0.0	0.0	0.0	0.0	9.100	0.0				

-	0.100	0.100	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
	SECNO 4316 STA 26+00 D/S FACE MIDDLEBELT SKEW BRIDGE FROM C.N. AND Q.M.									
X1	4316.000	13.000	42.300	57.800	300.000	100.000	200.000	0.0	0.0	0.0
X3	10.000	0.0	0.0	0.0	0.0	0.0	0.0	629.600	629.600	0.0
GR	650.000	0.0	634.000	1.000	633.700	2.000	632.600	32.000	622.700	42.300
GR	622.700	42.400	622.600	50.000	622.700	57.700	622.700	57.800	632.600	68.000
GR	633.700	98.000	634.000	99.000	650.000	100.000	0.0	0.0	0.0	0.0
SB	0.0	1.850	3.000	0.0	15.440	0.0	97.240	0.0	622.600	622.600
	SECNO 4403 U/S FACE MIDDLEBELT FROM CORPS NOTES AND QUAD MAPSKEW BR.									
X1	4403.000	0.0	0.0	0.0	87.000	87.000	87.000	0.0	0.0	0.0
X2	0.0	0.0	1.000	628.900	632.900	0.0	0.0	0.0	0.0	0.0
X3	10.000	0.0	0.0	0.0	0.0	0.0	0.0	632.900	632.900	0.0
BT	8.000	0.0	650.000	0.0	1.000	634.000	0.0	42.300	632.900	622.700
BT	42.400	635.400	628.900	57.700	635.400	628.900	57.800	632.900	622.700	99.000
BT	634.000	0.0	100.000	650.000	0.0	0.0	0.0	0.0	0.0	0.0
NC	0.0	0.0	0.0	0.400	0.600	0.0	0.0	0.0	0.0	0.0
ET	0.0	7.100	9.100	9.100	9.100	9.100	215.000	471.000	122.000	550.000
	SECNO 4453 STA 44+55 50' U/S MIDDLEBELT FROM CORPS NOTES AND QUAD MAP									
X1	4453.000	13.000	330.000	357.000	50.000	50.000	50.000	0.450	0.0	0.0
GR	640.000	0.0	635.000	100.000	630.000	150.000	630.000	260.000	625.000	310.000
GR	625.700	330.000	622.700	333.000	622.600	350.000	622.700	354.000	626.700	357.000
GR	625.000	480.000	630.000	510.000	635.000	550.000	0.0	0.0	0.0	0.0
ET	0.0	0.0	0.0	0.0	1.410	0.0	0.0	0.0	0.0	0.0
NC	0.100	0.100	0.040	0.0	0.0	0.0	0.0	0.0	0.0	0.0
	SECNO 5950 STA 59+50 FROM CORPS NOTES AND QUAD MAP									
X1	5950.000	11.000	235.000	265.000	1497.000	1497.000	1497.000	0.0	0.0	0.0
GR	640.000	0.0	632.000	70.000	630.000	235.000	627.000	240.000	626.700	245.000
GR	626.600	250.000	626.700	255.000	627.000	260.000	630.000	265.000	632.000	370.000
GR	640.000	410.000	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
	SECNO 6600 STA 66+00 FROM CORPS NOTES AND QUAD MAP									
X1	6600.000	7.000	110.000	165.000	650.000	500.000	650.000	0.0	0.0	0.0
GR	640.000	0.0	635.000	45.000	632.000	110.000	628.800	140.000	632.000	165.000
GR	635.000	350.000	640.000	400.000	0.0	0.0	0.0	0.0	0.0	0.0
	SECNO 7340 STA 73+40 FROM CORPS NOTES AND QUAD MAP									
X1	7340.000	9.000	200.000	222.000	740.000	740.000	740.000	0.0	0.0	0.0
GR	645.000	0.0	634.000	60.000	634.000	200.000	631.700	210.000	631.700	218.000
GR	634.000	222.000	634.000	300.000	640.000	320.000	645.000	345.000	0.0	0.0
	SECNO 8178 X									
X1	8178.000	9.000	210.000	240.000	837.000	808.000	730.000	0.0	0.0	0.0
GR	645.000	0.0	638.500	25.000	635.500	210.000	633.000	217.000	632.900	225.000
GR	633.000	232.000	635.500	240.000	640.000	365.000	645.000	425.000	0.0	0.0
	SECNO 8815 STA 88+15 FROM CORPS NOTES AND QUAD MAP									

Top of Trailing = 6354

X1	8815.000	10.000	210.000	253.000	840.000	810.000	737.000	0.0	0.0	0.0
GR	646.000	0.0	640.000	45.000	638.000	210.000	634.600	223.000	634.000	232.000
GR	634.600	242.000	638.000	253.000	640.000	355.000	644.000	415.000	646.000	590.000

SECNO 9276 X

X1	9276.000	10.000	205.000	250.000	461.000	461.000	461.000	0.0	-1.000	0.0
GR	655.000	0.0	643.000	95.000	640.000	205.000	636.100	223.000	635.900	230.000
GR	636.100	237.000	640.000	250.000	645.000	300.000	650.000	320.000	655.000	350.000

SECNO 9737 X

X1	9737.000	0.0	0.0	0.0	461.000	461.000	461.000	0.0	1.000	0.0

SECNO 10198 X

X1	10198.000	0.0	0.0	0.0	450.000	300.000	461.000	0.0	1.000	0.0

SECNO 10658 STA 106+90 50' D/S MERRIMAN FROM CORPS NOTES AND QUAD MAP

X1	10658.000	13.000	205.000	240.000	450.000	300.000	460.000	0.0	0.0	0.0
X3	0.0	0.0	0.0	183.000	0.0	263.000	0.0	0.0	0.0	0.0
GR	660.000	0.0	655.000	80.000	650.000	112.000	647.500	117.000	645.000	132.000
GR	642.500	205.000	637.900	226.000	637.800	232.000	637.900	238.000	642.500	240.000
GR	645.000	520.000	650.000	560.000	655.000	600.000	0.0	0.0	0.0	0.0

SECNO 10708 STA 107+40 D/S FACE MERRIMAN FROM CORPS NOTES AND QUAD MAP

X1	10708.000	18.000	208.000	272.000	50.000	50.000	50.000	0.0	0.0	0.0
X3	10.000	0.0	0.0	0.0	0.0	0.0	0.0	653.600	653.600	0.0
GR	660.000	0.0	655.000	65.000	652.000	130.000	645.500	208.000	645.500	208.100
GR	645.500	212.000	638.000	227.000	638.000	227.100	638.000	229.000	638.000	229.100
GR	638.000	251.000	638.000	251.100	638.000	253.000	638.000	253.100	645.500	268.000
GR	645.500	272.000	645.500	272.100	656.000	350.000	0.0	0.0	0.0	0.0
SB	1.250	1.300	3.000	0.0	26.000	2.000	793.700	2.280	638.000	638.000

SECNO 10782 U/S FACE MERRIMAN FROM CORPS NOTES AND QUAD MAP

X1	10782.000	0.0	0.0	0.0	74.000	74.000	74.000	0.0	0.0	0.0
X2	0.0	0.0	1.000	653.100	654.000	0.0	0.0	0.0	0.0	0.0
X3	10.000	0.0	0.0	0.0	0.0	0.0	0.0	654.000	655.000	0.0
BT	16.000	0.0	660.000	0.0	65.000	655.000	0.0	130.000	654.000	0.0
BT	208.000	654.200	645.500	208.100	654.200	653.100	227.000	654.200	653.100	227.100
BT	654.200	638.000	229.000	654.200	638.000	229.100	654.200	653.100	251.000	655.000
BT	653.100	251.100	655.000	638.000	253.000	655.000	638.000	253.100	655.000	653.100
BT	272.000	655.000	653.100	272.100	655.000	645.500	350.000	656.000	0.0	0.0
NC	0.100	0.100	0.040	0.300	0.500	0.0	0.0	0.0	0.0	0.0
QT	5.000	960.000	1410.000	1590.000	1590.000	1860.000	0.0	0.0	0.0	0.0

SECNO 10832 50' U/S MERRIMAN FROM CORPS NOTES AND QUAD MAP

X1	10832.000	13.000	197.000	247.000	50.000	50.000	50.000	0.0	0.0	0.0
X3	0.0	0.0	0.0	145.000	0.0	300.000	0.0	0.0	0.0	0.0
GR	660.000	0.0	655.000	80.000	650.000	112.000	647.500	117.000	645.000	132.000
GR	642.500	197.000	637.900	226.000	637.800	232.000	637.900	238.000	642.500	247.000
GR	645.000	520.000	650.000	560.000	655.000	600.000	0.0	0.0	0.0	0.0
NC	0.150	0.150	0.050	0.300	0.500	0.0	0.0	0.0	0.0	0.0

SECNO 11720

X1	11720.000	9.000	530.000	580.000	888.000	888.000	888.000	0.0	0.0	0.0
GR	660.000	150.000	646.000	375.000	646.500	530.000	642.800	550.000	642.700	560.000
GR	642.800	565.000	646.000	580.000	647.000	675.000	660.000	800.000	0.0	0.0

SECNO 12145 X

X1	12145.000	0.0	0.0	0.0	425.000	425.000	425.000	0.0	0.900	0.0

SECNO 12570 STA 126+20 FROM CORPS NOTES AND QUAD MAP

X1	12570.000	9.000	488.000	538.000	425.000	425.000	425.000	0.0	0.0	0.0
GR	660.000	0.0	650.000	272.000	648.800	412.000	647.800	483.000	645.800	488.000
GR	644.400	508.000	649.600	538.000	650.000	628.000	660.000	800.000	0.0	0.0

SECNO 12965 X

X1	12965.000	0.0	0.0	0.0	395.000	395.000	395.000	0.0	1.600	0.0
ET	0.0	0.0	0.0	0.0	9.100	0.0	0.0	0.0	1.000	824.000
NC	0.150	0.150	0.050	0.300	0.500	0.0	0.0	0.0	0.0	0.0

SECNO 13360 STA 159+20 FROM CORPS NOTES AND QUAD MAP

X1	13360.000	12.000	270.000	310.000	430.000	250.000	395.000	0.0	0.0	0.0
GR	665.000	0.0	660.000	35.000	655.000	165.000	650.000	270.000	649.200	282.000
GR	647.600	286.000	647.500	290.000	647.600	294.000	649.500	298.000	650.000	310.000
GR	655.000	400.000	662.000	430.000	0.0	0.0	0.0	0.0	0.0	0.0

SECNO 13704 X

X1	13704.000	0.0	0.0	0.0	209.000	344.000	344.000	0.0	1.800	0.0

SECNO 14047 X

X1	14047.000	0.0	0.0	0.0	208.000	343.000	343.000	0.0	1.800	0.0

VALLEY SECTION X

X1	14219.000	7.000	447.000	476.000	104.000	172.000	172.000	0.0	0.0	0.0
X3	0.0	0.0	0.0	400.000	0.0	524.000	0.0	0.0	0.0	0.0
GR	665.000	0.0	659.500	257.000	653.300	447.000	652.000	462.000	653.300	476.000
GR	659.500	570.000	665.000	570.000	0.0	0.0	0.0	0.0	0.0	0.0
NC	0.150	0.150	0.050	0.400	0.600	0.0	0.0	0.0	0.0	0.0

SECNO 14390 50' D/S 7 MILE FROM CORPS NOTES AND QUAD MAP SKEW

X1	14390.000	13.000	624.000	642.000	104.000	171.000	171.000	0.910	0.0	0.0
X3	0.0	0.0	0.0	612.000	0.0	654.000	0.0	0.0	0.0	0.0
GR	670.000	0.0	665.000	280.000	660.000	310.000	659.000	350.000	658.500	600.000
GR	653.000	624.000	652.900	634.000	653.000	642.000	655.400	655.000	656.500	660.000
GR	659.000	740.000	665.000	775.000	670.000	825.000	0.0	0.0	0.0	0.0

SECNO 14440 STA 174+50 D/S FACE 7 MILE FROM CORPS NOTES AND QUAD MAPSKEW

X1	14440.000	11.000	675.220	693.420	50.000	50.000	50.000	0.0	0.0	0.0
X3	10.000	.0	.	0.	.0	0.0	.0	6 .0	6 .0	.0

GR	670.000	599.000	665.000	600.000	654.500	675.220	654.500	675.320	652.900	686.140
GR	653.500	693.420	653.500	693.520	664.000	733.000	664.000	764.000	665.000	780.000
GR	670.000	781.000	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
SB	0.0	1.710	3.000	0.0	18.200	0.0	121.900	0.0	652.800	652.800

SECNO 14501 U/S FACE 7 MILE FROM CORPS NOTES AND QUAD MAP SKEW

X1	14501.000	0.0	0.0	0.0	61.000	61.000	61.000	0.0	0.0	0.0
X2	0.0	0.0	1.000	659.500	663.400	0.0	0.0	0.0	0.0	0.0
X3	10.000	0.0	0.0	0.0	0.0	0.0	0.0	663.600	663.600	0.0
BT	11.000	599.000	670.000	0.0	600.000	665.000	0.0	642.000	664.000	0.0
BT	675.220	663.400	654.500	675.320	663.400	659.500	693.420	663.400	659.500	693.520
BT	663.400	653.500	733.000	664.000	0.0	764.000	664.000	0.0	780.000	665.000
BT	0.0	781.000	670.000	0.0	0.0	0.0	0.0	0.0	0.0	0.0
ET	0.0	0.0	0.0	0.0	1.410	0.0	0.0	0.0	0.0	0.0

635
725
x 90ft weir

SECNO 14570 STA 175+10 69° U/S 7 MILE FROM CORPS NOTES AND QUAD MAP SKEW

X1	14570.000	7.000	325.000	346.000	69.000	69.000	69.000	0.910	0.0	0.0
X3	0.0	0.0	0.0	241.000	0.0	429.000	0.0	0.0	0.0	0.0
GR	670.000	0.0	660.000	140.000	655.600	325.000	651.800	342.000	655.600	346.000
GR	660.000	470.000	670.000	740.000	0.0	0.0	0.0	0.0	0.0	0.0

SECNO 15360 STA 184+40 FROM CORPS NOTES AND QUAD MAP

X1	15360.000	10.000	84.000	125.000	790.000	790.000	790.000	0.0	0.0	0.0
GR	670.000	0.0	660.000	30.000	658.000	40.000	657.500	84.000	656.500	110.000
GR	655.100	116.000	655.000	122.000	658.000	125.000	660.000	175.000	670.000	200.000

SECNO 16100 STA 192+60 FROM CORPS NOTES AND QUAD MAP

X1	16100.000	13.000	115.000	140.000	740.000	740.000	740.000	0.0	0.0	0.0
GR	672.000	0.0	670.000	30.000	666.000	40.000	663.000	60.000	662.000	115.000
GR	658.000	130.000	660.000	140.000	662.000	170.000	662.600	240.000	664.000	250.000
GR	666.000	450.000	670.000	480.000	672.000	510.000	0.0	0.0	0.0	0.0

SECNO 16500 X

X1	16500.000	8.000	173.000	209.000	550.000	275.000	400.000	0.0	0.0	0.0
GR	675.000	0.0	667.000	80.000	662.000	173.000	659.000	195.000	662.000	209.000
GR	663.500	310.000	670.000	510.000	675.000	600.000	0.0	0.0	0.0	0.0
NC	0.0	0.0	0.0	0.300	0.500	0.0	0.0	0.0	0.0	0.0

SECNO 16900 STA 201+70 FROM CORPS NOTES AND QUAD MAP

X1	16900.000	13.000	228.000	276.000	550.000	275.000	400.000	0.0	0.0	0.0
GR	680.000	0.0	675.000	90.000	670.000	130.000	666.000	170.000	664.000	228.000
GR	660.000	256.000	660.000	260.000	662.000	264.000	664.000	276.000	665.000	350.000
GR	670.000	580.000	675.000	680.000	680.000	900.000	0.0	0.0	0.0	0.0
NC	0.120	0.120	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

SECNO 17295 X

X1	17295.000	8.000	392.000	443.000	75.000	425.000	395.000	0.0	0.0	0.0
GR	680.000	0.0	672.000	190.000	667.500	330.000	666.500	392.000	662.400	420.000
GR	665.000	443.000	666.000	500.000	680.000	650.000	0.0	0.0	0.0	0.0

SECNO 17690 STA 210+80 FROM CORPS NOTES AND QUAD MAP

X1	17690.000	10.000	555.000	610.000	75.000	425.000	395.000	0.0	0.0	0.0
GR	680.000	0.0	675.000	250.000	669.100	495.000	669.000	555.000	664.800	577.000
GR	664.700	581.000	664.800	585.000	667.000	610.000	667.500	650.000	680.000	715.000

SECNO 18215 X

X1	18215.000	0.0	0.0	0.0	615.000	488.000	525.000	0.0	2.000	0.0
ET	0.0	0.0	0.0	0.0	9.100	0.0	0.0	0.0	1.000	574.000

SECNO 18739 X

X1	18739.000	10.000	415.000	465.000	614.000	488.000	524.000	0.0	-0.900	0.0
GR	685.000	0.0	680.000	250.000	678.000	345.000	674.000	415.000	669.600	430.000
GR	669.500	640.000	669.600	450.000	674.000	465.000	678.000	540.000	685.000	575.000

SECNO 19001 X

X1	19001.000	0.0	0.0	0.0	307.000	243.000	262.000	0.0	0.900	0.0
ET	0.0	0.0	0.0	0.0	1.410	0.0	0.0	0.0	0.0	0.0

SECNO 19263 50' D/S FARMINGTON FROM CORPS NOTES AND QUAD MAP

X1	19263.000	11.000	288.000	321.000	307.000	243.000	262.000	0.0	0.0	0.0
X3	0.0	0.0	0.0	277.000	0.0	332.000	0.0	0.0	0.0	0.0
GR	685.000	0.0	680.000	60.000	675.000	130.000	675.600	285.000	670.600	288.000
GR	670.500	305.000	670.600	314.000	672.600	321.000	681.800	343.000	680.000	350.000
GR	690.000	350.000	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
NC	0.0	0.0	0.0	0.400	0.600	0.0	0.0	0.0	0.0	0.0
ET	0.0	0.0	0.0	0.0	9.100	0.0	0.0	0.0	1.000	354.000

SECNO 19313 STA 230+00 D/S FACE FARMINGTON FROM CORPS NOTES AND QUAD MAP

X1	19313.000	13.000	290.000	320.000	50.000	50.000	50.000	0.0	0.0	0.0
X3	10.000	0.0	0.0	0.0	0.0	0.0	0.0	679.800	679.800	0.0
GR	685.000	0.0	680.000	60.000	675.000	265.000	675.600	287.000	670.600	290.000
GR	670.600	290.100	670.500	305.000	670.600	320.000	670.600	320.100	672.600	327.000
GR	681.800	349.000	680.000	355.000	690.000	355.000	0.0	0.0	0.0	0.0
SB	0.0	1.710	3.000	0.0	30.000	0.0	210.000	0.0	670.500	670.500

SECNO 19387 U/S FACE FARMINGTON FROM CORPS NOTES AND QUAD MAP

X1	19387.000	0.0	0.0	0.0	74.000	74.000	74.000	0.0	0.0	0.0
X2	0.0	0.0	1.000	677.500	681.100	0.0	0.0	0.0	0.0	0.0
X3	10.000	0.0	0.0	0.0	0.0	0.0	0.0	681.100	681.100	0.0
BT	8.000	0.0	690.000	0.0	0.0	685.000	0.0	290.000	681.100	670.600
BT	290.100	681.100	677.500	320.000	681.100	677.500	320.100	681.100	670.600	355.000
BT	682.000	0.0	355.000	690.000	0.0	0.0	0.0	0.0	0.0	0.0
QT	5.000	820.000	1200.000	1350.000	1350.000	1580.000	0.0	0.0	0.0	0.0
NC	0.120	0.120	0.035	0.300	0.500	0.0	0.0	0.0	0.0	0.0
ET	0.0	0.0	0.0	0.0	1.410	0.0	0.0	0.0	0.0	0.0

SECNO 19437 50' U/S FARMINGTON FROM CORPS NOTES, FIELD BOOK AND QUAD MAP

X1	19437.000	9.000	704.000	773.000	50.000	50.000	50.000	0.0	0.0	0.0
X3	0.0	0.0	0.0	660.000	0.0	820.000	0.0	0.0	0.0	0.0
GR	690.000	0.0	680.000	600.000	679.600	704.000	670.600	728.000	670.500	735.000
GR	670.0	751.0	680.00	773.00	6[illegible].000	91[illegible].0	795.000	1200.000	0.0	

C	0.095	0.095	0.048	0.300	0.500	0.0	0.0	0.0	0.0	0.0
	SECNO 19517									
X1	19517.000	13.000	100.000	180.000	80.000	80.000	80.000	0.0	0.0	0.0
X4	1.000	677.500	1.000	0.0	0.0	0.0	0.0	0.0	0.0	0.0
GR	690.000	0.0	677.000	100.000	674.000	140.000	672.400	155.000	671.600	160.000
GR	671.600	164.000	672.600	170.000	675.700	171.000	678.000	180.000	677.500	200.000
GR	678.300	226.000	681.800	245.000	682.600	280.000	0.0	0.0	0.0	0.0
	SECNO 20117									
X1	20117.000	12.000	275.000	330.000	450.000	750.000	600.000	0.0	0.0	0.0
X4	1.000	680.000	1.000	0.0	0.0	0.0	0.0	0.0	0.0	0.0
GR	690.000	0.0	680.000	124.000	681.500	150.000	681.500	152.000	680.000	185.000
GR	677.900	275.000	676.000	280.000	674.400	295.000	674.400	308.000	680.000	330.000
GR	682.000	368.000	684.000	385.000	0.0	0.0	0.0	0.0	0.0	0.0
	SECNO 20617 X									
X1	20617.000	8.000	410.000	475.000	575.000	425.000	500.000	0.0	0.0	0.0
GR	690.000	0.0	684.000	275.000	680.000	410.000	676.000	432.000	676.000	445.000
GR	680.000	475.000	684.000	525.000	690.000	575.000	0.0	0.0	0.0	0.0
ET	0.0	0.0	0.0	7.100	9.100	0.0	500.000	745.000	535.000	675.000
	SECNO 21117									
X1	21117.000	12.000	565.000	645.000	575.000	425.000	500.000	0.0	0.0	0.0
GR	690.200	0.0	688.100	65.000	685.900	265.000	684.000	335.000	682.000	565.000
GR	681.500	575.000	677.500	580.000	677.500	590.000	680.000	625.000	682.000	645.000
GR	684.000	785.000	685.000	1035.000	0.0	0.0	0.0	0.0	0.0	0.0
ET	0.0	0.0	0.0	0.0	1.410	0.0	0.0	0.0	0.0	0.0
	SECNO 21392 X									
X1	21392.000	7.000	355.000	435.000	200.000	350.000	275.000	0.0	0.0	0.0
GR	695.000	0.0	685.500	355.000	679.100	385.000	679.100	395.000	683.000	435.000
GR	686.000	500.000	695.000	850.000	0.0	0.0	0.0	0.0	0.0	0.0
	SECNO 21667									
X1	21667.000	7.000	130.000	230.000	200.000	350.000	275.000	0.0	0.0	0.0
GR	700.000	0.0	690.000	130.000	680.600	195.000	680.600	205.000	684.100	230.000
GR	690.000	378.000	700.000	1000.000	0.0	0.0	0.0	0.0	0.0	0.0
	SECNO 22128 X									
X1	22128.000	10.000	300.000	355.000	461.000	461.000	461.000	0.0	0.0	0.0
GR	700.000	0.0	691.000	125.000	689.000	200.000	688.000	300.000	682.100	330.000
GR	681.900	335.000	682.100	340.000	686.500	355.000	693.000	380.000	700.000	600.000
	SECNO 22589 X									
X1	22589.000	10.000	445.000	435.000	461.000	461.000	461.000	0.0	0.0	0.0
GR	700.000	50.000	691.000	200.000	689.000	300.000	688.000	445.000	685.000	465.000
GR	683.200	470.000	685.000	475.000	689.000	485.000	693.000	505.000	700.000	675.000
ET	0.0	0.0	0.0	0.0	9.100	0.0	0.0	0.0	1.000	799.000

STCNO 23050

X1	23050.000	16.000	600.000	613.000	461.000	461.000	461.000	0.0	0.0	0.0
GR	700.800	0.0	698.200	100.000	695.100	200.000	693.400	300.000	691.500	400.000
GR	690.400	500.000	690.600	575.000	689.000	600.000	685.500	602.000	684.500	606.000
GR	685.700	610.000	688.900	613.000	692.800	624.000	699.100	670.000	699.400	700.000
GR	700.800	800.000	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
ET	0.0	0.0	0.0	0.0	1.400	0.0	0.0	0.0	0.0	0.0

STCNO 23550

X1	23550.000	6.000	270.000	330.000	500.000	500.000	500.000	0.0	0.0	0.0
GR	701.000	0.0	690.000	270.000	687.500	295.000	687.500	305.000	690.000	330.000
GR	700.000	400.000	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
QT	5.000	730.000	1070.000	1210.000	1210.000	1410.000	0.0	0.0	0.0	0.0
NC	0.080	0.080	0.060	0.0	0.0	0.0	0.0	0.0	0.0	0.0

STCNO 24226 24° D/S 8 MILE

X1	24226.000	8.000	235.000	278.000	550.000	800.000	676.000	0.0	-0.040	0.0
X3	0.0	0.0	0.0	118.000	0.0	360.000	0.0	0.0	0.0	0.0
GR	698.500	0.0	692.500	235.000	690.500	242.000	689.200	255.000	690.500	269.000
GR	692.500	278.000	695.500	430.000	696.000	530.000	0.0	0.0	0.0	0.0
NC	0.050	0.050	0.030	0.0	0.0	0.0	0.0	0.0	0.0	0.0
ET	0.0	7.100	9.100	9.100	9.100	9.100	249.000	261.000	0.500	354.000

STCNO 24250 D/S FACE 8 MILE

X1	24250.000	0.0	0.0	0.0	24.000	24.000	24.000	0.0	0.040	0.0
EJ	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

*PROF 1

CCHV= 0.300 CEHV= 0.500

*SECNO 120.000

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IOC	ICONT	CORAR	TOPWID	ENDST
3470 ENCROACHMENT STATIONS=		250.0	540.0	TYPE=	1	TARGET=	290.000		
SECNO 120 CORPS STA 050									
120.00	6.80	620.00	0.0	620.00	620.76	0.76	0.0	0.0	616.40
1770.	270.	1261.	239.	143.	154.	148.	0.	0.	618.10
0.0	1.89	8.21	1.62	0.100	0.040	0.100	0.0	613.20	320.00
0.007132	0.	0.	0.	0	0	0	0.0	220.00	540.00

Mean Annual Flood in Bell Br.
100 yr elev. = 623.29

*SECNO 370.000

SECNO 370. X

370.00	6.42	621.72	0.0	0.0	622.35	0.63	1.55	0.06	618.00
1770.	418.	1138.	214.	201.	146.	106.	3.	1.	618.00
0.01	2.08	7.79	2.02	0.100	0.040	0.100	0.040	615.30	57.95
0.005459	250.	250.	250.	2	0	0	0.0	159.10	217.05

*SECNO 745.000

SECNO 745 X

745.00	7.60	623.30	0.0	0.0	623.72	0.42	1.31	0.06	618.00
1770.	343.	1175.	251.	198.	187.	151.	7.	2.	618.00
0.03	1.73	6.29	1.67	0.100	0.040	0.100	0.040	615.70	63.64
0.002429	375.	375.	375.	2	0	0	0.0	142.72	206.36

*SECNO 1120.000

SECNO 1120. STA 13+40

1120.00	8.21	624.21	0.0	0.0	624.88	0.67	1.03	0.12	618.00
1770.	197.	1271.	302.	116.	166.	158.	11.	4.	618.00
0.05	1.70	7.67	1.92	0.100	0.040	0.100	0.040	616.00	72.14
0.003128	375.	375.	375.	2	0	0	0.0	120.72	192.86

*SECNO 1770.000

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IOC	ICONT	CORAR	TOPWID	ENDST

SECNO 1770 X

770.00	8.81	625.[illegible]	0.0	0.0	626.[illegible]1	0.37	1.2[illegible]	0.09	618.00

0.09	1.36	5.48	1.35	0.100	0.040	0.100	0.040	617.00	133.14
0.001290	650.	650.	650.	2	0	0	0.0	121.13	254.27

CCHV= 0.300 CEHV= 0.500
*SECNO 2416.000

SECNO 2416 50' D/S 6 MILE FROM CORPS NOTES AND QUAD MAP

2416.00	8.77	626.67	0.0	0.0	627.19	0.52	0.91	0.08	618.00
1770.	82.	1556.	133.	69.	253.	107.	26.	7.	618.00
0.12	1.18	6.15	1.24	0.120	0.040	0.120	0.040	617.90	255.06
0.001527	646.	646.	646.	2	0	0	0.0	69.65	324.69

*SECNO 2466.000

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 631.00 ELREA= 631.00

SECNO 2466 D/S FACE 6 MILE FROM FIELD BOOKS AND QUAD MAP

C 2466.00	9.19	627.09	0.0	0.0	627.34	0.25	0.07	0.08	625.40
1770.	0.	1770.	0.	0.	438.	0.	26.	7.	625.40
0.13	0.0	4.04	0.0	0.120	0.040	0.120	0.040	617.90	371.60
0.001185	50.	50.	50.	2	0	0	0.0	73.80	445.40

SPECIAL BRIDGE

SB XR	XKOR	COEQ	RDLEN	BNC	BHP	BAREA	SS	ELCHU	ELCHD
1.05	1.79	3.00	0.0	22.80	2.00	582.00	2.91	617.90	617.90

*SECNO 2554.000
CLASS A LOW FLOW

3420 BRIDGE H.S.= 627.05 BRIDGE VELOCITY= 4.07 CALCULATED CHANNEL AREA= 435.

EGPRS	EGLWC	H3	QWEIR	QPR	BAREA	TRAPEZOID AREA	ELLC	ELTRD
0.0	627.35	0.02	0.	1770.	582.	624.	629.40	632.60

.0118×88 = .10ft

friction loss may be ≈.10ft

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 632.60 ELREA= 632.60

SECNO 2554 U/S FACE 6 MILE FROM FIELD BOOKS AND QUAD MAP

2554.00	9.20	627.10	0.0	0.0	627.35	0.25	0.01	0.0	625.40
1770.	0.	1770.	0.	0.	439.	0.	27.	7.	625.40
0.13	0.0	4.03	0.0	0.120	0.040	0.120	0.040	617.90	371.60
0.001176	88.	88.	88.	0	0	0	0.0	73.80	445.40

CCHV= 0.400 CEHV= 0.600
*SECNO 2604.000

3470 ENCROACHMENT STATIONS= 111.0 205.0 TYPE= 1 TARGET= 174.000

SECNO 2604 STA 25+20 50' U/S 6 MILE FROM CORPS NOTES AND QUAD MAP

2604.00	9.32	627.22	0.0	0.0	627.43	0.21	0.06	0.02	621.50
1770.	256.	1427.	87.	292.	355.	114.	28.	7.	622.20
0.12	0.87	4.04	0.74	0.15	0.50	0.150	0.0.0	617.90	111.00

0.001150	50.	50.	50.	2		0	0.0	[illegible]	[illegible]

*SECNO 3360.000

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	IWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	IOPRID	ENDST

SECNO 3360 X

3360.00	8.01	628.31	0.0	0.0	628.61	0.29	1.13	0.05	625.00
1770.	250.	1399.	121.	280.	288.	161.	39.	10.	625.00
0.19	0.89	4.85	0.75	0.150	0.050	0.150	0.063	620.30	66.86
0.002232	600.	756.	550.	2	0	0	0.0	237.48	304.34

*SECNO 4116.000

3470 ENCROACHMENT STATIONS= 123.0 273.0 TYPE= 1 TARGET= 150.000

SECNO 4116 200'D/S MIDDLEBELT FROM CORPS NOTES AND QUAD MAP

4116.00	7.47	630.07	0.0	0.0	630.42	0.35	1.78	0.03	626.20
1770.	191.	1418.	160.	151.	270.	137.	49.	13.	627.10
0.23	1.26	5.25	1.17	0.120	0.050	0.120	0.045	622.60	123.00
0.002742	600.	756.	550.	2	0	0	0.0	150.00	273.00

*SECNO 4316.000 2311'

3301 HV CHANGED MORE THAN HVINS 200

SECNO 4316 STA 26+00 D/S FACE MIDDLEBELT SKEW BRIDGE FROM C.N. AND Q.H.

4316.00	7.67	630.27	0.0	0.0	632.73	2.46	1.04	1.27	622.70
1770.	100.	1571.	99.	30.	118.	30.	50.	13.	622.70
0.24	3.35	13.30	3.34	0.100	0.050	0.100	0.045	622.60	34.42
0.013358	300.	200.	100.	2	0	0	0.0	31.10	65.60

channel is 155 ft wide which is width of bridge

SPECIAL BRIDGE

SS	XK	XKOR	COEQ	RDLEN	BWC	BWP	BAREA	SS	ELCHU	ELCHD
	0.0	1.35	3.00	0.0	15.44	0.0	97.24	0.0	622.60	622.60

*SECNO 4403.000

3301 HV CHANGED MORE THAN HVINS

Due to railing, all flow in channel must go pressure

PRESSURE AND WEIR FLOW

All weir flow is either LOB or ROB (≈ 260 cfs)

Top of Railing = 635.4

EGPRS	EGLWC	H3	QWEIR	QPR	BAREA	TRAPEZOID AREA	ELLC	ELTRD
639.79	633.76	0.0	513.	1266.	97.	97.	628.90	632.90

SECNO 4403 U/S FACE MIDDLEBELT FROM CORPS NOTES AND QUAD MAPSKEW BR.

4403.00	11.70	634.30	0.0	0	635.07	0.77	1.35	0.0	622.70

1770.	178.	1416.	176.	103.	181.	103.	51.	13.	62[illegible]
0.24	1.72	7.84	1.71	0.100	0.050	0.100	0.065	622.60	0.98
0.002637	87.	87.	87.	3	0	4	0.0	98.04	99.02

CCHV= 0.400 CEHV= 0.600
*SECNO 4453.000
3280 CROSS SECTION 4453.00 EXTENDED 0.37 FEET

3301 HV CHANGED MORE THAN HVINS

3470 ENCROACHMENT STATIONS= 54.9 247.5 TYPE= 1 TARGET= 428.000

SECNO 4453 STA 44+55 50' U/S MIDDLEBELT FROM CORPS NOTES AND QUAD MAP

4453.00	12.77	635.37	0.0	0.0	635.41	0.03	0.04	0.30	625.70
1770.	582.	366.	822.	583.	150.	685.	52.	13.	626.70
0.25	1.00	2.44	1.20	0.100	0.050	0.100	0.045	622.60	54.90
0.000371	50.	50.	50.	2	0	0	0.0	192.60	247.50

*SECNO 5950.000

SECNO	DEPTH	CHSEL	CRIWS	WSELK	EG	HV	HL	QLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

SECNO 5950 STA 59+50 FROM CORPS NOTES AND QUAD MAP

5950.00	9.29	635.89	0.0	0.0	635.94	0.05	0.52	0.01	630.00
1770.	656.	699.	415.	873.	257.	551.	105.	23.	630.00
0.52	0.75	2.72	0.75	0.100	0.040	0.100	0.044	626.60	35.95
0.000330	1497.	1497.	1497.	3	0	0	0.0	353.51	389.46

*SECNO 6600.000

SECNO 6600 STA 66+00 FROM CORPS NOTES AND QUAD MAP

6600.00	7.38	636.18	0.0	0.0	636.32	0.14	0.32	0.06	632.00
1770.	156.	1172.	442.	180.	318.	502.	123.	27.	632.00
0.58	0.87	3.69	0.88	0.100	0.040	0.100	0.044	628.80	34.42
0.000961	650.	650.	500.	2	0	0	0.0	327.33	361.75

*SECNO 7340.000

SECNO 7340 STA 73+40 FROM CORPS NOTES AND QUAD MAP

7340.00	5.56	637.26	0.0	0.0	637.42	0.16	1.09	0.01	634.00
1770.	781.	553.	436.	485.	106.	272.	139.	32.	634.00
0.66	1.61	5.21	1.61	0.100	0.040	0.100	0.043	631.70	42.23
0.002543	740.	740.	740.	2	0	0	0.0	260.62	310.86

*SECNO 8078.000

SECNO 8078 X

8078.00	6.34	639.24	0.0	0.0	639.56	0.32	2.04	0.10	635.50
1770.	541.	1005.	225.	415.	169.	194.	154.	38.	635.50
71	1.30	5	1.16	0.100	0.040	0.100	0.043	632	33.17

0.002642	837.	738.	808.						

*SECNO 8815.000

SECNO 8815 STA 88+15 FROM CORPS NOTES AND QUAD MAP

8815.00	7.02	641.02	0.0	0.0	641.29	0.27	1.71	0.02	638.00
1770.	345.	1209.	216.	337.	241.	214.	169.	44.	638.00
0.77	1.02	5.02	1.01	0.100	0.040	0.100	0.042	634.00	37.36
0.001890	840.	737.	810.	2	0	0	0.0	332.93	370.29

*SECNO 9276.000

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

SECNO 9276 X

9276.00	7.09	641.99	0.0	0.0	642.51	0.52	1.07	0.15	639.00
1770.	171.	1553.	46.	163.	251.	45.	176.	47.	639.00
0.80	1.04	6.19	1.04	0.100	0.040	0.100	0.042	634.90	95.54
0.002895	461.	461.	461.	2	0	0	0.0	184.31	279.85

*SECNO 9737.000

SECNO 9737 X

9737.00	7.39	643.29	0.0	0.0	643.73	0.43	1.18	0.04	640.00
1770.	207.	1509.	54.	198.	265.	54.	181.	49.	640.00
0.82	1.05	5.70	0.99	0.100	0.040	0.100	0.042	635.90	92.66
0.002282	461.	461.	461.	2	0	0	0.0	190.30	282.96

*SECNO 10198.000

SECNO 10198 X

10198.00	7.43	644.33	0.0	0.0	644.75	0.42	1.02	0.00	641.00
1770.	212.	1503.	55.	203.	267.	56.	186.	51.	641.00
0.85	1.05	5.64	0.98	0.100	0.040	0.100	0.042	636.90	92.32
0.002210	450.	461.	300.	0	0	0	0.0	191.07	283.39

*SECNO 10658.000

3470 ENCROACHMENT STATIONS= 183.0 263.0 TYPE= 1 TARGET= 80.000

SECNO 10658 STA 106+90 50' D/S MERRIMAN FROM CORPS NOTES AND QUAD MAP

10658.00	7.71	645.51	0.0	0.0	646.24	0.73	1.30	0.18	642.50
1770.	96.	1557.	117.	58.	214.	67.	190.	52.	642.50
0.87	1.66	7.28	1.75	0.100	0.040	0.100	0.042	637.80	183.00
0.003903	450.	460.	300.	2	0	0	0.0	80.00	263.00

*SECNO 10708.000

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 653.60 ELREA= 653.60

SECNO 10708 STA 107+40 D/S FACE MERRIMAN PRO.. CORPS NOTES AN...

10708.00	8.10	646.10	0.0	0.0	646.51	0.40	0.14	0.13	645.50
1770.	0.	1770.	0.	0.	347.	0.	191.	52.	645.50
0.87	0.0	5.10	0.0	0.100	0.040	0.100	0.042	638.00	208.00
0.002150	50.	50.	50.	2	0	0	0.0	64.00	272.00

SPECIAL BRIDGE

SB	XK	XKOR	COFQ	ROLEN	BWC	BWP	BAREA	SS	ELCHU	ELCHD
	1.25	1.30	3.00	0.0	26.00	2.00	793.70	2.28	638.00	638.00

*SECNO 10782.000

SECNO	DEPTH	CHSEL	CRIWS	WSELK	EG	HV	HL	QLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WIN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IOC	ICONT	CORAR	TOPWID	ENDST

CLASS A LOW FLOW

3420 BRIDGE W.S.E= 646.06 BRIDGE VELOCITY= 5.18 CALCULATED CHANNEL AREA= 342.

EGPRS	EGLWC	H3	QWEIR	QBR	BAREA	TRAPEZOID AREA	ELLC	ELTRD
0.0	646.55	0.05	0.	1770.	794.	882.	653.10	654.00

22 x 74 = 16 ft.

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 654.00 ELREA= 655.00

SECNO 10782 U/S FACE MERRIMAN FROM CORPS NOTES AND QUAD MAP

10782.00	8.16	646.16	0.0	0.0	646.55	0.40	0.05	0.0	645.50
1770.	0.	1770.	0.	0.	350.	0.	191.	52.	645.50
0.87	0.0	5.06	0.0	0.100	0.040	0.100	0.042	638.00	208.00
0.002093	74.	74.	74.	0	0	0	0.0	64.00	272.00

CCHV= 0.300 CEHV= 0.500

*SECNO 10832.000

3470 ENCROACHMENT STATIONS= 145.0 300.0 TYPE= 1 TARGET= 155.000

SECNO 10832.501 U/S MERRIMAN FROM CORPS NOTES AND QUAD MAP

10832.00	8.71	646.51	0.0	0.0	646.68	0.17	0.06	0.07	642.50
1590.	132.	1265.	192.	157.	344.	200.	192.	52.	642.50
0.88	0.84	3.68	0.96	0.100	0.040	0.100	0.042	637.00	145.00
0.000780	50.	50.	50.	2	0	0	0.0	155.00	300.00

CCHV= 0.300 CEHV= 0.500

*SECNO 11720.000

SECNO 11720

11720.00	5.22	647.92	0.0	0.0	648.31	0.38	1.52	0.11	646.50
1590.	311.	1142.	137.	289.	196.	139.	205.	57.	646.00
0.93	1.08	5.83	0.98	0.150	0.050	0.150	0.042	642.70	344.08
0.006333	888.	888.	888.	2	0	0	0.0	339.81	683.09

*SECNO 12140.000

SECNO 12145 X

12145.00	6.15	649.75	0.0	0.0	649.91	0.17	1.54	0.07	647.40
1590.	405.	989.	198.	468.	242.	239.	213.	61.	646.90
0.97	0.87	4.08	0.82	0.150	0.050	0.150	0.043	643.60	329.24
0.002348	425.	425.	425.	2	0	0	0.0	363.51	692.76

*SECNO 12570.000

SECNO 12570 STA 126+20 FROM CORPS NOTES AND QUAD MAP

12570.00	6.50	650.90	0.0	0.0	651.16	0.26	1.20	0.05	645.80
1590.	397.	1129.	64.	426.	233.	106.	221.	64.	649.60
1.00	0.93	4.85	0.60	0.150	0.050	0.150	0.043	644.40	247.51
0.003461	425.	425.	425.	3	0	0	0.0	395.98	643.49

*SECNO 12965.000

SECNO	DEPTH	CHSEL	CRIWS	WSELK	EG	HV	HL	QLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

SECNO 12965 X

12965.00	6.36	652.36	0.0	0.0	652.66	0.30	1.48	0.02	647.40
1590.	378.	1158.	54.	392.	226.	91.	228.	68.	651.20
1.03	0.97	5.13	0.60	0.150	0.050	0.150	0.043	646.00	251.47
0.004042	395.	395.	395.	2	0	0	0.0	389.52	640.98

CCHV= 0.300 CEHV= 0.500

*SECNO 13360.000

SECNO 13360 STA 159+20 FROM CORPS NOTES AND QUAD MAP

13360.00	6.54	654.04	0.0	0.0	654.50	0.46	1.76	0.08	650.00
1590.	193.	1232.	165.	171.	201.	147.	234.	70.	650.00
1.05	1.12	6.12	1.12	0.150	0.050	0.150	0.043	647.50	185.16
0.005054	430.	395.	250.	2	0	0	0.0	197.56	382.72

*SECNO 13704.000

SECNO 13704 X

13704.00	6.45	655.75	0.0	0.0	656.23	0.48	1.72	0.01	651.80
1590.	188.	1241.	161.	164.	197.	140.	237.	72.	651.80
1.07	1.15	6.28	1.15	0.150	0.050	0.150	0.044	649.30	187.12
0.005454	209.	344.	344.	2	0	0	0.0	193.93	381.04

*SECNO 14047.000

SECNO 14047 X

14047.00	6.44	657.54	0.0	0.0	658.02	0.49	1.79	0.00	653.60
1590.	188.	1242.	161.	163.	197.	139.	240.	73.	653.60
1.09	1.15	6.30	1.15	0.150	0.050	0.150	0.044	651.10	187.33
0.005498	208.	343.	343.	2	0	0	0.0	193.54	380.86

*SECNO 14219.000

3470 ENCROACHMENT STATIONS= 400.0 524.0 TYPE= 1 TARGET= 124.000

VALLEY SECTION X

14219.00	6.43	658.43	0.0	0.0	658.81	0.38	0.76	0.03	653.30
1590.	329.	1019.	243.	205.	168.	170.	242.	73.	653.30
1.10	1.60	6.08	1.43	0.150	0.050	0.150	0.044	652.00	400.00
0.004052	104.	172.	172.	2	0	0	0.0	124.00	524.00

CCHV= 0.400 CEHV= 0.600

*SECNO 14390.000

3301 HV CHANGED MORE THAN HVINS

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	QLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IOC	ICONT	CORAR	TOPWID	ENDST

3470 ENCROACHMENT STATIONS= 556.9 595.1 TYPE= 1 TARGET= 42.000

SECNO 14390 50' D/S 7 MILE FROM CORPS NOTES AND QUAD MAP SKEW

14390.00	6.01	658.91	0.0	0.0	661.08	2.17	1.20	1.07	653.00
1590.	150.	1279.	162.	50.	98.	52.	244.	74.	653.00
1.10	3.02	13.09	3.08	0.150	0.050	0.150	0.044	652.90	556.92
0.017921	104.	171.	171.	2	0	0	0.0	38.22	595.14

*SECNO 14440.000

3301 HV CHANGED MORE THAN HVINS

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 660.00 ELREA= 660.00

SECNO 14440 STA 174+50 D/S FACE 7 MILE FROM CORPS NOTES AND QUAD MAPSKEW

14440.00	6.76	659.64	659.54	0.0	662.79	3.15	1.12	0.59	654.50
1590.	0.	1590.	0.	0.	112.	0.	244.	74.	653.50
1.10	0.0	14.25	0.0	0.150	0.050	0.150	0.044	652.90	675.22
0.028591	50.	50.	50.	4	11	0	0.0	18.20	693.42

SPECIAL BRIDGE

SB	XK	XKOR	COFQ	RDLEN	BWC	BWP	BAREA	SS	ELCHU	ELCHD
	0.0	1.71	3.00	0.0	18.20	0.0	121.90	0.0	652.80	652.00

*SECNO 14501.000

3301 HV CHANGED MORE THAN HVINS

PRESSURE AND WEIR FLOW

EGPRS	EGLWC	H3	QWEIR	QPR	BAREA	TRAPEZOID AREA	ELLC	ELTRD

664.15 662.79 0.0 40. [illegible]

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 663.60 ELREA= 663.60

SECNO 14501 U/S FACE 7 MILE FROM CORPS NOTES AND QUAD MAP SKEW

Owen ELTRD=663.4

14501.00	9.48	662.38	0.0	0.0	663.88	1.50	1.10	0.0	654.50
1590.	0.	1590.	0.	0.	162.	0.	244.	74.	653.50
1.11	0.0	9.83	0.0	0.150	0.050	0.150	0.044	652.90	675.22
0.009620	61.	61.	61.	8	0	3	0.0	18.20	693.42

155.0

weir flow

*SECNO 14570.000

3301 HV CHANGED MORE THAN HVINS

3470 ENCROACHMENT STATIONS= 219.3 390.4 TYPE= 1 TARGET= 188.000

heavy shock loss with weir flow

$-\left(\left(\frac{61}{644}\right)^3 - .06\right).37 .09 = .24$

663.88 + .24 = 664.12

SECNO 14570 STA 175+10 69° U/S 7 MILE FROM CORPS NOTES AND QUAD MAP SKEW

14570.00	12.69	664.49	0.0	0.0	664.55	0.06	0.09	0.57	655.60
1590.	505.	631.	453.	603.	206.	560.	245.	74.	655.60
1.12	0.84	3.06	0.81	0.150	0.050	0.150	0.044	651.80	219.31
0.000511	69.	69.	69.	2	0	0	0.0	171.08	390.39

*SECNO 15360.000

SECNO 15360 STA 184+40 FROM CORPS NOTES AND QUAD MAP

15360.00	9.91	664.91	0.0	0.0	665.00	0.09	0.43	0.01	657.50
1590.	342.	1004.	244.	410.	345.	326.	267.	77.	658.00
1.22	0.83	2.91	0.75	0.150	0.050	0.150	0.044	655.00	15.27
0.000587	790.	790.	790.	3	0	0	0.0	172.01	187.28

*SECNO 16100.000

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	ULOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

SECNO 16100 STA 192+60 FROM CORPS NOTES AND QUAD MAP

16100.00	7.69	665.69	0.0	0.0	665.93	0.24	0.84	0.09	662.00
1590.	165.	821.	604.	160.	152.	545.	284.	82.	660.00
1.28	1.03	5.39	1.11	0.150	0.050	0.150	0.045	658.00	44.12
0.003071	740.	740.	740.	2	0	0	0.0	375.02	419.14

*SECNO 16500.000

SECNO 16500 X

16500.00	7.66	666.66	0.0	0.0	666.83	0.17	0.87	0.03	662.00
1590.	150.	937.	503.	202.	222.	540.	291.	85.	662.00
1.32	0.74	4.23	0.92	0.150	0.050	0.150	0.045	659.00	86.37
0.001828	550.	400.	275.	2	0	0	0.0	320.77	407.15

CCHV= 0.300 CEHV= 0.500

*SECNO 16900.000

SECNO 16900 STA 201+70 FROM CORPS NOTES AND QUAD MAP

16900.00	7.43	667.43	0.0	0.0	667.66	0.23	0.80	0.03	664.00
1590.	129.	1168.	293.	151.	261.	352.	299.	87.	664.00
1.35	0.85	4.48	0.83	0.150	0.050	0.150	0.045	660.00	155.72
0.002447	550.	400.	275.	2	0	0	0.0	305.99	461.71

*SECNO 17295.000

SECNO 17295 X

17295.00	6.16	668.56	0.0	0.0	668.86	0.30	1.17	0.03	666.50
1590.	112.	1156.	323.	114.	227.	210.	304.	89.	665.00
1.37	0.98	5.09	1.54	0.120	0.050	0.120	0.045	662.40	297.01
0.004060	75.	395.	425.	2	0	0	0.0	230.43	527.43

*SECNO 17690.000

SECNO 17690 STA 210+80 FROM CORPS NOTES AND QUAD MAP

17690.00	5.57	670.27	0.0	0.0	670.65	0.38	1.75	0.04	669.00
1590.	92.	1251.	247.	101.	227.	140.	308.	90.	667.00
1.40	0.91	5.51	1.76	0.120	0.050	0.120	0.045	664.70	446.68
0.005240	75.	395.	425.	2	0	0	0.0	217.69	664.37

*SECNO 18215.000

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	QLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

SECNO 18215 X

18215.00	5.95	672.65	0.0	0.0	672.94	0.28	2.26	0.03	671.00
1590.	130.	1206.	255.	146.	249.	162.	314.	93.	669.00
1.43	0.88	4.85	1.57	0.120	0.050	0.120	0.045	666.70	430.46
0.003602	615.	525.	488.	2	0	0	0.0	235.94	666.40

*SECNO 18739.000

SECNO 18739 X

18739.00	6.25	674.85	0.0	0.0	675.46	0.61	2.36	0.16	673.10
1590.	23.	1542.	25.	27.	243.	29.	319.	95.	673.10
1.46	0.86	6.36	0.86	0.120	0.050	0.120	0.046	668.60	384.35
0.005762	614.	524.	488.	2	0	0	0.0	113.48	497.83

*SECNO 19001.000

SECNO 19001 X

19001.00	6.77	676.27	0.0	0.0	676.74	0.47	1.24	0.04	674.00
1590.	38.	1511.	41.	45.	269.	48.	321.	96.	674.00
1.47	0.84	5.62	0.84	0.120	0.050	0.120	0.046	669.50	375.20
0.003930	307.	262.	243.	2	0	0	0.0	132.44	507.64

*SECNO 19263.000

3470 ENCROACHMENT STATIONS= 277.0 332.0 TYPE= 1 TARGET= 55.000

SECNO 19263 50' D/S FARMINGTON FROM CORPS NOTES AND QUAD MAP

19263.00	6.77	677.27	0.0	0.0	678.02	0.75	1.13	0.16	670.60
1590.	32.	1521.	37.	26.	214.	26.	323.	97.	672.60
1.48	1.23	7.10	1.43	0.120	0.050	0.120	0.046	670.50	277.00
0.004761	307.	262.	243.	2	0	0	0.0	55.00	332.00

CCHV= 0.400 CEHV= 0.600

*SECNO 19313.000

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 679.80 ELREA= 679.80

SECNO 19313 STA 230+00 D/S FACE FARMINGTON FROM CORPS NOTES AND QUAD MAP

19313.00	6.98	677.48	0.0	0.0	678.39	0.91	0.28	0.09	670.60
1590.	0.	1590.	0.	0.	208.	0.	323.	97.	670.60
1.48	0.0	7.64	0.0	0.120	0.050	0.120	0.046	670.50	290.00
0.006568	50.	50.	50.	0	0	0	0.0	30.00	320.00

SPECIAL BRIDGE

SB	XK	XKOR	COFQ	RDLEN	BWC	BWP	BAREA	SS	ELCHU	ELCHD
	0.0	1.71	3.00	0.0	30.00	0.0	210.00	0.0	670.50	670.50

*SECNO 19387.000

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

PRESSURE FLOW

EGPRS	EGLWC	H3	QWEIR	QPR	BAREA	TRAPEZOID AREA	ELLC	ELTRD
679.00	678.39	0.0	0.	1590.	210.	210.	677.50	681.10

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 681.10 ELREA= 681.10

SECNO 19387 U/S FACE FARMINGTON FROM CORPS NOTES AND QUAD MAP

19387.00	7.77	678.27	0.0	0.0	679.00	0.73	0.61	0.0	670.60
1590.	0.	1590.	0.	0.	232.	0.	324.	97.	670.60
1.49	0.0	6.86	0.0	0.120	0.050	0.120	0.046	670.50	290.00
0.004700	74.	74.	74.	2	0	0	0.0	30.00	320.00

CCHV= 0.300 CEHV= 0.500

*SECNO 19437.000

3301 HV CHANGED MORE THAN HVINS

ENCROACHMENT STATIONS= 660.0 820.0 TYPE= 1 TARGET= 160.000

SECNO 19437 50' U/S FARMINGTON FROM CORPS NOTES, FIELD BOOK AND QUAD MAP

19437.00	8.52	679.02	0.0	0.0	679.24	0.22	0.09	0.15	679.60
1350.	0.	1350.	0.	0.	357.	0.	324.	97.	682.20
1.49	0.0	3.79	0.0	0.120	0.035	0.120	0.046	670.50	705.54
0.000822	50.	50.	50.	2	0	0	0.0	61.43	766.97

CCHV= 0.300 CEHV= 0.500

*SECNO 19517.000

SECNO 19517

19517.00	7.63	679.23	0.0	0.0	679.35	0.12	0.08	0.03	677.00
1350.	173.	1132.	46.	197.	376.	67.	325.	97.	678.00
1.50	0.88	3.01	0.68	0.095	0.048	0.095	0.046	671.60	0.86
0.001254	80.	80.	80.	0	0	0	0.0	230.24	231.10

*SECNO 20117.000

3265 DIVIDED FLOW

SECNO 20117

20117.00	5.90	680.30	0.0	0.0	680.64	0.34	1.18	0.11	677.90
1350.	161.	1189.	0.	162.	239.	1.	332.	100.	680.00
1.53	0.99	4.98	0.28	0.095	0.048	0.095	0.046	674.40	0.97
0.003758	450.	600.	750.	2	0	0	0.0	286.06	335.87

*SECNO 20617.000

SECNO 20617 X

20617.00	6.02	682.02	0.0	0.0	682.31	0.29	1.65	0.02	680.00
1350.	57.	1271.	21.	68.	287.	25.	336.	103.	680.00
1.57	0.84	4.43	0.84	0.095	0.048	0.095	0.046	676.00	342.12
0.002872	575.	500.	425.	2	0	0	0.0	156.01	500.14

*SECNO 21117.000

SECNO	DEPTH	CWSEL	CRIWS	%SELK	EG	HV	HL	QLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WIN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

3470 ENCROACHMENT STATIONS= 500.0 745.0 TYPE= 1 TARGET= 245.000

SECNO 21117

21117.00	6.00	683.50	0.0	0.0	683.71	0.22	1.38	0.02	682.00
1350.	72.	1225.	53.	79.	313.	78.	341.	105.	682.00
1.61	0.91	3.91	0.68	0.095	0.048	0.095	0.046	677.50	500.00
0.002649	575.	500.	425.	2	0	0	0.0	245.00	745.00

*SECNO 21392.000

SECNO 21392 X

[illegible]	5.32	684.42	0.0	0.0	684.84	0.42	1.03	0.10	685.50
1350.	0.	1329.	21.	0.	255.	22.	344.	107.	683.00
1.62	0.0	5.22	0.94	0.095	0.048	0.095	0.046	679.10	360.05
0.005648	200.	275.	350.	2	0	0	0.0	105.79	465.83

*SECNO 21667.000

SECNO 21667

21667.00	5.40	686.00	0.0	0.0	686.42	0.42	1.58	0.00	690.00
1350.	0.	1298.	52.	0.	246.	45.	346.	107.	684.10
1.64	0.0	5.28	1.15	0.095	0.048	0.095	0.046	680.60	157.67
0.005749	200.	275.	350.	2	0	0	0.0	119.96	277.63

*SECNO 22128.000

SECNO 22128 X

22128.00	6.59	688.49	0.0	0.0	689.00	0.51	2.54	0.05	688.00
1350.	6.	1336.	9.	12.	231.	8.	348.	109.	686.50
1.66	0.45	5.77	1.11	0.095	0.048	0.095	0.046	681.90	250.12
0.005268	461.	461.	461.	1	0	0	0.0	112.57	362.69

*SECNO 22589.000

SECNO 22589 X

22589.00	7.46	690.66	0.0	0.0	690.88	0.21	1.78	0.09	688.00
1350.	498.	847.	5.	382.	185.	7.	353.	111.	689.00
1.70	1.30	4.57	0.74	0.095	0.048	0.095	0.046	683.20	216.92
0.002965	461.	461.	461.	2	0	0	0.0	276.38	493.31

*SECNO 23050.000

SECNO	DEPTH	CHSEL	CRIWS	WSELK	EG	HV	HL	QLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

SECNO 23050

23050.00	7.97	692.47	0.0	0.0	692.86	0.39	1.90	0.09	689.00
1350.	707.	612.	31.	392.	85.	18.	350.	114.	688.90
1.73	1.80	7.17	1.73	0.095	0.048	0.095	0.046	684.50	348.75
0.006098	461.	461.	461.	2	0	0	0.0	274.33	623.08

*SECNO 23550.000

SECNO 23550

23550.00	6.49	693.99	0.0	0.0	694.15	0.16	1.21	0.07	690.00
1350.	175.	1126.	49.	196.	327.	56.	365.	116.	690.00
1.77	0.89	3.44	0.89	0.095	0.048	0.095	0.046	687.50	172.01
0.001296	500.	500.	500.	3	0	0	0.0	185.94	357.95

*SECNO 24226.000

3470 ENCROACHMENT STATIONS= 118.0 360.0 TYPE= 1 TARGET= 242.000

SECNO 24226 24 D/S 8 MILE

24226.00	5.85	695.01	0.0	0.0	695.27	0.25	1.07	0.05	692.46
1210.	127.	910.	173.	128.	197.	143.	373.	119.	692.46
1.82	0.99	4.61	1.21	0.080	0.040	0.080	0.046	689.16	134.96
0.002058	550.	676.	800.	3	0	0	0.0	225.04	360.00

*SECNO 24250.000

3470 ENCROACHMENT STATIONS= 0.5 354.0 TYPE= 1 TARGET= 353.500

SECNO 24250 D/S FACE 8 MILE

24250.00	5.90	695.09	0.0	0.0	695.31	0.22	0.03	0.01	692.50
1210.	148.	864.	198.	132.	199.	140.	373.	119.	692.50
1.82	1.13	4.34	1.41	0.050	0.030	0.050	0.046	689.20	133.37
0.001013	24.	24.	24.	2	0	0	0.0	220.63	354.00

will weir flow or CWR, if not, flw. be much narrower

00BREAK00

1) COUNTY: Wayne

2) STUDY NAME: City of Livonia

3) WATERCOURSE: Tarabasi Creek

4) DOCUMENT TYPE: Enchroachment

00BREAK00

```
**********************************************************
  HEC2 RELEASE DATED NOV 76 UPDATED AUG1977
  ERROR CORR -  01,02
  MODIFICATION -  50,51,52,53
**********************************************************
T1 TARABUSI CREEK FIS HUD 2014 07 LIVONIA CITY FROM BELL BRANCH TO 8 MILE ROAD
T2ENCROACHMENT RUN
T3      TARABUSI CREEK LIVONIA C
J1  ICHECK    INQ       NINV      IDIR      STRT      METRIC    HVINS     U         WSEL      FQ
        0.        5.        0.        0.  0.0           0.0       0.0       0.  620.100     0.0
J2  NPROF     IPLOT     PRFVS     XSECV     XSECH     FN        ALLDC     IBW       CHNIM     ITRACE
     15.000     0.0      -1.000     0.0       0.0       0.0       0.0       0.0       0.0      15.000
```

*PROF 2

CCHV= 0.300 CEHV= 0.500
*SECNO 120.000

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	ULOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IUC	ICONT	CORAR	TOPWID	ENDST
120.00	6.90	620.10	0.0	620.00	620.79	0.69	0.0	0.0	616.40
1770.	279.	1239.	252.	152.	157.	158.	0.	0.	618.10
0.0	1.84	7.88	1.60	0.100	0.040	0.100	0.0	613.20	319.00
0.006385	0.	0.	0.	0	0	0	0.0	221.00	540.00

3470 ENCROACHMENT STATIONS= 250.0 540.0 TYPE= 1 TARGET= 290.000

SECNO 120 CORPS STA 050

FLOW DISTRIBUTION FOR SECNO= 120.00 CWSEL= 620.10

STA=	319.	340.	360.	405.	440.	540.
PER Q=	1.3	2.3	12.1	70.0	14.2	
AREA=	20.0	28.0	103.5	157.2	157.8	
VEL=	1.2	1.5	2.1	7.9	1.6	

*SECNO 370.000

2800 NAT Q1= 239.55 WSEL= 621.72 ENC Q1= 239.55 WSEL= 621.82 RATIO= 0.0000
NAT Q1= 250. RATIOS LOB,CH,ROB= 0.2403 0.6364 0.1233 WSEL= 621.82

3470 ENCROACHMENT STATIONS= 76.7 199.3 TYPE= 4 TARGET= 0.043

SECNO 370. X

370.00	6.35	621.65	0.0	621.72	622.39	0.74	1.58	0.03	618.00
1770.	394.	1191.	185.	174.	144.	83.	2.	1.	618.00
0.01	2.26	8.26	2.24	0.100	0.040	0.100	0.040	615.30	76.67
0.006257	250.	250.	250.	2	0	0	0.0	122.61	199.20

FLOW DISTRIBUTION FOR SECNO= 370.00 CWSEL= 621.65

STA=	77.	140.	170.	199.
PER Q=	22.3	67.3	10.5	
AREA=	174.1	144.1	82.5	
VEL=	2.3	8.3	2.2	

*SECNO 745.000

2800 NAT Q1= 359.15 WSEL= 623.30 ENC Q1= 359.15 WSEL= 623.40 RATIO= 0.0000
NAT Q1= 371. RATIOS LOB,CH,ROB= 0.1962 0.6596 0.1441 WSEL= 623.40

3470 ENCROACHMENT STATIONS= 85.8 184.2 TYPE= 4 TARGET= 0.033

SECNO 745 X

745.00	7.72	623.42	0.0	623.30	623.06	0.45	1.30	0.09	618.00
1770.	327.	1211.	232.	172.	190.	124.	6.	2.	618.00
0.03	1.90	6.36	1.87	0.100	0.040	0.100	0.040	615.70	
0.002425	375.	375.	375.	2	0	0			

FLOW DISTRIBUTION FOR SECNO= 745.00 CWSEL= 623.42

STA=	86.	90.	126.	155.	180.	184.
PER Q=	0.8	17.7	68.4	12.3	0.8	
AREA=	13.2	158.9	190.4	110.4	13.2	
VEL=	1.1	2.0	6.4	2.0	1.1	

*SECNO 1120.000

3470 ENCROACHMENT STATIONS= 1.0 264.0 TYPE= 1 TARGET= 263.000

B SECNO 1120. STA 13+40

1120.00	8.32	624.32	0.0	624.21	624.96	0.64	1.00	0.09	618.00
1770.	201.	1262.	307.	121.	168.	164.	10.	3.	618.00
0.05	1.66	7.50	1.87	0.100	0.040	0.100	0.040	616.00	71.14
0.002930	375.	375.	375.	2	0	0	0.0	122.73	193.86

FLOW DISTRIBUTION FOR SECNO= 1120.00 CWSEL= 624.32

STA=	71.	110.	117.	140.	155.	194.
PER Q=	6.3	5.0	71.3	11.0	6.3	
AREA=	83.9	37.2	168.3	79.8	83.9	
VEL=	1.3	2.4	7.5	2.4	1.3	

*SECNO 1770.000
2800 NAT Q1= 492.76 WSEL= 625.84 ENC Q1= 492.76 WSEL= 625.94 RATIO= 0.0
NAT Q1= 505. RATIOS LOB,CH,ROB= 0.1415 0.7715 0.0870 WSEL= 625.94

SECNO	DEPTH	CWSEL	CRIWS	WSELR	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	INA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	IOPT1D	ENDST

3470 ENCROACHMENT STATIONS= 161.3 237.3 TYPE= 4 TARGET= 0.024

SECNO 1770 X

1770.00	8.87	625.87	0.0	625.84	626.26	0.38	1.23	0.08	618.00
1770.	236.	1395.	139.	154.	251.	94.	17.	4.	618.00
0.09	1.54	5.55	1.47	0.100	0.040	0.100	0.040	617.00	161.34
0.001318	650.	650.	650.	2	0	0	0.0	75.98	237.32

FLOW DISTRIBUTION FOR SECNO= 1770.00 CWSEL= 625.87

STA=	161.	190.	220.	237.
PER Q=	13.4	78.8	7.8	
AREA=	153.8	251.2	94.4	
VEL=	1.5	5.6	1.5	

CCHV= 0.300 CEHV= 0.500
*SECNO 2416.000
2800 NAT Q1= 452.96 WSEL= 626.67 ENC Q1= 452.96 WSEL= 626.77 RATIO= 0.0
NAT Q1= 462. RATIOS LOB,CH,ROB= 0.0466 0.8778 0.0756 WSEL= 626.77

3470 ENCROACHMENT STATIONS= 262.5 313.9 TYPE= 4 TARGET= 0.020

SECNO 2416 50' D/S 6 MILE FROM CORPS NOTES AND QUAD MAP

2416.00	8.82	626.72	0.0	626.67	627.26	0.54	0.92	0.08	618.00
1770.	66.	1584.	120.	54.	254.	87.	24.	5.	618.00
0.12	1.22	6.21	1.37	0.100	0.040	0.100	0.040	617.00	262.53

```
 0.001555      646.      646.      646.         2         0         0      0.0     51.39    313.92

FLOW DISTRIBUTION FOR SECNO=   2416.00          CWSEL=    626.72

STA=     263.      271.      300.      314.
  PER Q=     3.7      89.5       6.8
   AREA=    54.3     254.3      87.3
    VEL=     1.2       6.2       1.4

*SECNO 2466.000
 2800 NAT Q1=    514.15  WSEL=    627.09  ENC Q1=    527.92  WSEL=    627.19  RATIO= -0.0268
 NAT Q1=    528.  RATIOS LOB,CH,ROB=  0.0     1.0000  0.0     WSEL=    627.19

3470 ENCROACHMENT STATIONS=     371.6     445.4  TYPE=      4  TARGET=       0.0

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA=      631.00 ELREA=      631.00

        SECNO 2466          D/S FACE 6 MILE FROM FIELD BOOKS AND QUAD MAP

C 2466.00      9.27   627.17      0.0   627.09   627.42      0.25      0.07      0.09   625.40
    1770.        0.     1770.       0.       0.     445.        0.       25.       5.    625.40
     0.12       0.0      3.98      0.0    0.120    0.040     0.120     0.040   617.90   371.60
 0.001170       50.       50.       50.        2         0         0      0.0     73.80   445.40

FLOW DISTRIBUTION FOR SECNO=   2466.00          CWSEL=    627.17

STA=     372.      445.
  PER Q=   100.0
   AREA=   446.5
    VEL=     4.0
```

```
SPECIAL BRIDGE

SB  XK        XKOR      COEQ      RDLEN     BWC       BWP       BAREA     SS        ELCHU     ELCHD
     1.05      1.79      3.00      0.0      22.80      2.00     582.00     2.91     617.90    617.90

*SECNO 2554.000
    3700.  BRIDGE STENCL=    371.60    STENCR=    445.40
CLASS A LOW FLOW

3420 BRIDGE W.S.=     627.15 BRIDGE VELOCITY=,       4.01       CALCULATED CHANNEL AREA=,      441.

 EGPRS      EGLWC       H3        QWEIR     QPR       BAREA     TRAPEZOID AREA     ELLC      ELTRD
   0.0     627.44      0.01         0.     1770.      582.        624.            629.40    632.60

3470 ENCROACHMENT STATIONS=      445.4       0.0  TYPE=      4  TARGET=       0.0
 ELENCL=      0.0   ELENCR=      0.0

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA=      632.60 ELREA=      632.60

        SECNO 2554 U/S FACE 6 MILE FROM FIELD BOOKS AND QUAD MAP

 2554.00      9.30   627.20      0.0   627.10   627.44      0.24      0.03      0.0    625.40
    1770.        0.     1770.       0.       0.     447.        0.       25.       6.    625.40
     0.13       0.0      3.96      0.0    0.120    0.040     0.120     0.040   617.90   371.60
 0.001115       88.       88.       88.        0         0         0      0.0     73.80   445.40
```

FLOW DISTRIBUTION FOR SECNO= 2554.00 CWSEL= 627.20

STA= 372. 445.
PER Q= 100.0
AREA= 446.7
VEL= 4.0

CCHV= 0.400 CEHV= 0.600
*SECNO 2604.000

3470 ENCROACHMENT STATIONS= 111.0 285.0 TYPE= 1 TARGET= 174.000

SECNO 2604 STA 25+20 50' U/S 6 MILE FROM CORPS NOTES AND QUAD MAP

2604.00	9.42	627.32	0.0	627.22	627.52	0.20	0.06	0.02	621.50
1770.	259.	1422.	89.	299.	359.	118.	26.	6.	622.20
0.13	0.87	3.97	0.76	0.150	0.050	0.150	0.040	617.90	111.00
0.001100	50.	50.	50.	2	0	0	0.0	145.96	256.96

FLOW DISTRIBUTION FOR SECNO= 2604.00 CWSEL= 627.32

STA= 111. 178. 221. 250. 257.
PER Q= 14.6 80.6 4.9 0.2
AREA= 298.5 358.7 109.7 8.1
VEL= 0.9 4.0 0.8 0.4

*SECNO 3360.000
2800 NAT Q1= 374.64 WSEL= 628.31 ENC Q1= 374.64 WSEL= 628.41 RATIO= 0.0
NAT Q1= 388. RATIOS LOB,CH,ROB= 0.1452 0.7832 0.0716 WSEL= 628.41

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	IOPWID	ENDST

3470 ENCROACHMENT STATIONS= 95.1 264.2 TYPE= 4 TARGET= 0.033

SECNO 3360 X

3360.00	8.08	628.38	0.0	628.31	628.69	0.31	1.11	0.07	625.00
1770.	234.	1437.	100.	247.	291.	112.	37.	8.	625.00
0.18	0.95	4.93	0.89	0.150	0.050	0.150	0.043	620.30	95.12
0.002277	600.	756.	550.	2	0	0	0.0	169.12	264.24

FLOW DISTRIBUTION FOR SECNO= 3360.00 CWSEL= 628.38

STA= 95. 180. 223. 264.
PER Q= 13.2 81.2 5.6
AREA= 247.0 291.3 111.9
VEL= 0.9 4.9 0.9

*SECNO 4116.000

3470 ENCROACHMENT STATIONS= 123.0 273.0 TYPE= 1 TARGET= 150.000

SECNO 4116 200'D/S MIDDLEBELT FROM CORPS NOTES AND QUAD MAP

4116.00	7.53	630.13	0.0	630.07	630.47	0.34	1.76	0.02	626.20
1770.	194.	1412.	164.	155.	273.	140.	46.	10.	627.10
0.23	1.25	5.17	1.17	0.120	0.050	0.120	0.045	622.60	123.00
0.002628	600.	756.	550.	2	0	0	0.0	150.00	273.00

FLOW DISTRIBUTION FOR SECNO= 4116.00 CWSEL= 630.13

STA= 123. 177. 219. 273.

PER Q=	11.0	79.8	9.2
AREA=	155.0	273.1	140.1
VEL=	1.3	5.2	1.2

*SECNO 4316.000

3301 HV CHANGED MORE THAN HVINS

3470 ENCROACHMENT STATIONS= 1.0 415.0 TYPE= 1 TARGET= 414.000

SECNO 4316 STA 26+00 D/S FACE MIDDLEBELT SKEW BRIDGE FROM C.N. AND Q.M.

4316.00	7.70	630.30	0.0	630.27	632.74	2.43	1.01	1.26	622.70
1770.	100.	1570.	99.	30.	119.	30.	48.	11.	622.70
0.23	3.34	13.23	3.33	0.100	0.050	0.100	0.045	622.60	34.39
0.013137	300.	200.	100.	2	0	0	0.0	31.25	65.64

FLOW DISTRIBUTION FOR SECNO= 4316.00 CWSEL= 630.30

STA=	34.	42.	58.	66.
PER Q=	5.7	88.7	5.6	
AREA=	30.1	118.7	29.8	
VEL=	3.3	13.2	3.3	

SPECIAL BRIDGE

SB	XK	XKOR	COFQ	RDLEN	BWC	BWP	BAREA	SS	ELCHU	ELCHD
	0.0	1.85	3.00	0.0	15.44	0.0	97.24	0.0	622.60	622.60

*SECNO 4403.000

3301 HV CHANGED MORE THAN HVINS

PRESSURE AND WEIR FLOW

EGPRS	EGLWC	H3	QWEIR	QPR	BAREA	TRAPEZOID AREA	ELLC	ELTRD
639.82	633.76	0.0	517.	1254.	97.	97.	628.90	632.90

SECNO 4403 U/S FACE MIDDLEBELT FROM CORPS NOTES AND QUAD MAPSKEW BR.

4403.00	11.71	634.31	0.0	634.30	635.08	0.77	2.35	0.0	622.70
1770.	178.	1415.	176.	104.	181.	103.	49.	11.	622.70
0.24	1.71	7.83	1.71	0.100	0.050	0.100	0.045	622.60	0.98
0.002625	87.	87.	87.	3	0	4	0.0	98.04	99.02

FLOW DISTRIBUTION FOR SECNO= 4403.00 CWSEL= 634.31

STA=	1.	2.	32.	42.	58.	68.	98.	99.
PER Q=	0.0	1.7	8.4	80.0	8.3	1.7	0.0	
AREA=	0.5	34.9	68.6	180.7	68.0	34.9	0.5	
VEL=	0.4	0.8	2.2	7.8	2.2	0.8	0.4	

CCHV= 0.400 CEHV= 0.600

*SECNO 4453.000

*3280 CROSS SECTION 4453.00 E TENSION 0.28 FEET

3301 HV CHANGED MORE THAN HVINS

3470 ENCROACHMENT STATIONS= 54.9 247.5 TYPE= 1 TARGET= 428.000

SECNO 4453 STA 44+55 50' U/S MIDDLEBELT FROM CORPS NOTES AND QUAD MAP

4453.00	12.78	635.38	0.0	635.37	635.42	0.03	0.04	0.29	625.70
1770.	582.	366.	822.	584.	150.	686.	50.	11.	626.70
0.25	1.00	2.44	1.20	0.100	0.050	0.100	0.045	622.60	54.90
0.000370	50.	50.	50.	2	0	0	0.0	192.60	247.50

FLOW DISTRIBUTION FOR SECNO= 4453.00 CWSEL= 635.38

STA=	55.	67.	117.	139.	148.	161.	216.	229.	247.
PER Q=	1.8	13.2	11.2	6.8	20.7	38.3	6.5	1.6	
AREA=	50.2	266.4	177.3	90.3	149.8	527.5	106.4	51.9	
VEL=	0.6	0.9	1.1	1.3	2.4	1.3	1.1	0.6	

*SECNO 5950.000
2800 NAT Q1= 974.24 WSEL= 635.89 ENC Q1= 974.24 WSEL= 635.99 RATIO= 0.0000
NAT Q1= 1003. RATIOS LOB,CH,ROB= 0.3727 0.3913 0.2360 WSEL= 635.99

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	QLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	IIRIAL	IOC	ICONT	CORAR	IOPWID	ENDST

3470 ENCROACHMENT STATIONS= 68.3 370.4 TYPE= 4 TARGET= 0.028

SECNO 5950 STA 59+50 FROM CORPS NOTES AND QUAD MAP

5950.00	9.31	635.91	0.0	635.89	635.96	0.05	0.53	0.01	630.00
1770.	645.	715.	409.	815.	257.	516.	101.	19.	630.00
0.51	0.79	2.78	0.79	0.100	0.040	0.100	0.044	626.60	68.26
0.000344	1497.	1497.	1497.	1	0	0	0.0	302.13	370.39

FLOW DISTRIBUTION FOR SECNO= 5950.00 CWSEL= 635.91

STA=	68.	70.	235.	265.	370.	370.
PER Q=	0.1	36.3	40.4	23.1	0.0	
AREA=	6.6	808.4	257.0	514.4	1.5	
VEL=	0.3	0.8	2.8	0.8	0.1	

*SECNO 6600.000
2800 NAT Q1= 570.98 WSEL= 636.18 ENC Q1= 570.98 WSEL= 636.28 RATIO= 0.0000
NAT Q1= 594. RATIOS LOB,CH,ROB= 0.0904 0.6547 0.2550 WSEL= 636.28

3470 ENCROACHMENT STATIONS= 71.2 306.3 TYPE= 4 TARGET= 0.039

SECNO 6600 STA 66+00 FROM CORPS NOTES AND QUAD MAP

6600.00	7.40	636.20	0.0	636.18	636.36	0.16	0.34	0.06	632.00
1770.	130.	1214.	427.	128.	319.	432.	118.	23.	632.00
0.56	1.01	3.80	0.99	0.100	0.040	0.100	0.044	628.80	71.15
0.001014	650.	650.	500.	2	0	0	0.0	235.13	306.29

FLOW DISTRIBUTION FOR SECNO= 6600.00 CWSEL= 636.20

```
STA=      71.      110.      165.      306.
  PER Q=      7.3      68.6      24.1
   AREA=    128.4     319.1     431.9
    VEL=      1.0       3.8       1.0

*SECNO 7340.000
 2800 NAT Q1=     350.98  WSEL=     637.26  ENC Q1=     350.98  WSEL=     637.36  RATIO=  0.0000
 NAT Q1=     368.  RATIOS LOB,CH,ROB=  0.4434  0.3088  0.2478  WSEL=     637.36

3470 ENCROACHMENT STATIONS=      59.7     298.0  TYPE=      4  TARGET=       0.046

        SECNO 7340 STA 73+40 FROM CORPS NOTES AND QUAD MAP

 7340.00      5.63   637.33      0.0    637.26    637.50      0.17      1.13      0.01    634.00
    1770.      785.      571.      414.      467.      108.      253.      133.       27.    634.00
    0.64      1.68      5.30      1.63     0.100     0.040     0.100     0.043    631.70     59.73
0.002575       740.      740.      740.         2         0         0       0.0    238.27    298.00

FLOW DISTRIBUTION FOR SECNO=    7340.00          CWSEL=     637.33

STA=      60.       60.      200.      222.      298.
  PER Q=       0.0      44.3      32.3      23.4
   AREA=       0.9     466.4     107.8     253.2
    VEL=       0.3       1.7       5.3       1.6

*SECNO 8078.000
 2800 NAT Q1=     344.33  WSEL=     639.24  ENC Q1=     344.33  WSEL=     639.34  RATIO=  0.0
 NAT Q1=     362.  RATIOS LOB,CH,ROB=  0.3134  0.5569  0.1298  WSEL=     639.34

3470 ENCROACHMENT STATIONS=      84.1     280.7  TYPE=      4  TARGET=       0.048

        SECNO 8078 X

 8078.00      6.43   639.33      0.0    639.24    639.68      0.35      2.07      0.11    635.50
    1770.      534.      1038.      198.      353.      172.      126.      146.       31.    635.50
    0.69      1.51      6.04      1.57     0.100     0.040     0.100     0.043    632.90     84.09
0.002680       837.      738.      808.         1         0         0       0.0    196.66    280.75

FLOW DISTRIBUTION FOR SECNO=    8078.00          CWSEL=     639.33

STA=      84.      210.      240.      281.
  PER Q=      30.2      58.6      11.2
   AREA=     352.8     171.7     125.9
    VEL=       1.5       6.0       1.6

*SECNO 8815.000
 2800 NAT Q1=     407.16  WSEL=     641.02  ENC Q1=     407.16  WSEL=     641.12  RATIO=  0.0
 NAT Q1=     427.  RATIOS LOB,CH,ROB=  0.2021  0.6714  0.1265  WSEL=     641.12

3470 ENCROACHMENT STATIONS=      88.0     320.6  TYPE=      4  TARGET=       0.046

        SECNO 8815 STA 88+15 FROM CORPS NOTES AND QUAD MAP

 8815.00      7.13   641.13      0.0    641.02    641.41      0.29      1.72      0.02    638.00
    1770.      332.      1245.      193.      291.      248.      167.      159.       35.    638.00
    0.74      1.14      5.07      1.16     0.100     0.040     0.100     0.042    634.00     88.02
0.001879       840.      737.      810.         2         0         0       0.0    232.62    320.64

FLOW DISTRIBUTION FOR SECNO=    8815.00          CWSEL=     641.13

STA=      88.      210.      253.      321.
  PER Q=      18.8      70.3      10.9
   AREA=     291.5     215.6     126.7
```

```
 .EL=      1.1       5.1       1.2

*SECNO 9276.000
 2800 NAT Q1=    328.96  WSEL=    641.99  ENC Q1=    328.96  WSEL=    642.08  RATIO=  0.0
 NAT Q1=    342.  RATIOS LOB,CH,ROB=  0.1030  0.8695  0.0275  WSEL=    642.08
   SECNO     DEPTH     CWSEL     CRIWS     WSELK      EG          HV          HL          QLOSS     BANK ELEV
   Q         QLOB      QCH       QROB      ALOB       ACH         AROB        VOL         TWA     LEFT/RIGHT
   TIME      VLOB      VCH       VROB      XNL        XNCH        XNR         HTN         ELMIN       SSIA
   SLOPE     XLOBL     XLCH      XLOBR     ITRIAL     IDC         ICONT       CORAR       TOPWID      ENDST


3470 ENCROACHMENT STATIONS=     161.2     253.9  TYPE=     4  TARGET=       0.038

        SECNO 9276 X

 9276.00      7.18    642.08       0.0    641.99    642.64      0.56      1.06      0.16    639.00
  1770.      156.     1602.       13.      109.      255.       11.       165.       37.    639.00
    0.77      1.43      6.28      1.14     0.100     0.040     0.100     0.042    634.90    161.18
0.002904      461.      461.      461.         2         0         0       0.0     92.70    253.88

FLOW DISTRIBUTION FOR SECNO=   9276.00          CWSEL=    642.08

STA=      161.      205.      250.      254.
  PER Q=      8.8      90.5       0.7
    AREA=   108.9     255.2      11.2
     VEL=     1.4       6.3       1.1

*SECNO 9737.000
 2800 NAT Q1=    370.52  WSEL=    643.29  ENC Q1=    370.52  WSEL=    643.39  RATIO=  0.0
 NAT Q1=    384.  RATIOS LOB,CH,ROB=  0.1234  0.8450  0.0316  WSEL=    643.39

3470 ENCROACHMENT STATIONS=     149.7     256.1  TYPE=     4  TARGET=       0.036

        SECNO 9737 X

 9737.00      7.51    643.41       0.0    643.29    643.86      0.46      1.18      0.04    640.00
  1770.      194.     1553.       22.      147.      270.       19.       169.       38.    640.00
    0.79      1.33      5.76      1.17     0.100     0.040     0.100     0.042    635.90    149.70
0.002273      461.      461.      461.         2         0         0       0.0    106.44    256.14

FLOW DISTRIBUTION FOR SECNO=   9737.00          CWSEL=    643.41

STA=      150.      205.      250.      256.
  PER Q=     11.0      87.8       1.3
    AREA=   146.6     269.7      19.0
     VEL=     1.3       5.8       1.2

*SECNO 10198.000
 2800 NAT Q1=    376.54  WSEL=    644.33  ENC Q1=    376.54  WSEL=    644.43  RATIO=  0.0000
 NAT Q1=    390.  RATIOS LOB,CH,ROB=  0.1257  0.8423  0.0321  WSEL=    644.43

3470 ENCROACHMENT STATIONS=     147.3     257.0  TYPE=     4  TARGET=       0.033

        SECNO 10198 X

10198.00      7.55    644.45       0.0    644.33    644.89      0.44      1.02      0.01    641.00
  1770.      201.     1544.       26.      153.      272.       22.       173.       39.    641.00
    0.82      1.31      5.68      1.18     0.100     0.040     0.100     0.042    636.90    147.31
0.002193      450.      461.      300.         3         0         0       0.0    109.70    257.01

FLOW DISTRIBUTION FOR SECNO=  10198.00          CWSEL=    644.45
```

```
STA=      147.      205.      250.      257.
  PER Q=     11.3      87.2       1.5
   AREA=    153.5     271.6      21.7
    VEL=      1.3       5.7       1.2

*SECNO 10658.000

3470 ENCROACHMENT STATIONS=      183.0      263.0  TYPE=      1  TARGET=      80.000

        SECNO 10658 STA 106+90 50° D/S MERRIMAN FROM CORPS NOTES AND QUAD MAP

10658.00     7.81   645.61      0.0   645.51   646.31     0.70     1.26     0.15   642.50
  1770.       99.     1552.      120.      60.      217.      69.      177.      40.   642.50
   0.83     1.64     7.14     1.73    0.100    0.040    0.100    0.042   637.80   183.00
0.003671      450.      460.      300.        2        0        0      0.0    80.00   263.00

FLOW DISTRIBUTION FOR SECNO=  10658.00          CWSEL=    645.61

STA=      183.      205.      240.      263.
  PER Q=      5.6      87.7       6.8
   AREA=     60.1     217.4      69.1
    VEL=      1.6       7.1       1.7

*SECNO 10708.000
 2800 NAT Q1=     381.74  WSEL=     646.10  ENC Q1=     392.36  WSEL=     646.20  RATIO= -0.0278
 NAT Q1=     392.  RATIOS LOB,CH,ROB=  0.0      1.0000  0.0      WSEL=     646.20

3470 ENCROACHMENT STATIONS=      208.0      272.0  TYPE=      4  TARGET=        0.0

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA=       653.60 ELREA=       653.60
```

```
        SECNO 10708 STA 107+40 D/S FACE MERRIMAN FROM CORPS NOTES AND QUAD MAP

10708.00     8.17   646.17      0.0   646.10   646.56     0.39     0.14     0.12   645.50
  1770.        0.     1770.       0.       0.      351.       0.      178.      40.   645.50
   0.84      0.0      5.04      0.0    0.100    0.040    0.100    0.042   638.00   208.00
0.002105       50.       50.       50.        2        0        0      0.0    64.00   272.00

FLOW DISTRIBUTION FOR SECNO=  10708.00          CWSEL=    646.17

STA=      208.      272.
  PER Q=    100.0
   AREA=    351.1
    VEL=      5.0

SPECIAL BRIDGE

SB  XK       XKOR      COEQ      RDLEN     BWC       BWP       BAREA     SS        ELCHU     ELCHD
     1.25      1.30      3.00      0.0      26.00      2.00    793.70     2.28    638.00    638.00

*SECNO 10782.000
   3700.  BRIDGE STENCL=    208.00    STENCR=    272.00
  SECNO     DEPTH     CWSEL     CRIWS     WSELK     EG        HV        HL        OLOSS     BANK ELEV
  Q         QLOB      QCH       QROB      ALOB      ACH       AROB      VOL       TWA    LEFT/RIGHT
  TIME      VLOB      VCH       VROB      XNL       XNCH      XNR       WTN       ELMIN       SSTA
  SLOPE     XLOBL     XLCH      XLUBR     ITRIAL    IUC       ICONT     CORAR     TOPWID      ENDST

CLASS A LOW FLOW

3420 BRIDGE W.S.=     646.13 BRIDGE VELOCITY=,       5.12      CALCULATED CHANNEL AREA=,       346.
```

CWRS	EGLWC	HS	QWEIR	QPR	BAREA	TRAPEZOID AREA	ELLC	ELTRD
0.0	646.64	0.05	0.	1770.	794.	882.	653.10	654.00

3470 ENCROACHMENT STATIONS= 272.0 0.0 TYPE= 4 TARGET= 0.0
ELENCL= 0.0 ELENCR= 0.0

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 654.00 ELREA= 655.00

SECNO 10782 U/S FACE MERRIMAN FROM CORPS NOTES AND QUAD MAP

10782.00	8.26	646.26	0.0	646.16	646.64	0.38	0.08	0.0	645.50
1770.	0.	1770.	0.	0.	356.	0.	178.	40.	645.50
0.84	0.0	4.97	0.0	0.100	0.040	0.100	0.042	638.00	208.00
0.001974	76.	76.	76.	0	0	0	0.0	64.00	272.00

FLOW DISTRIBUTION FOR SECNO= 10782.00 CWSEL= 646.26

STA= 208. 272.
PER Q= 100.0
AREA= 356.2
VEL= 5.0

CCHV= 0.300 CEHV= 0.500
*SECNO 10832.000

3470 ENCROACHMENT STATIONS= 145.0 300.0 TYPE= 1 TARGET= 155.000

SECNO 10832 50' U/S MERRIMAN FROM CORPS NOTES AND QUAD MAP

10832.00	8.80	646.60	0.0	646.51	646.76	0.16	0.06	0.07	642.50
1590.	135.	1260.	195.	161.	348.	204.	179.	40.	642.50
0.85	0.84	3.62	0.95	0.100	0.040	0.100	0.042	637.80	145.00
0.000742	50.	50.	50.	2	0	0	0.0	155.00	300.00

FLOW DISTRIBUTION FOR SECNO= 10832.00 CWSEL= 646.60

STA= 145. 197. 247. 300.
PER Q= 8.5 79.3 12.2
AREA= 161.2 348.2 204.4
VEL= 0.8 3.6 1.0

CCHV= 0.300 CEHV= 0.500
*SECNO 11720.000
2800 NAT Q1= 199.80 WSEL= 647.92 ENC Q1= 199.80 WSEL= 648.02 RATIO= 0.0000
NAT Q1= 212. RATIOS LOB,CH,ROB= 0.2036 0.7054 0.0910 WSEL= 648.02

3470 ENCROACHMENT STATIONS= 383.0 633.8 TYPE= 4 TARGET= 0.058

SECNO 11720

11720.00	5.25	647.95	0.0	647.92	648.39	0.44	1.49	0.14	646.50
1590.	287.	1201.	102.	249.	197.	90.	192.	44.	646.00
0.90	1.15	6.08	1.13	0.150	0.050	0.150	0.042	642.70	383.00
0.006834	888.	888.	888.	2	0	0	0.0	250.76	633.76

FLOW DISTRIBUTION FOR SECNO= 11720.00 CWSEL= 647.95

STA= 383. 530. 580. 634.
PER Q= 13.0 77.6

```
    AREA=     248.7     197.5      89.9
     VEL=       1.2       6.1       1.1

*SECNO 12145.000
 2800 NAT Q1=     328.14  WSEL=     649.75  ENC Q1=     328.14  WSEL=     649.85  RATIO=  0.0
 NAT Q1=     344.  RATIOS LOB,CH,ROB=  0.2594  0.6138  0.1268  WSEL=     649.85

3470 ENCROACHMENT STATIONS=     373.2     657.5  TYPE=     4  TARGET=       0.047

        SECNO 12145 X

12145.00      6.27   649.87      0.0   649.75   650.04      0.17      1.57      0.08   647.40
    1590.      393.     1023.      174.      426.      248.      198.      199.       47.    646.90
     0.94      0.92      4.12      0.88     0.150     0.050     0.150     0.043   643.60   373.21
0.002315      425.      425.      425.         1         0         0       0.0   284.32   657.53

FLOW DISTRIBUTION FOR SECNO=  12145.00          CWSEL=    649.87

STA=     373.      375.      530.      580.      658.
  PER Q=       0.2      24.6      64.3      10.9
   AREA=       5.2     421.1     248.1     198.4
    VEL=       0.5       0.9       4.1       0.9

*SECNO 12570.000
 2800 NAT Q1=     270.28  WSEL=     650.90  ENC Q1=     270.28  WSEL=     651.00  RATIO=  0.0000
 NAT Q1=     285.  RATIOS LOB,CH,ROB=  0.2571  0.6986  0.0443  WSEL=     651.00

3470 ENCROACHMENT STATIONS=     320.9     573.1  TYPE=     4  TARGET=       0.050

        SECNO 12570 STA 126+20 FROM CORPS NOTES AND QUAD MAP

12570.00      6.60   651.00      0.0   650.90   651.28      0.28      1.19      0.05   645.80
    1590.      389.     1169.       32.      379.      239.       47.      206.       50.    649.60
     0.97      1.03      4.90      0.69     0.150     0.050     0.150     0.043   644.40   320.94
0.003420      425.      425.      425.         1         0         0       0.0   252.20   573.14

FLOW DISTRIBUTION FOR SECNO=  12570.00          CWSEL=    651.00

STA=     321.      412.      483.      488.      538.      573.
  PER Q=       8.9      13.6       1.9      73.5       2.0
   AREA=     165.8     192.5      21.1     238.5      46.8
    VEL=       0.9       1.1       1.4       4.9       0.7

*SECNO 12965.000
 2800 NAT Q1=     250.08  WSEL=     652.36  ENC Q1=     250.08  WSEL=     652.46  RATIO=  0.0000
 NAT Q1=     264.  RATIOS LOB,CH,ROB=  0.2461  0.7156  0.0383  WSEL=     652.46
   SECNO     DEPTH     CWSEL     CRIWS     WSELK      EG        HV        HL       OLOSS    BANK ELEV
   Q         QLOB      QCH       QROB      ALOB       ACH       AROB      VOL      TWA    LEFT/RIGHT
   TIME      VLOB      VCH       VROB      XNL        XNCH      XNR       WTN      ELMIN      SSTA
   SLOPE     XLOBL     XLCH      XLOBR     ITRIAL     IDC       ICONT     CORAR    TOPWID     ENDST

3470 ENCROACHMENT STATIONS=     330.1     561.9  TYPE=     4  TARGET=       0.053

        SECNO 12965 X

12965.00      6.45   652.45      0.0   652.36   652.77      0.32      1.47      0.02   647.40
    1590.      368.     1202.       20.      341.      231.       29.      212.       52.    651.20
     0.99      1.08      5.21      0.69     0.150     0.050     0.150     0.043   646.00   330.14
0.004061      395.      395.      395.         2         0         0       0.0   231.79   561.93

FLOW DISTRIBUTION FOR SECNO=  12965.00          CWSEL=    652.45
```

```
STA=     330.     412.     483.     488.     538.     562.
  PER Q=     7.8     13.4      1.9     75.6      1.2
   AREA=   139.2    181.1     20.3    230.6     28.7
    VEL=     0.9      1.2      1.5      5.2      0.7

CCHV=   0.300 CEHV=   0.500
*SECNO 13360.000

3470 ENCROACHMENT STATIONS=       1.0     824.0  TYPE=     1  TARGET=     823.000

        SECNO 13360 STA 159+20 FROM CORPS NOTES AND QUAD MAP

13360.00     6.62   654.12      0.0   654.04   654.55     0.43     1.72     0.06   650.00
    1590.      196.    1225.      168.      178.      204.      152.      217.       54.   650.00
    1.02     1.10     6.00     1.10    0.150    0.050    0.150    0.043   647.50   183.56
0.004753      430.      395.      250.        2          0          0      0.0   200.53   384.09

FLOW DISTRIBUTION FOR SECNO=  13360.00          CWSEL=    654.12

STA=     184.     270.     310.     384.
  PER Q=    12.4     77.1     10.6
   AREA=   177.9    204.2    152.5
    VEL=     1.1      6.0      1.1

*SECNO 13704.000

        SECNO 13704 X

13704.00     6.46   655.76      0.0   655.75   656.24     0.48     1.66     0.02   651.80
    1590.      189.    1240.      162.      164.      198.      141.      220.       55.   651.80
    1.03     1.15     6.27     1.15    0.150    0.050    0.150    0.044   649.30   186.95
0.005419      209.      344.      344.        2          0          0      0.0   194.23   381.18

FLOW DISTRIBUTION FOR SECNO=  13704.00          CWSEL=    655.76

STA=     187.     270.     310.     381.
  PER Q=    11.9     78.0     10.2
   AREA=   164.2    197.8    140.8
    VEL=     1.1      6.3      1.1

*SECNO 14047.000

        SECNO 14047 X

14047.00     6.44   657.54      0.0   657.54   658.02     0.49     1.78     0.00   653.60
    1590.      188.    1242.      161.      163.      197.      140.      224.       56.   653.60
    1.05     1.15     6.30     1.15    0.150    0.050    0.150    0.044   651.10   187.32
0.005497      208.      343.      343.        2          0          0      0.0   193.55   380.87

FLOW DISTRIBUTION FOR SECNO=  14047.00          CWSEL=    657.54

STA=     187.     270.     310.     381.
  PER Q=    11.8     78.1     10.1
   AREA=   162.8    197.1    139.5
    VEL=     1.2      6.3      1.2

*SECNO 14219.000

3470 ENCROACHMENT STATIONS=     400.0     524.0  TYPE=     1  TARGET=     124.000

        VALLEY SECTION X
```

14219.00	6.43	658.43	0.0	658.43	658.81	0.38	0.76	0.03	653.30
1590.	329.	1019.	243.	205.	168.	170.	226.	57.	653.30
1.06	1.60	6.08	1.43	0.150	0.050	0.150	0.044	652.00	400.00
0.004053	104.	172.	172.	2	0	0	0.0	124.00	524.00

FLOW DISTRIBUTION FOR SECNO= 14219.00 CWSEL= 658.43

STA=	400.	447.	476.	524.
PER Q=	20.7	64.1	15.3	
AREA=	205.1	167.6	170.2	
VEL=	1.6	6.1	1.6	

CCHV= 0.400 CEHV= 0.600

*SECNO 14390.000

3301 HV CHANGED MORE THAN HVINS

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

3470 ENCROACHMENT STATIONS= 556.9 595.1 TYPE= 1 TARGET= 42.000

SECNO 14390 50' D/S 7 MILE FROM CORPS NOTES AND QUAD MAP SKEW

14390.00	6.01	658.91	0.0	658.91	661.08	2.17	1.20	1.07	653.00
1590.	150.	1279.	162.	50.	98.	52.	227.	57.	653.00
1.07	3.02	13.09	3.08	0.150	0.050	0.150	0.044	652.90	556.92
0.017925	104.	171.	171.	2	0	0	0.0	38.22	595.14

FLOW DISTRIBUTION FOR SECNO= 14390.00 CWSEL= 658.91

STA=	557.	568.	584.	595.
PER Q=	9.4	80.4	10.2	
AREA=	49.6	97.7	52.5	
VEL=	3.0	13.1	3.1	

*SECNO 14440.000

3301 HV CHANGED MORE THAN HVINS

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE.ELLEA= 660.00 ELREA= 660.00

SECNO 14440 STA 174+50 D/S FACE 7 MILE FROM CORPS NOTES AND QUAD MAPSKEW

14440.00	6.74	659.64	659.54	659.64	662.79	3.15	1.12	0.59	654.50
1590.	0.	1590.	0.	0.	112.	0.	227.	57.	653.50
1.07	0.0	14.25	0.0	0.150	0.050	0.150	0.044	652.90	675.22
0.028597	50.	50.	50.	4	11	0	0.0	10.20	693.42

FLOW DISTRIBUTION FOR SECNO= 14440.00 CWSEL= 659.64

STA=	675.	693.
PER Q=	100.0	
AREA=	111.6	
VEL=	14.2	

SPECIAL BRIDGE

SB	XK	XKOR	COFQ	RDLEN	BUC	BUP	BAREA	SS	ELCHU	ELCHD

0.0	1.71	3.00	0.0	18.20	0.0	121.90	0.0	652.80	652.80

*SECNO 14501.000

3301 HV CHANGED MORE THAN HVINS

PRESSURE AND WEIR FLOW

EGPRS	EGLWC	H3	QWEIR	QPR	BAREA	TRAPEZOID AREA	ELLC	ELTRD
664.15	662.79	0.0	40.	1542.	122.	122.	659.50	663.40

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 663.60 ELREA= 663.60

SECNO 14501 U/S FACE 7 MILE FROM CORPS NOTES AND QUAD MAP SKEW

14501.00	9.48	662.38	0.0	662.38	663.88	1.50	1.10	0.0	654.50
1590.	0.	1590.	0.	0.	162.	0.	227.	57.	653.50
1.07	0.0	9.83	0.0	0.150	0.050	0.150	0.044	652.90	675.22
0.009620	61.	61.	61.	8	0	3	0.0	18.20	693.42

FLOW DISTRIBUTION FOR SECNO= 14501.00 CWSEL= 662.38

STA=	675.	693.
PER Q=	100.0	
AREA=	101.8	
VEL=	9.8	

*SECNO 14570.000

3301 HV CHANGED MORE THAN HVINS

3470 ENCROACHMENT STATIONS= 219.3 390.4 TYPE= 1 TARGET= 188.000

SECNO 14570 STA 175+10 69' U/S 7 MILE FROM CORPS NOTES AND QUAD MAP SKEW

14570.00	12.69	664.49	0.0	664.49	664.55	0.06	0.09	0.57	655.60
1590.	505.	631.	453.	603.	206.	560.	220.	57.	655.60
1.08	0.84	3.06	0.81	0.150	0.050	0.150	0.044	651.80	219.31
0.000511	69.	69.	69.	2	0	0	0.0	171.08	390.39

FLOW DISTRIBUTION FOR SECNO= 14570.00 CWSEL= 664.49

STA=	219.	296.	315.	390.
PER Q=	31.8	39.7	28.5	
AREA=	603.0	206.1	560.0	
VEL=	0.8	3.1	0.8	

*SECNO 15360.000

2800 NAT Q1= 656.25 WSEL= 664.91 ENC Q1= 656.25 WSEL= 665.01 RATIO= 0.0

NAT Q1= 671. RATIOS LOB,CH,ROB= 0.2157 0.6295 0.1548 WSEL= 665.01

3470 ENCROACHMENT STATIONS= 28.0 177.6 TYPE= 4 TARGET= 0.022

SECNO 15360 STA 184+40 FROM CORPS NOTES AND QUAD MAP

15360.00	9.21	60.21	0.0	384.	345.	307.	250.	60.	658.00
1590.	334.	1017.	239.	0.150	0.050	0.150	0.044	655.00	27.96
1.18	0.87	2.95	0.78						

```
 0.000603     790.     790.     790.        0        0        0     0.0   149.61   177.57

 FLOW DISTRIBUTION FOR SECNO=  15360.00          CWSEL=    664.91

 STA=      28.      30.      40.      84.     125.     175.     178.
   PER Q=      0.2      2.9     17.9     64.0     14.8      0.2
    AREA=      9.3     59.1    315.1    344.8    295.6     11.3
     VEL=      0.3      0.8      0.9      3.0      0.8      0.3

 *SECNO 16100.000
  2800 NAT Q1=    286.91  WSEL=    665.69  ENC Q1=    286.91  WSEL=    665.79  RATIO=  0.0
  NAT Q1=    299.  RATIOS LOB,CH,ROB=  0.1058  0.5087  0.3855  WSEL=    665.79
     SECNO     DEPTH     CWSEL     CRIWS     WSELR     EG        HV        HL        OLOSS     BANK ELEV
     Q         QLOB      QCH       QROB      ALOB      ACH       AROB      VOL       TWA       LEFT/RIGHT
     TIME      VLOB      VCH       VROB      XNL       XNCH      XNR       WTN       ELMIN     SSTA
     SLOPE     XLOBL     XLCH      XLOBR     ITRIAL    IOC       ICONT     CORAR     TOPWID    ENDST


 3470 ENCROACHMENT STATIONS=      79.3     293.0  TYPE=      4  TARGET=       0.041

        SECNO 16100 STA 192+60 FROM CORPS NOTES AND QUAD MAP

 16100.00     7.72   665.72      0.0   665.69   665.98     0.27     0.87     0.11   662.00
    1590.     139.     849.     601.     114.     153.     469.     265.      63.   660.00
     1.24     1.21     5.56     1.28    0.150    0.050    0.150    0.045   658.00    79.28
0.003245     740.     740.     740.        2        0        0      0.0   213.74   293.01

 FLOW DISTRIBUTION FOR SECNO=  16100.00          CWSEL=    665.72

 STA=      79.      80.     115.     140.     170.     240.     250.     293.
   PER Q=      0.0      8.7     53.4     14.1     19.2      1.5      2.9
    AREA=      1.9    112.6    152.9    141.5    239.1     24.2     64.5
     VEL=      0.4      1.2      5.6      1.6      1.3      1.0      0.7

 *SECNO 16500.000
  2800 NAT Q1=    371.86  WSEL=    666.66  ENC Q1=    371.86  WSEL=    666.76  RATIO=  0.0
  NAT Q1=    386.  RATIOS LOB,CH,ROB=  0.0962  0.5836  0.3202  WSEL=    666.76

 3470 ENCROACHMENT STATIONS=      138.8     340.1  TYPE=      4  TARGET=       0.036

        SECNO 16500 X

 16500.00     7.73   666.73      0.0   666.66   666.91     0.18     0.89     0.03   662.00
    1590.     128.     965.     497.     130.     224.     484.     272.      65.   662.00
     1.27     0.99     4.31     1.03    0.150    0.050    0.150    0.045   659.00   138.84
0.001868     550.     400.     275.        0        0        0      0.0   201.22   340.05

 FLOW DISTRIBUTION FOR SECNO=  16500.00          CWSEL=    666.73

 STA=      139.      173.      209.      310.      340.
   PER Q=      8.1      60.7      27.1       4.1
    AREA=    130.0     224.1     401.4      82.2
     VEL=      1.0       4.3       1.1       0.8

 CCHV=   0.300 CEHV=   0.500
 *SECNO 16900.000
  2800 NAT Q1=    321.42  WSEL=    667.43  ENC Q1=    321.42  WSEL=    667.53  RATIO=  0.0
  NAT Q1=    335.  RATIOS LOB,CH,ROB=  0.0834  0.7270  0.1896  WSEL=    667.53
```

3470 ENCROACHMENT STATIONS= 189.4 379.2 TYPE= 4 TARGET= 0.040

SECNO 16900 STA 201+70 FROM CORPS NOTES AND QUAD MAP

16900.00	7.51	667.51	0.0	667.43	667.76	0.25	0.81	0.03	664.00
1590.	105.	1205.	280.	110.	264.	287.	278.	67.	664.00
1.30	0.95	4.56	0.98	0.150	0.050	0.150	0.045	660.00	189.43
0.002478	550.	400.	275.	2	0	0	0.0	189.72	379.16

FLOW DISTRIBUTION FOR SECNO= 16900.00 CWSEL= 667.51

STA=	189.	228.	276.	350.	379.
PER Q=	6.6	75.8	14.4	3.2	
AREA=	109.7	264.5	222.7	63.9	
VEL=	1.0	4.6	1.0	0.8	

*SECNO 17295.000
2800 NAT Q1= 249.53 WSEL= 668.56 ENC Q1= 249.53 WSEL= 668.66 RATIO= 0.0000
NAT Q1= 262. RATIOS LOB,CH,ROB= 0.0753 0.7193 0.2054 WSEL= 668.66

3470 ENCROACHMENT STATIONS= 351.0 501.5 TYPE= 4 TARGET= 0.047

SECNO 17295 *

17295.00	6.26	668.66	0.0	668.56	668.98	0.32	1.19	0.04	666.50
1590.	86.	1196.	308.	75.	232.	184.	283.	68.	665.00
1.32	1.15	5.15	1.67	0.120	0.050	0.120	0.045	662.40	350.95
0.004034	75.	395.	425.	2	0	0	0.0	150.50	501.45

FLOW DISTRIBUTION FOR SECNO= 17295.00 CWSEL= 668.66

STA=	351.	392.	443.	500.	501.
PER Q=	5.4	75.2	19.2	0.2	
AREA=	75.1	232.0	180.2	3.8	
VEL=	1.1	5.2	1.7	0.8	

*SECNO 17690.000
2800 NAT Q1= 219.66 WSEL= 670.27 ENC Q1= 219.66 WSEL= 670.37 RATIO= 0.0
NAT Q1= 231. RATIOS LOB,CH,ROB= 0.0641 0.7789 0.1569 WSEL= 670.37

3470 ENCROACHMENT STATIONS= 508.9 648.7 TYPE= 4 TARGET= 0.051

SECNO 17690 STA 210+80 FROM CORPS NOTES AND QUAD MAP

17690.00	5.68	670.38	0.0	670.27	670.78	0.41	1.76	0.04	669.00
1590.	65.	1304.	221.	61.	233.	121.	286.	69.	667.00
1.35	1.06	5.59	1.82	0.120	0.050	0.120	0.045	664.70	508.94
0.005215	75.	395.	425.	2	0	0	0.0	139.71	648.65

FLOW DISTRIBUTION FOR SECNO= 17690.00 CWSEL= 670.38

STA=	509.	555.	610.	649.
PER Q=	4.1	82.0	13.9	
AREA=	61.5	233.2	121.0	
VEL=	1.1	5.6	1.8	

*SECNO 18215.000
2800 NAT Q1= 264.93 WSEL= 672.65 ENC Q1= 264.93 WSEL= 672.75 RATIO= 0.0
NAT Q1= 277. RATIOS LOB,CH,ROB= 0.0875 0.7513 0.1612 WSEL= 672.75

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	QLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOB1	XLCH	XLOBR	ITRIAL	IDF	ICONT	CORAR	TOPWID	ENDST

3470 ENCROACHMENT STATIONS= 494.0 650.5 TYPE= 4 TARGET= 0.045

SECNO 18215 X

18215.00	6.05	672.75	0.0	672.65	673.05	0.30	2.24	0.03	671.00
1590.	109.	1242.	239.	104.	254.	142.	292.	71.	669.00
1.38	1.04	4.89	1.69	0.120	0.050	0.120	0.045	666.70	493.96
0.003554	615.	525.	488.	2	0	0	0.0	156.54	650.50

FLOW DISTRIBUTION FOR SECNO= 18215.00 CWSEL= 672.75

STA=	494.	495.	555.	610.	650.	651.
PER Q=	0.1	6.8	78.1	15.0	0.0	
AREA=	1.7	102.2	254.2	140.2	1.6	
VEL=	0.5	1.1	4.9	1.7	0.4	

*SECNO 18739.000

3470 ENCROACHMENT STATIONS= 1.0 574.0 TYPE= 1 TARGET= 573.000

SECNO 18739 X

18739.00	6.31	674.91	0.0	674.85	675.50	0.59	2.30	0.15	673.10
1590.	24.	1539.	26.	28.	245.	31.	297.	72.	673.10
1.41	0.86	6.28	0.86	0.120	0.050	0.120	0.046	668.60	383.42
0.005533	614.	524.	488.	2	0	0	0.0	115.42	498.84

FLOW DISTRIBUTION FOR SECNO= 18739.00 CWSEL= 674.91

STA=	383.	415.	465.	499.
PER Q=	1.5	96.8	1.7	
AREA=	28.5	245.2	30.5	
VEL=	0.9	6.3	0.9	

*SECNO 19001.000

SECNO 19001 X

19001.00	6.78	676.28	0.0	676.27	676.75	0.46	1.21	0.04	674.00
1590.	39.	1510.	41.	46.	269.	49.	299.	73.	674.00
1.42	0.84	5.61	0.84	0.120	0.050	0.120	0.046	669.50	375.05
0.003906	307.	262.	243.	2	0	0	0.0	132.76	507.80

FLOW DISTRIBUTION FOR SECNO= 19001.00 CWSEL= 676.28

STA=	375.	415.	465.	508.
PER Q=	2.4	95.0	2.6	
AREA=	45.6	269.1	48.9	
VEL=	0.8	5.6	0.8	

*SECNO 19263.000

3470 ENCROACHMENT STATIONS= 277.0 332.0 TYPE= 1 TARGET= 55.000

SECNO 19263 50' D/S FARMINGTON FROM CORPS NOTES AND QUAD MAP

19263.00	6.77	677.27	0.0	677.27	678.02	0.75	1.13	0.14	670.60
1590.	32.	1521.	37.	26.	214.	26.	301.	74.	672.60
1.43	1.23	7.09	1.43	0.120	0.050	0.120	0.046	670.50	277.00
0.007[illegible]	307.	262.	[illegible]	[illegible]	0	0	0.0	55.00	332.00

FLOW DISTRIBUTION FOR SECNO= 19263.00 CWSEL= 677.27

STA=	277.	285.	288.	321.	332.
PER Q=	0.9	1.1	95.6	2.3	
AREA=	13.5	12.5	214.4	26.1	
VEL=	1.1	1.4	7.1	1.4	

CCHV= 0.600 CEHV= 0.600
*SECNO 19313.000

3470 ENCROACHMENT STATIONS= 1.0 354.0 TYPE= 1 TARGET= 353.000

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 679.80 ELREA= 679.80

SECNO 19313 STA 230+00 D/S FACE FARMINGTON FROM CORPS NOTES AND QUAD MAP

19313.00	6.98	677.48	0.0	677.48	678.39	0.91	0.28	0.10	670.60
1590.	0.	1590.	0.	0.	208.	0.	301.	74.	670.60
1.43	0.0	7.64	0.0	0.120	0.050	0.120	0.046	670.50	290.00
0.006562	50.	50.	50.	0	0	0	0.0	30.00	320.00

FLOW DISTRIBUTION FOR SECNO= 19313.00 CWSEL= 677.48

STA=	290.	320.
PER Q=	100.0	
AREA=	208.0	
VEL=	7.6	

SPECIAL BRIDGE

SB	XK	XKOR	COEQ	ROLEN	BWC	BWP	BAREA	SS	ELCHU	ELCHD
	0.0	1.71	3.00	0.0	30.00	0.0	210.00	0.0	670.50	670.50

*SECNO 19387.000

SECNO	DEPTH	CWSEL	CRIWS	*SELK	EG	HV	HL	ULOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNW	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

PRESSURE FLOW

EGPRS	EGLOC	H3	QWEIR	QPR	BAREA	TRAPEZOID AREA	ELLC	ELTRD
679.00	678.39	0.0	0.	1590.	210.	210.	677.50	681.10

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 681.10 ELREA= 681.10

SECNO 19387 U/S FACE FARMINGTON FROM CORPS NOTES AND QUAD MAP

19387.00	7.78	678.28	0.0	678.27	679.00	0.73	0.61	0.0	670.60
1590.	0.	1590.	0.	0.	232.	0.	301.	74.	670.60
1.43	0.0	6.85	0.0	0.120	0.050	0.120	0.046	670.50	290.00
0.004694	74.	74.	74.	2	0	0	0.0	30.00	320.00

FLOW DISTRIBUTIO FOR SECNO= 19387.00 CWSEL= 7[illegible]

STA= 290. 320.
PER Q= 100.0
AREA= 232.0
VEL= 6.9

CCHV= 0.300 CEHV= 0.500
*SECNO 19437.000

3301 HV CHANGED MORE THAN HVINS

3470 ENCROACHMENT STATIONS= 660.0 820.0 TYPE= 1 TARGET= 160.000

SECNO 19437 50' U/S FARMINGTON FROM CORPS NOTES,FIELD BOOK AND QUAD MAP

19437.00	8.52	679.02	0.0	679.02	679.24	0.22	0.09	0.15	679.60
1350.	0.	1350.	0.	0.	357.	0.	302.	74.	682.20
1.44	0.0	3.78	0.0	0.120	0.035	0.120	0.046	670.50	705.54
0.000821	50.	50.	50.	2	0	0	0.0	61.44	766.98

FLOW DISTRIBUTION FOR SECNO= 19437.00 CWSEL= 679.02

STA= 706. 773.
PER Q= 100.0
AREA= 356.8
VEL= 3.8

CCHV= 0.300 CEHV= 0.500
*SECNO 19517.000
2800 NAT Q1= 381.15 WSEL= 679.23 ENC Q1= 381.15 WSEL= 679.33 RATIO= 0.0000
NAT Q1= 397. RATIOS LOB,CH,ROB= 0.1325 0.8312 0.0363 WSEL= 679.33

3470 ENCROACHMENT STATIONS= 17.3 200.2 TYPE= 4 TARGET= 0.040

SECNO 19517

19517.00	7.62	679.22	0.0	679.23	679.35	0.14	0.08	0.03	677.00
1350.	151.	1177.	22.	166.	375.	30.	302.	74.	678.00
1.45	0.91	3.14	0.74	0.095	0.048	0.095	0.046	671.60	17.33
0.001376	80.	80.	80.	2	0	0	0.0	102.85	200.18

FLOW DISTRIBUTION FOR SECNO= 19517.00 CWSEL= 679.22

STA= 17. 100. 180. 200. 200.
PER Q= 11.2 87.2 1.6 0.0
AREA= 166.2 374.7 29.4 0.3
VEL= 0.9 3.1 0.7 0.2

*SECNO 20117.000
2800 NAT Q1= 220.22 WSEL= 680.30 ENC Q1= 220.22 WSEL= 680.40 RATIO= 0.0000
NAT Q1= 231. RATIOS LOB,CH,ROB= 0.1317 0.8679 0.0003 WSEL= 680.40

3470 ENCROACHMENT STATIONS= 235.9 330.0 TYPE= 4 TARGET= 0.047

SECNO 20117

20117.00	5.97	680.37	0.0	680.30	680.74	0.37	1.27	0.12	677.90
1350.	119.	1231.	0.	79.	242.	0.	308.	76.	680.00
1.48	1.52	5.09	0.0	0.095	0.048	0.095	0.046	674.40	235.90
0.003891	450.	600.	750.	2	0	0	0.0	94.10	330.00

FLOW DISTRIBUTION FOR SECNO= 20117.00 CWSEL= 680.37

STA= 236. 275. 330.
PER Q= 8.8 91.2
AREA= 78.7 242.0
VEL= 1.5 5.1

*SECNO 20617.000
2800 NAT Q1= 251.91 WSEL= 682.02 ENC Q1= 251.91 WSEL= 682.12 RATIO= 0.0000
NAT Q1= 264. RATIOS LOB,CH,ROB= 0.0467 0.9360 0.0173 WSEL= 682.12

3470 ENCROACHMENT STATIONS= 399.3 475.0 TYPE= 4 TARGET= 0.046

SECNO 20617 X

20617.00	6.15	682.15	0.0	682.02	682.46	0.31	1.70	0.02	680.00
1350.	26.	1324.	0.	21.	296.	0.	312.	77.	680.00
1.51	1.21	4.48	0.0	0.095	0.048	0.095	0.046	676.00	399.30
0.002942	575.	500.	425.	2	0	0	0.0	75.70	475.00

FLOW DISTRIBUTION FOR SECNO= 20617.00 CWSEL= 682.15

STA= 399. 410. 475.
PER Q= 1.9 98.1
AREA= 21.3 295.7
VEL= 1.2 4.5

*SECNO 21117.000

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

3470 ENCROACHMENT STATIONS= 535.0 675.0 TYPE= 1 TARGET= 140.000

SECNO 21117

21117.00	6.12	683.62	0.0	683.50	683.85	0.22	1.37	0.02	682.00
1350.	48.	1264.	41.	45.	324.	42.	316.	78.	682.00
1.55	1.00	3.91	0.96	0.095	0.048	0.095	0.046	677.50	535.00
0.002539	575.	500.	425.	2	0	0	0.0	140.00	675.00

FLOW DISTRIBUTION FOR SECNO= 21117.00 CWSEL= 683.62

STA= 535. 565. 645. 675.
PER Q= 3.3 93.7 3.0
AREA= 44.8 323.6 42.3
VEL= 1.0 3.9 1.0

*SECNO 21392.000
2800 NAT Q1= 179.63 WSEL= 684.42 ENC Q1= 184.89 WSEL= 684.52 RATIO= -0.0293
NAT Q1= 188. RATIOS LOB,CH,ROB= 0.0 0.9826 0.0174 WSEL= 684.52

3470 ENCROACHMENT STATIONS= 355.0 435.0 TYPE= 4 TARGET= 0.017

SECNO 21392 X

21392.00	5.42	684.52	0.0	684.42	684.93	0.41	0.99	0.09	665.50
1350.	0.	1350.	0.	0.	262.	0.	318.	79.	683.00
1.56	0.0	5.16	0.0	0.095	0.048	0.095	0.046	679.10	359.60
0.005502	200.	275.	350.	2	0	0	0.0	75.40	435.00

```
 FLOW DISTRIBUTION FOR SECNO=  21392.00          CWSEL=    684.52

 STA=      360.      435.
   PER Q=    100.0
    AREA=    261.8
     VEL=      5.2

 *SECNO 21667.000
  2800 NAT Q1=    178.05  WSEL=    686.00  ENC Q1=    178.85  WSEL=    686.10  RATIO= -0.0045
  NAT Q1=    187.  RATIOS LOB,CH,ROB=  0.0     0.9579  0.0421  WSEL=    686.10

 3470 ENCROACHMENT STATIONS=     130.0     230.0  TYPE=     4  TARGET=       0.042

        SECNO 21667

 21667.00     5.48   686.08     0.0    686.00   686.53     0.45     1.58     0.02   690.00
    1350.       0.    1350.      0.        0.     252.       0.      320.      79.   684.10
     1.5N      0.0     5.36     0.0     0.095    0.048    0.095    0.046   680.60   157.09
 0.006009      200.     275.     350.        2        0        0      0.0    72.92   230.00

 FLOW DISTRIBUTION FOR SECNO=  21667.00          CWSEL=    686.08

 STA=      157.      230.
   PER Q=    100.0
    AREA=    252.1
     VEL=      5.4

 *SECNO 22128.000
  2800 NAT Q1=    185.99  WSEL=    688.49  ENC Q1=    190.75  WSEL=    688.59  RATIO= -0.0256
  NAT Q1=    193.  RATIOS LOB,CH,ROB=  0.0062  0.9869  0.0069  WSEL=    688.59

 3470 ENCROACHMENT STATIONS=     300.0     355.0  TYPE=     4  TARGET=       0.013

        SECNO 22128 X

 22128.00     6.73   688.63     0.0    688.49   689.13     0.50     2.58     0.03   680.00
    1350.       0.    1350.      0.        0.     239.       0.      323.      80.   686.50
     1.60      0.0     5.66     0.0     0.095    0.048    0.095    0.046   681.90   300.00
 0.005210      461.     461.     461.        1        0        0      0.0    55.00   355.00

 FLOW DISTRIBUTION FOR SECNO=  22128.00          CWSEL=    688.63

 STA=      300.      355.
   PER Q=    100.0
    AREA=    238.5
     VEL=      5.7

 *SECNO 22589.000
  2800 NAT Q1=    247.92  WSEL=    690.66  ENC Q1=    247.92  WSEL=    690.76  RATIO=  0.0
  NAT Q1=    262.  RATIOS LOB,CH,ROB=  0.3805  0.6152  0.0042  WSEL=    690.76

 3470 ENCROACHMENT STATIONS=     303.0     485.0  TYPE=     4  TARGET=       0.054

        SECNO 22589 X

 22589.00     7.59   690.79     0.0    690.66   691.01     0.22     1.79     0.08   688.00
    1350.      484.     866.      0.      326.     190.       0.      327.      81.   689.00
     1.64      1.48     4.55     0.0     0.095    0.048    0.095    0.046   683.20   302.96
 0.003014      461.     461.     461.        2        0        0      0.0   182.04   485.00

 FLOW DISTRIBUTION FOR SECNO=  22589.00          CWSEL=    690.79

 STA=      303.      485.
```

PER Q=	35.8	64.2
AREA=	326.2	190.5
VEL=	1.5	4.5

*SECNO 23050.000

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IOC	ICONT	CORAR	TOPWID	ENDST
3470 ENCROACHMENT STATIONS=		1.0	799.0	TYPE=	1	TARGET=	798.000		
SECNO 23050									
23050.00	8.06	692.56	0.0	692.47	692.91	0.35	1.83	0.06	689.00
1350.	725.	593.	31.	414.	86.	19.	332.	84.	688.90
1.67	1.75	6.86	1.67	0.095	0.048	0.095	0.046	684.50	344.30
0.005496	461.	461.	461.	2	0	0	0.0	279.02	623.32
FLOW DISTRIBUTION FOR SECNO=		23050.00		CWSEL=	692.56				

STA=	344.	400.	500.	575.	600.	613.	623.
PER Q=	1.7	19.0	21.5	11.6	44.0	2.3	
AREA=	29.5	160.8	154.4	69.0	86.5	18.9	
VEL=	0.8	1.6	1.9	2.3	6.9	1.7	

*SECNO 23550.000

2800 NAT Q1= 374.96 WSEL= 693.99 ENC Q1= 374.96 WSEL= 694.09 RATIO= 0.0
NAT Q1= 389. RATIOS LOB,CH,ROB= 0.1332 0.8291 0.0377 WSEL= 694.09

3470 ENCROACHMENT STATIONS= 227.7 336.9 TYPE= 4 TARGET= 0.035

SECNO 23550

23550.00	6.51	694.01	0.0	693.99	694.10	0.17	1.22	0.05	690.00
1350.	160.	1165.	25.	133.	328.	24.	338.	86.	690.00
1.71	1.20	3.55	1.05	0.095	0.048	0.095	0.046	687.50	227.69
0.001375	500.	500.	500.	2	0	0	0.0	109.16	336.85

FLOW DISTRIBUTION FOR SECNO= 23550.00 CWSEL= 694.01

STA=	228.	270.	330.	337.
PER Q=	11.8	86.3	1.9	
AREA=	133.1	327.9	24.1	
VEL=	1.2	3.6	1.0	

*SECNO 24226.000

3470 ENCROACHMENT STATIONS= 118.0 360.0 TYPE= 1 TARGET= 242.000

SECNO 24226 24' D/S 8 MILE

24226.00	5.90	695.06	0.0	695.01	695.30	0.24	1.08	0.04	692.46
1210.	130.	904.	177.	132.	199.	147.	345.	88.	692.46
1.76	0.98	4.53	1.20	0.080	0.040	0.080	0.046	689.16	133.19
0.001964	550.	676.	800.	3	0	0	0.0	226.81	360.00

FLOW DISTRIBUTION FOR SECNO= 24226.00 CWSEL= 695.06

STA=	133.	235.	278.	360.
PER Q=	10.7	7.7	1.1	

```
AREA=     13.3      1?.3      1 6.8
 VEL=      1.0       4.5       1.2

*SECNO 24250.000

3470 ENCROACHMENT STATIONS=        0.5      354.0  TYPE=      1  TARGET=      353.500

          SECNO 24250 D/S FACE 8 MILE

 24250.00      5.94    695.14       0.0    695.09    695.34      0.21      0.03      0.01    692.50
    1210.       151.      858.      200.      136.      201.      143.      345.       89.    692.50
     1.77      1.11      4.27      1.40     0.050     0.030     0.050     0.046    689.20    131.78
0.000971         24.       24.       24.         2         0         0       0.0    222.22    354.00

FLOW DISTRIBUTION FOR SECNO=  24250.00          CWSEL=     695.14

STA=      132.      235.      278.      354.
 PER Q=    12.5      70.9      16.6
 AREA=    136.0     200.9     143.3
  VEL=      1.1       4.3       1.4
```

****
HEC2 RELEASE DATED NOV 76 UPDATED AUG1977
ERROR CORR - 01,02
MODIFICATION - 50,51,52,53
****

NOTE- ASTERISK (*) AT LEFT OF CROSS-SECTION NUMBER INDICATES MESSAGE IN SUMMARY OF ERRORS LIST

TARABUSI CREEK LIVONIA C

SUMMARY PRINTOUT TABLE 110

SECNO	CWSEL	DIFKWS	EG	TOPWID	QLOB	QCH	QROB	PERENC	STENCL	STCHL	STCHR	STENCR
120.000	620.00	0.0	620.76	220.00	269.75	1261.32	238.93	290.00	250.00	405.00	440.00	540.00
120.000	620.10	0.10	620.79	221.00	279.10	1238.97	251.92	290.00	250.00	405.00	440.00	540.00
370.000	621.72	0.0	622.35	159.10	417.80	1138.34	213.85	0.0	0.0	140.00	170.00	0.0
370.000	621.65	-0.07	622.39	122.61	394.04	1190.91	185.04	0.04	76.67	140.00	170.00	199.28
745.000	623.30	0.0	623.72	142.72	343.06	1175.44	251.50	0.0	0.0	126.00	155.00	0.0
745.000	623.42	0.11	623.86	98.38	327.31	1211.17	231.52	0.03	85.81	126.00	155.00	184.19
1120.000	624.21	0.0	624.88	120.72	196.85	1271.08	302.06	0.0	0.0	117.00	140.00	0.0
1120.000	624.32	0.11	624.96	122.73	201.18	1262.14	306.68	263.00	1.00	117.00	140.00	264.00
1770.000	625.84	0.0	626.21	121.13	246.48	1371.91	151.60	0.0	0.0	190.00	220.00	0.0
1770.000	625.87	0.03	626.26	75.98	236.45	1394.94	138.60	0.02	161.34	190.00	220.00	237.33
2416.000	626.67	0.0	627.19	69.65	81.66	1555.83	132.51	0.0	0.0	271.00	300.00	0.0
2416.000	626.72	0.05	627.26	51.39	66.32	1584.02	119.66	0.02	262.53	271.00	300.00	313.92
2466.000	627.09	0.0	627.34	73.80	0.0	1770.00	0.0	0.0	0.0	371.60	445.40	0.0
2466.000	627.17	0.08	627.42	73.80	0.0	1770.00	0.0	0.0	371.60	371.60	445.40	445.40
2554.000	627.10	0.0	627.35	73.80	0.0	1770.00	0.0	0.0	0.0	371.60	445.40	0.0
2554.000	627.20	0.10	627.44	73.80	0.0	1770.00	0.0	0.0	445.40	371.60	445.40	0.0
2604.000	627.22	0.0	627.43	145.67	255.52	1427.38	87.10	174.00	111.00	177.50	220.50	285.00
2604.000	627.32	0.09	627.52	145.96	258.61	1422.31	89.08	174.00	111.00	177.50	220.50	285.00
3360.000	628.31	0.0	628.61	237.48	250.02	1398.99	120.99	0.0	0.0	180.00	223.00	0.0
3360.000	628.38	0.07	628.69	169.12	233.59	1436.87	99.55	0.03	95.12	180.00	223.00	264.24
4116.000	630.07	0.0	630.42	150.00	191.20	1418.41	160.39	150.00	123.00	177.00	219.00	273.00
4116.000	630.13	0.07	630.47	150.00	194.30	1412.03	163.67	150.00	123.00	177.00	219.00	273.00
4316.000	630.27	0.0	632.73	31.18	100.03	1571.22	98.75	0.0	0.0	42.30	57.80	0.0
4316.000	630.30	0.04	632.74	31.25	100.45	1570.38	99.17	414.00	1.00	42.30	57.80	415.00
4403.000	634.30	0.0	635.07	98.04	177.78	1416.34	175.88	0.0	0.0	42.30	57.80	0.0
4403.000	634.31	0.01	635.08	98.04	178.25	1415.41	176.35	0.0	0.0	42.30	57.80	0.0

SECNO	CWSEL	DIFKWS	EG	TOPWID	QLOB	QCH	QROB	PERENC	STENCL	STCHL	STCHR	STENCR
4453.000	635.37	0.0	635.41	192.60	582.18	366.03	821.80	428.00	54.90	148.50	160.65	247.50
4453.000	635.38	0.01	635.42	192.60	582.38	365.86	821.76	428.00	54.90	148.50	160.65	247.50
5950.000	635.89	0.0	635.94	353.51	655.60	699.16	415.23	0.0	0.0	235.00	265.00	0.0
5950.000	635.91	0.02	635.96	302.13	645.20	715.36	409.44	0.03	68.26	235.00	265.00	370.39
6600.000	636.18	0.0	636.32	327.33	156.26	1172.21	441.53	0.0	0.0	110.00	165.00	0.0
6600.000	636.20	0.03	636.36	235.13	129.50	1213.82	426.68	0.04	71.15	110.00	165.00	306.29
7340.000	637.26	0.0	637.42	268.62	780.52	553.34	406.14	0.0	0.0	200.00	222.00	0.0
7340.000	637.33	0.07	637.50	258.27	784.87	571.22	413.91	0.05	59.73	200.00	222.00	298.00
8078.000	639.24	0.0	639.56	321.62	540.82	1004.61	224.57	0.0	0.0	210.00	240.00	0.0
8078.000	639.33	0.09	639.68	196.66	534.41	1037.77	197.82	0.05	84.09	210.00	240.00	280.75
8815.000	641.02	0.0	641.29	332.93	345.36	1208.94	215.70	0.0	0.0	210.00	253.00	0.0
8815.000	641.13	0.11	641.41	232.62	332.44	1244.98	192.58	0.05	88.02	210.00	253.00	320.64
9276.000	641.99	0.0	642.51	184.31	170.59	1553.03	46.39	0.0	0.0	205.00	250.00	0.0
9276.000	642.08	0.10	642.64	92.70	155.65	1601.55	12.80	0.04	161.18	205.00	250.00	253.88
9737.000	643.29	0.0	643.73	190.30	207.19	1509.20	53.61	0.0	0.0	205.00	250.00	0.0
9737.000	643.41	0.11	643.86	106.44	194.48	1553.25	22.27	0.04	149.70	205.00	250.00	256.14
10198.000	644.33	0.0	644.75	191.07	212.12	1503.26	54.61	0.0	0.0	205.00	250.00	0.0
10198.000	644.45	0.12	644.89	109.70	200.72	1543.58	25.70	0.03	147.31	205.00	250.00	257.02
10658.000	645.51	0.0	646.24	80.00	95.86	1557.26	116.89	80.00	183.00	205.00	240.00	263.00
10658.000	645.61	0.10	646.31	80.00	98.66	1551.70	119.63	80.00	183.00	205.00	240.00	263.00
10708.000	646.10	0.0	646.51	64.00	0.0	1770.00	0.0	0.0	0.0	208.00	272.00	0.0
10708.000	646.17	0.07	646.56	64.00	0.0	1770.00	0.0	0.0	208.00	208.00	272.00	272.00
10782.000	646.16	0.0	646.55	64.00	0.0	1770.00	0.0	0.0	0.0	208.00	272.00	0.0
10782.000	646.26	0.10	646.64	64.00	0.0	1770.00	0.0	0.0	272.00	208.00	272.00	0.0
10832.000	646.51	0.0	646.68	155.00	132.20	1265.35	192.45	155.00	145.00	197.00	247.00	300.00
10832.000	646.60	0.09	646.76	155.00	135.03	1260.23	194.75	155.00	145.00	197.00	247.00	300.00
11720.000	647.92	0.0	648.31	339.81	311.27	1141.78	136.94	0.0	0.0	530.00	580.00	0.0
11720.000	647.95	0.03	648.39	250.76	286.64	1201.44	101.91	0.06	383.00	530.00	580.00	633.76
12145.000	649.75	0.0	649.91	363.51	404.59	988.95	196.46	0.0	0.0	530.00	580.00	0.0
12145.000	649.87	0.12	650.04	284.32	393.47	1022.84	173.69	0.05	373.21	530.00	580.00	657.53
12570.000	650.90	0.0	651.16	395.98	396.80	1129.30	63.90	0.0	0.0	488.00	538.00	0.0
12570.000	651.00	0.10	651.28	252.20	389.21	1168.65	32.14	0.05	320.94	488.00	538.00	573.15
12965.000	652.36	0.0	652.66	389.52	378.25	1157.65	54.10	0.0	0.0	488.00	538.00	0.0
12965.000	652.45	0.10	652.77	231.79	368.29	1201.92	19.79	0.05	330.14	488.00	538.00	561.93
13360.000	654.04	0.0	654.50	197.56	192.72	1232.12	165.16	0.0	0.0	270.00	310.00	0.0
13360.000	654.12	0.08	654.55	200.53	196.45	1225.20	168.35	823.00	1.00	270.00	310.00	824.00
13704.000	655.75	0.0	656.23	193.93	188.13	1240.66	161.21	0.0	0.0	270.00	310.00	0.0
13704.000	655.76	0.01	656.24	194.23	188.51	1239.94	161.55	0.0	0.0	270.00	310.00	0.0

SECNO	CWSEL	DIFKWS	EG	TOPWID	QLOB	QCH	QROB	PERENC	STENCL	STCHL	STCHR	STENCR
14047.000	657.54	0.0	658.02	193.54	187.63	1241.58	160.79	0.0	0.0	270.00	310.00	0.0
14047.000	657.54	0.00	658.02	193.55	187.65	1241.54	160.81	0.0	0.0	270.00	310.00	0.0
14219.000	658.43	0.0	658.81	124.00	328.63	1018.59	242.78	124.00	400.00	447.00	476.00	524.00
14219.000	658.43	0.00	658.81	124.00	328.63	1018.60	242.77	124.00	400.00	447.00	476.00	524.00
14390.000	658.91	0.0	661.08	38.22	149.74	1278.64	161.62	42.00	556.92	567.84	584.22	595.14
14390.000	658.91	0.00	661.08	38.22	149.74	1278.64	161.61	42.00	556.92	567.84	584.22	595.14
14440.000	659.64	0.0	662.79	18.20	0.0	1590.00	0.0	0.0	0.0	675.22	693.42	0.0
14440.000	659.64	0.00	662.79	18.20	0.0	1590.00	0.0	0.0	0.0	675.22	693.42	0.0
14501.000	662.38	0.0	663.88	18.20	0.0	1590.00	0.0	0.0	0.0	675.22	693.42	0.0
14501.000	662.38	0.0	663.88	18.20	0.0	1590.00	0.0	0.0	0.0	675.22	693.42	0.0
14570.000	664.49	0.0	664.55	171.08	505.28	631.35	453.37	188.00	219.31	295.75	314.86	390.39
14570.000	664.49	0.0	664.55	171.08	505.28	631.35	453.37	188.00	219.31	295.75	314.86	390.39
15360.000	664.91	0.0	665.00	172.01	342.06	1003.57	244.37	0.0	0.0	84.00	125.00	0.0
15360.000	664.91	0.00	665.01	149.61	334.10	1017.05	238.85	0.02	27.96	84.00	125.00	177.57
16100.000	665.69	0.0	665.93	375.02	165.15	820.87	603.98	0.0	0.0	115.00	140.00	0.0
16100.000	665.72	0.03	665.98	213.74	139.11	849.44	601.45	0.04	79.28	115.00	140.00	293.01
16500.000	666.66	0.0	666.83	320.77	149.98	937.30	502.73	0.0	0.0	173.00	209.00	0.0
16500.000	666.73	0.07	666.91	201.22	128.46	964.71	496.83	0.06	138.84	173.00	209.00	340.05
16900.000	667.43	0.0	667.66	305.99	128.64	1168.36	293.01	0.0	0.0	228.00	276.00	0.0
16900.000	667.51	0.08	667.76	189.72	104.69	1205.28	280.02	0.04	189.43	228.00	276.00	379.16
17295.000	668.56	0.0	668.86	230.43	111.74	1155.55	322.72	0.0	0.0	392.00	443.00	0.0
17295.000	668.66	0.10	668.98	150.50	86.31	1195.61	308.08	0.05	350.95	392.00	443.00	501.45
17690.000	670.27	0.0	670.65	217.69	91.82	1250.91	247.26	0.0	0.0	555.00	610.00	0.0
17690.000	670.38	0.11	670.78	139.71	65.45	1303.71	220.84	0.05	508.94	555.00	610.00	648.65
18215.000	672.65	0.0	672.94	235.94	129.53	1205.71	254.76	0.0	0.0	555.00	610.00	0.0
18215.000	672.75	0.10	673.05	156.54	108.62	1241.99	239.39	0.04	493.96	555.00	610.00	650.50
18739.000	674.85	0.0	675.46	113.48	23.06	1542.23	24.71	0.0	0.0	415.00	465.00	0.0
18739.000	674.91	0.05	675.50	115.42	24.49	1539.27	26.24	573.00	1.00	415.00	465.00	574.00
19001.000	676.27	0.0	676.74	132.44	38.23	1510.79	40.97	0.0	0.0	415.00	465.00	0.0
19001.000	676.28	0.01	676.75	132.76	38.51	1510.22	41.27	0.0	0.0	415.00	465.00	0.0
19263.000	677.27	0.0	678.02	55.00	32.04	1520.69	37.27	55.00	277.00	288.00	321.00	332.00
19263.000	677.27	0.00	678.02	55.00	32.08	1520.61	37.31	55.00	277.00	288.00	321.00	332.00
19313.000	677.48	0.0	678.39	30.00	0.0	1590.00	0.0	0.0	0.0	290.00	320.00	0.0
19313.000	677.48	0.00	678.39	30.00	0.0	1590.00	0.0	353.00	1.00	290.00	320.00	354.00
19387.000	678.27	0.0	679.00	30.00	0.0	1590.00	0.0	0.0	0.0	290.00	320.00	0.0
19387.000	678.28	0.00	679.00	30.00	0.0	1590.00	0.0	0.0	0.0	290.00	320.00	0.0
19437.000	679.02	0.0	679.24	61.43	0.0	1350.00	0.0	160.00	660.00	704.00	773.00	820.00
19437.000	679.02	0.00	679.24	61.44	0.0	1350.00	0.0	160.00	660.00	704.00	773.00	820.00

SECNO	CWSEL	DIFKWS	EG	TOPWID	QLOB	QCH	QROB	PERENC	STENCL	STCHL	STCHR	STENCR
19517.000	679.23	0.0	679.35	230.24	172.63	1131.62	45.75	0.0	0.0	100.00	180.00	0.0
19517.000	679.22	-0.01	679.35	182.85	151.39	1176.54	22.08	0.04	17.33	100.00	180.00	200.18
20117.000	680.30	0.0	680.64	286.06	161.07	1188.68	0.25	0.0	0.0	275.00	330.00	0.0
20117.000	680.37	0.07	680.74	94.10	119.28	1230.72	0.0	0.05	235.90	275.00	330.00	330.00
20617.000	682.02	0.0	682.31	158.01	57.41	1271.36	21.23	0.0	0.0	410.00	475.00	0.0
20617.000	682.15	0.13	682.46	75.70	25.72	1324.28	0.0	0.05	399.30	410.00	475.00	475.00
21117.000	683.50	0.0	683.71	245.00	71.58	1225.00	53.42	245.00	500.00	565.00	645.00	745.00
21117.000	683.62	0.13	683.85	140.00	44.73	1264.50	40.77	140.00	535.00	565.00	645.00	675.00
21392.000	684.42	0.0	684.84	105.79	0.0	1329.46	20.54	0.0	0.0	355.00	435.00	0.0
21392.000	684.52	0.10	684.93	75.40	0.0	1350.00	0.0	0.04	355.00	355.00	435.00	435.00
21667.000	686.00	0.0	686.42	119.96	0.0	1298.22	51.78	0.0	0.0	130.00	230.00	0.0
21667.000	686.08	0.08	686.53	72.92	0.0	1350.00	0.0	0.04	130.00	130.00	230.00	230.00
22128.000	688.49	0.0	689.00	112.57	5.59	1335.87	8.53	0.0	0.0	300.00	355.00	0.0
22128.000	688.63	0.14	689.13	55.00	0.0	1350.00	0.0	0.01	300.00	300.00	355.00	355.00
22589.000	690.66	0.0	690.88	276.38	498.24	846.63	5.13	0.0	0.0	445.00	485.00	0.0
22589.000	690.79	0.12	691.01	182.04	483.64	866.36	0.0	0.05	302.96	445.00	485.00	485.00
23050.000	692.47	0.0	692.86	274.33	706.91	611.94	31.15	0.0	0.0	600.00	613.00	0.0
23050.000	692.56	0.08	692.91	279.02	725.07	593.46	31.47	798.00	1.00	600.00	613.00	799.00
23550.000	693.99	0.0	694.15	185.94	174.56	1125.96	49.48	0.0	0.0	270.00	330.00	0.0
23550.000	694.01	0.02	694.18	109.16	159.92	1164.87	25.21	0.04	227.69	270.00	330.00	336.85
24226.000	695.01	0.0	695.27	225.04	126.68	909.93	173.39	242.00	118.00	235.00	278.00	360.00
24226.000	695.06	0.04	695.30	226.81	129.69	903.60	176.71	242.00	118.00	235.00	278.00	360.00
24250.000	695.09	0.0	695.31	220.63	148.36	864.04	197.60	353.50	0.50	235.00	278.00	354.00
24250.000	695.14	0.04	695.34	222.22	151.36	858.15	200.49	353.50	0.50	235.00	278.00	354.00

TARABUSI CREEK LIVONIA C

SUMMARY PRINTOUT TABLE 150

SECNO	XLCH	ELTRD	ELLC	ELMIN	Q	CWSEL	CRIWS	EG	10K*S	VCH	AREA	.01K
120.000	0.0	0.0	0.0	613.20	1770.00	620.00	0.0	620.76	71.32	8.21	444.48	209.58
120.000	0.0	0.0	0.0	613.20	1770.00	620.10	0.0	620.79	63.85	7.88	466.50	221.51
370.000	250.00	0.0	0.0	615.30	1770.00	621.72	0.0	622.35	54.59	7.79	452.61	239.55
370.000	250.00	0.0	0.0	615.30	1770.00	621.65	0.0	622.39	62.57	8.26	400.78	223.76
745.000	375.00	0.0	0.0	615.70	1770.00	623.30	0.0	623.72	24.29	6.29	535.77	359.15
745.000	375.00	0.0	0.0	615.70	1770.00	623.42	0.0	623.86	24.25	6.36	486.11	359.41
1120.000	375.00	0.0	0.0	616.00	1770.00	624.21	0.0	624.88	31.28	7.67	439.56	316.47
1120.000	375.00	0.0	0.0	616.00	1770.00	624.32	0.0	624.96	29.30	7.50	453.14	326.98
1770.000	650.00	0.0	0.0	617.00	1770.00	625.84	0.0	626.21	12.90	5.48	543.58	492.76
1770.000	650.00	0.0	0.0	617.00	1770.00	625.87	0.0	626.26	13.18	5.55	499.33	487.56
2416.000	646.00	0.0	0.0	617.90	1770.00	626.67	0.0	627.19	15.27	6.15	429.16	452.96
2416.000	646.00	0.0	0.0	617.90	1770.00	626.72	0.0	627.26	15.55	6.23	395.95	448.85
2466.000	50.00	0.0	0.0	617.90	1770.00	627.09	0.0	627.34	11.85	4.04	438.30	514.15
2466.000	50.00	0.0	0.0	617.90	1770.00	627.17	0.0	627.42	11.70	3.98	444.54	517.37
2554.000	88.00	632.60	629.40	617.90	1770.00	627.10	0.0	627.35	11.76	4.03	439.30	516.03
2554.000	88.00	632.60	629.40	617.90	1770.00	627.20	0.0	627.44	11.15	3.96	446.67	530.09
2604.000	50.00	0.0	0.0	617.90	1770.00	627.22	0.0	627.43	11.50	4.03	761.17	521.87
2604.000	50.00	0.0	0.0	617.90	1770.00	627.32	0.0	627.52	11.00	3.97	774.98	533.79
3360.000	756.00	0.0	0.0	620.30	1770.00	628.31	0.0	628.61	22.32	4.85	729.12	374.64
3360.000	756.00	0.0	0.0	620.30	1770.00	628.38	0.0	628.69	22.77	4.93	650.21	370.94
4116.000	756.00	0.0	0.0	622.60	1770.00	630.07	0.0	630.42	27.42	5.25	558.51	337.99
4116.000	756.00	0.0	0.0	622.60	1770.00	630.13	0.0	630.47	26.28	5.17	568.24	345.24
4316.000	200.00	0.0	0.0	622.60	1770.00	630.27	0.0	632.73	133.58	13.30	177.47	153.15
4316.000	200.00	0.0	0.0	622.60	1770.00	630.30	0.0	632.74	131.37	13.23	178.59	154.43
4403.000	87.00	632.90	628.90	622.60	1770.00	634.30	0.0	635.07	26.37	7.84	386.90	344.69
4403.000	87.00	632.90	628.90	622.60	1770.00	634.31	0.0	635.08	26.25	7.83	387.96	345.45
4453.000	50.00	0.0	0.0	622.60	1770.00	635.37	0.0	635.41	3.71	2.44	1418.44	919.18
4453.000	50.00	0.0	0.0	622.60	1770.00	635.38	0.0	635.42	3.70	2.44	1419.76	920.44
5950.000	1497.00	0.0	0.0	626.60	1770.00	635.89	0.0	635.94	3.30	2.72	1681.50	974.24
5950.000	1497.00	0.0	0.0	626.60	1770.00	635.91	0.0	635.96	3.44	2.78	1587.85	953.63
6600.000	650.00	0.0	0.0	628.80	1770.00	636.18	0.0	636.32	9.61	3.69	999.54	570.98
6600.000	650.00	0.0	0.0	628.80	1770.00	636.20	0.0	636.36	10.14	3.80	879.46	555.76
7340.000	740.00	0.0	0.0	631.70	1770.00	637.26	0.0	637.42	25.43	5.21	862.79	350.98
7340.000	740.00	0.0	0.0	631.70	1770.00	637.33	0.0	637.50	25.75	5.30	828.32	348.81
8078.000	738.00	0.0	0.0	632.90	1770.00	639.24	0.0	639.56	26.42	5.94	777.75	344.33
8078.000	738.00	0.0	0.0	632.90	1770.00	639.33	0.0	639.68	26.80	6.04	650.43	341.93

SECNO	XLCH	ELTRD	ELLC	ELMIN	Q	CWSEL	CRIWS	EG	10K*S	VCH	AREA	.01K
8815.000	737.00	0.0	0.0	634.00	1770.00	641.02	0.0	641.29	18.90	5.02	791.68	407.16
8815.000	737.00	0.0	0.0	634.00	1770.00	641.13	0.0	641.41	18.79	5.07	703.72	408.28
9276.000	461.00	0.0	0.0	634.90	1770.00	641.99	0.0	642.51	28.95	6.19	458.74	328.96
9276.000	461.00	0.0	0.0	634.90	1770.00	642.08	0.0	642.64	29.04	6.28	375.39	328.45
9737.000	461.00	0.0	0.0	635.90	1770.00	643.29	0.0	643.73	22.82	5.70	516.95	370.52
9737.000	461.00	0.0	0.0	635.90	1770.00	643.41	0.0	643.86	22.73	5.76	435.29	371.23
10198.000	461.00	0.0	0.0	636.90	1770.00	644.33	0.0	644.75	22.10	5.64	525.17	376.54
10198.000	461.00	0.0	0.0	636.90	1770.00	644.45	0.0	644.89	21.93	5.68	446.77	377.94
10658.000	460.00	0.0	0.0	637.80	1770.00	645.51	0.0	646.24	39.03	7.28	338.57	283.33
10658.000	460.00	0.0	0.0	637.80	1770.00	645.61	0.0	646.31	36.71	7.14	346.57	292.14
10708.000	50.00	0.0	0.0	638.00	1770.00	646.10	0.0	646.51	21.50	5.10	346.94	381.74
10708.000	50.00	0.0	0.0	638.00	1770.00	646.17	0.0	646.56	21.05	5.04	351.05	385.80
10782.000	74.00	654.00	653.10	638.00	1770.00	646.16	0.0	646.55	20.93	5.06	349.84	386.91
10782.000	74.00	654.00	653.10	638.00	1770.00	646.26	0.0	646.64	19.74	4.97	356.23	398.37
10832.000	50.00	0.0	0.0	637.80	1590.00	646.51	0.0	646.68	7.80	3.68	700.46	569.49
10832.000	50.00	0.0	0.0	637.80	1590.00	646.60	0.0	646.76	7.42	3.62	713.82	583.80
11720.000	888.00	0.0	0.0	642.70	1590.00	647.92	0.0	648.31	63.33	5.83	624.61	199.80
11720.000	888.00	0.0	0.0	642.70	1590.00	647.95	0.0	648.39	68.34	6.08	536.01	192.33
12145.000	425.00	0.0	0.0	643.60	1590.00	649.75	0.0	649.91	23.40	4.08	949.13	320.14
12145.000	425.00	0.0	0.0	643.60	1590.00	649.87	0.0	650.04	23.15	4.12	872.72	330.44
12570.000	425.00	0.0	0.0	644.40	1590.00	650.90	0.0	651.16	34.61	4.85	765.23	270.28
12570.000	425.00	0.0	0.0	644.40	1590.00	651.00	0.0	651.28	34.28	4.90	664.66	271.56
12965.000	395.00	0.0	0.0	646.00	1590.00	652.36	0.0	652.66	40.42	5.13	708.10	250.08
12965.000	395.00	0.0	0.0	646.00	1590.00	652.45	0.0	652.77	40.61	5.21	599.83	249.50
13360.000	395.00	0.0	0.0	647.50	1590.00	654.04	0.0	654.50	50.54	6.12	519.48	223.66
13360.000	395.00	0.0	0.0	647.50	1590.00	654.12	0.0	654.55	47.53	6.00	534.64	230.63
13704.000	344.00	0.0	0.0	649.30	1590.00	655.75	0.0	656.23	54.54	6.28	501.23	215.31
13704.000	344.00	0.0	0.0	649.30	1590.00	655.76	0.0	656.24	54.19	6.27	502.74	216.00
14047.000	343.00	0.0	0.0	651.10	1590.00	657.54	0.0	658.02	54.98	6.30	499.31	214.43
14047.000	343.00	0.0	0.0	651.10	1590.00	657.54	0.0	658.02	54.97	6.30	499.38	214.46
14219.000	172.00	0.0	0.0	652.00	1590.00	658.43	0.0	658.81	40.52	6.08	542.92	249.78
14219.000	172.00	0.0	0.0	652.00	1590.00	658.43	0.0	658.81	40.53	6.08	542.89	249.76
14390.000	171.00	0.0	0.0	652.90	1590.00	658.91	0.0	661.08	179.21	13.09	199.78	118.77
14390.000	171.00	0.0	0.0	652.90	1590.00	658.91	0.0	661.08	179.28	13.09	199.77	118.76
14440.000	50.00	0.0	0.0	652.90	1590.00	659.64	659.54	662.79	285.91	14.25	111.60	94.03
14440.000	50.00	0.0	0.0	652.90	1590.00	659.64	659.54	662.79	285.97	14.25	111.59	94.02
14501.000	61.00	663.40	659.50	652.90	1590.00	662.38	0.0	663.88	96.20	9.83	161.79	162.11
14501.000	61.00	663.40	659.50	652.90	1590.00	662.38	0.0	663.88	96.20	9.83	161.79	162.11

SECNO	XLCH	ELTRD	ELLC	ELMIN	Q	CWSEL	CRIWS	EG	10K*S	VCH	AREA	.01K
14570.000	69.00	0.0	0.0	651.80	1590.00	664.49	0.0	664.55	5.11	3.06	1369.19	703.17
14570.000	69.00	0.0	0.0	651.80	1590.00	664.49	0.0	664.55	5.11	3.06	1369.19	703.17
15360.000	790.00	0.0	0.0	655.00	1590.00	664.91	0.0	665.00	5.87	2.91	1080.89	656.25
15360.000	790.00	0.0	0.0	655.00	1590.00	664.91	0.0	665.01	6.03	2.95	1035.12	647.51
16100.000	740.00	0.0	0.0	658.00	1590.00	665.69	0.0	665.93	30.71	5.39	857.37	286.91
16100.000	740.00	0.0	0.0	658.00	1590.00	665.72	0.0	665.98	32.45	5.56	736.66	279.11
16500.000	400.00	0.0	0.0	659.00	1590.00	666.66	0.0	666.83	18.28	4.23	971.39	371.86
16500.000	400.00	0.0	0.0	659.00	1590.00	666.73	0.0	666.91	18.68	4.31	837.69	367.85
16900.000	400.00	0.0	0.0	660.00	1590.00	667.43	0.0	667.66	24.47	4.48	763.95	321.42
16900.000	400.00	0.0	0.0	660.00	1590.00	667.51	0.0	667.76	24.78	4.56	660.88	319.42
17295.000	395.00	0.0	0.0	662.40	1590.00	668.56	0.0	668.86	40.60	5.09	550.70	249.53
17295.000	395.00	0.0	0.0	662.40	1590.00	668.66	0.0	668.98	40.34	5.15	491.09	250.33
17690.000	395.00	0.0	0.0	664.70	1590.00	670.27	0.0	670.65	52.40	5.51	468.54	219.66
17690.000	395.00	0.0	0.0	664.70	1590.00	670.38	0.0	670.78	52.15	5.59	415.77	220.17
18215.000	525.00	0.0	0.0	666.70	1590.00	672.65	0.0	672.94	36.02	4.85	557.13	264.93
18215.000	525.00	0.0	0.0	666.70	1590.00	672.75	0.0	673.05	35.54	4.89	499.90	266.73
18739.000	524.00	0.0	0.0	668.60	1590.00	674.85	0.0	675.46	57.62	6.36	298.14	209.47
18739.000	524.00	0.0	0.0	668.60	1590.00	674.91	0.0	675.50	55.33	6.28	304.27	213.76
19001.000	262.00	0.0	0.0	669.50	1590.00	676.27	0.0	676.74	39.30	5.62	362.45	253.62
19001.000	262.00	0.0	0.0	669.50	1590.00	676.28	0.0	676.75	39.06	5.61	363.61	254.40
19263.000	262.00	0.0	0.0	670.50	1590.00	677.27	0.0	678.02	47.61	7.10	266.23	230.44
19263.000	262.00	0.0	0.0	670.50	1590.00	677.27	0.0	678.02	47.53	7.09	266.40	230.63
19313.000	50.00	0.0	0.0	670.50	1590.00	677.48	0.0	678.39	65.68	7.64	207.98	196.19
19313.000	50.00	0.0	0.0	670.50	1590.00	677.48	0.0	678.39	65.62	7.64	208.05	196.28
19387.000	74.00	681.10	677.50	670.50	1590.00	678.27	0.0	679.00	47.00	6.86	231.92	231.92
19387.000	74.00	681.10	677.50	670.50	1590.00	678.28	0.0	679.00	46.94	6.85	232.02	232.06
19437.000	50.00	0.0	0.0	670.50	1350.00	679.02	0.0	679.24	8.22	3.79	356.64	470.87
19437.000	50.00	0.0	0.0	670.50	1350.00	679.02	0.0	679.24	8.21	3.78	356.81	471.17
19517.000	80.00	0.0	0.0	671.60	1350.00	679.23	0.0	679.35	12.54	3.01	640.45	381.15
19517.000	80.00	0.0	0.0	671.60	1350.00	679.22	0.0	679.35	13.76	3.14	570.58	363.93
20117.000	600.00	0.0	0.0	674.40	1350.00	680.30	0.0	680.64	37.58	4.98	401.77	220.22
20117.000	600.00	0.0	0.0	674.40	1350.00	680.37	0.0	680.74	38.91	5.09	320.67	216.42
20617.000	500.00	0.0	0.0	676.00	1350.00	682.02	0.0	682.31	28.72	4.43	380.26	251.91
20617.000	500.00	0.0	0.0	676.00	1350.00	682.15	0.0	682.46	29.42	4.48	316.95	248.88
21117.000	500.00	0.0	0.0	677.50	1350.00	683.50	0.0	683.71	26.49	3.91	470.56	262.31
21117.000	500.00	0.0	0.0	677.50	1350.00	683.62	0.0	683.85	25.39	3.91	410.58	267.92
21392.000	275.00	0.0	0.0	679.10	1350.00	684.42	0.0	684.84	56.48	5.22	276.50	179.63
21392.000	275.00	0.0	0.0	679.10	1350.00	684.52	0.0	684.93	55.02	5.16	281.77	182.00

SECNO	XLCH	ELTRD	ELLC	ELMIN	Q	CWSEL	CRIWS	EG	10K*S	VCH	AREA	.01K
21667.000	275.00	0.0	0.0	680.60	1350.00	686.00	0.0	686.42	57.49	5.28	291.20	178.05
21667.000	275.00	0.0	0.0	680.60	1350.00	686.08	0.0	686.53	60.09	5.36	252.10	174.15
22128.000	461.00	0.0	0.0	681.90	1350.00	688.49	0.0	689.00	52.68	5.77	251.55	185.99
22128.000	461.00	0.0	0.0	681.90	1350.00	688.63	0.0	689.13	52.10	5.66	238.52	187.04
22589.000	461.00	0.0	0.0	683.20	1350.00	690.66	0.0	690.88	29.65	4.57	574.79	247.92
22589.000	461.00	0.0	0.0	683.20	1350.00	690.79	0.0	691.01	30.14	4.55	516.71	245.89
23050.000	461.00	0.0	0.0	684.50	1350.00	692.47	0.0	692.86	60.98	7.17	495.58	172.88
23050.000	461.00	0.0	0.0	684.50	1350.00	692.56	0.0	692.91	54.96	6.86	518.96	182.10
23550.000	500.00	0.0	0.0	687.50	1350.00	693.99	0.0	694.15	12.96	3.44	578.45	374.96
23550.000	500.00	0.0	0.0	687.50	1350.00	694.01	0.0	694.18	13.75	3.55	485.12	364.09
24226.000	676.00	0.0	0.0	689.16	1210.00	695.01	0.0	695.27	20.58	4.61	468.20	266.74
24226.000	676.00	0.0	0.0	689.16	1210.00	695.06	0.0	695.30	19.64	4.53	478.43	273.04
24250.000	24.00	0.0	0.0	689.20	1210.00	695.09	0.0	695.31	10.13	4.34	471.18	380.09
24250.000	24.00	0.0	0.0	689.20	1210.00	695.14	0.0	695.34	9.71	4.27	480.16	388.31

FORM E-413

TARABUSI CREEK LIVONIA C

SUMMARY PRINTOUT TABLE 150

SECNO	Q	CWSEL	DIFWSP	DIFWSX	DIFKWS	TOPWID	XLCH
120.000	1770.00	620.00	0.0	0.0	0.0	220.00	0.0
120.000	1770.00	620.10	0.10	0.0	0.10	221.00	0.0
370.000	1770.00	621.72	0.0	1.72	0.0	159.10	250.00
370.000	1770.00	621.65	-0.07	1.55	-0.07	122.61	250.00
745.000	1770.00	623.30	0.0	1.58	0.0	142.72	375.00
745.000	1770.00	623.42	0.11	1.76	0.11	98.38	375.00
1120.000	1770.00	624.21	0.0	0.91	0.0	120.72	375.00
1120.000	1770.00	624.32	0.11	0.90	0.11	122.73	375.00
1770.000	1770.00	625.84	0.0	1.64	0.0	121.13	650.00
1770.000	1770.00	625.87	0.03	1.56	0.03	75.98	650.00
2416.000	1770.00	626.67	0.0	0.83	0.0	69.65	646.00
2416.000	1770.00	626.72	0.05	0.84	0.05	51.39	646.00
2466.000	1770.00	627.09	0.0	0.41	0.0	73.80	50.00
2466.000	1770.00	627.17	0.08	0.45	0.08	73.80	50.00
2554.000	1770.00	627.10	0.0	0.02	0.0	73.80	88.00
2554.000	1770.00	627.20	0.10	0.03	0.10	73.80	88.00
2604.000	1770.00	627.22	0.0	0.12	0.0	145.67	50.00
2604.000	1770.00	627.32	0.09	0.12	0.09	145.96	50.00
3360.000	1770.00	628.31	0.0	1.09	0.0	237.48	756.00
3360.000	1770.00	628.38	0.07	1.06	0.07	169.12	756.00
4116.000	1770.00	630.07	0.0	1.75	0.0	150.00	756.00
4116.000	1770.00	630.13	0.07	1.75	0.07	150.00	756.00
4316.000	1770.00	630.27	0.0	0.20	0.0	31.18	200.00
4316.000	1770.00	630.30	0.04	0.17	0.04	31.25	200.00
4403.000	1770.00	634.30	0.0	4.03	0.0	98.04	87.00
4403.000	1770.00	634.31	0.01	4.01	0.01	98.04	87.00
4453.000	1770.00	635.37	0.0	1.07	0.0	192.60	50.00
4453.000	1770.00	635.38	0.01	1.07	0.01	192.60	50.00
5950.000	1770.00	635.89	0.0	0.62	0.0	353.51	1497.00
5950.000	1770.00	635.91	0.02	0.53	0.02	302.13	1497.00
6600.000	1770.00	636.18	0.0	0.28	0.0	327.33	650.00
6600.000	1770.00	636.20	0.03	0.30	0.03	235.13	650.00
7340.000	1770.00	637.26	0.0	1.08	0.0	268.62	740.00
7340.000	1770.00	637.33	0.07	1.13	0.07	238.27	740.00
8078.000	1770.00	639.24	0.0	1.98	0.0	321.62	738.00
8078.000	1770.00	639.33	0.09	2.00	0.09	196.66	738.00

SECNO	Q	CWSEL	DIFWSP	DIFWSX	DIFKWS	TOPWID	XLCH
8815.000	1770.00	641.02	0.0	1.78	0.0	332.93	737.00
8815.000	1770.00	641.13	0.11	1.80	0.11	232.62	737.00
9276.000	1770.00	641.99	0.0	0.97	0.0	184.31	461.00
9276.000	1770.00	642.08	0.10	0.96	0.10	92.70	461.00
9737.000	1770.00	643.29	0.0	1.31	0.0	190.30	461.00
9737.000	1770.00	643.41	0.11	1.32	0.11	106.44	461.00
10198.000	1770.00	644.33	0.0	1.04	0.0	191.07	461.00
10198.000	1770.00	644.45	0.12	1.04	0.12	109.70	461.00
10658.000	1770.00	645.51	0.0	1.18	0.0	80.00	460.00
10658.000	1770.00	645.61	0.10	1.16	0.10	80.00	460.00
10708.000	1770.00	646.10	0.0	0.60	0.0	64.00	50.00
10708.000	1770.00	646.17	0.07	0.56	0.07	64.00	50.00
10782.000	1770.00	646.16	0.0	0.05	0.0	64.00	74.00
10782.000	1770.00	646.26	0.10	0.09	0.10	64.00	74.00
10832.000	1590.00	646.51	0.0	0.36	0.0	155.00	50.00
10832.000	1590.00	646.60	0.09	0.34	0.09	155.00	50.00
11720.000	1590.00	647.92	0.0	1.41	0.0	339.81	888.00
11720.000	1590.00	647.95	0.03	1.35	0.03	250.76	888.00
12145.000	1590.00	649.75	0.0	1.83	0.0	363.51	425.00
12145.000	1590.00	649.87	0.12	1.92	0.12	284.32	425.00
12570.000	1590.00	650.90	0.0	1.15	0.0	395.98	425.00
12570.000	1590.00	651.00	0.10	1.13	0.10	262.20	425.00
12965.000	1590.00	652.36	0.0	1.46	0.0	389.52	395.00
12965.000	1590.00	652.45	0.10	1.45	0.10	231.79	395.00
13360.000	1590.00	654.04	0.0	1.69	0.0	197.56	395.00
13360.000	1590.00	654.12	0.08	1.67	0.08	200.53	395.00
13704.000	1590.00	655.75	0.0	1.71	0.0	193.93	344.00
13704.000	1590.00	655.76	0.01	1.64	0.01	194.23	344.00
14047.000	1590.00	657.54	0.0	1.79	0.0	193.54	343.00
14047.000	1590.00	657.54	0.00	1.78	0.00	193.55	343.00
14219.000	1590.00	658.43	0.0	0.89	0.0	124.00	172.00
14219.000	1590.00	658.43	0.00	0.89	0.00	124.00	172.00
14390.000	1590.00	658.91	0.0	0.48	0.0	38.22	171.00
14390.000	1590.00	658.91	0.00	0.48	0.00	38.22	171.00
14440.000	1590.00	659.64	0.0	0.72	0.0	18.20	50.00
14440.000	1590.00	659.64	0.00	0.72	0.00	18.20	50.00
14501.000	1590.00	662.38	0.0	2.75	0.0	18.20	61.00
14501.000	1590.00	662.38	0.0	2.75	0.0	18.20	61.00

SECNO	Q	CWSEL	DIFWSP	DIFWSX	DIFKWS	TOPWID	XLCH
14570.000	1590.00	664.49	0.0	2.10	0.0	171.08	69.00
14570.000	1590.00	664.49	0.0	2.10	0.0	171.08	69.00
15360.000	1590.00	664.91	0.0	0.42	0.0	172.01	790.00
15360.000	1590.00	664.91	0.00	0.43	0.00	149.61	790.00
16100.000	1590.00	665.69	0.0	0.78	0.0	375.02	740.00
16100.000	1590.00	665.72	0.03	0.80	0.03	213.74	740.00
16500.000	1590.00	666.66	0.0	0.97	0.0	320.77	400.00
16500.000	1590.00	666.73	0.07	1.01	0.07	201.22	400.00
16900.000	1590.00	667.43	0.0	0.77	0.0	305.99	400.00
16900.000	1590.00	667.51	0.08	0.78	0.08	189.72	400.00
17295.000	1590.00	668.56	0.0	1.13	0.0	230.43	395.00
17295.000	1590.00	668.66	0.10	1.15	0.10	150.50	395.00
17690.000	1590.00	670.27	0.0	1.71	0.0	217.69	395.00
17690.000	1590.00	670.38	0.11	1.71	0.11	139.71	395.00
18215.000	1590.00	672.65	0.0	2.39	0.0	235.94	525.00
18215.000	1590.00	672.75	0.10	2.38	0.10	156.54	525.00
18739.000	1590.00	674.85	0.0	2.20	0.0	113.48	524.00
18739.000	1590.00	674.91	0.05	2.15	0.05	115.42	524.00
19001.000	1590.00	676.27	0.0	1.42	0.0	132.44	262.00
19001.000	1590.00	676.28	0.01	1.38	0.01	132.76	262.00
19263.000	1590.00	677.27	0.0	0.99	0.0	55.00	262.00
19263.000	1590.00	677.27	0.00	0.99	0.00	55.00	262.00
19313.000	1590.00	677.48	0.0	0.21	0.0	30.00	50.00
19313.000	1590.00	677.48	0.00	0.21	0.00	30.00	50.00
19387.000	1590.00	678.27	0.0	0.79	0.0	30.00	74.00
19387.000	1590.00	678.28	0.00	0.79	0.00	30.00	74.00
19437.000	1350.00	679.02	0.0	0.75	0.0	61.43	50.00
19437.000	1350.00	679.02	0.00	0.75	0.00	61.44	50.00
19517.000	1350.00	679.23	0.0	0.21	0.0	230.24	80.00
19517.000	1350.00	679.22	-0.01	0.20	-0.01	182.86	80.00
20117.000	1350.00	680.30	0.0	1.07	0.0	286.06	600.00
20117.000	1350.00	680.37	0.07	1.15	0.07	94.10	600.00
20617.000	1350.00	682.02	0.0	1.72	0.0	158.01	500.00
20617.000	1350.00	682.15	0.13	1.78	0.13	75.70	500.00
21117.000	1350.00	683.50	0.0	1.48	0.0	245.00	500.00
21117.000	1350.00	683.62	0.13	1.47	0.13	140.00	500.00
21392.000	1350.00	684.42	0.0	0.93	0.0	105.79	275.00
21392.000	1350.00	684.52	0.10	0.89	0.10	75.40	275.00

SECNO	Q	CWSEL	DIFWSP	DIFWSX	DIFKWS	TOPWID	XLCH
21667.000	1350.00	686.00	0.0	1.58	0.0	119.96	275.00
21667.000	1350.00	686.08	0.08	1.56	0.08	72.92	275.00
22128.000	1350.00	688.49	0.0	2.49	0.0	112.57	461.00
22128.000	1350.00	688.63	0.14	2.55	0.14	55.00	461.00
22589.000	1350.00	690.66	0.0	2.17	0.0	276.38	461.00
22589.000	1350.00	690.79	0.12	2.16	0.12	182.06	461.00
23050.000	1350.00	692.47	0.0	1.81	0.0	274.33	461.00
23050.000	1350.00	692.56	0.08	1.77	0.08	279.02	461.00
23550.000	1350.00	693.99	0.0	1.52	0.0	185.94	500.00
23550.000	1350.00	694.01	0.02	1.45	0.02	109.16	500.00
24226.000	1210.00	695.01	0.0	1.02	0.0	225.04	676.00
24226.000	1210.00	695.06	0.04	1.05	0.04	226.81	676.00
24250.000	1210.00	695.09	0.0	0.08	0.0	220.63	24.00
24250.000	1210.00	695.14	0.04	0.08	0.04	222.22	24.00

SUMMARY OF ERRORS

FLOODWAY DATA. TARABUSI CREEK LIVONIA C

PROFILE NO. 2

STATION	FLOODWAY WIDTH (FT)	FLOODWAY SECTION AREA	FLOODWAY MEAN VELOCITY	WATER SURFACE ELEVATION WITH FLOODWAY	WITHOUT FLOODWAY	DIFFERENCE
120.000	221.	666.	3.8	620.1	620.0	0.1
370.000	123.	401.	4.4	621.7	621.7	0.0
745.000	98.	486.	3.6	623.4	623.3	0.1
1120.000	125.	453.	3.9	624.3	624.2	0.1
1770.000	76.	499.	3.5	625.8	625.8	0.0
2416.000	51.	396.	4.5	626.7	626.7	0.0
2466.000	74.	445.	4.0	627.2	627.1	0.1
2554.000	74.	447.	4.0	627.2	627.1	0.1
2604.000	146.	775.	2.3	627.3	627.2	0.1
3360.000	169.	650.	2.7	628.4	628.3	0.1
4116.000	150.	568.	3.1	630.2	630.1	0.1
4316.000	31.	179.	9.9	630.3	630.3	0.0
4403.000	98.	388.	4.6	634.3	634.3	0.0
4453.000	193.	1420.	1.2	635.4	635.4	0.0
5950.000	302.	1588.	1.1	635.9	635.9	0.0
6600.000	235.	879.	2.0	636.2	636.2	0.0
7340.000	238.	828.	2.1	637.4	637.3	0.1
8078.000	197.	650.	2.7	639.3	639.2	0.1
8815.000	233.	704.	2.5	641.1	641.0	0.1
9276.000	93.	375.	4.7	642.1	642.0	0.1
9737.000	106.	435.	4.1	643.4	643.3	0.1
10198.000	110.	447.	4.0	644.4	644.3	0.1
10658.000	80.	347.	5.1	645.6	645.5	0.1
10708.000	64.	351.	5.0	646.2	646.1	0.1
10782.000	64.	356.	5.0	646.3	646.2	0.1
10832.000	155.	714.	2.2	646.6	646.5	0.1
11720.000	251.	536.	3.0	647.9	647.9	0.0
12145.000	284.	873.	1.8	649.8	649.7	0.1
12570.000	252.	665.	2.4	651.0	650.9	0.1
12965.000	232.	600.	2.7	652.5	652.4	0.1
13360.000	201.	535.	3.0	654.1	654.0	0.1
13704.000	194.	503.	3.2	655.7	655.7	0.0
14047.000	194.	499.	3.2	657.6	657.5	0.0
14219.000	124.	543.	2.9	658.4	658.4	0.0
14390.000	38.	200.	8.0	658.9	658.9	0.0
14440.000	18.	112.	14.2	659.6	659.6	0.0
14501.000	18.	162.	9.8	662.4	662.4	0.0
14570.000	171.	1369.	1.2	664.5	664.5	0.0
15360.000	150.	1035.	1.5	664.9	664.9	0.0
16100.000	214.	737.	2.2	665.7	665.7	0.0
16500.000	201.	838.	1.9	666.8	666.7	0.1
16900.000	190.	661.	2.4	667.5	667.4	0.1
17295.000	150.	491.	3.2	668.7	668.6	0.1
17690.000	140.	416.	3.8	670.4	670.3	0.1
18215.000	157.	500.	3.2	672.8	672.7	0.1
18739.000	115.	304.	5.2	675.0	674.9	0.1
19001.000	133.	364.	4.4	676.3	676.3	0.0
19263.000	55.	266.	6.0	677.3	677.3	0.0
19313.000	30.	208.	7.6	677.5	677.5	0.0
19387.000	30.	232.	6.9	678.3	678.3	0.0

FLOODWAY DATA. TARABUSI CREEK LIVONIA C
PROFILE NO. 2

STATION	FLOODWAY WIDTH (FT)	FLOODWAY SECTION AREA	FLOODWAY MEAN VELOCITY	WATER SURFACE ELEVATION WITH FLOODWAY	WITHOUT FLOODWAY	DIFFERENCE
19437.000	61.	357.	3.8	679.0	679.0	0.0
19517.000	183.	571.	2.4	679.2	679.2	0.0
20117.000	94.	321.	4.2	680.4	680.3	0.1
20617.000	76.	317.	4.3	682.1	682.0	0.1
21117.000	140.	611.	3.3	683.6	683.5	0.1
21392.000	75.	262.	5.2	684.5	684.4	0.1
21667.000	73.	252.	5.4	686.1	686.0	0.1
22128.000	55.	239.	5.7	688.6	688.5	0.1
22589.000	182.	517.	2.6	690.8	690.7	0.1
23050.000	279.	519.	2.6	692.6	692.5	0.1
23550.000	109.	485.	2.8	694.0	694.0	0.0
24226.000	227.	478.	2.5	695.0	695.0	0.0
24250.000	222.	480.	2.5	695.1	695.1	0.0

FORM 0413

```
**************************************************
HEC2 RELEASE DATED NOV 76 UPDATED AUG1977
ERROR CORR - 01,02
MODIFICATION - 50,51,52,53
**************************************************
```




1) COUNTY: Wayne

2) STUDY NAME: City of Livonia

3) WATERCOURSE: Tarabusi Creek

4) DOCUMENT TYPE: High Water Marks



```
**************************************************
  HEC2 RELEASE DATED NOV 76 UPDATED FEB 1977
  ERROR CODE =  01
  VERIFICATION =  30,55,82
**************************************************

C
T1 TARABUSI CREEK CITY OF LIVONIA FIS MOD 2ND JD
T2 PROFILE VERIFICATION USING HIGH WATER MARKS
T3       TARABUSI CREEK LIVONIA C

J1  ICHECK    INQ        NINV       IDIR       STRT       METRIC     HVINS      Q          WSEL       FQ
          0.         2.         0.         0.  0.000500     1.00       0.0        0.       685.120     0.005

J2  NPROF     IPLOT      PRFVS      XSECV      XSECH      FN         ALLDC      IBW        CHNIM      ITRACE
       -1.000     0.050     -1.000     0.000     0.000     0.000     0.000     0.000     3.000     0.000

ET      1.400    95.000     0.300     0.000     1.000     0.000     0.300     0.000     0.300     0.650
ES      0.020     0.120     0.040     0.300     0.550     0.000     0.001     0.000     0.000     0.000

          D/S FACE OLD 6 MILE BRIDGE

NC   2498.000     0.000   200.000   230.000     0.000     0.000     0.000     0.000     0.000     0.000
NC     70.000     0.000     0.000     0.000     0.000     0.000     0.000   625.930   625.950     0.000
GR    653.000     0.300   629.500   130.000   619.500   200.000   619.500   200.100   619.500   230.000
GR    619.500   230.500   629.500   250.000   639.000   350.000     0.000     0.000     0.000     0.000
SU      0.000     1.790     3.000   200.000    20.700     0.030   127.000     0.000   619.300   619.300

          D/S FACE OLD 6 MILE BRIDGE

X1   2554.000     0.300     0.000     0.300    56.000    56.000    56.000     0.710     0.000     0.300
X2      0.000     0.000     1.000   625.400   629.000     0.000     0.000     0.000     0.000     0.000
X3     10.000     0.200     0.050     0.000     0.000     0.000     0.000   625.000   625.000     0.000
NC      0.150     0.150     0.050     0.400     0.600     0.000     0.000     0.000     0.000     0.000

          SECND 2604 STA 25+27.50' D/S 6 MILE FROM CORPS NOTES AND QUAD MAP

X1   2604.000    32.000   177.500   220.500    50.000    50.000    50.000     0.000     0.000     0.000
X2      0.000     0.000     0.000   111.000     0.000   265.000     0.000     0.000     0.000     0.000
GR    635.000     0.000   635.000    60.000   610.000    55.000   625.000    92.000   621.300   177.900
GR    619.000   192.500   617.500   200.000   610.000   212.500   622.200   220.500   625.000   250.000
GR    650.000   265.000   639.000   450.000     0.000     0.000     0.000     0.000     0.000     0.000

          SECND 4116 END D/S CIVILENGT FROM CORPS NOTES AND QUAD MAP

X1   4116.000     0.000   177.500   219.000  1200.000  1100.000  1182.000     0.000     0.000     0.000
X2      0.000     0.000     0.000   140.000     0.000   255.000     0.000     0.000     0.000     0.300
GR    655.000    11.000   634.000    60.000   626.200   177.000   622.700   191.000   622.600   193.500
GR    622.200   212.000   627.100   279.000   633.000   300.000   551.000   560.000     0.000     0.000
SU      0.000     0.000     1.400     0.000     1.100     1.000     0.900     0.000     1.000     1.000
NC      0.050     0.050     0.050     0.300     0.300     0.000     0.000     0.000     0.000     0.000
```

X1	4376.000	9.000	148.840	164.270	305.000	300.000	200.000	0.000	0.000	0.000
X5	10.000	0.000	0.000	0.000	0.000	0.000	0.000	626.900	626.900	0.000
GR	655.000	0.000	655.000	139.000	622.700	148.840	622.700	146.740	622.600	156.560
BR	622.700	164.270	622.700	164.370	635.000	175.000	635.000	416.000	0.000	0.000
SH	0.000	1.950	3.000	292.000	15.440	0.000	97.265	0.000	622.600	622.600

SECNO 4403 U/S FACE MIDDLEBELT FROM CORPS NOTES AND QUAD MAPS;SH BR.

X1	4403.000	0.000	0.000	0.000	87.000	87.000	87.000	0.000	0.000	0.000
X2	0.000	0.000	1.000	921.900	632.900	0.000	0.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	632.900	632.900	0.000
BT	0.000	0.000	675.000	0.000	148.840	632.900	622.700	148.840	632.900	628.900
BT	164.270	632.900	628.900	164.370	632.900	622.700	416.000	635.200	0.000	0.000
NC	0.000	0.000	0.000	0.400	0.500	0.000	0.000	0.000	0.000	0.000
ET	0.000	7.100	7.100	7.100	7.100	9.150	201.000	400.000	200.000	490.000

SEC 0 4455 STA 44+55 50' U/S MIDDLEBELT FROM CORPS NOTES AND QUAD MAP

X1	4455.000	13.000	330.000	557.000	50.000	0.000	50.000	0.450	0.000	0.000
X3	0.000	0.000	0.000	201.000	0.000	456.500	0.000	0.000	0.000	0.000
GR	640.000	0.000	655.000	100.000	630.000	150.000	630.000	200.000	625.000	310.000
GR	625.700	350.000	622.700	335.000	622.600	350.000	622.700	554.000	626.700	357.000
GR	625.000	480.000	630.000	510.000	635.000	550.000	0.000	0.000	0.000	0.000
ET	0.000	0.000	0.000	0.000	1.410	0.000	0.000	0.000	0.000	0.000
NC	0.100	0.100	0.040	0.000	0.000	0.300	0.000	0.000	0.000	0.000

SECNO 5950 STA 59+50 0FF[illegible] FROM CORPS NOTES AND QUAD MAP

X1	5950.000	13.000	255.000	255.000	1497.000	1497.000	1497.000	0.300	0.000	0.000
X3	640.000	0.000	632.000	70.000	530.000	235.000	627.000	240.000	626.700	245.000
GR	626.300	350.000	625.700	255.000	527.000	200.000	630.000	253.000	625.000	375.000
GR	640.300	470.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000

SECNO 6600 STA 66+00 FROM CORPS NOTES AND QUAD MAP

X1	6600.000	7.000	170.000	155.000	530.000	530.000	670.000	0.300	0.000	0.000
GR	640.000	0.000	625.000	45.000	355.000	130.000	625.000	140.000	623.000	165.000
GR	623.300	350.000	630.000	100.000	0.000	0.000	0.000	0.000	0.000	0.000

SEC 0 7340 STA 73+40 FROM CORPS NOTES AND QUAD MAP

X1	7340.000	9.000	200.000	322.000	740.000	740.000	740.000	0.000	0.000	0.000
GR	645.000	0.000	630.000	60.000	634.000	210.000	631.700	210.000	631.700	215.000
GR	634.000	222.000	634.000	300.000	640.200	320.000	625.000	365.000	0.000	0.000

SECNO 7915 STA 79+15 FROM CORPS NOTES AND QUAD MAP

X1	7915.000	10.000	210.000	235.000	627.000	701.000	740.000	0.000	0.000	0.000
GR	641.000	0.000	625.000	65.000	653.000	211.000	540.000	225.000	634.000	252.000
GR	634.000	242.000	635.000	253.000	640.000	355.000	644.000	415.000	636.000	390.000

SECNO 8750 STA 87+50 FROM CORPS NOTES AND QUAD MAP

X1	8750.000	9.000	205.000	250.000	922.000	922.000	922.000	0.000	0.000	0.000
X3	0.000	0.000	640.000	74.000	321.000	0.000	0.000	625.700	633.000	221.000
GR	640.000	252.000	640.000	260.000	640.000	300.000	650.000	340.000	633.000	0.000

SECNO 10650 STA 105+90 50' D/S MERRIMAN FROM CORPS NOTES AND QUAD MAP

XT	10650.000	15.000	295.300	240.200	900.000	600.000	927.000	0.000	0.000	0.000
XS	0.000	0.000	0.000	155.000	0.000	263.000	0.000	0.000	0.000	0.000
GR	660.000	0.000	655.000	80.000	650.000	112.000	647.500	117.000	645.000	132.000
GR	642.500	205.000	637.900	226.000	637.800	252.000	637.900	238.000	642.500	240.000
GR	645.000	520.000	650.000	560.000	655.000	600.000	0.000	0.000	0.000	0.000

SECNO 10708 STA 107+40 D/S FACE MERRIMAN FROM CORPS NOTES AND QUAD MAP

XT	10708.000	18.000	208.000	272.000	50.000	50.000	50.000	0.000	0.000	0.000
XS	10.000	0.000	0.000	0.000	0.000	0.000	0.000	653.600	653.600	0.000
GR	660.000	0.000	655.000	65.000	652.000	130.000	645.500	208.000	645.500	208.100
GR	645.500	212.000	638.000	227.000	638.000	227.100	638.000	229.000	638.000	229.100
GR	638.000	251.000	638.000	251.100	638.000	253.000	638.000	253.100	645.500	268.000
GR	645.500	272.000	645.500	272.100	656.000	350.000	0.000	0.000	0.000	0.000
SP	1.250	1.300	3.000	0.000	26.000	2.300	793.700	2.280	638.000	638.000

SECNO 10732 D/S FACE MERRIMAN FROM CORPS NOTES AND QUAD MAP

XT	10732.000	0.000	0.000	0.000	74.000	74.000	74.000	0.000	0.000	0.000
XS	0.000	0.000	1.000	653.100	654.000	0.000	0.000	0.000	0.000	0.000
XS	10.000	0.000	0.000	0.000	0.000	0.000	0.000	654.000	655.000	0.000
BT	16.000	0.000	660.000	0.000	65.000	655.000	0.000	130.000	654.000	0.000
BT	206.000	654.200	645.500	206.100	654.200	653.100	227.000	654.200	653.100	227.100
BT	654.200	639.000	229.000	654.200	638.000	229.100	654.200	653.100	251.000	655.500
BT	653.100	251.100	655.000	638.000	253.000	658.000	638.000	253.100	639.000	653.100
BT	272.000	653.000	653.100	272.100	655.000	645.500	330.000	656.000	0.000	0.000
NC	0.100	0.100	0.040	0.300	0.500	0.000	0.000	0.000	0.000	0.000

SECNO 10832 D/S FACE MERRIMAN FROM CORPS NOTES AND QUAD MAP

XT	10832.000	13.000	197.000	247.000	50.000	50.000	50.000	0.000	0.000	0.000
XS	0.000	0.000	0.000	145.000	0.000	300.000	0.000	0.000	0.000	0.000
GR	660.000	0.000	655.000	80.000	650.000	112.000	647.500	117.000	645.000	132.000
GR	642.500	197.800	637.900	226.000	637.800	252.000	637.900	238.000	642.500	247.000
GR	645.000	520.000	650.000	560.000	655.000	600.000	0.000	0.000	0.000	0.000
SP	0.150	0.150	0.050	0.950	0.300	0.300	0.000	0.000	0.500	0.000

SECNO 11720

XT	11720.000	9.000	570.000	540.000	886.000	835.000	687.000	0.000	0.000	0.000
GR	650.000	350.000	646.000	375.000	646.500	650.000	642.000	650.000	642.700	660.000
GR	642.000	565.000	646.000	580.000	647.000	675.000	660.000	850.000	0.000	0.000

SECNO 12745 X

XT	12745.000	0.000	0.000	0.000	425.000	425.000	425.000	0.000	0.000	0.000

SECNO 12570 STA 125+20 FROM CORPS NOTES AND QUAD MAP

XT	12570.000	9.000	284.000	351.000	455.000	455.000	455.000	0.000	0.000	0.000
GR	660.000	0.000	651.000	372.000	650.000	611.000	647.500	405.000	645.000	445.000
GR	645.000	900.000	647.000	951.000	650.000	674.000	652.000	901.000	0.000	0.000

SECNO 12965 X

X1	12965.000	0.000	0.000	0.000	395.000	395.000	395.000	0.000	1.600	0.000
NC	0.150	0.150	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000

SECNO 13360 STA 139+20, FROM CORPS NOTES AND QUAD MAP.

X1	13360.000	12.000	270.000	510.000	430.000	250.000	395.000	0.000	0.000	0.000
GR	665.000	0.000	660.000	33.000	655.000	165.000	650.000	270.000	649.200	2,2.000
ET	647.600	280.000	647.500	290.000	647.600	294.000	649.500	298.000	650.000	310.000
GR	655.000	400.000	662.000	630.000	0.000	0.000	0.000	0.000	0.000	0.000

SECNO 13704 X

X1	13704.000	0.000	0.000	0.000	208.000	344.000	344.000	0.000	1.300	0.000

SECNO 14067 X

X1	14067.000	0.000	0.000	0.000	208.000	343.000	343.000	0.000	1.400	0.000

VALLEY SECTION X

X1	14219.000	7.000	447.000	476.000	104.000	172.000	172.000	0.000	0.000	0.000
GR	665.000	0.000	659.500	257.000	653.300	447.000	652.000	462.000	653.300	476.000
GR	659.500	570.000	665.000	570.000	0.000	0.000	0.000	0.000	0.000	0.000
NC	0.150	0.150	0.000	0.400	0.600	0.000	0.000	0.000	0.000	0.000
ET	0.000	0.000	0.000	0.000	0.100	0.000	0.000	0.000	1.000	324.000

SECNO 14390 50' D/S / MILE FROM CORPS NOTES AND QUAD MAP SKEW

X1	14390.000	10.000	624.000	643.000	204.000	171.000	171.300	0.000	0.000	0.000
X3	0.000	0.000	0.000	611.000	0.000	654.000	0.000	0.000	0.000	0.000
GR	670.000	0.000	665.000	280.000	660.000	370.000	660.500	350.000	657.900	650.300
GR	655.000	624.000	652.900	634.000	653.000	542.000	655.400	655.000	650.000	660.000
GR	650.000	760.000	665.000	765.000	670.000	625.000	0.000	0.000	0.000	0.000

SECNO 14440 STA 174+50, D/S FACE / MILE FROM CORPS NOTES AND QUAD MAP SKEW

X1	14440.000	11.000	675.220	695.420	50.000	50.000	50.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	659.500	659.500	0.000
GR	670.000	599.300	659.000	600.000	655.500	675.220	654.500	675.320	652.970	666.140
GR	655.500	695.420	655.500	695.520	653.000	728.000	661.500	764.000	660.000	760.000
GR	670.000	781.300	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
SB	0.000	1.710	3.000	0.000	10.220	0.000	121.900	0.000	652.000	652.000

SECNO 14501 D/S FACE / MILE FROM CORPS NOTES AND QUAD MAP SKEW

X1	14501.000	7.000	0.000	2.000	61.000	51.000	51.200	0.000	0.000	0.000
X2	0.000	6.000	1.000	659.500	660.000	0.000	0.200	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	663.400	663.400	0.000
BT	10.000	599.000	670.000	0.000	600.000	65.000	0.000	675.220	663.400	694.500
GR	670.000	599.300	659.500	599.420	663.000	695.500	670.220	675.320	65[illegible]	771.250
BT	0.000	0.000	0.000	600.000	0.000	780.000	660.000	0.000	70.000	670.000
BT	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
ET	0.000	0.000	0.000	0.000	1.400	0.000	0.000	0.000	0.000	0.000

PRINTED IN U.S.A.
EQUIP WITH GUARANTEED & PROVEN MANIFOLD FORMS

SECNO 14570 STA 175+10 69° DVS 7 MILE FROM CORPS NOTES AND QUAD MAP SYEM

X1	14570.000	7.000	525.000	366.000	69.000	59.000	69.000	0.910	0.000	0.000	
X2	0.000	0.000	0.000	295.000	0.000	415.000	0.000	0.000	0.000	0.000	
GR	670.000	0.000	668.000	330.000	655.600	325.000	657.800	342.000	655.600	346.000	
GR	660.000	470.000	673.000	740.000	0.000	0.000	0.000	0.000	0.000	0.000	

SECNO 13360 STA 184+40 FROM CORPS NOTES AND QUAD MAP

X1	13360.000	10.000	84.000	125.000	790.000	790.000	790.000	0.000	0.000	0.000	
GR	670.000	0.000	668.000	30.000	658.000	90.000	657.500	85.000	658.500	110.000	
GR	655.100	110.000	654.000	122.000	668.000	125.300	660.000	173.000	670.000	200.000	

SECNO 16100 STA 192+60 FROM CORPS NOTES AND QUAD MAP

X1	16100.000	15.000	155.000	145.000	740.000	740.000	740.000	0.000	0.000	0.000	
GR	672.300	0.00	670.000	30.000	666.000	40.000	663.000	90.000	662.000	115.000	
GR	658.000	150.000	660.000	140.000	662.000	170.000	662.600	240.000	664.000	250.000	
GR	666.000	450.000	670.000	480.000	672.000	510.000	0.000	0.000	0.000	0.000	

SECNO 16500 T

X1	16500.000	8.000	173.000	209.000	550.000	275.000	400.000	0.000	0.000	0.000	
GR	675.000	0.000	667.000	80.000	662.000	173.000	659.000	195.000	662.000	209.000	
GR	663.500	310.000	670.000	510.000	675.000	400.000	0.000	0.000	0.000	0.000	
NC	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	

SECNO 16900 STA 201+70 FROM CORPS NOTES AND QUAD MAP

X1	16900.000	13.000	228.000	276.000	550.000	275.000	400.000	0.000	0.000	0.000	
GR	660.000	0.000	671.000	90.000	670.000	130.000	665.000	170.000	665.200	209.000	
GR	650.000	296.000	660.000	262.000	662.000	264.000	664.000	275.000	663.000	350.000	
GR	670.000	500.000	670.000	460.000	670.000	930.200	0.000	0.000	0.000	0.000	
NC	0.120	0.120	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	

SEC 0 17295 X

X1	17295.000	0.300	392.000	443.000	75.000	423.000	395.000	0.000	0.000	0.000	
GR	500.000	0.300	672.000	190.000	667.500	330.000	666.500	392.000	662.400	420.000	
SD	665.000	443.000	666.000	500.000	680.000	650.000	0.000	0.000	0.000	0.000	

SECNO 17690 STA 210+80 FROM CORPS NOTES AND QUAD MAP

X1	17690.000	10.000	555.000	610.000	75.000	425.000	395.000	0.000	0.000	0.000	
GR	680.000	0.000	675.000	250.000	669.100	395.000	669.000	555.000	664.800	377.000	
GR	664.700	561.000	664.400	595.000	667.000	610.000	667.500	650.000	680.000	715.000	

SECNO 18215 X

X1	18215.000	0.000	0.000	0.000	615.000	490.300	525.000	0.000	0.000	0.000	

SEC 0 18739

X1	18739.000	0.300	0.000	0.000	675.300	600.000	534.000	0.000	0.000	0.000	

SECNO 19265 50' D/S FARMINGTON FROM CORPS NOTES AND QUAD MAP

X1	19265.000	11.000	285.000	345.000	1843.000	1463.000	1575.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	276.000	0.000	352.000	0.000	0.000	0.000	0.000
GR	685.000	0.000	680.000	60.000	675.000	130.000	675.600	285.000	670.600	288.000
GR	670.500	305.000	670.600	314.000	672.600	321.000	684.600	343.000	690.000	350.000
GR	690.000	350.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
NC	0.000	0.000	0.000	0.600	0.600	0.000	0.000	0.000	0.000	0.000
ET	0.000	0.000	0.000	0.000	9.100	0.000	0.000	0.000	1.000	354.000

SECNO 19315 STA 230+00 D/S FACE FARMINGTON FROM CORPS NOTES AND QUAD MP

X1	19315.000	13.000	287.000	349.000	50.000	0.000	50.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	679.800	679.800	0.000
GR	685.000	0.000	680.000	60.000	675.000	265.000	675.600	287.000	670.600	290.000
GR	670.500	293.100	670.500	305.000	670.600	320.000	670.600	320.100	672.600	327.000
GR	681.000	349.000	690.000	355.000	690.000	355.000	0.000	0.000	0.000	0.000
SB	0.000	1.200	3.000	0.000	30.000	0.000	210.000	0.000	670.500	670.500

SECNO 19387 U/S FACE FARMINGTON FROM CORPS NOTES AND QUAD MAP

X1	19387.000	1.000	0.000	0.000	74.000	74.000	74.100	0.000	0.000	0.100
X2	0.000	33.000	1.300	677.500	681.100	0.000	0.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	681.100	681.100	0.000
BT	8.000	0.000	690.000	0.000	0.000	685.000	0.000	290.000	681.100	670.600
BT	290.100	681.100	677.500	320.000	681.100	677.500	320.100	681.100	670.600	355.000
BT	502.000	0.000	355.300	690.000	5.000	0.000	0.000	0.000	0.000	0.000
EJ	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000

00BREAK00

1) COUNTY: Wayne

2) STUDY NAME: City of Livonia

3) WATERCOURSE: Tarabasi Creek

4) DOCUMENT TYPE: Summary

00BREAK00

HEC2 RELEASE DATED NOV 76 UPDATED AUG1977
ERROR CORR - 01.02
MODIFICATION - 50.51.52.53

NOTE- ASTERISK (*) AT LEFT OF CROSS-SECTION NUMBER INDICATES MESSAGE IN SUMMARY OF ERRORS LIST

TARABUSI CREEK LIVONIA C

SUMMARY PRINTOUT TABLE 150

SECNO	XLCH	ELTRD	ELLC	ELMIN	Q	CHSEL	CRIWS	EG	10K*S	VCH	AREA	.01K
120.000	0.0	0.0	0.0	613.20	1070.00	620.00	0.0	620.28	26.09	4.96	444.48	209.58
120.000	0.0	0.0	0.0	613.20	1560.00	620.00	0.0	620.59	55.40	7.23	444.48	209.58
120.000	0.0	0.0	0.0	613.20	1770.00	620.00	0.0	620.76	71.32	8.21	444.48	209.58
120.000	0.0	0.0	0.0	613.20	2060.00	620.00	619.95	621.03	96.61	9.55	444.48	209.58
370.000	250.00	0.0	0.0	615.30	1070.00	620.70	0.0	621.28	51.55	6.56	309.41	149.03
370.000	250.00	0.0	0.0	615.30	1560.00	621.40	0.0	622.07	57.72	7.66	400.96	205.34
370.000	250.00	0.0	0.0	615.30	1770.00	621.72	0.0	622.35	54.89	7.79	452.61	239.56
370.000	250.00	0.0	0.0	615.30	2060.00	622.21	0.0	622.62	48.89	7.85	531.48	294.60
745.000	375.00	0.0	0.0	615.70	1070.00	622.16	0.0	622.46	19.56	4.97	386.48	241.91
745.000	375.00	0.0	0.0	615.70	1560.00	623.01	0.0	623.39	22.69	5.92	494.69	326.04
745.000	375.00	0.0	0.0	615.70	1770.00	623.36	0.0	623.72	24.29	6.29	535.77	359.15
745.000	375.00	0.0	0.0	615.70	2060.00	623.69	0.0	624.16	25.85	6.74	591.77	405.19
1120.000	375.00	0.0	0.0	616.00	1070.00	622.93	0.0	623.39	25.84	6.12	299.99	210.47
1120.000	375.00	0.0	0.0	616.00	1560.00	623.87	0.0	624.48	29.82	7.25	399.53	285.70
1120.000	375.00	0.0	0.0	616.00	1770.00	624.21	0.0	624.88	31.26	7.67	439.56	316.47
1120.000	375.00	0.0	0.0	616.00	2060.00	624.64	0.0	625.39	32.97	8.19	493.94	356.76
1770.000	650.00	0.0	0.0	617.00	1070.00	624.25	0.0	624.49	10.86	4.37	383.50	324.65
1770.000	650.00	0.0	0.0	617.00	1560.00	625.42	0.0	625.75	12.42	5.19	494.71	442.58
1770.000	650.00	0.0	0.0	617.00	1770.00	625.84	0.0	626.21	12.90	5.48	543.58	492.76
1770.000	650.00	0.0	0.0	617.00	2060.00	626.35	0.0	626.79	13.47	5.84	613.64	561.20
2416.000	646.00	0.0	0.0	617.90	1070.00	624.95	0.0	625.27	12.18	4.75	316.41	306.61
2416.000	646.00	0.0	0.0	617.90	1560.00	626.22	0.0	626.68	14.36	5.76	397.96	411.61
2416.000	646.00	0.0	0.0	617.90	1770.00	626.67	0.0	627.19	15.27	6.15	429.16	452.96
2416.000	646.00	0.0	0.0	617.90	2060.00	627.25	0.0	627.85	16.66	6.66	469.82	507.68
2466.000	50.00	0.0	0.0	617.90	1070.00	625.17	0.0	625.37	11.62	3.57	299.61	313.95
2466.000	50.00	0.0	0.0	617.90	1560.00	626.97	0.0	626.81	12.34	3.90	400.40	444.15
2466.000	50.00	0.0	0.0	617.90	1770.00	627.69	0.0	627.36	11.85	4.04	436.30	514.15
2466.000	50.00	0.0	0.0	617.90	2060.00	627.74	0.0	628.02	11.47	4.23	486.46	608.33
2554.000	88.00	632.60	629.40	617.90	1070.00	625.16	0.0	625.38	11.53	3.56	300.38	315.05
2554.000	88.00	632.60	629.40	617.90	1560.00	626.59	0.0	626.82	12.24	3.89	401.37	445.69
2554.000	88.00	632.60	629.40	617.90	1770.00	627.10	0.0	627.35	11.76	4.03	439.30	516.03
2554.000	88.00	632.60	629.40	617.90	2060.00	627.75	0.0	628.03	11.35	4.23	487.53	610.43

SECNO	XLCH	ELTRO	ELLC	ELMIN	Q	CUSEL	CRIVS	EG	10K*S	VCM	AREA	*01K
2604.000	50.00	0.0	0.0	617.90	1070.00	625.28	0.0	625.45	12.30	3.48	404.00	305.03
2604.000	50.00	0.0	0.0	617.90	1560.00	626.70	0.0	626.90	11.57	3.87	685.86	458.59
2604.000	50.00	0.0	0.0	617.90	1770.00	627.22	0.0	627.43	11.50	4.03	761.17	521.67
2604.000	50.00	0.0	0.0	617.90	2060.00	627.89	0.0	628.11	11.48	4.23	850.46	607.91
3360.000	756.00	0.0	0.0	620.30	1070.00	626.59	0.0	626.90	30.07	4.65	352.37	193.85
3360.000	756.00	0.0	0.0	620.30	1560.00	627.84	0.0	628.14	24.27	4.02	617.69	316.64
3360.000	756.00	0.0	0.0	620.30	1770.00	628.31	0.0	628.61	22.32	4.85	729.12	370.64
3360.000	756.00	0.0	0.0	620.30	2060.00	628.93	0.0	629.22	20.22	4.90	879.10	450.13
4116.000	756.00	0.0	0.0	622.60	1070.00	628.76	0.0	629.05	27.27	4.49	332.01	204.90
4116.000	756.00	0.0	0.0	622.60	1560.00	629.70	0.0	630.03	27.46	5.04	502.54	297.69
4116.000	756.00	0.0	0.0	622.60	1770.00	630.07	0.0	630.42	27.42	5.25	550.51	337.99
4116.000	756.00	0.0	0.0	622.60	2060.00	630.56	0.0	630.93	27.17	5.49	632.91	366.17
4316.000	200.00	0.0	0.0	622.60	1070.00	629.30	0.0	630.97	155.99	10.39	102.99	85.67
4316.000	200.00	0.0	0.0	622.60	1560.00	630.00	0.0	632.08	117.06	12.20	168.19	143.70
4316.000	200.00	0.0	0.0	622.60	1770.00	630.27	0.0	632.73	133.56	13.30	177.47	153.15
4316.000	200.00	0.0	0.0	622.60	2060.00	630.59	630.31	633.61	155.87	14.78	187.73	165.00
4403.000	87.00	632.90	628.90	622.60	1070.00	631.91	0.0	632.77	59.93	7.45	143.54	138.22
4403.000	87.00	632.90	628.90	622.60	1560.00	633.99	0.0	634.66	23.14	7.22	357.64	324.26
4403.000	87.00	632.90	628.90	622.60	1770.00	634.30	0.0	635.07	26.37	7.04	386.90	364.69
4403.000	87.00	632.90	628.90	622.60	2060.00	634.67	0.0	635.59	30.68	6.64	423.51	371.92
4453.000	50.00	0.0	0.0	622.60	1070.00	633.12	0.0	633.17	5.94	2.70	751.40	438.99
4453.000	50.00	0.0	0.0	622.60	1560.00	634.92	0.0	634.95	3.47	2.31	1331.13	837.56
4453.000	50.00	0.0	0.0	622.60	1770.00	635.37	0.0	635.41	3.71	2.44	1418.44	919.16
4453.000	50.00	0.0	0.0	622.60	2060.00	635.95	0.0	635.99	4.02	2.62	1528.80	1027.16
5950.000	1497.00	0.0	0.0	626.60	1070.00	633.91	0.0	633.97	4.78	2.75	1007.46	489.29
5950.000	1497.00	0.0	0.0	626.60	1560.00	635.43	0.0	635.48	3.60	2.66	1318.67	846.45
5950.000	1497.00	0.0	0.0	626.60	1770.00	635.89	0.0	635.94	3.30	2.72	1681.50	974.24
5950.000	1497.00	0.0	0.0	626.60	2060.00	636.46	0.0	636.53	3.22	2.81	1891.66	1147.92
6600.000	650.00	0.0	0.0	628.80	1070.00	634.38	0.0	634.60	19.42	4.09	455.13	242.50
6600.000	650.00	0.0	0.0	628.80	1560.00	635.73	0.0	635.88	10.90	3.73	855.53	472.45
6600.000	650.00	0.0	0.0	628.80	1770.00	636.18	0.0	636.32	9.61	3.69	999.54	570.96
6600.000	650.00	0.0	0.0	628.80	2060.00	636.75	0.0	636.80	8.41	3.68	1139.23	710.49
7340.000	740.00	0.0	0.0	631.70	1070.00	636.22	0.0	636.36	28.73	4.72	590.06	159.64
7340.000	740.00	0.0	0.0	631.70	1560.00	636.94	0.0	637.10	27.16	5.14	775.09	299.32
7340.000	740.00	0.0	0.0	631.70	1770.00	637.26	0.0	637.42	25.43	5.21	862.79	350.92
7340.000	740.00	0.0	0.0	631.70	2060.00	637.71	0.0	637.86	23.21	5.26	983.51	427.57
8078.000	738.00	0.0	0.0	632.90	1070.00	638.29	0.0	638.59	26.22	5.24	490.13	204.97
8078.000	738.00	0.0	0.0	632.90	1560.00	638.90	0.0	639.30	26.48	5.77	697.03	303.16
8078.000	738.00	0.0	0.0	632.90	1770.00	639.24	0.0	639.56	26.42	5.94	777.75	344.33
8078.000	738.00	0.0	0.0	632.90	2060.00	639.58	0.0	639.90	26.02	6.13	888.81	403.03
8815.000	737.00	0.0	0.0	634.00	1070.00	640.05	0.0	640.30	19.12	4.44	477.43	244.69
8815.000	737.00	0.0	0.0	634.00	1560.00	640.76	0.0	641.03	18.89	4.86	705.59	358.96
8815.000	737.00	0.0	0.0	634.00	1770.00	641.02	0.0	641.29	18.90	5.02	791.60	407.16
8815.000	737.00	0.0	0.0	634.00	2060.00	641.35	0.0	641.63	18.94	5.22	903.51	473.40

SECNO	XLCH	ELTRD	ELLC	ELMIN	Q	CWSEL	CRWS	FG	10*S	VCH	AREA	.01K
9276.000	461.00	0.0	0.0	634.90	1070.00	640.98	0.0	641.33	23.47	4.88	297.32	220.08
9276.000	461.00	0.0	0.0	634.90	1560.00	641.72	0.0	642.19	27.53	5.84	411.08	297.29
9276.000	461.00	0.0	0.0	634.90	1770.00	641.99	0.0	642.51	28.95	6.19	458.74	328.90
9276.000	461.00	0.0	0.0	634.90	2060.00	642.32	0.0	642.90	30.32	6.59	521.09	374.13
9737.000	461.00	0.0	0.0	635.90	1070.00	642.05	0.0	642.39	22.15	4.79	306.83	227.35
9737.000	461.00	0.0	0.0	635.90	1560.00	642.96	0.0	643.37	22.90	5.49	454.28	326.00
9737.000	461.00	0.0	0.0	635.90	1770.00	643.29	0.0	643.73	22.62	5.70	516.95	370.52
9737.000	461.00	0.0	0.0	635.90	2060.00	643.70	0.0	644.16	23.08	5.99	594.90	428.83
10198.000	461.00	0.0	0.0	636.90	1070.00	643.07	0.0	643.40	21.91	4.78	308.63	228.57
10198.000	461.00	0.0	0.0	636.90	1560.00	644.00	0.0	644.41	22.22	5.64	461.75	330.97
10198.000	461.00	0.0	0.0	636.90	1770.00	644.33	0.0	644.75	22.10	5.64	525.17	376.54
10198.000	461.00	0.0	0.0	636.90	2060.00	644.74	0.0	645.19	22.35	5.92	603.88	435.72
10658.000	460.00	0.0	0.0	637.80	1070.00	644.26	0.0	644.74	34.66	5.87	236.92	181.74
10658.000	460.00	0.0	0.0	637.80	1560.00	645.18	0.0	645.84	37.29	6.86	312.56	255.47
10658.000	460.00	0.0	0.0	637.80	1770.00	645.51	0.0	646.26	39.03	7.28	338.57	283.33
10658.000	460.00	0.0	0.0	637.80	2060.00	645.93	0.0	646.76	41.18	7.82	372.11	321.00
10708.000	50.00	0.0	0.0	638.00	1070.00	644.69	0.0	644.94	19.08	4.06	263.77	275.57
10708.000	50.00	0.0	0.0	638.00	1560.00	645.73	0.0	646.09	21.15	4.64	322.48	339.17
10708.000	50.00	0.0	0.0	638.00	1770.00	646.10	0.0	646.51	21.50	5.10	346.94	361.74
10708.000	50.00	0.0	0.0	638.00	2060.00	646.59	0.0	647.05	22.05	5.45	370.22	436.73
10782.000	74.00	654.00	653.10	638.00	1070.00	644.72	0.0	644.97	14.82	4.03	265.38	277.93
10782.000	74.00	654.00	653.10	638.00	1560.00	645.77	0.0	646.13	20.65	4.79	325.39	364.15
10782.000	74.00	654.00	653.10	638.00	1770.00	646.16	0.0	646.53	20.93	5.06	349.84	386.91
10782.000	74.00	654.00	653.10	638.00	2060.00	646.65	0.0	647.10	21.45	5.40	381.47	444.81
10832.000	50.00	0.0	0.0	637.80	960.00	644.92	0.0	645.06	8.24	3.17	453.96	334.42
10832.000	50.00	0.0	0.0	637.80	1410.00	646.09	0.0	646.25	7.91	3.55	634.73	501.35
10832.000	50.00	0.0	0.0	637.80	1590.00	646.51	0.0	646.63	7.80	3.68	700.46	569.49
10832.000	50.00	0.0	0.0	637.80	1860.00	647.06	0.0	647.25	7.88	3.89	785.16	662.71
11720.000	888.00	0.0	0.0	642.70	960.00	646.57	646.57	647.33	167.70	7.16	197.05	74.13
11720.000	888.00	0.0	0.0	642.70	1410.00	647.57	0.0	648.01	78.58	6.09	505.48	159.06
11720.000	888.00	0.0	0.0	642.70	1590.00	647.92	0.0	648.31	63.33	5.63	624.61	195.60
11720.000	888.00	0.0	0.0	642.70	1860.00	648.42	0.0	648.74	49.42	5.57	735.71	264.59
12145.000	425.00	0.0	0.0	643.60	960.00	649.08	0.0	649.19	16.57	3.15	714.72	233.07
12145.000	425.00	0.0	0.0	643.60	1410.00	649.56	0.0	649.71	22.20	3.87	880.86	299.27
12145.000	425.00	0.0	0.0	643.60	1590.00	649.75	0.0	649.91	23.48	4.08	949.13	320.14
12145.000	425.00	0.0	0.0	643.60	1860.00	650.04	0.0	650.22	24.58	4.35	1056.16	375.20
12570.000	425.00	0.0	0.0	644.40	960.00	650.02	0.0	650.25	34.38	4.21	636.17	163.72
12570.000	425.00	0.0	0.0	644.40	1410.00	650.67	0.0	650.93	34.78	4.70	676.18	239.08
12570.000	425.00	0.0	0.0	644.40	1590.00	650.90	0.0	651.16	34.61	4.85	765.20	270.28
12570.000	425.00	0.0	0.0	644.40	1860.00	651.22	0.0	651.49	34.26	5.04	693.66	317.80
12965.000	395.00	0.0	0.0	646.00	960.00	651.48	0.0	651.74	40.75	4.47	386.46	150.02
12965.000	395.00	0.0	0.0	646.00	1410.00	652.14	0.0	652.43	40.60	4.97	623.21	221.28
12965.000	395.00	0.0	0.0	646.00	1590.00	652.36	0.0	652.66	40.42	5.13	708.10	250.08
12965.000	395.00	0.0	0.0	646.00	1860.00	652.66	0.0	652.97	40.08	5.34	829.80	293.81

SECND	XLCH	ELTRD	ELLC	ELMIN	Q	CWSEL	CRIWS	EG	10K*S	VCH	AREA	.01K
13360.000	395.00	0.0	0.0	647.50	960.00	653.10	0.0	653.41	42.49	4.09	350.23	147.28
13360.000	395.00	0.0	0.0	647.50	1410.00	653.81	0.0	654.22	48.28	5.80	474.10	202.93
13360.000	395.00	0.0	0.0	647.50	1590.00	654.04	0.0	654.50	50.54	6.12	519.48	223.66
13360.000	395.00	0.0	0.0	647.50	1860.00	654.36	0.0	654.88	53.70	6.58	584.80	253.83
13704.000	344.00	0.0	0.0	649.30	960.00	654.65	0.0	655.02	54.10	5.29	312.32	130.52
13704.000	344.00	0.0	0.0	649.30	1410.00	655.47	0.0	655.92	54.27	6.03	448.70	191.41
13704.000	344.00	0.0	0.0	649.30	1590.00	655.76	0.0	656.23	54.54	6.22	501.23	215.31
13704.000	344.00	0.0	0.0	649.30	1860.00	656.13	0.0	656.65	55.01	6.63	570.23	250.77
14047.000	343.00	0.0	0.0	651.10	960.00	656.45	0.0	650.02	54.23	5.30	311.97	130.37
14047.000	343.00	0.0	0.0	651.10	1410.00	657.26	0.0	657.71	54.79	6.05	446.67	190.40
14047.000	343.00	0.0	0.0	651.10	1590.00	657.54	0.0	658.02	54.98	6.30	499.31	214.43
14047.000	343.00	0.0	0.0	651.10	1860.00	657.92	0.0	658.45	55.24	6.64	577.14	250.27
14219.000	172.00	0.0	0.0	652.00	960.00	657.30	0.0	657.55	36.52	4.85	402.44	163.38
14219.000	172.00	0.0	0.0	652.00	1410.00	650.14	0.0	658.49	38.76	5.74	507.28	226.48
14219.000	172.00	0.0	0.0	652.00	1590.00	658.43	0.0	658.81	40.52	6.00	542.92	249.78
14219.000	172.00	0.0	0.0	652.00	1860.00	658.82	0.0	659.26	43.26	6.53	591.28	282.80
14390.000	171.00	0.0	0.0	652.90	960.00	657.88	0.0	659.07	125.47	9.65	160.33	85.70
14390.000	171.00	0.0	0.0	652.90	1410.00	658.66	0.0	660.53	163.36	12.14	190.13	110.32
14390.000	171.00	0.0	0.0	652.90	1590.00	658.91	0.0	661.00	179.21	13.09	199.78	118.77
14390.000	171.00	0.0	0.0	652.90	1860.00	659.24	658.98	661.69	204.47	14.49	212.30	130.08
14440.000	50.00	0.0	0.0	652.90	960.00	653.63	0.0	660.21	201.44	10.71	89.66	67.64
14440.000	50.00	0.0	0.0	652.90	1410.00	659.33	659.20	662.08	261.84	13.30	106.05	87.14
14440.000	50.00	0.0	0.0	652.90	1590.00	659.64	659.54	662.79	285.91	14.25	111.60	94.03
14440.000	50.00	0.0	0.0	652.90	1860.00	660.14	660.14	662.14	144.39	12.54	259.78	154.79
14501.000	61.00	663.40	659.50	652.90	960.00	660.00	0.0	661.00	249.17	8.79	109.18	60.82
14501.000	61.00	663.40	659.50	652.90	1410.00	661.36	0.0	662.88	107.10	9.63	143.49	136.24
14501.000	61.00	663.40	659.50	652.90	1590.00	662.35	0.0	663.86	96.20	9.23	161.79	162.11
14501.000	61.00	663.40	659.50	652.90	1860.00	664.01	0.0	664.57	24.47	7.02	558.87	376.02
14570.000	69.00	0.0	0.0	651.80	960.00	662.32	0.0	662.37	4.76	2.55	998.18	439.85
14570.000	69.00	0.0	0.0	651.80	1410.00	663.50	0.0	663.56	5.97	3.10	1199.45	576.86
14570.000	69.00	0.0	0.0	651.80	1590.00	664.49	0.0	664.55	5.11	3.06	1369.19	703.17
14570.000	69.00	0.0	0.0	651.80	1860.00	664.76	0.0	664.84	6.33	3.47	1415.34	739.11
15360.000	790.00	0.0	0.0	655.00	960.00	662.75	0.0	662.82	6.64	2.54	722.21	372.46
15360.000	790.00	0.0	0.0	655.00	1410.00	664.00	0.0	664.09	7.13	2.97	926.70	520.12
15360.000	790.00	0.0	0.0	655.00	1590.00	664.91	0.0	665.00	6.87	2.91	1080.89	656.25
15360.000	790.00	0.0	0.0	655.00	1860.00	665.27	0.0	665.37	6.87	3.24	1142.20	709.49
16100.000	740.00	0.0	0.0	656.00	960.00	663.76	0.0	664.21	72.17	6.40	341.15	113.00
16100.000	740.00	0.0	0.0	656.00	1410.00	664.98	0.0	665.31	44.89	6.01	621.94	210.44
16100.000	740.00	0.0	0.0	656.00	1590.00	665.69	0.0	665.93	30.71	5.39	857.37	286.91
16100.000	740.00	0.0	0.0	656.00	1860.00	666.14	0.0	666.37	28.83	5.48	1035.34	346.38
16500.000	400.00	0.0	0.0	659.00	960.00	665.42	0.0	665.56	18.55	3.67	611.25	222.70
16500.000	400.00	0.0	0.0	659.00	1410.00	666.26	0.0	666.43	19.44	4.17	848.94	319.76
16500.000	400.00	0.0	0.0	659.00	1590.00	666.66	0.0	666.83	18.26	4.23	971.39	371.86
16500.000	400.00	0.0	0.0	659.00	1860.00	667.06	0.0	667.24	16.70	4.46	1104.20	430.13

SECND	ALCH	ELTRD	ELLC	ELMIN	D	OBSEL	CRIVS	EG	10K*S	VCM	AREA	.01K
16900.000	400.00	0.0	0.0	660.00	960.00	666.24	0.0	666.45	26.80	3.98	439.27	185.40
16900.000	400.00	0.0	0.0	660.00	1410.00	667.09	0.0	667.32	25.87	4.41	661.27	277.24
16900.000	400.00	0.0	0.0	660.00	1590.00	667.43	0.0	667.66	24.47	4.48	763.95	321.42
16900.000	400.00	0.0	0.0	660.00	1860.00	667.83	0.0	668.08	24.20	4.68	892.66	378.12
17295.000	395.00	0.0	0.0	662.40	960.00	667.53	0.0	667.79	44.48	4.47	335.72	143.95
17295.000	395.00	0.0	0.0	662.40	1410.00	668.29	0.0	668.50	41.79	4.95	489.02	218.11
17295.000	395.00	0.0	0.0	662.40	1590.00	668.56	0.0	668.86	40.60	5.09	550.70	249.53
17295.000	395.00	0.0	0.0	662.40	1860.00	668.93	0.0	669.25	39.52	5.30	639.09	295.85
17690.000	395.00	0.0	0.0	664.70	960.00	669.38	0.0	669.67	49.98	4.58	298.09	135.77
17690.000	395.00	0.0	0.0	664.70	1410.00	670.04	0.0	670.40	51.91	5.28	420.46	195.70
17690.000	395.00	0.0	0.0	664.70	1590.00	670.27	0.0	670.65	52.40	5.51	466.54	219.66
17690.000	395.00	0.0	0.0	664.70	1860.00	670.59	0.0	671.00	52.80	5.81	539.82	255.98
18215.000	525.00	0.0	0.0	666.70	960.00	671.67	0.0	671.82	30.29	4.12	348.50	159.37
18215.000	525.00	0.0	0.0	666.70	1410.00	672.40	0.0	672.67	36.01	4.66	498.79	234.96
18215.000	525.00	0.0	0.0	666.70	1590.00	672.65	0.0	672.94	36.02	4.86	557.13	264.93
18215.000	525.00	0.0	0.0	666.70	1860.00	673.00	0.0	673.31	36.11	5.10	642.10	309.54
18739.000	524.00	0.0	0.0	668.60	960.00	673.60	0.0	674.19	50.19	9.04	198.53	135.50
18739.000	524.00	0.0	0.0	668.60	1410.00	674.58	0.0	675.13	55.80	6.02	268.89	188.76
18739.000	524.00	0.0	0.0	668.60	1590.00	674.85	0.0	675.46	57.62	6.36	298.14	209.47
18739.000	524.00	0.0	0.0	668.60	1860.00	675.22	0.0	675.91	60.03	6.82	342.47	240.06
19001.000	262.00	0.0	0.0	669.50	960.00	675.62	0.0	675.34	37.86	4.62	226.56	156.01
19001.000	262.00	0.0	0.0	669.50	1410.00	675.95	0.0	676.38	39.00	5.37	321.65	225.79
19001.000	262.00	0.0	0.0	669.50	1590.00	676.27	0.0	676.74	38.30	5.62	362.45	253.62
19001.000	262.00	0.0	0.0	669.50	1860.00	676.72	0.0	677.23	39.63	5.95	424.92	295.46
19263.000	262.00	0.0	0.0	670.50	960.00	675.95	0.0	676.41	38.38	5.48	195.82	154.96
19263.000	262.00	0.0	0.0	670.50	1410.00	676.93	0.0	677.60	45.07	6.67	248.03	210.03
19263.000	262.00	0.0	0.0	670.50	1590.00	677.27	0.0	676.02	47.61	7.10	266.23	230.44
19263.000	262.00	0.0	0.0	670.50	1860.00	677.72	0.0	678.59	51.37	7.71	290.90	259.51
19313.000	50.00	0.0	0.0	670.50	960.00	676.14	0.0	676.65	46.64	5.72	167.76	140.56
19313.000	50.00	0.0	0.0	670.50	1410.00	677.14	0.0	677.93	60.30	7.13	197.81	181.57
19313.000	50.00	0.0	0.0	670.50	1590.00	677.68	0.0	678.39	65.68	7.64	207.98	196.19
19313.000	50.00	0.0	0.0	670.50	1860.00	677.94	0.0	679.03	73.76	8.39	221.79	216.56
19387.000	74.00	681.10	677.50	670.50	960.00	676.54	0.0	676.99	37.52	5.34	179.90	156.72
19387.000	74.00	681.10	677.50	670.50	1410.00	677.66	0.0	678.34	47.53	6.60	213.67	204.62
19387.000	74.00	681.10	677.50	670.50	1590.00	678.27	0.0	679.00	47.00	6.66	231.98	231.92
19387.000	74.00	681.10	677.50	670.50	1860.00	679.23	0.0	680.02	45.10	7.14	260.59	276.96
19437.000	50.00	0.0	0.0	670.50	820.00	676.97	0.0	677.15	9.01	3.41	240.18	273.13
19437.000	50.00	0.0	0.0	670.50	1200.00	678.35	0.0	678.57	9.03	3.79	316.31	399.41
19437.000	50.00	0.0	0.0	670.50	1350.00	679.02	0.0	679.26	8.22	3.79	356.64	470.87
19437.000	50.00	0.0	0.0	670.50	1580.00	680.05	0.0	680.27	6.91	3.74	438.36	601.23
19517.000	80.00	0.0	0.0	671.60	820.00	677.07	0.0	677.32	47.09	4.00	205.33	119.50
19517.000	80.00	0.0	0.0	671.60	1200.00	678.53	0.0	678.69	19.66	3.38	478.48	270.62
19517.000	80.00	0.0	0.0	671.60	1350.00	679.23	0.0	679.35	12.54	3.01	640.45	381.15
19517.000	80.00	0.0	0.0	671.60	1580.00	680.28	0.0	680.36	7.55	2.66	880.10	575.05

SECNO	XLCH	ELTRD	ELLC	ELMIN	Q	CWSEL	CRIWS	EG	10K*S	VCH	AREA	.01K
20117.000	600.00	0.0	0.0	674.40	820.00	679.41	0.0	679.66	33.10	4.13	238.42	142.52
20117.000	600.00	0.0	0.0	674.40	1200.00	680.03	0.0	680.38	39.77	4.91	326.04	190.29
20117.000	600.00	0.0	0.0	674.40	1350.00	680.30	0.0	680.64	37.50	4.98	401.77	220.22
20117.000	600.00	0.0	0.0	674.40	1580.00	680.93	0.0	681.19	26.66	4.59	591.09	305.80
20617.000	500.00	0.0	0.0	676.00	820.00	680.99	0.0	681.20	27.95	3.67	242.91	155.10
20617.000	500.00	0.0	0.0	676.00	1200.00	681.79	0.0	682.05	27.52	4.20	346.79	206.74
20617.000	500.00	0.0	0.0	676.00	1350.00	682.02	0.0	682.31	28.72	4.43	390.26	251.91
20617.000	500.00	0.0	0.0	676.00	1580.00	682.34	0.0	682.66	29.90	4.75	433.48	288.57
21117.000	500.00	0.0	0.0	677.50	820.00	682.49	0.0	682.68	30.99	3.48	256.69	147.30
21117.000	500.00	0.0	0.0	677.50	1200.00	683.20	0.0	683.45	27.52	3.61	435.07	228.77
21117.000	500.00	0.0	0.0	677.50	1350.00	683.50	0.0	683.71	26.49	3.91	470.56	262.31
21117.000	500.00	0.0	0.0	677.50	1580.00	683.64	0.0	684.05	24.36	3.96	656.34	320.25
21392.000	275.00	0.0	0.0	679.10	820.00	683.53	0.0	683.82	52.84	4.32	192.76	112.80
21392.000	275.00	0.0	0.0	679.10	1200.00	684.20	0.0	684.58	89.50	5.00	253.10	160.96
21392.000	275.00	0.0	0.0	679.10	1350.00	684.42	0.0	684.84	56.48	5.22	276.50	179.63
21392.000	275.00	0.0	0.0	679.10	1580.00	684.70	0.0	685.18	59.09	5.61	307.18	204.16
21667.000	275.00	0.0	0.0	680.60	820.00	685.03	0.0	685.35	56.99	4.54	109.84	100.62
21667.000	275.00	0.0	0.0	680.60	1200.00	685.75	0.0	686.15	57.47	5.16	262.42	156.29
21667.000	275.00	0.0	0.0	680.60	1350.00	686.00	0.0	686.42	57.49	5.28	291.20	178.05
21667.000	275.00	0.0	0.0	680.60	1580.00	686.36	0.0	686.81	56.71	5.69	337.11	206.80
22126.000	461.00	0.0	0.0	681.90	820.00	687.43	0.0	687.77	48.14	4.72	175.16	110.18
22126.000	461.00	0.0	0.0	681.90	1200.00	688.24	0.0	688.70	52.01	5.50	225.77	166.39
22126.000	461.00	0.0	0.0	681.90	1350.00	688.49	0.0	689.00	52.65	5.77	251.55	185.99
22126.000	461.00	0.0	0.0	681.90	1580.00	688.85	0.0	689.42	53.93	6.16	297.15	215.16
22589.000	461.00	0.0	0.0	683.20	820.00	689.60	0.0	689.85	41.21	4.52	311.57	127.74
22589.000	461.00	0.0	0.0	683.20	1200.00	690.40	0.0	690.82	31.82	4.53	503.41	213.42
22589.000	461.00	0.0	0.0	683.20	1350.00	690.66	0.0	690.88	29.65	4.57	574.79	247.92
22589.000	461.00	0.0	0.0	683.20	1580.00	691.04	0.0	691.25	27.20	4.61	683.65	302.95
23050.000	461.00	0.0	0.0	684.50	820.00	691.76	0.0	692.17	58.32	6.49	314.43	107.36
23050.000	461.00	0.0	0.0	684.50	1200.00	692.28	0.0	692.68	60.97	7.03	445.53	153.68
23050.000	461.00	0.0	0.0	684.50	1350.00	692.47	0.0	692.80	60.98	7.17	495.58	174.88
23050.000	461.00	0.0	0.0	684.50	1580.00	692.75	0.0	693.12	59.89	7.30	573.44	204.17
23550.000	500.00	0.0	0.0	687.50	820.00	693.13	0.0	693.22	9.42	2.62	429.60	267.12
23550.000	500.00	0.0	0.0	687.50	1200.00	693.77	0.0	693.91	12.07	3.23	538.10	345.37
23550.000	500.00	0.0	0.0	687.50	1350.00	693.99	0.0	694.15	12.96	3.44	578.45	374.96
23550.000	500.00	0.0	0.0	687.50	1580.00	694.29	0.0	694.47	14.33	3.75	635.61	417.41
24226.000	676.00	0.0	0.0	689.16	730.00	693.99	0.0	694.20	24.40	4.24	258.00	147.79
24226.000	676.00	0.0	0.0	689.16	1070.00	694.75	0.0	695.00	21.21	4.50	411.11	232.32
24226.000	676.00	0.0	0.0	689.16	1210.00	695.01	0.0	695.27	20.58	4.61	468.20	266.74
24226.000	676.00	0.0	0.0	689.16	1410.00	695.37	0.0	695.62	19.63	4.73	550.11	316.23
* 24250.000	24.00	0.0	0.0	689.20	730.00	694.33	694.33	696.78	167.23	12.56	58.11	56.45
24250.000	24.00	0.0	0.0	689.20	1070.00	694.83	0.0	695.05	10.53	4.26	414.81	329.68
24250.000	24.00	0.0	0.0	689.20	1210.00	695.09	0.0	695.31	10.13	4.34	471.18	380.09
24250.000	24.00	0.0	0.0	689.20	1410.00	695.45	0.0	695.66	9.59	4.43	551.60	455.21

TARAEUST CREEK LIVONIA C

SUMMARY PRINTOUT TABLE 150

SECNO	Q	CWSEL	DIFWSP	DIFWSX	DIFKHS	TOPWID	XLCH
120.000	1070.00	620.00	0.0	0.0	0.0	220.00	0.0
120.000	1560.00	620.00	0.0	0.0	0.0	220.00	0.0
120.000	1770.00	620.00	0.0	0.0	0.0	220.00	0.0
120.000	2060.00	620.00	0.0	0.0	0.0	220.00	0.0
370.000	1070.00	620.78	0.0	0.78	0.0	145.95	250.00
370.000	1560.00	621.40	0.61	1.40	0.0	154.40	250.00
370.000	1770.00	621.72	0.33	1.72	0.0	159.10	250.00
370.000	2060.00	622.21	0.49	2.21	0.0	165.89	250.00
745.000	1070.00	622.10	0.0	1.40	0.0	124.07	375.00
745.000	1560.00	623.01	0.83	1.61	0.0	138.04	375.00
745.000	1770.00	623.30	0.29	1.58	0.0	142.72	375.00
745.000	2060.00	623.69	0.39	1.48	0.0	148.87	375.00
1120.000	1070.00	622.93	0.0	0.75	0.0	97.72	375.00
1120.000	1560.00	623.87	0.96	0.86	0.0	114.59	375.00
1120.000	1770.00	624.21	0.34	0.91	0.0	120.72	375.00
1120.000	2060.00	624.64	0.44	0.98	0.0	128.57	375.00
1770.000	1070.00	624.25	0.0	1.32	0.0	88.00	650.00
1770.000	1560.00	625.42	1.17	1.55	0.0	107.90	650.00
1770.000	1770.00	625.84	0.43	1.64	0.0	121.13	650.00
1770.000	2060.00	626.38	0.54	1.74	0.0	137.90	650.00
2416.000	1070.00	624.95	0.0	0.71	0.0	61.59	606.00
2416.000	1560.00	626.22	1.26	0.80	0.0	67.51	606.00
2416.000	1770.00	626.67	0.46	0.83	0.0	69.65	606.00
2416.000	2060.00	627.25	0.57	0.86	0.0	72.33	606.00
2466.000	1070.00	625.17	0.0	0.21	0.0	60.61	50.00
2466.000	1560.00	626.57	1.40	0.35	0.0	73.20	50.00
2466.000	1770.00	627.09	0.51	0.41	0.0	73.60	50.00
2466.000	2060.00	627.74	0.65	0.49	0.0	73.90	50.00
2554.000	1070.00	625.18	0.0	0.01	0.0	60.67	88.00
2554.000	1560.00	626.59	1.41	0.01	0.0	73.80	88.00
2554.000	1770.00	627.10	0.51	0.02	0.0	73.80	88.00
2554.000	2060.00	627.75	0.65	0.02	0.0	73.80	88.00
2604.000	1070.00	625.28	0.0	0.10	0.0	139.25	50.00
2604.000	1560.00	626.70	1.42	0.12	0.0	144.11	50.00
2604.000	1770.00	627.22	0.52	0.12	0.0	145.67	50.00
2604.000	2060.00	627.89	0.66	0.13	0.0	147.66	50.00
3360.000	1070.00	626.59	0.0	1.30	0.0	187.72	756.00
3360.000	1560.00	627.84	1.25	1.13	0.0	230.17	756.00
3360.000	1770.00	628.31	0.48	1.09	0.0	237.46	756.00
3360.000	2060.00	628.93	0.62	1.05	0.0	246.97	756.00
4116.000	1070.00	628.76	0.0	2.17	0.0	115.00	756.00
4116.000	1560.00	629.70	0.94	1.86	0.94	150.00	756.00
4116.000	1770.00	630.07	0.37	1.75	1.31	150.00	756.00
4116.000	2060.00	630.56	0.49	1.63	1.80	150.00	756.00

SECNO	Q	CWSEL	DIFWSP	DIFWSX	DIFWS	TOPWID	XLCH
4316.000	1070.00	629.30	0.0	0.53	0.0	15.50	200.00
4316.000	1560.00	630.00	0.71	0.30	0.71	30.62	200.00
4316.000	1770.00	630.27	0.27	0.20	0.97	31.18	200.00
4316.000	2060.00	630.59	0.32	0.03	1.29	31.85	200.00
4403.000	1070.00	631.91	0.0	2.61	0.0	15.50	87.00
4403.000	1560.00	633.99	2.08	3.99	2.08	98.00	87.00
4403.000	1770.00	634.30	0.31	4.03	2.39	98.06	87.00
4403.000	2060.00	634.67	0.37	4.08	2.76	98.08	87.00
4453.000	1070.00	633.12	0.0	1.21	0.0	115.20	50.00
4453.000	1560.00	634.92	1.80	0.93	1.80	192.31	50.00
4453.000	1770.00	635.37	0.45	1.07	2.26	192.60	50.00
4453.000	2060.00	635.95	0.57	1.27	2.83	192.69	50.00
5950.000	1070.00	633.91	0.0	0.79	0.0	326.24	1497.00
5950.000	1560.00	635.43	1.52	0.51	1.52	347.11	1497.00
5950.000	1770.00	635.89	0.46	0.52	1.98	353.51	1497.00
5950.000	2060.00	636.48	0.59	0.63	2.57	361.59	1497.00
6600.000	1070.00	634.38	0.0	0.47	0.0	253.40	650.00
6600.000	1560.00	635.73	1.35	0.30	1.35	318.86	650.00
6600.000	1770.00	636.18	0.45	0.28	1.79	327.33	650.00
6600.000	2060.00	636.75	0.57	0.27	2.36	338.16	650.00
7340.000	1070.00	638.22	0.0	1.84	0.0	259.55	740.00
7340.000	1560.00	636.94	0.72	1.21	0.72	265.76	740.00
7340.000	1770.00	637.26	0.32	1.08	1.04	268.62	740.00
7340.000	2060.00	637.71	0.45	0.96	1.49	272.54	740.00
8078.000	1070.00	638.29	0.0	2.08	0.0	279.97	738.00
8078.000	1560.00	638.98	0.69	2.04	0.69	313.58	738.00
8078.000	1770.00	639.24	0.26	1.98	0.94	321.62	738.00
8078.000	2060.00	639.58	0.34	1.87	1.29	332.36	738.00
8815.000	1070.00	640.05	0.0	1.75	0.0	310.97	737.00
8815.000	1560.00	640.76	0.71	1.78	0.71	327.06	737.00
8815.000	1770.00	641.02	0.26	1.78	0.97	332.93	737.00
8815.000	2060.00	641.35	0.33	1.77	1.31	340.40	737.00
9276.000	1070.00	640.98	0.0	0.94	0.0	137.50	461.00
9276.000	1560.00	641.72	0.74	0.96	0.74	171.82	461.00
9276.000	1770.00	641.99	0.27	0.97	1.00	184.31	461.00
9276.000	2060.00	642.32	0.34	0.97	1.34	190.76	461.00
9737.000	1070.00	642.05	0.0	1.07	0.0	140.69	461.00
9737.000	1560.00	642.96	0.91	1.24	0.91	183.16	461.00
9737.000	1770.00	643.29	0.33	1.31	1.24	190.30	461.00
9737.000	2060.00	643.70	0.40	1.37	1.64	197.50	461.00
10198.000	1070.00	643.07	0.0	1.01	0.0	141.29	461.00
10198.000	1560.00	644.00	0.94	1.04	0.94	185.03	461.00
10198.000	1770.00	644.33	0.33	1.04	1.27	191.07	461.00
10198.000	2060.00	644.74	0.41	1.05	1.68	198.31	461.00

SECNO	Q	CWSEL	DIFWSP	DIFWSA	DIFXAS	TOPWID	XLCH
10658.000	1070.00	644.24	0.0	1.17	0.0	00.00	660.00
10658.000	1560.00	645.18	0.94	1.18	0.94	80.00	860.00
10658.000	1770.00	645.51	0.33	1.18	1.27	80.00	460.00
10658.000	2060.00	645.93	0.42	1.18	1.69	80.00	660.00
10708.000	1070.00	644.69	0.0	0.45	0.0	52.77	50.00
10708.000	1560.00	645.73	1.04	0.55	1.04	64.00	50.00
10708.000	1770.00	646.10	0.38	0.60	1.42	64.00	50.00
10708.000	2060.00	646.59	0.49	0.66	1.90	64.00	50.00
10782.000	1070.00	644.72	0.0	0.03	0.0	52.09	74.00
10782.000	1560.00	645.77	1.05	0.05	1.05	64.00	74.00
10782.000	1770.00	646.16	0.38	0.05	1.44	64.00	74.00
10782.000	2060.00	646.65	0.49	0.06	1.93	64.00	74.00
10832.000	960.00	644.92	0.0	0.20	0.0	155.00	50.00
10832.000	1410.00	646.09	1.17	0.32	1.17	155.00	50.00
10832.000	1590.00	646.51	0.42	0.36	1.59	155.00	50.00
10832.000	1860.00	647.06	0.55	0.41	2.14	155.00	50.00
11720.000	960.00	646.57	0.0	1.65	0.0	268.81	880.00
11720.000	1410.00	647.57	0.99	1.40	0.99	330.68	880.00
11720.000	1590.00	647.92	0.36	1.41	1.35	339.81	880.00
11720.000	1860.00	648.42	0.49	1.36	1.85	352.51	880.00
12145.000	960.00	649.08	0.0	2.51	0.0	346.56	425.00
12145.000	1410.00	649.56	0.48	1.99	0.48	350.66	425.00
12145.000	1590.00	649.75	0.19	1.83	0.67	363.51	425.00
12145.000	1860.00	650.04	0.29	1.62	0.96	371.00	425.00
12570.000	960.00	650.02	0.0	0.93	0.0	357.18	425.00
12570.000	1410.00	650.67	0.66	1.11	0.66	385.86	425.00
12570.000	1590.00	650.90	0.23	1.15	0.88	395.50	425.00
12570.000	1860.00	651.22	0.32	1.18	1.20	410.13	425.00
12965.000	960.00	651.46	0.0	1.46	0.0	315.82	395.00
12965.000	1410.00	652.14	0.66	1.46	0.66	379.72	395.00
12965.000	1590.00	652.36	0.22	1.46	0.88	389.52	395.00
12965.000	1860.00	652.66	0.31	1.44	1.19	403.15	395.00
13360.000	960.00	653.10	0.0	1.62	0.0	160.71	345.00
13360.000	1410.00	653.81	0.71	1.67	0.71	188.39	395.00
13360.000	1590.00	654.04	0.23	1.69	0.95	197.56	395.00
13360.000	1860.00	654.36	0.32	1.70	1.27	210.06	395.00
13704.000	960.00	654.65	0.0	1.56	0.0	151.24	344.00
13704.000	1410.00	655.47	0.82	1.66	0.82	183.06	344.00
13704.000	1590.00	655.75	0.28	1.71	1.09	193.63	344.00
13704.000	1860.00	656.13	0.38	1.77	1.48	208.84	344.00
14047.000	960.00	656.45	0.0	1.80	0.0	151.15	343.00
14047.000	1410.00	657.26	0.81	1.79	0.81	182.62	343.00
14047.000	1590.00	657.54	0.28	1.79	1.09	193.54	343.00
14047.000	1860.00	657.92	0.39	1.79	1.47	208.63	343.00

SECNO	Q	CWSEL	DIFWSP	DIFWSX	DIFKWS	TOPWID	XLCH
14219.000	960.00	657.30	0.0	0.85	0.0	124.00	172.00
14219.000	1410.00	658.14	0.85	0.88	0.85	124.00	172.00
14219.000	1590.00	658.43	0.29	0.89	1.13	124.00	172.00
14219.000	1860.00	658.82	0.39	0.90	1.52	124.00	172.00
14390.000	960.00	657.88	0.0	0.59	0.0	38.22	171.00
14390.000	1410.00	658.66	0.78	0.52	0.78	38.22	171.00
14390.000	1590.00	658.91	0.25	0.46	1.03	38.22	171.00
14390.000	1860.00	659.24	0.33	0.42	1.36	38.22	171.00
14440.000	960.00	658.43	0.0	0.55	0.0	18.20	50.00
14440.000	1410.00	659.33	0.90	0.67	0.90	18.20	50.00
14440.000	1590.00	659.64	0.31	0.72	1.21	18.20	50.00
* 14440.000	1860.00	660.14	0.50	0.90	1.71	62.97	50.00
14501.000	960.00	660.60	0.0	2.17	0.0	18.20	61.00
14501.000	1410.00	661.38	0.78	2.05	0.78	18.20	61.00
14501.000	1590.00	662.38	1.00	2.75	1.78	18.20	61.00
14501.000	1860.00	664.01	1.63	3.87	3.41	122.82	61.00
14570.000	960.00	662.32	0.0	1.72	0.0	171.08	69.00
14570.000	1410.00	663.50	1.18	2.11	1.18	171.08	69.00
14570.000	1590.00	664.49	0.99	2.10	2.17	171.08	69.00
14570.000	1860.00	665.76	0.27	0.75	2.44	171.08	69.00
15360.000	960.00	662.75	0.0	0.93	0.0	160.13	790.00
15360.000	1410.00	664.00	1.25	0.50	1.25	167.01	790.00
15360.000	1590.00	664.91	0.91	0.42	2.16	172.01	790.00
15360.000	1860.00	665.27	0.36	0.51	2.52	173.96	790.00
16100.000	960.00	663.76	0.0	1.01	0.0	175.35	740.00
16100.000	1410.00	664.98	1.23	0.98	1.23	295.43	740.00
16100.000	1590.00	665.69	0.71	0.78	1.93	375.02	740.00
16100.000	1860.00	666.14	0.45	0.87	2.38	411.48	740.00
16500.000	960.00	665.42	0.0	1.66	0.0	259.49	400.00
16500.000	1410.00	666.26	0.85	1.28	0.85	301.34	400.00
16500.000	1590.00	666.66	0.39	0.97	1.24	320.77	400.00
16500.000	1860.00	667.06	0.40	0.92	1.64	340.16	400.00
16900.000	960.00	666.24	0.0	0.82	0.0	239.30	400.00
16900.000	1410.00	667.09	0.85	0.82	0.85	286.56	400.00
16900.000	1590.00	667.43	0.34	0.77	1.19	305.99	400.00
16900.000	1860.00	667.83	0.41	0.76	1.60	325.70	400.00
17295.000	960.00	667.53	0.0	1.30	0.0	187.38	395.00
17295.000	1410.00	668.29	0.75	1.20	0.75	218.95	395.00
17295.000	1590.00	668.56	0.27	1.13	1.03	230.43	395.00
17295.000	1860.00	668.93	0.37	1.10	1.40	245.95	395.00
17690.000	960.00	669.38	0.0	1.85	0.0	176.68	395.00
17690.000	1410.00	670.04	0.66	1.75	0.66	207.11	395.00
17690.000	1590.00	670.27	0.23	1.71	0.89	217.69	395.00
17690.000	1860.00	670.59	0.32	1.65	1.20	232.49	395.00

SECNO	Q	CWSEL	DIFWSP	DIFWSX	DIFKWS	TOPWID	XLCH
18215.000	960.00	671.67	0.0	2.28	0.0	189.45	525.00
18215.000	1410.00	672.40	0.74	2.36	0.74	224.09	525.00
18215.000	1590.00	672.65	0.25	2.39	0.99	235.94	525.00
18215.000	1860.00	673.00	0.35	2.42	1.34	252.21	525.00
18739.000	960.00	673.80	0.0	2.13	0.0	75.21	524.00
18739.000	1410.00	674.58	0.79	2.18	0.79	103.72	524.00
18739.000	1590.00	674.85	0.27	2.20	1.06	113.45	524.00
18739.000	1860.00	675.22	0.37	2.22	1.42	126.85	524.00
19001.000	960.00	675.02	0.0	1.22	0.0	86.05	262.00
19001.000	1410.00	675.95	0.94	1.37	0.94	120.76	262.00
19001.000	1590.00	676.27	0.32	1.42	1.26	132.44	262.00
19001.000	1860.00	676.72	0.46	1.50	1.70	148.56	262.00
19263.000	960.00	675.85	0.0	0.96	0.0	52.01	262.00
19263.000	1410.00	676.93	0.98	0.98	0.98	54.36	262.00
19263.000	1590.00	677.27	0.33	0.99	1.31	55.00	262.00
19263.000	1860.00	677.72	0.45	1.00	1.76	55.00	262.00
19313.000	960.00	676.14	0.0	0.19	0.0	30.00	50.00
19313.000	1410.00	677.14	1.00	0.21	1.00	30.00	50.00
19313.000	1590.00	677.48	0.34	0.21	1.34	30.00	50.00
19313.000	1860.00	677.94	0.46	0.22	1.79	30.00	50.00
19387.000	960.00	676.54	0.0	0.40	0.0	30.00	74.00
19387.000	1410.00	677.66	1.12	0.62	1.12	30.00	74.00
19387.000	1590.00	678.27	0.61	0.79	1.73	30.00	74.00
19387.000	1860.00	679.23	0.96	1.29	2.68	30.00	74.00
19437.000	820.00	676.97	0.0	0.43	0.0	52.06	50.00
19437.000	1200.00	678.35	1.38	0.68	1.38	56.35	50.00
19437.000	1350.00	679.02	0.67	0.75	2.05	61.43	50.00
19437.000	1580.00	680.05	1.03	0.82	3.08	108.93	50.00
19517.000	820.00	677.07	0.0	0.11	0.0	91.00	80.00
19517.000	1200.00	678.53	1.46	0.19	1.46	226.33	80.00
19517.000	1350.00	679.23	0.70	0.21	2.16	230.24	80.00
19517.000	1580.00	680.28	1.04	0.23	3.20	235.90	80.00
20117.000	820.00	679.41	0.0	2.34	0.0	117.26	600.00
20117.000	1200.00	680.03	0.62	1.50	0.62	270.15	600.00
20117.000	1350.00	680.30	0.27	1.07	0.89	286.06	600.00
20117.000	1580.00	680.93	0.63	0.65	1.52	322.42	600.00
20617.000	820.00	680.99	0.0	1.59	0.0	110.74	500.00
20617.000	1200.00	681.79	0.80	1.76	0.80	147.69	500.00
20617.000	1350.00	682.02	0.23	1.72	1.03	158.01	500.00
20617.000	1580.00	682.34	0.32	1.41	1.34	172.69	500.00
21117.000	820.00	682.49	0.0	1.50	0.0	172.30	500.00
21117.000	1200.00	683.24	0.75	1.45	0.75	309.33	500.00
21117.000	1350.00	683.50	0.26	1.48	1.00	245.00	500.00
21117.000	1580.00	683.84	0.34	1.50	1.35	420.40	500.00

SECNO	Q	CWSEL	DIFWSP	DIFWSX	DIFKWS	TOPWID	XLCH
21392.000	820.00	683.53	0.0	1.04	0.0	82.32	275.00
21392.000	1200.00	684.20	0.66	0.95	0.66	99.79	275.00
21392.000	1350.00	684.42	0.23	0.93	0.89	105.79	275.00
21392.000	1580.00	684.70	0.28	0.86	1.17	113.17	275.00
21667.000	820.00	685.03	0.0	1.50	0.0	88.90	275.00
21667.000	1200.00	685.75	0.72	1.56	0.72	112.02	275.00
21667.000	1350.00	686.00	0.25	1.58	0.97	119.96	275.00
21667.000	1580.00	686.36	0.36	1.66	1.33	131.64	275.00
22128.000	820.00	687.43	0.0	2.40	0.0	55.68	461.00
22128.000	1200.00	688.24	0.81	2.48	0.81	85.56	461.00
22128.000	1350.00	688.49	0.25	2.49	1.06	112.57	461.00
22128.000	1580.00	688.85	0.36	2.48	1.42	148.80	461.00
22589.000	820.00	689.60	0.0	2.17	0.0	217.79	461.00
22589.000	1200.00	690.40	0.80	2.16	0.80	261.79	461.00
22589.000	1350.00	690.66	0.27	2.17	1.07	276.38	461.00
22589.000	1580.00	691.04	0.38	2.20	1.45	295.89	461.00
23050.000	820.00	691.76	0.0	2.17	0.0	234.88	461.00
23050.000	1200.00	692.28	0.52	1.88	0.52	264.02	461.00
23050.000	1350.00	692.47	0.19	1.81	0.71	274.33	461.00
23050.000	1580.00	692.75	0.28	1.71	0.99	289.64	461.00
23550.000	820.00	693.13	0.0	1.36	0.0	158.71	500.00
23550.000	1200.00	693.77	0.64	1.49	0.64	178.98	500.00
23550.000	1350.00	693.99	0.22	1.52	0.86	185.96	500.00
23550.000	1580.00	694.29	0.30	1.54	1.17	195.40	500.00
24226.000	730.00	693.99	0.0	0.86	0.0	180.20	676.00
24226.000	1070.00	694.75	0.77	0.98	0.77	214.87	676.00
24226.000	1210.00	695.01	0.26	1.02	1.03	225.04	676.00
24226.000	1410.00	695.37	0.35	1.07	1.38	238.87	676.00
* 24250.000	730.00	694.33	0.0	0.34	0.0	12.00	24.00
24250.000	1070.00	694.83	0.50	0.08	0.50	210.39	24.00
24250.000	1210.00	695.09	0.26	0.08	0.76	220.63	24.00
24250.000	1410.00	695.45	0.35	0.00	1.12	234.47	24.00

SUMMARY OF ERRORS

CAUTION SECNO=14440.000 PROFILE= 4 CRITICAL DEPTH ASSUMED
CAUTION SECNO=14440.000 PROFILE= 4 20 TRIALS ATTEMPTED TO BALANCE WSEL

CAUTION SECNO=24250.000 PROFILE= 1 CRITICAL DEPTH ASSUMED
CAUTION SECNO=24250.000 PROFILE= 1 PROBABLE MINIMUM SPECIFIC ENERGY
CAUTION SECNO=24250.000 PROFILE= 1 20 TRIALS ATTEMPTED TO BALANCE WSEL

FLOOD INSURANCE ZONE DATA FOR TARABUSI CREEK LIVONIA C

FLOOD HAZARD FACTOR FOR ENTIRE REACH USING SECTIONS

SECTION NUMBER	CUMULATIVE DISTANCE	ELEVATION DIFFERENCE BETWEEN BASE FLOOD AND 10	2	0.2
120.000	0.	0.0	0.0	0.0
370.000	250.	-0.94	-0.33	0.49
745.000	625.	-1.12	-0.29	0.39
1120.000	1000.	-1.28	-0.34	0.46
1770.000	1650.	-1.60	-0.43	0.54
2416.000	2296.	-1.72	-0.46	0.57
2466.000	2346.	-1.92	-0.51	0.65
2554.000	2434.	-1.92	-0.51	0.65
2604.000	2484.	-1.94	-0.52	0.66
3360.000	3240.	-1.73	-0.48	0.62
4116.000	3996.	-1.31	-0.37	0.49
4316.000	4196.	-0.97	-0.27	0.32
4403.000	4283.	-2.39	-0.31	0.37
4453.000	4333.	-2.26	-0.48	0.57
5950.000	5830.	-1.98	-0.46	0.59
6600.000	6480.	-1.79	-0.45	0.57
7340.000	7220.	-1.04	-0.32	0.45
8078.000	7958.	-0.94	-0.28	0.39
8815.000	8695.	-0.97	-0.28	0.33
9276.000	9156.	-1.00	-0.27	0.36
9737.000	9617.	-1.24	-0.33	0.40
10196.000	10078.	-1.27	-0.33	0.41
10658.000	10538.	-1.27	-0.33	0.42
10708.000	10588.	-1.42	-0.38	0.49
10782.000	10662.	-1.44	-0.38	0.49
10832.000	10712.	-1.59	-0.42	0.55
11720.000	11600.	-1.35	-0.36	0.44
12145.000	12025.	-0.67	-0.19	0.29
12570.000	12450.	-0.88	-0.23	0.32
12965.000	12845.	-0.88	-0.22	0.31
13360.000	13240.	-0.95	-0.23	0.32
13704.000	13584.	-1.09	-0.28	0.38
14047.000	13927.	-1.09	-0.28	0.39
14219.000	14099.	-1.13	-0.29	0.39
14390.000	14270.	-1.03	-0.29	0.33
14440.000	14320.	-1.21	-0.31	0.50
14501.000	14381.	-1.78	-1.00	1.63
14570.000	14450.	-2.17	-0.99	0.27
15360.000	15240.	-2.16	-0.91	0.36
16100.000	15980.	-1.93	-0.71	0.45
16500.000	16380.	-1.24	-0.39	0.40
16900.000	16780.	-1.19	-0.34	0.41
17295.000	17175.	-1.03	-0.27	0.37
17690.000	17570.	-0.89	-0.23	0.32
18215.000	18095.	-0.99	-0.25	0.35
18739.000	18619.	-1.06	-0.27	0.37
19001.000	18881.	-1.26	-0.32	0.44
19263.000	19143.	-1.31	-0.33	0.45
19313.000	19193.	-1.34	-0.34	0.46
19387.000	19267.	-1.73	-0.61	0.96
19437.000	19317.	-2.05	-0.67	1.03
19517.000	19397.	-2.1	-0.7	1.05

20617.000	20497.	-1.03	-0.23	0.32
21117.000	20997.	-1.00	-0.26	0.34
21392.000	21272.	-0.89	-0.23	0.28
21667.000	21547.	-0.97	-0.25	0.36
22128.000	22008.	-1.06	-0.25	0.36
22589.000	22469.	-1.07	-0.27	0.30
23050.000	22930.	-0.71	-0.19	0.28
23550.000	23430.	-0.86	-0.22	0.30
24226.000	24106.	-1.03	-0.26	0.35
24250.000	24130.	-0.76	-0.26	0.35
WEIGHTED AVG FOR REACH		-1.32	-0.37	0.44

FHF FOR THE REACH = 015 WITH 75.2 OF THE REACH WITHIN 0.5 FEET
ZONE FOR THE REACH = A 3

CONTINUOUS FLOOD HAZARD FACTORS BY EVEN INCREMENTS

INC NO.	TOTAL LENGTH	AVG ELEVATION DATA 10	1	DIFF.	WTD. AVG.	FHF	PERCENT WITHIN
	0.				SEC.	120.000	
1	100.	620.18	620.34	-0.16	-0.18	005	100.
2	200.	620.47	621.03	-0.56	-0.37	005	100.
	250.				SEC.	370.000	
3	300.	620.80	621.65	-0.85	-0.53	005	100.
4	400.	621.15	622.14	-0.99	-0.64	005	100.
5	500.	621.53	622.56	-1.03	-0.72	005	80.
6	600.	621.90	622.98	-1.08	-0.78	010	83.
	625.				SEC.	745.000	
7	700.	622.21	623.34	-1.13	-0.83	010	86.
8	800.	622.43	623.60	-1.17	-0.87	010	88.
9	900.	622.63	623.84	-1.21	-0.91	010	89.
	1000.				SEC.	1120.000	
10	1000.	622.83	624.09	-1.26	-0.95	010	90.
11	1100.	623.03	624.33	-1.30	-0.98	010	91.
12	1200.	623.23	624.58	-1.35	-1.01	010	92.
13	1300.	623.44	624.84	-1.40	-1.04	010	92.
14	1400.	623.64	625.09	-1.45	-1.07	010	66.
15	1500.	623.84	625.34	-1.50	-1.10	010	87.
16	1600.	624.04	625.59	-1.55	-1.13	010	88.
	1650.				SEC.	1770.000	
17	1700.	624.22	625.81	-1.59	-1.15	010	88.
18	1800.	624.36	625.97	-1.61	-1.18	010	89.
19	1900.	624.47	626.10	-1.63	-1.20	010	89.
20	2000.	624.58	626.23	-1.65	-1.22	010	90.
21	2100.	624.68	626.36	-1.68	-1.25	015	90.
22	2200.	624.79	626.49	-1.70	-1.27	015	91.
	2290.				SEC.	2410.000	
23	2300.	624.91	626.63	-1.72	-1.29	015	91.
	2346.				SEC.	2466.000	
24	2400.	625.07	626.90	-1.83	-1.31	015	88.
	2436.				SEC.	2554.000	
	2454.				SEC.	2604.000	
25	2500.	625.24	627.17	-1.93	-1.33	015	88.
26	2600.	625.40	627.32	-1.92	-1.36	015	81.
27	2700.	625.57	627.46	-1.89	-1.38	015	78.
28	2800.	625.74	627.61	-1.87	-1.39	015	82.
29	2 [illegible]	[illegible] 91	7 79	[illegible]	-1 41	015	83

30	3000.	626.09	627.90	-1.81	-1.42	015	89.
31	3100.	626.26	628.04	-1.78	-1.43	015	90.
32	3200.	626.43	628.18	-1.75	-1.44	015	91.

	3240.				SEC. 3360.000		
33	3300.	626.64	628.36	-1.72	-1.45	015	91.
34	3400.	626.90	628.57	-1.67	-1.46	015	91.
35	3500.	627.19	628.80	-1.61	-1.46	015	91.
36	3600.	627.48	629.03	-1.55	-1.47	015	92.
37	3700.	627.77	629.27	-1.50	-1.47	015	92.
38	3800.	628.05	629.50	-1.45	-1.47	015	92.
39	3900.	628.34	629.73	-1.39	-1.46	015	92.
	3996.				SEC. 4116.000		
40	4000.	628.63	629.96	-1.33	-1.46	015	93.
41	4100.	628.91	630.12	-1.21	-1.45	015	93.
	4196.				SEC. 4316.000		
42	4200.	629.23	630.31	-1.08	-1.45	015	93.
	4283.				SEC. 4403.000		
43	4300.	630.87	632.56	-1.69	-1.45	015	93.
	4333.				SEC. 4453.000		
44	4400.	632.74	635.03	-2.29	-1.47	015	91.
45	4500.	633.18	635.41	-2.23	-1.49	015	89.
46	4600.	633.23	635.46	-2.22	-1.50	015	85.
47	4700.	633.28	635.48	-2.20	-1.52	015	83.
48	4800.	633.34	635.52	-2.18	-1.53	015	81.
49	4900.	633.39	635.55	-2.16	-1.54	015	78.
50	5000.	633.44	635.59	-2.15	-1.56	015	76.
51	5100.	633.50	635.62	-2.12	-1.57	015	75.
52	5200.	633.55	635.66	-2.11	-1.58	015	73.
53	5300.	633.60	635.69	-2.09	-1.59	015	70.
54	5400.	633.65	635.73	-2.08	-1.60	015	70.
55	5500.	633.71	635.76	-2.05	-1.61	015	73.
56	5600.	633.76	635.79	-2.03	-1.61	015	73.
57	5700.	633.81	635.83	-2.02	-1.62	015	75.
58	5800.	633.87	635.86	-1.99	-1.63	015	76.
	5836.				SEC. 5950.000		
59	5900.	633.93	635.90	-1.97	-1.63	015	76.
60	6000.	634.00	635.94	-1.94	-1.64	015	75.
61	6100.	634.07	635.99	-1.92	-1.64	015	75.
62	6200.	634.14	636.03	-1.89	-1.65	015	77.
63	6300.	634.21	636.07	-1.86	-1.65	015	78.
64	6400.	634.29	636.12	-1.83	-1.65	015	78.
	6480.				SEC. 6600.000		
65	6500.	634.38	636.17	-1.79	-1.65	015	78.
66	6600.	634.55	636.28	-1.73	-1.66	015	80.
67	6700.	634.80	636.42	-1.62	-1.65	015	79.
68	6800.	635.05	636.57	-1.52	-1.65	015	79.
69	6900.	635.30	636.72	-1.42	-1.65	015	80.
70	7000.	635.55	636.86	-1.31	-1.64	015	79.
71	7100.	635.79	637.01	-1.22	-1.64	015	79.
72	7200.	636.04	637.16	-1.12	-1.63	015	79.
	7220.				SEC. 7340.000		
73	7300.	636.30	637.35	-1.05	-1.62	015	79.
74	7400.	636.58	637.61	-1.03	-1.62	015	78.
75	7500.	636.86	637.88	-1.02	-1.61	015	76.
76	7600.	637.15	638.14	-0.99	-1.60	015	74.
77	7700.	637.43	638.41	-0.98	-1.59	015	73.
78	7800.	637.71	638.68	-0.97	-1.58	015	73.
79	7900.	637.99	638.95	-0.96	-1.58	015	72.
	7958.				SEC. 8078.000		
80	8000.	638.26	639.21	-0.95	-1.57	015	70.
81	8100.	638.51	639.46	-0.95	-1.56	015	69.
82	8200.	638.75	639.70	-0.95	-1.55	015	70.
83	8300.	638.99	639.94	-0.95	-1.55	015	69.
84	8400.	639.23	640.19	-0.96	-1.56	015	67.
85	8500.	639.46	640.43	-0.97	-1.53	015	68.
86	8400.	63 .76	6 .7	-0.97	-1. 3	015	67.

	[illegible]				SEC. 8 15.0 0		
87	8700.	639.94	640.91	-0.97	-1.52	015	67.
88	8800.	640.16	641.14	-0.98	-1.51	015	66.
89	8900.	640.36	641.34	-0.98	-1.51	015	64.
90	9000.	640.56	641.55	-0.99	-1.50	015	63.
91	9100.	640.77	641.76	-0.99	-1.50	015	63.
	9156.				SEC. 9276.000		
92	9200.	640.98	641.99	-1.01	-1.49	015	67.
93	9300.	641.20	642.25	-1.05	-1.49	015	68.
94	9400.	641.43	642.54	-1.11	-1.48	015	70.
95	9500.	641.66	642.82	-1.16	-1.48	015	71.
96	9600.	641.90	643.10	-1.20	-1.48	015	71.
	9617.				SEC. 9737.000		
97	9700.	642.12	643.36	-1.24	-1.47	015	75.
98	9800.	642.34	643.59	-1.25	-1.47	015	76.
99	9900.	642.56	643.82	-1.26	-1.47	015	76.
100	10000.	642.78	644.04	-1.26	-1.47	015	76.
	10078.				SEC. 10198.000		
101	10100.	643.01	644.27	-1.26	-1.46	015	77.
102	10200.	643.25	644.51	-1.26	-1.46	015	77.
103	10300.	643.50	644.77	-1.27	-1.46	015	78.
104	10400.	643.76	645.03	-1.27	-1.46	015	78.
105	10500.	644.01	645.28	-1.27	-1.46	015	78.
	10538.				SEC. 10658.000		
	10588.				SEC. 10708.000		
106	10600.	644.42	645.76	-1.34	-1.46	015	78.
	10662.				SEC. 10782.000		
107	10700.	644.78	646.27	-1.49	-1.46	015	79.
	10712.				SEC. 10832.000		
108	10800.	644.98	646.56	-1.56	-1.46	015	79.
109	10900.	645.18	646.73	-1.55	-1.46	015	79.
110	11000.	645.37	646.89	-1.52	-1.46	015	79.
111	11100.	645.55	647.05	-1.50	-1.46	015	79.
112	11200.	645.74	647.21	-1.47	-1.46	015	79.
113	11300.	645.92	647.37	-1.45	-1.46	015	80.
114	11400.	646.11	647.53	-1.42	-1.46	015	80.
115	11500.	646.29	647.69	-1.40	-1.46	015	80.
	11[illegible]00.				SEC. 11720.000		
116	11600.	646.48	647.84	-1.36	-1.46	015	80.
117	11700.	646.87	648.14	-1.27	-1.46	015	80.
118	11800.	647.46	648.57	-1.11	-1.45	015	84.
119	11900.	646.05	649.00	-0.95	-1.45	015	86.
120	12000.	648.64	649.43	-0.79	-1.44	015	83.
	12025.				SEC. 12105.000		
121	12100.	649.09	649.80	-0.71	-1.44	015	83.
122	12200.	649.36	650.09	-0.73	-1.43	015	81.
123	12300.	649.58	650.36	-0.78	-1.43	015	80.
124	12400.	649.80	650.63	-0.83	-1.42	015	79.
	12450.				SEC. 12570.000		
125	12500.	650.05	650.92	-0.87	-1.42	015	78.
126	12600.	650.39	651.27	-0.88	-1.41	015	76.
127	12700.	650.76	651.64	-0.88	-1.41	015	76.
128	12800.	651.13	652.01	-0.88	-1.40	015	75.
	12845.				SEC. 12965.000		
129	12900.	651.51	652.39	-0.88	-1.40	015	74.
130	13000.	651.91	652.80	-0.89	-1.40	015	74.
131	13100.	652.32	653.23	-0.91	-1.39	015	75.
132	13200.	652.73	653.66	-0.93	-1.39	015	75.
	13240.				SEC. 13360.000		
133	13300.	653.15	654.10	-0.95	-1.39	015	75.
134	13400.	653.59	654.59	-1.00	-1.38	015	77.
135	13500.	654.05	655.08	-1.03	-1.38	015	77.
	13584.				SEC. 13704.000		
136	13600.	654.51	655.58	-1.07	-1.38	015	77.
137	13700.	655.00	656.09	-1.09	-1.37	015	77.
13[illegible]	13[illegible]00.	[illegible]	[illegible]	-1.09	[illegible]	01[illegible]	7[illegible]

139	13900.	656.05	657.14	-1.0	-1.37	015	78.
	13927.				SEC.	14047.000	
140	14000.	656.56	657.66	-1.10	-1.37	015	79.
	14099.				SEC.	14219.000	
141	14100.	657.06	658.17	-1.11	-1.37	015	79.
142	14200.	657.47	658.57	-1.10	-1.37	015	79.
	14270.				SEC.	14390.000	
143	14300.	657.93	659.03	-1.10	-1.36	015	76.
	14320.				SEC.	14440.000	
	14381.				SEC.	14501.000	
144	14400.	659.64	661.16	-1.52	-1.36	015	78.
	14450.				SEC.	14570.000	
145	14500.	661.71	663.74	-2.03	-1.37	015	79.
146	14600.	662.37	664.54	-2.17	-1.37	015	78.
147	14700.	662.43	664.59	-2.16	-1.38	015	77.
148	14800.	662.48	664.65	-2.17	-1.39	015	75.
149	14900.	662.54	664.70	-2.16	-1.39	015	74.
150	15000.	662.59	664.76	-2.17	-1.40	015	73.
151	15100.	662.65	664.81	-2.16	-1.40	015	73.
152	15200.	662.70	664.86	-2.16	-1.41	015	72.
	15240.				SEC.	15360.000	
153	15300.	662.78	664.93	-2.15	-1.41	015	72.
154	15400.	662.90	665.03	-2.13	-1.42	015	72.
155	15500.	663.04	665.13	-2.09	-1.42	015	72.
156	15600.	663.17	665.24	-2.07	-1.42	015	71.
157	15700.	663.31	665.34	-2.03	-1.43	015	71.
158	15800.	663.44	665.45	-2.01	-1.43	015	71.
159	15900.	663.58	665.55	-1.97	-1.44	015	70.
	15980.				SEC.	16100.000	
160	16000.	663.74	665.67	-1.93	-1.44	015	71.
161	16100.	664.05	665.86	-1.81	-1.44	015	71.
162	16200.	664.46	666.10	-1.64	-1.44	015	71.
163	16300.	664.88	666.36	-1.48	-1.44	015	71.
	16380.				SEC.	16500.000	
164	16400.	665.27	666.58	-1.31	-1.44	015	71.
165	16500.	665.56	666.79	-1.23	-1.44	015	72.
166	16600.	665.77	666.99	-1.22	-1.44	015	72.
167	16700.	665.97	667.16	-1.21	-1.44	015	72.
	16780.				SEC.	16900.000	
168	16800.	666.19	667.38	-1.19	-1.44	015	72.
169	16900.	666.47	667.63	-1.16	-1.43	015	72.
170	17000.	666.80	667.92	-1.12	-1.43	015	72.
171	17100.	667.12	668.20	-1.08	-1.43	015	73.
	17175.				SEC.	17295.000	
172	17200.	667.47	668.51	-1.04	-1.43	015	73.
173	17300.	667.89	668.89	-1.00	-1.43	015	73.
174	17400.	668.35	669.32	-0.97	-1.42	015	72.
175	17500.	668.82	669.75	-0.93	-1.42	015	72.
	17570.				SEC.	17690.000	
176	17600.	669.28	670.19	-0.91	-1.42	015	72.
177	17700.	669.73	670.63	-0.90	-1.41	015	71.
178	17800.	670.17	671.09	-0.92	-1.41	015	71.
179	17900.	670.60	671.54	-0.94	-1.41	015	72.
180	18000.	671.03	672.00	-0.97	-1.41	015	72.
	18095.				SEC.	18215.000	
181	18100.	671.47	672.45	-0.98	-1.40	015	72.
182	18200.	671.89	672.89	-1.00	-1.40	015	73.
183	18300.	672.30	673.30	-1.00	-1.40	015	73.
184	18400.	672.70	673.72	-1.02	-1.40	015	73.
185	18500.	673.11	674.14	-1.03	-1.40	015	73.
186	18600.	673.52	674.56	-1.04	-1.39	015	74.
	18619.				SEC.	18739.000	
187	18700.	673.95	675.03	-1.08	-1.39	015	74.
188	18800.	674.41	675.56	-1.15	-1.39	015	74.
	18881.				SEC.	19001.000	
189	18900.	674.87	676.07	-1.20	-1.39	015	7

190	19000.	675.26	676.54	-1.28	-1.3	015	74.
191	19100.	675.62	676.91	-1.29	-1.39	015	74.
	19143.				SEC.	19263.000	
	19193.				SEC.	19313.000	
192	19200.	675.99	677.33	-1.34	-1.39	015	74.
	19267.				SEC.	19387.000	
193	19300.	676.50	678.16	-1.66	-1.39	015	75.
	19317.				SEC.	19437.000	
	19397.				SEC.	19517.000	
194	19400.	676.95	679.00	-2.05	-1.39	015	74.
195	19500.	677.28	679.33	-2.05	-1.40	015	73.
196	19600.	677.67	679.50	-1.83	-1.40	015	73.
197	19700.	678.06	679.68	-1.62	-1.40	015	74.
198	19800.	678.45	679.86	-1.41	-1.40	015	74.
199	19900.	678.84	680.04	-1.20	-1.40	015	74.
	19997.				SEC.	20117.000	
200	20000.	679.22	680.22	-1.00	-1.40	015	74.
201	20100.	679.58	680.48	-0.90	-1.39	015	75.
202	20200.	679.89	680.83	-0.94	-1.39	015	75.
203	20300.	680.21	681.17	-0.96	-1.39	015	75.
204	20400.	680.53	681.51	-0.98	-1.39	015	75.
	20497.				SEC.	20617.000	
205	20500.	680.84	681.86	-1.02	-1.39	015	75.
206	20600.	681.15	682.18	-1.03	-1.38	015	76.
207	20700.	681.45	682.47	-1.02	-1.38	015	76.
208	20800.	681.75	682.77	-1.02	-1.38	015	76.
209	20900.	682.05	683.06	-1.01	-1.38	015	77.
	20997.				SEC.	21117.000	
210	21000.	682.35	683.36	-1.01	-1.38	015	77.
211	21100.	682.69	683.68	-0.99	-1.38	015	77.
212	21200.	683.07	684.01	-0.94	-1.37	015	77.
	21272.				SEC.	21392.000	
213	21300.	683.47	684.38	-0.91	-1.37	015	77.
214	21400.	683.96	684.87	-0.91	-1.37	015	78.
215	21500.	684.50	685.45	-0.95	-1.37	015	78.
	21547.				SEC.	21667.000	
216	21600.	685.04	686.01	-0.97	-1.37	015	78.
217	21700.	685.57	686.56	-0.99	-1.36	015	77.
218	21800.	686.09	687.10	-1.01	-1.36	015	78.
219	21900.	686.61	687.64	-1.03	-1.36	015	78.
220	22000.	687.12	688.18	-1.06	-1.36	015	78.
	22002.				SEC.	22122.000	
221	22100.	687.62	688.69	-1.07	-1.36	015	78.
222	22200.	688.09	689.16	-1.07	-1.36	015	78.
223	22300.	688.57	689.63	-1.06	-1.36	015	78.
224	22400.	689.04	690.10	-1.06	-1.35	015	78.
	22469.				SEC.	22589.000	
225	22500.	689.51	690.56	-1.05	-1.35	015	78.
226	22600.	689.98	690.98	-1.00	-1.35	015	78.
227	22700.	690.45	691.37	-0.92	-1.35	015	78.
228	22800.	690.92	691.77	-0.85	-1.35	015	79.
229	22900.	691.39	692.16	-0.77	-1.34	015	78.
	22930.				SEC.	23050.000	
230	23000.	691.79	692.52	-0.73	-1.34	015	78.
231	23100.	692.09	692.84	-0.75	-1.34	015	77.
232	23200.	692.36	693.14	-0.78	-1.34	015	77.
233	23300.	692.64	693.45	-0.81	-1.33	015	77.
234	23400.	692.91	693.75	-0.84	-1.33	015	77.
	23430.				SEC.	23550.000	
235	23500.	693.13	694.00	-0.87	-1.33	015	77.
236	23600.	693.28	694.17	-0.89	-1.33	015	77.
237	23700.	693.41	694.32	-0.91	-1.33	015	77.
238	23800.	693.53	694.48	-0.95	-1.33	015	77.
239	23900.	693.66	694.63	-0.97	-1.32	015	76.
240	24000.	693.79	694.78	-0.99	-1.32	015	76.
241	24100.	693.93	694.93	-1.01	-1.32	015	77.

24106. SEC. 24 _6.000
24130. SEC. 24250.000

THIS REACH CAN BE SUBDIVIDED BY INC NO. TO MEET FIA REQUIREMENTS
INPUT 20N WHERE N IS THE NUMBER OF REACHES AND THEN INPUT THE END
OF EACH REACH BY INC NO. FOR EXAMPLE 202 123 241
A NEGATIVE INC NO. WILL SUPPRESS INTERMEDIATE INC OUTPUT.

```
C*****************************************************************
C  HEC2 RELEASE DATED NOV 76 UPDATED AUG1977
C  ERROR CORR -  01,02
C  MODIFICATION -  50,51,52,53
C*****************************************************************
```



1) COUNTY: Wayne

2) STUDY NAME: City of Livonia

3) WATERCOURSE: Tributary 1

4) DOCUMENT TYPE: 100 Year



```
REC2 RELEASE DATED NOV 76 UPDATED  AUG1977
ERROR CORR -  01,02
MODIFICATION -  50,51,52,53
C
T1 TRIBUTARY  1 FIS HUD 2014 07 LIVONIA CITY FROM BELL BRANCH TO SHEFFIELD SUBD.
T2 100 YR FLOW
T3      TRIBUTARY  1 LIVONIA C.
```

J1	ICHECK	INQ	NINV	IDIR	STRT	METRIC	KVINS	0	MSFI	FU
	0.	4.	0.	0.	0.0	0.0	0.0	0.	642.500	0.0
J2	NPROF	IPLOT	PRFVS	XSECV	XSECH	FN	ALLOC	IBT	CHNIM	ITRACE
	1.000	1.000	-1.000	0.0	0.0	0.0	0.0	0.0	0.0	0.0
J3	VARIABLE CODES FOR SUMMARY PRINTOUT									
	110.000	150.000	200.000	0.0	0.0	0.0	0.0	0.0	0.0	0.0
QT	5.000	310.000	520.000	600.000	640.000	930.000	0.0	0.0	0.0	0.0
RC	0.100	0.100	0.035	0.100	0.300	0.0	0.0	0.0	0.0	0.0
	SECND 60, 60' U/S OF CONFLUENCE W/BELL BRANCH FROM FIELDBOOK AND TOPOMAP									
X1	60.000	9.000	356.000	374.000	0.0	0.0	0.0	0.0	0.0	0.0
X3	0.0	0.0	0.0	177.000	0.0	437.000	0.0	0.0	0.0	0.0
GR	660.000	0.0	650.000	170.000	642.700	350.000	639.200	360.000	638.300	365.000
GR	639.000	370.000	642.700	374.000	650.000	700.000	658.000	1040.000	0.0	0.0
QT	5.000	210.000	370.000	460.000	460.000	660.000	0.0	0.0	0.0	0.0
ET	0.0	0.0	0.0	0.0	1.410	0.0	0.0	0.0	0.0	0.0
NC	0.120	0.100	0.035	0.100	0.300	0.0	0.0	0.0	0.0	0.0
	VALLEY SECTION X									
X1	360.000	7.000	350.000	365.000	300.000	300.000	300.000	0.0	0.0	0.0
GR	660.000	0.0	650.000	175.000	642.800	350.000	639.600	358.000	642.200	360.000
GR	650.000	400.000	660.000	800.000	0.0	0.0	0.0	0.0	0.0	0.0
	SECND 660 X									
X1	660.000	7.000	343.000	350.000	300.000	300.000	300.000	0.0	0.0	0.0
GR	661.000	25.000	649.000	120.000	643.600	343.000	641.200	350.000	643.600	350.000
GR	649.500	362.000	662.500	720.000	0.0	0.0	0.0	0.0	0.0	0.0
	VALLEY SECTION X									
X1	960.000	7.000	314.000	325.000	300.000	300.000	300.000	0.0	0.0	0.0
GR	660.000	0.0	648.000	160.000	643.800	314.000	642.600	320.000	643.800	325.000
GR	655.000	445.000	660.000	580.000	0.0	0.0	0.0	0.0	0.0	0.0
NC	0.0	0.	0.040	0.	0.0	0.0	0.0	0.	0.	0.

SECNO 1250 150' U/S OF CONFLUENCE WITH WESTERLY TRIB. FROM FIELD BOOK

X1	1250.000	11.000	285.500	294.500	290.000	290.000	290.000	0.0	0.0	0.0
X3	0.0	0.0	0.0	170.000	0.0	343.000	0.0	0.0	0.0	0.0
GR	662.500	0.0	648.800	30.000	647.500	140.000	648.500	278.500	644.500	285.500
GR	644.000	290.000	644.400	294.500	648.300	302.500	648.900	345.500	668.000	378.500
GR	667.000	413.500	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
NC	0.0	0.0	0.035	0.0	0.0	0.0	0.0	0.0	0.0	0.0
ET	0.0	0.0	0.0	0.0	1.400	0.0	0.0	0.0	0.0	0.0

SECNO 2360 X

X1	2360.000	11.000	270.000	282.000	1110.000	1110.000	1110.000	0.0	0.0	0.0
GR	665.000	0.0	658.000	120.000	653.000	130.000	651.000	260.000	648.000	270.000
GR	647.500	276.000	648.000	282.000	651.000	297.000	653.000	300.000	650.000	315.000
GR	665.000	400.000	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
NC	0.080	0.100	0.035	0.300	0.500	0.0	0.0	0.0	0.0	0.0

SECNO 2915 X

X1	2915.000	8.000	223.000	264.000	559.000	555.000	555.000	0.0	0.0	0.0
GR	667.500	0.0	656.300	113.000	654.300	223.000	649.300	246.000	654.300	264.000
GR	657.900	290.000	661.300	325.000	666.200	406.000	0.0	0.0	0.0	0.0

SECNO 3470 STA 56+05 FROM FIELD BOOK

X1	3470.000	11.000	191.000	230.000	555.000	555.000	555.000	0.0	0.0	0.0
GR	668.000	0.0	661.800	54.000	659.600	100.000	657.700	191.000	651.400	213.000
GR	651.100	216.000	651.700	219.000	657.600	230.000	657.600	268.000	664.800	322.000
GR	667.400	416.000	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

SECNO 3853 X

X1	3853.000	6.000	153.000	195.000	383.000	383.000	383.000	0.0	0.0	0.0
GR	669.000	0.0	665.100	93.000	659.700	153.000	653.400	176.000	659.300	195.000
GR	658.900	223.000	664.800	276.000	667.700	340.000	0.0	0.0	0.0	0.0
NC	0.060	0.060	0.030	0.100	0.300	0.0	0.0	0.0	0.0	0.0

SECNO 4235 STA 40+40 FROM FIELD BOOK AND QUAD MAP

X1	4235.000	9.000	115.000	165.000	267.000	517.000	352.000	0.0	0.0	0.0
GR	670.600	86.000	661.600	115.000	655.800	131.000	655.600	136.000	655.800	141.000
GR	660.000	165.000	659.900	185.000	664.700	234.000	668.000	286.000	0.0	0.0

SECNO 4588 50' D/S 6 MILE BRIDGE BASED ON FIELD BOOK AND QUAD MAP

X1	4588.000	9.000	1222.000	1234.000	353.000	353.000	353.000	0.0	0.0	0.0
GR	680.000	0.0	670.000	930.000	671.600	1192.000	656.700	1222.000	656.600	1230.000
GR	656.700	1238.000	669.600	1264.000	670.000	1350.000	680.000	1630.000	0.0	0.0
NC	0.0	0.0	0.0	0.300	0.500	0.0	0.0	0.0	0.0	0.0
ET	0.0	0.0	0.0	0.0	9.100	0.0	0.0	0.0	1.000	1629.000

SECNO 4635 D/S FACE 6 MILE BRIDGE FROM FIELD BOOK AND QUAD MAP

X1	4635.000	0.0	0.0	0.0	50.000	50.000	50.000	0.0	0.0	0.0
X3	10.000	0.0	0.0	0.0	0.0	0.0	0.0	666.400	666.400	0.0
SB	0.0	2.[illegible]	[illegible].000	0.0	16.000	0.0	[illegible].040	0.0	[illegible]57.600	656.600

SECNO 4754 U/S FROM 6 MILE BRIDGE FROM FIELD BOOK AND QUAD MAP

X1	4754.000	11.000	1222.000	1238.000	116.000	116.000	116.000	0.0	0.0	0.0
X2	0.0	0.0	1.000	663.200	669.700	0.0	0.0	0.0	0.0	0.0
X3	10.000	0.0	0.0	0.0	0.0	0.0	0.0	669.700	669.700	0.0
BT	10.000	0.0	680.000	0.0	930.000	670.000	0.0	1202.000	670.000	0.0
BT	1222.000	669.700	657.900	1222.100	669.700	663.200	1237.900	669.700	663.200	1236.000
BT	669.700	657.900	1265.000	671.300	0.0	1350.000	670.000	0.0	1630.000	600.000
ET	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
GR	680.000	0.0	670.000	930.000	667.000	1202.000	657.900	1222.000	657.900	1222.100
GR	657.800	1230.000	657.900	1237.900	657.900	1238.000	671.300	1265.000	670.000	1350.000
GR	680.000	1630.000	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
NC	0.080	0.080	0.030	0.300	0.500	0.0	0.0	0.0	0.0	0.0

SECNO 4804 50' U/S 6 MILE BRIDGE BASED ON FIELD BOOK AND QUAD MAP

X1	4804.000	8.000	1217.000	1243.000	50.000	50.000	50.000	0.0	0.0	0.0
X3	0.0	0.0	0.0	1196.000	0.0	1259.000	0.0	0.0	0.0	0.0
GR	675.000	930.000	666.000	1145.000	661.000	1217.000	658.000	1225.000	657.900	1230.000
GR	658.000	1235.000	661.000	1243.000	670.000	1350.000	0.0	0.0	0.0	0.0
ET	0.0	0.0	0.0	7.100	9.100	0.0	226.000	265.000	1.000	669.000
NC	0.100	0.100	0.035	0.100	0.300	0.0	0.0	0.0	0.0	0.0

SECNO 5363 STA 37+12 FROM FIELD BOOK

X1	5363.000	22.000	246.000	254.000	559.000	559.000	559.000	0.0	0.0	0.0
GR	667.600	0.0	665.500	100.000	667.100	179.000	667.000	194.000	662.600	235.000
GR	661.300	240.000	659.500	246.000	650.900	250.000	659.000	254.000	661.400	257.000
GR	662.900	259.000	664.500	272.000	665.000	290.000	665.500	310.000	665.600	320.000
GR	667.100	370.000	667.900	400.000	668.500	450.000	669.000	500.000	669.500	550.000
GR	670.000	600.000	670.400	650.000	0.0	0.0	0.0	0.0	0.0	0.0
ET	0.0	0.0	0.0	7.100	7.100	0.0	507.000	544.000	0.0	0.0

SECNO 5735. X

X1	5735.000	13.000	520.000	531.000	372.000	75.000	372.000	0.0	0.0	0.0
GR	675.000	0.0	671.000	100.000	668.600	260.000	666.900	370.000	667.000	440.000
GR	663.500	513.000	661.000	520.000	660.400	525.000	660.800	531.000	664.700	534.000
GR	667.900	598.000	669.300	680.000	675.000	975.000	0.0	0.0	0.0	0.0

SECNO 6107 BASED ON FIELD BOOK AND QUAD MAP

X1	6107.000	23.000	793.000	807.000	372.000	75.000	372.000	0.0	0.0	0.0
X3	0.0	0.0	0.0	775.000	0.0	810.000	0.0	0.0	0.0	0.0
GR	660.000	0.0	676.500	80.000	677.100	160.000	675.600	240.000	674.100	320.000
GR	672.600	400.000	671.100	480.000	669.700	660.000	668.200	640.000	667.000	700.000
GR	667.000	770.000	665.800	785.000	662.500	793.000	661.900	800.000	662.500	807.000
GR	660.000	811.000	670.000	875.000	670.800	900.000	671.400	920.000	672.600	950.000
GR	675.100	1040.000	677.500	1120.000	680.000	1200.000	0.0	0.0	0.0	0.0

SECNO 6355 STA 27+20 FROM FIELD BOOK AND QUAD MAP

X1	6355.000	24.000	1131.000	1169.000	248.000	248.000	244.000	0.0	0.0	0.0
X3	0.0	0.0	0.0	1113.000	0.0	1354.000	0.0	0.0	0.0	0.0
GR	660.000	0.0	676.800	75.000	677.700	150.000	676.600	226.000	675.500	300.000
GR	674.400	375.000	673.400	450.000	672.300	525.000	671.200	600.000	670.100	675.000
GR	669.000	750.000	668.200	800.000	667.900	826.000	667.500	850.000	667.600	1000.000
GR	667.500	1131.000	663.200	1147.000	662.900	1150.000	662.900	1151.000	670.500	1169.000
GR	671.000	1200.000	672.000	1250.000	673.100	1300.000	674.500	1400.000	0.0	0.0

ET	0.0	0.0	0.0	0.0	1.400	0.0	0.0	0.0	0.0	0.0

SECNO 7080 X

XI	7080.000	5.000	26.000	70.000	725.000	725.000	725.000	0.0	0.0	0.0
GR	670.000	0.0	669.300	26.000	667.900	48.000	669.300	70.000	670.000	96.000
NC	0.0	0.0	0.025	0.300	0.500	0.0	0.0	0.0	0.0	0.0

SECNO 7975 WEIR BASED ON SUBD. MAP

XI	7975.000	4.000	18.000	72.000	895.000	895.000	895.000	0.0	0.0	0.0
AS	5.000	676.150	676.700	677.000	677.100	677.650	0.0	0.0	0.0	0.0
GR	679.600	0.0	675.000	18.000	675.000	72.000	679.600	90.000	0.0	0.0
QT	5.000	210.000	370.000	460.000	400.000	680.000	0.0	0.0	0.0	0.0
NC	0.0	0.0	0.035	0.100	0.300	0.0	0.0	0.0	0.0	0.0
EN	0.0	0.0	0.0	0.0	1.400	0.0	0.0	0.0	0.0	0.0

SECNO 0352 STA 7+23 FROM FIELD BOOK

XI	6352.000	8.000	280.000	320.000	377.000	377.000	377.000	0.0	0.0	0.0
GR	683.500	0.0	682.600	150.000	682.100	253.000	675.200	200.000	673.700	300.000
GR	675.200	320.000	681.000	341.000	682.200	401.000	0.0	0.0	0.0	0.0

SECNO 9075 BASED ON FIELD BOOK

XI	9075.000	0.0	0.0	0.0	723.000	723.000	723.000	0.0	4.600	0.0
EJ	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

*PROF 1

CCHV= 0.100 CEHV= 0.300
*SECNO 60.000

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	QLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ERDST

3720 CRITICAL DEPTH ASSUMED

3470 ENCROACHMENT STATIONS= 171.0 437.0 TYPE= 1 TARGET= 280.000

SECNO 60, 60' U/S OF CONFLUENCE W/BELL BRANCH FROM FIELDBOOK AND TOPOMAP

646.39 Yr on Bell Br.

60.00	5.07	643.37	643.37	642.50	644.73	1.36	0.0	0.0	642.70
640.	4.	628.	7.	5.	66.	10.	0.	0.	642.70
0.0	0.76	9.46	0.74	0.100	0.035	0.100	0.0	633.30	338.96
0.010615	0.	0.	0.	0	10	0	0.0	64.90	403.06

CCHV= 0.100 CEHV= 0.300
*SECNO 360.000

3301 HV CHANGED MORE THAN HVINS

VALLEY SECTION X

360.00	6.10	645.90	0.0	0.0	645.21	0.71	1.37	0.11	642.90
460.	88.	351.	21.	116.	69.	23.	1.	1.	642.80
0.02	0.76	5.09	0.69	0.120	0.035	0.100	0.035	639.80	274.76
0.002081	300.	300.	300.	3	0	0	0.0	105.28	360.05

*SECNO 660.000

SECND 660 X

660.00	5.40	646.60	0.0	0.0	647.01	0.42	0.78	0.03	643.60
460.	125.	331.	4.	135.	54.	5.	2.	1.	643.60
0.04	0.93	6.07	0.99	0.120	0.035	0.100	0.035	641.20	252.80
0.003302	300.	300.	300.	2	0	0	0.0	106.24	351.04

*SECNO 960.000

VALLEY SECTION X

960.00	4.95	647.55	0.0	0.0	647.68	0.13	0.64	0.03	643.80
460.	188.	206.	66.	258.	48.	75.	4.	2.	643.80
0.07	0.73	4.32	0.87	0.120	0.035	0.100	0.035	642.60	176.56
0.001502	300.	300.	300.	2	0	0	0.0	108.61	365.16

*SECNO 1250.000

3301 HV CHANGED MORE THAN HVINS

SECNO	DEPTH	C'SEL	CRI'S	'ELK	EG	HV	H.	QLO'S	B'NK ELEV

Q	QLOB	QCH	QROB	XLOB	XCH	XNR	VOL	INA	LOSS/	
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN		SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID		ENDST

3685 20 TRIALS ATTEMPTED WSEL,CWSEL
3693 PROBABLE MINIMUM SPECIFIC ENERGY
3720 CRITICAL DEPTH ASSUMED

3470 ENCROACHMENT STATIONS= 170.0 343.0 TYPE= 1 TARGET= 173.000

SECNO 1250 150' U/S OF CONFLUENCE WITH WESTERLY TRIB. FROM FIELD BOOK

1250.00	4.87	648.87	648.87	0.0	649.56	0.67	0.76	0.16	644.50
460.	89.	326.	45.	99.	42.	32.	6.	4.	644.40
0.09	0.90	7.79	1.41	0.120	0.040	0.100	0.036	644.00	170.00
0.005706	290.	290.	290.	20	8	0	0.0	173.00	343.00

*SECNO 2360.000

SECNO 2360 X

2360.00	5.16	652.66	0.0	0.0	652.97	0.31	3.39	0.04	646.00
460.	79.	315.	66.	122.	54.	50.	11.	8.	646.00
0.17	0.65	5.34	1.34	0.120	0.035	0.100	0.036	667.50	151.80
0.001900	1110.	1110.	1110.	3	0	0	0.0	167.70	299.50

CCHV= 0.300 CEHV= 0.500
*SECNO 2915.000

SECNO 2915 X

2915.00	4.83	654.13	0.0	0.0	654.49	0.36	1.45	0.03	654.30
460.	0.	460.	0.	0.	96.	0.	13.	9.	654.30
0.20	0.0	4.00	0.0	0.080	0.035	0.100	0.035	649.30	223.77
0.004105	555.	555.	555.	7	0	0	0.0	35.63	203.60

*SECNO 3470.000

SECNO 3470 STA 56+05 FROM FIELD BOOK

3470.00	5.19	656.29	0.0	0.0	656.68	0.40	2.17	0.02	647.70
460.	0.	460.	0.	0.	91.	0.	15.	9.	647.60
0.23	0.0	5.05	0.0	0.080	0.035	0.100	0.035	651.10	165.94
0.003737	555.	555.	555.	2	0	0	0.0	31.61	227.55

*SECNO 3853.000

SECNO 3853 X

3853.00	4.70	658.10	0.0	0.0	658.67	0.57	1.00	0.09	659.70
460.	0.	460.	0.	0.	76.	0.	15.	10.	659.30
0.25	0.0	6.07	0.0	0.080	0.035	0.100	0.035	653.40	154.85
0.006900	383.	383.	383.	2	1	0	0.0	36.25	191.13

CCHV= 0.100 CEHV= 0.300
*SECNO 4235.000

SECNO	DEPTH	CWSEL	CRIWS	WSELR	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	INA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

SECNO 4235 STA 46+40 FROM FIELD BOOK AND QUAD MAP

4235.00	4.21	659.81	0.0	0.0	660.08	0.28	1.38	0.03	661.60
460.	0.	460.	0.	0.	109.	0.	16.	10.	660.00
0.27	0.0	4.22	0.0	0.060	0.030	0.060	0.035	655.60	119.95
0.002227	267.	382.	517.	2	0	0	0.0	43.95	163.89

°SECNO 4588.000

SECNO 4588 50' D/S 6 MILE BRIDGE BASED ON FIELD BOOK AND QUAD MAP

4588.00	3.88	660.48	0.0	0.0	661.08	0.60	0.90	0.10	656.70
460.	28.	405.	28.	14.	61.	14.	17.	10.	656.70
0.29	1.92	6.61	1.92	0.060	0.030	0.060	0.034	656.60	1214.39
0.002968	353.	353.	353.	2	6	0	0.0	31.23	1245.62

CCHV= 0.300 CEHV= 0.500
°SECNO 4638.000

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE.ELLEA= 666.40 ELREA= 666.40

SECNO 4638 D/S FACE 6 MILE BRIDGE FROM FIELD BOOK AND QUAD MAP

4638.00	3.93	660.53	0.0	0.0	661.38	0.85	0.17	0.13	656.70
460.	0.	460.	0.	0.	62.	0.	17.	10.	656.70
0.29	0.0	7.42	0.0	0.060	0.030	0.060	0.034	656.60	1222.00
0.003956	50.	50.	50.	2	0	0	0.0	16.00	1238.00

SPECIAL BRIDGE

SB	AK	AKOR	COFQ	RDLEN	BWC	BWP	DAREA	SS	ELCHD	ELCAD
	0.0	2.03	3.00	0.0	16.00	0.0	86.40	0.0	657.00	656.80

°SECNO 4754.000

6070.LOW FLOW BY NORMAL BRIDGE

EGPRS= 0.0 EGLWC= 662.500 ELLC= 663.200 ENUSE= 660.326 ELTRD= 669.70

Channel is trapezoidal ✓

3370 NO NORMAL BRIDGE.NRD= 10 MIN ELTRD= 669.70 MAX ELLC= 663.20

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE.ELLEA= 669.70 ELREA= 669.70

SECNO 4754 U/S FACE 6 MILE BRIDGE FROM FIELD BOOK AND QUAD MAP

4754.00	3.17	660.97	0.0	0.0	662.30	1.32	0.68	0.23	657.90
460.	0.	460.	0.	0.	90.	0.	17.	10.	657.90
0.29	0.0	9.23	0.0	0.060	0.030	0.060	0.034	657.80	1222.00
0.009596	116.	116.	116.	3	0	0	-9.67	1[illegible].00	1236.00

CCHV= 0.300 CEHV= 0.500
°SECNO 4804.000

3301 HV CHANGED MORE THAN HVINS

3470 ENCROACHMENT STATIONS= 1196.0 1259.0 TYPE= 1 TARGET= 63.000

SECNO 4804 50' U/S 6 MILE BRIDGE BASED ON FIELD BOOK AND QUAD MAP

4804.00	4.52	662.42	0.0	0.0	662.77	0.35	0.18	0.29	661.00
460.	9.	443.	8.	14.	91.	12.	17.	10.	661.00
0.30	0.64	4.85	0.66	0.000	0.030	0.080	0.034	657.90	1196.59
0.001894	50.	50.	50.	4	0	0	0.0	62.41	1259.00

CCHV= 0.100 CEHV= 0.300

*SECNO 5363.000

3301 HV CHANGED MORE THAN HVINS

SECNO	DEPTH	CHSEL	CRIWS	WSELR	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

3470 ENCROACHMENT STATIONS= 226.0 265.0 TYPE= 1 TARGET= 39.000

SECNO 5363 STA 37+12 FROM FIELD BOOK

5363.00	4.77	663.67	663.33	0.0	664.85	1.18	1.83	0.25	659.50
460.	69.	360.	31.	32.	37.	10.	19.	11.	659.00
0.31	2.18	9.79	1.96	0.100	0.035	0.100	0.034	656.90	226.45
0.006994	559.	559.	559.	6	6	0	0.0	30.55	265.00

*SECNO 5735.000

3301 HV CHANGED MORE THAN HVINS

3470 ENCROACHMENT STATIONS= 507.0 544.0 TYPE= 1 TARGET= 37.000

SECNO 5735. A

5735.00	5.42	665.82	0.0	0.0	666.42	0.60	1.51	0.06	661.00
460.	59.	384.	17.	32.	57.	18.	19.	11.	660.80
0.33	1.54	6.76	0.56	0.100	0.035	0.100	0.034	660.40	507.00
0.002847	372.	372.	75.	2	0	0	0.0	37.00	544.00

*SECNO 6107.000

3470 ENCROACHMENT STATIONS= 775.0 810.0 TYPE= 1 TARGET= 35.000

SECNO 6107 BASED ON FIELD BOOK AND QUAD MAP

6107.00	4.99	666.89	0.0	0.0	667.46	0.57	1.04	0.00	662.50
460.	37.	417.	7.	29.	66.	7.	20.	11.	662.50
0.39	1.27	6.34	0.95	0.100	0.035	0.100	0.034	661.90	775.00
0.002850	372.	372.	75.	2	0	0	0.0	35.00	810.00

*SECNO 6355.000

3470 ENCROACHMENT STATIONS= 1113.0 1354.0 TYPE= 1 TARGET= 241.000

SECNO 6355 STA 27+20 FROM FIELD BOOK AND QUAD MAP

9353.00	4.70	66..88	0.0	0.0	668.29	0.35	0.75	0.02	667.50
4611.	3.	457.	3.	6.	46.	1.	21.	12.	670.50
0.36	0.42	4.76	0.0	0.100	0.035	0.100	0.035	662.90	1113.00
0.003175	248.	248.	243.	2	0	0	0.0	50.49	1163.48

*SECNO 7080.000

SECNO 7080 X

7080.00	2.72	670.62	0.0	0.0	670.94	0.32	2.71	0.00	669.30
410.	2.	606.	2.	3.	69.	3.	22.	13.	669.30
0.41	0.73	4.58	0.73	0.100	0.035	0.100	0.035	667.90	22.07
0.004575	725.	725.	725.	3	0	0	0.0	51.07	73.93

410 cfs from hand comps

flow diverted through 53"x34" conc pipe

≈ 53 cfs, remainder over weir

CCHV= 0.300 CEHV= 0.500

*SECNO 7975.000

WATER EL=X CARD= 677.000

SECNO	DEPTH	CHSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
0	GLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TW	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WIN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IOC	ICONT	CORAR	TOPWID	ENDST

no XSEC D/S of weir

SECNO 7975 WEIR BASED ON SUBD. MAP

7975.00	2.00	677.00	0.0	0.0	677.21	0.21	2.22	0.03	675.00
410.	4.	401.	4.	5.	100.	0.	25.	14.	675.00
0.40	0.57	3.71	0.57	0.100	0.025	0.100	0.033	675.00	10.17
0.001519	695.	695.	695.	0	0	0	0.0	69.05	79.83

CCHV= 0.100 CEHV= 0.300

*SECNO 8352.000

SECNO 8352 STA 7+23 FROM FIELD BOOK

8352.00	3.20	677.60	0.0	0.0	677.79	0.19	0.58	0.00	673.20
460.	7.	446.	7.	11.	126.	17.	26.	14.	675.20
0.51	0.64	3.55	0.64	0.100	0.045	0.103	0.044	673.20	10.19
0.001521	377.	377.	377.	2	0	5	0.0	50.04	326.67

*SECNO 9075.000

3301 HV CHANGED MORE THAN HVINS

SECNO	DEPTH	CHSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
0	GLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TW	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WIN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IOC	ICONT	CORAR	TOPWID	ENDST

3685 20 TRIALS ATTEMPTED WSEL,CHSEL
3693 PROBABLE MINIMUM SPECIFIC ENERGY
3726 CRITICAL DEPTH ASSUMED

SECNO 9175 BASED ON FIELD BOOK

9175.00	2.39	680.04	680.49	0.0	681.04	1.79	2.54	0.19	677.50
450.	1.	457.	1.	3.	64.	1.	25.	15.	680.00
0.43	1.01	7.17	1.01	0.100	0.035	0.100	0.030	671.50	210.49
0.015330	723.	723.	723.	20	14	6	0.0	40.37	323.05

00BREAK00

1) COUNTY: Wayne

2) STUDY NAME: City of Livonia

3) WATERCOURSE: Tributary 1

4) DOCUMENT TYPE: Encroachment

00BREAK00

FORM E-0415

```
oooooooooooooooooooooooooooooooooooooooooooooooooooooooooooooo
  REC2 RELEASE DATED NOV 76 UPDATED  AUG1977
  ERROR CORR -  01,02
  MODIFICATION -  50,51,52,53
oooooooooooooooooooooooooooooooooooooooooooooooooooooooooooooo

T1 TRIBUTARY  1 FIS HUD 2014 07 LIVONIA CITY FROM BELL BRANCH TO SHEFFIELD SUBD.
T2 ENCROACHMENT RUN
T3       TRIBUTARY  1 LIVONIA C.

J1  ICHECK     INQ       NINV      IDIR      STRT      METRIC    HVINS     Q         HSEL      FQ
        0.        5.        0.        0.  0.0           0.0       0.0       0.      643.470   0.0
J2  NPROF      IPLOT     PREVS     XSECV     XSECH     FN        ALLDC     IBW       CHNIM     ITRACE
    15.000     0.0       -1.000    0.0       0.0       0.0       0.0       0.0       0.0       15.000
```

*PROF 2

CCHV= 0.100 CEHV= 0.300

*SECNO 660.000

SECNO	DEPTH	CWSEL	CRITS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	LTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

3470 ENCROACHMENT STATIONS= 177.0 437.0 TYPE= 1 TARGET= 260.000

SECNO 60, 60, U/S OF CONFLUENCE W/BELL BRANCH FROM FIELDBOOK AND TOPOMAP

60.00	5.17	643.47	643.38	643.47	646.74	1.27	0.0	0.0	642.70
640.	6.	624.	10.	8.	68.	13.	0.	0.	642.70
0.0	0.77	9.14	0.77	0.100	0.035	0.100	0.0	638.30	336.38
0.009563	0.	0.	0.	0	0	0	0.0	72.01	408.39

FLOW DISTRIBUTION FOR SECNO= 60.00 CWSEL= 643.47

STA=	336.	356.	374.	408.
PER Q=	0.9	97.5	1.6	
AREA=	7.6	68.3	13.2	
VEL=	0.8	9.1	0.8	

CCHV= 0.100 CEHV= 0.300

*SECNO 360.000

2800 NAT Q1= 100.03 WSEL= 665.90 ENC Q1= 100.83 WSEL= 646.00 RATIO= 0.0

NAT Q1= 105. RATIOS LOB,CH,ROB= 0.1985 0.7545 0.0470 WSEL= 646.00

3301 HV CHANGED MORE THAN HVINS

3470 ENCROACHMENT STATIONS= 316.3 368.7 TYPE= 4 TARGET= 0.006

VALLEY SECTION X

360.00	6.07	645.87	0.0	645.90	646.23	0.36	1.41	0.09	642.00
460.	82.	368.	10.	80.	68.	10.	1.	0.	642.60
0.02	1.03	5.34	1.00	0.120	0.035	0.100	0.035	639.80	316.28
0.002339	300.	300.	300.	2	0	0	0.0	52.42	368.70

FLOW DISTRIBUTION FOR SECNO= 360.00 CWSEL= 665.87

STA=	316.	350.	365.	369.
PER Q=	17.9	80.0	2.1	
AREA=	79.9	68.6	9.9	
VEL=	1.0	5.4	1.0	

*SECNO 660.000

2800 NAT Q1= 80.06 WSEL= 646.60 ENC Q1= 80.06 WSEL= 646.70 RATIO= 0.0

NAT Q1= 85. RATIOS LOB,CH,ROB= 0.2828 0.7081 0.0091 WSEL= 646.70

3470 ENCROACHMENT STATIONS= 306.3 356.0 TYPE= 4 TARGET= 0.050

SECNO 660 X

660.00	5.54	646.74	0.0	646.60	647.13	0.39	0.89	0.01	643.60
460.	129.	331.	0.	93.	56.	0.	2.	1.	643.60
0.04	1.39	5.87	0.0	0.120	0.035	0.100	0.035	641.20	306.28
0.003889	300.	300.	300.	2	0	0	0.0	49.73	356.00

FLOW DISTRIBUTION FOR SECNO= 660.00 CWSEL= 646.74

STA=	306.	343.	356.
PER Q=	28.0	72.0	
AREA=	93.0	56.4	
VEL=	1.4	5.9	

*SECNO 960.000
2800 NAT Q1= 118.70 WSEL= 647.55 ENC Q1= 118.70 WSEL= 647.65 RATIO= 0.0
NAT Q1= 126. RATIOS LOB,CH,ROB= 0.4143 0.4408 0.1449 WSEL= 647.65

3470 ENCROACHMENT STATIONS= 247.6 341.6 TYPE= 4 TARGET= 0.054

VALLEY SECTION X

960.00	5.09	647.69	0.0	647.55	647.63	0.14	0.67	0.02	643.80
460.	189.	214.	57.	198.	69.	52.	3.	1.	643.80
0.07	0.96	4.33	1.10	0.120	0.035	0.100	0.035	642.60	247.56
0.001452	300.	300.	300.	2	0	0	0.0	94.04	341.60

FLOW DISTRIBUTION FOR SECNO= 960.00 CWSEL= 647.69

STA=	246.	314.	325.	342.
PER Q=	41.2	46.5	12.4	
AREA=	197.9	49.3	51.6	
VEL=	1.0	4.3	1.1	

*SECNO 1250.000

3301 EV CHANGED MORE THAN EVTOL

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TW#	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IOC	ICONT	CORAR	TOPWID	ENDST

3685 20 TRIALS ATTEMPTED WSEL,CWSEL
3693 PROBABLE MINIMUM SPECIFIC ENERGY
3720 CRITICAL DEPTH ASSUMED

3470 ENCROACHMENT STATIONS= 170.0 343.0 TYPE= 1 TARGET= 173.000

SECNO 1250 150' U/S OF CONFLUENCE WITH WESTERLY TRIB. FROM FIELD BOOK

1250.00	4.86	648.86	648.86	648.87	649.54	0.69	0.75	0.16	644.50
460.	88.	327.	44.	98.	42.	31.	5.	2.	644.40
0.08	0.90	7.85	1.43	0.120	0.040	0.100	0.036	644.00	170.00
0.005826	290.	290.	290.	20	11	0	0.0	172.46	342.46

FLOW DISTRIBUTION FOR SECNO= 1250.00 CWSEL= 648.86

STA=	170.	279.	286.	295.	303.	342.
PER Q=	13.7	5.5	71.2	8.5	1.2	
AREA=	81.3	16.5	41.7	20.1	11.1	
VEL=	0.0	1.5	7.9	1.9	0.5	

*SECNO 2360.000
2800 NAT Q1= 105.5 WSEL= 652.6 ENC Q1= 105.5 WSEL= 652.76 RATIO= 0.0

[illegible] RATIOS L OB,CH,ROB= 0.1 16 1.132 0.1 30 WSEL= 652.72

3470 ENCROACHMENT STATIONS= 220.9 295.0 TYPE= 4 TARGET= 0.048

SECNO 2360 X

2360.00	5.22	652.72	0.0	652.66	653.06	0.33	3.48	0.04	648.00
460.	75.	325.	59.	88.	60.	44.	10.	5.	648.00
0.16	0.86	5.45	1.33	0.120	0.035	0.100	0.036	647.50	220.86
0.001951	1110.	1110.	1110.	3	0	0	0.0	74.13	294.99

FLOW DISTRIBUTION FOR SECNO= 2360.00 CWSEL= 652.72

STA=	221.	260.	270.	282.	295.
PER Q=	8.2	8.1	70.8	12.9	
AREA=	55.7	32.2	59.7	44.5	
VEL=	0.7	1.2	5.5	1.3	

CCHV= 0.300 CEHV= 0.500

*SECNO 2915.000

2800 NAT QI= 71.79 WSEL= 654.13 ENC QI= 75.82 WSEL= 654.23 RATIO= -0.0561

NAT QI= 76. RATIOS LOB,CH,ROB= 0.0 1.0000 0.0 WSEL= 654.23

3470 ENCROACHMENT STATIONS= 223.0 264.0 TYPE= 4 TARGET= 0.0

SECNO 2915 X

2915.00	4.90	654.20	0.0	654.13	654.54	0.34	1.48	0.00	654.30
460.	0.	460.	0.	0.	98.	0.	11.	6.	656.30
0.19	0.0	4.69	0.0	0.080	0.035	0.100	0.035	649.30	223.50
0.003851	555.	555.	555.	2	0	0	0.0	40.10	263.61

FLOW DISTRIBUTION FOR SECNO= 2915.00 CWSEL= 654.20

STA=	224.	264.
PER Q=	100.0	
AREA=	98.1	
VEL=	6.7	

*SECNO 3470.000

2800 NAT QI= 75.25 WSEL= 656.29 ENC QI= 78.81 WSEL= 656.39 RATIO= -0.0474

NAT QI= 79. RATIOS LOB,CH,ROB= 0.0 1.0000 0.0 WSEL= 656.39

3470 ENCROACHMENT STATIONS= 191.0 230.0 TYPE= 4 TARGET= 0.0

SECNO 3470 STA 56+05 FROM FIELD BOOK

3470.00	5.18	656.28	0.0	656.29	656.63	0.40	2.12	0.03	657.70
460.	0.	460.	0.	0.	91.	0.	13.	6.	657.60
0.22	0.0	5.07	0.0	0.030	0.035	0.100	0.035	651.10	195.98
0.003774	555.	555.	555.	1	0	0	0.0	31.55	227.53

FLOW DISTRIBUTION FOR SECNO= 3470.00 CWSEL= 656.28

STA=	196.	230.
PER Q=	100.0	
AREA=	90.7	
VEL=	5.1	

*SECNO 3051.000

2800 NAT QI= 55.38 WSEL= 658.10 ENC QI= 58.58 WSEL= 650.20 RATIO= -0.0578

NAT QI= 59. RATIOS LOB,CH,ROB= 0.0 1.0000 0.0 WSEL= 658.20

3470 ENCROACHMENT STATIONS= 153.0 195.0 TYPE= 4 TARGET= 0.0

SECNO 3853 X

3853.00	4.70	658.10	0.0	658.10	658.67	0.57	1.90	0.08	659.70
460.	0.	460.	0.	0.	76.	0.	13.	7.	659.30
0.24	0.0	6.05	0.0	0.080	0.035	0.100	0.035	653.40	158.82
0.006852	383.	383.	383.	2	0	0	0.0	32.33	191.15

FLOW DISTRIBUTION FOR SECNO= 3853.00 CWSEL= 658.10

STA= 159. 195.
PER Q= 100.0
AREA= 76.0
VEL= 6.0

CCHV= 0.100 CEHV= 0.300
*SECNO 4235.000
2800 NAT Q1= 97.67 WSEL= 659.81 ENC Q1= 102.86 WSEL= 659.91 RATIO= -0.0553
NAT Q1= 103. RATIOS LOB,CH,ROB= 0.0 1.0000 0.0000 WSEL= 659.91

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	QLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	MTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IOC	ICONT	CORAR	TOPWID	ENDST

3470 ENCROACHMENT STATIONS= 115.0 165.0 TYPE= 4 TARGET= 0.000

SECNO 4235 STA 48+40 FROM FIELD BOOK AND QUAD MAP

4235.00	4.20	659.80	0.0	659.81	660.08	0.25	1.38	0.03	661.60
460.	0.	460.	0.	0.	109.	0.	15.	7.	660.00
0.26	0.0	4.21	0.0	0.060	0.030	0.060	0.035	655.60	119.94
0.002222	267.	382.	517.	1	0	0	0.0	43.97	163.91

FLOW DISTRIBUTION FOR SECNO= 4235.00 CWSEL= 659.80

STA= 120. 165.
PER Q= 100.0
AREA= 109.2
VEL= 4.2

*SECNO 4563.000
2600 NAT Q1= 86.44 WSEL= 660.48 ENC Q1= 86.46 WSEL= 660.58 RATIO= 0.0000
NAT Q1= 88. RATIOS LOB,CH,ROB= 0.0616 0.8772 0.0616 WSEL= 660.58

3470 ENCROACHMENT STATIONS= 1219.0 1241.0 TYPE= 4 TARGET= 0.045

SECNO 4588 50' D/S 6 MILE BRIDGE BASED ON FIELD BOOK AND QUAD MAP

4588.00	3.86	660.46	0.0	660.48	661.16	0.70	0.95	0.13	656.70
460.	17.	425.	18.	9.	61.	9.	15.	7.	656.70
0.26	1.96	6.98	1.96	0.060	0.030	0.060	0.034	656.60	1219.04
0.003339	353.	353.	353.	2	0	0	0.0	21.92	1240.96

FLOW DISTRIBUTION FOR SECNO= 4588.00 CWSEL= 660.46

STA= 1219. 1222. 1238. 1241.
PER Q= 3.8 92.4 3.8
AREA= 8.9 60.9 8.9
VEL= 2.0 7.0 2.0

CCHV= 0.300 CEHV= 0.500
*SECNO 4638.000

3470 ENCROACHMENT STATIONS= 1.0 1629.0 TYPE= 1 TARGET= 1628.000

3695 OVERBANK AREA ASSUMED NON-EFFECTIVE.ELLEA= 666.40 ELREA= 666.40

SECNO 4638 D/S FACE 6 MILE BRIDGE FROM FIELD BOOK AND QUAD MAP

4638.00	3.97	660.57	0.0	660.53	661.40	0.84	0.18	0.07	656.70
460.	0.	460.	0.	0.	63.	0.	15.	7.	656.70
0.28	0.0	7.34	0.0	0.060	0.030	0.060	0.034	656.60	1222.00
0.003830	50.	50.	50.	2	0	0	0.0	16.00	1238.00

FLOW DISTRIBUTION FOR SECNO= 4638.00 CHSEL= 660.57

STA= 1222. 1238.
PER Q= 100.0
AREA= 62.7
VEL= 7.3

SPECIAL BRIDGE

SM	XK	XKOR	COFQ	ROLEN	BWC	BWP	BAREA	SS	ELCHU	ELCHD
	0.0	2.03	3.00	0.0	16.00	0.0	86.40	0.0	657.80	656.60

*SECNO 4754.000

6070.LOW FLOW BY NORMAL BRIDGE

EGPRS= 0.0 EGLWC= 662.604 ELLC= 663.200 PCMSE= 660.508 ELTRD= 669.700

3370 NORMAL BRIDGE.NRD= 10 MIN ELTRD= 669.70 MAX ELLC= 663.20

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 669.70 ELREA= 669.70

SECNO 4754 U/S FACE 6 MILE BRIDGE FROM FIELD BOOK AND QUAD MAP

4754.00	3.20	661.00	0.0	660.97	662.30	1.30	0.66	0.23	657.90
460.	0.	460.	0.	0.	50.	0.	15.	7.	657.90
0.28	0.0	9.17	0.0	0.060	0.030	0.060	0.034	657.80	1222.00
0.009381	116.	116.	116.	3	0	0	-9.82	16.00	1238.00

FLOW DISTRIBUTION FOR SECNO= 4754.00 CHSEL= 661.00

STA= 1222. 1238.
PER Q= 100.0
AREA= 50.2
VEL= 9.2

CCHV= 0.300 CEHV= 0.500
*SECNO 4804.000

3301 HV CHANGED MORE THAN HVINS

3470 ENCROACHMENT STATIONS= 1198.0 1259.0 TYPE= 1 TARGET= 63.000

SECNO 4804 50' U/S 5 MILE BRIDGE BASED ON FIELD BOOK AND QUAD MAP

[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	0.35	0.18	0.29	661.00
460.	9.	443.	8.	14.	91.	12.	15.	7.	661.00
0.29	0.64	4.85	0.69	0.080	0.030	0.080	0.034	657.90	1196.64
0.001902	50.	50.	50.	4	0	0	0.0	62.35	1250.00

FORM 2913

FLOW DISTRIBUTION FOR SECNO= 4804.00 CWSEL= 662.41

STA=	1197.	1217.	1243.	1259.
PER Q=	2.0	96.3	1.7	
AREA=	14.4	91.3	11.9	
VEL=	0.6	4.9	0.7	

CCHV= 0.100 CEHV= 0.300
*SECNO 5363.000

3301 HV CHANGED MORE THAN HVINS

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	ULOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	CTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

3470 ENCROACHMENT STATIONS= 1.0 649.0 TYPE= 1 TARGET= 648.000

SECNO 5363 STA 37+12 FROM FIELD BOOK

5363.00	4.77	663.67	663.32	663.67	664.85	1.18	1.84	0.25	659.50
460.	69.	360.	31.	32.	37.	16.	17.	8.	659.00
0.31	2.17	9.78	1.96	0.100	0.035	0.100	0.034	658.90	226.43
0.006904	559.	559.	559.	6	8	0	0.0	38.89	265.32

FLOW DISTRIBUTION FOR SECNO= 5363.00 CWSEL= 663.67

STA=	226.	235.	240.	246.	254.	257.	259.	263.
PER Q=	0.6	3.0	11.4	78.3	5.5	0.9	0.4	
AREA=	3.8	8.1	19.7	36.0	10.4	3.1	2.5	
VEL=	0.7	1.7	2.7	9.8	2.4	1.4	0.7	

*SECNO 5735.000

3301 HV CHANGED MORE THAN HVINS

3470 ENCROACHMENT STATIONS= 507.0 544.0 TYPE= 1 TARGET= 37.000

SECNO 5735. X

5735.00	5.42	665.82	0.0	665.82	666.42	0.60	1.51	0.06	661.00
460.	59.	384.	17.	38.	57.	18.	17.	8.	660.80
0.32	1.54	6.76	0.96	0.100	0.035	0.100	0.034	660.40	507.00
0.002848	372.	372.	75.	2	8	0	0.0	37.00	544.00

FLOW DISTRIBUTION FOR SECNO= 5735.00 CWSEL= 665.82

STA=	507.	513.	520.	531.	534.	544.
PER Q=	3.1	9.7	83.5	2.4	1.3	
AREA=	13.0	25.0	56.9	9.2	8.7	
VEL=	1.1	1.3	6.8	1.2	0.7	

*SECNO 6107.000

3470 ENCROACHMENT STATION= 775.0 81 .0 TYPE= 1 TARGET= 35.00

SECNO 6107 BASED ON FIELD BOOK AND QUAD MAP

6107.00	4.99	666.89	0.0	666.89	667.46	0.57	1.04	0.00	662.50
460.	37.	417.	7.	29.	66.	7.	18.	9.	662.50
0.34	1.27	6.34	0.95	0.100	0.035	0.100	0.034	661.90	775.00
0.002851	372.	372.	75.	2	0	0	0.0	35.00	810.00

FLOW DISTRIBUTION FOR SECNO= 6107.00 CWSEL= 666.89

STA=	775.	785.	793.	807.	810.
PER Q=	0.9	7.0	90.6	1.4	
AREA=	6.9	22.0	65.7	7.0	
VEL=	0.6	1.5	6.3	0.9	

*SECNO 6355.000

3470 ENCROACHMENT STATIONS= 1113.0 1354.0 TYPE= 1 TARGET= 241.000

SECNO 6355 STA 27+20 FROM FIELD BOOK AND QUAD MAP

6355.00	4.98	667.88	0.0	667.08	668.23	0.35	0.75	0.02	667.50
460.	3.	457.	0.	6.	96.	0.	19.	9.	670.50
0.35	0.42	4.76	0.0	0.100	0.035	0.100	0.035	662.90	1113.00
0.003175	248.	248.	248.	2	0	0	0.0	50.48	1163.48

FLOW DISTRIBUTION FOR SECNO= 6355.00 CWSEL= 667.88

STA=	1113.	1131.	1169.
PER Q=	0.6	99.4	
AREA=	6.5	96.0	
VEL=	0.4	4.8	

*SECNO 7080.000

2800 NAT Q1= 60.62 WSEL= 670.62 ENC Q1= 65.30 WSEL= 670.72 RATIO= -0.0772

NAT Q1= 66. RATIOS LOB,CH,ROB= 0.0052 0.9896 0.0052 WSEL= 670.72

3470 ENCROACHMENT STATIONS= 26.0 70.0 TYPE= 6 TARGET= 0.010

SECNO 7080 X

7080.00	2.76	670.66	0.0	670.62	670.96	0.32	2.75	0.00	660.30
410.	0.	410.	0.	0.	91.	0.	20.	10.	660.30
0.40	0.0	4.52	0.0	0.100	0.035	0.100	0.035	667.90	26.00
0.004716	725.	725.	725.	3	0	0	0.0	44.00	70.00

FLOW DISTRIBUTION FOR SECNO= 7080.00 CWSEL= 670.66

STA=	26.	70.
PER Q=	100.0	
AREA=	90.7	
VEL=	4.5	

CCHV= 0.300 CEHV= 0.500

*SECNO 7975.000

WATER EL=XS CARD= 677.100

2800 NAT Q1= 104.18 WSEL= 677.00 ENC Q1= 110.53 WSEL= 677.10 RATIO= -0.0609

NAT Q1= 113. RATIOS LOB,CH,ROB= 0.0115 0.9771 0.0115 WSEL= 677.10

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	QLOSS	GANA ELEV
0	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	HTM	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

3470 ENCROACHMENT STATIONS= 18.0 72.0 TYPE= 4 TARGET= 0.023

SECNO 7975 WEIR BASED ON SUBD. MAP

7975.00	2.10	677.10	0.0	677.00	677.30	0.20	2.22	0.03	675.00
410.	0.	410.	0.	0.	113.	0.	22.	11.	675.00
0.47	0.0	3.62	0.0	0.100	0.025	0.100	0.033	675.00	18.00
0.001527	895.	895.	895.	0	0	0	0.0	54.00	72.00

FLOW DISTRIBUTION FOR SECNO= 7975.00 CWSEL= 677.10

STA= 18. 72.
PER Q= 100.0
AREA= 113.4
VEL= 3.6

CCHV= 0.100 CEHV= 0.300
*SECNO 8352.000
2800 NAT Q1= 117.95 WSEL= 677.60 ENC Q1= 120.85 WSEL= 677.70 RATIO= -0.0246
NAT Q1= 125. RATIOS LOB,CH,ROB= 0.0165 0.9682 0.0152 WSEL= 677.70

3470 ENCROACHMENT STATIONS= 280.0 320.0 TYPE= 4 TARGET= 0.032

SECNO 8352 STA 7+23 FROM FIELD BOOK

8352.00	4.02	677.72	0.0	677.60	677.91	0.19	0.60	0.00	675.20
460.	0.	460.	0.	0.	131.	0.	26.	11.	675.20
0.50	0.0	3.52	0.0	0.100	0.035	0.100	0.034	673.70	280.00
0.001670	377.	377.	377.	2	0	0	0.0	60.00	320.00

FLOW DISTRIBUTION FOR SECNO= 8352.00 CWSEL= 677.72

STA= 280. 320.
PER Q= 100.0
AREA= 130.6
VEL= 3.5

*SECNO 9075.000
2800 NAT Q1= 37.13 WSEL= 680.84 ENC Q1= 40.84 WSEL= 680.94 RATIO= -0.1000
NAT Q1= 41. RATIOS LOB,CH,ROB= 0.0037 0.9928 0.0035 WSEL= 680.94

3301 HV CHANGED MORE THAN HVINS

SECNO	DEPTH	CWSEL	CRINS	WSELK	EG	HV	HL	QLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	HTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IOC	ICONT	CORAR	TOPWID	ENDST

3685 20 TRIALS ATTEMPTED WSEL,CWSEL
3693 PROBABLE MINIMUM SPECIFIC ENERGY
3720 CRITICAL DEPTH ASSUMED

3470 ENCROACHMENT STATIONS= 280.0 320.0 TYPE= 4 TARGET= 0.007

SECNO 9075 BASED ON FIELD BOOK

9075.00	2.34	680.04	680.84	680.84	601.65	0.01	2.80	0.19	680.00
460.	0.	460.	0.	0.	64.	0.	25.	12.	680.00
0.52	0.0	7.24	0.0	0.100	0.035	0.100	0.034	674.50	280.00
0.016730	725.	723.	723.	20	14	0	0.0	40.00	320.00

FLOW DISTRIBUTION FOR SECNO= 9075.00 CNSEL= 680.84

STA=	280.	320.
PER Q=	100.0	
AREA=	63.5	
VEL=	7.2	

HEC2 RELEASE DATED NOV 76 UPDATED AUG1977
ERROR CORR - 01.02
MODIFICATION - 50,51,52,53

NOTE- ASTERISK (*) AT LEFT OF CROSS-SECTION NUMBER INDICATES MESSAGE IN SUMMARY OF ERRORS LIST

TRIBUTARY 1 LIVONIA C.

SUMMARY PRINTOUT TABLE 110

	SECNO	CHSEL	DIFKOS	EG	TOPWID	QLOB	QCH	QROB	PERENC	STENCL	STCHL	STCHR	STENCR
*	60.000	643.37	0.87	644.73	64.90	4.20	628.44	7.36	260.00	177.00	356.00	374.00	437.00
	60.000	643.47	0.0	644.74	72.01	5.81	624.01	10.18	260.00	177.00	356.00	374.00	437.00
	360.000	645.90	0.0	646.21	105.28	87.97	351.19	20.84	0.0	0.0	350.00	365.00	0.0
	360.000	645.87	-0.02	646.23	52.42	82.27	367.85	9.88	0.05	316.28	350.00	365.00	368.70
	660.000	646.60	0.0	647.01	106.24	125.28	330.68	4.04	0.0	0.0	343.00	356.00	0.0
	660.000	646.74	0.14	647.13	49.73	128.88	331.12	0.0	0.06	306.28	343.00	356.00	356.00
	960.000	647.55	0.0	647.68	108.61	187.87	206.42	65.71	0.0	0.0	314.00	325.00	0.0
	960.000	647.69	0.14	647.83	94.04	189.39	213.69	56.92	0.05	267.56	314.00	325.00	341.60
*	1250.000	646.87	0.0	649.54	173.00	89.42	325.74	44.03	173.00	170.00	285.50	294.50	343.00
*	1250.000	646.86	-0.01	649.54	172.46	88.07	327.43	44.50	173.00	170.00	285.50	294.50	343.00
	2360.000	652.66	0.0	652.97	147.70	78.78	314.76	66.47	0.0	0.0	270.00	282.00	0.0
	2360.000	652.72	0.06	653.06	74.13	75.23	325.47	59.30	0.05	220.86	270.00	282.00	294.99
	2915.000	654.13	0.0	654.49	39.63	0.0	460.00	0.0	0.0	0.0	223.00	264.00	0.0
	2915.000	654.20	0.06	654.54	40.10	0.0	460.00	0.0	0.0	223.00	223.00	264.00	264.00
	3470.000	656.24	0.0	656.60	31.61	0.0	460.00	0.0	0.0	0.0	191.00	230.00	0.0
	3470.000	656.28	-0.00	656.68	31.55	0.0	460.00	0.0	0.0	191.00	191.08	230.00	230.00
	3853.000	658.10	0.0	658.67	32.20	0.0	460.00	0.0	0.0	0.0	153.00	195.00	0.0
	3853.000	658.10	0.01	658.67	32.33	0.0	460.00	0.0	0.0	153.00	153.00	195.00	195.00
	4235.000	659.81	0.0	660.08	43.95	0.0	460.00	0.0	0.0	0.0	115.00	165.00	0.0
	4235.000	659.80	-0.00	660.08	43.97	0.0	460.00	0.0	0.00	115.00	115.00	165.00	165.00
	4588.000	660.48	0.0	661.08	31.23	27.57	404.82	27.60	0.0	0.0	1222.00	1238.00	0.0
	4588.000	660.46	-0.02	661.16	21.92	17.40	425.01	17.51	0.05	1219.04	1222.00	1238.00	1240.96
	4638.000	660.53	0.0	661.38	16.00	0.0	460.00	0.0	0.0	0.0	1222.00	1238.00	0.0
	4638.000	660.57	0.04	661.40	16.00	0.0	460.00	0.0	1624.00	1.00	1222.00	1238.00	1629.00
	4754.000	660.97	0.0	662.30	16.00	0.0	460.00	0.0	0.0	0.0	1222.00	1238.00	0.0
	4754.000	661.00	0.02	662.30	16.00	0.0	460.00	0.0	0.0	0.0	1222.00	1238.00	0.0

	SECNO	CHSEL	DIFKMS	EG	TOPWID	ALOB	QCH	QROH	PERENC	STENCL	STCHL	STCHR	STENCR
	4804.000	662.42	0.0	662.77	62.41	9.28	442.85	7.87	63.00	1196.00	1217.00	1243.00	1259.00
	4804.000	662.41	-0.00	662.77	62.35	9.23	442.95	7.82	63.00	1196.00	1217.00	1243.00	1259.00
	5363.000	663.67	0.0	664.85	38.55	68.61	360.19	31.20	39.00	226.00	246.00	254.00	265.00
	5363.000	663.67	0.00	664.85	38.89	68.65	360.17	31.18	668.00	1.00	246.00	254.00	649.00
	5735.000	665.82	0.0	666.42	37.00	58.68	384.25	17.07	37.00	507.00	520.00	531.00	544.00
	5735.000	665.82	-0.00	666.42	37.00	56.67	384.26	17.07	37.00	507.00	520.00	531.00	544.00
	6107.000	666.89	0.0	667.46	35.00	36.65	416.73	6.62	35.00	775.00	793.00	807.00	810.00
	6107.000	666.89	-0.00	667.46	35.00	36.64	416.75	6.62	35.00	775.00	793.00	807.00	810.00
	6355.000	667.88	0.0	668.23	50.49	2.71	457.29	0.0	241.00	1113.00	1131.00	1169.00	1354.00
	6355.000	667.88	-0.00	668.23	50.48	2.71	457.29	0.0	241.00	1113.00	1131.00	1169.00	1354.00
	7080.000	670.62	0.0	670.94	51.87	1.90	406.20	1.90	0.0	0.0	26.00	70.00	0.0
	7080.000	670.66	0.04	670.98	44.00	0.0	410.00	0.0	0.01	26.00	26.00	70.00	70.00
D	7975.000	677.00	0.0	677.21	69.65	6.68	401.04	6.48	0.0	0.0	18.00	72.00	0.0
D	7975.000	677.10	0.10	677.30	54.00	0.0	410.00	0.0	0.02	18.00	18.00	72.00	72.00
	8352.000	677.60	0.0	677.79	58.04	7.18	446.20	6.62	0.0	0.0	280.00	320.00	0.0
	8352.000	677.72	0.12	677.91	40.00	0.0	460.00	0.0	0.03	280.00	280.00	320.00	320.00
D	9075.000	680.84	0.0	681.04	46.37	1.42	457.27	1.31	0.0	0.0	280.00	320.00	0.0
D	9075.000	680.84	-0.01	681.05	40.00	0.0	460.00	0.0	0.01	280.00	280.00	320.00	320.00

TRIBUTARY 1 LIVONIA C.

SUMMARY PRINTOUT TABLE 150

	SECNO	ALCH	ELTRD	ELLC	ELMIN	D	CLSEL	CRIWS	EG	10K*S	VCH	AREA	.01K
*	60.000	0.0	0.0	0.0	638.30	640.00	643.37	643.37	644.73	106.15	9.46	82.12	62.12
	60.000	0.0	0.0	0.0	638.30	640.00	643.47	643.38	644.74	95.63	9.14	89.05	65.45
	360.000	300.00	0.0	0.0	639.80	460.00	645.90	0.0	646.21	20.81	5.09	208.66	100.83
	360.000	300.00	0.0	0.0	639.80	460.00	645.87	0.0	646.23	23.39	5.38	158.24	95.11
	660.000	300.00	0.0	0.0	641.20	460.00	646.60	0.0	647.01	33.02	6.07	193.75	80.06
	660.000	300.00	0.0	0.0	641.20	460.00	646.74	0.0	647.13	38.89	5.87	149.40	73.76
	960.000	300.00	0.0	0.0	642.60	460.00	647.55	0.0	647.88	15.02	4.32	380.71	118.70
	960.000	300.00	0.0	0.0	642.60	460.00	647.69	0.0	647.83	14.52	4.33	298.90	120.73
*	1250.000	290.00	0.0	0.0	644.00	460.00	648.07	648.07	649.54	57.06	7.79	173.16	60.89
*	1250.000	290.00	0.0	0.0	644.00	460.00	648.06	648.06	649.54	58.26	7.85	170.67	60.27
	2360.000	1110.00	0.0	0.0	647.50	460.00	652.66	0.0	652.97	19.00	5.34	230.22	105.54
	2360.000	1110.00	0.0	0.0	647.50	460.00	652.72	0.0	653.06	19.51	5.45	192.11	104.13
	2915.000	555.00	0.0	0.0	649.30	460.00	654.13	0.0	654.49	41.06	4.80	95.75	71.79
	2915.000	555.00	0.0	0.0	649.30	460.00	654.20	0.0	654.54	38.51	4.69	98.07	74.12
	3470.000	555.00	0.0	0.0	651.10	460.00	656.24	0.0	656.68	37.37	5.05	91.04	75.25
	3470.000	555.00	0.0	0.0	651.10	460.00	656.26	0.0	656.68	37.74	5.07	90.71	74.86
	3853.000	383.00	0.0	0.0	653.40	460.00	658.10	0.0	658.67	69.00	6.07	75.84	55.38
	3853.000	383.00	0.0	0.0	653.40	460.00	658.10	0.0	658.67	68.52	6.05	76.00	55.57
	4235.000	382.00	0.0	0.0	655.60	460.00	659.81	0.0	660.08	22.27	4.22	109.07	97.47
	4235.000	382.00	0.0	0.0	655.60	460.00	659.80	0.0	660.07	22.22	4.21	109.17	97.60
	4588.000	353.00	0.0	0.0	656.60	460.00	660.48	0.0	661.06	29.68	6.61	90.07	84.44
	4588.000	353.00	0.0	0.0	656.60	460.00	660.46	0.0	661.16	33.35	6.90	70.78	79.60
	4638.000	50.00	0.0	0.0	656.60	460.00	660.53	0.0	661.38	39.65	7.42	62.01	73.04
	4638.000	50.00	0.0	0.0	656.60	460.00	660.57	0.0	661.40	38.30	7.34	62.69	74.33
	4754.000	116.00	669.70	663.20	657.80	460.00	660.97	0.0	662.30	95.96	9.23	49.82	46.96
	4754.000	116.00	669.70	663.20	657.80	460.00	661.00	0.0	662.30	93.81	9.17	50.18	47.49
	4804.000	50.00	0.0	0.0	657.90	460.00	662.42	0.0	662.77	18.94	4.85	117.73	105.70
	4804.000	50.00	0.0	0.0	657.90	460.00	662.41	0.0	662.77	19.02	4.85	117.49	105.48
	5363.000	559.00	0.0	0.0	658.90	460.00	663.67	663.33	664.85	69.94	9.79	34.26	55.00
	5363.000	559.00	0.0	0.0	658.90	460.00	663.67	663.32	664.85	69.44	9.76	34.30	55.04
	5735.000	372.00	0.0	0.0	660.40	460.00	665.62	0.0	666.42	28.47	6.76	112.76	86.21
	5735.000	372.00	0.0	0.0	660.40	460.00	665.62	0.0	666.42	28.48	6.76	112.75	86.20
	6107.000	372.00	0.0	0.0	661.90	460.00	666.09	0.0	667.46	28.50	6.34	101.64	86.17
	6107.000	372.00	0.0	0.0	661.90	460.00	666.89	0.0	667.46	28.51	6.34	101.61	86.16
	6355.000	248.00	0.0	0.0	662.90	460.00	667.88	0.0	668.23	31.75	4.76	102.50	81.66
	6355.000	248.00	0.0	0.0	662.90	460.00	667.88	0.0	668.23	31.75	4.76	102.49	81.66

	SECNO	XLCH	ELTRO	ELLC	ELMIN	Q	CWSEL	CRITS	EG	10K*S	VCH	AREA	.01K
	7080.000	725.00	0.0	0.0	667.90	410.00	670.62	0.0	670.94	45.75	4.58	93.91	60.62
	7080.000	725.00	0.0	0.0	667.90	410.00	670.66	0.0	670.98	47.16	4.52	90.72	59.70
*	7975.000	895.00	0.0	0.0	675.00	410.00	677.00	0.0	677.21	15.49	3.71	123.65	104.18
*	7975.000	895.00	0.0	0.0	675.00	410.00	677.10	0.0	677.30	15.27	3.62	113.41	104.93
	8352.000	377.00	0.0	0.0	673.70	460.00	677.60	0.0	677.79	15.21	3.55	167.38	117.95
	8352.000	377.00	0.0	0.0	673.70	460.00	677.72	0.0	677.91	16.78	3.52	130.63	112.30
*	9075.000	723.00	0.0	0.0	678.50	460.00	680.84	680.84	681.64	153.50	7.17	66.49	37.13
*	9075.000	723.00	0.0	0.0	678.50	460.00	680.84	680.84	681.65	167.30	7.24	63.55	35.56

TRIBUTARY J LIVONIA C.

SUMMARY PRINTOUT TABLE 150

	SECNO	Q	CWSEL	DIFWSP	DIFWSX	DIFKWS	TOPWID	XLCH
*	60.000	640.00	643.37	0.0	0.0	0.87	64.90	0.0
	60.000	640.00	643.47	0.10	0.0	0.0	72.01	0.0
	360.000	460.00	645.90	0.0	2.53	0.0	105.28	300.00
	360.000	460.00	645.87	-0.02	2.40	-0.02	52.42	300.00
	660.000	460.00	646.60	0.0	0.70	0.0	106.24	300.00
	660.000	460.00	646.74	0.14	0.87	0.14	49.73	300.00
	960.000	460.00	647.55	0.0	0.95	0.0	188.61	300.00
	960.000	460.00	647.69	0.14	0.95	0.14	94.04	300.00
*	1250.000	460.00	648.87	0.0	1.32	0.0	173.00	290.00
*	1250.000	460.00	648.86	-0.01	1.17	-0.01	172.46	290.00
	2360.000	460.00	652.66	0.0	3.79	0.0	147.70	1110.00
	2360.000	460.00	652.72	0.06	3.87	0.06	74.13	1110.00
	2915.000	460.00	654.13	0.0	1.47	0.0	39.63	555.00
	2915.000	460.00	654.20	0.06	1.47	0.06	40.10	555.00
	3470.000	460.00	656.29	0.0	2.15	0.0	31.41	555.00
	3470.000	460.00	656.28	-0.00	2.09	-0.00	31.55	555.00
	3853.000	460.00	658.10	0.0	1.81	0.0	32.28	383.00
	3853.000	460.00	658.10	0.01	1.82	0.01	32.33	383.00
	4235.000	460.00	659.81	0.0	1.71	0.0	43.95	382.00
	4235.000	460.00	659.80	-0.00	1.70	-0.00	43.97	382.00
	4588.000	460.00	660.48	0.0	0.67	0.0	31.23	353.00
	4588.000	460.00	660.46	-0.02	0.65	-0.02	21.52	353.00
	4638.000	460.00	660.53	0.0	0.04	0.0	16.00	50.00
	4638.000	460.00	660.57	0.04	0.11	0.04	16.00	50.00
	4754.000	460.00	660.97	0.0	0.45	0.0	16.00	116.00
	4754.000	460.00	661.00	0.02	0.43	0.02	16.00	116.00
	4804.000	460.00	662.42	0.0	1.45	0.0	62.41	50.00
	4804.000	460.00	662.41	-0.00	1.42	-0.00	62.35	50.00
	5363.000	460.00	663.67	0.0	1.25	0.0	30.55	559.00
	5363.000	460.00	663.67	0.00	1.26	0.00	38.09	559.00
	5735.000	460.00	665.82	0.0	2.15	0.0	37.00	372.00
	5735.000	460.00	665.82	-0.00	2.15	-0.00	37.00	372.00
	6107.000	460.00	666.89	0.0	1.07	0.0	35.00	372.00
	6107.000	460.00	666.89	-0.00	1.07	-0.00	35.00	372.00
	6355.000	460.00	667.88	0.0	0.98	0.0	50.42	248.00
	6355.000	460.00	667.88	-0.00	0.98	-0.00	50.45	248.00

	SECNO	Q	CHSEL	DIFWSP	DIFWSX	DIFWIS	TOPWID	XLCH
	7080.000	410.00	670.62	0.0	2.74	0.0	51.87	725.00
	7030.000	410.00	670.66	0.04	2.78	0.04	44.00	725.00
*	7975.000	410.00	677.00	0.0	6.38	0.0	69.65	895.00
*	7975.000	410.00	677.10	0.10	6.44	0.10	54.00	895.00
	8352.000	460.00	677.60	0.0	0.60	0.0	50.64	377.00
	8352.000	460.00	677.72	0.12	0.62	0.12	40.00	377.00
*	9075.000	460.00	680.84	0.0	3.25	0.0	46.37	723.00
*	9075.000	460.00	680.84	-0.01	3.12	-0.01	40.00	723.00

SUMMARY OF ERRORS

CAUTION SECNO= 60.000 PROFILE= 1 CRITICAL DEPTH ASSUMED

CAUTION SECNO= 1250.000 PROFILE= 1 CRITICAL DEPTH ASSUMED
CAUTION SECNO= 1250.000 PROFILE= 1 PROBABLE MINIMUM SPECIFIC ENERGY
CAUTION SECNO= 1250.000 PROFILE= 1 20 TRIALS ATTEMPTED TO BALANCE WSEL
CAUTION SECNO= 1250.000 PROFILE= 2 CRITICAL DEPTH ASSUMED
CAUTION SECNO= 1250.000 PROFILE= 2 PROBABLE MINIMUM SPECIFIC ENERGY
CAUTION SECNO= 1250.000 PROFILE= 2 20 TRIALS ATTEMPTED TO BALANCE WSEL

NOTE SECNO= 7975.000 PROFILE= 1 WSEL BASED ON X5 CARD
NOTE SECNO= 7975.000 PROFILE= 2 WSEL BASED ON X5 CARD

CAUTION SECNO= 9075.000 PROFILE= 1 CRITICAL DEPTH ASSUMED
CAUTION SECNO= 9075.000 PROFILE= 1 PROBABLE MINIMUM SPECIFIC ENERGY
CAUTION SECNO= 9075.000 PROFILE= 1 20 TRIALS ATTEMPTED TO BALANCE WSEL
CAUTION SECNO= 9075.000 PROFILE= 2 CRITICAL DEPTH ASSUMED
CAUTION SECNO= 9075.000 PROFILE= 2 PROBABLE MINIMUM SPECIFIC ENERGY
CAUTION SECNO= 9075.000 PROFILE= 2 20 TRIALS ATTEMPTED TO BALANCE WSEL

FLOODWAY DATA. TRIBUTARY 1 LIVONIA C.
PROFILE NO. 2

STATION	FLOODWAY WIDTH (FT)	FLOODWAY SECTION AREA	FLOODWAY MEAN VELOCITY	WATER SURFACE ELEVATION WITH FLOODWAY	WITHOUT FLOODWAY	DIFFERENCE
60.000	72.	89.	7.2	663.5	663.4	0.1
360.000	52.	150.	2.9	665.9	665.9	0.0
660.000	50.	149.	3.1	666.7	666.6	0.1
960.000	94.	299.	1.5	667.6	667.5	0.1
1250.000	172.	171.	2.7	668.9	668.9	0.0
2360.000	74.	192.	2.4	652.8	652.7	0.1
2915.000	40.	98.	4.7	654.2	654.1	0.1
3470.000	32.	91.	5.1	656.3	656.3	0.0
3853.000	32.	76.	6.0	658.1	658.1	0.0
4235.000	44.	109.	4.2	659.8	659.8	0.0
4588.000	22.	79.	5.8	660.5	660.5	0.0
4638.000	16.	63.	7.3	660.5	660.5	0.0
4754.000	16.	50.	9.2	661.0	661.0	0.0
4804.000	62.	117.	3.9	662.4	662.4	0.0
5363.000	39.	84.	5.5	663.7	663.7	0.0
5735.000	37.	113.	4.1	665.8	665.8	0.0
6107.000	35.	102.	4.5	666.9	666.9	0.0
6355.000	50.	102.	4.5	667.9	667.9	0.0
7080.000	44.	91.	4.5	670.6	670.6	0.0
7975.000	54.	113.	3.6	677.1	677.0	0.1
8352.000	40.	131.	3.5	677.7	677.6	0.1
9075.000	60.	64.	7.2	680.8	680.8	0.0

```
**********************************************************
  MEC2 RELEASE DATED NOV 76 UPDATED  AUG1977
  ERROR CORR -  01,02
  MODIFICATION -  50,51,52,53
**********************************************************
```

00BREAK00

1) COUNTY: Wayne

2) STUDY NAME: City of Livonia

3) WATERCOURSE: Tributary 1

4) DOCUMENT TYPE: Summary

00BREAK00

```
**********************************************************
  HEC2 RELEASE DATED NOV 76 UPDATED  AUG1977
  ERROR CORR -  01,02
  MODIFICATION -  50,51,52,53
**********************************************************
```

NOTE- ASTERISK (*) AT LEFT OF CROSS-SECTION NUMBER INDICATES MESSAGE IN SUMMARY OF ERRORS LIST

TRIBUTARY) LIVONIA C.

SUMMARY PRINTOUT TABLE 150

	SECNO	ALCH	ELTRD	ELLC	ELMIN	Q	CWSEL	CRIWS	FQ	10K*S	VCH	AREA	.01K
	60.000	0.0	0.0	0.0	638.30	310.00	642.50	0.0	643.08	60.60	6.10	50.86	39.82
*	60.000	0.0	0.0	0.0	638.30	520.00	642.57	642.57	644.12	159.03	9.97	52.15	41.24
*	60.000	0.0	0.0	0.0	638.30	640.00	643.37	643.37	644.73	106.15	9.46	62.12	62.12
*	60.000	0.0	0.0	0.0	638.30	930.00	644.50	644.50	645.61	69.06	9.12	197.29	111.91
	360.000	300.00	0.0	0.0	639.80	210.00	644.16	0.0	644.40	31.29	4.55	69.85	37.57
	360.000	300.00	0.0	0.0	639.80	370.00	645.51	0.0	645.78	19.81	4.69	169.97	83.12
	360.000	300.00	0.0	0.0	639.80	460.00	645.90	0.0	646.21	20.81	5.09	200.66	100.83
	360.000	300.00	0.0	0.0	639.80	680.00	646.53	0.0	646.95	25.44	6.14	281.55	134.81
	660.000	300.00	0.0	0.0	641.20	210.00	645.13	0.0	645.65	40.10	5.09	75.04	33.16
	660.000	300.00	0.0	0.0	641.20	370.00	646.19	0.0	646.57	33.46	5.72	153.56	63.95
	660.000	300.00	0.0	0.0	641.20	460.00	646.60	0.0	647.01	33.02	6.07	193.75	80.06
	660.000	300.00	0.0	0.0	641.20	660.00	647.36	0.0	647.84	33.24	6.82	285.33	117.94
	960.000	300.00	0.0	0.0	642.60	210.00	646.21	0.0	646.34	18.38	3.74	170.64	48.90
	960.000	300.00	0.0	0.0	642.60	370.00	647.13	0.0	647.27	15.35	4.15	306.55	92.93
	960.000	300.00	0.0	0.0	642.60	460.00	647.55	0.0	647.64	15.02	4.32	360.71	118.70
	960.000	300.00	0.0	0.0	642.60	680.00	648.35	0.0	648.43	13.72	4.61	544.67	183.61
	1250.000	290.00	0.0	0.0	644.00	210.00	646.76	646.69	647.78	150.38	8.44	32.98	17.12
*	1250.000	290.00	0.0	0.0	644.00	370.00	648.51	648.51	649.29	61.75	7.67	114.69	47.00
*	1250.000	290.00	0.0	0.0	644.00	460.00	648.87	648.87	649.54	57.06	7.79	173.16	60.09
*	1250.000	290.00	0.0	0.0	644.00	680.00	649.39	649.39	650.06	60.51	8.61	242.83	87.42
	2360.000	1110.00	0.0	0.0	647.50	210.00	651.43	0.0	651.62	14.58	3.85	98.46	55.00
	2360.000	1110.00	0.0	0.0	647.50	370.00	652.32	0.0	652.59	17.44	4.87	163.35	88.61
	2360.000	1110.00	0.0	0.0	647.50	460.00	652.66	0.0	652.97	19.00	5.34	230.22	105.54
	2360.000	1110.00	0.0	0.0	647.50	680.00	653.37	0.0	653.72	20.24	6.03	347.84	151.13
	2915.000	555.00	0.0	0.0	649.30	210.00	652.76	0.0	653.04	50.86	4.28	49.08	29.45
	2915.000	555.00	0.0	0.0	649.30	370.00	653.73	0.0	654.05	42.36	4.60	80.38	56.85
	2915.000	555.00	0.0	0.0	649.30	460.00	654.13	0.0	654.49	41.05	4.80	95.75	71.79
	2915.000	555.00	0.0	0.0	649.30	680.00	654.83	0.0	655.29	38.78	5.43	133.24	109.20
	3470.000	555.00	0.0	0.0	651.10	210.00	654.49	0.0	655.22	30.71	3.85	54.55	37.90
	3470.000	555.00	0.0	0.0	651.10	370.00	655.88	0.0	656.22	35.78	4.71	78.64	61.86
	3470.000	555.00	0.0	0.0	651.10	460.00	656.29	0.0	656.60	37.37	5.09	91.04	75.25
	3470.000	555.00	0.0	0.0	651.10	680.00	657.04	0.0	657.37	42.31	5.64	116.43	104.54

SECNO	XLCH	ELTRO	ELLC	ELMIN	Q	CWSEL	CRIWS	FB	10R*S	VCH	AREA	.01K
3353.000	383.00	0.0	0.0	653.40	210.00	656.74	0.0	657.21	89.09	5.49	38.27	22.25
3353.000	383.00	0.0	0.0	653.40	370.00	657.68	0.0	658.22	73.36	5.88	62.95	43.20
3353.000	383.00	0.0	0.0	653.40	460.00	658.10	0.0	658.67	69.00	6.07	75.84	55.38
3353.000	383.00	0.0	0.0	653.40	680.00	658.94	0.0	659.59	62.72	6.45	105.44	85.86
4235.000	382.00	0.0	0.0	655.60	210.00	658.56	0.0	658.75	22.33	3.45	60.95	44.44
4235.000	382.00	0.0	0.0	655.60	370.00	659.42	0.0	659.67	22.47	4.00	92.48	78.05
4235.000	382.00	0.0	0.0	655.60	460.00	659.81	0.0	660.08	22.27	4.22	109.07	97.47
4235.000	382.00	0.0	0.0	655.60	680.00	660.57	0.0	660.90	20.72	4.66	157.94	149.39
4588.000	353.00	0.0	0.0	656.60	210.00	659.29	0.0	659.58	23.14	4.59	55.75	43.66
4588.000	353.00	0.0	0.0	656.60	370.00	660.12	0.0	660.62	27.47	5.94	70.92	70.59
4588.000	353.00	0.0	0.0	656.60	460.00	660.40	0.0	661.00	29.68	6.61	90.07	84.44
4588.000	353.00	0.0	0.0	656.60	680.00	661.12	0.0	662.03	37.23	8.20	110.84	111.46
4638.000	50.00	0.0	0.0	656.60	210.00	659.38	0.0	659.74	25.70	4.81	43.66	41.42
4638.000	50.00	0.0	0.0	656.60	370.00	660.19	0.0	660.05	34.27	6.53	56.67	63.21
4638.000	50.00	0.0	0.0	656.60	460.00	660.53	0.0	661.38	39.66	7.42	62.01	73.04
4638.000	50.00	0.0	0.0	656.60	680.00	661.09	0.0	662.51	56.17	8.97	71.06	90.73
4754.000	116.00	669.70	663.20	657.80	210.00	659.70	0.0	660.43	104.61	7.12	29.49	20.53
4754.000	116.00	669.70	663.20	657.80	370.00	660.58	0.0	661.70	94.23	8.49	43.59	38.12
4754.000	116.00	669.70	663.20	657.80	460.00	660.97	0.0	662.30	95.96	9.23	49.82	46.96
4754.000	116.00	669.70	663.20	657.80	680.00	661.74	661.87	660.61	106.10	10.95	62.09	66.02
4804.000	50.00	0.0	0.0	657.90	210.00	660.58	0.0	660.93	42.88	4.77	44.03	32.07
4804.000	50.00	0.0	0.0	657.90	370.00	661.78	0.0	662.15	25.38	4.90	82.53	73.45
4804.000	50.00	0.0	0.0	657.90	460.00	662.42	0.0	662.77	18.94	4.85	117.73	105.70
4804.000	50.00	0.0	0.0	657.90	680.00	663.98	0.0	664.20	10.76	4.62	211.26	207.11
5363.000	559.00	0.0	0.0	658.90	210.00	662.70	0.0	663.10	30.44	6.03	54.89	34.79
5363.000	559.00	0.0	0.0	658.90	370.00	663.44	0.0	664.33	56.08	8.45	75.43	49.41
5363.000	559.00	0.0	0.0	658.90	460.00	663.67	663.33	664.85	69.84	9.79	84.26	55.00
5363.000	559.00	0.0	0.0	658.90	680.00	664.46	664.46	666.01	79.33	11.58	120.26	76.35
5735.000	372.00	0.0	0.0	660.40	210.00	664.00	0.0	664.34	30.24	5.21	55.57	38.19
5735.000	372.00	0.0	0.0	660.40	370.00	665.24	0.0	665.72	26.87	6.07	113.68	71.37
5735.000	372.00	0.0	0.0	660.40	460.00	665.82	0.0	666.42	28.47	6.76	112.76	66.21
5735.000	372.00	0.0	0.0	660.40	680.00	666.91	0.0	667.37	20.50	8.53	287.00	150.19
6107.000	372.00	0.0	0.0	661.90	210.00	665.16	0.0	665.51	30.66	4.03	92.54	37.93
6107.000	372.00	0.0	0.0	661.90	370.00	666.27	0.0	666.79	31.08	6.02	60.48	66.36
6107.000	372.00	0.0	0.0	661.90	460.00	666.89	0.0	667.46	28.50	6.34	101.64	66.17
6107.000	372.00	0.0	0.0	661.90	680.00	667.60	0.0	668.47	36.91	7.93	126.55	111.93
6355.000	248.00	0.0	0.0	662.90	210.00	666.15	0.0	666.47	50.42	4.55	46.16	29.57
6355.000	248.00	0.0	0.0	662.90	370.00	667.31	0.0	667.66	38.09	4.73	78.14	59.95
6355.000	248.00	0.0	0.0	662.90	460.00	667.80	0.0	668.23	31.75	4.76	102.50	61.64
6355.000	248.00	0.0	0.0	662.90	680.00	668.89	0.0	669.28	26.02	5.05	155.05	133.30
7080.000	725.00	0.0	0.0	667.90	175.00	669.62	0.0	669.99	45.90	3.27	54.22	25.83
7080.000	725.00	0.0	0.0	667.90	315.00	670.35	0.0	670.60	43.54	4.06	80.31	47.74
7080.000	725.00	0.0	0.0	667.90	410.00	670.62	0.0	670.94	46.76	4.58	93.91	60.62
7080.000	725.00	0.0	0.0	667.90	610.00	671.21	0.0	671.63	42.32	5.23	125.69	93.77

	SECNO	XLCH	ELTRO	ELLC	ELMIN	Q	CNSEL	CRIWS	FG	10K*S	VCH	AREA	.01K
o	7975.000	895.00	0.0	0.0	675.00	175.00	676.15	0.0	676.27	18.19	2.78	67.27	41.03
o	7975.000	895.00	0.0	0.0	675.00	315.00	676.70	0.0	676.87	15.82	3.37	103.11	79.20
o	7975.000	895.00	0.0	0.0	675.00	410.00	677.00	0.0	677.21	15.49	3.71	123.65	104.18
o	7975.000	895.00	0.0	0.0	675.00	610.00	677.65	0.0	677.91	13.23	4.14	170.57	167.70
	8352.000	377.00	0.0	0.0	673.70	210.00	676.68	0.0	676.76	10.24	2.32	97.56	65.61
	8352.000	377.00	0.0	0.0	673.70	370.00	677.28	0.0	677.44	14.23	3.19	129.19	98.09
	8352.000	377.00	0.0	0.0	673.70	460.00	677.60	0.0	677.79	15.21	3.55	147.38	117.95
	8352.000	377.00	0.0	0.0	673.70	680.00	678.22	0.0	678.50	17.96	4.34	184.40	160.48
o	9075.000	723.00	0.0	0.0	678.50	210.00	680.20	680.20	680.67	181.34	5.52	38.20	15.59
o	9075.000	723.00	0.0	0.0	678.50	370.00	680.63	680.63	681.32	162.33	6.69	56.62	29.04
o	9075.000	723.00	0.0	0.0	678.50	460.00	680.84	680.84	681.64	153.50	7.17	66.49	37.13
o	9075.000	723.00	0.0	0.0	678.50	680.00	681.32	681.32	682.33	130.52	8.10	89.43	57.70

TRIBUTARY 1 LIVONIA C.

SUMMARY PRINTOUT TABLE 150

	SECNO	Q	CWSEL	DIFWSP	DIFWSX	DIFKWS	TOPWID	XLOM
	60.000	310.00	642.50	0.0	0.0	0.0	17.56	0.0
o	60.000	520.00	642.57	0.07	0.0	0.07	17.72	0.0
o	60.000	640.00	643.37	0.79	0.0	0.87	64.90	0.0
o	60.000	930.00	644.50	1.13	0.0	2.00	126.91	0.0
	360.000	210.00	644.16	0.0	1.66	0.0	54.66	300.00
	360.000	370.00	645.51	1.35	2.93	0.0	93.95	300.00
	360.000	460.00	645.90	0.39	2.53	0.0	105.26	300.00
	360.000	680.00	646.53	0.64	2.03	0.0	123.64	300.00
	660.000	210.00	645.18	0.0	1.02	0.0	62.28	300.00
	660.000	370.00	646.19	1.01	0.68	0.0	93.69	300.00
	660.000	460.00	646.60	0.41	0.70	0.0	106.24	300.00
	660.000	680.00	647.36	0.76	0.83	0.0	130.39	300.00
	960.000	210.00	646.21	0.0	1.03	0.0	125.16	300.00
	960.000	370.00	647.13	0.92	0.95	0.0	168.95	300.00
	960.000	460.00	647.55	0.41	0.95	0.0	180.61	300.00
	960.000	680.00	648.35	0.80	0.98	0.0	216.33	300.00
	1250.000	210.00	648.76	0.0	0.65	0.0	17.79	290.00
o	1250.000	370.00	648.51	1.75	1.37	0.0	147.36	290.00
o	1250.000	460.00	648.87	0.36	1.32	0.0	173.00	290.00
o	1250.000	680.00	649.39	0.52	1.04	0.0	173.00	290.00
	2360.000	210.00	651.43	0.0	4.68	0.0	65.49	1110.00
	2360.000	370.00	652.32	0.89	3.81	0.0	124.82	1110.00
	2360.000	460.00	652.66	0.34	3.79	0.0	147.70	1110.00
	2360.000	680.00	653.37	0.71	3.98	0.0	171.88	1110.00
	2915.000	210.00	652.76	0.0	1.32	0.0	28.37	555.00
	2915.000	370.00	653.73	0.97	1.41	0.0	36.31	555.00
	2915.000	460.00	654.13	0.41	1.47	0.0	39.63	555.00
	2915.000	680.00	654.83	0.70	1.46	0.0	74.21	555.00
	3470.000	210.00	654.99	0.0	2.23	0.0	24.66	555.00
	3470.000	370.00	655.88	0.89	2.15	0.0	29.43	555.00
	3470.000	460.00	656.29	0.41	2.15	0.0	31.61	555.00
	3470.000	680.00	657.04	0.76	2.21	0.0	35.69	555.00
	3853.000	210.00	656.74	0.0	1.75	0.0	22.93	383.00
	3853.000	370.00	657.68	0.94	1.60	0.0	29.41	383.00
	3853.000	460.00	658.10	0.42	1.81	0.0	32.28	383.00
	3853.000	680.00	658.94	0.84	1.90	0.0	41.04	383.00
	4235.000	210.00	658.56	0.0	1.63	0.0	33.41	382.00
	4235.000	370.00	659.42	0.86	1.74	0.0	40.62	382.00
	4235.000	460.00	659.81	0.39	1.71	0.0	43.85	382.00
	4235.000	680.00	660.57	0.76	1.63	0.0	73.84	382.00
	4588.000	210.00	659.29	0.0	0.72	0.0	26.43	353.00
	4588.000	370.00	660.12	0.83	0.70	0.0	29.76	353.00
	4588.000	460.00	660.48	0.36	0.67	0.0	31.23	353.00
	4588.000	680.00	661.12	0.64	0.64	0.0	33.80	353.00

	SECNO	θ	CWSEL	DIFWSP	DIFWSX	DIFWS	TOPWID	XLCH
	4630.000	210.00	659.33	0.0	0.09	0.0	16.00	50.00
	4630.000	370.00	660.19	0.81	0.07	0.0	16.00	50.00
	4638.000	460.00	660.53	0.33	0.04	0.0	16.00	50.00
	4638.000	680.00	661.09	0.56	-0.03	0.0	16.00	50.00
	4754.000	210.00	659.70	0.0	0.32	0.0	16.00	116.00
	4754.000	370.00	660.58	0.88	0.39	0.0	16.00	116.00
	4754.000	460.00	660.97	0.39	0.45	0.0	16.00	116.00
	4754.000	680.00	661.74	0.77	0.65	0.0	16.00	116.00
	4804.000	210.00	660.58	0.0	0.88	0.0	23.75	50.00
	4804.000	370.00	661.78	1.20	1.19	0.0	46.37	50.00
	4804.000	460.00	662.42	0.64	1.45	0.0	62.41	50.00
	4804.000	680.00	663.90	1.49	2.16	0.0	63.00	50.00
	5363.000	210.00	662.70	0.0	2.12	0.0	23.44	559.00
	5363.000	370.00	663.44	0.74	1.66	0.0	34.55	559.00
	5363.000	460.00	663.67	0.24	1.25	0.97	38.55	559.00
o	5363.000	680.00	664.46	0.79	0.66	0.0	52.89	559.00
	5735.000	210.00	664.00	0.0	1.30	0.0	30.80	372.00
	5735.000	370.00	665.24	1.25	1.81	0.0	68.24	372.00
	5735.000	460.00	665.82	0.58	2.15	1.83	37.00	372.00
	5735.000	680.00	666.93	1.11	2.47	0.0	159.12	372.00
	6107.000	210.00	665.16	0.0	1.17	0.0	22.38	372.00
	6107.000	370.00	666.27	1.11	1.03	0.0	30.61	372.00
	6107.000	460.00	666.89	0.62	1.07	1.73	35.00	372.00
	6107.000	680.00	667.60	0.70	0.67	0.0	35.00	372.00
	6355.000	210.00	666.15	0.0	0.99	0.0	23.77	248.00
	6355.000	370.00	667.31	1.16	1.04	0.0	30.62	248.00
	6355.000	460.00	667.88	0.57	0.96	1.73	50.49	248.00
	6355.000	680.00	668.89	1.01	1.29	0.0	52.63	248.00
	7080.000	175.00	669.82	0.0	3.67	0.0	47.07	725.00
	7080.000	315.00	670.35	0.53	3.04	0.0	50.20	725.00
	7080.000	410.00	670.62	0.27	2.74	0.80	51.87	725.00
	7080.000	610.00	671.21	0.59	2.32	0.0	55.41	725.00
*	7975.000	175.00	676.15	0.0	6.33	0.0	63.00	895.00
*	7975.000	315.00	676.70	0.55	6.35	0.0	67.30	895.00
*	7975.000	410.00	677.00	0.30	6.38	0.85	69.65	895.00
*	7975.000	610.00	677.65	0.65	6.44	0.0	74.74	895.00
	8352.000	210.00	676.68	0.0	0.53	0.0	51.17	377.00
	8352.000	370.00	677.28	0.60	0.58	0.0	55.63	377.00
	8352.000	460.00	677.60	0.32	0.60	0.92	58.04	377.00
	8352.000	680.00	678.22	0.62	0.57	0.0	62.66	377.00
*	9075.000	210.00	680.20	0.0	3.52	0.0	41.52	723.00
*	9075.000	370.00	680.63	0.43	3.35	0.0	44.73	723.00
*	9075.000	460.00	680.84	0.22	3.25	0.64	46.37	723.00
*	9075.000	680.00	681.32	0.48	3.10	0.0	49.95	723.00

SUMMARY OF ERRORS

```
CAUTION   SECNO=    60.000   PROFILE= 2  CRITICAL DEPTH ASSUMED
CAUTION   SECNO=    60.000   PROFILE= 3  CRITICAL DEPTH ASSUMED
CAUTION   SECNO=    60.000   PROFILE= 4  CRITICAL DEPTH ASSUMED

CAUTION   SECNO=  1250.000   PROFILE= 2  CRITICAL DEPTH ASSUMED
CAUTION   SECNO=  1250.000   PROFILE= 2  PROBABLE MINIMUM SPECIFIC ENERGY
CAUTION   SECNO=  1250.000   PROFILE= 2  20 TRIALS ATTEMPTED TO BALANCE WSEL
CAUTION   SECNO=  1250.000   PROFILE= 3  CRITICAL DEPTH ASSUMED
CAUTION   SECNO=  1250.000   PROFILE= 3  PROBABLE MINIMUM SPECIFIC ENERGY
CAUTION   SECNO=  1250.000   PROFILE= 3  20 TRIALS ATTEMPTED TO BALANCE WSEL
CAUTION   SECNO=  1250.000   PROFILE= 4  CRITICAL DEPTH ASSUMED
CAUTION   SECNO=  1250.000   PROFILE= 4  PROBABLE MINIMUM SPECIFIC ENERGY
CAUTION   SECNO=  1250.000   PROFILE= 4  20 TRIALS ATTEMPTED TO BALANCE WSEL

CAUTION   SECNO=  5363.000   PROFILE= 4  CRITICAL DEPTH ASSUMED
CAUTION   SECNO=  5363.000   PROFILE= 4  MINIMUM SPECIFIC ENERGY

NOTE      SECNO=  7975.000   PROFILE= 1  WSEL BASED ON XS CARD
NOTE      SECNO=  7975.000   PROFILE= 2  WSEL BASED ON XS CARD
NOTE      SECNO=  7975.000   PROFILE= 3  WSEL BASED ON XS CARD
NOTE      SECNO=  7975.000   PROFILE= 4  WSEL BASED ON XP CARD

CAUTION   SECNO=  9075.000   PROFILE= 1  CRITICAL DEPTH ASSUMED
CAUTION   SECNO=  9075.000   PROFILE= 1  PROBABLE MINIMUM SPECIFIC ENERGY
CAUTION   SECNO=  9075.000   PROFILE= 1  20 TRIALS ATTEMPTED TO BALANCE WSEL
CAUTION   SECNO=  9075.000   PROFILE= 2  CRITICAL DEPTH ASSUMED
CAUTION   SECNO=  9075.000   PROFILE= 2  PROBABLE MINIMUM SPECIFIC ENERGY
CAUTION   SECNO=  9075.000   PROFILE= 2  20 TRIALS ATTEMPTED TO BALANCE WSEL
CAUTION   SECNO=  9075.000   PROFILE= 3  CRITICAL DEPTH ASSUMED
CAUTION   SECNO=  9075.000   PROFILE= 3  PROBABLE MINIMUM SPECIFIC ENERGY
CAUTION   SECNO=  9075.000   PROFILE= 3  20 TRIALS ATTEMPTED TO BALANCE WSEL
CAUTION   SECNO=  9075.000   PROFILE= 4  CRITICAL DEPTH ASSUMED
CAUTION   SECNO=  9075.000   PROFILE= 4  PROBABLE MINIMUM SPECIFIC ENERGY
CAUTION   SECNO=  9075.000   PROFILE= 4  20 TRIALS ATTEMPTED TO BALANCE WSEL
```

FLOOD INSURANCE ZONE DATA FOR TRIBUTARY 1 LIVONIA C.

FLOOD HAZARD FACTOR FOR ENTIRE REACH USING SECTIONS

SECTION NUMBER	CUMULATIVE DISTANCE	ELEVATION DIFFERENCE BETWEEN BASE FLOOD AND 10	2	0.2
60.000	0.	-0.87	-0.79	1.13
360.000	300.	-1.74	-0.39	0.64
660.000	600.	-1.42	-0.41	0.76
960.000	900.	-1.34	-0.41	0.80
1250.000	1190.	-2.11	-0.36	0.52
2360.000	2300.	-1.23	-0.34	0.71
2915.000	2855.	-1.37	-0.41	0.70
3470.000	3410.	-1.30	-0.41	0.76
3853.000	3793.	-1.36	-0.42	0.85
4235.000	4175.	-1.24	-0.39	0.76
4588.000	4528.	-1.19	-0.36	0.64
4638.000	4578.	-1.15	-0.33	0.56
4754.000	4694.	-1.28	-0.39	0.77
4804.000	4744.	-1.84	-0.64	1.49
5363.000	5303.	-0.97	-0.24	0.79
5735.000	5675.	-1.83	-0.58	1.11
6107.000	6047.	-1.73	-0.62	0.70
6355.000	6295.	-1.73	-0.57	1.01
7080.000	7020.	-0.80	-0.27	0.59
7975.000	7915.	-0.85	-0.30	0.65
8352.000	8292.	-0.92	-0.32	0.62
9075.000	9015.	-0.64	-0.22	0.40
WEIGHTED AVG FOR REACH		-1.30	-0.39	0.74

FHF FOR THE REACH = 015 WITH 92.0 OF THE REACH WITHIN 0.5 FEET
ZONE FOR THE REACH = A 3

```
**********************************************************
  HEC2 RELEASE DATED NOV 76 UPDATED  AUG1977
  ERROR CORR -  01,02
  MODIFICATION -  50,51,52,53
**********************************************************
```




1) COUNTY: Wayne

2) STUDY NAME: City of Livonia

3) WATERCOURSE: Upper Rouge

4) DOCUMENT TYPE: 100 Year



```
HEC2 RELEASE DATED NOV 76 UPDATED AUG1977
ERROR CORR - 01,02
MODIFICATION - 50,51,52,53
C
T1 CITY OF LIVONIA FIS RUN 2014-07 UPPER ROUGE RIVER
T2 100 YR FLOW
T3       UPPER ROUGE LIVONIA CITY
J1  ICHECK     INQ       NINV      IDIR      STRT      METRIC    HVINS     Q         WSEL      FQ
          0.        4.        0.        0.  0.0           0.0       0.0       0.   624.690     0.0
J2  NPROF      IPLOT     PRFVS     XSECV     XSECH     FN        ALLOC     IBW       CHNIM     ITRACE
      1.000     1.000    -1.000     0.0       0.0       0.0       0.0       0.0       0.0       0.0
J3  VARIABLE CODES FOR SUMMARY PRINTOUT
    110.000   150.000   200.000     0.0       0.0       0.0       0.0       0.0       0.0       0.0
ET        0.0       0.0       0.0       0.0       0.100     0.0       0.0       0.0     224.000   315.000
OT        6.000  1160.000  2160.000  2690.000  2690.000  4200.000  1730.000     0.0       0.0       0.0
NC        0.100     0.100     0.040     0.300     0.500     0.0       0.0       0.0       0.0       0.0

       D/S INKSTER ROAD.
X1  22663.000    11.000   259.100   284.500     0.0       0.0       0.0       0.0       0.0       0.0
GR    630.000   228.000   631.300   224.000   631.200   235.000   621.900   [illegible]  621.400   [illegible]
GR    620.200   272.000   622.100   284.400   622.100   264.500   631.200   305.000   631.400   315.000
GR    650.000   316.000     0.0       0.0       0.0       0.0       0.0       0.0       0.0       0.0
NC      0.120     0.120     0.035     0.0       0.0       0.0       0.0       0.0       0.0       0.0
ET        0.0       5.100     5.100     0.0       0.0       0.0       0.0       0.0   259.100   264.500

       D/S FACE INKSTER RD. SKEW
X1  22696.000     0.0       0.0       0.0      30.000    30.000    30.000     0.0       0.0       0.0
SC        0.0     1.720     3.000     0.0      25.400     0.0     177.600     0.0     625.200   620.200

       D/S FACE INKSTER RD. SKEW
X1  22735.000     0.0       0.0       0.0      40.000    40.000    40.000     0.0       0.0       0.0
X2        0.0     0.0       1.000   627.200   631.200     0.0       0.0       0.0       0.0       0.0
GT       10.000   226.000   650.000     0.0     225.000   635.000     0.0     [illegible]  631.200     0.0
GT      [illegible]  631.200   621.900   259.200   631.200   627.200   254.400   631.200   627.200   284.500
GT      631.200   622.100   308.000   631.200     0.0     315.000   635.000     0.0     316.000   650.000
ET        0.0       0.0       0.0       0.0       0.0       0.0       0.0       0.0       0.0       0.0
NC        0.120     0.120     0.040     0.300     0.500     0.0       0.0       0.0       0.0       0.0
ET        0.0       0.0       0.0       0.0       1.410     0.0       0.0       0.0       0.0       0.0

       50 FT D/S INKSTER RD.
X1  22975.000    11.000   297.000   322.000    50.000    50.000    50.000     0.0       0.0       0.0
```

GR	636.000	0.0	634.000	95.000	632.000	146.000	630.000	267.000	622.000	297.000
GR	620.300	310.000	622.000	[illegible]	[illegible]	370.000	632.000	421.000	634.000	430.000
GR	636.000	533.000	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
NC	0.150	0.150	0.050	0.400	0.500	0.0	0.0	0.0	0.0	0.0

VALLEY SECTION

X1	23779.000	18.000	272.000	292.000	200.000	1100.000	700.000	0.0	0.0	0.0
GR	636.000	0.0	636.000	190.000	634.000	210.000	632.000	230.000	630.000	240.000
GR	629.800	250.000	621.900	272.000	620.400	282.000	622.200	292.000	625.700	314.000
GR	626.000	400.000	620.000	415.000	630.000	425.000	634.000	445.000	634.000	515.000
GR	636.000	545.000	638.000	655.000	640.000	710.000	0.0	0.0	0.0	0.0
NC	0.120	0.120	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

200 FT D/S 7 MILE RD.

X1	24852.000	9.000	80.000	100.000	1100.000	900.000	1077.000	0.0	0.0	0.0
GR	650.000	0.0	634.000	1.000	632.000	35.000	626.900	80.000	625.600	94.000
GR	626.700	108.000	630.000	150.000	636.000	175.000	636.000	290.000	0.0	0.0
NC	0.080	0.080	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

D/S FACE 7 MILE RD. SKEW

X1	25052.000	11.000	314.000	340.000	20.000	400.000	200.000	0.0	0.0	0.0
X3	10.000	0.0	0.0	0.0	0.0	0.0	0.0	631.600	631.400	0.0
X4	1.000	632.000	303.000	0.0	0.0	0.0	0.0	0.0	0.0	0.0
GR	650.000	225.000	634.000	227.000	632.500	228.000	626.900	314.000	626.900	314.100
GR	625.600	327.000	626.700	340.000	626.700	340.100	632.500	426.000	634.000	427.000
GR	650.000	428.000	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
SB	0.0	1.880	2.650	0.0	25.800	0.0	95.500	0.0	625.600	626.600

D/S FACE 7 MILE RD. SKEW

X1	25108.000	0.0	0.0	0.0	56.000	56.000	56.000	0.0	0.0	0.0
X2	0.0	0.0	1.000	629.300	633.700	0.0	0.0	0.0	0.0	0.0
X3	10.000	0.0	0.0	0.0	0.0	0.0	0.0	533.700	633.700	0.0
BT	10.000	226.000	650.000	0.0	227.000	634.000	0.0	226.000	634.000	0.0
BT	314.000	633.700	626.900	314.100	633.700	629.300	340.000	533.700	629.300	340.100
BT	633.700	626.700	426.000	634.000	0.0	427.000	634.000	0.0	426.000	650.000
BT	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
NC	0.120	0.120	0.050	0.300	0.500	0.0	0.0	0.0	0.0	0.0

75 FT D/S 7 MILE RD.

X1	25163.000	16.000	383.000	413.000	75.000	75.000	75.000	0.0	0.0	0.0
X3	0.0	0.0	0.0	262.000	0.0	642.000	0.0	0.0	0.0	0.0
GR	640.000	0.0	640.000	232.000	632.000	275.000	636.000	292.000	634.000	316.000
GR	632.000	374.000	630.000	383.000	626.000	391.000	625.700	400.000	626.000	413.000
GR	630.000	426.000	634.000	434.000	636.000	563.000	636.000	662.000	636.000	740.000
GR	640.000	912.000	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
NC	0.100	0.100	0.040	0.0	0.0	0.0	0.0	0.0	0.0	0.0

VALLEY SECTION

X1	25620.000	13.000	379.000	400.000	600.000	50.300	145.600	0.0	0.0	0.0
GR	640.000	0.0	640.000	360.000	630.000	375.300	627.600	379.000	625.600	383.000
GR	625.700	394.000	625.400	405.000	629.400	409.000	630.000	420.000	634.000	450.000
GR	636.000	725.000	638.000	740.000	640.000	1100.000	0.0	0.0	0.0	0.0
ET	0.0	0.0	0.0	0.0	0.0	9.100	0.0	0.0	73.000	296.000

50 FT D/S DEERING RD.

X1	25038.000	13.000	171.000	200.000	700.000	100.000	410.000	0.0	0.0	0.0
GR	640.000	0.0	638.000	45.000	636.000	75.000	634.000	130.000	630.000	145.000
GR	630.000	165.000	626.000	171.000	624.900	185.000	625.600	200.000	629.100	207.000
GR	630.000	235.000	638.000	260.000	639.700	375.000	0.0	0.0	0.0	0.0
NC	0.080	0.080	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

D/S FACE DEERING RD.

X1	26088.000	17.000	225.000	246.000	50.000	50.000	50.000	0.0	0.0	0.0
X3	10.000	0.0	0.0	0.0	0.0	0.0	0.0	633.400	633.400	0.0
GR	650.000	134.000	635.000	135.000	633.500	136.000	633.000	209.000	625.000	225.000
GR	625.000	226.500	625.000	225.500	625.000	231.500	625.000	235.500	625.000	239.500
GR	625.000	242.500	625.000	244.500	625.000	246.000	633.000	257.000	633.600	334.000
GR	635.000	335.000	650.000	336.000	0.0	0.0	0.0	0.0	0.0	0.0
SE	0.0	2.500	2.650	0.0	15.600	0.0	131.000	0.0	625.000	625.000

U/S FACE DEERING RD.

X1	26184.000	0.0	0.0	0.0	96.000	96.000	96.000	0.0	0.0	0.0
X2	0.0	0.0	1.000	633.400	634.900	0.0	0.0	0.0	0.0	0.0
X3	10.000	0.0	0.0	0.0	0.0	0.0	0.0	634.900	634.900	0.0
BT	16.000	134.000	650.000	0.0	135.000	635.000	0.0	136.000	635.000	0.0
BT	200.000	634.900	0.0	225.000	634.900	625.000	226.500	634.900	628.500	228.500
BT	634.900	631.000	231.500	634.900	632.600	235.500	634.900	633.400	239.500	634.900
BT	632.500	242.500	634.900	631.000	244.500	634.900	628.500	246.000	634.900	625.000
BT	334.000	635.000	0.0	335.000	635.000	0.0	336.000	650.000	0.0	0.0
NC	0.120	0.120	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

50 FT U/S DEERING RD.

X1	26234.000	14.000	160.000	205.000	50.000	50.000	50.000	0.0	0.0	0.0
X3	0.0	0.0	0.0	60.000	0.0	345.000	0.0	0.0	0.0	0.0
GR	640.000	0.0	638.000	80.000	636.000	100.000	634.000	110.000	632.000	120.000
GR	630.000	140.000	626.000	160.000	625.100	165.000	626.000	205.000	628.000	220.000
GR	630.000	300.000	636.000	370.000	638.000	375.000	640.000	670.000	0.0	0.0
NC	0.100	0.100	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

VALLEY SECTION

X1	26860.000	13.000	550.000	576.000	200.000	900.000	626.000	0.0	0.0	0.0
GR	642.000	0.0	640.000	275.000	630.000	345.000	626.000	480.000	629.500	550.000
GR	624.500	555.000	624.800	563.000	625.200	571.000	628.500	576.000	630.000	600.000
GR	640.000	620.000	642.000	640.000	644.000	800.000	0.0	0.0	0.0	0.0

D/S FOOTBRIDGE

X1	26232.000	10.000	70.000	110.000	1000.000	1400.000	1372.000	0.0	0.0	0.0
X3	10.000	0.0	0.0	0.0	0.0	0.0	0.0	631.900	631.900	0.0
GR	642.000	0.0	640.000	10.000	635.000	70.000	628.000	77.500	628.000	90.000
GR	629.000	102.500	635.000	110.000	635.000	265.000	640.000	400.000	644.000	650.000

FOOTBRIDGE TO SCHOOL D/S FACE

X1	23233.000	0.0	0.0	0.0	1.000	1.000	1.000	0.0	0.0	0.0
X2	0.0	0.0	0.0	633.500	635.000	0.0	0.0	0.0	0.0	0.0
X3	10.000	0.0	0.0	0.0	0.0	0.0	0.0	631.900	631.900	0.0

FOOTBRIDGE TO SCHOOL U/S FACE

X1	2824.000	0.0	0.0	0.0	7.000	7.000	7.000	0.0	0.0	0.0
X2	0.0	0.0	0.0	633.500	0.0	0.0	0.0	0.0	0.0	0.0
X3	10.000	0.0	0.0	0.0	0.0	0.0	0.0	635.000	635.000	0.0

U/S FOOTBRIDGE

X1	2824.000	0.0	0.0	0.0	1.000	1.000	1.000	0.0	0.0	0.0
X2	10.000	0.0	0.0	0.0	0.0	0.0	0.0	635.000	635.000	0.0
NC	0.150	0.150	0.050	0.100	0.200	0.0	0.0	0.0	0.0	0.0

VALLEY SECTION

X1	2556.000	20.000	57.000	86.000	350.000	500.000	319.000	0.0	0.0	0.0
GR	640.000	0.0	635.600	24.000	633.200	44.000	633.600	57.000	626.200	67.000
GR	626.200	70.000	628.600	71.000	632.700	84.000	632.700	104.000	632.500	124.000
GR	632.500	164.000	633.000	184.000	632.600	204.000	632.500	224.000	632.800	244.000
GR	633.200	264.000	634.200	284.000	635.600	304.000	633.500	324.000	636.000	344.000

VALLEY SECTION

X1	29040.000	14.000	305.000	339.000	300.000	250.000	400.000	0.0	0.0	0.0
GR	640.000	0.0	640.000	200.000	640.000	215.000	634.000	255.000	637.000	295.000
GR	630.200	305.000	628.700	312.000	627.600	322.000	626.400	332.000	631.500	339.000
GR	632.000	330.000	640.000	340.000	645.000	345.000	645.000	1020.000	0.0	0.0
NC	0.120	0.120	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

SCENO 3159O X

X1	3154.000	11.000	320.000	340.000	450.000	400.000	400.000	0.0	635.100	324.000
GR	655.000	0.0	643.000	50.000	630.000	150.000	637.500	320.000	0.0	0.0
GR	639.000	335.000	635.100	346.000	637.500	349.000	638.000	400.000	643.000	479.000
GR	655.000	550.000	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
ET	0.0	9.100	9.100	0.0	0.0	0.0	0.0	0.0	296.000	555.000
ET	0.0	0.0	0.0	4.100	9.100	0.0	0.0	0.0	170.000	500.000
ET	0.0	0.0	0.0	0.0	0.0	4.100	0.0	0.0	150.000	419.000

VALLEY SECTION

X1	3799.000	16.000	395.000	419.000	450.000	400.000	406.000	0.0	0.0	0.0
GR	650.000	0.0	645.000	637.000	120.000	632.200	1025.000	0.0	629.300	200.000
GR	629.370	210.000	632.000	220.000	635.000	640.000	900.000	650.000	650.000	801.000
NC	0.100	0.100	0.040	0.0	0.0	0.0	0.0	0.0	0.0	0.0

VALLEY SECTION

X1	3037.000	10.000	145.000	220.000	1400.000	1206.000	1335.000	0.0	0.0	0.0
GR	650.000	0.0	645.000	80.000	637.000	120.000	632.200	105.000	629.300	200.000
GR	629.370	210.000	632.000	220.000	635.000	640.000	900.000	650.000	650.000	801.000
NC	0.100	0.100	0.040	0.0	0.0	0.0	0.0	0.0	0.0	0.0

VALLEY SECTION

X1	3117.000	15.000	250.000	284.000	272.000	250.000	272.000	0.0	0.0	0.0
GR	656.000	0.0	650.000	40.000	640.000	170.000	640.000	180.000	636.000	200.000
GR	638.000	250.000	635.100	254.000	635.100	267.000	634.000	280.000	636.600	284.000
GR	638.000	470.000	640.000	475.000	646.000	510.000	642.000	515.000	650.000	725.000
TT	0.000	1150.000	2050.000	2550.000	2550.000	3900.000	1650.000	0.0	0.0	0.0
NC	0.100	0.100	0.030	0.0	0.0	0.0	0.0	0.0	0.0	0.0

SCENO 3159O X

X1	3154.000	11.000	320.000	340.000	450.000	400.000	400.000	0.0	635.100	324.000
GR	655.000	0.0	643.000	50.000	630.000	150.000	637.500	320.000	0.0	0.0
GR	639.000	335.000	635.100	346.000	637.500	349.000	638.000	400.000	643.000	479.000
GR	655.000	550.000	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
ET	0.0	9.100	9.100	0.0	0.0	0.0	0.0	0.0	296.000	555.000
ET	0.0	0.0	0.0	4.100	9.100	0.0	0.0	0.0	170.000	500.000
ET	0.0	0.0	0.0	0.0	0.0	4.100	0.0	0.0	150.000	419.000

VALLEY SECTION

X1	3199.000	16.000	395.000	419.000	450.000	400.000	406.000	0.0	0.0	0.0

GR	650.000	0.0	640.000	100.000	638.000	195.000	637.200	395.000	635.600	398.000
GR	635.100	407.000	635.500	416.000	637.600	419.000	640.000	425.000	650.000	445.000
GR	652.000	460.000	652.000	625.000	664.000	650.000	656.000	740.000	658.000	955.000
GR	660.000	1020.000	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
NC	0.080	0.080	0.030	0.0	0.0	0.0	0.0	0.0	0.0	0.0
ET	0.0	0.0	9.100	0.0	0.0	0.0	0.0	0.0	66.000	127.000
ET	0.0	0.0	0.0	0.0	9.100	0.0	0.0	0.0	1.000	359.000

70 FT D/S 8 MILE RD.

X1	32470.000	18.000	85.000	105.000	400.000	550.000	640.000	0.0	0.0	0.0
GR	651.700	0.0	651.000	5.000	650.000	12.000	642.500	32.000	642.500	40.000
GR	638.700	62.000	638.100	70.000	637.900	76.000	633.400	85.000	632.200	92.000
GR	632.300	96.000	635.000	105.000	638.000	110.000	638.500	110.000	638.900	120.000
GR	642.700	130.000	642.900	150.000	650.000	360.000	0.0	0.0	0.0	0.0
NC	0.080	0.080	0.030	0.300	0.500	0.0	0.0	0.0	0.0	0.0

D/S FACE 8 MILE RD.

X1	32540.000	21.000	600.000	627.000	70.000	70.000	70.000	0.0	0.0	0.0
X3	10.000	0.0	0.0	0.0	0.0	0.0	0.0	642.200	642.200	0.0
GR	650.000	0.0	648.900	100.000	648.200	200.000	646.900	300.000	646.900	400.000
GR	646.300	500.000	641.200	575.000	634.000	599.000	633.500	600.000	633.000	610.000
GR	633.500	620.000	633.800	627.000	634.200	630.000	637.400	646.000	642.700	660.000
GR	645.400	700.000	646.900	800.000	650.000	900.000	653.900	1000.000	653.100	1100.000
GR	651.100	1278.000	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
EJ	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

*PROF 1

CCHV= 0.300 CEHV= 0.500
*SECNO 22865.000

SECNO	DEPTH	CWSEL	CRIWS	WSELR	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TYPE	VLOB	VCH	VROB	XNL	XNCH	XNR	UTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

30' D/S INKSTER ROAD.

not the same XSEC as in COE FIS

22865.00	8.49	628.69	0.0	628.69	630.78	2.09	0.0	0.0	621.90
2890.	166.	2372.	152.	60.	193.	56.	0.	0.	622.10
0.0	2.77	12.32	2.72	0.100	0.040	0.100	0.0	620.20	241.50
0.007474	0.	0.	0.	0	0	0	0.0	60.01	301.52

*SECNO 22895.000

D/S FACE INKSTER RD. SKEW

628.77

628.71

22895.00	8.83	628.83	0.0	0.0	631.03	2.20	0.20	0.05	621.90
2590.	127.	2445.	117.	62.	196.	59.	0.	0.	622.10
0.00	2.05	12.46	2.01	0.120	0.035	0.120	0.034	620.20	241.14
0.005716	30.	30.	30.	2	0	0	0.0	60.75	301.80

SPECIAL BRIDGE

SW	XR	XRSW	CDPD	RDLEN	BRC	BRP	BAREA	SS	EL.CHS	EL.CHD
	0.0	1.72	3.00	0.0	25.40	0.0	177.60	0.0	620.20	620.20

*SECNO 22935.000

3301 HV CHANGED MORE THAN HVINS

PRESSURE AND WEIR FLOW

1715 @ 634.2

2227 @ 632.91

EGPRS	EGLWC	HV	QWEIR	QPR	BAREA	TRAPEZOID AREA	ELLC	ELTRD
634.96	631.03	0.0	505.	2195.	178.	176.	627.20	631.20

D/S FACE INKSTER RD. SKEW

22935.00	11.77	631.97	0.0	0.0	632.91	0.96	1.38	0.0	621.90
2690.	195.	2311.	184.	135.	276.	130.	1.	0.	622.10
0.00	1.44	8.37	1.42	0.120	0.035	0.120	0.034	620.20	224.96
0.001637	40.	40.	40.	3	1	2	0.0	60.07	315.03

CCHV= 0.300 CEHV= 0.500
*SECNO 22985.000

3301 HV CHANGED MORE THAN HVINS

50 FT U/S INKSTER RD.

22985.00	12.41	632.71	0.0	0.0	633.13	0.42	0.07	0.15	622.00
2690.	357.	1819.	514.	297.	289.	391.	1.	0.	622.00
0.01	1.20	6.29	1.31	0.120	0.040	0.120	0.036	620.30	227.00
0.001109	50.	50.	50.	2	0	0	0.0	176.00	403.00

CCHV= 0.400 CEHV= 0.600
*SECNO 23775.000

SECNO	DEPTH	CHSEL	CRIWS	HSELK	EG	FV	HL	QLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TOA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	ANL	ARCF	ANR	CTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

VALLEY SECTION

23775.00	13.46	633.86	0.0	0.0	634.01	0.14	0.76	0.11	621.90
2690.	354.	1134.	1202.	326.	253.	1096.	27.	4.	622.20
0.10	1.09	4.69	1.10	0.150	0.050	0.150	0.047	620.40	211.37
0.000788	200.	790.	1100.	2	0	0	0.0	232.95	444.32

*SECNO 24852.000

200 FT D/S 7 MILE RD.

24852.00	9.59	635.05	0.0	0.0	635.40	0.34	1.27	0.12	626.90
2690.	533.	1511.	646.	322.	269.	335.	56.	4.	626.70
0.16	1.66	6.06	1.93	0.120	0.050	0.120	0.030	625.50	0.93
0.002284	1100.	1077.	900.	2	0	0	0.0	170.13	171.06

*SECNO 25052.000

D/S FACE 7 MILE RD. SKEW

25052.00	10.07	635.67	0.0	0.0	635.83	0.16	0.36	0.07	626.90
2690.	502.	1100.	1088.	327.	246.	525.	51.	7.	626.70
0.18	1.53	4.47	2.07	0.080	0.050	0.080	0.049	625.80	226.70
0.001136	20.	200.	400.	2	0	0	0.0	200.21	427.10

SPECIAL BRIDGE

SW	XR	XKOR	CDFQ	RDLEN	BWC	BWP	BAREA	SS	ELCPU	ELCHD
	0.0	1.00	2.65	0.0	25.00	0.0	95.50	0.0	625.60	625.60

*SECNO 25100.000
PRESSURE AR. WEIR FLOW

EGPRS	EGLWC	WT	QWEIR	CPR	BAREA	TRAPEZOID AREA	ELLC	ELTRD
638.83	635.83	0.0	2172.	515.	96.	95.	629.30	633.70

U/S FACE 7 MILE RD. SKEW

25108.00	10.60	636.40	0.0	0.0	636.52	0.12	0.49	0.0	626.90

0.19	1.43	3.91	1.86	0.080	0.050	0.080	0.049	625.60	228.85
0.000789	56.	56.	56.	2	0	5	0.0	200.30	427.15

u/s EG = 636.52 /

HWATER M show .5 ft loss

CCRV= 0.300 CERV= 0.500
*SECNO 25183.000

3470 ENCROACHMENT STATIONS= 252.0 542.0 TYPE= 1 TARGET= 290.000

75 FT U/S 7 MILE RD.

25183.00	10.62	636.32	0.0	0.0	636.78	0.46	0.09	0.17	636.00
2590.	355.	1907.	429.	268.	297.	333.	65.	10.	626.00
0.19	1.32	6.42	1.42	0.120	0.050	0.120	0.049	625.70	289.29
0.002291	75.	75.	75.	2	0	0	0.0	252.71	542.00

*SECNO 25620.000

SECNO	DEPTH	CWSEL	CRITS	HSELK	EG	MV	KL	QLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TEA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	QTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

VALLEY SECTION

25620.00	13.30	637.00	0.0	0.0	637.32	0.32	0.50	0.06	627.60
2590.	86.	1807.	707.	70.	353.	784.	71.	11.	629.40
0.22	1.23	5.38	0.90	0.100	0.040	0.100	0.049	623.70	364.50
0.000469	600.	445.	50.	2	0	0	0.0	368.01	732.51

*SECNO 26035.000

50 FT D/S DEERING RD.

25935.00	12.47	637.37	0.0	0.0	637.62	0.25	0.27	0.02	626.00
2590.	475.	1708.	509.	429.	349.	374.	80.	13.	625.60
0.25	1.10	4.90	1.36	0.100	0.040	0.100	0.048	624.90	54.42
0.000633	700.	410.	100.	2	0	0	0.0	203.02	256.04

*SECNO 26058.000

D/S FACE DEERING RD.

26088.00	12.40	637.40	0.0	0.0	637.66	0.26	0.03	0.01	625.00
2590.	667.	1428.	595.	441.	260.	416.	71.	13.	625.00
0.25	1.51	5.46	1.43	0.090	0.040	0.080	0.046	625.00	134.84
0.000759	50.	50.	50.	1	0	0	0.0	200.32	335.16

ELTRD = 634.9

Probably better modeled as Normal Bridge

SPECIAL BRIDGE

SS	XK	XKOR	COFQ	ROLEN	BWC	SKP	BAREA	SS	ELCHO	ELCHD
	0.0	2.50	2.65	0.0	15.60	0.0	131.00	0.0	625.00	625.00

*SECNO 26184.000
PRESSURE AND WEIR FLOW

EGPRS	EGLWC	WSEL	QWEIR	QPR	BAREA	TRAPEZOID AREA	ELLC	ELTRD
653.77	637.66	0.0	2197.	490.	131.	131.	633.40	634.90

U/S FACE DEERING RD.

26184.00	12.71	637.71	0.0	0.0	637.94	0.23	0.28	0.0	625.00
2690.	686.	1369.	615.	478.	267.	443.	83.	14.	625.00
0.26	1.46	5.21	1.39	0.080	0.040	0.080	0.048	625.00	134.82
0.000662	96.	96.	96.	2	0	5	0.0	200.36	335.16

Loss may be a little high

*SECNO 26234.000

3470 ENCROACHMENT STATIONS= 60.0 345.0 TYPE= 1 TARGET= 285.000

50 FT U/S DEERING RD.

26234.00	12.83	637.93	0.0	0.0	638.00	0.08	0.02	0.05	626.00
2690.	286.	1574.	830.	434.	557.	1148.	85.	14.	625.00
0.27	0.66	2.83	0.72	0.120	0.040	0.120	0.048	625.10	80.73
0.000282	50.	50.	50.	2	0	0	0.0	264.27	345.00

*SECNO 26860.000

SECNO	DEPTH	CNSEL	CRIWS	WSELR	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNH	HTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

VALLEY SECTION

28060.00	13.58	638.08	0.0	0.0	638.11	0.03	0.10	0.01	629.50
2690.	1704.	781.	205.	2107.	324.	277.	112.	17.	625.50
0.38	0.81	2.41	0.74	0.100	0.040	0.100	0.045	624.50	201.45
0.000170	200.	626.	900.	2	0	0	0.0	327.71	616.16

*SECNO 28232.000

D/S FOOTBRIDGE

28232.00	10.39	638.39	0.0	0.0	638.74	0.35	0.47	0.16	628.00
2691.	94.	1943.	692.	69.	353.	566.	161.	25.	635.00
0.46	0.79	6.50	1.22	0.100	0.040	0.100	0.047	628.00	28.30
0.001403	1000.	1372.	1400.	2	0	0	0.0	259.44	285.74

*SECNO 28233.000

3370 NORMAL BRIDGE,NRD= 0 MIN ELTRD= 635.00 MAX ELLC= 633.50

Footbridge has eliminated
x 49ft² of channel area

28232, 28233, 28240, 28291 all repeats, except for bridge data

FOOTBRIDGE TO SCHOOL D/S FACE

28233.00	10.66	638.60	0.0	0.0	638.79	0.19	0.00	0.05	625.00
2690.	100.	1385.	1204.	76.	313.	604.	161.	25.	635.00
0.46	1.29	4.43	1.99	0.100	0.040	0.100	0.047	628.00	28.70
0.003451	1.	1.	1.	2	0	0	-48.75	203.47	200.22

*SECNO 28240.000

3370 NORMAL BRIDGE,NRD= 0 MIN ELTRD= 635.00 MAX ELLC= 633.50

FOOTBRIDGE TO SCHOOL U/S FACE

28240.00	10.63	638.63	0.0	0.0	638.81	0.10	0.02	0.00	635.00
2690.	101.	1382.	1207.	79.	314.	607.	162.	25.	635.00
0.46	1.29	4.41	1.99	0.100	0.040	0.100	0.047	628.00	26.57
0.003414	7.	7.	7.	0	0	0	-48.75	263.76	290.33

*SECNO 28241.000

U/S FOOTBRIDGE

28241.00	10.56	638.56	0.0	0.0	638.88	0.32	0.00	0.07	635.00
2690.	59.	1913.	718.	76.	360.	597.	162.	25.	635.00
0.46	0.78	5.31	1.20	0.100	0.040	0.100	0.047	628.00	27.25
0.001275	1.	1.	1.	2	0	0	0.0	262.69	209.94

CCHV= 0.100 CEHV= 0.300

*SECNO 28560.000

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	WARN ELEV
0	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	MTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

VALLEY SECTION

28560.00	12.92	639.12	0.0	0.0	639.22	0.10	0.32	0.02	633.60
2690.	180.	991.	1519.	203.	253.	1398.	170.	27.	632.70
0.50	0.69	3.92	1.09	0.150	0.050	0.150	0.047	626.20	4.79
0.001039	350.	319.	200.	2	0	0	0.0	327.50	332.29

*SECNO 29040.000

VALLEY SECTION

29040.00	11.79	639.39	0.0	0.0	639.46	0.06	0.23	0.00	630.20
2690.	321.	1389.	1280.	455.	362.	1636.	184.	29.	631.50
0.56	0.71	3.01	0.76	0.150	0.050	0.150	0.049	627.60	21.05
0.000453	300.	480.	250.	2	0	0	0.0	357.15	576.20

*SECNO 30374.000

VALLEY SECTION

30376.00	10.76	640.06	0.0	0.0	640.14	0.08	0.00	0.01	632.20
2690.	349.	1141.	1200.	376.	341.	1275.	248.	40.	632.00
0.74	0.92	3.35	0.94	0.120	0.050	0.120	0.049	629.30	104.73
0.000623	1400.	1335.	1200.	2	0	0	0.0	395.28	500.01

*SECNO 31190.000

VALLEY SECTION

31190.00	5.42	640.22	0.0	0.0	640.56	0.34	0.34	0.08	638.00
2690.	483.	1138.	1068.	237.	167.	547.	257.	42.	636.60
0.76	2.04	6.80	1.95	0.100	0.040	0.100	0.049	634.80	165.35
0.004213	272.	272.	250.	1	0	0	0.0	307.86	476.20

SECNO 31590 X

31590.00	6.34	641.34	0.0	0.0	641.69	0.35	1.13	0.00	637.50
2550.	1017.	1183.	350.	721.	174.	266.	287.	45.	637.50
0.79	1.41	6.82	1.31	0.100	0.030	0.100	0.048	635.00	83.30
0.001866	450.	400.	400.	2	0	0	0.0	366.73	450.03

*SECNO 31990.000

SECNO	DEPTH	CHSEL	CRIBS	WSELK	EG	HV	HL	QLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	UTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IUC	ICONY	CORMR	TOPWID	ENDST

3470 ENCROACHMENT STATIONS= 170.0 500.0 TYPE= 1 TARGET= 330.000

VALLEY SECTION

31990.00	7.02	642.12	0.0	0.0	642.39	0.26	0.69	0.01	637.20
2550.	1533.	990.	26.	1009.	156.	24.	279.	49.	637.60
0.82	1.52	6.34	1.07	0.100	0.030	0.100	0.047	634.40	173.00
0.001429	450.	400.	400.	2	0	0	0.0	366.73	427.24

*SECNO 32470.000

3301 HV CHANGED MORE THAN HVINS

70 FT D/S 8 MILE RD.

32470.00	9.90	642.10	0.0	0.0	643.66	1.56	0.68	0.39	633.40
2550.	362.	2021.	167.	146.	180.	75.	287.	50.	645.00
0.83	2.42	11.20	2.22	0.080	0.030	0.080	0.046	632.20	42.34
0.002813	400.	400.	550.	3	0	0	0.0	86.07	178.91

CCHV= 0.300 CEHV= 0.500

*SECNO 32541.000

3301 HV CHANGED MORE THAN HVINS

D/S FACE 8 MILE RD. XSEC 0+00 for Farmington Hills

32540.00	10.52	643.52	0.0	0.0	644.06	0.54	0.10	0.31	633.50
2551.	293.	1869.	386.	192.	275.	206.	286.	50.	633.60
0.64	1.53	6.81	1.69	0.080	0.030	0.080	0.046	633.00	540.84
0.000859	70.	70.	70.	3	0	0	0.0	131.35	672.19

have 'n' values been changed to match FES starting WSEL?

1968 run shows different "n" values




1) COUNTY: Wayne

2) STUDY NAME: City of Livonia

3) WATERCOURSE: Upper Rouge, Bell Branch, and tributaries

4) DOCUMENT TYPE: Report



FROM:

Wade, Trim & Associates, Inc.
25185 Goddard Road P.O. Box 10
Taylor, Michigan 48180

TO:

HYDRAULIC REPORT
CITY OF LIVONIA, MICHIGAN

HYDRAULIC REPORT
LIVONIA CITY

I. INTRODUCTION

The City of Livonia is located in the northwestern portion of Wayne County and is entirely within the Rouge River Basin. The City consists of approximately 36 square miles.

This report summarizes the hydraulic studies undertaken to support the detailed study of nearly 1.5 miles of the Upper Rouge River, over 5 miles of the Bell Branch, over 4 miles of the Tarabusi Creek, 1.5 miles of Tributary #1 and about 1 mile of the Beitz Drain. Tarabusi Creek, Tributary #1 and Beitz Drain are tributaries of the Bell Branch. In addition, 3.5 miles of the Middle Rouge River were studied by approximate methods.

This study was conducted by Wade, Trim & Associates, Inc., Consulting Engineers and Glen Roberts served as Project Manager.

RECEIVED
OCT 08 19/9
WATER MANAGEMENT

II. UPPER ROUGE RIVER (DETAILED)

Detailed studies were performed on the entire Upper Rouge River within the City of Livonia. This study incorporated data and information developed for Flood Insurance Studies being conducted for the Redford Township (Reference 1) and City of Farmington Hills (Reference 2). A total of eleven (11) cross sections, five (5) bridge and seven (7) valley sections were field surveyed by Wade, Trim & Associates, Inc. and were supplemented by U.S.G.S. Quad Maps of the study area which consist of five foot contour intervals (Reference 4) and topographic maps of the study area which consist of two foot contour intervals (References 6 and 7).

Table 1 cross references section designations by showing the computer section number which corresponds to the cross section letter shown in Exhibit 1. Table 2 lists discharges that have been approved by the Michigan Department of Natural Resources (M.D.N.R.). Exhibit 2 contains bridge sketches as well as bridge loss coefficients.

A. Method of Analysis

The HEC-2 backwater program was used in developing water surface profiles (Reference 13). Table 2 contains selected flood elevations from the HEC-2 printout. HEC-2 printouts including computer cross section plots are presented as Exhibit 3. (Exhibit 3 is contained in the 11" x 15" folder enclosed with this report). Water surface profiles resulting from the backwater analyses are presented as Exhibit 4.

B. Variables and Coefficients

Roughness coefficients (Mannings "n") were estimated by field inspection at each cross section. Typical roughness values for the main channel of the Upper Rouge River range from .03 to 0.05; roughness values for the overbank areas varied between 0.08 to 0.15 for all floods. These values are indicative of summer month conditions and are consistent with values recommended and used in engineering practice. Contraction and expansion coefficients ranged from 0.3 and 0.5 to 0.4 and 0.6 at bridge sections and 0.1 and 0.3 to 0.4 and 0.6 for channel transitions.

C. High Water Marks

Table 3 lists 8 documented high water marks for the June, 1968 storm from the Corps of Engineers Post Flood Report (Reference 12). A 1968 flood profile was developed (Exhibit 3) and the documented high water marks were matched at all locations except 8 Mile Road in order to calibrate the HEC-2 computer model. The high water mark at 8 Mile Road is listed in unknown condition. All possible adjustments, within good engineering practice, were made on the HEC-2 computer model in order to match this high water mark; however, the profile developed in this analysis could not be calibrated with the high water mark and consequently the high water mark is considered invalid.

D. Starting Conditions

The starting water surface elevations for the 10 year and 100 year backwater computations were taken from the FIS Report in Redford Township. The Redford Township FIS does not analyze the 50 year flow condition. Additionally, the 500 year flow from this study does not match the 500 year flow in the Redford Township FIS. Consequently, a rating curve (Exhibit 19) was made at the most upstream cross section of the Redford Township FIS, and the 50 and 500 year elevations were obtained from it.

E. Special Problems

The upstream limit of the Livonia study was matched with the Farmington Hills FIS at the downstream face of 8 Mile Road. Although the flows for each storm in this study were higher than the respective storm flows in the Farmington Hills FIS, the elevations in the Livonia study matched the elevations in the Farmington Hills FIS for the 50, 100, and 500 year storms. The 10 year elevation was not matched due to the large difference in flow.

F. General

Computed water surface elevations were developed to an accuracy of 0.5 feet for floods of the selected recurrence intervals.

All elevations are referenced to the U.S. Geological and Coastal Survey (U.S.G.C.S.) Datum. This datum is equivalent to the National Vertical Datum of 1929 (N.G.V.D.).

The hydraulic analyses for this study were based only on the effects of flow unobstructed by ice or debris. The flood elevations are considered valid only if hydraulic structures, in general, remain unobstructed and do not fail.

TABLE 1

CITY OF LIVONIA, MICHIGAN

UPPER ROUGE RIVER

CROSS REFERENCE INDEX

COMPUTER SECTION NUMBER	STATION	FW & FB LETTER	DESCRIPTION
22865.	0	A	30' D/S Inkster Rd. (Redford FIS)
22895.	30	B	D/S Face Inkster Rd.
22935.	70	C	U/S Face Inkster Rd.
23775.	910	D	Valley Section
25052.	2187	E	D/S Face 7 Mile
25108.	2243	F	U/S Face 7 Mile
25628.	2763	G	Valley Section
26088.	3223	H	D/S Face Deering
26184.	3319	I	U/S Face Deering
26860.	3995	J	Valley Section
28241.	5376	K	Footbridge to School
28560.	5695	L	Valley Section
29040.	6175	M	Valley Section
30375.	7510	N	Valley Section
31190.	8325	O	Valley Section
31990.	9125	P	Valley Section
32540.	9675	Q	D/S Face 8 Mile (Farmington Hills FIS)

TABLE 2

CITY OF LIVONIA

UPPER ROUGE RIVER FLOOD FLOW DATA

LOCATION		DISCHARGE - CFS 10 YEAR	50 YEAR	100 YEAR	500 YEAR
Inkster Road		1160	2160	2690	4200
(X-Section A)	ELEV.	625.78	627.80	628.69	630.80
u/s Clarenceville Drain		1150	2050	2550	3900
(X-Section P)	ELEV.	640.51	641.59	642.12	643.59

TABLE 3

CITY OF LIVONIA, MICHIGAN

UPPER ROUGE RIVER

HIGH WATER MARK VERIFICATION

BRIDGE LOCATION	HIGH WATER MARK ELEVATION	HIGH WATER MARK CONDITION	COMPUTER SECTION NUMBER	WTA MODEL OF 1968 FLOOD 1) FLOW (CFS)	WTA MODEL OF 1968 FLOOD ELEVATION
INKSTER RD.					
d/s	629.88	Fair	22865	1730	629.88
			22935		631.55
u/s	631.63	Fair			
			22985		631.84
7 MILE RD.					
d/s	634.00	Fair			
			25052		633.99
d/s	634.80	Fair			
DEERING RD.					
u/s	636.99	Unknown			
			26234		636.69
u/s	635.45	Unknown			
FOOTBRIDGE	637.22	Excellent	28241		637.22
				1630	
8 MILE RD.					
d/s face	2) 644.53	Unknown	32540		2) 643.46

1) Discharges are from the Corps of Engineers Flood Information Report (Reference 3).

2) Not considered valid.

III. BELL BRANCH (DETAILED)

Detailed studies were performed on Bell Branch from the eastern City of Livonia Corporate Boundary at Inkster Road to the Ellen Road bridge. This study incorporated data and information developed for the Redford Township Flood Insurance Study (Reference 1). A total of fourteen (14) valley and six (6) bridge cross sections were field surveyed and completed in March, 1979. Additionally, eight (8) valley sections were provided by the Corps of Engineers (Reference 3). Cross section locations are shown in Exhibit 1 and were supplemented by U.S.G.S. Quad Maps of the study area which consist of five and ten foot contour intervals and Topographic Maps of the study area which consist of two foot contour intervals (References 4, 5, 8, 9, 10 and 11).

Table 4 cross references section designations by showing the computer section number which corresponds to the cross section letter shown in Exhibit 1. Table 5 lists discharges that have been approved by the Michigan Department of Natural Resources (M.D.N.R.). Exhibit 5 contains bridge notes and sketches as well as bridge loss coefficients.

A. Method of Analysis

The HEC-2 backwater program was used in developing water surface profiles (Reference 13). Table 5 contains selected flood elevations from the HEC-2 printout. HEC-2 printouts including computer cross section plots are presented as Exhibit 6. (Exhibit 6 is contained in the 11" x 15" folder enclosed with this report). Water surface profiles resulting from the backwater analyses are presented as Exhibit 7.

B. Variables and Coefficients

Roughness coefficients (Mannings "n") were estimated by field inspection to range from .03 to .04; roughness values for the overbank areas varied between .07 to .12 for all floods. These values are indicative of summer month conditions and are consistent with values recommended and used in engineering practice. Contraction and expansion coefficients were selected as 0.3 and 0.5 at bridge sections and 0.1 and 0.3 for gradual channel transitions.

C. High Water Marks

Table 6 lists 12 documented high water marks for the June, 1968 storm from the Corps of Engineers Post Flood Report (Reference 12).

The HEC-2 computer model for this study was calibrated with the documented high water marks. Since the 1968 flood is considered to be slightly less than a 50 year storm, the WTA 50 year flood profile and the documented high water marks for the 1968 flood were compared. Results of this analysis (Table 6) indicate that the WTA 50 year flood profile is slightly higher than the documented high water marks.

Higher priority was placed on high water marks which are listed in excellent condition since some of the high water marks contradict each other or do not appear to fit in the profile.

D. Starting Conditions

The starting water surface elevations for the 10 year and 100 year frequency floods used in the backwater computations are taken from the most upstream section of the FIS report on Bell Branch in Redford Township. The Redford Township FIS does not list a 50 year flow and elevation. Therefore, a rating curve (Exhibit 20) was made at the same upstream section and the 50 year starting elevation for this study was obtained from it. The 500 year flow of this study does not match the 500 year flow of the Redford Township FIS. The starting elevation was obtained from the same rating curve using the 500 year flow of this study.

E. Special Problems

No special problems were encountered in the hydraulic analysis of the Bell Branch.

F. General

Computed water surface elevations were developed to an accuracy of 0.5 feet for floods of the selected recurrence intervals.

All elevations are referenced to the U.S. Geological and Coastal Survey (U.S.G.C.S.) Datum. This datum is equivalent to the National Geodetic Vertical Datum of 1929 (N.G.V.D.).

The hydraulic analyses for this study were based only on the effects of flow unobstructed by ice or debris. The flood elevations are considered valid only if hydraulic structures, in general, remain unobstructed and do not fail.

TABLE 4
CITY OF LIVONIA, MICHIGAN
BELL BRANCH
CROSS REFERENCE INDEX

CORPS STATION	COMPUTER SECTION NUMBER	FW & FB LETTER	DESCRIPTION
	0	A	50' D/S Inkster Road Last C.S. in Redford Township FIS
	50	B	D/S Face Inkster Road Bridge
	120	C	U/S Face Inkster Road Bridge
153+70	640	D	Valley Section
166+20	1950	E	Valley Section
172+10	2750	F	Valley Section
183+10	3950	G	200' D/S of Confluence with Tarabusi Creek
190+70	4520	H	Valley Section
196+00	5050	I	Valley Section
201+40	5520	J	Valley Section
207+00	6100	K	Valley Section
	6370	L	D/S Face Middlebelt Road Bridge
	6446	M	U/S Face Middlebelt Road Bridge
	7796	N	Valley Section
	8896	O	Valley Section
	12076	P	Valley Section
	12826	Q	Valley Section
	14026	R	D/S Face Merriman Road Bridge
	14100	S	U/S Face Merriman Road Bridge
	14660	T	Valley Section
	16305	U	Valley Section

TABLE 4
CITY OF LIVONIA, MICHIGAN
BELL BRANCH
CROSS REFERENCE INDEX
(Continued)

CORPS STATION	COMPUTER SECTION NUMBER	FW & FB LETTER	DESCRIPTION
	17780	V	D/S Face Hubbard Road Bridge
	17826	W	U/S Face Hubbard Road Bridge
	18500	X	Valley Section
	20180	Y	Valley Section
	22060	Z	D/S Face Farmington Road Bridge
	22146	AA	U/S Face Farmington Road Bridge
	23296	AB	Valley Section
	24096	AC	Confluence with Beitz Drain
	25668	AD	Valley Section
	26728	AE	Valley Section
	28628	AF	Confluence with Tributary #1
	29488	AG	Valley Section
	30868	AH	D/S Face Ellen Road Bridge
	30921	AI	U/S Face Ellen Road Bridge

TABLE 5
CITY OF LIVONIA
BELL BRANCH FLOOD FLOW DATA

LOCATION		DISCHARGE - CFS 10 YEAR	50 YEAR	100 YEAR	500 YEAR
Inkster Road		1,650	2,900	3,600	5,500
(X-Section A)	Elev.	616.70	619.20	620.50	624.00
U/S Tarabusi Creek		1,110	1,720	2,120	3,120
(X-Section H)	Elev.	621.58	622.79	623.61	626.08
U/S Beitz Drain		800	1,410	1,740	2,610
(X-Section AD)	Elev.	642.24	643.71	644.36	645.74
U/S Tributary #1		500	890	1,100	1,550
(X-Section AG)	Elev.	647.70	648.31	648.63	649.55
U/S Patter Drain		400	710	880	1,230
(X-Section AH)	Elev.	648.88	650.07	650.58	651.63

TABLE 6

CITY OF LIVONIA, MICHIGAN

BELL BRANCH

HIGH WATER MARK VERIFICATION

BRIDGE LOCATION	HIGH WATER MARK ELEVATION	HIGH WATER MARK CONDITION	COMPUTER SECTION NUMBER	WTA MODEL OF 50 Yr. FLOOD PROFILE FLOW (CFS)	WTA MODEL OF 50 Yr. FLOOD PROFILE ELEVATION
INKSTER RD.				2900	
d/s	618.91	Excellent	0		[1] 619.20
d/s face	619.3	Excellent	50		619.69
u/s face	618.85	Good	120		619.94
u/s	619.56	Excellent	170		619.89
				1720	
MIDDLEBELT RD.					
d/s face	624.61	Excellent	6370		624.91
u/s face	623.86	Unknown	6446		624.91
HENRY RUFF RD.					
dead end	628.73	Excellent			
MERRIMAN RD.					
d/s face	631.77	Excellent	14026		631.81
u/s face	631.92	Excellent	14100		632.17
FARMINGTON RD.					
d/s	640.94	Unknown	22010		639.73
d/s	639.73	Good	22010		639.73
				710	
ELLEN RD.					
d/s face	649.43	Fair	30868		650.07

[1] The 50 yr. flood elevation of 619.2 was obtained from a rating curve at X-section 16 of the Redford Township F.I.S. (Reference 1).

IV. TARABUSI CREEK (DETAILED)

Detailed studies were performed on Tarabusi Creek from Bell Branch to the northern City of Livonia Corporate Boundary at 8 Mile Road. A total of twenty-six (26) cross sections were provided by the Corps of Engineers (Reference 3). The cross sections included five (5) bridges and twenty-one (21) valley cross sections. Additionally, one bridge cross section was field surveyed by Wade, Trim & Associates, Inc. Cross section locations are shown in Exhibit 1 and were supplemented by U.S.G.S. Quad Maps of the study area which consist of five and ten foot contour intervals (References 4 and 5).

Table 7 cross references section designations by showing the computer section number which corresponds to the cross section letter shown in Exhibit 1. Table 8 lists discharges that have been approved by the Michigan Department of Natural Resources (M.D.N.R.). Exhibit 8 contains bridge notes and sketches as well as bridge loss coefficients.

A. Method of Analysis

The HEC-2 backwater program was used in developing water surface profiles (Reference 13). Table 8 contains selected flood elevations from the HEC-2 printout. HEC-2 printouts including computer cross section plots are presented as Exhibit 9. (Exhibit 9 is contained in the 11" x 15" folder enclosed with this report). Water surface profiles resulting from the backwater analyses are presented as Exhibit 10.

B. Variables and Coefficients

Roughness coefficients (Mannings "n") were estimated by field inspection to range from .03 to .05 for the channel and to range from .05 to .15 for the overbank areas for all floods. These values are indicative of summer month conditions and are consistent with values recommended and used in engineering practice. Contraction and expansion coefficients ranged from 0.3 and 0.5 to 0.4 and 0.6 at bridge sections and channel transitions.

C. High Water Marks

Table 9 lists 9 documented high water marks for the June, 1968 storm from the Corps of Engineers Post Flood Report (Reference 12).

The HEC-2 computer model for Tarabusi Creek was calibrated with the documented high water marks for the 1968 flood. The 1968 flow rate presented by the Corps of Engineers was used to develop a 1968 flood profile (Reference 3). This flow rate was input to the HEC-2 model at 6 Mile Road. Comparison of the resulting elevations, at the upstream and downstream faces of 6 Mile Road bridge, with the documented high water marks indicates that the flow rate is correct. Since the 6 Mile Road bridge has been replaced since 1968, the old structure was input into the HEC-2 model for this analysis.

Most of the documented high water marks for Tarabusi Creek are listed in poor and unknown condition; therefore, some of these marks were not matched exactly. However, these marks were used as a guide to insure that the model was working in the proper range.

D. Starting Conditions

The starting water surface elevation used in all backwater computations is the mean annual elevation for the Bell Branch at the confluence of the Tarabusi Creek (Exhibit 18).

E. Special Problems

No special problems were encountered in the hydraulic analysis of the Tarabusi Creek.

F. General

Computed water surface elevations were developed to an accuracy of 0.5 feet for floods of the selected reoccurrence intervals.

All elevations are referenced to the U.S. Geological and Coastal Survey (U.S.G.C.S.) Datum. This datum is equivalent to the National Geodetic Vertical Datum of 1929 (N.G.V.D.).

The hydraulic analyses for this study were based only on the effects of flow unobstructed by ice or debris. The flood elevations are considered valid only if hydraulic structures, in general, remain unobstructed and do not fail.

TABLE 7

CITY OF LIVONIA, MICHIGAN

TARABUSI CREEK

CROSS REFERENCE INDEX

CORPS STATION	COMPUTER SECTION NUMBER	FW & FB LETTER	DESCRIPTION
0+50	120	A	50' U/S of Confluence with Bell Branch
	1340	B	Valley Section
	2466	C	D/S Face 6 Mile Road Bridge
	2554	D	U/S Face 6 Mile Road Bridge
26+00	4316	E	D/S Face Middlebelt Road Bridge
	4403	F	U/S Face Middlebelt Road Bridge
59+50	5950	G	Valley Section
66+00	6600	H	Valley Section
73+40	7340	I	Valley Section
88+15	8815	J	Valley Section
107+40	10708	K	D/S Face Merriman Road Bridge
	10782	L	U/S Face Merriman Road Bridge
119+60	11720	M	Valley Section
126+20	12570	N	Valley Section
159+20	13360	O	Valley Section
174+50	14440	P	D/S Face 7 Mile Road Bridge
	14501	Q	U/S Face 7 Mile Road Bridge
184+40	15360	R	Valley Section
192+60	16100	S	Valley Section
201+70	16900	T	Valley Section
210+80	17690	U	Valley Section
230+00	19313	V	D/S Face Farmington Road Bridge
	19387	W	U/S Face Farmington Road Bridge
	19517	X	Valley Section
	20117	Y	Valley Section
	21117	Z	Valley Section
	21667	AA	Valley Section
	23050	AB	Valley Section
	23550	AC	Valley Section
	24250	AD	D/S Face 8 Mile Road Bridge

TABLE 8
CITY OF LIVONIA
TARABUSI CREEK FLOOD FLOW DATA

LOCATION		DISCHARGE - CFS 10 YEAR	50 YEAR	100 YEAR	500 YEAR
Confluence with Bell Branch		1,070	1,560	1,770	2,060
(X-Section A)	Elev.	620.00	620.00	620.00	620.00
U/S Merriman Road		960	1,410	1,590	1,860
(X-Section M)	Elev.	646.57	647.57	647.92	648.42
U/S Farmington Road		820	1,200	1,350	1,580
(X-Section X)	Elev.	677.07	678.53	679.23	680.28
8 Mile Road		730	1,070	1,210	1,410
(X-Section AD)	Elev.	694.33	694.83	695.09	695.45

TABLE 9

CITY OF LIVONIA, MICHIGAN

TARABUSI CREEK

HIGH WATER MARK VERIFICATION

BRIDGE LOCATION	1968 HIGH WATER MARK ELEVATION	CONDITION	COMPUTER SECTION NUMBER	WTA MODEL OF 1968 FLOOD PROFILE [1] FLOW (CFS)	ELEVATION
6 MILE ROAD				950	
d/s face	626.12	Good	2498		626.12
u/s face	627.19	Good	2554		627.18
u/s	626.30	Unknown	2604		627.84
MIDDLEBELT ROAD					
d/s face	629.84	Unknown	4316		629.22
u/s face	632.00	Unknown	4453		632.10
u/s	631.89	Unknown			
7 MILE ROAD					
d/s face	658.65	Poor	14440		658.36
FARMINGTON ROAD					
d/s face	677.98	Poor	19313		677.52
u/s	678.04	Poor	19387		677.92

[1] The 1968 flood flow of 950 cfs is from the Corps of Engineers Post Flood Report (Reference 12) and was verified by matching the two good condition high water marks at 6 Mile Road.

V. TRIBUTARY #1 (DETAILED)

Detailed studies were performed on Tributary #1 from the confluence with Bell Branch to the north property line of Sheffield Subdivision. A total of one bridge and seven valley cross sections were field surveyed and completed in February, 1978 by Wade, Trim & Associates, Inc. Cross section locations are shown in Exhibit 1 and were supplemented by U.S.G.S. Quad Maps consisting of 10 foot contour intervals and Subdivision Maps consisting of given elevations (References 5, and 16).

Table 10 cross references section designations by showing the computer section number which corresponds to the cross section letter shown in Exhibit 1. Table 11 lists discharges that have been approved by the Michigan Department of Natural Resources (M.D.N.R.). Exhibit 11 contains bridge notes and sketches as well as bridge loss coefficients.

A. Method of Analysis

The HEC-2 backwater program was used in developing water surface profiles (Reference 13). Table 11 contains selected flood elevations from the HEC-2 printout. HEC-2 printouts including computer cross section plots are presented as Exhibit 12. (Exhibit 12 is contained in the 11" x 15" folder enclosed with this report). Water surface profiles resulting from the backwater analysis are presented as Exhibit 13.

B. Variables and Coefficients

Roughness coefficients (Mannings "n") were estimated by field inspection to range from .025 to .04; roughness values for the overbank areas varied between .06 and .12 for all floods. These values are indicative of summer month conditions and are consistent with values recommended and used in engineering practice. Contraction and expansion coefficients selected were 0.3 and 0.5 at bridge sections and 0.1 and 0.3 for gradual transitions.

C. High Water Marks

No documented high water data exists for flood elevations on the Tributary #1.

D. Starting Conditions

The mean annual water surface elevation of the Bell Branch at the confluence with the Tributary #1 was used as the starting water surface elevation (Exhibit 18).

E. Special Problems

Tributary #1 was relocated from approximately cross section H to the upstream limit of this study. However, the old natural channel was maintained to handle low flows and local runoff. A weir and low flow structure are located at cross section I and the following flow distribution results:

1. Low flows are diverted to the old channel through a 53" x 34" elliptical concrete pipe.

2. Flood flows are discharged to the relocated channel with a small amount of flow being diverted to the old channel in the low flow pipe.

The upstream limit of the old channel terminates at the low flow pipe. The channel upstream of the weir and low flow structure is all relocated and the old channel has been filled in.

The weir and low flow structure could not be handled adequately by the HEC-2 computer program; therefore, hand calculations were performed (Exhibit 17) and the resulting elevations and flow distribution were input to the HEC-2 model. These calculations indicate that the low flow handles only minor amounts of flow for all the floods analyzed. Therefore, a floodway is maintained at the banks of the old channel to insure the safe passage of low flows and the floodway for the relocated channel which handles the majority of flow was established by equal conveyance reduction in the HEC-2 model.

F. General

Computed water surface elevations were developed to an accuracy of 0.5 feet for floods of the selected recurrence intervals.

All elevations are referenced to the U.S. Geological and Coastal Survey (U.S.G.C.S.) Datum. This datum is equivalent to the National Geodetic Vertical Datum of 1929 (N.G.V.D.).

The hydraulic analyses for this study were based only on the effects of flow unobstructed by ice or debris. The flood elevations are considered valid only if hydraulic structures, in general, remain unobstructed and do not fail.

TABLE 10
CITY OF LIVONIA, MICHIGAN
TRIBUTARY #1
CROSS REFERENCE INDEX

WTA FIELD BOOK NO.	COMPUTER SECTION NUMBER	FW & FB LETTER	DESCRIPTION
	60	A	60' U/S of Confluence with Bell Branch
	1250	B	150' U/S of Confluence with Westerly Tributary
56+05	3470	C	Valley Section
48+40	4235	D	Valley Section
44+37	4938	E	D/S Face Six Mile Road Bridge
43+21	4754	F	U/S Face Six Mile Road Bridge
37+12	5363	G	Valley Section
27+20	6355	H	Valley Section
	7975	I	Weir
7+23	8352	J	Valley Section
	9075	K	Valley Section

TABLE 11
CITY OF LIVONIA
TRIBUTARY #1 FLOOD FLOW DATA

LOCATION		DISCHARGE - CFS 10 YEAR	50 YEAR	100 YEAR	500 YEAR
U/S Bell Branch		310	520	640	930
(X-Section A)	Elev.	642.50	642.57	643.37	644.50
U/S Westerly Tributary		210	370	460	680
(X-Section B)	Elev.	646.76	648.51	648.87	649.39
*Weir		175	315	410	610
(X-Section I)	Elev.	676.15	676.70	677.00	677.65

*From hand calculations

VI. BEITZ DRAIN (DETAILED)

Detailed studies were performed on Beitz Drain from the confluence with Bell Branch to the Curtis Road bridge. A total of one bridge, one culvert, and three valley cross sections were field surveyed and completed in February, 1978. Cross section locations are shown in Exhibit 1 and were supplemented by U.S.G.S. Quad Maps consisting of 10 foot contour intervals and Subdivision Maps (References 5, 14 and 15).

Table 12 cross references section designations by showing the computer section number which corresponds to the cross section letter shown in Exhibit 1. Table 13 lists discharges that have been approved by the Michigan Department of Natural Resources (M.D.N.R.). Exhibit 14 contains bridge notes and sketches as well as bridge loss coefficients.

A. Method of Analysis

The HEC-2 backwater program was used in developing water surface profiles (Reference 13). Table 13 contains selected flood elevations from the HEC-2 printout. HEC-2 printouts including computer cross section plots are presented as Exhibit 15. (Exhibit 15 is contained in the 11" x 15" folder enclosed with this report). Water surface profiles resulting from the backwater analysis are presented as Exhibit 16.

B. Variables and Coefficients

Roughness coefficients (Mannings "n") were estimated by field inspection to range from .02 to .035; roughness values for the overbank areas varied between .06 and .12 for all floods. These values are indicative of summer month conditions and are consistent with values recommended and used in engineering practice. Contraction and expansion coefficients selected were 0.3 and 0.5 at bridge sections and 0.1 and 0.3 for gradual transitions.

C. High Water Marks

No documented high water data exists for flood elevations on the Beitz Drain.

D. Starting Conditions

The mean annual elevation of the Bell Branch at the confluence with the Beitz Drain was used as the starting water surface elevation for all floods (Exhibit 18).

E. Special Problems

No special problems were encountered in the hydraulic analysis of the Beitz Drain.

F. General

Computed water surface elevations were developed to an accuracy of 0.5 feet for floods of the selected recurrence intervals.

All elevations are referenced to the U.S. Geological and Coastal Survey (U.S.G.C.S.) Datum. This datum is equivalent to the National Geodetic Vertical Datum of 1929 (N.G.V.D.).

The hydraulic analyses for this study were based only on the effects of flow unobstructed by ice or debris. The flood elevations are considered valid only if hydraulic structures, in general, remain unobstructed and do not fail.

TABLE 12
CITY OF LIVONIA, MICHIGAN
BEITZ DRAIN
CROSS REFERENCE INDEX

WTA FIELD BOOK NO.	COMPUTER SECTION NUMBER	FW & FB LETTER	DESCRIPTION
	70	A	70' U/S of Confluence with Bell Branch
24+50	2115	B	Valley Section
21+56	2409	C	D/S Face Six Mile Road Bridge
20+39	2526	D	U/S Face Six Mile Road Bridge
5+00	4065	E	Valley Section
0+00	4565	F	D/S Face Francavilla Culvert
	5640	G	U/S Face Francavilla Culvert

TABLE 13
CITY OF LIVONIA
BEITZ DRAIN FLOOD FLOW DATA

LOCATION		DISCHARGE - CFS 10 YEAR	50 YEAR	100 YEAR	500 YEAR
U/S Bell Branch		180	310	380	560
(X-Section A)	Elev.	639.80	639.80	639.80	639.80

VII. MIDDLE ROUGE RIVER (APPROXIMATE)

Approximate studies were performed on Middle Rouge River through its entire length in the City of Livonia. There are two control structures which affect the elevations on Middle Rouge River through Livonia:

1. The Nankin Lake dam and

2. The Newburgh Lake dam.

The 100 year flood elevations on Nankin Lake and Newburgh Lake were calculated using the weir flow equation (Reference 17). The approximate boundary on the reach of river between the two lakes was taken from the Federal Insurance Administration's Flood Hazard Boundary Map (Reference 20). Table 13 lists estimated 100 year flood elevations on Nankin Lake and Newburgh Lake.

TABLE 13

	LOCATION	APPROXIMATE 100 YEAR FLOOD ELEVATION
1.	Nankin Lake	642.1
2.	Newburgh Lake	667.3

REFERENCES

1. Redford Township, Michigan, Flood Insurance Study, Flood Insurance Administration - Draft, 1973.

2. City of Farmington Hills, Michigan, Flood Insurance Study - Draft, 1979.

3. Corps of Engineers, U.S. Army, Flood Plain Information Upper River Rouge, Minnow Pond Drain, Bell Branch and Tarabusi Creek, Wayne and Oakland Counties, Michigan, January, 1972.

4. U.S. Geological Survey Topographical Maps - Redford Quadrangle, Wayne-Oakland County, 7.5 Minute Series - Photo Revised 1973.

5. U.S. Geological Survey Topographical Maps - Northville Quadrangle, Wayne-Oakland County, 7.5 Minute Series - Photo Revised 1973.

6. Topographic Map - City of Livonia, Section 1, R. 9 E., T. 1 S., Wayne County, Michigan, 1964.

7. Topographic Map - City of Livonia, Section 12, R. 9 E., T. 1 S., Wayne County, Michigan 1964.

8. Topographic Map - City of Livonia, Section 13, R. 9 E., T. 1 S., Wayne County, Michigan, 1964.

9. Topographic Map - City of Livonia, Section 14, R. 9 E., T. 1 S., Wayne County, Michigan, 1964.

10. Topographic Map - City of Livonia, Section 15, R. 9 E., T. 1 S., Wayne County, Michigan, 1964.

11. Topographic Map - City of Livonia, Section 16, R. 9 E., T. 1 S., Wayne County, Michigan, 1964.

12. U.S. Army Corps of Engineers, Post Flood Report of Southeast Michigan Flood 25-27, June, 1968, 1969.

13. HEC-2 Water Surface Profile - Users Manual - U.S. Army Corps of Engineers - 1976.

14. Development Plan for Drain Enclosure Francavilla Subdivision, Orchard, Papke, Hiltz, & McCliment, Inc., Sheet 22 of 33, May, 1977.

15. Grading Limits at Inlet Structure, Beitz Drain, Francavilla Subdivision No. 2, Orchard, Papke, Hiltz, & McCliment, Inc., Sheet 33 of 33, March, 1977.

16. Sheffield Subdivision, McNeely, Lincoln, & Schrader, Inc., Sheets 1A & 1B of 21, September, 1976.

17. Handbook of Hydraulics, H.W. King and E.F. Brater, McGraw-Hill, Inc., 1963.

18. Open Channel Hydraulics, V.T. Chow, McGraw-Hill, Inc., 1959.

19. Bureau of Public Roads, Circular #5, Chart #3, January, 1963.

20. Department of Housing and Urban Development, Federal Insurance Administration, Flood Hazard Boundary Map, City of Livonia, Michigan, June 11, 1976.

CITY OF LIVONIA, MICHIGAN

UPPER ROUGE RIVER, BELL BRANCH,

TARABUSI CREEK, TRIBUTARY #1, and

BEITZ DRAIN

EXHIBIT 1

Field Cross-Section Location

and 100 Year Flood Plain

Floodway Map

CITY OF LIVONIA, MICHIGAN

UPPER ROUGE RIVER

EXHIBIT 2

Bridge Notes and Sketches

Bridge Location : INKSTER ROAD STA 229+35

REFERENCE

Bridge Losses - SB Card

1. XK (Pier Shape Coefficient) 0.0 — HEC-2 manual

XKOR (Loss Coefficient) = 1.0 + Σk, $\Sigma k = k_f + k_e + k_p$

where k_f = friction loss coefficient
k_e = entrance loss coefficient
k_p = loss from intermediate piers

Description of Bridge :


$K_f = 29.1\, n^2 L / R^{4/3}$ for English units

Area = 24.5 x 7 = 206.5 WP = 73.0

$R = A/WP$ 206.5/73.0 $R^{4/3}$ = 4.0 L = 40.

n (composite) = .04(.42) + .017(.58) = 0.027

$K_f = 29.1 \times \frac{(0.027)^2}{(.05)^2} \times 40.0 / 40 = 0.22$



Hydraulic Charts for Selection of Highway Culverts Circular No. 5 Dec. 1965 pg #3

K_c = 0.5

K_p = 0 if bridge has no intermediate piers

K_p = 0.05 if bridge has intermediate piers — HEC-2 manual

Skew Angle = 31°
Correction factor = .22


2. XKOR = 1 + 0.22 + 0.5 + 0.0 = 1.72
3. COFQ - Coefficient of discharge = 3.0 — HEC-2 manual
4. RDLEN = Length of weir = 0.0 (0 if read off BT cards)
5. BWC = bottom width of bridge opening (inc. piers) = 25.4
6. BWP = total width of obstruction = 0.0 — field data
7. BAREA = bridge opening inc. piers = 172.6
8. SS = side slope = 0 (horizontal per 1 vertical unit)
9. ELCHU = Elevation of channel invert U/S side = 620.2 (0 if equal to minimum elevation in previous x-sect.)
10. ELCHD = Elevation of channel invert D/S side = 620.2 (0 if equal to minimum elevation in previous x-sect.)


SUBJECT	BY	CHK.	SHEET NO	File Code No (Job No) Owner	Project	Suffix
U.R.R. CITY OF LIVONIA	DRB			HUD	2014	07
	DATE 4/79	DATE	OF			

HUD 2014-07

BRIDGE DETAIL
UPPER ROUGE RIVER
INKSTER RD.

FIR #947 A.P. M.S MAR. 19-1979 27.





Bridge Location : 7 Mile Rd. STA. 251+09

Bridge Losses - SB Card

1. XK (Pier Shape Coefficient) 0.0 — HEC-2 Manual

XKOR (Loss Coefficient) = 1.0 + ΣK, $\Sigma k = k_f + k_e + k_p$

where k_f = friction loss coefficient
k_e = entrance loss coefficient
k_p = loss from intermediate piers

Description of Bridge:

$K_f = 29.1\, n^2 L / R^{4/3}$ for English units

Area = 147 W_p = 63


$R = A/W_p$ 2.33 $R^{4/3}$ = 3.09 L = 56.0

n (composite) = .027

$K_f = 29.1 \times (0.027)^2 \times 56 / 3.09$ = 0.65 .38

Hydraulic Design of Highway Culverts Hydraulic Design Series No. 5 FHWA-IP-85-15 Circular No. 5 Dec. 1965 pg 43

$K_e = 0.5$



($K_p = 0$ if bridge has no intermediate piers)

$K_p = 0.05$ if bridge has intermediate piers — HEC-2 manual

Skew angle = 31°
factor = .86

2. XKOR = 1 + .38 + 0.5 + 0.0 = 1.88
3. COFQ - Coefficient of discharge = 2.65 — HEC-2 manual
4. RDLEN = Length of weir = 0.0 (0 if read off BT cards)
5. BWC = bottom width of bridge opening (inc. piers) = 25.8
6. BWP = total width of obstruction = 0.0 — field data
7. BAREA = bridge opening inc. piers = 95.5
8. SS = side slope = 0.0 (horizontal per 1 vertical unit)
9. ELCHU = Elevation of channel invert U/S side = 625.6 (0 if equal to minimum elevation in previous x-sect.)
10. ELCHD = Elevation of channel invert D/S side = 625.6 (0 if equal to minimum elevation in previous x-sect.)

SUBJECT	BY	CHK	SHEET NO	File Code No (Job No) Owner Project Suffix
U.R.R. CITY OF LIVONIA	DRB		___ OF ___	HUD • 2014 • 07
	DATE 4/79	DATE		

HUD 2014-07

BRIDGE DETAIL


UPPER ROUGE RIVER


7 MILE RD.

F.B. # 947

A.P. M.S.

MAR. 19-1979 28





Bridge Location: DEARBORN RD (CMP) STA 261+94

Bridge Losses - SB Carr (MODLED AS BOX CULVERT)

1. XK (Pier Shape Coefficient) 0.0 — HEC-2 manual

XKOR (Loss Coefficient) = 1.0 + ΣK, $\Sigma k = k_f + k_e + k_p$

where k_f = friction loss coefficient
k_e = entrance loss coefficient
k_p = loss from intermediate piers

Description of Bridge:

$K_f = 29.1\, n^2 L / R^{4/3}$ for English units


Area = 8.4 (15.6) = 131. Wp = 43.

$R = A/wp$ 131/43 $R^{4/3}$ = 3.81 L = 96

n (composite) = 0.033

K_f = 29.1 x (0.033)^2 x 96 / 3.81 = 0.80

K_c = 0.7



Hydraulic Charts for Selection of Highway Culverts Circular No. 5 Dec. 1965 pg. 49

(K_p = 0) if bridge has no intermediate piers

K_p = 0.05 if bridge has intermediate piers — HEC-2 manual


2. XKOR = 1 + 0.80 + 0.7 + 0.0 = 2.050
3. COFQ = Coefficient of discharge = 2.65 — HEC-2 manual
4. RDLEN = Length of weir = 0.0 (0 if read off BT cards)
5. BWC = bottom width of bridge opening (inc. piers): 15.6
6. BWP = total width of obstruction = 0.0 — field data
7. BAREA = bridge opening inc. piers = 131.0 — field data
8. SS = side slope = 0.0 (horizontal per 1 vertical unit)
9. ELCHU = Elevation of channel invert U/S side = 625. (0 if equal to minimum elevation in previous x-sect.)
10. ELCHD = Elevation of channel invert D/S side = 625. (0 if equal to minimum elevation in previous x-sect.)


SUBJECT	BY	CHK	SHEET NO	File Code No (Job No) Owner Project Suffix
D.R.R CITY OF LIVONIA	DRB		___ OF ___	HUD • 2014 • 07
	DATE 4/29	DATE		

HUD 2014-07

BRIDGE DETAIL
UPPER ROUGE RIVER

F.B. # 947 A.P. M.S. MAR. 19-1979 29.







HUD 2014-07

BRIDGE DETAIL
UPPER ROUGE RIVER.
FOOT BRIDGE FOR SCHOOL

F.B. #947 A.P. M.S. MAR. 19-1979 30.



UPSTREAM FACING DOWNSTREAM



CITY OF LIVONIA, MICHIGAN

UPPER ROUGE RIVER

EXHIBIT 3

Computer Printouts

HEC-2 Backwater Analysis

with

Cross Section Plots

(See Separate Folder)

CITY OF LIVONIA, MICHIGAN

UPPER ROUGE RIVER

EXHIBIT 4

Stream Profile

CITY OF LIVONIA, MICHIGAN

BELL BRANCH

EXHIBIT 5

Bridge Notes and Sketches

FORM 25 0
(313) 291-5400
Wade Trim & Associates, Inc.
Civil Engineers • Land Surveyors
WORK SHEET
25185 GODDARD ROAD
TAYLOR, MICHIGAN 48180

Bridge Location: Inster Rd.
Bridge Losses - SB Card

REFERENCE

1. XK (Pier Shape Coefficient) 1.25 — HEC-2 manual

XKOR (Loss Coefficient) = 1.0 + Σk, $\Sigma k = k_f + k_e + k_p$

where k_f = friction loss coefficient
k_e = entrance loss coefficient
k_p = loss from intermediate piers

Description of Bridge:

$K_f = 29.1 n^2 L / R^{4/3}$ for English units

Area = 749.5 ✓ = ____ Wp = 223.6 ✓

$R = A/wp$ = ____ $R^{4/3} = 5.61$ $L = 70$


n (composite) = .02

$K_f = 29.1 \times (.02)^2 \times 70/5.61 = .16$

$K_e = .5$ — Hydraulic Charts for the Selection of Highway Culverts Circular No. 5 Dec. 1965 pg. 49

$K_p = 0$ if bridge has no intermediate piers

$K_p = 0.05$ if bridge has intermediate piers — HEC-2 manual



750. - 471.2 = 278.8

2. XKOR = 1 + .16 + .5 + .05 = 1.71 ✓
3. COFQ = Coefficient of discharge = 3. — HEC-2 manual
4. RDLEN = Length of weir = 0. (0 if read off BT cards)
5. BWC = bottom width of bridge opening (inc. piers) = 35.
6. BWP = total width of obstruction = 4. — field data
7. BAREA = bridge opening (inc.) piers = 750. ✓
8. SS = side slope = 1:1.8 (does not include piers)
(horizontal per 1 vertical unit)
9. ELCHU = Elevation of channel invert U/S side = 604.
(0 if equal to minimum elevation in previous X-sect.)
10. ELCHD = Elevation of channel invert D/S side = 604.
(0 if equal to minimum elevation in previous X-sect.)

SUBJECT	BY	CHK	SHEET NO	File Code No (Job No) Owner Project Suffix
Bell Branch, Livonia Hydraulics	T C		____ OF ____	HUD • 2014 • 07
	DATE 4/6/79	DATE		


HUD 2014-07

BRIDGE DETAIL
BELL BRANCH
INKSTER RD.

F.B. # 947

A.P.
M.S.
J.R

MAR. 26-1979



Bridge Location: MIDDLEBELT RD.
Bridge Losses - SB Card

REFERENCE

1. XK (Pier Shape Coefficient) .9 — HEC-2 manual

XKOR (Loss Coefficient) = 1.0 + Σk, $\Sigma k = k_f + k_e + k_p$


where k_f = friction loss coefficient
k_e = entrance loss coefficient
k_p = loss from intermediate piers

Description of Bridge:

$K_f = 29.1\, n^2 L / R^{4/3}$ for English units

Area = 712.5 = ____ Wp = 140.78
$R = A/wp$ = 5.06 $R^{4/3}$ = 8.69 L = 76'
n (composite) = .02

$K_f = 29.1 \times (.02)^2 \times 76/8.69 = .10$



K_e = .9 Obstructions in front of bridge opening — Hydraulic Charts for the Selection of Highway Culverts Circular No. 5 Dec. 1965 pg. 49

K_p = 0 if bridge has no intermediate piers

K_p = 0.05 if bridge has intermediate piers — HEC-2 manual

Skew Bridge at 70°, factor = .94

2. XKOR = 1 + .10 + .9 + .05 = 2.05
3. COFQ = Coefficient of discharge = 3. — HEC-2 manual
4. RDLEN = Length of weir = 0. (0 if read off BT cards)
5. BWC = bottom width of bridge opening (inc. piers) = 55.46
6. BWP = total width of obstruction = 1.88 — field data
7. BAREA = bridge opening inc. piers = 669.75
8. SS = side slope = 0 (horizontal per 1 vertical unit)
9. ELCHU = Elevation of channel invert U/S side = 615.1 (0 if equal to minimum elevation in previous X-sect.)
10. ELCHD = Elevation of channel invert D/S side = 615.1 (0 if equal to minimum elevation in previous X-sect.)

SUBJECT	BY	CHK	SHEET NO	File Code No (Job No) Owner Project Suffix
Bell Branch Limits - Hydraulics	7.6.		____ OF ____	HU0 • 2014 • 07
	DATE 4/6/79	DATE		


HUD
2014-07

BRIDGE DETAIL
BELL BRANCH
MIDDLEBELT RD.

F.B. #947

A.P.
M.S.
I.R.

MAR. 26-19 71. 46.



Bridge Location : MERRIMAN RD.
Bridge Losses - SB Card

REFERENCE

1. XK (Pier Shape Coefficient) .9 — HEC-2 manual

XKOR (Loss Coefficient) = 1.0 + Σk, $\Sigma k = k_f + k_e + k_p$

where k_f = friction loss coefficient
k_e = entrance loss coefficient
k_p = loss from intermediate piers

Description of Bridge :


$K_f = 29.1\, n^2 L / R^{4/3}$ for English units

Area = 432.65 = ____ WP = 143

$R = A/wp = 3.03$ $R^{4/3} = 4.38$ $L = 74$

n (composite) = .02

$K_f = 29.1 \times (.02)^2 \times 74/4.38 = .20$



K_e = .9 Obstructions in front of bridge opening — Hydraulic Charts for the Selection of Highway Culverts Circular No. 5 Dec. 1965 pg. 49

K_p = 0 if bridge has no intermediate piers

K_p = 0.05 if bridge has intermediate piers — HEC-2 manual

Skew Bridge at 64°, factor = .9


2. XKOR = 1 + .20 + .9 + .05 = 2.15
3. COFQ = Coefficient of discharge = 3.0 — HEC-2 manual
4. RDLEN = Length of weir = 0 (0 if read off BT cards)
5. BWC = bottom width of bridge opening (inc. piers) = 53.68
6. BWP = total width of obstruction = 2.27 — field data
7. BAREA = bridge opening inc. piers = 393.6
8. SS = side slope = 0. (horizontal per 1 vertical unit)
9. ELCHU = Elevation of channel invert U/S side = 624.4 (0 if equal to minimum elevation in previous x-sect.)
10. ELCHD = Elevation of channel invert D/S side = 624.4 (0 if equal to minimum elevation in previous x-sect.)


SUBJECT	BY	CHK.	SHEET NO.	File Code No (Job No) Owner Project Suffix
LIVONIA-HYDRAULICS, BELL BRANCH	T.G.		____ OF ____	H40 • 2014 • 07
	DATE 4/5/79	DATE		

1440
2014-07

BRIDGE DETAIL
BELL BRANCH
MERRIMAN RD.
~~FARMINGTON RD.~~

F.B. #947 A.P. M.S. I.R. MAR. 26-1979 49.





Wade Trim & Associates Inc.
Civil Engineers • Land Surveyors
25185 GODDARD ROAD
TAYLOR, MICHIGAN 48180
(313) 291-5400

FORM 25 0

WORK SHEET

Bridge Location: Hubbard Rd.
Bridge Losses - SB Card

REFERENCE

1. XK (Pier Shape Coefficient) 1.25 — HEC-2 manual

XKOR (Loss Coefficient) = 1.0 + Σk, Σk = $k_f + k_e + k_p$

where k_f = friction loss coefficient
k_e = entrance loss coefficient
k_p = loss from intermediate piers

Description of Bridge:


$K_f = 29.1\, n^2 L / R^{4/3}$ for English units

Area = 867. = ____ Wp = 229.8

$R = A/wp = 3.77$ $R^{4/3} = 5.87$ $L = 46$

n (composite) = .02

$K_f = 29.1 \times (.02)^2 \times 46/5.87 = .09$




K_e = .1

Hydraulic Charts for the Selection of Highway Culverts Circular No. 5 Dec. 1965 pg. 43

K_p = 0 if bridge has no intermediate piers

K_p = 0.05 if bridge has intermediate piers — HEC-2 manual



408


2. XKOR = 1 + .09 + .1 + .05 = 1.24
3. COFQ = Coefficient of discharge = 3.0 — HEC-2 manual
4. RDLEN = Length of weir = 0 (0 if read off BT cards)
5. BWC = bottom width of bridge opening (inc. piers) = 36
6. BWP = total width of obstruction = 2 — field data
7. BAREA = bridge opening inc. piers = 867
8. SS = side slope = 2.24 (horizontal per 1 vertical unit)
9. ELCHU = Elevation of channel invert U/S side = 626.5 (0 if equal to minimum elevation in previous x-sect.)
10. ELCHD = Elevation of channel invert D/S side = 626.5 (0 if equal to minimum elevation in previous x-sect.)


SUBJECT	BY	CHK	SHEET NO	File Code No (Job No) Owner Project Suffix
Bell Overch, Livonia - Hydraulics	T G.		____ OF ____	Hud • 2014 • 07
	DATE 4/10/79	DATE		

HUD
2014-07

BRIDGE DETAIL
BELL BRANCH

HUBBARD RD.





FIB. #947

A.P.
m.s.
J.R.

MAR. 26-1979 48.

Wade, Trim & Associates, Inc.
Civil Engineers • Land Surveyors
25185 GODDARD ROAD
TAYLOR, MICHIGAN 48180

WORK SHEET

Bridge Location: Farmington Rd.
Bridge Losses - SB Card


REFERENCE

1. XK (Pier Shape Coefficient) = 1.05 — HEC-2 manual

XKOR (Loss Coefficient) = 1.0 + ΣK, $\Sigma K = K_f + K_e + K_p$

where K_f = friction loss coefficient
K_e = entrance loss coefficient
K_p = loss from intermediate piers

Description of Bridge:



$K_f = 29.1\, n^2 L / R^{4/3}$ for English units

Area = 1044. = ____ Wp = 169.

$R = A/wp = 6.18$ $R^{4/3} = 11.33$ $L = 86$


n (composite) = .02

$K_f = 29.1 \times (.02)^2 \times 86/1133 = .09$

$K_e = .2$ — Hydraulic Charts for the Selection of Highway Culverts Circular No. 5 Dec. 1965 pg. 49

$K_p = 0$ if bridge has no intermediate piers

$K_p = 0.05$ if bridge has intermediate piers — HEC-2 manual



2. XKOR = 1 + .09 + .2 + .05 = 1.34
3. COFQ = Coefficient of discharge = 3. — HEC-2 manual
4. RDLEN = Length of weir = ____ (0 if read off BT cards)
5. BWC = bottom width of bridge opening (inc. piers) = 32
6. BWP = total width of obstruction = 1.74 — field data
7. BAREA = bridge opening inc. piers = 1.044
8. SS = side slope = 1.46 (horizontal per 1 vertical unit)
9. ELCHU = Elevation of channel invert U/S side = 632.6 (0 if equal to minimum elevation in previous X-sect.)
10. ELCHD = Elevation of channel invert D/S side = 632.6 (0 if equal to minimum elevation in previous X-sect.)

SUBJECT	BY	CHK	SHEET NO	File Code No (Job No) Owner Project Suffix
Livonia - Hydraulics Bridge	T.G.			1-90 • 20 14 • 07
	DATE 4/19/74	DATE	OF	


HUD 2014-07

BRIDGE DETAIL
BELL BRANCH
FARMINGTON RD.
~~MERRIMAN RD.~~

F.B. # 947

R.P.
M.S.
J.R.

MAR. 26-197: 47.




FORM 25-0
(313) 291-5400

Wade Trim & Associates, Inc.
Civil Engineers • Land Surveyors
WORK SHEET

25185 GODDARD ROAD
TAYLOR, MICHIGAN 48180

REFERENCE

FARMINGTON RD.
SKEW BRIDGE CALCULATIONS



Factor to multiply BT cords by = cos 30° = .87
" " " GR " " " = .87

SUBJECT	BY	CHK.	SHEET NO.	File Code No. (Job No.) Owner	Project	Suffix
Livonia - Hydraulics Bell Br.	T. G			11-00	2014	07
	DATE 3/19/79	DATE	____OF____			

Bridge Location : ELLIN [illegible]

Bridge Losses - SB Card

REFERENCE

1. XK (Pier Shape Coefficient) 0. — HEC-2 manual

XKOR (Loss Coefficient) = 1.0 + Σk, $\Sigma k = k_f + k_e + k_p$

where k_f = friction loss coefficient
k_e = entrance loss coefficient
k_p = loss from intermediate piers

Description of Bridge :

$K_f = 29.1\, n^2 L / R^{4/3}$ for English units

Area = ____ = ____ Wp = ____

$R = A/wp = 2.9$ $R^{4/3} = 4.19$ $L = 53$

n (composite) = .0[illegible]

$K_f = 29.1 \times (.0[illegible])^2 \times 53/4.19 = .4$

$K_e = .7$ — Hydraulic Charts for the Selection of Highway Culverts Circular No. 5 Dec. 1965 pg. 4

$K_p = 0$ if bridge has no intermediate piers

$K_p = 0.05$ if bridge has intermediate piers — HEC-2 manual

2. XKOR = 1 + .4 + .7 + 0 = 2.1
3. COFQ = Coefficient of discharge = 3. — HEC-2 manual
4. RDLEN = Length of weir = 0. (0 if read off BT cards)
5. BWC = bottom width of bridge opening (inc. piers) = 15.8
6. BWP = total width of obstruction = 0. — field data
7. BAREA = bridge opening = ____
8. SS = side slope = 0
   (horizontal per 1 vertical unit)
9. ELCHU = Elevation of channel invert U/S side = 644.9
   (0 if equal to minimum elevation in previous X-sect.)
10. ELCHD = Elevation of channel invert D/S side = 644.9
    (0 if equal to minimum elevation in previous X-sect.)

SUBJECT	BY	CHK.	SHEET NO.	File Code No (Job No) Owner Project, Suffix
[illegible]	DATE 5/2/79	DATE	____ OF ____	[illegible]


HUD
2014-07


BRIDGE DETAIL
BELL BRANCH.
ELLEN RD.

F.R. II 947

A:P
M.E.
J.R

MAR: 26-1979 50.





CITY OF LIVONIA, MICHIGAN

BELL BRANCH

EXHIBIT 6

Computer Printouts

HEC-2 Backwater Analysis

with

Cross Section Plots

(See Separate Folder)

CITY OF LIVONIA, MICHIGAN

BELL BRANCH

EXHIBIT 7

Stream Profile

CITY OF LIVONIA, MICHIGAN

TARABUSI CREEK

EXHIBIT 8

Bridge Notes and Sketches

Bridge Location: 6 Mile Bridge (old) '68 Profile
Bridge Losses - SB Card Verification

REFERENCE

1. XK (Pier Shape Coefficient) 0 — HEC-2 manual

XKOR (Loss Coefficient) = 1.0 + Σk, Σk = $k_f + k_e + k_p$

where k_f = friction loss coefficient
k_e = entrance loss coefficient
k_p = loss from intermediate piers

Description of Bridge:

$K_f = 29.1\, n^2 L / R^{4/3}$ for English units

Area = 183 = _____ Wp = 72.2

$R = A/wp = 2.53$ $R^{4/3} = 3.46$ $L = 56$

n (composite) $= \frac{30}{72}(.04) + \frac{42}{72}(.015) = .025$

$K_f = 29.1 \times (.025)^2 \times 56 / 3.46 = .29$

6.1 / 30.

$K_e = .5$

Hydraulic Charts for the Selection of Highway Culverts Circular No. 5 Dec. 1965 pg. 49

$K_p = 0$ if bridge has no intermediate piers


$K_p = 0.05$ if bridge has intermediate piers — HEC-2 manual

SKEW BRIDGE $\Delta = 44°$
factor = .69

2. XKOR = 1 + .5 + .29 + 0 = 1.79
3. COFQ = Coefficient of discharge = .5 — HEC-2 manual
4. RDLEN = Length of weir = 200 (0 if read off BT cards)
5. BWC = bottom width of bridge opening (inc. piers): 20.7
6. BWP = total width of obstruction = _____ — field data
7. BAREA = bridge opening = 127
8. SS = side slope = _____ (horizontal per 1 vertical unit)
9. ELCHU = Elevation of channel invert U/S side = 619.3
(0 if equal to minimum elevation in previous X-sect.)
10. ELCHD = Elevation of channel invert D/S side = 619.3
(0 if equal to minimum elevation in previous X-sect.)

SUBJECT	BY	CHK.	SHEET NO	File Code No (Job No) Owner Project Suffix
Verification of 6 Mi Br.	T.G.		____ OF ____	AUD • 2014 • 17
	DATE 8-1-17	DATE		

BRIDGE SECTION T2
BENCH MARK NO 9: SQUARE CUT IN N.W. COR. OF CONC. WAND WALL ON N. SIDE OF SIX MILE & TARABUSI BRIDGE ELEV. 632.15
DATA SHEET T-T2



Old 6 Mile Bridge
for Profile Verification.
('68 Flood H.W.M.)
Scale: 1" = 20'


LOOK NORTH

TARABUSI BRIDGE AT SIX MILE RD.
Sta. 26+80

C.S. 2.

C.S. 3

CROSS SECTION T3
BENCH MARK NO 9: SQUARE CUT IN N.W.
TARABUSI BRIDGE AT



Wade Trim & Associates, Inc.
Civil Engineers • Land Surveyors
25185 GODDARD ROAD
TAYLOR, MICHIGAN 48180

WORK SHEET

Bridge Location: 6 Mile


Bridge Losses - SB Card

REFERENCE

1. XK (Pier Shape Coefficient) = 1.05 — HEC-2 manual

XKOR (Loss Coefficient) = 1.0 + Σk, $\Sigma k = k_f + k_e + k_p$

where k_f = friction loss coefficient
k_e = entrance loss coefficient
k_p = loss from intermediate piers



Description of Bridge:

$K_f = 29.1\, n^2 L / R^{4/3}$ for English units

Area = 581.6 = ____ Wp = 195.5

$R = A/wp = 2.97$ $R^{4/3} = 4.27$ $L = 88$

n (composite) $= \frac{.11}{147}(.013) + \left(\frac{30}{147}\right)(.035)$ $= .02$


$K_f = 29.1 \times (.02)^2 \times 88 / 4.27 = .24$

$K_e = .5$

Hydraulic Charts for the Selection of Highway Culverts Circular No. 5 Dec. 1965 pg. 49

$K_p = 0$ if bridge has no intermediate piers

$K_p = 0.05$ if bridge has intermediate piers — HEC-2 manual



$\frac{115 \cdot x}{2} = 131$

$x = 29.74$

2. XKOR = 1 + .24 + .5 + .05 = 1.79
3. COFQ = Coefficient of discharge = 3.0 — HEC-2 manual
4. RDLEN = Length of weir = 0 (0 if read off BT cards)
5. BWC = bottom width of bridge opening (inc. piers) = 32.8
6. BWP = total width of obstruction = 2 — field data
7. BAREA = bridge opening ~~inc. piers~~ = 582.
8. SS = side slope = 2.59 (horizontal per 1 vertical unit)
9. ELCHU = Elevation of channel invert U/S side = 617.9 (0 if equal to minimum elevation in previous X-sect.)
10. ELCHD = Elevation of channel invert D/S side = 617.9 (0 if equal to minimum elevation in previous X-sect.)

SUBJECT	BY	CHK	SHEET NO	File Code No (Job No) Owner Project Suffix
Livonia Hydr. for Levan Cr.	T.G.		___ OF ___	Hyd 2014 07
	DATE 3/15/06	DATE		


HUD 2014-07


BRIDGE DETAIL TARABUSI CREEK. CONT FROM PG #25

F.B. #947

A.P. M.S

MAR. 20-14





Bridge Location : Middlebelt

Bridge Losses - SB Card

REFERENCE

1. XK (Pier Shape Coefficient) 0 — HEC-2 manual

XKOR (Loss Coefficient) = 1.0 + Σk , Σk = $k_f + k_e + k_p$

where k_f = friction loss coefficient
k_e = entrance loss coefficient
k_p = loss from intermediate piers

Description of Bridge :

$K_f = 29.1\, n^2 L / R^{4/3}$ for English units

Area = 97.24 = _____ Wp = 43.5'

$R = A/wp = 2.24$ $R^{4/3} = 2.93$ $L = 88$

15.44
63 .63
15 .37

n (composite) = $\frac{34}{55}(.013) + \frac{21}{55}(.035) = .02$

$K_f = 29.1 \times (.02)^2 \times 88/2.93 = .35$

$K_e = .5$

Hydraulic Charts for the Selection of Highway Culverts Circular No. 5 Dec. 1965 pg. 49

$K_p = 0$ if bridge has no intermediate piers

$K_p = 0.05$ if bridge has intermediate piers — HEC-2 manual

Skew Bridge $\phi = 50°$

factor = .63


2. XKOR = 1 + .35 + .5 + 0 = 1.95
3. COFQ = Coefficient of discharge = 3. — HEC-2 manual
4. RDLEN = Length of weir = _____ (0 if read off BT cards)
5. BWC = bottom width of bridge opening (inc. piers) = 15.44
6. BWP = total width of obstruction = 0. — field data
7. BAREA = bridge opening inc. piers = 97.24 (has this been skewed?)
8. SS = side slope = 0.
   (horizontal per 1 vertical unit)
9. ELCHU = Elevation of channel invert U/S side = 622.6
   (0 if equal to minimum elevation in previous X-sect.)
10. ELCHD = Elevation of channel invert D/S side = 622.6
    (0 if equal to minimum elevation in previous X-sect.)

SUBJECT	BY	CHK	SHEET NO	File Code No (Job No) Owner • Project • Suffix
Livonia - Hydraulics Tarabus Creek	T.C		____ OF ____	Hud • 2014 • 07
	DATE 4/10/90	DATE		

SCALE 1" = 200 FT

25+20 C.L. 13

CROSS SECTION T 8
BENCH MARK NO. 1 [illegible]
TARABUSI BRIDGE AT SIX MILE [illegible]



Bridge Location: MERRIMAN

Bridge Losses - SB Card


REFERENCE

1. XK (Pier Shape Coefficient) 1.25 — HEC-2 manual

XKOR (Loss Coefficient) = 1.0 + ΣK, $\Sigma k = k_f + k_e + k_p$

where k_f = friction loss coefficient
k_e = entrance loss coefficient
k_p = loss from intermediate piers

Description of Bridge:



$k_f = 29.1\, n^2 L / R^{4/3}$ for English units

Area = 763.5 = _____ WP = 150

$R = A/wp$ 5.09 $R^{4/3} = 8.76$ $L = 74$


n (composite) $= \frac{17}{140}(.013) + \frac{23}{140}(.015) = .02$

$k_f = 29.1 \times (.02)^2 \times 74 / 8.76 = .10$

$k_e = .2$ — Hydraulic Charts for the Selection of Highway Culverts Circular No. 5 Dec. 1965 pg. 49


$k_p = 0$ if bridge has no intermediate piers

$k_p = 0.05$ if bridge has intermediate piers — HEC-2 manual



2. XKOR = 1 + .10 + .2 + 0 = 1.3
3. COFQ = Coefficient of discharge = 3.0 — HEC-2 manual
4. RDLEN = Length of weir = 0. (0 if read off BT cards)
5. BWC = bottom width of bridge opening (inc. piers) = 26.
6. BWP = total width of obstruction = 2. — field data
7. BAREA = bridge opening inc. piers = 793.7
8. SS = side slope = 2:28 (horizontal per 1 vertical unit)
9. ELCHU = Elevation of channel invert U/S side = 638. (0. if equal to minimum elevation in previous X-sect.)
10. ELCHD = Elevation of channel invert D/S side = 638. (0 if equal to minimum elevation in previous x-sect.)

SUBJECT	BY	CHK	SHEET NO.	File Code No (Job No) Owner Project Suffix
LIVONIA - HYD Ten. Lwic Co.	T G		___ OF ___	HWD 2014 • 07
	DATE 3/19/79	DATE		


3-19-34
MERRIMAN RD. BRIDGE
NEW BRIDGE

FORM 25-0
(313) 291-5400
Wade Trim & Associates Inc.
Civil Engineers • Land Surveyors
25185 GODDARD ROAD
TAYLOR, MICHIGAN 48180

WORK SHEET

Bridge Location: 7 MILE

Bridge Losses - SB Card


REFERENCE

1. XK (Pier Shape Coefficient) = 0 — HEC-2 manual

XKOR (Loss Coefficient) = 1.0 + Σk, $\Sigma k = k_f + k_e + k_p$

where k_f = friction loss coefficient
k_e = entrance loss coefficient
k_p = loss from intermediate piers

Description of Bridge:



$K_f = 29.1\, n^2 L / R^{4/3}$ for English units

Area = 134 = ____ Wp = 53.4

$R = A/wp = 2.51$ $R^{4/3} = 3.41$ $L = 61$

n (composite) = .02

$K_f = 29.1 \times (.02)^2 \times 61/3.41 = .21$

$K_e = .5$ — Hydraulic Charts for the Selection of Highway Culverts Circular No. 5 Dec. 1965 pg. 49

$K_p = 0$ if bridge has no intermediate piers

$K_p = 0.05$ if bridge has intermediate piers — HEC-2 manual


2. XKOR = 1 + .21 + .5 + 0 = 1.71
3. COFQ = Coefficient of discharge = 3.0 — HEC-2 manual
4. RDLEN = Length of weir = 0 (0 if read off BT cards)
5. BWC = bottom width of bridge opening (inc. piers) = 20
6. BWP = total width of obstruction = 0 — field data
7. BAREA = bridge opening inc. piers = 134.
8. SS = side slope = 0 (horizontal per 1 vertical unit)
9. ELCHU = Elevation of channel invert U/S side = 652.8 (0 if equal to minimum elevation in previous x-sect.)
10. ELCHD = Elevation of channel invert D/S side = 652.8 (0 if equal to minimum elevation in previous x-sect.)


SUBJECT	BY	CHK.	SHEET NO.	File Code No (Job No.) Owner Project Suffix
Tarabus. Creek Livonia-MI	T.G.		____ OF ____	HUD •2014 •07
	DATE 3/19/79	DATE		

HUD 2014-07

BRIDGE DETAIL TARABUSI CREEK.

FIB. # 974 A.P. M.S MAR 20-1979 35.





Bridge Location : FARMINGTON


Bridge Losses - SB Card

REFERENCE

1. XK (Pier Shape Coefficient) = 0 — HEC-2 manual

XKOR (Loss Coefficient) = 1.0 + ΣK, $\Sigma K = k_f + k_e + k_p$

where k_f = friction loss coefficient
k_e = entrance loss coefficient
k_p = loss from intermediate piers



Description of Bridge :

$K_f = 29.1\, n^2 L / R^{4/3}$ for English units

Area = 210 = ____ Wp = 74

$R = A/wp = 2.84$ $R^{4/3} = 4.02$ $L = 74$

n (composite) = .02

$K_f = 29.1 \times (.02)^2 \times 74/4.02 = .21$

$K_e = .5$ — Hydraulic Charts for the Selection of Highway Culverts Circular No. 5 Dec. 1965 pg. 49

$K_p = 0$ if bridge has no intermediate piers

$K_p = 0.05$ if bridge has intermediate piers — HEC-2 manual

2. XKOR = 1 + .21 + .5 + 0 = 1.71
3. COFQ = Coefficient of discharge = 3.0 — HEC-2 manual
4. RDLEN = Length of weir = 0 (0 if read off BT cards)
5. BWC = bottom width of bridge opening (inc. piers) = 30
6. BWP = total width of obstruction = 0 — field data
7. BAREA = bridge opening inc. piers = 210
8. SS = side slope = 0 (horizontal per 1 vertical unit)
9. ELCHU = Elevation of channel invert U/S side = 670.5 (0 if equal to minimum elevation in previous x-sect.)
10. ELCHD = Elevation of channel invert D/S side = 670.5 (0 if equal to minimum elevation in previous x-sect.)

SUBJECT	BY	CHK.	SHEET NO.	File Code No (Job No) Owner Project Suffix
Jervbusi cr. Livonia-Hyd.	I.b.		5 OF	Hyd •2014•07
	DATE 3/19/74	DATE		

FARMINGTON RD. OVER TARABUSI DRAIN
STA. 250+00
WB
PROP. GRADE
SCALE: HOR. 1"=20'
VERT. 1"=10'
650
600
550

URR.WO 5-26

CITY OF LIVONIA, MICHIGAN

TARABUSI CREEK

EXHIBIT 9

Computer Printouts

HEC-2 Backwater Analysis

with

Cross Section Plots

(See Separate Folder)

CITY OF LIVONIA, MICHIGAN

TARABUSI CREEK

EXHIBIT 10

Stream Profile

CITY OF LIVONIA, MICHIGAN

TRIBUTARY #1

EXHIBIT 11

Bridge Notes and Sketches

Wade Trim & Associates, Inc.
Civil Engineers • Land Surveyors
25185 GODDARD ROAD
TAYLOR, MICHIGAN 48180

WORK SHEET

Bridge Location: 6 Mile Rd. + Tributary #1
Bridge Losses - SB Card

REFERENCE

1. XK (Pier Shape Coefficient) 0 — HEC-2 manual

XKOR (Loss Coefficient) = 1.0 + ΣK, $\Sigma k = k_f + k_e + k_p$


where k_f = friction loss coefficient
k_e = entrance loss coefficient
k_p = loss from intermediate piers

Description of Bridge:

$K_f = 29.1 n^2 L / R^{4/3}$ for English units

Area = 86.4 = 86.4 Wp = 42.8
R = A/wp = 2.02 $R^{4/3}$ = 2.55 L = 116
n (composite) = .02

$K_f = 29.1 \times (.02)^2 \times 116/2.55 = .53$



$K_e = .5$ — Hydraulic Charts for the Selection of Highway Culverts Circular No. 5 Dec. 1965 pg. 4

$K_p = 0$ if bridge has no intermediate piers

$K_p = 0.05$ if bridge has intermediate piers — HEC-2 manual


2. XKOR = 1 + .53 + .5 + 0 = 2.03
3. COFQ = Coefficient of discharge = 3.0 — HEC-2 manual
4. RDLEN = Length of weir = 0 (0 if read off BT cards)
5. BWC = bottom width of bridge opening (inc. piers): 16
6. BWP = total width of obstruction = 0 — field data
7. BAREA = bridge opening = 86.4
8. SS = side slope = 0
(horizontal per 1 vertical unit)
9. ELCHU = Elevation of channel invert U/S side = 657.5
(0 if equal to minimum elevation in previous X-sect.)
10. ELCHD = Elevation of channel invert D/S side = 656.6
(0 if equal to minimum elevation in previous X-sect.)

SUBJECT	BY	CHK	SHEET NO	File Code No (Job No.) Owner Project Suffix
Trib. #1, 6 Mile Bridge, Hydraulics	T.G.			HUD •2014 •07
	DATE 8-15	DATE	___ OF ___	

HUD 20140S

Bridge Detail w/ 4 Drain &


6 Mile Rd.



FB 941

2-6-78 EDW MN

10



8"WC x 24" DEEP FOOTING WALL ALL AROUND

#4 -12 o/c EACH WAY

SOD. SODDED INVERT

67.50

24"

8"

2 #4 CONT

½" EXP. JT

#4 @ o/c

#5 @ o/c

OPAQUE ANTI-VAPOR

2-#4

ALL CONCRETE 3500 PSI

4'-0" Min

2'-6"

KEYWAY

#5 - 12" o/c

#4 12" o/c

1'-3"

6'-3"

CONCRETE WEIR

1" = 1'

SECTION A-A

SECNO 7975

File no. 2269.31
Livonia, Wayne Co.

From Sheffield Subd.
McNeely, Lincoln, &
Schroeder Inc.
4-14-75 sheet 1-B

As Built 9/10/76 8"

CITY OF LIVONIA, MICHIGAN

TRIBUTARY #1

EXHIBIT 12

Computer Printouts

HEC-2 Backwater Analysis

with

Cross Section Plots

(See Separate Folder)

CITY OF LIVONIA, MICHIGAN

TRIBUTARY #1

EXHIBIT 13

Stream Profile

CITY OF LIVONIA, MICHIGAN

BEITZ DRAIN

EXHIBIT 14

Bridge Notes and Sketches

Bridge Location: 6 Mile Rd.

Bridge Losses - SB Card


REFERENCE

1. XK (Pier Shape Coefficient) 0 — HEC-2 manual

XKOR (Loss Coefficient) = 1.0 + ΣK, $\Sigma k = k_f + k_e + k_p$

where. k_f = friction loss coefficient
k_e = entrance loss coefficient
k_p = loss from intermediate piers

looking D/S



Description of Bridge:

$K_f = 29.1\, n^2 L / R^{4/3}$ for English units

Area = 89.3 = ____ WP = 38.2

$R = A/wp = 2.34$ $R^{4/3} = 3.10$ $L = 117$

n (composite) = .022

$K_f = 29.1 \times (.022)^2 \times 117 \;/\; 3.1 = .53$

$K_e = .5$

Hydraulic Charts for the Selection of Highway Culverts Circular No. 5 Dec. 1965 pg. 49

$K_p = 0$ if bridge has no intermediate piers


$K_p = 0.05$ if bridge has intermediate piers — HEC-2 manual

2. XKOR = 1 + .53 + .5 + 0 = 2.03
3. COFQ = Coefficient of discharge = 3.0 — HEC-2 manual
4. RDLEN = Length of weir = 0.0 (0 if read off BT cards)
5. BWC = bottom width of bridge opening (inc. piers) = 12.75
6. BWP = total width of obstruction = 0 — field data
7. BAREA = bridge opening inc. piers = 89.3
8. SS = side slope = 0.0 (horizontal per 1 vertical unit)
9. ELCHU = Elevation of channel invert U/S side = 643.8 (0 if equal to minimum elevation in previous x-sect.)
10. ELCHD = Elevation of channel invert D/S side = 644.3 (0 if equal to minimum elevation in previous x-sect.)

SUBJECT	BY	CHK.	SHEET NO	File Code No (Job No) Owner Project Suffix
Livonia Dept. of Drain 6 Mile Bridge	J. G.		____ OF ____	Hud • 2004 • 07
	DATE 2-18-99	DATE		


HUD 2014-05

BRIDGE DETAIL BEITER DRAIN & 6 MILE RD.



2-8-78 REVISED MN

M.C.R.C. DATUM




UPSTREAM (20+39) 20+64 & 21+34 & 21+56

DOWNSTREAM VIEW (TYP) FACING DOWNSTREAM

(VIEWS OF BRIDGE EXTENSION)

ORIGINAL BRIDGE @ STA'S 20+64 & 21+34

FACING DOWNSTREAM



HWY 204-05

BRIDGE & VALLEY SECTIONS BELTZ DRAIN


STA	+	HI	−	ELEV	
BM				681.67	
	0.25	681.92			
EX DRAIN BOTTOM			23.47	658.45	
OUTSIDE TOP CULV			17.63	664.29	
	14.19	678.48			
T.P.			5.72	672.76	
	1.15	673.91			
EX DRAIN BOTTOM			22.66	651.25	
44R			13.70	660.21	
36L			13.90	660.01	
TOP HW @ S END 96"			12.92	660.99	- 9.76 =
	12.35	673.34			
			CONT ON PG 19		

FB

2-8-79 REVISED

WARE DRIVE


UPSTREAM END 96" CULV.



ADD ON F.H. @ N.W. COR. MYRON DR. & CURTIS (FRANCONIA SUBD'N - ORCHARD-PARKE-HAIG-MCCLEMENT INC)

664.29
- 8.73
655.56 INV 96"

DOWNSTREAM END 96" CULV (0+00)



651.23 INV 96"

D.W.


VBB

Wade Trim & Associates, Inc.
Civil Engineers • Land Surveyors
25185 GODDARD ROAD
TAYLOR, MICHIGAN 48180

WORK SHEET

REFERENCE

u/s End Francaville Culvert



SUBJECT Livonia-Hydraulics	BY	CHK.	SHEET NO.	File Code No (Job No) Owner • Project • Suffix
	DATE	DATE	____OF____	HUD • 2014 • 07

REFERENCE


lost Ref.

King & Brater's Handbook of Hydraulics

4th Ed. by Curtis

Beitz Drain, Francaville
Culvert Bend Loss Calculations

$$\text{Head loss at bend} = .25\sqrt{\frac{\alpha}{90^\circ}} \cdot \frac{V^2}{2g}$$



$$V = \frac{1.49}{n} S^{1/2} R^{2/3}$$


$$R = \frac{A}{P} = \frac{16\pi}{8\pi} = 2$$

$$S = .0039$$

$$V = \frac{1.49}{.013} (.0039)^{1/2} \cdot 2^{2/3}$$

$$n = .013$$

$$V = 114 \text{ ft/sec}$$



Location Sketch

Bend 1

$\alpha = 18^\circ$

$$H_L = .25\sqrt{\frac{18}{90}} \cdot \frac{11.4^2}{32.2} = .23'$$ 3

Bend 2

$\alpha = 12^\circ$ $\quad H_L = .25\sqrt{\frac{12}{90}} \cdot \frac{11.4^2}{32.2} = .18'$

.53

Bend 3

$\alpha = 43^\circ$ $\quad H_L = .25\sqrt{\frac{43}{90}} \cdot \frac{11.4^2}{32.2} = .35'$

SUBJECT	BY	CHK.	SHEET NO.	File Code No (Job No) Owner Project Suffix
Livonia - Hydraulics	T. G.		____ OF ____	Hud • 2014 • 07
	DATE 8-27	DATE		

CITY OF LIVONIA, MICHIGAN

BEITZ DRAIN

EXHIBIT 15

Computer Printouts

HEC-2 Backwater Analysis

with

Cross Section Plots

(See Separate Folder)

CITY OF LIVONIA, MICHIGAN

BEITZ DRAIN

EXHIBIT 16

Stream Profile

CITY OF LIVONIA, MICHIGAN

TRIBUTARY #1

EXHIBIT 17


Weir Calculations

REFERENCE

Channel D/S of Weir (Rating Curve)

$$Q = \frac{1.486}{n} A R^{2/3} S^{1/2}$$

$S = .0076$?
Invert = El 672.9
$n = .03$



Scale: 1" = 2' Vertical
1" = 20' Horiz.

Section ① – Area = 31.24 ft²
W.P. = 44.09 ft

Section ② – Area = 159 ft²
WP = 18.97

Q @ Elev 673.32


$$Q = \frac{1.486}{.03}(31.24)\left(\frac{31.24}{44.09}\right)^{2/3}(.0076)^{1/2} = 107 \text{ cfs}$$

Q @ Elev. 676.32

$$Q = \frac{1.486}{.03}(31.24 + 159)\left[\frac{(31.24+159)}{(44.09+18.97)}\right]^{2/3}(.0076)^{1/2} = 1078$$

★ Q = 1715 cfs

SUBJECT	BY	CHK.	SHEET NO.	File Code No (Job No) Owner • Project • Suffix
Sheridan's Subdivision Livonia FIS - Trib #1	WJ Weaver		1 OF	
	DATE 7/21/99	DATE		



* Reduced 100yr Flowrate from Pg. 10 of These Calculations

Froude # = $\frac{V}{\sqrt{g D_H}}$

Flow Regime for Normal Depth

$D_H = \frac{\text{Area}}{\text{Top width}}$

Top width = 62.6'

Area = 62 ft²

$\therefore$ Fr. # = $\frac{4.10}{\sqrt{(32.2)\frac{62.0}{62.6}}} = 1.17 > 1.0$ [Supercritical]

LIVONIA FIS


TRIB #1

WJ Woos 7/3/79

46 1320
KEUFFEL & ESSER CO MADE IN U.S.A.

REFERENCE

Rating Curve for Weir



Use Weir flow equation

$Q = C L H^{3/2}$

"C" Values from King + Brater, Handbook of Hydraulics, McGraw-Hill, N.Y., 5th Edit., 1963, Pg. 5-46

① $Q = 0$ @ Elev. 675.0

② Try Elevation 675.5 :

$Q = C L H^{3/2} = 2.63(54).5^{3/2} = 47.3$ cfs

③ Try Elevation 676.0 :

$Q = (2.68)54(1)^{3/2} = 144.7$ cfs

④ Try Elevation 676.5 :

$Q = (2.65)\,54\,(1.5)^{1.5} = 262.9$ cfs

⑤ Try Elevation 676.83:

$Q = (2.64)\,54\,(1.83)^{1.5} = 353$ cfs

⑥ Try Elevation 677.0:

$Q = (2.64)\,54\,(2.0)^{1.5} = 403$ cfs

SUBJECT	BY	CHK.	SHEET NO.	File Code No (Job No.) Owner • Project • Suffix
Livonia FIS - Trib #1	W.J. Weaver		3 OF	
	DATE 7/3/79	DATE		

REFERENCE

Rating Curve for Weir (continued)

⑦ Try Elevation 677.5 :

$$Q = (2.64)\,54\,(2.5)^{1.5} = \underline{564 \text{ cfs}}$$

⑧ Try Elevation 678.0 :

$$Q = (2.64)\,(54)\,(3.0)^{1.5} = \underline{741 \text{ cfs}}$$

Comment:

① Normal Depth Analysis D/S of the weir indicates that weir submergence will not occur until a flowrate of 1430 cfs.

② The above weir flow rating curve will be combined with the rating curve for the low flow pipe (calculations to follow) to obtain a rating curve for the control section. Also, distribution of flow between the two channels will be determined.

REFERENCE

Low Flow Pipe – Rating Curve

The low flow pipe (53" x 34" E.C.P.) has a slope of 0; thus, the following analysis will be used to develop a rating curve:

① Inlet Control Eleu./Flows shall be computed based on Bureau of Public Roads #5, chart #3, Pg. 5-23.

② Pressure Flow Eleu./Flows shall be computed based on the pressure flow equation as presented in the HEC 2, Users Manual by the U.S. Army, Corps of Engineers.

③ The highest/lowest Eleu/Flow resulting from ① + ② above will be used for the rating curve.

The pressure flow equation is as follows:

$$Q = A\sqrt{\frac{2gH}{K}}, \text{ where } K_{friction} = \frac{29.1\,n^2 L}{R^{4/3}}$$

$A = 10.2\ ft^2$, $R_H = .875$, $n = .015$ (Trash Rack) } Concrete Pipe Design Manual

Thus $K_{friction} = \dfrac{29.1(.015)^2\ 350'(long)}{(.875)^{4/3}}$

$\therefore K_f = 2.74$

Total $K = K_{entrance} + K_{friction} + K_{exit} = .2 + 2.74 + 1.0 = 3.94$

$Q = 10.2\sqrt{\frac{64.4(H)}{3.94}} = 10.2\sqrt{16.35\,H}$, where H is variable.

SUBJECT	BY	CHK.	SHEET NO	File Code No (Job No) Owner • Project • Suffix
Livonia-FIS, Trib #1	WJ Weaver		5 OF	
	DATE 7/3/80	DATE		

REFERENCE

Low Flow Pipe - Rating Curve

$D = 34" = 2.83'$

(1) Elevation 674.0 :

$Q = 0$

(2) Elevation 675.0 :

Inlet Control -

$\frac{H_w}{d} = \frac{1.0}{2.83} = .35 \quad \therefore Q = 9 cfs$

Pressure Flow -

$H_w = 1.0 \qquad Q = 10.2\sqrt{16.35(.5)} = 29 cfs$

Assume TW = .5

Use $Q = 9 cfs$

(3) Elevation 675.5 :

Inlet Control -

$\frac{H_w}{d} = \frac{1.5}{2.83} = .53 \quad \therefore Q = 19 cfs$

Pressure Flow -

$H_w = 1.5 \qquad Q = 10.2\sqrt{(16.35).7} = 35 cfs$

Assume TW = .8

Use $Q = 19 cfs$

(4) Elevation 676.0 :

Inlet Control -

$\frac{H_w}{d} = \frac{2.0}{2.83} = .71 \quad \therefore Q = 31 cfs$

Pressure Flow -

$H_w = 2.0 \qquad Q = 10.2\sqrt{16.35(2.0)} = 41 cfs$

Assume Tailwater = 1.0'

Use $Q = 31 cfs$

SUBJECT	BY	CHK.	SHEET NO	File Code No (Job No.) Owner • Project • Suffix
Livonia FIS - Trib #1	DATE 9/12/2000	DATE	6 OF	

REFERENCE

Low Flow Pipe - Rating Curve

(5.) Elevation 676.5 :

Inlet Control -

$\frac{H_w}{d} = \frac{2.5}{2.83} = .88 \quad \therefore Q = 45 cfs$

Pressure Flow -

$H_w = 2.5 \quad Q = 10.2\sqrt{15.35(1.3)} = 47 cfs$

Assume $T_w = 1.2$

Use $Q = 45 cfs$.

(6) Elevation 676.83 :

Inlet Control -

$\frac{H_w}{d} = \frac{2.83}{2.83} = 1.0 \quad \therefore Q = 52 cfs$

Pressure Flow -

$H_w = 2.83 \quad Q = 10.2\sqrt{16.35(1.50)} = 52 cfs$

Assume $T_w = 1.3$

Use $Q = 52 cfs$.

(7) Elevation 677.0 :

Inlet Control -

$\frac{H_w}{d} = \frac{3}{2.83} = 1.06 \quad \therefore Q = 58 cfs$

Pressure Flow -

$H_w = 3.0$

Assume $T_w = 1.5$

$Q = 10.2\sqrt{16.35(1.5)} = 52 cfs.$

Use $Q = 52 cfs$

(8.) Elevation 677.5 :

Inlet Control -

$H_w/d = \frac{3.5}{2.83} = 1.24 \quad \therefore Q = 72 cfs$

Pressure Flow -

$H_w = 3.5 \quad Q = 10.2\sqrt{16.35(2.0)} = 58 cfs$

Assume $T_w = 1.5$

Use $Q = 58 cfs$

SUBJECT	BY	CHK.	SHEET NO	File Code No. (Job No.) Owner • Project • Suffix
Livonia TIS - Trib #2	DATE 7/9/14	DATE	7 OF	

REFERENCE

Low Flow Pipe - Rating Curve

(a) Elevation 678.0 :

Inlet Control -

$$H_w/d = 4.0/2.83 = 1.41 \quad \therefore \quad Q = 85 \text{ cfs}$$


Pressure Flow -

$H_w = 4.0$

Assume $T_w = 1.5$

$$Q = 10.2\sqrt{16.35(2.5)} = 65 \text{ cfs}$$

Use $Q = 65$ cfs



46 1320
KE 10 X 10 TO ½ INCH 7 X 10 INCHES
KEUFFEL & ESSER CO MADE IN U.S.A.

Conclusion

REFERENCE

① During 10, 50, 100 + 500 yr. storms, the following division of flow will occur:

Storm (Yr)	Qi (cfs)	Weir (Main Channel) (cfs)	Lo. Flow Pipe (Old channel) (cfs)	Flood Elev.
10	210	175	37	676.15
50	370	315	50	676.70
100	460	410	53	677.00
500	680	610	60	677.65

② The old channel which the low flow pipe discharges into will only handle a minor amount of flow (60 cfs during 500 yr storm); therefore, a floodway will be established at the banks of the old channel in addition to the floodway shown for the new channel.

③ Flow D/S of the Weir is super critical and well within the banks @ Elev. 673.9. (See Pg 2 for this calculation).

SUBJECT	BY	CHK.	SHEET NO.	File Code No. (Job No.) Owner • Project • Suffix
Livonia FIS - Trib #1	DATE 7/3/79	DATE	10 OF	

CITY OF LIVONIA, MICHIGAN

TARABUSI CREEK, TRIBUTARY #1,

and BEITZ DRAIN

EXHIBIT 18

Mean Annual Elevation Calculations

Wade Trim & Associates, Inc.
Civil Engineers • Land Surveyors
25185 GODDARD ROAD
TAYLOR, MICHIGAN 48180

WORK SHEET

REFERENCE

Exhibit 18

Mean Annual Elevation Determination on Bell Branch at Torabusi Creek


SECNO 3950 200' D/S Confluence
4150 Confluence of Bell Branch + Torebusi Creek
SECNO 4520 Valley Section U/S Confluence

	10YR	Q	50 YR	Q	100 YR	Q	500 YR	Q
3950 Curve 1	620.76	1650	622.35	2900	623.29	3600	625.91	5500
4120 Curve 2	621.58	1100	622.79	1720	623.61	2120	626.08	3120


1. Plot Frequency vs Flow for the 4 storms at SECNO 3950 and SECNO 4520 on Bell Branch.
2. Calculate Mean Annual Flow at each SECNO.
3. Plot Stage Discharge Curves for SECNO 3950 and SECNO 4920.
5. Calculate Mean Annual Elevation at the Confluence of Torabusi Creek and Bell Branch by straight line interpolation.

$$M.A.E. = 619.6 + \left[\left(\frac{4150 - 3950}{4520 - 4150}\right) \times 1.1\right] = 620.0$$

SUBJECT	BY	CHK.	SHEET NO	File Code No (Job No) Owner Project Suffi
M.A.E. determination Torabusi Cr. Livonia - Wayne	T.E.		1 OF 9	HUD • 20 LI • 37
	DATE 7/21/89	DATE		


PROBABILITY X 2 LOG CYCLES
KEUFFEL & ESSER CO MADE IN U.S.A.
46 8040
RECURRENCE INTERVAL (YEARS)
10 50 100 500
99 99 99.9 99.8 99 98 95 90 80 70 60 50 40 30 20 10 5 2 1 0.5 0.2 0.1 0.05 0.01
0.01 0.05 0.1 0.2 0.5 1 2 5 10 20 30 40 50 60 70 80 90 95 98 99 99.8 99.9 99.99
FLOW (C.F.S.)
10 9 8 000 7 000 6 000 5 000 4 000 3 000 2000 1000 900 800 700 600 500 4 3 2 1
MEAN ANNUAL
FLOW DETERMINATION
FOR BELL BRANCH
AT TARABUSI CREEK
CURVE 1
CURVE 2
700
600

K&E 10 X 10 TO ½ INCH 7 X 10 INCHES
KEUFFEL & ESSER CO MADE IN U.S.A.



Wade, Trim & Associates, Inc.
Civil Engineers • Land Surveyors
25185 GODDARD ROAD
TAYLOR, MICHIGAN 48180

WORK SHEET

REFERENCE


Mean Annual Flow & Elev. determination for Bell Branch at Tributary #1

	FLOW	ELEV. & SECNO 28628 Bell Branch
10 YR	800	644.1
50	1410	645.73
100	1740	646.39
500	2610	647.84

Mean Annual Flow = 350 cfs


Mean Annual Elev. = 642.5

SUBJECT	BY	CHK.	SHEET NO	File Code No (Job No) Owner Project Suffix
Livonia - Hydraulics	T. G.		4 OF 9	MUD • 2014 • 07
	DATE 8/27/79	DATE		


PROBABILITY 2 LOG CYCLES
KEUFFEL & ESSER CO MADE IN U.S.A.
46 8040
RETURN PERIOD 2.33 10 50 100 500
(YEARS)
MEAN ANNUAL FLOW
DETERMINATION FOR
B.F.I. BRANCH AT
CONFLUENCE WITH
TRIBUTARY "A".
FLOW (C.F.S.)
350
99 99 99 9 99 8 99 98 95 90 80 70 60 50 40 30 20 10 5 2 1 0.5 0.2 0.1 0.05 0 01
0 01 0 05 0 1 0 2 0.5 1 2 5 10 20 30 40 50 60 70 80 90 95 98 99 99 8 99 9 99 99
10 9 8 7 6 5 4 3000 2000 1 000 900 800 700 600 500 400 300 200 100
1 9 8 7 6 5 4 3 2 1

b/s

10 X 10 TO ½ INCH 7 X 10 INCHES
KEUFFEL & ESSER CO MADE IN U.S.A.



Wade Trim & Associates, Inc.
Civil Engineers • Land Surveyors
25185 GODDARD ROAD
TAYLOR, MICHIGAN 48180

WORK SHEET

REFERENCE

Mean Annual Flow and Elevation Determination for Bell Branch of Berlz Drain


	Flow (cfs)	Elev.
10 YR	1110	640.61
50	1720	641.81
100	2120	642.33
500	3120	644.19

& SCCNO 24096 Bell Branch

Mean Annual Flow = 550 cfs

Mean Annual Elev. = 639.8

SUBJECT Livonia - Hydraulics | BY T.G. | DATE 8/27/79 | CHK. | DATE | SHEET NO. 2 OF 9 | File Code No. (Job No.) Owner Project Suffix 7405-2014-07


KEUFFEL & ESSER CO
99.99 99 9 99.8 99 98 95 90 80 70 60 50 40 30 20 10 5 2 1 0.5 0.2 0 1 0.05 0 01
RATIO P-BION 2.33
(YEARS)
MEAN ANNUAL FLOW
DETERMINATION FOR
BEAVER CREEK AT
BEAVER DAM
FLOW (C.F.S.)
Y = 555
10 9 8 7 6 5 000 4 000 3 000 2 000 1 000 900 800 700 600 500 400 300 200 less
0.01 0.05 0.1 0 2 0 5 1 2 5 10 20 30 40 50 60 70 80 90 95 98 99 99 8 99 9 99 99

10 X 10 TO 1 INCH 5 X 5 INCHES
KEUFFEL & ESSER CO MADE IN U.S.A.

STAGE DISCHARGE CURVE FOR MEAN ANNUAL ELEVATION AT REITZ DRAIN

STAGE (FT.)

6.84
6.83
6.82
6.81
6.80
6.99
9.50
ELEV. 6398

500 1000 1500 2000 2500 3000 3500 4000

FLOW (C.F.S.)


6/6

CITY OF LIVONIA, MICHIGAN

UPPER ROUGE RIVER

EXHIBIT 19

Rating Curve


EXHIBIT 19
Rating Curve
Upper Range River
633.0
632.0
631.0
630.0
629.0
628.0
627.0
626.0
625.0
624.0
630.8
4200 500 YR
627.3
2160 50 YR
Rating Curve
from SECND
22 DAS, Redford
Twp. FCS
0
1000
2000
3000
4000
5000
6000
Stage (Feet, N.S.V.D.)
Discharge (cfs)
46 1320
10 X 10 TO ½ INCH
7 X 10 INCHES
KEUFFEL & ESSER CO
MADE IN U.S.A.


CITY OF LIVONIA, MICHIGAN

BELL BRANCH

EXHIBIT 20

Rating Curve

10 X 10 TO ½ INCH 7 X 10 INCHES
KEUFFEL & ESSER CO MADE IN U.S.A.



1) COUNTY: Wayne

2) STUDY NAME: City of Livonia

3) WATERCOURSE: Upper Rouge

4) DOCUMENT TYPE: Summary

FORM 6413

HEC2 RELEASE DATED NOV 76 UPDATED AUG1977
ERROR CORR - 01,02
MODIFICATION - 50,51,52,53

NOTE- ASTERISK (*) AT LEFT OF CROSS-SECTION NUMBER INDICATES MESSAGE IN SUMMARY OF ERRORS LIST

UPPER ROUGE LIVONIA CITY

SUMMARY PRINTOUT TABLE 150

SECNO	XLCH	ELTRD	ELLC	ELMIN	Q	CHSEL	CRIWS	EG	10K*S	VCH	AREA	.01K
22865.000	0.0	0.0	0.0	620.20	1160.00	625.78	0.0	627.01	79.02	9.17	155.71	130.49
22865.000	0.0	0.0	0.0	620.20	2160.00	627.80	0.0	629.63	75.87	11.42	257.08	247.98
22865.000	0.0	0.0	0.0	620.20	2690.00	628.69	0.0	630.78	74.74	12.32	308.43	311.15
22865.000	0.0	0.0	0.0	620.20	4200.00	630.80	0.0	633.56	73.64	14.40	446.59	489.44
22895.000	30.00	0.0	0.0	620.20	1160.00	625.95	0.0	627.33	87.36	9.42	123.13	124.11
22895.000	30.00	0.0	0.0	620.20	2160.00	627.72	0.0	630.28	122.79	12.66	168.02	194.93
22895.000	30.00	0.0	0.0	620.20	2690.00	628.83	0.0	631.03	57.16	12.46	316.99	355.81
22895.000	30.00	0.0	0.0	620.20	4200.00	630.03	630.09	633.91	60.70	14.97	440.96	539.09
22935.000	40.00	631.20	627.20	620.20	1160.00	626.55	0.0	627.65	41.99	8.43	137.60	179.00
22935.000	40.00	631.20	627.20	620.20	2160.00	630.66	0.0	631.51	17.13	7.86	436.76	521.83
22935.000	40.00	631.20	627.20	620.20	2690.00	631.97	0.0	632.91	16.37	8.37	540.67	664.78
22935.000	40.00	631.20	627.20	620.20	4200.00	633.77	0.0	635.26	22.05	10.76	695.60	894.34
22985.000	50.00	0.0	0.0	620.30	1160.00	627.46	0.0	627.96	24.69	6.26	302.94	233.43
22985.000	50.00	0.0	0.0	620.30	2160.00	631.24	0.0	631.70	13.33	6.30	717.26	491.64
22985.000	50.00	0.0	0.0	620.30	2690.00	632.71	0.0	633.13	11.09	6.29	977.12	807.03
22985.000	50.00	0.0	0.0	620.30	4200.00	635.12	0.0	635.63	11.57	7.20	1398.85	1234.99
23775.000	790.00	0.0	0.0	620.40	1160.00	629.31	0.0	629.46	11.71	4.06	749.94	339.05
23775.000	790.00	0.0	0.0	620.40	2160.00	632.54	0.0	632.66	8.39	4.30	1380.50	745.72
23775.000	790.00	0.0	0.0	620.40	2690.00	633.66	0.0	634.01	7.08	4.49	1674.79	956.21
23775.000	790.00	0.0	0.0	620.40	4200.00	636.39	0.0	636.55	6.01	5.11	2515.26	1483.84
24852.000	1077.00	0.0	0.0	625.50	1160.00	631.30	0.0	631.69	42.77	5.78	357.52	177.36
24852.000	1077.00	0.0	0.0	625.50	2160.00	633.87	0.0	634.23	27.05	6.02	708.04	415.34
24852.000	1077.00	0.0	0.0	625.50	2690.00	635.05	0.0	635.40	22.64	6.06	906.32	565.35
24852.000	1077.00	0.0	0.0	625.50	4200.00	637.51	0.0	637.87	19.15	6.55	1396.76	969.70
25052.000	200.00	0.0	0.0	625.60	1160.00	632.24	0.0	632.46	21.74	4.58	420.28	248.78
25052.000	200.00	0.0	0.0	625.60	2160.00	634.57	0.0	634.74	13.73	4.53	878.08	502.95
25052.000	200.00	0.0	0.0	625.60	2690.00	635.67	0.0	635.83	11.36	4.47	1097.86	797.99
25052.000	200.00	0.0	0.0	625.60	4200.00	638.07	0.0	638.24	9.37	4.72	1578.54	1371.59
25108.000	56.00	633.70	629.30	625.60	1160.00	634.48	0.0	634.54	4.18	2.48	860.96	567.55
25108.000	56.00	633.70	629.30	625.60	2160.00	635.77	0.0	635.87	6.93	3.52	1119.32	820.66
25108.000	56.00	633.70	629.30	625.60	2690.00	636.40	0.0	536.62	7.09	3.91	1243.79	967.79
25108.000	56.00	633.70	629.30	625.60	4200.00	638.50	0.0	638.65	7.95	4.45	1665.34	1429.54

SECNO	XLCH	ELTRD	ELLC	ELMIN	Q	CHSEL	CRIWS	EG	10K*S	VCH	AREA	.01K
25183.000	75.00	0.0	0.0	625.70	1160.00	634.46	0.0	634.66	11.47	3.95	465.51	342.58
25183.000	75.00	0.0	0.0	625.70	2160.00	635.71	0.0	636.11	20.52	5.02	714.97	476.78
25183.000	75.00	0.0	0.0	625.70	2690.00	636.32	0.0	636.78	22.91	6.42	868.14	561.98
25183.000	75.00	0.0	0.0	625.70	4200.00	638.44	0.0	638.89	20.07	6.84	1424.94	937.54
25628.000	445.00	0.0	0.0	623.70	1160.00	634.79	0.0	634.96	4.92	3.53	511.25	522.75
25628.000	445.00	0.0	0.0	623.70	2160.00	636.32	0.0	636.61	8.08	4.98	956.72	759.74
25628.000	445.00	0.0	0.0	623.70	2690.00	637.00	0.0	637.32	8.69	5.38	1206.04	912.70
25628.000	445.00	0.0	0.0	623.70	4200.00	639.04	0.0	639.33	7.76	5.66	2071.94	1507.65
26038.000	410.00	0.0	0.0	624.90	1160.00	635.04	0.0	635.19	3.05	2.95	731.18	663.82
26038.000	410.00	0.0	0.0	624.90	2160.00	636.69	0.0	636.89	5.31	4.32	1017.37	937.22
26038.000	410.00	0.0	0.0	624.90	2690.00	637.37	0.0	637.62	6.33	4.90	1151.63	1069.33
26038.000	410.00	0.0	0.0	624.90	4200.00	639.29	0.0	639.63	7.86	6.03	1536.50	1497.72
26088.000	50.00	0.0	0.0	625.00	1160.00	635.02	0.0	635.18	4.85	3.00	640.88	526.65
26088.000	50.00	0.0	0.0	625.00	2160.00	636.70	0.0	636.94	6.31	5.00	977.04	820.02
26088.000	50.00	0.0	0.0	625.00	2690.00	637.40	0.0	637.66	7.59	5.48	1116.95	976.60
26088.000	50.00	0.0	0.0	625.00	4200.00	639.37	0.0	639.60	8.26	6.31	1511.54	1461.01
26184.000	96.00	634.90	633.40	625.00	1160.00	635.83	0.0	635.96	3.06	3.19	802.60	661.31
26184.000	96.00	634.90	633.40	625.00	2160.00	637.04	0.0	637.24	5.78	4.69	1045.05	890.65
26184.000	96.00	634.90	633.40	625.00	2690.00	637.71	0.0	637.94	6.62	5.21	1177.95	1045.31
26184.000	96.00	634.90	633.40	625.00	4200.00	639.59	0.0	639.80	7.62	6.12	1556.30	1521.70
26234.000	50.00	0.0	0.0	625.10	1160.00	635.94	0.0	635.97	0.77	1.55	1634.06	1323.95
26234.000	50.00	0.0	0.0	625.10	2160.00	637.24	0.0	637.30	1.66	2.65	1959.90	1684.52
26234.000	50.00	0.0	0.0	625.10	2690.00	637.93	0.0	638.00	2.02	2.03	2139.16	1891.68
26234.000	50.00	0.0	0.0	625.10	4200.00	639.84	0.0	639.96	2.75	3.63	2576.96	2531.50
26860.000	626.00	0.0	0.0	624.50	1160.00	636.00	0.0	636.01	0.72	1.39	2044.69	1371.03
26860.000	626.00	0.0	0.0	624.50	2160.00	637.36	0.0	637.39	1.42	2.12	2474.80	1811.06
26860.000	626.00	0.0	0.0	624.50	2690.00	638.08	0.0	638.11	1.70	2.41	2707.70	2064.52
26860.000	626.00	0.0	0.0	624.50	4200.00	640.05	0.0	640.10	2.19	3.02	3372.53	2841.15
28232.000	1372.00	0.0	0.0	628.00	1160.00	636.11	0.0	636.35	11.35	4.06	446.58	344.38
28232.000	1372.00	0.0	0.0	628.00	2160.00	637.62	0.0	637.95	14.27	5.22	793.59	571.79
28232.000	1372.00	0.0	0.0	628.00	2690.00	638.39	0.0	638.74	14.03	5.50	988.08	716.22
28232.000	1372.00	0.0	0.0	628.00	4200.00	640.45	0.0	640.78	12.05	5.87	1573.61	1209.60
28233.000	1.00	635.00	633.50	628.00	1160.00	636.11	0.0	636.36	57.20	4.42	398.04	153.38
28233.000	1.00	635.00	633.50	628.00	2160.00	637.79	0.0	638.00	40.83	4.48	787.89	338.02
28233.000	1.00	635.00	633.50	628.00	2690.00	638.60	0.0	638.79	34.51	4.43	994.79	457.93
28233.000	1.00	635.00	633.50	628.00	4200.00	640.69	0.0	640.84	23.51	4.28	1613.76	886.16
28240.000	7.00	635.00	633.50	628.00	1160.00	636.16	0.0	636.40	54.24	4.33	408.68	157.50
28240.000	7.00	635.00	633.50	628.00	2160.00	637.83	0.0	638.02	40.07	4.45	793.70	341.21
28240.000	7.00	635.00	633.50	628.00	2690.00	638.63	0.0	638.81	34.14	4.41	998.85	460.41
28240.000	7.00	635.00	633.50	628.00	4200.00	640.70	0.0	640.86	23.36	4.27	1618.19	868.93
28241.000	1.00	0.0	0.0	628.00	1160.00	636.18	0.0	636.41	10.86	3.59	459.67	351.96
28241.000	1.00	0.0	0.0	628.00	2160.00	637.77	0.0	638.06	12.99	5.05	831.29	599.26
28241.000	1.00	0.0	0.0	628.00	2690.00	638.56	0.0	638.86	12.75	5.31	1032.78	753.41
28241.000	1.00	0.0	0.0	628.00	4200.00	640.62	0.0	640.94	11.09	5.69	1638.96	1261.26

	SECNO	XLCH	ELTRD	ELLC	ELMIN	Q	CWSEL	CRIWS	EG	10K*S	VCH	AREA	.01K
	28560.000	319.00	0.0	0.0	626.20	1160.00	636.64	0.0	636.70	8.81	2.87	1086.53	390.85
	28560.000	319.00	0.0	0.0	626.20	2160.00	638.33	0.0	638.42	10.57	3.64	1600.06	664.31
	28560.000	319.00	0.0	0.0	626.20	2690.00	639.12	0.0	639.22	10.89	3.92	1853.33	815.10
	28560.000	319.00	0.0	0.0	626.20	4200.00	641.13	0.0	641.25	11.00	4.48	2534.56	1266.34
	29040.000	480.00	0.0	0.0	627.60	1160.00	636.84	0.0	636.87	2.83	1.98	1577.56	689.75
	29040.000	480.00	0.0	0.0	627.60	2160.00	638.59	0.0	638.64	4.11	2.72	2164.84	1066.10
	29040.000	480.00	0.0	0.0	627.60	2690.00	639.39	0.0	639.46	4.53	3.01	2467.07	1263.92
	29040.000	480.00	0.0	0.0	627.60	4200.00	641.41	0.0	641.50	5.20	3.62	3188.72	1842.44
	30375.000	1335.00	0.0	0.0	629.30	1160.00	637.33	0.0	637.39	5.85	2.60	1034.29	479.71
	30375.000	1335.00	0.0	0.0	629.30	2160.00	639.22	0.0	639.29	6.23	3.15	1672.88	865.14
	30375.000	1335.00	0.0	0.0	629.30	2690.00	640.06	0.0	640.14	6.23	3.35	1994.40	1077.51
	30375.000	1335.00	0.0	0.0	629.30	4200.00	642.12	0.0	642.21	5.92	3.71	2819.97	1725.61
*	31190.000	272.00	0.0	0.0	634.80	1160.00	638.21	638.21	638.83	109.00	7.73	352.24	111.11
	31190.000	272.00	0.0	0.0	634.80	2160.00	639.32	0.0	639.80	69.73	7.67	682.87	258.67
	31190.000	272.00	0.0	0.0	634.80	2690.00	640.22	0.0	640.56	42.13	6.00	950.03	414.42
	31190.000	272.00	0.0	0.0	634.80	4200.00	642.20	0.0	642.52	21.69	6.16	1615.70	901.73
	31590.000	400.00	0.0	0.0	635.00	1150.00	639.92	0.0	640.15	14.33	4.99	677.24	303.80
	31590.000	400.00	0.0	0.0	635.00	2050.00	640.84	0.0	641.16	18.34	6.38	982.88	470.72
	31590.000	400.00	0.0	0.0	635.00	2550.00	641.34	0.0	641.69	16.66	6.82	1160.51	590.32
	31590.000	400.00	0.0	0.0	635.00	3900.00	642.95	0.0	643.27	14.13	6.96	1799.20	1037.54
	31990.000	400.00	0.0	0.0	635.10	1150.00	640.51	0.0	640.77	14.87	5.35	555.51	298.17
	31990.000	400.00	0.0	0.0	635.10	2050.00	641.59	0.0	642.02	20.76	7.21	739.36	449.97
	31990.000	400.00	0.0	0.0	635.10	2550.00	642.12	0.0	642.39	14.29	6.36	1109.49	674.45
	31990.000	400.00	0.0	0.0	635.10	3900.00	643.59	0.0	643.81	11.14	6.41	1930.79	1168.29
	32470.000	480.00	0.0	0.0	632.20	1150.00	640.90	0.0	641.40	10.25	6.15	306.80	359.12
	32470.000	480.00	0.0	0.0	632.20	2050.00	642.03	0.0	643.16	19.80	9.36	356.76	460.29
	32470.000	480.00	0.0	0.0	632.20	2550.00	642.10	0.0	643.66	20.13	11.20	401.35	600.83
*	32470.000	480.00	0.0	0.0	632.20	3900.00	642.83	642.83	645.66	47.25	15.30	468.77	967.37
	32540.000	70.00	0.0	0.0	633.00	1150.00	640.99	0.0	641.47	9.62	5.58	206.23	370.82
	32540.000	70.00	0.0	0.0	633.00	2050.00	642.16	0.0	643.31	19.64	8.62	237.88	462.61
	32540.000	70.00	0.0	0.0	633.00	2550.00	643.52	0.0	644.06	8.59	6.81	671.64	870.30
	32540.000	70.00	0.0	0.0	633.00	3900.00	645.78	0.0	646.43	8.62	7.79	1046.67	1328.60

UPPER ROUGE LIVONIA CITY

SUMMARY PRINTOUT TABLE 150

SECNO	Q	CHSEL	DIFWSP	DIFWSX	DIFKWS	TOPWID	XLOM
22865.000	1160.00	625.78	0.0	0.0	0.0	64.96	0.0
22865.000	2160.00	627.80	2.02	0.0	0.0	55.41	0.0
22865.000	2690.00	628.69	0.89	0.0	0.0	60.01	0.0
22865.000	4200.00	630.80	2.11	0.0	0.0	70.93	0.0
22895.000	1160.00	625.95	0.0	0.17	0.0	25.40	30.00
22895.000	2160.00	627.72	1.76	-0.08	1.76	25.40	30.00
22895.000	2690.00	628.83	1.11	0.14	0.0	60.75	30.00
22895.000	4200.00	630.83	2.00	0.03	0.0	71.10	30.00
22935.000	1160.00	626.55	0.0	0.59	0.0	48.90	40.00
22935.000	2160.00	630.66	4.11	2.94	4.11	70.21	40.00
22935.000	2690.00	631.97	1.32	3.14	0.0	86.07	40.00
22935.000	4200.00	633.77	1.79	2.93	0.0	86.26	40.00
22985.000	1160.00	627.46	0.0	0.91	0.0	78.22	50.00
22985.000	2160.00	631.24	3.78	0.58	3.70	174.67	50.00
22985.000	2690.00	632.71	1.47	0.74	0.0	176.00	50.00
22985.000	4200.00	635.12	2.41	1.35	0.0	176.00	50.00
23775.000	1160.00	629.31	0.0	1.05	0.0	179.67	790.00
23775.000	2160.00	632.54	3.23	1.30	3.23	213.16	790.00
23775.000	2690.00	633.86	1.32	1.15	0.0	232.95	790.00
23775.000	4200.00	636.39	2.52	1.27	0.0	412.99	790.00
24852.000	1160.00	631.30	0.0	2.00	0.0	114.30	1077.00
24852.000	2160.00	633.87	2.57	1.33	2.57	162.94	1077.00
24852.000	2690.00	635.05	1.18	1.19	0.0	170.13	1077.00
24852.000	4200.00	637.51	2.45	1.12	0.0	260.87	1077.00
25052.000	1160.00	632.24	0.0	0.94	0.0	155.64	200.00
25052.000	2160.00	634.57	2.33	0.70	2.33	200.07	200.00
25052.000	2690.00	635.67	1.10	0.61	0.0	200.21	200.00
25052.000	4200.00	638.07	2.40	0.56	0.0	200.51	200.00
25108.000	1160.00	634.48	0.0	2.24	0.0	200.06	56.00
25108.000	2160.00	635.77	1.29	1.21	1.29	200.22	56.00
25108.000	2690.00	636.40	0.62	0.73	0.0	200.30	56.00
25108.000	4200.00	638.50	2.10	0.43	0.0	200.56	56.00
25183.000	1160.00	634.46	0.0	-0.03	0.0	151.47	75.00
25183.000	2160.00	635.71	1.25	-0.07	1.25	246.18	75.00
25183.000	2690.00	636.32	0.61	-0.08	0.0	252.71	75.00
25183.000	4200.00	638.44	2.12	-0.06	0.0	276.50	75.00
25623.000	1160.00	634.79	0.0	0.34	0.0	191.53	445.00
25623.000	2160.00	636.32	1.52	0.61	1.52	361.64	445.00
25623.000	2690.00	637.00	0.69	0.68	0.0	368.01	445.00
25623.000	4200.00	639.04	2.04	0.60	0.0	566.65	445.00
26038.000	1160.00	635.04	0.0	0.24	0.0	149.21	410.00
26038.000	2160.00	636.69	1.65	0.36	1.66	191.29	410.00
26038.000	2690.00	637.37	0.68	0.37	0.0	203.62	410.00
26038.000	4200.00	639.29	1.92	0.24	4.25	225.00	410.00

SECNO	Q	CWSEL	DIFWSP	DIFWSX	DIFKWS	TOPWID	XLCH
26088.000	1160.00	635.02	0.0	-0.01	0.0	200.00	50.00
26088.000	2160.00	636.70	1.68	0.01	1.68	200.23	50.00
26088.000	2690.00	637.40	0.69	0.03	0.0	200.32	50.00
26088.000	4200.00	639.37	1.97	0.08	4.35	200.58	50.00
26184.000	1160.00	635.83	0.0	0.81	0.0	200.11	96.00
26184.000	2160.00	637.04	1.21	0.34	1.21	200.27	96.00
26184.000	2690.00	637.71	0.66	0.31	0.0	200.36	96.00
26184.000	4200.00	639.59	1.89	0.22	3.76	200.61	96.00
26234.000	1160.00	635.94	0.0	0.11	0.0	244.70	50.00
26234.000	2160.00	637.24	1.30	0.20	1.30	257.40	50.00
26234.000	2690.00	637.93	0.69	0.22	0.0	264.27	50.00
26234.000	4200.00	639.84	1.91	0.24	3.90	285.00	50.00
26660.000	1160.00	636.00	0.0	0.05	0.0	306.96	626.00
26660.000	2160.00	637.36	1.36	0.12	1.36	321.25	626.00
26660.000	2690.00	638.08	0.72	0.15	0.0	327.71	626.00
26660.000	4200.00	640.05	1.97	0.22	4.06	352.81	626.00
28232.000	1160.00	636.11	0.0	0.12	0.0	216.17	1372.00
28232.000	2160.00	637.62	1.51	0.26	1.51	244.78	1372.00
28232.000	2690.00	638.39	0.77	0.31	0.0	259.44	1372.00
28232.000	4200.00	640.45	2.05	0.39	4.33	353.60	1372.00
28233.000	1160.00	636.11	0.0	-0.01	0.0	216.19	1.00
28233.000	2160.00	637.79	1.68	0.17	1.68	248.10	1.00
28233.000	2690.00	638.60	0.81	0.21	0.0	263.47	1.00
28233.000	4200.00	640.69	2.08	0.24	4.58	387.77	1.00
28240.000	1160.00	636.16	0.0	0.05	0.0	217.12	7.00
28240.000	2160.00	637.83	1.66	0.03	1.66	248.54	7.00
28240.000	2690.00	638.63	0.80	0.03	0.0	263.76	7.00
28240.000	4200.00	640.70	2.07	0.02	4.54	389.40	7.00
28241.000	1160.00	636.18	0.0	0.02	0.0	217.32	1.00
28241.000	2160.00	637.77	1.59	-0.05	1.59	247.89	1.00
28241.000	2690.00	638.56	0.79	-0.07	0.0	262.69	1.00
28241.000	4200.00	640.62	2.06	-0.06	4.44	379.01	1.00
28560.000	1160.00	636.64	0.0	0.46	0.0	292.81	319.00
28560.000	2160.00	638.33	1.70	0.56	1.70	313.76	319.00
28560.000	2690.00	639.12	0.79	0.56	0.0	327.50	319.00
28560.000	4200.00	641.13	2.01	0.51	4.49	344.00	319.00
29040.000	1160.00	636.84	0.0	0.20	0.0	324.18	480.00
29040.000	2160.00	638.59	1.75	0.26	1.75	346.79	480.00
29040.000	2690.00	639.39	0.80	0.27	0.0	357.15	480.00
29040.000	4200.00	641.41	2.02	0.28	4.57	373.84	480.00
30375.000	1160.00	637.33	0.0	0.49	0.0	306.73	1335.00
30375.000	2160.00	639.22	1.89	0.62	1.89	369.10	1335.00
30375.000	2690.00	640.06	0.84	0.66	0.0	395.28	1335.00
30375.000	4200.00	642.12	2.06	0.70	4.79	405.79	1335.00

	SECNO	Q	CWSEL	DIFWSP	DIFWSX	DIFKWS	TOPWID	XLCH
*	31190.000	1160.00	638.21	0.0	0.88	0.0	291.54	272.00
	31190.000	2160.00	639.32	1.12	0.11	1.12	299.92	272.00
	31190.000	2690.00	640.22	0.89	0.16	0.0	307.86	272.00
	31190.000	4200.00	642.28	2.06	0.16	4.07	336.41	272.00
	31590.000	1150.00	639.92	0.0	1.71	0.0	317.27	400.00
	31590.000	2050.00	640.84	0.92	1.52	0.92	349.37	400.00
	31590.000	2550.00	641.34	0.50	1.12	0.0	366.73	400.00
	31590.000	3900.00	642.95	1.62	0.68	3.03	423.32	400.00
	31990.000	1150.00	640.51	0.0	0.59	0.0	170.03	400.00
	31990.000	2050.00	641.59	1.08	0.75	1.08	172.17	400.00
	31990.000	2550.00	642.12	0.53	0.79	1.61	259.24	400.00
	31990.000	3900.00	643.59	1.47	0.64	3.08	368.05	400.00
	32470.000	1150.00	640.90	0.0	0.39	0.0	76.04	480.00
	32470.000	2050.00	642.03	1.13	0.44	1.13	83.00	480.00
	32470.000	2550.00	642.10	0.06	-0.03	1.19	86.07	480.00
*	32470.000	3900.00	642.83	0.74	-0.75	1.93	109.97	480.00
	32540.000	1150.00	640.99	0.0	0.09	0.0	27.00	70.00
	32540.000	2050.00	642.16	1.16	0.13	1.16	27.00	70.00
	32540.000	2550.00	643.52	1.37	1.43	2.53	131.35	70.00
	32540.000	3900.00	645.78	2.25	2.94	4.79	217.43	70.00

SUMMARY OF ERRORS

CAUTION SECNO=31190.000 PROFILE= 1 CRITICAL DEPTH ASSUMED
CAUTION SECNO=31190.000 PROFILE= 1 PROBABLE MINIMUM SPECIFIC ENERGY
CAUTION SECNO=31190.000 PROFILE= 1 20 TRIALS ATTEMPTED TO BALANCE WSEL

CAUTION SECNO=32470.000 PROFILE= 4 CRITICAL DEPTH ASSUMED
CAUTION SECNO=32470.000 PROFILE= 4 MINIMUM SPECIFIC ENERGY

FLOOD INSURANCE ZONE DATA FOR UPPER ROUGE LIVONIA CITY

FLOOD HAZARD FACTOR FOR ENTIRE REACH USING SECTIONS

SECTION NUMBER	CUMULATIVE DISTANCE	ELEVATION DIFFERENCE BETWEEN BASE FLOOD AND 10	2	0.2
22865.000	0.	-2.91	-0.89	2.11
22895.000	30.	-2.88	-1.11	2.00
22935.000	70.	-5.43	-1.32	1.79
22985.000	120.	-5.25	-1.47	2.41
23775.000	910.	-4.55	-1.32	2.52
24852.000	1987.	-3.75	-1.18	2.45
25052.000	2187.	-3.42	-1.10	2.40
25108.000	2243.	-1.91	-0.62	2.10
25183.000	2318.	-1.86	-0.61	2.12
25628.000	2763.	-2.21	-0.69	2.04
26038.000	3173.	-2.34	-0.68	1.92
26088.000	3223.	-2.37	-0.69	1.97
26184.000	3319.	-1.87	-0.66	1.89
26234.000	3369.	-1.99	-0.69	1.91
26860.000	3995.	-2.08	-0.72	1.97
28232.000	5367.	-2.28	-0.77	2.05
28233.000	5368.	-2.49	-0.81	2.08
28240.000	5375.	-2.46	-0.80	2.07
28241.000	5376.	-2.38	-0.79	2.06
28560.000	5695.	-2.48	-0.79	2.01
29040.000	6175.	-2.55	-0.80	2.02
30375.000	7510.	-2.73	-0.84	2.06
31190.000	7782.	-2.01	-0.89	2.06
31590.000	8182.	-1.42	-0.50	1.62
31990.000	8582.	-1.61	-0.53	1.47
32470.000	9062.	-1.19	-0.06	0.74
32540.000	9132.	-2.53	-1.37	2.25
WEIGHTED AVG FOR REACH		-2.70	-0.85	2.04

FHF FOR THE REACH = 025 WITH 68.9 OF THE REACH WITHIN 1.0 FEET
ZONE FOR THE REACH = A 5

CONTINUOUS FLOOD HAZARD FACTORS BY EVEN INCREMENTS

INC NO.	TOTAL LENGTH	AVG ELEVATION DATA 10	1	DIFF.	WTD. AVG.	FHF	PERCENT WITHIN
	0.				SEC.	22865.000	
	30.				SEC.	22895.000	
	70.				SEC.	22935.000	
1	100.	627.08	631.07	-3.99	-3.99	040	100.
	120.				SEC.	22985.000	
2	200.	626.09	633.19	-5.10	-4.55	045	100.
3	300.	627.93	633.00	-5.07	-4.72	048	100.
4	400.	628.16	633.15	-4.99	-4.79	050	100.

							100.
6	600.	628.63	633.44	-4.81	-4.81	050	100.
7	700.	628.86	633.59	-4.73	-4.80	050	100.
8	800.	629.10	633.73	-4.63	-4.78	050	100.
9	900.	629.33	633.88	-4.55	-4.75	050	100.
	910.				SEC. 23775.000		
10	1000.	629.53	634.00	-4.47	-4.72	045	100.
11	1100.	629.70	634.10	-4.40	-4.69	045	100.
12	1200.	629.88	634.21	-4.33	-4.66	045	100.
13	1300.	630.07	634.32	-4.25	-4.63	045	100.
14	1400.	630.25	634.43	-4.18	-4.60	045	100.
15	1500.	630.44	634.54	-4.10	-4.57	045	100.
16	1600.	630.62	634.65	-4.03	-4.53	045	100.
17	1700.	630.81	634.76	-3.95	-4.50	045	100.
18	1800.	630.99	634.87	-3.88	-4.46	045	100.
19	1900.	631.18	634.98	-3.80	-4.43	045	100.
	1987.				SEC. 24852.000		
20	2000.	631.48	635.17	-3.69	-4.39	045	100.
21	2100.	631.93	635.46	-3.53	-4.35	045	100.
	2187.				SEC. 25052.000		
22	2200.	633.86	636.18	-2.32	-4.26	045	95.
	2243.				SEC. 25108.000		
23	2300.	635.00	636.51	-1.51	-4.14	040	91.
	2318.				SEC. 25183.000		
24	2400.	634.51	636.41	-1.90	-4.05	040	79.
25	2500.	634.61	636.63	-2.02	-3.96	040	72.
26	2600.	634.69	636.78	-2.09	-3.89	040	69.
27	2700.	634.76	636.93	-2.17	-3.83	040	63.
	2763.				SEC. 25620.000		
28	2800.	634.83	637.05	-2.22	-3.77	040	57.
29	2900.	634.89	637.14	-2.25	-3.72	035	52.
30	3000.	634.95	637.23	-2.28	-3.67	035	50.
31	3100.	635.00	637.32	-2.32	-3.63	035	40.
	3173.				SEC. 26038.000		
32	3200.	635.02	637.39	-2.37	-3.59	035	44.
	3223.				SEC. 26088.000		
33	3300.	635.64	637.65	-2.01	-3.54	035	39.
	3319.				SEC. 26184.000		
	3369.				SEC. 26234.000		
34	3400.	636.11	637.91	-1.80	-3.49	035	36.
35	3500.	635.95	637.96	-2.01	-3.45	035	34.
36	3600.	635.96	637.99	-2.03	-3.41	035	33.
37	3700.	635.97	638.01	-2.04	-3.37	035	32.
38	3800.	635.98	638.04	-2.06	-3.34	035	32.
39	3900.	635.99	638.06	-2.07	-3.30	035	33.
	3995.				SEC. 26860.000		
40	4000.	636.00	638.08	-2.08	-3.27	035	35.
41	4100.	636.01	638.11	-2.10	-3.24	030	34.
42	4200.	636.02	638.13	-2.11	-3.22	030	36.
43	4300.	636.02	638.15	-2.13	-3.19	030	35.
44	4400.	636.03	638.18	-2.15	-3.17	030	34.
45	4500.	636.04	638.20	-2.16	-3.15	030	38.
46	4600.	636.05	638.22	-2.17	-3.12	030	41.
47	4700.	636.06	638.24	-2.18	-3.10	030	47.
48	4800.	636.07	638.27	-2.20	-3.09	030	48.
49	4900.	636.08	638.29	-2.21	-3.07	030	53.
50	5000.	636.08	638.31	-2.23	-3.05	030	56.
51	5100.	636.09	638.33	-2.24	-3.04	030	59.
52	5200.	636.10	638.36	-2.26	-3.02	030	62.
53	5300.	636.11	638.38	-2.27	-3.01	030	66.
	5367.				SEC. 28232.000		
	5368.				SEC. 28233.000		
	5375.				SEC. 28241.000		
	5376.				SEC. 28241.000		
54	5400.	636.22	638.56	-2.34	-2.99	030	67.
55	5500.	636.39	638.82	-2.43	-2.98	030	65.

	5695.				SEC. 28560.000		
57	5700.	636.64	639.12	-2.48	-2.97	030	67.
58	5800.	636.69	639.19	-2.50	-2.96	030	67.
59	5900.	636.73	639.25	-2.52	-2.95	030	68.
60	6000.	636.77	639.31	-2.54	-2.94	030	67.
61	6100.	636.82	639.36	-2.54	-2.94	030	67.
	6175.				SEC. 29040.000		
62	6200.	636.86	639.41	-2.55	-2.93	030	68.
63	6300.	636.89	639.46	-2.57	-2.92	030	68.
64	6400.	636.93	639.51	-2.58	-2.92	030	69.
65	6500.	636.97	639.56	-2.59	-2.91	030	69.
66	6600.	637.00	639.61	-2.61	-2.91	030	70.
67	6700.	637.04	639.66	-2.62	-2.91	030	70.
68	6800.	637.07	639.71	-2.64	-2.90	030	72.
69	6900.	637.11	639.76	-2.65	-2.90	030	72.
70	7000.	637.15	639.81	-2.66	-2.89	030	73.
71	7100.	637.18	639.86	-2.68	-2.89	030	73.
72	7200.	637.22	639.91	-2.69	-2.89	030	74.
73	7300.	637.26	639.96	-2.70	-2.89	030	74.
74	7400.	637.29	640.01	-2.72	-2.88	030	74.
75	7500.	637.33	640.06	-2.73	-2.88	030	75.
	7510.				SEC. 30375.000		
76	7600.	637.59	640.12	-2.53	-2.80	030	75.
77	7700.	638.00	640.18	-2.18	-2.87	030	74.
	7762.				SEC. 31190.000		
78	7800.	638.37	640.34	-1.97	-2.80	030	74.
79	7900.	638.80	640.60	-1.80	-2.84	030	73.
80	8000.	639.22	640.88	-1.66	-2.83	030	73.
81	8100.	639.65	641.16	-1.51	-2.81	030	72.
	8182.				SEC. 31590.000		
82	8200.	639.96	641.40	-1.44	-2.80	030	73.
83	8300.	640.12	641.61	-1.49	-2.78	030	71.
84	8400.	640.27	641.80	-1.53	-2.76	030	70.
85	8500.	640.42	642.00	-1.58	-2.75	030	69.
	8582.				SEC. 31990.000		
86	8600.	640.54	642.11	-1.57	-2.74	025	69.
87	8700.	640.62	642.11	-1.49	-2.72	025	68.
88	8800.	640.71	642.11	-1.40	-2.71	025	67.
89	8900.	640.79	642.10	-1.31	-2.69	025	66.
90	9000.	640.87	642.10	-1.23	-2.68	025	64.
	9062.				SEC. 32470.000		
91	9100.	640.97	643.20	-2.23	-2.67	025	65.
	9132.				SEC. 32540.000		

THIS REACH CAN BE SUBDIVIDED BY INC NO. TO MEET FIA REQUIREMENTS
INPUT 20N WHERE N IS THE NUMBER OF REACHES AND THEN INPUT THE END
OF EACH REACH BY INC NO. FOR EXAMPLE 202 23 91
A NEGATIVE INC NO. WILL SUPPRESS INTERMEDIATE INC OUTPUT.

00BREAK00

1) COUNTY: Wayne

2) STUDY NAME: City of Livonia

3) WATERCOURSE: Upper Rouge

4) DOCUMENT TYPE: Summary

00BREAK00

```
**************************************************
  HEC2 RELEASE DATED NOV 76 UPDATED FEB 1977
  ERROR CORR -  01
  MODIFICATION -  50,51,52
**************************************************
```

RECEIVED
OCT 08 1979
WATER MANAGEMENT

```
C
T1      CITY OF LIVONIA FIS HUD 2014-07 UPPER ROUGE RIVER
T2      Q10YR=1150 Q50YR=2050 Q100YR=2550 Q500YR=3900 AT INKSTER RD.
T3      UPPER ROUGE LIVONIA CITY

J1  ICHECK     INQ       NINV      IDIR      STRT      METRIC    HVINS     Q         WSEL      FQ
        0.       7.        0.        0.  0.000000      0.00      0.0       0.    629.880     0.000

J2  NPROF      IPLOT     PRFVS     XSECV     XSECH     FN        ALLDC     IBW       CHNIM     ITRACE
    -1.000     0.000     -1.000    0.000     0.000     0.000     0.000     0.000     0.000     0.000

J3  VARIABLE CODES FOR SUMMARY PRINTOUT
    150.000    0.000     0.000     0.000     0.000     0.000     0.000     0.000     0.000     0.000

QT      6.000  1160.000  2160.000  2690.000  2690.000  4200.000  1730.000     0.000     0.000     0.000
NC      0.100     0.100     0.040     0.300     0.500     0.000     0.000     0.000     0.000     0.000

          30' D/S INKSTER ROAD.

X1  22865.000    11.000   259.100   284.500     0.000     0.000     0.000     0.000     0.000     0.000
GR    650.000   228.000   631.300   229.000   631.200   235.000   621.900   259.100   621.900   259.200
GR    620.200   272.000   622.100   284.400   622.100   284.500   631.200   308.000   631.400   315.000
GR    650.000   316.000     0.000     0.000     0.000     0.000     0.000     0.000     0.000     0.000
NC      0.120     0.120     0.035     0.000     0.000     0.000     0.000     0.000     0.000     0.000

          D/S FACE INKSTER RD. SKEW

X1  22895.000     0.000     0.000     0.000    30.000    30.000    30.000     0.000     0.000     0.000
X3     10.000     0.000     0.000     0.000     0.000     0.000     0.000   627.200   627.200     0.000
SB      0.000     1.720     3.000     0.000    25.400     0.000   177.600     0.000   620.200   620.200

          U/S FACE INKSTER RD. SKEW

X1  22935.000     0.000     0.000     0.000    40.000    40.000    40.000     0.000     0.000     0.000
X2      0.000     0.000     1.000   627.200   631.200     0.000     0.000     0.000     0.000     0.000
X3     10.000     0.000     0.000     0.000     0.000     0.000     0.000   631.200   631.200     0.000
BT     10.000   228.000   650.000     0.000   229.000   635.000     0.000   235.000   631.200     0.000
BT    259.100   631.200   621.900   259.200   631.200   627.200   284.400   631.200   627.200   284.500
BT    631.200   622.100   308.000   631.200     0.000   315.000   635.000     0.000   316.000   650.000
BT      0.000     0.000     0.000     0.000     0.000     0.000     0.000     0.000     0.000     0.000
NC      0.120     0.120     0.040     0.300     0.500     0.000     0.000     0.000     0.000     0.000
ET      0.000     0.000     0.000     0.000     1.400     0.000     0.000     0.000     0.000     0.000

          50 FT U/S INKSTER RD. SKEW

X1  22985.000    11.000   297.000   322.000    50.000    50.000    50.000     0.000     0.000     0.000
GR    636.000     0.000   634.000    95.000   632.000   146.000   630.000   207.000   622.000   297.000
```

GR	620.300	310.000	622.000	322.000	630.000	370.000	632.000	421.000	634.000	430.000
GR	636.000	533.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
NC	0.150	0.150	0.050	0.400	0.600	0.000	0.000	0.000	0.000	0.000

VALLEY SECTION

X1	23775.000	18.000	272.000	292.000	260.000	1100.000	790.000	0.000	0.000	0.000
GR	638.000	0.000	636.000	190.000	634.000	210.000	632.000	230.000	630.000	240.000
GR	625.800	250.000	621.900	272.000	620.400	282.000	622.200	292.000	625.700	314.000
GR	626.000	400.000	628.000	415.000	630.000	425.000	634.000	445.000	634.000	515.000
GR	636.000	545.000	638.000	655.000	640.000	710.000	0.000	0.000	0.000	0.000

200 FT D/S 7 MILE RD.

X1	24852.000	9.000	80.000	108.000	1100.000	900.000	1077.000	0.000	0.000	0.000
GR	650.000	0.000	634.000	1.000	632.000	35.000	626.900	80.000	625.500	94.000
GR	626.700	108.000	630.000	150.000	636.000	175.000	638.000	290.000	0.000	0.000

D/S FACE 7 MILE RD. SKEW

X1	25052.000	11.000	314.000	340.000	20.000	400.000	200.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	631.400	631.400	0.000
GR	650.000	251.000	634.000	252.000	633.700	280.000	626.900	314.000	626.900	314.100
GR	625.600	327.000	626.700	340.000	626.700	340.100	633.700	374.000	634.000	402.000
GR	650.000	403.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
SB	0.000	1.880	3.000	0.000	25.800	0.000	95.500	0.000	625.600	625.600

U/S FACE 7 MILE RD. SKEW

X1	25108.000	0.000	0.000	0.000	56.000	56.000	56.000	0.000	0.000	0.000
X2	0.000	0.000	1.000	629.300	633.700	0.000	0.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	633.700	633.700	0.000
BT	10.000	251.000	650.000	0.000	252.000	634.000	0.000	265.000	633.700	0.000
BT	314.000	633.700	626.900	314.100	633.700	629.300	340.000	633.700	629.300	340.100
BT	633.700	626.700	390.000	633.700	0.000	402.000	634.000	0.000	403.000	650.000
BT	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
NC	0.130	0.130	0.050	0.300	0.500	0.000	0.000	0.000	0.000	0.000

75 FT U/S 7 MILE RD. SKEW

X1	25183.000	16.000	383.000	413.000	75.000	75.000	75.000	0.000	0.000	0.000
GR	640.000	0.000	640.000	232.000	638.000	275.000	636.000	292.000	634.000	318.000
GR	632.000	374.000	630.000	383.000	626.000	391.000	625.700	400.000	626.000	413.000
GR	630.000	426.000	634.000	434.000	636.000	563.000	636.000	662.000	638.000	740.000
GR	640.000	912.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000

VALLEY SECTION

X1	25628.000	13.000	379.000	409.000	600.000	50.000	445.000	0.000	0.000	0.000
GR	640.000	0.000	640.000	360.000	630.000	375.000	627.600	379.000	625.600	383.000
GR	623.700	394.000	625.400	405.000	629.400	409.000	630.000	420.000	634.000	450.000
GR	636.000	725.000	636.000	740.000	640.000	1100.000	0.000	0.000	0.000	0.000

50 FT D/S DEERING RD.

X1	26038.000	13.000	171.000	200.000	700.000	100.000	410.000	0.000	0.000	0.000
G	640.000	0.000	38.000	45.000	636.000	75.000	634.000	130.000	630.000	145.000

GR	630.000	165.000	626.000	171.000	624.900	185.000	625.600	200.000	629.100	207.000
GR	630.000	235.000	638.000	260.000	639.700	375.000	0.000	0.000	0.000	0.000

D/S FACE DEERING RD.

X1	26088.000	16.000	225.000	246.000	50.000	50.000	50.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	633.400	633.400	0.000
GR	650.000	64.000	637.800	65.000	635.000	150.000	634.900	200.000	625.000	225.000
GR	625.000	226.500	625.000	228.500	625.000	231.500	625.000	235.500	625.000	239.500
GR	625.000	242.500	625.000	244.500	625.000	246.000	634.900	270.000	635.000	356.000
GR	650.000	357.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
SB	0.000	2.500	3.000	0.000	15.600	0.000	131.000	0.000	625.000	625.000

U/S FACE DEERING RD.

X1	26184.000	0.000	0.000	0.000	96.000	96.000	96.000	0.000	0.000	0.000
X2	0.000	0.000	1.000	633.400	636.900	0.000	0.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	634.900	634.900	0.000
BT	16.000	64.000	650.000	0.000	65.000	637.800	0.000	150.000	635.000	0.000
BT	200.000	634.900	0.000	225.000	634.900	625.000	226.500	634.900	628.500	228.500
BT	634.900	631.000	231.500	634.900	632.500	235.500	634.900	633.400	239.500	634.900
BT	632.500	242.500	634.900	631.000	244.500	634.900	628.500	246.000	634.900	625.000
BT	270.000	634.900	0.000	389.000	635.000	0.000	390.000	650.000	0.000	0.000
NC	0.120	0.120	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000

50 FT U/S DEERING RD.

X1	26234.000	14.000	160.000	205.000	50.000	50.000	50.000	0.000	0.000	0.000
GR	640.000	0.000	638.000	80.000	636.000	100.000	634.000	110.000	632.000	120.000
GR	630.000	140.000	628.000	160.000	625.100	185.000	626.000	205.000	628.000	220.000
GR	630.000	300.000	636.000	370.000	638.000	375.000	640.000	670.000	0.000	0.000
NC	0.100	0.100	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000

VALLEY SECTION

X1	26860.000	13.000	550.000	576.000	200.000	900.000	626.000	0.000	0.000	0.000
GR	642.000	0.000	640.000	275.000	630.000	345.000	628.000	480.000	629.500	550.000
GR	624.500	555.000	624.800	563.000	625.200	571.000	628.500	576.000	630.000	600.000
GR	640.000	620.000	642.000	640.000	644.000	800.000	0.000	0.000	0.000	0.000

D/S FOOTBRIDGE

X1	28232.000	10.000	70.000	110.000	1000.000	1400.000	1372.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	631.900	631.900	0.000
GR	642.000	0.000	640.000	10.000	635.000	70.000	628.000	77.500	628.000	90.000
GR	629.000	102.500	635.000	110.000	635.000	265.000	640.000	300.000	644.000	850.000

FOOTBRIDGE TO SCHOOL D/S FACE

X1	28233.000	0.000	0.000	0.000	1.000	1.000	1.000	0.000	0.000	0.000
X2	0.000	0.000	0.000	631.900	635.000	0.000	0.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	631.900	631.900	0.000

FOOTBRIDGE TO SCHOOL U/S FACE

X1	28240.000	0.000	0.000	0.000	7.000	7.000	7.000	0.000	0.000	0.000
X2	0.000	0.000	0.000	631.900	635.000	0.000	0.000	0.000	0.000	0.000

X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	635.000	635.000	0.000

U/S FOOTBRIDGE

X1	28241.000	0.000	0.000	0.000	1.000	1.000	1.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	635.000	635.000	0.000
NC	0.150	0.150	0.050	0.000	0.000	0.000	0.000	0.000	0.000	0.000

VALLEY SECTION

X1	28560.000	20.000	57.000	84.000	350.000	200.000	319.000	0.000	0.000	0.000
GR	640.000	0.000	635.600	24.000	633.200	44.000	633.600	57.000	626.200	67.000
GR	626.200	70.000	628.600	71.000	632.700	84.000	632.700	104.000	632.500	124.000
GR	632.500	164.000	633.000	184.000	632.600	204.000	632.500	224.000	632.800	244.000
GR	633.200	264.000	634.200	284.000	635.600	304.000	638.500	324.000	640.000	344.000

VALLEY SECTION

X1	29040.000	14.000	305.000	339.000	300.000	250.000	480.000	0.000	0.000	0.000
GR	646.000	0.000	644.000	200.000	640.000	215.000	634.000	255.000	632.000	285.000
GR	630.200	305.000	628.700	312.000	627.600	322.000	628.400	332.000	631.500	339.000
GR	632.000	530.000	640.000	580.000	642.000	585.000	644.000	1020.000	0.000	0.000

VALLEY SECTION

X1	30375.000	9.000	185.000	220.000	635.000	565.000	605.000	0.000	0.000	0.000
GR	650.000	0.000	645.000	80.000	637.000	120.000	632.200	185.000	629.300	200.000
GR	629.300	210.000	632.000	220.000	635.000	360.000	640.000	500.000	0.000	0.000
NC	0.120	0.120	0.060	0.400	0.600	0.000	0.000	0.000	0.000	0.000

VALLEY SECTION

X1	31190.000	15.000	250.000	284.000	815.000	750.000	815.000	0.000	0.000	0.000
GR	656.000	0.000	650.000	90.000	640.000	170.000	638.000	180.000	636.000	200.000
GR	638.000	250.000	635.100	254.000	635.100	267.000	634.800	280.000	636.600	284.000
GR	638.000	470.000	640.000	475.000	646.000	510.000	648.000	515.000	650.000	725.000
QT	6.000	1150.000	2050.000	2550.000	2550.000	3900.000	1630.000	0.000	0.000	0.000
NC	0.000	0.000	0.000	0.500	0.800	0.000	0.000	0.000	0.000	0.000
NH	4.000	0.200	300.000	0.150	395.000	0.050	419.000	0.150	1020.000	0.000
ET	0.000	0.000	0.000	0.000	0.000	0.000	9.100	0.000	150.000	419.000

VALLEY SECTION

X1	31990.000	16.000	395.000	419.000	900.000	800.000	800.000	0.000	0.000	0.000
X4	1.000	637.500	300.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
GR	650.000	0.000	640.000	100.000	638.000	195.000	637.200	395.000	635.600	398.000
GR	635.100	407.000	635.500	416.000	637.600	419.000	640.000	425.000	650.000	445.000
GR	652.000	460.000	652.000	625.000	654.000	650.000	656.000	740.000	658.000	955.000
GR	660.000	1020.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
NC	0.000	0.000	0.060	0.600	0.800	0.000	0.000	0.000	0.000	0.000
ET	0.000	0.000	0.000	0.000	0.000	0.000	9.100	0.000	9.000	180.000

70 FT D/S 8 MILE RD.

X1	32470.000	18.000	85.000	105.000	400.000	550.000	460.000	0.000	0.000	0.000
GR	651.700	0.000	651.000	8.000	650.000	12.000	642.900	32.000	642.500	40.000
GR	638.700	62.000	638.100	70.000	637.900	76.000	633.400	85.000	632.200	92.000

GR	632.300	96.000	635.000	105.000	638.000	110.000	638.500	110.000	638.900	120.000
GR	642.700	130.000	642.900	150.000	650.000	360.000	0.000	0.000	0.000	0.000

D/S FACE 8 MILE RD.

X1	32540.000	21.000	600.000	627.000	70.000	70.000	70.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	643.000	643.000	0.000
GR	650.000	0.000	648.900	100.000	648.200	200.000	646.900	300.000	646.900	400.000
GR	646.300	500.000	641.200	575.000	634.000	599.000	633.500	600.000	633.000	610.000
GR	633.500	620.000	633.800	627.000	634.200	630.000	637.400	646.000	642.700	660.000
GR	645.400	700.000	646.900	800.000	650.000	900.000	653.900	1000.000	658.100	1100.000
GR	661.100	1278.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
EJ	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000

*PROF 1

CCHV= 0.300 CEHV= 0.500

*SECNO 22865.000

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IH2	ICONT	CORAR	TOPWID	ENDST
22865.00	9.68	629.88	0.00	629.88	630.48	0.60	0.00	0.00	621.90
1730.	125.	1488.	117.	83.	223.	78.	0.	0.	622.10
0.00	1.52	6.68	1.49	0.100	0.040	0.100	0.000	620.20	238.42
0.001809	0.	0.	0.	0	0	0	0.00	66.17	304.59

30' D/S INKSTER ROAD.

*SECNO 22895.000

D/S FACE INKSTER RD. SKEW

22895.00	9.70	629.90	0.00	0.00	630.56	0.67	0.05	0.03	621.90
1730.	95.	1546.	89.	83.	223.	78.	0.	0.	622.10
0.00	1.15	6.93	1.13	0.120	0.035	0.120	0.034	620.20	238.38
0.001487	30.	30.	30.	2	0	0	0.00	66.25	304.63

SPECIAL BRIDGE

SB	XK	XKOR	COFQ	RDLEN	BWC	BWP	BAREA	SS	ELCHU	ELCHD
	0.00	1.72	3.00	0.00	25.40	0.00	177.60	0.00	620.20	620.20

*SECNO 22935.000

PRESSURE AND WEIR FLOW

EGPRS	EGLWC	H3	QWEIR	QPR	BAREA	TRAPEZOID AREA	ELLC	ELTRD
632.43	630.83	0.00	153.	1570.	178.	178.	627.20	631.20

U/S FACE INKSTER RD. SKEW

22935.00	11.35	631.55	0.00	0.00	631.98	0.43	1.42	0.00	621.90
1730.	117.	1502.	111.	122.	265.	117.	1.	0.	622.10
0.00	0.96	5.66	0.95	0.120	0.035	0.120	0.034	620.20	228.99
0.000790	40.	40.	40.	2	0	2	0.00	86.02	315.01

CCHV= 0.300 CEHV= 0.500

*SECNO 22985.000

50 FT U/S INKSTER RD. SKEW

22985.00	11.54	631.84	0.00	0.00	632.08	0.23	0.04	0.06	622.00
1730.	207.	1225.	298.	278.	267.	324.	1.	0.	622.00
0.01	0.74	4.58	0.92	0.120	0.040	0.120	0.036	620.30	155.42
0.000653	50.	50.	50.	2	0	0	0.00	261.60	417.03

CCHV= 0.400 CEHV= 0.600
*SECNO 23775.000

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IH2	ICONT	CORAR	TOPWID	ENDST
VALLEY SECTION									
23775.00	12.13	632.53	0.00	0.00	632.62	0.09	0.48	0.06	621.90
1730.	217.	780.	733.	254.	226.	898.	23.	4.	622.20
0.12	0.85	3.45	0.82	0.150	0.050	0.150	0.047	620.40	224.69
0.000541	260.	790.	1100.	2	0	0	0.00	212.97	437.66
*SECNO 24852.000									
200 FT D/S 7 MILE RD.									
24852.00	7.97	633.47	0.00	0.00	633.81	0.34	1.04	0.15	626.90
1730.	236.	1157.	337.	199.	205.	240.	46.	8.	626.70
0.19	1.18	5.65	1.40	0.150	0.050	0.150	0.050	625.50	9.99
0.002553	1100.	1077.	900.	2	0	0	0.00	154.47	164.46
*SECNO 25052.000									
D/S FACE 7 MILE RD. SKEW 63.40 ~ 63.48									
25052.00	8.39	633.99	0.00	0.00	634.57	0.58	0.61	0.14	626.90
1730.	172.	1378.	180.	129.	202.	133.	48.	9.	626.70
0.20	1.33	6.81	1.36	0.150	0.050	0.150	0.050	625.60	253.05
0.003417	20.	200.	400.	2	0	0	0.00	147.90	400.95

SPECIAL BRIDGE

SB	XK	XKOR	COFQ	RDLEN	BWC	BWP	BAREA	SS	ELCHU	ELCHD
	0.00	1.88	3.00	0.00	25.80	0.00	95.50	0.00	625.60	625.60

*SECNO 25108.000
PRESSURE AND WEIR FLOW

EGPRS	EGLWC	M3	QWEIR	QPR	BAREA	TRAPEZOID AREA	ELLC	ELTRD
643.57	634.57	0.00	1052.	684.	96.	95.	629.30	633.70
U/S FACE 7 MILE RD. SKEW								
25108.00	9.53	635.13	0.00	0.00	635.49	0.36	0.92	0.00	626.90
1730.	218.	1287.	225.	200.	232.	204.	49.	9.	626.70
0.20	1.09	5.55	1.11	0.150	0.050	0.150	0.049	625.60	251.93
0.001891	56.	56.	56.	2	0	4	0.00	150.14	402.07

CCHV= 0.300 CEHV= 0.500
*SECNO 25183.000

75 FT U/S 7 MILE RD. SKEW

25183.00	9.61	635.31	0.00	0.00	635.63	0.32	0.13	0.01	630.00
1730.	158.	1364.	208.	180.	267.	178.	50.	10.	626.00
0.21	0.88	5.11	1.17	0.130	0.050	0.130	0.049	625.70	300.88
0.001674	75.	75.	75.	1	0	0	0.00	218.08	518.96

*SECNO 25628.000

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IH2	ICONT	CORAR	TOPWID	ENDST

VALLEY SECTION

25628.00	12.23	635.93	0.00	0.00	636.17	0.24	0.51	0.03	627.60
1730.	52.	1397.	281.	55.	321.	442.	55.	11.	629.40
0.24	0.95	4.36	0.64	0.130	0.050	0.130	0.050	623.70	366.11
0.001012	600.	445.	50.	2	0	0	0.00	348.96	715.06

*SECNO 26038.000

50 FT D/S DEERING RD.

26038.00	11.45	636.35	0.00	0.00	636.50	0.15	0.30	0.03	626.00
1730.	251.	1173.	306.	317.	319.	316.	62.	12.	625.60
0.28	0.79	3.68	0.97	0.130	0.050	0.130	0.051	624.90	69.76
0.000627	700.	410.	100.	2	0	0	0.00	185.09	254.84

*SECNO 26088.000

D/S FACE DEERING RD.

26088.00	11.31	636.31	0.00	0.00	636.61	0.30	0.04	0.08	625.00
1730.	247.	1230.	254.	254.	238.	270.	63.	13.	625.00
0.28	0.97	5.18	0.94	0.130	0.050	0.130	0.051	625.00	110.08
0.001193	50.	50.	50.	2	0	0	0.00	246.01	356.09

SPECIAL BRIDGE

SB	XK	XKOR	COFQ	RDLEN	BWC	BWP	BAREA	SS	ELCHU	ELCHD
	0.00	2.50	3.00	0.00	15.60	0.00	131.00	0.00	625.00	625.00

*SECNO 26184.000

PRESSURE AND WEIR FLOW

EGPRS	EGLWC	H3	QWEIR	QPR	BAREA	TRAPEZOID AREA	ELLC	ELTRD
643.09	636.61	0.00	1360.	369.	131.	131.	633.40	634.90

U/S FACE DEERING RD.

26184.00	11.32	636.32	0.00	0.00	636.62	0.30	0.01	0.00	625.00

1730.	247.	1229.	254.	255.	238.	271.	65.	13.	625.00
0.29	0.97	5.17	0.94	0.130	0.050	0.130	0.051	625.00	109.76
0.001187	96.	96.	96.	2	0	5	0.00	246.33	356.09

*SECNO 26234.000

50 FT U/S DEERING RD.

635.45

636.99

26234.00	11.59	636.69	0.00	0.00	636.72	0.03	0.02	0.08	626.00
1730.	191.	955.	584.	344.	501.	1019.	66.	14.	626.00
0.30	0.56	1.91	0.57	0.120	0.050	0.120	0.051	625.10	93.14
0.000166	50.	50.	50.	2	0	0	0.00	278.58	371.72

*SECNO 26860.000

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	THA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IH2	ICONT	CORAR	TOPWID	ENDST

VALLEY SECTION

26860.00	12.29	636.79	0.00	0.00	636.80	0.01	0.08	0.01	629.50
1730.	1142.	455.	134.	1775.	290.	227.	90.	17.	628.50
0.46	0.64	1.57	0.59	0.100	0.050	0.100	0.052	624.50	297.50
0.000130	200.	626.	900.	2	0	0	0.00	316.07	613.57

*SECNO 28232.000

D/S FOOTBRIDGE

28232.00	9.07	637.07	0.00	0.00	637.33	0.26	0.41	0.12	635.00
1730.	17.	1369.	344.	26.	300.	336.	129.	24.	635.00
0.55	0.66	4.36	1.03	0.100	0.050	0.100	0.053	628.00	45.15
0.001866	1000.	1372.	1400.	2	0	0	0.00	234.34	279.49

*SECNO 28233.000

3370 NORMAL BRIDGE,NRD= 0 MIN ELTRD= 635.00 MAX ELLC= 631.90

FOOTBRIDGE TO SCHOOL D/S FACE

28233.00	9.17	637.17	0.00	0.00	637.35	0.19	0.00	0.02	635.00
1730.	42.	876.	812.	28.	204.	353.	129.	24.	635.00
0.55	1.47	4.30	2.30	0.100	0.050	0.100	0.053	628.00	43.96
0.008652	1.	1.	1.	2	0	0	-100.75	236.23	280.19

*SECNO 28240.000

3370 NORMAL BRIDGE,NRD= 0 MIN ELTRD= 635.00 MAX ELLC= 631.90

FOOTBRIDGE TO SCHOOL U/S FACE

28240.00	9.24	637.24	0.00	0.00	637.42	0.17	0.06	0.00	635.00
1730.	44.	861.	825.	30.	207.	365.	129.	25.	635.00
0.55	1.45	4.17	2.26	0.100	0.050	0.100	0.053	628.00	43.07

0.008149	7.	7.	7.	2	0	0	-100.75	237.64	280.71

*SECNO 28241.000

U/S FOOTBRIDGE 637.22

28241.00	9.22	637.22	0.00	0.00	637.45	0.24	0.00	0.03	635.00
1730.	19.	1343.	367.	29.	306.	361.	129.	25.	635.00
0.55	0.65	4.39	1.02	0.100	0.050	0.100	0.053	628.00	43.41
0.001686	1.	1.	1.	2	0	0	0.00	237.11	280.51

*SECNO 28560.000

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IH2	ICONT	CORAR	TOPWID	ENDST

VALLEY SECTION

28560.00	11.56	637.76	0.00	0.00	637.84	0.07	0.34	0.05	633.60
1730.	96.	708.	926.	137.	216.	1071.	135.	26.	632.70
0.59	0.70	3.28	0.87	0.150	0.050	0.150	0.053	626.20	12.21
0.000939	350.	319.	200.	2	0	0	0.00	306.70	318.91

*SECNO 29040.000

VALLEY SECTION

29040.00	10.40	638.00	0.00	0.00	638.04	0.04	0.19	0.01	630.20
1730.	188.	753.	789.	341.	315.	1305.	146.	28.	631.50
0.66	0.55	2.40	0.60	0.150	0.050	0.150	0.054	627.60	228.36
0.000346	300.	480.	250.	2	0	0	0.00	339.11	567.47

*SECNO 30375.000

VALLEY SECTION

30375.00	8.97	638.27	0.00	0.00	638.38	0.10	0.31	0.03	632.20
1730.	165.	956.	609.	243.	279.	818.	168.	33.	632.00
0.74	0.68	3.43	0.74	0.150	0.050	0.150	0.054	629.30	113.65
0.000857	635.	605.	565.	2	0	0	0.00	337.93	451.58

CCHV= 0.400 CEHV= 0.600

*SECNO 31190.000

VALLEY SECTION

31190.00	4.83	639.64	0.00	0.00	639.80	0.17	1.39	0.04	638.00
1730.	326.	702.	701.	191.	148.	438.	187.	38.	636.60
0.81	1.71	4.75	1.60	0.120	0.060	0.120	0.054	634.80	171.83
0.005446	815.	815.	750.	3	0	0	0.00	302.26	474.09

CCHV= 0.500 CEHV= 0.800

1490 NH CARD USED

*SECNO 31990.000

3470 ENCROACHMENT STATIONS= 150.0 419.0 TYPE= 1 TARGET= 269.000

VALLEY SECTION

31990.00	7.07	642.17	0.00	0.00	642.26	0.09	2.42	0.04	637.20
1630.	1039.	591.	0.	1088.	157.	0.	207.	44.	100000.00
0.93	0.96	3.75	0.00	0.174	0.050	0.120	0.055	635.10	150.00
0.001724	900.	800.	800.	2	0	0	0.00	269.00	419.00

CCHV= 0.600 CEHV= 0.800

*SECNO 32470.000

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IH2	ICONT	CORAR	TOPWID	ENDST

3470 ENCROACHMENT STATIONS= 9.0 180.0 TYPE= 1 TARGET= 171.000

70 FT D/S 8 MILE RD.

32470.00	10.83	643.03	0.00	0.00	643.40	0.37	0.92	0.23	633.40
1630.	329.	1143.	158.	190.	199.	103.	216.	46.	635.00
0.96	1.73	5.74	1.53	0.120	0.060	0.120	0.055	632.20	31.64
0.002592	400.	460.	550.	2	0	0	0.00	122.17	153.80

*SECNO 32540.000

D/S FACE 8 MILE RD. 642.55

32540.00	10.46	643.46	0.00	0.00	643.64	0.18	0.12	0.12	633.50
1630.	227.	1100.	303.	188.	273.	203.	216.	46.	633.80
0.97	1.21	4.03	1.49	0.120	0.060	0.120	0.055	633.00	541.80
0.001216	70.	70.	70.	2	0	0	0.00	129.43	671.23

```
**************************************************
  HEC2 RELEASE DATED NOV 76 UPDATED FEB 1977
  ERROR CORR -  01
  MODIFICATION -  50,51,52
**************************************************
```

NOTE- ASTERISK (*) AT LEFT OF CROSS-SECTION NUMBER INDICATES MESSAGE IN SUMMARY OF ERRORS LIST

UPPER ROUGE LIVONIA CITY

SUMMARY PRINTOUT TABLE 150

SECNO	XLCH	ELTRD	ELLC	ELMIN	Q	CWSEL	CRIWS	EG	10K*S	VCH	AREA	.01K
22865.000	0.00	0.00	0.00	620.20	1730.00	629.88	0.00	630.48	18.09	6.68	383.51	406.71
22895.000	30.00	0.00	0.00	620.20	1730.00	629.90	0.00	630.56	14.87	6.93	384.53	448.62
22935.000	40.00	631.20	627.20	620.20	1730.00	631.55	0.00	631.98	7.90	5.66	504.42	615.59
22985.000	50.00	0.00	0.00	620.30	1730.00	631.84	0.00	632.08	6.53	4.58	869.46	676.91
23775.000	790.00	0.00	0.00	620.40	1730.00	632.53	0.00	632.62	5.41	3.45	1377.78	743.80
24852.000	1077.00	0.00	0.00	625.50	1730.00	633.47	0.00	633.81	25.53	5.65	644.54	362.40
25052.000	200.00	0.00	0.00	625.60	1730.00	633.99	0.00	634.57	34.17	6.81	464.82	295.96
25108.000	56.00	633.70	629.30	625.60	1730.00	635.13	0.00	635.49	18.91	5.55	635.94	397.87
25183.000	75.00	0.00	0.00	625.70	1730.00	635.31	0.00	635.63	16.74	5.11	624.31	422.79
25628.000	445.00	0.00	0.00	623.70	1730.00	635.93	0.00	636.17	10.12	4.36	817.32	543.77
26038.000	410.00	0.00	0.00	624.90	1730.00	636.35	0.00	636.50	6.27	3.68	952.95	691.05
26088.000	50.00	0.00	0.00	625.00	1730.00	636.31	0.00	636.61	11.93	5.18	761.50	500.79
26184.000	96.00	634.90	633.40	625.00	1730.00	636.32	0.00	636.62	11.87	5.17	764.08	502.04
26234.000	50.00	0.00	0.00	625.10	1730.00	636.69	0.00	636.72	1.66	1.91	1863.49	1344.56
26860.000	626.00	0.00	0.00	624.50	1730.00	636.79	0.00	636.80	1.30	1.57	2291.52	1519.32
28232.000	1372.00	0.00	0.00	628.00	1730.00	637.07	0.00	637.33	18.66	4.56	661.99	400.51
28233.000	1.00	635.00	631.90	628.00	1730.00	637.17	0.00	637.35	88.52	4.30	584.61	183.88
28240.000	7.00	635.00	631.90	628.00	1730.00	637.24	0.00	637.42	81.49	4.17	602.20	191.64
28241.000	1.00	0.00	0.00	628.00	1730.00	637.22	0.00	637.45	16.86	4.39	696.29	421.32
28560.000	319.00	0.00	0.00	626.20	1730.00	637.76	0.00	637.84	9.39	3.28	1423.56	564.52

SECNO	XLCH	ELTRD	ELLC	ELMIN	Q	CWSEL	CRIWS	EG	10K*S	VCH	AREA	.01K
29040.000	480.00	0.00	0.00	627.60	1730.00	638.00	0.00	638.04	3.46	2.40	1960.88	929.66
30375.000	605.00	0.00	0.00	629.30	1730.00	638.27	0.00	638.38	8.57	3.43	1339.04	590.95
31190.000	815.00	0.00	0.00	634.80	1730.00	639.64	0.00	639.80	54.46	4.75	776.72	236.42
31990.000	800.00	0.00	0.00	635.10	1630.00	642.17	0.00	642.26	17.24	3.75	1245.23	392.62
32470.000	460.00	0.00	0.00	632.20	1630.00	643.03	0.00	643.40	25.92	5.74	491.84	320.14
32540.000	70.00	0.00	0.00	633.00	1630.00	643.46	0.00	643.64	12.16	6.03	663.45	467.52

UPPER ROUGE LIVONIA CITY

SUMMARY PRINTOUT TABLE 150

SECNO	Q	CWSEL	DIFWSP	DIFWSX	DIFKWS	TOPWID	XLCH
22865.000	1730.00	629.88	0.00	0.00	0.00	66.17	0.00
22895.000	1730.00	629.90	0.00	0.02	0.00	66.25	30.00
22935.000	1730.00	631.55	0.00	1.65	0.00	86.02	40.00
22985.000	1730.00	631.84	0.00	0.30	0.00	261.60	50.00
23775.000	1730.00	632.53	0.00	0.69	0.00	212.97	790.00
24852.000	1730.00	633.47	0.00	0.94	0.00	154.47	1077.00
25052.000	1730.00	633.99	0.00	0.52	0.00	147.90	200.00
25108.000	1730.00	635.13	0.00	1.14	0.00	150.14	56.00
25183.000	1730.00	635.31	0.00	0.18	0.00	218.08	75.00
25628.000	1730.00	635.93	0.00	0.62	0.00	348.96	445.00
26038.000	1730.00	636.35	0.00	0.42	0.00	185.09	410.00
26088.000	1730.00	636.31	0.00	-0.03	0.00	246.01	50.00
26184.000	1730.00	636.32	0.00	0.01	0.00	246.33	96.00
26234.000	1730.00	636.69	0.00	0.36	0.00	278.58	50.00
26860.000	1730.00	636.79	0.00	0.10	0.00	316.07	626.00
28232.000	1730.00	637.07	0.00	0.28	0.00	234.34	1372.00
28233.000	1730.00	637.17	0.00	0.10	0.00	236.23	1.00
28240.000	1730.00	637.24	0.00	0.07	0.00	237.64	7.00
28241.000	1730.00	637.22	0.00	-0.03	0.00	237.11	1.00
28560.000	1730.00	637.76	0.00	0.55	0.00	306.70	319.00
29040.000	1730.00	638.00	0.00	0.23	0.00	339.11	480.00
30375.000	1730.00	638.27	0.00	0.28	0.00	337.93	605.00
31190.000	1730.00	639.64	0.00	1.36	0.00	302.26	815.00
31990.000	1630.00	642.17	0.00	2.53	0.00	269.00	800.00
32470.000	1630.00	643.03	0.00	0.86	0.00	122.17	460.00
32540.000	1630.00	643.46	0.00	0.43	0.00	129.43	70.00

SUMMARY OF ERRORS

```
**********************************************************
     HEC2 RELEASE DATED NOV 76 UPDATED FEB 1977
     ERROR CORR -  01
     MODIFICATION -  50,51,52
**********************************************************
```

```
**************************************************************
*                                                            *
*                    E R R O R   S U M M A R Y               *
*                                                            *
*                                                            *
*       0  ERROR(S) DETECTED BY THE USER PROGRAM             *
*       0  ERROR(S) DETECTED BY THE MATHEMATICAL PACKAGE     *
*       0  ERROR(S) DETECTED FOR INPUT/OUPUT STATEMENTS      *
*                                                            *
**************************************************************
```

MATCH LINE SEE SHEET 2

MATCH LINE SEE SHEET 3

Bryant Jr High Sch

St Mathews Ch

Sunset Park

Meadows Park

Mt Hope Memorial Garden (Cemetery)

Northwest Hebrew Cem

Bethel Memorial Park (Cemetery)

Tarabusi

Wolfrom Dr

Terrace Ct

Bell

Riley Jr High Sch

Madison Sch

Bell Creek

LIVONIA

5 MILE RD.

6 MILE RD.

GMILE RD.

MERRIMAN RD.

MIDDLEBELT RD.

INKSTER RD.

OAK GRV AVE

DEERING AVE

FOCH AVE

GREEN

BM 643

BM 629

635

637

639

640

625

T1

T2

T3

T4

LEGEND

FLOODWAY — 100 YEAR BOUNDARY — 500 YEAR BOUNDARY

CROSS SECTION

CORPORATE LIMIT

COUNTY BOUNDARY

FLOOD MAP

OAKLAND COUNTY

PLYMOUTH TWP

NORTHVILLE TWP

LIVONIA

REDFORD TWP

WESTLAND

DEARBORN HEIGHTS

GARDEN CITY

INKSTER

DEARBORN

WAYNE

VICINITY MAP
NO SCALE

8 MI. RD.

7 MI. RD.

6 MI. RD.

SHT. 4

SHT. 2

SHT. 3

SHT. 1

HAGGERTY RD.

FARMINGTON RD.

MERRIMAN RD.

MIDDLEBELT RD.

WESTERN RD.

JOY RD.

SHEET INDEX MAP

CITY OF LIVONIA

WAYNE COUNTY, MICHIGAN

SCALE: 1"=400'

SHEET 1 of 4

HUD 2014-10

MATCH LINE SEE SHEET 4

MATCH LINE SEE SHEET 1

CITY OF LIVONIA

WAYNE COUNTY, MICHIGAN

SCALE: 1"=400'

FLOOD MAP

LEGEND

FLOODWAY — 100 YEAR BOUNDARY — 500 YEAR BOUNDARY

CROSS SECTION

CORPORATE LIMIT


COUNTY BOUNDARY

SHEET 2 of 4

HUD 2014-10

MATCH LINE SEE SHEET 4

MATCH LINE SEE SHEET 1



N

LEGEND

FLOODWAY — 100 YEAR BOUNDARY — 500 YEAR BOUNDARY

A — A CROSS SECTION

CORPORATE LIMIT

COUNTY BOUNDARY

FLOOD MAP

CITY OF LIVONIA

WAYNE COUNTY, MICHIGAN

SCALE: 1" = 400'

SHEET 3 of 4

HUD 2014-10

8 MILE ROAD

BM 693

Creek

700

675

698

4

3

690

100

GILL RD.

FARMINGTON RD.

Tyler Sch

MATCH LINE SEE SHEET 2

7 MILE

BM 688

ROAD

BM 664

Pilgrim Ch

RD

DR

GOLFVIEW

IS RD

Pierson Sch

Hebr Sch

MATCH LINE SEE SHEET 3

N

LEGEND

FLOODWAY — 100 YEAR BOUNDARY — 500 YEAR BOUNDARY

A — A CROSS SECTION

CORPORATE LIMIT

COUNTY BOUNDARY

FLOOD MAP

CITY OF LIVONIA

WAYNE COUNTY, MICHIGAN

SCALE: 1" = 400'

SHEET 4 of 4

HUD 2014-10

1) COUNTY: Wayne

2) STUDY NAME: City of Northville

3) WATERCOURSE: Middle Branch Rouge River and Johnson Drain

4) DOCUMENT TYPE: Floodway

Received 9/79

```
C
T1      CITY OF ROSEVILLE, MN SUB 7906-07
T2      MISC. ROAD STUDY SECTIONS FROM COSER START  S. CROSS ST. TO T.H. 51
T5      MID.ROUGE R. W.VILLE C.

J1  ICHECK   IPO      NINP     IOUT     STPR     METRIC   DUMPS    I        IOPT     EU
          0.       0.       0.       0.  3.000000     0.30      0.5       0.   744.075     3.000

J2  NPROF    IPLOT    PROWS    XSLOW    XSCOH    FN       ALPHA    TMP      CHAIN    ITRACE
        1.000    0.000   -1.000    0.300    0.000    0.000    0.000    5.000    0.000    0.000

J3  JA TABLE CODE FOR SUMMARY PRINTOUT
      130.000  150.000  200.000    0.300    0.000    0.000    0.000    0.000    0.000    0.000

      5.001    0.300    5.000    0.000    1.410    5.000    5.000    5.000    0.000    0.000
      5.100    0.000    0.010    0.100    0.300    1.000    1.000    5.000    0.000    0.000
      0.000 2270.000 3170.000 4640.000 5600.000 6092.000 7610.000    0.000    0.000    0.130

S/S PARK ENTOSE FROM NOVILLE TWP F/S

      5.000    3.300  365.000  465.000    0.300    5.020    5.000    3.000    6.000    3.000
      5.000    0.300    5.000  165.000    0.500  705.000    1.000    3.000    5.000    0.000
      0.000    0.300  275.000  110.000  751.000  162.000   26.000  113.000  762.000    2.000
      1.000  410.300  759.500  425.000  750.000  630.000  757.100  440.000  759.000  465.000
      1.500  480.300  762.000  590.000  765.000  685.000  777.500 1255.000  779.000 1250.000

      300.000    0.300    5.000    0.000  300.000  300.000  300.000    0.000    0.000    0.000
        0.000    0.000    0.000  230.000    0.000  600.000    0.000    0.000    0.000    0.000

      900.000    0.300    0.000    0.000  300.000  300.000  300.000    0.000    0.000    0.000
        0.000    0.300    0.000  505.000    0.000  545.000    0.000    0.000    0.000    0.000
        0.100    0.100    0.025    0.300    0.500    0.300    0.000    0.000    0.000    0.000

      975.000    0.300  575.000  600.000  300.000  375.000  375.000    0.000    0.300    0.000
        0.000    0.300    0.000  545.000    0.000  600.000    0.300    0.300    0.000    0.000
      500.000    0.300  250.000    0.000  300.000  300.000  225.000  350.000  700.000  500.000
      750.000  525.300  750.000  575.000  700.000  705.000  775.000  750.000  750.000  500.000
      750.000  750.300  750.000  600.000  765.000  770.000  775.000  750.000  750.000 1250.000
        0.100    0.100    0.025    0.300    0.500    0.300    0.000    0.000    0.000    0.000
```

FORM 1411-GD PRINTED BY ROTARY MANIFOLD FORMS.

D/S FACE 7 MILE RD. BRIDGE CORPS C.S.#31

X1	1023.000	16.000	975.000	1035.000	50.000	50.000	50.000	0.000	0.000	0.000
X2	10.000	0.000	0.000	0.000	0.000	0.000	0.000	775.000	775.000	0.000
X3	990.000	0.000	771.000	20.000	771.000	770.500	770.500	940.000	765.000	940.000
X4	775.000	975.000	754.000	950.000	760.000	930.000	957.400	1055.000	760.000	1024.000
X5	995.000	1025.000	775.000	1035.000	767.500	1140.000	765.000	1247.000	765.000	1247.000
X6	775.000	1690.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
X7	1.050	1.500	3.000	0.000	25.000	2.000	691.570	1.170	757.400	757.400

D/S FACE 7 MILE RD. BRIDGE

X1	1078.000	0.000	0.000	0.000	50.000	50.000	50.000	0.000	0.000	0.000
X2	0.000	0.000	1.000	775.000	775.000	1.000	0.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	775.000	775.000	0.000
X4	5.000	1240.000	1615.000	1650.000	1650.000	2490.000	1005.000	0.000	0.000	0.000

D/S NORTHVILLE DOUNS BOX CULVERT

X1	1113.000	12.000	959.000	1011.000	35.000	45.000	75.000	0.000	0.000	0.000
X2	10.000	1.000	0.000	965.000	0.000	1045.000	0.000	769.000	769.000	0.000
X3	980.000	0.000	771.000	20.000	771.000	770.000	770.000	940.000	765.000	940.000
X4	767.000	989.000	767.000	1013.000	766.500	1.45.000	767.000	1140.000	765.000	1247.000
X5	766.000	1660.000	775.000	1690.000	0.000	0.000	0.000	0.000	0.000	0.000
X6	0.100	0.170	0.340	0.300	0.500	0.000	0.000	0.000	0.000	0.000

D/S FACE TIMES ST. BRIDGE CORPS C.S.#35

X1	2163.000	16.000	316.000	342.000	1050.000	1050.000	1050.000	0.000	0.000	0.000
X2	0.000	0.000	0.000	777.200	778.800	0.000	0.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	205.000	0.000	365.000	0.000	775.000	775.000	0.000
X4	0.000	0.000	779.250	775.000	779.700	0.000	0.000	0.000	0.000	0.000
X5	0.000	0.000	0.000	0.000	318.000	370.000	0.000	315.000	775.000	775.000
X6	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
X7	770.500	777.000	342.000	778.800	777.200	242.000	774.000	0.000	695.000	761.500
X8	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
X9	770.250	0.000	753.000	0.000	779.000	120.000	778.500	295.000	773.500	307.300
X10	770.000	777.000	770.000	777.000	770.000	774.000	777.000	0.000	765.000	842.000
X11	770.000	0.000	775.000	0.000	772.000	0.000	0.000	550.000	775.000	0.000
X12	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000

D/S ST U/S RIVER ST. BRIDGE CORPS C.S.#36

X1	3.000	17.000	60.000	775.000	50.000	50.000	50.000	0.000	0.000	0.000
X2	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
X3	770.000	0.000	771.000	0.000	771.000	50.000	775.000	50.000	775.000	50.000
X4	770.000	53.000	770.000	125.000	775.000	125.000	775.000	0.000	775.000	335.000
X5	775.000	343.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000

PRINTED IN U.S.A.
FORM 1411-00 PRINTED BY ROTARY MANIFOLD FORMS.

X1	2863.000	10.000	108.000	140.000	305.000	350.000	350.300	0.000	0.000	0.000
GR	790.500	0.000	790.000	95.000	785.000	105.000	776.300	100.000	775.800	120.000
G	777.500	140.000	737.500	170.000	789.000	130.000	789.300	460.000	791.000	570.000

[illegible] FACE MAIN ST. BRIDGE [illegible] CORPS C.S.456

X1	2963.000	10.000	210.000	240.000	105.000	100.000	100.000	0.707	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	788.000	788.000	0.000
GR	907.000	0.000	794.000	20.000	790.000	208.000	776.500	410.000	775.900	224.000
GR	775.900	130.000	775.500	240.000	790.000	241.000	762.000	370.000	787.000	390.000
GR	1.250	1.000	3.000	0.000	22.400	1.500	200.000	0.000	77.900	77.900

J/S FACE MAIN ST. BRIDG

X1	3063.000	10.000	210.000	240.000	130.000	100.000	100.000	0.707	0.000	0.000
GR	0.000	0.000	1.000	785.400	794.300	0.000	0.000	0.000	0.707	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	791.000	791.000	0.000
BT	11.000	0.000	807.000	0.000	20.000	794.000	0.000	210.000	791.300	0.000
BT	210.000	791.300	785.400	224.000	791.300	785.400	224.000	791.300	0.000	226.000
BT	791.300	0.000	226.000	791.300	785.400	242.000	791.300	785.400	242.000	791.300
BT	0.000	791.300	787.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
GR	807.000	0.000	794.500	20.000	790.000	208.000	776.500	210.000	775.900	224.000
GR	775.900	226.000	776.500	240.000	790.000	241.000	762.000	370.000	787.000	390.000
NC	0.150	0.100	0.040	0.300	0.500	0.030	0.000	0.000	0.000	0.000

[illegible] FT U/S MAIN ST. BRIDGE

X1	3113.000	7.000	75.000	110.000	50.000	50.000	50.000	0.000	0.000	0.000
GR	806.000	0.000	790.000	30.000	787.500	58.000	776.000	75.000	776.000	110.000
GR	787.000	127.000	800.000	150.000	0.000	0.000	0.000	0.000	0.000	0.000

[illegible] U/S [illegible] MOTOR CO. BR [illegible] CORPS C.S.433

X1	3276.000	13.000	75.000	139.000	165.000	165.000	165.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	66.000	0.000	165.000	0.000	0.000	0.000	0.000
[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]
[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]
[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]

U/S FORD MOTOR CO. BR

X1	3327.000	10.000	90.000	146.000	49.000	49.000	10.000	0.000	0.000	0.000
[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]
GR	806.000	0.000	799.500	30.000	789.000	65.000	783.000	80.000	776.500	[illegible]
GR	775.500	130.000	791.000	140.000	788.000	142.000	787.500	300.000	800.000	800.000
BC	0.000	1.500	3.000	0.000	0.100	0.300	0.100	0.000	776.500	776.500

[illegible] STR. CO. 3 [illegible] CORPS C.S.440

X1	3426.000	0.700	5.000	0.300	1.500	1.650	0.062	0.000	0.000	0.000
X3	10.000	0.000	5.000	0.100	0.200	0.500	0.000	795.000	795.000	0.000
[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]
[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]
[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]
[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]
[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]
[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]
[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]

PRINTED IN U.S.A.
FORM 1411-08-PRINTED BY ROTARY MANIFOLD FORMS.

D/S FACE TRUCK BRIDGE

	5672.000	0.000	675.000	545.300	345.000	524.000	374.000	0.000	0.000	0.000
	10.000	0.300	0.000	0.300	0.000	0.000	0.000	791.500	791.500	0.000
	0.000	0.000	791.500	525.000	787.700	700.000	495.000	791.100	791.100	516.000
G6	787.700	522.000	790.500	525.000	791.300	700.000	810.000	700.000	0.000	0.000
S1	0.000	1.500	3.000	0.000	20.500	0.000	195.000	1.500	783.100	783.100

D/S FACE TRUCK BRIDGE

X1	3694.000	0.000	0.000	0.000	12.000	12.000	12.000	0.000	0.000	0.000
X2	0.000	0.000	1.000	787.700	790.500	0.000	0.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	791.500	791.000	0.000
	0.000	0.000	516.000	0.000	475.000	790.500	0.000	482.000	790.500	0.000
B1	495.000	790.500	787.700	525.000	790.500	787.500	562.000	791.500	1.000	525.000
	790.500	0.000	791.000	791.000	0.000	790.500	812.000	0.500	0.000	0.000

VALLEY SECTION

	3695.000	0.000	495.000	516.600	141.300	141.300	141.000	0.500	-1.000	0.000
	527.100	0.000	785.000	525.000	792.500	495.000	784.000	305.500	784.000	516.600
	787.100	516.600	784.000	530.000	793.300	660.000	796.000	830.000	801.500	923.000

D/S FACE CRISWALD ST. BRIDGE

	3695.000	10.000	495.000	516.600	140.300	140.000	140.000	0.891	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	791.100	791.100	0.000
3P	517.500	0.000	795.000	479.000	784.600	495.000	784.600	505.000	784.600	506.600
	785.100	516.600	794.000	530.000	793.000	660.000	796.000	830.000	801.500	920.000
50	1.200	1.400	11.000	0.000	40.250	1.400	110.000	0.300	714.600	716.600

U/S FACE CRISWALD ST. BRIDGE

X1	4023.000	10.000	495.000	516.600	63.000	63.000	63.000	0.891	0.000	0.000
	0.000	0.000	1.000	791.100	787.500	0.000	0.000	0.000	0.000	0.000
	10.000	0.000	0.000	450.000	0.000	505.000	0.000	794.500	794.500	0.000
	0.000	0.000	516.600	0.000	479.500	784.600	0.000	505.000	794.500	0.000
U1	493.000	794.500	791.100	505.000	794.500	791.100	505.000	794.500	0.000	506.600
U1	794.500	0.000	506.600	794.500	791.100	516.600	794.500	791.100	516.600	794.500
B1	0.000	530.000	794.500	0.000	660.000	797.500	0.000	830.000	796.000	0.000
U1	920.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
5P	17.300	7.450	794.000	479.000	784.600	495.000	794.000	505.000	784.600	506.600
3P	785.100	516.600	793.500	530.000	793.000	660.000	796.000	830.000	801.500	920.000
9C	0.100	0.100	0.700	0.300	0.500	0.000	0.000	0.000	0.000	0.000

FORM 1411-GB PRINTED BY ROTARY MANIFOLD FORMS, IN U.S.A.

G2	788.100	440.000	799.800	460.000	794.000	400.000	800.000	615.000	810.000	655.000
QT	5.000	1040.000	1590.000	1820.000	1820.000	2460.000	0.000	0.000	0.000	0.000
ET	0.000	0.000	0.000	5.000	9.100	0.000	0.000	0.000	417.440	480.960

30 FT D/S DILL POND DAM — CORPS C.S.#45

X1	4858.000	11.000	425.000	480.000	300.000	500.000	390.000	0.000	0.000	0.000
G1	870.000	0.000	800.300	100.000	302.000	410.000	794.000	425.000	794.000	440.000
G2	792.000	450.000	796.000	460.000	794.000	480.000	805.300	500.000	805.000	550.000
G3	807.000	390.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
ET	0.300	9.100	9.100	9.100	9.100	9.100	0.300	0.000	396.000	396.000

D/S DILL POND DAM

X1	4907.000	11.000	394.000	396.000	49.000	75.000	50.000	0.000	0.000	0.000
G1	410.000	0.000	807.000	100.000	804.000	200.000	800.000	394.000	795.000	385.000
G2	794.000	385.000	794.000	390.000	799.000	355.000	804.000	396.000	805.000	430.000
QT	807.000	480.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
SD	0.000	1.500	2.000	0.000	0.100	0.000	0.100	0.000	794.000	794.000

DILL POND #3 — CORPS C.S.#44

X1	4908.000	1.000	0.000	0.000	1.000	1.000	1.000	0.000	0.000	0.000
X2	0.000	0.000	1.000	0.000	661.000	0.000	0.000	0.000	0.000	0.000
X3	12.000	0.000	0.000	0.000	0.000	0.000	0.000	810.000	810.000	0.000
QT	0.000	1.000	810.000	0.000	394.000	614.000	1.000	394.000	801.000	0.000
ST	395.000	1.000	0.000	396.000	612.000	1.000	410.000	810.000	0.000	0.000
SD	0.100	0.100	0.000	0.100	0.000	0.000	0.000	0.000	0.000	0.000

DILL POND

X1	4910.000	11.000	41.000	320.000	402.000	402.000	400.000	0.000	0.000	0.000
X2	999.000	1.000	810.000	41.000	812.000	1.000	10.000	0.000	800.000	40.000
G1	502.000	800.000	794.000	520.000	815.000	560.000	810.500	460.000	819.000	510.000
X3	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000

30 FT D/S C.O. R.R. BRIDGE #1

X1	5924.000	6.000	90.000	250.000	520.000	520.000	620.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	3.000	0.000	0.000	0.000	810.000	810.000	0.000
G1	830.000	0.000	810.000	50.000	800.000	80.000	100.000	250.000	805.000	280.000
QT	815.000	300.000	0.000	0.000	0.000	0.000	1.000	0.000	0.000	1.000

30 FT D/S C.O. R.R. BRIDGE #2

X1	5078.000	12.000	270.000	290.000	150.000	140.000	150.000	0.000	0.000	0.000
X2	3.000	0.000	0.000	257.500	0.000	312.500	0.000	0.000	0.000	0.000
X3	820.000	0.000	810.000	50.000	805.000	120.000	100.000	140.000	805.000	280.000
QT	795.000	0.000	0.000	0.000	0.000	50.000	0.000	0.000	801.000	0.000
SD	400.000	500.000	810.000	800.000	0.000	0.000	0.000	0.000	0.000	0.000

SR	798.400	240.000	798.500	242.000	798.600	244.000	798.700	246.000	798.800	248.000
SF	796.900	250.000	802.500	251.000	0.000	0.000	0.000	0.000	0.000	0.000
SB	0.000	1.630	3.300	0.000	15.300	0.000	150.300	0.000	796.400	798.400

U/S EAST SIDE, S.W. QUEUE

X1	5176.000	0.300	0.300	0.300	50.000	50.000	50.000	0.000	0.000	0.000
X2	0.000	0.300	1.300	800.200	813.700	0.000	0.000	0.000	0.000	0.000
X3	10.000	0.300	0.300	0.300	1.000	0.000	0.000	815.000	815.000	0.000
[illegible]	11.000	0.200	813.700	0.300	50.000	313.700	0.000	50.000	813.700	0.000
[illegible]	360.000	255.700	0.300	255.300	813.700	50.000	298.000	813.700	0.000	258.000
[illegible]	813.700	813.300	332.300	555.700	000.000	258.000	813.700	806.200	256.000	311.300
[illegible]	807.000	758.300	813.700	808.300	240.000	813.700	308.200	242.000	813.700	308.000
[illegible]	244.000	805.700	807.000	246.000	813.700	306.200	246.000	813.700	805.000	257.000
[illegible]	813.700	802.700	250.000	813.700	0.000	251.000	812.700	0.000	0.000	0.000

[illegible] S.W. [illegible] SOUTH S.W. EAST

X1	5224.000	12.300	270.000	220.300	50.000	50.000	50.000	0.000	0.000	0.000
X3	0.000	0.300	0.000	215.300	0.000	335.000	0.000	0.000	0.000	0.000
[illegible]	68.[illegible]	[illegible].10	[illegible]	50.300	813.500	101.000	312.000	[illegible].000	805.000	250.000
[illegible]	[illegible]	[illegible].30	[illegible].70	220.300	0.000	[illegible]	[illegible].000	300.000	301.500	301.000
[illegible]	[illegible]	[illegible].30	[illegible]	70.300	0.000	0.000	0.000	0.000	0.000	
[illegible]	0.120	0.170	0.[illegible]	0.300	0.540	0.000	0.000	0.000	0.000	0.000
[illegible]	0.000	0.[illegible]	0.[illegible]	7.100	7.100	7.100	215.000	450.000	299.300	597.1

[illegible] STEEL

[illegible]	[illegible]	15.300	335.000	359.000	[illegible].000	700.000	922.000	0.000	0.000	0.000
[illegible]	0.000	0.300	320.000	50.300	813.000	120.000	306.900	150.000	806.000	247.000
[illegible]	805.000	733.700	302.300	338.300	801.700	342.000	801.300	356.000	803.300	359.000
[illegible]	[illegible]	[illegible]	[illegible].[illegible]	526.300	[illegible].[illegible]	[illegible].000	[illegible].000	556.000	812.[illegible]	[illegible]

[illegible] [illegible] [illegible] FIELD [illegible] STA. 25+18

[illegible]	340.[illegible]	12.000	224.650	261.[illegible]	500.000	120.300	150.[illegible]	0.200	0.000	0.000
[illegible]	[illegible].[illegible]	[illegible].000	[illegible]	[illegible].000	0.000	[illegible].[illegible]	[illegible].[illegible]	824.900	[illegible].[illegible]	0.000
[illegible]	120.[illegible]	[illegible].000	805.[illegible]	15.000	300.000	54.[illegible]	[illegible].[illegible]	15.[illegible]	[illegible].[illegible]	5.000
[illegible]	[illegible].[illegible]	[illegible].[illegible]	605.[illegible]	325.[illegible]	502.700	[illegible].[illegible]	[illegible].[illegible]	[illegible].[illegible]	[illegible].[illegible]	[illegible].[illegible]
[illegible]	502.[illegible]	160.000	[illegible].000	361.000	0.300	[illegible].000	[illegible].[illegible]	[illegible].[illegible]	[illegible].000	0.000
[illegible]	0.[illegible]	[illegible].[illegible]	[illegible].000	[illegible].000	23.700	[illegible].[illegible]	114.000	[illegible].[illegible]	[illegible].[illegible]	852.[illegible]

[illegible] [illegible] [illegible] [illegible] FIELD BOX [illegible], 2+30

[illegible]	[illegible]	0.300	0.300	0.300	[illegible].[illegible]	[illegible].000	[illegible].000	[illegible].000	0.000	0.000
[illegible]	[illegible]	0.[illegible]	.300	[illegible].[illegible]	[illegible].[illegible]	[illegible].000	0.000	[illegible].000	[illegible].000	0.000
[illegible]	[illegible]	[illegible]	0.300	[illegible].[illegible]	[illegible]	3.[illegible].000	0.000	[illegible].[illegible]	[illegible].[illegible]	[illegible].000
[illegible]	[illegible]	[illegible]	[illegible].300	[illegible].[illegible]	[illegible]	[illegible]	0.300	[illegible].000	83.[illegible]	0.000
[illegible]	[illegible].[illegible]	0.[illegible]	[illegible].[illegible]	361.[illegible]	[illegible].[illegible]	[illegible].[illegible]	[illegible].[illegible]	[illegible].[illegible]	[illegible].[illegible]	554.[illegible]
[illegible]	[illegible]	[illegible]	[illegible].[illegible]	[illegible].[illegible]	[illegible].[illegible]	[illegible].[illegible]	[illegible].[illegible]	[illegible].300	[illegible]	0.000

[illegible] [illegible] [illegible] FIELD INLET ST. 25+00

[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]
[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]
[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]

53 FT D/S C.O. R.R. BRIDGE #2 FIELD BOOK STA. 22+50

X1	7868.000	13.000	551.200	569.000	350.000	350.200	350.200	0.000	0.200	0.200
X3	0.200	0.000	0.200	553.000	0.000	551.000	0.200	0.200	0.200	0.200
GR	830.000	0.000	822.200	20.000	814.700	260.000	813.100	360.000	812.700	400.000
GT	807.700	423.000	806.800	548.000	806.000	551.000	805.700	560.000	806.000	569.000
GT	811.700	573.000	813.400	602.000	840.000	603.000	0.000	0.000	0.000	0.000

D/S FACE C.O. R.R. BRIDGE #2 FIELD BOOK STA. 21+97

X1	7921.000	13.000	546.500	573.500	53.000	53.200	53.000	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	816.300	816.300	0.000
GR	830.000	0.000	822.000	20.000	814.700	260.000	813.100	360.000	812.700	400.000
GT	807.700	423.000	806.000	546.500	806.000	552.300	806.000	561.500	807.300	573.500
GT	811.700	574.000	813.000	603.000	840.000	595.300	0.000	0.000	0.200	0.000
GT	1.284	1.840	30.000	0.200	27.000	3.000	145.000	0.000	806.300	876.000

U/S FACE C.O. R.R. BRIDGE #2 FIELD BOOK STA. 21+55

X1	7865.000	13.000	0.000	0.000	44.000	44.000	44.000	0.000	0.200	0.000
X3	0.000	0.200	1.000	811.700	819.200	0.000	0.000	0.000	0.000	0.000
X5	10.000	0.000	0.000	0.000	0.000	0.000	0.000	820.000	820.000	0.000
GT	14.000	0.200	840.000	0.000	20.000	822.000	0.000	260.000	820.000	0.000
GT	360.000	812.700	0.000	546.500	819.200	0.000	546.500	819.200	811.700	558.500
GT	819.200	811.700	558.500	819.200	0.000	561.500	819.200	0.000	561.500	819.200
GT	811.700	573.500	819.200	811.700	573.500	819.200	0.000	573.000	819.200	0.000
GT	575.000	847.000	0.000	0.000	0.000	0.000	0.000	0.000	0.200	0.000
GC	0.100	3.100	0.035	0.300	8.500	0.000	0.000	0.000	0.000	0.000

153 FT U/S C.O. R.R. BRIDGE #2 FIELD BOOK STA. 20+00

X1	7813.200	13.000	557.000	573.000	60.200	57.000	141.200	0.200	0.000	0.000
X3	0.000	0.000	0.000	275.000	0.000	325.000	0.000	0.000	0.000	0.000
GR	830.000	0.000	814.700	3.000	813.900	102.000	309.100	200.000	809.400	287.000
GT	807.000	293.000	806.600	330.000	806.700	307.000	808.600	313.000	810.200	326.000
GT	329.000	347.000	330.300	425.000	821.000	340.000	0.000	0.000	0.200	0.000
GC	0.100	3.100	0.035	0.300	8.500	0.000	0.000	0.000	0.000	0.000

33 FT D/S 8 FILE 10. CULVERT FIELD BOOK STA. 16+00

X1	8316.000	14.200	307.000	333.000	125.000	250.000	400.000	0.000	0.200	0.000
X3	0.000	0.100	0.000	297.000	1.000	301.000	0.000	0.000	0.200	0.000
GR	828.000	41.900	816.000	20.200	814.500	90.000	812.400	120.000	811.400	240.000
GT	811.700	307.200	807.700	312.000	807.800	320.000	305.100	326.000	810.000	331.000
GT	811.900	338.200	321.000	456.000	822.200	491.000	850.000	1041.000	0.000	0.000

U/S FACE 10. CULVERT

X1	8565.000	13.200	0.200	44.000	37.000	37.000	37.000	0.000	0.000	0.200
GT	140.000	2.100	811.700	0.000	307.100	2.200	115.700	4.000	827.100	10.200
GT	670.700	19.000	806.700	29.000	809.200	37.200	809.500	40.200	840.000	41.000
GC	0.200	5.137	0.230	2.850	0.500	0.200	0.200	0.200	0.000	1.700

U/S FACE 8' FILE RD. CULVERT FIELD BOOK STA. 15+82

X1	8569.000	13.200	0.200	44.000	44.200	0.000	0.000	0.000	0.000	0.000

PRINTED IN U.S.A.
FORM 141-GB-PRINTED BY ROTARY MANIFOLD FORMS.

BT	67.000	0.000	840.000	0.000	0.000	840.000	811.700	0.500	840.000	814.200
BT	1.000	840.000	815.000	2.000	340.000	816.100	3.000	840.000	816.800	4.000
BT	840.000	817.400	5.300	840.000	817.600	6.600	840.000	817.700	7.000	840.000
BT	817.600	8.000	840.000	817.400	9.000	840.000	816.800	10.000	840.000	816.100
BT	11.000	840.000	815.000	11.500	340.000	814.200	12.000	840.100	811.700	10.000
BT	840.000	811.700	16.500	840.000	814.200	17.000	840.000	815.000	20.000	840.000
BT	816.100	21.000	840.000	815.800	22.000	840.000	817.400	23.000	840.000	817.600
BT	24.000	840.000	817.700	25.000	840.000	817.500	26.000	840.000	817.400	27.000
BT	840.000	816.800	28.000	840.000	816.100	29.000	840.000	815.000	29.500	840.000
BT	814.200	30.000	840.000	811.700	36.000	840.000	811.700	36.500	840.000	816.200
BT	37.000	840.000	815.000	38.000	840.000	816.100	39.000	840.000	816.800	40.000
BT	840.000	817.400	41.000	840.000	817.600	42.000	841.000	817.700	43.000	840.000
BT	817.600	44.000	840.000	817.400	45.000	840.000	816.800	46.000	840.000	816.100
BT	47.000	840.000	815.000	47.500	840.000	814.200	48.000	840.000	811.700	48.000
BT	840.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
GR	840.000	0.000	811.700	0.000	809.100	0.500	808.300	1.000	807.100	2.000
GR	807.100	3.000	806.000	4.000	805.800	5.000	806.700	6.000	805.800	7.000
GR	806.000	9.000	806.500	9.000	807.100	10.000	808.300	11.000	809.100	11.500
GR	811.700	13.000	807.700	13.000	809.100	14.500	808.700	19.000	809.100	20.000
GR	808.700	21.000	808.700	22.000	808.700	23.500	808.700	24.000	808.700	25.000
GR	808.700	26.000	808.700	27.000	808.700	28.000	808.700	29.000	809.100	29.500
GR	811.700	30.000	811.700	35.000	809.500	36.500	809.500	37.500	809.500	38.500
GR	809.500	39.000	809.500	40.000	809.300	41.500	810.500	42.500	809.500	43.000
GR	810.500	44.000	809.500	45.000	809.100	46.500	809.500	47.000	809.500	47.500
GR	811.700	48.000	810.100	48.000	0.000	0.500	0.000	0.000	0.000	1.000

U/S FACE N MILE RD. CULVERT FIELD BOOK STA. 1+00

BT	3671.300	67.000	0.000	45.000	255.000	253.300	255.000	0.500	0.000	0.000
BT	67.000	0.000	840.000	0.000	0.000	842.300	0.000	0.500	840.000	815.000
BT	1.000	840.000	816.000	2.000	340.000	807.100	3.000	840.000	817.600	4.000
BT	840.000	818.300	5.000	840.000	816.500	6.500	840.000	818.600	7.000	840.000
BT	818.500	8.000	840.000	818.300	9.000	840.000	817.600	10.000	840.000	817.100
BT	11.000	840.000	816.000	11.500	340.000	814.200	12.000	840.100	812.600	10.000
BT	840.000	812.600	20.000	840.000	815.300	19.500	840.000	815.000	20.000	840.000
BT	817.100	21.000	840.000	817.800	22.000	840.000	817.400	23.000	840.000	815.000
BT	24.000	840.000	813.600	25.000	840.000	818.500	26.000	840.000	818.300	27.000
BT	840.000	817.000	29.000	840.000	817.100	29.000	840.000	816.000	29.500	840.000
BT	815.000	30.000	840.000	812.600	36.000	840.000	812.600	36.500	840.000	815.000
BT	37.000	840.000	815.000	38.000	840.000	817.100	39.000	840.000	817.000	40.000
BT	840.000	816.800	41.000	840.000	816.100	42.000	840.000	815.000	42.000	840.000
BT	814.200	44.000	840.000	812.600	45.000	840.000	812.600	46.000	840.000	812.100
BT	47.000	840.000	815.000	47.500	840.000	815.000	48.000	840.000	812.600	48.000
BT	840.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
GR	840.000	0.000	812.600	0.000	810.200	0.500	809.200	1.000	808.400	2.000
GR	807.100	3.000	807.500	4.000	807.500	5.000	807.200	6.000	807.500	7.000
GR	807.500	9.000	807.500	9.000	808.100	10.000	809.200	11.000	810.200	11.500
GR	812.600	13.000	809.500	13.000	810.000	16.500	810.300	19.000	810.700	20.000
GR	810.000	21.000	810.000	22.000	810.000	23.000	810.200	24.000	810.000	25.000
GR	810.000	26.000	810.000	27.000	810.000	28.000	810.000	29.000	810.000	29.500
GR	812.600	30.000	812.600	36.000	810.200	36.500	809.600	37.500	809.000	38.500
GR	809.000	39.000	809.000	40.000	809.000	41.500	809.000	42.500	809.000	43.000
GR	809.000	44.000	809.000	45.000	809.000	46.500	809.000	47.000	810.200	47.500
GR	812.600	48.000	812.600	48.000	0.000	0.500	0.000	0.000	0.000	1.000
GR	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000

PRINTED IN U.S.A.
FORM 1411 GB PRINTED BY ROTARY MANIFOLD FORMS.

107 FT D/S 8 MILE RD. CULVERT FIELD BOOK STA. 12+00

X1	8918.000	14.000	441.000	431.300	104.000	104.000	104.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	367.000	0.000	585.000	0.000	0.000	0.000	0.000
SF	825.500	0.000	819.400	800.000	819.800	846.000	812.700	846.000	817.500	424.000
SP	804.600	846.000	805.400	446.700	828.600	691.000	810.100	851.600	813.400	817.000
GP	813.400	546.000	813.900	646.000	821.200	691.000	630.000	953.000	0.000	0.000
VC	0.080	0.080	0.040	0.100	0.300	0.000	0.000	0.000	0.000	0.000

VALLEY SCOTIA FIELD BOOK STA. 0+58

X1	9453.000	13.000	401.000	419.000	800.600	400.000	535.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	255.000	0.000	565.000	0.000	0.000	0.000	0.000
SF	823.500	0.000	818.200	200.000	810.000	290.000	814.300	316.000	812.900	397.000
SP	810.100	401.000	810.000	410.000	810.700	419.000	813.100	423.000	815.000	557.000
GP	123.400	813.000	424.500	654.000	830.200	760.000	0.000	0.000	0.000	0.000
VC	0.100	0.000	0.040	0.300	0.500	0.000	0.000	0.000	0.000	0.000

36.5 FT D/S NEW HOVE RD. BRIDGE FIELD BOOK STA. 2+00

X1	9914.000	13.000	952.100	931.300	125.000	60.000	463.000	0.000	0.000	0.000
X3	0.000	0.000	0.000	902.300	0.000	960.500	0.000	0.000	0.000	0.000
GP	350.000	0.000	819.700	740.300	818.000	792.000	819.900	812.000	817.200	875.000
GP	816.300	903.000	812.200	912.300	810.500	922.000	812.700	951.000	818.000	945.000
GP	817.300	984.000	819.300	1040.000	830.000	2240.000	0.000	0.000	0.000	0.000

D/S FACE OF NEW HOVE RD. BRIDGE FIELD BOOK STA. 1+44.5

X1	9973.500	10.000	1524.500	1575.500	55.500	55.500	55.500	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	823.500	823.500	0.000
SF	823.500	0.000	823.000	1560.000	820.700	1584.900	815.900	1540.000	812.500	1541.000
SP	812.700	1530.000	813.500	1555.000	813.500	1546.000	820.700	1525.500	830.000	2400.000
GP	1.000	0.000	1.000	0.000	21.000	2.300	235.300	1.250	870.000	870.700

U/S FACE NEW HOVE RD. BRIDGE FIELD BOOK STA. 1+07

X1	10311.000	0.200	0.000	0.000	37.300	37.300	37.300	0.300	0.300	0.300
X2	0.000	0.000	1.000	491.200	533.500	0.000	0.300	0.300	0.300	0.100
X3	10.000	0.000	0.000	0.000	0.300	0.300	0.300	823.500	823.500	0.000
SF	14.000	0.000	830.000	0.000	1524.500	823.500	0.300	1524.500	823.500	821.100
LT	1540.000	823.500	821.100	1540.000	823.500	0.000	1541.000	823.500	0.000	1541.000
RT	823.000	821.100	1559.000	823.500	821.100	1559.300	823.500	0.000	1563.000	823.500
GP	0.400	1561.000	823.300	121.200	1575.500	823.500	821.200	1575.500	823.500	821.200
VC	3620.200	823.000	0.000	0.300	0.300	0.300	0.300	0.000	0.000	0.000

D/S FACE C.O. R.R. BRIDGE #3 FIELD BOOK STA. 0+24

X1	11084.000	0.300	1553.000	1567.000	77.000	75.000	53.000	0.000	0.300	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.000	0.000	823.500	823.500	0.000
SF	850.000	0.000	823.000	1533.000	812.900	1533.000	812.900	1567.000	820.500	1567.000
SP	850.000	2420.300	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
GP	0.000	0.000	3.000	0.000	54.000	0.000	245.000	0.300	812.900	812.900

U/S FACE C.O. R.R. BRIDGE #3 FIELD BOOK STA. 0+24

X1	13094.000	0.000	0.300	0.300	10.000	10.000	10.000	0.000	0.000	0.000
X2	0.000	0.000	0.000	820.300	824.100	0.300	0.000	0.000	0.000	0.000

X3	10.300	0.000	0.000	0.000	0.000	0.000	0.000	826.100	826.100	0.000
BT	6.000	0.000	830.300	0.000	1533.000	826.100	0.000	1533.000	829.150	821.100
ST	1567.000	826.100	820.200	1567.000	826.100	0.000	2400.000	830.000	0.000	0.000

D/S E . Sock[illegible]

X1	10103.000	0.000	1539.300	1561.000	0.000	0.300	0.000	0.000	0.000	0.300
X3	10.000	0.000	0.300	0.000	0.000	0.300	0.000	826.300	826.100	0.300
BT	330.000	0.000	823.700	1533.000	813.300	1539.300	812.600	1550.300	613.100	1561.300
ST	823.100	0.000	830.300	2403.000	0.000	0.300	0.300	0.300	0.300	0.300

D/S FACE OLD LOVI RD. BRIDGE FIELD BOOK STA. C+14

X1	10104.000	0.000	0.000	0.000	1.000	1.300	1.000	0.000	0.300	0.300
X3	10.000	0.300	0.000	0.300	0.000	0.000	0.000	826.100	826.100	0.000
BT	6.000	0.000	830.300	0.000	1559.000	826.100	0.300	1539.300	826.100	829.100
ST	1561.000	826.100	823.100	1561.000	826.100	0.300	2401.000	830.100	0.000	0.300

D/S FACE OLD LOVI RD. BRIDGE FIELD BOOK STA. C-14

X1	10102.300	0.000	0.300	0.000	28.000	28.300	28.000	0.300	0.000	0.000
X2	0.000	0.000	0.000	0.000	0.000	0.300	1.300	0.300	0.000	0.000
X3	10.000	0.000	0.300	0.000	0.000	0.300	0.000	826.300	826.100	0.300

D/S OLD LOVI RD.

X1	10103.000	0.000	0.300	0.000	1.000	1.01	1.300	0.000	0.000	0.000
X3	10.000	0.000	0.000	0.000	0.000	0.300	0.000	826.100	826.100	0.000

C.L.E DOOR ST. . U-00 FOR D/S C.L OLD LOVI RD. BRIDGE

BT	10102.300	0.000	831.300	402.013	26.000	28.300	27.300	0.300	0.300	0.000
X3	0.300	0.000	0.000	389.000	0.000	415.000	0.000	0.300	0.000	0.000
ST	830.000	0.000	827.500	367.000	818.700	371.000	815.400	385.000	812.600	352.000
BT	812.700	402.000	812.000	402.000	815.300	415.000	823.900	715.000	830.000	1765.000
X1	0.300	0.000	0.000	0.000	0.000	0.000	0.000	0.300	0.000	0.000

PRINTED IN U.S.A.
FORM T611 GB PRINTED BY ROTARY MANIFOLD FORMS.

*PROF 1

CCHV= 0.100 CEHV= 0.300

*SECNO ***									
SECNO	DEPTH	CWSEL	CRITWS	WSELK	EG	FV	SA	PLOSS	MIN EL BR
1	7.61	FCH	0.00	0.00	0.00	0.00	0.00	1.5	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	CTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IN2	ICONT	CORAR	TOPWID	ERDST
3420 ENCROACHMENT STATION=		705.0	725.0	TYPE=	1	TARGET=	362.500		

D/S PARK BRIDGE FROM NEVILLE TWP P/S

3.07	10.97	768.07	0.00	769.07	768.14	0.07	0.10	0.50	759.50
3080.	1191.	1277.	1111.	1171.	402.	1459.	1.	0.	759.00
0.20	5.81	3.29	0.29	0.100	0.035	0.300	0.250	758.50	187.50
0.000303	0.	0.	0.	0	0	0	0.00	560.00	7.5.00

*SECNO 100.000

3470 ENCROACHMENT STATION=		210.0	440.0	TYPE=	1	TARGET=	430.000		

VALLEY SECTION

470.30	11.13	768.17	0.00	0.20	768.30	0.17	0.13	0.03	760.40
3337.	1308.	1775.	1527.	954.	369.	925.	29.	3.	759.90
0.95	1.06	4.69	1.04	0.100	0.035	0.105	0.255	758.00	230.00
0.000627	300.	300.	300.	2	1	0	0.00	430.00	660.00

*SECNO 400.000

3520 ENCROACHMENT STATION=		305.0	365.0	TYPE=	1	TARGET=	430.000		

VALLEY SECTION

10.03	9.29	770.29	3.00	5.07	769.06	0.17	0.11	0.12	761.20
3230.	844.	2523.	365.	473.	323.	467.	31.	6.	760.60
1.05	1.58	5.39	1.43	0.100	0.035	0.100	0.235	758.50	205.00
0.001901	300.	300.	300.	2	0	0	0.00	280.00	585.00

CCHV= 0.300 CEHV= 0.500

*SECNO 700.000

3800 HW CHANGED MORE THAN HWTOL

3870 ENCROACHMENT STATION=		545.0	630.0	TYPE=	1	TARGET=	90.000		
90 FT T/S					CRIS 3.2.93				
998.00	6.20	760.56	0.00	0.00	771.46	0.36	0.00	0.70	761.30
3030.	761.	3502.	417.	192.	191.	137.	39.	7.	764.00
1.02	1.98	5.11	0.00	0.100	0.035	0.100	0.335	760.10	548.10
0.000	0.	0.	0.	0	0	0	0.00	0.00	0.00

CCHV= 0.300 CEHV= 0.500

*SECNO 1025.000

PRINTED IN U.S.A.
FORM 1411.0B-PRINTED BY ROTARY MANIFOLD FORMS.

3265 DIVIDED FLOW

9301 HY CHANGED MORE THAN HYDIN									
SECNO	QLOB	VOL	CONV	DSTK	SB	HV	FL	WSEL	ELBW
0	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XSL	XNCH	XNR	STN	FLPIN	SSTA
SLOPE	XLOB	XLCH	XROB	ITRIAL	IEP	ICONT	CROWR	TOPWID	SBOST

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,FLEV= 775.00 ELMEA= 775.00

9/5 FACE 7 MILE RD. BRIDGE					COMP# 2.5.13				
1078.00	12.43	769.63	0.00	0.00	770.94	1.12	0.16	0.00	773.09
3680.	0.	3680.	0.	0.	434.	0.	40.	0.	773.03
0.36	0.00	8.48	0.00	0.100	0.025	0.100	0.034	737.40	941.91
0.001618	50.	50.	50.	0	1	0	0.00	49.43	1035.00

SPECIAL BRIDGE

BR	KS	XKOR	COEC	BOLEN	BHC	BUP	AREA	SS	ELCHK	ELCRD
	1.05	5.53	3.00	0.00	23.04	2.00	691.20	1.37	757.46	757.47

*SEC.0 TOPR DCJ

3265 DIVIDED FLOW

CLASS A LOW FLOW

EGPRS	EGLOC	LJ	GLOIR	QPR	SAREA	TRAPEZOID AREA	ELLC	ELTRD
1.00	777.94	7.17	0.	3680.	39..	392.	771.80	775.00

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELEV= 775.00 ELMEA= 775.00

9/5 FACE 7 MILE RD. BRIDGE									
1078.00	12.43	769.63	0.00	0.00	770.94	1.12	0.16	0.00	773.09
3680.	0.	3680.	0.	0.	434.	0.	40.	0.	773.03
0.36	0.00	8.48	0.00	0.100	0.025	0.100	0.034	737.40	941.91
0.001618	50.	50.	50.	0	1	0	0.00	49.43	1035.00

*RECNO 1113.000

9301 HY CHANGED MORE THAN HYDIN

9/5 FACE 7 MILE RD. BRIDGE									

9/5 NORTHVILLE DOWN BOX CULVERT

1113.00	12.99	770.39	0.00	0.00	771.21	0.31	0.22	0.24	757.90
1850.	227.	1449.	175.	253.	286.	209.	40.	8.	757.90
0.06	3.90	5.06	0.84	0.100	0.025	0.100	0.034	757.90	965.80
0.000237	35.	35.	35.	2	0	0	0.00	70.00	1035.30

[illegible]

*SECNO 2163.000

WATER EL=XS CARD= 779.600

[illegible] ENCROACHMENT STATIONS= 295.0 365.0 TYPE= 1 TARGET= 70.700

[illegible] CONAS C.S.335

2963.00	9.70	779.60	0.00	0.00	780.11	0.51	0.50	0.10	770.00
1850.	290.	1474.	86.	143.	231.	71.	55.	9.	769.90
0.12	3.96	5.38	1.22	0.120	0.042	0.300	0.237	769.90	295.60
0.001344	1350.	1350.	1350.	0	0	0	0.30	70.00	565.00

*SECNO 2213.000

[illegible] ENCROACHMENT STATIONS= 35.0 205.0 TYPE= 1 TARGET= 170.000

[illegible] CONAS C.S.336

2213.00	9.96	779.96	0.00	0.00	780.24	0.28	0.26	0.07	773.00
1850.	120.	1512.	217.	118.	324.	232.	56.	9.	775.10
0.12	1.06	4.66	0.24	0.150	0.040	0.100	0.037	770.00	48.28
0.002342	50.	50.	50.	2	0	0	0.00	154.72	205.00

*SECNO 2513.000

SPC ID	DEPTH	CHSEL	ELEVS	SELK	CO	WV	HL	CLOSS	BANK ELEV
	0.00	WC=	ORCO	WLOL	XCH	XPCO	VOL	TAX	LE-T/RIGHT
TYPE	0.00	LC=	VMOH	WTL	XREC	416	STR	E.61.	5670
COUPS	X.OEL	CLEL	XE.IRO	XTLOSL	192	JCCIE	[illegible]	[illegible]	[illegible]

[illegible] SECTION

2513.00	9.63	781.[illegible]	1.[illegible]	0.00	781.63	2.63	0.55	0.42	771.[illegible]
1850.	160.	1526.	164.	112.	254.	121.	0.	11.	771.75
0.14	1.43	6.30	1.35	0.100	0.040	0.100	0.032	771.75	365.49
0.001509	250.	300.	400.	2	0	2	0.00	132.96	459.95

[illegible] [illegible] 0.500

*SECNO 2803.000

[illegible] CHANGED MORE THAN 1 FOOT

[illegible] CONAS C.S.337

2803.00	9.83	790.04	0.30[illegible]	1.00	788.45	1.79	1.07	0.62	770.00
1850.	6.	1523.	23.	6.	163.	19.	62.	11.	777.53
0.15	0.69	5.62	1.37	0.120	0.060	0.120	0.037	770.00	304.46
0.001[illegible]	100.	250.	350.	2	0	0	0.00	142.05	1349.[illegible]

*SECNO 2[illegible]3.000

PRINTED IN U.S.A.
FORM 1411-GB-93 PRINTED BY ROTARY MANIFOLD FORMS.

5301 HV CHANGED MORE THAN HVINS

	SECNO	DEPTH	CWSEL	CRTWS	WSELK	EG	HV	HL	QLOSS	BANK ELEV
	3	9LOB	OCH	3305	ALOB	ACH	ARCH	WOL	TWA	LEFT/RIGHT
1	TIME	VLOB	VCH	AJNT	RYL	XLCH	XMH	WTN	ELMIN	SSTA
2	SLOPE	SLOBL	VLCH	ALOB1	ITRIAL	IN2	ICONT	CORAR	TOPWID	DIST
3										

3645 20 TRIALS ATTEMPTED WSEL,CWSEL
3645 ACCEPTABLE MINIMUM SPECIFIC ENERGY
3720 CRITICAL DEPTH ASSUMED
3645 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELEV= 780.00 ELMIN= 768.01

D/S FACE MAIN ST. BRIDGE CODES C.S.930

7863.30	8.93	794.23	782.34	0.00	785.45	3.11	.11	1.06	776.2
BRI	3	1150	0.	0.	13.	0	13.	1.	780.50
0.15	0.00	14.14	0.00	0.120	0.030	0.120	0.034	775.96	168.47
0.014458	100.	100.	100.	20	11	0	0.00	21.21	169.68

3827 CRITICAL DEPTH

3227 DOWNSTREAM ELEV IS 780.90 +101 782.34 HYDRAULIC JUMP OCCURS DOWNSTREAM (IF LOW FLOW CONTROLS)

SL	SF	AROB	QTOT	ROLEV	INC	TOP	B.AREA	BS	ELCHU	ELCHD
	1.25	1.98	3.00	3.00	22.46	1.40	220.00	0.30	77.90	775.95

*SECNO 3303.000

5301 HV CHANGED MORE THAN HVINS

CLASS B LOW FLOW

5420 BRIDGE W.S.= 782.12 BRIDGE VELOCITY= 14.15 CALCULATED CHANNEL AREA= 131.

EGPRS	ELCHC	FB	CHSIN	OPP	OAREA	TRAPEZOID	ELIC	ELTRD
784.77	784.54	0.00	0.	1550.	200.	151.	782.03	781.20

3645 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELEV= 781.30 E.GRD= 781.01

BACK "MAIN ST." BRIDGE

3063.00	7.93	783.33	0.00	0.00	786.85	2.02	0.39	0.00	776.50
1850	0.	1850.	2.	0.	152.	0.	69.	11.	776.30
3.16	4.03	11.51	0.00	0.125	0.360	0.120	0.034	775.96	168.47
0.003365	100.	100.	100.	5	0	0	1.00	21.21	169.68

CONV= 0.370 CONV= 0.630

*SECNO 3113.000

5301 HV CHANGED MORE THAN HVINS

CLASS B LOW FLOW

MAIN ST. BRIDGE

3113.00	90.04	736.04	2.00	0.00	736.49	0.43	0.11	0.49	778.00
1850.	66.	1685.	100.	53.	316.	78.	63.	19.	776.00
0.15	1.13	5.32	1.28	0.100	0.040	0.100	0.038	776.00	60.61
0.001092	52.	52.	50.	3	0	0	0.00	66.91	125.52

*SECNO 3321.000

SECNO	DEPTH	QSEL	ORIFWS	WSELK	EG	HV	HL	CLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	ALTA	CLMTC	SST
ELOPE	XLOBL	XLCH	XLOBR	ITRIAL	I42	ICONT	CORIOL	TOPWID	BADST

3470 ENCROACHMENT STATIONS= 66.0 149.0 TYPE= 1 TARGET= 83.000

50 FT 375 FWD HOPSR CO. DAM CORPS C.S.USV

3335.00	10.00	736.50	0.00	0.00	736.62	0.13	0.09	0.00	776.00
1850.	37.	1803.	10.	54.	613.	23.	66.	12.	766.00
0.17	0.69	2.92	0.42	0.100	0.040	0.100	0.038	776.40	66.00
0.000352	165.	165.	165.	2	0	0	0.01	83.00	149.00

*ENNO 3327.000

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 790.00 E.HEA= 790.00

375 FORD HOPR, CO. DAM

3327.00	10.00	736.50	0.00	0.00	786.66	0.16	0.02	0.02	788.00
1850.	0.	1850.	0.	0.	560.	0.	65.	12.	791.00
0.17	0.00	3.26	0.00	0.100	0.040	0.100	0.038	776.53	80.13
0.000527	79.	69.	65.	2	0	0	0.00	57.03	958.75

SPECIAL BRIDGE

CD	SP	KRFT	CPRA	SKCW	DXC	EXP	BXPA	SS	B Wid	PLOWE
	0.70	1.50	2.10	0.00	0.10	0.00	0.10	0.00	776.53	776.50

*SECNO 3326.000

3265 DIVERSION FLOW

PRESSURE AND WEIR FLOW

PERKS	EGLIC	WS	OBJFN	QPR	BAREA	TRAPEZOID AREA	ELLC	ELTRD

WEIR,SID	PASSED	5.00	1850.	1.	0.	-79.	0.00	78.53	

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 790.00 ELREA= 790.00

PRINTED IN U.S.A.
FORM 1411-GB-PRINTED BY ROTARY MANIFOLD FORMS.

FORD MOTOR CO. DAM CORPS C.S.#40

5328.30	12.09	788.59	0.00	0.00	788.73	0.14	2.04	6.00	796.05
4050.	6.	7950.	0.	0.	691.	5.	66.	12.	79.50
0.17	0.30	8.63	0.00	0.000	0.040	0.150	0.013	776.55	45.00
0.000484	3	12.	1.	2	0	2	0.00	48.98	524.69

CCHV= 0.900 CSHV= 0.800

*SECTION 5672.000

BRIDGE

5495 OVERBANK AREA ASSUMED NON-EFFECTIVE-ELLEA= 790.50 ELREA= 790.50

U/S FACE TRUCK BRIDGE

5672.00	7.50	798.70	0.00	0.00	799.65	0.95	0.28	0.47	790.50
1850.	3.	7950.	0.	0.	236.	0.	70.	12.	790.50
0.19	0.30	7.97	1.01	0.100	0.250	0.100	0.059	761.10	479.69
0.000484	544.	564.	444.	8	0	0	0.00	48.98	524.69

SPECIAL BRIDGE

[illegible]	[illegible]	COEF	ADD'L	BWS	BWP	BAREA	SS	ELCHD	CLCHE
		0.90	0.00	20.00	0.00	195.05	2.15	793.10	791.10

*SECTION 5384.000

PRESSURE AND WTR FLOW

[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]
						AREA			
790.89	789.55	0.00	37.	1803.	195.	197.	787.70	790.50	

SOME OVERBANK AREA ASSUMED NON-EFFECTIVE-ELLEA= 791.00 ELREA= 791.0

U/S FACE TRUCK BRIDGE

5384.00	7.50	798.91	0.00	1.00	799.77	0.86	1.12	1.00	790.89
1850.	3.	7950.	0.	0.	336.	0.	70.	12.	790.50
0.19	0.00	6.94	0.00	0.100	0.250	0.100	0.039	761.10	479.72
0.000484	58	12.	13.	12.	2	0	3	0.00	48.98	524.69

*SECTION 5095.000

BRIDGE

BSLO IN CHANNEL MORE THAN OVERB

SECNO	DEPTH	CHESL	CELLS	WSELK	SS	V	[illegible]	[illegible]	DLOSS	D/S ELEV
[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]
[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]
[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]

FORM 1411-SD PRINTED BY ROTARY MANIFOLD FORMS.
PRINTED IN U.S.A.

VALLEY SECTION

3025.00	8.00	790.80	0.00	0.00	791.87	1.07	0.69	0.40	782.80
1850.	209.	1537.	103.	77.	170.	42.	71.	12.	783.30
0.19	2.72	9.03	2.44	0.100	0.050	0.100	0.039	782.80	475.70
0.005697	161.	211.	151.	2	0	0	0.01	82.19	527.39

#SECNO 3965.000

5301 HW CHANGED MORE THAN 4VELS

D/S FACE CRISWALD ST. BRIDGE

3765.00	7.16	791.76	3.00	0.00	793.33	1.79	1.19	0.58	784.60
1850.	150.	3177.	90.	55.	136.	33.	78.	12.	785.70
0.19	3.45	11.11	9.09	0.100	0.050	0.100	0.045	784.60	425.70
0.111256	140.	16.	140.	2	0	0	0.00	4.58	269.25

SPECIAL CASES

SECT XK=1.25 BOX STRUCTURE HW=793.25 ZUC= 791.76 HYDRAULIC JUMP OCCURS DOWNSTREAM AT 42. FT. 5.00 (WATER ES)

SE	XK	XKOR	COSQ	RDLEN	BUC	BWP	UAREA	SS	ELCHC	ELCHO
	1.25	1.69	1.00	0.00	10.25	1.43	116.00	0.00	784.60	784.60

#LEGNT 4020.000

5301 HW CHANGED MORE THAN 4VELS

PRESSURE AND WEIR FLOW

ESPEA	ZOL=		ALE	ZUC		H.ES	TAILWATER AREA	ALE	ALTI
799.23	795.49	3.00	556.	1296.	118.	116.	791.13	792.50	

[illegible] TYPE 1 STATION= 401.0 402.0 TYPE= 1 TAILWA= 110.00

U/S FACE CRISWALD ST. BRIDGE

4270.00	0.20	795.70	3.00	0.00	795.42	0.51	1.17	0.00	794.60
1850.	275.	1941.	255.	13.	195.	133.	72.	13.	785.10
0.20	2.38	6.85	2.75	0.100	0.050	0.113	0.00	784.60	403.95
0.302516	55.	63.	63.	2	0	5	0.00	95.96	498.96

[illegible] 0.300 CFS= 3.550

[illegible] 4020.200

BACK BACKWATER STATION= 340.0 940.2 TYPE= TARGET= 220.100

5' FT U/S CRISWALD ST. BRIDGE [illegible] 0.442

0.30	0.16	794.12	3.00	0.00	795.81	1.69	0.06	0.15	792.00
1850.	1255.	4[illegible]	1[illegible]	1[illegible]	1[illegible]	1[illegible]	1[illegible]	1[illegible]	1[illegible]
0.80	1.46	3.04	1.32	0.100	0.040	0.10[illegible]	0.[illegible]	784.60	552.50
0.011[illegible]	91.	50.	50.	2	0	5	0.00	177.47	240.00

PRINTED IN U.S.A.
FORM 1411-08 PRINTED BY ROTARY MANIFOLD FORMS.

*SECNO 4478.050

*SOIL PV CHANGES MORE THAN PVINS

4478.00	7.58	795.68	0.00	0.00	796.75	1.06	0.85	0.34	789.80
1650	191.	1340.	518.	62.	140.	143.	77.	14.	239.00
0.22	2.32	5.60	2.20	5.100	0.040	0.100	0.040	786.10	389.72
0.305270	300.	630.	750.	2	1	0	0.00	127.99	547.21

*SECNO 4856.000

SEC O	DEPTH	INSEL	CRINS	HSELV	SG	HV	L	DLOSS	DAR ELEV
B	0L.00	10F	3700	FLOB	ACI	4903	VOL	T..	LEFT/RIGHT
TYPE	0L.00	10F	V900	SOL	RNF4	RNF	USN	ELM	0FTA
S.OF=	0L.00	RATE	3.000	ATTAN	INF	F.O.I	I.C.A.R	TEMP	3UNST

SO FT LT'S SIL. POND ATT CORPS C.S.743

4850.20	.00	798.03	0.00	2.00	798.34	0.30	3.11	2.00	794.00
72.	24.	1765.	30.	15.	242.	15.	80.	15.	794.30
1.23	1.91	7.10	1.64	0.100	0.240	0.100	0.040	792.00	417.44
0.004619	300.	300.	500.	3	0	3	2.00	71.52	408.94

*SECNO 4910.000

3470 ENCROACHMENT STATIONS= 334.0 396.0 TYPE= 1 TARGET= 62.000

873 TILL POND 390

4907.00	7.37	799.37	0.00	0.10	799.22	1.93	0.31	5.00	794.05
1820.	0.	1820.	0.	0.	232.	0.	81.	15.	102300.00
0.25	0.00	7.63	0.00	0.100	0.040	0.100	0.040	794.00	385.72
0.307556	49.	49.	49.	1	1	1	0.00	56.56	392.26

SPECIAL BRIDGE

B	YR	HKOR	COFQ	ROLEN	BHC	BWP	SOFFA	SS	FLCHO	FLCRO
	0.33	.50	3.00	3.00	0.10	0.00	0.10	0.00	794.05	794.50

*SECNO 4911.000

3321 HV CHANGES MORE THAN HVINS

PREPARE FOR TEST FLOW

SOURCE	ECLHC	HS	JUNCT	QF	BOREA	TRAPEZOID	F.L.S	W.TRD
						BASIN		

716.13.00 798.23 .40 1825 8. 794. 5.00 831.20

FORM 1411 GB PRINTED BY ROTARY MANIFOLD FORMS.
PRINTED IN U.S.A.

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELEV= 810.00 ELAREA= 810.00

4908.00	11.78	805.78	0.00	0.00	805.80	0.11	0.06	0.00	804.00
1820.	0.	1820.	0.	0.	690.	0.	31.	15.	304.00
3.23	3.00	2.64	0.07	0.100	0.260	0.100	0.047	794.00	334.00
0.002265	1.	1.	1.	2	0	1	2.00	00.00	394.05

CCHV= 0.100 CEHV= 0.300

*SECNO 5306.000

5304.00	5.94	305.94	0.00	0.00	305.97	0.03	0.02	0.01	804.50
1420.	1.	1418.	1.	4.	1181.	7.	69.	16.	804.00
0.37	0.15	1.54	0.38	0.100	0.035	0.100	0.039	800.00	64.73
0.050167	400.	400.	400.	2	1	0	0.30	282.23	327.65

CCHV= 0.600 CEHV= 0.800

*SECNO 5928.000

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELEV= 810.00 ELAREA= 650.00

7001 D/S C.O. R.R.BRIDGE #1

5920.00	6.05	806.05	0.00	0.20	806.11	0.05	0.12	0.01	650.00
3823.	0.	1420.	0.	5.	975.	0.	14.	15.	302.00
0.41	0.01	1.14	0.30	0.050	0.042	0.300	0.040	790.20	40.20
0.002122	400.	400.	400.	2	1	0	0.30	282.23	327.65

*SECNO 6078.000

SOIL AT C.O. IS IN THIS REACH

SECNO	DEPTH	CNSEL	CHNS	USELK	EG	FV	FL	OLOSS	BANK ELEV
FLOW	FLOW	FLOW	VIOS	XNL	XNCL	XNR	WTP	CL/EM	LEFT/RIGHT
SLOPE	SLOPE	SLOPE	X.OBS	ITRIAL	CHS	SCONT	CCHAN	TOPWID	ENDST

8472 ENCROACHMENT STATION= 257.5 302.9 TYPE= 1 TARGET= 45.200

6020.00	7.02	121.52	0.00	0.20	667.13	0.11	0.00	0.01	525.25
1420.	230.	1391.	191.	67.	141.	57.	137.	80.	794.00
0.41	3.45	8.23	3.33	0.080	0.040	0.080	0.240	790.20	257.50
0.002121	150.	150.	150.	2	1	0	0.00	35.10	322.20

8504 CONFINED TIDE TRAN 4/185

FORM 1411-GB PRINTED BY ROTARY MANIFOLD FORMS.
PRINTED IN U.S.A.

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 815.00 ELREA= 815.00

1820.	0.	1820.	0.	0.	148.	0.	107.	20.	798.90	
0.40	0.00	12.29	0.00	0.080	0.045	0.080	0.040	798.40	230.00	
0.012524	50.	30.	50.	0		0	0.30	20.00	250.00	

SPECIAL BRIDGE

SKI XR	XKOR	CORA	ROLEX	BWC	SWP	DAREA	SS	ELCHO	ELCHP
0.0	1.87	5.00	1.00	19.30	0.00	150.00	0.30	798.70	798.41

SHAPE 6726.INC

SHUT HV CHANGED MORE THAN 1VIUS

PRESSURE FLOW

CDCAS	ESLVE	AD	SAREA	OPR	DPREA	TRAPEZOID AREA	ELLC	ELTRD
802.77	806.40	0.00	0.	1820.	150.	150.	802.30	813.75

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 815.00 ELREA= 815.00

Sect. S 0/S FACE C.O. R.R. BRIDGE #1

1821.	0.	1820.	0.	0.	195.	0.	107.	20.	798.90	
0.43	0.00	9.31	0.00	0.080	0.040	0.010	0.040	799.40	230.00	
0.004673	50.	30.	50.	3		0	0.30	20.00	250.00	

U/S FACE C.O. R.R. BRIDGE #1

SHUT HV CHANGED MORE THAN TWICE

3495 CROSS INFLT STATIONS= 213.3 335.0 TYPE= TABLE= 120.500

50 FT U/S C.C. R.R. BRIDGE #1 CORPS C.S.447

532.00	12.53	570.43	3.00	5.00	810.35	0.13	0.05	0.70	797.91	
1320.	320.	997.	530.	230.	240.	391.	130.	20.	796.62	
0.40	0.21	3.50	1.90	0.080	0.130	0.080	0.10	797.90	230.00	
0.005513	50.	50.	50.	3	0	0	0.30	20.00	250.00	

CCHV= 0.300 CEHV= 0.500

SHUTLEY BRIDGE

7450.00	9.25	810.35	0.00	0.00	611.06	0.39	0.47	0.01	802.00
1820.	850.	702.	268.	1021.	189.	359.	140.	26.	603.30
0.56	0.65	3.72	0.76	0.120	0.040	0.120	0.039	601.70	115.50
0.700555	1400.	952.	700.	2	0	0	0.00	335.00	450.00

SECNO	DEPTH	CHSEL	CRITS	WSELK	EC	IW	IL	QLOPS	OALK ELEV
	QLOD	QCH	QTOT	ALOB	ACH	AROB	VOL	TAZ	LEFT/RIGHT
TIME	VLOD	JCH	VTOT	XLO	XLCH	XMP	XTH	ELMIN	SST
SLOPE	XLOBL	ALCH	XLOBJ	ITRIAL	IP2	ICONT	CORAT	TOPWID	E.G.

347 ENCROACHMENT STATIONS= 100.0 760.0 TYPE= 1 TARGET= 260.700

SECT 7 D/S FACE OLD NCHL TO, BRIDGE FIELD UCOK STA. 28+10

7300.00	9.25	811.18	0.00	0.00	611.35	0.13	0.20	0.01	802.10
1820.	591.	308.	421.	665.	261.	479.	133.	29.	602.70
0.60	0.89	4.22	0.9	0.120	0.040	0.120	0.038	802.10	100.60
0.700678	600.	15	100.	2	0	0	0.00	262.00	365.00

SPECIAL BRIDGE

BL	AS	XCOD	COEF	ROLEX	IWC	EMP	BACKA	SS	FLOW	ELCHD
	7.03	7.01	8.73	0.55	25.70	0.00	111.00	0.00	302.10	812.10

*SECNO 7283.000

PRESSUR AND WEIR FLOW

SECNO	DS	XD	HP	DARSA	TRAPEZOID	SLLP	SLTOL		
					AREA				

SECN 7283.000 BRIDGE SECTION 1.0 360.0 TYPE 1 TARGET 260.000

7328.00	9.00	811.70	0.00	0.00	611.02	0.39	0.47	0.00	802.10
1820	697.	769.	637.	753.	256.	533.	356.	25.	602.20
1.00	0.60	4.05	0.75	0.120	0.040	0.120	0.03	802.10	101.00
0.700383	600.	2	100.	2	0	0	0.00	262.00	360.00

*SECNO 7518.000

7778.00	9.19	811.86	0.00	0.00	611.35	0.86	0.15	0.15	805.50
1820.	472.	1266.	92.	365.	215.	98.	59.	56.	807.30
1.00	0.57	5.35	0.44	0.120	0.040	0.120	0.034	802.10	200.00
0.700	900.	900.	100.	2	0	0	0.00	262.00	360.00

*SECNO 7566.000

PRINTED IN U.S.A.
FORM 7411-6D-PRINTED BY ROTARY MANIFOLD FORMS.

5301 HV CHANGED MORE THAN HVINS

SECNO	DEPTH	CHSEL	CRIWS	HSELK	EG	HV	LL	OLOSS	BANK ELEV
3	GLOB	GCH	GROB	ALOB	ACE	AROE	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNE	CTN	PENIK	SSTA
GLOBAL	GLOBL	GLCH	GLOBAL	INITIAL	INE	ICONV	CONVG	TOTMIN	ENDST

7185 MINIMUM SPECIFIC ENERGY
5725 CRITICAL DEPTH ASSUMED

14 ENCROACHMENT STATIONS= 533.0 SEC.D TYPE= 1 THALT= 45.00

55 FT D/S C.G. R.R. BRIDGE #2 FIELD BOOK STA. 22+50

7868.00	6.64	312.34	812.34	0.00	315.02	2.67	1.27	1.14	305.00
1320.	195.	1621.	7.	65.	117.	4.	162.	31.	317.30
1.63	2.79	14.17	0.82	4.153	0.040	0.120	0.038	525.73	5[illegible].20
0.711506	191.	351.	393.	3	18	0	0.10	42.0	34.52

+ FCHG 7921.000

5305 BY-PASS FLOW NOT, THRU HVINS

5495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 818.30 ELTEA= 818.30

75 FT D/S C.G. R.R. BRIDGE #2 FIELD BOOK STA. 21+97

7921.00	6.16	314.84	0.00	0.00	315.80	0.97	0.20	0.51	305.00
1320.	0.	1320.	0.	0.	251.	0.	162.	31.	317.30
0.62	0.00	7.88	0.00	0.120	0.040	0.120	0.038	806.00	543.57
0.302962	0.	56.	53.	4	0	0	0.10	12.02	274.52

SPECIAL BRIDGE

3.	[illegible]	CDTA	HOLE	0.0	SWP	[illegible]	55	BLIND	[illegible]
[illegible]	2.04	12.03	1.00	17.00	3.93	1[illegible].0	0.10	130.00	7[illegible].00

FCHG 7921.000

SEC	DEPTH	CHSEL	CRIWS	HSELK	EG	HV	LL	OLOSS	BANK ELEV
	GLOB	GCH	GROB	ALOB	ACE	AROE	VOL	TWA	LEFT/RIGHT
[illegible]	VLOB	VCH	VROB	XNL	XNCH	XNE	CTN	PENIK	SSTA
[illegible]	GLOBAL	GLCH	GLOBAL	INITIAL	CHE	ICONV	CONVG	TOTMIN	ENDST

PRESSURE FLOW

[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]
146.45	316.16	0.68	0.	120.	145.	132.	811.70	819.20	

[illegible] 0/S FACE C.G. R.R. BRIDGE #2 FIELD BOOK STA. 21+59

PRINTED IN U.S.A.
FORM 1411.08 PRINTED BY ROTARY MANIFOLD FORMS.

7965.00	12.37	818.37	0.00	0.00	818.85	0.48	3.05	0.00	806.00
1820.	0.	1820.	0.	0.	326.	0.	163.	31.	807.30
0.62	0.00	5.58	0.00	0.120	0.040	0.120	0.038	806.00	546.50
0.001736	44.	44.	44.	2	0	0	0.00	27.00	373.50

CC IV= 0.300 CCHV= 0.500
*SECNO 8110.000

3420 ENCROACHMENT STATIONS= 275.0 325.0 TYPE= 1 TARGET= 50.000

153 FT W/S U.S. R.R. BRIDGE #2 FIELD BOOK STA. 2+00

8118.00	12.02	818.62	0.00	0.00	819.30	0.38	0.12	0.03	809.40
1820.	125.	1556.	129.	111.	295.	111.	164.	31.	838.60
0.63	1.13	5.51	1.16	0.100	0.035	0.120	0.038	806.60	275.50
1.000059	60.	153.	50.	2	0	0	0.00	50.00	325.50

CC IV= 0.300 CCHV= 0.500
*SECNO 8510.000

3420 ENCROACHMENT STATIONS= 257.0 381.0 TYPE= 1 TARGET= 124.000

38 FT W/S TITLE RR. BRIDGE FIELD BOOK STA. 16+20

8513.00	11.38	819.08	0.00	0.00	819.25	0.17	0.16	0.06	811.70
1820.	343.	1871.	436.	373.	257.	412.	169.	31.	810.00
0.67	0.98	6.17	0.91	0.120	0.035	0.120	0.038	807.70	457.30
0.000455	125.	400.	250.	2	0	0	0.00	124.00	551.50

*SECNO 8555.000

C/S 2 SCALE TO. CONCRT

8555.00	13.18	819.95	0.00	0.00	819.23	0.20	0.51	0.08	812.00
1820.	0.	1820.	0.	0.	311.	0.	169.	31.	840.30
0.57	0.00	5.96	0.00	0.120	0.035	0.120	0.038	805.70	0.00
0.000484	37.	37.	37.	2	0	0	1.00	48.00	48.00

LSHL= 0.000 RSHL= 0.000
*SECNO 8556.000

3570 NORPAL BRIDGE,NOD= 67 MIN ELTRD= 840.00 MAX ELLC= 817.70

16 FOOT S WIDE RD. CULVERT FIELD BOOK STA. 15+00

8556.00	15.18	819.95	0.00	0.00	819.50	0.44	0.01	0.22	840.00
1820.	0.	1820.	0.	0.	283.	0.	169.	31.	840.00
0.67	0.13	4.41	0.00	0.100	0.035	0.120	0.038	806.70	0.00
1.000218	1.	16.	16.	2	2	0	0.00	66.00	66.00

*SECNO 8571.000

SECNO	DEPTH	CLSEL	CLSUS	WSELK	EG	KV	KL	D-LOSS	BANK ELEV

PRINTED IN U.S.A.
FORM 1411.08 PRINTED BY ROTARY MANIFOLD FORMS.

3370 NORMAL BRIDGE,ADD= 47 MIN ELTRO= 312.60 MAX ELLC= 318.60

U/S FACE N MILE RD. CULVERT FIELD BOOK STA. 13+07

[illegible]	[illegible]	579.44	1.05	0.00	320.04	0.62	5.51	0.11	830.00
1820.	1.	1482.	0.	1.	395.	0.	121.	23.	425.00
0.68	0.00	4.23	0.00	0.100	0.020	0.103	0.038	807.50	0.00
0.001964	255.	255.	255.	2	0	3	-158.30	48.00	48.00

[illegible] 0.301 CHAN= 0.87

[illegible] 8432.000

U/S 4 MILE RD. CULVERT

[illegible]	15.47	819.97	0.50	1.01	320.17	0.19	0.50	0.12	830.00
1425.	0.	1821.	0.	0.	399.	0.	121.	23.	440.00
0.58	1.00	5.51	0.80	0.052	0.40	3.100	0.038	807.50	0.00
0.000604	1.	1.	1.	2	0	0	0.00	48.00	48.00

[illegible] 9913.000

[illegible] ENCROACH EXT STATIONS= 362.0 555.0 TYPE= 1 TARGET= 155.000

10/ FT U/S N MILE Rd. CULVERT FIELD BOOK STA. 12+00

6978.2	11.63	820.13	0.00	0.00	320.29	0.11	0.06	0.02	830.00
1082.	325.	546.	1164.	225.	116.	277.	173.	13.	90.00
0.59	1.00	6.21	1.22	0.090	0.040	0.056	0.138	806.50	157.00
0.000536	106.	106.	106.	2	0	1	0.00	156.00	525.00

SCS= 0.100 CHAN= 0.503

ASELD 9655.700

3470 ENCROACHMENT STATIONS= 255.0 555.0 TYPE= 1 TARGET= 310.000

VALLEY SECTION FIELD BOOK ST. 6-00

9657.00	10.37	820.17	0.00	0.00	320.40	0.13	0.19	0.01	830.00
1420.	0.	1821.	792.	774.	0.	35.	121.	31.	440.00
0.87	0.00	2.45	0.84	0.000	0.040	0.000	0.038	810.00	255.00
0.003195	600.	600.	600.	2	0	0	0.00	310.00	560.00

SCS= 0.500 CHAN= 0.500

ASELD 9218.000

3500 HV CHANGE MORE THAN HVINS

3470 ENCROACHMENT STATIONS= 402.0 560.0 TYPE= 1 TARGET= 77.500

96.5 FT D/S NEW HWY RD. BRIDGE FIELD BOOK STA. 2-00

9954.0	9.65	820.25	0.00	0.00	820.60	0.67	0.20	0.32	830.20
1[illegible]	2[illegible]	[illegible]	30.	120.	14.	0.	120.	23.	314.00
[illegible]	1.00	[illegible]	[illegible]	0.000	0.140	0.000	0.038	810.00	255.00
[illegible]	12.	[illegible]	60.	2	[illegible]	[illegible]	[illegible]	76.00	550.00

9973.50

FORM 1411-08 PRINTED BY ROTARY MANIFOLD FORMS.
PRINTED IN U.S.A.

SECNO	DEPTH	CWSEL	CRWS	WSELK	EG	RV	ML	QLOSS	BANK ELEV
Q	CLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	UTN	ELMIN	SSTA
SLOPE	XLOB	XLCH	XLOBR	ITRIAL	IB2	ICONT	CORAR	TOPWID	ENDST

5495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 823.50 ELREA= 823.50

D/S FACE NEW MOVI RD. BRIDGE FIELD BOOK STA. 144+.5

9971.50	0.42	820.92	0.00	0.70	821.58	2.69	2.16	2.12	823.70
1820.	0.	1820.	0.	0.	278.	0.	199.	36.	820.20
0.87	0.00	6.54	0.00	0.100	0.040	0.060	0.033	810.70	1525.07
0.003511	56	56.	56.	2	0	0	0.30	50.43	1575.50

SPECIAL BRIDGE

SS	XK	XKOB	COCO	ROLL	EJC	WP	QAREA	SS	CLOW	ELCHO
	1.35	1.89	1.00	1.00	27.00	2.00	355.70	4.23	811.23	820.70

SPECIAL 3D(1.00)

CLASS A LOW FLOW

3420 BRIDGE U.S.= 820.34 BRIDGE VELOCITY= 6.12 CALCULATED CHANNEL AREA= 297.

EGPRS	EGLAS	HJ	FACIR	QPR	BAREA	TRAPEZOID AREA	CLL	LITHO
0.00	821.16	0.13	3.	1020.	335.	335.	821.20	823.50

5495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 823.50 ELREA= 823.50

D/S FACE NEW MOVI RD. BRIDGE FIELD BOOK STA. 144+7

9971.50	0.41	820.91	0.00	0.69	821.60	0.34	0.07	0.20	823.70
1820.	0.	1820.	0.	0.	278.	0.	199.	36.	820.20
0.87	0.00	6.54	0.00	0.100	0.040	0.060	0.033	810.70	1525.07
0.003526	54.	54.	54.	2	0	0	0.30	50.43	1575.50

SPECIAL BRIDGE

5495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 823.50 ELREA= 823.50

D/S FACE C.C. R.R. BRIDGE #3 FIELD BOOK STA. 1+34

9971.50	0.39	820.93	1.00	0.00	821.43	0.34	0.13	0.04	823.70
1820.	0.	1820.	0.	0.	278.	0.	199.	36.	820.20
0.87	0.00	6.54	0.00	0.100	0.040	0.060	0.033	810.70	1525.07
0.003549	73.	73.	73.	2	0	0	0.00	34.00	1567.00

SPECIAL BRIDGE

SS	XK	XKOB	COCO	ROLL	EJC	WP	QAREA	SS	CLOW	ELCHO
	1.35	1.89	1.00	1.00	34.00	2.00	345.00	4.23	812.91	820.70

PRINTED IN U.S.A.
FORM 1411-SB-PRINTED BY ROTARY MANIFOLD FORMS.

*SECNO 10094.000
PRESSURE FLOW

TOPWS	SAL.S	FR	HO	NUMER	CRO	CAREA	TRAP.ECLD	ELLC	ALTHO
822.20	821.45	0.00	0.	1820.	243.	245.	820.10	826.10	

*SAVE OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 826.10 ELRE.= 820.10

U/S FACE C.O. R.R. BRIDGE #3 FIELD BOOK STA. 0+24

10094.00	0.72	821.62	0.00	0.00	822.20	0.58	0.76	0.00	820.00
1820.	0.	1180.	0.	0.	297.	0.	199.	36.	821.00
0.35	0.00	0.00	0.00	0.100	0.040	0.000	0.000	0.00	1539.00
0.002528	0.	10.	10.	2	2	0	0.00	34.00	1567.00

*SECNO 10103.000

SAVE BY EMBANKMENT SIDE SLOPE WEIR

5495 CHILDBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 826.10 ELRE.= 826.10

10103.00	0.57	821.17	0.00	0.00	822.72	1.55	0.00	0.48	813.30
1820.	0.	1820.	0.	0.	182.	0.	199.	36.	815.10
0.35	0.00	10.00	0.00	0.100	0.040	0.000	0.000	812.60	1539.00
0.005736	0.	0.	0.	2	2	0	0.00	22.00	1551.00

*SECNO 10104.000

SECNO	CRPTN	CASEL	CRINS	USFLR	EG	IV	FL	OLOSS	LANK ELEV
0	0.0	0.0	0.0	0.00	0.0	0.00	0.0	TW	0.00
7100	VLOW	SC	UNCO	ANL	SUCP	PSR	LTS	0.0	SOTH
0.0	VLOW	LOW	BLOCK	STATAL	ZNE	ICONT	CRITAL	TOPWID	CONT

*SAVE NORMAL DEPTH,VEC= 0.0 WSEL ELTRD= 826.10 ELLC= 823.10

SAVE OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 826.10 ELTRD= 826.10

*SAVE CROSS SECTION WITH CRITICAL DEPTH FIELD BOOK STA. 0+24

10104.00	0.57	821.17	0.00	0.00	822.72	1.55	0.00	0.48	813.30
1820.	0.	1820.	0.	0.	182.	0.	199.	36.	815.10
0.35	0.00	10.00	0.00	0.100	1.040	0.000	0.000	812.60	1539.00
1.005736	1.	1.	1.	0	0	0	0.00	22.00	1551.00

*SAVE NORMAL DEPTH,VEC= 0.0 WSEL ELTRD= 826.10 VALCI.= 823.10

PRINTED IN U.S.A.
FORM 3411-GB PRINTED BY ROTARY MANIFOLD FORMS.

5495 OVERBANK AREA ASSUMED NON-EFFECTIVE>ELLEA= 826.10 ELREA= 826.10

U/S FACE OLD NOVI RD. BRIDGE FIELD POOL STA. 0-14

10132.00	8.84	821.44	0.00	0.00	822.90	1.46	0.00	0.00	813.30
1820.	0.	1820.	0.	0.	188.	0.	199.	37.	813.10
0.83	0.00	9.70	0.00	0.100	0.040	0.080	0.038	812.60	1539.00
0.004664	26.	26.	24.	2	0	0	0.00	22.00	1561.00

*SECNO 10133.000

5495 OVERBANK AREA ASSUMED NON-EFFECTIVE>ELLEA= 826.10 ELREA= 826.10

U/S OLD NOVI RD.

10133.00	8.84	821.44	0.00	0.00	822.90	1.46	0.00	0.00	813.30
1820.	0.	1820.	0.	0.	188.	0.	199.	37.	813.10
0.83	0.00	9.69	0.00	0.100	0.040	0.080	0.039	812.60	1538.00
0.004654	1.	1.	1.	0	0	0	0.00	22.00	1561.00

*SECNO 10157.000

5361 HV CHANGED MORE THAN 0.01FT

5470 ENCROACHMENT STATION= 384.0 416.0 TYPE= 1 TABLE= 32.000

FIELD POOL STA. 0-39 25' U/S OLD NOVI RD. BRIDGE

10157.00	8.67	821.17	0.00	0.00	823.10	0.96	0.19	0.13	813.30
1820.	177.	1641.	913.	93.	137.	53.	413.	32.	813.30
.83	2.81	.85	2.29	2.106	0.360	0.380	0.116	11.33	284.50
0.002635	24.	24.	24.	3	0	0	0.00	32.50	496.00

PRINTED IN U.S.A.
FORM 1411.08 PRINTED BY ROTARY MANIFOLD FORMS

```
**********************************************************************
     HFC2 RELEASE DATED NOV 76 UPDATED FEB 1977
     ERROR CORR. - 37
     COMPILATION - 5:25:27
**********************************************************************

          CITY OF JACKSONVILLE FIS HUD 2006-07
     1    SUBSONIC BRIDGE HOWEY SECTIONS FROM CARDS START ...6. FROM FIL..T.P. 110
          N.JONES E. ..PELT ..

 J1  ICHECK     INO        NINV       IOPR       STRT       METRIC     AVINS      0          MSEL       FQ
        0.          0.         0.         1.  0.000000       0.00       1.0         1.     768.170       1.000
 J2  MPROF      IAPT       ESTWS      HSECW      HSECR         FU      ALLOC       ZRW        CINPS      CTRACE
    15.000      0.030     -1.200      0.000      0.000      0.000      0.000      0.000      0.000      0.000
```

PRINTED IN U.S.A.

FORM 1411-GB PRINTED BY ROTARY MANIFOLD FORMS.

*PROF 2

CCHV= 0.100 CEHV= 0.300

*SECNO ***1*

SECNO	DEPTH	CHECK	CRI.S	HSCLE	DG	AV	AL	LOSS	BASE ELEV
	0.00	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]
TIME	VLOM	VCH	VROU	XYL	XACH	XNR	WTM	ELMIN	SSTA
SLOPE	XLOAL	XLCH	XLOOR	XTRIAL	IBZ	ICONT	CORAR	TOPWID	ENDST

[illegible] [illegible] [illegible] [

2800 NAT Q1= 914.96 WSEL= 769.65 CNC Q1= 929.82 WSEL= 769.75 RATIO= -0.0162
NAT Q1= 930. RATIOS LOB,CH,ROB= 0.0000 1.0000 0.0000 WSEL= 769.75

3301 UV CHANGED MODE THAN MAINS

SECNO	DEPTH	CWSEL	CTIME	WSELK	EG	KV	HL	OLLSC	EGNS ELEV
0	ORIFH	KOUT	FROUD	ALOW	ACH	AROB	WCI	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	MIN	EL MIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	LTRIAL	I42	ICONT	COPAR	TOPWID	ENDST

5470 ENCROACHMENT STATIONS= 975.0 1035.0 TYPE= 4 TARGET= 0.000

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 775.00 ELREA= 775.00

PATH	MIN EL	INVERT	CORPS C.S.NO
1028.00	12.27	769.67	0.00	769.65	770.83	1.16	0.14	0.21	773.30
3680.	1.	3680.	0.	0.	428.	0.	40.	8.	773.60
0.06	0.30	8.64	0.00	0.100	0.025	0.100	0.034	757.40	981.67
0.001510	80.	50.	50.	3	2	6	0.00	19.91	1031.97

SPECIAL BRIDGE

SK	CD	KRGT	SOFD	SOLSP	OPC	OPR	BAREA	SK	ELCHD	ELCRD
	1.05	1.50	5.70	0.00	25.00	2.30	441.50	1.17	757.40	757.40

*SECNO 1073.000

3265 DIVIDED FLOW

CROSS SECTION 2647

5420 BRIDGE U.S.= 769.54 BRIDGE VELOCITY= 8.15 CALCULATED CHANNEL AREA= 452.

EGPRS	EGLSC	HT	ANCH	APP	BAREA	TRAPEZOID AREA	ELLC	ELTRD
0.00	771.06	0.17	0.	3461.	692.	692.	775.30	775.30

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 775.30 ELREA= 775.30

PATH	MIN EL	INVERT	CORPS C.S.NO
1073.00	12.53	769.73	0.00	769.03	771.02	1.29	0.19	3.00	773.60
3520.	0.	3682.	0.	0.	639.	0.	41.	8.	773.90
0.06	41.00	8.17	1.07	0.100	0.025	0.102	0.044	757.40	981.65
0.001552	80.	50.	50.	0	2	6	0.00	34.37	1031.30

*SECNO 1115.000

3001 UV CHANGED MODE THAN MAINS

5470 ENCROACHMENT STATIONS= 965.0 1035.0 TYPE= 1 TARGET= 70.000

3/8 WOOTHEAD CORPS CSA CULVERT

1113.00	13.07	770.97	0.00	770.89	771.28	0.31	0.02	0.23	757.90
1850.	227.	1448.	175.	254.	283.	219.	41.	0.	757.90
0.05	0.89	5.04	0.83	0.100	0.325	0.100	0.034	757.90	965.00
0.000233	35.	35.	35.	2	0	0	0.00	97.00	1035.00

CCHV= 0.300 CEHV= 0.500
*SECNO 2163.000
WATER ELEVS CORR= 779.730

3470 ENCROACHMENT STATIONS= 295.0 365.0 TYPE= 1 TARGET= 70.000

D/S FACE RIVER ST. BRIDGE CORPS C.S.#35

2163.00	9.80	779.70	0.00	779.60	780.20	0.56	0.40	0.10	770.00
1850.	201.	1472.	87.	151.	233.	73.	46.	9.	769.52
0.12	1.93	6.31	1.15	0.100	0.040	0.100	0.057	770.70	295.00
0.003569	4230.	1050.	1000.	4	0	0	0.00	70.00	295.00

*SECNO 2213.000

3471 ENCROACHMENT STATIONS= 38.0 203.0 TYPE= 1 TARGET= 170.500

50 FT D/S RIVER ST. BRIDGE CORPS C.S.#36

2213.00	10.86	780.06	0.00	779.96	780.33	0.27	0.00	0.07	771.00
1850.	1234.	1503.	224.	122.	327.	239.	56.	9.	775.30
0.12	1.39	5.95	0.96	0.100	0.045	0.100	0.037	773.00	47.52
0.200402	50.	50.	50.	2	2	0	0.00	102.48	305.00

*SECNO 2515.000

2513.00	6.35	780.10	0.00	780.25	780.78	0.68	0.39	0.11	771.79
1850.	144.	1554.	151.	93.	336.	76.	61.	31.	775.75
0.14	1.58	6.25	1.57	0.100	0.040	0.100	0.037	771.75	302.85
0.001515	230.	300.	400.	3	5	0	0.00	65.79	458.62

CCHV= 0.300 CEHV= 0.500
*SECNO 2514.500

3501 HV CHANGED MORE THAN .01FT

3472 ENCROACHMENT STATIONS= 105.3 149.4 TYPE= 1 TARGET= 42.940

100 FT D/S RAILROAD BRIDGE CORPS C.S.#37

2563.00	6.94	780.97	0.00	780.64	782.40	1.72	0.53	0.62	774.03

PRINTED IN U.S.A.
FORM 1411-08 PRINTED BY ROTARY MANIFOLD FORMS.

1650.	4.	1822.	25.	4.	172.	10.	63.	11.	777.50
0.15	0.96	10.61	1.57	0.120	0.040	0.120	0.037	773.00	106.46
0.008864	300.	350.	350.	2	0	0	0.00	42.94	149.43

*SECND 2935.000

3301 HV CHANGED MORE THAN HVINS

SECNO	DEPTH	CHSEL	CRIWS	WSSLK	FB	EV	HL	OLOSS	BANK ELEV
T	C_OD	CH	QROD	ALOB	ACI	AROB	VOL	TWP	LEFT/RIGHT
WSEL HP	V_HL	VCH	VSTO	XNL	XNCH	XLP	WTF	CL IN	SSTA
QPR	K_OL	ACSA	NLOBE	FTRIAL	IHP	ICOLT	CCR_P	TOPWID	ENDST

3645 20 TRIALS ATTEMPTED LOPL,CHSEL
5091 PRODABLE HYDRAULIC SPECIFIC ENERGY
5720 CRITICAL DEPTH ASSUMED

5495 OVERBANK AREA ASSUMED NON-EFFECTIVE,E.LEA= 780.00 ELREA= 780.00

D/S FACE MAIN ST. BRIDGE CORPS C.S.433

2963.00	4.44	782.36	782.36	782.36	785.63	3.12	1.00	0.00	776.50
1850.	0.	1850.	0.	0.	131.	0.	63.	11.	776.50
0.15	0.00	14.17	0.00	0.120	0.040	0.120	0.035	775.90	148.47
0.014472	100.	100.	100.	20	11	0	0.00	21.21	169.68

SPECIAL BRIDGE

5287 DOWNSTREAM ELEV = 780.00 ENCR 782.36 HYDRAULIC JUMP OCCURS DOWNSTREAM (IF LOW FLOW CONTROLS)

ALT	WSEL	QBR	TOPWID	AREA	QWR	WTOPW	SF	ELOSS	FLOSS
1.25	[illegible]	3.00	0.20	32.40	1.00	[illegible]	0.00	[illegible]	[illegible]

*SECND 3053.300

5571 ENCROACHMENT NOT ALLOWED

CLASS 2 FLOW FIELD

3420 BRIDGE W.S.= 782.42 BRIDGE VELOCITY= 14.19 CALCULATED CHANNEL AREA= 131.

C_OD	OGL_D	IB	QLEIB	QBR	AREA	TEMPEROIL	C_LC	ELTRD
						NCLS		
0.00	782.42	3.00	0.	1850.	200.	99.	785.00	791.63

5495 OVERBANK AREA ASSUMED NON-EFFECTIVE,E.LEA= 791.00 EL.EA= 791.00

U/S FACE MAIN ST. BRIDGE

3063.00	7.97	783.37	0.00	785.63	785.65	2.02	0.39	0.00	776.50
1850.	0.	1850.	0.	0.	132.	0.	64.	11.	776.50
0.15	0.00	14.01	0.00	0.120	0.041	0.120	0.038	775.90	148.47
0.007405	100.	100.	100.	20	11	0	0.00	21.21	169.68

COMMENT: D/S FACE MAIN ST. BRIDGE

FORM 1411 GB-PRINTED BY ROTARY MANIFOLD FORMS.

PRINTED IN U.S.A.

*SECNO 3113.000

3503 KV CHANGED MORE THAN HVINS

3113.00	10.04	786.04	0.00	786.04	786.45	0.40	0.11	0.49	776.30
1850.	66.	1685.	100.	56.	316.	78.	64.	11.	776.00
0.15	1.13	5.32	1.28	0.100	0.040	0.300	0.093	776.20	60.61
0.0070092	50%	50.	50.	3	3	0	0.30	64.65	135.52

*SECNO 3278.000

SECNO	DEPTH	QUSEL	CHNS	USELK	ES	KV	HL	QLOSS	RANK ELEV
Q	QLOB	QCH	TRCS	ALOB	ACH	ARCH	VOL	TIC	LEFT/RIGHT
TYPE	QROB	VCL	VTOT	KCL	XSCH	XBR	QTH	ELOSS	SSTA
ERONE	LOBL	ALCH	ALOB	CTRIAL	I42	ICONT	CORAR	TOP.TP	E 183

3470 ENCROACHMENT STATIONS= 56.0 149.0 TYPE= 1 TARGET= 33.000

3278.00	10.09	786.49	0.00	786.49	786.62	0.13	0.09	0.08	776.00
1850.	37.	1805.	10.	54.	615.	23.	66.	11.	786.00
0.17	0.69	2.92	0.62	0.100	0.040	0.100	0.038	776.40	66.00
0.0070352	66%	165.	165.	2	0	1	0.00	33.00	135.00

*SECNO 3327.000

3695 OF CHANK AREA ASSUMED NON-EFFECTIVE.EL.EQ= 790.00 EL.REA= 790.00

3327.00	10.02	786.50	0.00	786.50	786.65	0.16	0.02	0.02	786.00
1850.	0.	1850.	0.	0.	506.	0.	67.	11.	791.00
0.18	0.00	1.20	0.00	0.100	0.040	0.100	0.038	776.80	10.15
0.0070329	49%	99.	49.	2	1	0	0.00	50.50	135.75

SPECIAL BRIDGE

90	WIDE	CWSEL	RWLEN	INC	SHP	SAREA	QE	ELMIN	ELCHD
.05	2.97	0.00	0.00	0.70	0.50	0.00	0.00	776.17	776.17

*SECNO 3328.000

3695 OF CHANK AREA ASSUMED NON-EFFECTIVE.EL.EQ= 790.00 EL.REA= 790.00

ESTRS	FOLIC	P3	QWEIR	QBR	SAREA	TRAPEZOID	F.LC	ELTRD	
					APEA				

FORM 1411-GB-PRINTED BY ROTARY MANIFOLD FORMS.
PRINTED IN U.S.A.

972445.00	766.66	0.03	1859.	1.	0.	-76.	0.00	784.50	

3445 OVERBANK AREA ASSIGNED NON-EFFECTIVE,ELLEA=						790.00 ELREA=		790.00	

FORD MOTOR CO. DA[illegible] CORPS C.S.#40

3320.00	42.05	780.59	0.30	788.19	786.70	0.11	2.04	0.00	768.00
1950.	2.	1950.	0.	0.	191.	0.	65.	41.	791.00
0.16	0.00	7.34	0.30	0.100	0.960	0.150	0.034	77[illegible].[illegible]	67.00
0.000291	1.	1.	1.	2	0	9	0.00	59.33	140.00

3445	0.000	CEHV=	0.930						
SECND	3672.000								

J501 HV CHANGED MORE THAN HVIIG

3445 OVERBANK AREA ASSIGNED NON-EFFECTIVE,ELLEA=						790.50 ELREA=		790.50	

D/S FACE TRUCK BRIDGE

3672.00	7.50	788.70	0.00	788.70	789.65	0.25	0.24	0.67	790.50
1950.	2.	1850.	0.	0.	236.	0.	71.	2.	790.50
0.19	0.00	7.82	0.00	0.100	0.950	0.160	0.039	781.10	479.49
0.000358	344.	344.	344.	2	0	1	0.00	61.51	526.07

[illegible] BRIDGE

[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]
0.00	1.96	3.30	0.00	20.00	7.00	395.00	1.52	781.10	781.10

[illegible] 3684.000
[illegible] ABUTMENT

LOBRS	EGLWC	WS	WETP	QPR	BAREA	TRAPEZOID AREA	LLLC	E_TRD
793.88	789.55	0.00	37.	1888.	193.	197.	787.70	790.50

3445 OVERBANK AREA ASSU ED NON-EFFECTIVE,ELLEA= 791.00 E_REA= 791.00

[illegible] BRIDGE

[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]
0.00	0.00	1850.	0.	0.	305.	0.	71.	12.	790.50
0.29	0.00	6.04	0.00	0.100	0.950	0.160	0.055	781.10	475.76
0.006138	12.	12.	12.	2	0	3	0.00	48.96	524.69

[illegible] 3645.000

3501 HV CHANGED MORE THAN [illegible]

FORM 1411-GB-PRINTED BY ROTARY MANIFOLD FORMS.
PRINTED IN U.S.A.

SECNO	DEPTH	CHSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
C	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	UTH	ELMIN	SSTA
SLOPE	KLOB	XLCS	XLOBS	ITRIAL	IH2	XCONT	CONAR	TCRWID	ENDST

VALLEY SECTION

3925.00	8.00	790.80	0.00	790.80	791.07	1.07	0.69	7.46	792.67
1850.	209.	537.	103.	77.	170.	42.	94.	12.	793.30
4.37	2.22	9.05	2.44	0.100	0.050	0.100	0.040	781.80	475.78
0.005329	143.	141.	141.	2	0	0	0.00	82.11	547.05

*SECNO 3965.000

* CS. IS CHANGED FROM HYDRAULIC JUMP

D/S FACE CRISWALD ST. BRIDGE

3965.00	7.70	791.71	0.00	791.76	793.35	1.99	0.71	7.56	794.60
1850.	196.	537.	90.	55.	136.	33.	72.	12.	785.10
2.28	1.45	9.98	3.01	0.100	0.050	0.100	0.040	784.60	423.73
0.011236	143.	143.	140.	2	0	0	0.00	63.53	469.23

SPECIAL BRIDGE

5227 DOWNSTREAM ELEV IS 789.93 FLOW 791.76 HYDRAULIC JUMP OCCURS DOWNSTREAM (IF LOW FLOW CONTROLS)

SC	XK	XKOB	COPO	ADLEN	BLC	BWP	DWIDA	SS	ELCHU	ELCHD
	1.25	1.27	0.70	0.00	19.25	1.63	31.00	1.00	789.60	792.60

FLOW 402.00I

3301 HW CHANGED MORE THAN HWINS

PRESSURE AND MIXED FLOW

ESPPS	SHLW2	H3	QLEIP	QWR	SAREA	TRAPEZOID AREA	FLLC	ELTRD
794.23	795.41	0.00	938.	1298.	916.	116.	791.10	796.00

3640 ENCROACHMENT STATIONS= 401.0 499.0 TYPE= 1 TARGET= 140.000

U/S FACE CRISWALD ST. BRIDGE

4000.00	11.40	794.10	0.00	794.80	795.48	2.56	11.37	8.72	795.50
1851.	276.	1291.	284.	181.	736.	113.	73.	12.	785.10
0.20	2.09	5.35	1.72	0.100	0.050	0.100	0.040	784.60	402.99
0.002416	63.	63.	63.	2	2	5	0.00	95.96	496.96

3640 ENCROACHMENT STATIONS= 310.0 340.0 TYPE= 1 TARGET= 250.000

50 FT U/S CRISWALD ST. BRIDGE CORPS C.S.942

4878.00	10.36	795.17	0.00	795.17	795.55	0.39	0.08	0.05	785.00
1850.	178.	1230.	433.	123.	205.	326.	74.	32.	786.30
0.20	1.40	4.34	1.32	0.100	0.140	0.190	0.040	764.30	397.29
0.001197	50.	80.	55.	2	0	0	2.00	147.47	543.01

*SECNO 4478.000

3501 HW CHANGED FROM TRAP AVE'S

VALLEY SECTION

4478.00	7.58	795.48	0.00	795.68	796.75	1.06	0.85	0.34	788.60
1150.	191.	1340.	318.	92.	140.	145.	78.	13.	789.80
0.37	2.32	9.00	2.20	0.100	0.340	0.170	1.050	769.13	387.72
0.005200	200.	360.	450.	2	0	0	0.50	182.98	517.31

*SECNO 4858.000

SECNO	DEPTH	CHSEL	CHNS	LSEL	LP	RV	TL	CORR	B/R ELEV
E	SLOP	DCH	SPCS	XLOT	ACT	LROD	POL	PMA	LSTR/PSH
FOR	MANN	SWR	PSHS	XNL	XWID	XWR	WT	ELMD	CBTA
SLOPE	XLOSL	XLCH	XLCBR	ITRIAL	IHP	ICONT	CORAD	TOPWID	E.OST

SECT ENCROACHMENT ST. ING= 417.4 469.0 TYPE= 1 TARGET= 71.320

51 FT D/S MILL POND DAM CORPS C.S.943

4858.00	6.03	798.03	0.00	798.03	798.84	0.80	2.03	0.08	795.00
11.	34.	17.	30.	15.	242.	1.	64.	14.	792.10
0.20	1.60	7.90	1.82	0.100	0.340	0.190	1.040	993.00	617.44
0.015	220.	340.	500.	3	1	0	0.	2.52	203.94

*SECNO 4907.000

SECT ENCROACHMENT STATION = 334.0 396.0 TYPE= 1 TARGET= 23.150

D/S MILL POND DAM

4907.00	6.27	798.27	1.00	798.37	799.22	0.95	3.51	5.07	804.00
1230.	1.	902.	0.	0.	232.	0.	11.	24.	10.3000.10
0.23	0.10	7.56	0.00	0.100	0.340	2.150	0.940	794.00	395.72
0.007358	90.	90.	90.	1	0	0	2.00	85.58	324.25

SHEET LAYOUT

0.00	1.50	2.90	0.50	0.10	0.30	0.90	0.00	794.00	795.10

*SECNO 4908.000

PRESSURE AND NEED FLOW

FORM 1411-GB-PRINTED BY ROYARY MANIFOLD FORMS.
PRINTED IN U.S.A.

ESPRS	ESLSC	AB	QWEIR	QPR	DAREA	TRAPEZOID AREA	ELLC	ELTRD
716512.00	799.23	0.00	1825.	2.	0.	-79.	0.00	801.00

BANK SUBCHANNEL AREA ASSUMED NON-EFFECTIVE,ELLEA= 810.00 ELREA= 810.00

MILL POND DAM CORPS C.S.644

4903.00	11.76	805.76	0.00	805.76	805.93	0.13	0.66	0.00	806.00
1481.	0.	1820.	0.	0.	693.	0.	1.	0.	806.00
0.73	0.00	2.64	0.00	0.100	0.040	0.100	0.010	794.00	354.00
0.000266	1.	1.	1.	2	0	10	0.00	62.00	396.00

QCAP= 3,170 CFS= 0.710
ASECID 3,806,000

MILL POND CORPS C.S.#45

5704.00	3.94	805.94	0.00	805.94	805.97	0.34	3.01	7.01	806.50
1440.	1.	1811.	1.	4.	1187.	1.	90.	6.	806.00
0.31	0.15	1.82	0.11	0.100	0.035	2.100	0.038	400.00	64.71
0.000187	400.	407.	400.	2	0	0	0.06	262.25	327.05

QCAP= 0.90 CFS= 1.000
ASLOPE 3W= 1.500

34YS OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 810.00 ELREA= 810.00

3926.00	9.33	805.93	0.00	836.73	836.11	0.05	0.11	0.00	836.50
1023.	0.	1820.	0.	0.	970.	0.	105.	14.	830.00
0.40	1.00	1.06	0.00	0.060	0.040	0.080	2.040	800.00	93.00
0.000231	520.	520.	520.	1	0	0	0.00	162.00	250.00

SECND DYS.DIS

3531 HY CHANGED 40.1E THAT LOINS

SUBID	DEPTH	ENLEN	COINS	MSELL	AS	IN	DE	ELEBS	PAVE ELEV
ST	ELEV	ISH	DROP	ELSD	SID	ABOD	VC	TOP	SSTA
SLOPE	KLOBL	XLCF	XLOBD	ETRIAL	IHS	ICONT	CORAP	TOPWID	EASET

SWIH ENCROACHMENT STATION= 3291.5 ELEV= 1 [illegible] 45.00

50 FT WIDE R.O. REGRADED

6578.00	2.62	805.93	0.00	836.58	807.11	0.19	0.51	0.00	808.00

FORM 1211-00 PRINTED BY ROTARY MANIFOLD FORMS.

PRINTED IN U.S.A.

	1820.	239.	1399.	191.	69.	141.	57.	107.	19.	799.40
	0.40	5.45	9.83	3.53	0.000	0.340	0.080	3.040	798.30	257.50
	0.005171	150.	150.	950.	2	0	0	0.00	45.00	302.50

#SECNO 6128.000

3301 HV CHANGED MORE THAN HVINS

SAVS OVERBANK AREA ASSIGNED NON-EFFECTIVE,ELLEA= 813.00 ELBEA= 815.00

D/S FACE C.O. R.R. BRIDGE #1 CORPS C.S.466

6129.00	7.65	806.05	0.00	806.05	808.39	2.35	0.36	0.93	799.00	
1320.	0.	1327.	0.	0.	148.	3.	107.	19.	796.90	
0.40	0.20	12.23	0.00	0.030	0.040	0.020	0.040	798.60	256.60	
0.011324	50.	50.	50.	0	0	0	0.00	30.00	351.00	

SPECIAL BRIDGE

SO	X	MODE	OPT2	OPT3	WSEL	UNC	UNC2	BOPX	SS	FLEN	LENL
	0.00	1.65	3.00	0.00	15.50	0.00	150.00	0.00	798.40	798.40

#SECNO 6170.000

3301 HV CHANGED MORE THAN HVINS

PRESSURE FLOW

EGPTS	ERLSS	PI	WPRIM	GTR	SAFES	TRAPEZOID AREA	ILLS	ELTRT
429.77	100.00	0.00	0.	1320.	125.	125.	803.17	813.20

3495 SVS,OVBNK AREA ASSIGNED NON-EFFECTIVE,ELLEA= 815.00 ELBEA= 815.00

U/S FACE C.O. R.R. BRIDGE #

6170.00	10.75	803.43	0.00	803.43	805.77	1.35	1.35	0.00	799.00
3128.	3.	1325.	0.	0.	175.	0.	133.	44.	796.82
0.40	0.20	2.22	3.00	0.080	0.040	0.230	0.240	798.60	230.30
0.005373	50.	50.	50.	1	0	0	0.00	30.00	450.30

#SECNO 6226.000

3301 HV CHANGED MORE THAN HVINS

3470 ENCROACHMENT STATIONS= 815.0 859.0 TYPE= 1 TARGET= 120.000

6226.00	11.50	813.43	2.00	813.43	816.45	0.35	0.35	0.00	799.00	
1320.	378.	510.	532.	30.	240.	321.	133.	15.	796.82	
0.41	1.23	3.06	1.96	0.030	0.040	0.230	0.240	797.50	295.30	
0.001367	50.	50.	50.	3	0	0	0.00	120.20	330.30	

PRINTED IN U.S.A.
FORM 5411-08 PRINTED BY ROTARY MANIFOLD FORMS.

CCHV= 0.300 CZHV= 0.500

*SECNO 7150.000

340? ENCROACHMENT STATIONS= 115.0 450.0 TYPE= 1 TARGET= 335.000

VALLEY SECTION

7150.00	9.25	810.95	0.00	811.95	811.04	0.09	0.42	0.01	802.02
1320.	950.	922.	269.	1121.	139.	350.	146.	95.	803.40
0.45	0.63	3.78	0.70	2.120	0.040	0.120	3.039	801.2?	810.00
0.000355	4400.	535.	100.	2	0	0	0.00	355.00	55.00

*SECNO 7300.000

SECNO	DEPTH	DWSEL	CRITS	WSEL	EL	HV	TW	BLOSS	ANK BLEV
XR	QL30	ACH	PROT	ALOB	ACH	.ECB	VOL	TRK	LEFT/RIGHT
TYPE	QL20	SICE	DPCH	K0	SLOP	SHR	TM	CODE	DEPT
SLOPE	XLCOL	XLCH	XLOB	ITRIAL	IP2	ICONT	CORAR	ICPLOT	END;T

540? ENCROACHMENT STATIONS= 170.0 360.0 TYPE= 1 TARGET= 265.000

D/S FACE OLD MOVIE RD. BRIDGE FIELD BOOK STA. 28+10

7300.27	9.03	811.13	0.00	811.13	811.25	0.12	0.20	0.21	802.10
1480.	991.	906.	421.	803.	201.	470.	134.	29.	902.24
0.65	0.89	4.02	0.95	0.120	0.040	0.120	0.036	802.30	130.20
0.000678	900.	750.	100.	2	1	0	0.00	250.20	50.20

SPECIAL BRIDGE

BR XR	BRLEN	TYPE	BRSKEW	WIDE	WINP	LSLOPE	RSLOPE	LSEL	RSEL
0.00	4.03	3.00	0.00	25.70	0.00	114.00	0.00	802.10	802.10

*SECNO 7325.000

PRESSURE FLOW FROM FLOW

CDPRS	EGLSC	HS	JUNIT	DPR	BARCA	TRAPEZOID AREA	ELLC	ELTRD
817.58	811.25	0.00	1211.	518.	114.	114.	802.90	810.10

540? ENCROACHMENT STATIONS= 100.0 360.0 TYPE= 1 TARGET= 260.000

D/S FACE OLD MOVIE RD. BRIDGE FIELD BOOK STA. 27+90

7325.00	9.00	810.78	0.00	811.78	811.87	0.09	0.43	0.00	802.10
1351.	914.	726.	347.	734.	219.	321.	115.	21.	902.24
0.60	0.82	3.55	0.83	0.120	0.040	0.120	0.036	802.10	100.00
0.000480	24.	29.	25.	2	0	4	0.00	260.00	550.00

*SECNO 7349.000

540? ENCROACHMENT STATIONS= 200.0 372.0 TYPE= 1 TARGET= 172.000

D/S FACE D/S OLD MOVIE RD. FIELD BOOK STA. 26+00

PRINTED IN U.S.A.
FORM 141-08-PRINTED BY ROTARY MANIFOLD FORMS.

7518.00	9.09	811.79	0.00	811.79	812.18	0.30	0.16	0.15	806.50	
1820.	472.	1266.	32.	360.	215.	98.	159.	25.	807.30	
0.61	1.31	5.09	0.84	0.120	0.040	0.120	0.033	802.70	200.00	
0.001757	190.	190.	190.	2	0	0	0.20	172.10	372.00	

*SECNO 7656.000

3301 HV CHANGED MORE THAN HVIVS

SECNO	DEPTH	SHEEL	SPANS	JSELK	EG	IV	"I"	FLOWS	DRAW ELEV
	FLOW	ASI	ONES	BLOC	ASH	4303	1.01	2.5" LEFT/2356.1T	
TIME	VLOJ	VCH	VROJ	ANL	XNCH	XVR	ATN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IH2	ICONT	CORAR	TCPWSO	ENDST

3473 ENCROACHMENT STATIONS= 533.0 581.0 TYPE= 1 TARGET= 46.000

SS CT 675 C.O. P.T. BRIDGE #2 FIELD BOOK STA. 22+50

7656.00	6.84	843.34	852.34	813.94	815.02	2.67	1.22	0.14	806.80
1820.	193.	1621.	7.	69.	117.	6.	163.	30.	806.80
0.32	2.79	13.87	0.82	0.120	0.040	0.120	0.038	805.70	533.00
0.011504	353.	350.	350.	3	15	2	0.00	46.00	501.00

*SECNO 7921.000

5301 HV CHANGED MORE THAN HVIVS

3475 OVERBANK AREA ENCROACHMENT ON LOB= 600.30 ELEV.= 816.30

D/S FACE C.O. R.R. BRIDGE #2 FIELD BOOK STA. 21+97

7921.00	8.84	1.6.18	0.00	827.34	835.80	0.37	0.93	0.81	806.50
1820.	0.	1820.	0.	0.	221.		1599.	21.	807.30
0.66	0.00	0.00	0.00	0.120	0.040	0.120	0.040	802.70	200.00
0.002962	55.	55.	55.	4	0	0	0.00	27.00	575.50

SPECIAL BRIDGE

SW	XP	YPCR	COPD	ROUGH	JUC	BWP	LAMPA	SS	ELCHO	FLCHD
	1.25	1.56	30.00	0.00	27.00	3.30	145.00	2.00	830.30	806.00

SECNO	DEPTH	SHEEL	SPANS	ASELK	EG	IV	"I"	FLOWS	DRAW ELEV
TIME	VLOJ	VCH	VROJ	XNL	XNCH	XVR	ATN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IH2	ICONT	CORAR	TCPWSO	ENDST

EGPRS	FLOW	HV	QUOT	SPE	DEPTH	VELOCITY	FLOW	ERROR		

PRINTED IN U.S.A.
FORM 1411-GB PRINTED BY ROTARY MANIFOLD FORMS.

818.85 816.18 0.48 0. 1820. 145. 157. 811.70 819.20

3495 OVERFLOW AREA ASSUMED NOT-EFFECTIVE-ELLEV= 820.00 ELDEA= 820.00

U/S FACE C.O. R.R. BRIDGE #2 FIELD BOOK STA. 21+55

7965.00 12.32 818.47 0.00 818.37 816.85 0.48 5.65 0.00 804.00
1820. 0. 1820. 0. 0. 526. 0. 165. 0. 807.50
0.67 0.00 5.30 0.00 0.120 0.034 0.120 2.034 564.00 546.50
0.000736 34. 61. 46. 2 0 0 2.00 32.00 325.50

CONV= 0.300 CENV= 0.500
ELEVO 811.00

3495 ENCROACHMENT STATIONS= 273.0 325.0 TYPE= 1 TARGET= 50.000

153 FT U/S C.O. R.R. BRIDGE #2 FIELD BOOK STA. 20+01

7998.00 14.32 808.82 0.00 814.82 815.00 0.36 0.18 0.00 806.82
1820. 0. 1820. 0. 0. 295. 111. 65. 0. 838.50
0.67 1.00 5.31 0.00 0.105 0.033 0.120 2.033 564.63 325.00
0.000639 60. 153. 60. 2 0 0 0.00 52.00 325.00

CONV= 0.300 CENV= 0.500
ELEVO 811.00

3470 ENCROACHMENT STATIONS= 257.0 381.0 TYPE= 1 TARGET= 124.000

33 FT D/S 8 TILE RD. CULVERT FIELD BOOK STA. 16+00

8018.00 11.98 809.20 0.00 809.53 810.25 0.47 0.20 0.00 801.20
1820. 0. 1820. 0. 0. 295. 111. 65. 0. 1820.00
0.67 0.00 5.47 0.00 0.120 0.035 0.120 2.035 564.70 257.00
0.000655 125. 600. 250. 2 2 0 0.20 124.00 300.00

ELEVO 811.00

D/S 8 TILE RD. CULVERT

8555.00 13.38 809.18 0.00 809.00 810.20 0.20 0.00 0.00 800.00
1820. 0. 1820. 0. 0. 511. 0. 172. 0. 840.00
0.67 0.00 5.30 0.00 0.120 0.035 0.120 2.035 563.75 0.00
0.000684 35. 57. 37. 1 0 0 0.20 69.00 0.00

CONV= 0.300 CENV= 0.500
ELEVO 8050.00

3470 ENCROACHMENT STATIONS= 257.0 381.0 TYPE= 1 TARGET= 124.000

D/S FACE 8 TILE RD. CULVERT FIELD BOOK STA. 22+62

8500.00 13.18 809.20 0.00 808.53 810.20 0.40 0.20 0.00 800.20
1820. 0. 1820. 0. 0. 295. 111. 65. 0. 1820.00
0.67 0.00 5.43 0.00 0.120 0.035 0.120 2.035 564.70 257.00
0.000672 1. 11. 2 2 0 -175.53 41.00 25.00

PRINTED IN U.S.A.
FORM 1411-00 PRINTED BY ROTARY MANIFOLD FORMS,

*SECNO 8811.000

SECNO	DEPTH	CHSEL	CHINS	MSCLK	EG	HV	HL	OLOSS	BANK ELEV
0	ALOB	OCF	3808	ALOB	ACI	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VOF	V80B	XNL	XNCH	KNB	ETA	ELMIN	SSTA
SLOPE	XSDIF	KLB1	KLB2B	ITRIAL	IP?	ICONT	CORAB	TCPHIS	ZRDST

3470 NORMAL PROF.280= 47 MIN ELTOP= 812.60 MAX ELLC= 818.60

W/S FACE 3 MILE RD. CROSSING — FIELD BOOK STA. 1220

8811.00	11.94	819.44	0.00	819.44	820.04	0.60	0.53	0.01	830.00
1820.	0.	1820.	0.	0.	292.	0.	172.	31.	430.00
0.68	0.00	5.23	0.00	0.110	0.020	0.100	0.336	807.30	0.00
0.001964	25.	255.	255.	2	0	0	50.30	48.00	48.00

CCHV= 0.300 CEHV= 0.500

*SECNO 8812.000

W/S FACE 3 MILE RD. CROSSING

8812.00	12.47	819.97	0.00	819.97	820.17	0.19	0.00	0.12	840.90
1820.	0.	1820.	0.	0.	>19.	0.	172.	31.	846.02
0.68	0.30	3.51	0.00	0.080	0.040	0.055	0.296	807.30	0.00
0.020634	6.	6.	6.	2	0	0	5.00	48.00	48.00

*SECNO 8818.000

3470 ENCROACHMENT STATIONS= 367.0 525.0 TYPE= 1 TARGET= 158.000

137 FT W/S 3 MILE RD. CROSSING — FIELD BOOK STA. 1240

8818.00	11.73	820.13	0.00	820.13	820.23	0.11	0.06	0.02	830.60
1820.	269.	514.	1361.	725.	115.	517.	173.	31.	908.80
0.69	1.03	4.41	1.72	0.080	0.040	0.083	0.136	808.40	367.00
0.006856	104.	81.	105.	2	4	4	0.00	48.00	52.00

CCHV= 0.700 CEHV= 0.300

*SECNO 9458.000

3470 ENCROACHMENT STATIONS= 255.0 568.3 TYPE= 1 TARGET= 313.000

WALL= 0.0 FT — FIELD BOOK STA. 1268

9458.00	10.67	820.37	0.00	820.37	820.40	0.03	0.10	0.01	830.10
1820.	635.	645.	722.	776.	135.	658.	165.	34.	840.70
0.82	5.04	2.45	0.94	0.065	0.040	0.240	0.015	810.30	258.60
0.003165	500.	533.	533.	2	0	0	0.10	48.00	565.50

CCHV= 0.300 CEHV= 0.500

*SECNO 9478.000

3470 ENCROACHMENT STATIONS= 255.0 568.3 TYPE= 1 TARGET= 281.000

FORM 1411-GB PRINTED BY ROTARY MANIFOLD FORMS.

PRINTED IN U.S.A.

36.5 FT D/S NEW NOVI RD. BRIDGE FIELD BOOK STA. 2+00

9918.00	9.75	820.25	0.00	820.25	820.92	0.67	0.20	0.32	812.20
1820.	238.	1279.	303.	128.	167.	104.	199.	36.	812.70
0.82	1.06	7.56	2.87	0.100	0.240	0.060	0.033	810.50	832.51
0.003611	135.	463.	500.	2	0	0	3.07	78.00	960.53

*SECNO 9973.500

SECNO	DEPTH	ZWSEL	CAINS	WSELK	EG	HV	L	DLOSS	HALF ELEV
9	9LOB	0C.	CHOB	ALOB	ACL	4ROW	VOL	TRA	LEFT/RIGHT
TOWC	VLOB	0C.	V10C		/INCH	KMR	%TM	EL PR	SST
FLOP:	XLOB	ALOB	RLOCR	17318.	TOP	LOCST	CLOB	CLCHN	CLROB

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 823.50 CLREA= 823.50

D/S FACE NEW NOVI RD. BRIDGE FIELD BOOK STA. 1+44.5

9973.50	9.72	820.42	0.00	820.42	821.08	0.66	0.16	0.00	820.76
1820.	0.	1820.	0.	0.	278.	0.	199.	36.	820.29
2.03	0.00	6.54	3.00	0.100	0.240	0.060	0.032	810.70	1925.07
1.003611	58.	52.	37.	2	0	0	2.01	96.43	1975.50

SPECIAL BRIDGE

BR NO	FLOW	DATA	BLOCK	T-S	WSP	FAREA	SS	LWRU	LCHR
1.05	1.69	3.00	3.00	21.00	2.00	335.00	1.23	810.70	810.70

*SECNO 10011.000

CLASS A CHN FLO.

3493 [illegible] VELOCITY= 6.12 CR SECTION AREAS 197.

EGPRS	ESLOB	HB	SWDIR	QPR	LAREA	TRAPEZOID AREA	ELLC	ELTRD
0.10	821.4	0.0	1.	702.	325.	325.	821.23	823.20

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 823.50 CLREA= 823.50

U/S FACE NEW NOVI RD. BRIDGE FIELD BOOK STA. 1+97

10011.00	9.81	820.51	0.00	820.51	821.16	0.65	0.07	0.00	820.71
1820.	0.	1820.	0.	0.	283.	0.	199.	36.	820.29
0.63	0.00	6.43	3.00	0.100	0.240	0.060	0.036	810.70	1924.87
0.003520	30.	31.	38.	0.	0	3	2.09	80.43	1976.50

*SECNO 10084.000

3493 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 826.10 CLREA= 826.10

[illegible] FIELD BOOK STA. 0+32

10146.00	9.82	820.32	0.00	820.32	821.45	0.73	0.29	0.34	820.90
1820.	0.	1820.	0.	0.	265.	0.	220.	36.	820.47

FORM 1411-GB-PRINTED BY ROTARY MANIFOLD FORMS.
PRINTED IN U.S.A.

	0.83	0.00	6.14	0.00	0.100	0.040	0.060	0.038	812.90	1533.00
	0.303969	73.	73.	73.	2	0	0	0.00	34.00	1567.00

SPECIAL BRIDGE

SA	MK	KJOB	CCFQ	RDLLR	B.C	B.P	BAREA	SS	ELCHD	ELCHC
	0.00	1.73	3.00	0.00	34.00	0.00	245.00	0.00	812.90	812.90

ASECTO 10094.000
PASSAGE FROM

EGPRS	CGLNC	MR	JHEIR	QPR	BAREA	YR/PARCID AREA	ELLC	ELTRD
827.20	821.49	0.00	0.	1120.	245.	245.	820.10	826.10

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 826.10 ELREA= 826.10

U/S FACE G.T. I.E. BRIDGE NO FIELD LOOK STA. CREW

10094.00	8.72	821.62	0.00	821.62	822.20	0.58	0.76	0.00	820.60
1120.	0.	1820.	0.	0.	297.	0.	200.	36.	820.00
0.83	0.00	6.14	0.00	0.100	0.040	0.060	0.038	812.90	1533.00
0.000520	10.	10.	10.	2	0	0	0.00	34.00	1567.00

*SECTO 10103.000

3501 SW (U/S)GD POOR THAN PARTS.

10103.00	6.37	821.77	0.00	821.77	822.78	1.53	0.00	0.00	812.90
1120.	1.	1821.	0.	0.	172.	0.	0.	0.	812.90
0.83	0.00	30.30	0.00	0.100	0.040	0.060	0.038	812.80	1539.00
0.003328	1.	9.	9.	2	0	0	0.00	22.00	1561.00

SECTO 10110.700

ARCID	DATA	STSEL	SECNO	SEE.K	SQ	HV	STL	LCRS	ROOF ELEV	
0	QLOW	QC	QQCQ	QLQT	ACH	ZRCQ	VOL	TW2	LEFT/RIGHT	
TYPE	VLOW	VC2	VQC2	XNL	XTCH	XNA	XTA	ICRSW	SSTA	
SLOPL	SLOUL	SLC1	SLQC2	ZTOTAL	I+2	ICORT	CORAR	YCPNTO	E.JCT	

3502 LOWING RIDGE,MED= 5 WTH ELTR.= 826.10 MAX ELLC= 826.10

3503 (U/S)NO ARCH ASSUMED NON-EFFECTIVE,ELLEA= 826.10 ELREA= 826.10

U/S FACE OLD MCVICS. BRIDGE FIELD LOOK STA. CREW

0110.00	4.52	821.17	0.00	821.17	822.73	1.56	0.01	0.10	813.30

FORM 1411-OB-PRINTED BY ROTARY MANIFOLD FORMS.

PRINTED IN U.S.A.

1620.	0.	1823.	0.	0.	182.	0.	205.	36.	813.10
0.83	0.00	10.00	0.00	0.100	0.040	0.060	0.038	812.60	1539.00
0.005326	1.	1.	1.	0	0	0	0.00	22.00	1561.00

*SECHC 10132.000

5370 NORMAL BRIDGE,NBR= 6 MIN ELTRD= 826.10 MAX ELLC= 823.10

5490 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 826.10 ELREA= 826.10

U/S FACE OLD NOVI RD. BRIDGE FIELD BOOK STA. 0+16

10132.00	8.33	829.43	0.00	821.43	822.89	1.46	0.14	0.03	813.30
1820.	1.	1827.	0.	0.	183.	2.	206.	36.	813.10
0.83	0.00	9.73	0.03	0.100	0.040	0.060	0.037	812.60	1539.00
0.005326	30.	4.	30.	2	0	0	0.00	22.00	1561.00

*SECLD 10153.000

5490 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 826.10 ELREA= 826.10

U/S OLD NOVI RD.

10153.00	8.44	831.44	0.00	821.44	822.93	1.49	0.00	0.03	813.30
1820.	0.	1827.	0.	0.	186.	0.	206.	36.	813.10
0.83	0.00	9.79	0.00	0.100	0.040	0.060	0.038	812.60	1539.00
0.004657	1.	1.	1.	0	0	0	0.00	22.00	1561.00

*SECLD 10157.000

5490 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 826.10 ELREA= 826.10

5370 ENCROACHMENT STATIONS= 364.0 416.0 TYPE= 1 WIDTH= 52.000

FIELD SURVEY, 6-80" 25' U/S OLD NOVI RD. BRIDGE

10157.00	9.47	832.17	0.00	822.17	823.13	0.96	0.09	0.15	812.80
1820.	177.	1831.	312.	63.	151.	65.	209.	36.	812.50
0.83	2.81	8.33	8.79	0.100	0.040	0.060	0.038	812.30	564.00
0.005438	24.	24.	24.	3	1	0	0.00	22.00	1561.00

PRINTED IN U.S.A.
FORM 1411-08-PRINTED BY ROTARY MANIFOLD FORMS.

PRINTED IN U.S.A.

FORM 1411-08 PRINTED BY ROTARY MANIFOLD FORMS,

```
**********************************************************
   HEC2 RELEASE DATED NOW TO UPDATED FEB 1977
   ERROR CORR =  01
   MODIFICATIO = 30.54.45
**********************************************************

 NOTE= ASTERISK (*) AT LEFT OF CROSS-SECTION NUMBER INDICATES MESSAGE IN SUMMARY OF ERRORS LIST

 MID.ROUGE R. N.VILLE C.

 SUMMARY PRINTOUT TABLE  150
```

SECNO	CLSSN	FRICTS	PS	TOPWID	ELCHL	XCH	ELOB	PCHNL	STRCHL	STRNL	STRCHR	STRNR
0.000	769.07	0.00	768.15	560.00	1191.43	1377.90	1171.47	560.00	165.00	425.00	465.00	725.00
0.000	769.17	0.12	768.24	560.00	1196.61	1365.83	1197.56	561.02	165.00	425.00	465.00	725.00
300.000	769.18	1.00	768.25	430.00	1008.15	1764.72	938.12	431.02	230.00	425.00	465.00	660.00
300.000	769.21	0.12	768.39	430.00	1016.97	1730.69	942.45	581.00	230.00	425.00	465.00	660.00
600.000	769.19	0.00	768.58	280.00	692.34	2322.96	664.70	280.00	305.00	425.00	465.00	585.00
600.000	769.29	0.09	768.73	280.00	720.66	2305.79	673.55	280.00	305.00	425.00	465.00	585.00
975.000	769.39	0.00	770.46	85.00	760.97	2502.07	416.99	85.00	545.00	575.00	600.00	635.00
975.000	769.53	0.13	770.60	85.00	761.47	2499.27	419.27	85.00	545.00	575.00	600.00	635.00
1025.000	769.65	0.00	770.82	49.47	0.00	3650.00	0.00	0.00	0.00	975.00	1035.00	0.00
1025.000	769.67	0.02	770.83	49.51	0.00	3680.00	0.00	0.00	975.00	975.00	1035.00	1035.00
1075.000	769.83	0.00	771.96	49.91	0.00	3680.00	0.00	0.00	0.00	975.00	1035.00	0.00
1075.000	769.99	0.00	771.98	49.97	0.00	3680.00	0.00	0.00	0.00	975.00	1035.00	0.00
1113.000	770.89	0.00	771.21	70.00	226.77	1468.52	174.71	70.00	965.00	989.00	1011.00	1035.00
1113.000	770.97	0.07	771.26	70.00	226.04	1468.00	175.18	70.00	965.00	989.00	1011.00	1035.00
2105.000	777.05	0.00	780.11	70.00	897.13	1473.66	77.21	70.00	295.00	318.00	342.00	365.00
2105.000	777.11	0.10	780.20	70.00	899.04	1471.52	77.33	70.00	295.00	318.00	342.00	365.00
2213.000	779.94	0.00	780.24	156.72	125.23	1512.32	217.42	170.00	35.00	90.00	123.00	205.00
2213.000	780.06	0.09	780.33	157.48	122.60	1503.41	223.99	170.00	35.00	90.00	123.00	205.00
2513.000	780.21	0.00	780.69	134.34	140.26	1525.16	208.18	0.00	0.00	411.00	440.00	0.00
2513.000	780.30	0.07	780.76	65.79	247.90	1561.01	191.01	0.00	295.38	415.00	440.00	465.62
2853.000	780.61	0.00	782.45	42.95	3.51	1823.31	23.13	0.00	0.00	108.00	144.00	0.00
2853.000	780.74	0.10	782.46	42.94	3.60	1821.70	24.72	42.44	108.46	108.00	144.00	144.40
2953.000	782.34	0.00	783.05	21.21	0.00	1850.00	0.00	0.00	0.00	148.47	169.68	0.00
2953.000	782.84	0.00	783.08	21.21	0.00	1850.00	0.00	0.00	0.00	148.47	169.68	0.00
3053.000	783.63	0.00	784.05	21.21	0.00	1850.00	0.00	0.00	0.00	148.47	169.68	0.00
3053.000	783.83	0.00	784.08	21.21	0.00	1850.00	0.00	0.00	0.00	148.47	169.68	0.00

	SECND	CWSEL	DIFKNS	EG	TOPSID	GLOD	SCH	CNDT	PERENC	STENCL	STCHL	STCHR	STENCR
	3133.000	786.04	0.00	786.45	64.91	65.64	1684.52	99.86	0.00	0.30	75.00	110.00	0.00
	3133.000	786.04	0.00	786.45	64.91	65.64	1684.52	99.86	0.00	0.30	75.00	110.00	0.00
	3278.000	786.69	0.00	786.62	83.00	57.22	1803.17	9.61	83.00	66.00	75.00	140.00	149.50
	3278.000	786.69	0.00	786.62	83.00	57.22	1803.17	9.61	83.00	66.00	75.00	140.00	149.50
	3327.000	786.50	0.00	786.66	58.63	0.00	1850.00	0.00	0.00	0.00	0.00	140.00	0.00
	3327.000	786.50	0.00	786.66	58.63	0.00	1850.00	0.00	0.00	0.00	0.00	140.00	0.00
	3384.000	786.49	0.00	786.70	59.33	0.00	1905.00	0.00	0.00	0.00	0.00	140.00	0.00
	3384.000	786.49	0.00	786.70	59.33	0.00	1905.00	0.00	0.00	0.00	0.00	140.00	0.00
	3672.000	788.70	0.00	789.65	63.58	0.00	1850.00	0.00	0.00	0.00	475.00	525.00	0.00
	3672.000	788.70	0.00	789.65	63.58	0.00	1850.00	0.00	0.00	0.00	475.00	525.00	0.00
	3686.000	788.87	0.00	789.77	63.93	0.00	1850.00	0.00	0.00	0.00	475.00	525.00	0.00
	3686.000	788.87	0.00	789.77	63.93	0.00	1850.00	0.00	0.00	0.00	475.00	525.00	0.00
	3825.000	790.80	0.00	791.87	52.11	209.46	1557.43	103.11	0.00	0.00	435.00	516.60	0.00
	3825.000	790.80	0.00	791.87	52.11	209.46	1557.43	103.11	0.00	0.00	435.00	516.60	0.00
	3965.000	791.76	0.00	793.55	63.53	109.73	1569.96	91.31	0.00	0.00	441.04	465.29	0.00
	3965.000	791.76	0.00	793.55	43.53	109.73	1569.96	91.31	0.00	0.00	441.04	465.29	0.00
*	4020.000	794.88	0.00	795.42	95.96	273.82	1341.46	234.70	140.00	400.95	441.05	460.29	498.96
*	4020.000	794.87	0.00	795.42	95.96	273.82	1341.46	234.70	140.00	400.95	441.05	460.29	498.96
	4070.000	795.17	0.00	795.55	147.47	177.69	1237.20	433.12	200.00	340.00	430.00	450.00	540.00
	4070.000	795.17	0.00	795.55	147.47	177.69	1237.20	433.12	200.00	340.00	430.00	450.00	540.00
	4078.000	795.68	0.00	796.73	127.99	191.46	1340.04	318.50	0.00	0.00	430.00	450.00	0.00
	4078.000	795.68	0.00	796.73	127.99	191.46	1340.04	318.50	0.00	0.00	430.00	450.00	0.00
	4138.000	795.80	0.00	796.84	71.53	24.46	1705.86	23.66	0.00	0.00	429.00	447.00	0.00
	4858.000	795.03	0.00	796.04	71.52	24.46	1705.86	23.66	71.52	417.44	425.00	450.00	465.96
	4507.000	798.27	0.00	799.22	58.56	0.00	1426.00	0.00	62.50	334.00	334.00	396.00	396.00
	4507.000	798.27	0.00	799.22	58.56	0.00	1426.00	0.00	62.50	334.00	334.00	396.00	396.00
	4908.000	805.78	0.00	806.88	62.00	0.00	1820.00	0.00	0.00	0.00	334.00	396.00	0.00
	4908.000	805.78	0.00	806.88	62.00	0.00	1820.00	0.00	0.00	0.00	334.00	396.00	0.00
	5300.000	805.94	0.00	805.97	262.25	0.56	1818.19	1.25	0.00	0.00	71.00	320.00	0.00
	5300.000	805.94	0.00	805.97	262.25	0.56	1818.19	1.25	0.00	0.00	71.00	320.00	0.00
	5929.000	806.83	0.00	806.11	150.00	0.00	1820.00	0.00	0.00	0.00	90.00	240.00	0.00
	5929.000	806.83	0.00	806.11	150.00	0.00	1820.00	0.00	0.00	0.00	90.00	240.00	0.00
	6078.000	805.93	0.00	807.11	45.00	238.64	1390.77	140.34	45.00	257.50	270.00	290.00	302.50
	6078.000	805.93	0.00	807.11	45.00	238.64	1390.77	140.34	45.00	257.50	270.00	290.00	302.50
	6128.000	806.53	0.00	808.39	20.00	0.00	1820.00	0.00	0.00	0.00	230.00	250.00	0.00
	6128.000	806.53	0.00	808.39	20.00	0.00	1820.00	0.00	0.00	0.00	230.00	250.00	0.00
	6178.000	806.43	0.00	809.77	20.00	0.00	1820.00	0.00	0.00	0.00	230.00	250.00	0.00
	6178.000	806.43	0.00	809.77	20.00	0.00	1820.00	0.00	0.00	0.00	230.00	250.00	0.00

PRINTED IN U.S.A.
FORM 1411-9B PRINTED BY ROTARY MANIFOLD FORMS.

SECNO	CWSEL	DIFKWS	EG	TOPWID	QLOB	QCH	QROB	PERENC	STENCL	STCHL	STCHR	STENCR
6228.000	810.43	0.00	810.55	120.00	377.89	910.00	532.16	120.00	215.00	270.00	290.00	335.00
6228.000	810.43	0.00	810.55	120.00	377.89	910.00	532.16	120.00	215.00	270.00	290.00	335.00
7153.000	811.59	0.00	811.04	335.00	850.39	732.00	267.91	335.00	115.00	338.00	359.00	450.00
7150.000	810.95	0.00	811.04	335.00	850.39	732.00	267.91	335.00	115.00	338.00	359.00	450.00
7320.000	811.13	0.00	811.25	260.00	591.11	807.61	421.26	260.00	100.00	237.65	261.35	360.00
7330.000	811.19	0.00	811.25	260.00	591.11	807.61	421.26	260.00	100.00	237.65	261.35	360.00
7328.000	811.78	0.00	811.87	260.00	513.85	769.45	430.71	260.00	100.00	237.65	261.35	360.00
7518.000	811.79	0.00	812.13	172.00	471.80	1265.46	82.33	172.00	200.00	287.00	313.00	372.00
7518.000	811.79	0.00	812.18	172.00	471.80	1265.46	82.33	172.00	200.00	287.00	313.00	372.00
7808.000	812.34	0.00	813.02	48.00	192.66	1620.84	6.53	48.00	553.00	551.00	569.00	581.00
7921.000	814.04	0.00	815.80	27.00	0.00	1020.00	0.00	0.00	0.00	546.53	573.50	0.00
7921.000	814.04	0.00	815.80	27.00	0.00	1020.00	0.00	0.00	0.00	546.53	573.50	0.00
7965.000	818.37	0.00	818.85	27.00	0.00	1020.00	0.00	0.00	0.00	546.53	573.50	0.00
8118.000	818.63	0.00	819.00	53.00	125.22	1566.12	128.67	50.00	275.00	287.00	313.00	325.00
8118.000	818.63	0.00	819.00	53.00	125.22	1566.12	128.67	50.00	275.00	287.00	313.00	325.00
8518.000	819.03	0.00	819.25	124.00	343.16	1071.33	405.51	124.00	257.00	307.00	331.00	381.00
8555.000	819.08	0.00	819.26	48.00	0.00	1020.00	0.00	0.00	0.00	0.00	48.00	0.00
8555.000	819.08	0.00	819.26	48.00	0.00	1020.00	0.00	0.00	0.00	0.00	48.00	0.00
8556.000	819.08	0.00	819.59	48.00	0.00	1020.00	0.00	0.00	0.00	0.00	48.00	0.00
8811.000	819.44	0.00	820.04	48.00	0.00	1020.00	0.00	0.00	0.00	0.00	48.00	0.00
8811.000	819.44	0.00	820.04	48.00	0.00	1020.00	0.00	0.00	0.00	0.00	48.00	0.00
8812.000	819.97	0.00	820.17	48.00	0.00	1020.00	0.00	0.00	0.00	0.00	48.00	0.00
8978.000	820.19	0.00	820.29	158.00	242.63	513.66	1063.71	158.00	367.00	441.00	451.00	525.00
8978.000	820.19	0.00	820.29	158.00	242.63	513.66	1063.71	158.00	367.00	441.00	451.00	525.00
9453.000	820.37	0.00	820.40	340.00	653.06	445.19	731.77	340.00	255.00	411.00	419.00	565.00
9978.000	820.25	0.00	820.92	78.00	238.14	1278.56	303.44	0.00	362.50	912.00	931.00	960.50
9978.000	820.25	0.00	820.97	78.00	238.14	1278.56	303.44	78.00	362.50	912.00	931.00	960.50
9978.000	820.42	0.00	821.07	53.00	0.00	1020.00	0.00	0.00	0.00	1524.50	1575.50	0.00
9978.000	820.59	0.00	821.16	53.00	0.00	1020.00	0.00	0.00	0.00	1524.50	1575.50	0.00

SECNO	CABEL	DIPKUS	SG	TOPWID	BLOD	BCH	GROB	PERENC	STENCL	STCHL	STCHR	STENCH
10094.000	820.72	0.00	821.45	34.00	0.00	1320.00	0.00	0.00	0.00	1533.00	1567.00	0.00
10094.000	820.72	0.00	821.45	34.00	0.00	1320.00	0.00	0.00	0.00	1533.00	1567.00	0.00
10394.000	821.37	0.00	822.20	34.00	0.00	1627.00	0.00	0.00	0.00	1533.00	1567.00	0.00
10394.000	821.62	0.00	822.30	34.00	0.00	1625.00	0.00	0.00	0.00	1533.00	1567.00	0.00
10703.000	821.37	0.00	822.72	22.00	0.00	1625.00	0.00	0.00	0.00	1539.00	1561.00	0.00
10703.100	821.37	0.00	822.72	22.00	0.00	1625.00	0.00	0.00	0.00	1539.00	1561.00	0.00
10704.000	821.37	0.00	822.73	22.00	0.00	1625.00	0.00	0.00	0.00	1539.00	1561.00	0.00
10704.000	821.17	0.00	822.73	22.00	0.00	1620.00	0.00	0.00	0.00	1539.00	1561.00	0.00
10132.000	821.43	0.00	822.89	22.00	0.00	1623.00	0.00	0.00	0.00	1539.00	1561.00	0.00
10132.100	821.43	0.00	822.89	22.00	0.00	1620.00	0.00	0.00	0.00	1539.00	1561.00	0.00
10133.000	821.44	0.00	822.92	22.00	0.00	1620.00	0.00	0.00	0.00	1539.00	1561.00	0.00
10135.000	821.44	0.00	822.92	22.00	0.00	1620.00	0.00	0.00	0.00	1539.00	1561.00	0.00
10157.000	822.17	0.00	823.13	32.00	177.25	1331.20	211.56	32.00	364.00	542.00	408.00	416.00
10157.000	822.17	0.00	823.13	32.00	177.25	1331.20	211.56	32.00	364.00	542.00	408.00	416.00

R

PRINTED IN U.S.A.

FORM 1411-GG-PRINTED BY ROTARY MANIFOLD FORMS,

MID.ROUGE R. N.VILLE C.

SUMMARY PRINTOUT TABLE 150

	FROND	STAGE	FLOW	ELEV	ELEV	S	CSEL	COND	HO	VOL+S	VOL	AREA	DIR
	0.000	0.00	0.00	0.00	757.10	3680.00	768.07	0.00	768.14	3.03	3.42	3282.36	2115.19
	0.000	0.00	0.00	0.00	757.10	3680.00	768.17	0.00	768.24	2.68	3.36	3338.42	2168.13
	300.000	300.00	0.00	0.00	758.00	3680.00	768.13	0.00	768.80	6.27	4.65	2267.04	1469.66
	300.000	300.00	0.00	0.00	758.00	3680.00	768.23	0.00	768.89	5.96	4.56	2269.22	1517.77
	900.000	300.00	0.00	0.00	758.90	3680.00	768.19	0.00	768.66	15.81	6.93	1274.60	925.56
	900.000	300.00	0.00	0.00	758.90	3680.00	768.29	0.00	768.75	15.02	6.80	1300.51	949.49
	978.000	978.00	0.00	0.00	760.10	3680.00	769.58	0.00	770.46	66.48	11.11	519.97	451.34
	978.000	978.00	0.00	0.00	760.10	3680.00	769.67	0.00	770.55	66.05	13.02	534.55	456.99
	1028.000	50.00	0.00	0.00	757.40	3680.00	769.65	0.00	770.82	14.18	8.65	425.19	914.96
	1028.000	50.00	0.00	0.00	757.40	3680.00	769.67	0.00	770.83	14.16	8.64	425.98	917.27
	1078.030	50.00	775.30	775.30	757.40	3680.00	769.52	0.00	770.91	15.30	8.48	431.13	940.69
	1078.030	50.00	775.30	775.30	757.40	3680.00	769.62	0.00	771.00	14.95	8.36	432.94	955.33
	1113.000	35.00	0.00	0.00	757.90	1850.00	770.89	0.00	771.21	2.37	5.06	747.41	1200.45
	1113.000	35.00	0.00	0.00	757.90	1850.00	770.97	0.00	771.28	2.33	5.04	752.42	1211.22
*	2163.030	1050.30	100300.00	100300.00	769.90	1850.00	775.66	0.00	780.10	14.41	6.36	453.22	487.37
*	2163.030	1050.30	100300.00	100300.00	769.90	1850.00	775.70	0.00	781.20	13.38	6.31	457.21	496.56
	2213.000	50.00	0.00	0.00	770.00	1850.00	779.96	0.00	780.24	4.42	4.66	673.60	602.64
	2213.000	50.00	0.00	0.00	770.00	1850.00	780.06	0.00	780.33	4.02	4.59	688.36	615.92
	2313.000	100.00	0.00	0.00	771.70	1850.00	780.29	0.00	781.62	13.39	6.00	467.72	423.61
	2313.100	100.01	0.00	0.00	771.70	1850.00	780.36	0.00	781.71	13.13	5.96	468.70	425.33
	2863.300	550.00	0.00	0.00	773.80	1850.00	780.64	0.00	782.63	94.70	10.32	186.01	190.10
	2863.300	550.00	0.00	0.00	773.80	1850.00	780.74	0.00	782.46	88.04	10.61	191.21	196.49
	2963.200	100.00	0.00	0.00	774.00	1850.00	780.75	0.00	782.85	148.32	14.19	150.00	153.96
	2963.300	100.00	0.00	0.00	774.00	1850.00	780.85	0.00	782.95	148.72	14.47	150.00	153.96
	3063.100	100.00	791.20	785.60	775.90	1850.00	785.85	0.00	785.85	73.85	11.42	162.17	215.24
	3063.000	100.00	791.20	785.60	775.90	1850.00	785.93	0.00	785.95	73.85	11.41	162.17	215.24
	3113.000	50.00	0.00	0.00	776.00	1850.00	786.04	0.00	786.65	10.96	8.32	459.27	559.55
	3113.000	50.00	0.00	0.00	776.00	1850.00	786.04	0.00	786.65	10.96	8.32	459.27	559.79
	3278.000	165.00	0.00	0.00	776.40	1850.00	786.19	0.00	786.62	3.52	2.92	894.95	986.54
	3278.000	165.00	0.00	0.00	776.40	1850.00	786.29	0.00	786.62	3.52	2.92	894.95	986.54
	3328.000	50.00	0.00	0.00	776.50	1850.00	786.40	0.00	786.66	5.81	3.26	587.91	713.70
	3328.200	50.00	0.00	0.00	776.50	1850.00	786.50	0.00	786.69	5.81	3.26	587.91	713.70
	3528.000	1.00	784.50	0.00	776.50	1850.00	790.99	0.00	788.70	2.61	2.63	691.22	1564.37
	3528.000	1.00	784.50	0.00	776.50	1850.00	790.99	0.00	788.70	2.91	2.66	691.22	1564.37
	3728.000	200.00	0.00	0.00	781.10	1850.00	791.74	0.00	789.45	83.34	7.52	246.45	804.38
	3728.000	200.00	0.00	0.00	781.10	1850.00	791.84	0.00	789.58	83.34	7.52	246.45	804.38

FORM 1411-GB PRINTED BY ROTARY MANIFOLD FORMS, U.S.A.

SECND	XLCH	ELTRO	ELLC	ELMIN	Q	CHSEL	CPINS	EO	TORQS	VCH	AREA	.DTK
3684.000	12.00	790.50	787.70	781.10	1850.00	790.21	3.00	790.77	61.38	6.04	306.39	287.56
3684.000	12.00	790.50	787.70	781.10	1850.00	790.21	3.00	790.77	61.38	6.04	306.39	287.56
3825.000	141.00	0.00	0.00	782.00	1850.00	791.00	0.00	791.87	55.91	9.03	269.43	241.04
3825.000	141.00	0.00	0.00	782.00	1850.00	791.00	0.00	791.87	55.91	9.03	269.43	241.04
3965.000	140.00	0.00	0.00	784.60	1850.00	791.76	0.00	793.55	112.36	11.53	220.36	174.52
3965.000	140.00	0.00	0.00	784.60	1850.00	791.76	0.00	793.55	112.36	11.53	220.36	174.52
4028.000	63.00	794.50	791.10	794.60	1650.00	794.83	0.00	795.42	24.16	6.85	462.18	376.37
4028.000	63.00	794.50	791.10	794.60	1650.00	794.83	0.00	795.42	24.16	6.85	462.18	376.37
4078.000	50.00	0.00	0.00	736.30	1850.00	795.17	0.00	795.55	11.97	6.04	656.79	534.63
4078.000	50.00	0.00	0.00	736.30	1850.00	795.17	0.00	795.55	11.97	6.04	656.79	534.63
4478.000	400.00	0.00	0.00	783.10	1850.00	795.63	0.00	796.73	50.70	9.60	366.75	259.61
4478.000	400.00	0.00	0.00	780.10	1850.00	795.63	0.00	796.73	50.70	9.60	366.75	259.61
4858.000	380.00	0.00	0.00	792.00	1320.00	796.04	0.00	798.54	54.99	7.30	275.78	247.24
4858.000	380.00	0.00	0.00	792.00	1320.00	796.01	0.00	798.32	54.99	7.30	275.03	247.24
4937.000	79.00	0.00	0.00	794.00	1320.00	796.27	0.00	799.22	76.56	7.83	232.33	203.01
4937.000	79.00	0.00	0.00	794.00	1320.00	796.27	0.00	799.22	76.56	7.83	232.33	203.01
4938.000	1.00	801.00	0.00	794.00	1820.00	805.76	0.00	805.83	2.66	2.64	690.07	1114.98
4938.000	1.00	801.00	0.00	794.00	1820.00	805.76	0.00	805.83	2.66	2.64	690.07	1114.98
5338.000	400.00	0.00	0.00	800.00	1820.00	805.94	0.00	805.97	1.67	1.54	1191.63	1609.32
5338.000	400.00	0.00	0.00	800.00	1820.00	805.94	0.00	805.97	1.67	1.54	1191.63	1609.32
5928.000	620.00	0.00	0.00	800.00	1820.00	806.05	0.00	806.11	2.31	1.88	970.00	1197.61
5928.000	620.00	0.00	0.00	800.00	1820.00	806.05	0.00	806.11	2.31	1.88	970.00	1197.61
6073.000	145.00	0.00	0.00	799.30	1320.00	805.92	0.00	807.31	31.71	5.64	267.92	255.10
6073.000	150.00	0.00	0.00	799.30	1020.00	805.92	0.00	807.31	31.71	9.03	267.92	255.10
6128.000	50.00	0.00	0.00	798.40	1320.00	806.05	0.00	808.39	105.24	12.29	148.63	177.42
6128.000	50.00	0.00	0.00	798.40	1320.00	806.05	0.00	808.39	105.24	12.29	148.63	177.42
6178.000	50.00	813.70	800.20	798.40	1320.00	806.45	0.00	809.77	46.75	9.51	195.46	266.19
6178.000	50.00	813.70	800.20	798.40	1320.00	806.45	0.00	809.77	46.75	9.51	195.46	266.19
6224.000	50.00	0.00	0.00	797.90	1320.00	810.45	0.00	810.55	3.92	3.80	938.77	522.60
6224.000	50.00	0.00	0.00	797.90	1320.00	810.45	0.00	810.55	3.42	3.80	938.77	930.90
7150.000	926.00	0.00	0.00	801.70	1320.00	810.95	0.00	811.84	8.25	3.72	1560.25	772.42
7150.000	926.00	0.00	0.00	801.70	1820.00	810.95	0.00	811.84	8.25	3.72	1560.25	772.42
7300.000	150.00	0.00	0.00	802.10	1820.00	811.12	0.00	811.45	6.78	4.02	1334.13	698.73
7300.000	150.00	0.00	0.00	802.10	1820.00	811.12	0.00	811.45	6.78	4.02	1334.13	698.73
7328.000	28.00	813.10	804.90	802.10	1820.00	811.26	0.00	811.87	4.80	3.55	1504.63	830.35
7328.000	28.00	813.10	804.90	802.10	1820.00	811.26	0.00	811.87	4.80	3.55	1504.63	830.35
7518.000	190.00	0.00	0.00	802.70	1820.00	811.79	0.00	812.38	17.57	5.69	672.95	434.15
7518.000	190.00	0.00	0.00	802.70	1820.00	811.79	0.00	812.38	17.57	5.69	672.95	434.15

PRINTED IN U.S.A.
FORM 1411-08 PRINTED BY ROTARY MANIFOLD FORMS.

	SECNO	XLCH	ELTRD	ELLC	ELMIN	B	CWSEL	CRIWS	EG	10K*S	VCH	AREA	.01K
*	7968.000	350.00	0.00	0.00	805.70	1820.00	812.34	812.34	815.02	115.04	13.87	193.82	169.69
	7968.000	350.00	0.00	0.00	805.70	1820.00	812.34	812.34	815.02	115.04	13.87	193.82	169.69
	7925.000	83.00	0.00	0.00	806.50	1820.00	814.84	0.00	815.80	29.62	7.88	230.13	334.44
	7921.000	53.00	0.00	0.00	806.50	1820.00	814.84	0.00	815.80	29.62	7.88	230.13	334.44
	7965.000	44.00	819.20	811.70	806.50	1820.00	818.37	0.00	818.85	10.34	5.58	326.13	565.99
	7965.000	44.00	819.20	811.70	806.50	1820.00	818.37	0.00	818.85	10.34	5.58	326.13	565.99
	8178.000	153.00	0.00	0.00	806.60	1820.00	819.62	0.00	819.90	6.39	3.31	517.07	720.23
	8178.000	153.00	0.00	0.00	806.60	1820.00	819.62	0.00	819.90	6.39	3.31	517.07	720.23
	8556.000	407.00	0.00	0.00	807.70	1820.00	819.05	0.00	819.25	4.55	4.17	1042.50	853.08
	8556.000	407.00	0.00	0.00	807.70	1820.00	819.05	0.00	819.25	4.55	4.17	1042.50	853.08
	8555.000	37.00	0.00	0.00	805.70	1820.00	819.03	0.00	819.28	4.84	3.36	511.04	827.21
	8555.000	37.00	0.00	0.00	805.70	1820.00	819.03	0.00	819.26	4.84	3.36	511.04	827.21
	8556.000	1.00	840.00	817.70	805.70	1820.00	818.86	0.00	819.50	24.72	6.45	283.05	390.53
	8556.000	1.00	840.00	817.70	805.70	1820.00	818.86	0.00	819.50	24.72	6.45	283.05	390.53
	8811.000	255.00	812.60	813.60	807.50	1820.00	819.44	0.00	820.04	19.64	6.23	292.31	410.63
	8812.000	1.00	0.00	0.00	807.50	1820.00	819.97	0.00	820.17	6.04	3.51	518.50	740.52
	8812.000	1.00	0.00	0.00	807.50	1820.00	819.97	0.00	820.17	6.04	3.51	518.50	740.52
	8916.000	106.00	0.00	0.00	808.40	1820.00	820.13	0.00	820.25	5.56	4.41	957.98	785.97
	8916.000	106.00	0.00	0.00	808.40	1820.00	820.13	0.00	820.25	5.56	4.41	957.98	785.97
	9443.000	535.00	0.00	0.00	810.00	1820.00	820.37	0.00	820.40	1.95	2.43	1817.16	1304.69
	9443.000	535.00	0.00	0.00	810.00	1820.00	820.37	0.00	820.40	1.95	2.43	1817.16	1304.69
	9918.000	485.00	0.00	0.00	810.90	1820.00	820.25	0.00	820.92	24.11	7.66	401.04	370.06
	9918.000	485.00	0.00	0.00	810.90	1820.00	820.25	0.00	820.92	24.11	7.66	401.04	370.06
	9973.500	55.50	0.00	0.00	810.70	1820.00	820.42	0.00	821.05	35.11	6.54	278.19	307.16
	9973.500	55.50	0.00	0.00	810.70	1820.00	820.42	0.00	821.01	35.11	6.54	278.19	307.16
	10011.000	37.50	823.50	811.20	810.70	1820.00	820.51	0.00	821.16	32.29	6.43	283.20	315.39
	10011.000	37.50	823.50	811.20	810.70	1820.00	820.51	0.00	821.16	32.29	6.43	283.20	315.39
	10084.000	73.00	0.00	0.00	812.90	1820.00	820.72	0.00	821.45	55.49	6.84	205.96	305.49
	10084.000	73.00	0.00	0.00	812.90	1820.00	820.72	0.00	821.45	55.49	6.84	205.96	305.49
	10084.000	13.00	826.10	820.10	812.90	1820.00	821.09	0.00	822.26	25.28	6.14	206.28	564.99
	10084.000	13.00	826.10	820.10	812.90	1820.00	821.09	0.00	822.26	25.28	6.14	206.28	564.99
	10105.000	9.00	0.00	0.00	812.40	1820.00	820.17	0.00	822.72	51.26	10.00	101.96	254.20
	10105.000	9.00	0.00	0.00	812.40	1820.00	820.17	0.00	822.72	51.26	10.00	101.96	254.20
	10106.000	1.00	826.10	820.10	812.40	1820.00	821.17	0.00	822.73	51.26	10.00	101.96	254.20
	10106.000	1.00	826.10	820.10	812.40	1820.00	821.17	0.00	822.73	51.26	10.00	101.96	254.20
	10132.000	26.00	826.10	820.10	812.60	1820.00	821.43	0.00	822.06	46.64	9.70	107.85	266.52
	10132.000	26.00	826.10	820.10	812.60	1820.00	821.43	0.00	822.06	46.64	9.70	107.85	266.52

PRINTED IN U.S.A.
FORM 1411 SB PRINTED BY ROTARY MANIFOLD FORMS.

SECNO	XLOC	ELTID	ELLC	ELMIN	Q	CNSEL	CRIBS	EG	13K*S	VOM	AREA	.01K
10133.000	1.00	0.00	0.00	812.60	1820.00	821.44	0.00	822.90	46.57	9.69	187.77	266.71
10133.100	1.00	0.00	0.00	812.60	1820.00	821.44	0.00	822.90	46.57	9.69	187.77	266.71
10157.000	24.00	0.00	0.00	812.70	1820.00	822.17	0.00	823.13	27.38	8.83	278.92	347.64
10157.000	24.00	0.00	0.00	812.70	1820.00	822.17	0.00	823.13	27.38	8.83	278.92	347.64

PRINTED IN U.S.A.
FORM 1411-GB-PRINTED BY ROTARY MANIFOLD FORMS,

RIO.ROUGE R. \.VILLE C.

SUMMARY PRINTOUT TABLE 150

	0.000	3680.00	758.07	0.00	0.00	0.00	560.00	0.00
	0.000	3680.00	758.17	0.30	0.00	0.10	560.00	0.00
	[illegible]	[illegible]	[illegible]	0.30	0.36	0.00	550.00	300.00
	[illegible]	[illegible]	[illegible]	0.00	0.06	0.10	[illegible]	[illegible]
	600.000	3680.00	768.19	0.00	0.06	0.00	260.00	300.00
	600.000	3680.00	768.29	0.00	0.06	0.09	260.00	300.00
	[illegible]	[illegible]	[illegible]	0.00	0.36	0.00	85.00	[illegible]
	[illegible]	[illegible]	[illegible]	0.00	0.36	0.05	89.00	[illegible]
	1028.000	3680.00	759.65	0.00	1.00	0.00	49.47	50.00
	1028.000	3680.00	759.57	0.00	1.00	0.02	49.51	50.00
	[illegible]	[illegible]	[illegible]	0.00	0.17	0.00	49.91	[illegible]
	[illegible]	[illegible]	[illegible]	0.30	0.35	0.10	[illegible]	[illegible]
	1113.000	1850.00	770.89	0.00	1.07	0.00	70.00	35.00
	1113.000	1850.00	770.97	0.00	1.04	0.07	70.00	35.00
	[illegible]	1850.00	[illegible]	0.00	0.71	0.00	[illegible]	[illegible]
	[illegible]	1850.00	[illegible]	0.00	0.75	0.10	[illegible]	[illegible]
	2213.000	1850.00	770.96	0.00	0.36	0.00	156.72	50.00
	2213.000	1850.00	730.36	0.30	0.36	0.09	157.46	50.00
	[illegible]	[illegible]	[illegible]	0.30	0.30	0.00	[illegible]	300.00
	[illegible]	[illegible]	[illegible]	0.30	0.26	0.07	[illegible]	[illegible]
	2863.300	1850.00	770.67	0.00	0.41	0.00	42.95	350.00
	2863.000	1850.00	770.74	0.00	0.56	0.00	42.92	530.00
	[illegible]	[illegible]	[illegible]	1.00	1.71	0.00	21.31	[illegible]
	[illegible]	[illegible]	[illegible]	0.10	1.50	0.00	21.31	[illegible]
	3663.000	1850.00	767.87	0.00	1.46	0.00	21.31	100.00
	3663.000	1850.00	755.85	0.00	1.49	0.00	21.31	100.00
	[illegible]	[illegible]	[illegible]	2.00	2.22	0.00	56.85	[illegible]
	[illegible]	[illegible]	[illegible]	1.00	2.28	0.00	57.35	[illegible]
	3278.000	1850.00	766.69	2.00	2.46	0.00	83.30	165.00
	3278.000	1850.00	786.69	2.00	2.25	0.00	83.30	165.00
	[illegible]	[illegible]	[illegible]	1.00	1.00	0.00	[illegible]	[illegible]
	[illegible]	[illegible]	[illegible]	1.00	1.00	0.00	[illegible]	[illegible]
	3328.000	1850.00	780.79	0.00	2.06	0.00	59.58	1.00
	3326.000	1850.00	738.39	0.00	2.09	0.00	59.54	1.00
	[illegible]	[illegible]	[illegible]	0.30	0.18	0.00	[illegible]	[illegible]
	[illegible]	[illegible]	[illegible]	0.30	0.21	0.00	[illegible]	[illegible]

PRINTED IN U.S.A.

FORM 1411 GB-PRINTED BY ROTARY MANIFOLD FORMS.

SECND	Q	CHSEL	DIFWSP	DIFUSX	DIFANS	TOPWID	XLCP
3684.020	1850.00	790.21	0.00	1.51	0.00	48.98	92.30
3684.070	1850.00	790.21	0.00	1.51	0.00	48.98	12.30
3825.000	1850.00	790.80	0.00	0.59	0.00	92.11	371.00
3825.300	1850.00	790.80	0.00	0.59	0.00	92.11	371.00
3965.300	1850.00	791.36	0.00	0.97	0.00	43.53	240.00
3965.300	1850.00	791.36	0.00	0.97	0.00	43.53	141.00
4028.000	1850.00	791.89	0.00	0.12	0.00	95.96	63.00
4628.000	1850.00	794.89	0.00	3.12	0.00	95.96	63.00
4678.000	1850.00	795.17	0.00	0.29	0.00	147.47	50.00
4678.000	1850.00	795.17	0.00	0.29	0.00	147.47	50.00
4728.000	1850.00	795.53	0.00	0.31	0.00	132.00	400.00
4778.000	1850.00	795.68	0.00	0.91	0.00	127.99	400.00
4858.000	1820.00	796.05	0.00	2.36	0.00	71.52	390.00
4858.020	1820.00	796.05	0.00	2.36	0.00	71.52	230.70
4907.000	1820.00	796.37	0.00	1.24	0.00	58.56	49.00
4907.030	1820.00	796.37	0.00	0.24	0.00	58.56	49.00
4964.030	1820.00	805.71	0.00	7.57	0.00	62.50	1.00
4971.030	1820.00	805.75	0.00	7.53	0.00	62.50	1.00
5025.030	1820.00	805.94	0.00	0.19	0.00	232.25	405.00
5305.030	1820.00	805.97	0.00	0.16	0.00	232.25	300.00
5528.000	1820.00	806.05	0.00	0.12	0.00	140.50	620.00
5536.000	1820.00	806.09	0.00	0.12	0.00	140.50	220.00
5073.030	1820.00	805.93	0.00	-0.14	0.00	45.00	150.30
5074.030	1820.00	805.92	0.00	-0.13	0.00	45.00	150.30
5128.030	1820.00	806.05	0.00	0.13	0.00	20.00	50.30
5129.030	1820.00	806.09	0.00	0.13	0.00	20.00	20.30
5171.030	1820.00	806.43	0.00	2.51	0.00	23.00	40.30
5173.030	1820.00	806.43	0.00	2.31	0.00	20.00	50.30
5228.030	1820.00	810.53	0.00	2.00	0.00	120.00	90.30
5228.030	1820.00	810.43	0.00	2.00	0.00	120.00	50.30
7155.030	1820.00	810.95	0.00	0.52	0.00	335.00	922.30
7150.000	1820.00	810.95	0.00	0.52	0.00	335.00	922.30
7300.000	1820.00	811.93	0.00	0.18	0.00	262.00	150.00
7300.000	1820.00	811.93	0.00	0.18	0.00	262.00	150.00
7326.000	1820.00	811.78	0.00	0.56	0.00	242.00	29.00
7326.000	1820.00	811.78	0.00	0.56	0.00	242.00	29.00
7516.000	1820.00	811.79	0.00	0.01	0.00	172.00	190.00
7516.000	1820.00	811.79	0.00	0.01	0.00	172.00	190.00

PRINTED IN U.S.A.
FORM 1411 OB-PRINTED BY ROTARY MANIFOLD FORMS.

SECNO	G	CWSEL	DIFWSP	DIFWSX	DIFKWS	TOPWID	XLCH
7868.000	1827.00	812.34	0.00	0.55	0.30	48.00	350.00
7868.000	1820.00	812.34	0.00	0.55	0.00	46.00	350.00
7921.000	1820.00	814.84	0.00	2.49	0.00	27.00	53.00
7921.000	1820.00	814.84	0.30	2.49	0.00	27.00	53.00
7965.000	1820.00	858.37	0.30	3.53	0.00	27.00	44.00
7965.000	1820.00	858.37	0.00	3.53	0.00	27.00	44.00
8178.000	1820.00	815.62	0.00	0.25	0.00	50.00	153.00
8178.000	1820.00	815.62	0.00	0.25	0.00	50.00	153.00
8518.000	1820.00	819.08	0.00	3.46	0.00	124.00	470.00
8518.000	1820.00	819.08	0.00	3.46	0.00	124.00	470.00
8535.000	1820.00	819.08	0.00	3.00	0.00	48.00	17.00
8535.000	1820.00	819.08	0.00	0.00	0.00	48.00	37.00
8556.000	1827.00	813.86	3.00	-0.22	0.00	48.00	1.00
8556.000	1820.00	813.86	3.00	-0.22	0.00	48.00	1.00
8811.000	1820.00	819.44	0.00	0.53	0.00	48.00	255.00
8811.000	1820.00	819.44	0.00	0.53	0.00	48.00	255.00
8812.000	1820.00	819.97	0.00	0.55	0.00	48.00	1.00
8812.000	1820.00	819.97	0.00	0.53	0.00	48.00	1.00
8918.000	1820.00	820.33	0.00	0.16	0.00	155.00	106.00
8918.000	1820.00	820.33	0.00	0.16	0.00	156.00	106.00
9453.000	1820.00	820.37	0.00	0.26	0.00	310.00	535.00
9453.000	1820.00	820.37	0.00	0.26	0.00	310.00	535.00
9510.000	1820.00	821.35	0.00	-0.16	0.00	93.00	165.00
9510.000	1820.00	820.25	0.00	-0.12	0.00	93.00	165.00
9973.000	1820.00	820.42	0.00	0.16	0.00	92.00	55.00
9973.000	1820.00	820.42	0.00	0.16	0.00	93.00	55.00
10039.000	1820.00	820.59	0.00	0.15	0.00	93.00	66.00
10039.000	1820.00	820.51	0.00	0.13	0.00	90.00	67.00
10084.000	1820.00	820.72	0.00	0.21	0.00	24.00	24.00
10095.000	1820.00	820.72	0.00	0.21	0.00	24.00	23.00
10095.000	1820.00	821.62	0.00	0.00	0.00	25.00	12.00
10094.000	1820.00	821.62	0.00	0.00	0.00	34.00	12.00
10133.000	1820.00	821.17	0.00	-0.45	0.00	22.00	5.00
10133.000	1820.00	821.17	0.00	-0.45	0.00	22.00	5.00
10134.000	1820.00	821.17	0.00	0.01	0.00	22.00	1.00
10134.000	1820.00	821.17	0.00	0.01	0.00	22.00	1.00
10173.000	1820.00	821.43	0.00	0.26	0.00	22.00	39.00
10173.000	1820.00	821.43	0.00	0.26	0.00	22.00	39.00

PRINTED IN U.S.A.

PRINTED BY ROTARY MANIFOLD FORMS,

SECNO	Q	CWSEL	DIFWSP	DIFWSX	DIFKWS	TOPWID	ALOB
10133.000	1620.30	822.44	0.00	0.00	0.00	22.00	1.00
10133.000	1620.30	822.44	0.00	0.00	0.00	22.00	1.00
10197.000	1620.30	822.17	0.00	0.74	0.00	32.00	24.00
10197.000	1620.30	822.17	0.00	0.74	0.00	32.00	24.00

SUMMARY OF ERRORS

NOTE SECNO= 2163.000 PROFILE= 1 WSEL BASED ON XS CARD
NOTE SECNO= 2163.000 PROFILE= 2 WSEL BASED ON XS CARD

CAUTION SECNO= 2963.000 PROFILE= 1 CRITICAL DEPTH ASSUMED
CAUTION SECNO= 2963.000 PROFILE= 1 PROBABLE MINIMUM SPECIFIC ENERGY
CAUTION SECNO= 2963.000 PROFILE= 1 20 TRIALS ATTEMPTED TO BALANCE WSEL
CAUTION SECNO= 2963.000 PROFILE= 2 CRITICAL DEPTH ASSUMED
CAUTION SECNO= 2963.000 PROFILE= 2 PROBABLE MINIMUM SPECIFIC ENERGY
CAUTION SECNO= 2963.000 PROFILE= 2 20 TRIALS ATTEMPTED TO BALANCE WSEL

CAUTION SECNO= 3063.000 PROFILE= 1 HYDRAULIC JUMP D.S.
CAUTION SECNO= 3063.000 PROFILE= 2 HYDRAULIC JUMP D.S.

CAUTION SECNO= 4023.000 PROFILE= 1 HYDRAULIC JUMP D.S.
CAUTION SECNO= 4023.000 PROFILE= 2 HYDRAULIC JUMP D.S.

CAUTION SECNO= 7658.000 PROFILE= 1 CRITICAL DEPTH ASSUMED
CAUTION SECNO= 7658.000 PROFILE= 1 MINIMUM SPECIFIC ENERGY
CAUTION SECNO= 7868.000 PROFILE= 2 CRITICAL DEPTH ASSUMED
CAUTION SECNO= 7868.000 PROFILE= 2 MINIMUM SPECIFIC ENERGY

PRINTED IN U.S.A.
FORM 1411-68-PRINTED BY ROTARY MANIFOLD FORMS.

FLOODWAY DATA, MID.ROUGE R. N.VILLE C.
PROFILE NO. 2


STATION	FLOODWAY WIDTH (FT)	FLOODWAY SECTION AREA	FLOODWAY MEAN VELOCITY	WATER SURFACE ELEVATION WITH FLOODWAY	WITHOUT FLOODWAY	DIFFERENCE
0.000	561.	3534.	1.1	768.2	768.1	0.1
700.000	437.	2249.	1.5	769.7	769.1	0.6
800.000	251.	1301.	2.9	768.7	768.2	0.5
978.000	85.	524.	7.0	768.7	768.6	0.1
1028.000	51.	426.	8.6	769.7	769.7	0.0
1078.000	50.	459.	8.4	769.9	769.8	0.1
1315.000	70.	752.	2.1	771.0	770.9	0.1
1765.000	71.	727.	6.0	771.7	771.6	0.1
2213.000	133.	1[illegible].	2.7	786.1	786.0	0.1
2513.000	60.	446.	4.3	780.3	780.2	0.1
2863.000	41.	191.	9.7	780.7	780.6	0.1
2963.000	21.	131.	14.2	782.3	782.3	0.0
3063.000	29.	182.	11.4	783.0	783.0	0.0
3213.000	65.	402.	4.1	784.8	784.8	0.0
3378.000	96.	495.	2.7	786.5	786.5	0.0
3527.000	59.	566.	3.3	785.5	786.5	0.0
3528.000	59.	571.	2.7	788.6	788.6	0.0
3672.000	46.	236.	7.8	788.7	788.7	0.0
3814.000	49.	408.	6.0	793.2	793.2	0.0
3925.000	32.	208.	6.4	790.6	790.6	0.0
3961.000	46.	355.	8.4	793.8	793.8	0.0
4023.000	96.	462.	4.0	794.9	794.9	0.0
4034.000	147.	657.	2.8	795.2	795.2	0.0
4473.000	128.	767.	5.0	795.7	795.7	0.0
4814.000	77.	399.	6.3	798.0	798.0	0.0
4907.000	34.	252.	7.9	798.8	798.8	0.0
4918.000	9.	41.	2.6	803.8	803.8	0.0
5508.000	242.	1192.	1.5	805.9	805.9	0.0
5984.000	150.	970.	1.9	806.1	806.1	0.0
6078.000	15.	265.	6.6	805.9	805.9	0.0
6128.000	20.	176.	12.5	806.0	806.0	0.0
6174.000	30.	99.	5.5	806.4	806.4	0.0
6224.000	141.	459.	1.5	811.6	811.6	0.0
7150.000	355.	1660.	1.2	812.9	812.9	0.0
7300.000	250.	1334.	1.6	811.1	811.1	0.0
7528.000	250.	1505.	1.2	811.0	811.0	0.0
7719.000	172.	972.	2.7	811.8	811.8	0.0
7867.000	93.	494.	5.3	812.5	812.5	0.0
8021.000	37.	251.	7.9	814.8	814.8	0.0
7965.000	27.	126.	5.3	818.4	818.4	0.0
8218.000	50.	317.	3.3	818.6	818.6	0.0
8511.000	124.	1051.	1.7	819.1	819.1	0.0
8555.000	48.	511.	3.3	816.2	816.1	0.0
8756.000	19.	254.	6.4	817.9	817.9	0.0
8871.000	19.	178.	8.4	819.6	819.6	0.0
8912.000	48.	510.	3.5	820.0	820.0	0.0
8970.000	153.	950.	1.9	820.3	820.	0.0
9455.000	519.	1877.	1.0	820.3	820.4	0.2
9516.000	99.	994.	2.3	820.3	820.0	0.3
9573.500	72.	737.	4.6	820.4	820.0	0.4

PRINTED IN U.S.A.
FORM 1411 OB-PRINTED BY ROTARY MANIFOLD FORMS.

FLOODWAY DATA, MID.ROUGE R. N.VILLE C.
PROFILE NO. 2

STATION	WIDTH (FT)	SECTION AREA	MEAN VELOCITY	WATER SURFACE ELEVATION FLOODWAY	WATER SURFACE ELEVATION FLOODWAY	INCREASE
10091.050	51.	293.	6.6	320.5	320.5	0.0
10094.000	34.	250.	6.8	320.7	320.7	0.0
10094.001	34.	294.	6.	321.6	321.6	0.0
10103.000	22.	102.	10.0	321.2	321.2	0.0
10104.000	22.	102.	10.0	321.2	321.2	0.0
10132.001	22.	106.	9.7	321.4	321.4	0.0
10133.000	22.	65.	9.7	321.4	321.4	0.0
10157.001	57.	299.	6.5	322.2	322.2	0.0

PRINTED IN U.S.A.
FORM 1411-GB-PRINTED BY ROTARY MANIFOLD FORMS.




1) COUNTY: Wayne

2) STUDY NAME: City of Northville

3) WATERCOURSE: Middle Branch Rouge River and Johnson Drain

4) DOCUMENT TYPE: Report



AMENDED HYDRAULICS REPORT
CITY OF NORTHVILLE, MICHIGAN

I. INTRODUCTION

The City of Northville is located in the northwest portion of Wayne County, as well as, entirely within the Rouge River Basin. The City contains slightly more than one square mile and has maintained its suburban nature over the years.

This report summarizes the amended hydraulic studies undertaken to support detailed studies of approximately 2 miles of the Middle Branch of the Rouge River and an approximate study of 1/2 mile of the Johnson Drain. Detailed studies on approximately 1.5 miles of the Randolph Drain was approved by the Michigan Department of Natural Resources on July 9, 1979.

This study was conducted by Wade, Trim & Associates, Inc., Consulting Engineers, and Glen Roberts served as Project Manager.

II. MIDDLE BRANCH OF ROUGE RIVER (DETAILED)

Detailed studies were performed of the entire Middle Branch of the Rouge River within the City of Northville. This study incorporated data and information developed for Flood Insurance Studies conducted for the City of Novi (Reference 1) and Northville Township (Reference 2). A total of fifteen (15) cross sections were provided by the Corps of Engineers (Reference 3). The cross sections included 5 road bridges, 1 railroad bridge, 2 dams, 2 ponds and 1 culvert. Sixteen (16) additional cross sections were field surveyed by Wade, Trim & Associates including 5 road crossings. Cross-section locations are shown in Exhibit 1 and were supplemented by U.S.G.S. Quad maps of the study area which consists of 10 foot contour intervals. (Reference 4 & 5.) Table 1 cross references section designations by showing the computer section number which corresponds to the cross section letter shown in Exhibit 1. Table 2 lists discharges that have been approved by the Michigan Department of Natural Resources (M.D.N.R.).

A. Method of Analysis

The HEC-2 backwater program was used in developing water surface profiles (Reference 6). Table 2 contains selected flood elevations from the HEC-2 printout. HEC-2 printouts including computer cross sections plots are presented as Exhibit 3. (Exhibit 3 is contained in the 11"x15" folder enclosed with this report.) Water surface profiles resulting from the backwater analyses are presented as Exhibit 4.

B. Variables and Coefficients

Roughness coefficients (Mannings "n") were estimated by field inspection at each cross section. Typical roughness values for the main channel for the Rouge River ranged from 0.020 to 0.040; roughness values for the overbank area varied between 0.08 to 0.12 for the several floods investigated. Contraction and expansion coefficients for abrupt transitions and bridges vary from 0.3 to 0.4 and 0.5 to 0.6, respectively, and normal channel transition coefficients are 0.1 and 0.3, respectively. Bridge loss calculations are presented in Exhibit 2. Variables and coefficients selected are indicative of summer month conditions and are consistent with values recommended and used in engineering practice.

C. High Water Marks

The 17 documented high water marks (Reference 8) for the June, 1968 flood in the City of Northville are presented in Table 3. The Corps of Engineers determined that the flow rate for the 1968 storm was 1,005 cfs (Reference 1) which is slightly lower than the 10 year flow rate of 1,040 cfs used in this study. Therefore, the 10 year storm was calibrated with the 1968 storm to insure the accuracy of the HEC-2 model. Most of the high water marks were matched with the following exceptions:

1. The Northville Downs culvert (Beal St./River St.) has been lengthened by approximately 150 feet since 1968; therefore, resulting flood elevations are higher than the high water marks.

why not clearify try to the data.

2. Some of the high water marks contradict themselves and are in poor or unknown condition.

D. Starting Conditions

The starting water surface elevations in all backwater computations were taken from the FIS report on the Middle Branch of the Rouge River in Northville Township. (Reference 2.)

E. Special Problems

The Northville Downs culvert which is 1,050 feet long was handled as a divided flow situation. Rating curves (Exhibit 5) were developed for low flow and pressure flow in the culvert and overland flow. Low flow and pressure flow curves were compared to determine the rating curve for the culvert. This rating curve was combined with the overland flow rating curve to determine flood elevations for the various flow rates. Elevations determined in this analysis were then input into the HEC-2 computer model.

F. General

Computed water surface elevations were developed to an accuracy of 0.5 feet for floods of the selected reoccurrence intervals.

All elevations are referenced to the U.S. Geological and Coastal Survey (USGCS) Datum. This datum is equivalent to the National Geodetic Vertical Datum of 1929 (NGVD).

The hydraulic analyses for this study were based only on the effects of flow unobstructed by ice or debris. The flood elevations are considered valid only if hydraulic structures, in general, remain unobstructed and do not fail.

TABLE 1
CITY OF NORTHVILLE, MICHIGAN
MIDDLE BRANCH OF THE ROUGE RIVER
CROSS REFERENCE INDEX

FLOODWAY MAP IDENTIFICATION	SECTION NUMBER HEC-2	CORPS C.S.#	DESCRIPTION
A	0+00	28	u/s Park Street Last C.S. in Northville Township FIS
B	10+28	31	d/s Face 7 Mile Road Bridge
C	10+78		u/s Face 7 Mile Road Bridge
D	11+13		d/s Face Northville Downs Culvert
E	21+63	35	u/s Face River St. Bridge
F	29+63	38	d/s Face Main St. Bridge
G	30+63		u/s Face Main St. Bridge
H	32+78	39	d/s Ford Dam
I	33+28	40	Ford Dam
J	36+72	41	d/s Face Truck Bridge
K	36+84		u/s Face Truck Bridge
L	39+65		d/s Face Griswald St. Bridge
M	40+28		u/s Face Griswald St. Bridge
N	48+58	43	d/s Mill Pond Dam
O	49+08	44	Mill Pond Dam
P	53+08	45	Mill Pond
Q	59+28		Mill Pond
R	61+28	46	d/s Face C.O. R.R. Bridge
S	61+78		u/s Face C.O. R.R. Bridge
		WTA FIELD BOOK STA.	
T	73+00	28+18	d/s Face Old Novi Rd. Bridge
U	73+28	27+90	u/s Face Old Novi Rd. Bridge

TABLE 1
CITY OF NORTHVILLE, MICHIGAN
MIDDLE BRANCH OF THE ROUGE RIVER
CROSS REFERENCE INDEX
(CONTINUED)

FLOODWAY MAP IDENTIFICATION	SECTION NUMBER HEC-2	CORPS C.S.#	DESCRIPTION
V	79+21	21+97	d/s Face C.O. R.R. Bridge #2
W	79+65	21+53	u/s Face C.O. R.R. Bridge #2
X	85+56	15+62	d/s Face 8 Mile Rd. Culvert
Y	88+11 220.17 EG	13+07	u/s Face 8 Mile Rd. Culvert
Z	94+53 220.40 EG	6+65	Valley Section
AA	99+73.5	1+44.5	d/s Face New Novi Rd. Bridge
AB	100+11	1+07	u/s Face New Novi Rd. Bridge
AC	100+84	0+34	d/s Face C.O. R.R. Bridge #3
AD	100+94	0+24	u/s Face C.O. R.R. Bridge #3
AE	101+04	0+14	d/s Face Old Novi Rd. Bridge
AF	101+32	0-14	u/s Face Old Novi Rd. Bridge

TABLE 2

CITY OF NORTHVILLE

MIDDLE BRANCH ROUGE RIVER FLOOD FLOW DATA

LOCATION		10 Yr.	50 Yr.	100 Yr.	500 Yr.
u/s Randolph Dr.		1040	1590	1820	2460
	Elev.	796.9	797.6	798.0	798.9
u/s Johnson Dr.		1040	1610	1850	2490
	Elev.	768.5	770.1	770.9	773.0
d/s Johnson Dr.		2270	3170	3680	5090
	Elev.	768.0	769.2	769.8	771.6

TABLE 3

CITY OF NORTHVILLE, MICHIGAN

MIDDLE BRANCH OF THE ROUGE RIVER

DOCUMENTED HIGH WATER MARKS - JUNE, 1968

LOCATION	DESCRIPTION		COMPUTER SEC. NO.	H.W.M. ELEV.	W.T.A. ELEV.	CONDITION OF H.W.M.
7 Mile Road Bridge	u/s, left bank		1078	768.64	768.02	Poor
7 Mile Road Area	u/s, left bank			767.15		Unknown
Beal St. Bridge	u/s, right bank			776.23		Good
(River St. Bridge)			2163		777.30	
Beal St. Bridge (River St. Bridge)	u/s, left bank			775.79		Unknown
Main St. Bridge	u/s, left bank	H	3063	782.09	781.30	Fair
Main St. Bridge	u/s, left bank		3113		782.87	
Griswald St. Bridge Area	u/s of Dam, right bank	I	3328	787.83	787.78	Excellent
Griswald St. Bridge Area	u/s of Dam, right bank			787.54		Unknown
Griswald St. Bridge Area	d/s side truck road bridge	J	3672	787.73	787.82	Fair
Griswald St. Bridge Area	u/s side truck road bridge	K	3684	788.11	788.14	Fair
Griswald St. Bridge Area	d/s of bridge right bank		3825	788.70	788.70	Unknown
Griswald St. Bridge Area	d/s, right bank	L	3965	791.32	789.76	Good
Griswald St. Bridge Area	u/s, right bank		4028	791.59	790.95	Good
Griswald St. Bridge Area	u/s, right bank		4078		792.05	
Northville Pond Area (Mill Pond)	u/s, of Dam	O	4908	804.50	804.31	Poor
Novi Road & Old 8 Mile Bridge	u/s, right bank		7328	809.37	809.40	Fair
Novi Road Bridge (E-W)	u/s, right bank		8812	814.43	814.95	Unknown
Novi Road Bridge Area	u/s, left bank		9453	816.67	816.18	Unknown
Novi Road Bridge (N-S)	d/s side, left bank		9973	817.79	817.74	Good

REFERENCES

1. Flood Insurance Study, City of Novi, Michigan, Flood Insurance Administration - March, 1977.

2. Flood Insurance Study, Northville Township, Michigan, Flood Insurance Administration - Currently Underway.

3. Corps of Engineers, U.S. Army, Flood Plain Information Middle Rouge River, Northville, Michigan, 1971.

4. U.S. Geological Survey Topographical Maps - Northville Quadrangle, Wayne - Oakland County, 7.5 Minute Series - Photo Revised 1973.

5. U.S. Geological Survey Topographical Maps - Salem Quadrangle, Wayne - Oakland County, 7.5 Minute Series - Photo Revised 1973.

6. HEC-2 - Water Surface Profile - Users Manual - U.S. Army Corps of Engineers - 1976.

7. Improvements to Randolph Street Drain, Johnson and Anderson, Inc., Pontiac, Michigan, 1975.

8. Post Flood Report of Southeast Michigan Flood 25-27, June, 1968, U.S. Army Engineer District, Detroit, Michigan, 1969.

CITY OF NORTHVILLE, MICHIGAN
Middle Branch Rouge River and
Randolph Drain

EXHIBIT 1

Field Cross-Section Location
and 100 Year Flood Plain -
Floodway Map

CITY OF NORTHVILLE, MICHIGAN

MIDDLE BRANCH ROUGE RIVER

EXHIBIT 2

Bridge Notes and Sketches

Wade Trim & Associates Inc.
Civil Engineers • Land Surveyors
FORM 25 0
(313) 291 5400
WORK SHEET
25185 GODDARD ROAD
TAYLOR, MICHIGAN 48180

Bridge Location: 7 MILE RD.
Bridge Losses - SB Crt

REFERENCE

1. XK (Pier Shape Coefficient) 1.025 — HEC-2 Manual

XKOR (Loss Coefficient) = 1.0 + Σk, $\Sigma k = k_f + k_e + k_p$

where k_f = friction loss coefficient
k_e = entrance loss coefficient
k_p = loss from intermediate piers

Description of Bridge:

$K_f = 29.1\, n^2 L / R^{4/3}$ for English units

Area = ____ $R^{4/3}$ = ____ Wp = ____ L = ____

$R = A/wp$

n (composite) =


$K_f = 29.1 \times (\quad)^2 \times \quad / \quad =$

K_c =

Hydraulic Charts for the Selection of Highway Culverts Circular No. 5 Dec. 1965 pg. 49

$K_p = 0$ if bridge has no intermediate piers

$K_p = 0.05$ if bridge has intermediate piers — HEC-2 manual



A_1 13.8(23) = 317.4

$9_{1/2}$(32) = 304.0


$1/2$ 2.6 (23) 30

691.5

2. XKOR = 1 + + + = 1.05
3. COFQ - Coefficient of discharge = 3.0 — HEC-2 manual
4. RDLEN = Length of weir = 0.0 (0 if read off BT cards)
5. BWC = bottom width of bridge opening (inc. piers) = 25.0
6. BWP = total width of obstruction = 2.0 — field data
7. BAREA = bridge opening inc. piers = 691.5
8. SS = side slope = 1.17 (horizontal per 1 vertical unit)
9. ELCHU = Elevation of channel invert U/s side = 757.4 (0 if equal to minimum elevation in previous x-sect.)
10. ELCHD = Elevation of channel invert D/s side = 757.4 (0 if equal to minimum elevation in previous x-sect.)

SUBJECT	BY	CHK	SHEET NO.	File Code No (Job No) Owner	Project	Suffix
NORTHVILLE CITY	DRB		___ OF ___	HUD	2006	07
	DATE 7/29	DATE				

7 MILE ROAD STA. 10+78



Bridge Location: RIVER ST.

Bridge Losses - SB Card

REFERENCE

1. XK (Pier Shape Coefficient) 1.25 — HEC-2 manual

XKOR (Loss Coefficient) = 1.0 + Σk, $\Sigma k = k_f + k_e + k_p$

where k_f = friction loss coefficient
k_e = entrance loss coefficient
k_p = loss from intermediate piers

Description of Bridge:

$K_f = 29.1\, n^2 L / R^{4/3}$ for English units

Area = 154 = _____ WP = _____

$R = A/wp$ $R^{4/3}$ = _____ $L = 42' + 1008'$

n (composite) =

K_f = 29.1 x ( )^2 x _____ / _____ =

K_e = .5 (Upstream Portion) (D/S Portion)

$K_f = \frac{29.1(.02)^2 42}{(154/42)^{4/3}} + \frac{29.1(.02)^2 1008}{(154/58)^{4/3}} = 3.37$

Hydraulic Charts for the Selection of Highway Culverts Circular No. 5 Dec. 1965 pg. 49


K_p = 0 if bridge has no intermediate piers

K_p = 0.05 if bridge has intermediate piers — HEC-2 manual

2. XKOR = 1 + 3.37 + .05 + .5 = 4.92
3. COFQ - Coefficient of discharge = 3.0 — HEC-2 manual
4. RDLEN = Length of weir = 0 (0 if read off BT cards)
5. BWC = bottom width of bridge opening (inc. piers) = 24
6. BWP = total width of obstruction = 2.0 — field data
7. BAREA = bridge opening ~~inc.~~ piers = 154
8. SS = side slope = 0
   (horizontal per 1 vertical unit)
9. ELCHU = Elevation of channel invert U/S side = 770.0
   (0 if equal to minimum elevation in previous x-sect.)
10. ELCHD = Elevation of channel invert D/S side = 757.9
    (0 if equal to minimum elevation in previous x-sect.)

SUBJECT	BY	CHK	SHEET NO	File Code No (Job No) Owner	Project	Suffix
River Street Rating Curve	W.J.W		___ OF ___	HUD	2006	07
	DATE 8/9/79	DATE				

RIVER ST. BRIDGE AND STA 21+63
NORTHVILLE DOWNS CULVERT



Bridge Location : MAIN ST. BRIDGE STA. 31+63
Bridge Losses - SB Card

REFERENCE

1. XK (Pier Shape Coefficient) 1.025 — HEC-2 manual

XKOR (Loss Coefficient) = 1.0 + Σk, $\Sigma k = k_f + k_e + k_p$

where k_f = friction loss coefficient
k_e = entrance loss coefficient
k_p = loss from intermediate piers

BRIDGE @ 45° SKEW

Description of Bridge :


$K_f = 29.1\, n^2 L / R^{4/3}$ for English units

Area = 30 x 9.5 (cos 45°) = 200.0 Wp = 80.4

$R = A/wp$ 200/80.4 $R^{4/3} = 3.37$ $L = 100$

n (composite) =

$K_f = 29.1 \times (0.02)^2 \times 100 / 3.37 = 0.35$



$K_e = 0.5$

Hydraulic Charts for the Selection of Highway Culverts Circular No. 5 Dec. 1965 pg. 4


$K_p = 0$ if bridge has no intermediate piers


$K_p = 0.05$ if bridge has intermediate piers — HEC-2 manual

2. XKOR = 1 + 0.35 + 0.5 + .05 = 1.90
3. COFQ = Coefficient of discharge = 3.0 — HEC-2 manual
4. RDLEN = Length of weir = 0. (0 if read off BT cards)
5. BWC = bottom width of bridge opening (inc. piers) = 22.4
6. BWP = total width of obstruction = 1.4 — field data
7. BAREA = bridge opening inc. piers = 200.
8. SS = side slope = 0.0
   (horizontal per 1 vertical unit)
9. ELCHU = Elevation of channel invert U/S side = 775.9
   (0 if equal to minimum elevation in previous X-sect.)
10. ELCHD = Elevation of channel invert D/S side = 775.9
    (0 if equal to minimum elevation in previous X-sect.)

SUBJECT	BY	CHK.	SHEET NO.	File Code No (Job No) Owner Project Suffix
NORTHVILLE CITY	DRB		___ OF ___	HOD • 2006 • 02
	DATE 2/79	DATE		

MAIN ST. BRIDGE STA 3+62





STA 33+28

Bridge Location : TRUCK BRIDGE

Bridge Losses - SB Crk

REFERENCE

1. XK (Pier Shape Coefficient) 0.00 — HEC-2 manual

XKOR (Loss Coefficient) = 1.0 + ΣK, $\Sigma K = k_f + k_e + k_p$

where k_f = friction loss coefficient
k_e = entrance loss coefficient
k_p loss from intermediate piers

Description of Bridge :

$K_f = 29.1\, n^2 L / R^{4/3}$ for English units

Area = $= \frac{195}{R^{4/3}}$ Wp = 100

R = A/wp 195/100 $R^{4/3} = 2.43$ L = 12'

n (composite) =


$K_f = 29.1 \times (0.02)^2 \times 12 / 2.43 = 0.06$

K_e =

Hydraulic Charts for the Selection of Highway Culverts Circular No. 5 Dec. 1965 pg. 49

K_p = 0 if bridge has no intermediate piers

K_p = 0.05 if bridge has intermediate piers — HEC-2 manual



2. XKOR = 1 + 0.06 + 0.5 + 0.0 = 1.56
3. COFQ - Coefficient of discharge = 3.0 — HEC-2 manual
4. RDLEN = Length of weir = 0.0 (0 if read off BT cards)
5. BWC = bottom width of bridge opening (inc. piers) = 20.0
6. BWP = total width of obstruction = 0.0 — field data
7. BAREA = bridge opening inc. piers = 195
8. SS = side slope = 1.5
   (horizontal per 1 vertical unit)
9. ELCHU = Elevation of channel invert U/S side = 781.1
   (0 if equal to minimum elevation in previous X-sect.)
10. ELCHD = Elevation of channel invert D/S side = 781.1
    (0 if equal to minimum elevation in previous X-sect.)

SUBJECT	BY	CHK	SHEET NO.	File Code No (Job No) Owner Project Suffix
TRUCK BRIDGE	DRR		___ OF ___	40D • 2006 • 07
	DATE 8/19	DATE		

Bridge Location: [illegible] FARMINGTON 30 [illegible]

Bridge Losses - SB Conf

REFERENCE

1. XK (Pier Shape Coefficient) 1.025 — HEC-2 Manual

XKOR (Loss Coefficient) = 1.0 + ΣK, $\Sigma k = k_f + k_e + k_p$

where k_f = friction loss coefficient
k_e = entrance loss coefficient
k_p = loss from intermediate piers

Description of Bridge:

$K_f = 29.1\, n^2 L / R^{4/3}$ for English units

Area = 116 Wp = 66

$R = A/wp$. $R^{4/3} = 2.12$ L =

n (composite) =

$K_f = 29.1 \times (0.02)^2 \times 63 \;/\; 2.12 = 0.034$

$K_e = 0.5$ — Hydraulic Charts for the Selection of Highway Culverts Circular No. 5 Dec. 1965 pg. 49


$K_p = 0$ if bridge has no intermediate piers

$K_p = 0.05$ if bridge has intermediate piers — HEC-2 manual


2. XKOR = 1 + 0.034 + 0.5 + 0.005 = 1.089
3. COFQ = Coefficient of discharge = 3.0 — HEC-2 manual
4. RDLEN = Length of weir = 0.0 (0 if read off BT cards)
5. BWC = bottom width of bridge opening (inc. piers) = 19.3
6. BWP = total width of obstruction = 10.42 — field data
7. BAREA = bridge opening inc. piers = 116.0
8. SS = side slope = 0.0 (horizontal per 1 vertical unit)
9. ELCHU = Elevation of channel invert U/S side = 784.6 (0 if equal to minimum elevation in previous x-sect.)
10. ELCHD = Elevation of channel invert D/S side = 784.6 (0 if equal to minimum elevation in previous x-sect.)

SUBJECT	BY	CHK	SHEET NO.	File Code No (Job No) Owner Project Suffix
Northville City	DRB		___ OF ___	HUD • 2006 • 07
	DATE 8-79	DATE		

GRISWOLD ST. BRIDGE
STA. 40+28



NORTHVILLE DAM STA. 49+08



Bridge Location : C.O. 2.82 B.R. #1
Bridge Losses - SB Conf

REFERENCE

1. XK (Pier Shape Coefficient) 0.0 — HEC-2 Manual

XKOR (Loss Coefficient) = 1.0 + Σk, $\Sigma k = k_f + k_e + k_p$

where k_f = friction loss coefficient
k_e = entrance loss coefficient
k_p = loss from intermediate piers

Description of Bridge:

$k_f = 29.1\, n^2 L / R^{4/3}$ for English units

Area = 150 Wp = 43

$R = A/wp$ $R^{4/3} = 4.57$ $L = 50$

n (composite) =

$k_f = 29.1 \times (0.02)^2 \times 50 \;/\; 4.57 = 0.13$

$k_e = 0.5$ — Hydraulic Charts for the Selection of Highway Culverts, Circular No. 5, Dec. 1965 pg. 43


$k_p = 0$ if bridge has no intermediate piers

$k_p = 0.05$ if bridge has intermediate piers — HEC-2 manual

2. XKOR = 1 + 0.13 + 0.5 + 0.0 = 1.63
3. COFQ = Coefficient of discharge = 3.0 — HEC-2 manual
4. RDLEN = Length of weir = 0.0 (0 if read off BT cards)
5. BWC = bottom width of bridge opening (inc. piers) = 150.3
6. BWP = total width of obstruction = 0.0 — field data
7. BAREA = bridge opening inc. piers = 1500
8. SS = side slope = 0.0
   (horizontal per 1 vertical unit)
9. ELCHU = Elevation of channel invert U/S side = 798.41
   (0 if equal to minimum elevation in previous X-sect.)
10. ELCHD = Elevation of channel invert D/S side = 798.41
    (0 if equal to minimum elevation in previous X-sect.)

SUBJECT	BY	CHK.	SHEET NO	File Code No (Job No.) Owner Project Suffix
NORTHVILLE CITY	DRB		___ OF ___	HUD • 2003 • 07
	DATE 8-29	DATE		

Co + O. RAILROAD BRIDGE STA. 61+78



Bridge Location : [illegible]
Bridge Losses - SB Conrail

REFERENCE

1. XK (Pier Shape Coefficient) [illegible] — HEC-2 manual

XKOR (Loss Coefficient) = 1.0 + Σk, $\Sigma k = k_f + k_e + k_p$

where k_f = friction loss coefficient
k_e = entrance loss coefficient
k_p = loss from intermediate piers

Description of Bridge :

$K_f = 29.1\, n^2 L / R^{4/3}$ for English units

Area = [illegible] = 11' WP = 5[illegible]
$R = A/wp$ $R^{4/3}$ = 2.30 L = 2.3
n (composite) =

K_f = 29.1 x (0.30)^2 x 2.8 / 2.30 = 3.13


K_c = 0.5 — Hydraulic Charts for the Selection of Highway Culverts Circular No. 5 Dec. 1965 pg. 45

~~K_p~~ = 0 if bridge has no intermediate piers

K_p = 0.05 if bridge has intermediate piers — HEC-2 manual

2. XKOR = 1 + 0.13 + 0.5 + 0.0 = 1.63
3. COFQ = Coefficient of discharge = 3.0 — HEC-2 manual
4. RDLEN = Length of weir = 0.0 (0 if read off BT cards)
5. BWC = bottom width of bridge opening (inc. piers) = 23.7
6. BWP = total width of obstruction = 0.0 — field data
7. BAREA = bridge opening inc. piers = [illegible]
8. SS = side slope = 0.0
   (horizontal per 1 vertical unit)
9. ELCHU = Elevation of channel invert U/S side = 802.1
   (0 if equal to minimum elevation in previous X-sect.)
10. ELCHD = Elevation of channel invert D/S side = 802.1
    (0 if equal to minimum elevation in previous x-sect.)

SUBJECT	BY	CHK	SHEET NO	File Code No (Job No) Owner • Project • Suffix
N. U. City	DRB		___ OF ___	407 • 2006 • 07
	DATE 8/29	DATE		


BRIDGE LENGTH 28'
TOP VIEW
CROSS SECTION B
N 48° E
STA 27+00
BRIDGE
CROSS SECTION B

Bridge Location : C.O.G. RR BRIDGE STA. 79+65

Bridge Losses - SB Card

REFERENCE

1. XK (Pier Shape Coefficient) 1.25 — HEC-2 Manual

XKOR (Loss Coefficient) = 1.0 + Σk, $\Sigma k = k_f + k_e + k_p$

where k_f = friction loss coefficient
k_e = entrance loss coefficient
k_p = loss from intermediate piers

Description of Bridge :

$K_f = 29.1 n^2 L / R^{4/3}$ for English units

Area = 145 Wp = 70

$R = A/wp$ 145/70 $R^{4/3} = 2.64$ $L = 44$


n (composite) =

$K_f = 29.1 \times (0.02)^2 \times 44 / 2.64 = 0.19$

K_e = WINGWALLS 30° TO 75° TO BARREL 0.4 — Hydraulic Charts for the Selection of Highway Culverts Circular No. 5 Dec. 1965 pg. 4

K_p = 0 if bridge has no intermediate piers

~~K_p~~ = 0.05 if bridge has intermediate piers — HEC-2 manual



2. XKOR = 1 + 0.19 + 0.4 + 0.005 = 1.64
3. COFQ = Coefficient of discharge = 3.0 — HEC-2 manual
4. RDLEN = Length of weir = 0. (0 if read off BT cards)
5. BWC = bottom width of bridge opening (inc. piers) = 27.0
6. BWP = total width of obstruction = 3.0 — field data
7. BAREA = bridge opening inc. piers = 145.
8. SS = side slope = 0.
   (horizontal per 1 vertical unit)
9. ELCHU = Elevation of channel invert U/S side = 806.
   (0 if equal to minimum elevation in previous X-sect.)
10. ELCHD = Elevation of channel invert D/S side = 806.
    (0 if equal to minimum elevation in previous X-sect.)


SUBJECT	BY	CHK	SHEET NO.	File Code No (Job No.) Owner • Project • Suffix
	DATE	DATE	___ OF ___	

HUD 2006-07

NORTHVILLE CITY E.I.S. (PATNALES DRAIN)

STA	+	=	ELEV.
	823.97		
A		5.57	818.30
B		5.56	818.31
C		5.52	818.35
D		12.12	811.75
E		12.10	811.77
F		16.6	807.27
G		17.9	805.97
H		10.38	813.49
I		13.23	810.64
J		10.43	813.44
K		13.93	809.94
L		10.53	813.54
M		11.45	812.42
N		10.46	813.41
O		11.34	812.53
P		12.06	811.81
R		4.6	819.27
S		18.2	805.67
T		18.1	805.77
U		5.5	818.37

FEB 7 '77 JR ANDS FEB 20, 1978 51



FEB 949 JR MN OS FEB 20, 1979 48

HDD 2006-07

NORTHVILLE CITY F. S. (PATHFINDER DRIVE)


STA	+	H.I.	−	ELEV	
BM				820.16	
	16.69	944.90			
400' R			12.69	832.11	
200' R			11.96	834.84	
100' R			11.00	837.78	
Ω			10.75	840.85	(CODE T)
100' L			10.75	843.85	
200' L			(+11.25)	846.05	
400' L			(+11.60)	846.40	
BM			24.49	820.21	
	1.72	820.05			
A			9.76	820.29	
B			12.24	817.81	
C			12.37	817.68	
D			12.30	817.75	
E			10.60	809.45	
F			21.20	808.85	
G			22.50	807.55	

REMOVE W/S DR FROM G SE CORNER PM & 1 MILE RD TURNPIKE

L & MILE RD BRIDGE (STA 15+76)

UPPER CODE T EXTREME SOUTHERLY HEADWALL FOR CULV. UNDER 8 MILE RD. (S/S)

HEADWALL S/S PIKE 10 STA 15+42 GR




NOTE: HEADWALL IS OF SAME TYPE AS THAT ON W/S OF 9 MILE RD WITH THE EXCEPTION OF THE PLUG SHOWN FOR BREAKERS.

FEB 19 1990

FB 949

h	5.44	821.36
b	.16	821.24
C	5.47	821.33
D	12.47	813.33
E	2.66	814.42
F	2.40	818.69
G	2.19	818.61
H	10.16	816.34
I	15.10	816.24
J	17.19	813.70
K	20.41	806.46
L	17.71	307.70
M	10.88	810.00
N	17.28	804.00
O	12.60	814.20



DETAIL OF 60" RCP HEADWALL N/S 8 MI RD & NOVI RD

ELEVATION TO EXTREME NE COR HEADWALL FOR PROPOSED CULVERT UNDER 8 MI RD BRIDGE @ NOVI RD.

Bridge Location : Novi RD S7-A99+92
Bridge Losses - SB Culv

REFERENCE

1. XK (Pier Shape Coefficient) 1.05 — HEC-2 manual

XKOR (Loss Coefficient) = 1.0 + ΣK , $\Sigma k = k_f + k_e + k_p$

where k_f = friction loss coefficient
k_e = entrance loss coefficient
k_p = loss from intermediate piers

Description of Bridge :

$K_f = 29.1\, n^2 L / R^{4/3}$ for English units

Area = 335 Wp = 14.5

$R = A/wp$ 335/14.5 $R^{4/3} = 3.0$ L = 37.5


n (composite) =

$K_f = 29.1 \times (0.02)^2 \times 37.5 / 3.0 = .14$

$K_e = 0.5$ — Hydraulic Charts for the Selection of Highway Culverts Circular No. 5 Dec. 1965 pg. 45

$K_p = 0$ if bridge has no intermediate piers

$K_p = 0.05$ if bridge has intermediate piers — HEC-2 manual




2. XKOR = 1 + 0.14 + 0.5 + 0.05 = 1.69
3. COFQ = Coefficient of discharge = 3.0 — HEC-2 manual
4. RDLEN = Length of weir = 0.0 (0 if read off BT cards)
5. BWC = bottom width of bridge opening (inc. piers) = 21.0
6. BWP = total width of obstruction = 20.0 — field data
7. BAREA = bridge opening inc. piers = 335.
8. SS = side slope = 1.23 (horizontal per 1 vertical unit)
9. ELCHU = Elevation of channel invert U/S side = 810.7 (0 if equal to minimum elevation in previous X-sect.)
10. ELCHD = Elevation of channel invert D/S side = 810.7 (0 if equal to minimum elevation in previous X-sect.)

SUBJECT	BY	CHK	SHEET NO.	File Code No (Job No) Owner Project Suffix
NORTHVILLE CITY	B.T.G DATE DRR	DATE	___ OF ___	HUD 2006 07

1100
2006-07

NORTHVILLE CITY F.I.S. (PATHALES DRAIN)

STA	+	HI.	−	ELEV.	
		830.81			
300' L			9.37	821.44	
200' L			8.95	821.86	
100' L			8.55	822.26	
0			7.97	822.84	N 30° E
100' R			7.77	823.04	
200' R			7.18	823.63	
300' R			6.77	824.04	
A			7.33	823.48	
B			10.74	820.07	
C			11.66	819.15	
D			17.9	812.91	
E			20.1	810.71	
F			17.3	813.51	
G			12.81	818.00	
H			10.64	820.17	
I			11.9	818.91	
J			18.5	812.31	
K			19.0	811.81	
L			18.9	811.91	
M			14.5	816.31	
N			1.56	823.25	
O			7.26	823.55	



Bridge Location: C.O. RR STA 100+77

Bridge Losses - SB Card

REFERENCE

1. XK (Pier Shape Coefficient) 0.0 — HEC-2 Manual

XKOR (Loss Coefficient) = 1.0 + Σk, $\Sigma k = k_f + k_e + k_p$

where k_f = friction loss coefficient
k_e = entrance loss coefficient
k_p = loss from intermediate piers

Description of Bridge:

$k_f = 29.1 n^2 L / R^{4/3}$ for English units

Area = 34 x 7.2 = 245 WP = 82.4

$R = A/wp$ 245/82.4 $R^{4/3} = 4.27$ $L = 10$

n (composite) =

$k_f = 29.1 \times (0.02)^2 \times 10. / 4.27 = 0.03$

$k_e = 0.7$ WINGWALLS PARALLEL — Hydraulic Charts for the Selection of Highway Culverts Circular No. 5 Dec. 1965 pg. 43

~~$k_p = 0$~~ if bridge has no intermediate piers

$k_p = 0.05$ if bridge has intermediate piers — HEC-2 manual


2. XKOR = 1 + 0.03 + 0.7 + 0.0 = 1.73
3. COFQ = Coefficient of discharge = 3.0 — HEC-2 manual
4. RDLEN = Length of weir = 0. (0 if read off BT cards)
5. BWC = bottom width of bridge opening (inc. piers): 34.0
6. BWP = total width of obstruction = 0. — field data
7. BAREA = bridge opening inc. piers = 245.
8. SS = side slope = 0.
   (horizontal per 1 vertical unit)
9. ELCHU = Elevation of channel invert U/S side = 812.90
   (0 if equal to minimum elevation in previous X-sect.)
10. ELCHD = Elevation of channel invert D/S side = 812.90
    (0 if equal to minimum elevation in previous X-sect.)

SUBJECT	BY	CHK.	SHEET NO.	File Code No (Job No.) Owner Project Suffix
NORTHVILLE CITY	DRB		___ OF ___	HUD • 2006 • 07
	DATE 2/24	DATE		

NASHVILLE CITY L. S. (NOAH'S GRAIN)

STA	HI (B.S. + R.P.)	R.P.	EL
[illegible]		5.42	825.37
[illegible]		5.06	825.79
[illegible]		4.78	825.93
[illegible]		4.10	826.11
[illegible]		[illegible]	[illegible]
[illegible]		3.73	827.65
[illegible]		2.94	827.57
A		10.7[illegible]	820.66
[illegible]		10.64	820.17
[illegible]		17.9	813.91
L		17.9	813.91
E		17.7	813.91
[illegible]		12.[illegible]	818.61
[illegible]		4.65	826.16
[illegible]		11.[illegible]	819.21
T		4.51	826.27
T		3.97	827.81
K		11.66	819.15
L		[illegible]	823.19
M		[illegible]	825.52
N		[illegible]	823.37
O		7.77	823.70

FS 749




FB 947

NASHVILLE CITY P.I.S. (PARTIAL ORIG.)

STA		H.I.	ELEV.
BM			826.45
0+00	COLD SPRING RD. BRIDGE CENTER LINE		
		6.10	823.91
		7.00	823.81
		6.60	824.51
		4.10	826.11
		4.10	826.55
A		4.44	826.33
B		7.44	823.16
C		7.71	823.10
D		13.15	813.31
E		12.[illegible]	814.61
F		13.[illegible]	813.11
G		10.[illegible]	820.51
H		7.[illegible]	818.1
I		15.1	815.41
J		13.1	812.71
K		15.2	815.01
L		4.[illegible]	826.21
M		4.[illegible]	826.20

N 2° E



CITY OF NORTHVILLE, MICHIGAN

MIDDLE BRANCH ROUGE RIVER

EXHIBIT 3

Computer Printouts

HEC-2 Backwater Analysis

with

Cross Section Plots

(See Separate Folder)

CITY OF NORTHVILLE, MICHIGAN

MIDDLE BRANCH ROUGE RIVER

EXHIBIT 5

Northville Downs Rating Curves

NORTHVILLE DOWNS / RIVER STREET CULVERT 10-YEAR RATING CURVE

KEY


++++ = Comb. Rating Curve for C.L. #1

x = Overland Flow

° = Pressure Flow

Δ = Low Flow

□ = Total Rating Curve (Not Needed for 10 yr. Flow)




HUD 2006 07

W.J. Weaver


8/9/79

46 1320
K&E 10 X 10 TO ½ INCH 7 X 10 INCHES
KEUFFEL & ESSER CO MADE IN U.S.A.




W.J. Weaver
8/9/79

K&E 10 X 10 TO 5 X 10 INCH 7 X 10 INCHES
KEUFFEL & ESSER CO MADE IN U.S.A.
46 1320



46 1320
K+E 10 X 10 TO ½ INCH 7 X 10 INCHES
KEUFFEL & ESSER CO MADE IN USA


NORTHVILLE DOWNS / RIVER ST. - 500 YR.
RATING CURVE
KEY
X = Overland Flow.
° = Pressure Flow.
Δ = Low Flow.
□ = Total Rating Curve.
HH = Final Combination Rating Curve.
Flow Distribution:
Overland Flow = 900 cfs
Culvert Flow = 1590 cfs
ELEVATION
794
793
792
791
790
789
788
787
786
785
784
783
782
781
780
779
500 YR Flood El. = 780.55
Overland Flow
Pressure Flow Control
Low Flow Control
Combination
Curve A
0
400
800
1200
1600
2000
2400
FLOW RATE (cfs)
500 YR. Flow = 2490 cfs
HUD2006.07
W.J. Weaver
8/9/79
46 1320
K&E 10 X 10 TO ½ INCH 7 X 10 INCHES
KEUFFEL & ESSER CO MADE IN U.S.A.

Wade Trim & Associates, Inc.
Civil Engineers • Land Surveyors
WORK SHEET
25185 GODDARD ROAD
TAYLOR, MICHIGAN 48180

Bridge Location: NORTHVILLE DOWNS CULVERT & RIVER ST. B.R.

REFERENCE

Bridge Losses - SB Card STA. 21+63

1. XK (Pier Shape Coefficient): 0.0 — HEC-2 manual

XKOR (Loss Coefficient) = $1.0 + \Sigma k$, $\Sigma k = k_f + k_e + k_p$

where k_f = friction loss coefficient
k_e = entrance loss coefficient
k_p = loss from intermediate piers

Description of Bridge:

$K_f = 29.1\, n^2 L / R^{4/3}$ for English units — NORTHVILLE DOWNS CULVERT / RIVER ST BRIDGE

Area = 22×7 = 154 Wp = 58

$R = A/wp$ 154/58 $R^{4/3} = 3.68$ $L = 1008 + 50 = 1058$

n (composite) = .013 (SIDES + TOP) 0.004 (BOTTOM) ⇒ 0.017

$K_f = 29.1 \times (0.017)^2 \times 1058 / 3.68 = 2.41$

$K_e = 0.5$ — Hydraulic Charts for the Selection of Highway Culverts Circular No. 5 Dec. 1965 pg. 49

$K_p = 0$ if bridge has no intermediate piers

$K_p = 0.05$ if bridge has ~~no~~ intermediate piers — HEC-2 manual

NOTE: NORTHVILLE DOWNS CULVERT HAS NO INTERMEDIATE PIERS, THE 0.05 IN XKOR IS FOR THE PEIR AT THE RIVER ST. BRIDGE.

2. XKOR = 1 + 2.41 + 0.5 + 0.05 = 3.97
3. COFQ = Coefficient of discharge = 3.0 — HEC-2 manual
4. RDLEN = Length of weir = 0. (0 if read off BT cards)
5. BWC = bottom width of bridge opening (inc. piers) = 22.
6. BWP = total width of obstruction = 0. — field data
7. BAREA = bridge opening inc. piers = 154.
8. SS = side slope = 0 (horizontal per 1 vertical unit)
9. ELCHU = Elevation of channel invert U/S side = 770.0 (0 if equal to minimum elevation in previous X-sect.)
10. ELCHD = Elevation of channel invert D/S side = 757.9 (0 if equal to minimum elevation in previous X-sect.)

SUBJECT	BY	CHK	SHEET NO.	File Code No (Job No.) Owner	Project	Suffix
NORTHVILLE CITY	DATE 1/13/89	DATE	___ OF ___	HUD	2006	07




1) COUNTY: Wayne

2) STUDY NAME: City of Northville

3) WATERCOURSE: Middle Rouge River and Johnson Drain

4) DOCUMENT TYPE: Summary



PRINTED IN U.S.A.

FORM 1411.6B PRINTED BY ROTARY MANIFOLD FORMS

```
**************************************************
 HEC2 RELEASE DATED NOV 76 UPDATED FEB 1977
 ERROR CORR -  01
 MODIFICATION -  50,51,52
**************************************************

 NOTE- ASTERISK (*) AT LEFT OF CROSS-SECTION NUMBER INDICATES MESSAGE IN SUMMARY OF ERRORS LIST

 OLD.ROUGE R. N.VILLE C.

 SUMMARY PRINTOUT TABLE  150
```

	SECNO	XLCH	ELTRD	ELLC	ELMIN	Q	CLSEL	CRIWS	EG	1.KAS	VCH	AREA	.LIK
	0.000	0.00	0.00	0.00	757.10	2270.00	765.88	0.00	765.97	4.24	3.44	2055.86	1102.03
	0.000	0.00	0.00	0.00	757.10	3170.00	767.25	0.00	767.33	3.47	3.46	2823.12	1702.60
	0.000	0.00	0.00	0.00	757.10	3680.00	768.17	0.00	768.14	3.05	3.42	3282.36	2115.19
	0.000	0.00	0.00	0.00	757.10	5090.00	770.20	0.00	770.44	2.15	3.31	4375.86	3471.47
	500.000	300.00	0.00	0.00	758.00	2270.00	765.97	0.00	766.19	9.56	4.80	1319.20	734.29
	300.000	300.00	0.00	0.00	758.00	3170.00	767.32	0.00	767.51	7.37	4.74	1900.16	1167.86
	300.000	300.00	0.00	0.00	758.00	3680.00	768.13	0.00	768.30	6.27	4.65	2247.64	1469.66
	300.000	300.00	0.00	0.00	758.00	5090.00	770.42	0.00	770.55	4.22	4.48	3230.67	2477.15
	600.000	300.00	0.00	0.00	758.90	2270.00	766.13	0.00	766.74	23.68	7.02	697.85	486.52
	600.000	300.00	0.00	0.00	758.90	3170.00	767.41	0.00	767.95	18.67	7.05	1056.26	753.64
	600.000	300.00	0.00	0.00	758.90	3680.00	768.19	0.00	768.68	15.81	6.93	1276.60	925.36
	600.000	300.00	0.00	0.00	758.90	5090.00	770.43	0.00	770.61	10.34	6.56	1901.25	1563.29
	978.000	378.00	0.00	0.00	760.10	2270.00	767.13	0.00	768.35	54.65	10.36	397.33	306.42
	978.000	378.00	0.00	0.00	760.10	3170.00	768.05	0.00	769.71	64.54	12.30	474.17	394.60
	978.000	378.00	0.00	0.00	760.10	3680.00	768.52	0.00	770.46	66.48	13.11	519.91	451.32
	978.000	378.00	0.00	0.00	760.10	5090.00	770.31	0.00	772.30	60.60	14.35	667.45	653.05
	1028.000	50.00	0.00	0.00	757.40	2270.00	765.74	0.00	768.51	10.93	5.59	343.66	866.57
	1028.000	50.00	0.00	0.00	757.40	3170.00	766.05	0.00	770.05	14.36	8.01	395.57	830. 9
	1028.000	50.00	0.00	0.00	757.40	3680.00	765.85	0.00	770.32	15.12	9.15	435.15	914.94
	1028.000	50.00	0.00	0.00	757.40	5090.00	771.31	0.00	772.80	18.77	9.96	510.87	1174.70
	1028.000	50.00	775.30	775.80	757.40	2270.00	768.02	0.00	768.48	10.65	6.53	347.96	695.64
	1028.000	50.00	775.30	775.80	757.40	3170.00	769.19	0.00	770.76	13.91	7.87	402.83	849.91
	1028.000	50.00	775.30	775.80	757.40	3680.00	769.69	0.00	770.94	15.30	8.49	433.93	940.06
	1028.000	50.00	775.30	775.80	757.40	5090.00	771.36	0.00	773.02	17.31	9.7	504.20	1216.93
	1113.000	35.00	0.00	0.00	757.90	1340.00	766.50	0.00	768.81	2.78	4.46	233.28	624.28
	1113.000	35.00	0.00	0.00	757.90	1610.00	770.11	0.00	770.33	2.25	4.71	692.50	1677.35
	1113.000	35.00	0.00	0.00	757.90	1850.00	770.49	0.00	771.45	2.57	5.06	747.71	1810.15
	1113.000	35.00	0.00	0.00	757.90	2490.00	772.59	0.00	773.30	2.60	5.04	893.06	1544.01
*	2163.000	1050.00	1000.00	1000.00	759.90	1040.00	777.30	0.00	777.84	23.05	5.92	175.79	252.23
*	2163.000	1050.00	1000.00	1000.00	759.90	1610.00	779.25	0.00	779.60	12.46	5.79	425.71	456.06
*	2163.000	1050.00	1000.00	1000.00	759.90	1850.00	779.85	0.00	780.11	14.41	6.38	450.22	487.37
*	2163.000	1050.00	1000.00	1000.00	759.90	2490.00	780.55	0.00	781.20	13.58	7.71	516.71	577.67

	SECNO	XLCH	ELTRD	ELLC	ELMIN	Q	CASEL	CRIDS	EG	10K*S	VCH	AREA	.01K
	2213.000	50.00	0.00	0.00	770.00	1040.00	777.79	0.00	778.01	8.89	3.84	359.88	348.79
1	2213.000	50.00	0.00	0.00	770.00	1610.00	779.55	0.00	779.78	8.78	4.37	606.02	543.35
2	2213.000	50.00	0.00	0.00	770.00	1850.00	779.96	0.00	780.24	9.42	4.66	673.60	602.64
3	2213.000	50.00	0.00	0.00	770.00	2490.00	781.16	0.00	781.48	10.04	5.20	860.22	765.79
4													
5	2513.000	300.00	0.00	0.00	771.75	1040.00	778.08	0.00	778.39	14.30	4.80	300.12	275.03
6	2513.000	300.00	0.00	0.00	771.75	1610.00	779.78	0.00	780.19	14.16	5.61	432.97	427.59
7	2513.000	300.00	0.00	0.00	771.75	1850.00	780.23	0.00	780.69	15.09	6.00	487.72	476.21
8	2513.000	300.00	0.00	0.00	771.75	2490.00	781.43	0.00	781.96	15.46	6.62	689.06	633.36
9													
10	2863.000	350.00	0.00	0.00	773.80	1040.00	778.64	778.55	780.16	150.17	9.92	107.69	64.87
11	2863.000	350.00	0.00	0.00	773.80	1610.00	780.20	0.00	781.83	95.95	10.29	168.59	164.37
12	2863.000	350.00	0.00	0.00	773.80	1850.00	780.64	0.00	782.43	94.70	10.82	186.81	190.10
13	2863.000	350.00	0.00	0.00	773.80	2490.00	781.67	0.00	783.89	92.65	12.07	235.26	258.71
14													
15	2963.000	100.00	0.00	0.00	775.90	1040.00	780.38	780.38	782.50	155.35	11.69	88.99	83.44
16	* 2963.000	100.00	0.00	0.00	775.90	1610.00	781.79	781.79	784.65	146.87	13.53	119.01	132.85
17	* 2963.000	100.00	0.00	0.00	775.90	1850.00	782.34	782.34	785.45	144.38	14.16	130.68	153.96
18	* 2963.000	100.00	0.00	0.00	775.90	2490.00	783.67	783.67	787.48	142.38	15.67	156.91	208.68
19													
20	* 3063.000	100.00	791.20	785.40	775.90	1040.00	781.30	0.00	782.72	82.06	9.58	108.56	114.61
21	* 3063.000	100.00	791.20	785.40	775.90	1610.00	782.13	0.00	784.98	75.24	10.93	147.30	185.61
22	* 3063.000	100.00	791.20	785.40	775.90	1850.00	783.83	0.00	785.95	73.65	11.41	162.17	215.28
23	* 3063.000	100.00	791.20	785.40	775.90	2490.00	786.05	0.00	788.25	81.95	11.90	209.30	316.35
24													
25	3113.000	50.00	0.00	0.00	776.00	1040.00	782.07	0.00	783.20	15.47	4.73	263.24	264.15
26	3113.000	50.00	0.00	0.00	776.00	1610.00	783.16	0.00	785.54	11.86	5.13	396.16	467.59
27	3113.000	50.00	0.00	0.00	776.00	1850.00	783.64	0.00	786.45	10.92	5.32	452.27	559.96
28	3113.000	50.00	0.00	0.00	776.00	2490.00	784.45	0.00	788.07	8.47	5.49	622.97	855.52
29													
30	3213.000	150.00	0.00	0.00	776.40	1040.00	783.30	0.00	783.39	4.13	2.48	438.87	511.94
31	3213.000	150.00	0.00	0.00	776.40	1610.00	785.01	0.00	785.72	3.03	2.81	621.02	859.19
32	3213.000	150.00	0.00	0.00	776.40	1850.00	785.49	0.00	786.62	3.52	2.92	694.05	986.54
33	3213.000	150.00	0.00	0.00	776.40	2490.00	786.61	0.00	788.03	3.01	3.13	891.13	1434.76
34													
35	3327.000	49.00	0.00	0.00	776.50	1040.00	783.31	0.00	783.42	5.43	2.72	392.96	446.40
36	3327.000	49.00	0.00	0.00	776.50	1610.00	785.61	0.00	785.76	5.26	3.12	515.96	702.26
37	3327.000	49.00	0.00	0.00	776.50	1850.00	786.20	0.00	786.36	5.21	3.23	562.91	811.70
38	3327.000	49.00	0.00	0.00	776.50	2490.00	787.36	0.00	789.17	4.96	3.39	704.59	1124.46
39													
40	3527.000	1.00	796.30	0.00	776.50	1040.00	787.78	0.00	787.92	1.13	1.62	643.70	976.37
41	3527.000	1.00	796.30	0.00	776.50	1610.00	788.39	0.00	788.48	2.32	2.37	879.58	1057.64
42	3527.000	1.00	796.30	0.00	776.50	1850.00	788.59	0.00	788.70	2.91	2.68	991.22	1084.37
43	3527.000	1.00	796.30	0.00	776.50	2490.00	789.37	0.00	789.54	4.36	3.38	737.65	1192.65
44													
45	3672.000	345.00	0.00	0.00	781.90	1040.00	787.85	0.00	788.24	41.85	5.21	199.46	160.79
46	3672.000	344.00	0.00	0.00	781.90	1610.00	788.48	0.00	789.26	70.70	7.10	226.81	191.67
47	3672.000	344.00	0.00	0.00	781.90	1850.00	788.70	0.00	789.65	83.39	7.82	236.45	202.58
48	3672.000	344.00	0.00	0.00	781.90	2490.00	789.56	0.00	790.83	100.31	9.05	275.07	248.62
49													
50	3864.000	12.00	790.50	787.70	781.90	1040.00	788.11	0.00	788.51	35.19	4.64	217.50	175.38
51	3864.000	12.00	790.50	787.70	781.90	1610.00	789.11	0.00	790.12	40.71	5.98	277.62	251.78
52	3864.000	12.00	790.50	787.70	781.90	1850.00	790.27	0.00	790.77	41.30	6.04	308.39	287.38
53	3864.000	12.00	790.50	787.70	781.90	2490.00	790.82	0.00	791.67	56.72	7.50	336.31	330.62
54													
55													
56													
57													

PRINTED IN U.S.A.
FORM 1411-GS-PRINTED BY ROTARY MANIFOLD FORMS.

		SECNO	XLCH	ELTRD	ELLC	ELMIN	Q	CWSEL	CRIWS	EG	10K*S	VCH	AREA	.01K
		3825.000	141.00	0.00	0.00	782.80	1040.00	788.70	0.00	789.42	57.73	7.26	188.26	136.88
1		3825.000	141.00	0.00	0.00	782.80	1690.00	790.20	0.00	791.19	59.41	8.81	259.25	208.66
2		3825.000	141.00	0.00	0.00	782.80	1850.00	790.80	0.00	791.67	58.91	9.09	289.43	241.04
3		3825.000	141.00	0.00	0.00	782.80	2490.00	791.60	0.00	793.12	74.60	10.65	382.37	288.14
5		3965.000	140.00	0.00	0.00	784.60	1040.00	789.76	0.00	791.54	164.90	10.71	97.08	80.99
6		3965.000	140.00	0.00	0.00	784.60	1610.00	791.20	0.00	792.86	115.15	11.08	196.41	150.04
7		3965.000	140.00	0.00	0.00	784.60	1850.00	791.70	0.00	793.35	112.36	11.53	220.36	174.52
8		3965.000	140.00	0.00	0.00	784.60	2490.00	792.77	0.00	795.10	125.12	13.35	265.73	222.91
10	*	4028.000	63.00	794.50	791.10	784.60	1040.00	790.95	0.00	792.12	84.46	8.66	120.14	113.17
11	*	4028.000	63.00	794.50	791.10	784.60	1610.00	794.66	0.00	795.11	20.16	5.17	441.59	358.59
12	*	4028.000	63.00	794.50	791.10	784.60	1850.00	794.88	0.00	795.42	24.16	6.65	462.18	376.37
13	*	4028.000	63.00	794.50	791.10	784.60	2490.00	795.09	0.00	796.01	39.98	9.94	482.38	393.78
		4078.000	50.00	0.00	0.00	784.30	1040.00	792.05	0.00	792.50	18.72	3.94	203.24	240.36
16		4078.000	50.00	0.00	0.00	784.30	1610.00	794.68	0.00	795.21	10.35	5.51	616.08	500.36
17		4078.000	50.00	0.00	0.00	784.30	1850.00	795.17	0.00	795.55	11.97	6.04	656.79	534.83
18		4078.000	50.00	0.00	0.00	784.30	2490.00	795.66	0.00	796.24	17.28	7.48	731.30	598.98
20		4478.000	400.00	0.00	0.00	788.10	1040.00	793.14	792.82	794.44	108.87	10.25	153.09	99.71
21		4478.000	400.00	0.00	0.00	788.10	1610.00	795.32	0.00	796.29	48.30	9.05	324.78	231.67
22		4478.000	400.00	0.00	0.00	788.10	1850.00	795.68	0.00	796.73	50.70	9.60	366.78	259.81
23		4478.000	400.00	0.00	0.00	788.10	2490.00	796.42	0.00	797.71	57.40	10.94	476.78	328.67
25		4858.000	380.00	0.00	0.00	792.00	1040.00	796.90	0.00	797.39	44.76	5.68	196.61	146.94
26		4858.000	380.00	0.00	0.00	792.00	1590.00	797.63	0.00	798.38	57.42	7.05	246.52	209.82
27		4858.000	380.00	0.00	0.00	792.00	1820.00	798.03	0.00	798.84	58.19	7.30	275.00	247.24
28		4858.000	380.00	0.00	0.00	792.00	2460.00	798.94	0.00	799.93	82.21	8.12	341.56	340.48
30		4907.000	49.00	0.00	0.00	794.00	1040.00	797.13	0.00	797.73	71.24	6.26	166.07	123.22
31		4907.000	49.00	0.00	0.00	794.00	1590.00	797.85	0.00	798.75	80.56	7.59	229.66	177.12
32		4907.000	49.00	0.00	0.00	794.00	1820.00	798.24	0.00	799.22	76.30	7.83	258.33	206.01
33		4907.000	49.00	0.00	0.00	794.00	2460.00	799.15	0.00	800.32	75.04	8.63	336.25	283.99
35		4908.000	1.00	801.00	0.00	794.00	1040.00	804.31	0.00	804.36	1.36	1.74	599.31	892.78
36		4908.000	1.00	801.00	0.00	794.00	1590.00	805.38	0.00	805.47	2.20	2.39	665.49	1053.19
37		4908.000	1.00	801.00	0.00	794.00	1820.00	805.79	0.00	805.90	2.63	2.63	699.07	1114.26
38		4908.000	1.00	801.00	0.00	794.00	2460.00	806.79	0.00	806.96	3.70	3.57	759.12	1278.61
40		5308.000	400.00	0.00	0.00	800.00	1040.00	804.60	0.00	804.45	2.02	1.33	797.29	737.40
41		5308.000	400.00	0.00	0.00	800.00	1590.00	805.52	0.00	805.55	1.74	1.48	1032.52	1206.93
42		5308.000	400.00	0.00	0.00	800.00	1820.00	805.94	0.00	805.97	1.67	1.54	1191.63	1409.30
43		5308.000	400.00	0.00	0.00	800.00	2460.00	807.02	0.00	807.03	1.95	1.89	1479.05	1939.24
45		5928.000	620.00	0.00	0.00	800.00	1040.00	804.52	0.00	804.36	2.01	1.44	722.30	732.10
46		5928.000	620.00	0.00	0.00	800.00	1590.00	805.64	0.00	805.69	2.24	1.72	902.85	1062.72
47		5928.000	620.00	0.00	0.00	800.00	1820.00	806.05	0.00	806.11	2.31	1.88	970.00	1197.61
48		5928.000	620.00	0.00	0.00	800.00	2460.00	807.13	0.00	807.20	2.46	2.16	1140.63	1568.65
50		6078.000	150.00	0.00	0.00	798.20	1040.00	804.10	0.00	803.84	30.84	7.27	202.01	167.96
51		6078.000	150.00	0.00	0.00	798.20	1590.00	805.15	0.00	805.57	43.01	9.15	250.24	236.76
52		6078.000	150.00	0.00	0.00	798.20	1820.00	805.62	0.00	807.19	51.71	9.93	267.32	253.10
53		6078.000	150.00	0.00	0.00	798.20	2460.00	806.92	0.00	808.53	59.27	11.45	312.93	319.68

PRINTED IN U.S.A.
FORM 1411-GD-PRINTED BY ROTARY MANIFOLD FORMS.

SECNO	XLCH	ELTRD	ELLC	ELMIN	Q	CUBEL	CRIWS	EG	10K*S	VCH	AREA	.01K
6128.000	50.00	0.00	0.00	798.40	1040.00	806.62	0.00	805.80	65.54	8.72	119.30	128.46
6128.000	50.00	0.00	0.00	798.40	1590.00	805.57	0.00	807.67	94.70	11.55	140.04	165.39
6128.000	50.00	0.00	0.00	798.40	1820.00	806.05	0.00	808.39	105.24	12.29	148.03	177.42
6128.000	50.00	0.00	0.00	798.40	2460.00	807.00	0.00	810.37	135.13	14.74	166.88	211.62
6178.000	50.00	813.70	808.20	798.40	1040.00	805.20	0.00	806.23	72.09	8.15	127.61	122.49
6178.000	50.00	813.70	808.20	798.40	1590.00	806.46	0.00	808.31	134.26	10.93	145.44	137.22
6178.000	50.00	813.70	808.20	798.40	1820.00	806.43	0.00	809.77	46.75	9.31	195.43	266.19
6178.000	50.00	813.70	808.20	798.40	2460.00	812.53	0.00	813.75	31.79	8.86	277.38	436.29
6228.000	50.00	0.00	0.00	797.90	1040.00	806.70	0.00	806.82	6.09	3.74	508.05	421.45
6228.000	50.00	0.00	0.00	797.90	1590.00	809.28	0.00	809.41	4.47	3.84	801.13	751.65
6228.000	50.00	0.00	0.00	797.90	1820.00	810.43	0.00	810.55	3.82	3.80	938.77	930.60
6228.000	50.00	0.00	0.00	797.90	2460.00	814.28	0.00	814.45	2.25	3.48	1410.76	1658.56
7150.000	922.00	0.00	0.00	801.70	1040.00	807.03	0.00	808.21	34.57	6.84	292.69	176.59
7150.000	922.00	0.00	0.00	801.70	1590.00	809.90	0.00	810.02	8.20	6.16	1212.64	555.26
7150.000	922.00	0.00	0.00	801.70	1820.00	810.95	0.00	811.04	5.55	3.72	1560.25	772.48
7150.000	922.00	0.00	0.00	801.70	2460.00	814.65	0.00	814.69	1.87	2.72	2801.28	1797.09
7300.000	150.00	0.00	0.00	802.10	1040.00	808.17	0.00	809.15	49.94	7.95	130.80	147.14
7300.000	150.00	0.00	0.00	802.10	1590.00	810.15	0.00	810.30	9.31	4.34	1030.92	521.05
7300.000	150.00	0.00	0.00	802.10	1820.00	811.13	0.00	811.25	6.73	4.02	1334.15	698.73
7300.000	150.00	0.00	0.00	802.10	2460.00	814.71	0.00	814.77	2.61	3.15	2264.31	1522.59
7520.000	29.00	810.10	806.90	802.10	1040.00	809.40	0.00	810.05	26.17	6.29	160.19	203.30
7520.000	29.00	810.10	806.90	802.10	1590.00	811.28	0.00	811.37	4.75	3.41	1374.94	729.39
7520.000	29.00	810.10	806.90	802.10	1820.00	811.78	0.00	811.87	4.80	3.55	1504.63	830.30
7520.000	29.00	810.10	806.90	802.10	2460.00	814.35	0.00	814.41	2.49	3.16	2300.94	1560.01
7570.000	193.00	0.00	0.00	802.70	1040.00	810.26	0.00	810.53	14.65	4.69	429.97	271.75
7570.000	193.00	0.00	0.00	802.70	1590.00	811.50	0.00	811.67	17.87	5.70	507.62	378.14
7570.000	193.00	0.00	0.00	802.70	1820.00	811.99	0.00	812.18	7.57	5.09	672.75	434.13
7570.000	193.00	0.00	0.00	802.70	2460.00	814.87	0.00	815.00	7.76	4.02	1197.46	885.04
7860.000	350.00	0.00	0.00	803.70	1040.00	810.59	810.48	812.43	115.98	11.29	124.73	96.57
7860.000	350.00	0.00	0.00	803.70	1590.00	811.78	811.78	814.31	121.67	13.42	168.59	144.15
7860.000	350.00	0.00	0.00	803.70	1820.00	812.27	812.37	815.02	120.36	13.87	193.52	169.09
7860.000	350.00	0.00	0.00	803.70	2460.00	812.81	0.00	816.64	50.46	13.03	288.21	274.24
7921.000	53.00	0.00	0.00	804.00	1040.00	812.46	0.00	813.07	27.21	6.25	166.52	199.38
7921.000	53.00	0.00	0.00	804.00	1590.00	814.24	0.00	815.09	28.39	7.41	234.52	298.42
7921.000	53.00	0.00	0.00	804.00	1820.00	814.84	0.00	815.80	29.62	7.86	230.83	334.44
7921.000	53.00	0.00	0.00	804.00	2460.00	816.19	0.00	817.50	34.44	9.20	307.25	619.16
7965.000	44.00	819.20	811.70	805.00	1040.00	813.39	0.00	813.77	18.00	5.49	139.36	265.15
7965.000	44.00	819.20	811.70	805.00	1590.00	816.89	0.00	817.30	17.94	5.60	284.15	460.77
7965.000	44.00	819.20	811.70	805.00	1820.00	818.37	0.00	818.35	10.34	5.58	326.13	563.99
7965.000	44.00	819.20	811.70	805.00	2460.00	815.78	0.00	819.61	17.07	7.29	337.43	595.36
8119.000	153.00	0.00	0.00	805.60	1040.00	813.61	0.00	814.03	15.17	5.55	261.30	267.05
8119.000	153.00	0.00	0.00	805.60	1590.00	817.08	0.00	817.47	7.95	5.83	442.05	363.95
8119.000	153.00	0.00	0.00	805.60	1820.00	818.72	0.00	819.00	8.59	5.31	517.07	726.23
8119.000	153.00	0.00	0.00	805.60	2460.00	819.23	0.00	819.29	5.06	6.81	570.50	785.79

PRINTED IN U.S.A.
FORM 1411-GB-PRINTED BY ROTARY MANIFOLD FORMS

	SECNO	XLOW	ELTRD	ELLC	ELMIN	Q	CWSEL	CRWS	EG	TOK*S	VCH	AREA	.01K
	8518.000	400.00	0.00	0.00	807.70	1040.00	814.31	0.00	814.61	15.18	5.14	451.36	266.90
	8518.000	400.00	0.00	0.00	807.70	1590.00	817.58	0.00	817.77	6.14	4.38	856.53	641.50
	8518.000	400.00	0.00	0.00	807.70	1820.00	819.05	0.00	819.25	4.58	4.17	1042.50	853.56
	8518.000	400.00	0.00	0.00	807.70	2460.00	819.98	0.00	820.23	6.17	5.13	1154.18	990.63
	8555.000	37.00	0.00	0.00	805.70	1040.00	814.43	0.00	814.68	8.68	3.59	289.39	353.04
	8555.000	37.00	0.00	0.00	805.70	1590.00	817.60	0.00	817.80	5.76	3.62	439.48	662.62
	8555.000	37.00	0.00	0.00	805.70	1820.00	819.09	0.00	819.28	4.84	3.56	511.04	827.21
	8555.000	37.00	0.00	0.00	805.70	2460.00	819.98	0.00	820.28	7.01	4.45	553.43	928.93
	8556.000	1.00	840.00	817.70	805.70	1040.00	814.38	0.00	814.77	10.87	5.00	208.10	315.43
	8556.000	1.00	840.00	817.70	805.70	1590.00	817.45	0.00	817.95	14.56	5.65	281.40	416.65
	8556.000	1.00	840.00	817.70	805.70	1820.00	818.86	0.00	819.50	21.72	6.43	283.05	390.53
	8556.000	1.00	840.00	817.70	805.70	2460.00	820.54	0.00	820.72	40.33	8.69	283.05	387.39
	8811.000	255.00	812.60	818.60	807.50	1040.00	814.56	0.00	815.10	13.02	5.37	193.72	288.26
	8811.000	255.00	812.60	818.60	807.50	1590.00	817.79	0.00	818.29	12.20	5.66	282.10	455.28
	8811.000	255.00	812.60	818.60	807.50	1820.00	819.44	0.00	820.04	19.64	6.23	292.31	410.68
	8811.000	255.00	812.60	818.60	807.50	2460.00	820.62	0.00	821.72	36.77	8.41	292.61	405.70
	8812.000	1.00	0.00	0.00	807.50	1040.00	814.95	0.00	815.17	12.83	3.75	277.60	290.39
	8812.000	1.00	0.00	0.00	807.50	1590.00	818.14	0.00	818.37	7.92	3.69	451.39	565.05
	8812.000	1.00	0.00	0.00	807.50	1820.00	819.97	0.00	820.17	6.04	3.51	518.50	740.52
	8812.000	1.00	0.00	0.00	807.50	2460.00	821.71	0.00	821.97	7.16	4.08	602.21	919.50
	8918.000	106.00	0.00	0.00	808.40	1040.00	815.09	0.00	815.42	26.16	6.68	349.86	203.35
	8918.000	106.00	0.00	0.00	808.40	1590.00	818.30	0.00	818.47	9.32	5.19	660.01	520.85
	8918.000	106.00	0.00	0.00	808.40	1820.00	820.13	0.00	820.25	5.36	4.41	957.92	765.97
	8918.000	106.00	0.00	0.00	808.40	2460.00	821.96	0.00	822.08	4.86	4.63	1245.28	1116.12
	9418.000	465.00	0.00	0.00	810.50	1040.00	816.77	0.00	817.93	67.35	9.15	148.70	126.54
	9418.000	465.00	0.00	0.00	810.50	1590.00	818.60	0.00	819.67	46.38	9.24	272.20	233.40
	9418.000	465.00	0.00	0.00	810.50	1820.00	820.25	0.00	820.92	24.77	7.18	401.06	370.60
	9418.000	465.00	0.00	0.00	810.50	2460.00	822.02	0.00	822.39	20.07	7.02	539.12	549.09
	9473.000	55.50	0.00	0.00	810.70	1040.00	817.74	0.00	818.42	96.79	6.61	157.24	140.56
	9473.000	55.50	0.00	0.00	810.70	1590.00	819.20	0.00	820.01	91.73	7.25	219.26	221.07
	9473.000	55.50	0.00	0.00	810.70	1820.00	820.42	0.00	821.08	55.71	6.54	278.19	307.16
	9473.000	55.50	0.00	0.00	810.70	2460.00	822.15	0.00	822.84	24.50	6.73	365.74	476.93
	10311.000	37.50	823.50	821.20	810.70	1040.00	817.87	0.00	818.54	49.89	6.59	142.38	147.24
	10311.000	37.50	823.50	821.20	810.70	1590.00	819.35	0.00	820.12	47.41	7.02	226.43	230.03
	10311.000	37.50	823.50	821.20	810.70	1820.00	820.51	0.00	821.16	33.26	6.43	283.20	315.38
	10311.000	37.50	823.50	821.20	810.70	2460.00	822.94	0.00	823.52	18.69	6.03	407.80	569.04
	10384.000	73.00	0.00	0.00	812.90	1040.00	816.37	0.00	816.65	34.18	5.60	165.84	177.93
	10384.000	73.00	0.00	0.00	812.90	1590.00	819.72	0.00	820.45	41.44	6.37	235.41	247.06
	10384.000	73.00	0.00	0.00	812.90	1820.00	820.79	0.00	821.45	25.49	6.04	303.96	305.40
	10384.000	73.00	0.00	0.00	812.90	2460.00	823.09	0.00	823.81	29.28	7.15	345.65	454.84

PRINTED IN U.S.A.

FORM 1411-GB PRINTED BY ROTARY MANIFOLD FORMS.

SECNO	XLCH	ELTRD	ELLC	ELMIN	Q	CWSEL	CRIVS	EG	10K*S	VCH	AREA	.01K
10094.000	10.00	826.10	820.10	812.90	1040.00	818.41	0.00	818.89	53.38	5.55	187.30	180.00
10094.000	10.00	826.10	820.10	812.90	1590.00	820.22	0.00	820.85	55.31	6.39	248.95	275.51
10094.000	10.00	826.10	820.10	812.90	1820.00	821.62	0.00	822.20	25.28	6.14	296.62	361.99
10094.000	10.00	826.10	820.10	812.90	2460.00	825.18	0.00	825.72	14.10	5.39	417.67	611.55
10103.000	9.00	0.00	0.00	812.60	1040.00	818.04	0.00	819.35	74.43	9.19	113.12	120.55
10103.000	9.00	0.00	0.00	812.60	1590.00	819.70	0.00	821.45	71.49	10.62	149.77	188.05
10103.000	9.00	0.00	0.00	812.60	1820.00	821.17	0.00	822.72	51.26	10.00	181.96	254.20
10103.000	9.00	0.00	0.00	812.60	2460.00	824.79	0.00	826.46	31.72	9.41	281.49	436.89
10104.000	1.00	826.10	823.10	812.60	1040.00	818.04	0.00	819.36	74.49	9.20	113.09	120.55
10104.000	1.00	826.10	823.10	812.60	1590.00	819.71	0.00	821.46	71.61	10.62	149.69	187.89
10104.000	1.00	826.10	823.10	812.60	1820.00	821.17	0.00	822.73	51.26	10.00	181.96	254.20
10104.000	1.00	826.10	823.10	812.60	2460.00	824.81	0.00	826.55	102.25	10.57	232.70	243.28
10132.000	28.00	826.10	823.10	812.60	1040.00	818.40	0.00	819.62	56.71	8.44	123.17	130.10
10132.000	28.00	826.10	823.10	812.60	1590.00	820.17	0.00	821.70	57.96	9.93	160.20	208.85
10132.000	28.00	826.10	823.10	812.60	1820.00	821.43	0.00	822.89	46.64	9.70	187.68	266.50
10132.000	28.00	826.10	823.10	812.60	2460.00	824.93	0.00	826.64	100.37	10.49	234.65	245.55
10133.000	1.00	0.00	0.00	812.60	1040.00	818.50	0.00	819.80	56.73	8.44	123.16	138.07
10133.000	1.00	0.00	0.00	812.60	1590.00	820.18	0.00	821.71	57.96	9.93	160.18	208.81
10133.000	1.00	0.00	0.00	812.60	1820.00	821.44	0.00	822.90	46.57	9.69	187.77	266.71
10133.000	1.00	0.00	0.00	812.60	2460.00	825.59	0.00	826.79	26.21	8.81	279.34	480.52
10157.000	24.00	0.00	0.00	812.75	1040.00	819.09	0.00	819.82	37.56	7.78	179.34	169.69
10157.000	24.00	0.00	0.00	812.75	1590.00	821.01	0.00	821.90	34.29	8.89	241.53	271.52
10157.000	24.00	0.00	0.00	812.75	1820.00	822.17	0.00	823.13	23.38	8.83	270.92	341.64
10157.000	24.00	0.00	0.00	812.75	2460.00	826.13	0.00	826.95	15.54	8.25	405.44	624.10

PRINTED IN U.S.A.
FORM 1411-09-PRINTED BY ROTARY MANIFOLD FORMS

MID.ROUGE R. N.VILLE C.

SUMMARY PRINTOUT TABLE 150

SECNO	Q	CRSEL	DIFWSP	DIFUSX	DIFKWS	TOPWID	XLCH
0.000	2270.00	765.88	0.00	0.00	0.00	560.00	0.00
0.000	3170.00	767.25	0.00	0.00	0.00	560.00	0.00
0.000	3680.00	768.07	0.00	0.00	0.00	560.00	0.00
0.000	5090.00	770.38	0.00	0.00	0.00	560.00	0.00
300.000	2270.00	765.97	0.00	0.09	0.00	430.00	300.00
300.000	3170.00	767.32	0.00	0.07	0.00	430.00	300.00
300.000	3680.00	768.13	0.00	0.06	0.00	430.00	300.00
300.000	5090.00	770.42	0.00	0.04	0.00	430.00	300.00
600.000	2270.00	766.33	0.00	0.10	0.00	280.00	300.00
600.000	3170.00	767.41	0.00	0.09	0.00	280.00	300.00
600.000	3680.00	768.19	0.00	0.06	0.00	280.00	300.00
600.000	5090.00	770.45	0.00	0.01	0.00	280.00	300.00
978.000	2270.00	767.13	0.00	1.00	0.00	85.00	378.00
978.000	3170.00	768.04	0.00	0.62	0.00	85.00	378.00
978.000	3680.00	768.58	0.00	0.38	0.00	85.00	378.00
978.000	5090.00	770.31	0.00	-0.12	0.00	85.00	378.00
1028.000	2270.00	767.94	0.00	0.81	0.00	45.15	50.00
1028.000	3170.00	769.05	0.00	1.02	0.00	47.94	50.00
1028.000	3680.00	769.65	0.00	1.30	0.00	49.47	50.00
1028.000	5090.00	771.31	0.00	1.01	0.00	53.69	50.00
1078.000	2270.00	768.92	0.00	0.08	0.00	45.33	50.00
1078.000	3170.00	769.19	0.00	0.14	0.00	47.91	50.00
1078.000	3680.00	769.43	0.00	0.17	0.00	48.91	50.00
1078.000	5090.00	771.36	0.00	0.27	0.00	54.31	50.00
1113.000	1040.00	768.90	0.00	0.48	0.00	22.00	35.00
1113.000	1610.00	770.11	0.00	0.92	0.00	70.00	35.00
1113.000	1850.00	770.09	0.00	1.07	0.00	75.00	35.00
1113.000	2490.00	772.25	0.00	1.39	0.00	90.00	35.00
* 2163.000	1040.00	777.30	0.00	8.80	0.00	24.00	1055.00
* 2163.000	1610.00	779.25	0.00	9.44	0.00	70.00	1050.00
* 2163.000	1850.00	779.60	0.00	8.71	0.00	75.00	1050.00
* 2163.000	2490.00	780.35	0.00	7.60	0.00	75.00	1050.00
2213.000	1040.00	777.79	0.00	0.48	0.00	101.16	50.00
2213.000	1610.00	779.53	0.00	0.28	0.00	153.24	50.00
2213.000	1850.00	779.96	0.00	0.36	0.00	156.78	50.00
2213.000	2490.00	781.16	0.00	0.61	0.00	170.00	50.00
2513.000	1040.00	778.08	0.00	0.20	0.00	64.00	300.00
2513.000	1610.00	779.70	0.00	0.29	0.00	110.00	300.00
2513.000	1850.00	780.23	0.00	0.26	0.00	134.34	300.00
2513.000	2490.00	781.43	0.00	0.27	0.00	204.32	300.00
2863.000	1040.00	778.66	0.00	0.56	0.00	36.29	350.00
2863.000	1610.00	780.20	0.00	0.43	0.00	61.31	350.00
2863.000	1850.00	780.96	0.00	0.41	0.00	62.75	350.00
2863.000	2490.00	781.97	0.00	0.26	0.00	46.44	350.00

PRINTED IN U.S.A.
FORM 1611-OD PRINTED BY ROTARY MANIFOLD FORMS.

	SECNO	Q	CUSEL	DIFWSP	DIFWSX	DIFKWS	TOPWID	XLCH
*	2963.000	1040.00	780.38	0.00	1.74	0.00	21.21	100.00
*	2963.000	1610.00	781.79	0.00	1.59	0.00	21.21	100.00
*	2963.000	1850.00	782.34	0.00	1.71	0.00	21.21	100.00
*	2965.000	2490.00	783.67	0.00	2.09	0.00	21.21	100.00
*	3063.000	1040.00	781.30	0.00	0.92	0.00	21.21	100.00
*	3063.000	1610.00	783.13	0.00	1.33	0.00	21.21	100.00
*	3063.000	1850.00	783.63	0.00	1.46	0.00	21.21	100.00
*	3063.000	2490.00	786.05	0.00	2.39	0.00	21.21	100.00
	3113.000	1040.00	782.87	0.00	1.57	0.00	54.34	50.00
	3113.000	1610.00	785.16	0.00	2.03	0.00	61.96	50.00
	3113.000	1850.00	786.04	0.00	2.22	0.00	64.91	50.00
	3113.000	2490.00	788.45	0.00	2.41	0.00	32.35	50.00
	3276.000	1040.00	783.30	0.00	0.62	0.00	72.70	165.00
	3278.000	1610.00	785.60	0.00	0.44	0.00	82.76	165.00
	3278.000	1850.00	786.49	0.00	0.45	0.00	83.00	165.00
	3278.000	2490.00	788.80	0.00	0.43	0.00	83.00	165.00
	3327.000	1040.00	787.31	0.00	0.21	0.00	57.47	49.00
	3327.000	1610.00	793.61	0.00	0.31	0.00	58.50	49.00
	3327.000	1850.00	786.50	0.00	0.00	0.00	58.63	49.00
	3327.000	2490.00	788.88	0.00	-0.00	0.00	59.41	49.00
	3328.000	1040.00	787.78	0.00	4.67	0.00	56.05	1.00
	3328.000	1610.00	788.39	0.00	2.76	0.00	59.28	1.00
	3328.000	1850.00	788.59	0.00	2.09	0.00	59.33	1.00
	3329.000	2490.00	789.37	0.00	0.49	0.00	59.55	1.00
	3672.000	1040.00	787.82	0.00	0.04	0.00	40.44	346.00
	3672.000	1610.00	788.48	0.00	0.09	0.00	42.72	346.00
	3672.000	1850.00	788.70	0.00	0.12	0.00	43.57	346.00
	3672.000	2490.00	789.36	0.00	0.15	0.00	45.84	346.00
	3684.000	1040.00	788.14	0.00	0.35	0.00	61.58	12.00
	3684.000	1610.00	789.41	0.00	1.13	0.00	46.83	12.00
	3684.000	1850.00	790.21	0.00	1.51	0.00	45.64	12.00
	3684.000	2490.00	792.02	0.00	1.26	0.00	59.01	12.00
	3825.000	1040.00	788.70	0.00	0.56	0.00	43.67	141.00
	3825.000	1610.00	790.20	0.00	0.60	0.00	49.50	141.00
	3825.000	1850.00	790.80	0.00	0.59	0.00	52.11	141.00
	3825.000	2490.00	791.60	0.00	0.78	0.00	55.74	141.00
	3965.000	1040.00	789.76	0.00	1.06	0.00	16.25	140.00
	3965.000	1610.00	791.20	0.00	0.99	0.00	41.57	140.00
	3965.000	1850.00	791.76	0.00	0.97	0.00	43.53	140.00
	3965.000	2490.00	792.77	0.00	1.17	0.00	47.02	140.00
*	4024.000	1040.00	790.95	0.00	1.20	0.00	93.20	63.00
*	4024.000	1610.00	794.68	0.00	1.47	0.00	98.64	63.00
*	4024.000	1850.00	794.08	0.00	2.12	0.00	93.06	63.00
	4028.000	2490.00	795.09	0.00	2.33	0.00	98.01	61.00

PRINTED IN U.S.A.
FORM 1411-62-PRINTED BY ROTARY MANIFOLD FORMS

SECNO	Q	CWSEL	DIFWSP	DIFWSX	DIFKWS	TOPWID	XLOB
4078.000	1040.00	792.05	0.00	1.10	0.00	63.65	50.00
4078.000	1610.00	794.88	0.00	0.22	0.30	163.87	50.00
4078.000	1850.00	795.17	0.00	0.29	0.00	147.47	50.00
4078.000	2490.00	795.66	0.00	0.57	0.30	154.36	50.00
4478.000	1040.00	793.04	0.00	0.98	0.00	56.79	400.00
4478.000	1610.00	795.32	0.00	0.44	0.00	109.62	400.00
4478.000	1850.00	795.60	0.00	0.31	0.00	127.99	400.00
4478.000	2490.00	796.42	0.00	0.77	0.00	163.43	400.00
4858.000	1040.00	796.90	0.00	3.86	0.00	66.67	380.00
4858.000	1590.00	797.63	0.00	2.31	0.00	69.87	380.00
4858.000	1820.00	798.05	0.00	2.36	0.00	71.52	380.00
4858.000	2460.00	798.96	0.00	2.52	0.00	75.23	380.00
4907.000	1040.00	797.12	0.00	0.22	0.00	56.25	49.00
4907.000	1590.00	797.89	0.00	0.26	0.76	57.77	49.00
4907.000	1820.00	798.27	0.00	0.24	1.15	58.56	49.30
4907.000	2460.00	799.15	0.00	0.22	2.03	60.66	49.30
4908.000	1040.00	804.31	0.00	7.19	0.00	62.50	1.00
4908.000	1590.00	805.38	0.00	7.48	2.07	62.50	1.00
4908.000	1820.00	805.78	0.00	7.53	1.46	62.00	1.00
4908.000	2460.00	806.79	0.00	7.64	2.48	62.00	1.00
5318.000	1040.00	804.40	0.00	0.09	0.30	231.32	400.00
5318.000	1590.00	805.52	0.00	0.14	1.12	239.21	400.00
5320.000	1820.00	805.94	0.00	0.16	1.54	242.25	400.00
5320.000	2460.00	807.02	0.00	0.22	2.52	270.10	400.00
5928.000	1040.00	804.82	0.00	0.12	0.30	160.00	620.00
5928.000	1590.00	805.84	0.00	0.12	1.11	160.30	620.30
5928.000	1820.00	806.05	0.00	0.12	1.54	160.30	620.30
5928.000	2460.00	807.12	0.00	0.12	2.52	160.30	620.30
6078.000	1040.00	804.68	0.00	-0.05	0.00	45.00	150.00
6078.000	1590.00	805.53	0.00	-0.11	1.35	45.00	150.00
6078.000	1820.00	805.92	0.00	-0.13	1.45	45.00	150.00
6078.000	2460.00	806.92	0.00	-0.21	2.43	45.00	150.00
6128.000	1040.00	806.62	0.00	0.14	0.00	20.00	50.00
6128.000	1590.00	805.67	0.00	0.16	1.35	20.00	50.00
6128.000	1820.00	806.05	0.00	0.13	1.43	20.00	50.00
6128.000	2460.00	807.00	0.00	0.00	2.38	20.00	50.00
6278.000	1040.00	806.20	0.00	0.30	0.00	20.00	50.00
6278.000	1590.00	806.46	0.00	0.79	1.26	20.00	50.00
6278.000	1820.00	808.43	0.00	2.30	3.25	20.00	50.00
6278.000	2460.00	810.53	0.00	5.34	7.33	20.00	50.00
6228.000	1040.00	806.70	0.00	1.30	0.00	102.03	50.00
6228.000	1590.00	809.23	0.00	2.32	2.58	120.00	50.00
6228.000	1820.00	810.43	0.00	2.00	3.72	120.00	50.00
6228.000	2460.00	814.36	0.00	1.22	7.58	120.00	50.00

PRINTED IN U.S.A.
FORM 1411.69-PRINTED BY ROTARY MANIFOLD FORMS

	SECNO	Q	CWSEL	DIFUSP	DIFUSX	DIFUUS	TOPWID	XLCH
	7150.000	1040.00	807.63	0.00	0.93	0.00	98.00	922.00
	7150.000	1590.00	809.90	0.00	0.62	2.24	329.01	922.00
	7150.000	1820.00	810.95	0.00	0.52	3.31	333.00	922.00
	7150.000	2460.00	814.65	0.00	0.29	7.01	339.00	922.00
	7300.000	1040.00	808.17	0.00	0.54	0.00	23.70	150.00
	7300.000	1590.00	810.15	0.00	0.26	1.98	260.00	150.00
	7300.000	1820.00	811.15	0.00	0.18	2.96	260.00	150.00
	7300.000	2460.00	814.71	0.00	0.06	6.54	260.00	150.00
	7328.000	1040.00	809.40	0.00	1.23	0.00	23.70	28.00
	7328.000	1590.00	811.28	0.00	1.13	1.88	260.00	28.00
	7328.000	1820.00	811.78	0.00	0.66	2.38	260.00	28.00
	7328.000	2460.00	814.85	0.00	0.14	5.44	260.00	28.00
	7518.000	1040.00	812.24	0.00	0.86	0.00	131.70	190.00
	7518.000	1590.00	813.30	0.00	0.01	1.06	172.00	190.00
	7518.000	1820.00	811.79	0.00	0.01	1.53	172.00	190.00
	7518.000	2460.00	814.84	0.00	-0.00	4.58	172.00	190.00
	7868.000	1040.00	810.53	0.00	0.43	0.00	38.01	350.00
	7868.000	1590.00	811.70	0.00	0.46	1.19	38.04	350.00
*	7868.000	1820.00	812.34	0.00	0.35	1.75	46.00	350.00
	7868.000	2460.00	814.31	0.00	-0.54	3.71	46.00	350.00
	7921.000	1040.00	812.46	0.00	1.06	0.00	27.00	53.00
	7921.000	1590.00	814.24	0.00	2.46	1.78	27.00	53.00
	7921.000	1820.00	814.84	0.00	2.49	2.35	27.00	53.00
	7921.000	2460.00	816.19	0.00	1.83	5.73	27.00	53.00
	7963.000	1040.00	813.30	0.00	0.84	0.00	27.00	44.00
	7963.000	1590.00	816.31	0.00	4.53	3.51	47.00	44.00
	7963.000	1820.00	816.37	0.00	3.57	3.87	27.00	44.00
	7963.000	2460.00	816.75	0.00	2.50	5.59	27.00	44.00
	8118.000	1040.00	813.40	0.00	0.93	0.00	50.00	153.00
	8118.000	1590.00	817.08	0.00	3.27	3.67	50.00	153.00
	8118.000	1820.00	815.62	0.00	0.25	5.02	50.00	153.00
	8118.000	2460.00	819.23	0.00	1.45	5.62	50.00	153.00
	8518.000	1040.00	814.31	0.00	0.71	0.00	124.00	400.00
	8518.000	1590.00	817.58	0.00	0.50	3.27	124.00	400.00
	8518.000	1820.00	819.08	0.00	0.46	4.77	124.00	400.00
	8518.000	2460.00	819.98	0.00	0.23	5.67	124.00	400.00
	8555.000	1040.00	814.40	0.00	0.83	0.00	48.00	37.00
	8555.000	1590.00	817.60	0.00	0.61	3.12	48.00	37.00
	8555.000	1820.00	819.08	0.00	0.06	4.61	48.00	37.00
	8555.000	2460.00	819.98	0.00	-0.01	5.55	48.00	37.00
	8596.000	1040.00	814.23	0.00	-0.09	0.00	48.00	1.00
	8596.000	1590.00	817.45	0.00	-0.15	3.07	48.00	1.00
	8596.000	1820.00	818.92	0.00	-0.22	4.48	48.00	1.00
	8596.000	2460.00	819.54	0.00	-0.43	5.10	48.00	1.00

FORM 1411-GB-PRINTED BY ROTARY MANIFOLD FORM.
PRINTED IN U.S.A.

	SECNO	Q	CWSEL	DIFWSP	DIFWSX	DIFKWS	TOPWID	XLCH
	8811.000	1040.00	814.66	0.00	0.27	0.00	48.00	255.00
1	8811.000	1590.00	817.79	0.00	0.34	3.14	48.00	255.00
2	8811.000	1820.00	819.44	0.00	0.56	4.78	48.00	255.00
3	8811.000	2460.00	820.62	0.00	1.06	5.97	48.00	255.00
4								
5	8812.000	1040.00	814.95	0.00	0.30	0.00	48.00	1.00
6	8812.000	1590.00	818.16	0.00	0.37	3.21	48.00	1.00
7	8812.000	1820.00	819.97	0.00	0.53	5.02	48.00	1.00
8	8812.000	2460.00	821.71	0.00	1.09	6.74	48.00	1.00
9								
10	8918.000	1040.00	815.09	0.00	0.13	0.00	96.40	106.00
11	8918.000	1590.00	818.30	0.00	0.14	3.22	129.45	106.00
12	8918.000	1820.00	820.13	0.00	0.16	5.05	158.00	106.00
13	8918.000	2460.00	821.96	0.00	0.24	6.87	158.00	106.00
14								
15	9453.000	1040.00	815.18	0.00	0.10	0.00	236.20	535.00
16	9453.000	1590.00	818.71	0.00	0.41	2.53	310.00	535.00
17	9453.000	1820.00	820.37	0.00	0.24	4.19	310.00	535.00
18	9453.000	2460.00	822.18	0.00	0.22	6.00	310.00	535.00
19								
20	9918.000	1040.00	816.77	0.00	0.19	0.00	53.36	465.00
21	9918.000	1590.00	818.80	0.00	-0.11	1.83	78.00	465.00
22	9918.000	1820.00	820.25	0.00	-0.12	3.49	78.00	465.00
23	9918.000	2460.00	822.02	0.00	-0.16	5.26	78.00	465.00
24								
25	9973.500	1040.00	817.74	0.00	0.07	0.00	39.61	55.50
26	9973.500	1590.00	819.20	0.00	0.60	1.46	45.64	55.50
27	9973.500	1820.00	820.62	0.00	0.16	2.88	50.43	55.50
28	9973.500	2460.00	822.13	0.00	0.11	4.40	51.00	55.50
29								
30	10011.000	1040.00	817.87	0.00	0.14	0.00	43.00	37.50
31	10011.000	1590.00	819.35	0.00	0.15	1.48	46.25	37.50
32	10011.000	1820.00	820.51	0.00	0.10	2.64	50.63	37.50
33	10011.000	2460.00	822.96	0.00	0.02	5.09	51.00	37.50
34								
35	10084.000	1040.00	816.87	0.00	0.09	0.00	34.00	73.00
36	10084.000	1590.00	819.72	0.00	0.37	1.35	34.00	73.00
37	10084.000	1820.00	820.72	0.00	0.21	2.36	54.05	73.00
38	10084.000	2460.00	822.01	0.00	0.05	4.65	54.00	73.00
39								
40	10094.000	1040.00	816.41	0.00	0.04	0.00	34.00	10.00
41	10094.000	1590.00	820.22	0.00	0.50	1.81	34.00	10.00
42	10094.000	1820.00	821.62	0.00	0.90	3.21	34.00	10.00
43	10094.000	2460.00	823.16	0.00	2.17	4.77	34.00	10.00
44								
45	10103.000	1040.00	816.06	0.00	-0.37	0.00	22.00	9.00
46	10103.000	1590.00	819.70	0.00	-0.52	1.66	22.00	9.00
47	10103.000	1820.00	821.17	0.00	-0.45	3.13	22.00	9.00
48	10103.000	2460.00	824.79	0.00	-0.60	6.75	22.00	9.00
49								
50	10104.000	1040.00	816.03	0.00	0.01	0.00	22.00	1.00
51	10104.000	1590.00	819.71	0.00	0.01	1.66	22.00	1.00
52	10104.000	1820.00	821.17	0.00	0.01	3.13	22.00	1.00
53	10104.000	2460.00	824.61	0.00	-0.18	6.57	22.00	1.00
54								
55								
56								
57								

PRINTED IN U.S.A.
FORM 1411.08-PRINTED BY ROTARY MANIFOLD FORMS.

SECNO	Q	CHSEL	DIFXSP	DIFWSX	DIFKWS	TOPWID	XLCH
10132.000	1040.00	818.49	0.00	0.45	0.00	22.00	28.00
10132.000	1590.00	820.17	0.00	0.47	1.68	22.00	26.00
10132.000	1820.00	821.43	0.00	0.26	2.94	22.00	26.00
10132.000	2460.00	824.93	0.00	0.32	6.44	22.00	28.00
10133.000	1040.00	818.50	0.00	0.01	0.00	22.00	1.00
10133.000	1590.00	820.19	0.00	0.01	1.69	22.00	1.00
10133.000	1820.00	821.44	0.00	0.01	2.94	22.00	1.00
10133.000	2460.00	825.59	0.00	0.66	7.09	22.00	1.00
10157.000	1040.00	819.06	0.00	0.56	0.30	32.00	24.00
10157.000	1590.00	821.01	0.00	0.83	1.94	32.00	24.00
10157.000	1820.00	822.17	0.00	0.76	3.11	32.00	24.00
10157.000	2460.00	826.13	0.00	0.34	7.06	32.00	24.00

SUMMARY OF ERRORS

NOTE SECNO= 2163.000 PROFILE= 1 USEL BASED ON X5 CARD
NOTE SECNO= 2163.000 PROFILE= 2 USEL BASED ON X5 CARD
NOTE SECNO= 2163.000 PROFILE= 3 USEL BASED ON X5 CARD
NOTE SECNO= 2163.000 PROFILE= 4 USEL BASED ON X5 CARD

CAUTION SECNO= 2963.000 PROFILE= 1 CRITICAL DEPTH ASSUMED
CAUTION SECNO= 2963.000 PROFILE= 1 MINIMUM SPECIFIC ENERGY
CAUTION SECNO= 2963.000 PROFILE= 2 CRITICAL DEPTH ASSUMED
CAUTION SECNO= 2963.000 PROFILE= 2 PROBABLE MINIMUM SPECIFIC ENERGY
CAUTION SECNO= 2963.000 PROFILE= 2 20 TRIALS ATTEMPTED TO BALANCE WSEL
CAUTION SECNO= 2963.000 PROFILE= 3 CRITICAL DEPTH ASSUMED
CAUTION SECNO= 2963.000 PROFILE= 3 PROBABLE MINIMUM SPECIFIC ENERGY
CAUTION SECNO= 2963.000 PROFILE= 3 20 TRIALS ATTEMPTED TO BALANCE WSEL
CAUTION SECNO= 2963.000 PROFILE= 4 CRITICAL DEPTH ASSUMED
CAUTION SECNO= 2963.000 PROFILE= 4 PROBABLE MINIMUM SPECIFIC ENERGY
CAUTION SECNO= 2963.000 PROFILE= 4 20 TRIALS ATTEMPTED TO BALANCE WSEL

CAUTION SECNO= 3063.000 PROFILE= 1 HYDRAULIC JUMP D.S.
CAUTION SECNO= 3063.000 PROFILE= 2 HYDRAULIC JUMP D.S.
CAUTION SECNO= 3063.000 PROFILE= 3 HYDRAULIC JUMP D.S.
CAUTION SECNO= 3063.000 PROFILE= 4 HYDRAULIC JUMP D.S.

CAUTION SECNO= 4028.000 PROFILE= 1 HYDRAULIC JUMP D.S.
CAUTION SECNO= 4028.000 PROFILE= 2 HYDRAULIC JUMP D.S.
CAUTION SECNO= 4028.000 PROFILE= 3 HYDRAULIC JUMP D.S.
CAUTION SECNO= 4028.000 PROFILE= 4 HYDRAULIC JUMP D.S.

CAUTION SECNO= 7868.000 PROFILE= 2 CRITICAL DEPTH ASSUMED
CAUTION SECNO= 7868.000 PROFILE= 2 MINIMUM SPECIFIC ENERGY
CAUTION SECNO= 7868.000 PROFILE= 3 CRITICAL DEPTH ASSUMED
CAUTION SECNO= 7868.000 PROFILE= 3 MINIMUM SPECIFIC ENERGY

PRINTED IN U.S.A.
FORM 141-08 PRINTED BY ROTARY MANIFOLD FORMS.

FLOOD INSURANCE ZONE DATA FOR MID.ROUGE R. N.VILLE C.

FLOOD HAZARD FACTOR FOR ENTIRE REACH USING SECTIONS

SECTION NUMBER	CUMULATIVE DISTANCE	ELEVATION DIFFERENCE BETWEEN BASE FLOOD AND@ 10@	2@	0.2%
0.000	0.	-2.2	-0.5	2.3
300.000	300.	-2.2	-0.8	2.3
600.000	600.	-2.1	-0.8	2.2
978.000	978.	-1.4	-0.5	1.7
1028.000	1028.	-1.7	-0.6	1.7
1078.000	1078.	-1.8	-0.6	1.7
1113.000	1113.	-2.6	-0.9	2.1
2163.000	2163.	-0.3	-0.4	0.9
2213.000	2213.	-2.2	-0.4	1.2
2513.000	2513.	-2.2	-0.4	1.2
2863.000	2863.	-2.0	-0.4	1.0
2963.000	2963.	-2.0	-0.6	1.3
3063.000	3063.	-3.5	-1.2	2.8
3113.000	3113.	-3.2	-0.9	2.4
3278.000	3278.	-3.2	-0.9	2.4
3327.000	3327.	-3.2	-0.9	2.4
3328.000	3328.	-0.8	-0.2	0.9
3672.000	3672.	-0.9	-0.2	0.9
3684.000	3684.	-2.1	-0.6	0.6
3825.000	3825.	-2.1	-0.6	0.3
3965.000	3955.	-2.0	-0.6	1.0
4028.000	4028.	-3.9	-0.2	0.2
4078.000	4078.	-3.1	-0.3	0.5
4471.000	4478.	-2.8	-0.5	0.7
4551.000	4738.	-1.3	-0.4	0.9
4907.000	4907.	-1.4	-0.5	0.9
4908.000	4908.	-1.5	-0.4	1.0
5508.000	5508.	-1.5	-0.6	1.1
5928.000	5928.	-1.5	-0.4	1.1
6078.000	6078.	-1.4	-0.5	1.0
6128.000	6128.	-1.4	-0.5	1.0
6178.000	6178.	-3.2	-1.0	2.1
6228.000	6228.	-3.7	-1.1	2.9
7150.000	7150.	-3.5	-1.0	3.7
7300.000	7300.	-3.0	-1.0	3.6
7523.000	7521.	-2.6	-0.5	3.1
7518.000	7518.	-1.3	-0.4	3.1
7868.000	7868.	-1.0	-0.6	2.0
7921.000	7921.	-2.4	-0.6	1.3
7965.000	7965.	-5.1	-1.6	0.4
8118.000	8118.	-5.0	-1.5	0.5
8518.000	8518.	-4.8	-1.5	0.7
8555.000	8555.	-4.6	-1.3	0.9
8556.000	8556.	-4.3	-1.4	0.7
8811.000	8811.	-4.8	-1.5	1.2
8812.000	8812.	-5.0	-1.3	1.7
8918.000	8918.	-5.0	-1.8	1.8
9453.000	9433.	-4.2	-1.2	1.8
9813.000	9813.	-3.3	-1.2	1.8
9972.500	9972.	-3.7	-1.2	1.7
10019.000	10019.	-2.5	-1.2	2.5
10044.000	10044.	-2.6	-1.2	2.3
10074.000	10074.	-3.1	-1.1	3.1

PRINTED IN U.S.A.
FORM 1411-68-PRINTED BY ROTARY MANIFOLD FORMS.

10103.000	10103.	-3.1	-1.5	3.6
10104.000	10104.	-3.1	-1.5	3.4
10132.000	10132.	-2.9	-1.3	3.5
10133.000	10133.	-2.9	-1.3	4.2
10157.000	10157.	-3.1	-1.2	4.0
WEIGHTED AVG FOR REACH		-2.7	-0.8	1.7

FHF FOR THE REACH = 025 WITH 60.4% OF THE REACH WITHIN 1.0 FEET
ZONE FOR THE REACH = A 5

CONTINUOUS FLOOD HAZARD FACTORS BY EVEN INCREMENTS

INC NO.	TOTAL LENGTH	AVG ELEVATION DATA 100	10	DIFF.	WTD. AVG.	FHF	PERCENT WITHIN
	0.				SEC.		0.000
1	100.	765.9	768.1	-2.2	-2.2	020	100.
2	200.	765.9	768.1	-2.2	-2.2	020	100.
	300.				SEC.		300.000
3	300.	766.0	768.1	-2.2	-2.2	020	100.
4	400.	766.0	768.1	-2.1	-2.2	020	100.
5	500.	766.1	768.2	-2.1	-2.2	020	100.
	600.				SEC.		600.000
6	600.	766.1	768.2	-2.1	-2.1	020	100.
7	700.	766.4	768.2	-2.0	-2.1	020	100.
8	800.	766.5	768.3	-1.8	-2.1	020	100.
9	900.	766.8	768.4	-1.7	-2.0	020	100.
	978.				SEC.		978.000
10	1000.	767.2	768.8	-1.6	-1.8	020	100.
	1028.				SEC.		1028.000
	1078.				SEC.		1078.000
11	1100.	768.2	770.2	-2.0	-2.0	020	100.
	1113.				SEC.		1113.000
12	1200.	769.8	771.1	-1.3	-2.3	020	100.
13	1300.	769.7	772.0	-2.4	-2.3	020	100.
14	1400.	770.3	772.9	-2.6	-2.4	020	100.
15	1500.	771.9	773.7	-1.8	-2.1	020	100.
16	1600.	772.2	774.5	-2.4	-2.1	020	100.
17	1700.	773.0	775.3	-2.3	-2.1	020	100.
18	1800.	773.8	775.2	-1.4	-2.1	020	100.
19	1900.	774.7	777.0	-2.3	-2.1	020	100.
20	2000.	775.5	777.8	-2.3	-2.1	020	100.
21	2100.	776.4	778.7	-2.3	-2.2	020	100.
	2163.				SEC.		2163.000
22	2200.	777.2	779.5	-2.3	-2.2	020	100.
	2213.				SEC.		2213.000
23	2300.	777.8	780.0	-2.2	-2.2	020	100.
24	2400.	777.9	780.1	-2.2	-2.2	020	100.
25	2500.	778.0	780.2	-2.2	-2.2	020	100.
	2513.				SEC.		2513.000
26	2600.	778.1	780.3	-2.2	-2.2	020	100.
27	2700.	778.3	780.4	-2.1	-2.2	020	100.
28	2800.	778.5	780.5	-2.0	-2.2	020	100.
	2863.				SEC.		2863.000
29	2900.	778.9	781.0	-2.0	-2.1	020	100.
	2963.				SEC.		2963.000
30	3000.	780.0	782.1	-2.1	-2.1	020	100.

PRINTED IN U.S.A.
FORM 1411-05-PRINTED BY ROTARY MANIFOLD FORMS.

	3063.					SEC.	3063.000	
31	3100.	781.6	784.2	-2.6	-2.2	020		100.
	3113.					SEC.	3113.000	
32	3200.	782.8	785.9	-3.1	-2.2	020		100.
	3278.					SEC.	3278.000	
33	3300.	783.2	786.4	-3.2	-2.2	020		100.
	3327.					SEC.	3327.000	
	3328.					SEC.	3328.000	
34	3400.	787.8	788.6	-0.8	-2.2	020		94.
35	3500.	787.8	788.6	-0.8	-2.1	020		91.
36	3600.	787.9	788.7	-0.9	-2.1	020		89.
	3672.					SEC.	3672.000	
	3684.					SEC.	3684.000	
37	3700.	786.3	790.2	-2.1	-2.1	020		89.
38	3800.	790.4	790.5	-2.1	-2.1	020		89.
	3825.					SEC.	3825.000	
39	3900.	786.9	789.0	-2.1	-2.1	020		90.
	3965.					SEC.	3965.000	
40	4000.	789.8	792.4	-2.6	-2.1	020		90.
	4028.					SEC.	4028.000	
	4078.					SEC.	4078.000	
41	4100.	792.1	795.2	-3.1	-2.1	020		90.
42	4200.	792.2	795.3	-3.0	-2.2	020		90.
43	4300.	792.5	795.4	-2.9	-2.2	020		91.
44	4400.	792.7	795.5	-2.8	-2.2	020		93.
	4478.					SEC.	4478.000	
45	4500.	793.1	795.7	-2.6	-2.2	020		93.
46	4600.	793.8	796.1	-2.4	-2.2	020		93.
47	4700.	794.8	796.7	-2.0	-2.2	020		94.
48	4800.	795.8	797.4	-1.6	-2.2	020		92.
	4858.					SEC.	4858.000	
49	4900.	796.7	798.0	-1.3	-2.2	020		92.
	4907.					SEC.	4907.000	
	4908.					SEC.	4908.000	
50	5000.	804.3	805.8	-1.5	-2.2	020		92.
51	5100.	804.2	805.8	-1.5	-2.1	020		92.
52	5200.	804.4	805.9	-1.5	-2.1	020		92.
53	5300.	804.4	805.9	-1.5	-2.1	020		92.
	5306.					SEC.	5306.000	
54	5400.	804.4	805.9	-1.5	-2.1	020		93.
55	5500.	804.4	806.0	-1.5	-2.1	020		93.
56	5600.	804.4	806.0	-1.5	-2.1	020		93.
57	5700.	804.5	806.0	-1.5	-2.1	020		93.
58	5800.	804.5	806.0	-1.5	-2.1	020		90.
59	5900.	804.5	806.0	-1.5	-2.1	020		90.
	5928.					SEC.	5928.000	
60	6000.	804.5	805.8	-1.3	-2.0	020		90.
	6078.					SEC.	6078.000	
61	6100.	804.3	805.8	-1.5	-2.0	020		90.
	6128.					SEC.	6128.000	
	6178.					SEC.	6178.000	
62	6200.	805.5	808.9	-3.3	-2.1	020		39.
	6234.					SEC.	6234.000	
63	6300.	806.3	809.9	-3.6	-2.2	020		37.
64	6400.	806.8	810.5	-3.7	-2.2	020		39.
65	6500.	806.9	810.6	-3.6	-2.2	020		88.
66	6600.	807.0	810.6	-3.6	-2.2	020		86.
67	6700.	807.1	810.7	-3.5	-2.2	020		85.
68	6800.	807.2	810.7	-3.5	-2.2	020		83.
69	6900.	807.5	810.9	-3.4	-2.2	020		84.
70	7000.	807.4	810.8	-3.4	-2.2	020		83.
71	7100.	807.5	810.9	-3.4	-2.2	020		82.
	7150.					SEC.	7150.000	
72	7200.	807.7	811.0	-3.3	-2.2	020		79.

PRINTED IN U.S.A.
FORM 1411-OD PRINTED BY ROTARY MANIFOLD FORMS

	7300.				SEC.	7300.000	
75	7300.	808.0	811.1	-3.1	-2.3	025	81.
	7328.				SEC.	7328.000	
76	7400.	808.9	811.5	-2.5	-2.3	025	81.
75	7500.	810.0	811.8	-1.8	-2.3	025	81.
	7518.				SEC.	7518.000	
76	7600.	810.3	811.9	-1.6	-2.3	025	80.
77	7700.	810.4	812.0	-1.6	-2.2	020	82.
78	7800.	810.5	812.2	-1.7	-2.2	020	82.
	7868.				SEC.	7868.000	
79	7900.	811.1	813.0	-1.9	-2.2	020	82.
	7921.				SEC.	7921.000	
	7965.				SEC.	7965.000	
80	8000.	813.3	818.6	-5.1	-2.3	025	81.
81	8100.	813.5	818.5	-5.0	-2.3	025	80.
	8118.				SEC.	8118.000	
82	8200.	813.7	818.7	-5.0	-2.3	025	80.
83	8300.	813.9	818.8	-4.9	-2.4	025	81.
84	8400.	814.0	818.9	-4.9	-2.4	025	80.
85	8500.	814.2	819.0	-4.8	-2.4	025	80.
	8518.				SEC.	8518.000	
	8555.				SEC.	8553.000	
	8556.				SEC.	8556.000	
86	8600.	814.4	819.0	-4.5	-2.5	023	80.
87	8700.	814.5	819.1	-4.6	-2.5	025	77.
88	8800.	814.6	819.3	-4.7	-2.5	025	76.
	8811.				SEC.	8811.000	
	8812.				SEC.	8812.000	
89	8900.	815.0	820.3	-5.0	-2.3	023	71.
	8918.				SEC.	8918.000	
90	9000.	815.2	820.1	-5.0	-2.4	023	86.
91	9100.	815.4	820.2	-4.8	-2.6	025	65.
92	9200.	815.6	820.2	-4.7	-2.6	025	63.
93	9300.	815.8	820.3	-4.5	-2.6	025	62.
94	9400.	816.0	820.3	-4.4	-2.6	023	62.
	9453.				SEC.	9453.201	
95	9500.	815.2	820.5	-5.2	-2.7	021	50.
96	9600.	815.3	820.5	-5.0	-2.7	025	60.
97	9700.	815.4	820.3	-4.9	-2.7	025	59.
98	9800.	815.6	820.3	-4.7	-2.7	025	58.
99	9900.	815.7	820.3	-4.	-2.7	025	59.
	9916.				SEC.	9916.000	
	9976.				SEC.	9973.300	
100	10000.	817.0	820.5	-2.7	-2.7	023	59.
	10011.				SEC.	10011.000	
	10064.				SEC.	10064.000	
	10094.				SEC.	10094.300	
101	10100.	818.3	821.5	-3.2	-2.7	023	59.
	10103.				SEC.	10103.200	
	10104.				SEC.	10104.000	
	10132.				SEC.	10132.000	
	10133.				SEC.	10133.300	
	10157.				SEC.	10157.300	

*NCS REACH CAN BE SUBDIVIDED BY INC NO. TO INCL FIA REQUIREMENTS
ENPUT 20Y WHERE M IS THE NUMBER OF REACHES AND THEN INPUT THE END
OF EACH REACH BY INC NO. FOR EXAMPLE 202 80 101
A NEGATIVE INC NO. WILL SUPPRESS INTERMEDIATE INC OUTPUT.

PRINTED IN U.S.A.
FORM 1411-08-PRINTED BY ROTARY MANIFOLD FORMS

00BREAK00

1) COUNTY: Wayne

2) STUDY NAME: City of Northville

3) WATERCOURSE: Randolph Drain

4) DOCUMENT TYPE: Report

00BREAK00

RECEIVED

JAN 16 1992

NATURAL RESOURCES
LAND & WATER MGMT.

CITY OF NORTHVILLE

RANDOLPH STREET DRAIN

FLOOD STUDY

EXISTING CONDITION

HYDROLOGIC & HYDRAULIC

ANALYSIS


BETWEEN LEXINGTON BLVD. AND BECK ROAD

BY


McNEELY & LINCOLN ASSOCIATES, INC.

459 EAST CADY, NORTHVILLE MI-48167

CITY OF NORTHVILLE - MICHIGAN




CITY OF NORTHVILLE - MICHIGAN



RANDOLPH DRAIN FLOOD LEVEL STUDY

CITY OF NORTHVILLE - MICHIGAN




500-YEAR FLOO
CONTAINED IN CUL

LEXINGTON STR

RANDOLPH DRAIN FLOOD LEVEL STUDY

RANDOLPH STREET DRAIN


PRECIPITATION DATA



SOURCE: 210-VI-TR-55, Second Ed., June 1986

SELECT - 3.5 Inches


Figure B-5.—Ten-year, 24-hour rainfall.



SOURCE: 210-VI-TR-55, Second Ed., June 1986

SELECT - 4.45 Inches

Figure B-7.—Fifty-year, 24-hour rainfall.



SOURCE: 210-VI-TR-55, Second Ed., June 1986

SELECT - 4.85 Inches

Figure B-6.—One-hundred-year, 24-hour rainfall.

RANDOLPH STREET DRAIN

EXISTING CONDITION

HYDROLOGIC ANALYSIS

****

FLOOD HYDROGRAPH PACKAGE HEC-1 (IBM XT 512K VERSION) -FEB 1,1985

U.S. ARMY CORPS OF ENGINEERS, THE HYDROLOGIC ENGINEERING CENTER, 609 SECOND STREET, DAVIS, CA. 95616

****

THIS HEC-1 VERSION CONTAINS ALL OPTIONS EXCEPT ECONOMICS, AND THE NUMBER OF PLANS ARE REDUCED TO 3

```
LINE      ID.....1.....2.....3.....4.....5.....6.....7.....8.....9.....10

  1       ID   RANDOLPH DRAIN FLOOD ANALYSIS    NOV 2, 1987    FILE: 100H1
  2       ID   100 YEAR EVENT
  3       ID   DEVELOPED CONDITIONS
          *DIAGRAM
  4       IT       5  1MAR86    0000     300
  5       IO       5       0       20
  6       IN      30  1MAR86    0000
  7       JR    PREC  1.0000  1.2714  1.3857  1.5286

  8       KK  RANDB2  RANDOLPH DISTRICT
  9       PB    3.50
 10       PC  0.0000  0.0053  0.0108  0.0164  0.0223  0.0284  0.0347  0.0414  0.0483  0.0555
 11       PC  0.0623  0.0712  0.0797  0.0887  0.0984  0.1089  0.1203  0.1328  0.1467  0.1625
 12       PC  0.1808  0.2042  0.2351  0.2833  0.6632  0.7351  0.7724  0.7989  0.8197  0.8380
 13       PC  0.8538  0.8676  0.8801  0.8914  0.9019  0.9115  0.9206  0.9291  0.9371  0.9446
 14       PC  0.9519  0.9588  0.9653  0.9717  0.9777  0.9836  0.9892  0.9947  1.0000
 15       KM          SCS RUNOFF FOR RANDOLPH DISTRICT B2
 16       BA   0.100
 17       LS       0      68
 18       UD    0.66

 19       KK  RANDB2
 20       KM        ROUTING FOR POND AT NW CORNER OF BECK AND 9 MILE
 21       RS       1    ELEV   947.6       0
 22       SA       0    1.62    1.82    2.03    2.22    2.43    2.56
 23       SQ       0    1.90    7.40   12.00   15.20   17.60   95.00
 24       SE   947.6     948   948.5   949.0   949.5   950.0   950.3

 25       KK  RANDB2
 26       KM        CHANNEL ROUTE TO CULVERT, W. SIDE OF BECK
 27       RK     755 0.0071    0.030       0

 28       KK  RANDB1
 29       KM        SCS RUNOFF FOR RANDOLPH DISTRICT B1
 30       BA   0.084
 31       LS       0      68
 32       UD    0.26

 33       KK   RANDB
 34       KM        COMBINE RANDOLPH B1 AND B2
 35       HC       2

 36       KK   RANDB
 37       KM        CHANNEL ROUTE TO RANDOLPH A POND (CULVERT)
 38       RK    1045  .0065    0.024            CIRC       2

 39       KK   RANDB
 40       KM        CHANNEL ROUTE TO RANDOLPH A POND (DITCH)
 41       RK     435    1.84     .03            TRAP       2       4
```

```
LINE  ID.....1.....2.....3.....4.....5.....6.....7.....8.....9.....10

  42  KK  RANDA
  43  KM      SCS RUNOFF FOR RANDOLPH A DISTRICT
  44  BA  0.108
  45  LS     0      72
  46  UD   0.32

  47  KK  RANDA
  48  KM      COMBINE RANDOLPH A RUNOFF WITH RANDOLPH B OUTFLOW
  49  HC     2

  50  KK  RANDA
  51  KM      RANDOLPH A POND ROUTING
  52  RS     1    ELEV   926.2       0
  53  SA     0    0.01    0.72    2.07    2.17    2.22    2.35    2.80
  54  SQ     0     9.0     45.     97.    140.    180.    230.    650.
  55  SE 926.2     927     928   930.2   930.3   930.4   930.5   931.0

  56  KK  CTYLW
  57  KM      SCS RUNOFF FOR CITY LINE WEST DISTRICT
  58  BA  0.031
  59  LS     0      78
  60  UD   0.24

  61  KK  CTYLW
  62  KM      COMBINE CITY LINE WEST RUNOFF WITH RANDOLPH A FLOW
  63  HC     2

  64  KK  RANDA
  65  KM      CHANNEL ROUTE TO 60" CULVERT ENTRANCE BASIN
  66  RK   1450  0.0033    0.04                0       0       2

  67  KK  CTYLE
  68  KM      SCS RUNOFF FOR CITY LINE EAST DISTRICT
  69  BA  0.062
  70  LS     0      78
  71  UD   0.24

  72  KK    60"
  73  KM      COMBINE RANDOLPH A AND CITY LINE OUTFLOWS
  74  HC     2

  75  KK    60"
  76  KM      ROUTE COMBINED FLOWS AHEAD OF 60" CULVERT
  77  RS     1    ELEV   910.3       0
  78  SA 0.033   0.082   0.140   0.198   0.256     1.0
  79  SQ     0      55      84     160     212     278
  80  SE 909.3     911     913     915     917     919

  81  KK    60"
  82  KM      CHANNEL ROUTE THROUGH 60" CULVERT
  83  RK    580   0.006   0.013            CIRC       5
```

```
LINE      ID.....1.....2.....3.....4.....5.....6.....7.....8.....9.....10

  84      KK    60"
  85      KM       CHANNEL ROUTE THROUGH CULVERT OUTLET DITCH
  86      RK    550  0.0056   0.030            TRAP       4       3

  87      KK   NVEST
  88      KM       SCS RUNOFF FOR NORTHVILLE ESTATES
  89      BA   0.100
  90      LS       0       70
  91      UD    0.37

  92      KK   ABBEY
  93      KM       SCS RUNOFF FOR DEVELOPED ABBEY KNOLL ESTATES SUBDIVISION
  94      BA   0.072
  95      LS       0       80
  96      UD    0.42

  97      KK    RANJ
  98      KM       SCS RUNOFF FOR RANDOLPH JUNCTION (NOVI - WEST OF LEXINGTON GREEN)
  99      BA   0.182
 100      LS       0       69
 101      UD    0.65

 102      KK   JUNCT
 103      KM       COMBINE RANDOLPH JUNCTION, 60" CULVERT & NORTHVILLE ESTATES/ABBEY KNOLL
 104      HC       4

 105      KK   JUNCT
 106      KM       ROUTE COMBINED FLOWS THROUGH ABBEY POND/WETLANDS
 107      RS       1    FLOW       2       0
 108      SA    1.24    4.30    5.90    8.30   10.28   11.20
 109      SQ       0      10      48     250     573     747
 110      SE   902.8   903.5     904     905     906   906.5

 111      KK   LEXGR
 112      KM       SCS RUNOFF FOR LEXINGTON GREEN SUBDIVISION
 113      BA   0.144
 114      LS       0       72
 115      UD    0.30

 116      KK   LEXGR
 117      KM       LEXINGTON GREEN DETENTION POND ROUTING
 118      RS       1    ELEV   904.6       0
 119      SA    1.55    1.65    1.84    1.88    1.94    2.00
 120      SQ       0     1.3     4.0      39     159     350
 121      SE   904.6     905   905.8     906   906.5     907

 122      KK   LEXGR
 123      KM       CHANNEL ROUTING OF LEXINGTON GREEN DISCHARGE
 124      RK     950   0.001   0.040            TRAP       0      50
```


```
LINE      ID.....1.....2.....3.....4.....5.....6.....7.....8.....9.....10


  125     KK  JUNCT
  126     KM       COMBINE LEXINGTON GREEN, RANDOLPH JUNCTION, N'VILLE ESTATES & 60" FLOWS
  127     HC       2

  128     KK  PHILLS
  129     KM       SCS RUNOFF AND KINEMATIC ROUTING ACROSS PHEASANT HILLS
  130     BA  0.159
  131     LS       0      77                      77
  132     UK    1000    0.05     .25      47
  133     UK     500    0.05     .25      53
  134     RK    2700  0.0056    .030           TRAP      10       1     YES
  135     ZZ
```

SCHEMATIC DIAGRAM OF STREAM NETWORK

INPUT LINE NO. — (V) ROUTING, (.) CONNECTOR, (---->) DIVERSION OR PUMP FLOW, (<----) RETURN OF DIVERTED OR PUMPED FLOW





(***) RUNOFF ALSO COMPUTED AT THIS LOCATION

1

****

FLOOD HYDROGRAPH PACKAGE HEC-1 (IBM XT 512K VERSION) -FEB 1,1985

U.S. ARMY CORPS OF ENGINEERS, THE HYDROLOGIC ENGINEERING CENTER, 609 SECOND STREET, DAVIS, CA. 95616

****

RANDOLPH DRAIN FLOOD ANALYSIS NOV 2, 1987 FILE: 100H1

100 YEAR EVENT

DEVELOPED CONDITIONS

5 IO OUTPUT CONTROL VARIABLES

IPRNT	5	PRINT CONTROL
IPLOT	0	PLOT CONTROL
QSCAL	20.	HYDROGRAPH PLOT SCALE

IT HYDROGRAPH TIME DATA

NMIN	5	MINUTES IN COMPUTATION INTERVAL
IDATE	1MAR86	STARTING DATE
ITIME	0000	STARTING TIME
NQ	300	NUMBER OF HYDROGRAPH ORDINATES
NDDATE	2MAR86	ENDING DATE
NDTIME	0055	ENDING TIME

COMPUTATION INTERVAL .08 HOURS

TOTAL TIME BASE 24.92 HOURS

ENGLISH UNITS

JP MULTI-PLAN OPTION

NPLAN 1 NUMBER OF PLANS

JR MULTI-RATIO OPTION

RATIOS OF PRECIPITATION

1.00 1.27

1.39 1.53

WARNING *** TIME INTERVAL IS GREATER THAN .29*LAG

*** WARNING *** MODIFIED PULS ROUTING MAY BE NUMERICALLY UNSTABLE FOR OUTFLOWS BETWEEN 0. TO 650.
THE ROUTED HYDROGRAPH SHOULD BE EXAMINED FOR OSCILLATIONS OR OUTFLOWS GREATER THAN PEAK INFLOWS.
THIS CAN BE CORRECTED BY DECREASING THE TIME INTERVAL OR INCREASING STORAGE (USE A LONGER REACH.)

WARNING *** TIME INTERVAL IS GREATER THAN .29*LAG

WARNING *** TIME INTERVAL IS GREATER THAN .29*LAG

*** WARNING *** MODIFIED PULS ROUTING MAY BE NUMERICALLY UNSTABLE FOR OUTFLOWS BETWEEN 0. TO 55.
THE ROUTED HYDROGRAPH SHOULD BE EXAMINED FOR OSCILLATIONS OR OUTFLOWS GREATER THAN PEAK INFLOWS.
THIS CAN BE CORRECTED BY DECREASING THE TIME INTERVAL OR INCREASING STORAGE (USE A LONGER REACH.)

1

PEAK FLOW AND STAGE (END-OF-PERIOD) SUMMARY FOR MULTIPLE PLAN-RATIO ECONOMIC COMPUTATIONS
FLOWS IN CUBIC FEET PER SECOND, AREA IN SQUARE MILES
TIME TO PEAK IN HOURS

OPERATION	STATION	AREA	PLAN		RATIOS APPLIED TO PRECIPITATION RATIO 1	RATIO 2	RATIO 3	RATIO 4
					1.00	1.27	1.39	1.53
HYDROGRAPH AT								
+	RANDB2	.10	1	FLOW	24.	43.	52.	63.
				TIME	12.58	12.58	12.58	12.50
ROUTED TO								
+	RANDB2	.10	1	FLOW	9.	14.	16.	24.
				TIME	13.67	13.75	13.75	13.50
			** PEAK STAGES IN FEET **					
			1	STAGE	948.71	949.37	949.67	950.02
				TIME	13.67	13.75	13.75	13.50
ROUTED TO								
+	RANDB2	.10	1	FLOW	9.	14.	16.	24.
				TIME	13.75	13.75	13.83	13.58
HYDROGRAPH AT								
+	RANDB1	.08	1	FLOW	34.	59.	71.	86.
				TIME	12.17	12.17	12.17	12.08
2 COMBINED AT								
+	RANDB	.18	1	FLOW	35.	61.	74.	90.
				TIME	12.17	12.17	12.17	12.17
ROUTED TO								
+	RANDB	.18	1	FLOW	34.	61.	73.	89.
				TIME	12.17	12.17	12.17	12.17
ROUTED TO								
+	RANDB	.18	1	FLOW	34.	61.	73.	89.
				TIME	12.25	12.17	12.17	12.17
HYDROGRAPH AT								
+	RANDA	.11	1	FLOW	52.	86.	101.	121.
				TIME	12.17	12.17	12.17	12.17
2 COMBINED AT								
+	RANDA	.29	1	FLOW	85.	147.	174.	210.
				TIME	12.17	12.17	12.17	12.17
ROUTED TO								
+	RANDA	.29	1	FLOW	59.	89.	127.	179.
				TIME	12.42	12.50	12.42	12.33

				** PEAK STAGES IN FEET **				
			1	STAGE	928.59	929.84	930.27	930.40
				TIME	12.42	12.50	12.42	12.33
HYDROGRAPH AT								
+	CTYLW	.03	1	FLOW	23.	36.	41.	48.
				TIME	12.08	12.08	12.08	12.08
2 COMBINED AT								
+	CTYLW	.32	1	FLOW	73.	106.	146.	207.
				TIME	12.25	12.25	12.42	12.33
ROUTED TO								
+	RANDA	.32	1	FLOW	73.	106.	139.	207.
				TIME	12.25	12.33	12.50	12.42
HYDROGRAPH AT								
+	CTYLE	.06	1	FLOW	47.	71.	82.	96.
				TIME	12.08	12.08	12.08	12.08
2 COMBINED AT								
+	60"	.38	1	FLOW	115.	166.	189.	250.
				TIME	12.17	12.17	12.17	12.42
ROUTED TO								
+	60"	.38	1	FLOW	112.	162.	182.	233.
				TIME	12.25	12.25	12.25	12.50
				** PEAK STAGES IN FEET **				
			1	STAGE	913.75	915.07	915.84	917.64
				TIME	12.25	12.25	12.25	12.50
ROUTED TO								
+	60"	.38	1	FLOW	112.	162.	181.	233.
				TIME	12.25	12.25	12.25	12.50
ROUTED TO								
+	60"	.38	1	FLOW	110.	161.	180.	232.
				TIME	12.25	12.25	12.33	12.50
HYDROGRAPH AT								
+	NVEST	.10	1	FLOW	39.	67.	80.	96.
				TIME	12.25	12.25	12.25	12.25
HYDROGRAPH AT								
+	ABBEY	.07	1	FLOW	47.	70.	81.	94.
				TIME	12.25	12.25	12.25	12.25
HYDROGRAPH AT								
+	RANJ	.18	1	FLOW	47.	83.	100.	122.
				TIME	12.58	12.50	12.50	12.50
4 COMBINED AT								
+	JUNCT	.74	1	FLOW	231.	362.	421.	508.
				TIME	12.33	12.33	12.33	12.33

ROUTED TO								
+	JUNCT	.74	1	FLOW	159.	265.	323.	407.
				TIME	12.83	12.75	12.67	12.67
				** PEAK STAGES IN FEET **				
			1	STAGE	904.55	905.05	905.23	905.49
				TIME	12.83	12.75	12.67	12.67
HYDROGRAPH AT								
+	LEXGR	.14	1	FLOW	71.	118.	139.	166.
				TIME	12.17	12.17	12.17	12.17
ROUTED TO								
+	LEXGR	.14	1	FLOW	45.	101.	125.	153.
				TIME	12.42	12.33	12.25	12.25
				** PEAK STAGES IN FEET **				
			1	STAGE	906.03	906.26	906.36	906.47
				TIME	12.42	12.33	12.25	12.25
ROUTED TO								
+	LEXGR	.14	1	FLOW	44.	102.	121.	148.
				TIME	12.67	12.42	12.50	12.42
2 COMBINED AT								
+	JUNCT	.88	1	FLOW	198.	352.	428.	531.
				TIME	12.75	12.58	12.58	12.58
HYDROGRAPH AT								
+	PHILL	1.04	1	FLOW	236.	414.	494.	609.
				TIME	12.75	12.58	12.58	12.58

*** NORMAL END OF HEC-1 ***

RANDOLPH STREET DRAIN

EXISTING CONDITION

HYDRAULIC ANALYSIS

1**********

****

* WATER SURFACE PROFILES *
* VERSION OF NOVEMBER 1976 *
* UPDATED MAY 1984 *
* IBM-PC-XT VERSION AUGUST 1985 *
* RUN DATE 01-13-92 TIME 09:32:21 *

****

* U.S. ARMY CORPS OF ENGI
* THE HYDROLOGIC ENGINEER
* 609 SECOND STREET, SUIT
* DAVIS, CALIFORNIA 95616
* (916) 440-2105 (FTS)

****

```
X     X  XXXXXXX   XXXXX              XXXXX
X     X  X        X     X            X     X
X     X  X        X                        X
XXXXXXX  XXXX     X          XXXXX    XXXXX
X     X  X        X                   X
X     X  X        X     X             X
X     X  XXXXXXX  XXXXX               XXXXXXX
```

1

01-13-92 09:32:22 PAGE

THIS RUN EXECUTED 01-13-92

****

HEC2 RELEASE DATED NOV 76 UPDATED MAY 1984
ERROR CORR - 01,02,03,04,05,06
MODIFICATION - 50,51,52,53,54,55,56
IBM-PC-XT VERSION AUGUST 1985

****

T1 RANDOLPH DRAIN FLOOD ANALYSIS - 10/87 APPEAL FILE:APPEAL

T2 CITY OF NORTHVILLE JOB NO. 6800-50 10-YEAR EVENT

T3 RANDOLPH DRAIN

J1	ICHECK	INQ	NINV	IDIR	STRT	METRIC	HVINS	Q	WSEL	FQ
	0.	2.	0.	0.	.000000	.00	.0	0.	886.340	.000

J2	NPROF	IPLOT	PRFVS	XSECV	XSECH	FN	ALLDC	IBW	CHNIM	ITRACE
	1.000	.000	-1.000	.000	.000	.000	.000	.000	.000	.000

J3 VARIABLE CODES FOR SUMMARY PRINTOUT

150.000	.000	.000	.000	.000	.000	.000	.000	.000	.000

QT	4.000	236.000	414.000	494.000	609.000	.000	.000	.000	.000	.000
NC	.030	.030	.030	.400	.600	.000	.000	.000	.000	.000
X1	1.000	8.000	32.000	44.000	.000	.000	.000	.000	-.600	.000
GR	889.600	.000	888.500	20.000	883.600	32.000	882.900	34.000	882.900	42.000
GR	883.800	44.000	889.800	57.000	890.600	79.000	.000	.000	.000	.000
X1	2.000	8.000	32.000	44.000	55.000	45.000	52.000	.000	.000	.000
GR	889.600	.000	888.500	20.000	883.600	32.000	882.900	34.000	882.900	36.000
GR	883.800	44.000	889.800	57.000	890.600	79.000	.000	.000	.000	.000
X1	2.250	10.000	32.000	42.000	154.000	157.000	159.000	.000	.000	.000
GR	890.000	.000	888.800	20.000	885.800	32.000	884.600	34.000	884.600	36.000
GR	884.900	40.000	885.100	42.000	888.500	52.000	889.800	57.000	891.200	72.000
X1	2.500	11.000	127.000	139.000	154.000	156.000	159.000	.000	.000	.000
GR	894.000	.000	892.000	50.000	890.000	105.000	888.000	127.000	886.400	129.000
GR	886.300	132.000	886.700	136.000	888.000	139.000	892.000	166.000	894.000	206.000
GR	894.000	225.000	.000	.000	.000	.000	.000	.000	.000	.000
X1	3.000	11.000	63.000	72.000	582.000	482.000	637.000	.000	.000	.000
GR	898.700	.000	896.400	25.000	894.900	50.000	894.600	63.000	893.300	64.000
GR	893.200	67.000	893.600	71.000	894.600	72.000	895.500	100.000	896.700	125.000
GR	898.200	143.000	.000	.000	.000	.000	.000	.000	.000	.000
NC	.060	.060	.035	.000	.000	.000	.000	.000	.000	.000
X1	3.500	14.000	135.000	146.000	710.000	615.000	750.000	.000	-1.300	.000
GR	906.000	.000	904.000	66.000	903.000	91.000	902.300	116.000	902.100	135.000
GR	901.300	136.000	900.500	140.000	901.400	143.000	901.800	146.000	902.400	166.000
GR	903.100	191.000	904.100	216.000	905.300	241.000	906.500	255.000	.000	.000
X1	3.750	10.000	281.000	291.000	195.000	265.000	250.000	.000	.000	.000
GR	904.400	.000	904.000	255.000	902.000	280.000	901.200	281.000	899.900	285.000
GR	899.800	288.000	901.700	291.000	902.000	315.000	904.000	350.000	906.000	387.000
X1	4.000	14.000	135.000	146.000	230.000	245.000	265.000	.000	.000	.000
GR	906.000	.000	904.000	66.000	903.000	91.000	902.300	116.000	902.100	135.000
GR	901.300	136.000	900.500	140.000	901.400	143.000	901.800	146.000	902.400	166.000
GR	903.100	191.000	904.100	216.000	905.300	241.000	906.500	255.000	.000	.000

QT	4.000	159.000	265.000	323.000	407.000	.000	.000	.000	.000	.000
ET	.000	7.100	7.100	7.100	.000	.000	125.000	332.000	157.000	267.000
X1	5.000	15.000	214.000	232.000	905.000	920.000	915.000	.000	.000	.000
GR	906.000	.000	908.000	125.000	906.000	135.000	904.000	145.000	903.800	157.000
GR	903.500	182.000	903.600	207.000	903.100	214.000	902.600	225.000	903.100	229.000
GR	903.600	232.000	903.600	257.000	904.500	282.000	905.400	307.000	906.200	332.000
ET	.000	9.100	9.100	9.100	9.100	.000	.000	.000	110.000	330.000
X1	5.500	18.000	170.000	270.000	280.000	305.000	285.000	.000	.000	.000
GR	906.000	.000	908.000	110.000	906.000	118.000	904.000	126.000	902.800	145.000
GR	902.900	170.000	902.300	195.000	902.700	220.000	902.400	245.000	903.000	270.000
GR	903.100	295.000	903.000	320.000	903.700	345.000	904.000	370.000	904.000	395.000
GR	904.400	420.000	905.100	445.000	906.000	465.000	.000	.000	.000	.000
QT	4.000	110.000	161.000	180.000	232.000	.000	.000	.000	.000	.000
ET	.000	9.100	9.100	9.100	9.100	.000	.000	.000	113.000	175.000
X1	6.000	15.000	160.000	170.000	160.000	170.000	160.000	.000	.000	.000
GR	905.200	.000	905.300	25.000	905.700	50.000	905.400	75.000	906.000	100.000
GR	905.700	125.000	905.100	160.000	905.300	170.000	905.900	172.000	906.100	175.000
GR	906.900	200.000	907.400	225.000	907.600	250.000	908.800	275.000	909.500	300.000
ET	.000	7.100	7.100	7.100	7.100	.000	.200	31.800	.000	.000
X1	6.900	9.000	10.000	16.250	80.000	80.000	80.000	.000	.000	.000
GR	909.000	.000	906.700	8.000	905.500	10.000	905.300	11.000	905.300	16.000
GR	905.500	16.250	906.200	17.000	906.200	19.000	910.000	32.000	.000	.000
ET	.000	7.100	7.100	7.100	7.100	.000	75.000	208.000	.000	.000
X1	6.940	13.000	95.000	105.000	20.000	20.000	20.000	.000	-1.020	.000
GR	909.800	.000	911.300	25.000	912.200	50.000	912.800	75.000	907.600	95.000
GR	906.700	97.000	906.400	100.000	906.600	102.000	907.500	105.000	916.200	134.000
GR	916.600	159.000	917.300	184.000	917.400	209.000	.000	.000	.000	.000
ET	.000	7.100	7.100	7.100	7.100	.000	75.000	208.000	.000	.000
X1	6.950	13.000	95.000	105.000	40.000	40.000	40.000	.000	-.870	.000
GR	909.800	.000	911.300	25.000	912.200	50.000	912.800	75.000	907.600	95.000
GR	906.700	97.000	906.400	100.000	906.600	102.000	907.500	105.000	916.200	134.000
GR	916.600	159.000	917.300	184.000	917.400	209.000	.000	.000	.000	.000
ET	.000	7.100	7.100	7.100	7.100	.000	75.000	208.000	.000	.000
X1	7.000	.000	.000	.000	225.000	225.000	225.000	.000	.900	.000
ET	.000	7.100	7.100	7.100	7.100	.000	1.000	79.000	.000	.000
X1	8.000	10.000	5.000	55.000	578.000	578.000	578.000	.000	.000	.000
X5	4.000	913.480	914.410	915.110	917.430	.000	.000	.000	.000	.000
GR	917.700	.000	917.400	5.000	910.100	26.000	909.300	27.000	909.300	30.000
GR	909.100	33.500	909.600	34.300	916.700	55.000	917.300	60.000	918.100	80.000
QT	4.000	73.000	106.000	139.000	207.000	.000	.000	.000	.000	.000
ET	.000	7.100	7.100	7.100	7.100	.000	1.000	161.000	.000	.000
X1	9.000	10.000	70.500	95.500	185.000	185.000	185.000	.000	.000	.000
GR	920.200	.000	920.100	25.000	919.700	40.000	918.700	65.000	913.500	70.500
GR	910.200	80.500	910.200	85.500	913.500	95.500	920.000	116.000	921.000	161.000
ET	.000	7.100	7.100	7.100	7.100	.000	1.000	161.000	.000	.000

NC	.030	.030	.030	.800	.900	.000	.000	.000	.000	.000
X1	10.000	10.000	70.500	95.500	8.600	8.600	8.600	.000	.000	.000
GR	920.200	.000	920.100	25.000	919.700	40.000	918.700	65.000	915.500	70.500
GR	914.500	80.500	914.500	85.500	915.500	95.500	920.000	116.000	921.000	161.000
NC	.030	.030	.030	.400	.600	.000	.000	.000	.000	.000
ET	.000	7.100	7.100	7.100	7.100	.000	1.000	108.000	.000	.000
X1	11.000	8.000	37.000	60.000	179.000	179.000	179.000	.000	.000	.000
GR	920.900	.000	918.800	37.000	915.100	50.000	915.100	53.000	918.000	60.000
GR	918.300	90.000	920.000	185.000	920.900	190.000	.000	.000	.000	.000
X1	11.900	7.000	15.000	43.000	300.000	300.000	300.000	.000	.000	.000
GR	924.400	.000	920.000	15.000	916.100	31.500	916.100	34.500	919.400	43.000
GR	920.000	68.000	922.000	88.000	.000	.000	.000	.000	.000	.000
ET	.000	7.100	7.100	7.100	7.100	.000	1.000	309.000	.000	.000
X1	12.000	8.000	70.000	110.000	100.000	100.000	95.000	.000	.000	.000
GR	923.400	.000	922.000	40.000	920.400	70.000	920.200	100.000	920.400	110.000
GR	920.900	135.000	922.000	195.000	924.000	310.000	.000	.000	.000	.000
EJ	.000	.000	.000	.000	.000	.000	.000	.000	.000	.000

1

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

*PROF 1

CCHV= .400 CEHV= .600

*SECNO 1.000

1.00	4.04	886.34	.00	886.34	886.54	.20	.00	.00	883.00
236.	30.	185.	22.	14.	47.	11.	0.	0.	883.20
.00	2.16	3.94	2.05	.030	.030	.030	.000	882.30	23.82
.001063	0.	0.	0.	0	0	0	.00	26.98	50.80

0

*SECNO 2.000

2.00	3.46	886.36	.00	.00	886.71	.35	.08	.09	883.60
236.	27.	190.	19.	9.	37.	7.	0.	0.	883.80
.00	2.86	5.11	2.68	.030	.030	.030	.000	882.90	25.24
.002398	55.	52.	45.	2	0	0	.00	24.31	49.55

0

*SECNO 2.250

7185 MINIMUM SPECIFIC ENERGY

3720 CRITICAL DEPTH ASSUMED

2.25	2.65	887.25	887.25	.00	888.09	.84	.64	.29	885.80
236.	15.	190.	31.	4.	24.	7.	0.	0.	885.10
.01	3.59	7.91	4.59	.030	.030	.030	.000	884.60	26.18
.008346	154.	159.	157.	0	15	0	.00	22.16	48.34

0

*SECNO 2.500

7185 MINIMUM SPECIFIC ENERGY

3720 CRITICAL DEPTH ASSUMED

2.50	2.86	889.16	889.16	.00	889.85	.69	1.22	.06	888.00
236.	21.	202.	13.	7.	28.	5.	0.	0.	888.00
.02	2.90	7.10	2.89	.030	.030	.030	.000	886.30	114.26
.007136	154.	159.	156.	2	8	0	.00	32.55	146.82

0

*SECNO 3.000

3685 20 TRIALS ATTEMPTED WSEL,CWSEL

3693 PROBABLE MINIMUM SPECIFIC ENERGY

3720 CRITICAL DEPTH ASSUMED

3.00	2.48	895.68	895.68	.00	896.09	.41	4.23	.11	894.60
236.	58.	126.	53.	17.	20.	18.	1.	1.	894.60
.05	3.38	6.39	2.95	.030	.030	.030	.000	893.20	37.08
.006824	582.	637.	482.	20	9	0	.00	66.57	103.65

0

1

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

```
*SECNO 3.500
7185 MINIMUM SPECIFIC ENERGY
3720 CRITICAL DEPTH ASSUMED
     3.50      2.55    901.75    901.75       .00    902.12       .37      5.86       .02    900.80
     236.       50.      131.       55.       26.       21.       27.       2.        2.     900.50
      .10      1.91      6.32      2.07      .060      .035      .060      .000    899.20     89.66
   .010195      710.      750.      615.         9         8         0       .00     99.68    189.34
0
 *SECNO 3.750
     3.75      3.51    903.31       .00       .00    903.54       .23      1.35       .06    901.20
     236.       15.      140.       81.       12.       29.       50.       2.        3.     901.70
      .11      1.18      4.82      1.63      .060      .035      .060      .000    899.80     263.67
   .003421      195.      250.      265.         3         0         0       .00     74.20    337.87
0
 *SECNO 4.000
     4.00      3.49    903.99       .00       .00    904.03       .05       .42       .07    902.10
     236.       77.       80.       78.       80.       31.       79.       3.        3.     901.80
      .16       .97      2.60       .99      .060      .035      .060      .000    900.50     66.20
   .001003      230.      265.      245.         3         0         0       .00    147.09    213.30
0
 *SECNO 5.000

 3470 ENCROACHMENT STATIONS=      125.0      332.0  TYPE=      1  TARGET=      207.000
     5.00      2.22    904.82       .00       .00    904.84       .02       .80       .01    903.10
     159.       64.       60.       35.       85.       34.       52.       7.        6.     903.60
      .39       .76      1.75       .68      .060      .035      .060      .000    902.60     140.85
   .000732      905.      915.      920.         3         0         0       .00    150.31    291.16
0
 *SECNO 5.500

 3470 ENCROACHMENT STATIONS=      110.0      330.0  TYPE=      1  TARGET=      220.000
     5.50      2.58    904.88       .00       .00    904.88       .00       .03       .01    902.90
     159.       20.      113.       26.       80.      229.      109.       9.        8.     903.00
      .58       .24       .49       .24      .060      .035      .060      .000    902.30     122.47
   .000044      280.      285.      305.         2         0         0       .00    207.52    330.00
0
 *SECNO 6.000
 3685 20 TRIALS ATTEMPTED WSEL,CWSEL

    SECNO     DEPTH     CWSEL     CRIWS     WSELK     EG        HV        HL        OLOSS     BANK ELEV
    Q         QLOB      QCH       QROB      ALOB      ACH       AROB      VOL       TWA     LEFT/RIGHT
    TIME      VLOB      VCH       VROB      XNL       XNCH      XNR       WTN       ELMIN       SSTA
    SLOPE     XLOBL     XLCH      XLOBR     ITRIAL    IDC       ICONT     CORAR     TOPWID      ENDST


 3693 PROBABLE MINIMUM SPECIFIC ENERGY
 3720 CRITICAL DEPTH ASSUMED

 3470 ENCROACHMENT STATIONS=      113.0      175.0  TYPE=      1  TARGET=       62.000
     6.00       .91    906.01    906.01       .00    906.28       .27       .02       .16    905.10
     110.       62.       46.        2.       24.        8.        1.       10.        8.     905.30
      .59      2.58      5.66      1.84      .060      .035      .060      .000    905.10     113.00
   .023503      160.      160.      170.        20        22         0       .00     60.65    173.65
0
```

```
*SECNO 6.900
7185 MINIMUM SPECIFIC ENERGY
3720 CRITICAL DEPTH ASSUMED

3470 ENCROACHMENT STATIONS=        .2      31.8  TYPE=     1  TARGET=      31.600
     6.90      1.99    907.29    907.29      .00    907.98      .69      1.32      .26    905.50
     110.       7.       90.       13.       3.       12.       5.        10.       8.    905.50
      .59      2.45      7.31      2.45     .060      .035     .060      .000    905.30     5.96
   .012254      80.       80.       80.        3        17        0       .00     16.75    22.72
0
 *SECNO 6.940

 3470 ENCROACHMENT STATIONS=       75.0     208.0  TYPE=     1  TARGET=     133.000
      6.94      2.59    907.97       .00       .00    908.27      .31       .14       .16    906.58
      110.       5.       101.       5.        4.       22.       4.        10.       8.    906.48
       .59      1.26      4.63      1.31     .060      .035     .060      .000    905.38    89.68
   .004416       20.       20.       20.        4         0        0       .00     20.27   109.94
0
 *SECNO 6.950

 3470 ENCROACHMENT STATIONS=       75.0     208.0  TYPE=     1  TARGET=     133.000
      6.95      2.63    908.16       .00       .00    908.45      .29       .17       .01    906.73
      110.       5.       100.       5.        4.       22.       4.        10.       8.    906.63
       .60      1.24      4.50      1.28     .060      .035     .060      .000    905.53    89.48
   .004052       40.       40.       40.        2         0        0       .00     20.63   110.11
0
 *SECNO 7.000

 3470 ENCROACHMENT STATIONS=       75.0     208.0  TYPE=     1  TARGET=     133.000
      7.00      2.64    909.07       .00       .00    909.36      .29       .91       .00    907.63
      110.       5.       100.       5.        4.       22.       4.        10.       8.    907.53
       .61      1.23      4.48      1.28     .060      .035     .060      .000    906.43    89.46
   .004006      225.      225.      225.        2         0        0       .00     20.68   110.14
0
1
  01-13-92     09:32:22                                                                    PAGE


    SECNO     DEPTH     CWSEL     CRIWS     WSELK     EG        HV        HL        OLOSS     BANK ELEV
    Q         QLOB      QCH       QROB      ALOB      ACH       AROB      VOL       TWA     LEFT/RIGHT
    TIME      VLOB      VCH       VROB      XNL       XNCH      XNR       WTN       ELMIN       SSTA
    SLOPE     XLOBL     XLCH      XLOBR     ITRIAL    IDC       ICONT     CORAR     TOPWID      ENDST


 *SECNO 8.000
  WATER EL=X5 CARD=   913.480

 3470 ENCROACHMENT STATIONS=        1.0      79.0  TYPE=     1  TARGET=      78.000
      8.00      4.38    913.48       .00       .00    913.52      .04       .54       .10    917.40
      110.       0.       110.       0.        0.       73.       0.        11.       9.    916.70
       .72       .00      1.51       .00     .060      .035     .060      .000    909.10    16.28
   .000402      578.      578.      578.        0         0        0       .00     29.34    45.61
```

```
 *SECNO 9.000

 3470 ENCROACHMENT STATIONS=       1.0     161.0  TYPE=     1  TARGET=     160.000
      9.00      3.36   913.56      .00       .00   913.60      .03       .08       .00   913.50
       73.        0.      73.       0.        0.      51.       0.       11.        9.   913.50
       .75       .01     1.43      .01      .060     .035     .060      .000   910.20    70.43
    .000461     185.     185.     185.         2        0        0       .00    25.27    95.70
0
 CCHV=    .800 CEHV=    .900
 *SECNO 10.000
 3685 20 TRIALS ATTEMPTED WSEL,CWSEL
 3693 PROBABLE MINIMUM SPECIFIC ENERGY
 3720 CRITICAL DEPTH ASSUMED

 3470 ENCROACHMENT STATIONS=       1.0     161.0  TYPE=     1  TARGET=     160.000
     10.00      1.04   915.54   915.54       .00   915.86      .33       .01       .27   915.50
       73.        0.      73.       0.        0.      16.       0.       11.        9.   915.50
       .75       .06     4.60      .06      .030     .030     .030      .000   914.50    70.44
    .015861       9.       9.       9.        20       17        0       .00    25.22    95.66
0
 CCHV=    .400 CEHV=    .600
 *SECNO 11.000

 3470 ENCROACHMENT STATIONS=       1.0     108.0  TYPE=     1  TARGET=     107.000
     11.00      2.04   917.14      .00       .00   917.38      .24      1.48       .04   918.80
       73.        0.      73.       0.        0.      19.       0.       11.        9.   918.00
       .77       .00     3.93      .00      .030     .030     .030      .000   915.10    42.80
    .005072     179.     179.     179.         3        0        0       .00    15.15    57.95
0
1
  01-13-92     09:32:22                                                                  PAGE


    SECNO     DEPTH     CWSEL     CRIWS     WSELK     EG        HV        HL        OLOSS     BANK ELEV
    Q         QLOB      QCH       QROB      ALOB      ACH       AROB      VOL       TWA     LEFT/RIGHT
    TIME      VLOB      VCH       VROB      XNL       XNCH      XNR       WTN       ELMIN       SSTA
    SLOPE     XLOBL     XLCH      XLOBR     ITRIAL    IDC       ICONT     CORAR     TOPWID      ENDST


 *SECNO 11.900
     11.90      2.26   918.36      .00       .00   918.50      .14      1.08       .04   920.00
       73.        0.      73.       0.        0.      24.       0.       11.        9.   919.40
       .80       .00     3.01      .00      .030     .030     .030      .000   916.10    21.93
    .002696     300.     300.     300.         4        0        0       .00    18.40    40.33
0
 *SECNO 12.000
 3685 20 TRIALS ATTEMPTED WSEL,CWSEL
 3693 PROBABLE MINIMUM SPECIFIC ENERGY
 3720 CRITICAL DEPTH ASSUMED

 3470 ENCROACHMENT STATIONS=       1.0     309.0  TYPE=     1  TARGET=     308.000
     12.00       .55   920.75   920.75       .00   920.94      .18       .50       .02   920.40
       73.        2.      65.       6.        1.      18.       3.       11.        9.   920.40
       .80      1.90     3.56     1.90      .030     .030     .030      .000   920.20    63.35
    .014821     100.      95.     100.        20       14        0       .00    64.37   127.72
```

```
**************************************************
  HEC2 RELEASE DATED NOV 76 UPDATED MAY  1984
  ERROR CORR -  01,02,03,04,05,06
  MODIFICATION -  50,51,52,53,54,55,56
  IBM-PC-XT VERSION AUGUST 1985
**************************************************


T1+     RANDOLPH DRAIN FLOOD ANALYSIS - 10/87 APPEAL  FILE:APPEAL
T2      CITY OF NORTHVILLE  JOB NO. 6800-50  50-YEAR EVENT
T3      RANDOLPH DRAIN

J1  ICHECK    INQ       NINV      IDIR      STRT      METRIC    HVINS     Q         WSEL      FQ

     -10.       3.        0.        0.   .000000       .00        .0        0.   888.050      .000

J2  NPROF     IPLOT     PRFVS     XSECV     XSECH     FN        ALLDC     IBW       CHNIM     ITRACE

     2.000     .000    -1.000      .000      .000      .000      .000      .000      .000      .000

1
 01-13-92     09:32:22                                                                          PAGE


   SECNO     DEPTH     CWSEL     CRIWS     WSELK     EG        HV        HL        OLOSS     BANK ELEV
   Q         QLOB      QCH       QROB      ALOB      ACH       AROB      VOL       TWA    LEFT/RIGHT
   TIME      VLOB      VCH       VROB      XNL       XNCH      XNR       WTN       ELMIN       SSTA
   SLOPE     XLOBL     XLCH      XLOBR     ITRIAL    IDC       ICONT     CORAR     TOPWID      ENDST


 *PROF 2

 CCHV=    .400 CEHV=    .600
 *SECNO 1.000
      1.00      5.75    888.05       .00    888.05    888.26       .21       .00       .00    883.00
      414.       75.      281.       58.       31.       67.       25.        0.        0.    883.20
       .00      2.40      4.17      2.27      .030      .030      .030      .000    882.30     17.27
    .000734       0.        0.        0.         0         0         0       .00     37.23     54.51
0
 *SECNO 2.000
      2.00      5.16    888.06       .00       .00    888.37       .31       .05       .06    883.60
      414.       70.      289.       54.       24.       58.       20.        0.        0.    883.80
       .00      2.89      5.02      2.77      .030      .030      .030      .000    882.90     21.08
    .001294       55.       52.       45.         2         0         0       .00     32.15     53.23
0
 *SECNO 2.250

 3301 HV CHANGED MORE THAN HVINS

      2.25      3.60    888.20       .00       .00    889.13       .92       .39       .37    885.80
      414.       51.      290.       73.       12.       34.       14.        0.        0.    885.10
       .01      4.39      8.66      5.12      .030      .030      .030      .000    884.60     22.36
    .006381       154.      159.      157.         1         0         0       .00     28.79     51.15
0
```

```
 *SECNO 2.500
 7185 MINIMUM SPECIFIC ENERGY
 3720 CRITICAL DEPTH ASSUMED
      2.50      3.58    889.88    889.88       .00    890.65       .77      1.00       .06    888.00
      414.       73.       296.       45.       19.       37.       12.       1.        0.     888.00
       .02      3.77      7.99      3.76      .030      .030      .030      .000    886.30    106.33
    .006335      154.      159.      156.         5         5         0       .00     45.36    151.69
0
 *SECNO 3.000
 7185 MINIMUM SPECIFIC ENERGY
 3720 CRITICAL DEPTH ASSUMED
      3.00      2.90    896.10    896.10       .00    896.55       .45      3.80       .13    894.60
      414.       120.      165.      128.       30.       24.       33.       2.        1.     894.60
       .05      4.06      7.03      3.87      .030      .030      .030      .000    893.20     29.97
    .006515      582.      637.      482.        16        14         0       .00     82.56    112.53
0
1
  01-13-92      09:32:22                                                                                PAGE


    SECNO     DEPTH     CWSEL     CRIWS     WSELK     EG        HV        HL        OLOSS     BANK ELEV
    Q         QLOB      QCH       QROB      ALOB      ACH       AROB      VOL       TWA     LEFT/RIGHT
    TIME      VLOB      VCH       VROB      XNL       XNCH      XNR       WTN       ELMIN       SSTA
    SLOPE     XLOBL     XLCH      XLOBR     ITRIAL    IDC       ICONT     CORAR     TOPWID      ENDST


 *SECNO 3.500
 7185 MINIMUM SPECIFIC ENERGY
 3720 CRITICAL DEPTH ASSUMED
      3.50      2.91    902.11    902.11       .00    902.56       .44      5.88       .00    900.80
      414.       113.      184.      117.       44.       25.       44.       3.        3.     900.50
       .09      2.55      7.48      2.65      .060      .035      .060      .000    899.20     80.67
    .011295      710.      750.      615.         9         5         0       .00    118.17    198.83
0
 *SECNO 3.750
      3.75      4.08    903.88       .00       .00    904.18       .31      1.57       .06    901.20
      414.       38.       206.      169.       24.       35.       79.       4.        3.     901.70
       .11      1.59      5.94      2.14      .060      .035      .060      .000    899.80    256.63
    .004113      195.      250.      265.         2         0         0       .00     91.09    347.72
0
 *SECNO 4.000
      4.00      4.16    904.66       .00       .00    904.71       .05       .43       .10    902.10
      414.       152.      111.      151.      134.       38.      129.       5.        4.     901.80
       .15      1.14      2.89      1.17      .060      .035      .060      .000    900.50     44.04
    .000932      230.      265.      245.         3         0         0       .00    183.74    227.78
0
 *SECNO 5.000

 3470 ENCROACHMENT STATIONS=      125.0      332.0  TYPE=      1  TARGET=      207.000
      5.00      2.80    905.40       .00    904.82    905.42       .02       .70       .01    903.10
      265.       112.       84.       70.      128.       45.       91.       11.       8.     903.60
       .37       .87      1.88       .77      .060      .035      .060      .000    902.60    137.96
    .000591      905.      915.      920.         3         0         0       .00    169.31    307.26
```

*SECNO 5.500

3470 ENCROACHMENT STATIONS= 110.0 330.0 TYPE= 1 TARGET= 220.000

5.50	3.17	905.47	.00	904.88	905.47	.00	.04	.01	902.90
265.	35.	183.	47.	109.	288.	144.	14.	9.	903.00
.51	.32	.64	.32	.060	.035	.060	.000	902.30	120.14
.000055	280.	285.	305.	2	0	0	.00	209.86	330.00

0

*SECNO 6.000

3685 20 TRIALS ATTEMPTED WSEL,CWSEL

1

01-13-92 09:32:22 PAGE

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

3693 PROBABLE MINIMUM SPECIFIC ENERGY

3720 CRITICAL DEPTH ASSUMED

3470 ENCROACHMENT STATIONS= 113.0 175.0 TYPE= 1 TARGET= 62.000

6.00	1.07	906.17	906.17	906.01	906.50	.33	.02	.20	905.10
161.	96.	62.	3.	32.	10.	2.	15.	9.	905.30
.52	3.03	6.42	2.12	.060	.035	.060	.000	905.10	113.00
.023912	160.	160.	170.	20	22	0	.00	62.00	175.00

0

*SECNO 6.900

7185 MINIMUM SPECIFIC ENERGY

3720 CRITICAL DEPTH ASSUMED

3470 ENCROACHMENT STATIONS= .2 31.8 TYPE= 1 TARGET= 31.600

6.90	2.43	907.73	907.73	907.29	908.55	.82	1.29	.29	905.50
161.	14.	123.	24.	5.	15.	8.	15.	10.	905.50
.53	2.73	8.15	2.86	.060	.035	.060	.000	905.30	4.41
.011606	80.	80.	80.	2	17	0	.00	19.83	24.24

0

*SECNO 6.940

3470 ENCROACHMENT STATIONS= 75.0 208.0 TYPE= 1 TARGET= 133.000

6.94	3.11	908.49	.00	907.97	908.86	.37	.13	.18	906.58
161.	11.	140.	10.	7.	27.	7.	15.	10.	906.48
.53	1.51	5.18	1.56	.060	.035	.060	.000	905.38	87.65
.004149	20.	20.	20.	5	0	0	.00	24.04	111.70

0

*SECNO 6.950

3470 ENCROACHMENT STATIONS= 75.0 208.0 TYPE= 1 TARGET= 133.000

6.95	3.14	908.67	.00	908.16	909.02	.36	.16	.00	906.73
161.	11.	140.	11.	7.	27.	7.	15.	10.	906.63
.53	1.50	5.11	1.54	.060	.035	.060	.000	905.53	87.54
.003978	40.	40.	40.	2	0	0	.00	24.26	111.80

0

*SECNO 7.000

3470 ENCROACHMENT STATIONS= 75.0 208.0 TYPE= 1 TARGET= 133.000

7.00	3.13	909.56	.00	909.07	909.92	.36	.89	.00	907.63
161.	11.	139.	11.	7.	27.	7.	15.	10.	907.53
.54	1.50	5.11	1.54	.060	.035	.060	.000	906.43	87.54
.003973	225.	225.	225.	1	0	0	.00	24.26	111.80

0

1

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

*SECNO 8.000

WATER EL=X5 CARD= 914.410

3470 ENCROACHMENT STATIONS= 1.0 79.0 TYPE= 1 TARGET= 78.000

8.00	5.31	914.41	.00	913.48	914.45	.04	.48	.13	917.40
161.	0.	161.	0.	0.	103.	0.	16.	10.	916.70
.65	.00	1.57	.00	.060	.035	.060	.000	909.10	13.60
.000345	578.	578.	578.	0	0	0	.00	34.72	48.32

0

*SECNO 9.000

3470 ENCROACHMENT STATIONS= 1.0 161.0 TYPE= 1 TARGET= 160.000

9.00	4.28	914.48	.00	913.56	914.51	.03	.06	.00	913.50
106.	0.	106.	0.	1.	74.	2.	16.	10.	913.50
.68	.21	1.43	.25	.060	.035	.060	.000	910.20	69.47
.000281	185.	185.	185.	2	0	0	.00	29.12	98.59

0

CCHV= .800 CEHV= .900

*SECNO 10.000

3685 20 TRIALS ATTEMPTED WSEL,CWSEL

3693 PROBABLE MINIMUM SPECIFIC ENERGY

3720 CRITICAL DEPTH ASSUMED

3470 ENCROACHMENT STATIONS= 1.0 161.0 TYPE= 1 TARGET= 160.000

10.00	1.21	915.71	915.71	915.54	916.13	.42	.01	.35	915.50
106.	0.	106.	0.	0.	20.	0.	17.	10.	915.50
.68	.06	5.21	1.32	.030	.030	.030	.000	914.50	70.14
.014696	9.	9.	9.	20	17	0	.00	26.33	96.47

0

CCHV= .400 CEHV= .600

*SECNO 11.000

3470 ENCROACHMENT STATIONS= 1.0 108.0 TYPE= 1 TARGET= 107.000

11.00	2.33	917.43	.00	917.14	917.76	.32	1.59	.04	918.80
106.	0.	106.	0.	0.	23.	0.	17.	10.	918.00
.69	.00	4.57	.00	.030	.030	.030	.000	915.10	41.79
.005927	179.	179.	179.	3	0	0	.00	16.84	58.64

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	KNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

*SECNO 11.900

11.90	2.68	918.78	.00	918.36	918.95	.16	1.12	.06	920.00
106.	0.	106.	0.	0.	33.	0.	17.	10.	919.40
.72	.00	3.26	.00	.030	.030	.030	.000	916.10	20.15
.002577	300.	300.	300.	4	0	0	.00	21.26	41.41

0

*SECNO 12.000

3685 20 TRIALS ATTEMPTED WSEL,CWSEL

3693 PROBABLE MINIMUM SPECIFIC ENERGY

3720 CRITICAL DEPTH ASSUMED

3470 ENCROACHMENT STATIONS= 1.0 309.0 TYPE= 1 TARGET= 308.000

12.00	.66	920.86	920.86	920.75	921.08	.22	.48	.04	920.40
106.	4.	90.	12.	2.	22.	5.	17.	11.	920.40
.73	2.22	4.02	2.22	.030	.030	.030	.000	920.20	61.39
.014286	100.	95.	100.	20	11	0	.00	71.58	132.96

0

1

THIS RUN EXECUTED 01-13-92

****

HEC2 RELEASE DATED NOV 76 UPDATED MAY 1984

ERROR CORR - 01,02,03,04,05,06

MODIFICATION - 50,51,52,53,54,55,56

IBM-PC-XT VERSION AUGUST 1985

****

```
T1      RANDOLPH DRAIN FLOOD ANALYSIS - 10/87 APPEAL  FILE:APPEAL
T2      CITY OF NORTHVILLE  JOB NO. 6800-50  100-YEAR EVENT
T3      RANDOLPH DRAIN

J1  ICHECK    INQ       NINV      IDIR      STRT      METRIC    HVINS     Q         WSEL      FQ

     -10.       4.        0.        0.   .000000       .00        .0        0.   888.800      .000

J2  NPROF     IPLOT     PRFVS     XSECV     XSECH     FN        ALLDC     IBW       CHNIM     ITRACE

     3.000      .000    -1.000      .000      .000      .000      .000      .000      .000      .000

1
 01-13-92     09:32:22                                                                          PAGE

   SECNO     DEPTH     CWSEL     CRIWS     WSELK     EG        HV        HL        OLOSS     BANK ELEV
   Q         QLOB      QCH       QROB      ALOB      ACH       AROB      VOL       TWA     LEFT/RIGHT
   TIME      VLOB      VCH       VROB      XNL       XNCH      XNR       WTN       ELMIN       SSTA
   SLOPE     XLOBL     XLCH      XLOBR     ITRIAL    IDC       ICONT     CORAR     TOPWID      ENDST


 *PROF 3

 CCHV=    .400 CEHV=    .600
 *SECNO 1.000
      1.00      6.50    888.80       .00    888.80    888.99       .19       .00       .00    883.00
      494.       108.      310.       76.       48.       76.       34.        0.        0.    883.20
       .00      2.27      4.06      2.24      .030      .030      .030      .000    882.30      3.64
   .000589        0.        0.        0.         0         0         0       .00     52.50     56.13
0
 *SECNO 2.000
      2.00      5.90    888.80       .00       .00    889.08       .28       .04       .06    883.60
      494.       97.      324.       73.       34.       67.       27.        0.        0.    883.80
       .00      2.86      4.87      2.71      .030      .030      .030      .000    882.90     14.51
   .001002        55.       52.       45.         2         0         0       .00     40.33     54.84
0
 *SECNO 2.250
      2.25      4.32    888.92       .00       .00    889.60       .68       .28       .24    885.80
      494.       81.      309.      104.       20.       41.       22.        1.        0.    885.10
       .01      4.12      7.60      4.81      .030      .030      .030      .000    884.60     17.89
   .003803        154.      159.      157.         0         0         0       .00     35.75     53.64
0
 *SECNO 2.500
 7185 MINIMUM SPECIFIC ENERGY
 3720 CRITICAL DEPTH ASSUMED
      2.50      3.85    890.15    890.15       .00    890.91       .77       .74       .05    888.00
      494.       105.      328.       61.       26.       40.       16.        1.        0.    888.00
       .02      4.11      8.14      3.96      .030      .030      .030      .000    886.30    100.98
   .005890        154.      159.      156.         4        15         0       .00     52.51     153.49
```

```
*SECNO 3.000
7185 MINIMUM SPECIFIC ENERGY
3720 CRITICAL DEPTH ASSUMED
     3.00     3.05   896.25   896.25      .00   896.73      .47     3.62      .12   894.60
     494.     149.     181.     164.      35.      25.      40.      2.       1.    894.60
      .05     4.27     7.27     4.14     .030     .030     .030     .000   893.20    27.42
   .006444     582.     637.     482.       16       14        0      .00    88.30   115.72
0
1
 01-13-92     09:32:22                                                                    PAGE

   SECNO     DEPTH     CWSEL     CRIWS     WSELK     EG        HV        HL        OLOSS     BANK ELEV
   Q         QLOB      QCH       QROB      ALOB      ACH       AROB      VOL       TWA     LEFT/RIGHT
   TIME      VLOB      VCH       VROB      XNL       XNCH      XNR       WTN       ELMIN       SSTA
   SLOPE     XLOBL     XLCH      XLOBR     ITRIAL    IDC       ICONT     CORAR     TOPWID      ENDST


*SECNO 3.500
     3.50     3.03   902.23   902.22      .00   902.72      .49     5.98      .01   900.80
     494.     142.     207.     146.      51.      26.      50.      4.       3.    900.50
      .09     2.79     7.99     2.89     .060     .035     .060     .000   899.20    77.76
   .012028     710.     750.     615.       11        5        0      .00   123.98   201.74
0
*SECNO 3.750
     3.75     4.28   904.08      .00      .00   904.40      .32     1.62      .07   901.20
     494.      53.     230.     211.      32.      37.      92.      5.       4.    901.70
      .10     1.64     6.24     2.30     .060     .035     .060     .000   899.80   200.41
   .004189     195.     250.     265.        1        0        0      .00   151.17   351.58
0
*SECNO 4.000
     4.00     4.39   904.89      .00      .00   904.94      .05      .43      .11   902.10
     494.     187.     124.     183.     155.      41.     148.      6.       5.    901.80
      .14     1.20     3.03     1.24     .060     .035     .060     .000   900.50    36.55
   .000940     230.     265.     245.        3        0        0      .00   195.96   232.51
0
*SECNO 5.000

3470 ENCROACHMENT STATIONS=     125.0     332.0  TYPE=     1  TARGET=     207.000
     5.00     3.03   905.63      .00   904.82   905.66      .03      .70      .01   903.10
     323.     136.      97.      90.     145.      49.     109.      13.      8.    903.60
      .35      .94     1.99      .83     .060     .035     .060     .000   902.60   136.82
   .000589     905.     915.     920.        3        0        0      .00   177.54   314.36
0
*SECNO 5.500

3470 ENCROACHMENT STATIONS=     110.0     330.0  TYPE=     1  TARGET=     220.000
     5.50     3.40   905.70      .00   904.88   905.70      .01      .04      .01   902.90
     323.      44.     222.      58.     121.     311.     158.      16.      10.    903.00
      .48      .36      .71      .36     .060     .035     .060     .000   902.30   119.21
   .000062     280.     285.     305.        2        0        0      .00   210.79   330.00
```

*SECNO 6.000

3685 20 TRIALS ATTEMPTED WSEL,CWSEL

3693 PROBABLE MINIMUM SPECIFIC ENERGY

3720 CRITICAL DEPTH ASSUMED

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

3470 ENCROACHMENT STATIONS= 113.0 175.0 TYPE= 1 TARGET= 62.000

6.00	1.12	906.22	906.22	906.01	906.57	.35	.02	.21	905.10
180.	108.	68.	4.	34.	10.	2.	17.	10.	905.30
.49	3.17	6.64	2.23	.060	.035	.060	.000	905.10	113.00
.023822	160.	160.	170.	20	17	0	.00	62.00	175.00

0

*SECNO 6.900

7185 MINIMUM SPECIFIC ENERGY

3720 CRITICAL DEPTH ASSUMED

3470 ENCROACHMENT STATIONS= .2 31.8 TYPE= 1 TARGET= 31.600

6.90	2.58	907.88	907.88	907.29	908.73	.85	1.27	.30	905.50
180.	17.	134.	29.	6.	16.	10.	17.	10.	905.50
.50	2.81	8.39	2.97	.060	.035	.060	.000	905.30	3.89
.011339	80.	80.	80.	2	17	0	.00	20.87	24.75

0

*SECNO 6.940

3470 ENCROACHMENT STATIONS= 75.0 208.0 TYPE= 1 TARGET= 133.000

6.94	3.27	908.65	.00	907.97	909.04	.39	.13	.18	906.58
180.	13.	154.	13.	8.	29.	8.	17.	10.	906.48
.50	1.59	5.37	1.63	.060	.035	.060	.000	905.38	87.02
.004121	20.	20.	20.	5	0	0	.00	25.23	112.25

0

*SECNO 6.950

3470 ENCROACHMENT STATIONS= 75.0 208.0 TYPE= 1 TARGET= 133.000

6.95	3.30	908.83	.00	908.16	909.21	.38	.16	.00	906.73
180.	13.	154.	13.	8.	29.	8.	17.	10.	906.63
.50	1.58	5.31	1.62	.060	.035	.060	.000	905.53	86.92
.003975	40.	40.	40.	2	0	0	.00	25.42	112.34

0

*SECNO 7.000

3470 ENCROACHMENT STATIONS= 75.0 208.0 TYPE= 1 TARGET= 133.000

7.00	3.29	909.72	.00	909.07	910.10	.38	.89	.00	907.63
180.	13.	154.	13.	8.	29.	8.	17.	10.	907.53
.51	1.58	5.31	1.62	.060	.035	.060	.000	906.43	86.92
.003979	225.	225.	225.	1	0	0	.00	25.42	112.34

0

1

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

*SECNO 8.000
WATER EL=X5 CARD= 915.110

915.25

3470 ENCROACHMENT STATIONS= 1.0 79.0 TYPE= 1 TARGET= 78.000

8.00	6.01	915.11	.00	913.48	915.14	.03	.35	.14	917.40
180.	0.	180.	0.	0.	128.	0.	18.	11.	916.70
.63	.00	1.40	.00	.060	.035	.060	.000	909.10	11.59
.000237	578.	578.	578.	0	0	0	.00	38.78	50.36

Ground ~ 919

0
*SECNO 9.000

3470 ENCROACHMENT STATIONS= 1.0 161.0 TYPE= 1 TARGET= 160.000

9.00	4.95	915.15	.00	913.56	915.19	.04	.04	.00	913.50
139.	0.	137.	1.	1.	91.	4.	19.	11.	913.50
.66	.27	1.51	.33	.060	.035	.060	.000	910.20	68.75
.000240	185.	185.	185.	2	0	0	.00	31.95	100.71

0
CCHV= .800 CEHV= .900
*SECNO 10.000
3685 20 TRIALS ATTEMPTED WSEL,CWSEL
3693 PROBABLE MINIMUM SPECIFIC ENERGY
3720 CRITICAL DEPTH ASSUMED

3470 ENCROACHMENT STATIONS= 1.0 161.0 TYPE= 1 TARGET= 160.000

10.00	1.39	915.89	915.89	915.54	916.37	.48	.01	.40	915.50
139.	0.	138.	1.	0.	25.	0.	19.	11.	915.50
.66	1.72	5.58	1.86	.030	.030	.030	.000	914.50	69.83
.012958	9.	9.	9.	20	14	0	.00	27.44	97.27

0
CCHV= .400 CEHV= .600
*SECNO 11.000

3470 ENCROACHMENT STATIONS= 1.0 108.0 TYPE= 1 TARGET= 107.000

11.00	2.54	917.64	.00	917.14	918.06	.42	1.67	.02	918.80
139.	0.	139.	0.	0.	27.	0.	19.	11.	918.00
.67	.00	5.22	.00	.030	.030	.030	.000	915.10	41.10
.007027	179.	179.	179.	2	0	0	.00	18.01	59.11

0
1

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

```
 *SECNO 11.900
    11.90     3.04   919.14     .00   918.36   919.32     .18    1.16     .10   920.00
     139.       0.     139.      0.       0.     41.       0.     19.      11.    919.40
      .70      .00     3.41     .00     .030     .030     .030    .000   916.10    18.61
   .002435     300.     300.     300.        3        0        0     .00    23.73    42.35
0
 *SECNO 12.000
 3685 20 TRIALS ATTEMPTED WSEL,CWSEL
 3693 PROBABLE MINIMUM SPECIFIC ENERGY
 3720 CRITICAL DEPTH ASSUMED

 3470 ENCROACHMENT STATIONS=       1.0     309.0  TYPE=     1  TARGET=     308.000
    12.00      .77   920.97   920.97   920.75   921.20      .23      .44      .03   920.40
     139.       7.     111.      20.       3.      27.       8.      19.      11.    920.40
      .70     2.35     4.16     2.51     .030     .030     .030     .000   920.20    59.32
   .012070     100.      95.     100.       20       11        0      .00    79.46   138.78
0
1
  01-13-92     09:32:22                                                                PAGE



                                                                  THIS RUN EXECUTED 01-13-92

 **************************************************
   HEC2 RELEASE DATED NOV 76 UPDATED MAY  1984
   ERROR CORR -  01,02,03,04,05,06
   MODIFICATION -  50,51,52,53,54,55,56
   IBM-PC-XT VERSION AUGUST 1985
 **************************************************
```

```
T1      RANDOLPH DRAIN FLOOD ANALYSIS - 10/87 APPEAL  FILE:APPEAL
T2      CITY OF NORTHVILLE  JOB NO. 6800-50  500-YEAR EVENT
T3      RANDOLPH DRAIN

J1  ICHECK    INQ       NINV      IDIR      STRT      METRIC    HVINS     Q         WSEL      FQ

     -10.       5.        0.        0.   .000000       .00        .0        0.   891.090      .000

J2  NPROF     IPLOT     PRFVS     XSECV     XSECH     FN        ALLDC     IBW       CHNIM     ITRACE

     15.000     .000    -1.000     .000      .000      .000      .000      .000      .000      .000

1
 01-13-92     09:32:22                                                                          PAGE


   SECNO     DEPTH     CWSEL     CRIWS     WSELK     EG        HV        HL        OLOSS     BANK ELEV
   Q         QLOB      QCH       QROB      ALOB      ACH       AROB      VOL       TWA     LEFT/RIGHT
   TIME      VLOB      VCH       VROB      XNL       XNCH      XNR       WTN       ELMIN       SSTA
   SLOPE     XLOBL     XLCH      XLOBR     ITRIAL    IDC       ICONT     CORAR     TOPWID      ENDST


*PROF 4

CCHV=    .400 CEHV=    .600
*SECNO 1.000
3280 CROSS SECTION      1.00 EXTENDED      2.09 FEET

     1.00      8.79   891.09      .00   891.09   891.16      .07      .00      .00   883.00
     609.       193.     278.      138.      120.      104.       96.       0.       0.    883.20
      .00      1.60     2.68      1.43      .030      .030      .030      .000   882.30      .00
   .000170       0.       0.       0.         0         0         0      .00    79.00    79.00
0
*SECNO 2.000
3280 CROSS SECTION      2.00 EXTENDED      1.50 FEET

     2.00      8.19   891.09      .00      .00   891.19      .10      .01      .02   883.60
     609.       187.     296.      126.      102.       94.       76.       0.       0.    883.80
      .01      1.84     3.15      1.67      .030      .030      .030      .000   882.90      .00
   .000264        55.       52.       45.         0         0         0      .00    79.00    79.00
0
*SECNO 2.250
3280 CROSS SECTION      2.25 EXTENDED      1.12 FEET

     2.25      6.52   891.12      .00      .00   891.29      .16      .06      .04   885.80
     609.       193.     254.      162.       80.       63.       62.       1.       0.    885.10
      .02      2.40     4.06      2.60      .030      .030      .030      .000   884.60      .00
   .000608       154.       159.       157.         0         0         0      .00    71.18    71.18
0
*SECNO 2.500
     2.50      4.92   891.22      .00      .00   891.53      .30      .16      .08   888.00
     609.       211.     295.      103.       69.       53.       35.       2.       1.    888.00
      .03      3.03     5.55      2.94      .030      .030      .030      .000   886.30    71.36
   .001890       154.       159.       156.         2         0         0      .00    89.39   160.76
0
```

```
*SECNO 3.000
3685 20 TRIALS ATTEMPTED WSEL,CWSEL
3693 PROBABLE MINIMUM SPECIFIC ENERGY
3720 CRITICAL DEPTH ASSUMED
     3.00      3.24    896.44    896.44      .00    896.95      .51     1.84      .12   894.60
     609.       191.      202.      215.      42.      27.      48.       4.       2.   894.60
      .06      4.59      7.61      4.48     .030     .030     .030     .000   893.20    24.57
   .006492      582.      637.      482.       20       18        0      .00    94.99   119.57
0
1
 01-13-92     09:32:22                                                                    PAGE

   SECNO     DEPTH     CWSEL     CRIWS     WSELK     EG        HV        HL        OLOSS    BANK ELEV
   Q         QLOB      QCH       QROB      ALOB      ACH       AROB      VOL       TWA    LEFT/RIGHT
   TIME      VLOB      VCH       VROB      XNL       XNCH      XNR       WTN       ELMIN      SSTA
   SLOPE     XLOBL     XLCH      XLOBR     ITRIAL    IDC       ICONT     CORAR     TOPWID     ENDST


*SECNO 3.500
     3.50      3.21    902.41    902.37      .00    902.92      .51     5.97      .00   900.80
     609.       186.      234.      189.      62.      28.      61.       6.       4.   900.50
      .10      3.02      8.38      3.11     .060     .035     .060     .000   899.20    73.20
   .011975      710.      750.      615.       11        5        0      .00   133.10   206.30
0
*SECNO 3.750
     3.75      4.51    904.31    903.76      .00    904.64      .34     1.65      .07   901.20
     609.       85.      259.      265.      65.      39.      105.       7.       5.   901.70
      .11      1.31      6.63      2.52     .060     .035     .060     .000   899.80    60.77
   .004375      195.      250.      265.        4       12        0      .00   294.86   355.64
0
*SECNO 4.000
     4.00      4.65    905.15      .00      .00    905.21      .06      .45      .11   902.10
     609.       236.      142.      230.      181.      44.      171.       8.       6.   901.80
      .15      1.30      3.26      1.35     .060     .035     .060     .000   900.50    28.09
   .000994      230.      265.      245.        3        0        0      .00   209.76   237.85
0
*SECNO 5.000
     5.00      3.31    905.91      .00      .00    905.94      .03      .73      .01   903.10
     407.       172.      115.      120.      167.      54.      133.       16.      10.   903.60
      .35      1.03      2.14      .90      .060     .035     .060     .000   902.60   135.40
   .000596      905.      915.      920.        3        0        0      .00   187.84   323.24
0
*SECNO 5.500

3470 ENCROACHMENT STATIONS=     110.0      330.0  TYPE=      1  TARGET=      220.000
     5.50      3.69    905.99      .00    904.88    906.00      .01      .05      .01   902.90
     407.       56.      277.       74.      136.      340.      176.       20.      12.   903.00
      .46       .42       .81       .42      .060      .035      .060      .000   902.30   118.04
   .000072      280.      285.      305.        2        0        0      .00   211.96   330.00
0
*SECNO 6.000
3685 20 TRIALS ATTEMPTED WSEL,CWSEL
3693 PROBABLE MINIMUM SPECIFIC ENERGY
3720 CRITICAL DEPTH ASSUMED
```

3470 ENCROACHMENT STATIONS= 113.0 175.0 TYPE= 1 TARGET= 62.000

1

01-13-92 09:32:22 PAGE

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST
6.00	1.25	906.35	906.35	906.01	906.77	.42	.03	.25	905.10
232.	142.	84.	7.	40.	11.	3.	21.	12.	905.30
.47	3.54	7.28	2.57	.060	.035	.060	.000	905.10	113.00
.024442	160.	160.	170.	20	22	0	.00	62.00	175.00

0

*SECNO 6.900

3301 HV CHANGED MORE THAN HVINS

7185 MINIMUM SPECIFIC ENERGY

3720 CRITICAL DEPTH ASSUMED

3470 ENCROACHMENT STATIONS= .2 31.8 TYPE= 1 TARGET= 31.600

6.90	2.94	908.24	908.24	907.29	909.18	.94	1.26	.31	905.50
232.	25.	165.	42.	8.	18.	13.	21.	12.	905.50
.47	3.03	9.02	3.24	.060	.035	.060	.000	905.30	2.65
.011021	80.	80.	80.	2	17	0	.00	23.33	25.98

0

*SECNO 6.940

3301 HV CHANGED MORE THAN HVINS

3470 ENCROACHMENT STATIONS= 75.0 208.0 TYPE= 1 TARGET= 133.000

6.94	3.69	909.07	.00	907.97	909.51	.44	.12	.20	906.58
232.	21.	190.	20.	12.	33.	11.	21.	12.	906.48
.48	1.78	5.81	1.81	.060	.035	.060	.000	905.38	85.42
.004014	20.	20.	20.	5	0	0	.00	28.22	113.64

0

*SECNO 6.950

3470 ENCROACHMENT STATIONS= 75.0 208.0 TYPE= 1 TARGET= 133.000

6.95	3.70	909.23	.00	908.16	909.67	.43	.16	.00	906.73
232.	21.	190.	20.	12.	33.	11.	21.	12.	906.63
.48	1.77	5.77	1.80	.060	.035	.060	.000	905.53	85.36
.003939	40.	40.	40.	2	0	0	.00	28.33	113.69

0

*SECNO 7.000

1

01-13-92 09:32:22 PAGE

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

3470 ENCROACHMENT STATIONS= 75.0 208.0 TYPE= 1 TARGET= 133.000

7.00	3.69	910.12	.00	909.07	910.56	.44	.89	.00	907.63
232.	21.	190.	20.	12.	33.	11.	21.	12.	907.53
.49	1.77	5.79	1.81	.060	.035	.060	.000	906.43	85.39
.003978	225.	225.	225.	0	0	0	.00	28.27	113.66

0

*SECNO 8.000

WATER EL=X5 CARD= 917.430

3470 ENCROACHMENT STATIONS= 1.0 79.0 TYPE= 1 TARGET= 78.000

8.00	8.33	917.43	.00	913.48	917.45	.02	.14	.17	917.40
232.	0.	232.	0.	0.	233.	2.	23.	13.	916.70
.65	.00	.99	.11	.060	.035	.060	.000	909.10	4.50
.000076	578.	578.	578.	0	0	0	.00	58.75	63.25

0

*SECNO 9.000

3470 ENCROACHMENT STATIONS= 1.0 161.0 TYPE= 1 TARGET= 160.000

9.00	7.24	917.44	.00	913.56	917.47	.03	.02	.01	913.50
207.	3.	195.	9.	8.	148.	24.	24.	13.	913.50
.69	.31	1.32	.37	.060	.035	.060	.000	910.20	66.33
.000095	185.	185.	185.	2	0	0	.00	41.60	107.93

0

CCHV= .800 CEHV= .900

*SECNO 10.000

3470 ENCROACHMENT STATIONS= 1.0 161.0 TYPE= 1 TARGET= 160.000

10.00	2.93	917.43	.00	915.54	917.56	.13	.00	.09	915.50
207.	5.	189.	13.	3.	64.	9.	24.	13.	915.50
.69	1.43	2.98	1.55	.030	.030	.030	.000	914.50	67.16
.001045	9.	9.	9.	0	0	0	.00	37.19	104.35

0

CCHV= .400 CEHV= .600

*SECNO 11.000

3301 HV CHANGED MORE THAN HVINS

7185 MINIMUM SPECIFIC ENERGY

1

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

```
 3720 CRITICAL DEPTH ASSUMED

 3470 ENCROACHMENT STATIONS=       1.0     108.0  TYPE=     1  TARGET=     107.000
     11.00      2.66    917.76    917.76    917.14    918.55       .79       .45       .40    918.80
      207.        0.      207.        0.        0.       29.        0.       24.       13.    918.00
       .70       .00      7.13       .00      .030      .030      .030      .000    915.10     40.64
    .012350      179.      179.      179.         0        12         0       .00     18.79     59.43
0
 *SECNO 11.900

 3301 HV CHANGED MORE THAN HVINS

     11.90      3.71    919.81       .00    918.36    920.00       .19      1.21       .24    920.00
      207.        0.      204.        3.        0.       58.        3.       25.       13.    919.40
       .72       .00      3.54       .76      .030      .030      .030      .000    916.10     15.81
    .001970      300.      300.      300.         4         0         0       .00     44.21     60.02
0
 *SECNO 12.000
 3685 20 TRIALS ATTEMPTED WSEL,CWSEL
 3693 PROBABLE MINIMUM SPECIFIC ENERGY
 3720 CRITICAL DEPTH ASSUMED

 3470 ENCROACHMENT STATIONS=       1.0     309.0  TYPE=     1  TARGET=     308.000
     12.00       .92    921.12    921.12    920.75    921.41       .29       .38       .06    920.40
      207.        13.      154.       40.        5.       33.       13.       25.       14.    920.40
       .73      2.70      4.68      3.03      .030      .030      .030      .000    920.20     56.45
    .011569      100.       95.      100.        20        11         0       .00     90.70    147.15
0
1
   01-13-92     09:32:22                                                                          PAGE


                                                                                  THIS RUN EXECUTED 01-13-92

 **************************************************
   HEC2 RELEASE DATED NOV 76 UPDATED MAY  1984
   ERROR CORR -  01,02,03,04,05,06
   MODIFICATION -  50,51,52,53,54,55,56
   IBM-PC-XT VERSION AUGUST 1985
 **************************************************
```

NOTE- ASTERISK (*) AT LEFT OF CROSS-SECTION NUMBER INDICATES MESSAGE IN SUMMARY OF ERRORS LIST

RANDOLPH DRAIN

SUMMARY PRINTOUT TABLE 150

	SECNO	XLCH	ELTRD	ELLC	ELMIN	Q	CWSEL	CRIWS	EG	10K*S	VCH	AREA	.01K
	1.000	.00	.00	.00	882.30	236.00	886.34	.00	886.54	10.63	3.94	71.22	72.37
	1.000	.00	.00	.00	882.30	414.00	888.05	.00	888.26	7.34	4.17	124.29	152.84
	1.000	.00	.00	.00	882.30	494.00	888.80	.00	888.99	5.89	4.06	157.94	203.63
	1.000	.00	.00	.00	882.30	609.00	891.09	.00	891.16	1.70	2.68	320.71	466.45
	2.000	52.00	.00	.00	882.90	236.00	886.36	.00	886.71	23.98	5.11	53.66	48.19
	2.000	52.00	.00	.00	882.90	414.00	888.06	.00	888.37	12.94	5.02	101.60	115.10
	2.000	52.00	.00	.00	882.90	494.00	888.80	.00	889.08	10.02	4.87	127.48	156.08
	2.000	52.00	.00	.00	882.90	609.00	891.09	.00	891.19	2.64	3.15	271.29	374.89
*	2.250	159.00	.00	.00	884.60	236.00	887.25	887.25	888.09	83.46	7.91	35.01	25.83
	2.250	159.00	.00	.00	884.60	414.00	888.20	.00	889.13	63.81	8.66	59.36	51.83
	2.250	159.00	.00	.00	884.60	494.00	888.92	.00	889.60	38.03	7.60	81.93	80.11
	2.250	159.00	.00	.00	884.60	609.00	891.12	.00	891.29	6.08	4.06	205.45	246.93
*	2.500	159.00	.00	.00	886.30	236.00	889.16	889.16	889.85	71.36	7.10	40.30	27.94
*	2.500	159.00	.00	.00	886.30	414.00	889.88	889.88	890.65	63.35	7.99	68.41	52.01
*	2.500	159.00	.00	.00	886.30	494.00	890.15	890.15	890.91	58.90	8.14	81.31	64.37
	2.500	159.00	.00	.00	886.30	609.00	891.22	.00	891.53	18.90	5.55	157.72	140.08
*	3.000	637.00	.00	.00	893.20	236.00	895.68	895.68	896.09	68.24	6.39	54.54	28.57
*	3.000	637.00	.00	.00	893.20	414.00	896.10	896.10	896.55	65.15	7.03	86.34	51.29
*	3.000	637.00	.00	.00	893.20	494.00	896.25	896.25	896.73	64.44	7.27	99.42	61.54
*	3.000	637.00	.00	.00	893.20	609.00	896.44	896.44	896.95	64.92	7.61	116.34	75.58
*	3.500	750.00	.00	.00	899.20	236.00	901.75	901.75	902.12	101.95	6.32	73.67	23.37
*	3.500	750.00	.00	.00	899.20	414.00	902.11	902.11	902.56	112.95	7.48	112.95	38.95
	3.500	750.00	.00	.00	899.20	494.00	902.23	902.22	902.72	120.28	7.99	127.02	45.04
	3.500	750.00	.00	.00	899.20	609.00	902.41	902.37	902.92	119.75	8.38	150.47	55.65

	3.750	250.00	.00	.00	899.80	236.00	903.31	.00	903.54	34.21	4.82	91.35	40.35
	3.750	250.00	.00	.00	899.80	414.00	903.88	.00	904.18	41.13	5.94	137.86	64.55
	3.750	250.00	.00	.00	899.80	494.00	904.08	.00	904.40	41.89	6.24	160.54	76.33
	3.750	250.00	.00	.00	899.80	609.00	904.31	903.76	904.64	43.75	6.63	209.39	92.07
	SECNO	XLCH	ELTRD	ELLC	ELMIN	Q	CWSEL	CRIWS	EG	10K*S	VCH	AREA	.01K
	4.000	265.00	.00	.00	900.50	236.00	903.99	.00	904.03	10.03	2.60	189.68	74.51
	4.000	265.00	.00	.00	900.50	414.00	904.66	.00	904.71	9.32	2.89	301.20	135.60
	4.000	265.00	.00	.00	900.50	494.00	904.89	.00	904.94	9.40	3.03	344.29	161.13
	4.000	265.00	.00	.00	900.50	609.00	905.15	.00	905.21	9.94	3.26	396.29	193.12
	5.000	915.00	.00	.00	902.60	159.00	904.82	.00	904.84	7.32	1.75	170.62	58.77
	5.000	915.00	.00	.00	902.60	265.00	905.40	.00	905.42	5.91	1.88	263.08	109.00
	5.000	915.00	.00	.00	902.60	323.00	905.63	.00	905.66	5.89	1.99	302.49	133.14
	5.000	915.00	.00	.00	902.60	407.00	905.91	.00	905.94	5.96	2.14	354.38	166.70
	5.500	285.00	.00	.00	902.30	159.00	904.88	.00	904.88	.44	.49	418.86	238.42
	5.500	285.00	.00	.00	902.30	265.00	905.47	.00	905.47	.55	.64	540.68	357.17
	5.500	285.00	.00	.00	902.30	323.00	905.70	.00	905.70	.62	.71	589.81	410.06
	5.500	285.00	.00	.00	902.30	407.00	905.99	.00	906.00	.72	.81	651.63	480.44
*	6.000	160.00	.00	.00	905.10	110.00	906.01	906.01	906.28	235.03	5.66	33.24	7.18
*	6.000	160.00	.00	.00	905.10	161.00	906.17	906.17	906.50	239.12	6.42	42.84	10.41
*	6.000	160.00	.00	.00	905.10	180.00	906.22	906.22	906.57	238.22	6.64	46.20	11.66
*	6.000	160.00	.00	.00	905.10	232.00	906.35	906.35	906.77	244.42	7.28	54.10	14.84
*	6.900	80.00	.00	.00	905.30	110.00	907.29	907.29	907.98	122.54	7.31	20.53	9.94
*	6.900	80.00	.00	.00	905.30	161.00	907.73	907.73	908.55	116.06	8.15	28.67	14.94
*	6.900	80.00	.00	.00	905.30	180.00	907.88	907.88	908.73	113.39	8.39	31.74	16.90
*	6.900	80.00	.00	.00	905.30	232.00	908.24	908.24	909.18	110.21	9.02	39.63	22.10
	6.940	20.00	.00	.00	905.38	110.00	907.97	.00	908.27	44.16	4.63	29.08	16.55
	6.940	20.00	.00	.00	905.38	161.00	908.49	.00	908.86	41.49	5.18	40.75	25.00
	6.940	20.00	.00	.00	905.38	180.00	908.65	.00	909.04	41.21	5.37	44.81	28.04
	6.940	20.00	.00	.00	905.38	232.00	909.07	.00	909.51	40.14	5.81	55.94	36.62
	6.950	40.00	.00	.00	905.53	110.00	908.16	.00	908.45	40.52	4.50	30.12	17.28
	6.950	40.00	.00	.00	905.53	161.00	908.67	.00	909.02	39.78	5.11	41.46	25.53
	6.950	40.00	.00	.00	905.53	180.00	908.83	.00	909.21	39.75	5.31	45.49	28.55
	6.950	40.00	.00	.00	905.53	232.00	909.23	.00	909.67	39.39	5.77	56.39	36.97

	7.000	225.00	.00	.00	906.43	110.00	909.07	.00	909.36	40.06	4.48	30.25	17.38
	7.000	225.00	.00	.00	906.43	161.00	909.56	.00	909.92	39.73	5.11	41.48	25.54
	7.000	225.00	.00	.00	906.43	180.00	909.72	.00	910.10	39.79	5.31	45.46	28.54
	7.000	225.00	.00	.00	906.43	232.00	910.12	.00	910.56	39.78	5.79	56.16	36.79
*	8.000	578.00	.00	.00	909.10	110.00	913.48	.00	913.52	4.02	1.51	72.98	54.86
*	8.000	578.00	.00	.00	909.10	161.00	914.41	.00	914.45	3.45	1.57	102.77	86.72
*	8.000	578.00	.00	.00	909.10	180.00	915.11	.00	915.14	2.37	1.40	128.49	116.89
*	8.000	578.00	.00	.00	909.10	232.00	917.43	.00	917.45	.76	.99	235.63	266.82
	9.000	185.00	.00	.00	910.20	73.00	913.56	.00	913.60	4.61	1.43	51.11	33.99
	9.000	185.00	.00	.00	910.20	106.00	914.48	.00	914.51	2.81	1.43	75.97	63.23
	9.000	185.00	.00	.00	910.20	139.00	915.15	.00	915.19	2.40	1.51	96.50	89.70
	9.000	185.00	.00	.00	910.20	207.00	917.44	.00	917.47	.95	1.32	180.75	211.93
	SECNO	XLCH	XLTRD	XLLC	ELMIN	Q	CWSEL	CRIWS	EG	10X*S	VCH	AREA	.01K
*	10.000	8.60	.00	.00	914.50	73.00	915.54	915.54	915.86	158.61	4.60	15.88	5.80
*	10.000	8.60	.00	.00	914.50	106.00	915.71	915.71	916.13	146.96	5.21	20.45	8.74
*	10.000	8.60	.00	.00	914.50	139.00	915.89	915.89	916.37	129.58	5.58	25.21	12.21
	10.000	8.60	.00	.00	914.50	207.00	917.43	.00	917.56	10.45	2.98	75.39	64.02
	11.000	179.00	.00	.00	915.10	73.00	917.14	.00	917.38	50.72	3.93	18.60	10.25
	11.000	179.00	.00	.00	915.10	106.00	917.43	.00	917.76	59.27	4.57	23.17	13.77
	11.000	179.00	.00	.00	915.10	139.00	917.64	.00	918.06	70.27	5.22	26.62	16.58
*	11.000	179.00	.00	.00	915.10	207.00	917.76	917.76	918.55	123.50	7.13	29.03	18.63
	11.900	300.00	.00	.00	916.10	73.00	918.36	.00	918.50	26.96	3.01	24.22	14.06
	11.900	300.00	.00	.00	916.10	106.00	918.78	.00	918.95	25.77	3.26	32.54	20.88
	11.900	300.00	.00	.00	916.10	139.00	919.14	.00	919.32	24.35	3.41	40.71	28.17
	11.900	300.00	.00	.00	916.10	207.00	919.81	.00	920.00	19.70	3.54	61.19	46.64
*	12.000	95.00	.00	.00	920.20	73.00	920.75	920.75	920.94	148.21	3.56	22.50	6.00
*	12.000	95.00	.00	.00	920.20	106.00	920.86	920.86	921.08	142.86	4.02	29.62	8.87
*	12.000	95.00	.00	.00	920.20	139.00	920.97	920.97	921.20	120.70	4.16	37.93	12.65
*	12.000	95.00	.00	.00	920.20	207.00	921.12	921.12	921.41	115.69	4.68	50.97	19.25

SUMMARY PRINTOUT TABLE 150

	SECNO	Q	CWSEL	DIFWSP	DIFWSX	DIFKWS	TOPWID	XLCH
	1.000	236.00	886.34	.00	.00	.00	26.98	.00
	1.000	414.00	888.05	1.71	.00	.00	37.23	.00
	1.000	494.00	888.80	.75	.00	.00	52.50	.00
	1.000	609.00	891.09	2.29	.00	.00	79.00	.00
	2.000	236.00	886.36	.00	.02	.00	24.31	52.00
	2.000	414.00	888.06	1.70	.01	.00	32.15	52.00
	2.000	494.00	888.80	.74	.00	.00	40.33	52.00
	2.000	609.00	891.09	2.29	.00	.00	79.00	52.00
*	2.250	236.00	887.25	.00	.89	.00	22.16	159.00
	2.250	414.00	888.20	.95	.14	.00	28.79	159.00
	2.250	494.00	888.92	.72	.12	.00	35.75	159.00
	2.250	609.00	891.12	2.21	.04	.00	71.18	159.00
*	2.500	236.00	889.16	.00	1.90	.00	32.55	159.00
*	2.500	414.00	889.88	.72	1.68	.00	45.36	159.00
*	2.500	494.00	890.15	.27	1.23	.00	52.51	159.00
	2.500	609.00	891.22	1.08	.10	.00	89.39	159.00
*	3.000	236.00	895.68	.00	6.52	.00	66.57	637.00
*	3.000	414.00	896.10	.43	6.22	.00	82.56	637.00
*	3.000	494.00	896.25	.15	6.11	.00	88.30	637.00
*	3.000	609.00	896.44	.18	5.22	.00	94.99	637.00
*	3.500	236.00	901.75	.00	6.08	.00	99.68	750.00
*	3.500	414.00	902.11	.36	6.01	.00	118.17	750.00
	3.500	494.00	902.23	.12	5.97	.00	123.98	750.00
	3.500	609.00	902.41	.18	5.97	.00	133.10	750.00
	3.750	236.00	903.31	.00	1.55	.00	74.20	250.00
	3.750	414.00	903.88	.57	1.76	.00	91.09	250.00
	3.750	494.00	904.08	.21	1.85	.00	151.17	250.00
	3.750	609.00	904.31	.22	1.89	.00	294.86	250.00
	4.000	236.00	903.99	.00	.68	.00	147.09	265.00
	4.000	414.00	904.66	.67	.79	.00	183.74	265.00
	4.000	494.00	904.89	.23	.81	.00	195.96	265.00
	4.000	609.00	905.15	.26	.84	.00	209.76	265.00
	5.000	159.00	904.82	.00	.83	.00	150.31	915.00
	5.000	265.00	905.40	.58	.74	.58	169.31	915.00
	5.000	323.00	905.63	.23	.74	.81	177.54	915.00
	5.000	407.00	905.91	.29	.77	.00	187.84	915.00

	SECNO	Q	CWSEL	DIFWSP	DIFWSX	DIFKWS	TOPWID	XLCH
	5.500	159.00	904.88	.00	.06	.00	207.52	285.00
	5.500	265.00	905.47	.58	.07	.58	209.86	285.00
	5.500	323.00	905.70	.23	.07	.82	210.79	285.00
	5.500	407.00	905.99	.29	.08	1.11	211.96	285.00
*	6.000	110.00	906.01	.00	1.13	.00	60.65	160.00
*	6.000	161.00	906.17	.16	.70	.16	62.00	160.00
*	6.000	180.00	906.22	.05	.52	.21	62.00	160.00
*	6.000	232.00	906.35	.13	.36	.34	62.00	160.00
*	6.900	110.00	907.29	.00	1.28	.00	16.75	80.00
*	6.900	161.00	907.73	.45	1.57	.45	19.83	80.00
*	6.900	180.00	907.88	.15	1.66	.60	20.87	80.00
*	6.900	232.00	908.24	.36	1.89	.95	23.33	80.00
	6.940	110.00	907.97	.00	.68	.00	20.27	20.00
	6.940	161.00	908.49	.52	.76	.52	24.04	20.00
	6.940	180.00	908.65	.16	.77	.69	25.23	20.00
	6.940	232.00	909.07	.41	.83	1.10	28.22	20.00
	6.950	110.00	908.16	.00	.19	.00	20.63	40.00
	6.950	161.00	908.67	.51	.18	.51	24.26	40.00
	6.950	180.00	908.83	.16	.18	.67	25.42	40.00
	6.950	232.00	909.23	.41	.17	1.07	28.33	40.00
	7.000	110.00	909.07	.00	.91	.00	20.68	225.00
	7.000	161.00	909.56	.49	.90	.49	24.26	225.00
	7.000	180.00	909.72	.16	.89	.65	25.42	225.00
	7.000	232.00	910.12	.40	.89	1.05	28.27	225.00
*	8.000	110.00	913.48	.00	4.41	.00	29.34	578.00
*	8.000	161.00	914.41	.93	4.85	.93	34.72	578.00
*	8.000	180.00	915.11	.70	5.39	1.63	38.78	578.00
*	8.000	232.00	917.43	2.32	7.31	3.95	58.75	578.00
	9.000	73.00	913.56	.00	.08	.00	25.27	185.00
	9.000	106.00	914.48	.91	.07	.91	29.12	185.00
	9.000	139.00	915.15	.67	.04	1.59	31.95	185.00
	9.000	207.00	917.44	2.29	.01	3.88	41.60	185.00
*	10.000	73.00	915.54	.00	1.97	.00	25.22	8.60
*	10.000	106.00	915.71	.18	1.23	.18	26.33	8.60
*	10.000	139.00	915.89	.18	.74	.35	27.44	8.60
	10.000	207.00	917.43	1.54	-.01	1.90	37.19	8.60
	11.000	73.00	917.14	.00	1.61	.00	15.15	179.00
	11.000	106.00	917.43	.29	1.72	.29	16.84	179.00
	11.000	139.00	917.64	.20	1.75	.50	18.01	179.00
*	11.000	207.00	917.76	.12	.33	.62	18.79	179.00

	SECNO	Q	CWSEL	DIFWSP	DIFWSX	DIFKWS	TOPWID	XLCH
	11.900	73.00	918.36	.00	1.22	.00	18.40	300.00
	11.900	106.00	918.78	.42	1.35	.42	21.26	300.00
	11.900	139.00	919.14	.35	1.50	.78	23.73	300.00
	11.900	207.00	919.81	.67	2.04	1.45	44.21	300.00
*	12.000	73.00	920.75	.00	2.39	.00	64.37	95.00
*	12.000	106.00	920.86	.10	2.08	.10	71.58	95.00
*	12.000	139.00	920.97	.11	1.83	.21	79.46	95.00
*	12.000	207.00	921.12	.15	1.32	.37	90.70	95.00

SUMMARY OF ERRORS AND SPECIAL NOTES

CAUTION	SECNO=	2.250	PROFILE= 1	CRITICAL DEPTH ASSUMED
CAUTION	SECNO=	2.250	PROFILE= 1	MINIMUM SPECIFIC ENERGY
CAUTION	SECNO=	2.500	PROFILE= 1	CRITICAL DEPTH ASSUMED
CAUTION	SECNO=	2.500	PROFILE= 1	MINIMUM SPECIFIC ENERGY
CAUTION	SECNO=	2.500	PROFILE= 2	CRITICAL DEPTH ASSUMED
CAUTION	SECNO=	2.500	PROFILE= 2	MINIMUM SPECIFIC ENERGY
CAUTION	SECNO=	2.500	PROFILE= 3	CRITICAL DEPTH ASSUMED
CAUTION	SECNO=	2.500	PROFILE= 3	MINIMUM SPECIFIC ENERGY
CAUTION	SECNO=	3.000	PROFILE= 1	CRITICAL DEPTH ASSUMED
CAUTION	SECNO=	3.000	PROFILE= 1	PROBABLE MINIMUM SPECIFIC ENERGY
CAUTION	SECNO=	3.000	PROFILE= 1	20 TRIALS ATTEMPTED TO BALANCE WSEL
CAUTION	SECNO=	3.000	PROFILE= 2	CRITICAL DEPTH ASSUMED
CAUTION	SECNO=	3.000	PROFILE= 2	MINIMUM SPECIFIC ENERGY
CAUTION	SECNO=	3.000	PROFILE= 3	CRITICAL DEPTH ASSUMED
CAUTION	SECNO=	3.000	PROFILE= 3	MINIMUM SPECIFIC ENERGY
CAUTION	SECNO=	3.000	PROFILE= 4	CRITICAL DEPTH ASSUMED
CAUTION	SECNO=	3.000	PROFILE= 4	PROBABLE MINIMUM SPECIFIC ENERGY
CAUTION	SECNO=	3.000	PROFILE= 4	20 TRIALS ATTEMPTED TO BALANCE WSEL
CAUTION	SECNO=	3.500	PROFILE= 1	CRITICAL DEPTH ASSUMED
CAUTION	SECNO=	3.500	PROFILE= 1	MINIMUM SPECIFIC ENERGY
CAUTION	SECNO=	3.500	PROFILE= 2	CRITICAL DEPTH ASSUMED
CAUTION	SECNO=	3.500	PROFILE= 2	MINIMUM SPECIFIC ENERGY
CAUTION	SECNO=	6.000	PROFILE= 1	CRITICAL DEPTH ASSUMED
CAUTION	SECNO=	6.000	PROFILE= 1	PROBABLE MINIMUM SPECIFIC ENERGY
CAUTION	SECNO=	6.000	PROFILE= 1	20 TRIALS ATTEMPTED TO BALANCE WSEL
CAUTION	SECNO=	6.000	PROFILE= 2	CRITICAL DEPTH ASSUMED
CAUTION	SECNO=	6.000	PROFILE= 2	PROBABLE MINIMUM SPECIFIC ENERGY
CAUTION	SECNO=	6.000	PROFILE= 2	20 TRIALS ATTEMPTED TO BALANCE WSEL
CAUTION	SECNO=	6.000	PROFILE= 3	CRITICAL DEPTH ASSUMED
CAUTION	SECNO=	6.000	PROFILE= 3	PROBABLE MINIMUM SPECIFIC ENERGY
CAUTION	SECNO=	6.000	PROFILE= 3	20 TRIALS ATTEMPTED TO BALANCE WSEL
CAUTION	SECNO=	6.000	PROFILE= 4	CRITICAL DEPTH ASSUMED
CAUTION	SECNO=	6.000	PROFILE= 4	PROBABLE MINIMUM SPECIFIC ENERGY
CAUTION	SECNO=	6.000	PROFILE= 4	20 TRIALS ATTEMPTED TO BALANCE WSEL
CAUTION	SECNO=	6.900	PROFILE= 1	CRITICAL DEPTH ASSUMED
CAUTION	SECNO=	6.900	PROFILE= 1	MINIMUM SPECIFIC ENERGY
CAUTION	SECNO=	6.900	PROFILE= 2	CRITICAL DEPTH ASSUMED
CAUTION	SECNO=	6.900	PROFILE= 2	MINIMUM SPECIFIC ENERGY
CAUTION	SECNO=	6.900	PROFILE= 3	CRITICAL DEPTH ASSUMED
CAUTION	SECNO=	6.900	PROFILE= 3	MINIMUM SPECIFIC ENERGY
CAUTION	SECNO=	6.900	PROFILE= 4	CRITICAL DEPTH ASSUMED
CAUTION	SECNO=	6.900	PROFILE= 4	MINIMUM SPECIFIC ENERGY
NOTE	SECNO=	8.000	PROFILE= 1	WSEL BASED ON X5 CARD
NOTE	SECNO=	8.000	PROFILE= 2	WSEL BASED ON X5 CARD
NOTE	SECNO=	8.000	PROFILE= 3	WSEL BASED ON X5 CARD

NOTE SECNO= 8.000 PROFILE= 4 WSEL BASED ON X5 CARD

CAUTION SECNO= 10.000 PROFILE= 1 CRITICAL DEPTH ASSUMED
CAUTION SECNO= 10.000 PROFILE= 1 PROBABLE MINIMUM SPECIFIC ENERGY
CAUTION SECNO= 10.000 PROFILE= 1 20 TRIALS ATTEMPTED TO BALANCE WSEL
CAUTION SECNO= 10.000 PROFILE= 2 CRITICAL DEPTH ASSUMED
CAUTION SECNO= 10.000 PROFILE= 2 PROBABLE MINIMUM SPECIFIC ENERGY
CAUTION SECNO= 10.000 PROFILE= 2 20 TRIALS ATTEMPTED TO BALANCE WSEL
CAUTION SECNO= 10.000 PROFILE= 3 CRITICAL DEPTH ASSUMED
CAUTION SECNO= 10.000 PROFILE= 3 PROBABLE MINIMUM SPECIFIC ENERGY
CAUTION SECNO= 10.000 PROFILE= 3 20 TRIALS ATTEMPTED TO BALANCE WSEL

CAUTION SECNO= 11.000 PROFILE= 4 CRITICAL DEPTH ASSUMED
CAUTION SECNO= 11.000 PROFILE= 4 MINIMUM SPECIFIC ENERGY

CAUTION SECNO= 12.000 PROFILE= 1 CRITICAL DEPTH ASSUMED
CAUTION SECNO= 12.000 PROFILE= 1 PROBABLE MINIMUM SPECIFIC ENERGY
CAUTION SECNO= 12.000 PROFILE= 1 20 TRIALS ATTEMPTED TO BALANCE WSEL
CAUTION SECNO= 12.000 PROFILE= 2 CRITICAL DEPTH ASSUMED
CAUTION SECNO= 12.000 PROFILE= 2 PROBABLE MINIMUM SPECIFIC ENERGY
CAUTION SECNO= 12.000 PROFILE= 2 20 TRIALS ATTEMPTED TO BALANCE WSEL
CAUTION SECNO= 12.000 PROFILE= 3 CRITICAL DEPTH ASSUMED
CAUTION SECNO= 12.000 PROFILE= 3 PROBABLE MINIMUM SPECIFIC ENERGY
CAUTION SECNO= 12.000 PROFILE= 3 20 TRIALS ATTEMPTED TO BALANCE WSEL
CAUTION SECNO= 12.000 PROFILE= 4 CRITICAL DEPTH ASSUMED
CAUTION SECNO= 12.000 PROFILE= 4 PROBABLE MINIMUM SPECIFIC ENERGY
CAUTION SECNO= 12.000 PROFILE= 4 20 TRIALS ATTEMPTED TO BALANCE WSEL

THIS RUN EXECUTED 01-13-92

****
HEC2 RELEASE DATED NOV 76 UPDATED MAY 1984
ERROR CORR - 01,02,03,04,05,06
MODIFICATION - 50,51,52,53,54,55,56
IBM-PC-XT VERSION AUGUST 1985
****

60 INCH RCP CULVERT

X5 CARD "WSEL"

CALCULATION




Figure B–2. Headwater depth for concrete pipe culverts with inlet control.

CULVERTS

50 yr

DIAMETER (IN)	? 60
LENGTH (FT)	? 578
FRICTION COEFF (FT^1/6)	? .013
[redacted]+EXIT COEFF	? .5
INLET CONTROL COEFF	? .61
INV ELEV OUT (FT)	? 906.4
INV ELEV IN (FT)	? 909.1
TAILWATER ELEV (FT)	? 909.57
ELEV INCREMENT (FT)	? .03

RESULTS

HEADWATER (FT)		FLOWRATE (CFS)
914.10	IC	151.98
914.13	IC	152.88
914.16	IC	153.79
914.19	IC	154.69
914.22	IC	155.58
914.25	IC	156.47
914.28	IC	157.35
914.31	IC	158.23
914.34	IC	159.10
914.37	IC	159.97
914.40	IC	160.84
914.43 ←	IC	161.69
914.46	IC	162.55
914.49	IC	163.40
914.52	IC	164.25

<Shift> <Prt Sc> print <Return> repeat <Space Bar> back to menu

---

$Q = 161$ cfs

H.w = 914.41

CULVERTS

100-Yr.

DIAMETER (IN)	? 60
LENGTH (FT)	? 578
FRICTION COEFF (FT^1/6)	? .013
EXIT COEFF	? .5
INLET CONTROL COEFF	? .61
INV ELEV OUT (FT)	? 906.4
INV ELEV IN (FT)	? 909.1
TAILWATER ELEV (FT)	? 909.73
ELEV INCREMENT (FT)	? .2

RESULTS

HEADWATER (FT)		FLOWRATE (CFS)
914.10	IC	151.98
914.30	IC	157.94
914.50	IC	163.68
914.70	IC	169.23
914.90	IC	174.61
915.10	IC	179.82
915.30	IC	184.89
915.50	IC	189.82
915.70	IC	194.62
915.90	IC	199.31
916.10	IC	203.90
916.30	IC	208.38
916.50	IC	212.77
916.70	IC	217.06
916.90	IC	221.28

<Shift> <Prt Sc> print <Return> repeat <Space Bar> back to menu

---

Q = 180 cfs

H.W = 915.11

915.30 Chart

915.25 Equation

CULVERTS

500 yr.

DIAMETER (IN)	? 60
LENGTH (FT)	? 578
FRICTION COEFF (FT^1/6)	? .013
EXIT COEFF	? .5
INLET CONTROL COEFF	? .61
INV ELEV OUT (FT)	? 906.4
INV ELEV IN (FT)	? 909.1
TAILWATER ELEV (FT)	? 910.13
ELEV INCREMENT (FT)	? .3

RESULTS

HEADWATER (FT)		FLOWRATE (CFS)
914.10	IC	151.98
914.40	IC	160.84
914.70	IC	169.23
915.00	IC	177.23
915.30	IC	184.89
915.60	IC	192.24
915.90	IC	199.31
916.20	IC	206.15
916.50	IC	212.77
916.80	IC	219.18
917.10	IC	225.42
917.40	IC	231.48 ←
917.70	IC	237.39
918.00	IC	243.16
918.30	IC	248.79
918.60	IC	254.30

<Shift> <Prt Sc> print <Return> repeat <Space Bar> back to menu

---

Q = 232

H.W = 917.43

RANDOLPH STREET DRAIN

ENCROACHMENT

AND

FLOODWAY ANALYSIS

```
1*******************************************************
****************************************
 *  WATER SURFACE PROFILES                          *                              *  U.S. ARMY CORPS OF ENGI
 *  VERSION OF NOVEMBER 1976                        *                              *  THE HYDROLOGIC ENGINEER
 *  UPDATED MAY 1984                                *                              *  609 SECOND STREET, SUIT
 *  IBM-PC-XT VERSION AUGUST 1985                   *                              *  DAVIS, CALIFORNIA 95616
 *  RUN DATE  01-13-92   TIME  11:17:19               *                              *  (916) 440-2105 (FTS)
 *******************************************************                            **************************

                                        X     X  XXXXXXX   XXXXX              XXXXX
                                        X     X  X        X     X           X     X
                                        X     X  X        X                       X
                                        XXXXXXX  XXXX     X          XXXXX    XXXXX
                                        X     X  X        X                  X
                                        X     X  X        X     X            X
                                        X     X  XXXXXXX   XXXXX             XXXXXXX
1
  01-13-92     11:17:19                                                                PAGE



                                                                    THIS RUN EXECUTED 01-13-92

 ************************************************
   HEC2 RELEASE DATED NOV 76 UPDATED MAY  1984
   ERROR CORR -  01,02,03,04,05,06
   MODIFICATION -  50,51,52,53,54,55,56
   IBM-PC-XT VERSION AUGUST 1985
 ************************************************
```

```
T1      RANDOLPH DRAIN FLOOD ANALYSIS - 10/87 APPEAL  FILE:APPEAL
T2      CITY OF NORTHVILLE  JOB NO. 6800-50  10-YEAR EVENT
T3      RANDOLPH DRAIN

J1  ICHECK    INQ       NINV      IDIR      STRT      METRIC    HVINS     Q         WSEL      FQ

       0.       2.        0.        0.   .000000       .00        .0        0.   888.800      .000

J2  NPROF     IPLOT     PRFVS     XSECV     XSECH     FN        ALLDC     IBW       CHNIM     ITRACE

     1.000      .000    -1.000      .000      .000      .000      .000      .000      .000      .000

J3  VARIABLE CODES FOR SUMMARY PRINTOUT

    110.000   200.000      .000      .000      .000      .000      .000      .000      .000      .000


QT      2.000   494.000   494.000      .000      .000      .000      .000      .000      .000      .000
NC       .030      .030      .030      .400      .600      .000      .000      .000      .000      .000
ET       .000      .000     1.400      .000      .000      .000      .000      .000      .000      .000
X1      1.000     8.000    32.000    44.000      .000      .000      .000      .000     -.600      .000
GR    889.600      .000   888.500    20.000   883.600    32.000   882.900    34.000   882.900    42.000
GR    883.800    44.000   889.800    57.000   890.600    79.000      .000      .000      .000      .000

X1      2.000     8.000    32.000    44.000    55.000    45.000    52.000      .000      .000      .000
GR    889.600      .000   888.500    20.000   883.600    32.000   882.900    34.000   882.900    36.000
GR    883.800    44.000   889.800    57.000   890.600    79.000      .000      .000      .000      .000

X1      2.250    10.000    32.000    42.000   154.000   157.000   159.000      .000      .000      .000
GR    890.000      .000   888.800    20.000   885.800    32.000   884.600    34.000   884.600    36.000
GR    884.900    40.000   885.100    42.000   888.500    52.000   889.800    57.000   891.200    72.000

X1      2.500    11.000   127.000   139.000   154.000   156.000   159.000      .000      .000      .000
GR    894.000      .000   892.000    50.000   890.000   105.000   888.000   127.000   886.400   129.000
GR    886.300   132.000   886.700   136.000   888.000   139.000   892.000   166.000   894.000   206.000
GR    894.000   225.000      .000      .000      .000      .000      .000      .000      .000      .000

ET       .000      .000      .400      .000      .000      .000      .000      .000      .000      .000
X1      3.000    11.000    63.000    72.000   582.000   482.000   637.000      .000      .000      .000
GR    898.700      .000   896.400    25.000   894.900    50.000   894.600    63.000   893.300    64.000
GR    893.200    67.000   893.600    71.000   894.600    72.000   895.500   100.000   896.700   125.000
GR    898.200   143.000      .000      .000      .000      .000      .000      .000      .000      .000

NC       .060      .060      .035      .000      .000      .000      .000      .000      .000      .000
X1      3.500    14.000   135.000   146.000   710.000   615.000   750.000      .000    -1.300      .000
GR    906.000      .000   904.000    66.000   903.000    91.000   902.300   116.000   902.100   135.000
GR    901.300   136.000   900.500   140.000   901.400   143.000   901.800   146.000   902.400   166.000
GR    903.100   191.000   904.100   216.000   905.300   241.000   906.500   255.000      .000      .000

ET       .000      .000      .400      .000      .000      .000      .000      .000      .000      .000
X1      3.750    10.000   281.000   291.000   195.000   265.000   250.000      .000      .000      .000
GR    904.400      .000   904.000   255.000   902.000   280.000   901.200   281.000   899.900   285.000
GR    899.800   288.000   901.700   291.000   902.000   315.000   904.000   350.000   906.000   387.000

ET       .000      .000     1.400      .000      .000      .000      .000      .000      .000      .000
```

X1	4.000	14.000	135.000	146.000	230.000	245.000	265.000	.000	.000	.000
GR	906.000	.000	904.000	66.000	903.000	91.000	902.300	116.000	902.100	135.000
GR	901.300	136.000	900.500	140.000	901.400	143.000	901.800	146.000	902.400	166.000
GR	903.100	191.000	904.100	216.000	905.300	241.000	906.500	255.000	.000	.000
QT	2.000	323.000	323.000	.000	.000	.000	.000	.000	.000	.000
ET	.000	7.100	7.100	.000	.000	.000	125.000	332.000	.000	.000
X1	5.000	15.000	214.000	232.000	905.000	920.000	915.000	.000	.000	.000
GR	906.000	.000	908.000	125.000	906.000	135.000	904.000	145.000	903.800	157.000
GR	903.500	182.000	903.600	207.000	903.100	214.000	902.600	225.000	903.100	229.000
GR	903.600	232.000	903.600	257.000	904.500	282.000	905.400	307.000	906.200	332.000
ET	.000	9.100	9.100	.000	.000	.000	.000	.000	110.000	330.000
X1	5.500	18.000	170.000	270.000	280.000	305.000	285.000	.000	.000	.000
GR	906.000	.000	908.000	110.000	906.000	118.000	904.000	126.000	902.800	145.000
GR	902.900	170.000	902.300	195.000	902.700	220.000	902.400	245.000	903.000	270.000
GR	903.100	295.000	903.000	320.000	903.700	345.000	904.000	370.000	904.000	395.000
GR	904.400	420.000	905.100	445.000	906.000	465.000	.000	.000	.000	.000
QT	2.000	180.000	180.000	.000	.000	.000	.000	.000	.000	.000
ET	.000	9.100	9.100	.000	.000	.000	.000	.000	113.000	175.000
X1	6.000	15.000	160.000	170.000	160.000	170.000	160.000	.000	.000	.000
GR	905.200	.000	905.300	25.000	905.700	50.000	905.400	75.000	906.000	100.000
GR	905.700	125.000	905.100	160.000	905.300	170.000	905.900	172.000	906.100	175.000
GR	906.900	200.000	907.400	225.000	907.600	250.000	908.800	275.000	909.500	300.000
ET	.000	7.100	7.100	.000	.000	.000	.200	31.800	.000	.000
X1	6.900	9.000	10.000	16.250	80.000	80.000	80.000	.000	.000	.000
GR	909.000	.000	906.700	8.000	905.500	10.000	905.300	11.000	905.300	16.000
GR	905.500	16.250	906.200	17.000	906.200	19.000	910.000	32.000	.000	.000
ET	.000	7.100	7.100	.000	.000	.000	75.000	208.000	.000	.000
X1	6.940	13.000	95.000	105.000	20.000	20.000	20.000	.000	-1.020	.000
GR	909.800	.000	911.300	25.000	912.200	50.000	912.800	75.000	907.600	95.000
GR	906.700	97.000	906.400	100.000	906.600	102.000	907.500	105.000	916.200	134.000
GR	916.600	159.000	917.300	184.000	917.400	209.000	.000	.000	.000	.000
ET	.000	7.100	7.100	.000	.000	.000	75.000	208.000	.000	.000
X1	6.950	13.000	95.000	105.000	40.000	40.000	40.000	.000	-.870	.000
GR	909.800	.000	911.300	25.000	912.200	50.000	912.800	75.000	907.600	95.000
GR	906.700	97.000	906.400	100.000	906.600	102.000	907.500	105.000	916.200	134.000
GR	916.600	159.000	917.300	184.000	917.400	209.000	.000	.000	.000	.000
ET	.000	7.100	7.100	.000	.000	.000	75.000	208.000	.000	.000
X1	7.000	.000	.000	.000	225.000	225.000	225.000	.000	.900	.000
ET	.000	.000	.400	.000	.000	.000	.000	.000	.000	.000
X1	8.000	10.000	5.000	55.000	578.000	578.000	578.000	.000	.000	.000
X5	4.000	915.110	915.110	.000	.000	.000	.000	.000	.000	.000
GR	917.700	.000	917.400	5.000	910.100	26.000	909.300	27.000	909.300	30.000
GR	909.100	33.500	909.600	34.300	916.700	55.000	917.300	60.000	918.100	80.000
QT	2.000	139.000	139.000	.000	.000	.000	.000	.000	.000	.000
X1	9.000	10.000	70.500	95.500	185.000	185.000	185.000	.000	.000	.000
GR	920.200	.000	920.100	25.000	919.700	40.000	918.700	65.000	913.500	70.500

GR	910.200	80.500	910.200	85.500	913.500	95.500	920.000	116.000	921.000	161.000
NC	.030	.030	.030	.800	.900	.000	.000	.000	.000	.000
ET	.000	.000	1.400	.000	.000	.000	.000	.000	.000	.000
X1	10.000	10.000	70.500	95.500	8.600	8.600	8.600	.000	.000	.000
GR	920.200	.000	920.100	25.000	919.700	40.000	918.700	65.000	915.500	70.500
GR	914.500	80.500	914.500	85.500	915.500	95.500	920.000	116.000	921.000	161.000
NC	.030	.030	.030	.400	.600	.000	.000	.000	.000	.000
ET	.000	7.100	7.100	7.100	7.100	.000	1.000	108.000	.000	.000
X1	11.000	8.000	37.000	60.000	179.000	179.000	179.000	.000	.000	.000
GR	920.900	.000	918.800	37.000	915.100	50.000	915.100	53.000	918.000	60.000
GR	918.300	90.000	920.000	185.000	920.900	190.000	.000	.000	.000	.000
X1	11.900	7.000	15.000	43.000	300.000	300.000	300.000	.000	.000	.000
GR	924.400	.000	920.000	15.000	916.100	31.500	916.100	34.500	919.400	43.000
GR	920.000	68.000	922.000	88.000	.000	.000	.000	.000	.000	.000
ET	.000	.000	1.400	.000	.000	.000	.000	.000	.000	.000
X1	12.000	8.000	70.000	110.000	100.000	100.000	95.000	.000	.000	.000
GR	923.400	.000	922.000	40.000	920.400	70.000	920.200	100.000	920.400	110.000
GR	920.900	135.000	922.000	195.000	924.000	310.000	.000	.000	.000	.000
EJ	.000	.000	.000	.000	.000	.000	.000	.000	.000	.000

1

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

*PROF 1

CCHV= .400 CEHV= .600

*SECNO 1.000

1.00	6.50	888.80	.00	888.80	888.99	.19	.00	.00	883.00
494.	108.	310.	76.	48.	76.	34.	0.	0.	883.20
.00	2.27	4.06	2.24	.030	.030	.030	.000	882.30	3.64
.000589	0.	0.	0.	0	0	0	.00	52.50	56.13

0

*SECNO 2.000

2.00	5.90	888.80	.00	.00	889.08	.28	.04	.06	883.60
494.	97.	324.	73.	34.	67.	27.	0.	0.	883.80
.00	2.86	4.87	2.71	.030	.030	.030	.000	882.90	14.51
.001002	55.	52.	45.	2	0	0	.00	40.33	54.84

0

*SECNO 2.250

2.25	4.32	888.92	.00	.00	889.60	.68	.28	.24	885.80
494.	81.	309.	104.	20.	41.	22.	1.	0.	885.10
.01	4.12	7.60	4.81	.030	.030	.030	.000	884.60	17.89
.003803	154.	159.	157.	0	0	0	.00	35.75	53.64

0

*SECNO 2.500

7185 MINIMUM SPECIFIC ENERGY

3720 CRITICAL DEPTH ASSUMED

2.50	3.85	890.15	890.15	.00	890.91	.77	.74	.05	888.00
494.	105.	328.	61.	26.	40.	16.	1.	0.	888.00
.02	4.11	8.14	3.96	.030	.030	.030	.000	886.30	100.98
.005890	154.	159.	156.	4	15	0	.00	52.51	153.49

0

*SECNO 3.000

7185 MINIMUM SPECIFIC ENERGY

3720 CRITICAL DEPTH ASSUMED

3.00	3.05	896.25	896.25	.00	896.73	.47	3.62	.12	894.60
494.	149.	181.	164.	35.	25.	40.	2.	1.	894.60
.05	4.27	7.27	4.14	.030	.030	.030	.000	893.20	27.42
.006444	582.	637.	482.	16	14	0	.00	88.30	115.72

0

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

*SECNO 3.500

3.50	3.03	902.23	902.22	.00	902.72	.49	5.98	.01	900.80
494.	142.	207.	146.	51.	26.	50.	4.	3.	900.50
.09	2.79	7.99	2.89	.060	.035	.060	.000	899.20	77.76
.012028	710.	750.	615.	11	5	0	.00	123.98	201.74

```
0
 *SECNO 3.750
      3.75     4.28   904.08      .00      .00   904.40      .32     1.62      .07   901.20
      494.      53.      230.     211.      32.      37.      92.      5.       4.    901.70
       .10     1.64     6.24     2.30     .060     .035     .060     .000   899.80   200.41
   .004189     195.     250.     265.        1        0        0      .00   151.17   351.58
0
 *SECNO 4.000
      4.00     4.39   904.89      .00      .00   904.94      .05     .43      .11   902.10
      494.     187.     124.     183.     155.      41.     148.      6.       5.    901.80
       .14     1.20     3.03     1.24     .060     .035     .060     .000   900.50    36.55
   .000940     230.     265.     245.        3        0        0      .00   195.96   232.51
0
 *SECNO 5.000

 3470 ENCROACHMENT STATIONS=     125.0     332.0  TYPE=     1  TARGET=     207.000
      5.00     3.03   905.63      .00      .00   905.66      .03     .70      .01   903.10
      323.     136.      97.      90.     145.      49.     109.     13.       8.    903.60
       .35      .94     1.99      .83     .060     .035     .060     .000   902.60   136.82
   .000589     905.     915.     920.        3        0        0      .00   177.54   314.36
0
 *SECNO 5.500

 3470 ENCROACHMENT STATIONS=     110.0     330.0  TYPE=     1  TARGET=     220.000
      5.50     3.40   905.70      .00      .00   905.70      .01     .04      .01   902.90
      323.      44.      222.     58.      121.     311.     158.     16.      10.    903.00
       .48      .36      .71      .36     .060     .035     .060     .000   902.30   119.21
   .000062     280.     285.     305.        2        0        0      .00   210.79   330.00
0
 *SECNO 6.000
 3685 20 TRIALS ATTEMPTED WSEL,CWSEL
 3693 PROBABLE MINIMUM SPECIFIC ENERGY
 3720 CRITICAL DEPTH ASSUMED
1
  01-13-92     11:17:19                                                              PAGE

    SECNO     DEPTH     CWSEL     CRIWS     WSELK     EG        HV        HL        OLOSS    BANK ELEV
    Q         QLOB      QCH       QROB      ALOB      ACH       AROB      VOL       TWA    LEFT/RIGHT
    TIME      VLOB      VCH       VROB      XNL       XNCH      XNR       WTN       ELMIN      SSTA
    SLOPE     XLOBL     XLCH      XLOBR     ITRIAL    IDC       ICONT     CORAR     TOPWID     ENDST


 3470 ENCROACHMENT STATIONS=     113.0     175.0  TYPE=     1  TARGET=      62.000
      6.00     1.12   906.22   906.22      .00   906.57      .35     .02      .21   905.10
      180.     108.      68.      4.       34.      10.      2.      17.      10.    905.30
       .49     3.17     6.64     2.23     .060     .035     .060     .000   905.10   113.00
   .023822     160.     160.     170.       20       17        0      .00    62.00   175.00
```

0

*SECNO 6.900

7185 MINIMUM SPECIFIC ENERGY

3720 CRITICAL DEPTH ASSUMED

3470 ENCROACHMENT STATIONS=			.2	31.8	TYPE=	1	TARGET=	31.600	
6.90	2.58	907.88	907.88	.00	908.73	.85	1.27	.30	905.50
180.	17.	134.	29.	6.	16.	10.	17.	10.	905.50
.50	2.81	8.39	2.97	.060	.035	.060	.000	905.30	3.89
.011339	80.	80.	80.	2	17	0	.00	20.87	24.75

0

*SECNO 6.940

3470 ENCROACHMENT STATIONS=			75.0	208.0	TYPE=	1	TARGET=	133.000	
6.94	3.27	908.65	.00	.00	909.04	.39	.13	.18	906.58
180.	13.	154.	13.	8.	29.	8.	17.	10.	906.48
.50	1.59	5.37	1.63	.060	.035	.060	.000	905.38	87.02
.004121	20.	20.	20.	5	0	0	.00	25.23	112.25

0

*SECNO 6.950

3470 ENCROACHMENT STATIONS=			75.0	208.0	TYPE=	1	TARGET=	133.000	
6.95	3.30	908.83	.00	.00	909.21	.38	.16	.00	906.73
180.	13.	154.	13.	8.	29.	8.	17.	10.	906.63
.50	1.58	5.31	1.62	.060	.035	.060	.000	905.53	86.92
.003975	40.	40.	40.	2	0	0	.00	25.42	112.34

0

*SECNO 7.000

3470 ENCROACHMENT STATIONS=			75.0	208.0	TYPE=	1	TARGET=	133.000	
7.00	3.29	909.72	.00	.00	910.10	.38	.89	.00	907.63
180.	13.	154.	13.	8.	29.	8.	17.	10.	907.53
.51	1.58	5.31	1.62	.060	.035	.060	.000	906.43	86.92
.003979	225.	225.	225.	1	0	0	.00	25.42	112.34

0

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

*SECNO 8.000

WATER EL=X5 CARD= 915.110

8.00	6.01	915.11	.00	.00	915.14	.03	.35	.14	917.40
180.	0.	180.	0.	0.	128.	0.	18.	11.	916.70
.63	.00	1.40	.00	.060	.035	.060	.000	909.10	11.59
.000237	578.	578.	578.	0	0	0	.00	38.78	50.36

0

*SECNO 9.000

9.00	4.95	915.15	.00	.00	915.19	.04	.04	.00	913.50
139.	0.	137.	1.	1.	91.	4.	19.	11.	913.50
.66	.27	1.51	.33	.060	.035	.060	.000	910.20	68.75
.000240	185.	185.	185.	2	0	0	.00	31.95	100.71

0

```
CCHV=    .800 CEHV=    .900
*SECNO 10.000
3685 20 TRIALS ATTEMPTED WSEL,CWSEL
3693 PROBABLE MINIMUM SPECIFIC ENERGY
3720 CRITICAL DEPTH ASSUMED
    10.00     1.39   915.89   915.89      .00   916.37      .48      .01      .40   915.50
     139.       0.     138.       1.       0.      25.       0.      19.      11.   915.50
      .66     1.72     5.58     1.86     .030     .030     .030     .000   914.50    69.83
   .012958       9.       9.       9.       20       14        0      .00    27.44    97.27
0
CCHV=    .400 CEHV=    .600
*SECNO 11.000

3470 ENCROACHMENT STATIONS=       1.0     108.0  TYPE=     1  TARGET=     107.000
    11.00     2.54   917.64      .00      .00   918.06      .42     1.67      .02   918.80
     139.       0.     139.       0.       0.      27.       0.      19.      11.   918.00
      .67      .00     5.22      .00     .030     .030     .030     .000   915.10    41.10
   .007027     179.     179.     179.        2        0        0      .00    18.01    59.11
0
 *SECNO 11.900
    11.90     3.04   919.14      .00      .00   919.32      .18     1.16      .10   920.00
     139.       0.     139.       0.       0.      41.       0.      19.      11.   919.40
      .70      .00     3.41      .00     .030     .030     .030     .000   916.10    18.61
   .002435     300.     300.     300.        3        0        0      .00    23.73    42.35
0
1
  01-13-92     11:17:19                                                                PAGE


    SECNO     DEPTH     CWSEL     CRIWS     WSELK     EG        HV        HL        OLOSS    BANK ELEV
    Q         QLOB      QCH       QROB      ALOB      ACH       AROB      VOL       TWA    LEFT/RIGHT
    TIME      VLOB      VCH       VROB      XNL       XNCH      XNR       WTN       ELMIN       SSTA
    SLOPE     XLOBL     XLCH      XLOBR     ITRIAL    IDC       ICONT     CORAR     TOPWID      ENDST


 *SECNO 12.000
 3685 20 TRIALS ATTEMPTED WSEL,CWSEL
 3693 PROBABLE MINIMUM SPECIFIC ENERGY
 3720 CRITICAL DEPTH ASSUMED
    12.00      .77   920.97   920.97      .00   921.20      .23      .44      .03   920.40
     139.       7.     111.      20.       3.      27.       8.      19.      11.   920.40
      .70     2.35     4.16     2.51     .030     .030     .030     .000   920.20    59.32
   .012070     100.       95.     100.       20       11        0      .00    79.46   138.78
0
1
  01-13-92     11:17:19                                                                PAGE


 ***************************************************
   HEC2 RELEASE DATED NOV 76 UPDATED MAY  1984
   ERROR CORR -  01,02,03,04,05,06
   MODIFICATION -  50,51,52,53,54,55,56
   IBM-PC-XT VERSION AUGUST 1985
 ***************************************************
```

```
T1       RANDOLPH DRAIN FLOOD ANALYSIS - 10/87 APPEAL  FILE:APPEAL
T2       CITY OF NORTHVILLE  JOB NO. 6800-50  100-YEAR EVENT ENCR
T3       RANDOLPH DRAIN

J1  ICHECK    INQ       NINV      IDIR      STRT      METRIC    HVINS     Q         WSEL      FQ

     -10.       3.        0.        0.   .000000       .00        .0        0.   888.800      .000

J2  NPROF     IPLOT     PRFVS     XSECV     XSECH     FN        ALLDC     IBW       CHNIM     ITRACE

     15.000     .000    -1.000     .000      .000      .000      .000      .000      .000      .000

1
 01-13-92     11:17:19                                                                          PAGE


   SECNO     DEPTH     CWSEL     CRIWS     WSELR     EG        HV        EL        OLOSS     BANK ELEV
   Q         QLOB      QCH       QROB      ALOB      ACH       AROB      VOL       TWA     LEFT/RIGHT
   TIME      VLOB      VCH       VROB      XNL       XNCH      XNR       WTN       ELMIN       SSTA
   SLOPE     XLOBL     XLCH      XLOBR     ITRIAL    IDC       ICONT     CORAR     TOPWID      ENDST


 *PROF 2

 CCHV=    .400 CEHV=    .600
 *SECNO 1.000
  2800 NAT Q1=   203.63  WSEL=    888.80  ENC Q1=    203.63  WSEL=    888.90  RATIO=   .0000
  NAT Q1=    211.  RATIOS LOB,CH,ROB=   .2239   .6206   .1555  WSEL=    888.90

 3470 ENCROACHMENT STATIONS=      19.0      51.7  TYPE=     4  TARGET=       .036
      1.00      6.50   888.80      .00   888.80   889.01      .21      .00      .00   883.00
      494.      106.      317.      72.      41.      76.      29.       0.       0.   883.20
       .00      2.57      4.15     2.44     .030     .030     .030     .000   882.30    19.01
    .000615       0.        0.       0.        0        0        0      .00    32.66    51.67
0
 *SECNO 2.000
  2800 NAT Q1=    156.08  WSEL=    888.80  ENC Q1=    156.08  WSEL=    888.90  RATIO=   .0000
  NAT Q1=    162.  RATIOS LOB,CH,ROB=   .2009   .6486   .1505  WSEL=    888.90

 3470 ENCROACHMENT STATIONS=      22.8      50.7  TYPE=     4  TARGET=       .039
      2.00      5.90   888.80      .00   888.80   889.11      .31      .04      .06   883.60
      494.       95.      331.      68.      31.      67.      23.       0.       0.   883.80
       .00      3.10      4.98     2.95     .030     .030     .030     .000   882.90    22.80
    .001049      55.       52.      45.        2        0        0      .00    27.87    50.67
0
 *SECNO 2.250
  2800 NAT Q1=     80.11  WSEL=    888.92  ENC Q1=     80.11  WSEL=    889.02  RATIO=   .0000
  NAT Q1=     85.  RATIOS LOB,CH,ROB=   .1703   .6154   .2143  WSEL=    889.02

 3470 ENCROACHMENT STATIONS=      25.1      49.7  TYPE=     4  TARGET=       .053
      2.25      4.31   888.91      .00   888.92   889.68      .77      .29      .28   885.80
      494.       74.      321.      99.      16.      41.      19.       1.       0.   885.10
       .01      4.76      7.91     5.17     .030     .030     .030     .000   884.60    25.06
    .004136     154.      159.     157.        2        0        0      .00    24.59    49.65
```

0

*SECNO 2.500

2800 NAT Q1= 64.37 WSEL= 890.15 ENC Q1= 64.37 WSEL= 890.25 RATIO= .0000

NAT Q1= 70. RATIOS LOB,CH,ROB= .2266 .6435 .1299 WSEL= 890.25

7185 MINIMUM SPECIFIC ENERGY

3720 CRITICAL DEPTH ASSUMED

3470 ENCROACHMENT STATIONS= 115.5 144.3 TYPE= 4 TARGET= .076

1

01-13-92 11:17:19 PAGE

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST
2.50	3.70	890.00	890.00	890.15	891.09	1.09	.89	.19	888.00
494.	93.	357.	45.	17.	38.	8.	1.	0.	888.00
.02	5.47	9.27	5.30	.030	.030	.030	.000	886.30	115.53
.008114	154.	159.	156.	2	15	0	.00	28.74	144.27

0

*SECNO 3.000

3301 HV CHANGED MORE THAN HVINS

7185 MINIMUM SPECIFIC ENERGY

3720 CRITICAL DEPTH ASSUMED

3.00	2.99	896.19	896.19	896.25	896.73	.54	4.64	.22	894.60
494.	147.	188.	159.	32.	24.	37.	2.	1.	894.60
.04	4.52	7.75	4.35	.030	.030	.030	.000	893.20	28.57
.007574	582.	637.	482.	5	15	0	.00	85.71	114.28

0

*SECNO 3.500

3.50	3.12	902.32	902.25	902.23	902.72	.40	5.94	.06	900.80
494.	147.	198.	150.	56.	27.	56.	4.	3.	900.50
.09	2.61	7.35	2.69	.060	.035	.060	.000	899.20	75.47
.009684	710.	750.	615.	12	5	0	.00	128.56	204.03

0

*SECNO 3.750

3.75	4.20	904.00	.00	904.08	904.37	.37	1.63	.01	901.20
494.	49.	238.	207.	27.	36.	86.	4.	3.	901.70
.10	1.80	6.62	2.41	.060	.035	.060	.000	899.80	255.10
.004868	195.	250.	265.	5	0	0	.00	94.76	349.86

0

*SECNO 4.000

2800 NAT Q1= 161.13 WSEL= 904.89 ENC Q1= 161.13 WSEL= 904.99 RATIO= .0000

NAT Q1= 173. RATIOS LOB,CH,ROB= .3821 .2438 .3740 WSEL= 904.99

3470 ENCROACHMENT STATIONS= 75.1 202.3 TYPE= 4 TARGET= .067

4.00	4.41	904.91	.00	904.89	904.97	.06	.49	.12	902.10
494.	184.	131.	179.	133.	41.	128.	6.	4.	901.80
.14	1.38	3.20	1.40	.060	.035	.060	.000	900.50	75.15
.001043	230.	265.	245.	2	0	0	.00	127.17	202.32

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

*SECNO 5.000

3470 ENCROACHMENT STATIONS= 125.0 332.0 TYPE= 1 TARGET= 207.000

5.00	3.08	905.68	.00	905.63	905.71	.03	.72	.02	903.10
323.	137.	96.	91.	149.	49.	112.	12.	7.	903.60
.35	.92	1.94	.81	.060	.035	.060	.000	902.60	136.59
.000546	905.	915.	920.	4	0	0	.00	179.20	315.79

0

*SECNO 5.500

3470 ENCROACHMENT STATIONS= 110.0 330.0 TYPE= 1 TARGET= 220.000

5.50	3.45	905.75	.00	905.70	905.75	.01	.04	.01	902.90
323.	44.	221.	58.	123.	316.	161.	15.	8.	903.00
.49	.36	.70	.36	.060	.035	.060	.000	902.30	119.01
.000059	280.	285.	305.	2	0	0	.00	210.99	330.00

0

*SECNO 6.000

3685 20 TRIALS ATTEMPTED WSEL,CWSEL

3693 PROBABLE MINIMUM SPECIFIC ENERGY

3720 CRITICAL DEPTH ASSUMED

3470 ENCROACHMENT STATIONS= 113.0 175.0 TYPE= 1 TARGET= 62.000

6.00	1.12	906.22	906.22	906.22	906.57	.35	.02	.21	905.10
180.	108.	68.	4.	34.	10.	2.	16.	9.	905.30
.50	3.17	6.65	2.24	.060	.035	.060	.000	905.10	113.00
.023887	160.	160.	170.	20	17	0	.00	62.00	175.00

0

*SECNO 6.900

7185 MINIMUM SPECIFIC ENERGY

3720 CRITICAL DEPTH ASSUMED

3470 ENCROACHMENT STATIONS= .2 31.8 TYPE= 1 TARGET= 31.600

6.90	2.58	907.88	907.88	907.88	908.73	.85	1.27	.30	905.50
180.	17.	134.	29.	6.	16.	10.	16.	9.	905.50
.50	2.81	8.38	2.97	.060	.035	.060	.000	905.30	3.89
.011333	80.	80.	80.	2	17	0	.00	20.87	24.76

0

*SECNO 6.940

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

```
 3470 ENCROACHMENT STATIONS=      75.0     208.0  TYPE=     1  TARGET=     133.000
      6.94      3.27   908.65      .00   908.65   909.04      .39      .13      .18   906.58
      180.       13.      154.      13.       8.      29.       8.      16.       9.    906.48
       .50      1.59      5.37     1.63     .060     .035     .060     .000   905.38    87.02
   .004122       20.       20.       20.        5        0        0      .00    25.23   112.25
0
 *SECNO 6.950

 3470 ENCROACHMENT STATIONS=      75.0     208.0  TYPE=     1  TARGET=     133.000
      6.95      3.30   908.83      .00   908.83   909.21      .38      .16      .00   906.73
      180.       13.      154.      13.       8.      29.       8.      16.       9.    906.63
       .50      1.58      5.31     1.62     .060     .035     .060     .000   905.53    86.92
   .003975       40.       40.       40.        2        0        0      .00    25.42   112.34
0
 *SECNO 7.000

 3470 ENCROACHMENT STATIONS=      75.0     208.0  TYPE=     1  TARGET=     133.000
      7.00      3.29   909.72      .00   909.72   910.10      .38      .89      .00   907.63
      180.       13.      154.      13.       8.      29.       8.      17.       9.    907.53
       .52      1.58      5.31     1.62     .060     .035     .060     .000   906.43    86.92
   .003979      225.      225.      225.        1        0        0      .00    25.42   112.34
0
 *SECNO 8.000
  WATER EL=X5 CARD=   915.110
      8.00      6.01   915.11      .00   915.11   915.14      .03      .35      .14   917.40
      180.        0.      180.       0.        0.      128.       0.      18.      10.    916.70
       .63       .00      1.40      .00     .060     .035     .060     .000   909.10    11.59
   .000237      578.      578.      578.        0        0        0      .00    38.78    50.36
0
 *SECNO 9.000
  2800 NAT Q1=      89.70  WSEL=    915.15  ENC Q1=      89.70  WSEL=    915.15  RATIO=    .0000
  NAT Q1=      90.  RATIOS LOB,CH,ROB=    .0028    .9870    .0101  WSEL=    915.15

 3470 ENCROACHMENT STATIONS=      69.3      99.0  TYPE=     4  TARGET=        .001
      9.00      4.95   915.15      .00   915.15   915.19      .04      .04      .00   913.50
      139.        0.      137.       1.        1.      91.       4.      18.      10.    913.50
       .67       .27      1.51      .36     .060     .035     .060     .000   910.20    69.30
   .000240      185.      185.      185.        0        0        0      .00    29.71    99.01
0
1
  01-13-92     11:17:19                                                                  PAGE


    SECNO     DEPTH     CWSEL     CRIWS     WSELK     EG        HV        HL        OLOSS    BANK ELEV
    Q         QLOB      QCH       QROB      ALOB      ACH       AROB      VOL       TWA    LEFT/RIGHT
    TIME      VLOB      VCH       VROB      XNL       XNCH      XNR       WTN       ELMIN       SSTA
    SLOPE     XLOBL     XLCH      XLOBR     ITRIAL    IDC       ICONT     CORAR     TOPWID      ENDST


  CCHV=    .800 CEHV=    .900
  *SECNO 10.000
   2800 NAT Q1=      12.21  WSEL=    915.89  ENC Q1=      14.25  WSEL=    915.99  RATIO=  -.1667
   NAT Q1=      14.  RATIOS LOB,CH,ROB=    .0025    .9902    .0072  WSEL=    915.99
```

```
3685 20 TRIALS ATTEMPTED WSEL,CWSEL
3693 PROBABLE MINIMUM SPECIFIC ENERGY
3720 CRITICAL DEPTH ASSUMED

3470 ENCROACHMENT STATIONS=      70.5      95.5  TYPE=     4  TARGET=        .010
    10.00      1.38   915.88   915.88   915.89   916.38      .50      .01      .42   915.50
     139.        0.     139.       0.       0.      25.       0.      18.      10.   915.50
      .67       .00     5.65      .00     .030     .030     .030     .000   914.50    70.50
   .013943       9.       9.       9.       20       14        0      .00    25.00    95.50
0
 CCHV=    .400 CEHV=    .600
 *SECNO 11.000

 3470 ENCROACHMENT STATIONS=       1.0     108.0  TYPE=     1  TARGET=     107.000
    11.00      2.57   917.67      .00   917.64   918.07      .40     1.66      .04   918.80
     139.        0.     139.       0.       0.      27.       0.      18.      10.   918.00
      .68       .00     5.10      .00     .030     .030     .030     .000   915.10    40.97
   .006581     179.     179.     179.        3        0        0      .00    18.23    59.20
0
 *SECNO 11.900
    11.90      3.03   919.13      .00   919.14   919.31      .19     1.15      .09   920.00
     139.        0.     139.       0.       0.      40.       0.      19.      10.   919.40
      .70       .00     3.45      .00     .030     .030     .030     .000   916.10    18.70
   .002511     300.     300.     300.        4        0        0      .00    23.60    42.29
0
 *SECNO 12.000
  2800 NAT Q1=     12.65  WSEL=    920.97  ENC Q1=     12.80  WSEL=    921.07  RATIO=  -.0115
  NAT Q1=     17.  RATIOS LOB,CH,ROB=    .0597    .7626    .1778  WSEL=    921.07
 3685 20 TRIALS ATTEMPTED WSEL,CWSEL
 3693 PROBABLE MINIMUM SPECIFIC ENERGY
 3720 CRITICAL DEPTH ASSUMED

 3470 ENCROACHMENT STATIONS=      70.0     110.0  TYPE=     4  TARGET=        .237
    12.00       .82   921.02   921.02   920.97   921.38      .36      .48      .11   920.40
     139.        0.     139.       0.       0.      29.       0.      19.      10.   920.40
      .71       .00     4.84      .00     .030     .030     .030     .000   920.20    70.00
   .015470     100.      95.     100.       20       14        0      .00    40.00   110.00
0
1
  01-13-92     11:17:19                                                              PAGE


                                                                  THIS RUN EXECUTED 01-13-92

 **************************************************
   HEC2 RELEASE DATED NOV 76 UPDATED MAY  1984
   ERROR CORR -  01,02,03,04,05,06
   MODIFICATION -  50,51,52,53,54,55,56
   IBM-PC-XT VERSION AUGUST 1985
 **************************************************
```

NOTE- ASTERISK (*) AT LEFT OF CROSS-SECTION NUMBER INDICATES MESSAGE IN SUMMARY OF ERRORS LIST

RANDOLPH DRAIN

SUMMARY PRINTOUT TABLE 110

	SECNO	CWSEL	DIFKWS	EG	TOPWID	QLOB	QCH	QROB	PERENC	STENCL	STCHL	STCHR	STENCR
	1.000	888.80	.00	888.99	52.50	107.93	310.03	76.05	.00	.00	32.00	44.00	.00
	1.000	888.80	.00	889.01	32.66	105.63	316.81	71.57	.04	19.01	32.00	44.00	51.67
	2.000	888.80	.00	889.08	40.33	96.94	323.65	73.41	.00	.00	32.00	44.00	.00
	2.000	888.80	.00	889.11	27.87	94.77	331.13	68.10	.04	22.80	32.00	44.00	50.68
	2.250	888.92	.00	889.60	35.75	80.86	309.21	103.93	.00	.00	32.00	42.00	.00
	2.250	888.91	-.01	889.68	24.59	74.14	320.54	99.32	.05	25.06	32.00	42.00	49.65
*	2.500	890.15	.00	890.91	52.51	104.90	327.60	61.50	.00	.00	127.00	139.00	.00
*	2.500	890.00	-.15	891.09	28.74	92.64	356.51	44.85	.08	115.53	127.00	139.00	144.27
*	3.000	896.25	.00	896.73	88.30	148.97	180.89	164.13	.00	.00	63.00	72.00	.00
*	3.000	896.19	-.07	896.73	85.71	146.52	188.01	159.47	.00	.00	63.00	72.00	.00
	3.500	902.23	.00	902.72	123.98	141.72	206.67	145.61	.00	.00	135.00	146.00	.00
	3.500	902.32	.09	902.72	128.56	146.57	197.62	149.81	.00	.00	135.00	146.00	.00
	3.750	904.08	.00	904.40	151.17	52.52	230.17	211.32	.00	.00	281.00	291.00	.00
	3.750	904.00	-.09	904.37	94.76	48.92	237.70	207.38	.00	.00	281.00	291.00	.00
	4.000	904.89	.00	904.94	195.96	186.85	123.75	183.41	.00	.00	135.00	146.00	.00
	4.000	904.91	.02	904.97	127.17	183.56	131.18	179.26	.07	75.15	135.00	146.00	202.32
	5.000	905.63	.00	905.66	177.54	136.46	96.91	89.63	207.00	125.00	214.00	232.00	332.00
	5.000	905.68	.05	905.71	179.20	136.51	95.95	90.53	207.00	125.00	214.00	232.00	332.00
	5.500	905.70	.00	905.70	210.79	43.73	221.73	57.54	220.00	110.00	170.00	270.00	330.00
	5.500	905.75	.05	905.75	210.99	43.91	221.39	57.70	220.00	110.00	170.00	270.00	330.00
*	6.000	906.22	.00	906.57	62.00	107.98	67.77	4.25	62.00	113.00	160.00	170.00	175.00
*	6.000	906.22	.00	906.57	62.00	107.97	67.78	4.24	62.00	113.00	160.00	170.00	175.00

	SECNO	CWSEL	DIFKWS	EG	TOPWID	QLOB	QCH	QROB	PERENC	STENCL	STCHL	STCHR	STENCR
*	6.900	907.88	.00	908.73	20.87	16.87	134.28	28.85	31.60	.20	10.00	16.25	31.80
*	6.900	907.88	.00	908.73	20.87	16.87	134.27	28.85	31.60	.20	10.00	16.25	31.80
	6.940	908.65	.00	909.04	25.23	13.20	153.92	12.88	133.00	75.00	95.00	105.00	208.00
	6.940	908.65	.00	909.04	25.23	13.20	153.93	12.88	133.00	75.00	95.00	105.00	208.00
	6.950	908.83	.00	909.21	25.42	13.41	153.52	13.06	133.00	75.00	95.00	105.00	208.00
	6.950	908.83	.00	909.21	25.42	13.41	153.52	13.06	133.00	75.00	95.00	105.00	208.00
	7.000	909.72	.00	910.10	25.42	13.40	153.54	13.06	133.00	75.00	95.00	105.00	208.00
	7.000	909.72	.00	910.10	25.42	13.40	153.54	13.06	133.00	75.00	95.00	105.00	208.00
*	8.000	915.11	.00	915.14	38.78	.00	180.00	.00	.00	.00	5.00	55.00	.00
*	8.000	915.11	.00	915.14	38.78	.00	180.00	.00	.00	.00	5.00	55.00	.00
	9.000	915.15	.00	915.19	31.95	.39	137.20	1.40	.00	.00	70.50	95.50	.00
	9.000	915.15	.00	915.19	29.71	.36	137.26	1.39	.00	69.30	70.50	95.50	99.01
*	10.000	915.89	.00	916.37	27.44	.22	138.13	.64	.00	.00	70.50	95.50	.00
*	10.000	915.88	-.01	916.38	25.00	.00	139.00	.00	.01	70.50	70.50	95.50	95.50
	11.000	917.64	.00	918.06	18.01	.00	139.00	.00	107.00	1.00	37.00	60.00	108.00
	11.000	917.67	.03	918.07	18.23	.00	139.00	.00	107.00	1.00	37.00	60.00	108.00
	11.900	919.14	.00	919.32	23.73	.00	139.00	.00	.00	.00	15.00	43.00	.00
	11.900	919.13	-.01	919.31	23.60	.00	139.00	.00	.00	.00	15.00	43.00	.00
*	12.000	920.97	.00	921.20	79.46	7.15	111.48	20.37	.00	.00	70.00	110.00	.00
*	12.000	921.02	.05	921.38	40.00	.00	139.00	.00	.24	70.00	70.00	110.00	110.00

SUMMARY OF ERRORS AND SPECIAL NOTES

```
CAUTION  SECNO=     2.500  PROFILE= 1  CRITICAL DEPTH ASSUMED
CAUTION  SECNO=     2.500  PROFILE= 1  MINIMUM SPECIFIC ENERGY
CAUTION  SECNO=     2.500  PROFILE= 2  CRITICAL DEPTH ASSUMED
CAUTION  SECNO=     2.500  PROFILE= 2  MINIMUM SPECIFIC ENERGY

CAUTION  SECNO=     3.000  PROFILE= 1  CRITICAL DEPTH ASSUMED
CAUTION  SECNO=     3.000  PROFILE= 1  MINIMUM SPECIFIC ENERGY
CAUTION  SECNO=     3.000  PROFILE= 2  CRITICAL DEPTH ASSUMED
CAUTION  SECNO=     3.000  PROFILE= 2  MINIMUM SPECIFIC ENERGY

CAUTION  SECNO=     6.000  PROFILE= 1  CRITICAL DEPTH ASSUMED
CAUTION  SECNO=     6.000  PROFILE= 1  PROBABLE MINIMUM SPECIFIC ENERGY
CAUTION  SECNO=     6.000  PROFILE= 1  20 TRIALS ATTEMPTED TO BALANCE WSEL
CAUTION  SECNO=     6.000  PROFILE= 2  CRITICAL DEPTH ASSUMED
CAUTION  SECNO=     6.000  PROFILE= 2  PROBABLE MINIMUM SPECIFIC ENERGY
CAUTION  SECNO=     6.000  PROFILE= 2  20 TRIALS ATTEMPTED TO BALANCE WSEL

CAUTION  SECNO=     6.900  PROFILE= 1  CRITICAL DEPTH ASSUMED
CAUTION  SECNO=     6.900  PROFILE= 1  MINIMUM SPECIFIC ENERGY
CAUTION  SECNO=     6.900  PROFILE= 2  CRITICAL DEPTH ASSUMED
CAUTION  SECNO=     6.900  PROFILE= 2  MINIMUM SPECIFIC ENERGY

NOTE     SECNO=     8.000  PROFILE= 1  WSEL BASED ON X5 CARD
NOTE     SECNO=     8.000  PROFILE= 2  WSEL BASED ON X5 CARD

CAUTION  SECNO=    10.000  PROFILE= 1  CRITICAL DEPTH ASSUMED
CAUTION  SECNO=    10.000  PROFILE= 1  PROBABLE MINIMUM SPECIFIC ENERGY
CAUTION  SECNO=    10.000  PROFILE= 1  20 TRIALS ATTEMPTED TO BALANCE WSEL
CAUTION  SECNO=    10.000  PROFILE= 2  CRITICAL DEPTH ASSUMED
CAUTION  SECNO=    10.000  PROFILE= 2  PROBABLE MINIMUM SPECIFIC ENERGY
CAUTION  SECNO=    10.000  PROFILE= 2  20 TRIALS ATTEMPTED TO BALANCE WSEL

CAUTION  SECNO=    12.000  PROFILE= 1  CRITICAL DEPTH ASSUMED
CAUTION  SECNO=    12.000  PROFILE= 1  PROBABLE MINIMUM SPECIFIC ENERGY
CAUTION  SECNO=    12.000  PROFILE= 1  20 TRIALS ATTEMPTED TO BALANCE WSEL
CAUTION  SECNO=    12.000  PROFILE= 2  CRITICAL DEPTH ASSUMED
CAUTION  SECNO=    12.000  PROFILE= 2  PROBABLE MINIMUM SPECIFIC ENERGY
CAUTION  SECNO=    12.000  PROFILE= 2  20 TRIALS ATTEMPTED TO BALANCE WSEL
```

FLOODWAY DATA, RANDOLPH DRAIN
PROFILE NO. 2

STATION	FLOODWAY WIDTH	FLOODWAY SECTION AREA	FLOODWAY MEAN VELOCITY	WATER SURFACE ELEVATION WITH FLOODWAY	WITHOUT FLOODWAY	DIFFERENCE
1.000	33.	147.	3.4	888.8	888.8	.0
2.000	28.	120.	4.1	888.8	888.8	.0
2.250	25.	75.	6.6	888.9	888.9	.0
2.500	29.	64.	7.7	890.1	890.1	.0
3.000	86.	93.	5.3	896.3	896.3	.0
3.500	129.	139.	3.6	902.3	902.2	.1
3.750	95.	149.	3.3	904.1	904.1	.0
4.000	127.	302.	1.6	904.9	904.9	.0
5.000	179.	311.	1.0	905.7	905.6	.1
5.500	211.	600.	.5	905.7	905.7	.0
6.000	62.	46.	3.9	906.2	906.2	.0
6.900	21.	32.	5.7	907.9	907.9	.0
6.940	25.	45.	4.0	908.7	908.7	.0
6.950	25.	45.	4.0	908.8	908.8	.0
7.000	25.	45.	4.0	909.7	909.7	.0
8.000	39.	128.	1.4	915.1	915.1	.0
9.000	30.	96.	1.4	915.2	915.2	.0
10.000	25.	25.	5.7	915.9	915.9	.0
11.000	18.	27.	5.1	917.6	917.6	.0
11.900	24.	40.	3.5	919.1	919.1	.0
12.000	40.	29.	4.8	921.0	921.0	.0

1

THIS RUN EXECUTED 01-13-92

****
HEC2 RELEASE DATED NOV 76 UPDATED MAY 1984
ERROR CORR - 01,02,03,04,05,06
MODIFICATION - 50,51,52,53,54,55,56
IBM-PC-XT VERSION AUGUST 1985
****

RANDOLPH STREET DRAIN

EXISTING & PROPOSED

CONDITION

COMPARISON TABLES

RANDOLPH STREET DRAIN - FLOOD STUDY: 100 YEAR FLOOD PROFILE COMPARISON TABLE.

McNEELY & LINCOLN ASSOCIATES						FEMA			
X-SEC #	EXIST FLOW	EXIST CWSEL	PROP FLOW	PROP CWSEL	GROUND ELEVATION	X-SEC #	FLOW	CWSEL	GROUND ELEVATION
1.00			433.0	882.50	877.80				
1.25			433.0	885.91	881.53	M	400	884.00	881.53
1.50			433.0	888.55	882.63	N	400	888.00	882.63
2.00	494.0	888.80	433.0	888.99	883.06				
2.10			433.0	889.05	883.06				
2.25	494.0	888.92	433.0	889.36	884.60				
2.40			433.0	889.66	885.30				
2.50	494.0	890.15	433.0	890.35	886.30				
2.60			433.0	891.43	889.50				
2.70			433.0	893.28	890.21				
2.80			433.0	896.74	890.70				
2.90			433.0	897.15	891.00				
2.95			433.0	897.19	891.00				
						O	400	895.31	892.00
3.00	494.0	896.25	433.0	897.22	893.20				
3.50	494.0	902.23	433.0	902.29	899.20				
3.75	494.0	904.08	433.0	903.93	899.80				
4.00	494.0	904.89	433.0	904.70	900.50				
4.25			433.0	904.72	900.80				
4.50			433.0	905.88	900.90				
4.75			433.0	905.91	901.30				
						P	400	904.20	901.80
5.00	323.0	905.63	323.0	906.09	902.60				
						Q	400	905.81	902.5
5.50	323.0	905.70	323.0	906.14	902.60				
						R	400	906.50	904.00
6.00	180.0	906.22	180.0	906.19	905.10				
6.90	180.0	907.88	180.0	907.84	905.30				
6.94	180.0	908.65	180.0	908.78	905.38				
6.95	180.0	908.83	180.0	908.97	905.53				
						S	400	910.60	905.60
7.00	180.0	909.72	180.0	909.89	906.43				
8.00	180.0	915.11	180.0	915.11	909.10	T	400	914.75	909.10
9.00	139.0	915.15	139.0	915.17	910.20				
10.00	139.0	915.89	139.0	915.89	914.50				
11.00	139.0	917.64	139.0	918.10	915.10				
11.90	139.0	919.14	139.0	919.43	916.10				
12.00	139.0	920.97	139.0	920.98	920.20	U	400	922.20	920.20

RANDOLPH STREET DRAIN - FLOOD STUDY: FLOW IN cfs. COMPARISON TABLE.


EXIST. X-SEC. #	"EXISTING CONDITION" 1987 - STUDY FLOW 10-Yr	FLOW 50-Yr	FLOW 100-Yr	FLOW 500-Yr	PROPOSED X-SEC. #	"PROPOSED CONDITION" 1991 - STUDY FLOW 10-Yr	FLOW 50-Yr	FLOW 100-Yr	FLOW 500-Yr
					1.00	215.0	363.0	433.0	541.0
					1.25	215.0	363.0	433.0	541.0
1.00	236.0	414.0	494.0	609.0	1.50	215.0	363.0	433.0	541.0
2.00	236.0	414.0	494.0	609.0	2.00	215.0	363.0	433.0	541.0
					2.10	215.0	363.0	433.0	541.0
2.25	236.0	414.0	494.0	609.0	2.25	215.0	363.0	433.0	541.0
					2.40	215.0	363.0	433.0	541.0
2.50	236.0	414.0	494.0	609.0	2.50	215.0	363.0	433.0	541.0
					2.60	215.0	363.0	433.0	541.0
					2.70	215.0	363.0	433.0	541.0
					2.80	215.0	363.0	433.0	541.0
					2.90	215.0	363.0	433.0	541.0
					2.95	215.0	363.0	433.0	541.0
3.00	236.0	414.0	494.0	609.0	3.00	215.0	363.0	433.0	541.0
3.50	236.0	414.0	494.0	609.0	3.50	215.0	363.0	433.0	541.0
3.75	236.0	414.0	494.0	609.0	3.75	215.0	363.0	433.0	541.0
4.00	236.0	414.0	494.0	609.0	4.00	215.0	363.0	433.0	541.0
					4.25	207.0	356.0	433.0	532.0
					4.50	207.0	356.0	433.0	532.0
					4.75	207.0	356.0	433.0	532.0
5.00	159.0	265.0	323.0	407.0	5.00	159.0	265.0	323.0	407.0
5.50	159.0	265.0	323.0	407.0	5.50	159.0	265.0	323.0	407.0
6.00	110.0	161.0	180.0	232.0	6.00	110.0	161.0	180.0	232.0
6.90	110.0	161.0	180.0	232.0	6.90	110.0	161.0	180.0	232.0
6.94	110.0	161.0	180.0	232.0	6.94	110.0	161.0	180.0	232.0
6.95	110.0	161.0	180.0	232.0	6.95	110.0	161.0	180.0	232.0
7.00	110.0	161.0	180.0	232.0	7.00	110.0	161.0	180.0	232.0
8.00	110.0	161.0	180.0	232.0	8.00	110.0	161.0	180.0	232.0
9.00	73.0	106.0	139.0	207.0	9.00	73.0	106.0	139.0	207.0
10.00	73.0	106.0	139.0	207.0	10.00	73.0	106.0	139.0	207.0
11.00	73.0	106.0	139.0	207.0	11.00	73.0	106.0	139.0	207.0
11.90	73.0	106.0	139.0	207.0	11.90	73.0	106.0	139.0	207.0
12.00	73.0	106.0	139.0	207.0	12.00	73.0	106.0	139.0	207.0

RANDOLPH STREET DRAIN - FLOOD STUDY: WATER SURFACE ELEVATION COMPARISON TABLE.

EXIST. X-SEC. #	"EXISTING CONDITION" 1987 - STUDY CWSEL 10-Yr	CWSEL 50-Yr	CWSEL 100-Yr	CWSEL 500-Yr	PROPOSED X-SEC. #	GROUND ELEVATION	"PROPOSED CONDITION" 1991 - STUDY CWSEL 10-Yr	CWSEL 50-Yr	CWSEL 100-Yr	CWSEL 500-Yr
					1.00	877.80	881.60	882.00	882.50	883.0
					1.25	881.53	884.69	885.57	885.91	886.4
1.00	886.34	888.05	888.80	891.09	1.50	882.63	886.34	887.89	888.55	889.5
2.00	886.36	888.06	888.80	891.09	2.00	883.06	886.46	888.24	888.99	890.0
					2.10	883.06	886.66	888.33	889.05	890.1
2.25	887.25	888.20	888.92	891.12	2.25	884.60	887.48	888.74	889.36	890.3
					2.40	885.30	888.27	889.18	889.66	890.4
2.50	889.16	889.88	890.15	891.22	2.50	886.30	889.25	890.03	890.35	890.9
					2.60	889.50	890.90	891.27	891.43	891.6
					2.70	890.21	892.14	892.94	893.28	893.7
					2.80	890.70	894.49	896.07	896.74	898.3
					2.90	891.00	894.72	896.42	897.15	898.7
					2.95	891.00	894.76	896.46	897.19	898.7
3.00	895.68	896.10	896.25	896.44	3.00	893.20	895.81	896.49	897.22	898.7
3.50	901.75	902.11	902.23	902.41	3.50	899.20	901.96	902.17	902.29	902.4
3.75	903.31	903.88	904.08	904.31	3.75	899.80	903.13	903.74	903.93	904.2
4.00	903.99	904.66	904.89	905.15	4.00	900.50	903.87	904.48	904.70	904.9
					4.25	900.80	903.90	904.50	904.72	905.0
					4.50	900.90	904.75	905.70	905.88	906.0
					4.75	901.30	904.86	905.72	905.91	906.1
5.00	904.82	905.40	905.63	905.91	5.00	902.60	905.07	905.88	906.09	906.3
5.50	904.88	905.47	905.70	905.99	5.50	902.60	905.12	905.92	906.14	906.3
6.00	906.01	906.17	906.22	906.35	6.00	905.10	905.99	906.14	906.19	906.3
6.90	907.29	907.73	907.88	908.24	6.90	905.30	907.40	907.72	907.84	908.1
6.94	907.97	908.49	908.65	909.07	6.94	905.38	907.96	908.56	908.78	909.1
6.95	908.16	908.67	908.83	909.23	6.95	905.53	908.22	908.78	908.97	909.3
7.00	909.07	909.56	909.72	910.12	7.00	906.43	909.23	909.73	909.89	910.3
8.00	913.48	914.41	915.11	917.43	8.00	909.10	913.48	914.41	915.11	917.4
9.00	913.56	914.48	915.15	917.44	9.00	910.20	913.59	914.50	915.17	917.4
10.00	915.54	915.71	915.89	917.43	10.00	914.50	915.54	915.73	915.89	917.4
11.00	917.14	917.43	917.64	917.76	11.00	915.10	917.49	917.81	918.10	918.1
11.90	918.36	918.78	919.14	919.81	11.90	916.10	918.63	919.07	919.43	920.0
12.00	920.75	920.86	920.97	921.12	12.00	920.20	920.76	920.88	920.98	921.1

RANDOLPH STREET DRAIN


PRECIPITATION DATA



SOURCE: 210-VI-TR-55, Second Ed., June 1986

SELECT - 3.5 Inches

Figure B-5.—Ten-year, 24-hour rainfall.



SOURCE: 210-VI-TR-55, Second Ed., June 1986

SELECT - 4.45 Inches

Figure B-7.—Fifty-year, 24-hour rainfall.

CITY OF NORTHVILLE

RANDOLPH STREET DRAIN

FLOOD STUDY

PROPOSED CONDITION

REVISED PER DNR LT: DT:1-30-92

HYDROLOGIC & HYDRAULIC


ANALYSIS

BETWEEN LEXINGTON BLVD. AND BECK ROAD

BY

McNEELY & LINCOLN ASSOCIATES, INC.

459 EAST CADY, NORTHVILLE MI-48167



SOURCE: 210-VI-TR-55, Second Ed., June 1986

SELECT - 4.85 Inches

Figure 3-8.—One-hundred-year, 24-hour rainfall.

RANDOLPH STREET DRAIN

PROPOSED CONDITION

HYDROLOGIC ANALYSIS

****

FLOOD HYDROGRAPH PACKAGE HEC-1 (IBM XT 512K VERSION) -FEB 1,1985

U.S. ARMY CORPS OF ENGINEERS, THE HYDROLOGIC ENGINEERING CENTER, 609 SECOND STREET, DAVIS, CA. 95616

****

THIS HEC-1 VERSION CONTAINS ALL OPTIONS EXCEPT ECONOMICS, AND THE NUMBER OF PLANS ARE REDUCED TO 3

```
LINE      ID.....1.....2.....3.....4.....5.....6.....7.....8.....9.....10

    1     ID   RANDOLPH DRAIN FLOOD ANALYSIS    DEC 6, 1991    FILE: 100RR1
    2     ID   MULTIFLOOD ANALYSIS (10YR, 50YR, 100YR, 500YR)
    3     ID   DEVELOPED CONDITIONS
          *DIAGRAM
    4     IT       5  1MAR86    0000     300
    5     IO       5       0      20
    6     IN      30  1MAR86    0000
    7     JR    PREC  1.0000  1.2714  1.3857  1.5286

    8     KK  RANDB2  RANDOLPH DISTRICT
    9     PB    3.50
   10     PC  0.0000  0.0053  0.0108  0.0164  0.0223  0.0284  0.0347  0.0414  0.0483  0.0555
   11     PC  0.0623  0.0712  0.0797  0.0887  0.0984  0.1089  0.1203  0.1328  0.1467  0.1625
   12     PC  0.1808  0.2042  0.2351  0.2833  0.6632  0.7351  0.7724  0.7989  0.8197  0.8380
   13     PC  0.8538  0.8676  0.8801  0.8914  0.9019  0.9115  0.9206  0.9291  0.9371  0.9446
   14     PC  0.9519  0.9588  0.9653  0.9717  0.9777  0.9836  0.9892  0.9947  1.0000
   15     KM          SCS RUNOFF FOR RANDOLPH DISTRICT B2
   16     BA   0.100
   17     LS       0      68
   18     UD    0.66

   19     KK  RANDB2
   20     KM        ROUTING FOR POND AT NW CORNER OF BECK AND 9 MILE
   21     RS       1    ELEV   947.6       0
   22     SA       0    1.62    1.82    2.03    2.22    2.43    2.56
   23     SQ       0    1.90    7.40   12.00   15.20   17.60   95.00
   24     SE   947.6     948   948.5   949.0   949.5   950.0   950.3

   25     KK  RANDB2
   26     KM        CHANNEL ROUTE TO CULVERT, W. SIDE OF BECK
   27     RK     755 0.0071    0.030       0

   28     KK  RANDB1
   29     KM        SCS RUNOFF FOR RANDOLPH DISTRICT B1
   30     BA   0.084
   31     LS       0      68
   32     UD    0.26

   33     KK   RANDB
   34     KM        COMBINE RANDOLPH B1 AND B2
   35     HC       2

   36     KK   RANDB
   37     KM        CHANNEL ROUTE TO RANDOLPH A POND (CULVERT)
   38     RK    1045  .0065    0.024            CIRC       2

   39     KK   RANDB
   40     KM        CHANNEL ROUTE TO RANDOLPH A POND (DITCH)
   41     RK     435    1.84     .03            TRAP       2       4
```

```
LINE      ID.....1.....2.....3.....4.....5.....6.....7.....8.....9.....10
   42     KK  RANDA
   43     KM       SCS RUNOFF FOR RANDOLPH A DISTRICT
   44     BA  0.108
   45     LS      0      72
   46     UD   0.32

   47     KK  RANDA
   48     KM       COMBINE RANDOLPH A RUNOFF WITH RANDOLPH B OUTFLOW
   49     HC      2

   50     KK  RANDA
   51     KM       RANDOLPH A POND ROUTING
   52     RS      1    ELEV   926.2       0
   53     SA      0    0.01    0.72    2.07    2.17    2.22    2.35    2.80
   54     SQ      0     9.0     45.     97.    140.    180.    230.    650.
   55     SE  926.2     927     928   930.2   930.3   930.4   930.5   931.0

   56     KK  CTYLW
   57     KM       SCS RUNOFF FOR CITY LINE WEST DISTRICT
   58     BA  0.031
   59     LS      0      78
   60     UD   0.24

   61     KK  CTYLW
   62     KM       COMBINE CITY LINE WEST RUNOFF WITH RANDOLPH A FLOW
   63     HC      2

   64     KK  RANDA
   65     KM       CHANNEL ROUTE TO 60" CULVERT ENTRANCE BASIN
   66     RK    1450  0.0033    0.04                0       0       2

   67     KK  CTYLE
   68     KM       SCS RUNOFF FOR CITY LINE EAST DISTRICT
   69     BA  0.062
   70     LS      0      78
   71     UD   0.24

   72     KK    60"
   73     KM       COMBINE RANDOLPH A AND CITY LINE OUTFLOWS
   74     HC      2

   75     KK    60"
   76     KM       ROUTE COMBINED FLOWS AHEAD OF 60" CULVERT
   77     RS      1    ELEV   910.3       0
   78     SA  0.033   0.082   0.140   0.198   0.256     1.0
   79     SQ      0      55      84     160     212     278
   80     SE  909.3     911     913     915     917     919

   81     KK    60"
   82     KM       CHANNEL ROUTE THROUGH 60" CULVERT
   83     RK     580   0.006   0.013            CIRC       5
```

```
LINE      ID.....1.....2.....3.....4.....5.....6.....7.....8.....9.....10

  84      KK    60"
  85      KM        CHANNEL ROUTE THROUGH CULVERT OUTLET DITCH
  86      RK     550  0.0056   0.030            TRAP       4       3

  87      KK   NVEST
  88      KM        SCS RUNOFF FOR NORTHVILLE ESTATES
  89      BA   0.100
  90      LS       0      70
  91      UD    0.37

  92      KK   ABBEY
  93      KM        SCS RUNOFF FOR DEVELOPED ABBEY KNOLL ESTATES SUBDIVISION
  94      BA   0.072
  95      LS       0      80
  96      UD    0.42

  97      KK    RANJ
  98      KM        SCS RUNOFF FOR RANDOLPH JUNCTION (NOVI - WEST OF LEXINGTON GREEN)
  99      BA   0.182
 100      LS       0      69
 101      UD    0.65

 102      KK   JUNCT
 103      KM        COMBINE RANDOLPH JUNCTION, 60" CULVERT & NORTHVILLE ESTATES/ABBEY KNOLL
 104      HC       4

 105      KK   JUNCT
 106      KM        ROUTE COMBINED FLOWS THROUGH ABBEY POND/WETLANDS
 107      RS       1    FLOW       2       0
 108      SA    1.24    4.30    5.90    8.30   10.28   11.20
 109      SQ       0      10      48     250     573     747
 110      SE   902.8   903.5     904     905     906   906.5

 111      KK   LEXGR
 112      KM        SCS RUNOFF FOR LEXINGTON GREEN SUBDIVISION
 113      BA   0.144
 114      LS       0      72
 115      UD    0.30

 116      KK   LEXGR
 117      KM        LEXINGTON GREEN DETENTION POND ROUTING
 118      RS       1    ELEV   904.6       0
 119      SA    1.55    1.65    1.84    1.88    1.94    2.00
 120      SQ       0     1.3     4.0      39     159     350
 121      SE   904.6     905   905.8     906   906.5     907

 122      KK   LEXGR
 123      KM        CHANNEL ROUTING OF LEXINGTON GREEN DISCHARGE
 124      RK     950   0.001   0.040            TRAP       0       5
```

```
LINE      ID.....1.....2.....3.....4.....5.....6.....7.....8.....9.....10

  125     KK  JUNCT
  126     KM       COMBINE LEXINGTON GREEN, RANDOLPH JUNCTION, N'VILLE ESTATES & 60" FLOWS
  127     HC       2

  128     KK  PHLEX
  129     KM       SCS RUNOFF UPSTREAM OF LEXINGTON GREEN #2 DETENTION POND
  130     BA  0.053
  131     LS       0       72
  132     UD   0.42

  133     KK  PHLEX
  134     KM       MODIFIED PULS ROUTING LEXINGTON GREEN DETENTION POND
  135     RS       1    STOR        0        0
  136     SV       0    0.82     2.19
  137     SQ       0    2.76    39.79

  138     KK  PHSL2
  139     BA  0.030
  140     LS       0       72
  141     UD   0.42

  142     KK  PHILLS
  143     KM       COMBINE PHLEX AND PHSL2
  144     HC       2

  145     KK  PHILLS
  146     KM       MODIFIED PULS ROUTING PHEASANT HILLS #2 WETLAND AREA
  147     RS       1    STOR        0        0
  148     SV       0     .12     1.01     2.52
  149     SQ       0     1.8     15.9     24.0

  150     KK  PHILLS
  151     KM       CHANNEL ROUTE THROUGH 21" X 15" C.S.P
  152     RK      60  0.0033   0.025            TRAP    1.75

  153     KK  PHILLS
  154     KM       CHANNEL ROUTE THROUGH CULVERT OUTLET DITCH
  155     RK     450   0.004   0.030            TRAP       4       3

  156     KK  PHILL1
  157     KM       COMBINE JUNCT & PHILLS
  158     HC       2

  159     KK  PHILL1
  160     KM       CHANNEL ROUTE UPSTREAM OF COLD SPRING DRIVE CULVERTS
  161     RS       1    STOR        0
  162     RC    0.03    0.04    0.03     125   .0036
  163     RX       0      35     116     123     131     134     218     252
  164     RY   904.9   904.0   903.4   901.4   901.4   903.4   904.0   905.0
```

```
LINE      ID.....1.....2.....3.....4.....5.....6.....7.....8.....9.....10

  165     KK  PHILL1
  166     KM       CHANNEL ROUTE THROUGH CULVERTS (5#) AT COLD SPRING DR.
  167     RK      60  0.0017   0.025            TRAP    17.5

  168     KK  PHILL1
  169     KM       CHANNEL ROUTE TO CULVERT AT MACDONALD DRIVE
  170     RK    1630   0.004   0.030            TRAP       4       3

  171     KK  PHILL2
  172     KM       SCS RUNOFF FOR PHEASANT HILLS
  173     BA  0.062
  174     LS       0      77
  175     UD   0.25

  176     KK  PHILL1
  177     KM       COMBINE PHILL1 & PHILL2
  178     HC       2

  179     KK  PHILL1
  180     KM       MODIFIED PULS ROUTING UPSTREAM OF MACDONALDS DRIVE
  181     RS       1    STOR       0       0
  182     SV       0    0.01    0.08    0.23   0.482   0.907   1.607   2.697   4.213   6.187
  183     SQ       0      50     100     150     195     270     340     420     498     858

  184     KK  PHILL1
  185     KM       CHANNEL ROUTE THROUGH 2# OF 66" X 51" C.S.P
  186     RK      68   0.007   0.025            TRAP      11

  187     KK  PHILL1
  188     KM       CHANNEL ROUTE TO LEXINGTON DRIVE
  189     RK     300   0.002   0.030            TRAP       4       3

  190     KK  PHILL1
  191     KM       CHANNEL ROUTE THROUGH 2 # OF 72" CIRC. CULVERTS
  192     RK      60   0.023   0.025            CIRC      12
  193     ZZ
```

(***) RUNOFF ALSO COMPUTED AT THIS LOCATION

1 ****

FLOOD HYDROGRAPH PACKAGE HEC-1 (IBM XT 512K VERSION) -FEB 1,1985

U.S. ARMY CORPS OF ENGINEERS, THE HYDROLOGIC ENGINEERING CENTER, 609 SECOND STREET, DAVIS, CA. 95616

****

RANDOLPH DRAIN FLOOD ANALYSIS DEC 6, 1991 FILE: 100RR1

MULTIFLOOD ANALYSIS (10YR, 50YR, 100YR, 500YR)

DEVELOPED CONDITIONS

5 IO OUTPUT CONTROL VARIABLES

IPRNT	5	PRINT CONTROL
IPLOT	0	PLOT CONTROL
QSCAL	20.	HYDROGRAPH PLOT SCALE

IT HYDROGRAPH TIME DATA

NMIN	5	MINUTES IN COMPUTATION INTERVAL
IDATE	1MAR86	STARTING DATE
ITIME	0000	STARTING TIME
NQ	300	NUMBER OF HYDROGRAPH ORDINATES
NDDATE	2MAR86	ENDING DATE
NDTIME	0055	ENDING TIME

COMPUTATION INTERVAL .08 HOURS

TOTAL TIME BASE 24.92 HOURS

ENGLISH UNITS

JP MULTI-PLAN OPTION

NPLAN	1	NUMBER OF PLANS

JR MULTI-RATIO OPTION

RATIOS OF PRECIPITATION

1.00 1.27

1.39 1.53

WARNING *** TIME INTERVAL IS GREATER THAN .29*LAG

*** WARNING *** MODIFIED PULS ROUTING MAY BE NUMERICALLY UNSTABLE FOR OUTFLOWS BETWEEN 0. TO 650.
THE ROUTED HYDROGRAPH SHOULD BE EXAMINED FOR OSCILLATIONS OR OUTFLOWS GREATER THAN PEAK INFLOWS.
THIS CAN BE CORRECTED BY DECREASING THE TIME INTERVAL OR INCREASING STORAGE (USE A LONGER REACH.)

WARNING *** TIME INTERVAL IS GREATER THAN .29*LAG

WARNING *** TIME INTERVAL IS GREATER THAN .29*LAG

*** WARNING *** MODIFIED PULS ROUTING MAY BE NUMERICALLY UNSTABLE FOR OUTFLOWS BETWEEN 0. TO 55.
THE ROUTED HYDROGRAPH SHOULD BE EXAMINED FOR OSCILLATIONS OR OUTFLOWS GREATER THAN PEAK INFLOWS.
THIS CAN BE CORRECTED BY DECREASING THE TIME INTERVAL OR INCREASING STORAGE (USE A LONGER REACH.)

*** WARNING *** MODIFIED PULS ROUTING MAY BE NUMERICALLY UNSTABLE FOR OUTFLOWS BETWEEN 1. TO 1031.
THE ROUTED HYDROGRAPH SHOULD BE EXAMINED FOR OSCILLATIONS OR OUTFLOWS GREATER THAN PEAK INFLOWS.

THIS CAN BE CORRECTED BY DECREASING THE TIME INTERVAL OR INCREASING STORAGE (USE A LONGER REACH.)

WARNING *** TIME INTERVAL IS GREATER THAN .29*LAG

*** WARNING *** MODIFIED PULS ROUTING MAY BE NUMERICALLY UNSTABLE FOR OUTFLOWS BETWEEN 0. TO 150.
THE ROUTED HYDROGRAPH SHOULD BE EXAMINED FOR OSCILLATIONS OR OUTFLOWS GREATER THAN PEAK INFLOWS.
THIS CAN BE CORRECTED BY DECREASING THE TIME INTERVAL OR INCREASING STORAGE (USE A LONGER REACH.)

1

PEAK FLOW AND STAGE (END-OF-PERIOD) SUMMARY FOR MULTIPLE PLAN-RATIO ECONOMIC COMPUTATIONS
FLOWS IN CUBIC FEET PER SECOND, AREA IN SQUARE MILES
TIME TO PEAK IN HOURS

					RATIOS APPLIED TO PRECIPITATION			
OPERATION	STATION	AREA	PLAN		RATIO 1	RATIO 2	RATIO 3	RATIO 4
					1.00	1.27	1.39	1.53
HYDROGRAPH AT								
+	RANDB2	.10	1	FLOW	24.	43.	52.	63.
				TIME	12.58	12.58	12.58	12.50
ROUTED TO								
+	RANDB2	.10	1	FLOW	9.	14.	16.	24.
				TIME	13.67	13.75	13.75	13.50
			** PEAK STAGES IN FEET **					
			1	STAGE	948.71	949.37	949.67	950.02
				TIME	13.67	13.75	13.75	13.50
ROUTED TO								
+	RANDB2	.10	1	FLOW	9.	14.	16.	24.
				TIME	13.75	13.75	13.83	13.58
HYDROGRAPH AT								
+	RANDB1	.08	1	FLOW	34.	59.	71.	86.
				TIME	12.17	12.17	12.17	12.08
2 COMBINED AT								
+	RANDB	.18	1	FLOW	35.	61.	74.	90.
				TIME	12.17	12.17	12.17	12.17
ROUTED TO								
+	RANDB	.18	1	FLOW	34.	61.	73.	89.
				TIME	12.17	12.17	12.17	12.17
ROUTED TO								
+	RANDB	.18	1	FLOW	34.	61.	73.	89.
				TIME	12.25	12.17	12.17	12.17
HYDROGRAPH AT								
+	RANDA	.11	1	FLOW	52.	86.	101.	121.
				TIME	12.17	12.17	12.17	12.17
2 COMBINED AT								
+	RANDA	.29	1	FLOW	85.	147.	174.	210.
				TIME	12.17	12.17	12.17	12.17
ROUTED TO								
+	RANDA	.29	1	FLOW	59.	89.	127.	179.
				TIME	12.42	12.50	12.42	12.33


				** PEAK STAGES IN FEET **				
			1	STAGE	928.59	929.84	930.27	930.40
				TIME	12.42	12.50	12.42	12.33
HYDROGRAPH AT								
+	CTYLW	.03	1	FLOW	23.	36.	41.	48.
				TIME	12.08	12.08	12.08	12.08
2 COMBINED AT								
+	CTYLW	.32	1	FLOW	73.	106.	146.	207.
				TIME	12.25	12.25	12.42	12.33
ROUTED TO								
+	RANDA	.32	1	FLOW	73.	106.	139.	207.
				TIME	12.25	12.33	12.50	12.42
HYDROGRAPH AT								
+	CTYLE	.06	1	FLOW	47.	71.	82.	96.
				TIME	12.08	12.08	12.08	12.08
2 COMBINED AT								
+	60"	.38	1	FLOW	115.	166.	189.	250.
				TIME	12.17	12.17	12.17	12.42
ROUTED TO								
+	60"	.38	1	FLOW	112.	162.	182.	233.
				TIME	12.25	12.25	12.25	12.50
				** PEAK STAGES IN FEET **				
			1	STAGE	913.75	915.07	915.84	917.64
				TIME	12.25	12.25	12.25	12.50
ROUTED TO								
+	60"	.38	1	FLOW	112.	162.	181.	233.
				TIME	12.25	12.25	12.25	12.50
ROUTED TO								
+	60"	.38	1	FLOW	110.	161.	180.	232.
				TIME	12.25	12.25	12.33	12.50
HYDROGRAPH AT								
+	NVEST	.10	1	FLOW	39.	67.	80.	96.
				TIME	12.25	12.25	12.25	12.25
HYDROGRAPH AT								
+	ABBEY	.07	1	FLOW	47.	70.	81.	94.
				TIME	12.25	12.25	12.25	12.25
HYDROGRAPH AT								
+	RANJ	.18	1	FLOW	47.	83.	100.	122.
				TIME	12.58	12.50	12.50	12.50
4 COMBINED AT								
+	JUNCT	.74	1	FLOW	231.	362.	421.	508.
				TIME	12.33	12.33	12.33	12.33


ROUTED TO								
+	JUNCT	.74	1	FLOW	159.	265.	323.	407.
				TIME	12.83	12.75	12.67	12.67
			** PEAK STAGES IN FEET **					
			1	STAGE	904.55	905.05	905.23	905.49
				TIME	12.83	12.75	12.67	12.67
HYDROGRAPH AT								
+	LEXGR	.14	1	FLOW	71.	118.	139.	166.
				TIME	12.17	12.17	12.17	12.17
ROUTED TO								
+	LEXGR	.14	1	FLOW	45.	101.	125.	153.
				TIME	12.42	12.33	12.25	12.25
			** PEAK STAGES IN FEET **					
			1	STAGE	906.03	906.26	906.36	906.47
				TIME	12.42	12.33	12.25	12.25
ROUTED TO								
+	LEXGR	.14	1	FLOW	46.	99.	121.	148.
				TIME	12.50	12.42	12.42	12.33
2 COMBINED AT								
+	JUNCT	.88	1	FLOW	198.	341.	414.	513.
				TIME	12.67	12.58	12.58	12.58
HYDROGRAPH AT								
+	PHLEX	.05	1	FLOW	22.	37.	43.	52.
				TIME	12.25	12.25	12.25	12.25
ROUTED TO								
+	PHLEX	.05	1	FLOW	10.	21.	26.	32.
				TIME	12.92	12.75	12.67	12.67
HYDROGRAPH AT								
+	PHSL2	.03	1	FLOW	12.	21.	25.	29.
				TIME	12.25	12.25	12.25	12.25
2 COMBINED AT								
+	PHILL	.08	1	FLOW	16.	35.	43.	54.
				TIME	12.67	12.50	12.50	12.42
ROUTED TO								
+	PHILL	.08	1	FLOW	12.	19.	22.	25.
				TIME	13.33	13.33	13.33	13.42
ROUTED TO								
+	PHILL	.08	1	FLOW	12.	19.	22.	25.
				TIME	13.33	13.33	13.33	13.42

ROUTED TO								
+	PHILL	.08	1	FLOW	12.	19.	22.	25.
				TIME	13.33	13.33	13.42	13.42
2 COMBINED AT								
+	PHILL	.97	1	FLOW	206.	356.	431.	533.
				TIME	12.75	12.58	12.58	12.58
ROUTED TO								
+	PHILL	.97	1	FLOW	207.	356.	433.	532.
				TIME	12.75	12.67	12.58	12.58
			** PEAK STAGES IN FEET **					
			1	STAGE	904.02	904.28	904.39	904.51
				TIME	12.75	12.67	12.58	12.58
ROUTED TO								
+	PHILL	.97	1	FLOW	207.	356.	433.	532.
				TIME	12.75	12.67	12.58	12.58
ROUTED TO								
+	PHILL	.97	1	FLOW	206.	354.	431.	531.
				TIME	12.83	12.67	12.67	12.67
HYDROGRAPH AT								
+	PHILL	.06	1	FLOW	44.	67.	78.	91.
				TIME	12.08	12.08	12.08	12.08
2 COMBINED AT								
+	PHILL	1.03	1	FLOW	217.	377.	454.	560.
				TIME	12.75	12.58	12.67	12.58
ROUTED TO								
+	PHILL	1.03	1	FLOW	215.	363.	432.	542.
				TIME	12.83	12.83	12.83	12.75
ROUTED TO								
+	PHILL	1.03	1	FLOW	215.	363.	432.	541.
				TIME	12.83	12.83	12.83	12.75
ROUTED TO								
+	PHILL	1.03	1	FLOW	215.	363.	431.	538.
				TIME	12.92	12.83	12.83	12.83
ROUTED TO								
+	PHILL	1.03	1	FLOW	215.	363.	431.	538.
				TIME	12.92	12.83	12.83	12.83

*** NORMAL END OF HEC-1 ***

SCHEMATIC DIAGRAM OF STREAM NETWORK




81
60"
84
60"
87
NVEST
92
ABBEY
97
RANJ
102
JUNCT
105
JUNCT
111
LEXGR
116
LEXGR
122
LEXGR
125
JUNCT
128
PHLEX
133
PHLEX
138
PHSL2
142
PHILL
145
PHILL
150
PHILL
153
PHILL
156
PHILL

```
                V
                V
159         PHILL
                V
                V
165         PHILL
                V
                V
168         PHILL
                .
                .
171             .       PHILL
                .           .
                .           .
176         PHILL.............
                V
                V
179         PHILL
                V
                V
184         PHILL
                V
                V
187         PHILL
                V
                V
190         PHILL
```

RANDOLPH STREET DRAIN

PROPOSED CONDITION

HYDRAULIC ANALYSIS

1**********

****

* WATER SURFACE PROFILES *

* VERSION OF NOVEMBER 1976 *

* UPDATED MAY 1984 *

* IBM-PC-XT VERSION AUGUST 1985 *

* RUN DATE 02-06-92 TIME 18:06:19 *

****

* U.S. ARMY CORPS OF ENG

* THE HYDROLOGIC ENGINEE

* 609 SECOND STREET, SUI

* DAVIS, CALIFORNIA 9561

* (916) 440-2105 (FTS)

****

```
X     X  XXXXXXX   XXXXX              XXXXX
X     X  X        X     X            X     X
X     X  X        X                        X
XXXXXXX  XXXX     X          XXXXX    XXXXX
X     X  X        X                   X
X     X  X        X     X             X
X     X  XXXXXXX  XXXXX               XXXXXXX
```

1

THIS RUN EXECUTED 02-06-92

HEC 2 · DOT

****

HEC2 RELEASE DATED NOV 76 UPDATED MAY 1984

ERROR CORR - 01,02,03,04,05,06

MODIFICATION - 50,51,52,53,54,55,56

IBM-PC-XT VERSION AUGUST 1985

****

T1 RANDOLPH DRAIN FLOOD LEVEL STUDY DEVELOPED CONDITION

T2 STRETCH BETWEEN BECK ROAD AND 6 FT CULVERTS AT LEXINGTON DR

T3 McNEELY & LINCOLN ASSOCIATES, INC. DT: NOV. 19, 1991

J1	ICHECK	INQ	NINV	IDIR	STRT	METRIC	HVINS	Q	WSEL	FQ
	0.	2.	0.	0.	.000000	.00	.0	0.	881.600	.000

J2	NPROF	IPLOT	PRFVS	XSECV	XSECH	FN	ALLDC	IBW	CHNIM	ITRACE
	1.000	.000	-1.000	.000	.000	.000	.000	.000	.000	.000

J3 VARIABLE CODES FOR SUMMARY PRINTOUT

	150.000	.000	.000	.000	.000	.000	.000	.000	.000	.000

NC	.080	.080	.030	.300	.500	.000	.000	.000	.000	.00
QT	4.000	215.000	363.000	433.000	541.000	.000	.000	.000	.000	.00
X1	1.000	9.000	22.000	60.000	.000	.000	.000	.000	-1.500	.00
GR	884.400	.000	883.700	22.000	880.000	30.000	879.300	31.000	879.300	35.00
GR	880.000	36.000	880.200	46.000	887.100	60.000	891.900	126.000	.000	.00
X1	1.250	8.000	20.000	57.000	60.000	60.000	60.000	.000	-1.100	.00
GR	890.100	.000	888.500	20.000	883.600	32.000	882.630	34.000	882.630	36.00
GR	883.800	44.000	889.800	57.000	890.600	79.000	.000	.000	.000	.00
X1	1.500	8.000	20.000	57.000	60.000	60.000	60.000	.000	.000	.00
X5	4.000	886.830	888.330	889.290	891.330	.000	.000	.000	.000	.00
GR	890.100	.000	888.500	20.000	883.600	32.000	882.630	34.000	882.630	36.00
GR	883.800	44.000	889.800	57.000	890.600	79.000	.000	.000	.000	.00
X1	2.000	8.000	20.000	57.000	15.000	15.000	15.000	.000	.160	.00
GR	889.600	.000	888.500	20.000	883.600	32.000	882.900	34.000	882.900	36.00
GR	883.800	44.000	889.800	57.000	890.600	79.000	.000	.000	.000	.00
X1	2.100	.000	.000	.000	40.000	30.000	37.000	.000	.000	.00
X1	2.250	10.000	10.000	57.000	154.000	157.000	159.000	.000	.000	.00
GR	890.000	.000	889.500	10.000	885.800	32.000	884.600	34.000	884.600	36.00
GR	884.900	40.000	885.100	42.000	888.500	52.000	889.800	57.000	891.200	72.00
X1	2.400	.000	.000	.000	35.000	36.000	36.000	.000	.700	.00
X1	2.450	.000	.000	.000	35.000	35.000	37.000	.000	.300	.00
X1	2.500	11.000	40.000	166.000	84.000	85.000	86.000	.000	.000	.00
GR	894.000	.000	892.500	40.000	890.000	105.000	888.000	127.000	886.400	129.00
GR	886.300	132.000	886.700	136.000	888.000	139.000	892.000	166.000	894.000	206.00
GR	894.000	225.000	.000	.000	.000	.000	.000	.000	.000	.00
X1	2.550	.000	.000	.000	18.000	40.000	30.000	.000	.200	.00
X1	2.560	.000	.000	.000	26.000	60.000	45.000	.000	.300	.00

X1	2.570	.000	.000	.000	13.000	30.000	22.000	.000	.200	.00
ET	.000	7.100	7.100	7.100	7.100	.000	68.500	120.500	.000	.00
X1	2.600	10.000	55.000	192.000	13.000	30.000	23.000	.000	-.400	.00
GR	898.000	.000	896.000	17.000	894.000	31.000	892.000	55.000	890.000	74.00
GR	889.500	88.000	889.500	101.000	890.000	106.000	892.000	192.000	894.000	217.00
NC	.000	.000	.025	.300	.500	.000	.000	.000	.000	.00
X1	2.700	19.000	164.900	179.020	130.000	60.000	75.000	.000	.000	.00
X3	10.000	.000	.000	.000	.000	.000	.000	895.000	895.000	.00
GR	902.470	.000	895.000	75.000	890.220	164.900	890.210	166.000	890.210	167.10
GR	890.210	168.200	890.210	169.300	890.210	170.400	890.210	170.500	890.210	173.50
GR	890.220	174.600	890.220	175.700	890.220	176.800	890.220	177.900	890.220	178.99
GR	892.000	179.020	892.000	214.000	895.000	279.000	900.450	365.000	.000	.00
SB	1.050	2.490	3.000	.000	14.000	4.200	38.600	.000	890.700	890.21
X1	2.800	.000	.000	.000	68.000	68.000	68.000	.000	.000	.00
X2	.000	.000	1.000	895.000	898.660	.000	.000	.000	.000	.00
X3	10.000	.000	.000	.000	.000	.000	.000	898.660	898.660	.00
BT	19.000	.000	902.470	902.470	75.000	900.150	895.000	164.900	898.900	890.22
BT	166.000	898.900	892.450	167.100	898.890	894.210	168.200	898.890	894.450	169.30
BT	898.870	894.200	170.400	898.870	892.450	170.500	898.860	890.210	173.500	898.86
BT	890.210	174.600	898.850	892.450	175.700	898.850	894.200	176.800	898.840	894.45
BT	177.900	898.840	894.200	178.990	898.830	892.460	179.020	898.830	890.220	214.00
BT	899.660	892.000	279.000	899.260	895.000	365.000	900.450	900.450	.000	.00
NC	.000	.000	.040	.800	.900	.000	.000	.000	.000	.00
ET	.000	7.100	7.100	7.100	7.100	.000	92.000	146.000	.000	.00
X1	2.900	9.000	91.000	173.000	10.000	30.000	20.000	.000	-1.000	.00
GR	900.000	.000	898.000	28.000	896.000	54.000	894.000	91.000	892.000	119.00
GR	894.000	173.000	896.000	186.000	898.000	215.000	900.400	240.000	.000	.00
X1	2.950	.000	.000	.000	40.000	150.000	100.000	.000	.000	.00
X1	3.000	12.000	63.000	72.000	264.000	15.000	259.000	.000	.000	.00
GR	898.700	.000	896.400	25.000	894.900	50.000	894.600	63.000	893.300	64.00
GR	893.200	67.000	893.600	71.000	894.600	72.000	895.500	100.000	896.700	125.00
GR	898.200	143.000	899.800	164.000	.000	.000	.000	.000	.000	.00
NC	.060	.060	.035	.300	.500	.000	.000	.000	.000	.00
X1	3.500	14.000	135.000	146.000	710.000	615.000	750.000	.000	-1.300	.00
GR	906.000	.000	904.000	66.000	903.000	91.000	902.800	116.000	902.100	135.00
GR	901.300	136.000	900.500	140.000	901.400	143.000	901.800	146.000	902.400	166.00
GR	903.100	191.000	904.100	216.000	905.300	241.000	906.500	255.000	.000	.00
X1	3.750	10.000	281.000	291.000	195.000	265.000	250.000	.000	.000	.00
GR	904.400	.000	904.000	255.000	902.000	280.000	901.200	281.000	899.900	285.00
GR	899.800	288.000	901.700	291.000	902.000	315.000	904.000	350.000	906.000	387.00
X1	4.000	14.000	135.000	146.000	230.000	245.000	265.000	.000	.000	.00
GR	906.000	.000	904.000	66.000	903.000	91.000	902.300	116.000	902.100	135.00
GR	901.300	136.000	900.500	140.000	901.400	143.000	901.800	146.000	902.400	166.00
GR	903.100	191.000	904.100	216.000	905.300	241.000	906.500	255.000	.000	.00
QT	4.000	207.000	356.000	433.000	532.000	.000	.000	.000	.000	.00

NC	.000	.000	.025	.600	.800	.000	.000	.000	.000	.00
X1	4.250	43.000	144.250	167.750	50.000	50.000	50.000	.000	.000	.00
X3	10.000	.000	.000	.000	.000	.000	.000	903.300	903.300	.00
GR	906.880	.000	904.800	50.000	904.100	107.000	900.900	143.250	900.800	144.25
GR	900.800	144.350	900.800	144.750	900.800	146.000	900.800	147.250	900.800	147.65
GR	900.800	147.750	900.800	149.250	900.800	149.350	900.800	149.750	900.800	151.00
GR	900.800	152.250	900.800	152.650	900.800	152.750	900.800	154.250	900.800	154.35
GR	900.800	154.750	900.800	156.000	900.800	157.250	900.800	157.650	900.800	157.75
GR	900.800	159.250	900.800	159.350	900.800	159.750	900.800	161.000	900.800	162.25
GR	900.800	162.650	900.800	162.750	900.800	164.250	900.800	164.350	900.800	164.75
GR	900.800	166.000	900.800	167.250	900.810	167.650	900.810	167.750	900.900	168.75
GR	903.000	200.000	904.300	250.000	908.440	377.000	.000	.000	.000	.00
SB	1.050	3.330	3.000	.000	23.500	8.000	34.000	.000	900.900	900.80
X1	4.500	.000	.000	.000	60.000	60.000	60.000	.000	.000	.00
X2	.000	.000	1.000	903.300	905.010	.000	.000	.000	.000	.00
X3	10.000	.000	.000	.000	.000	.000	.000	905.010	905.600	.00
BT	43.000	.000	906.880	906.880	50.000	905.540	904.800	107.000	905.010	904.10
BT	143.250	905.190	900.900	144.250	905.190	900.800	144.350	905.190	901.220	144.75
BT	905.200	903.000	146.000	905.220	903.220	147.250	905.230	903.000	147.650	905.24
BT	901.220	147.750	905.250	900.800	149.250	905.260	900.800	149.350	905.280	901.22
BT	149.750	905.290	903.000	151.000	905.300	903.220	152.250	905.310	903.000	152.65
BT	905.320	901.220	152.750	905.340	900.800	154.250	905.350	900.800	154.350	905.36
BT	901.220	154.750	905.370	903.000	156.000	905.380	903.220	157.250	905.400	903.00
BT	157.650	905.410	901.220	157.750	905.420	900.800	159.250	905.430	900.800	159.35
BT	905.440	901.220	159.750	905.460	903.000	161.000	905.470	903.220	162.250	905.48
BT	903.000	162.650	905.490	901.220	162.750	905.500	900.800	164.250	905.520	900.80
BT	164.350	905.530	901.220	164.750	905.540	903.000	166.000	905.550	903.220	167.25
BT	905.560	903.000	167.650	905.580	901.220	167.750	905.590	900.800	168.750	905.60
BT	900.900	200.000	906.060	903.000	250.000	906.600	904.300	377.000	908.440	908.44
NC	.000	.000	.040	.400	.600	.000	.000	.000	.000	.00
X1	4.750	8.000	163.000	176.000	110.000	20.000	60.000	.000	.000	.00
GR	906.880	.000	906.200	44.000	904.000	80.000	902.200	163.000	901.300	170.00
GR	902.300	176.000	904.000	262.000	908.500	290.000	.000	.000	.000	.00
QT	4.000	159.000	265.000	323.000	407.000	.000	.000	.000	.000	.00
ET	.000	7.100	7.100	7.100	7.100	.000	125.000	332.000	.000	.00
X1	5.000	15.000	214.000	232.000	685.000	790.000	745.000	.000	.000	.00
GR	906.000	.000	908.000	125.000	906.000	135.000	904.000	145.000	903.800	157.00
GR	903.500	182.000	903.600	207.000	903.100	214.000	902.600	225.000	903.100	229.00
GR	903.600	232.000	903.600	257.000	904.500	282.000	905.400	307.000	906.200	332.00
ET	.000	9.100	9.100	9.100	9.100	.000	.000	.000	110.000	330.00
X1	5.500	19.000	170.000	270.000	280.000	305.000	285.000	.000	.000	.00
GR	906.000	.000	908.000	110.000	906.000	118.000	904.000	126.000	902.800	145.00
GR	902.900	170.000	902.600	195.000	902.700	220.000	902.600	245.000	903.000	270.00
GR	903.100	295.000	903.000	320.000	903.700	345.000	904.000	370.000	904.000	395.00
GR	904.400	420.000	905.100	445.000	906.000	465.000	906.400	473.000	.000	.00
NC	.000	.000	.040	.600	.950	.000	.000	.000	.000	.00
QT	4.000	110.000	161.000	180.000	232.000	.000	.000	.000	.000	.00
ET	.000	9.100	9.100	9.100	9.100	.000	.000	.000	113.000	175.00
X1	6.000	15.000	160.000	170.000	160.000	170.000	160.000	.000	.000	.00
GR	905.200	.000	905.300	25.000	905.700	50.000	905.400	75.000	906.000	100.00

GR	905.700	125.000	905.100	160.000	905.300	170.000	905.900	172.000	906.100	175.00
GR	906.900	200.000	907.400	225.000	907.600	250.000	908.800	275.000	909.500	300.00
ET	.000	7.100	7.100	7.100	7.100	.000	.200	31.800	.000	.00
X1	6.900	9.000	10.000	16.250	80.000	80.000	80.000	.000	.000	.00
GR	909.000	.000	906.700	8.000	905.500	10.000	905.300	11.000	905.300	16.00
GR	905.500	16.250	906.200	17.000	906.200	19.000	910.000	32.000	.000	.00
ET	.000	7.100	7.100	7.100	7.100	.000	75.000	208.000	.000	.00
X1	6.940	13.000	95.000	105.000	20.000	20.000	20.000	.000	-1.020	.00
GR	909.800	.000	911.300	25.000	912.200	50.000	912.800	75.000	907.600	95.00
GR	906.700	97.000	906.400	100.000	906.600	102.000	907.500	105.000	916.200	134.00
GR	916.600	159.000	917.300	184.000	917.400	209.000	.000	.000	.000	.00
ET	.000	7.100	7.100	7.100	7.100	.000	75.000	208.000	.000	.00
X1	6.950	13.000	95.000	105.000	40.000	40.000	40.000	.000	-.870	.00
GR	909.800	.000	911.300	25.000	912.200	50.000	912.800	75.000	907.600	95.00
GR	906.700	97.000	906.400	100.000	906.600	102.000	907.500	105.000	916.200	134.00
GR	916.600	159.000	917.300	184.000	917.400	209.000	.000	.000	.000	.00
ET	.000	7.100	7.100	7.100	7.100	.000	75.000	208.000	.000	.00
X1	7.000	.000	.000	.000	225.000	225.000	225.000	.000	.900	.00
ET	.000	7.100	7.100	7.100	7.100	.000	1.000	79.000	.000	.00
X1	8.000	10.000	5.000	55.000	578.000	578.000	578.000	.000	.000	.00
X5	4.000	913.480	914.410	915.110	917.430	.000	.000	.000	.000	.00
GR	917.700	.000	917.400	5.000	910.100	26.000	909.300	27.000	909.300	30.00
GR	909.100	33.500	909.600	34.300	916.700	55.000	917.300	60.000	918.100	80.00
QT	4.000	73.000	106.000	139.000	207.000	.000	.000	.000	.000	.00
ET	.000	7.100	7.100	7.100	7.100	.000	1.000	161.000	.000	.00
X1	9.000	10.000	70.500	95.500	185.000	185.000	185.000	.000	.000	.00
GR	920.200	.000	920.100	25.000	919.700	40.000	918.700	65.000	913.500	70.50
GR	910.200	80.500	910.200	85.500	913.500	95.500	920.000	116.000	921.000	161.00
ET	.000	7.100	7.100	7.100	7.100	.000	1.000	161.000	.000	.00
NC	.000	.000	.000	.600	.950	.000	.000	.000	.000	.00
X1	10.000	10.000	70.500	95.500	8.600	8.600	8.600	.000	.000	.00
GR	920.200	.000	920.100	25.000	919.700	40.000	918.700	65.000	915.500	70.50
GR	914.500	80.500	914.500	85.500	915.500	95.500	920.000	116.000	921.000	161.00
ET	.000	7.100	7.100	7.100	7.100	.000	1.000	108.000	.000	.00
X1	11.000	8.000	37.000	60.000	179.000	179.000	179.000	.000	.000	.00
GR	920.900	.000	918.800	37.000	915.100	50.000	915.100	53.000	918.000	60.00
GR	918.300	90.000	920.000	185.000	920.900	190.000	.000	.000	.000	.00
X1	11.900	7.000	15.000	43.000	300.000	300.000	300.000	.000	.000	.00
GR	924.400	.000	920.000	15.000	916.100	31.500	916.100	34.500	919.400	43.00
GR	920.000	68.000	922.000	88.000	.000	.000	.000	.000	.000	.00
ET	.000	7.100	7.100	7.100	7.100	.000	1.000	309.000	.000	.00
X1	12.000	8.000	70.000	110.000	100.000	100.000	95.000	.000	.000	.00
GR	923.400	.000	922.000	40.000	920.400	70.000	920.200	100.000	920.400	110.00
GR	920.900	135.000	922.000	195.000	924.000	310.000	.000	.000	.000	.00
EJ	.000	.000	.000	.000	.000	.000	.000	.000	.000	.00

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

*PROF 1

CCEV= .300 CEEV= .500

*SECNO 1.000

1.00	3.80	881.60	.00	881.60	881.74	.14	.00	.00	882.20
215.	0.	215.	0.	0.	71.	0.	0.	0.	885.60
.00	.00	3.03	.00	.080	.030	.080	.000	877.80	23.30
.001204	0.	0.	0.	0	0	0	.00	28.59	51.88

0

*SECNO 1.250

3301 HV CHANGED MORE THAN HVINS

3685 20 TRIALS ATTEMPTED WSEL,CWSEL

3693 PROBABLE MINIMUM SPECIFIC ENERGY

3720 CRITICAL DEPTH ASSUMED

1.25	2.54	884.07	884.07	.00	884.87	.80	.17	.33	887.40
215.	0.	215.	0.	0.	30.	0.	0.	0.	888.70
.00	.00	7.20	.00	.080	.030	.080	.000	881.53	28.16
.012139	60.	60.	60.	20	14	0	.00	18.81	46.97

0

*SECNO 1.500

WATER EL=X5 CARD= 886.830

1.50	4.20	886.83	.00	.00	886.99	.16	.18	.19	888.50
215.	0.	215.	0.	0.	67.	0.	0.	0.	889.80
.01	.00	3.19	.00	.080	.030	.080	.000	882.63	24.09
.001286	60.	60.	60.	0	0	0	.00	26.48	50.57

0

*SECNO 2.000

2.00	3.78	886.84	.00	.00	887.03	.19	.02	.02	888.66
215.	0.	215.	0.	0.	62.	0.	0.	0.	889.96
.01	.00	3.49	.00	.080	.030	.080	.000	883.06	24.47
.001670	15.	15.	15.	2	0	0	.00	25.77	50.23

0

*SECNO 2.100

2.10	3.85	886.91	.00	.00	887.09	.18	.06	.00	888.66
215.	0.	215.	0.	0.	63.	0.	0.	0.	889.96
.01	.00	3.39	.00	.080	.030	.080	.000	883.06	24.29
.001536	40.	37.	30.	2	0	0	.00	26.11	50.39

0

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	EV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

*SECNO 2.250

2.25	2.61	887.21	.00	.00	887.77	.55	.49	.19	889.50
215.	0.	215.	0.	0.	36.	0.	0.	0.	889.80
.02	.00	5.96	.00	.080	.030	.080	.000	884.60	23.59
.009099	154.	159.	157.	2	0	0	.00	24.63	48.22

0

*SECNO 2.400

7185 MINIMUM SPECIFIC ENERGY

3720 CRITICAL DEPTH ASSUMED

2.40	2.44	887.74	887.74	.00	888.45	.71	.38	.08	890.20
215.	0.	215.	0.	0.	32.	0.	0.	0.	890.50
.02	.00	6.74	.00	.080	.030	.080	.000	885.30	24.63
.012583	35.	36.	36.	0	11	0	.00	23.07	47.70

0

*SECNO 2.450

2.45	2.84	888.44	.00	.00	888.85	.42	.32	.09	890.50
215.	0.	215.	0.	0.	42.	0.	0.	0.	890.80
.02	.00	5.17	.00	.080	.030	.080	.000	885.60	22.31
.006251	35.	37.	35.	3	0	0	.00	26.55	48.85

0

*SECNO 2.500

2.50	2.78	889.08	.00	.00	889.58	.50	.69	.04	892.50
215.	0.	215.	0.	0.	38.	0.	1.	0.	892.00
.03	.00	5.68	.00	.080	.030	.080	.000	886.30	115.12
.010607	84.	86.	85.	3	0	0	.00	31.18	146.29

0

*SECNO 2.550

2.55	3.04	889.54	.00	.00	889.88	.33	.24	.05	892.70
215.	0.	215.	0.	0.	46.	0.	1.	0.	892.20
.03	.00	4.64	.00	.080	.030	.080	.000	886.50	112.30
.006415	18.	30.	40.	3	0	0	.00	35.72	148.02

0

*SECNO 2.560

2.56	3.03	889.83	.00	.00	890.17	.34	.29	.00	893.00
215.	0.	215.	0.	0.	46.	0.	1.	0.	892.50
.03	.00	4.65	.00	.080	.030	.080	.000	886.80	112.35
.006474	26.	45.	60.	2	0	0	.00	35.64	147.99

0

1

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	EV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

```
*SECNO 2.570
     2.57     2.97   889.97      .00      .00   890.34      .37      .15      .02   893.20
     215.       0.     215.       0.       0.     44.       0.       1.       0.   892.70
      .03      .00     4.88      .00     .080     .030     .080     .000   887.00   113.02
   .007277      13.      22.      30.        0        0        0      .00    34.56   147.58
0
 *SECNO 2.600
 7185 MINIMUM SPECIFIC ENERGY
 3720 CRITICAL DEPTH ASSUMED

 3470 ENCROACHMENT STATIONS=      68.5     120.5  TYPE=     1  TARGET=      52.000
     2.60     1.16   890.26   890.26      .00   890.68      .41      .23      .02 99999.60
     215.       0.     215.       0.       0.     42.       0.       1.       0.  99999.60
      .03      .00     5.15      .00     .080     .030     .080     .000   889.10    68.50
   .014651      13.      23.      30.        2       18        0      .00    52.00   120.50
0
 CCHV=     .300 CEHV=     .500
 *SECNO 2.700

 3301 HV CHANGED MORE THAN HVINS

 3685 20 TRIALS ATTEMPTED WSEL,CWSEL
 3693 PROBABLE MINIMUM SPECIFIC ENERGY
 3720 CRITICAL DEPTH ASSUMED

 3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA=      895.00 ELREA=      895.00

     2.70     1.93   892.14   892.14      .00   893.11      .97      .83      .28   890.22
     215.       0.     215.       0.       0.     27.       0.       1.       0.   892.00
      .04      .00     7.92      .00     .080     .025     .080     .000   890.21   164.90
   .008664      130.     75.      60.       20       14        0      .00    14.12   179.02
0

 SPECIAL BRIDGE

 5227 DOWNSTREAM ELEV IS    891.47 ,NOT    892.14 HYDRAULIC JUMP OCCURS DOWNSTREAM (IF LOW FLOW CONTROLS)

1
  02-06-92     18:06:19                                                                    PAGE

    SECNO     DEPTH     CWSEL     CRIWS     WSELK     EG        HV        HL        OLOSS    BANK ELEV
    Q         QLOB      QCH       QROB      ALOB      ACH       AROB      VOL       TWA    LEFT/RIGHT
    TIME      VLOB      VCH       VROB      XNL       XNCH      XNR       WTN       ELMIN       SSTA
    SLOPE     XLOBL     XLCH      XLOBR     ITRIAL    IDC       ICONT     CORAR     TOPWID      ENDST

 SB  XK         XKOR       COFQ       RDLEN      BWC        BWP        BAREA      SS         ELCHU      ELCHD
      1.05       2.49       3.00        .00      14.00       4.20       38.60       .00     890.70     890.21
```

*SECNO 2.800

3301 HV CHANGED MORE THAN HVINS

CLASS B LOW FLOW

3420 BRIDGE W.S.= 892.92 BRIDGE VELOCITY=, 8.91 CALCULATED CHANNEL AREA=, 22.

EGPRS	EGLWC	H3	QWEIR	QLOW	BAREA	TRAPEZOID AREA	ELLC	ELTRD
.00	894.68	.00	0.	215.	39.	42.	895.00	898.66

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 898.66 ELREA= 898.66

2.80	4.28	894.49	.00	.00	894.68	.20	1.57	.00	890.22
215.	0.	215.	0.	0.	60.	0.	1.	0.	892.00
.04	.00	3.57	.00	.000	.025	.000	.000	890.21	164.90
.000607	68.	68.	68.	0	0	0	.00	14.12	179.02

0

CCHV= .800 CEHV= .900

*SECNO 2.900

3470 ENCROACHMENT STATIONS= 92.0 146.0 TYPE= 1 TARGET= 54.000

2.90	3.80	894.80	.00	.00	894.83	.03	.01	.14	99999.00
215.	0.	215.	0.	0.	166.	0.	1.	0.	99999.00
.05	.00	1.30	.00	.080	.040	.080	.000	891.00	92.00
.000305	10.	20.	30.	2	0	0	.00	54.00	146.00

0

*SECNO 2.950

2.95	3.85	894.85	.00	.00	894.86	.01	.02	.01	893.00
215.	7.	206.	2.	32.	233.	11.	1.	1.	893.00
.08	.21	.88	.21	.080	.040	.080	.000	891.00	56.83
.000140	40.	100.	150.	0	0	0	.00	128.18	185.01

0

*SECNO 3.000

3685 20 TRIALS ATTEMPTED WSEL,CWSEL

3693 PROBABLE MINIMUM SPECIFIC ENERGY

1

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

3720 CRITICAL DEPTH ASSUMED

3.00	2.63	895.83	895.83	.00	896.28	.45	.11	.40	894.60
215.	38.	139.	38.	21.	21.	23.	2.	1.	894.60
.09	1.81	6.60	1.65	.080	.040	.080	.000	893.20	34.54
.011809	264.	259.	15.	20	20	0	.00	72.27	106.82

0

CCHV= .300 CEHV= .500

*SECNO 3.500

3.50	2.74	901.94	.00	.00	902.19	.25	5.85	.06	900.80
215.	33.	118.	63.	24.	23.	36.	3.	3.	900.50
.15	1.37	5.20	1.78	.060	.035	.060	.000	899.20	84.88
.006054	710.	750.	615.	6	0	0	.00	109.74	194.62

0

*SECNO 3.750

3.75	3.33	903.13	.00	.00	903.38	.25	1.19	.00	901.20
215.	11.	135.	69.	10.	27.	42.	4.	3.	901.70
.17	1.17	4.93	1.62	.060	.035	.060	.000	899.80	265.73
.003866	195.	250.	265.	3	0	0	.00	69.25	334.98

0

*SECNO 4.000

4.00	3.36	903.86	.00	.00	903.91	.05	.47	.06	902.10
215.	68.	77.	69.	71.	30.	70.	5.	4.	901.80
.21	.96	2.61	.98	.060	.035	.060	.000	900.50	69.43
.001080	230.	265.	245.	3	0	0	.00	140.64	210.07

0

CCHV= .600 CEHV= .800

*SECNO 4.250

4.25	3.10	903.90	.00	.00	903.94	.04	.02	.01	900.80
207.	27.	139.	41.	54.	73.	79.	5.	4.	900.81
.22	.50	1.90	.52	.060	.025	.060	.000	900.80	109.29
.000227	50.	50.	50.	2	0	0	.00	125.22	234.52

0

SPECIAL BRIDGE

1

02-06-92 18:06:19 PAGE

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

SB	XK	XKOR	COFQ	RDLEN	BWC	BWP	BAREA	SS	ELCHU	ELCHD
	1.05	3.33	3.00	.00	23.50	8.00	34.00	.00	900.90	900.80

*SECNO 4.500

PRESSURE AND WEIR FLOW

EGPRS	EGLWC	H3	QWEIR	QPR	BAREA	TRAPEZOID AREA	ELLC	ELTRD
905.81	904.05	.03	26.	182.	34.	37.	903.30	905.01

```
3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA=      905.01 ELREA=      905.60

     4.50     4.55   905.35      .00      .00   905.37      .02     1.43      .00   900.80
     207.       57.      150.       0.      163.      107.       0.       5.       4.    900.81
      .24      .35     1.40      .00      .060      .025      .000      .000   900.80    36.81
  .000074       60.       60.       60.        2         0         4      .00   130.94   167.75
0
 CCHV=     .400 CEHV=     .600
 *SECNO 4.750
     4.75     4.08   905.38      .00      .00   905.38      .00      .01      .01   902.20
     207.       84.       41.       82.      205.       47.      198.       6.       4.    902.30
      .27      .41      .87      .42      .060      .040      .060      .000   901.30    57.42
  .000100      110.       60.       20.        2         0         0      .00   213.17   270.59
0
 *SECNO 5.000

 3470 ENCROACHMENT STATIONS=      125.0      332.0  TYPE=     1  TARGET=      207.000
     5.00     2.88   905.48      .00      .00   905.48      .01      .10      .00   903.10
     159.       70.       45.       44.      133.       46.       96.       12.       8.    903.60
      .59      .52      .98      .46      .060      .040      .060      .000   902.60   137.62
  .000204      685.      745.      790.        2         0         0      .00   171.75   309.37
0
 *SECNO 5.500

 3470 ENCROACHMENT STATIONS=      110.0      330.0  TYPE=     1  TARGET=      220.000
     5.50     2.90   905.50      .00      .00   905.50      .00      .02      .00   902.90
     159.       24.      103.       32.      111.      279.      146.       15.       9.    903.00
      .85      .22      .37      .22      .060      .040      .060      .000   902.60   120.00
  .000025      280.      285.      305.        2         0         0      .00   210.00   330.00
0
1
  02-06-92      18:06:19                                                                  PAGE


    SECNO     DEPTH     CWSEL     CRIWS     WSELK     EG        HV        HL        OLOSS     BANK ELEV
    Q         QLOB      QCH       QROB      ALOB      ACH       AROB      VOL       TWA     LEFT/RIGHT
    TIME      VLOB      VCH       VROB      XNL       XNCH      XNR       WTN       ELMIN       SSTA
    SLOPE     XLOBL     XLCH      XLOBR     ITRIAL    IDC       ICONT     CORAR     TOPWID      ENDST


 CCHV=     .600 CEHV=     .950
 *SECNO 6.000
 3685 20 TRIALS ATTEMPTED WSEL,CWSEL
 3693 PROBABLE MINIMUM SPECIFIC ENERGY
 3720 CRITICAL DEPTH ASSUMED

 3470 ENCROACHMENT STATIONS=      113.0      175.0  TYPE=     1  TARGET=       62.000
     6.00      .89   905.99   905.99      .00   906.24      .26      .01      .24   905.10
     110.       65.       43.        2.       23.        8.        1.       16.       9.    905.30
      .86     2.83     5.45     2.05      .060      .040      .060      .000   905.10   113.00
  .029676      160.      160.      170.       20        17         0      .00    60.30   173.30
```

0
*SECNO 6.900

3470 ENCROACHMENT STATIONS= .2 31.8 TYPE= 1 TARGET= 31.600

6.90	2.10	907.40	.00	.00	907.95	.54	1.43	.27	905.50
110.	9.	86.	16.	3.	13.	6.	16.	9.	905.50
.86	2.52	6.57	2.56	.060	.040	.060	.000	905.30	5.54
.011952	80.	80.	80.	3	0	0	.00	17.59	23.13

0
*SECNO 6.940

3470 ENCROACHMENT STATIONS= 75.0 208.0 TYPE= 1 TARGET= 133.000

6.94	2.58	907.96	.00	.00	908.26	.29	.16	.15	906.58
110.	5.	99.	5.	4.	22.	4.	16.	9.	906.48
.86	1.42	4.56	1.48	.060	.040	.060	.000	905.38	89.66
.005581	20.	20.	20.	2	0	0	.00	20.30	109.96

0
*SECNO 6.950

3470 ENCROACHMENT STATIONS= 75.0 208.0 TYPE= 1 TARGET= 133.000

6.95	2.69	908.22	.00	.00	908.48	.26	.20	.02	906.73
110.	6.	98.	6.	4.	23.	4.	16.	9.	906.63
.87	1.36	4.30	1.41	.060	.040	.060	.000	905.53	89.26
.004678	40.	40.	40.	2	0	0	.00	21.04	110.31

0
*SECNO 7.000

3470 ENCROACHMENT STATIONS= 75.0 208.0 TYPE= 1 TARGET= 133.000

1
02-06-92 18:06:19 PAGE

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST
7.00	2.80	909.23	.00	.00	909.46	.23	.96	.02	907.63
110.	6.	97.	7.	5.	24.	5.	16.	9.	907.53
.88	1.31	4.06	1.35	.060	.040	.060	.000	906.43	88.85
.003914	225.	225.	225.	2	0	0	.00	21.82	110.67

0
*SECNO 8.000
WATER EL=X5 CARD= 913.480

3470 ENCROACHMENT STATIONS= 1.0 79.0 TYPE= 1 TARGET= 78.000

8.00	4.38	913.48	.00	.00	913.52	.04	.65	.12	917.40
110.	0.	110.	0.	0.	73.	0.	17.	10.	916.70
.99	.00	1.51	.00	.060	.040	.060	.000	909.10	16.28
.000525	578.	578.	578.	0	0	0	.00	29.34	45.61

0

*SECNO 9.000

3470 ENCROACHMENT STATIONS= 1.0 161.0 TYPE= 1 TARGET= 160.000

9.00	3.39	913.59	.00	.00	913.62	.03	.10	.00	913.50
73.	0.	73.	0.	0.	52.	0.	17.	10.	913.50
1.03	.01	1.41	.01	.060	.040	.060	.000	910.20	70.41
.000579	185.	185.	185.	2	0	0	.00	25.37	95.78

0

CCHV= .600 CEHV= .950

*SECNO 10.000

3685 20 TRIALS ATTEMPTED WSEL,CWSEL

3693 PROBABLE MINIMUM SPECIFIC ENERGY

3720 CRITICAL DEPTH ASSUMED

3470 ENCROACHMENT STATIONS= 1.0 161.0 TYPE= 1 TARGET= 160.000

10.00	1.04	915.54	915.54	.00	915.86	.33	.02	.28	915.50
73.	0.	73.	0.	0.	16.	0.	17.	10.	915.50
1.03	.04	4.60	.04	.060	.040	.060	.000	914.50	70.44
.028197	9.	9.	9.	20	17	0	.00	25.22	95.66

0

*SECNO 11.000

3470 ENCROACHMENT STATIONS= 1.0 108.0 TYPE= 1 TARGET= 107.000

11.00	2.39	917.49	.00	.00	917.63	.14	1.65	.11	918.80
73.	0.	73.	0.	0.	24.	0.	17.	10.	918.00
1.04	.00	3.04	.00	.060	.040	.060	.000	915.10	41.62
.004536	179.	179.	179.	6	0	0	.00	17.14	58.76

0

1

02-06-92 18:06:19 PAGE

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

*SECNO 11.900

11.90	2.53	918.63	.00	.00	918.73	.10	1.07	.03	920.00
73.	0.	73.	0.	0.	29.	0.	17.	10.	919.40
1.08	.00	2.49	.00	.060	.040	.060	.000	916.10	20.81
.002872	300.	300.	300.	5	0	0	.00	20.20	41.01

0

*SECNO 12.000

3685 20 TRIALS ATTEMPTED WSEL,CWSEL

3693 PROBABLE MINIMUM SPECIFIC ENERGY

3720 CRITICAL DEPTH ASSUMED

3470 ENCROACHMENT STATIONS= 1.0 309.0 TYPE= 1 TARGET= 308.000

12.00	.56	920.76	920.76	.00	920.95	.19	.62	.09	920.40
73.	2.	67.	4.	1.	18.	3.	17.	10.	920.40
1.08	1.31	3.67	1.31	.060	.040	.060	.000	920.20	63.28
.027549	100.	95.	100.	20	17	0	.00	64.64	127.92

THIS RUN EXECUTED 02-06-92

```
**************************************************
  HEC2 RELEASE DATED NOV 76 UPDATED MAY  1984
  ERROR CORR -  01,02,03,04,05,06
  MODIFICATION -  50,51,52,53,54,55,56
  IBM-PC-XT VERSION AUGUST 1985
**************************************************
```

T1 RANDOLPH DRAIN FLOOD LEVEL STUDY DEVELOPED CONDITION
T2 STRETCH BETWEEN BECK ROAD AND 6 FT CULVERTS AT LEXINGTON DR
T3 McNEELY & LINCOLN ASSOCIATES, INC. DT: DEC. 06, 1991

J1	ICHECK	INQ	NINV	IDIR	STRT	METRIC	HVINS	Q	WSEL	FQ
	-10.	3.	0.	0.	.000000	.00	.0	0.	882.000	.000

J2	NPROF	IPLOT	PRFVS	XSECV	XSECH	FN	ALLDC	IBW	CHNIM	ITRACE
	2.000	.000	-1.000	.000	.000	.000	.000	.000	.000	.000

1
02-06-92 18:06:19 PAGE

SECNO	DEPTH	CWSEL	CRIWS	WSELR	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

*PROF 2

CCHV= .300 CEHV= .500
*SECNO 1.000

1.00	4.20	882.00	.00	882.00	882.30	.30	.00	.00	882.20
363.	0.	363.	0.	0.	83.	0.	0.	0.	885.60
.00	.00	4.38	.00	.080	.030	.080	.000	877.80	22.43
.002228	0.	0.	0.	0	0	0	.00	30.26	52.70

0
*SECNO 1.250

3301 HV CHANGED MORE THAN HVINS

3685 20 TRIALS ATTEMPTED WSEL,CWSEL
3693 PROBABLE MINIMUM SPECIFIC ENERGY
3720 CRITICAL DEPTH ASSUMED

1.25	3.26	884.79	884.79	.00	885.82	1.03	.26	.36	887.40
363.	0.	363.	0.	0.	45.	0.	0.	0.	888.70
.00	.00	8.14	.00	.080	.030	.080	.000	881.53	26.39
.011377	60.	60.	60.	20	15	0	.00	22.14	48.53

0
*SECNO 1.500
WATER EL=X5 CARD= 888.330

1.50	5.70	888.33	.00	.00	888.49	.16	.13	.26	888.50
363.	0.	363.	0.	0.	112.	0.	0.	0.	889.80
.01	.00	3.23	.00	.080	.030	.080	.000	882.63	20.42
.000919	60.	60.	60.	0	0	0	.00	33.40	53.82

0
*SECNO 2.000

2.00	5.27	888.33	.00	.00	888.52	.18	.02	.01	888.66
363.	0.	363.	0.	0.	105.	0.	0.	0.	889.96
.01	.00	3.45	.00	.080	.030	.080	.000	883.06	20.80
.001101	15.	15.	15.	2	0	0	.00	32.68	53.48

0

*SECNO 2.100

2.10	5.32	888.38	.00	.00	888.56	.18	.04	.00	888.66
363.	0.	363.	0.	0.	107.	0.	0.	0.	889.96
.01	.00	3.41	.00	.080	.030	.080	.000	883.06	20.71
.001069	40.	37.	30.	0	0	0	.00	32.84	53.55

0

1

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

*SECNO 2.250

2.25	3.98	888.58	.00	.00	888.92	.34	.28	.08	889.50
363.	0.	363.	0.	0.	78.	0.	1.	0.	889.80
.02	.00	4.65	.00	.080	.030	.080	.000	884.60	15.47
.003385	154.	159.	157.	2	0	0	.00	36.84	52.31

0

*SECNO 2.400

2.40	3.29	888.59	.00	.00	889.27	.68	.18	.17	890.20
363.	0.	363.	0.	0.	55.	0.	1.	0.	890.50
.02	.00	6.62	.00	.080	.030	.080	.000	885.30	19.56
.008597	35.	36.	36.	2	0	0	.00	30.65	50.21

0

*SECNO 2.450

2.45	3.34	888.94	.00	.00	889.59	.65	.31	.01	890.50
363.	0.	363.	0.	0.	56.	0.	1.	0.	890.80
.02	.00	6.48	.00	.080	.030	.080	.000	885.60	19.32
.008103	35.	37.	35.	3	0	0	.00	31.01	50.33

0

*SECNO 2.500

2.50	3.55	889.85	.00	.00	890.31	.46	.66	.06	892.50
363.	0.	363.	0.	0.	67.	0.	1.	0.	892.00
.03	.00	5.42	.00	.080	.030	.080	.000	886.30	106.66
.007212	84.	86.	85.	3	0	0	.00	44.82	151.48

0

*SECNO 2.550

2.55	3.58	890.08	.00	.00	890.52	.44	.21	.00	892.70
363.	0.	363.	0.	0.	68.	0.	1.	0.	892.20
.03	.00	5.32	.00	.080	.030	.080	.000	886.50	106.37
.006895	18.	30.	40.	0	0	0	.00	45.29	151.66

0

*SECNO 2.560

2.56	3.60	890.40	.00	.00	890.83	.43	.31	.00	893.00
363.	0.	363.	0.	0.	69.	0.	1.	0.	892.50
.03	.00	5.27	.00	.080	.030	.080	.000	886.80	106.20
.006718	26.	45.	60.	0	0	0	.00	45.56	151.76

0

1

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

*SECNO 2.570

2.57	3.54	890.54	.00	.00	891.00	.46	.15	.01	893.20
363.	0.	363.	0.	0.	67.	0.	1.	0.	892.70
.03	.00	5.42	.00	.080	.030	.080	.000	887.00	106.67
.007225	13.	22.	30.	0	0	0	.00	44.80	151.47

0

*SECNO 2.600

3470 ENCROACHMENT STATIONS= 68.5 120.5 TYPE= 1 TARGET= 52.000

2.60	1.62	890.72	.00	890.26	891.20	.48	.19	.01	99999.60
363.	0.	363.	0.	0.	65.	0.	1.	0.	99999.60
.03	.00	5.54	.00	.080	.030	.080	.000	889.10	68.50
.009532	13.	23.	30.	2	0	0	.00	52.00	120.50

0

CCHV= .300 CEHV= .500

*SECNO 2.700

3301 HV CHANGED MORE THAN HVINS

3685 20 TRIALS ATTEMPTED WSEL,CWSEL

3693 PROBABLE MINIMUM SPECIFIC ENERGY

3720 CRITICAL DEPTH ASSUMED

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 895.00 ELREA= 895.00

2.70	2.73	892.94	892.94	892.14	894.32	1.38	.64	.45	890.22
363.	0.	363.	0.	0.	39.	0.	1.	1.	892.00
.04	.00	9.42	.00	.080	.025	.080	.000	890.21	164.90
.007708	130.	75.	60.	20	14	0	.00	14.12	179.02

0

SPECIAL BRIDGE

5227 DOWNSTREAM ELEV IS 892.00 ,NOT 892.94 HYDRAULIC JUMP OCCURS DOWNSTREAM (IF LOW FLOW CONTROLS)

SB	XK	XKOR	COFQ	RDLEN	BWC	BWP	BAREA	SS	ELCHU	ELCHD
	1.05	2.49	3.00	.00	14.00	4.20	38.60	.00	890.70	890.21

*SECNO 2.800

3301 HV CHANGED MORE THAN HVINS

1

SECNO	DEPTH	CWSEL	CRIWS	WSELR	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

CLASS B LOW FLOW

3420 BRIDGE W.S.= 893.95 BRIDGE VELOCITY=, 10.61 CALCULATED CHANNEL AREA=, 32.

EGPRS	EGLWC	H3	QWEIR	QLOW	BAREA	TRAPEZOID AREA	ELLC	ELTRD
896.36	896.37	.00	0.	363.	39.	42.	895.00	898.66

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 898.66 ELREA= 898.66

2.80	5.86	896.07	.00	894.49	896.37	.30	2.05	.00	890.22
363.	0.	363.	0.	0.	83.	0.	1.	1.	892.00
.04	.00	4.39	.00	.000	.025	.000	.000	890.21	164.90
.000605	68.	68.	68.	0	0	0	.00	14.12	179.02

0
CCHV= .800 CEHV= .900
*SECNO 2.900

3470 ENCROACHMENT STATIONS= 92.0 146.0 TYPE= 1 TARGET= 54.000

2.90	5.56	896.56	.00	894.80	896.59	.03	.01	.22	99999.00
363.	0.	363.	0.	0.	261.	0.	1.	1.	99999.00
.05	.00	1.39	.00	.080	.040	.080	.000	891.00	92.00
.000208	10.	20.	30.	2	0	0	.00	54.00	146.00

0
*SECNO 2.950

2.95	5.61	896.61	.00	894.85	896.62	.01	.01	.02	893.00
363.	30.	321.	12.	113.	377.	52.	2.	1.	893.00
.08	.27	.85	.23	.080	.040	.080	.000	891.00	33.20
.000069	40.	100.	150.	0	0	0	.00	175.99	209.20

0
*SECNO 3.000

3.00	3.43	896.63	.00	895.83	896.91	.28	.05	.24	894.60
363.	92.	168.	103.	49.	28.	58.	4.	1.	894.60
.10	1.86	5.93	1.79	.080	.040	.080	.000	893.20	22.48
.006443	264.	259.	15.	0	0	0	.00	101.11	123.59

0
1

SECNO	DEPTH	CWSEL	CRIWS	WSELR	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

CCHV= .300 CEHV= .500

```
*SECNO 3.500
7185 MINIMUM SPECIFIC ENERGY
3720 CRITICAL DEPTH ASSUMED
     3.50     2.95   902.15   902.15   901.94   902.57      .41     5.48      .07   900.80
     363.       72.      176.      116.       35.       25.       46.        6.        3.   900.50
      .14     2.02     7.01     2.51     .060     .035     .060     .000   899.20    79.67
   .009697      710.      750.      615.       11        9        0      .00   120.15   199.83
0
*SECNO 3.750
     3.75     3.96   903.76      .00   903.13   904.03      .28     1.43      .04   901.20
     363.       31.      187.      144.       21.       33.       72.        6.        4.   901.70
      .16     1.47     5.59     2.00     .060     .035     .060     .000   899.80   258.14
   .003820      195.      250.      265.        2        0        0      .00    87.46   345.60
0
*SECNO 4.000
     4.00     3.98   904.48      .00   903.86   904.53      .05      .43      .07   902.10
     363.      130.      103.      129.      118.       36.      115.        8.        4.   901.80
      .20     1.11     2.84     1.13     .060     .035     .060     .000   900.50    50.06
   .000964      230.      265.      245.        3        0        0      .00   173.92   223.98
0
CCHV=    .600 CEHV=    .800
*SECNO 4.250
     4.25     3.70   904.50      .00   903.90   904.56      .06      .03      .01   900.80
     356.       55.      217.       85.       83.       87.      127.        8.        5.   900.81
      .21      .66     2.49      .67     .060     .025     .060     .000   900.80    74.17
   .000306       50.       50.       50.        2        0        0      .00   182.06   256.23
0

SPECIAL BRIDGE

SB  XX        XKOR      COFQ      RDLEN     BWC       BWP       BAREA     SS        ELCHU     ELCHD
     1.05      3.33      3.00       .00     23.50      8.00     34.00      .00     900.90    900.80

*SECNO 4.500
PRESSURE AND WEIR FLOW

1
  02-06-92      18:06:19                                                                  PAGE

    SECNO     DEPTH     CWSEL     CRIWS     WSELK     EG        EV        HL        OLOSS     BANK ELEV
    Q         QLOB      QCH       QROB      ALOB      ACH       AROB      VOL       TWA     LEFT/RIGHT
    TIME      VLOB      VCH       VROB      XNL       XNCH      XNR       WTN       ELMIN       SSTA
    SLOPE     XLOBL     XLCH      XLOBR     ITRIAL    IDC       ICONT     CORAR     TOPWID      ENDST

  EGPRS       EGLWC       H3        QWEIR       QPR       BAREA     TRAPEZOID      ELLC      ELTRD
                                                                     AREA
    910.17    904.80        .04       182.       175.       34.       37.       903.30    905.01

     4.50      5.05   905.85      .00   905.35   905.87      .02     1.30      .00   900.80
     356.       80.      169.      108.      221.      119.      275.        9.        5.   900.81
      .23      .36     1.42      .39     .060     .025     .060     .000   900.80    24.54
   .000066       60.       60.       60.        1        0        6      .00   273.29   297.83
```

0

CCHV= .400 CEHV= .600

*SECNO 4.750

4.75	4.57	905.87	.00	905.38	905.88	.01	.01	.00	902.20
356.	149.	63.	144.	258.	53.	244.	9.	5.	902.30
.25	.58	1.18	.59	.060	.040	.060	.000	901.30	49.52
.000158	110.	60.	20.	0	0	0	.00	224.07	273.59

0

*SECNO 5.000

3470 ENCROACHMENT STATIONS= 125.0 332.0 TYPE= 1 TARGET= 207.000

5.00	3.40	906.00	.00	905.48	906.01	.01	.14	.00	903.10
265.	116.	67.	82.	174.	55.	141.	17.	9.	903.60
.51	.67	1.21	.58	.060	.040	.060	.000	902.60	134.98
.000239	685.	745.	790.	2	0	0	.00	190.90	325.88

0

*SECNO 5.500

3470 ENCROACHMENT STATIONS= 110.0 330.0 TYPE= 1 TARGET= 220.000

5.50	3.44	906.04	.00	905.50	906.04	.00	.02	.00	902.90
265.	42.	168.	55.	138.	332.	178.	21.	10.	903.00
.70	.30	.51	.31	.060	.040	.060	.000	902.60	117.85
.000038	280.	285.	305.	2	0	0	.00	212.15	330.00

0

CCHV= .600 CEHV= .950

*SECNO 6.000

7185 MINIMUM SPECIFIC ENERGY

3720 CRITICAL DEPTH ASSUMED

1

02-06-92 18:06:19 PAGE

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

3470 ENCROACHMENT STATIONS= 113.0 175.0 TYPE= 1 TARGET= 62.000

6.00	1.04	906.14	906.14	905.99	906.46	.32	.01	.30	905.10
161.	100.	58.	3.	30.	9.	1.	22.	11.	905.30
.71	3.32	6.18	2.31	.060	.040	.060	.000	905.10	113.00
.030322	160.	160.	170.	2	17	0	.00	62.00	175.00

0

*SECNO 6.900

3470 ENCROACHMENT STATIONS= .2 31.8 TYPE= 1 TARGET= 31.600

6.90	2.43	907.73	907.70	907.40	908.49	.76	1.62	.42	905.50
161.	15.	119.	27.	5.	15.	8.	22.	11.	905.50
.71	3.04	7.92	3.17	.060	.040	.060	.000	905.30	4.45
.014419	80.	80.	80.	2	17	0	.00	19.76	24.21

0

*SECNO 6.940

3470 ENCROACHMENT STATIONS= 75.0 208.0 TYPE= 1 TARGET= 133.000

6.94	3.21	908.59	.00	907.96	908.90	.32	.15	.27	906.58
161.	13.	136.	12.	8.	28.	7.	22.	11.	906.48
.71	1.64	4.85	1.68	.060	.040	.060	.000	905.38	87.27
.004533	20.	20.	20.	4	0	0	.00	24.75	112.03

0

*SECNO 6.950

3470 ENCROACHMENT STATIONS= 75.0 208.0 TYPE= 1 TARGET= 133.000

6.95	3.26	908.79	.00	908.22	909.09	.30	.17	.01	906.73
161.	13.	135.	13.	8.	29.	8.	22.	11.	906.63
.72	1.60	4.73	1.64	.060	.040	.060	.000	905.53	87.05
.004180	40.	40.	40.	2	0	0	.00	25.17	112.22

0

*SECNO 7.000

3470 ENCROACHMENT STATIONS= 75.0 208.0 TYPE= 1 TARGET= 133.000

7.00	3.30	909.73	.00	909.23	910.02	.29	.92	.01	907.63
161.	13.	135.	13.	8.	29.	8.	22.	11.	907.53
.73	1.58	4.66	1.62	.060	.040	.060	.000	906.43	86.93
.004005	225.	225.	225.	2	0	0	.00	25.39	112.33

0

1

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

*SECNO 8.000

WATER EL=X5 CARD= 914.410

3470 ENCROACHMENT STATIONS= 1.0 79.0 TYPE= 1 TARGET= 78.000

8.00	5.31	914.41	.00	913.48	914.45	.04	.58	.15	917.40
161.	0.	161.	0.	0.	103.	0.	23.	11.	916.70
.83	.00	1.57	.00	.060	.040	.060	.000	909.10	13.60
.000450	578.	578.	578.	0	0	0	.00	34.72	48.32

0

*SECNO 9.000

3470 ENCROACHMENT STATIONS= 1.0 161.0 TYPE= 1 TARGET= 160.000

9.00	4.30	914.50	.00	913.59	914.53	.03	.08	.00	913.50
106.	0.	105.	0.	1.	74.	2.	24.	11.	913.50
.87	.24	1.42	.29	.060	.040	.060	.000	910.20	69.44
.000359	185.	185.	185.	2	0	0	.00	29.20	98.65

0
CCHV= .600 CEHV= .950
*SECNO 10.000
3685 20 TRIALS ATTEMPTED WSEL,CWSEL
3693 PROBABLE MINIMUM SPECIFIC ENERGY
3720 CRITICAL DEPTH ASSUMED

3470 ENCROACHMENT STATIONS= 1.0 161.0 TYPE= 1 TARGET= 160.000

10.00	1.23	915.73	915.73	915.54	916.13	.40	.01	.35	915.50
106.	0.	106.	0.	0.	21.	0.	24.	11.	915.50
.87	.04	5.10	.90	.060	.040	.060	.000	914.50	70.10
.024267	9.	9.	9.	20	14	0	.00	26.45	96.55

0
*SECNO 11.000

3470 ENCROACHMENT STATIONS= 1.0 108.0 TYPE= 1 TARGET= 107.000

11.00	2.71	917.81	.00	917.49	918.00	.19	1.74	.13	918.80
106.	0.	106.	0.	0.	30.	0.	24.	12.	918.00
.89	.00	3.52	.00	.060	.040	.060	.000	915.10	40.44
.005217	179.	179.	179.	4	0	0	.00	19.13	59.57

0
*SECNO 11.900

11.90	2.97	919.07	.00	918.63	919.18	.12	1.13	.05	920.00
106.	0.	106.	0.	0.	39.	0.	24.	12.	919.40
.92	.00	2.73	.00	.060	.040	.060	.000	916.10	18.95
.002854	300.	300.	300.	5	0	0	.00	23.19	42.14

0
1
02-06-92 18:06:19 PAGE

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

*SECNO 12.000
3685 20 TRIALS ATTEMPTED WSEL,CWSEL
3693 PROBABLE MINIMUM SPECIFIC ENERGY
3720 CRITICAL DEPTH ASSUMED

3470 ENCROACHMENT STATIONS= 1.0 309.0 TYPE= 1 TARGET= 308.000

12.00	.68	920.88	920.88	920.76	921.11	.23	.61	.11	920.40
106.	3.	94.	9.	2.	23.	6.	24.	12.	920.40
.92	1.50	4.07	1.51	.060	.040	.060	.000	920.20	61.03
.024866	100.	95.	100.	20	17	0	.00	72.91	133.93

****
HEC2 RELEASE DATED NOV 76 UPDATED MAY 1984
ERROR CORR - 01,02,03,04,05,06
MODIFICATION - 50,51,52,53,54,55,56
IBM-PC-XT VERSION AUGUST 1985
****

```
T1      RANDOLPH DRAIN FLOOD LEVEL STUDY   DEVELOPED CONDITION
T2      STRETCH BETWEEN BECK ROAD AND 6 FT CULVERTS AT LEXINGTON DR
T3      McNEELY & LINCOLN ASSOCIATES, INC. DT: DEC. 06, 1991

J1  ICHECK     INQ       NINV      IDIR      STRT      METRIC    HVINS     Q         WSEL      FQ

      -10.       4.        0.        0.   .000000       .00        .0        0.   882.500      .000

J2  NPROF      IPLOT     PRFVS     XSECV     XSECH     FN        ALLDC     IBW       CHNIM     ITRACE

       3.000     .000    -1.000     .000      .000      .000      .000      .000      .000      .000

1
  02-06-92     18:06:19                                                                          PAGE


    SECNO     DEPTH     CWSEL     CRIWS     WSELK     EG        HV        HL        OLOSS     BANK ELEV
    Q         QLOB      QCH       QROB      ALOB      ACH       AROB      VOL       TWA     LEFT/RIGHT
    TIME      VLOB      VCH       VROB      XNL       XNCH      XNR       WTN       ELMIN       SSTA
    SLOPE     XLOBL     XLCH      XLOBR     ITRIAL    IDC       ICONT     CORAR     TOPWID      ENDST


 *PROF 3

 CCHV=    .300 CEHV=    .500
 *SECNO 1.000
      1.00      4.70    882.50       .00    882.50    882.80       .30       .00       .00    882.20
      433.       0.      433.        0.        1.       98.        0.        0.        0.    885.60
       .00       .23     4.40       .00      .080      .030      .080      .000    877.80     12.57
   .001903       0.       0.        0.         0         0         0       .00     41.14     53.71
0
 *SECNO 1.250

 3301 HV CHANGED MORE THAN HVINS

 3685 20 TRIALS ATTEMPTED WSEL,CWSEL
 3693 PROBABLE MINIMUM SPECIFIC ENERGY
 3720 CRITICAL DEPTH ASSUMED
      1.25      3.55    885.08    885.08       .00    886.19      1.11       .23       .40    887.40
      433.       0.      433.        0.        0.       51.        0.        0.        0.    888.70
       .00       .00     8.44       .00      .080      .030      .080      .000    881.53     25.68
   .011041       60.      60.       60.        20        15         0       .00     23.48     49.16
0
 *SECNO 1.500
  WATER EL=X5 CARD=    889.290
      1.50      6.66    889.29       .00       .00    889.43       .14       .10       .29    888.50
      433.       1.      432.        0.        4.       146.        0.        0.        0.    889.80
       .01       .25     2.96       .00      .080      .030      .080      .000    882.63     10.13
   .000604       60.      60.       60.         0         0         0       .00     45.77     55.89
```

0

*SECNO 2.000

2.00	6.23	889.29	.00	.00	889.44	.15	.01	.01	888.66
433.	1.	432.	0.	4.	138.	0.	0.	0.	889.96
.01	.23	3.13	.00	.080	.030	.080	.000	883.06	8.51
.000708	15.	15.	15.	2	0	0	.00	47.04	55.55

0

*SECNO 2.100

2.10	6.26	889.32	.00	.00	889.47	.15	.03	.00	888.66
433.	1.	432.	0.	4.	139.	0.	0.	0.	889.96
.01	.23	3.11	.00	.080	.030	.080	.000	883.06	8.08
.000695	40.	37.	30.	0	0	0	.00	47.52	55.60

0

1

02-06-92 18:06:19 PAGE

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

*SECNO 2.250

2.25	4.85	889.45	.00	.00	889.68	.22	.17	.04	889.50
433.	0.	433.	0.	0.	114.	0.	1.	0.	889.80
.02	.00	3.81	.00	.080	.030	.080	.000	884.60	10.29
.001800	154.	159.	157.	2	0	0	.00	45.37	55.66

0

*SECNO 2.400

2.40	4.15	889.45	.00	.00	889.86	.41	.09	.09	890.20
433.	0.	433.	0.	0.	84.	0.	1.	0.	890.50
.03	.00	5.13	.00	.080	.030	.080	.000	885.30	14.45
.003918	35.	36.	36.	2	0	0	.00	38.52	52.97

0

*SECNO 2.450

2.45	3.98	889.58	.00	.00	890.06	.48	.16	.04	890.50
433.	0.	433.	0.	0.	78.	0.	1.	0.	890.80
.03	.00	5.56	.00	.080	.030	.080	.000	885.60	15.49
.004839	35.	37.	35.	2	0	0	.00	36.80	52.29

0

*SECNO 2.500

2.50	3.78	890.08	.00	.00	890.56	.48	.50	.00	892.50
433.	0.	433.	0.	0.	78.	0.	1.	0.	892.00
.03	.00	5.57	.00	.080	.030	.080	.000	886.30	103.03
.007237	84.	86.	85.	2	0	0	.00	49.98	153.01

0

*SECNO 2.550

2.55	3.83	890.33	.00	.00	890.78	.45	.21	.01	892.70
433.	0.	433.	0.	0.	81.	0.	1.	1.	892.20
.03	.00	5.38	.00	.080	.030	.080	.000	886.50	101.59
.006734	18.	30.	40.	3	0	0	.00	51.79	153.38

```
*SECNO 2.560
     2.56     3.84   890.64      .00      .00   891.08      .45      .30      .00   893.00
     433.       0.     433.       0.       0.      81.       0.       1.       1.   892.50
      .04      .00     5.36      .00     .080     .030     .080     .000   886.80   101.46
   .006689      26.      45.      60.        0        0        0      .00    51.96   153.42
0
1
  02-06-92     18:06:19                                                                PAGE

    SECNO    DEPTH    CWSEL    CRIWS    WSELK    EG       EV       HL       OLOSS    BANK ELEV
    Q        QLOB     QCH      QROB     ALOB     ACH      AROB     VOL      TWA    LEFT/RIGHT
    TIME     VLOB     VCH      VROB     XNL      XNCH     XNR      WTN      ELMIN       SSTA
    SLOPE    XLOBL    XLCH     XLOBR    ITRIAL   IDC      ICONT    CORAR    TOPWID      ENDST


 *SECNO 2.570
     2.57     3.77   890.77      .00      .00   891.25      .48      .15      .02   893.20
     433.       0.     433.       0.       0.      78.       0.       1.       1.   892.70
      .04      .00     5.55      .00     .080     .030     .080     .000   887.00   102.86
   .007175      13.      22.      30.        0        0        0      .00    50.20   153.06
0
 *SECNO 2.600

 3470 ENCROACHMENT STATIONS=      68.5     120.5  TYPE=     1  TARGET=      52.000
     2.60     1.84   890.94      .00   890.26   891.44      .50      .18      .01 99999.60
     433.       0.     433.       0.       0.      76.       0.       1.       1.  99999.60
      .04      .00     5.66      .00     .080     .030     .080     .000   889.10    68.50
   .008170      13.      23.      30.        1        0        0      .00    52.00   120.50
0
 CCHV=    .300 CEHV=    .500
 *SECNO 2.700

 3301 HV CHANGED MORE THAN HVINS

 3685 20 TRIALS ATTEMPTED WSEL,CWSEL
 3693 PROBABLE MINIMUM SPECIFIC ENERGY
 3720 CRITICAL DEPTH ASSUMED

 3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA=      895.00 ELREA=      895.00

     2.70     3.07   893.28   893.28   892.14   894.84     1.55      .58      .53   890.22
     433.       0.     433.       0.       0.      43.       0.       2.       1.   892.00
      .04      .00     9.99      .00     .080     .025     .080     .000   890.21   164.90
   .007410     130.      75.      60.       20       14        0      .00    14.12   179.02
0

 SPECIAL BRIDGE

 5227 DOWNSTREAM ELEV IS    892.22 ,NOT    893.28 HYDRAULIC JUMP OCCURS DOWNSTREAM (IF LOW FLOW CONTROLS)

 SB  XK        XKOR      COFQ      RDLEN     BWC       BWP       BAREA     SS        ELCHU     ELCHD
     1.05      2.49      3.00        .00     14.00      4.20     38.60       .00    890.70    890.21
```

*SECNO 2.800

3301 HV CHANGED MORE THAN HVINS

1

02-06-92 18:06:19 PAGE

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

PRESSURE FLOW

EGPRS	EGLWC	H3	QWEIR	QPR	BAREA	TRAPEZOID AREA	ELLC	ELTRD
898.15	897.09	.00	0.	433.	39.	42.	895.00	898.66

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 898.66 ELREA= 898.66

2.80	7.69	897.90	.00	894.49	898.15	.25	3.31	.00	890.22
433.	0.	433.	0.	0.	109.	0.	2.	1.	892.00
.04	.00	3.99	.00	.000	.025	.000	.000	890.21	164.90
.000347	68.	68.	68.	2	0	0	.00	14.12	179.02

0

CCHV= .800 CEHV= .900

*SECNO 2.900

3470 ENCROACHMENT STATIONS= 92.0 146.0 TYPE= 1 TARGET= 54.000

2.90	7.31	898.31	.00	894.80	898.33	.02	.00	.18	99999.00
433.	0.	433.	0.	0.	355.	0.	2.	1.	99999.00
.05	.00	1.22	.00	.080	.040	.080	.000	891.00	92.00
.000114	10.	20.	30.	2	0	0	.00	54.00	146.00

0

*SECNO 2.950

2.95	7.35	898.35	.00	894.85	898.35	.01	.00	.01	893.00
433.	54.	352.	27.	234.	520.	134.	3.	1.	893.00
.10	.23	.68	.20	.080	.040	.080	.000	891.00	9.26
.000028	40.	100.	150.	1	0	0	.00	219.68	228.94

0

*SECNO 3.000

3.00	5.16	898.36	.00	895.83	898.40	.05	.02	.04	894.60
433.	140.	124.	169.	135.	44.	166.	6.	2.	894.60
.13	1.03	2.84	1.02	.080	.040	.080	.000	893.20	3.72
.000821	264.	259.	15.	0	0	0	.00	141.35	145.07

0

CCHV= .300 CEHV= .500

1

02-06-92 18:06:19 PAGE

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

*SECNO 3.500

3685 20 TRIALS ATTEMPTED WSEL,CWSEL

3693 PROBABLE MINIMUM SPECIFIC ENERGY

3720 CRITICAL DEPTH ASSUMED

3.50	3.04	902.24	902.24	901.94	902.72	.47	1.40	.21	900.80
433.	92.	199.	142.	40.	26.	51.	9.	4.	900.50
.17	2.27	7.66	2.77	.060	.035	.060	.000	899.20	77.44
.010971	710.	750.	615.	20	14	0	.00	124.61	202.06

0

*SECNO 3.750

3.75	4.18	903.98	.00	903.13	904.27	.29	1.50	.06	901.20
433.	42.	209.	181.	27.	36.	85.	10.	4.	901.70
.19	1.59	5.86	2.13	.060	.035	.060	.000	899.80	255.33
.003843	195.	250.	265.	2	0	0	.00	94.21	349.54

0

*SECNO 4.000

4.00	4.21	904.71	.00	903.86	904.76	.05	.42	.07	902.10
433.	160.	114.	158.	138.	39.	133.	12.	5.	901.80
.23	1.16	2.94	1.19	.060	.035	.060	.000	900.50	42.41
.000944	230.	265.	245.	3	0	0	.00	186.41	228.81

0

CCHV= .600 CEHV= .800

*SECNO 4.250

4.25	3.93	904.73	.00	903.90	904.81	.07	.03	.02	900.80
433.	71.	253.	110.	101.	92.	148.	12.	5.	900.81
.24	.70	2.73	.74	.060	.025	.060	.000	900.80	55.33
.000340	50.	50.	50.	2	0	0	.00	208.00	263.33

0

SPECIAL BRIDGE

5227 DOWNSTREAM ELEV IS 902.18 ,NOT 904.73 HYDRAULIC JUMP OCCURS DOWNSTREAM (IF LOW FLOW CONTROLS)

SB	KK	KKOR	COPQ	RDLEN	BWC	BWP	BAREA	SS	ELCHU	ELCHD
	1.05	3.33	3.00	.00	23.50	8.00	34.00	.00	900.90	900.80

*SECNO 4.500

PRESSURE AND WEIR FLOW

1

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

EGPRS	EGLWC	E3	QWEIR	QPR	BAREA	TRAPEZOID AREA	ELLC	ELTRD
913.12	905.49	.00	263.	170.	34.	37.	903.30	905.01

4.50	5.21	906.01	.00	905.35	906.03	.02	1.22	.00	900.80
433.	100.	200.	133.	238.	122.	294.	13.	6.	900.81
.26	.42	1.64	.45	.060	.025	.060	.000	900.80	21.02
.000084	60.	60.	60.	2	0	7	.00	281.30	302.32

0

CCHV= .400 CEHV= .600

*SECNO 4.750

4.75	4.73	906.03	.00	905.38	906.04	.01	.01	.00	902.20
433.	182.	74.	176.	276.	55.	259.	13.	6.	902.30
.28	.66	1.35	.68	.060	.040	.060	.000	901.30	46.96
.000194	110.	60.	20.	0	0	0	.00	227.60	274.56

0

*SECNO 5.000

3470 ENCROACHMENT STATIONS= 125.0 332.0 TYPE= 1 TARGET= 207.000

5.00	3.59	906.19	.00	905.48	906.20	.01	.16	.00	903.10
323.	141.	79.	103.	189.	59.	159.	22.	10.	903.60
.51	.75	1.34	.65	.060	.040	.060	.000	902.60	134.05
.000273	685.	745.	790.	2	0	0	.00	197.65	331.70

0

*SECNO 5.500

3470 ENCROACHMENT STATIONS= 110.0 330.0 TYPE= 1 TARGET= 220.000

5.50	3.63	906.23	.00	905.50	906.23	.00	.03	.00	902.90
323.	52.	204.	67.	148.	352.	190.	26.	11.	903.00
.68	.35	.58	.35	.060	.040	.060	.000	902.60	117.08
.000046	280.	285.	305.	2	0	0	.00	212.92	330.00

0

CCHV= .600 CEHV= .950

*SECNO 6.000

3470 ENCROACHMENT STATIONS= 113.0 175.0 TYPE= 1 TARGET= 62.000

6.00	1.13	906.23	.00	905.99	906.53	.30	.02	.28	905.10
180.	114.	62.	5.	35.	10.	2.	27.	12.	905.30
.69	3.28	6.00	2.32	.060	.040	.060	.000	905.10	113.00
.025049	160.	160.	170.	2	0	0	.00	62.00	175.00

0

1

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

*SECNO 6.900

3301 HV CHANGED MORE THAN HVINS

7185 MINIMUM SPECIFIC ENERGY
3720 CRITICAL DEPTH ASSUMED

3470 ENCROACHMENT STATIONS= .2 31.8 TYPE= 1 TARGET= 31.600

6.90	2.54	907.84	907.84	907.40	908.66	.82	1.51	.49	905.50
180.	18.	130.	31.	6.	16.	9.	27.	12.	905.50
.69	3.17	8.27	3.34	.060	.040	.060	.000	905.30	4.03
.014728	80.	80.	80.	3	17	0	.00	20.59	24.62

0
*SECNO 6.940

3470 ENCROACHMENT STATIONS= 75.0 208.0 TYPE= 1 TARGET= 133.000

6.94	3.39	908.77	.00	907.96	909.10	.33	.15	.29	906.58
180.	16.	149.	15.	9.	30.	9.	27.	12.	906.48
.69	1.71	4.99	1.75	.060	.040	.060	.000	905.38	86.57
.004403	20.	20.	20.	5	0	0	.00	26.07	112.64

0
*SECNO 6.950

3470 ENCROACHMENT STATIONS= 75.0 208.0 TYPE= 1 TARGET= 133.000

6.95	3.43	908.96	.00	908.22	909.28	.31	.17	.01	906.73
180.	16.	148.	16.	10.	30.	9.	27.	12.	906.63
.69	1.68	4.89	1.72	.060	.040	.060	.000	905.53	86.39
.004138	40.	40.	40.	2	0	0	.00	26.41	112.80

0
*SECNO 7.000

3470 ENCROACHMENT STATIONS= 75.0 208.0 TYPE= 1 TARGET= 133.000

7.00	3.46	909.89	.00	909.23	910.20	.31	.92	.00	907.63
180.	16.	148.	16.	10.	31.	9.	27.	12.	907.53
.71	1.67	4.84	1.70	.060	.040	.060	.000	906.43	86.30
.004014	225.	225.	225.	2	0	0	.00	26.58	112.87

0
*SECNO 8.000
1

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

WATER EL=X5 CARD= 915.110

3470 ENCROACHMENT STATIONS= 1.0 79.0 TYPE= 1 TARGET= 78.000

8.00	6.01	915.11	.00	913.48	915.14	.03	.44	.17	917.40
180.	0.	180.	0.	0.	128.	0.	28.	12.	916.70
.82	.00	1.40	.00	.060	.040	.060	.000	909.10	11.59
.000310	578.	578.	578.	0	0	0	.00	38.78	50.36

0

```
 *SECNO 9.000

 3470 ENCROACHMENT STATIONS=       1.0     161.0  TYPE=     1  TARGET=     160.000
      9.00     4.97   915.17      .00   913.59   915.20      .03      .06      .00   913.50
      139.       0.     137.       2.       1.      91.       4.      29.      12.   913.50
       .86      .31     1.50      .37     .060     .040     .060     .000   910.20    68.74
   .000309      185.     185.     185.        2        0        0      .00    32.01   100.75
0
 CCHV=    .600 CEHV=    .950
 *SECNO 10.000
 3685 20 TRIALS ATTEMPTED WSEL,CWSEL
 3693 PROBABLE MINIMUM SPECIFIC ENERGY
 3720 CRITICAL DEPTH ASSUMED

 3470 ENCROACHMENT STATIONS=       1.0     161.0  TYPE=     1  TARGET=     160.000
     10.00     1.39   915.89   915.89   915.54   916.37      .49      .01      .43   915.50
      139.       0.     138.       0.       0.      25.       0.      29.      12.   915.50
       .86     1.15     5.61     1.25     .060     .040     .060     .000   914.50    69.83
   .023322       9.       9.       9.       20       14        0      .00    27.43    97.26
0
 *SECNO 11.000

 3470 ENCROACHMENT STATIONS=       1.0     108.0  TYPE=     1  TARGET=     107.000
     11.00     3.00   918.10      .00   917.49   918.33      .24     1.81      .15   918.80
      139.       0.     139.       0.       0.      36.       0.      29.      13.   918.00
       .87      .00     3.90      .25     .060     .040     .060     .000   915.10    39.46
   .005616      179.     179.     179.        4        0        0      .00    30.46    69.92
0
 *SECNO 11.900
     11.90     3.33   919.43      .00   918.63   919.56      .13     1.16      .06   920.00
      139.       0.     139.       0.       0.      48.       0.      29.      13.   919.40
       .90      .00     2.92      .01     .060     .040     .060     .000   916.10    17.42
   .002831      300.     300.     300.        4        0        0      .00    26.70    44.12
0
1
  02-06-92     18:06:19                                                                PAGE


    SECNO     DEPTH     CWSEL     CRIWS     WSELK     EG        HV        HL        OLOSS     BANK ELEV
    Q         QLOB      QCH       QROB      ALOB      ACH       AROB      VOL       TWA       LEFT/RIGHT
    TIME      VLOB      VCH       VROB      XNL       XNCH      XNR       WTN       ELMIN     SSTA
    SLOPE     XLOBL     XLCH      XLOBR     ITRIAL    IDC       ICONT     CORAR     TOPWID    ENDST


 *SECNO 12.000
 3685 20 TRIALS ATTEMPTED WSEL,CWSEL
 3693 PROBABLE MINIMUM SPECIFIC ENERGY
 3720 CRITICAL DEPTH ASSUMED

 3470 ENCROACHMENT STATIONS=       1.0     309.0  TYPE=     1  TARGET=     308.000
     12.00      .78   920.98   920.98   920.76   921.24      .26      .59      .12   920.40
      139.       5.     119.      15.       3.      27.       8.      29.      13.   920.40
       .91     1.64     4.35     1.77     .060     .040     .060     .000   920.20    59.08
   .022852      100.      95.     100.       20       17        0      .00    80.41   139.49
0
```

THIS RUN EXECUTED 02-06-92

```
**************************************************
  HEC2 RELEASE DATED NOV 76 UPDATED MAY  1984
  ERROR CORR -  01,02,03,04,05,06
  MODIFICATION - '50,51,52,53,54,55,56
  IBM-PC-XT VERSION AUGUST 1985
**************************************************
```

```
T1      RANDOLPH DRAIN FLOOD LEVEL STUDY   DEVELOPED CONDITION
T2      STRETCH BETWEEN BECK ROAD AND 6 FT CULVERTS AT LEXINGTON DR
T3      McNEELY & LINCOLN ASSOCIATES, INC. DT: DEC. 06, 1991

J1  ICHECK    INQ       NINV      IDIR      STRT      METRIC    HVINS     Q         WSEL      FQ

      -10.       5.        0.        0.   .000000       .00        .0        0.   883.000      .000

J2  NPROP     IPLOT     PRFVS     XSECV     XSECH     FN        ALLDC     IBW       CHNIM     ITRACE

     15.000      .000    -1.000      .000      .000      .000      .000      .000      .000      .000

1
  02-06-92     18:06:19                                                                          PAGE

    SECNO     DEPTH     CWSEL     CRIWS     WSELK     EG        HV        HL        OLOSS     BANK ELEV
    Q         QLOB      QCH       QROB      ALOB      ACH       AROB      VOL       TWA     LEFT/RIGHT
    TIME      VLOB      VCH       VROB      XNL       XNCH      XNR       WTN       ELMIN       SSTA
    SLOPE     XLOBL     XLCH      XLOBR     ITRIAL    IDC       ICONT     CORAR     TOPWID      ENDST


 *PROF 4

 CCHV=    .300 CEHV=    .500
 *SECNO 1.000
 3280 CROSS SECTION      1.00 EXTENDED       .10 FEET

      1.00      5.20    883.00       .00    883.00    883.34       .34       .00       .00    882.20
      541.        5.      536.        0.       10.      114.        0.        0.        0.    885.60
       .00       .47      4.69       .00      .080      .030      .080      .000    877.80       .00
    .001843        0.        0.        0.         0         0         0       .00     54.72     54.72
0
 *SECNO 1.250

 3301 HV CHANGED MORE THAN HVINS

 3685 20 TRIALS ATTEMPTED WSEL,CWSEL
 3693 PROBABLE MINIMUM SPECIFIC ENERGY
 3720 CRITICAL DEPTH ASSUMED
      1.25      3.95    885.48    885.48       .00    886.70      1.22       .22       .44    887.40
      541.        0.      541.        0.        0.       61.        0.        0.        0.    888.70
       .00       .00      8.87       .00      .080      .030      .080      .000    881.53     24.71
    .010739       60.       60.       60.        20        15         0       .00     25.31     50.02
0
 *SECNO 1.500
  WATER EL=X5 CARD=   891.330
 3280 CROSS SECTION      1.50 EXTENDED       1.23 FEET

      1.50      8.70    891.33       .00       .00    891.41       .08       .04       .34    888.50
      541.        17.      516.        7.        41.      221.        25.        0.        0.    889.80
       .01       .43      2.34       .30      .080      .030      .080      .000    882.63       .00
    .000225       60.       60.       60.         0         0         0       .00     79.00     79.00
```

0

*SECNO 2.000

3280 CROSS SECTION 2.00 EXTENDED 1.57 FEET

2.00	8.27	891.33	.00	.00	891.42	.09	.00	.00	888.66
541.	20.	515.	6.	42.	213.	21.	0.	0.	889.96
.01	.46	2.42	.28	.080	.030	.080	.000	883.06	.00
.000251	15.	15.	15.	2	0	0	.00	79.00	79.00

0

1

02-06-92 18:06:19 PAGE

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

*SECNO 2.100

3280 CROSS SECTION 2.10 EXTENDED 1.58 FEET

2.10	8.28	891.34	.00	.00	891.43	.09	.01	.00	888.66
541.	20.	515.	6.	43.	214.	22.	1.	0.	889.96
.02	.46	2.41	.28	.080	.030	.080	.000	883.06	.00
.000250	40.	37.	30.	0	0	0	.00	79.00	79.00

0

*SECNO 2.250

3280 CROSS SECTION 2.25 EXTENDED 1.38 FEET

2.25	6.78	891.38	.00	.00	891.48	.10	.05	.01	889.50
541.	8.	529.	4.	16.	204.	13.	2.	0.	889.80
.03	.47	2.59	.34	.080	.030	.080	.000	884.60	.00
.000401	154.	159.	157.	0	0	0	.00	72.00	72.00

0

*SECNO 2.400

3280 CROSS SECTION 2.40 EXTENDED .69 FEET

2.40	6.08	891.38	.00	.00	891.53	.15	.02	.02	890.20
541.	4.	535.	1.	9.	172.	4.	2.	1.	890.50
.04	.46	3.12	.29	.080	.030	.080	.000	885.30	.00
.000734	35.	36.	36.	1	0	0	.00	66.49	66.49

0

*SECNO 2.450

3280 CROSS SECTION 2.45 EXTENDED .40 FEET

2.45	5.79	891.39	.00	.00	891.57	.18	.03	.01	890.50
541.	3.	538.	0.	6.	158.	2.	2.	1.	890.80
.04	.42	3.40	.26	.080	.030	.080	.000	885.60	.00
.000974	35.	37.	35.	0	0	0	.00	63.40	63.40

0

*SECNO 2.500

2.50	5.26	891.56	.00	.00	891.69	.13	.10	.02	892.50
541.	0.	541.	0.	0.	188.	0.	2.	1.	892.00
.05	.00	2.88	.00	.080	.030	.080	.000	886.30	64.41
.001450	84.	86.	85.	2	0	0	.00	98.62	163.04

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

*SECNO 2.550

2.55	5.10	891.60	.00	.00	891.75	.15	.05	.01	892.70
541.	0.	541.	0.	0.	172.	0.	2.	1.	892.20
.05	.00	3.14	.00	.080	.030	.080	.000	886.50	68.70
.001805	18.	30.	40.	0	0	0	.00	93.22	161.92

0

*SECNO 2.560

2.56	4.87	891.67	.00	.00	891.87	.20	.09	.02	893.00
541.	0.	541.	0.	0.	152.	0.	3.	1.	892.50
.05	.00	3.56	.00	.080	.030	.080	.000	886.80	74.64
.002463	26.	45.	60.	0	0	0	.00	85.74	160.38

0

*SECNO 2.570

2.57	4.71	891.71	.00	.00	891.95	.23	.06	.02	893.20
541.	0.	541.	0.	0.	139.	0.	3.	1.	892.70
.06	.00	3.89	.00	.080	.030	.080	.000	887.00	78.61
.003045	13.	22.	30.	0	0	0	.00	80.74	159.35

0

*SECNO 2.600

3470 ENCROACHMENT STATIONS= 68.5 120.5 TYPE= 1 TARGET= 52.000

2.60	2.64	891.74	.00	890.26	892.06	.32	.07	.04	99999.60
541.	0.	541.	0.	0.	118.	0.	3.	1.	99999.60
.06	.00	4.57	.00	.080	.030	.080	.000	889.10	68.50
.003103	13.	23.	30.	2	0	0	.00	52.00	120.50

0

CCHV= .300 CEHV= .500

*SECNO 2.700

3301 HV CHANGED MORE THAN HVINS

3685 20 TRIALS ATTEMPTED WSEL,CWSEL

3693 PROBABLE MINIMUM SPECIFIC ENERGY

3720 CRITICAL DEPTH ASSUMED

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 895.00 ELREA= 895.00

2.70	3.57	893.78	893.78	892.14	895.57	1.80	.34	.74	890.22
541.	0.	541.	0.	0.	50.	0.	3.	1.	892.00
.06	.00	10.76	.00	.080	.025	.080	.000	890.21	164.90
.007037	130.	75.	60.	20	11	0	.00	14.12	179.02

0

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

SPECIAL BRIDGE

5227 DOWNSTREAM ELEV IS 892.54 ,NOT 893.78 HYDRAULIC JUMP OCCURS DOWNSTREAM (IF LOW FLOW CONTROLS)

SB	XX	XKOR	COFQ	RDLEN	BWC	BWP	BAREA	SS	ELCHU	ELCHD
	1.05	2.49	3.00	.00	14.00	4.20	38.60	.00	890.70	890.21

*SECNO 2.800

3301 HV CHANGED MORE THAN HVINS

PRESSURE AND WEIR FLOW

EGPRS	EGLWC	H3	QWEIR	QPR	BAREA	TRAPEZOID AREA	ELLC	ELTRD
901.37	898.12	.00	73.	471.	39.	42.	895.00	898.66

2.80	9.31	899.52	.00	894.49	899.53	.01	3.95	.00	890.22
541.	195.	138.	208.	724.	131.	816.	4.	1.	892.00
.10	.27	1.05	.25	.080	.025	.080	.000	890.21	29.57
.000019	68.	68.	68.	0	0	5	.00	320.84	350.41

0
CCHV= .800 CEHV= .900
*SECNO 2.900

3470 ENCROACHMENT STATIONS= 92.0 146.0 TYPE= 1 TARGET= 54.000

2.90	8.52	899.52	.00	894.80	899.54	.03	.00	.02	99999.00
541.	0.	541.	0.	0.	420.	0.	5.	1.	99999.00
.10	.00	1.29	.00	.080	.040	.080	.000	891.00	92.00
.000106	10.	20.	30.	2	0	0	.00	54.00	146.00

0
*SECNO 2.950
3280 CROSS SECTION 2.95 EXTENDED .56 FEET

2.95	8.56	899.56	.00	894.85	899.56	.01	.00	.02	893.00
541.	80.	417.	44.	342.	620.	209.	6.	2.	893.00
.15	.23	.67	.21	.080	.040	.080	.000	891.00	.00
.000022	40.	100.	150.	2	0	0	.00	240.00	240.00

0
1

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

*SECNO 3.000
3280 CROSS SECTION 3.00 EXTENDED .87 FEET

3.00	6.37	899.57	.00	895.83	899.60	.03	.01	.02	894.60
541.	186.	126.	229.	211.	55.	264.	10.	2.	894.60
.20	.88	2.30	.87	.080	.040	.080	.000	893.20	.00
.000400	264.	259.	15.	0	0	0	.00	160.99	160.99

0
CCHV= .300 CEHV= .500
*SECNO 3.500
3685 20 TRIALS ATTEMPTED WSEL,CWSEL
3693 PROBABLE MINIMUM SPECIFIC ENERGY
3720 CRITICAL DEPTH ASSUMED

3.50	3.24	902.44	902.44	901.94	902.92	.48	.77	.23	900.80
541.	131.	225.	185.	52.	28.	63.	15.	5.	900.50
.24	2.51	7.97	2.96	.060	.035	.060	.000	899.20	72.54
.010696	710.	750.	615.	20	8	0	.00	134.42	206.96

0
*SECNO 3.750

3.75	4.40	904.20	.00	903.13	904.52	.32	1.56	.05	901.20
541.	65.	241.	235.	45.	38.	99.	16.	6.	901.70
.25	1.44	6.36	2.38	.060	.035	.060	.000	899.80	129.52
.004176	195.	250.	265.	2	0	0	.00	224.12	353.64

0
*SECNO 4.000

4.00	4.49	904.99	.00	903.86	905.04	.06	.44	.08	902.10
541.	207.	132.	202.	165.	42.	157.	18.	7.	901.80
.29	1.25	3.15	1.29	.060	.035	.060	.000	900.50	33.38
.000981	230.	265.	245.	3	0	0	.00	201.13	234.51

0
CCHV= .600 CEHV= .800
*SECNO 4.250

4.25	4.21	905.01	.00	903.90	905.09	.08	.03	.02	900.80
532.	95.	294.	142.	128.	99.	176.	18.	7.	900.81
.30	.75	2.98	.81	.060	.025	.060	.000	900.80	44.95
.000369	50.	50.	50.	2	0	0	.00	226.83	271.78

0
1

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

SPECIAL BRIDGE

5227 DOWNSTREAM ELEV IS 902.38 ,NOT 905.01 HYDRAULIC JUMP OCCURS DOWNSTREAM (IF LOW FLOW CONTROLS)

SB	XK	XKOR	COFQ	RDLEN	BWC	BWP	BAREA	SS	ELCHU	ELCHD
	1.05	3.33	3.00	.00	23.50	8.00	34.00	.00	900.90	900.80

*SECNO 4.500
PRESSURE AND WEIR FLOW

EGPRS	EGLWC	H3	QWEIR	QPR	BAREA	TRAPEZOID AREA	ELLC	ELTRD
917.67	906.17	.00	370.	163.	34.	37.	903.30	905.01
4.50	5.37	906.17	.00	905.35	906.20	.03	1.11	.00	900.80
532.	126.	239.	166.	259.	126.	317.	19.	7.	900.81
.31	.49	1.90	.52	.060	.025	.060	.000	900.80	17.02
.000108	60.	60.	60.	2	0	7	.00	290.41	307.43

0
CCHV= .400 CEHV= .600
*SECNO 4.750

4.75	4.90	906.20	.00	905.38	906.21	.01	.01	.01	902.20
532.	226.	89.	218.	296.	57.	277.	20.	8.	902.30
.33	.76	1.54	.79	.060	.040	.060	.000	901.30	44.10
.000241	110.	60.	20.	1	0	0	.00	231.55	275.65

0
*SECNO 5.000
3280 CROSS SECTION 5.00 EXTENDED .20 FEET

3470 ENCROACHMENT STATIONS= 125.0 332.0 TYPE= 1 TARGET= 207.000

5.00	3.80	906.40	.00	905.48	906.42	.02	.20	.00	903.10
407.	177.	96.	134.	206.	62.	180.	29.	11.	903.60
.54	.86	1.53	.75	.060	.040	.060	.000	902.60	133.00
.000326	685.	745.	790.	2	0	0	.00	199.00	332.00

0
*SECNO 5.500
3280 CROSS SECTION 5.50 EXTENDED .05 FEET

1
02-06-92 18:06:19 PAGE

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

```
3470 ENCROACHMENT STATIONS=     110.0     330.0  TYPE=     1  TARGET=     220.000
     5.50     3.85   906.45      .00   905.50   906.45      .01      .03      .00   902.90
     407.       66.      256.      85.      160.      374.      203.      33.      13.    903.00
      .68       .41       .69      .42      .060      .040      .060      .000   902.60   116.20
   .000059      280.      285.      305.        2         0         0      .00   213.80   330.00
0
 CCHV=     .600 CEHV=     .950
 *SECNO 6.000

 3470 ENCROACHMENT STATIONS=     113.0     175.0  TYPE=     1  TARGET=      62.000
     6.00     1.36   906.46      .00   905.99   906.74      .29      .02      .27   905.10
     232.      150.       74.       8.       45.       13.       3.       34.      13.    905.30
      .69      3.32      5.89     2.47      .060      .040      .060      .000   905.10   113.00
   .018537      160.      160.      170.        2         0         0      .00    62.00   175.00
0
 *SECNO 6.900

 3301 HV CHANGED MORE THAN HVINS

 7185 MINIMUM SPECIFIC ENERGY
 3720 CRITICAL DEPTH ASSUMED

 3470 ENCROACHMENT STATIONS=         .2      31.8  TYPE=     1  TARGET=      31.600
     6.90     2.88   908.18   908.18   907.40   909.09      .91     1.30      .59   905.50
     232.       27.      159.      45.       8.       18.      12.       35.      13.    905.50
      .69      3.42      8.91     3.65      .060      .040      .060      .000   905.30     2.84
   .014420       80.       80.       80.        3        17         0      .00    22.94    25.78
0
 *SECNO 6.940

 3301 HV CHANGED MORE THAN HVINS


 3470 ENCROACHMENT STATIONS=      75.0     208.0  TYPE=     1  TARGET=     133.000
     6.94     3.81   909.19      .00   907.96   909.56      .37      .14      .32   906.58
     232.       25.      183.      24.       13.       34.      12.       35.      13.    906.48
      .69      1.90      5.38     1.93      .060      .040      .060      .000   905.38    84.94
   .004289       20.       20.       20.        5         0         0      .00    29.11   114.05
0
1
  02-06-92     18:06:19                                                                    PAGE

    SECNO     DEPTH     CWSEL     CRIWS     WSELK     EG        HV        HL        OLOSS     BANK ELEV
    Q         QLOB      QCH       QROB      ALOB      ACH       AROB      VOL       TWA     LEFT/RIGHT
    TIME      VLOB      VCH       VROB      XNL       XNCH      XNR       WTN       ELMIN       SSTA
    SLOPE     XLOBL     XLCH      XLOBR     ITRIAL    IDC       ICONT     CORAR     TOPWID      ENDST
```

```
 *SECNO 6.950

 3470 ENCROACHMENT STATIONS=      75.0     208.0  TYPE=     1  TARGET=     133.000
      6.95      3.85    909.38      .00    908.22    909.73      .36       .17       .01    906.73
      232.       25.      183.      24.       14.       34.      13.       35.       13.     906.63
       .70      1.87      5.30     1.91      .060      .040     .060      .000    905.53     84.80
   .004103       40.       40.      40.         2         0        0       .00     29.38    114.18
0
 *SECNO 7.000

 3470 ENCROACHMENT STATIONS=      75.0     208.0  TYPE=     1  TARGET=     133.000
      7.00      3.87    910.30      .00    909.23    910.65      .35       .91       .00    907.63
      232.       26.      182.      24.       14.       35.      13.       35.       14.     907.53
       .71      1.86      5.27     1.90      .060      .040     .060      .000    906.43     84.73
   .004019      225.      225.     225.         2         0        0       .00     29.50    114.23
0
 *SECNO 8.000
  WATER EL=X5 CARD=   917.430

 3470 ENCROACHMENT STATIONS=       1.0      79.0  TYPE=     1  TARGET=      78.000
      8.00      8.33    917.43      .00    913.48    917.45      .02       .17       .20    917.40
      232.        0.      232.       0.        0.      233.       2.       37.       14.     916.70
       .87       .00       .99      .13      .060      .040     .060      .000    909.10      4.50
   .000099      578.      578.     578.         0         0        0       .00     58.75     63.25
0
 *SECNO 9.000

 3470 ENCROACHMENT STATIONS=       1.0     161.0  TYPE=     1  TARGET=     160.000
      9.00      7.25    917.45      .00    913.59    917.47      .03       .02       .01    913.50
      207.        3.      194.      10.        8.      148.      25.       38.       14.     913.50
       .91       .35      1.31      .42      .060      .040     .060      .000    910.20     66.32
   .000122      185.      185.     185.         2         0        0       .00     41.63    107.96
0
 CCHV=     .600' CEHV=     .950
 *SECNO 10.000

 3470 ENCROACHMENT STATIONS=       1.0     161.0  TYPE=     1  TARGET=     160.000
     10.00      2.95    917.45      .00    915.54    917.58      .14       .00       .11    915.50
      207.        3.      195.       9.        3.       64.       9.       38.       14.     915.50
       .91       .98      3.05     1.06      .060      .040     .060      .000    914.50     67.15
   .001947        9.        9.       9.         0         0        0       .00     37.24    104.39
0
1
  02-06-92     18:06:19                                                                    PAGE


    SECNO     DEPTH     CWSEL     CRIWS     WSELK     EG        HV        HL        OLOSS     BANK ELEV
    Q         QLOB      QCH       QROB      ALOB      ACH       AROB      VOL       TWA     LEFT/RIGHT
    TIME      VLOB      VCH       VROB      XNL       XNCH      XNR       WTN       ELMIN       SSTA
    SLOPE     XLOBL     XLCH      XLOBR     ITRIAL    IDC       ICONT     CORAR     TOPWID      ENDST
```

*SECNO 11.000

3470 ENCROACHMENT STATIONS= 1.0 108.0 TYPE= 1 TARGET= 107.000

11.00	3.03	918.13	.00	917.49	918.63	.50	.70	.34	918.80
207.	0.	207.	0.	0.	36.	1.	38.	15.	918.00
.92	.00	5.67	.45	.060	.040	.060	.000	915.10	39.33
.011656	179.	179.	179.	2	0	0	.00	34.41	73.73

0

*SECNO 11.900

11.90	3.96	920.06	.00	918.63	920.21	.15	1.37	.21	920.00
207.	0.	201.	6.	0.	65.	9.	38.	15.	919.40
.95	.01	3.11	.62	.060	.040	.060	.000	916.10	14.79
.002411	300.	300.	300.	2	0	0	.00	53.83	68.62

0

*SECNO 12.000

7185 MINIMUM SPECIFIC ENERGY

3720 CRITICAL DEPTH ASSUMED

3470 ENCROACHMENT STATIONS= 1.0 309.0 TYPE= 1 TARGET= 308.000

12.00	.96	921.16	921.16	920.76	921.46	.31	.51	.15	920.40
207.	10.	166.	30.	5.	34.	14.	39.	15.	920.40
.96	1.88	4.86	2.11	.060	.040	.060	.000	920.20	55.83
.021103	100.	95.	100.	0	14	0	.00	93.11	148.94

0

1

THIS RUN EXECUTED 02-06-92

****

HEC2 RELEASE DATED NOV 76 UPDATED MAY 1984

ERROR CORR - 01,02,03,04,05,06

MODIFICATION - 50,51,52,53,54,55,56

IBM-PC-XT VERSION AUGUST 1985

****

NOTE- ASTERISK (*) AT LEFT OF CROSS-SECTION NUMBER INDICATES MESSAGE IN SUMMARY OF ERRORS LIST

McNEELY & LINCOLN ASSOCIATES

SUMMARY PRINTOUT TABLE 150

	SECNO	XLCH	ELTRD	ELLC	ELMIN	Q	CWSEL	CRIWS	EG	10K*S	VCH	AREA	.01K
	1.000	.00	.00	.00	877.80	215.00	881.60	.00	881.74	12.04	3.03	71.02	61.96
	1.000	.00	.00	.00	877.80	363.00	882.00	.00	882.30	22.28	4.38	82.79	76.90
	1.000	.00	.00	.00	877.80	433.00	882.50	.00	882.80	19.03	4.40	99.76	99.26
	1.000	.00	.00	.00	877.80	541.00	883.00	.00	883.34	18.43	4.69	124.36	126.03
*	1.250	60.00	.00	.00	881.53	215.00	884.07	884.07	884.87	121.39	7.20	29.87	19.51
*	1.250	60.00	.00	.00	881.53	363.00	884.79	884.79	885.82	113.77	8.14	44.62	34.03
*	1.250	60.00	.00	.00	881.53	433.00	885.08	885.08	886.19	110.41	8.44	51.28	41.21
*	1.250	60.00	.00	.00	881.53	541.00	885.48	885.48	886.70	107.39	8.87	60.96	52.20
*	1.500	60.00	.00	.00	882.63	215.00	886.83	.00	886.99	12.86	3.19	67.47	59.95
*	1.500	60.00	.00	.00	882.63	363.00	888.33	.00	888.49	9.19	3.23	112.38	119.72
*	1.500	60.00	.00	.00	882.63	433.00	889.29	.00	889.43	6.04	2.96	149.70	176.26
*	1.500	60.00	.00	.00	882.63	541.00	891.33	.00	891.41	2.25	2.34	286.46	361.01
	2.000	15.00	.00	.00	883.06	215.00	886.84	.00	887.03	16.70	3.49	61.56	52.61
	2.000	15.00	.00	.00	883.06	363.00	888.33	.00	888.52	11.01	3.45	105.33	109.38
	2.000	15.00	.00	.00	883.06	433.00	889.29	.00	889.44	7.08	3.13	141.90	162.76
	2.000	15.00	.00	.00	883.06	541.00	891.33	.00	891.42	2.51	2.42	277.00	341.48
	2.100	37.00	.00	.00	883.06	215.00	886.91	.00	887.09	15.36	3.39	63.48	54.87
	2.100	37.00	.00	.00	883.06	363.00	888.38	.00	888.56	10.69	3.41	106.51	111.03
	2.100	37.00	.00	.00	883.06	433.00	889.32	.00	889.47	6.95	3.11	143.01	164.26
	2.100	37.00	.00	.00	883.06	541.00	891.34	.00	891.43	2.50	2.41	277.67	342.41

2.250	159.00	.00	.00	884.60	215.00	887.21	.00	887.77	90.99	5.96	36.07	22.54
2.250	159.00	.00	.00	884.60	363.00	888.58	.00	888.92	33.85	4.65	77.99	62.39
2.250	159.00	.00	.00	884.60	433.00	889.45	.00	889.68	18.00	3.81	113.79	102.05
2.250	159.00	.00	.00	884.60	541.00	891.38	.00	891.48	4.01	2.59	233.68	270.20
2.400	36.00	.00	.00	885.30	215.00	887.74	887.74	888.45	125.83	6.74	31.88	19.17
2.400	36.00	.00	.00	885.30	363.00	888.59	.00	889.27	85.97	6.62	54.80	39.15
2.400	36.00	.00	.00	885.30	433.00	889.45	.00	889.86	39.18	5.13	84.45	69.18
2.400	36.00	.00	.00	885.30	541.00	891.38	.00	891.53	7.34	3.12	185.14	199.67

SECNO	XLCH	ELTRD	ELLC	ELMIN	Q	CWSEL	CRIWS	EG	10K*S	VCH	AREA	.01K
2.450	37.00	.00	.00	885.60	215.00	888.44	.00	888.85	62.51	5.17	41.59	27.19
2.450	37.00	.00	.00	885.60	363.00	888.94	.00	889.59	81.03	6.48	56.04	40.33
2.450	37.00	.00	.00	885.60	433.00	889.58	.00	890.06	48.39	5.56	77.84	62.24
2.450	37.00	.00	.00	885.60	541.00	891.39	.00	891.57	9.74	3.40	166.43	173.36
2.500	86.00	.00	.00	886.30	215.00	889.08	.00	889.58	106.07	5.68	37.82	20.88
2.500	86.00	.00	.00	886.30	363.00	889.85	.00	890.31	72.12	5.42	67.03	42.74
2.500	86.00	.00	.00	886.30	433.00	890.08	.00	890.56	72.37	5.57	77.69	50.90
2.500	86.00	.00	.00	886.30	541.00	891.56	.00	891.69	14.50	2.88	188.05	142.05
2.550	30.00	.00	.00	886.50	215.00	889.54	.00	889.88	64.15	4.64	46.39	26.84
2.550	30.00	.00	.00	886.50	363.00	890.08	.00	890.52	68.95	5.32	68.22	43.72
2.550	30.00	.00	.00	886.50	433.00	890.33	.00	890.78	67.34	5.38	80.51	52.76
2.550	30.00	.00	.00	886.50	541.00	891.60	.00	891.75	18.05	3.14	172.23	127.34
2.560	45.00	.00	.00	886.80	215.00	889.83	.00	890.17	64.74	4.65	46.22	26.72
2.560	45.00	.00	.00	886.80	363.00	890.40	.00	890.83	67.18	5.27	68.92	44.29
2.560	45.00	.00	.00	886.80	433.00	890.64	.00	891.08	66.89	5.36	80.77	52.94
2.560	45.00	.00	.00	886.80	541.00	891.67	.00	891.87	24.63	3.56	151.79	109.01
2.570	22.00	.00	.00	887.00	215.00	889.97	.00	890.34	72.77	4.88	44.09	25.20
2.570	22.00	.00	.00	887.00	363.00	890.54	.00	891.00	72.25	5.42	66.99	42.71
2.570	22.00	.00	.00	887.00	433.00	890.77	.00	891.25	71.75	5.55	78.03	51.12
2.570	22.00	.00	.00	887.00	541.00	891.71	.00	891.95	30.45	3.89	139.08	98.04

*	2.600	23.00	.00	.00	889.10	215.00	890.26	890.26	890.68	146.51	5.15	41.76	17.76
	2.600	23.00	.00	.00	889.10	363.00	890.72	.00	891.20	95.32	5.54	65.50	37.18
	2.600	23.00	.00	.00	889.10	433.00	890.94	.00	891.44	81.70	5.66	76.50	47.90
	2.600	23.00	.00	.00	889.10	541.00	891.74	.00	892.06	31.03	4.57	118.28	97.12
*	2.700	75.00	.00	.00	890.21	215.00	892.14	892.14	893.11	86.64	7.92	27.16	23.10
*	2.700	75.00	.00	.00	890.21	363.00	892.94	892.94	894.32	77.08	9.42	38.52	41.35
*	2.700	75.00	.00	.00	890.21	433.00	893.28	893.28	894.84	74.10	9.99	43.32	50.30
*	2.700	75.00	.00	.00	890.21	541.00	893.78	893.78	895.57	70.37	10.76	50.29	64.49
*	2.800	68.00	898.66	895.00	890.21	215.00	894.49	.00	894.68	6.07	3.57	60.30	87.28
*	2.800	68.00	898.66	895.00	890.21	363.00	896.07	.00	896.37	6.05	4.39	82.64	147.59
*	2.800	68.00	898.66	895.00	890.21	433.00	897.90	.00	898.15	3.47	3.99	108.54	232.46
*	2.800	68.00	898.66	895.00	890.21	541.00	899.52	.00	899.53	.19	1.05	1672.38	1251.63
	2.900	20.00	.00	.00	891.00	215.00	894.80	.00	894.83	3.05	1.30	165.84	123.05
	2.900	20.00	.00	.00	891.00	363.00	896.56	.00	896.59	2.08	1.39	260.76	251.66
	2.900	20.00	.00	.00	891.00	433.00	898.31	.00	898.33	1.14	1.22	355.17	406.12
	2.900	20.00	.00	.00	891.00	541.00	899.52	.00	899.54	1.06	1.29	420.47	525.26
	2.950	100.00	.00	.00	891.00	215.00	894.85	.00	894.86	1.40	.88	276.11	181.57
	2.950	100.00	.00	.00	891.00	363.00	896.61	.00	896.62	.69	.85	542.35	438.38
	2.950	100.00	.00	.00	891.00	433.00	898.35	.00	898.35	.28	.68	887.12	812.74
	2.950	100.00	.00	.00	891.00	541.00	899.56	.00	899.56	.22	.67	1171.18	1150.84

	SECNO	XLCH	ELTRD	ELLC	ELMIN	Q	CWSEL	CRIWS	EG	10K*S	VCH	AREA	.01K
*	3.000	259.00	.00	.00	893.20	215.00	895.83	895.83	896.28	118.09	6.60	65.10	19.78
	3.000	259.00	.00	.00	893.20	363.00	896.63	.00	896.91	64.43	5.93	135.26	45.22
	3.000	259.00	.00	.00	893.20	433.00	898.36	.00	898.40	8.21	2.84	344.82	151.13
	3.000	259.00	.00	.00	893.20	541.00	899.57	.00	899.60	4.00	2.30	529.77	270.52
	3.500	750.00	.00	.00	899.20	215.00	901.94	.00	902.19	60.54	5.20	82.74	27.63
*	3.500	750.00	.00	.00	899.20	363.00	902.15	902.15	902.57	96.97	7.01	106.68	36.86
*	3.500	750.00	.00	.00	899.20	433.00	902.24	902.24	902.72	109.71	7.66	117.59	41.34
*	3.500	750.00	.00	.00	899.20	541.00	902.44	902.44	902.92	106.96	7.97	143.00	52.31

3.750	250.00	.00	.00	899.80	215.00	903.13	.00	903.38	38.66	4.93	79.50	34.58
3.750	250.00	.00	.00	899.80	363.00	903.76	.00	904.03	38.20	5.59	127.07	58.74
3.750	250.00	.00	.00	899.80	433.00	903.98	.00	904.27	38.43	5.86	147.51	69.84
3.750	250.00	.00	.00	899.80	541.00	904.20	.00	904.52	41.76	6.36	181.41	83.72
4.000	265.00	.00	.00	900.50	215.00	903.86	.00	903.91	10.80	2.61	171.10	65.41
4.000	265.00	.00	.00	900.50	363.00	904.48	.00	904.53	9.64	2.84	268.58	116.92
4.000	265.00	.00	.00	900.50	433.00	904.71	.00	904.76	9.44	2.94	310.37	140.95
4.000	265.00	.00	.00	900.50	541.00	904.99	.00	905.04	9.81	3.15	363.37	172.72
4.250	50.00	.00	.00	900.80	207.00	903.90	.00	903.94	2.27	1.90	206.11	137.27
4.250	50.00	.00	.00	900.80	356.00	904.50	.00	904.56	3.06	2.49	296.62	203.54
4.250	50.00	.00	.00	900.80	433.00	904.73	.00	904.81	3.40	2.73	341.76	234.83
4.250	50.00	.00	.00	900.80	532.00	905.01	.00	905.09	3.69	2.98	402.03	277.01
4.500	60.00	905.01	903.30	900.80	207.00	905.35	.00	905.37	.74	1.40	269.48	240.90
4.500	60.00	905.01	903.30	900.80	356.00	905.85	.00	905.87	.66	1.42	614.36	439.33
* 4.500	60.00	905.01	903.30	900.80	433.00	906.01	.00	906.03	.84	1.64	654.98	472.28
* 4.500	60.00	905.01	903.30	900.80	532.00	906.17	.00	906.20	1.08	1.90	702.56	511.54
4.750	60.00	.00	.00	901.30	207.00	905.38	.00	905.38	1.00	.87	449.39	207.05
4.750	60.00	.00	.00	901.30	356.00	905.87	.00	905.88	1.58	1.18	554.96	283.57
4.750	60.00	.00	.00	901.30	433.00	906.03	.00	906.04	1.94	1.35	590.24	310.73
4.750	60.00	.00	.00	901.30	532.00	906.20	.00	906.21	2.41	1.54	630.35	342.52
5.000	745.00	.00	.00	902.60	159.00	905.48	.00	905.48	2.04	.98	274.60	111.42
5.000	745.00	.00	.00	902.60	265.00	906.00	.00	906.01	2.39	1.21	370.37	171.24
5.000	745.00	.00	.00	902.60	323.00	906.19	.00	906.20	2.73	1.34	406.57	195.62
5.000	745.00	.00	.00	902.60	407.00	906.40	.00	906.42	3.26	1.53	448.28	225.30
5.500	285.00	.00	.00	902.60	159.00	905.50	.00	905.50	.25	.37	535.38	317.71
5.500	285.00	.00	.00	902.60	265.00	906.04	.00	906.04	.38	.51	648.75	432.58
5.500	285.00	.00	.00	902.60	323.00	906.23	.00	906.23	.46	.58	689.73	477.41
5.500	285.00	.00	.00	902.60	407.00	906.45	.00	906.45	.59	.69	736.65	530.72

*	6.000	160.00	.00	.00	905.10	110.00	905.99	905.99	906.24	296.76	5.45	31.83	6.39
*	6.000	160.00	.00	.00	905.10	161.00	906.14	906.14	906.46	303.22	6.18	40.91	9.25
	6.000	160.00	.00	.00	905.10	180.00	906.23	.00	906.53	250.49	6.00	46.90	11.37
	6.000	160.00	.00	.00	905.10	232.00	906.46	.00	906.74	185.37	5.89	60.88	17.04
	SECNO	XLCH	ELTRD	ELLC	ELMIN	Q	CWSEL	CRIWS	EG	10K*S	VCH	AREA	.01K
	6.900	80.00	.00	.00	905.30	110.00	907.40	.00	907.95	119.52	6.57	22.60	10.06
	6.900	80.00	.00	.00	905.30	161.00	907.73	907.70	908.49	144.19	7.92	28.48	13.41
*	6.900	80.00	.00	.00	905.30	180.00	907.84	907.84	908.66	147.28	8.27	30.90	14.83
*	6.900	80.00	.00	.00	905.30	232.00	908.18	908.18	909.09	144.20	8.91	38.31	19.32
	6.940	20.00	.00	.00	905.38	110.00	907.96	.00	908.26	55.81	4.56	29.18	14.72
	6.940	20.00	.00	.00	905.38	161.00	908.59	.00	908.90	45.33	4.85	43.15	23.91
	6.940	20.00	.00	.00	905.38	180.00	908.77	.00	909.10	44.03	4.99	47.83	27.13
	6.940	20.00	.00	.00	905.38	232.00	909.19	.00	909.56	42.89	5.38	59.50	35.43
	6.950	40.00	.00	.00	905.53	110.00	908.22	.00	908.48	46.78	4.30	31.32	16.08
	6.950	40.00	.00	.00	905.53	161.00	908.79	.00	909.09	41.80	4.73	44.60	24.90
	6.950	40.00	.00	.00	905.53	180.00	908.96	.00	909.28	41.38	4.89	49.05	27.98
	6.950	40.00	.00	.00	905.53	232.00	909.38	.00	909.73	41.03	5.30	60.59	36.22
	7.000	225.00	.00	.00	906.43	110.00	909.23	.00	909.46	39.14	4.06	33.64	17.58
	7.000	225.00	.00	.00	906.43	161.00	909.73	.00	910.02	40.05	4.66	45.39	25.44
	7.000	225.00	.00	.00	906.43	180.00	909.89	.00	910.20	40.14	4.84	49.67	28.41
	7.000	225.00	.00	.00	906.43	232.00	910.30	.00	910.65	40.19	5.27	61.11	36.60
*	8.000	578.00	.00	.00	909.10	110.00	913.48	.00	913.52	5.25	1.51	72.98	48.00
*	8.000	578.00	.00	.00	909.10	161.00	914.41	.00	914.45	4.50	1.57	102.77	75.88
*	8.000	578.00	.00	.00	909.10	180.00	915.11	.00	915.14	3.10	1.40	128.49	102.28
*	8.000	578.00	.00	.00	909.10	232.00	917.43	.00	917.45	.99	.99	235.63	233.51
	9.000	185.00	.00	.00	910.20	73.00	913.59	.00	913.62	5.79	1.41	51.72	30.33
	9.000	185.00	.00	.00	910.20	106.00	914.50	.00	914.53	3.59	1.42	76.53	55.97
	9.000	185.00	.00	.00	910.20	139.00	915.17	.00	915.20	3.09	1.50	96.91	79.12
	9.000	185.00	.00	.00	910.20	207.00	917.45	.00	917.47	1.22	1.31	181.09	187.39

*	10.000	8.60	.00	.00	914.50	73.00	915.54	915.54	915.86	281.97	4.60	15.88	4.35
*	10.000	8.60	.00	.00	914.50	106.00	915.73	915.73	916.13	242.67	5.10	20.93	6.80
*	10.000	8.60	.00	.00	914.50	139.00	915.89	915.89	916.37	233.22	5.61	25.15	9.10
	10.000	8.60	.00	.00	914.50	207.00	917.45	.00	917.58	19.47	3.05	75.70	46.91
	11.000	179.00	.00	.00	915.10	73.00	917.49	.00	917.63	45.36	3.04	24.02	10.84
	11.000	179.00	.00	.00	915.10	106.00	917.81	.00	918.00	52.17	3.52	30.12	14.68
	11.000	179.00	.00	.00	915.10	139.00	918.10	.00	918.33	56.16	3.90	36.14	18.55
	11.000	179.00	.00	.00	915.10	207.00	918.13	.00	918.63	116.56	5.67	37.37	19.17
	11.900	300.00	.00	.00	916.10	73.00	918.63	.00	918.73	28.72	2.49	29.32	13.62
	11.900	300.00	.00	.00	916.10	106.00	919.07	.00	919.18	28.54	2.73	38.84	19.84
	11.900	300.00	.00	.00	916.10	139.00	919.43	.00	919.56	28.31	2.92	47.67	26.12
	11.900	300.00	.00	.00	916.10	207.00	920.06	.00	920.21	24.11	3.11	73.82	42.16
*	12.000	95.00	.00	.00	920.20	73.00	920.76	920.76	920.95	275.49	3.67	22.76	4.40
*	12.000	95.00	.00	.00	920.20	106.00	920.88	920.88	921.11	248.66	4.07	31.02	6.72
*	12.000	95.00	.00	.00	920.20	139.00	920.98	920.98	921.24	228.52	4.35	38.96	9.19
*	12.000	95.00	.00	.00	920.20	207.00	921.16	921.16	921.46	211.03	4.86	54.00	14.25

SUMMARY PRINTOUT TABLE 150

	SECNO	Q	CWSEL	DIFWSP	DIFWSX	DIFKWS	TOPWID	XLCH
	1.000	215.00	881.60	.00	.00	.00	28.59	.00
	1.000	363.00	882.00	.40	.00	.00	30.26	.00
	1.000	433.00	882.50	.50	.00	.00	41.14	.00
	1.000	541.00	883.00	.50	.00	.00	54.72	.00
*	1.250	215.00	884.07	.00	2.47	.00	18.81	60.00
*	1.250	363.00	884.79	.72	2.79	.00	22.14	60.00
*	1.250	433.00	885.08	.29	2.58	.00	23.48	60.00
*	1.250	541.00	885.48	.40	2.48	.00	25.31	60.00
*	1.500	215.00	886.83	.00	2.76	.00	26.48	60.00
*	1.500	363.00	888.33	1.50	3.54	.00	33.40	60.00
*	1.500	433.00	889.29	.96	4.21	.00	45.77	60.00
*	1.500	541.00	891.33	2.04	5.85	.00	79.00	60.00
	2.000	215.00	886.84	.00	.01	.00	25.77	15.00
	2.000	363.00	888.33	1.50	.00	.00	32.68	15.00
	2.000	433.00	889.29	.96	.00	.00	47.04	15.00
	2.000	541.00	891.33	2.04	.00	.00	79.00	15.00
	2.100	215.00	886.91	.00	.07	.00	26.11	37.00
	2.100	363.00	888.38	1.47	.05	.00	32.84	37.00
	2.100	433.00	889.32	.94	.03	.00	47.52	37.00
	2.100	541.00	891.34	2.02	.01	.00	79.00	37.00
	2.250	215.00	887.21	.00	.30	.00	24.63	159.00
	2.250	363.00	888.58	1.37	.20	.00	36.84	159.00
	2.250	433.00	889.45	.87	.13	.00	45.37	159.00
	2.250	541.00	891.38	1.93	.04	.00	72.00	159.00
*	2.400	215.00	887.74	.00	.53	.00	23.07	36.00
	2.400	363.00	888.59	.85	.01	.00	30.65	36.00
	2.400	433.00	889.45	.86	.00	.00	38.52	36.00
	2.400	541.00	891.38	1.93	.00	.00	66.49	36.00
	2.450	215.00	888.44	.00	.70	.00	26.55	37.00
	2.450	363.00	888.94	.50	.35	.00	31.01	37.00
	2.450	433.00	889.58	.64	.12	.00	36.80	37.00
	2.450	541.00	891.39	1.82	.02	.00	63.40	37.00
	2.500	215.00	889.08	.00	.64	.00	31.18	86.00
	2.500	363.00	889.85	.77	.91	.00	44.82	86.00
	2.500	433.00	890.08	.23	.50	.00	49.98	86.00
	2.500	541.00	891.56	1.48	.17	.00	98.62	86.00

	SECNO	Q	CWSEL	DIFWSP	DIFWSX	DIFKWS	TOPWID	XLCH
	2.550	215.00	889.54	.00	.46	.00	35.72	30.00
	2.550	363.00	890.08	.54	.23	.00	45.29	30.00
	2.550	433.00	890.33	.25	.25	.00	51.79	30.00
	2.550	541.00	891.60	1.27	.04	.00	93.22	30.00
	2.560	215.00	889.83	.00	.29	.00	35.64	45.00
	2.560	363.00	890.40	.57	.32	.00	45.56	45.00
	2.560	433.00	890.64	.24	.31	.00	51.96	45.00
	2.560	541.00	891.67	1.03	.07	.00	85.74	45.00
	2.570	215.00	889.97	.00	.13	.00	34.56	22.00
	2.570	363.00	890.54	.58	.14	.00	44.80	22.00
	2.570	433.00	890.77	.23	.14	.00	50.20	22.00
	2.570	541.00	891.71	.94	.04	.00	80.74	22.00
*	2.600	215.00	890.26	.00	.30	.00	52.00	23.00
	2.600	363.00	890.72	.46	.18	.46	52.00	23.00
	2.600	433.00	890.94	.22	.17	.68	52.00	23.00
	2.600	541.00	891.74	.80	.03	1.47	52.00	23.00
*	2.700	215.00	892.14	.00	1.87	.00	14.12	75.00
*	2.700	363.00	892.94	.80	2.22	.80	14.12	75.00
*	2.700	433.00	893.28	.34	2.34	1.14	14.12	75.00
*	2.700	541.00	893.78	.49	2.04	1.64	14.12	75.00
*	2.800	215.00	894.49	.00	2.35	.00	14.12	68.00
*	2.800	363.00	896.07	1.58	3.13	1.58	14.12	68.00
*	2.800	433.00	897.90	1.83	4.62	3.42	14.12	68.00
*	2.800	541.00	899.52	1.62	5.74	5.03	320.84	68.00
	2.900	215.00	894.80	.00	.32	.00	54.00	20.00
	2.900	363.00	896.56	1.76	.49	1.76	54.00	20.00
	2.900	433.00	898.31	1.75	.41	3.51	54.00	20.00
	2.900	541.00	899.52	1.21	.00	4.72	54.00	20.00
	2.950	215.00	894.85	.00	.05	.00	128.18	100.00
	2.950	363.00	896.61	1.76	.05	1.76	175.99	100.00
	2.950	433.00	898.35	1.74	.04	3.50	219.68	100.00
	2.950	541.00	899.56	1.21	.04	4.71	240.00	100.00
*	3.000	215.00	895.83	.00	.98	.00	72.27	259.00
	3.000	363.00	896.63	.80	.02	.80	101.11	259.00
	3.000	433.00	898.36	1.73	.01	2.53	141.35	259.00
	3.000	541.00	899.57	1.21	.01	3.74	160.99	259.00
	3.500	215.00	901.94	.00	6.12	.00	109.74	750.00
*	3.500	363.00	902.15	.21	5.52	.21	120.15	750.00
*	3.500	433.00	902.24	.09	3.88	.30	124.61	750.00
*	3.500	541.00	902.44	.20	2.87	.50	134.42	750.00

	SECNO	Q	CWSEL	DIFWSP	DIFWSX	DIFKWS	TOPWID	XLCH
	3.750	215.00	903.13	.00	1.19	.00	69.25	250.00
	3.750	363.00	903.76	.62	1.60	.62	87.46	250.00
	3.750	433.00	903.98	.22	1.74	.85	94.21	250.00
	3.750	541.00	904.20	.22	1.76	1.07	224.12	250.00
	4.000	215.00	903.86	.00	.73	.00	140.64	265.00
	4.000	363.00	904.48	.62	.72	.62	173.92	265.00
	4.000	433.00	904.71	.23	.73	.85	186.41	265.00
	4.000	541.00	904.99	.27	.79	1.12	201.13	265.00
	4.250	207.00	903.90	.00	.04	.00	125.22	50.00
	4.250	356.00	904.50	.61	.02	.61	182.06	50.00
	4.250	433.00	904.73	.23	.02	.84	208.00	50.00
	4.250	532.00	905.01	.28	.02	1.11	226.83	50.00
	4.500	207.00	905.35	.00	1.45	.00	130.94	60.00
	4.500	356.00	905.85	.50	1.35	.50	273.29	60.00
*	4.500	433.00	906.01	.15	1.27	.66	281.30	60.00
*	4.500	532.00	906.17	.17	1.16	.82	290.41	60.00
	4.750	207.00	905.38	.00	.03	.00	213.17	60.00
	4.750	356.00	905.87	.49	.02	.49	224.07	60.00
	4.750	433.00	906.03	.16	.02	.65	227.60	60.00
	4.750	532.00	906.20	.17	.03	.82	231.55	60.00
	5.000	159.00	905.48	.00	.10	.00	171.75	745.00
	5.000	265.00	906.00	.53	.14	.53	190.90	745.00
	5.000	323.00	906.19	.19	.16	.71	197.65	745.00
	5.000	407.00	906.40	.21	.20	.92	199.00	745.00
	5.500	159.00	905.50	.00	.02	.00	210.00	285.00
	5.500	265.00	906.04	.54	.03	.54	212.15	285.00
	5.500	323.00	906.23	.19	.04	.73	212.92	285.00
	5.500	407.00	906.45	.22	.05	.95	213.80	285.00
*	6.000	110.00	905.99	.00	.49	.00	60.30	160.00
*	6.000	161.00	906.14	.15	.10	.15	62.00	160.00
	6.000	180.00	906.23	.10	.00	.24	62.00	160.00
	6.000	232.00	906.46	.23	.01	.47	62.00	160.00
	6.900	110.00	907.40	.00	1.42	.00	17.59	80.00
	6.900	161.00	907.73	.33	1.59	.33	19.76	80.00
*	6.900	180.00	907.84	.11	1.61	.44	20.59	80.00
*	6.900	232.00	908.18	.34	1.72	.78	22.94	80.00
	6.940	110.00	907.96	.00	.56	.00	20.30	20.00
	6.940	161.00	908.59	.63	.86	.63	24.75	20.00
	6.940	180.00	908.77	.18	.93	.81	26.07	20.00
	6.940	232.00	909.19	.42	1.01	1.23	29.11	20.00

	SECNO	Q	CWSEL	DIFWSP	DIFWSX	DIFKWS	TOPWID	XLCH
	6.950	110.00	908.22	.00	.26	.00	21.04	40.00
	6.950	161.00	908.79	.57	.20	.57	25.17	40.00
	6.950	180.00	908.96	.17	.19	.74	26.41	40.00
	6.950	232.00	909.38	.41	.19	1.16	29.38	40.00
	7.000	110.00	909.23	.00	1.01	.00	21.82	225.00
	7.000	161.00	909.73	.50	.94	.50	25.39	225.00
	7.000	180.00	909.89	.16	.93	.66	26.58	225.00
	7.000	232.00	910.30	.41	.92	1.07	29.50	225.00
*	8.000	110.00	913.48	.00	4.25	.00	29.34	578.00
*	8.000	161.00	914.41	.93	4.68	.93	34.72	578.00
*	8.000	180.00	915.11	.70	5.22	1.63	38.78	578.00
*	8.000	232.00	917.43	2.32	7.13	3.95	58.75	578.00
	9.000	73.00	913.59	.00	.11	.00	25.37	185.00
	9.000	106.00	914.50	.91	.09	.91	29.20	185.00
	9.000	139.00	915.17	.67	.06	1.58	32.01	185.00
	9.000	207.00	917.45	2.28	.02	3.86	41.63	185.00
*	10.000	73.00	915.54	.00	1.95	.00	25.22	8.60
*	10.000	106.00	915.73	.20	1.23	.20	26.45	8.60
*	10.000	139.00	915.89	.16	.72	.35	27.43	8.60
	10.000	207.00	917.45	1.56	.00	1.91	37.24	8.60
	11.000	73.00	917.49	.00	1.95	.00	17.14	179.00
	11.000	106.00	917.81	.33	2.08	.33	19.13	179.00
	11.000	139.00	918.10	.29	2.21	.61	30.46	179.00
	11.000	207.00	918.13	.03	.68	.65	34.41	179.00
	11.900	73.00	918.63	.00	1.14	.00	20.20	300.00
	11.900	106.00	919.07	.44	1.25	.44	23.19	300.00
	11.900	139.00	919.43	.36	1.33	.80	26.70	300.00
	11.900	207.00	920.06	.64	1.93	1.43	53.83	300.00
*	12.000	73.00	920.76	.00	2.13	.00	64.64	95.00
*	12.000	106.00	920.88	.12	1.81	.12	72.91	95.00
*	12.000	139.00	920.98	.10	1.56	.22	80.41	95.00
*	12.000	207.00	921.16	.17	1.09	.40	93.11	95.00

1

SUMMARY OF ERRORS AND SPECIAL NOTES

CAUTION	SECNO=	1.250	PROFILE= 1	CRITICAL DEPTH ASSUMED
CAUTION	SECNO=	1.250	PROFILE= 1	PROBABLE MINIMUM SPECIFIC ENERGY
CAUTION	SECNO=	1.250	PROFILE= 1	20 TRIALS ATTEMPTED TO BALANCE WSEL
CAUTION	SECNO=	1.250	PROFILE= 2	CRITICAL DEPTH ASSUMED
CAUTION	SECNO=	1.250	PROFILE= 2	PROBABLE MINIMUM SPECIFIC ENERGY
CAUTION	SECNO=	1.250	PROFILE= 2	20 TRIALS ATTEMPTED TO BALANCE WSEL
CAUTION	SECNO=	1.250	PROFILE= 3	CRITICAL DEPTH ASSUMED
CAUTION	SECNO=	1.250	PROFILE= 3	PROBABLE MINIMUM SPECIFIC ENERGY
CAUTION	SECNO=	1.250	PROFILE= 3	20 TRIALS ATTEMPTED TO BALANCE WSEL
CAUTION	SECNO=	1.250	PROFILE= 4	CRITICAL DEPTH ASSUMED
CAUTION	SECNO=	1.250	PROFILE= 4	PROBABLE MINIMUM SPECIFIC ENERGY
CAUTION	SECNO=	1.250	PROFILE= 4	20 TRIALS ATTEMPTED TO BALANCE WSEL
NOTE	SECNO=	1.500	PROFILE= 1	WSEL BASED ON X5 CARD
NOTE	SECNO=	1.500	PROFILE= 2	WSEL BASED ON X5 CARD
NOTE	SECNO=	1.500	PROFILE= 3	WSEL BASED ON X5 CARD
NOTE	SECNO=	1.500	PROFILE= 4	WSEL BASED ON X5 CARD
CAUTION	SECNO=	2.400	PROFILE= 1	CRITICAL DEPTH ASSUMED
CAUTION	SECNO=	2.400	PROFILE= 1	MINIMUM SPECIFIC ENERGY
CAUTION	SECNO=	2.600	PROFILE= 1	CRITICAL DEPTH ASSUMED
CAUTION	SECNO=	2.600	PROFILE= 1	MINIMUM SPECIFIC ENERGY
CAUTION	SECNO=	2.700	PROFILE= 1	CRITICAL DEPTH ASSUMED
CAUTION	SECNO=	2.700	PROFILE= 1	PROBABLE MINIMUM SPECIFIC ENERGY
CAUTION	SECNO=	2.700	PROFILE= 1	20 TRIALS ATTEMPTED TO BALANCE WSEL
CAUTION	SECNO=	2.700	PROFILE= 2	CRITICAL DEPTH ASSUMED
CAUTION	SECNO=	2.700	PROFILE= 2	PROBABLE MINIMUM SPECIFIC ENERGY
CAUTION	SECNO=	2.700	PROFILE= 2	20 TRIALS ATTEMPTED TO BALANCE WSEL
CAUTION	SECNO=	2.700	PROFILE= 3	CRITICAL DEPTH ASSUMED
CAUTION	SECNO=	2.700	PROFILE= 3	PROBABLE MINIMUM SPECIFIC ENERGY
CAUTION	SECNO=	2.700	PROFILE= 3	20 TRIALS ATTEMPTED TO BALANCE WSEL
CAUTION	SECNO=	2.700	PROFILE= 4	CRITICAL DEPTH ASSUMED
CAUTION	SECNO=	2.700	PROFILE= 4	PROBABLE MINIMUM SPECIFIC ENERGY
CAUTION	SECNO=	2.700	PROFILE= 4	20 TRIALS ATTEMPTED TO BALANCE WSEL
CAUTION	SECNO=	2.800	PROFILE= 1	HYDRAULIC JUMP D.S.
CAUTION	SECNO=	2.800	PROFILE= 2	HYDRAULIC JUMP D.S.
CAUTION	SECNO=	2.800	PROFILE= 3	HYDRAULIC JUMP D.S.
CAUTION	SECNO=	2.800	PROFILE= 4	HYDRAULIC JUMP D.S.
CAUTION	SECNO=	3.000	PROFILE= 1	CRITICAL DEPTH ASSUMED
CAUTION	SECNO=	3.000	PROFILE= 1	PROBABLE MINIMUM SPECIFIC ENERGY
CAUTION	SECNO=	3.000	PROFILE= 1	20 TRIALS ATTEMPTED TO BALANCE WSEL
CAUTION	SECNO=	3.500	PROFILE= 2	CRITICAL DEPTH ASSUMED
CAUTION	SECNO=	3.500	PROFILE= 2	MINIMUM SPECIFIC ENERGY
CAUTION	SECNO=	3.500	PROFILE= 3	CRITICAL DEPTH ASSUMED
CAUTION	SECNO=	3.500	PROFILE= 3	PROBABLE MINIMUM SPECIFIC ENERGY
CAUTION	SECNO=	3.500	PROFILE= 3	20 TRIALS ATTEMPTED TO BALANCE WSEL

```
CAUTION  SECNO=     3.500  PROFILE= 4  CRITICAL DEPTH ASSUMED
CAUTION  SECNO=     3.500  PROFILE= 4  PROBABLE MINIMUM SPECIFIC ENERGY
CAUTION  SECNO=     3.500  PROFILE= 4  20 TRIALS ATTEMPTED TO BALANCE WSEL

CAUTION  SECNO=     4.500  PROFILE= 3  HYDRAULIC JUMP D.S.
CAUTION  SECNO=     4.500  PROFILE= 4  HYDRAULIC JUMP D.S.

CAUTION  SECNO=     6.000  PROFILE= 1  CRITICAL DEPTH ASSUMED
CAUTION  SECNO=     6.000  PROFILE= 1  PROBABLE MINIMUM SPECIFIC ENERGY
CAUTION  SECNO=     6.000  PROFILE= 1  20 TRIALS ATTEMPTED TO BALANCE WSEL
CAUTION  SECNO=     6.000  PROFILE= 2  CRITICAL DEPTH ASSUMED
CAUTION  SECNO=     6.000  PROFILE= 2  MINIMUM SPECIFIC ENERGY

CAUTION  SECNO=     6.900  PROFILE= 3  CRITICAL DEPTH ASSUMED
CAUTION  SECNO=     6.900  PROFILE= 3  MINIMUM SPECIFIC ENERGY
CAUTION  SECNO=     6.900  PROFILE= 4  CRITICAL DEPTH ASSUMED
CAUTION  SECNO=     6.900  PROFILE= 4  MINIMUM SPECIFIC ENERGY

NOTE     SECNO=     8.000  PROFILE= 1  WSEL BASED ON X5 CARD
NOTE     SECNO=     8.000  PROFILE= 2  WSEL BASED ON X5 CARD
NOTE     SECNO=     8.000  PROFILE= 3  WSEL BASED ON X5 CARD
NOTE     SECNO=     8.000  PROFILE= 4  WSEL BASED ON X5 CARD

CAUTION  SECNO=    10.000  PROFILE= 1  CRITICAL DEPTH ASSUMED
CAUTION  SECNO=    10.000  PROFILE= 1  PROBABLE MINIMUM SPECIFIC ENERGY
CAUTION  SECNO=    10.000  PROFILE= 1  20 TRIALS ATTEMPTED TO BALANCE WSEL
CAUTION  SECNO=    10.000  PROFILE= 2  CRITICAL DEPTH ASSUMED
CAUTION  SECNO=    10.000  PROFILE= 2  PROBABLE MINIMUM SPECIFIC ENERGY
CAUTION  SECNO=    10.000  PROFILE= 2  20 TRIALS ATTEMPTED TO BALANCE WSEL
CAUTION  SECNO=    10.000  PROFILE= 3  CRITICAL DEPTH ASSUMED
CAUTION  SECNO=    10.000  PROFILE= 3  PROBABLE MINIMUM SPECIFIC ENERGY
CAUTION  SECNO=    10.000  PROFILE= 3  20 TRIALS ATTEMPTED TO BALANCE WSEL

CAUTION  SECNO=    12.000  PROFILE= 1  CRITICAL DEPTH ASSUMED
CAUTION  SECNO=    12.000  PROFILE= 1  PROBABLE MINIMUM SPECIFIC ENERGY
CAUTION  SECNO=    12.000  PROFILE= 1  20 TRIALS ATTEMPTED TO BALANCE WSEL
CAUTION  SECNO=    12.000  PROFILE= 2  CRITICAL DEPTH ASSUMED
CAUTION  SECNO=    12.000  PROFILE= 2  PROBABLE MINIMUM SPECIFIC ENERGY
CAUTION  SECNO=    12.000  PROFILE= 2  20 TRIALS ATTEMPTED TO BALANCE WSEL
CAUTION  SECNO=    12.000  PROFILE= 3  CRITICAL DEPTH ASSUMED
CAUTION  SECNO=    12.000  PROFILE= 3  PROBABLE MINIMUM SPECIFIC ENERGY
CAUTION  SECNO=    12.000  PROFILE= 3  20 TRIALS ATTEMPTED TO BALANCE WSEL
CAUTION  SECNO=    12.000  PROFILE= 4  CRITICAL DEPTH ASSUMED
CAUTION  SECNO=    12.000  PROFILE= 4  MINIMUM SPECIFIC ENERGY
```

1


THIS RUN EXECUTED 02-06-92

```
**************************************************
  HEC2 RELEASE DATED NOV 76 UPDATED MAY  1984
  ERROR CORR -  01,02,03,04,05,06
  MODIFICATION -  50,51,52,53,54,55,56
  IBM-PC-XT VERSION AUGUST 1985
**************************************************
```

RANDOLPH STREET DRAIN

STARTING WATER SURFACE ELEVATION

SOURCE: FEMA - CITY OF NORTHVILLE
MICHIGAN


REACH 3
ZONE A1
DAM NO 2
DAM NO 3
LEXINGTON STREET
CONFLUENCE OF RANDOLPH DRAIN DIVERSION
STARTING WATER SURFACE ELEVATION FOR THE PROPOSED MODEL
ELEVATION IN FEET (NGVD)
910
900
890
880
870
4400
4800
5200
5600
6000
6400
6800
7200
7600
8000
8400
STREAM DISTANCE IN FEET ABOVE MOUTH
K
L
M
N
O
P
Q
R
LEGEND
50
10
50
10
ST
CF
A

4781 41

*

XKOR VALUE

FOR CULVERTS

MODELLED USING SB CARD

RANDOLPH STREET DRAIN - FLOOD STUDY
PRESSURE FLOW LOSS COEFFICIENT FOR CULVERTS.

EQUATION:

$$XKOR = Ke + Kf + Kp + Ko \quad \text{-------- --------} \quad 1$$

Where

Ke = entrance loss coefficient

Kf = friction loss coefficient

Kp = pier loss coefficient

Ko = outlet loss coefficient

$$Kf = (29\, n^2 L)/(R^{4/3}) \quad \text{------ -------- --------} \quad 2$$

Where

n = manning's roughness coefficient (0.0025)

L = length of culvert

R = hydraulic radius

For Multiple Culvert Analysis, XKOR equivalent is computed as:

$$XKOR\ eq. = \frac{AT^2}{\left(\sum_{i=1}^{n} \sqrt{A_i^2/K_i}\right)^2} \quad \text{-------- --------} \quad 3$$

Where

AT = total area

Ai = area of individual culvert

Ki = coefficient for individual culvert

n = number of culverts


CULVERT LOCATION	DESCRIPTION	HYD. Rad. ft	Ke	Kf	Kp	Ko	XKOR	XKOR eq.
~~LEXINGTON BLVD.~~	~~2 # 72" C.M.P.~~	~~1.50~~	~~0.7~~	~~0.64~~	~~0.05~~	~~1.0~~	~~2.39~~	~~2.39~~
McDONALD DR.	2 # 66"X51" ARCH	1.23	0.5	0.94	0.05	1.0	2.49	2.49
COLDSPRING DR.	5 # 42"X29" ARCH	0.69	0.5	1.78	0.05	1.0	3.33	3.33


References:
1) AISI Handbook of Steel Drainage & Construction Products, page 198-199
2) Bureau of Public Roads, 1958; Table on Ent. Loss Coeff. for Culverts

RANDOLPH STREET DRAIN

CROSS SECTION


DETAIL



RANDOLPH STREET DRAIN
CROSS SECTION # 1
ELEVATION IN FT. M.S.L
892
890
888
886
884
882
880
878
876
0
20
40
60
80
100
120
140
DISTANCE IN FEET



RANDOLPH DRAIN FLOOD LEVEL STUDY
CROSS SECTION #2
TOE
ELEVATION IN M.S.L
891
890
889
888
887
886
885
884
883
882
0
10
20
30
40
50
60
70
80
DISTANCE IN FEET


RANDOLPH DRAIN FLOOD LEVEL STUDY

CROSS SECTION #62·25





RANDOLPH DRAIN FLOOD LEVEL STUDY
CROSS SECTION #2·50
ELEVATION IN M.S.L
894
893
892
891
890
889
888
887
886
0
50
100
150
200
250
DISTANCE IN FEET


RANDOLPH STREET DRAIN
CROSS SECTION # 2.6
ELEVATION IN FT. M.S.L
898
897
896
895
894
893
892
891
890
889
0
50
100
150
200
250
DISTANCE IN FEET



RANDOLPH STREET DRAIN
TWIN 66X51 C.S.P @ McDONALD DRIVE
ELEVATION IN FT. M.S.L
904
902
900
898
896
894
892
890
0
50
100
150
200
250
300
350
400
DISTANCE IN FEET


RANDOLPH STREET DRAIN
CROSS SECTION # 2.9



RANDOLPH DRAIN FLOOD LEVEL STUDY


CROSS SECTION #~~1~~ 3






RANDOLPH DRAIN FLOOD LEVEL STUDY
CROSS SECTION # ~~12~~ 3.5
907
906
905
904
903
902
901
900
ELEVATION IN M.S.L
0
50
100
150
200
250
300
DISTANCE IN FEET


RANDOLPH DRAIN FLOOD LEVEL STUDY


CROSS SECTION #~~13~~ 375






RANDOLPH DRAIN FLOOD LEVEL STUDY
CROSS SECTION # M 4
907
906
905
904
903
902
901
900
ELEVATION IN M.S.L
0
50
100
150
200
250
300
DISTANCE IN FEET


RANDOLPH STREET DRAIN
5# 42X29 C.S.P @ COLDSPRING DRIVE
ELEVATION IN FT. M.S.L
909
908
907
906
905
904
903
902
901
900
0
50
100
150
200
250
300
350
400
DISTANCE IN FEET


RANDOLPH STREET DRAIN
CROSS SECTION # 4.75
ELEVATION IN FT. M.S.L
909
908
907
906
905
904
903
902
901
0
50
100
150
200
250
300
DISTANCE IN FEET



RANDOLPH DRAIN FLOOD LEVEL STUDY
CROSS SECTION #~~18~~ 5
908
907
906
905
904
903
902
ELEVATION IN M.S.L
Encroachment
0
50
100
150
200
250
300
350
DISTANCE IN FEET



RANDOLPH DRAIN FLOOD LEVEL STUDY
CROSS SECTION #~~10~~ 5.5
908
907
906
905
904
903
902
ELEVATION IN M.S.L
Encroachment
0
50
100
150
200
250
300
350
400
450
500
DISTANCE IN FEET



RANDOLPH DRAIN FLOOD LEVEL STUDY
CROSS SECTION #~~20~~ 6
909.5
909
908.5
908
907.5
907
906.5
906
905.5
905
ELEVATION IN M.S.L
Encroachment
0
50
100
150
200
250
300
DISTANCE IN FEET


RANDOLPH DRAIN FLOOD LEVEL STUDY


CROSS SECTION #~~21~~ 6.9




RANDOLPH DRAIN FLOOD LEVEL STUDY
CROSS SECTION #22 6.94
ELEVATION IN M.S.L
DISTANCE IN FEET
Encroachment
918
916
914
912
910
908
906
0
50
100
150
200
250


RANDOLPH DRAIN FLOOD LEVEL STUDY
CROSS SECTION #26 9
922
920
918
916
914
912
910
ELEVATION IN M.S.L
0
20
40
60
80
100
120
140
160
180
DISTANCE IN FEET
Encroachment


RANDOLPH DRAIN FLOOD LEVEL STUDY
CROSS SECTION # 10
ELEVATION IN M.S.L
921
920
919
918
917
916
915
914
0
20
40
60
80
100
120
140
160
180
DISTANCE IN FEET
Encroachment


RANDOLPH DRAIN FLOOD LEVEL STUDY
CROSS SECTION #~~2~~12
924
923.5
923
922.5
922
921.5
921
920.5
920
ELEVATION IN M.S.L
0
50
100
150
200
250
300
350
DISTANCE IN FEET
Encroachment

RANDOLPH STREET DRAIN

ENCROACHMENT

AND

FLOODWAY ANALYSIS

```
1*********************************************************
*****************************************
 *  WATER SURFACE PROFILES                          *                              *  U.S. ARMY CORPS OF ENGI
 *  VERSION OF NOVEMBER 1976                        *                              *  THE HYDROLOGIC ENGINEER
 *  UPDATED MAY 1984                                *                              *  609 SECOND STREET, SUIT
 *  IBM-PC-XT VERSION AUGUST 1985                   *                              *  DAVIS, CALIFORNIA 95616
 *  RUN DATE  02-07-92   TIME  08:42:51               *                              *  (916) 440-2105 (FTS)
 ****************************************************                              ****************************

                                                                  X     X  XXXXXXX   XXXXX              XXXXX
                                                                  X     X  X        X     X            X     X
                                                                  X     X  X        X                        X
                                                                  XXXXXXX  XXXX     X          XXXXX    XXXXX
                                                                  X     X  X        X                   X
                                                                  X     X  X        X     X             X
                                                                  X     X  XXXXXXX   XXXXX              XXXXXXX

1
  02-07-92     08:42:51                                                                                    PAGE


                                                                                                THIS RUN EXECUTED 02-07-92

 ************************************************
   HEC2 RELEASE DATED NOV 76 UPDATED MAY  1984
   ERROR CORR -  01,02,03,04,05,06
   MODIFICATION -  50,51,52,53,54,55,56
   IBM-PC-XT VERSION AUGUST 1985
 ************************************************
```

T1 RANDOLPH DRAIN FLOOD LEVEL STUDY DEVELOPED CONDITION

T2 STRETCH BETWEEN BECK ROAD AND 6 FT CULVERTS AT LEXINGTON DR

T3 McNEELY & LINCOLN ASSOCIATES, INC. DT: NOV. 19, 1991

J1	ICHECK	INQ	NINV	IDIR	STRT	METRIC	HVINS	Q	WSEL	FQ
	0.	2.	0.	0.	.000000	.00	.0	0.	882.500	.000

J2	NPROF	IPLOT	PRFVS	XSECV	XSECH	FN	ALLDC	IBW	CHNIM	ITRACE
	1.000	.000	-1.000	.000	.000	.000	.000	.000	.000	.000

J3 VARIABLE CODES FOR SUMMARY PRINTOUT

110.000	200.000	.000	.000	.000	.000	.000	.000	.000	.000

NC	.080	.080	.030	.300	.500	.000	.000	.000	.000	.000
QT	2.000	433.000	433.000	.000	.000	.000	.000	.000	.000	.000
ET	.000	.000	1.400	.000	.000	.000	.000	.000	.000	.000
X1	1.000	9.000	22.000	60.000	.000	.000	.000	.000	-1.500	.000
GR	884.400	.000	883.700	22.000	880.000	30.000	879.300	31.000	879.300	35.000
GR	880.000	36.000	880.200	46.000	887.100	60.000	891.900	126.000	.000	.000
X1	1.250	8.000	20.000	57.000	60.000	60.000	60.000	.000	-1.100	.000
GR	890.100	.000	888.500	20.000	883.600	32.000	882.630	34.000	882.630	36.000
GR	883.800	44.000	889.800	57.000	890.600	79.000	.000	.000	.000	.000
X1	1.500	8.000	20.000	57.000	60.000	60.000	60.000	.000	.000	.000
X5	2.000	889.290	889.290	.000	.000	.000	.000	.000	.000	.000
GR	890.100	.000	888.500	20.000	883.600	32.000	882.630	34.000	882.630	36.000
GR	883.800	44.000	889.800	57.000	890.600	79.000	.000	.000	.000	.000
X1	2.000	8.000	20.000	57.000	15.000	15.000	15.000	.000	.160	.000
GR	889.600	.000	888.500	20.000	883.600	32.000	882.900	34.000	882.900	36.000
GR	883.800	44.000	889.800	57.000	890.600	79.000	.000	.000	.000	.000
ET	.000	.000	1.400	.000	.000	.000	.000	.000	.000	.000
X1	2.100	.000	.000	.000	40.000	30.000	37.000	.000	.000	.000
X1	2.250	10.000	10.000	57.000	154.000	157.000	159.000	.000	.000	.000
GR	890.000	.000	889.500	10.000	885.800	32.000	884.600	34.000	884.600	36.000
GR	884.900	40.000	885.100	42.000	888.500	52.000	889.800	57.000	891.200	72.000
X1	2.400	.000	.000	.000	35.000	36.000	36.000	.000	.700	.000
X1	2.450	.000	.000	.000	35.000	35.000	37.000	.000	.300	.000
X1	2.500	11.000	40.000	166.000	84.000	85.000	86.000	.000	.000	.000
GR	894.000	.000	892.500	40.000	890.000	105.000	888.000	127.000	886.400	129.000
GR	886.300	132.000	886.700	136.000	888.000	139.000	892.000	166.000	894.000	206.000
GR	894.000	225.000	.000	.000	.000	.000	.000	.000	.000	.000
X1	2.550	.000	.000	.000	18.000	40.000	30.000	.000	.200	.000

X1	2.560	.000	.000	.000	26.000	60.000	45.000	.000	.300	.000
X1	2.570	.000	.000	.000	13.000	30.000	22.000	.000	.200	.000
ET	.000	7.100	7.100	.000	.000	.000	68.500	120.500	.000	.000
X1	2.600	10.000	55.000	192.000	13.000	30.000	23.000	.000	-.400	.000
GR	898.000	.000	896.000	17.000	894.000	31.000	892.000	55.000	890.000	74.000
GR	889.500	88.000	889.500	101.000	890.000	106.000	892.000	192.000	894.000	217.000
NC	.000	.000	.025	.300	.500	.000	.000	.000	.000	.000
ET	.000	.000	1.400	.000	.000	.000	.000	.000	.000	.000
X1	2.700	19.000	164.900	179.020	130.000	60.000	75.000	.000	.000	.000
X3	10.000	.000	.000	.000	.000	.000	.000	895.000	895.000	.000
GR	902.470	.000	895.000	75.000	890.220	164.900	890.210	166.000	890.210	167.100
GR	890.210	168.200	890.210	169.300	890.210	170.400	890.210	170.500	890.210	173.500
GR	890.220	174.600	890.220	175.700	890.220	176.800	890.220	177.900	890.220	178.990
GR	892.000	179.020	892.000	214.000	895.000	279.000	900.450	365.000	.000	.000
SB	1.050	2.490	3.000	.000	14.000	4.200	38.600	.000	890.700	890.210
X1	2.800	.000	.000	.000	68.000	68.000	68.000	.000	.000	.000
X2	.000	.000	1.000	895.000	898.660	.000	.000	.000	.000	.000
X3	10.000	.000	.000	.000	.000	.000	.000	898.660	898.660	.000
BT	19.000	.000	902.470	902.470	75.000	900.150	895.000	164.900	898.900	890.220
BT	166.000	898.900	892.450	167.100	898.890	894.210	168.200	898.890	894.450	169.300
BT	898.870	894.200	170.400	898.870	892.450	170.500	898.860	890.210	173.500	898.860
BT	890.210	174.600	898.850	892.450	175.700	898.850	894.200	176.800	898.840	894.450
BT	177.900	898.840	894.200	178.990	898.830	892.460	179.020	898.830	890.220	214.000
BT	899.660	892.000	279.000	899.260	895.000	365.000	900.450	900.450	.000	.000
NC	.000	.000	.040	.800	.900	.000	.000	.000	.000	.000
ET	.000	7.100	7.100	.000	.000	.000	92.000	146.000	.000	.000
X1	2.900	9.000	91.000	173.000	10.000	30.000	20.000	.000	-1.000	.000
GR	900.000	.000	898.000	28.000	896.000	54.000	894.000	91.000	892.000	119.000
GR	894.000	173.000	896.000	186.000	898.000	215.000	900.400	240.000	.000	.000
ET	.000	.000	1.400	.000	.000	.000	.000	.000	.000	.000
X1	2.950	.000	.000	.000	40.000	150.000	100.000	.000	.000	.000
X1	3.000	12.000	63.000	72.000	264.000	15.000	259.000	.000	.000	.000
GR	898.700	.000	896.400	25.000	894.900	50.000	894.600	63.000	893.300	64.000
GR	893.200	67.000	893.600	71.000	894.600	72.000	895.500	100.000	896.700	125.000
GR	898.200	143.000	899.800	164.000	.000	.000	.000	.000	.000	.000
NC	.060	.060	.035	.300	.500	.000	.000	.000	.000	.000
ET	.000	.000	.400	.000	.000	.000	.000	.000	.000	.000
X1	3.500	14.000	135.000	146.000	710.000	615.000	750.000	.000	-1.300	.000
GR	906.000	.000	904.000	66.000	903.000	91.000	902.800	116.000	902.100	135.000
GR	901.300	136.000	900.500	140.000	901.400	143.000	901.800	146.000	902.400	166.000
GR	903.100	191.000	904.100	216.000	905.300	241.000	906.500	255.000	.000	.000
X1	3.750	10.000	281.000	291.000	195.000	265.000	250.000	.000	.000	.000
GR	904.400	.000	904.000	255.000	902.000	280.000	901.200	281.000	899.900	285.000
GR	899.800	288.000	901.700	291.000	902.000	315.000	904.000	350.000	906.000	387.000

X1	4.000	14.000	135.000	146.000	230.000	245.000	265.000	.000	.000	.000
GR	906.000	.000	904.000	66.000	903.000	91.000	902.300	116.000	902.100	135.000
GR	901.300	136.000	900.500	140.000	901.400	143.000	901.800	146.000	902.400	166.000
GR	903.100	191.000	904.100	216.000	905.300	241.000	906.500	255.000	.000	.000
QT	2.000	433.000	433.000	.000	.000	.000	.000	.000	.000	.000
NC	.000	.000	.025	.600	.800	.000	.000	.000	.000	.000
X1	4.250	43.000	144.250	167.750	50.000	50.000	50.000	.000	.000	.000
X3	10.000	.000	.000	.000	.000	.000	.000	903.300	903.300	.000
GR	906.880	.000	904.800	50.000	904.100	107.000	900.900	143.250	900.800	144.250
GR	900.800	144.350	900.800	144.750	900.800	146.000	900.800	147.250	900.800	147.650
GR	900.800	147.750	900.800	149.250	900.800	149.350	900.800	149.750	900.800	151.000
GR	900.800	152.250	900.800	152.650	900.800	152.750	900.800	154.250	900.800	154.350
GR	900.800	154.750	900.800	156.000	900.800	157.250	900.800	157.650	900.800	157.750
GR	900.800	159.250	900.800	159.350	900.800	159.750	900.800	161.000	900.800	162.250
GR	900.800	162.650	900.800	162.750	900.800	164.250	900.800	164.350	900.800	164.750
GR	900.800	166.000	900.800	167.250	900.810	167.650	900.810	167.750	900.900	168.750
GR	903.000	200.000	904.300	250.000	908.440	377.000	.000	.000	.000	.000
SB	1.050	3.330	3.000	.000	23.500	8.000	34.000	.000	900.900	900.800
X1	4.500	.000	.000	.000	60.000	60.000	60.000	.000	.000	.000
X2	.000	.000	1.000	903.300	905.010	.000	.000	.000	.000	.000
X3	10.000	.000	.000	.000	.000	.000	.000	905.010	905.600	.000
BT	43.000	.000	906.880	906.880	50.000	905.540	904.800	107.000	905.010	904.100
BT	143.250	905.190	900.900	144.250	905.190	900.800	144.350	905.190	901.220	144.750
BT	905.200	903.000	146.000	905.220	903.220	147.250	905.230	903.000	147.650	905.240
BT	901.220	147.750	905.250	900.800	149.250	905.260	900.800	149.350	905.280	901.220
BT	149.750	905.290	903.000	151.000	905.300	903.220	152.250	905.310	903.000	152.650
BT	905.320	901.220	152.750	905.340	900.800	154.250	905.350	900.800	154.350	905.360
BT	901.220	154.750	905.370	903.000	156.000	905.380	903.220	157.250	905.400	903.000
BT	157.650	905.410	901.220	157.750	905.420	900.800	159.250	905.430	900.800	159.350
BT	905.440	901.220	159.750	905.460	903.000	161.000	905.470	903.220	162.250	905.480
BT	903.000	162.650	905.490	901.220	162.750	905.500	900.800	164.250	905.520	900.800
BT	164.350	905.530	901.220	164.750	905.540	903.000	166.000	905.550	903.220	167.250
BT	905.560	903.000	167.650	905.580	901.220	167.750	905.590	900.800	168.750	905.600
BT	900.900	200.000	906.060	903.000	250.000	906.600	904.300	377.000	908.440	908.440
NC	.000	.000	.040	.400	.600	.000	.000	.000	.000	.000
ET	.000	.000	1.400	.000	.000	.000	.000	.000	.000	.000
X1	4.750	8.000	163.000	176.000	110.000	20.000	60.000	.000	.000	.000
GR	906.880	.000	906.200	44.000	904.000	80.000	902.200	163.000	901.300	170.000
GR	902.300	176.000	904.000	262.000	908.500	290.000	.000	.000	.000	.000
QT	2.000	323.000	323.000	.000	.000	.000	.000	.000	.000	.000
ET	.000	7.100	7.100	7.100	7.100	.000	125.000	332.000	.000	.000
X1	5.000	15.000	214.000	232.000	685.000	790.000	745.000	.000	.000	.000
GR	906.000	.000	908.000	125.000	906.000	135.000	904.000	145.000	903.800	157.000
GR	903.500	182.000	903.600	207.000	903.100	214.000	902.600	225.000	903.100	229.000
GR	903.600	232.000	903.600	257.000	904.500	282.000	905.400	307.000	906.200	332.000
ET	.000	9.100	9.100	9.100	9.100	.000	.000	.000	110.000	330.000
X1	5.500	19.000	170.000	270.000	280.000	305.000	285.000	.000	.000	.000
GR	906.000	.000	908.000	110.000	906.000	118.000	904.000	126.000	902.800	145.000
GR	902.900	170.000	902.600	195.000	902.700	220.000	902.600	245.000	903.000	270.000
GR	903.100	295.000	903.000	320.000	903.700	345.000	904.000	370.000	904.000	395.000

GR	904.400	420.000	905.100	445.000	906.000	465.000	906.400	473.000	.000	.000
NC	.000	.000	.040	.600	.950	.000	.000	.000	.000	.000
QT	2.000	180.000	180.000	.000	.000	.000	.000	.000	.000	.000
ET	.000	7.100	7.100	.000	.000	.000	113.000	175.000	.000	.000
X1	6.000	15.000	160.000	170.000	160.000	170.000	160.000	.000	.000	.000
GR	905.200	.000	905.300	25.000	905.700	50.000	905.400	75.000	906.000	100.000
GR	905.700	125.000	905.100	160.000	905.300	170.000	905.900	172.000	906.100	175.000
GR	906.900	200.000	907.400	225.000	907.600	250.000	908.800	275.000	909.500	300.000
ET	.000	.000	.400	.000	.000	.000	.000	.000	.000	.000
X1	6.900	9.000	10.000	16.250	80.000	80.000	80.000	.000	.000	.000
GR	909.000	.000	906.700	8.000	905.500	10.000	905.300	11.000	905.300	16.000
GR	905.500	16.250	906.200	17.000	906.200	19.000	910.000	32.000	.000	.000
ET	.000	7.100	7.100	7.100	7.100	.000	75.000	208.000	.000	.000
X1	6.940	13.000	95.000	105.000	20.000	20.000	20.000	.000	-1.020	.000
GR	909.800	.000	911.300	25.000	912.200	50.000	912.800	75.000	907.600	95.000
GR	906.700	97.000	906.400	100.000	906.600	102.000	907.500	105.000	916.200	134.000
GR	916.600	159.000	917.300	184.000	917.400	209.000	.000	.000	.000	.000
ET	.000	7.100	7.100	7.100	7.100	.000	75.000	208.000	.000	.000
X1	6.950	13.000	95.000	105.000	40.000	40.000	40.000	.000	-.870	.000
GR	909.800	.000	911.300	25.000	912.200	50.000	912.800	75.000	907.600	95.000
GR	906.700	97.000	906.400	100.000	906.600	102.000	907.500	105.000	916.200	134.000
GR	916.600	159.000	917.300	184.000	917.400	209.000	.000	.000	.000	.000
ET	.000	7.100	7.100	.000	.000	.000	75.000	208.000	.000	.000
X1	7.000	.000	.000	.000	225.000	225.000	225.000	.000	.900	.000
ET	.000	.000	.400	.000	.000	.000	.000	.000	.000	.000
X1	8.000	10.000	5.000	55.000	578.000	578.000	578.000	.000	.000	.000
X5	2.000	915.110	915.110	.000	.000	.000	.000	.000	.000	.000
GR	917.700	.000	917.400	5.000	910.100	26.000	909.300	27.000	909.300	30.000
GR	909.100	33.500	909.600	34.300	916.700	55.000	917.300	60.000	918.100	80.000
QT	2.000	139.000	139.000	.000	.000	.000	.000	.000	.000	.000
X1	9.000	10.000	70.500	95.500	185.000	185.000	185.000	.000	.000	.000
GR	920.200	.000	920.100	25.000	919.700	40.000	918.700	65.000	913.500	70.500
GR	910.200	80.500	910.200	85.500	913.500	95.500	920.000	116.000	921.000	161.000
NC	.000	.000	.000	.600	.950	.000	.000	.000	.000	.000
ET	.000	.000	1.400	.000	.000	.000	.000	.000	.000	.000
X1	10.000	10.000	70.500	95.500	8.600	8.600	8.600	.000	.000	.000
GR	920.200	.000	920.100	25.000	919.700	40.000	918.700	65.000	915.500	70.500
GR	914.500	80.500	914.500	85.500	915.500	95.500	920.000	116.000	921.000	161.000
ET	.000	7.100	7.100	.000	.000	.000	1.000	108.000	.000	.000
X1	11.000	8.000	37.000	60.000	179.000	179.000	179.000	.000	.000	.000
GR	920.900	.000	918.800	37.000	915.100	50.000	915.100	53.000	918.000	60.000
GR	918.300	90.000	920.000	185.000	920.900	190.000	.000	.000	.000	.000
X1	11.900	7.000	15.000	43.000	300.000	300.000	300.000	.000	.000	.000
GR	924.400	.000	920.000	15.000	916.100	31.500	916.100	34.500	919.400	43.000
GR	920.000	68.000	922.000	88.000	.000	.000	.000	.000	.000	.000

ET	.000	.000	1.400	.000	.000	.000	.000	.000	.000	.000
X1	12.000	8.000	70.000	110.000	100.000	100.000	95.000	.000	.000	.000
GR	923.400	.000	922.000	40.000	920.400	70.000	920.200	100.000	920.400	110.000
GR	920.900	135.000	922.000	195.000	924.000	310.000	.000	.000	.000	.000
EJ	.000	.000	.000	.000	.000	.000	.000	.000	.000	.000

1

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

```
 *PROF 1

 CCHV=    .300 CEHV=    .500
 *SECNO 1.000
      1.00     4.70   882.50      .00   882.50   882.80      .30      .00      .00   882.20
      433.       0.     433.       0.       1.      98.       0.       0.       0.   885.60
       .00      .23     4.40      .00     .080     .030     .080     .000   877.80    12.57
    .001903       0.       0.       0.        0        0        0      .00    41.14    53.71
0
 *SECNO 1.250

 3301 HV CHANGED MORE THAN HVINS

 3685 20 TRIALS ATTEMPTED WSEL,CWSEL
 3693 PROBABLE MINIMUM SPECIFIC ENERGY
 3720 CRITICAL DEPTH ASSUMED
      1.25     3.55   885.08   885.08      .00   886.19     1.11      .23      .40   887.40
      433.       0.     433.       0.       0.      51.       0.       0.       0.   888.70
       .00      .00     8.44      .00     .080     .030     .080     .000   881.53    25.68
    .011041      60.      60.      60.       20       15        0      .00    23.48    49.16
0
 *SECNO 1.500
  WATER EL=X5 CARD=   889.290
      1.50     6.66   889.29      .00      .00   889.43      .14      .10      .29   888.50
      433.       1.     432.       0.       4.     146.       0.       0.       0.   889.80
       .01      .25     2.96      .00     .080     .030     .080     .000   882.63    10.13
    .000604      60.      60.      60.        0        0        0      .00    45.77    55.89
0
 *SECNO 2.000
      2.00     6.23   889.29      .00      .00   889.44      .15      .01      .01   888.66
      433.       1.     432.       0.       4.     138.       0.       0.       0.   889.96
       .01      .23     3.13      .00     .080     .030     .080     .000   883.06     8.51
    .000708      15.      15.      15.        2        0        0      .00    47.04    55.55
0
 *SECNO 2.100
      2.10     6.26   889.32      .00      .00   889.47      .15      .03      .00   888.66
      433.       1.     432.       0.       4.     139.       0.       0.       0.   889.96
       .01      .23     3.11      .00     .080     .030     .080     .000   883.06     8.08
    .000695      40.      37.      30.        0        0        0      .00    47.52    55.60
0
1
```


SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

*SECNO 2.250

2.25	4.85	889.45	.00	.00	889.68	.22	.17	.04	889.50
433.	0.	433.	0.	0.	114.	0.	1.	0.	889.80
.02	.00	3.81	.00	.080	.030	.080	.000	884.60	10.29
.001800	154.	159.	157.	2	0	0	.00	45.37	55.66

0

*SECNO 2.400

2.40	4.15	889.45	.00	.00	889.86	.41	.09	.09	890.20
433.	0.	433.	0.	0.	84.	0.	1.	0.	890.50
.03	.00	5.13	.00	.080	.030	.080	.000	885.30	14.45
.003918	35.	36.	36.	2	0	0	.00	38.52	52.97

0

*SECNO 2.450

2.45	3.98	889.58	.00	.00	890.06	.48	.16	.04	890.50
433.	0.	433.	0.	0.	78.	0.	1.	0.	890.80
.03	.00	5.56	.00	.080	.030	.080	.000	885.60	15.49
.004839	35.	37.	35.	2	0	0	.00	36.80	52.29

0

*SECNO 2.500

2.50	3.78	890.08	.00	.00	890.56	.48	.50	.00	892.50
433.	0.	433.	0.	0.	78.	0.	1.	0.	892.00
.03	.00	5.57	.00	.080	.030	.080	.000	886.30	103.03
.007237	84.	86.	85.	2	0	0	.00	49.98	153.01

0

*SECNO 2.550

2.55	3.83	890.33	.00	.00	890.78	.45	.21	.01	892.70
433.	0.	433.	0.	0.	81.	0.	1.	1.	892.20
.03	.00	5.38	.00	.080	.030	.080	.000	886.50	101.59
.006734	18.	30.	40.	3	0	0	.00	51.79	153.38

0

*SECNO 2.560

2.56	3.84	890.64	.00	.00	891.08	.45	.30	.00	893.00
433.	0.	433.	0.	0.	81.	0.	1.	1.	892.50
.04	.00	5.36	.00	.080	.030	.080	.000	886.80	101.46
.006689	26.	45.	60.	0	0	0	.00	51.96	153.42

0

1

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

*SECNO 2.570

2.57	3.77	890.77	.00	.00	891.25	.48	.15	.02	893.20
433.	0.	433.	0.	0.	78.	0.	1.	1.	892.70
.04	.00	5.55	.00	.080	.030	.080	.000	887.00	102.86
.007175	13.	22.	30.	0	0	0	.00	50.20	153.06

0

```
*SECNO 2.600

3470 ENCROACHMENT STATIONS=      68.5     120.5  TYPE=     1  TARGET=      52.000
     2.60     1.84   890.94      .00      .00   891.44      .50      .18      .01 99999.60
     433.       0.     433.       0.       0.      76.       0.       1.       1.  99999.60
      .04      .00     5.66      .00     .080     .030     .080     .000   889.10    68.50
   .008170      13.      23.      30.        1        0        0      .00    52.00   120.50
0
 CCHV=     .300 CEHV=     .500
 *SECNO 2.700

 3301 HV CHANGED MORE THAN HVINS

 3685 20 TRIALS ATTEMPTED WSEL,CWSEL
 3693 PROBABLE MINIMUM SPECIFIC ENERGY
 3720 CRITICAL DEPTH ASSUMED

 3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA=      895.00 ELREA=      895.00

     2.70     3.07   893.28   893.28      .00   894.84     1.55      .58      .53   890.22
     433.       0.     433.       0.       0.      43.       0.       2.       1.    892.00
      .04      .00     9.99      .00     .080     .025     .080     .000   890.21   164.90
   .007410      130.     75.      60.       20       14        0      .00    14.12   179.02
0

 SPECIAL BRIDGE

 5227 DOWNSTREAM ELEV IS    892.22 ,NOT    893.28 HYDRAULIC JUMP OCCURS DOWNSTREAM (IF LOW FLOW CONTROLS)

 SB  XK        XKOR      COFQ      RDLEN     BWC       BWP       BAREA     SS        ELCHU     ELCHD
     1.05      2.49      3.00       .00     14.00      4.20     38.60       .00     890.70    890.21

 *SECNO 2.800

 3301 HV CHANGED MORE THAN HVINS

1
  02-07-92     08:42:51                                                                    PAGE


    SECNO     DEPTH     CWSEL     CRIWS     WSELK     EG        HV        HL        OLOSS     BANK ELEV
    Q         QLOB      QCH       QROB      ALOB      ACH       AROB      VOL       TWA     LEFT/RIGHT
    TIME      VLOB      VCH       VROB      XNL       XNCH      XNR       WTN       ELMIN       SSTA
    SLOPE     XLOBL     XLCH      XLOBR     ITRIAL    IDC       ICONT     CORAR     TOPWID      ENDST


 PRESSURE FLOW


  EGPRS      EGLWC      H3       QWEIR      QPR       BAREA    TRAPEZOID      ELLC      ELTRD
                                                                AREA
     898.15    897.09       .00         0.      433.       39.       42.      895.00    898.66
```

```
3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA=      898.66 ELREA=      898.66

     2.80      7.69   897.90      .00      .00   898.15      .25     3.31      .00   890.22
     433.        0.     433.       0.       0.     109.       0.       2.       1.   892.00
      .04       .00     3.99      .00     .000     .025     .000     .000   890.21   164.90
  .000347       68.     68.       68.        2        0        0      .00    14.12   179.02
0
 CCHV=     .800 CEHV=     .900
 *SECNO 2.900

 3470 ENCROACHMENT STATIONS=      92.0     146.0  TYPE=      1  TARGET=      54.000
     2.90      7.31   898.31      .00      .00   898.33      .02      .00      .18 99999.00
     433.        0.     433.       0.       0.     355.       0.       2.       1. 99999.00
      .05       .00     1.22      .00     .080     .040     .080     .000   891.00    92.00
  .000114       10.     20.       30.        2        0        0      .00    54.00   146.00
0
 *SECNO 2.950
     2.95      7.35   898.35      .00      .00   898.35      .01      .00      .01   893.00
     433.        54.     352.      27.      234.     520.     134.       3.       1.   893.00
      .10       .23      .68      .20      .080     .040     .080     .000   891.00     9.26
  .000028       40.     100.      150.       1        0        0      .00   219.68   228.94
0
 *SECNO 3.000
     3.00      5.16   898.36      .00      .00   898.40      .05      .02      .04   894.60
     433.        140.    124.      169.     135.      44.     166.       6.       2.   894.60
      .13      1.03     2.84      1.02     .080     .040     .080     .000   893.20     3.72
  .000821       264.    259.       15.        0        0        0      .00   141.35   145.07
0
 CCHV=     .300 CEHV=     .500
1
  02-07-92      08:42:51                                                              PAGE


   SECNO     DEPTH     CWSEL     CRIWS     WSELK     EG        HV        HL        OLOSS    BANK ELEV
   Q         QLOB      QCH       QROB      ALOB      ACH       AROB      VOL       TWA    LEFT/RIGHT
   TIME      VLOB      VCH       VROB      XNL       XNCH      XNR       WTN       ELMIN      SSTA
   SLOPE     XLOBL     XLCH      XLOBR     ITRIAL    IDC       ICONT     CORAR     TOPWID     ENDST


 *SECNO 3.500
 3685 20 TRIALS ATTEMPTED WSEL,CWSEL
 3693 PROBABLE MINIMUM SPECIFIC ENERGY
 3720 CRITICAL DEPTH ASSUMED
     3.50      3.04   902.24   902.24      .00   902.72      .47     1.40      .21   900.80
     433.        92.     199.      142.      40.      26.      51.       9.       4.   900.50
      .17      2.27     7.66      2.77     .060     .035     .060     .000   899.20    77.44
  .010971       710.    750.      615.       20       14        0      .00   124.61   202.06
0
 *SECNO 3.750
     3.75      4.18   903.98      .00      .00   904.27      .29     1.50      .06   901.20
     433.        42.     209.      181.      27.      36.      85.      10.       4.   901.70
      .19      1.59     5.86      2.13     .060     .035     .060     .000   899.80   255.33
  .003843       195.    250.      265.        2        0        0      .00    94.21   349.54

0
```

```
*SECNO 4.000
     4.00     4.21   904.71      .00      .00   904.76      .05      .42      .07   902.10
     433.      160.     114.     158.     138.      39.     133.      12.       5.   901.80
      .23      1.16     2.94     1.19     .060     .035     .060     .000   900.50    42.41
   .000944     230.     265.     245.        3        0        0      .00   186.41   228.81
0
 CCHV=     .600 CEHV=     .800
 *SECNO 4.250
     4.25     3.93   904.73      .00      .00   904.81      .07      .03      .02   900.80
     433.       71.     253.     110.     101.      92.     148.      12.       5.   900.81
      .24       .70     2.73      .74     .060     .025     .060     .000   900.80    55.33
   .000340      50.      50.      50.        2        0        0      .00   208.00   263.33
0

 SPECIAL BRIDGE

 5227 DOWNSTREAM ELEV IS    902.18 ,NOT    904.73 HYDRAULIC JUMP OCCURS DOWNSTREAM (IF LOW FLOW CONTROLS)

 SB  XK         XKOR       COPQ       RDLEN      BWC        BWP        BAREA      SS         ELCHU      ELCHD
      1.05       3.33       3.00        .00      23.50       8.00      34.00       .00      900.90     900.80

 *SECNO 4.500
 PRESSURE AND WEIR FLOW

1
  02-07-92      08:42:51                                                                                PAGE

    SECNO     DEPTH     CWSEL     CRIWS     WSELK     EG        HV        HL        OLOSS     BANK ELEV
    Q         QLOB      QCH       QROB      ALOB      ACH       AROB      VOL       TWA    LEFT/RIGHT
    TIME      VLOB      VCH       VROB      XNL       XNCH      XNR       WTN       ELMIN       SSTA
    SLOPE     XLOBL     XLCH      XLOBR     ITRIAL    IDC       ICONT     CORAR     TOPWID      ENDST


  EGPRS       EGLWC       H3        QWEIR       QPR        BAREA    TRAPEZOID      ELLC      ELTRD
                                                                        AREA
     913.12    905.49        .00       263.       170.        34.        37.      903.30    905.01


      4.50     5.21   906.01      .00      .00   906.03      .02     1.22      .00   900.80
      433.      100.     200.     133.     238.     122.     294.      13.       6.   900.81
       .26       .42     1.64      .45     .060     .025     .060     .000   900.80    21.02
   .000084       60.      60.      60.        2        0        7      .00   281.30   302.32
0
 CCHV=     .400 CEHV=     .600
 *SECNO 4.750
     4.75     4.73   906.03      .00      .00   906.04      .01      .01      .00   902.20
     433.      182.      74.     176.     276.      55.     259.      13.       6.   902.30
      .28       .66     1.35      .68     .060     .040     .060     .000   901.30    46.96
   .000194      110.      60.      20.        0        0        0      .00   227.60   274.56
```

0
*SECNO 5.000

3470 ENCROACHMENT STATIONS= 125.0 332.0 TYPE= 1 TARGET= 207.000

5.00	3.59	906.19	.00	.00	906.20	.01	.16	.00	903.10
323.	141.	79.	103.	189.	59.	159.	22.	10.	903.60
.51	.75	1.34	.65	.060	.040	.060	.000	902.60	134.05
.000273	685.	745.	790.	2	0	0	.00	197.65	331.70

0
*SECNO 5.500

3470 ENCROACHMENT STATIONS= 110.0 330.0 TYPE= 1 TARGET= 220.000

5.50	3.63	906.23	.00	.00	906.23	.00	.03	.00	902.90
323.	52.	204.	67.	148.	352.	190.	26.	11.	903.00
.68	.35	.58	.35	.060	.040	.060	.000	902.60	117.08
.000046	280.	285.	305.	2	0	0	.00	212.92	330.00

0
CCHV= .600 CEHV= .950
*SECNO 6.000

3470 ENCROACHMENT STATIONS= 113.0 175.0 TYPE= 1 TARGET= 62.000

6.00	1.13	906.23	.00	.00	906.53	.30	.02	.28	905.10
180.	114.	62.	5.	35.	10.	2.	27.	12.	905.30
.69	3.28	6.00	2.32	.060	.040	.060	.000	905.10	113.00
.025049	160.	160.	170.	2	0	0	.00	62.00	175.00

0
1
02-07-92 08:42:51 PAGE

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

*SECNO 6.900

3301 HV CHANGED MORE THAN HVINS

7185 MINIMUM SPECIFIC ENERGY
3720 CRITICAL DEPTH ASSUMED

6.90	2.54	907.84	907.84	.00	908.66	.82	1.51	.49	905.50
180.	18.	130.	31.	6.	16.	9.	27.	12.	905.50
.69	3.17	8.27	3.34	.060	.040	.060	.000	905.30	4.03
.014729	80.	80.	80.	3	17	0	.00	20.59	24.62

0
*SECNO 6.940

3470 ENCROACHMENT STATIONS= 75.0 208.0 TYPE= 1 TARGET= 133.000

6.94	3.39	908.77	.00	.00	909.10	.33	.15	.29	906.58
180.	16.	149.	15.	9.	30.	9.	27.	12.	906.48
.69	1.71	4.99	1.75	.060	.040	.060	.000	905.38	86.57
.004404	20.	20.	20.	5	0	0	.00	26.07	112.64

0

```
 *SECNO 6.950

 3470 ENCROACHMENT STATIONS=      75.0     208.0  TYPE=     1  TARGET=     133.000
      6.95      3.43    908.96      .00      .00    909.28      .31      .17      .01    906.73
      180.       16.      148.       16.      10.       30.       9.       27.      12.    906.63
       .69      1.68     4.89     1.72     .060      .040     .060     .000    905.53     86.39
    .004138       40.      40.      40.        2         0        0      .00     26.41    112.80
0
 *SECNO 7.000

 3470 ENCROACHMENT STATIONS=      75.0     208.0  TYPE=     1  TARGET=     133.000
      7.00      3.46    909.89      .00      .00    910.20      .31      .92      .00    907.63
      180.       16.      148.       16.      10.       31.       9.       27.      12.    907.53
       .71      1.67     4.84     1.70     .060      .040     .060     .000    906.43     86.30
    .004014      225.     225.     225.        2         0        0      .00     26.58    112.87
0
 *SECNO 8.000
  WATER EL=X5 CARD=   915.110
      8.00      6.01    915.11      .00      .00    915.14      .03      .44      .17    917.40
      180.        0.      180.        0.       0.     128.        0.       28.      12.    916.70
       .82       .00     1.40      .00     .060      .040     .060     .000    909.10     11.59
    .000310      578.     578.     578.        0         0        0      .00     38.78     50.36
0
1
  02-07-92      08:42:51                                                                  PAGE


    SECNO     DEPTH     CWSEL     CRIWS     WSELK     EG        HV        EL        OLOSS     BANK ELEV
    Q         QLOB      QCH       QROB      ALOB      ACH       AROB      VOL       TWA     LEFT/RIGHT
    TIME      VLOB      VCH       VROB      XNL       XNCH      XNR       WTN       ELMIN       SSTA
    SLOPE     XLOBL     XLCH      XLOBR     ITRIAL    IDC       ICONT     CORAR     TOPWID      ENDST

 *SECNO 9.000
      9.00      4.97    915.17      .00      .00    915.20      .03      .06      .00    913.50
      139.       0.      137.       2.       1.       91.       4.       29.      12.    913.50
       .86       .31     1.50      .37     .060      .040     .060     .000    910.20     68.74
    .000309      185.     185.     185.        2         0        0      .00     32.01    100.75
0
 CCHV=    .600 CEHV=    .950
 *SECNO 10.000
 3685 20 TRIALS ATTEMPTED WSEL,CWSEL
 3693 PROBABLE MINIMUM SPECIFIC ENERGY
 3720 CRITICAL DEPTH ASSUMED
     10.00      1.39    915.89    915.89      .00    916.37      .49      .01      .43    915.50
      139.       0.      138.       0.       0.       25.       0.       29.      12.    915.50
       .86      1.15     5.61     1.25     .060      .040     .060     .000    914.50     69.83
    .023322        9.       9.       9.       20        14        0      .00     27.43     97.26
0
 *SECNO 11.000

 3470 ENCROACHMENT STATIONS=       1.0     108.0  TYPE=     1  TARGET=     107.000
     11.00      3.00    918.10      .00      .00    918.33      .24     1.81      .15    918.80
      139.       0.      139.       0.       0.       36.       0.       29.      13.    918.00
       .87       .00     3.90      .25     .060      .040     .060     .000    915.10     39.46
    .005616      179.     179.     179.        4         0        0      .00     30.46     69.92
```

```
0
 *SECNO 11.900
    11.90     3.33   919.43      .00      .00   919.56      .13     1.16      .06   920.00
     139.       0.      139.       0.       0.      48.       0.      29.      13.   919.40
      .90      .00     2.92      .01     .060     .040     .060     .000   916.10    17.42
   .002831     300.     300.     300.        4        0        0      .00    26.70    44.12
0
 *SECNO 12.000
 3685 20 TRIALS ATTEMPTED WSEL,CWSEL
 3693 PROBABLE MINIMUM SPECIFIC ENERGY
 3720 CRITICAL DEPTH ASSUMED
    12.00      .78   920.98   920.98      .00   921.24      .26      .59      .12   920.40
     139.       5.      119.      15.       3.      27.       8.      29.      13.   920.40
      .91     1.64     4.35     1.77     .060     .040     .060     .000   920.20    59.08
   .022852     100.       95.     100.       20       17        0      .00    80.41   139.49
0
1
  02-07-92      08:42:51                                                                PAGE


                                                                  THIS RUN EXECUTED 02-07-92

 ************************************************
   HEC2 RELEASE DATED NOV 76 UPDATED MAY  1984
   ERROR CORR -  01,02,03,04,05,06
   MODIFICATION -  50,51,52,53,54,55,56
   IBM-PC-XT VERSION AUGUST 1985
 ************************************************
```

```
T1      RANDOLPH DRAIN FLOOD LEVEL STUDY   DEVELOPED CONDITION
T2      STRETCH BETWEEN BECK ROAD AND 6 FT CULVERTS AT LEXINGTON DR
T3      McNEELY & LINCOLN ASSOCIATES, INC. DT: DEC. 06, 1991

J1  ICHECK     INQ        NINV       IDIR       STRT       METRIC     HVINS      Q          WSEL       FQ

      -10.        3.         0.         0.    .000000        .00         .0         0.    882.500       .000

J2  NPROF      IPLOT      PRFVS      XSECV      XSECH      FN         ALLDC      IBW        CHNIM      ITRACE

     15.000       .000     -1.000       .000       .000       .000       .000       .000       .000       .000

1
  02-07-92      08:42:51                                                                                  PAGE


    SECNO     DEPTH     CWSEL     CRIWS     WSELK     EG        HV        HL        OLOSS     BANK ELEV
    Q         QLOB      QCH       QROB      ALOB      ACH       AROB      VOL       TWA     LEFT/RIGHT
    TIME      VLOB      VCH       VROB      XNL       XNCH      XNR       WTN       ELMIN       SSTA
    SLOPE     XLOBL     XLCH      XLOBR     ITRIAL    IDC       ICONT     CORAR     TOPWID      ENDST


 *PROF 2

 CCHV=    .300 CEHV=    .500
 *SECNO 1.000
  2800 NAT Q1=     99.26  WSEL=    882.50  ENC Q1=    104.13  WSEL=    882.60  RATIO=  -.0490
  NAT Q1=    104.  RATIOS LOB,CH,ROB=   .0015   .9985   .0000  WSEL=    882.60

 3470 ENCROACHMENT STATIONS=      22.0       60.0  TYPE=     4  TARGET=        .002
      1.00      4.70   882.50       .00   882.50   882.80       .30       .00       .00   882.20
      433.       0.     433.        0.       0.      98.        0.        0.        0.    885.60
       .00       .00     4.40       .00      .080     .030      .080      .000   877.80    22.00
    .001928       0.       0.        0.        0        0         0       .00    31.71    53.71
0
 *SECNO 1.250
  2800 NAT Q1=     41.21  WSEL=    885.08  ENC Q1=     43.84  WSEL=    885.18  RATIO=  -.0639
  NAT Q1=     44.  RATIOS LOB,CH,ROB=   .0000  1.0000   .0000  WSEL=    885.18

 3301 HV CHANGED MORE THAN HVINS

 3685 20 TRIALS ATTEMPTED WSEL,CWSEL
 3693 PROBABLE MINIMUM SPECIFIC ENERGY
 3720 CRITICAL DEPTH ASSUMED

 3470 ENCROACHMENT STATIONS=      20.0       57.0  TYPE=     4  TARGET=        .000
      1.25      3.55   885.08   885.08   885.08   886.19      1.11       .23       .40   887.40
      433.       0.     433.        0.       0.      51.        0.        0.        0.    888.70
       .00       .00     8.44       .00      .080     .030      .080      .000   881.53    25.68
    .011041      60.      60.       60.       20       15         0       .00    23.48    49.16
0
 *SECNO 1.500
  WATER EL=X5 CARD=   889.290
  2800 NAT Q1=    176.26  WSEL=    889.29  ENC Q1=    182.41  WSEL=    889.39  RATIO=  -.0349
  NAT Q1=    183.  RATIOS LOB,CH,ROB=   .0029   .9971   .0000  WSEL=    889.39
```

```
3470 ENCROACHMENT STATIONS=      20.0      57.0  TYPE=     4  TARGET=        .003
     1.50     6.66   889.29      .00   889.29   889.43      .14      .10      .29   888.50
     433.       0.     433.       0.       0.     146.       0.       0.       0.   889.80
      .01      .00     2.97      .00     .080     .030     .080     .000   882.63    20.00
   .000623      60.      60.      60.        0        0        0      .00    35.89    55.89
0
1
 02-07-92     08:42:51                                                                PAGE

   SECNO    DEPTH    CWSEL    CRIWS    WSELK    EG       HV       HL       OLOSS    BANK ELEV
   Q        QLOB     QCH      QROB     ALOB     ACH      AROB     VOL      TWA    LEFT/RIGHT
   TIME     VLOB     VCH      VROB     XNL      XNCH     XNR      WTN      ELMIN      SSTA
   SLOPE    XLOBL    XLCH     XLOBR    ITRIAL   IDC      ICONT    CORAR    TOPWID     ENDST


*SECNO 2.000
 2800 NAT Q1=    162.76  WSEL=    889.29  ENC Q1=    168.78  WSEL=    889.39  RATIO=  -.0370
 NAT Q1=    169.  RATIOS LOB,CH,ROB=   .0027   .9973   .0000  WSEL=    889.39

3470 ENCROACHMENT STATIONS=      20.0      57.0  TYPE=     4  TARGET=        .003
     2.00     6.23   889.29      .00   889.29   889.44      .15      .01      .01   888.66
     433.       0.     433.       0.       0.     139.       0.       0.       0.   889.96
      .01      .00     3.13      .00     .080     .030     .080     .000   883.06    20.00
   .000722      15.      15.      15.        0        0        0      .00    35.57    55.57
0
*SECNO 2.100
 2800 NAT Q1=    164.26  WSEL=    889.32  ENC Q1=    170.60  WSEL=    889.42  RATIO=  -.0386
 NAT Q1=    171.  RATIOS LOB,CH,ROB=   .0030   .9970   .0000  WSEL=    889.42

3470 ENCROACHMENT STATIONS=      20.0      57.0  TYPE=     4  TARGET=        .003
     2.10     6.26   889.32      .00   889.32   889.47      .15      .03      .00   888.66
     433.       0.     433.       0.       0.     139.       0.       0.       0.   889.96
      .01      .00     3.11      .00     .080     .030     .080     .000   883.06    20.00
   .000713      40.      37.      30.        0        0        0      .00    35.61    55.61
0
*SECNO 2.250
 2800 NAT Q1=    102.05  WSEL=    889.45  ENC Q1=    107.91  WSEL=    889.55  RATIO=  -.0575
 NAT Q1=    108.  RATIOS LOB,CH,ROB=   .0000  1.0000   .0000  WSEL=    889.55

3470 ENCROACHMENT STATIONS=      10.0      57.0  TYPE=     4  TARGET=        .000
     2.25     4.85   889.45      .00   889.45   889.68      .22      .17      .04   889.50
     433.       0.     433.       0.       0.     114.       0.       1.       0.   889.80
      .02      .00     3.80      .00     .080     .030     .080     .000   884.60    10.27
   .001793     154.     159.     157.        2        0        0      .00    45.40    55.67
0
*SECNO 2.400
 2800 NAT Q1=     69.18  WSEL=    889.45  ENC Q1=     73.35  WSEL=    889.55  RATIO=  -.0603
 NAT Q1=     73.  RATIOS LOB,CH,ROB=   .0000  1.0000   .0000  WSEL=    889.55

3470 ENCROACHMENT STATIONS=      10.0      57.0  TYPE=     4  TARGET=        .000
     2.40     4.16   889.46      .00   889.45   889.86      .41      .09      .09   890.20
     433.       0.     433.       0.       0.      85.       0.       1.       0.   890.50
      .03      .00     5.12      .00     .080     .030     .080     .000   885.30    14.43
   .003899      35.      36.      36.        2        0        0      .00    38.56    52.98
```

SECNO	DEPTH	CWSEL	CRIWS	WSELR	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

*SECNO 2.450
2800 NAT Q1= 62.24 WSEL= 889.58 ENC Q1= 66.13 WSEL= 889.68 RATIO= -.0624
NAT Q1= 66. RATIOS LOB,CH,ROB= .0000 1.0000 .0000 WSEL= 889.68

3470 ENCROACHMENT STATIONS= 10.0 57.0 TYPE= 4 TARGET= .000

2.45	3.98	889.58	.00	889.58	890.06	.48	.16	.04	890.50
433.	0.	433.	0.	0.	78.	0.	1.	0.	890.80
.03	.00	5.55	.00	.080	.030	.080	.000	885.60	15.48
.004822	35.	37.	35.	2	0	0	.00	36.83	52.30

0
*SECNO 2.500
2800 NAT Q1= 50.90 WSEL= 890.08 ENC Q1= 54.46 WSEL= 890.18 RATIO= -.0700
NAT Q1= 54. RATIOS LOB,CH,ROB= .0000 1.0000 .0000 WSEL= 890.18

3470 ENCROACHMENT STATIONS= 40.0 166.0 TYPE= 4 TARGET= .000

2.50	3.78	890.08	.00	890.08	890.56	.48	.50	.00	892.50
433.	0.	433.	0.	0.	78.	0.	1.	0.	892.00
.03	.00	5.56	.00	.080	.030	.080	.000	886.30	102.91
.007195	84.	86.	85.	2	0	0	.00	50.13	153.04

0
*SECNO 2.550
2800 NAT Q1= 52.76 WSEL= 890.33 ENC Q1= 56.42 WSEL= 890.43 RATIO= -.0693
NAT Q1= 56. RATIOS LOB,CH,ROB= .0000 1.0000 .0000 WSEL= 890.43

3470 ENCROACHMENT STATIONS= 40.0 166.0 TYPE= 4 TARGET= .000

2.55	3.81	890.31	.00	890.33	890.78	.46	.21	.00	892.70
433.	0.	433.	0.	0.	79.	0.	1.	0.	892.20
.03	.00	5.47	.00	.080	.030	.080	.000	886.50	102.28
.006973	18.	30.	40.	2	0	0	.00	50.92	153.20

0
*SECNO 2.560
2800 NAT Q1= 52.94 WSEL= 890.64 ENC Q1= 56.65 WSEL= 890.74 RATIO= -.0700
NAT Q1= 57. RATIOS LOB,CH,ROB= .0000 1.0000 .0000 WSEL= 890.74

3470 ENCROACHMENT STATIONS= 40.0 166.0 TYPE= 4 TARGET= .000

2.56	3.84	890.64	.00	890.64	891.09	.45	.31	.00	893.00
433.	0.	433.	0.	0.	81.	0.	1.	1.	892.50
.04	.00	5.37	.00	.080	.030	.080	.000	886.80	101.56
.006722	26.	45.	60.	2	0	0	.00	51.84	153.39

0
1

```
   SECNO     DEPTH     CWSEL     CRIWS     WSELK     EG        HV        HL        OLOSS     BANK ELEV
   Q         QLOB      QCH       QROB      ALOB      ACH       AROB      VOL       TWA    LEFT/RIGHT
   TIME      VLOB      VCH       VROB      XNL       XNCH      XNR       WTN       ELMIN       SSTA
   SLOPE     XLOBL     XLCH      XLOBR     ITRIAL    IDC       ICONT     CORAR     TOPWID      ENDST


*SECNO 2.570
 2800 NAT Q1=      51.12  WSEL=     890.77  ENC Q1=      54.27  WSEL=     890.87  RATIO=  -.0616
 NAT Q1=      54.  RATIOS LOB,CH,ROB=    .0000  1.0000    .0000  WSEL=     890.87

3470 ENCROACHMENT STATIONS=       40.0      166.0  TYPE=      4  TARGET=         .000
     2.57      3.78    890.78       .00    890.77    891.26       .48       .15       .01    893.20
     433.       0.      433.        0.        0.       78.        0.        1.        1.     892.70
      .04       .00      5.55       .00      .080      .030      .080      .000    887.00    102.84
   .007170      13.       22.       30.         0         0         0       .00     50.22    153.06
0
 *SECNO 2.600

 3470 ENCROACHMENT STATIONS=       68.5      120.5  TYPE=      1  TARGET=        52.000
     2.60      1.85    890.95       .00    890.94    891.44       .49       .17       .01 99999.60
     433.       0.      433.        0.        0.       77.        0.        1.        1.  99999.60
      .04       .00      5.64       .00      .080      .030      .080      .000    889.10     68.50
   .008059      13.       23.       30.         1         0         0       .00     52.00    120.50
0
 CCHV=     .300 CEHV=     .500
 *SECNO 2.700
  2800 NAT Q1=      50.30  WSEL=     893.28  ENC Q1=      53.06  WSEL=     893.38  RATIO=  -.0549
  NAT Q1=      53.  RATIOS LOB,CH,ROB=    .0000  1.0000    .0000  WSEL=     893.38

 3301 HV CHANGED MORE THAN HVINS

 3685 20 TRIALS ATTEMPTED WSEL,CWSEL
 3693 PROBABLE MINIMUM SPECIFIC ENERGY
 3720 CRITICAL DEPTH ASSUMED

 3470 ENCROACHMENT STATIONS=      164.9      179.0  TYPE=      4  TARGET=         .000

 3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA=       895.00 ELREA=       895.00

     2.70      3.07    893.28    893.28    893.28    894.84      1.55       .61       .53    890.22
     433.       0.      433.        0.        0.       43.        0.        1.        1.     892.00
      .04       .00     10.00       .00      .080      .025      .080      .000    890.21    164.90
   .008222     130.       75.       60.        20        14         0       .00     14.12    179.02
0
1
  02-07-92     08:42:51                                                                        PAGE


   SECNO     DEPTH     CWSEL     CRIWS     WSELK     EG        HV        HL        OLOSS     BANK ELEV
   Q         QLOB      QCH       QROB      ALOB      ACH       AROB      VOL       TWA    LEFT/RIGHT
   TIME      VLOB      VCH       VROB      XNL       XNCH      XNR       WTN       ELMIN       SSTA
   SLOPE     XLOBL     XLCH      XLOBR     ITRIAL    IDC       ICONT     CORAR     TOPWID      ENDST
```

SPECIAL BRIDGE

5227 DOWNSTREAM ELEV IS 892.22 ,NOT 893.28 HYDRAULIC JUMP OCCURS DOWNSTREAM (IF LOW FLOW CONTROLS)

SB	XK	XKOR	COFQ	RDLEN	BWC	BWP	BAREA	SS	ELCHU	ELCHD
	1.05	2.49	3.00	.00	14.00	4.20	38.60	.00	890.70	890.21

*SECNO 2.800
PRESS FLOW BECAUSE EGLWC OF 898.24 EXCEEDS 1.5 DEPTH
2800 NAT Q1= 232.46 WSEL= 897.90 ENC Q1= 237.51 WSEL= 898.00 RATIO= -.0217
NAT Q1= 238. RATIOS LOB,CH,ROB= .0000 1.0000 .0000 WSEL= 898.00
WATER EL=CHANGE FROM NATURAL PROFILES BRIDGE

3470 ENCROACHMENT STATIONS= 164.9 179.0 TYPE= 4 TARGET= .000

3495 OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 898.66 ELREA= 898.66

2.80	7.69	897.90	.00	897.90	898.15	.25	.09	.39	890.22
433.	0.	433.	0.	0.	109.	0.	2.	1.	892.00
.04	.00	3.99	.00	.080	.025	.080	.000	890.21	164.90
.000529	68.	68.	68.	0	0	0	.00	14.12	179.02

0
CCHV= .800 CEHV= .900
*SECNO 2.900

3470 ENCROACHMENT STATIONS= 92.0 146.0 TYPE= 1 TARGET= 54.000

2.90	7.31	898.31	.00	898.31	898.33	.02	.00	.18	99999.00
433.	0.	433.	0.	0.	355.	0.	2.	1.	99999.00
.05	.00	1.22	.00	.080	.040	.080	.000	891.00	92.00
.000114	10.	20.	30.	2	0	0	.00	54.00	146.00

0
*SECNO 2.950
2800 NAT Q1= 812.74 WSEL= 898.35 ENC Q1= 812.74 WSEL= 898.45 RATIO= .0000
NAT Q1= 840. RATIOS LOB,CH,ROB= .1263 .8090 .0646 WSEL= 898.45

3470 ENCROACHMENT STATIONS= 44.5 197.3 TYPE= 4 TARGET= .032

2.95	7.34	898.34	.00	898.35	898.35	.01	.01	.01	893.00
433.	49.	363.	21.	189.	520.	90.	3.	1.	893.00
.09	.26	.70	.24	.080	.040	.080	.000	891.00	44.47
.000030	40.	100.	150.	2	0	0	.00	152.83	197.30

0
1

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

*SECNO 3.000
2800 NAT Q1= 151.13 WSEL= 898.36 ENC Q1= 151.13 WSEL= 898.46 RATIO= .0000
NAT Q1= 159. RATIOS LOB,CH,ROB= .3242 .2814 .3944 WSEL= 898.46

```
3470 ENCROACHMENT STATIONS=      24.7      125.2  TYPE=     4  TARGET=        .052
     3.00      5.16   898.36      .00   898.36   898.41      .06       .02       .04   894.60
     433.      135.      130.      168.      115.       44.      149.        6.        1.   894.60
      .13      1.17      2.97      1.13      .080      .040      .080      .000   893.20    24.66
   .000898      264.      259.       15.         2         0         0       .00   100.52   125.17
0
 CCHV=    .300 CEHV=    .500
 *SECNO 3.500
 7185 MINIMUM SPECIFIC ENERGY
 3720 CRITICAL DEPTH ASSUMED
     3.50      3.04   902.24   902.24   902.24   902.72      .47      1.50       .21   900.80
     433.       92.      199.      142.       40.       26.       51.        9.        3.   900.50
      .17      2.27      7.66      2.77      .060      .035      .060      .000   899.20    77.44
   .010971      710.      750.      615.       19        14         0       .00   124.61   202.06
0
 *SECNO 3.750
  2800 NAT Q1=      69.84  WSEL=    903.98  ENC Q1=      69.84  WSEL=    903.98  RATIO=    .0000
  NAT Q1=      70.  RATIOS LOB,CH,ROB=    .0984    .4828    .4188  WSEL=    903.98

 3470 ENCROACHMENT STATIONS=     266.5      333.6  TYPE=     4  TARGET=        .004
     3.75      4.17   903.97      .00   903.98   904.27      .30      1.51       .05   901.20
     433.       42.      210.      181.       22.       36.       78.       10.        4.   901.70
      .18      1.92      5.88      2.32      .060      .035      .060      .000   899.80   266.54
   .003869      195.      250.      265.         1         0         0       .00    67.06   333.60
0
 *SECNO 4.000
     4.00      4.22   904.72      .00   904.71   904.77      .05       .42       .08   902.10
     433.      160.      114.      158.      138.       39.      133.       11.        4.   901.80
      .23      1.16      2.94      1.19      .060      .035      .060      .000   900.50    42.51
   .000948      230.      265.      245.         0         0         0       .00   186.24   228.75
0
 CCHV=    .600 CEHV=    .800
 *SECNO 4.250
     4.25      3.94   904.74      .00   904.73   904.81      .07       .03       .02   900.80
     433.       71.      253.      110.      101.       92.      148.       11.        5.   900.81
      .23       .70      2.73       .74      .060      .025      .060      .000   900.80    55.33
   .000340       50.       50.       50.         0         0         0       .00   208.00   263.33
0
1
  02-07-92     08:42:51                                                                    PAGE


    SECNO     DEPTH     CWSEL     CRIWS     WSELK     EG        HV        HL        OLOSS    BANK ELEV
    Q         QLOB      QCH       QROB      ALOB      ACH       AROB      VOL       TWA    LEFT/RIGHT
    TIME      VLOB      VCH       VROB      XNL       XNCH      XNR       WTN       ELMIN       SSTA
    SLOPE     XLOBL     XLCH      XLOBR     ITRIAL    IDC       ICONT     CORAR     TOPWID      ENDST


 SPECIAL BRIDGE

 5227 DOWNSTREAM ELEV IS    902.18 ,NOT    904.74 HYDRAULIC JUMP OCCURS DOWNSTREAM (IF LOW FLOW CONTROLS)

 SB  XK        XKOR      COFQ      RDLEN     BWC       BWP       BAREA     SS        ELCHU     ELCHD
      1.05      3.33      3.00       .00     23.50      8.00     34.00       .00   900.90    900.80
```

```
*SECNO 4.500
PRESSURE AND WEIR FLOW

 EGPRS      EGLWC       H3       QWEIR      QPR       BAREA   TRAPEZOID      ELLC      ELTRD
                                                                 AREA
    913.13    906.08      .00       264.      169.       34.       37.      903.30    905.01


     4.50      5.21   906.01       .00   906.01   906.03       .02      1.21       .00   900.80
     433.      100.      200.      133.      238.      122.      294.      12.        5.    900.81
      .25       .42      1.64       .45       .060      .025      .060      .000   900.80    21.02
   .000084      60.       60.       60.         0         0         7       .00   281.30   302.32
0
 CCHV=    .400 CEHV=    .600
 *SECNO 4.750
  2800 NAT Q1=    310.73  WSEL=    906.03  ENC Q1=    310.73  WSEL=    906.13  RATIO=    .0000
  NAT Q1=    330.  RATIOS LOB,CH,ROB=    .4232    .1686    .4083  WSEL=    906.13

 3470 ENCROACHMENT STATIONS=      77.7      257.5  TYPE=     4  TARGET=        .059
     4.75      4.73   906.03       .00   906.03   906.04       .01       .01       .00   902.20
     433.      182.       78.      173.      247.       55.      237.      13.        5.    902.30
      .27       .74      1.42       .73       .060      .040      .060      .000   901.30    77.67
   .000215     110.       60.       20.         1         0         0       .00   179.80   257.46
0
 *SECNO 5.000

 3470 ENCROACHMENT STATIONS=     125.0      332.0  TYPE=     1  TARGET=     207.000
     5.00      3.60   906.20       .00   906.19   906.21       .01       .17       .00   903.10
     323.      141.       79.      103.      190.       59.      160.      21.        8.    903.60
      .51       .74      1.34       .65       .060      .040      .060      .000   902.60   134.00
   .000269     685.      745.      790.         2         0         0       .00   197.98   331.99
0
1
  02-07-92     08:42:51                                                                    PAGE


    SECNO     DEPTH     CWSEL     CRIWS     WSELK     EG        EV        HL        OLOSS    BANK ELEV
    Q         QLOB      QCH       QROB      ALOB      ACH       AROB      VOL       TWA    LEFT/RIGHT
    TIME      VLOB      VCH       VROB      XNL       XNCH      XNR       WTN       ELMIN       SSTA
    SLOPE     XLOBL     XLCH      XLOBR     ITRIAL    IDC       ICONT     CORAR     TOPWID      ENDST


 *SECNO 5.500

 3470 ENCROACHMENT STATIONS=     110.0      330.0  TYPE=     1  TARGET=     220.000
     5.50      3.64   906.24       .00   906.23   906.24       .00       .03       .00   902.90
     323.       52.      204.       67.      149.      353.      190.      24.       10.    903.00
      .67       .35       .58       .35       .060      .040      .060      .000   902.60   117.05
   .000045     280.      285.      305.         2         0         0       .00   212.95   330.00
```

0
 CCHV= .600 CEHV= .950
 *SECNO 6.000

 3470 ENCROACHMENT STATIONS= 113.0 175.0 TYPE= 1 TARGET= 62.000

6.00	1.14	906.24	.00	906.23	906.53	.29	.02	.27	905.10
180.	114.	62.	5.	35.	10.	2.	26.	10.	905.30
.68	3.24	5.93	2.30	.060	.040	.060	.000	905.10	113.00
.024174	160.	160.	170.	2	0	0	.00	62.00	175.00

0
 *SECNO 6.900

 3301 HV CHANGED MORE THAN HVINS

 7185 MINIMUM SPECIFIC ENERGY
 3720 CRITICAL DEPTH ASSUMED

6.90	2.54	907.84	907.84	907.84	908.66	.82	1.49	.50	905.50
180.	18.	130.	31.	6.	16.	9.	26.	10.	905.50
.68	3.17	8.28	3.34	.060	.040	.060	.000	905.30	4.03
.014735	80.	80.	80.	5	17	0	.00	20.59	24.62

0
 *SECNO 6.940

 3470 ENCROACHMENT STATIONS= 75.0 208.0 TYPE= 1 TARGET= 133.000

6.94	3.39	908.77	.00	908.77	909.10	.33	.15	.29	906.58
180.	16.	149.	15.	9.	30.	9.	26.	10.	906.48
.68	1.71	4.99	1.75	.060	.040	.060	.000	905.38	86.57
.004401	20.	20.	20.	5	0	0	.00	26.08	112.64

0
 *SECNO 6.950

 3470 ENCROACHMENT STATIONS= 75.0 208.0 TYPE= 1 TARGET= 133.000
1
 02-07-92 08:42:51 PAGE

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	KLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST
6.95	3.43	908.96	.00	908.96	909.28	.31	.17	.01	906.73
180.	16.	148.	16.	10.	30.	9.	26.	10.	906.63
.69	1.68	4.89	1.72	.060	.040	.060	.000	905.53	86.39
.004138	40.	40.	40.	2	0	0	.00	26.41	112.80

0
 *SECNO 7.000

 3470 ENCROACHMENT STATIONS= 75.0 208.0 TYPE= 1 TARGET= 133.000

7.00	3.46	909.89	.00	909.89	910.20	.31	.92	.00	907.63
180.	16.	148.	16.	10.	31.	9.	26.	11.	907.53
.70	1.67	4.84	1.70	.060	.040	.060	.000	906.43	86.30
.004013	225.	225.	225.	2	0	0	.00	26.58	112.88

0

```
*SECNO 8.000
 WATER EL=X5 CARD=   915.110
     8.00     6.01   915.11      .00   915.11   915.14      .03      .44      .17   917.40
      180.       0.     180.       0.       0.     128.       0.      27.      11.   916.70
       .82      .00     1.40      .00     .060     .040     .060     .000   909.10    11.59
   .000310     578.     578.     578.        0        0        0      .00    38.78    50.36
0
 *SECNO 9.000
 2800 NAT Q1=    79.12  WSEL=    915.17  ENC Q1=     79.12  WSEL=    915.17  RATIO=   .0000
 NAT Q1=     79.  RATIOS LOB,CH,ROB=   .0033   .9850   .0117  WSEL=    915.17

 3470 ENCROACHMENT STATIONS=      69.5      98.8  TYPE=     4  TARGET=        .002
     9.00     4.97   915.17      .00   915.17   915.20      .03      .06      .00   913.50
      139.       0.     137.       2.       1.      91.       4.      28.      11.   913.50
       .85      .30     1.50      .41     .060     .040     .060     .000   910.20    69.52
   .000308     185.     185.     185.        0        0        0      .00    29.28    98.79
0
 CCHV=    .600 CEHV=    .950
 *SECNO 10.000
 2800 NAT Q1=      9.10  WSEL=    915.89  ENC Q1=     10.65  WSEL=    915.99  RATIO=  -.1696
 NAT Q1=     11.  RATIOS LOB,CH,ROB=   .0017   .9935   .0048  WSEL=    915.99
 3685 20 TRIALS ATTEMPTED WSEL,CWSEL
 3693 PROBABLE MINIMUM SPECIFIC ENERGY
 3720 CRITICAL DEPTH ASSUMED

 3470 ENCROACHMENT STATIONS=      70.5      95.5  TYPE=     4  TARGET=        .006
1
  02-07-92     08:42:51                                                          PAGE


    SECNO    DEPTH    CWSEL    CRIWS    WSELK    EG       HV       HL       OLOSS    BANK ELEV
    Q        QLOB     QCH      QROB     ALOB     ACH      AROB     VOL      TWA   LEFT/RIGHT
    TIME     VLOB     VCH      VROB     XNL      XNCH     XNR      WTN      ELMIN      SSTA
    SLOPE    XLOBL    XLCH     XLOBR    ITRIAL   IDC      ICONT    CORAR    TOPWID     ENDST


     10.00     1.38   915.88   915.88   915.89   916.38      .50      .01      .44   915.50
      139.       0.     139.       0.       0.      25.       0.      28.      11.   915.50
       .85      .00     5.66      .00     .060     .040     .060     .000   914.50    70.50
   .024807       9.       9.       9.       20       14        0      .00    25.00    95.50
0
 *SECNO 11.000

 3470 ENCROACHMENT STATIONS=       1.0     108.0  TYPE=     1  TARGET=     107.000
     11.00     3.02   918.11      .00   918.10   918.35      .23     1.81      .16   918.80
      139.       0.     139.       0.       0.      36.       1.      28.      11.   918.00
       .86      .00     3.85      .28     .060     .040     .060     .000   915.10    39.40
   .005434     179.     179.     179.        4        0        0      .00    32.43    71.82
0
 *SECNO 11.900
     11.90     3.32   919.42      .00   919.43   919.55      .13     1.15      .06   920.00
      139.       0.     139.       0.       0.      48.       0.      28.      12.   919.40
       .89      .00     2.92      .01     .060     .040     .060     .000   916.10    17.44
   .002850     300.     300.     300.        4        0        0      .00    26.50    43.95
0
```

```
*SECNO 12.000
 2800 NAT Q1=      9.19  WSEL=    920.98  ENC Q1=      9.87  WSEL=    921.08  RATIO=  -.0732
 NAT Q1=     12.  RATIOS LOB,CH,ROB=   .0440   .8244   .1316  WSEL=    921.08
3685 20 TRIALS ATTEMPTED WSEL,CWSEL
3693 PROBABLE MINIMUM SPECIFIC ENERGY
3720 CRITICAL DEPTH ASSUMED

3470 ENCROACHMENT STATIONS=      70.0     110.0  TYPE=     4  TARGET=        .176
    12.00      .82   921.02   921.02   920.98   921.38      .37      .62      .22   920.40
     139.       0.     139.       0.       0.      29.       0.      28.      12.    920.40
      .90      .00     4.86      .00     .060     .040     .060     .000   920.20    70.00
   .027812     100.      95.     100.       20       11        0      .00    40.00   110.00
0
1
  02-07-92     08:42:51                                                                PAGE


                                                                    THIS RUN EXECUTED 02-07-92

 ************************************************
   HEC2 RELEASE DATED NOV 76 UPDATED MAY  1984
   ERROR CORR -  01,02,03,04,05,06
   MODIFICATION -  50,51,52,53,54,55,56
   IBM-PC-XT VERSION AUGUST 1985
 ************************************************
```

NOTE- ASTERISK (*) AT LEFT OF CROSS-SECTION NUMBER INDICATES MESSAGE IN SUMMARY OF ERRORS LIST

McNEELY & LINCOLN ASSOCIATES

SUMMARY PRINTOUT TABLE 110

	SECNO	CWSEL	DIFKWS	EG	TOPWID	QLOB	QCH	QROB	PERENC	STENCL	STCHL	STCHR	STENCR
	1.000	882.50	.00	882.80	41.14	.32	432.68	.00	.00	.00	22.00	60.00	.00
	1.000	882.50	.00	882.80	31.71	.00	433.00	.00	.00	22.00	22.00	60.00	60.00
*	1.250	885.08	.00	886.19	23.48	.00	433.00	.00	.00	.00	20.00	57.00	.00
*	1.250	885.08	.00	886.19	23.48	.00	433.00	.00	.00	20.00	20.00	57.00	57.00
*	1.500	889.29	.00	889.43	45.77	.96	432.04	.00	.00	.00	20.00	57.00	.00
*	1.500	889.29	.00	889.43	35.89	.00	433.00	.00	.00	20.00	20.00	57.00	57.00
	2.000	889.29	.00	889.44	47.04	.83	432.17	.00	.00	.00	20.00	57.00	.00
	2.000	889.29	.00	889.44	35.57	.00	433.00	.00	.00	20.00	20.00	57.00	57.00
	2.100	889.32	.00	889.47	47.52	.91	432.09	.00	.00	.00	20.00	57.00	.00
	2.100	889.32	.00	889.47	35.61	.00	433.00	.00	.00	20.00	20.00	57.00	57.00
	2.250	889.45	.00	889.68	45.37	.00	433.00	.00	.00	.00	10.00	57.00	.00
	2.250	889.45	.00	889.68	45.40	.00	433.00	.00	.00	10.00	10.00	57.00	57.00
	2.400	889.45	.00	889.86	38.52	.00	433.00	.00	.00	.00	10.00	57.00	.00
	2.400	889.46	.00	889.86	38.56	.00	433.00	.00	.00	10.00	10.00	57.00	57.00
	2.450	889.58	.00	890.06	36.80	.00	433.00	.00	.00	.00	10.00	57.00	.00
	2.450	889.58	.00	890.06	36.83	.00	433.00	.00	.00	10.00	10.00	57.00	57.00
	2.500	890.08	.00	890.56	49.98	.00	433.00	.00	.00	.00	40.00	166.00	.00
	2.500	890.08	.00	890.56	50.13	.00	433.00	.00	.00	40.00	40.00	166.00	166.00
	2.550	890.33	.00	890.78	51.79	.00	433.00	.00	.00	.00	40.00	166.00	.00
	2.550	890.31	-.02	890.78	50.92	.00	433.00	.00	.00	40.00	40.00	166.00	166.00

	2.560	890.64	.00	891.08	51.96	.00	433.00	.00	.00	.00	40.00	166.00	.00
	2.560	890.64	.00	891.09	51.84	.00	433.00	.00	.00	40.00	40.00	166.00	166.00
	SECNO	CWSEL	DIFKWS	EG	TOPWID	QLOB	QCH	QROB	PERENC	STENCL	STCHL	STCHR	STENCR
	2.570	890.77	.00	891.25	50.20	.00	433.00	.00	.00	.00	40.00	166.00	.00
	2.570	890.78	.01	891.26	50.22	.00	433.00	.00	.00	40.00	40.00	166.00	166.00
	2.600	890.94	.00	891.44	52.00	.00	433.00	.00	52.00	68.50	55.00	192.00	120.50
	2.600	890.95	.01	891.44	52.00	.00	433.00	.00	52.00	68.50	55.00	192.00	120.50
*	2.700	893.28	.00	894.84	14.12	.00	433.00	.00	.00	.00	164.90	179.02	.00
*	2.700	893.28	.00	894.84	14.12	.00	433.00	.00	.00	164.90	164.90	179.02	179.02
*	2.800	897.90	.00	898.15	14.12	.00	433.00	.00	.00	.00	164.90	179.02	.00
*	2.800	897.90	.00	898.15	14.12	.00	433.00	.00	.00	164.90	164.90	179.02	179.02
	2.900	898.31	.00	898.33	54.00	.00	433.00	.00	54.00	92.00	91.00	173.00	146.00
	2.900	898.31	.00	898.33	54.00	.00	433.00	.00	54.00	92.00	91.00	173.00	146.00
	2.950	898.35	.00	898.35	219.68	53.74	352.02	27.24	.00	.00	91.00	173.00	.00
	2.950	898.34	.00	898.35	152.83	48.65	363.04	21.31	.03	44.47	91.00	173.00	197.30
	3.000	898.36	.00	898.40	141.35	139.52	124.28	169.21	.00	.00	63.00	72.00	.00
	3.000	898.36	.00	898.41	100.52	134.63	129.94	168.43	.05	24.66	63.00	72.00	125.17
*	3.500	902.24	.00	902.72	124.61	92.07	199.15	141.78	.00	.00	135.00	146.00	.00
*	3.500	902.24	.00	902.72	124.61	92.07	199.15	141.78	.00	.00	135.00	146.00	.00
	3.750	903.98	.00	904.27	94.21	42.47	209.42	181.11	.00	.00	281.00	291.00	.00
	3.750	903.97	-.01	904.27	67.06	41.78	210.24	180.98	.00	266.54	281.00	291.00	333.61
	4.000	904.71	.00	904.76	186.41	160.44	114.28	158.28	.00	.00	135.00	146.00	.00
	4.000	904.72	.01	904.77	186.24	160.38	114.39	158.23	.00	.00	135.00	146.00	.00
	4.250	904.73	.00	904.81	208.00	70.92	252.57	109.51	.00	.00	144.25	167.75	.00
	4.250	904.74	.01	904.81	208.00	70.92	252.57	109.51	.00	.00	144.25	167.75	.00

*	4.500	906.01	.00	906.03	281.30	99.76	200.24	133.00	.00	.00	144.25	167.75	.00
*	4.500	906.01	.00	906.03	281.30	99.76	200.24	133.00	.00	.00	144.25	167.75	.00
	4.750	906.03	.00	906.04	227.60	182.33	74.39	176.28	.00	.00	163.00	176.00	.00
	4.750	906.03	.00	906.04	179.80	181.61	78.34	173.05	.06	77.67	163.00	176.00	257.47
	5.000	906.19	.00	906.20	197.65	141.14	78.78	103.07	207.00	125.00	214.00	232.00	332.00
	5.000	906.20	.01	906.21	197.98	141.12	78.66	103.22	207.00	125.00	214.00	232.00	332.00
	5.500	906.23	.00	906.23	212.92	51.74	204.43	66.84	220.00	110.00	170.00	270.00	330.00
	5.500	906.24	.01	906.24	212.95	51.76	204.39	66.85	220.00	110.00	170.00	270.00	330.00
	6.000	906.23	.00	906.53	62.00	113.52	61.93	4.54	62.00	113.00	160.00	170.00	175.00
	6.000	906.24	.01	906.53	62.00	113.68	61.72	4.60	62.00	113.00	160.00	170.00	175.00
*	6.900	907.84	.00	908.66	20.59	18.25	130.42	31.33	.00	.00	10.00	16.25	.00
*	6.900	907.84	.00	908.66	20.59	18.25	130.42	31.33	.00	.00	10.00	16.25	.00

	SECNO	CWSEL	DIPKWS	EG	TOPWID	QLOB	QCH	QROB	PERENC	STENCL	STCHL	STCHR	STENCR
	6.940	908.77	.00	909.10	26.07	15.80	148.88	15.32	133.00	75.00	95.00	105.00	208.00
	6.940	908.77	.00	909.10	26.08	15.81	148.87	15.32	133.00	75.00	95.00	105.00	208.00
	6.950	908.96	.00	909.28	26.41	16.21	148.12	15.67	133.00	75.00	95.00	105.00	208.00
	6.950	908.96	.00	909.28	26.41	16.21	148.12	15.67	133.00	75.00	95.00	105.00	208.00
	7.000	909.89	.00	910.20	26.58	16.41	147.75	15.85	133.00	75.00	95.00	105.00	208.00
	7.000	909.89	.00	910.20	26.58	16.41	147.74	15.85	133.00	75.00	95.00	105.00	208.00
*	8.000	915.11	.00	915.14	38.78	.00	180.00	.00	.00	.00	5.00	55.00	.00
*	8.000	915.11	.00	915.14	38.78	.00	180.00	.00	.00	.00	5.00	55.00	.00
	9.000	915.17	.00	915.20	32.01	.46	136.92	1.63	.00	.00	70.50	95.50	.00
	9.000	915.17	.00	915.20	29.28	.35	137.09	1.56	.00	69.52	70.50	95.50	98.79
*	10.000	915.89	.00	916.37	27.43	.15	138.43	.43	.00	.00	70.50	95.50	.00
*	10.000	915.88	.00	916.38	25.00	.00	139.00	.00	.01	70.50	70.50	95.50	95.50

	11.000	918.10	.00	918.33	30.46	.00	138.88	.12	107.00	1.00	37.00	60.00	108.00
	11.000	918.11	.02	918.35	32.43	.00	138.81	.19	107.00	1.00	37.00	60.00	108.00
	11.900	919.43	.00	919.56	26.70	.00	139.00	.00	.00	.00	15.00	43.00	.00
	11.900	919.42	.00	919.55	26.50	.00	139.00	.00	.00	.00	15.00	43.00	.00
*	12.000	920.98	.00	921.24	80.41	5.22	118.78	15.00	.00	.00	70.00	110.00	.00
*	12.000	921.02	.03	921.38	40.00	.00	139.00	.00	.18	70.00	70.00	110.00	110.00

1

SUMMARY OF ERRORS AND SPECIAL NOTES

```
CAUTION  SECNO=     1.250  PROFILE= 1  CRITICAL DEPTH ASSUMED
CAUTION  SECNO=     1.250  PROFILE= 1  PROBABLE MINIMUM SPECIFIC ENERGY
CAUTION  SECNO=     1.250  PROFILE= 1  20 TRIALS ATTEMPTED TO BALANCE WSEL
CAUTION  SECNO=     1.250  PROFILE= 2  CRITICAL DEPTH ASSUMED
CAUTION  SECNO=     1.250  PROFILE= 2  PROBABLE MINIMUM SPECIFIC ENERGY
CAUTION  SECNO=     1.250  PROFILE= 2  20 TRIALS ATTEMPTED TO BALANCE WSEL

NOTE     SECNO=     1.500  PROFILE= 1  WSEL BASED ON X5 CARD
NOTE     SECNO=     1.500  PROFILE= 2  WSEL BASED ON X5 CARD

CAUTION  SECNO=     2.700  PROFILE= 1  CRITICAL DEPTH ASSUMED
CAUTION  SECNO=     2.700  PROFILE= 1  PROBABLE MINIMUM SPECIFIC ENERGY
CAUTION  SECNO=     2.700  PROFILE= 1  20 TRIALS ATTEMPTED TO BALANCE WSEL
CAUTION  SECNO=     2.700  PROFILE= 2  CRITICAL DEPTH ASSUMED
CAUTION  SECNO=     2.700  PROFILE= 2  PROBABLE MINIMUM SPECIFIC ENERGY
CAUTION  SECNO=     2.700  PROFILE= 2  20 TRIALS ATTEMPTED TO BALANCE WSEL

CAUTION  SECNO=     2.800  PROFILE= 1  HYDRAULIC JUMP D.S.
CAUTION  SECNO=     2.800  PROFILE= 2  HYDRAULIC JUMP D.S.

CAUTION  SECNO=     3.500  PROFILE= 1  CRITICAL DEPTH ASSUMED
CAUTION  SECNO=     3.500  PROFILE= 1  PROBABLE MINIMUM SPECIFIC ENERGY
CAUTION  SECNO=     3.500  PROFILE= 1  20 TRIALS ATTEMPTED TO BALANCE WSEL
CAUTION  SECNO=     3.500  PROFILE= 2  CRITICAL DEPTH ASSUMED
CAUTION  SECNO=     3.500  PROFILE= 2  MINIMUM SPECIFIC ENERGY

CAUTION  SECNO=     4.500  PROFILE= 1  HYDRAULIC JUMP D.S.
CAUTION  SECNO=     4.500  PROFILE= 2  HYDRAULIC JUMP D.S.

CAUTION  SECNO=     6.900  PROFILE= 1  CRITICAL DEPTH ASSUMED
CAUTION  SECNO=     6.900  PROFILE= 1  MINIMUM SPECIFIC ENERGY
CAUTION  SECNO=     6.900  PROFILE= 2  CRITICAL DEPTH ASSUMED
CAUTION  SECNO=     6.900  PROFILE= 2  MINIMUM SPECIFIC ENERGY

NOTE     SECNO=     8.000  PROFILE= 1  WSEL BASED ON X5 CARD
NOTE     SECNO=     8.000  PROFILE= 2  WSEL BASED ON X5 CARD

CAUTION  SECNO=    10.000  PROFILE= 1  CRITICAL DEPTH ASSUMED
CAUTION  SECNO=    10.000  PROFILE= 1  PROBABLE MINIMUM SPECIFIC ENERGY
CAUTION  SECNO=    10.000  PROFILE= 1  20 TRIALS ATTEMPTED TO BALANCE WSEL
CAUTION  SECNO=    10.000  PROFILE= 2  CRITICAL DEPTH ASSUMED
CAUTION  SECNO=    10.000  PROFILE= 2  PROBABLE MINIMUM SPECIFIC ENERGY
CAUTION  SECNO=    10.000  PROFILE= 2  20 TRIALS ATTEMPTED TO BALANCE WSEL

CAUTION  SECNO=    12.000  PROFILE= 1  CRITICAL DEPTH ASSUMED
CAUTION  SECNO=    12.000  PROFILE= 1  PROBABLE MINIMUM SPECIFIC ENERGY
CAUTION  SECNO=    12.000  PROFILE= 1  20 TRIALS ATTEMPTED TO BALANCE WSEL
CAUTION  SECNO=    12.000  PROFILE= 2  CRITICAL DEPTH ASSUMED
CAUTION  SECNO=    12.000  PROFILE= 2  PROBABLE MINIMUM SPECIFIC ENERGY
CAUTION  SECNO=    12.000  PROFILE= 2  20 TRIALS ATTEMPTED TO BALANCE WSEL
1
```

FLOODWAY DATA, cNEELY & LINCOLN ASSOCIA
PROFILE NO. 2

STATION	FLOODWAY WIDTH	FLOODWAY SECTION AREA	FLOODWAY MEAN VELOCITY	WATER SURFACE ELEVATION WITH FLOODWAY	WITHOUT FLOODWAY	DIFFERENCE
1.000	32.	98.	4.4	882.5	882.5	.0
1.250	23.	51.	8.4	885.1	885.1	.0
1.500	36.	146.	3.0	889.3	889.3	.0
2.000	36.	139.	3.1	889.3	889.3	.0
2.100	36.	139.	3.1	889.3	889.3	.0
2.250	45.	114.	3.8	889.5	889.5	.0
2.400	39.	85.	5.1	889.5	889.5	.0
2.450	37.	78.	5.6	889.6	889.6	.0
2.500	50.	78.	5.6	890.1	890.1	.0
2.550	51.	79.	5.5	890.3	890.3	.0
2.560	52.	81.	5.4	890.6	890.6	.0
2.570	50.	78.	5.5	890.8	890.8	.0
2.600	52.	77.	5.6	890.9	890.9	.0
2.700	14.	43.	10.0	893.3	893.3	.0
2.800	14.	109.	4.0	897.9	897.9	.0
2.900	54.	355.	1.2	898.3	898.3	.0
2.950	153.	799.	.5	898.3	898.3	.0
3.000	101.	308.	1.4	898.4	898.4	.0
3.500	125.	118.	3.7	902.2	902.2	.0
3.750	67.	135.	3.2	904.0	904.0	.0
4.000	186.	310.	1.4	904.7	904.7	.0
4.250	208.	342.	1.3	904.7	904.7	.0
4.500	281.	655.	.7	906.0	906.0	.0
4.750	180.	540.	.8	906.0	906.0	.0
5.000	198.	408.	.8	906.2	906.2	.0
5.500	213.	692.	.5	906.2	906.2	.0
6.000	62.	47.	3.8	906.2	906.2	.0
6.900	21.	31.	5.8	907.8	907.8	.0
6.940	26.	48.	3.8	908.8	908.8	.0
6.950	26.	49.	3.7	909.0	909.0	.0
7.000	27.	50.	3.6	909.9	909.9	.0
8.000	39.	128.	1.4	915.1	915.1	.0
9.000	29.	96.	1.4	915.2	915.2	.0
10.000	25.	25.	5.7	915.9	915.9	.0
11.000	32.	37.	3.8	918.1	918.1	.0
11.900	27.	48.	2.9	919.4	919.4	.0
12.000	40.	29.	4.9	921.0	921.0	.0

```
**************************************************
  HEC2 RELEASE DATED NOV 76 UPDATED MAY  1984
  ERROR CORR -  01,02,03,04,05,06
  MODIFICATION -  50,51,52,53,54,55,56
  IBM-PC-XT VERSION AUGUST 1985
**************************************************
```

72 INCH C.M.P @ LEXINGTON BLVD.

INLET CONTROL NOMOGRAPH

X-5 CARD WSEL




Figure 4-28 *Inlet control* nomograph for corrugated steel *pipe* culverts The manufacturers recommended keeping *HW/D* to a maximum of 1 5 and preferably to no more than 1 0

60 INCH RCP CULVERT

X5 CARD "WSEL"

CALCULATION




Figure B–2. Headwater depth for concrete pipe culverts with inlet control.

CULVERTS

50-YEAR

DIAMETER (IN)	? 60
L[illegible]TH (FT)	? 578
F[illegible]TION COEFF (FT^1/6)	? .013
E[illegible]EXIT COEFF	? .5
INLET CONTROL COEFF	? .61
INV ELEV OUT (FT)	? 906.4
INV ELEV IN (FT)	? 909.1
TAILWATER ELEV (FT)	? 909.73
ELEV INCREMENT (FT)	? .03

RESULTS

HEADWATER (FT)		FLOWRATE (CFS)
914.10	IC	151.98
914.13	IC	152.88
914.16	IC	153.79
914.19	IC	154.69
914.22	IC	155.58
914.25	IC	156.47
914.28	IC	157.35
914.31	IC	158.23
914.34	IC	159.10
914.37	IC	159.97
914.40	IC	160.84 ←
914.43	IC	161.69
914.46	IC	162.55
914.49	IC	163.40
914.52	IC	164.25

<Shift> <Prt Sc> print <Return> repeat <Space Bar> back to menu

---

Q = 161 cfs

HW = 914.41

CULVERTS

100 YEAR

DIAMETER (IN)	? 60
LENGTH (FT)	? 578
FRICTION COEFF (FT^1/6)	? .013
EXIT COEFF	? .5
INLET CONTROL COEFF	? .61
INV ELEV OUT (FT)	? 906.4
INV ELEV IN (FT)	? 909.1
TAILWATER ELEV (FT)	? 909.9
ELEV INCREMENT (FT)	? .2

RESULTS

HEADWATER (FT)		FLOWRATE (CFS)
914.10	IC	151.98
914.30	IC	157.94
914.50	IC	163.68
914.70	IC	169.23
914.90	IC	174.61
915.10	IC	179.82
915.30	IC	184.89
915.50	IC	189.82
915.70	IC	194.62
915.90	IC	199.31
916.10	IC	203.90
916.30	IC	208.38
916.50	IC	212.77
916.70	IC	217.06
916.90	IC	221.28

<Shift> <Prt Sc> print <Return> repeat <Space Bar> back to menu

---

$Q = 180$ cfs

$HW = 915.11$

CULVERTS

50 yr

DIAMETER (IN)	? 60
LENGTH (FT)	? 578
FRICTION COEFF (FT^1/6)	? .013
BORDA EXIT COEFF	? .5
INLET CONTROL COEFF	? .61
INV ELEV OUT (FT)	? 906.4
INV ELEV IN (FT)	? 909.1
TAILWATER ELEV (FT)	? 910.3
ELEV INCREMENT (FT)	? .3

RESULTS

HEADWATER (FT)		FLOWRATE (CFS)
914.10	IC	151.98
914.40	IC	160.84
914.70	IC	169.23
915.00	IC	177.23
915.30	IC	184.89
915.60	IC	192.24
915.90	IC	199.31
916.20	IC	206.15
916.50	IC	212.77
916.80	IC	219.18
917.10	IC	225.42
917.40	IC	231.48
917.70	IC	237.39
918.00	IC	243.16
918.30	IC	248.79
918.60	IC	254.30

<Shift> <Prt Sc> print <Return> repeat <Space Bar> back to menu

---

Q = 232 cfs

HW = 917.43

RANDOLPH STREET DRAIN

EXISTING & PROPOSED

CONDITION

COMPARISON TABLES

RANDOLPH STREET DRAIN - FLOOD STUDY: WATER SURFACE ELEVATION COMPARISON TABLE.

EXIST. X-SEC. #	"EXISTING CONDITION" 1987 - STUDY CWSEL 10-Yr	CWSEL 50-Yr	CWSEL 100-Yr	CWSEL 500-Yr	PROPOSED X-SEC. #	GROUND ELEVATION	"PROPOSED CONDITION" 1991 - STUDY CWSEL 10-Yr	CWSEL 50-Yr	CWSEL 100-Yr	CWSEL 500-Yr
					1 00	877.80	881.60	882.00	882.50	883.00
					1.25	881.53	884.07	884.79	885.08	885.48
1.00	886.34	888.05	888 80	891 09	1.50	882.63	886.83	888.33	889.29	891.33
2.00	886.36	888.06	888 80	891.09	2.00	883.06	886.84	888.33	889.29	891.33
					2.10	883.06	886.91	888.38	889.32	891.34
2.25	887.25	888.20	888.92	891.12	2.25	884 60	887.21	888.58	889.45	891.38
					2.45	885.60	888.44	888.94	889.58	891.39
2.50	889.16	889.88	890.15	891.22	2.50	886.30	889.08	889.85	890 08	891.56
					2.60	889.10	890.26	890.72	890.94	891.74
					2.70	890.21	892.14	892.94	893.28	893.77
					2.80	890.70	894.49	896.07	897.90	899.52
					2.90	891.00	894.80	896.56	898.31	899.52
					2.95	891.00	894.85	896.61	898.35	899.56
3.00	895.68	896.10	896.25	896.44	3.00	893.20	895.83	896.63	898.36	899.57
3 50	901.75	902.11	902.23	902.41	3.50	899.20	901.94	902.15	902.24	902.44
3.75	903.31	903.88	904.08	904 31	3.75	899.80	903.13	903.76	903.98	904.20
4.00	903.99	904.66	904.89	905.15	4.00	900.50	903.86	904.48	904.71	904.99
					4.25	900.80	903.90	904.50	904.73	905.01
					4.50	900.90	905.35	905.85	906.01	906 17
					4.75	901.30	905.38	905.87	906 03	906 20
5 00	904.82	905.40	905.63	905.91	5.00	902.60	905.48	906.00	906.19	906.40
5 50	904.88	905.47	905.70	905.99	5.50	902.60	905.50	906.04	906.23	906 45
6.00	906.01	906.17	906.22	906.35	6.00	905.10	905.99	906.14	906.23	906 46
6 90	907.29	907.73	907.88	908.24	6.90	905.30	907.40	907.73	907.84	908.18
6.94	907.97	908.49	908.65	909.07	6.94	905.38	907.96	908.59	908.77	909.19
6.95	908.16	908.67	908 83	909.23	6.95	905.53	908.22	908.79	908.96	909.38
7.00	909.07	909.56	909.72	910.12	7.00	906.43	909.23	909.73	909.89	910.30
8.00	913.48	914.41	915.11	917.43	8.00	909.10	913.48	914.41	915.11	917.43
9.00	913 56	914.48	915.15	917.44	9.00	910.20	913.59	914.50	915.17	917.45
10.00	915.54	915.71	915 89	917.43	10.00	914.50	915.54	915.73	915.89	917.45
11.00	917.14	917.43	917.64	917.76	11.00	915.10	917.49	917.81	918.10	918.13
11.90	918.36	918.78	919.14	919.81	11.90	916.10	918.63	919.07	919.43	920.06
12.00	920.75	920.86	920.97	921.12	12.00	920.20	920.76	920.88	920.98	921.16

RANDOLPH STREET DRAIN - FLOOD STUDY· 100 YEAR FLOOD PROFILE COMPARISON TABLE.

	McNEELY & LINCOLN ASSOCIATES					FEMA			
X-SEC #	EXIST FLOW	EXIST CWSEL	PROP FLOW	PROP CWSEL	GROUND ELEVATION	X-SEC #	FLOW	CWSEL	GROUND ELEVATIO
1.00			433.0	882.50	877.80				
1.25			433.0	885.08	881.53	M	400	884.00	881.53
1 50			433 0	889.29	882.63	N	400	888.00	882.63
2.00	494.0	888.80	433 0	889.29	883.06				
2.10			433.0	889.32	883.06				
2.25	494.0	888.92	433.0	889.45	884.60				
2.45			433.0	889.58	885.50				
2.50	494.0	890.15	433.0	890.08	886.30				
2.60			433.0	890.94	889.50				
2.70			433 0	893.28	890.21				
2.80			433 0	897.90	890.70				
2.90			433.0	898.31	891.00				
2.95			433 0	898.35	891.00				
						O	400	895.31	892.00
3.00	494.0	896.25	433 0	898.36	893.20				
3.50	494.0	902.23	433 0	902.24	899.20				
3.75	494.0	904.08	433.0	903.98	899.80				
4.00	494.0	904.89	433.0	904.71	900 50				
4.25			433.0	904.73	900 80				
4.50			433.0	906.01	900.90				
4.75			433.0	906 03	901.30				
						P	400	904.20	901.80
5 00	323.0	905.63	323.0	906 19	902.60				
						Q	400	905 81	902.5
5.50	323.0	905.70	323.0	906.23	902.60				
						R	400	906 50	904.00
6.00	180.0	906.22	180 0	906 23	905.10				
6.90	180.0	907.88	180 0	907.84	905.30				
6.94	180.0	908 65	180.0	908.77	905 38				
6.95	180.0	908.83	180.0	908.96	905 53				
						S	400	910.60	905.60
7.00	180.0	909.72	180.0	909.89	906.43				
8.00	180.0	915.11	180 0	915.11	909.10	T	400	914.75	909.10
9.00	139.0	915.15	139 0	915.17	910.20				
10.00	139.0	915.89	139.0	915.89	914.50				
11.00	139.0	917.64	139.0	918.10	915.10				
11.90	139.0	919.14	139.0	919.43	916.10				
12.00	139.0	920.97	139.0	920.98	920.20	U	400	922.20	920.20

RANDOLPH STREET DRAIN - FLOOD STUDY: FLOW IN cfs. COMPARISON TABLE.

EXIST. X-SEC. #	"EXISTING CONDITION" 1987 - STUDY FLOW 10-Yr	FLOW 50-Yr	FLOW 100-Yr	FLOW 500-Yr	PROPOSED X-SEC. #	"PROPOSED CONDITION" 1991 - STUDY FLOW 10-Yr	FLOW 50-Yr	FLOW 100-Yr	FLOW 500-Yr
					1.00	215.0	363.0	433.0	541.0
					1.25	215.0	363.0	433.0	541.0
1.00	236.0	414.0	494.0	609.0	1.50	215.0	363.0	433.0	541.0
2.00	236.0	414.0	494.0	609.0	2.00	215.0	363.0	433.0	541.0
					2.10	215.0	363.0	433.0	541.0
2.25	236.0	414.0	494.0	609.0	2.25	215.0	363.0	433.0	541.0
					2.40	215.0	363.0	433.0	541.0
2.50	236.0	414.0	494.0	609.0	2.50	215.0	363.0	433.0	541.0
					2.60	215.0	363.0	433.0	541.0
					2.70	215.0	363.0	433.0	541.0
					2.80	215.0	363.0	433.0	541.0
					2.90	215.0	363.0	433.0	541.0
					2.95	215.0	363.0	433.0	541.0
3.00	236.0	414.0	494.0	609.0	3.00	215.0	363.0	433.0	541.0
3.50	236.0	414.0	494.0	609.0	3.50	215.0	363.0	433.0	541.0
3.75	236.0	414.0	494.0	609.0	3.75	215.0	363.0	433.0	541.0
4.00	236.0	414.0	494.0	609.0	4.00	215.0	363.0	433.0	541.0
					4.25	207.0	356.0	433.0	532.0
					4.50	207.0	356.0	433.0	532.0
					4.75	207.0	356.0	433.0	532.0
5.00	159.0	265.0	323.0	407.0	5.00	159.0	265.0	323.0	407.0
5.50	159.0	265.0	323.0	407.0	5.50	159.0	265.0	323.0	407.0
6.00	110.0	161.0	180.0	232.0	6.00	110.0	161.0	180.0	232.0
6.90	110.0	161.0	180.0	232.0	6.90	110.0	161.0	180.0	232.0
6.94	110.0	161.0	180.0	232.0	6.94	110.0	161.0	180.0	232.0
6.95	110.0	161.0	180.0	232.0	6.95	110.0	161.0	180.0	232.0
7.00	110.0	161.0	180.0	232.0	7.00	110.0	161.0	180.0	232.0
8.00	110.0	161.0	180.0	232.0	8.00	110.0	161.0	180.0	232.0
9.00	73.0	106.0	139.0	207.0	9.00	73.0	106.0	139.0	207.0
10.00	73.0	106.0	139.0	207.0	10.00	73.0	106.0	139.0	207.0
11.00	73.0	106.0	139.0	207.0	11.00	73.0	106.0	139.0	207.0
11.90	73.0	106.0	139.0	207.0	11.90	73.0	106.0	139.0	207.0
12.00	73.0	106.0	139.0	207.0	12.00	73.0	106.0	139.0	207.0

McNeely & Lincoln Associates, Inc.
Civil Engineering • Land Surveying • Municipal Consulting
459 East Cady • Northville, Michigan 48167
Phone (313) 349-4920 • Fax 349-5786

RECEIVED
JAN 16 1992
NATURAL RESOURCES
LAND & WATER MGMT.

January 14, 1992

Michigan Department of Natural Resources
Land and Water Management Division
Stevens T. Mason Building
530 West Alligan
Lansing, Michigan 48933

ATTN: Bruce E. Menerey, P.E.
Technical Programs

RE: Randolph Street Drain
City of Northville; Order No. 6800-50

Dear Bruce:

Attached please find technical documentation package to amend a Letter of Map Revision request submitted on behalf of the City of Northville. As you will recall, the original request which originated in 1987 was directed at the elimination of the Randolph Drain Diversion. Following approval by your office, that request was forwarded to Greenhorne & O'Mara (G&O), FEMA's review consultant. After during the first few review cycles, G&O required certification of conditions which no longer existed, due to development along the Randolph Street Drain. It became apparent that the conditions modeled in the Letter of Map Revision request obsolete. Hence, work in support of the original request was terminated, and "as-built" data was subsequently collected and incorporated into the hydraulic and hydrologic computer models. The attached materials include these revisions.

The Existing Conditions packet contains essentially the same input and output files used for the original Letter of Map Revision request, with two exceptions. First, the cross sections in the vicinity of the original Randolph Drain Diversion have been modified to reflect recent construction in the north end of the Northville Estates subdivision. This development was permitted in advance of the anticipated Letter of Map Revision by the Northville Board of Zoning Appeals, who were notified of MDNR's approval of the Letter of Map Revision request. The second change is the use of 24 hour precipitation values of 3.5 inches, 4.45 inches, and 4.85 inches for the 10-year, 50-year, and 100-year rainfall events, based on isohyetal maps provided in the TR-55.

RE: Randolph Street Drain
City of Northville; Order No. 6800-50

The Proposed Conditions packet reflects "as-built" conditions of the two newer subdivisions, Abbey Knoll Estates and Pheasant Hills. Both of these developments were required to provide stormwater detention to reduce flood risk to downstream areas. Both utilized "in-line" detention, as encouraged by the Michigan Department of Natural Resources, largely to utilize the wetland areas along this section of the Randolph Street Drain for water quality enhancement, while minimizing their disruption. The hydrologic model for the Proposed Conditions packet also includes a revision to the hydrologic model, which now includes a detention pond and a wetland area along a tributary extending through the northeast corner of the Pheasant Hills subdivision. This tributary is shown on an enclosed drawing. You should note that revision does not have a significant effect on the projected peak flows in the Randolph Street Drain.

In the case of the Pheasant Hills development, the stream crossing at McDonald Drive was designed to provide stormwater detention for storm events of a magnitude exceeding the 10-year frequency. The Coldspring Drive crossing was intended to minimize the change in upstream flood elevations. Analysis of the regulated floodway indicated that the backwater effect of the Coldspring Drive crossing would dissipate before reaching properties beyond the limits of the new subdivisions. Easements and house grades were set based on the flood elevations anticipated to result from these two crossings of the regulated floodway.

It was subsequently learned that, in addition to flood plain easements, a Letter of Map Revision was also required for any change to a regulated floodway which would result in an increase in base flood elevation. While we understand that MDNR does not assume jurisdiction for water courses with drainage areas less than 2 square miles in area, we request that you review the hydraulics and hydrology in this packet, as a part of the Letter of Map Revision procedure.

Bruce E. Menerey, P.E.
Michigan Department of Natural Resources
January 14, 1992 Page 3

RE: Randolph Street Drain
City of Northville; Order No. 6800-50

To review the hydrology for this submittal, we request that you review our original submittal. In the event that those materials are no longer available, or your require additional materials to complete your review, please contact me.

Thank you for your assistance in this matter.

Very truly yours,


McNEELY & LINCOLN ASSOCIATES, INC.
Consulting Engineers to the City of Northville


Robert M. Warner

Robert M. Warner, P.E.

encls.


cc: City of Northville
Gary L. Word, City Manager
Ted Mapes, Superintendent, D.P.W., w/o encls.
Federal Emergency Management Agency
Norbert Schwartz, w/o encls.
file


HEADWALL SEE DETAIL SHT #
CHANNEL DROP SEE DETAIL SHT # 17
APPROACH BASIN
60" CULVERT
NORTH 1" = 50'
N POOR CONDITION IN PLACES
22-33-100-010
30' PERM ESMT.
PROP. TOP OF BANK
MED BRUSH & MED. WOODS
NOVI CORP LINE
MED BRUSH & MED WOODS
HEAVY BRUSH
PROP. TOP OF BANK
CORP LINE
THORN APPLES
HEAVY WEEDS
7
(22-33-301-007)
8
(22-33-301-008)
9
(22-33-301-009)
30' PERM ESMT.
12' DRAINAGE EASEMENT
MED
MED
NOTE: TAKEN FROM RANDOLPH STREET DRAIN IMPROVEMENTS JUNE 16, 1975
ELMSMERE DR.
"NORTHVILLE ESTATES
L-85, P-4 CITY OF NORTHVILLE
P.R. 7'
P.O.E. 15" RCP 167'
P.O.B. 15" RCP
P.R. 7'
P.P. & TRANSFORMER 6'



OLPH STREET DRAIN
MPROVEMENTS

INTER - COUNTY DR
RANDOLPH STREET DF



SCALE VERT. 1" = 5'
HORIZ. 1" = 50'

? - COUNTY DRAINAGE BOARD
PH STREET DRAINAGE DISTRICT

JOB NO. 4429
DATE ISSUED
SHEET NO. 13 OF 21

CONSTRUCTION PLANS

INTER-COUNTY DRAINAGE BOARD, RANDOLPH STREET DRAINAGE DIST.

SHT. 4 OF 21

22-33-100-010

BECK ROAD

BRUSHING LIMITS

50' (TYP.)

BRUSHING LIMITS

CONSTRUCTION LIMITS

APPROACH BASIN

60" CULVERT

33'

WEST 1/4 CORNER, SEC. 33

NOVI

NORTHVILLE

30'

30'

60'

1 (22-33-301-001)

2 (22-33-301-002)

3 (22-33-301-003)

4 (22-33-301-004)

5 (22-33-301-005)

6 (22-33-301-006)

7 (22-33-301-007)

8 (22-33-301-008)

9 (22-33-301-009)

10 (22-33-301-010)

(22-3...

ELMERE DRIVE 60'

NORTHVILLE ESTATES SUBDIVISION

1" = 100'

SUMMERS... LANE

SHEET #14

SHEET #13

22-33-100-011

22-33-100-012

22-33-200-001

22

60" CULVERT

30'

30'

20'

20'

0

NOVI

NORTHVILLE

COEP.

COEP

LINE

LINE

CONSTRUCTION LIMITS

BRUSHING LIMITS

BRUSHING LIMITS

200 ft

#14

SHEET

80'

650 ft

155'

25'

120'

11
(22-33-301-011)

12
(22-33-301-012)

10
(22-33-301-010)

SUMMERSIDE LANE 60'

13
(22-33-301-013)

14
(22-33-301-014)

22-33-377-002

BRUSHING LIMITS

22-33-401-002

110

22-33-402-001

410

EXISTING DRAIN

SHEET #12

SHEET #11

EET

AS BUILT

RMED.
JTILITY

k, the
owners
e shall
noted in
es that
on.

22-33-100-010

MED WOODS

MATCH LINE SHT #13

30' PERM ESMT

50+00

12' PRIVATE EASEMENT FOR PUBLIC UTILITIES

15' PERM. ESMT.

6' PRIVATE EASEMENT FOR PUBLIC UTILITIES

179°-35'-14"

FNC. IN POOR CONDITION DOWN IN PLACES

20' PERM ESMT

PERM ESMT

20'

10'

45+00

PROP.

30'

NORTHVILLE CORP. LINE

PROP TOP OF B.

HEADWALL SEE DETAIL SHT #20

4' bottom

NOTE: PLACE TOPSOIL, FERTILIZER, SEED, & MULCH ON CHANNEL SIDES & BOTTOM

MED BRUS

MED WOOD

4'

1 / 3

1 / 3

TYPICAL CHANNEL SECTION

(22-33-301-011)
11

12
(22-33-301-012)

"NORTHVILLE ESTATES SUBDIVISION"
L-85, P-4

1"=50'

SAVE

PP & TRANSFORMER 7'
18" DEAD TREE 48'
24" BEECH 43'
PP 7'
8" THORN APPLE 54'
10" BEECH 67'
14" BEECH 51'
9' DEAD TREE 25'
8" BEECH 41'
PP 5'
14" BEECH 18'
GUY WIRE 6'
GUY WIRE 6'
14" BEECH 14'
8" DEAD TREE 36'
10" DEAD TREE 63'
10" DEAD TREE 30'
28" HICKORY 19'
PP 65'
GUY WIRE 46'
GUY WIRE 41'
PP 4'
GUY WIRE 4'
10" BEECH 16'
8" DEAD TREE 25'
10" DEAD TREE 8'
10" DEAD TREE 23'
28" BEECH 9'
12" BEECH 3'
14" HICKORY 52'
16" HICKORY 49'
18" HICKORY 25'
8" BEECH 7'
8" BEECH 50'
8" BEECH 27'
8" BEECH 47'
10" BEECH 3'
14" DEAD TREE 62'
18" HICKORY 28'
8" HICKORY 16'
8" BEECH 29'
10" BEECH 21'
8" BEECH 25'
16" HICKORY 60'
FND 1" PIPE & FNC COR 8.00'
10" BEECH 26'
9" DEAD TREE 9'
FNC 8'
8" BEECH 25'
10" BEECH 3'
16" DEAD TREE 44'
16" HICKORY 12'

325'-60"@0.60%
C76 CL III

110'-60"@0.60%
C76 CL III

80'-60"@0.60%
C76 CL III

395 L.F. 4' BOTTOM CHANNEL @ 0.40%
(see typical section this sht)

MANHOLE

MANHOLE

SHT. 12 OF 21

to have work area staked, and he shall protect, or have relocated, as noted in the specifications, all utilities that might interfere with construction.

PP & T.
18" DEA.
24" BEC.
PR 7'
8" THOR.
10" BEEC.
14" BEEC.
9' DEAD T
8" BEECH
P.P. 5'
14" BEECH
GUY WIRE
GUY WIRE
14" BEECH
8" DEAD T
10" DEAD .
10" DEAD .
28" HICKOR
PP 65'
GUY WIRE
GUY WIRE .
PR. 4'
GUY WIRE
10" BEEC.
8" DEAD T
10" DEAD .
10" DEAD T
28" BEECH
12" BEECH
14" HICKOR.
16" HICKOR.
18" HICKOR
8" BEECH
8" BEECH
8" BEECH
8" BEECH

325'-60"@0.60%
C76 CL III

110'-60"@0.60%
C76 CL III

395 L.

80'-60"@0.60%
C76 CL III

925
920
915
910
905
900

Match line 52+12

MANHOLE

PIT

8'±

MANHOLE

8'±

Exist ground 50' R

Exist ground 50'
L survey line

Pro

9058.9

16.74

6.08

5.60

SHT. 12 OF 20

"8" BEEC
12" DE
3-10" E
TREE
8" DEAL
10" DEA
1-12" E
TREE
10" BEE
8" BEE
8" STUI
10" STUI
FNC. 8'
14" STUI
TWIN 8
10" DEA
8" BEE
10" OAI
FNC. CO
FNC 7
3-10" TA
FNC. 6
16" DEA.
8" DEAL
10" APPL
18" BEE
TWIN 10
TWIN 8
8" BEE
FNC. 6
8" DEA.
8" DEA
10" DEA
8" DEAL
24" DE
10" DEA
15" DEA
FNC. 5
14" DEA
8" DEAL
16" DEA
FNC. 7'

67+79 94
E-ROD
VEY LINE)

HEADWALL SEE DETAIL SHT # 20

CHANNEL DROP SEE DETAIL SHT # 17

30' FLOOD PLAIN ESMT.

FNC. IN POOR CONDITION DOWN IN PLACES

22-33-100-010

30' PERM ESMT.

PROP. TOP OF BANK

MED BRUSH & MED. WOODS

MATCH LINE SHT # 12

HEAVY WEEDS

MED. BRUSH & MED WOODS

NOVI CORP. LINE

SWAMP

HEAVY BRUSH

PROP. TOP OF BANK

NORTHVILLE CORP. LINE

THORN APPLES

HEAVY WEEDS

HEAVY WEEDS

MED BRUSH & MED WOODS

230°-18'-19"

5
(22-33-301-005)
PRIVATE EASEMENT
PUBLIC UTILITIES

6
(22-33-301-006)

7
(22-33-301-007)

8
(22-33-301-008)

9
(22-33-301-009)

12' DRAINAGE EASEMENT

PP @ B M 6'

B.M. ELEV 919.71
RR SPIKE SW SIDE
P POLE.

P.P @ TRANSFORMER 6'

PP 7'

POE 15" RCP (62')
POB 15" RCP 6'

PP 7'

1" = 50'

"NORTHVILLE ESTATES SUBDIVISI
L-85, P-4

SHT. 13 OF 21

185 L.F 4' BOTTOM CHAI
(See typical section sh.

"NORTHVILLE ESTATES SUBDIVISION"
L-85, P-4

PP 7'

POE 15" RCP
POB 15" RCP

PP 7'

NOTE
TOPO IS REFERENCED OFF SURVEY LINE

185 L.F. 4' BOTTOM CHANNEL @ 0.60%
(see typical section sht

63'-60" @ 0.40%
C76 CI III

Match line 52+12

Exist. ground 50' R survey line

Existing ground along survey line

Exist. ground 50' L survey line

Proposed channel bottom

925
920
915
910
905

SHT. 13 OF 21

00BREAK00

1) COUNTY: Wayne

2) STUDY NAME: City of Plymouth and Plymouth Twp

3) WATERCOURSE: Middle River Rouge

4) DOCUMENT TYPE: 100 year

00BREAK00

```
EEEEEEE   EEEEEEE          K   K     OOOO    BBBBB    Y     Y   L         IIIII    N     N    SSSS    K   K
E         E                K  K     O    O   B    B    Y   Y    L           I      NN    N   S        K  K
E         E        ------  K K      O    O   BBBBB      YY      L           I      N N   N    SSSS    K K
EEEE      EEEE             KKK      O    O   B    B     Y       L           I      N  N  N        S   KKK
E         E                K  K     O    O   B    B     Y       L           I      N   NN   S    S   K  K
EEEEEEE   EEEEEEE          K   K     OOOO    BBBBB     Y       LLLLLL    IIIII    N    N    SSSS    K   K


                  USACOE DETROIT H800 VOS 7.1.0      PRINTER:  6

                  EE-KOBYLINSK                  19 OCT 92 13:05:40

                  TERMINAL: 106
```

City of Plymouth and Plymouth Twp.
Middle River Rouge

Revised HEC-2

```
**********************************************************
*  WATER SURFACE PROFILES                                *
*  VERSION OF SEPTEMBER 1988                             *
*  ERROR: 01, 02, 03, 04                                 *
*  UPDATED:   JUNE 1990                                  *
*  RUN DATE     19OCT92     TIME    13:00:29             *
**********************************************************
```

```
**********************************
*  U S. ARMY CORPS OF ENGINEERS  *
*  THE HYDROLOGIC ENGINEERING CENTER *
*  609 SECOND STREET, SUITE D    *
*  DAVIS, CALIFORNIA 95616-4687  *
*        (916) 756-1104          *
**********************************
```

```
X      X  XXXXXXX   XXXXX              XXXXX
X      X  X         X     X            X     X
X      X  X         X                        X
XXXXXXX   XXXX      X          XXXXX    XXXXX
X      X  X         X                   X
X      X  X         X     X             X
X      X  XXXXXXX   XXXXX               XXXXXXX
```

END OF BANNER

THIS RUN EXECUTED 19OCT92 13:00:29

```
**************************************************
  HEC2 RELEASE DATED SEP 88 UPDATED JUN  1990

  ERROR CORR -  01,02,03,04
  MODIFICATION -
**************************************************

T1      CITY OF PLYMOUTH AND PLYMOUTH TWP.  LMMP
T2      MIDDLE RIVER ROUGE
T3      100-YEAR FLOOD

J1  ICHECK     INQ        NINV       IDIR       STRT       METRIC     HVINS      G          WSEL       FQ
       0         2          0          0          0          0          0          0        667.5        0
J2  NPROF      IPLOT      PRFVS      XSECV      XSECH      FN         ALLDC      IBW        CHNIM      ITRACE
      -1         0         -1

J3  VARIABLE CODES FOR SUMMARY PRINTOUT

    150

NC      .035       .035       .035         .3          .5
NC      .035       .035       .035         .3          .5
QT         1       4100
X1      1000         13         25        155           0          0          0
GR     684.0          0      682.0          2      680.0         15      670.0         25      660.0         47
GR     658.0         97      656.5        102      655.0        110      656.0        118      658.0        126
GR     660.0        130      665.0        155      662.0        360

X1      1700         13         25        155         700        700        700
GR     684.0          0      682.0          2      680 0         15      670.0         25      660.0         47
GR     658.0         97      656.5        102      655.6        110      656.0        118      658.0        126
GR     660.0        130      665.0        155      662.0        360

NC                                          .5         1.0
X1      2100         22        250        420        400        400        400
GR     682.7          0      682.8         50      682.9        150      682.8        250      679.1        252
GR     676.4        252      658.9        299      656.7        302      656.1        309      656.9        316
GR     658.0        324      659.0        329      660.6        331      660.4        338      660.8        342
GR     661.9        381      675.7        418      679.2        418      683.1        420      683.3        500
GR     683.3        600      683.4        670

NC      .035       .035       .035
            D/S FACE OF N.B.  I-275 BRIDGE
X1      2101         22        250        420          1          1          1
BT        10        250      682.8          0        252      682.8      676.4        252      682.8      679.1
BT       338      682.9      679.2        338      682.9      660.4        342      682.9      660.8        342
BT     682.9      679.2        418      683.1      679.2        418      683.1      675.7        420      683.1
BT         0
GR     682.7          0      682.8         50      682.9        150      682.8        250      679.1        252
GR     676.4        252      658.9        299      656.7        302      656.1        309      656.9        316
GR     658.0        324      659.0        329      660.6        331      660.4        338      660.8        342
```

```
GR    661.9      381     675.7      418     679.2      418     683.1      420     683.3      500
GR    683.3      600     683.4      670

NC                                   .3        .5
          U/S FACE OF N.B. I-275 BRIDGE
X1   2157          0          0          0         56         56         56
X2      0          0          0          0          0          0          1          0          0          0

NC    .035       .035       .035
X1   2158         22        250        420          1          1          1
GR    682.7          0      682.8         50      682.9        150      682.8        250      679.1        252
GR    676.4        252      658.9        299      656.7        302      656.1        309      656.9        316
GR    658.0        324      659.0        329      660.6        331      660.4        338      660.8        342
GR    661.9        381      675.7        418      679.2        418      683.1        420      683.3        500
GR    683.3        600      683.4        670

X1   2188         22        250        420         30         30         30
GR    682.7          0      682.8         50      682.9        150      682.8        250      679.1        252
GR    676.4        252      658.9        299      656.7        302      656.1        309      656.9        316
GR    658.0        324      659.0        329      660.6        331      660.4        338      660.8        342
GR    661.9        381      675.7        418      679.2        418      683.1        420      683.3        500
GR    683.3        600      683.4        670

NC    .035       .035       .035
          D/S FACE OF S.B. I-275 BRIDGE
X1   2189         22        250        420          1          1          1
BT     10        250      682.8          0        252      682.8      676.4        252      682.8      679.1
BT    338      682.9      679.2        338      682.9      660.4        342      682.9      660.8        342
BT  682.9      679.2        418      683.1      679.2        418      683.1      675.7        420      683.1
BT      0
GR    682.7          0      682.8         50      682.9        150      682.8        250      679.1        252
GR    676.4        252      658.9        299      656.7        302      656.1        309      656.9        316
GR    658.0        324      659.0        329      660.6        331      660.4        338      660.8        342
GR    661.9        381      675.7        418      679.2        418      683.1        420      683.3        500
GR    683.3        600      683.4        670

          U/S FACE OF S.B. I-275 BRIDGE
X1   2245          0          0          0         56         56         56
X2      0          0          0          0          0          0          1          0          0          0

NC                              .035
X1   2246         22        250        420          1          1          1
GR    682.7          0      682.8         50      682.9        150      682.8        250      679.1        252
GR    676.4        252      658.9        299      656.7        302      656.1        309      656.9        316
GR    658.0        324      659.0        329      660.6        331      660.4        338      660.8        342
GR    661.9        381      675.7        418      679.2        418      683.1        420      683.3        500
GR    683.3        600      683.4        670

NC                              .035       .5        1.0
X1   3000         20        415        485        754        754        754
GR    690.0          0      688.0         20      686.0         40      684.0         50      682.0         60
GR    680.0         80      670.0        150      664.0        180      662.0        195      661.0        415
GR    657.0        435      657.0        465      661.0        485      662.0        530      664.0        600
GR    666.0        630      668.0        700      670.0        720      680.0        755      670.0        775
```

```
NC                                        .3        .5
X1      4000          16         340      410      1000      1000      1000
GR     690.0           0       680.0       30     670.0        70     668.0       100     666.0       120
GR     664.0         160       662.0      340     658.0       360     658.0       390     662.0       410
GR     664.0         430       664.0      650     666.0       670     670.0       680     680.0       695
GR     690.0         800

NC                                      .035        .5       1.0
X1      4800           0          0        0       800       800       800
X3                                               340                 596

X1      5075           0          0        0       275       275       275
X3                                               340                 458

NC                                                .5       1.0
X1      5146          31        250    338.8        71        71        71
GR     704.0           0       701.8       25     699.7        50     697.2        75     694.8       100
GR     692.1         125       689.3      150     686.1       175     683.4       200     681.1       225
GR     679.3         250       673.0      250     663.9       268     663.0     269.8     660.6       275
GR     660.2         285       660.2      294     659.4       301     659.6       309     662.2       310
GR     663.1       314.7       663.5      316     664.0     317.4     666.2       325     667.0     338.8
GR     674.5       338.8       673.0      400     672.2       450     671.4       500     670.8       550
GR     670.3         600

NC      .042        .042       .035        .3        .5
          D/S FACE OF HAGGERTY RD.  BRIDGE
X1      5147          31        250    338.8         1         1         1
X3                                               258                 338
BT        12         250     679.9      673.0       250     679.9     677.8       268     678.9     676.8
BT       268       678.9     663.9      269.8     678.8     663.0     269.8     678.8     675.3       316
BT     676.5       672.9       316      676.5     663.5     317.4     676.4     664.0     317.4     676.4
BT     674.2       338.8     675.3      673.3     338.8     675.3     667.0
GR     704.0           0     701.8         25     699.7        50     697.2        75     694.8       100
GR     692.1         125     689.3        150     686.1       175     683.4       200     681.1       225
GR     679.9         250     673.0        250     663.9       268     663.0     269.8     660.6       275
GR     660.2         285     660.2        294     659.4       301     659.6       309     662.2       310
GR     663.1       314.7     663.5        316     664.0     317.4     666.2       325     667.0     338.8
GR     675.3       388.8     673.0        400     672.2       450     671.4       500     670.8       550
GR     670.3         600

          U/S FACE OG HAGGERTY RD.  BRIDGE
X1      5181           0          0        0        34        34        34
X2         0           0          0        0         0         0         1         0         0         0
X3                                               258                 338

NC      .035        .035       .035        .5       1.0
X1      5182          31        250    338.8         1         1         1
GR     704.0           0     701.8         25     699.7        50     697.2        75     694.8       100
GR     692.1         125     689.3        150     686.1       175     683.4       200     681.1       225
GR     679.3         250     673.0        250     663.9       268     663.0     269.8     660.6       275
GR     660.2         285     660.2        294     659.4       301     659.6       309     662.2       310
GR     663.1       314.7     663.5        316     664.0     317.4     666.2       325     667.0     338.8
GR     674.5       338.8     673.0        400     672.2       450     671.4       500     670.8       550
```

```
GR    670.3      600

X1     5232       16      290      380       50       50       50
X3                                 245                428
GR    690.0        0    680.0       20    670.0       50    668.0       55    664.0       85
GR    666.0       95    666.0      290    663.6      310    660.0      330    658.2      350
GR    664.0      370    666.0      380    668.0      620    670.0      650    672.0      770
GR    680.0      850

X1     5382       16      290      380      150      150      150
X3                                  95                578
GR    690.0        0    680.0       20    670.0       50    668.0       55    664.0       85
GR    666.0       95    666.0      290    663.6      310    660.0      330    658.2      350
GR    664.0      370    666.0      380    668.0      620    670.0      650    672.0      770
GR    680.0      850

NC                                  .3       .5
X1     6000       16      290      380      618      618      618
GR    690.0        0    680.0       20    670.0       50    668.0       55    664.0       85
GR    666.0       95    666.0      290    663.6      310    660.0      330    658.2      350
GR    664.0      370    666.0      380    668.0      620    670.0      650    672.0      770
GR    680.0      850

X1     6183       34      680      776      183      183      183
X3                                 383               1028
GR    700.0        0    698.0       40    696.0       55    690.0       75    680.0      100
GR    670.0      120    668.0      135    666.0      140    666.0      190    664.0      270
GR    667.6      520    670.8      680    669.8      685    663.6      703    663.6      704
GR    663.5      705    663.3      708    663.2      710    663.1      715    663.0      720
GR    662.7      728    662.6      731    660.6      734    659.7      739    659.2      742
GR    659.0      745    658.2      749    659.6      753    662.2      760    665.8      767
GR    670.4      776    668.0      926    674.0     1126    680.0     1186

X1     6196       27      680      776       13       13       13
GR    700.0        0    698.0       40    696.0       55    690.0       75    680.0      100
GR    670.0      120    668.0      135    666.0      140    666.0      190    664.0      270
GR    667.6      520    672.0      533    672.0      680    672.1      716    672.2      717
GR    672.3      721    672.4      728    672.5      733    672.6      741    672.5      747
GR    672.2      750    672.0      752    672.0      776    669.6     1040    672.0     1150
GR    678.0     1220    680.0     1240

NC                                  .3       .5
X1     6409       33      680      776      213      213      213
GR    700.0        0    698.0       40    696.0       55    690.0       75    680.0      100
GR    670.0      120    668.0      135    666.0      140    666.0      190    664.0      270
GR    667.6      520    670.8      680    669.8      685    663.6      703    663.6      704
GR    663.5      705    663.3      708    663.2      710    663.1      715    663.0      720
GR    662.7      728    662.6      731    660.6      734    659.7      739    659.2      742
GR    659.0      745    658.2      749    659.6      753    662.2      760    665.8      767
GR    670.4      776    680.0      800    690.0      850
```

```
X1     7900        13       350       430      1491      1491      1491
GR     672.0        0     670.0        30     670.0       320     668.0       340     666.0       350
GR     665.0       350    662.0       355     662.0       405     666.0       430     670.0       450
GR     680.0       470    690.0       500     700.0       540

NC                                      .5       1.0
          D/S FACE OF E. HINES DRIVE BRIDGE
X1     8201        28       453       505      301       301       301
X4        1     670.0       310
GR     680.0        0     678.0        20     676.0        40     674.0       170     672.0       190
GR     670.0       210    670.0       430     669.6       435     664.9       453     664.0       464
GR     663.0       457    663.0       460     663.2       465     663.4       468     664.0       473
GR     664.9       478    664.9       485     665.0       490     665.0       495     665.1       500
GR     665.2       504    665.2       505     665.8       517     670.0       526     670.0       526
GR     680.0       586    690.0       610     700.0       630

SB        0      1.75      2.5         0       52         0       340
NC     .035      .035      .025
          U/S FACE OF E. HINES DRIVE BRIDGE
X1     8227         0         0         0       26        26        26
X2        0         0         1     671.8      673.0
BT       28         0     680.0         0       20     678.0         0        40     676.0         0
BT      170     674.0         0       190     672.0         0       210     670.0         0       310
BT     670.0         0       430     674.1     670.0       435     674.1     669.6       453     674.3
BT     664.9       454     674.3     666.4       457     674.4     669.7       460     674.5     670.6
BT      465     674.5     671.2       468     674.6     671.6       473     674.7     671.9       478
BT     674.7     672.0       485     674.6     671.9       490     674.4     671.7       495     674.2
BT     671.4       500     674.2     670.0       504     674.1     666.4       505     674.1     665.2
BT      517     674.1     665.8       526     674.1     670.0       586     680.0         0       610
BT     690.0         0       630     700.0         0

NC      .05       .05      .040        .3        .5
X1     8257         0         0         0       30        30        30

NC                                    .04
X1     9600        16       470       530     1343      1343      1343
X4        1     671.5       540
GR     720.0         0     710.0        50     700.0        70     690.0       110     680.0       170
GR     676.0       220     674.0       440     672.0       470     670.0       480     666.0       490
GR     666.0       520     670.0       530     672.0       640     674.0       680     676.0       910
GR     680.0       940
```

```
NC                                      .5       1.0
X1    10200        17       400       445      600       600       600
X3                                    100       555
X4        2     674.0       110     674.0       135
GR     720.0         0     710.0        10     700.0        25     690.0        40     680.0        75
GR     676.0        90     676.0       380     672.0       400     670.0       403     669.0       406
GR     669.0       439     670.0       442     672.0       445     674.0       450     676.0       460
GR     676.0       510     680.0       530
```

```
X1    10500                                    300    300    300                1.2
X3                                 175          555

X1    10600                                    100    100    100                .4
X3                                 200          555

X1    10700          15      740    780       100    100    100
X3                                 600          880
X4        2       676.0      600    677.0     650
GR    720.0           0    710.0    180    700.0    200  690.0  240  680.0    280
GR    676.0         290    676.0    690    675.0    740  671.0  745  671.0    775
GR    676.0         780    678.0    870    680.0    880  690.0  890  700.0    920

NC                                  .5     1.0
X1    10800                                    100    100    100                .25
X3                                 625          855

          D/S FACE OF MIDDLE WOODS DRIVE BRIDGE
X1    10901          17      250   292.5     101    101    101
X3                                 155          388
GR    679.5           0    679.9    100    679.5    200  680.0  250  672.1    250
GR    672.1         260    671.5    271    671.7    281  673.0  291  674.1  292.5
GR    680.0       292.5    678.2    322    678.2    339  677.4  356  678.6    366
GR    677.1         450    677.9    550

SB        0        1.73      2.5      0       41      0    232
NC     .042        .042      .03
          U/S FACE OF MIDDLE WOODS DRIVE BRIDGE
X1    10930           0        0      0       29     29     29
X2        0           0        1  677.4    680.0
X3                                 161          381
BT        5         250    680.0  672.1      250  680.0  677.4  271  680.0  677.4
BT    292.5       680.0    677.4  292.5    680.0  674.1

X1    10980          17      250   292.5      50     50     50
X3                                 166          377
GR    679.5           0    679.9    100    679.5    200  680.0  250  672.1    250
GR    672.1         260    671.5    271    671.7    281  673.0  291  674.1  292.5
GR    680.0       292.5    678.2    322    678.2    339  677.4  356  678.6    366
GR    677.1         450    677.9    550

X1    11200          25      218   345      220    220    220
GR    702.8           0    700.7     50    698.5    100  696.8  150  695.3    200
GR    694.5         218    692.5    218    677.7    250  676.6  253  674.9    258
GR    674.0         260    673.8    265    673.2    271  672.9  281  673.0    290
GR    673.5         295    674.5    306    675.3    311  676.4  313  692.2    345
GR    692.9         345    693.0    400    692.9    450  693.1  500  693.1    570
```

```
NC      .035      .035      .025
          D/S FACE OF PLYMOUTH ROAD BRIDGE
X1    11201        25       218       345         1         1         1
BT       14       218      694.5     692.5       250     694.2     677.7       253     694.2     676.6
BT      258     694.1      683.5       260     694.0     685.2       265     694.0     688.2       271
BT    693.9     690.0       281     693.7     691.2       290     693.5     690.8       295     693.4
BT    690.0       306     693.3     684.0       311     693.3     675.3       313     693.3     676.1
BT      345     692.9      692.2
GR    702.8         0     700.7        50     698.5       100     696.8       150     695.3       200
GR    694.5       218     692.5       218     677.7       250     676.6       253     674.9       258
GR    674.0       260     673.8       265     673.2       271     672.9       281     673.0       290
GR    673.5       295     674.5       306     675.3       311     676.1       313     692.2       345
GR    692.9       345     693.0       400     692.9       450     693.1       500     693.1       570

          U/S FACE OF PLYMOUTH ROAD BRIDGE
X1    11255         0         0         0        54        54        54
X2        0         0         0         0         0         0         1         0         0         0

NC                            .035
X1    11256        25       218       345         1         1         1
GR    702.8         0     700.7        50     698.5       100     696.8       150     695.3       200
GR    694.5       218     692.5       218     677.7       250     676.6       253     674.9       258
GR    674.0       260     673.8       265     673.2       271     672.9       281     673.0       290
GR    673.5       295     674.5       306     675.3       311     676.1       313     692.2       345
GR    692.9       345     693.0       400     692.9       450     693.1       500     693.1       570

NC                                      .3        .5
X1    11356         0         0         0       100       100       100                   .2

X1    12150        17       200       300       794       794       794
X3                                    200                 300
GR    712.0         0     710.0        15     710.0        35     700.0        55     690.0        70
GR    684.0       100     682.0       200     677.0       220     675.0       230     675.0       270
GR    677.0       280     682.0       300     681.5       350     680.0       450     684.0       590
GR    690.0       670     700.0       710

NC                                      .5       1.0
X1    12850        30       250       306       700       700       700                  -.7
GR    731.2         0     731.6       100     732.1       200     732.3       250     679.2       250
GR    672.2       251     679.2       253     679.2       256     679.2       259     679.2     262.5
GR    679.2       265     679.2       268     679.2       272     679.2       274     679.2       275
GR    678.8       281     678.8       282     678.8       285     678.8       288     678.7       291
GR    678.7     293.5     678.7       297     678.7       300     678.8       303     678.8       305
GR    678.8       306     732.5       306     732.7       350     733.2       450     733.7       550

X1    13000        30       250       306       150       150       150
GR    731.2         0     731.6       100     732.1       200     732.3       250     679.2       250
GR    679.2       251     679.2       253     679.2       256     679.2       259     679.2     262.5
GR    679.2       265     679.2       268     679.2       272     679.2       274     679.2       275
GR    678.8       281     678.8       282     678.8       285     678.8       288     678.7       291
GR    678.7     293.5     678.7       297     678.7       300     678.8       303     678.8       305
GR    678.8       306     732.5       306     732.7       350     733.2       450     733.7       550
```

```
NC      .038      .038      .025
          D/S FACE OF C&O R.R. BRIDGE
X1    13001        30       250       306         1         1         1
BT       26       250     732.3     679.2       250     732.3     687.0       251     732.3     691.0
BT      253     732.3     695.0       256     732.3     697.3       259     732.4     699.0     262.5
BT    732.4     699.1       265     732.4     699.0       268     732.4     697.6       272     732.5
BT    695.0       274     732.5     691.0       275     732.5     687.0       275     732.5     679.2
BT      281     732.5     678.8       281     732.5     687.0       282     732.5     690.0       285
BT    732.5     695.7       288     732.5     697.6       291     732.5     698.7     293.5     732.5
BT    699.0       297     732.5     698.7       300     732.5     697.2       303     732.5     694.8
BT      305     732.5     691.0       306     732.5     687.0       306     732.5     678.8
GR    731.2         0     731.6       100     732.1       200     732.3       250     679.2       250
GR    679.2       251     679.2       253     679.2       256     679.2       259     679.2     262.5
GR    679.2       265     679.2       268     679.2       272     679.2       274     679.2       275
GR    678.8       281     678.8       282     678.8       285     678.8       288     678.7       291
GR    678.7     293.5     678.7       297     678.7       300     678.8       303     678.8       305
GR    678.8       306     732.5       306     732.7       350     733.2       450     733.7       550

          U/S FACE OF C&O R.R. BRIDGE
X1    13135         0         0         0       134       134       134
X2        0         0         0         0         0         0         1         0         0

NC      .038      .038      .035
X1    13136        30       250       306         1         1         1
GR    731.2         0     731.6       100     732.1       200     732.3       250     679.2       250
GR    679.2       251     679.2       253     679.2       256     679.2       259     679.2     262.5
GR    679.2       265     679.2       268     679.2       272     679.2       274     679.2       275
GR    678.8       281     678.8       282     678.8       285     678.8       288     678.7       291
GR    678.7     293.5     678.7       297     678.7       300     678.8       303     678.8       305
GR    678.8       306     732.5       306     732.7       350     733.2       450     733.7       550

X1    13236         0         0         0       100       100       100                 .7

NC                                      .3        .5
X1    13800        10       245       290       564       564       564
X3                                      90       346
GR    690.0         0     688.0       110     686.0       230     685.0       245     683.5       250
GR    683.5       285     685.0       290     686.0       410     690.0       430     692.0       450

NC                                      .5       1.0
X1    14400        12       175       220       600       600       600
X3                                     125       273
GR    704.0         0     702.0        40     700.0        50     696.0        65     694.0       175
GR    688.3       180     688.3       215     694.0       220     694.0       480     700.0       520
GR    710.0       535     720.0       560

NC                                      .5       1.0
X1    14600        18       250       298       200       200       200
GR    706.7         0     707.0        50     707.3       100     707.5       150     707.7       200
GR    707.7       250     689.9       250     690.0       265     690.0     266.5     687.9     281.5
GR    689.9       283     690.0       298     707.5       298     704.4       350     704.2       400
GR    704.6       450     705.5       500     707.1       550
```

```
          D/S FACE OF E. HINES DRIVE & WILCOX RD.
X1     14601        18       250       298         1         1         1
BT        12       250     707.7     689.9       250     707.7     703.6       265     707.7     703.6
BT       265     707.7     690.0     266.5     703.6     690.0     266.5     707.7     703.6     281.5
BT     707.6     703.6     281.5     707.6     689.9       283     707.6     689.9       283     707.6
BT     703.6       298     707.5     703.6       298     707.5     690.0
GR     706.7         0     707.0        50     707.3       100     707.5       150     707.7       200
GR     707.7       250     689.9       250     690.0       265     690.0     266.5     689.9     281.5
GR     689.9       283     690.0       298     707.5       298     704.4       350     704.2       400
GR     704.6       450     705.5       500     707.1       550

          U/S FACE OF E. HINES DRIVE & WILCOX RD.
X1     14776         0         0         0       175       175       175
X2         0         0         0         0         0         0         1         0         0

X1     14777        18       250       298         1         1         1
GR     706.7         0     707.0        50     707.3       100     707.5       150     707.7       200
GR     707.7       250     689.9       250     690.0       265     690.0     266.5     689.9     281.5
GR     689.9       283     690.0       298     707.5       298     704.4       350     704.2       400
GR     704.6       450     705.5       500     707.1       550

          SPILLWAY #1 AT FACE OF BRIDGE
X1     14778        19       250       298         1         1         1
GR     706.7         0     707.0        50     707.3       100     707.5       150     707.7       200
GR     707.7       250     693.8       250     693.6       265     693.5       283     693.5       298
GR     707.5       298     704.4       350     704.0       500     706.0       550     708.0       600
GR     710.0       625     712.0       665     714.0       695     716.0       725

          SPILLWAY #2
X1     14798        17       244       304        20        20        20
GR     706.7         0     707.0        50     707.3       100     707.5       150     707.7       200
GR     706.6       244     696.1       244     696.0       304     706.5       304     704.4       350
GR     704.0       500     706.0       550     708.0       600     710.0       625     712.0       665
GR     714.0       695     716.0       725

          SPILLWAY #3
X1     14828        19       864       949        30        30        30
GR     705.8         0     705.5       460     706.7       630     707.0       680     707.3       730
GR     707.5       780     707.7       830     706.6       864     701.5       864     701.5       949
GR     706.6       949     704.4       980     704.0      1130     706.0      1180     708.0      1230
GR     710.0      1255     712.0      1300     714.0      1330     716.0      1360

          MANUFACTURED SECTION, BOTTOM BASED ON INVERTS OF THE BRIDGE SECTIONS
X1     14980        11       100       500       152       152       152
X3                              100                 500
GR     720.0         0     710.0        20     700.0        40     700.0        70     702.0        90
GR     704.0       100     692.0       110     692.0       490     704.0       500     710.0       530
GR     720.0       560
```

```
NC                                          .3          .5
        MANUFACTURED SECTION, BOTTOM BASED ON INVERTS OF THE BRIDGE SECTIONS
X1    15400          8        200         620         420         420         420
X3                                        200                     620
GR    706.0          0      704.0         180       702.0         200       695.0       210       695.0       610
GR    702.0        620      710.0         650       720.0         670

        MANUFACTURED SECTION, BOTTOM BASED ON INVERTS OF THE BRIDGE SECTIONS
X1    15800          8        200         520         400         400         400
X3                                        200                     520
GR    706.0          0      706.0         180       704.0         200       696.0       210       696.0       510
GR    704.0        520      710.0         550       720.0         580

NC                                          .5          1.0
        D/S FACE OF NORTHVILLE RD. BRIDGE
X1    16001         25        250         318         201         201         201
X3                                        250                     318
GR    714.9          0      714.5          30       713.5         100       712.9       150       712.5       200
GR    713.0        227      713.5         250       704.8         250       702.0       253       699.3       263
GR    698.2        273      698.4         282       698.8         286       697.9       296       699.4       306
GR    702.0        313      702.9         315       704.5         318       714.1       318       714.2       342
GR    714.9        350      718.0         418       719.2         450       720.7       475       722.1       500

SB      .90       1.77        2.5           0          68           4         682
NC     .045       .045        .03
        U/S FACE OF NORTHVILLE RD. BRIDGE
X1    16063          0          0           0          62          62          62
X2        0          0          1       710.1      714.2
X3                                        203                     318
BT        8        250      713.5       704.8         250       713.5       710.1       282       713.8       710.4
BT      282      713.8      698.4         286       713.8       698.8         286       713.8       710.4       318
BT    714.1      710.7        318       714.1       704.5

NC     .035       .040       .035          .3          .5
X1    16113         25        250         318          50          50          50
GR    714.9          0      714.5          30       713.5         100      7712.9       150       712.5       200
GR    713.0        227      713.5         250       704.8         250       702.0       253       699.3       263
GR    698.2        273      698.4         282       698.8         286       697.9       296       699.4       306
GR    702.0        313      702.9         315       704.5         318       714.1       318       714.2       342
GR    714.9        350      718.0         418       719.2         450       720.7       475       722.1       500

X1    16764         27        249         300         651         651         651
GR    709.3          0      709.2          25       709.2          50       709.2        75       709.3       100
GR    709.5        125      709.9         150       710.3         175       710.7       200       712.0       225
GR    711.4        249      701.9         249       700.2         260       699.2       270       698.8       275
GR    698.5        280      699.8         290       701.5         300       712.2       300       712.7       323
GR    712.7        325      713.3         350       713.9         375       714.7       400       715.5       425
GR    716.5        450      717.6         475
```

```
NC      .040      .040      .035       .5       1.0
          D/S FACE OF E. HINES DRIVE BRIDGE (MIDDLE ROUGE PARKWAY)
X1    16864        27       249       300       100       100       100
GR    709.3         0     709.2        25     709.2        50     709.2        75     709.3       100
GR    709.5       125     709.9       150     710.3       175     710.7       200     712.0       225
GR    711.4       249     701.9       249     700.2       260     699.2       270     698.8       275
GR    698.7       280     699.8       290     701.5       300     712.2       300     712.7       323
GR    712.7       325     713.3       350     713.9       375     714.7       400     715.5       425
GR    716.5       450     717.6       475

SB        0      1.65       2.5         0        51         0       325
NC     .045      .045      .025
          U/S FACE OF E. HINES DRIVE BRIDGE (MIDDLE ROUGE PARKWAY)
X1    16900         0         0         0        36        36        36
X2        0         0         1     708.1     712.7
BT       25         0     709.3         0        25     709.2         0        50     709.2         0
BT       75     709.2         0       100     709.3         0       125     709.5         0       150
BT    709.9         0       175     710.3         0       200     710.7         0       225     712.0
BT        0       249     711.4     701.9       260     711.5     706.2       270     711.7     707.8
BT      275     711.8     708.1       280     711.9     707.8       290     712.0     706.2       300
BT    712.2     701.5       323     712.7         0       325     712.7         0       350     713.3
BT        0       375     713.9         0       400     714.7         0       425     715.5         0
BT      450     716.5         0       475     717.6         0

NC      .035      .040      .035        .3        .5
X1    16950        27       249       300        50        50        50
GR    709.3         0     709.2        25     709.2        50     709.2        75     709.3       100
GR    709.5       125     709.9       150     710.3       175     710.7       200     712.0       225
GR    711.4       249     701.9       249     700.2       260     699.2       270     698.8       275
GR    698.8       280     699.8       290     701.5       300     712.2       300     712.7       323
GR    712.7       325     713.3       350     713.9       375     714.7       400     715.5       425
GR    716.5       450     717.6       475

X1    18100        15       430       520      1150      1150      1150
GR    740.0         0     738.0       100     736.0       150     734.0       200     732.0       250
GR    730.0       310     728.0       360     720.0       420     715.0       430     710.0       450
GR    700.0       500     704.0       520     706.0       650     708.0       820     710.0       830

X1    19850        22       250     367.5      1750      1750      1750
GR    723.9         0     724.1        50     724.8       150     726.4       250     714.9       250
GR    711.4       260     710.3       270     704.5       276     702.6       281     703.2       291
GR    704.4       301     704.9       307     705.3     313.5     705.9       323     710.1       332
GR    710.9       352     716.3       366     721.8       366     728.0     367.5     729.3       450
GR    730.8       550     731.6       600

NC                          .035
          D/S FACE OF M-14 HWY. BRIDGE
X1    19851        22       250     367.5         1         1         1
BT        5       250     726.4     714.9       250     726.4     720.2       366     728.0     721.8
BT      366     728.0     716.3     367.5     728.0         0
GR    723.9         0     724.1        50     724.8       150     726.4       250     714.9       250
GR    711.4       260     710.3       270     704.5       276     702.6       281     703.2       291
GR    704.4       301     704.9       307     705.3     313.5     705.9       323     710.1       332
```

```
GR    710.9      352     716.3      366     721.8      366     728.0     367.5     729.3      450
GR    730.8      550     731.6      600

          U/S FACE OF M-14 HWY. BRIDGE
X1    19932        0         0        0        81       81       81
X2        0        0         0        0         0        0        1         0         0

NC     .030     .030      .035
X1    19933        0         0        0         1        1        1

NC                                   .5       1.0
X1    20033        0         0        0       100      100      100

NC                                   .3        .5
X1    20300       12       100      140       267      267      267
GR    713.0        0     712.0       60     710.0       80    708.0        90    706.0      100
GR    702.7      110     702.7      130     706.0      140    708.0       200    710.0      210
GR    712.0      220     714.0      230

NC     .040     .040      .035       .5       1.0
          D/S FACE OF BRIDGE AT ENTRANCE TO D.P.W.
X1    20470       30       249      280       170      170      170
X3                                  125                400
GR    711.4        0     711.4       30     712.3       55    713.3        80    713.8      105
GR    714.2      130     714.5      155     714.0      180    713.7       205    713.5      230
GR    712.9      249     707.8      249     707.0    250.3    703.5     256.2    702.5    257.5
GR    702.1      260     701.1      265     703.2      270    704.2     272.7    705.0      274
GR    707.2    278.7     707.9      280     712.8      280    713.2       305    713.8      330
GR    714.6      355     716.0      380     716.4      394    716.7       413    716.8      425

SB    1.05     1.76       2.5        0        28      2.6      218
NC     .045     .045      .030
          U/S FACE OF BRIDGE AT ENTRANCE TO D.P.W.
X1    20492        0         0        0        22       22       22
X2        0        0         1    710.9     712.9
X3                                   31                295
BT       33        0     711.4        0        30    711.4        0        55    712.3        0
BT       80    713.3         0      105     713.8        0      130     714.2        0      155
BT    714.5        0       180    714.0        0      205    713.7         0      230    713.5
BT        0      249     712.9    707.8      249    712.9    709.2     250.3    712.9    709.2
BT    250.3    712.9     710.9    256.2    712.9    710.9    256.2     712.9    703.5    257.5
BT    712.9    702.5     257.5    712.9    710.9    272.7    712.8     710.9    272.7    712.8
BT    704.2      274     712.8    705.0      274    712.8    710.9       278.7    712.8    710.9
BT    278.7    712.8     709.1      280     712.8    709.1      280     712.8    707.9      305
BT    713.2        0       330    713.8        0      355    714.6         0      380    716.0
BT        0      394     716.4        0      413    716.7        0       425    716.8        0

NC     .040     .040      .035       .3       .5
X1    20542       30       249      280       50       50       50
X3                                  143               382
GR    711.4        0     711.4       30     712.3       55    713.3        80    713.8      105
GR    714.2      130     714.5      155     714.0      180    713.7       205    713.5      230
GR    712.9      249     707.8      249     707.0    250.3    703.5     256.2    702.5    257.5
GR    702.1      260     701.1      265     703.2      270    704.2     272.7    705.0      274
```

```
GR    707.2     278.7     707.9     280     712.8     280     713.2     305     713.8     330
GR    714.6       355     716.0     380     716.4     394     716.7     413     716.8     425

X1    20750        13       280     320       258     258       258
X3                                 245               355
GR    714.0         0     714.0     230     712.0     260     710.0     270     708.0     280
GR    702.8       290     702.8     310     710.0     320     712.0     330     714.0     345
GR    716.0       360     720.0     385     722.0     400

NC                                   .5       1.0
X1    20850        36     255.7   316.1       100     100       100
GR    733.6         0     732.7      25       731 8    50     731.0      75     730.2     100
GR    729.6       125     729.0     150     728.4     175     727.9     200     727.4     225
GR    727.3       250     727.3   255.7     705.2   255.7     705.0     257     704.6     260
GR    703.7       267     703.2     275     703.0     282     702.9     286     703.9     292
GR    705.1       300     706.0     305     706.6   307.5     707.7     313     708.4   316.1
GR    727.6     316.1     727.6     350     728.0     375     728.4     400     729.0     425
GR    729.7       450     730.4     475     731.4     500     731.8     525     732.7     550
GR    733.4       575

NC     .030      .030      .025
          D/S FACE OF NORTHVILLE RD.  BRIDGE
X1    20851        36     255.7   316.1         1       1         1
BT       13     255.7     727.3   705.2       257   727.3     710.0     260     727.3   713.5
BT      267     727.3     719.2     275     727.3   723.0       282   727.4     724.3     286
BT    727.4     724.7       292   727.5     724.0     300     727 5   721.4       305   725.5
BT    718.7     307.5     727.6   716.6       313   727.6     711.5   316.1     727.6   708.4
GR    733.6         0     732.7      25       731.8    50     731.0      75     730.2     100
GR    729.6       125     729.0     150     728.4     175     727.9     200     727.4     225
GR    727.3       250     727.3   255.7     705.2   255.7     705.0     257     704.6     260
GR    703.7       267     703.2     275     703.0     282     702.9     286     703.9     292
GR    705.1       300     706.0     305     706.6   307.5     707.7     313     708.4   316.1
GR    727.6     316.1     727.6     350     728.0     375     728.4     400     729.0     425
GR    729.7       450     730.4     475     731.4     500     731.8     525     732.7     550
GR    733.4       575

          U/S FACE OF NORTHVILLE RD.  BRIDGE
X1    20885         0         0       0        34      34        34
X2        0         0         0       0         0       0         1         0       0       0

NC                                  .035
X1    20886         0         0       0         1       1         1
```

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	L-BANK ELEV
Q	GLOB	GCH	GROB	ALOB	ACH	AROB	VOL	TWA	R-BANK ELEV
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

*PROF 1

CCHV= 0.300 CEHV= 0.500
*SECNO 1000.000
3280 CROSS SECTION 1000.00 EXTENDED 5.50 FEET

1000.000	12.50	667.50	0.00	667.50	667.59	0.09	0.00	0.00	670.00
4100.0	0.0	2660.9	1439.1	0.0	971.1	820.0	0.0	0.0	665.00
0.00	0.00	2.74	1.75	0.000	0.035	0.035	0.000	655.00	30.50
0.000279	0.	0.	0.	0	0	0	0.00	329.50	360.00

*SECNO 1700.000
3280 CROSS SECTION 1700.00 EXTENDED 5.70 FEET

1700.000	12.09	667.69	0.00	0.00	667.78	0.09	0.19	0.00	670.00
4100.0	0.0	2616.5	1483.5	0.0	990.7	860.0	29.3	5.3	665.00
0.08	0.00	2.64	1.73	0.000	0.035	0.035	0.000	655.60	30.07
0.000253	700.	700.	700.	0	0	0	0.00	329.93	360.00

CCHV= 0.500 CEHV= 1.000
*SECNO 2100.000

3302 WARNING- CONVEYANCE CHANGE OUTSIDE OF ACCEPTABLE RANGE, KRATIO = 0.48

2100.000	11.78	667.88	0.00	0.00	668.26	0.38	0.19	0.29	682.80
4100.0	0.0	4100.0	0.0	0.0	828.4	0.0	41.6	7.4	683.10
0.11	0.00	4.95	0.00	0.000	0.035	0.000	0.000	656.10	274.88
0.001108	400.	400.	400.	2	0	0	0.00	122.15	397.03

*SECNO 2101.000

3370- NORMAL BRIDGE, NRD= 10- MIN ELTRD= 682.80 MAX ELLC= 679.20

D/S FACE OF N.B. I-275 BRIDGE

2101.000	11.78	667.88	0.00	0.00	668.29	0.41	0.00	0.03	682.80
4100.0	0.0	4100.0	0.0	0.0	799.4	0.0	41.6	7.4	683.10
0.11	0.00	5.13	0.00	0.000	0.035	0.000	0.000	656.10	274.88
0.001389	1.	1.	1.	0	0	0	-29.12	122.15	397.03

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	L-BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	R-BANK ELEV
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

CCHV= 0.300 CEHV= 0.500
*SECNO 2157.000

3370 NORMAL BRIDGE, NRD= 10 MIN ELTRD= 682.80 MAX ELLC= 679.20

U/S FACE OF N.B. I-275 BRIDGE

2157.000	11.87	667.97	0.00	0.00	668.37	0.40	0.08	0.00	682.80
4100.0	0.0	4100.0	0.0	0.0	810.1	0.0	42.6	7.5	683.10
0.11	0.00	5.06	0.00	0.000	0.035	0.000	0.000	656.10	274.64
0.001337	56.	56.	56.	2	0	0	-29.49	122.64	397.28

*SECNO 2158.000

2158.000	11.91	668.01	0.00	0.00	668.38	0.37	0.00	0.01	682.80
4100.0	0.0	4100.0	0.0	0.0	844.9	0.0	42.6	7.5	683.10
0.11	0.00	4.85	0.00	0.000	0.035	0.000	0.000	656.10	274.52
0.001046	1.	1.	1.	2	0	0	0.00	122.87	397.39

*SECNO 2188.000

2188.000	11.95	668.05	0.00	0.00	668.41	0.36	0.03	0.00	682.80
4100.0	0.0	4100.0	0.0	0.0	849.3	0.0	43.2	7.6	683.10
0.11	0.00	4.83	0.00	0.000	0.035	0.000	0.000	656.10	274.43
0.001030	30.	30.	30.	0	0	0	0.00	123.06	397.49

*SECNO 2189.000

3370 NORMAL BRIDGE, NRD= 10 MIN ELTRD= 682.80 MAX ELLC= 679.20

D/S FACE OF S.B. I-275 BRIDGE

2189.000	11.94	668.04	0.00	0.00	668.43	0.39	0.00	0.01	682.80
4100.0	0.0	4100.0	0.0	0.0	818.8	0.0	43.2	7.6	683.10
0.11	0.00	5.01	0.00	0.000	0.035	0.000	0.000	656.10	274.44
0.001297	1.	1.	1.	1	0	0	-29.78	123.03	397.47

*SECNO 2245.000

3370 NORMAL BRIDGE, NRD= 10 MIN ELTRD= 682.80 MAX ELLC= 679.20

U/S FACE OF S.B. I-275 BRIDGE

2245.000	12.02	668.12	0.00	0.00	668.50	0.38	0.07	0.00	682.80
4100.0	0.0	4100.0	0.0	0.0	826.7	0.0	44.3	7.8	683.10
0.11	0.00	4.96	0.00	0.000	0.035	0.000	0.000	656.10	274.26
0.001263	56.	56.	56.	1	0	0	-30.04	123.39	397.65

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	L-BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	R-BANK ELEV
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	EI.MIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

*SECNO 2246.000

2246.000	12.06	668.16	0.00	0.00	663.51	0.35	0.00	0.01	682.80
4100.0	0.0	4100.0	0.0	0.0	863.0	0.0	44.3	7.8	683.10
0.11	0.00	4.75	0.00	0.000	0.035	0.000	0.000	656.10	274.13
0.000983	1.	1.	1.	2	0	0	0.00	123.66	397.79

CCHV= 0.500 CEHV= 1.000
*SECNO 3000.000

3302 WARNING: CONVEYANCE CHANGE OUTSIDE OF ACCEPTABLE RANGE, KRATIO = 4.19

3000.000	11.76	668.76	0.00	0.00	668.78	0.02	0.11	0.16	661.00
4100.0	2022.6	1132.4	945.0	1740.5	743.3	969.0	81.7	13.6	661.00
0.29	1.16	1.52	0.98	0.035	0.035	0.035	0.000	657.00	156.20
0.000056	754.	754.	754.	2	0	0	0.00	551.41	707.61

CCHV= 0.300 CEHV= 0.500
*SECNO 4000.000

4000.000	10.83	668.83	0.00	0.00	668.86	0.03	0.07	0.00	662.00
4100.0	1495.7	1194.6	1409.8	1243.5	677.9	1264.9	157.9	26.7	662.00
0.49	1.20	1.76	1.11	0.035	0.035	0.035	0.000	658.00	87.60
0.000085	1000.	1000.	1000.	2	0	0	0.00	589.47	677.07

CCHV= 0.500 CEHV= 1.000
*SECNO 4800.000

3302 WARNING: CONVEYANCE CHANGE OUTSIDE OF ACCEPTABLE RANGE, KRATIO = 0.54

3470 ENCROACHMENT STATIONS= 340.0 596.0 TYPE= 1 TARGET= 256.000

4800.000	10.94	668.94	0.00	0.00	669.05	0.11	0.11	0.08	662.00
4100.0	0.0	2125.0	1975.0	0.0	685.9	939.1	202.1	34.5	662.00
0.58	0.00	3.10	2.10	0.000	0.035	0.035	0.000	658.00	340.00
0.000292	800.	800.	800.	2	0	0	0.00	256.00	596.00

*SECNO 5075.000

3302 WARNING: CONVEYANCE CHANGE OUTSIDE OF ACCEPTABLE RANGE, KRATIO = 0.67

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	L-BANK ELEV
Q	GLOB	GCH	GROB	ALOB	ACH	AROB	VOL	TWA	R-BANK ELEV
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

3470 ENCROACHMENT STATIONS= 340.0 458.0 TYPE= 1 TARGET= 118.000

5075.000	11.06	669.06	0.00	0.00	669.36	0.30	0.12	0.19	662.00
4100.0	0.0	3254.9	845.1	0.0	694.0	262.7	210.2	35.7	662.00
0.60	0.00	4.69	3.22	0.000	0.035	0.035	0.000	658.00	340.00
0.000660	275.	275.	275.	2	0	0	0.00	118.00	458.00

CCHV= 0.500 CEHV= 1.000
*SECNO 5146.000

3301 HV CHANGED MORE THAN HVINS

3302 WARNING: CONVEYANCE CHANGE OUTSIDE OF ACCEPTABLE RANGE, KRATIO = 0.43

5146.000	9.75	669.15	0.00	0.00	670.17	1.02	0.09	0.71	679.30
4100.0	0.0	4100.0	0.0	0.0	506.2	0.0	211.4	35.8	674.50
0.60	0.00	8.10	0.00	0.000	0.035	0.000	0.000	659.40	257.62
0.003515	71.	71.	71.	2	0	0	0.00	81.18	338.80

CCHV= 0.300 CEHV= 0.500
*SECNO 5147.000

3370 NORMAL BRIDGE, NRD= 12 MIN ELTRD= 675.30 MAX ELLC= 677.80

3470 ENCROACHMENT STATIONS= 258.0 338.0 TYPE= 1 TARGET= 80.000
D/S FACE OF HAGGERTY RD. BRIDGE

5147.000	9.70	669.10	0.00	0.00	670.22	1.12	0.00	0.05	100000.00
4100.0	0.0	4100.0	0.0	0.0	483.2	0.0	211.4	35.8	100000.00
0.60	0.00	8.49	0.00	0.000	0.035	0.000	0.000	659.40	258.00
0.005230	1.	1.	1.	2	0	0	-17.67	80.00	338.00

*SECNO 5181.000

3370 NORMAL BRIDGE, NRD= 12 MIN ELTRD= 675.30 MAX ELLC= 677.80

3470 ENCROACHMENT STATIONS= 258.0 338.0 TYPE= 1 TARGET= 80.000
U/S FACE OG HAGGERTY RD. BRIDGE

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	L-BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	R-BANK ELEV
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST
5181.000	10.00	669.40	0.00	0.00	670.42	1.02	0.17	0.03	100000.00
4100.0	0.0	4100.0	0.0	0.0	505.8	0.0	211.8	35.9	100000.00
0.60	0.00	8.11	0.00	0.000	0.035	0.000	0.000	659.40	258.00
0.004590	34.	34.	34.	2	0	0	-18.61	80.00	338.00

CCHV= 0.500 CEHV= 1.000
*SECNO 5182.000

5182.000	10.21	669.61	0.00	0.00	670.49	0.88	0.00	0.07	679.30
4100.0	0.0	4100.0	0.0	0.0	543.9	0.0	211.8	35.9	674.50
0.60	0.00	7.54	0.00	0.000	0.035	0.000	0.000	659.40	256.71
0.002830	1.	1.	1.	2	0	0	0.00	82.09	338.80

*SECNO 5232.000

3301 HV CHANGED MORE THAN HVINS

3302 WARNING: CONVEYANCE CHANGE OUTSIDE OF ACCEPTABLE RANGE, KRATIO = 2.38

3470 ENCROACHMENT STATIONS= 245.0 428.0 TYPE= 1 TARGET= 183.000

5232.000	12.47	670.67	0.00	0.00	670.88	0.20	0.05	0.34	666.00
4100.0	522.7	3054.2	523.1	210.3	774.7	214.8	212.8	36.0	666.00
0.60	2.49	3.94	2.44	0.035	0.035	0.035	0.000	658.20	245.00
0.000500	50.	50.	50.	3	0	0	0.00	183.00	428.00

*SECNO 5382.000

3302 WARNING: CONVEYANCE CHANGE OUTSIDE OF ACCEPTABLE RANGE, KRATIO = 1.90

3470 ENCROACHMENT STATIONS= 95.0 578.0 TYPE= 1 TARGET= 483.000

5382.000	12.75	670.95	0.00	0.00	670.99	0.05	0.04	0.08	666.00
4100.0	1374.2	1690.4	1035.4	964.7	799.3	816.2	219.3	37.2	666.00
0.63	1.42	2.11	1.27	0.035	0.035	0.035	0.000	658.20	95.00
0.000138	150.	150.	150.	2	0	0	0.00	483.00	578.00

CCHV= 0.300 CEHV= 0.500

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	L-BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	R-BANK ELEV
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST
*SECNO 6000.000									
6000.000	12.84	671.04	0.00	0.00	671.07	0.03	0.07	0.00	666.00
4100.0	1518.5	1477.3	1104.2	1205.6	807.4	1062.3	259.4	45.3	666.00
0.75	1.26	1.83	1.04	0.035	0.035	0.035	0.000	658.20	46.89
0.000102	618.	618.	618.	2	0	0	0.00	665.35	712.24
*SECNO 6183.000									
3302 WARNING: CONVEYANCE CHANGE OUTSIDE OF ACCEPTABLE RANGE, KRATIO = 0.55									
3470 ENCROACHMENT STATIONS=		383.0	1028.0	TYPE=	1	TARGET=	645.000		
6183.000	12.84	671.04	0.00	0.00	671.13	0.08	0.03	0.03	670.80
4100.0	1597.9	2014.7	487.4	904.1	704.8	432.8	270.2	48.1	670.40
0.77	1.77	2.86	1.13	0.035	0.035	0.035	0.000	658.20	383.00
0.000338	183.	183.	183.	1	0	0	0.00	644.70	1027.70
*SECNO 6196.000									
3265 DIVIDED FLOW									
6196.000	7.08	671.08	0.00	0.00	671.14	0.05	0.00	0.01	672.00
4100.0	4013.2	0.0	86.8	2133.0	0.0	171.8	270.8	48.3	672.00
0.78	1.88	0.00	0.51	0.035	0.000	0.035	0.000	664.00	117.83
0.000211	13.	13.	13.	2	0	0	0.00	643.85	1108.05
CCHV= 0.300 CEHV= 0.500									
*SECNO 6409.000									
3302 WARNING: CONVEYANCE CHANGE OUTSIDE OF ACCEPTABLE RANGE, KRATIO = 1.46									
6409.000	12.95	671.15	0.00	0.00	671.18	0.03	0.03	0.01	670.80
4100.0	2988.9	1111.0	0.1	2449.6	713.7	0.7	284.2	51.5	670.40
0.82	1.22	1.56	0.21	0.035	0.035	0.035	0.000	658.20	117.71
0.000099	213.	213.	213.	0	0	0	0.00	660.14	777.86
*SECNO 7900.000									

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	L-BANK ELEV
Q	GLOB	GCH	GROB	ALOB	ACH	AROB	VOL	TWA	R-BANK ELEV
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

3302 WARNING: CONVEYANCE CHANGE OUTSIDE OF ACCEPTABLE RANGE, KRATIO = 0.38

7900.000	9.34	671.34	0.00	0.00	671.61	0.27	0.31	0.12	666.00
4100.0	756.9	3177.4	165.7	492.2	689.7	68.6	359.7	70.3	666.00
0.93	1.54	4.61	2.42	0.035	0.035	0.035	0.000	662.00	9.90
0.000690	1491.	1491.	1491.	2	0	0	0.00	442.78	452.68

CCHV= 0.500 CEHV= 1.000
*SECNO 8201.000

3302 WARNING: CONVEYANCE CHANGE OUTSIDE OF ACCEPTABLE RANGE, KRATIO = 0.67

D/S FACE OF E. HINES DRIVE BRIDGE

8201.000	8.64	671.64	0.00	0.00	672.05	0.42	0.30	0.15	664.90
4100.0	1210.2	2345.3	544.5	461.4	379.9	115.3	367.4	73.1	665.20
0.94	2.62	6.17	4.72	0.035	0.035	0.035	0.000	663.00	193.64
0.001516	301.	301.	301.	2	0	0	0.00	342.17	535.82

SPECIAL BRIDGE

5070, VARIABLE ELCHU OR ELCHD ON SB CARD NOT SPECIFIED

SB	XK	XKOR	CDFQ	RDLEN	BWC	BWP	BAREA	SS	ELCHU	ELCHD
	0.00	1.75	2.50	0.00	52.00	0.00	340.00	0.00	663.00	663.00

*SECNO 8227.000

3302 WARNING: CONVEYANCE CHANGE OUTSIDE OF ACCEPTABLE RANGE, KRATIO = 1.77

PRESSURE AND WEIR FLOW, Weir Submergence Based on TRAPEZOIDAL Shape

EGPRS	EGLWC	H3	QWEIR	QPR	BAREA	TRAPEZOID AREA	ELLC	ELTRD	WEIRLN
675.59	672.18	0.00	1764.	2336.	340.	458.	671.80	673.00	215.

U/S FACE OF E. HINES DRIVE BRIDGE

8227.000	9.64	672.64	0.00	0.00	672.92	0.28	0.37	0.00	664.70
4100.0	1379.3	2296.0	424.7	728.2	432.3	149.4	368.0	73.3	665.20
0.95	1.89	5.31	2.84	0.035	0.025	0.035	0.000	663.00	183.55
0.000482	26.	26.	26.	2	0	4	0.00	358.32	541.87

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	L-BANK ELEV
Q	GLOB	GCH	GROB	ALOB	ACH	AROB	VOL	TWA	R-BANK ELEV
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

CCHV= 0.300 CEHV= 0.500
*SECNO 8257.000

3302 WARNING: CONVEYANCE CHANGE OUTSIDE OF ACCEPTABLE RANGE, KRATIO = 0.67

8257.000	9.71	672.71	0.00	0.00	672.95	0.24	0.02	0.01	664.90
4100.0	1490.5	2159.0	450.5	746.7	435.9	152.0	369.0	73.5	665.20
0.95	2.00	4.95	2.96	0.050	0.040	0.050	0.000	663.00	182.86
0.001061	30.	30.	30.	2	0	0	0.00	359.42	542.28

*SECNO 9600.000

3302 WARNING: CONVEYANCE CHANGE OUTSIDE OF ACCEPTABLE RANGE, KRATIO = 0.66

9600.000	8.64	674.64	0.00	0.00	675.15	0.51	2.06	0.13	672.00
4100.0	114.8	2842.2	1143.0	71.6	428.3	416.7	403.7	85.0	670.00
1.02	1.60	6.64	2.74	0.050	0.040	0.050	0.000	666.00	369.77
0.002411	1343.	1343.	1343.	3	0	0	0.00	383.65	753.42

CCHV= 0.500 CEHV= 1.000
*SECNO 10200.000

3470 ENCROACHMENT STATIONS= 100.0 555.0 TYPE= 1 TARGET= 455.000

10200.000	7.46	676.46	0.00	0.00	677.21	0.76	1.82	0.25	672.00
4100.0	1274.0	2696.5	129.5	486.3	320.4	55.1	415.9	90.5	672.00
1.04	2.62	8.41	2.35	0.050	0.040	0.050	0.000	669.00	100.00
0.003916	600.	600.	600.	2	0	0	0.00	412.27	512.27

*SECNO 10500.000

3470 ENCROACHMENT STATIONS= 175.0 555.0 TYPE= 1 TARGET= 380.000

10500.000	7.55	677.75	677.67	0.00	678.78	1.03	1.29	0.27	673.20
4100.0	907.0	3033.0	160.1	334.3	324.6	61.2	421.4	93.0	673.20
1.05	2.71	9.34	2.61	0.050	0.040	0.050	0.000	670.20	175.00
0.004748	300.	300.	300.	4	5	0	0.00	337.73	512.73

*SECNO 10600.000

3470 ENCROACHMENT STATIONS= 200.0 555.0 TYPE= 1 TARGET= 355.000

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	L-BANK ELEV
Q	GLOB	GCH	GROB	ALOB	ACH	AROB	VOL	TWA	R-BANK ELEV
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST
10600.000	7.62	678.22	678.12	0.00	679.31	1.08	0.48	0.05	673.60
4100.0	816.0	3106.7	177.2	296.9	328.1	66.5	423.0	73.8	673.60
1.06	2.75	9.47	2.66	0.050	0.040	0.050	0.000	670.60	200.00
0.004807	100.	100.	100.	4	5	0	0.00	313.12	513.12

*SECNO 10700.000

3301 HV CHANGED MORE THAN HVINS

3302 WARNING: CONVEYANCE CHANGE OUTSIDE OF ACCEPTABLE RANGE, KRATIO = 1.53

3470 ENCROACHMENT STATIONS= 600.0 880.0 TYPE= 1 TARGET= 200.000

10700.000	8.58	679.58	0.00	0.00	679.96	0.38	0.30	0.35	675.00
4100.0	1467.0	2039.7	593.2	481.1	320.7	238.4	425.0	94.5	676.00
1.06	3.05	6.36	2.49	0.050	0.040	0.050	0.000	671.00	600.00
0.002042	100.	100.	100.	4	0	0	0.00	277.90	877.90

CCHV= 0.500 CEHV= 1.000
*SECNO 10800.000

3470 ENCROACHMENT STATIONS= 625.0 855.0 TYPE= 1 TARGET= 230.000

10800.000	8.55	679.80	0.00	0.00	680.28	0.47	0.22	0.09	675.25
4100.0	1318.1	2210.2	571.7	394.8	319.6	203.9	427.2	95.0	676.25
1.07	3.34	6.92	2.80	0.050	0.040	0.050	0.000	671.25	625.00
0.002424	100.	100.	100.	2	0	0	0.00	230.00	855.00

*SECNO 10901.000
3280 CROSS SECTION 10901.00 EXTENDED 2.28 FEET

3301 HV CHANGED MORE THAN HVINS

3302 WARNING: CONVEYANCE CHANGE OUTSIDE OF ACCEPTABLE RANGE, KRATIO = 0.62

3470 ENCROACHMENT STATIONS= 155.0 388.0 TYPE= 1 TARGET= 233.000
D/S FACE OF MIDDLE WOODS DRIVE BRIDGE

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	L-BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	R-BANK ELEV
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST
10901.000	8.68	680.18	679.95	0.00	681.48	1.31	0.37	0.83	680.00
4100.0	72.4	3438.0	589.7	47.8	346.9	166.6	428.9	95.6	680.00
1.07	1.51	9.91	3.54	0.050	0.040	0.050	0.000	671.50	155.00
0.006368	101.	101.	101.	4	5	0	0.00	233.00	388.00

SPECIAL BRIDGE

5070, VARIABLE ELCHU OR ELCHD ON SB CARD NOT SPECIFIED

SB	XK	XKOR	CDFG	RDLEN	BWC	BWP	BAREA	SS	ELCHU	ELCHD
	0.00	1.73	2.50	0.00	41.00	0.00	232.00	0.00	671.50	671.50

*SECNO 10930.000
3280 CROSS SECTION 10930.00 EXTENDED 6.64 FEET

3301 HV CHANGED MORE THAN HVINS

3302 WARNING: CONVEYANCE CHANGE OUTSIDE OF ACCEPTABLE RANGE, KRATIO = 4.31

PRESSURE AND WEIR FLOW, Weir Submergence Based on TRAPEZOIDAL Shape

EGPRS	EGLWC	H3	QWEIR	QPR	BAREA	TRAPEZOID AREA	ELLC	ELTRD	WEIRLN
688.57	681.48	0.00	1086.	3014.	232.	242.	677.40	680.00	43.

3470 ENCROACHMENT STATIONS= 161.0 381.0 TYPE= 1 TARGET= 220.000
U/S FACE OF MIDDLE WOODS DRIVE BRIDGE

10930.000	13.04	684.54	0.00	0.00	684.71	0.17	3.23	0.00	680.00
4100.0	787.4	2170.9	1141.7	433.4	532.5	539.8	429.6	95.7	680.00
1.07	1.82	4.08	2.12	0.042	0.030	0.042	0.000	671.50	161.00
0.000342	29.	29.	29.	2	0	2	0.00	220.00	381.00

*SECNO 10980.000
3280 CROSS SECTION 10980.00 EXTENDED 6.66 FEET

3470 ENCROACHMENT STATIONS= 166.0 377.0 TYPE= 1 TARGET= 211.000

10980.000	13.06	684.56	0.00	0.00	684.74	0.18	0.02	0.01	680.00
4100.0	760.9	2220.4	1118.8	410.4	533.3	516.5	431.3	96.0	680.00
1.08	1.85	4.16	2.17	0.042	0.030	0.042	0.000	671.50	166.00
0.000356	50.	50.	50.	2	0	0	0.00	211.00	377.00

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	L-BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	R-BANK ELEV
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST
*SECNO 11200.000									
11200.000	11.77	684.67	0.00	0.00	685.08	0.42	0.11	0.24	694.50
4100.0	0.0	4100.0	0.0	0.0	792.7	0.0	437.0	96.8	692.90
1.09	0.00	5.17	0.00	0.000	0.030	0.000	0.000	672.90	234.93
0.000684	220.	220.	220.	2	0	0	0.00	94.81	329.74
*SECNO 11201.000									
3370 NORMAL BRIDGE, NRD= 14 MIN ELTRD= 692.90 MAX ELLC= 692.50									
D/S FACE OF PLYMOUTH ROAD BRIDGE									
11201.000	11.77	684.67	0.00	0.00	685.44	0.77	0.00	0.36	694.50
4100.0	0.0	4100.0	0.0	0.0	581.4	0.0	437.0	96.8	692.90
1.09	0.00	7.05	0.00	0.000	0.025	0.000	0.000	672.90	234.93
0.001006	1.	1.	1.	0	0	0	-211.31	94.81	329.75
*SECNO 11255.000									
3370 NORMAL BRIDGE, NRD= 14 MIN ELTRD= 692.90 MAX ELLC= 692.50									
U/S FACE OF PLYMOUTH ROAD BRIDGE									
11255.000	11.83	684.73	0.00	0.00	685.50	0.77	0.05	0.00	694.50
4100.0	0.0	4100.0	0.0	0.0	583.9	0.0	437.7	96.9	692.90
1.09	0.00	7.02	0.00	0.000	0.025	0.000	0.000	672.90	234.82
0.000996	54.	54.	54.	1	0	0	-214.00	95.04	329.86
*SECNO 11256.000									
11256.000	12.45	685.35	0.00	0.00	685.70	0.35	0.00	0.21	694.50
4100.0	0.0	4100.0	0.0	0.0	858.9	0.0	437.8	96.9	692.90
1.09	0.00	4.77	0.00	0.000	0.035	0.000	0.000	672.90	233.45
0.000744	1.	1.	1.	2	0	0	0.00	97.69	331.14
CCHV= 0.300 CEHV= 0.500									
*SECNO 11356.000									
11356.000	12.32	685.42	0.00	0.00	685.79	0.36	0.08	0.01	694.70
4100.0	0.0	4100.0	0.0	0.0	846.6	0.0	439.7	97.1	693.10
1.10	0.00	4.84	0.00	0.000	0.035	0.000	0.000	673.10	233.72
0.000774	100.	100.	100.	1	0	0	0.00	97.16	330.88

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	L-BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	R-BANK ELEV
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	ISTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

*SECNO 12150.000

3470 ENCROACHMENT STATIONS= 200.0 300.0 TYPE= 1 TARGET= 100.000

12150.000	11.06	686.06	0.00	0.00	686.38	0.32	0.58	0.01	682.00
4100.0	0.0	4100.0	0.0	0.0	905.7	0.0	455.7	98.9	100000.00
1.15	0.00	4.53	0.00	0.000	0.035	0.000	0.000	675.00	200.00
0.000681	794.	794.	794.	2	0	0	0.00	100.00	300.00

CCHV= 0.500 CEHV= 1.000
*SECNO 12850.000

3301 HV CHANGED MORE THAN HVINS

3302 WARNING: CONVEYANCE CHANGE OUTSIDE OF ACCEPTABLE RANGE, KRATIO = 0.44

12850.000	15.48	686.98	0.00	0.00	688.03	1.05	0.92	0.74	731.60
4100.0	0.0	4100.0	0.0	0.0	497.8	0.0	467.0	100.1	731.80
1.17	0.00	8.24	0.00	0.000	0.035	0.000	0.000	671.50	250.00
0.003550	700.	700.	700.	2	0	0	0.00	56.00	306.00

*SECNO 13000.000

13000.000	8.80	687.50	0.00	0.00	688.64	1.15	0.52	0.09	732.30
4100.0	0.0	4100.0	0.0	0.0	477.1	0.0	468.6	100.3	732.50
1.18	0.00	8.59	0.00	0.000	0.035	0.000	0.000	678.70	250.00
0.003354	150.	150.	150.	2	0	0	0.00	56.00	306.00

*SECNO 13001.000

3370 NORMAL BRIDGE, NRD= 26 MIN ELTRD= 732.30 MAX ELLC= 679.10

D/S FACE OF C&O R.R. BRIDGE

13001.000	8.80	687.50	0.00	0.00	688.94	1.44	0.00	0.29	732.30
4100.0	0.0	4100.0	0.0	0.0	426.1	0.0	468.7	100.3	732.50
1.18	0.00	9.62	0.00	0.000	0.025	0.000	0.000	678.70	250.00
0.003797	1.	1.	1.	0	0	0	-51.14	56.00	306.00

*SECNO 13135.000

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	L-BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	R-BANK ELEV
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

3370 NORMAL BRIDGE, NRD= 26 MIN ELTRD= 732.30 MAX ELLC= 699.10

U/S FACE OF C&O R.R. BRIDGE

13135.000	9.60	688.30	0.00	0.00	689.50	1.21	0.45	0.12	732.30
4100.0	0.0	4100.0	0.0	0.0	465.3	0.0	470.0	100.5	732.50
1.18	0.00	8.81	0.00	0.000	0.025	0.000	0.000	678.70	250.00
0.002957	134.	134.	134.	2	0	0	-56.72	56.00	306.00

*SECNO 13136.000

13136.000	10.12	688.82	0.00	0.00	689.68	0.86	0.00	0.17	732.30
4100.0	0.0	4100.0	0.0	0.0	551.6	0.0	470.0	100.5	732.50
1.18	0.00	7.43	0.00	0.000	0.035	0.000	0.000	678.70	250.00
0.002168	1.	1.	1.	2	0	0	0.00	56.00	306.00

*SECNO 13236.000

13236.000	9.65	689.05	0.00	0.00	690.00	0.95	0.23	0.09	733.00
4100.0	0.0	4100.0	0.0	0.0	525.0	0.0	471.3	100.6	733.20
1.18	0.00	7.81	0.00	0.000	0.035	0.000	0.000	679.40	250.00
0.002514	100.	100.	100.	2	0	0	0.00	56.00	306.00

CCHV= 0.300 CEHV= 0.500
*SECNO 13800.000

3301 HV CHANGED MORE THAN HVINS

3302 WARNING: CONVEYANCE CHANGE OUTSIDE OF ACCEPTABLE RANGE, KRATIO = 1.73

3470 ENCROACHMENT STATIONS= 90.0 346.0 TYPE= 1 TARGET= 256.000

13800.000	7.28	690.78	0.00	0.00	690.98	0.20	0.76	0.22	685.00
4100.0	1618.9	1444.7	1036.4	584.6	320.1	310.6	482.5	102.7	685.00
1.23	2.77	4.51	3.34	0.038	0.035	0.038	0.000	683.50	90.00
0.000837	564.	564.	564.	2	0	0	0.00	256.00	346.00

CCHV= 0.500 CEHV= 1.000
*SECNO 14400.000

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	L-BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	R-BANK ELEV
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

3301 HV CHANGED MORE THAN HVINS

7185 MINIMUM SPECIFIC ENERGY
3720 CRITICAL DEPTH ASSUMED

3470 ENCROACHMENT STATIONS= 125.0 273.0 TYPE= 1 TARGET= 148.000

14400.000	7.51	695.81	695.81	0.00	697.45	1.63	1.07	1.43	694.00
4100.0	249.6	3427.0	423.5	67.9	309.6	96.1	494.2	105.4	694.00
1.24	3.67	11.07	4.41	0.038	0.035	0.038	0.000	688.30	125.00
0.006003	600.	600.	600.	2	8	0	0.00	148.00	273.00

CCHV= 0.500 CEHV= 1.000
*SECNO 14600.000

3301 HV CHANGED MORE THAN HVINS

14600.000	7.28	697.18	0.00	0.00	699.35	2.17	1.37	0.53	707.70
4100.0	0.0	4100.0	0.0	0.0	347.1	0.0	496.1	105.9	707.50
1.25	0.00	11.81	0.00	0.000	0.035	0.000	0.000	689.90	250.00
0.007864	200.	200.	200.	2	0	0	0.00	48.00	298.00

*SECNO 14601.000

3302 WARNING: CONVEYANCE CHANGE OUTSIDE OF ACCEPTABLE RANGE, KRATIO = 0.64

3370 NORMAL BRIDGE, NRD= 12 MIN ELTRD= 703.60 MAX ELLC= 703.60

D/S FACE OF E. HINES DRIVE & WILCOX RD.

14601.000	7.29	697.19	0.00	0.00	699.65	2.46	0.01	0.29	707.70
4100.0	0.0	4100.0	0.0	0.0	325.7	0.0	496.1	105.9	707.50
1.25	0.00	12.59	0.00	0.000	0.035	0.000	0.000	689.90	250.00
0.018911	1.	1.	1.	0	0	0	-21.72	48.00	298.00

*SECNO 14776.000

3301 HV CHANGED MORE THAN HVINS

stages not likely high

4100 cfs will not all be through culvert d/s of dam. Flow over embankment

~~4100~~ 3000 through culvert

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	L-BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	R-BANK ELEV
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

3302 WARNING: CONVEYANCE CHANGE OUTSIDE OF ACCEPTABLE RANGE, KRATIO = 1.72

3370 NORMAL BRIDGE, NRD= 12 MIN ELTRD= 703.60 MAX ELLC= 703.60

U/S FACE OF E. HINES DRIVE & WILCOX RD.

14776.000	11.22	701.12	0.00	0.00	702.15	1.03	1.78	0.71	707.70
4100.0	0.0	4100.0	0.0	0.0	502.5	0.0	497.7	106.1	707.50
1.25	0.00	3.16	0.00	0.000	0.035	0.000	0.000	689.90	250.00
0.006361	175.	175.	175	3	0	0	-33.50	48.00	298.00

4100 cfs not going through culvert?

*SECNO 14777.000

3302 WARNING: CONVEYANCE CHANGE OUTSIDE OF ACCEPTABLE RANGE, KRATIO = 1.77

14777.000	11.47	701.37	0.00	0.00	702.24	0.87	0.00	0.08	707.70
4100.0	0.0	4100.0	0.0	0.0	548.1	0.0	497.7	106.1	707.50
1.25	0.00	7.48	0.00	0.000	0.035	0.000	0.000	689.90	250.00
0.002029	1.	1.	1.	2	0	0	0.00	48.00	298.00

*SECNO 14778.000

3301 HV CHANGED MORE THAN HVINS

3302 WARNING: CONVEYANCE CHANGE OUTSIDE OF ACCEPTABLE RANGE, KRATIO = 0.57

SPILLWAY #1 AT FACE OF BRIDGE

14778.000	7.87	701.87	0.00	0.00	703.24	1.87	0.00	1.00	707.70
4100.0	0.0	4100.0	0.0	0.0	373.9	0.0	497.8	106.1	707.50
1.25	0.00	10.97	0.00	0.000	0.035	0.000	0.000	693.50	250.00
0.006265	1.	1.	1.	0	0	0	0.00	48.00	298.00

$Q = (44)(3)(1')^{1.5}$

200 - 699.3
300 - 701.1
3500 701.9
4100 - 702.8

*SECNO 14798.000

3301 HV CHANGED MORE THAN HVINS

SPILLWAY #2

14798.000	5.53	701.53	0.00	0.00	703.94	2.41	0.16	0.54	706.60
4100.0	0.0	4100.0	0.0	0.0	329.0	0.0	497.9	106.1	706.50
1.26	0.00	12.46	0.00	0.000	0.035	0.000	0.000	696.00	244.00
0.011141	20.	20.	20.	2	0	0	0.00	60.00	304.00

$Q = (60)(3)(H)^{1.5}$

w/ SUB
2000 - 703.8
3000 703.9
3500 704.7
4100 706

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	L -BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	R -BANK ELEV
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

*SECNO 14828.000

3265 DIVIDED FLOW

3280 CROSS SECTION 14828.00 EXTENDED 0.12 FEET

3301 HV CHANGED MORE THAN HVINS

7185 MINIMUM SPECIFIC ENERGY
3720 CRITICAL DEPTH ASSUMED
SPILLWAY #3

14828.000	4.42	705.92	705.92	0.00	706.56	0.64	0.21	0.89	706.60
4100.0	152.0	2786.8	1161.2	136.4	375.7	320.2	498.3	106.4	706.60
1.26	1.11	7.42	3.63	0.038	0.035	0.038	0.000	701.50	0.00
0.004803	30.	30.	30.	4	15	0	0.00	823.81	1177.99

*SECNO 14980.000

3301 HV CHANGED MORE THAN HVINS

3302 WARNING: CONVEYANCE CHANGE OUTSIDE OF ACCEPTABLE RANGE, KRATIO = 24.27


3470 ENCROACHMENT STATIONS= 100.0 500.0 TYPE= 1 TARGET= 400.000
MANUFACTURED SECTION, BOTTOM BASED ON INVERTS OF THE BRIDGE SECTIONS

14980.000	14.87	706.87	0.00	0.00	706.88	0.01	0.00	0.32	704.00
4100.0	0.0	4100.0	0.0	0.0	5828.6	0.0	509.9	108.6	100000.00
1.32	0.00	0.70	0.00	0.000	0.035	0.000	0.000	692.00	100.00
0.000008	152.	152.	152.	2	0	0	0.00	400.00	500.00

CCHV= 0.300 CEHV= 0.500
*SECNO 15400.000

3470 ENCROACHMENT STATIONS= 200.0 620.0 TYPE= 1 TARGET= 420.000
MANUFACTURED SECTION, BOTTOM BASED ON INVERTS OF THE BRIDGE SECTIONS

15400.000	11.87	706.87	0.00	0.00	706.89	0.01	0.00	0.00	702.00
4100.0	0.0	4100.0	0.0	0.0	4917.3	0.0	561.7	112.5	100000.00
1.46	0.00	0.83	0.00	0.000	0.035	0.000	0.000	695.00	200.00
0.000015	420.	420.	420.	2	0	0	0.00	420.00	620.00



may be slightly high

$(89)(3)(H)^{1.5}$ 2000 705.3
3000 707

~706.5

w/sub

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	L-BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	R-BANK ELEV
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

*SECNO 15800.000

3302 WARNING: CONVEYANCE CHANGE OUTSIDE OF ACCEPTABLE RANGE, KRATIO = 0.65

3470 ENCROACHMENT STATIONS= 200.0 520.0 TYPE= 1 TARGET= 320.000
MANUFACTURED SECTION, BOTTOM BASED ON INVERTS OF THE BRIDGE SECTIONS

15800.000	10.88	706.88	0.00	0.00	706.90	0.02	0.01	0.01	704.00
4100.0	0.0	4100.0	0.0	0.0	3401.4	0.0	599.9	115.9	100000.00
1.55	0.00	1.21	0.00	0.000	0.035	0.000	0.000	696.00	200.00
0.000036	400.	400.	400.	0	0	0	0.00	320.00	520.00

CCHV= 0.500 CEHV= 1.000
*SECNO 16001.000

3301 HV CHANGED MORE THAN HVINS

3302 WARNING: CONVEYANCE CHANGE OUTSIDE OF ACCEPTABLE RANGE, KRATIO = 0.11

3470 ENCROACHMENT STATIONS= 250.0 318.0 TYPE= 1 TARGET= 68.000
D/S FACE OF NORTHVILLE RD. BRIDGE

16001.000	9.00	706.90	0.00	0.00	707.97	1.07	0.02	1.05	713.50
4100.0	0.0	4100.0	0.0	0.0	494.5	0.0	608.9	116.8	100000.00
1.56	0.00	8.29	0.00	0.000	0.035	0.000	0.000	697.90	250.00
0.003098	201.	201.	201.	1	0	0	0.00	68.00	318.00

SPECIAL BRIDGE

5070, VARIABLE ELCHU OR ELCHD ON SB CARD NOT SPECIFIED

SB	XK	XKOR	COFQ	RDLEN	BWC	BWP	BAREA	SS	ELCHU	ELCHD
	0.90	1.77	2.50	0.00	68.00	4.00	682.00	0.00	697.90	697.90

*SECNO 16063.000
CLASS A LOW FLOW

3420 BRIDGE W.S.= 706.79 BRIDGE VELOCITY= 7.21 CALCULATED CHANNEL AREA= 569.

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	L-BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	R-BANK ELEV
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

EGPRS	EGLWC	H3	QWEIR	QLOW	BAREA	TRAPEZOID AREA	ELLC	ELTRD	WEIRLN
0.00	708.09	0.17	0.	4100.	682.	781.	710.10	714.20	0.

3470 ENCROACHMENT STATIONS= 203.0 318.0 TYPE= 1 TARGET= 115.000

U/S FACE OF NORTHVILLE RD. BRIDGE

16063.000	9.17	707.07	0.00	0.00	708.09	1.02	0.12	0.00	713.50
4100.0	0.0	4100.0	0.0	0.0	506.5	0.0	609.6	116.9	100000.00
1.56	0.00	8.09	0.00	0.000	0.030	0.000	0.000	697.90	250.00
0.002113	62.	62.	62.	0	0	0	0.00	68.00	318.00

CCHV= 0.300 CEHV= 0.500

*SECNO 16113.000

16113.000	9.35	707.25	0.00	0.00	708.22	0.97	0.12	0.01	713.50
4100.0	0.0	4100.0	0.0	0.0	518.8	0.0	610.2	117.0	714.10
1.56	0.00	7.90	0.00	0.000	0.035	0.000	0.000	697.90	250.00
0.002673	50.	50.	50.	2	0	0	0.00	68.00	318.00

*SECNO 16764.000

16764.000	10.53	709.03	0.00	0.00	710.23	1.20	1.70	0.12	711.40
4100.0	0.0	4100.0	0.0	0.0	465.6	0.0	617.6	117.9	712.20
1.58	0.00	8.80	0.00	0.000	0.035	0.000	0.000	698.50	249.00
0.003184	651.	651.	651.	2	0	0	0.00	51.00	300.00

CCHV= 0.500 CEHV= 1.000

*SECNO 16864.000

3265 DIVIDED FLOW

3280 CROSS SECTION 16864.00 EXTENDED 0.22 FEET

D/S FACE OF E. HINES DRIVE BRIDGE (MIDDLE ROUGE PARKWAY)

16864.000	10.82	709.52	0.00	0.00	710.59	1.07	0.29	0.07	711.40
4100.0	26.6	4073.4	0.0	32.3	489.1	0.0	618.7	118.1	712.20
1.58	0.82	8.33	0.00	0.040	0.035	0.000	0.000	698.70	0.00
0.002718	100.	100.	100.	2	0	0	0.00	177.16	300.00

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	L-BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	R-BANK ELEV
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

SPECIAL BRIDGE

5070, VARIABLE ELCHU OR ELCHD ON SB CARD NOT SPECIFIED

SB	XK	XKOR	COFQ	RDLEN	BWC	BWP	BAREA	SS	ELCHU	ELCHD
	0.00	1.65	2.50	0.00	51.00	0.00	325.00	0.00	698.70	698.70

*SECNO 16900.000

3265 DIVIDED FLOW

3280 CROSS SECTION 16900.00 EXTENDED 1.43 FEET

3302 WARNING: CONVEYANCE CHANGE OUTSIDE OF ACCEPTABLE RANGE, KRATIO = 1.77

PRESSURE AND WEIR FLOW, Weir Submergence Based on TRAPEZOIDAL Shape

EGPRS	EGLWC	H3	QWEIR	QPR	BAREA	TRAPEZOID AREA	ELLC	ELTRD	WEIRLN
713.60	710.60	0.00	1302.	2804.	325.	479.	708.10	712.70	219.

U/S FACE OF E. HINES DRIVE BRIDGE (MIDDLE ROUGE PARKWAY)

16900.000	12.03	710.73	0.00	0.00	711.43	0.70	0.84	0.00	711.40
4100.0	267.2	3832.8	0.0	230.3	550.7	0.0	619.3	118.3	712.20
1.58	1.16	6.96	0.00	0.045	0.025	0.000	0.000	698.70	0.00
0.000867	36.	36.	36.	3	0	4	0.00	251.50	300.00

CCHV= 0.300 CEHV= 0.500
*SECNO 16950.000

3265 DIVIDED FLOW

3280 CROSS SECTION 16950.00 EXTENDED 1.72 FEET

16950.000	12.22	711.02	0.00	0.00	711.54	0.52	0.05	0.06	711.40
4100.0	600.4	3499.6	0.0	290.9	565.2	0.0	620.2	118.6	712.20
1.59	2.06	6.19	0.00	0.035	0.035	0.000	0.000	698.80	0.00
0.001314	50.	50.	50.	2	0	0	0.00	257.24	300.00

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	L-BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	R-BANK ELEV
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

*SECNO 18100.000
3280 CROSS SECTION 18100.00 EXTENDED 2.06 FEET

3302 WARNING: CONVEYANCE CHANGE OUTSIDE OF ACCEPTABLE RANGE, KRATIO = 2.74

18100.000	12.06	712.06	0.00	0.00	712.11	0.05	0.43	0.14	715.00
4100.0	0.0	1162.6	2937.4	0.0	563.0	1809.7	662.8	127.1	704.00
1.77	0.00	2.07	1.62	0.000	0.035	0.040	0.000	700.00	441.75
0.000175	1150.	1150.	1150.	2	0	0	0.00	388.25	830.00

*SECNO 19850.000

3301 HV CHANGED MORE THAN HVINS

3302 WARNING: CONVEYANCE CHANGE OUTSIDE OF ACCEPTABLE RANGE, KRATIO = 0.21

19850.000	9.84	712.44	0.00	0.00	713.42	0.98	0.84	0.47	726.40
4100.0	0.0	4100.0	0.0	0.0	515.1	0.0	720.8	136.9	728.00
1.83	0.00	7.96	0.00	0.000	0.035	0.000	0.000	702.60	257.03
0.004122	1750.	1750.	1750.	3	0	0	0.00	98.96	355.99

*SECNO 19851.000

3370 NORMAL BRIDGE, NRD= 5 MIN ELTRD= 726.40 MAX ELLC= 721.80

D/S FACE OF M-14 HWY. BRIDGE

19851.000	9.84	712.44	0.00	0.00	713.43	0.98	0.00	0.00	726.40
4100.0	0.0	4100.0	0.0	0.0	515.3	0.0	720.8	136.9	728.00
1.83	0.00	7.96	0.00	0.000	0.035	0.000	0.000	702.60	257.03
0.004118	1.	1.	1.	0	0	0	0.00	98.97	356.00

*SECNO 19932.000

3370 NORMAL BRIDGE, NRD= 5 MIN ELTRD= 726.40 MAX ELLC= 721.80

U/S FACE OF M-14 HWY. BRIDGE

19932.000	10.36	712.96	0.00	0.00	713.77	0.81	0.29	0.05	726.40
4100.0	0.0	4100.0	0.0	0.0	567.1	0.0	721.8	137.1	728.00
1.83	0.00	7.23	0.00	0.000	0.035	0.000	0.000	702.60	255.55
0.003109	81.	81.	81.	2	0	0	0.00	101.78	357.33

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	L-BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	R-BANK ELEV
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST
*SECNO 19933.000									
19933.000	10.36	712.96	0.00	0.00	713.77	0.81	0.00	0.00	726.40
4100.0	0.0	4100.0	0.0	0.0	567.3	0.0	721.7	137.1	728.00
1.83	0.00	7.23	0.00	0.000	0.035	0.000	0.000	702.60	255.55
0.003106	1.	1.	1.	0	0	0	0.00	101.79	357.34
CCHV= 0.500 CEHV= 1.000									
*SECNO 20033.000									
20033.000	10.81	713.41	0.00	0.00	714.11	0.69	0.28	0.06	726.40
4100.0	0.0	4100.0	0.0	0.0	614.2	0.0	723.2	137.3	728.00
1.84	0.00	6.68	0.00	0.000	0.035	0.000	0.000	702.60	254.24
0.002462	100.	100.	100.	2	0	0	0.00	104.27	358.52
CCHV= 0.300 CEHV= 0.500									
*SECNO 20300.000									
3280 CROSS SECTION 20300.00 EXTENDED 1.28 FEET									
3301 HV CHANGED MORE THAN HVINS									
3302 WARNING: CONVEYANCE CHANGE OUTSIDE OF ACCEPTABLE RANGE, KRATIO = 2.62									
20300.000	11.58	714.28	0.00	0.00	714.46	0.18	0.20	0.15	706.00
4100.0	681.1	1653.8	1765.1	298.1	430.2	535.3	729.0	138.4	706.00
1.86	2.28	3.84	3.30	0.030	0.035	0.030	0.000	702.70	0.00
0.000357	267.	267.	267.	2	0	0	0.00	230.00	230.00
CCHV= 0.500 CEHV= 1.000									
*SECNO 20470.000									
3265 DIVIDED FLOW									
3301 HV CHANGED MORE THAN HVINS									
3302 WARNING: CONVEYANCE CHANGE OUTSIDE OF ACCEPTABLE RANGE, KRATIO = 0.26									

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	L-BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	R-BANK ELEV
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

3470 ENCROACHMENT STATIONS= 125.0 400.0 TYPE= 1 TARGET= 275.000
D/S FACE OF BRIDGE AT ENTRANCE TO D.P.W.

20470.000	13.33	714.43	711.92	0.00	716.35	1.92	0.15	1.74	712.90
4100.0	156.7	3753.4	189.9	67.2	324.0	65.4	732.3	139.2	712.80
1.87	2.33	11.58	2.90	0.040	0.035	0.040	0.000	701.10	125.00
0.005221	170.	170.	170.	4	10	0	0.00	215.93	349.80

SPECIAL BRIDGE

5070: VARIABLE ELCHU OR ELCHD ON SB CARD NOT SPECIFIED

SB	XK	XKOR	COFQ	RDLEN	BWC	BWP	BAREA	SS	ELCHU	ELCHD
	1.05	1.76	2.50	0.00	28 00	2.60	218.00	0.00	701.10	701.10

*SECNO 20492.000
6870 D.S. ENERGY OF 716.35 IS HIGHER THAN COMPUTED ENERGY OF 715.37

3301 HV CHANGED MORE THAN HVINS

3302 WARNING: CONVEYANCE CHANGE OUTSIDE OF ACCEPTABLE RANGE, KRATIO = 1.74

PRESSURE AND WEIR FLOW, Weir Submergence Based on TRAPEZOIDAL Shape

EGPRS	EGLWC	H3	QWEIR	QPR	BAREA	TRAPEZOID AREA	ELLC	ELTRD	WEIRLN
724.10	717.06	0.71	2849.	1274.	218.	249.	710.90	712.90	369.

3470 ENCROACHMENT STATIONS= 31.0 295.0 TYPE= 1 TARGET= 264.000
U/S FACE OF BRIDGE AT ENTRANCE TO D.P.W.

20492.000	14.44	715.54	0.00	0.00	716.35	0.81	0.00	0.00	712.90
4100.0	1021.4	2985.5	93.1	444.2	358.6	39.4	732.6	139.3	712.80
1.87	2.30	8.33	2.36	0.045	0.030	0.045	0.000	701.10	31.00
0.001730	22.	22.	22.	2	0	4	0.00	264.00	295.00

CCHV= 0.300 CEHV= 0.500
*SECNO 20542.000

3470 ENCROACHMENT STATIONS= 143.0 382.0 TYPE= 1 TARGET= 239.000

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	L-BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	R-BANK ELEV
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST
20542.000	14.50	715.60	0.00	0.00	716.50	0.90	0.10	0.05	712.90
4100.0	521.6	3097.9	480.5	187.4	360.2	161.6	733.5	139.6	712.80
1.87	2.78	8.60	2.97	0.040	0.035	0.040	0.000	701.10	143.00
0.002498	50.	50.	50.	2	0	0	0.00	229.89	372.89

*SECNO 20750.000

3302 WARNING: CONVEYANCE CHANGE OUTSIDE OF ACCEPTABLE RANGE, KRATIO = 1.65

3470 ENCROACHMENT STATIONS= 245.0 355.0 TYPE= 1 TARGET= 110.000

20750.000	13.66	716.46	0.00	0.00	716.98	0.52	0.37	0.11	708.00
4100.0	649.9	3101.6	348.5	188.6	484.4	124.5	738.0	140.6	710.00
1.88	3.45	6.40	2.80	0.040	0.035	0.040	0.000	702.80	245.00
0.000917	258.	258.	258.	2	0	0	0.00	110.00	355.00

CCHV= 0.500 CEHV= 1.000

*SECNO 20850.000

20850.000	13.69	716.59	0.00	0.00	717.09	0.49	0.09	0.01	727.30
4100.0	0.0	4100.0	0.0	0.0	726.8	0.0	739.7	140.8	727.60
1.89	0.00	5.64	0.00	0.000	0.035	0.000	0.000	702.90	255.70
0.000940	100.	100.	100.	2	0	0	0.00	60.40	316.10

*SECNO 20851.000

3370 NORMAL BRIDGE, NRD= 13 MIN ELTRD= 725.50 MAX ELLC= 724.70

D/S FACE OF NORTHVILLE RD. BRIDGE

20851.000	13.69	716.59	0.00	0.00	717.19	0.60	0.00	0.10	727.30
4100.0	0.0	4100.0	0.0	0.0	660.2	0.0	739.8	140.8	727.60
1.89	0.00	6.21	0.00	0.000	0.025	0.000	0.000	702.90	255.70
0.000736	1.	1.	1.	0	0	0	-66.69	60.40	316.10

*SECNO 20885.000

3370 NORMAL BRIDGE, NRD= 13 MIN ELTRD= 725.50 MAX ELLC= 724.70

U/S FACE OF NORTHVILLE RD. BRIDGE

20885.000	13.72	716.62	0.00	0.00	717.22	0.60	0.02	0.00	727.30
4100.0	0.0	4100.0	0.0	0.0	661.5	0.0	740.3	140.9	727.60
1.89	0.00	6.20	0.00	0.000	0.025	0.000	0.000	702.90	255.70
0.000733	34.	34.	34.	0	0	0	-67.16	60.40	316.10

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	L-BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	R-BANK ELEV
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST
*SECNO 20886.000									
20886.000	13.90	716.80	0.00	0.00	717.28	0.48	0.00	0.06	727.30
4100.0	0.0	4100.0	0.0	0.0	739.5	0.0	740.3	140.9	727.60
1.89	0.00	5.54	0.00	0.000	0.035	0.000	0.000	702.90	255.70
0.000894	1.	1.	1.	2	0	0	0.00	60.40	316.10

THIS RUN EXECUTED 19OCT92 13:00:48

```
**************************************************
  HEC2 RELEASE DATED SEP 88 UPDATED JUN  1990

  ERROR CORR -  01,02,03,04
  MODIFICATION -
**************************************************
```

NOTE- ASTERISK (*) AT LEFT OF CROSS-SECTION NUMBER INDICATES MESSAGE IN SUMMARY OF ERRORS LIST

100-YEAR FLOOD

SUMMARY PRINTOUT TABLE 150

	SECNO	XLCH	ELTRD	ELLC	ELMIN	Q	CWSEL	CRIWS	EG	10*KS	VCH	AREA	.01K
	1000.000	0.00	0.00	0.00	655.00	4100.00	667.50	0.00	667.59	2.79	2.74	1791.13	2455.65
	1700.000	700.00	0.00	0.00	655.60	4100.00	667.69	0.00	667.78	2.53	2.64	1850.66	2577.24
*	2100.000	400.00	0.00	0.00	656.10	4100.00	667.88	0.00	668.26	11.08	4.95	828.41	1231.77
	2101.000	1.00	682.80	679.20	656.10	4100.00	667.98	0.00	668.29	13.89	5.13	799.37	1100.28
	2157.000	56.00	682.80	679.20	656.10	4100.00	667.97	0.00	668.37	13.37	5.06	810.13	1121.25
	2158.000	1.00	0.00	0.00	656.10	4100.00	668.01	0.00	668.38	10.46	4.85	844.88	1267.71
	2188.000	30.00	0.00	0.00	656.10	4100.00	668.05	0.00	668.41	10.30	4.83	849.27	1277.64
	2189.000	1.00	682.80	679.20	656.10	4100.00	668.04	0.00	668.43	12.97	5.01	818.84	1138.99
	2245.000	56.00	682.80	679.20	656.10	4100.00	668.12	0.00	668.50	12.63	4.96	826.68	1153.68
	2246.000	1.00	0.00	0.00	656.10	4100.00	668.16	0.00	668.51	9.83	4.75	862.96	1307.50
*	3000.000	754.00	0.00	0.00	657.00	4100.00	668.76	0.00	668.78	0.56	1.52	3452.77	5478.93
	4000.000	1000.00	0.00	0.00	658.00	4100.00	668.83	0.00	668.86	0.85	1.76	3186.31	4454.62
*	4800.000	800.00	0.00	0.00	658.00	4100.00	668.94	0.00	669.05	2.92	3.10	1624.95	2399.29
*	5075.000	275.00	0.00	0.00	658.00	4100.00	669.06	0.00	669.36	6.60	4.69	956.73	1595.81
*	5146.000	71.00	0.00	0.00	659.40	4100.00	669.15	0.00	670.17	35.15	8.10	506.24	691.92
	5147.000	1.00	675.30	677.80	659.40	4100.00	669.10	0.00	670.22	52.30	8.49	483.15	566.95
	5181.000	34.00	675.30	677.80	659.40	4100.00	669.40	0.00	670.42	45.90	8.11	505.81	605.18

	SECNO	XLCH	ELTRD	ELLC	ELMIN	Q	CWSEL	CRIWS	FG	10*KS	VCH	AREA	.01K
	5182.000	1.00	0.00	0.00	659.40	4100.00	669.61	0.00	670.49	28.30	7.54	543.91	770.72
*	5232.000	50.00	0.00	0.00	658.20	4100.00	670.67	0.00	670.88	5.00	3.94	1199.77	1833.33
*	5382.000	150.00	0.00	0.00	658.20	4100.00	670.95	0.00	670.99	1.38	2.11	2580.20	3489.49
	6000.000	618.00	0.00	0.00	658.20	4100.00	671.04	0.00	671.07	1.02	1.83	3075.27	4060.59
*	6183.000	183.00	0.00	0.00	658.20	4100.00	671.04	0.00	671.13	3.38	2.86	2041.73	2229.01
	6196.000	13.00	0.00	0.00	664.00	4100.00	671.08	0.00	671.14	2.11	0.00	2304.83	2823.73
*	6409.000	213.00	0.00	0.00	658.20	4100.00	671.15	0.00	671.18	0.99	1.56	3163.91	4127.10
*	7900.000	1491.00	0.00	0.00	662.00	4100.00	671.34	0.00	671.61	6.90	4.61	1250.50	1560.93
*	8201.000	301.00	0.00	0.00	663.00	4100.00	671.64	0.00	672.05	15.16	6.17	956.55	1052.96
*	8227.000	26.00	673.00	671.80	663.00	4100.00	672.64	0.00	672.92	4.82	5.31	1309.93	1868.16
*	8257.000	30.00	0.00	0.00	663.00	4100.00	672.71	0.00	672.95	10.61	4.95	1334.61	1258.86
*	9600.000	1343.00	0.00	0.00	666.00	4100.00	674.64	0.00	675.15	24.11	6.64	916.58	834.98
	10200.000	600.00	0.00	0.00	669.00	4100.00	676.46	0.00	677.21	39.16	8.41	861.83	650.21
	10500.000	300.00	0.00	0.00	670.20	4100.00	677.75	677.67	678.78	47.48	9.34	720.09	595.02
	10600.000	100.00	0.00	0.00	670.60	4100.00	678.22	678.12	679.31	48.07	9.47	691.50	591.37
*	10700.000	100.00	0.00	0.00	671.00	4100.00	679.58	0.00	679.96	20.42	6.36	1040.12	907.41
	10800.000	100.00	0.00	0.00	671.25	4100.00	679.80	0.00	680.28	24.24	6.92	918.34	832.81
*	10901.000	101.00	0.00	0.00	671.50	4100.00	680.18	679.95	681.48	63.68	9.91	561.28	513.78
*	10930.000	29.00	680.00	677.40	671.50	4100.00	684.54	0.00	684.71	3.42	4.08	1505.71	2216.09
	10980.000	50.00	0.00	0.00	671.50	4100.00	684.56	0.00	684.74	3.56	4.16	1460.15	2171.72
	11200.000	220.00	0.00	0.00	672.90	4100.00	684.67	0.00	685.08	6.84	5.17	792.67	1567.35
	11201.000	1.00	692.90	692.50	672.90	4100.00	684.67	0.00	685.44	10.06	7.05	581.41	1292.42
	11255.000	54.00	692.90	692.50	672.90	4100.00	684.73	0.00	685.50	9.96	7.02	583.87	1299.43
	11256.000	1.00	0.00	0.00	672.90	4100.00	685.35	0.00	685.70	7.44	4.77	858.86	1503.55
	11356.000	100.00	0.00	0.00	673.10	4100.00	685.42	0.00	685.79	7.74	4.84	846.63	1473.62
	12150.000	794.00	0.00	0.00	675.00	4100.00	686.06	0.00	686.38	6.81	4.53	905.74	1570.64

	SECNO	XLCH	ELTRD	ELLC	ELMIN	Q	CWSEL	CRIWS	EG	10*KS	VCH	AREA	.01K
*	12850.000	700.00	0.00	0.00	671.50	4100.00	686.98	0.00	688.03	35.50	8.24	497.76	608.11
	13000.000	150.00	0.00	0.00	678.70	4100.00	687.50	0.00	688.64	33.54	8.59	477.05	707.93
	13001.000	1.00	732.30	699.10	678.70	4100.00	687.50	0.00	688.94	37.97	9.62	426.11	665.39
	13135.000	134.00	732.30	699.10	678.70	4100.00	688.30	0.00	689.50	29.57	8.81	465.31	753.94
	13136.000	1.00	0.00	0.00	678.70	4100.00	688.82	0.00	689.68	21.68	7.43	551.60	880.49
	13236.000	100.00	0.00	0.00	679.40	4100.00	689.05	0.00	690.00	25.14	7.81	525.00	817.72
*	13800.000	564.00	0.00	0.00	683.50	4100.00	690.78	0.00	690.98	8.37	4.51	1215.21	1417.65
*	14400.000	600.00	0.00	0.00	688.30	4100.00	695.81	695.81	697.45	60.03	11.07	473.68	529.19
	14600.000	200.00	0.00	0.00	689.90	4100.00	697.19	0.00	699.35	78.64	11.81	347.09	462.35
*	14601.000	1.00	703.60	703.60	689.90	4100.00	697.19	0.00	699.65	189.11	12.59	325.73	298.14
*	14776.000	175.00	703.60	703.60	689.90	4100.00	701.12	0.00	702.15	63.61	8.16	502.46	514.08
*	14777.000	1.00	0.00	0.00	689.90	4100.00	701.37	0.00	702.24	20.29	7.48	548.06	910.39
*	14778.000	1.00	0.00	0.00	693.50	4100.00	701.37	0.00	703.24	62.65	10.97	373.71	518.00
	14798.000	20.00	0.00	0.00	696.00	4100.00	701.53	0.00	703.94	111.41	12.46	329.03	388.44
*	14828.000	30.00	0.00	0.00	701.50	4100.00	705.92	705.92	706.56	48.03	7.42	832.27	591.61
*	14980.000	152.00	0.00	0.00	692.00	4100.00	706.87	0.00	706.88	0.08	0.70	5828.63	14361.07
	15400.000	420.00	0.00	0.00	695.00	4100.00	706.87	0.00	706.89	0.15	0.83	4917.33	10530.15
*	15800.000	400.00	0.00	0.00	696.00	4100.00	706.88	0.00	706.90	0.36	1.21	3401.35	6821.22
*	16001.000	201.00	0.00	0.00	697.90	4100.00	706.70	0.00	707.97	30.98	8.29	494.46	736.59
	16063.000	62.00	714.20	710.10	697.90	4100.00	707.07	0.00	708.09	21.13	8.09	506.54	891.84
	16113.000	50.00	0.00	0.00	697.90	4100.00	707.25	0.00	708.22	26.73	7.90	518.81	793.01
	16764.000	651.00	0.00	0.00	698.50	4100.00	709.03	0.00	710.23	31.84	8.80	465.65	726.64
	16864.000	100.00	0.00	0.00	698.70	4100.00	709.52	0.00	710.59	27.18	8.33	521.47	786.41
*	16900.000	36.00	712.70	708.10	698.70	4100.00	710.73	0.00	711.43	8.67	6.96	781.00	1392.58
	16950.000	50.00	0.00	0.00	698.80	4100.00	711.02	0.00	711.54	13.14	6.19	856.04	1131.12
*	18100.000	1150.00	0.00	0.00	700.00	4100.00	712.06	0.00	712.11	1.75	2.07	2372.70	3098.41

	SECNO	XLCH	ELTRD	ELLC	ELMIN	Q	CWSEL	CRIWS	FG	10*KS	VCH	AREA	.01K
*	19850.000	1750.00	0.00	0.00	702.60	4100.00	712.44	0.00	713.42	41.22	7.96	515.14	638.57
	19851.000	1.00	726.40	721.80	702.60	4100.00	712.44	0.00	713.43	41.18	7.96	515.37	638.89
	19932.000	81.00	726.40	721.80	702.60	4100.00	712.96	0.00	713.77	31.09	7.23	567.09	795.26
	19933.000	1.00	0.00	0.00	702.60	4100.00	712.96	0.00	713.77	31.06	7.23	567.27	795.51
	20033.000	100.00	0.00	0.00	702.60	4100.00	713.41	0.00	714.11	24.62	6.68	614.23	826.22
*	20300.000	267.00	0.00	0.00	702.70	4100.00	714.28	0.00	714.46	3.57	3.84	1263.59	2168.54
*	20470.000	170.00	0.00	0.00	701.10	4100.00	714.43	711.92	716.35	52.21	11.58	456.63	567.45
*	20492.000	22.00	712.90	710.90	701.10	4100.00	715.54	0.00	716.35	17.30	8.33	842.21	985.65
	20542.000	50.00	0.00	0.00	701.10	4100.00	715.60	0.00	716.50	24.98	8.60	709.16	820.32
*	20750.000	258.00	0.00	0.00	702.80	4100.00	716.46	0.00	716.98	9.17	6.40	797.56	1354.07
	20850.000	100.00	0.00	0.00	702.90	4100.00	716.59	0.00	717.09	9.40	5.64	726.85	1336.93
	20851.000	1.00	725.50	724.70	702.90	4100.00	716.59	0.00	717.19	7.36	6.21	660.22	1511.07
	20885.000	34.00	725.50	724.70	702.90	4100.00	716.62	0.00	717.22	7.33	6.20	661.46	1514.78
	20886.000	1.00	0.00	0.00	702.90	4100.00	716.80	0.00	717.28	8.94	5.54	739.48	1371.13

100-YEAR FLOOD

SUMMARY PRINTOUT TABLE 150

	SECNO	Q	CWSEL	DIFWSP	DIFWSX	DIFKWS	TOPWID	XLCH
	1000.000	4100.00	667.50	0.00	0.00	0.00	329.50	0.00
	1700.000	4100.00	667.69	0.00	0.19	0.00	329.93	700.00
*	2100.000	4100.00	667.88	0.00	0.19	0.00	122.15	400.00
	2101.000	4100.00	667.88	0.00	0.00	0.00	122.15	1.00
	2157.000	4100.00	667.97	0.00	0.09	0.00	122.64	56.00
	2158.000	4100.00	668.01	0.00	0.04	0.00	122.87	1.00
	2188.000	4100.00	668.05	0.00	0.04	0.00	123.06	30.00
	2189.000	4100.00	668.04	0.00	-0.01	0.00	123.03	1.00
	2245.000	4100.00	668.12	0.00	0.08	0.00	123.39	56.00
	2246.000	4100.00	668.16	0.00	0.04	0.00	123.66	1.00
*	3000.000	4100.00	668.76	0.00	0.60	0.00	551.41	754.00
	4000.000	4100.00	668.83	0.00	0.07	0.00	589.47	1000.00
*	4800.000	4100.00	668.94	0.00	0.11	0.00	256.00	800.00
*	5075.000	4100.00	669.06	0.00	0.12	0.00	118.00	275.00
*	5146.000	4100.00	669.15	0.00	0.09	0.00	81.18	71.00
	5147.000	4100.00	669.10	0.00	-0.05	0.00	80.00	1.00
	5181.000	4100.00	669.40	0.00	0.29	0.00	80.00	34.00
	5182.000	4100.00	669.61	0.00	0.21	0.00	82.07	1.00
*	5232.000	4100.00	670.67	0.00	1.07	0.00	183.00	50.00
*	5382.000	4100.00	670.95	0.00	0.27	0.00	483.00	150.00
	6000.000	4100.00	671.04	0.00	0.09	0.00	665.35	618.00
*	6183.000	4100.00	671.04	0.00	0.01	0.00	644.70	183.00
	6196.000	4100.00	671.08	0.00	0.04	0.00	643.85	13.00
*	6409.000	4100.00	671.15	0.00	0.06	0.00	660.14	213.00

	SECNO	Q	CWSEL	DIFWSP	DIFWSX	DIFKWS	TOPWID	XLCH
*	7900.000	4100.00	671.34	0.00	0.19	0.00	442.78	1491.00
*	8201.000	4100.00	671.64	0.00	0.30	0.00	342.17	301.00
*	8227.000	4100.00	672.64	0.00	1.01	0.00	358.32	26.00
*	8257.000	4100.00	672.71	0.00	0.07	0.00	359.42	30.00
*	9600.000	4100.00	674.64	0.00	1.92	0.00	383.65	1343.00
	10200.000	4100.00	676.46	0.00	1.82	0.00	412.27	600.00
	10500.000	4100.00	677.75	0.00	1.29	0.00	337.73	300.00
	10600.000	4100.00	678.22	0.00	0.48	0.00	313.12	100.00
*	10700.000	4100.00	679.58	0.00	1.36	0.00	277.70	100.00
	10800.000	4100.00	679.80	0.00	0.22	0.00	230.00	100.00
*	10901.000	4100.00	680.18	0.00	0.37	0.00	233.00	101.00
*	10930.000	4100.00	684.54	0.00	4.37	0.00	220.00	29.00
	10980.000	4100.00	684.56	0.00	0.02	0.00	211.00	50.00
	11200.000	4100.00	684.67	0.00	0.11	0.00	94.81	220.00
	11201.000	4100.00	684.67	0.00	0.00	0.00	94.81	1.00
	11255.000	4100.00	684.73	0.00	0.06	0.00	95.04	54.00
	11256.000	4100.00	685.35	0.00	0.62	0.00	97.69	1.00
	11356.000	4100.00	685.42	0.00	0.07	0.00	97.16	100.00
	12150.000	4100.00	686.06	0.00	0.64	0.00	100.00	794.00
*	12850.000	4100.00	686.98	0.00	0.92	0.00	56.00	700.00
	13000.000	4100.00	687.50	0.00	0.52	0.00	56.00	150.00
	13001.000	4100.00	687.50	0.00	0.00	0.00	56.00	1.00
	13135.000	4100.00	688.30	0.00	0.80	0.00	56.00	134.00
	13136.000	4100.00	688.82	0.00	0.52	0.00	56.00	1.00
	13236.000	4100.00	689.05	0.00	0.23	0.00	56.00	100.00
*	13800.000	4100.00	690.78	0.00	1.73	0.00	256.00	564.00

	SECNO	Q	CWSEL	DIFWSP	DIFWSX	DIFKWS	TOPWID	XLCH
*	14400.000	4100.00	695.81	0.00	5.03	0.00	148.00	600.00
	14600.000	4100.00	697.18	0.00	1.37	0.00	48.00	200.00
*	14601.000	4100.00	697.19	0.00	0.01	0.00	48.00	1.00
*	14776.000	4100.00	701.12	0.00	3.92	0.00	48.00	175.00
*	14777.000	4100.00	701.37	0.00	0.25	0.00	48.00	1.00
*	14778.000	4100.00	701.37	0.00	0.00	0.00	48.00	1.00
	14798.000	4100.00	701.53	0.00	0.16	0.00	60.00	20.00
*	14828.000	4100.00	705.92	0.00	4.39	0.00	323.81	30.00
*	14980.000	4100.00	706.87	0.00	0.95	0.00	400.00	152.00
	15400.000	4100.00	706.87	0.00	0.00	0.00	420.00	420.00
*	15800.000	4100.00	706.88	0.00	0.00	0.00	320.00	400.00
*	16001.000	4100.00	706.90	0.00	0.02	0.00	68.00	201.00
	16063.000	4100.00	707.07	0.00	0.17	0.00	68.00	62.00
	16113.000	4100.00	707.25	0.00	0.18	0.00	68.00	50.00
	16764.000	4100.00	709.03	0.00	1.78	0.00	51.00	651.00
	16864.000	4100.00	709.52	0.00	0.49	0.00	177.16	100.00
*	16900.000	4100.00	710.73	0.00	1.20	0.00	251.50	36.00
	16950.000	4100.00	711.02	0.00	0.30	0.00	257.24	50.00
*	18100.000	4100.00	712.06	0.00	1.04	0.00	388.25	1150.00
*	19850.000	4100.00	712.44	0.00	0.37	0.00	98.96	1750.00
	19851.000	4100.00	712.44	0.00	0.00	0.00	98.97	1.00
	19932.000	4100.00	712.96	0.00	0.51	0.00	101.78	81.00
	19933.000	4100.00	712.96	0.00	0.00	0.00	101.79	1.00
	20033.000	4100.00	713.41	0.00	0.45	0.00	104.27	100.00
*	20300.000	4100.00	714.28	0.00	0.87	0.00	230.00	267.00
*	20470.000	4100.00	714.43	0.00	0.15	0.00	215.93	170.00

	SECNO	Q	CWSEL	DIFWSP	DIFWSX	DIFKWS	TOPWID	XLCH
*	20492.000	4100.00	715.54	0.00	1.11	0.00	264.00	22.00
	20542.000	4100.00	715.60	0.00	0.06	0.00	229.89	50.00
*	20750.000	4100.00	716.46	0.00	0.86	0.00	110.00	258.00
	20850.000	4100.00	716.59	0.00	0.13	0.00	60.40	100.00
	20851.000	4100.00	716.59	0.00	0.00	0.00	60.40	1.00
	20885.000	4100.00	716.62	0.00	0.03	0.00	60.40	34.00
	20886.000	4100.00	716.80	0.00	0.18	0.00	60.40	1.00

SUMMARY OF ERRORS AND SPECIAL NOTES

WARNING SECNO= 2100.000 PROFILE= 1 CONVEYANCE CHANGE OUTSIDE ACCEPTABLE RANGE
WARNING SECNO= 3000.000 PROFILE= 1 CONVEYANCE CHANGE OUTSIDE ACCEPTABLE RANGE
WARNING SECNO= 4800.000 PROFILE= 1 CONVEYANCE CHANGE OUTSIDE ACCEPTABLE RANGE
WARNING SECNO= 5075.000 PROFILE= 1 CONVEYANCE CHANGE OUTSIDE ACCEPTABLE RANGE
WARNING SECNO= 5146.000 PROFILE= 1 CONVEYANCE CHANGE OUTSIDE ACCEPTABLE RANGE
WARNING SECNO= 5232.000 PROFILE= 1 CONVEYANCE CHANGE OUTSIDE ACCEPTABLE RANGE
WARNING SECNO= 5382.000 PROFILE= 1 CONVEYANCE CHANGE OUTSIDE ACCEPTABLE RANGE
WARNING SECNO= 6183.000 PROFILE= 1 CONVEYANCE CHANGE OUTSIDE ACCEPTABLE RANGE
WARNING SECNO= 6409.000 PROFILE= 1 CONVEYANCE CHANGE OUTSIDE ACCEPTABLE RANGE
WARNING SECNO= 7900.000 PROFILE= 1 CONVEYANCE CHANGE OUTSIDE ACCEPTABLE RANGE
WARNING SECNO= 8201.000 PROFILE= 1 CONVEYANCE CHANGE OUTSIDE ACCEPTABLE RANGE
WARNING SECNO= 8227.000 PROFILE= 1 CONVEYANCE CHANGE OUTSIDE ACCEPTABLE RANGE
WARNING SECNO= 8257.000 PROFILE= 1 CONVEYANCE CHANGE OUTSIDE ACCEPTABLE RANGE
WARNING SECNO= 9600.000 PROFILE= 1 CONVEYANCE CHANGE OUTSIDE ACCEPTABLE RANGE
WARNING SECNO= 10700.000 PROFILE= 1 CONVEYANCE CHANGE OUTSIDE ACCEPTABLE RANGE
WARNING SECNO= 10901.000 PROFILE= 1 CONVEYANCE CHANGE OUTSIDE ACCEPTABLE RANGE
WARNING SECNO= 10930.000 PROFILE= 1 CONVEYANCE CHANGE OUTSIDE ACCEPTABLE RANGE
WARNING SECNO= 12850.000 PROFILE= 1 CONVEYANCE CHANGE OUTSIDE ACCEPTABLE RANGE
WARNING SECNO= 13800.000 PROFILE= 1 CONVEYANCE CHANGE OUTSIDE ACCEPTABLE RANGE
CAUTION SECNO= 14400.000 PROFILE= 1 CRITICAL DEPTH ASSUMED
CAUTION SECNO= 14400.000 PROFILE= 1 MINIMUM SPECIFIC ENERGY
WARNING SECNO= 14601.000 PROFILE= 1 CONVEYANCE CHANGE OUTSIDE ACCEPTABLE RANGE
WARNING SECNO= 14776.000 PROFILE= 1 CONVEYANCE CHANGE OUTSIDE ACCEPTABLE RANGE
WARNING SECNO= 14777.000 PROFILE= 1 CONVEYANCE CHANGE OUTSIDE ACCEPTABLE RANGE
WARNING SECNO= 14778.000 PROFILE= 1 CONVEYANCE CHANGE OUTSIDE ACCEPTABLE RANGE
CAUTION SECNO= 14828.000 PROFILE= 1 CRITICAL DEPTH ASSUMED
CAUTION SECNO= 14828.000 PROFILE= 1 MINIMUM SPECIFIC ENERGY

WARNING SECNO= 14980.000 PROFILE= 1 CONVEYANCE CHANGE OUTSIDE ACCEPTABLE RANGE

WARNING SECNO= 15800.000 PROFILE= 1 CONVEYANCE CHANGE OUTSIDE ACCEPTABLE RANGE

WARNING SECNO= 16001.000 PROFILE= 1 CONVEYANCE CHANGE OUTSIDE ACCEPTABLE RANGE

WARNING SECNO= 16900.000 PROFILE= 1 CONVEYANCE CHANGE OUTSIDE ACCEPTABLE RANGE

WARNING SECNO= 18100.000 PROFILE= 1 CONVEYANCE CHANGE OUTSIDE ACCEPTABLE RANGE

WARNING SECNO= 19850.000 PROFILE= 1 CONVEYANCE CHANGE OUTSIDE ACCEPTABLE RANGE

WARNING SECNO= 20300.000 PROFILE= 1 CONVEYANCE CHANGE OUTSIDE ACCEPTABLE RANGE

WARNING SECNO= 20470.000 PROFILE= 1 CONVEYANCE CHANGE OUTSIDE ACCEPTABLE RANGE

WARNING SECNO= 20492.000 PROFILE= 1 CONVEYANCE CHANGE OUTSIDE ACCEPTABLE RANGE

WARNING SECNO= 20750.000 PROFILE= 1 CONVEYANCE CHANGE OUTSIDE ACCEPTABLE RANGE

00BREAK00

1) COUNTY: Wayne

2) STUDY NAME: City of Plymouth and Plymouth Twp.

3) WATERCOURSE: Middle River Rouge

4) DOCUMENT TYPE: Report

00BREAK00

City of Plymouth and Plymouth Township, Michigan, FIS
Limited Map Maintenance Program
Hydraulic and Hydrologic Background Information

The Limited Map Maintenance Program (LMMP) for the City of Plymouth and Plymouth Township, Michigan covers the Middle River Rouge from the downstream corporate limit to the upstream corporate limit. The study was performed to verify the validity of the discharges used in the existing FIS, due to additional years of gage data and so to redefine the flood profile for the indicated reach of the river. This study was limited to only the 100-year flood. At the time of the original study, the Middle River Rouge was studied by approximate methods.

A discharge-frequency analysis of the Middle River Rouge was based on peak annual flows obtained from a U.S. Geological Survey gage located on the Middle River Rouge at Inkster Road near Garden City, Michigan (USGS gage #167000). The Inkster Road gage is about 7.5 miles downstream of the study limit.

Flows on the Middle River Rouge have been published from 1931 through 1933 and then for the period of 1948-1990. The period of record from 1934 through 1947 for the Inkster Road gage was then extended by correlation with the systematic records for the Rouge River at the Plymouth Road gage at Detroit. A discharge relationship was developed for these two gages using coincidental flows and the computer program #704-G1-L2020, which is based on the criteria described in the Hydrologic Engineering Center, Multiple Linear Regression. Then a gage analysis was performed on the data for the Inkster Road gage on the Middle River Rouge, using the period of record, 1931-1990. The HECWRC computer program, which is based on the criteria described in the U.S. Water Resources Council Bulletin #17B, Guidelines for Determining Flood Flow Frequency, was used to determine the existing relationship. A generalized skew of -0.05, taken from the Detroit District's generalized skew was determined to be 0.32. A 100-year discharge of 3,320 cfs was computed for this gage.

A second discharge-frequency analysis was performed using the Michigan Department of Natural Resources' (MDNR's) generalized skew of 0.55 and the mean square error of the generalized skew of 0.32. The 100-year discharge for this trial was computed to be 3,530 cfs. The 90% confidence interval for this run ranges from 2,960 cfs to 4,440 cfs.

The MDNR had expressed concern that the flow should remain unchanged from the value of 4,100 cfs used in the existing FIS. Flood discharges for the Middle River Rouge within the City of Plymouth were obtained from data contained in the Flood Insurance Studies for the City of Novi, the City of Northville, and the Township of Northville. The flow of 4,100 cfs developed upstream of Phoenix Lake at Northville Township, about 3,000 feet upstream

from the City of Plymouth, would be carried through the City of Plymouth as recommended by MDNR. This flood discharge is consistent with urbanization of this watershed. Further record was obtained from the MDNR concerning the flood of the 1940's, which was estimated in 1970's to be 4,100 cfs. Since this value is within the 90% confidence interval of this flow, the 100-year discharge of 4,100 cfs will be used in the study area.

As part of this study a field survey was made in March 1992. The survey only collected data at bridge sections and the Wilcox Dam. All bridges were field measured to obtain elevation data and structural geometry. Valley sections were estimated using a new two-foot topographic map developed for the U.S. Army Corps of Engineers, Detroit District from aerial photography flown in March 1992.

Channel and overbank roughness factors (Manning's "n") used in the hydraulic computations were chosen by engineering judgment and were based on field observations.

The starting water surface elevation was determined based on information included in the National Dam Safety Program Inspection Report for Middle River Rouge Basin, Newburgh Dam.

Water surface elevations were computed using the Corps' HEC-2 step-backwater computer program. The HEC-2 model for this study began at the upstream side of Newburgh Lake and was continued to the upstream side of Northville Road, near the downstream side of Phoenix Lake. The E. Hines Drive bridge located upstream of Haggerty Road was modeled as a regular cross section. Since the bridge is oriented parallel to general direction of flow in the floodplain, there is minimal head loss in the general vicinity of the bridge. The floodway run is not included as part of this study.


The City of Livonia borders the Plymouth Township at the downstream corporate limit. Within the City of Livonia, the Middle River Rouge has unnumbered A zones. Northville Township borders Plymouth Township at the upstream Plymouth Township corporate limit. Detailed studies were performed on the Middle River Rouge in Northville Township. In both cases, this study is compatible with the adjoining studies.

The work map used for this study is a new two-foot topographic map developed from aerial photography flown in March 1992. The flood plain delineation for the Middle River Rouge was supplemented over the entire study area by use of the two-foot contour map and then it was electronically transferred to the MDNR base maps in GIS design files. In addition, the existing flood plain and applicable floodway delineations, as shown on the existing FIS panels, for 1.5 miles of the Tonquish Creek and 1.0 mile of the South Branch Tonquish Creek were electronically transferred to the MDNR base map.


The final work map is being submitted in two forms. One paper reference map is being provided, covering both communities, for a general overview of the study area. The actual work map is being supplied in digital format as specified by the contract for this work. Again, only one map is being submitted. For elevation reference marks, the original numbers were maintained for the existing reference marks and new numbers were assigned for the new elevation reference marks. However, to distinguish between elevavation reference marks in the City of Plymouth, Plymouth Township or new reference marks, the letter C for the city; letter T for township and letter N for new were placed by the numbers.

A new flood profile is also being provided. Only one profile is being submitted covering both communities, the City of Plymouth and Plymouth Township. A new Floodway Data Table is not being provided. Also being provided is the HEC-2 output for the 100-year profile. The HEC-2 run has been approved by the MDNR.

DIETZGEN CORPORATION
MADE IN U.S.A.



DIETZGEN CORPORATION
MADE IN U.S.A.
10 X 10 PER INCH



DEPARTMENT OF THE ARMY
DETROIT DISTRICT, CORPS OF ENGINEERS
BOX 1027
DETROIT, MICHIGAN 48231-1027

IN REPLY REFER TO

Great Lakes Hydraulics and Hydrology Branch

RECEIVED
OCT 20 1992
NATURAL RESOURCES
LAND & WATER MGMT.

Mr. Bruce Menerey, P.E.
Technical Programs
Land and Water Management Division
Michigan Department of Natural Resources
P.O. Box 30028
Lansing, Michigan 48909

Dear Mr. Menerey:

In response to your review comments dated October 12, 1992, on the Limited Map Maintenance Program for the Middle Rouge River within the City of Plymouth and Plymouth Township, we have revised the hydraulics accordingly. The enclosed HEC-2 computer run incorporates your comments as follows:

1. For XSEC 2100 - 2245, I-275 bridges, the model has been corrected by recoding the BT cards.

2. For XSEC 13136 - 14600, the reach length was corrected at XSEC 14600 and the invert elevations were interpolated for XSEC 13800 and 14400.

3. For XSEC 14601 - 14980, Wilcox Lake Dam was remodeled based on the plan drawing of the E. Hines Drive and Wilcox Road bridge, and dam, provided by the Wayne County Road Commission, and the two-foot topographic map.

4. For XSEC 16113 - 19850, the new survey was made for two missing bridges - the Middle Rouge Parkway bridge and the unnamed bridge. These two bridges were included in the analysis.

If you have any further comments or questions regarding the enclosed data, please contact Ms. Hanna Kobylinski as soon as possible at (313) 226-4761.

Sincerely,

Ronald E. Wilshaw, P.E.
Chief, G.L. Hydraulics and
Hydrology Branch

Enclosure

Great Lakes Hydraulics and Hydrology Branch

Mr. Bruce Menerey, P.E.
Technical Programs
Land and Water Management Division
Michigan Department of Natural Resources
P.O. Box 30028
Lansing, Michigan 48909

Dear Mr. Menerey:

In response to your review comments dated October 12, 1992, on the Limited Map Maintenance Program for the Middle Rouge River within the City of Plymouth and Plymouth Township, we have revised the hydraulics accordingly. The enclosed HEC-2 computer run incorporates your comments as follows:

1. For XSEC 2100 - 2245, I-275 bridges, the model has been corrected by recoding the BT cards.

2. For XSEC 13136 - 14600, the reach length was corrected at XSEC 14600 and the invert elevations were interpolated for XSEC 13800 and 14400.

3. For XSEC 14601 - 14980, Wilcox Lake Dam was remodeled based on the plan drawing of the E. Hines Drive and Wilcox Road bridge, and dam, provided by the Wayne County Road Commission, and the two-foot topographic map.


4. For XSEC 16113 - 19850, the new survey was made for two missing bridges - the Middle Rouge Parkway bridge and the unnamed bridge. These two bridges were included in the analysis.

If you have any further comments or questions regarding the enclosed data, please contact Ms. Hanna Kobylinski as soon as possible at (313) 226-4761.

Sincerely,

Ronald E. Wilshaw, P.E.
Chief, G.L. Hydraulics and
Hydrology Branch

Enclosure


PLYMOUTH
Plymouth State Home and Training Sch
St John Seminary
Plymouth Ch
Epiphany Ch
Tanger Sch
St Lukes Ch
Holy Trinity Ch
Fuland Sch
Wilcox Lake
Phoenix Lake
Newburgh Lake
Ann Arbor Trail
Plymouth-Riverside Park
Riverside Cemetery
Kellogg Park
Hough Park
Starkweather Sch
High Sch
Our Lady of Good Counsel Sch
Ashburn Playground
Smith Sch
Allen Sch
Jr High Sch
Playground
Park
Picnic Area
Castle Gardens Park
Randolph Sch
Webster Sch
Ladywood High Sch
Madonna College
St Edith Sch
Holmes Jr High Sch
Sybsta
Gun Branch
Rouge River
Middle Rouge
Lower Rouge
Tonquish Creek
Pere Marquette Rwy
Conrail
Penn Central
Ann Arbor RR
Detroit Edison
Corp
Storage Tks
Bridge
Ann Arbor
Plymouth
Ann Arbor Trail
Ann Arbor Rd
Schoolcraft
Newburgh
Lake
Middle
Rouge
Johnson
Washington
Sheldon
Rouge
Hilltop
Road
Corporate
Lancaster
Sussex St
Sherwood
Roycroft
5 Mile
Elsie
Ross
Lyndon
Mason
Livonia
Knolson
Hix
Skiles
Blue
Newburgh
Levan
Eckles
Chesapeake
Amrhein
Wilcox
Gilbert
Morgan
Hagberty
Terry
Bird
Corp
Ann Arbor
Junction
Farmer
Arthur
Adams
York
Union
Penniman
Pk St
Wing
Linden
Palmer
Burroughs
Ross
Byron
Marion
Hill
Old Arbor
Southworth
Hines Dr
Riverside Park
Elmwood
Edward
Gilbert
Morgan
Hagberty
Terry
Bird
Corp
Ann Arbor
Schoolcraft
Chesapeake
Amrhein
Wilcox
Newburgh
Lake
Middle
Rouge
Johnson
Washington
BM 745
BM 716
BM 712
BM 675
BM 681
B1
B2
B3
B4
B5
B6
B7
B8
B9
B10
B11
B12
#14
#19
(3)
(9)
(14)
(31)
(32)
?
BRIDGE
BRIDGE TO CONRAIL
B1 B2
B2 B3
B3 B4
B4 B5
B5 B6
B6 B7
B7 B8
B8 B9
B9 B10
B10 B11
B11 B12
B12 B1

PLYMOUTH MICH.

MIDDLE ROUGE RIV.

OCT. 15, 1992

T. ROZNOWSKI

K DRAKE

AUTO LEVEL ZIESS Ni. 2

DESCRIPTIONS

BM 82A

A BRASS DISC STAMPED W.C.R.C. BM LOCATED ON THE N.E. CORNER OF BRIDGE ON E. END OF SIDE-WALK ON U/S SIDE OF BRIDGE OVER MIDDLE ROUGE RIVER ON EDWARD HINES DR.

ELEV. 710.67

TBM "FL 2-3"

CHISELED □ ON TOP OF N. END OF CONC. WALL ON E. SIDE OF BRIDGE, BRIDGE IS LOCATED ON NORTHVILLE Rd. OVER MIDDLE ROUGE RIV. S. OF THE INTER. OF NORTHVILLE Rd & HINES DR. N. of W.C.R.C. PHOENIX YARD. ELEV. 730.22

TBM D.P.W. (Pg-8)

A CHISELED □ ON N.W. CORNER of BRIDGE ON N.W. CORNER of CONC. RAILING U/S SIDE, AT ENTRANCE TO W.C.R.C. D.P.W. HINES DR. (SET BY OTHERS)

ELEV. 715.34

EDWARD HINES DR

BRIDGE & RD SECTION

82A

BM B2A				710.67		BRASS DISK ON N.E. US SIDE OF BRIDGE ON BINES DR OVER MIDDLE Rouge RIVER.
	6.93	717.60				ROAD SECTION
	DIST	Rod	ELEV.			DESCRIPTION
	0'	5.41	712.19			TOP & Rd AT BTM ABUT & ARCH
	25' RT	4.90	712.70			& R
	50' RT	4.27	713.33			
	75' RT	3.67	713.93			
	100' RT	2.88	714.72			
	125' RT	2.08	715.52			
	150' RT	1.06	716.54			
	175' RT	0.02	717.58			
						Rd CONT. TO RISE 4'± NEXT 200'
	51' LT	6.20	711.40			TOP & Rd @ BTM ABUT & ARCH.
	75' LT	5.56	712.04			& R⊥ BINES DR.
	100' LT	6.87	710.73			
	125' LT	7.30	710.30			
	150' LT	7.70	709.90			
	175 LT	8.09	709.51			
	200' LT	8.31	709.29			
✓ KD						

	+	HI	-	ELEV.						
		717.60								
	DIST	Rod	ELEV			DESCRIPTION				
	225' LT	8.42	709.18			℄ Rd		HINES DR.		
	250' LT	8.42	709.18			"				
	275' LT	8.39	709.21			"				
	300' LT	8.26	709.34			"				
						Rd. CONT. TO RISE NEXT 100'				


V
K D


	+	HI	−	ELEV		DESCRIPTION
		717.60				
	DIST	Rod	ELEV			
	0'	16.1	701.5	ON CONC.		BTM ARCH & BTM ABUT. (IN WATER) & BTM CONC. BNK
	6.5' RT	14.0	703.6			TOP CONC. BNK
	3.0' RT	15.1	702.5			S/L W/S
	10' LT	2.7	699.8	SND6		SND6
	20' LT	3.8	698.7	"		"
	30' LT	3.3	699.2	"		"
	40' LT	2.3	700.2	SND6		SND6
	53' LT	15.1	702.5			S/L W/S
	51' LT	15.7	701.9			BTM ARCH & BTM ABUT & BTM BNK
	61' LT	12.35	~~701.25~~ 705.25			TOP CONC. BANK
	25' LT	9.5	708.1			L/S & TOP ARCH
SM B2A	CK	6.93	710.67			
K.V						

BRIDGE DRAWING

⊗ B 2A

BRIDGE ON EDWARD HINES DRIVE





U/S LOOKING D/S

RAILING WIDTH = 1.0'

" HEIGHT = 2.7'

SIDE WALK U/S = 4.3'

" D/S = 10.0'

Rd. WAY WIDTH = 35.5'

OVER HANG = 2.5'

WIDTH of opening = 51'

TOTAL Length BRIDGE = 97.5'

BRIDGE SECTION

B 1A

AT ENTRANCE TO D.P.W.

W.C.P.C

	+	HI	-	ELEV.	
TBM D.P.W.				715.34	
	3.77	719.11			
	DIST	Rod	ELEV		DESCRIPTIONS
	0'	6.36	712.75		TOP ℄ Rd AT FACE of HEADWALL
	2.5' RT	5.86	713.25		℄ Rd ENT. DR TO D.P.W.
	50' RT	5.32	713.79		"
	75' RT	4.55	714.56		"
	100' RT	3.09	716.02		"
	114' RT	2.68	716.43		LT. Edge HINES DR
	133' RT	2.45	716.66		℄ " "
	145' RT	2.32	716.79		RT " " "
	30 LT	6.21	712.90		TOP ℄ Rd ENTRANCE TO D.P.W. @ FACE of HEADWALL. D.P.W YARD
	50' LT	5.62	713.49		
	75' LT	5.41	713.70		
	100' LT	5.08	714.03		
	125' LT	4.59	714.52		
	150' LT	4.93	714.18		
	175' LT	5.32	713.79		
K.D					

Pg-14

CHISELED □ ON N.W. CORNER of BRIDGE ON N.W. CORNER of CONC. RAILING U/S SIDE AT ENTRANCE TO D.P.W./w CRC Edward HINES DR. (SET BY OTHERS)
(Refer Pg 14)

+	HI	-	ELEV.		Desc.
	719.11				
Dist	Rod	ELEV			
200' LT	5.83	713.28			D.P.W. YARD
225' LT	6.81	712.30			
250' LT	7.69	711.42			
280' LT	7.76	711.35			LAND declines to embankment
			✓K.V		I-96 Freeway


HI
719.11


	Dist	Rod	ELEV.			Desc				
	1.3' LT	7.1	712.0		RT	Top of Retaining wall @ Face				
	1.3' LT	10.0	709.1	2		BTM	"		"	"
	0'	11.2	707.9			W/S	S/L			
	0'	9.33	709.78			Top of Pipe				
	6.0' LT	14.1	705.0			RT	Side	Pier 1	BTM	CR
	7.3' LT	14.9	704.2			LT	"	"	"	
	10' LT	15.9	703.2			BTM	CR			
	15' LT	18.0	701.1			"	"			
	20' LT	17.0	702.1			"	"			
	22.5 LT	16.6	702.5			BTM	CR	RT	Side	Pier 2
	23.8 LT	15.6	703.5			"		LT	"	"
	29.7 LT	7.2	711.9		LT	Top	Retaining	Wall	@	Face
	29.7 LT	9.9	709.2 ~~699.8~~			BTM				
	30 LT	11.3	707.8			W/S	S/L			
	29.7' LT	8.2	710.9			L/S	@	LT		
	1.3' LT	8.2	710.9			L/S	@	RT		
TBM D.P.W.	CK	3.77	715.34	V.V.						

BRIDGE DRAWING

BRIDGES AT D.P.W.

@ SECTION B1A





6' PIPE with 4 brackets

2.3' below BTM BRIDGE Deck

Level Loop

	+	HI	-	ELEV.		
TBM "FL 2-3"				730.22		Gosling Czubak Assoc.
	1.18	731.40				
TP 1			12.85	718.55	- 11.67	DOT E EDGE HINES DR
	2.08	720.63				
TBM D.P.W.			5.29	715.34	- 3.21	Refer TO Pg - 8
		RETURN				
TBM D.P.W				715.34		Pg - 8
	5.19	720.53				
TP- 1			1.98	718.55	3.21	above
	12.71	731.26				
TBM "FL 2-3"			1.03	730.23	11.68	above

V.L.D

October 12. 1992

Ms. Hannah Kobylinski
Engineering Division
Great Lakes Hydraulics & Hydrology Branch
Detroit District Corps of Engineers
P.O. Box 1027
Detroit, Michigan 48231-1027

Re: LMMP
City & Township of Plymouth
Middle Rouge River
Wayne County

Dear Ms. Kobylinski:

We have completed our review of the Limited Map Maintenance Program for the Middle Rouge River within the City and Township of Plymouth. Based on our review, there are several comments and concerns that should be addressed.

1. **XSEC 2100 - 2245 I-275 Bridges**
   It is suggested that the BT cards be reviewed. It appears that a significant amount of bridge area is being eliminated because of how the low cord has been input on the BT cards. In particular, it appears that an additional BT station will be needed between station 252 and 338. Upstream stages may be lower up to a foot by such a correction.

2. **XSEC 13136 - 14600**
   The reach lengths and invert elevations should be reviewed in this reach. At XSEC 14600, the reach length is shown to be 1464 feet between XSEC 14400 and 14600. If the invert elevations are a result of interpolation between XSEC 13135 and XSEC 14601, the invert elevations at 13800 and 14400 should be reviewed.

3. **XSEC 14601 - 14980 Wilcox Lake Dam**
   The analysis has assumed that all of the flow will be through the principal spillway. However, the computed stage of 712.19 is about 6 feet over the dam embankment. It is suggested that the analysis at the Dam consider the over-topping of the dam embankment. The National Dam Safety Program Inspection Report shows that at a stage of 706.0, the dam will pass about 5000 cfs. It appears that the computed stages may be about 6 feet high.

I have included a copy of the rating curve and a plan view of the dam, taken from the Dam Safety Report.

4. **XSEC 16113 - 19850**
The U.S. Geological Survey Maps and aerial photographs indicate that the Middle Rouge Parkway crosses the River in this reach. The bridge has not been included in the analysis. What type of loss may be expected at this crossing?

We request that you consider these comments, and adjust the hydraulic model as necessary. If you have any questions, please feel free to contact me.

Sincerely,

Bruce E. Menerey, P.E.
Floodplain Mapping/Delineation
Land & Water Management Division
517-335-3181

Enclosures

DEPARTMENT OF THE ARMY
DETROIT DISTRICT, CORPS OF ENGINEERS
BOX 1027
DETROIT, MICHIGAN 48231-1027

OCT 0 7 1992
NATURAL RESOURCES
LAND & WATER MGMT.

IN REPLY REFER TO

SEP 30 1992

Great Lakes Hydraulics and Hydrology Branch

Mr. Bruce Menerey, P.E.
Technical Programs
Land and Water Management Division
Michigan Department of Natural Resources
P.O. Box 30028
Lansing, Michigan 48909

Dear Mr. Menerey:

Submitted for your review and approval is a copy of the hydraulic calculations for the City of Plymouth and Plymouth Township, Michigan Limited Map Maintenance Program. Enclosed are the HEC-2 100-year run, field notes from all new survey work, and a brief write-up dealing with items that will assist the review process.

If you have any questions regarding the enclosed data, please contact Ms. Hanna Kobylinski at (313) 226-4761 or Mr. David Schweiger at (313) 226-4886.

Sincerely,

David L. Schweiger

for Ronald E. Wilshaw, P.E.
Chief, G.L. Hydraulics and
Hydrology Branch

Enclosure

Great Lakes Hydraulics and Hydrology Branch

Mr. Bruce Menerey, P.E.
Technical Programs
Land and Water Management Division
Michigan Department of Natural Resources
P.O. Box 30028
Lansing, Michigan 48909

Dear Mr. Menerey:

Submitted for your review and approval is a copy of the hydraulic calculations for the City of Plymouth and Plymouth Township, Michigan Limited Map Maintenance Program. Enclosed are the HEC-2 100-year run, field notes from all new survey work, and a brief write-up dealing with items that will assist the review process.

If you have any questions regarding the enclosed data, please contact Ms. Hanna Kobylinski at (313) 226-4761 or Mr. David Schweiger at (313) 226-4886.

Sincerely,

Ronald E. Wilshaw, P.E.
Chief, G.L. Hydraulics and
Hydrology Branch

Enclosure

City of Plymouth and Plymouth Township, Michigan, FIS
Limited Map Maintenance Program
Hydraulic Computation Background Information

This study covers the Middle River Rouge from the downstream corporate limit of Plymouth Township to the upstream township corporate limit, including the City of Plymouth. Since this is a limited study, only the 100-year flood is being modeled with discharge as previously approved by the Michigan Department of Natural Resources. In the existing study, the Middle River Rouge was studied by approximate methods.


As part of this study a field survey was made in March 1992. The survey only collected data at bridge sections. All bridges were field measured to obtain elevation data and structural geometry. Valley sections were estimated using a new two-foot topographic map developed for the U.S. Army Corps of Engineers, Detroit District from aerial photography flown in March 1992.

Channel and overbank roughness factors (Manning's "n") used in the hydraulic computations were chosen by engineering judgment and were based on field observations.

The starting water surface elevation was determined based on information included in the National Dam Safety Program Inspection Report for Middle River Rouge Basin, Newburgh Dam.

Water surface elevations were computed using the COE HEC-2 step-backwater computer program. The HEC-2 model for this study began at the upstream side of Newburgh Lake and was continued to the upstream side of Northville Road, near the downstream side of Phoenix Lake. The E. Hines Drive bridge located upstream of Haggerty Road (station 6183 in the HEC-2 model) was modeled as a regular cross section. Since the bridge is oriented parallel to general direction of flow in the floodplain, there is minimal head loss in the general vicinity of the bridge.

The floodway run is not included as part of this study. The copy of the HEC-2 output for the 100-year profile which covers both communities has been included for your information.



NOTE: WAYNE COUNTY DATUM IS 0.512 FEET HIGHER THAN USGS DATUM.

NATIONAL DAM SAFETY PROGRAM

WILCOX DAM


SPILLWAY AND TAILWATER RATING CURVES

FIGURE 10

This is to certify that all work accomplished in the conduct of this study was done in accordance with the Statement of Work and General Provisions of Interagency Agreement No. EMW-91-E-3529, Project Order No. 4A and Project Order 4B, together with all such modifications, either written or oral, as the Project Officer and/or the Contracting Officer or their representatives have directed, as such modifications affect this contract, and that all such work has been accomplished in accordance with sound and accepted engineering practice within the contract provisions for respective phases of the work.


David L. Schweiger

DAVID L. SCHWEIGER, P.E.
Chief, Riverine and Coastal Section,
Great Lakes Hydraulics and Hydrology
Branch


PLYMOUTH
PLYMOUTH
PLYMOUTH
Plymouth State Home and Training Sch
St John Seminary
Plymouth Ch
Epiphany Ch
Tanger Sch
St Lukes Ch
Holy Trinity Ch
Farland Sch
Wilcox Lake
Phoenix Lake
Rouge River
Middle Rouge River
Newburgh Lake
Riverside Cemetery
PLYMOUTH RIVERSIDE PARK
Kellogg Park
Hough Park
Starkweather Sch
Our Lady of Good Counsel Sch
High Sch
Jr High Sch
Smith Sch
Allen Sch
Auburn Playground
Playground
Picnic Area
Castle Gardens Park
Randolph Sch
Webster Sch
St Edith Sch
Ladywood High Sch
Madonna College
Sybsta
Johnson
Washington
OHIO
JUNCTION
ANN ARBOR
ANN ARBOR TRAIL
SCHOOLCRAFT
5 MILE
LIVONIA
NEWBURGH
LEVAN
SHELDON
HAGGERTY
CORPORATE
CHESAPEAKE
AMRHEIN
MERIDALE
RIVERSIDE PARK
PLYMOUTH RD
BM 745
BM 716
BM 712
BM 681
BM 676

GOSLING CZUBAK ASSOCIATES, P. C.
525 WEST 14th STREET
TRAVERSE CITY, MI 49684

89/zon



BRIDGE B-1
NORTHVILLE RD O...
MIDDLEBELT ...
FOR ... / 1-14 ...
THE ... ...
PHOENIX ...
REFER W.C.R.C. JOB # 340-#2

DO: 0011

3-26-92
J. CROSS ... E...
J. LITA E...

90/200 BRIDGE FL-1

STA	BS	HI	FS	ELEV	REMARKS
FL2-3				730.22	TBM FL2-3 SEE FG. 94/200
	0.30	730.52			
①			3.25	727.27	① 0+00 TOP / LT. FOOT.
②			5.80	724.72	② TOP / CONC. WINGWALL
③			12.5	718.0	③ GR. @ BOTTOM CONC WING WALL
④			21.9	708.6	④ WATERS EDGE 0+00 (TOP/WATER) @ GROUND
⑤			2.94	727.58	⑤ 0+66.1 ZT TOP / RT. FOOT.
⑥			8.97	721.55	⑥ TOP / CONC WING WALL
⑦			13.2	717.3	⑦ GR @ BOTTOM / CONC. WING WALL
⑧			21.9	708.6	⑧ 0+65 RT WATERS EDGE @ GROUND (TOP/WATER
FL2-3			0.30	730.22 ✓	

ROD 11 5-12-92

91/200

94/200

STA	BS	HI	FS	ELEV.
FLZ-3				730.22
	5.08	735.30		
0+00 ℄ RD			8.05	727.25
0+30 RT ℄ RD & BRIDGE			7.80	727.50
0+72 RT ℄ RD & END BRIDGE			7.68	727.62
1+00 RT ℄ RD			7.65	727.65
1+25 RT ℄ RD			7.34	727.96
1+50 LT ℄ RD			6.85	728.45
1+75 RT ℄ RD			6.33	728.97
2+00 RT ℄ RD			5.62	729.68
2+25 LT ℄ RD			4.85	730.45
2+50 RT ℄ RD			3.90	731.40
2+75 RT ℄ RD.			3.52	731.78
2+00 RT ℄ RD.			2.58	732.72
2+25 RT ℄ RD			1.90	732.40
0+25 LT ℄ RD.			7.65	727.45
0+50 LT ℄ RD			7.38	727.92
0+75 LT ℄ RD.			6.84	728.44
1+00 LT ℄ RD			6.34	728.96
1+25 LT ℄ RD			5.73	729.57
1+50 LT ℄ RD			5.10	730.20
1+75 LT ℄ RD.			4.33	730.97
2+00 LT ℄ RD.			3.54	731.76
2+25 LT. ℄ RD			2.63	732.67
		(CONT.)		

95/200

BM FLZ-3: CHISELED SQUARE ON TOP OF N. END CONC. WALL ON E. SIDE OF BRIDGE OVER M.D. TRIBE RIVER ON JOHNSVILLE RD. S/ INT. JOHNSVILLE RD & HINES DR., N. OF W.C.C. PHOENIX YARD.


NOTE RD SLOPES UP 2% AFTER 3+25 RT

4064 5-12-92

GOSLING CZUBAK ASSOCIATES, P. C.
525 WEST 14th STREET
TRAVERSE CITY, MI 49684

STA	BS	HI	FS	ELEV	
	(DWR)	735.30			
2+50 LT @ RA			1.69	733.61	
FL2-3			5.08	730.22	✓

DOGH 5-12-92



100/200

GO LING CZUBAK ASSOCIATES, P.C.
525 WEST 14th STREET
TRAVERSE CITY, MI 49684

97/200

NOTE RD SLOPE UP AWAY AFFECT 2ND LT.
DM FL2-3 SEE FD. 94/200

102/200

BRIDGE L-3

STA	BS	HI	FS	ELEV	REMARKS
FL3-1				708.05	BM FL3-1 - P K. NAIL ON TOP OF W GUARD RAIL POST ON E. SIDE OF E ENTRANCE TO PARKING AREA ON N SIDE EG. NINES OF E/NORTHVILLE RD (W. COX LAKE AREA).
	10.27	718.30			
TEM "WIL"			1.91	716.39	TBM "WIL" CHISSELED SQUARE ON S. END/CONC. WALL E. SIDE OF NORTHVILLE RD @ STA 1 REMARKS BRIDGE OVER MED. ROUGE RIVER, E./ENT. NORTHVILLE RD. & EL. HOUSE DR. (WILLOW LAKE AREA)
	1.74	718.13			
FL3-1			10.10	708.03 ✓	SEE ABOVE
TEM "WIL"	8.43			716.39	TBM "WIL" SEE ABOVE
	8.43	724.82			
0+00 ℄ RD.			11.98	712.84	
0+25 RT ℄-℄ ROUTE LINE			11.62	713.20	
0+68 RT ℄ RD			11.11	713.71	
1+00 RT ℄ RD.			9.90	714.92	
1+68 RT ℄-℄ MILL ST & STARKWEATHER			6.87 ~~6.75~~	717.95	
2+00 RT ℄ STARKWEATHER			5.57 ~~6.07~~	719.25	
2+25 RT ℄ RD			4.13	720.69	
2+50 LT ℄ RD			2.72	722.10	NOTE RD SLOPES UP 4% AFTER 2+50 RT
0+50 LT ℄ RD.			12.30	712.52	
1+00 LT ℄ RD			11.94	712.88	
1+50 LT ℄ RD			11.32	713.50	
2+20 LT. ℄-℄ NORTHVILLE & ℄ E. NINES DR			10.35	714.47	
			(OVER)		

103/200

CZUBAK ASSOCIATES, P. C.
520 WEST 14th STREET
TRAVERSE CITY, MI 49684

104/200


STA	BS	HI	FS	ELEV	
	CONT	724.82			
2.50 LT @ RD.			9.95	714.87	
TBM "WIL"			8.43	716.39	✓

K DGH 5-12-92

101/200

BRIDGE B-3
NORTHVILLE RD
220' S. OF E. HINES DR.
STATE REWIRE BRIDGE
REFER WAYNE CO. RD. CO. JOB #339


3-26-92
J. CROSS T
J. LIRA L



STA	BS	HI	FS	ELEV.	
TBM "WDL"				716.39 ✓	SEE PG 102/200
	2.03	718.42			
①			5.43	712.99	0+22' LT TOP/CONC.
②			6.1	712.3	0+22 LT GR.
③			7.5	710.9	0+14.5' LT GR.
④			13.6	704.8	0+00 GR.
⑤			16.38	702.04	0+03 GR@ EDGE WTR
⑥			4.93	713.49	0+00 LT. ASH
⑦			8.33	710.09	0+00 LOW STEEL
⑧			4.58	713.84	0+34 RT TOP/CONC.
⑨			8.05	710.37	0+34 LT LOW STEEL
⑩			4.29	714.14	0+68 RT ASH
⑪			7.68	710.74	0+69 LT LOW STEEL
⑫			4.21	714.21	0+92 LT TOP/CONC.
⑬			4.3	714.1	0+92 RT GROUND
⑭			4.5	713.9	0+83 RT GR
⑮			16.38	702.04	0+62 LT GR@ EDGE WTR
⑯			13.9	704.5	0+68 RT GROUND
⑰			15.5	702.9	0+65 RT GROUND
TBM "WDL"			2.03	716.39 ✓	SEE PG. 102/200

KDOH 5-12-92

C ...ING CZUDAK ASSOCIATES, ...
525 WEST 14th STREET
TRAVERSE CITY, MI 49684



NOTE RD SLOPES UP 4% APPROX 2-50'
TO M "WEL" --SEE PG 102/200

110/200

B-A & DAM

STA	B.S	HI.	F.S	ELEV	REMARKS
FL3-1				708.03 ✓	FL3-1 SEE PAGE 102/200
	3.65	711.68			
TBM "DAM"			5.28	706.40	TBM "DAM" CHISELED SQUARE ON N.W. END OF WINGWALL AT WILCOX DAM; N.W. OF INT. OF E. HOWES DR. & WILCOX TL.
	5.38	711.78			
FL3-1			3.75	708.03 ✓	BM FL3-1 SEE PG. 102/200
TBM "DAM"	~~5.38~~			706.40	TBM "DAM" SEE ABOVE
	5.38	711.78			
0+00 ℄ Rd			4.09	707.69	
0+50 LT ℄ Rd			4.10	707.68	
1+00 LT ℄ Rd			4.25	707.53	
1+50 LT ℄ Rd			4.48	707.30	
2+00 LT ℄ Rd			4.76	707.02	
2+50 LT ℄ Rd			5.07	706.71	NOTE RD. RUNS LEVEL AFTER 2+50
℄ Rd					
℄ Rd			4.23	707.45	
0+98 RT ℄ Rd			5.50	706.28	
1+00 RT ℄ Rd.			7.33	704.45	
1+50 RT ℄ Rd			7.60	704.18	
2+00 ℄ Rd			7.20	704.58	
2+50 ℄ Rd			6.27	705.51	
3+00 ℄ Rd			4.71	707.07	NOTE RD. RUNS UP 10% AFTER 2+50
TBM "DAM"			5.38	706.40 ✓	


KDGH 5-12-92

111/200

GOSLING CZUBAK ASSOCIATES, P.C.
525 WEST 14th STREET
TRAVERSE CITY, MI 49684


117/200

109/200



DAM @
BRIDGE B-4
E. HINES DR @
WILCOX RD.
ROSS-WAYNE CO. RD. CO. JOB #A17 #1 & #4

3-26-92
J. Gross
J. Lera




STA	B.S	H.I.	F.S	ELEV.	
TEP. "DAM"				706.40	SEE Pg. 110/EE
	4.00	710.40			
①			8.91	701.49	TOP SPILLWAY
②			14.36	696.04	TOP SPILLWA
③			3.85	706.55	0+00 TOP AEJT
④			6.78	703.62	0+00 EOT "A" STLL
⑤			3.77	706.63	0+15.7 TO AEJT
⑥			6.77	703.63	0+15.7 EOT "A" STLL
⑦			3.77	706.63	0+32.2 T AEJT.
⑧			6.77	703.63	0+32.2 EOT "A" STLL
⑨			3.79	706.61	0+48 TO ABUT
⑩			6.76	703.64	0+48 BOTTOM STLL
⑪			14.32	696.08	TOP SPILLWAY
⑫			8.89	701.51	TOP SPILLWA
⑬			4.2	706.2	TOP BANK
⑭			4.5	705.9	TOP BANK
⑮			8.35	702.05	TOP WATER
⑯			16.07	694.33	TOP WATER
⑰			16.04	694.36	TOP WATER
⑱			3.95	706.45	TOP CONC. WA
⑲			3.90	706.59	"
⑳			3.81	706.59	"
㉑			3.82	706.58	"
TEM "DAM"			4.00	706.40	SEE Pg. 119/EE

KDGH 5-12-92

GOSLING CZUBAK ASSOCIATES, P.C.
525 WEST 14th STREET
TRAVERSE CITY, MI 49684

11/200



* EXTREMELY FAST CURRENT

119/200

STA	BS	HI	FS	ELEV	
FL3-160				709.84 ✓	BM FL3-160 GOOD NAIL IN W FACE OF TELEPHONE POLE ON THE E. SIDE/E. HINES DR 83' S. R.R. VIADUCT, N./PLYMOUTH RD.
	1.92	711.76			
T.P.			7.43	704.28	
	4 22	708.50			
SET TBM "R.R."			5.45	703.05	TBM "R.R" CHISELED SQUARE ON W. END OF N.R.R. BRIDGE ABUT. OVER THE HEAD. ROUGE RIVER. E./E HINES DR. & S./WILCOX RD.
	5.48	708.53			
T.P.			4.20	704.33	
	7.86	712.19			
FL3-160			2.34	709.85	SEE ABOVE
			S.B	709.84	
			ERROR	+0.01	

KDGH 5-12-92

119/200

GOSLING CZUBAK ASSOCIATES, P.C.
525 WEST 14th STREET
TRAVERSE CITY, MI 49684

120/200


STA	BS	HI	FS	ELEV	
TBM "R.R."				703.05	
	24.12	727.17			
T.P.			1.47	725.70	
	9.86	735.56			
0+00 ℄ R.R			3.27	732.29 ~~735.56~~	
0+00 0+28 Rt			6.2	729.4	
℄ RR			3.09	732.47	
0+28 Rt T/Bank			5.8	729.8	
0+50 Lt ℄ RR			3.06	732.50	
0+50 Lt T/Bank			5.7	729.9	
1+00 Rt ℄ R.R.			2.84	732.72	
1+00 Rt T/Bank			5.8	729.8	
2+00 Rt ℄ R.R			2.37	733.19	
2+00 Rt T/Bank			5.1	730.5	
3+00 Rt ℄ R.R.			1.82	733.74	LEVEL TO THE WEST
3+00 Rt T/Bank			3.6	732.0	
0+50 Lt ℄ RR.			3.48	732.08	
0+50 Lt T/Bank			5.7	729.9	
1+50 Lt ℄ R.R.			4.01	731.55	
1+50 Lt T/Bank			7.0	728.6	
2+50 Lt ℄ R.R.			4.34	731.22	LEVEL TO THE EAST
2+50 Lt T/Bank			6.8	728.76	


(CONT) ON PG 121/200)

117/200

BRIDGE B-5
C&O. R.R. BRIDGE OVER
MED. ROUGE RIVER
E./ED HINEL DR. & S./
WILCOX RD.
NO I.D. PLAQUE IN BRIDGE

3-30-92
J. CROSS
J. LIRA


LOW STEEL
LOW STEEL
7.10'
7.34'
679.9
679.9
679.7
679.7
3'
3'
75'
25'
134.4'
134.4'
12.3'
15.0'
28.0'
2.6 WIDE
2.6 WIDE
Note: @ R.R. Grade
50' Pave. T/Bank
To T/Bank



OSLING CZUBAK ASSOCIATES, P.C.
525 WEST 14th STREET
TRAVERSE CITY, MI 49684

REMARKS:

TBM "R.R." SEE PG. 118/200

NOTE USED E.P.K. TEE FOR SHOT T/CURB IS 18'± N. OF TRACK "N" TO L)

STA	BS	HI	FS	ELEV.	
	(BM)	735.56			
T.P.			9.16 ~~10.4~~	726.40	
	0.72	727.12			
TBM "C.R."			24.06	703.06	SEE PG 118/2
			SB	703.05	
KDGH 5-12-92			ERROR	+0.01	


126/200

STA	B.S.	H.I.	F.S.	Elev.
		690.70		
T.P.			4.57	686.13
	20.57	706.70		
TBM NA			3.63	703.07
			S.B.	703.05
			Error	+0.02

See Pg. 118/Rem

& DGH 5/12/92

127/200



GOSLING CZUBAK ASSOCIATES, P.C.
525 WEST 14th STREET
TRAVERSE CITY, MI 49684

STA	BS	HI	FS	ELEV	
TEMP B.L.				703.05	SEE P 118/20
	2.92	705.97			
①			2.88	703.09	CMP T/ASPH
②			6.85	699.14	LOW STEEL
③			2.94	703.03	C-28R T/CONC
④			6.95	699.02	LOW STEEL
⑤			2.94	703.05	C-56R T/ASPH
5A			4.91	701.06	C-56R T/WINGW
⑪			4.99	700.98	C-20 T/WINGW
T.P.			15.43	690.54	
	0.16	690.70			
⑥			3.02	687.68	TOP U/S AT GR
⑦			8.65	682.05	C-54 T TOP C
⑧			9.53	681.17	GR @ U/S
⑨			10.67	680.03	GR @ U/S
⑩			10.78	679.92	C-51.5 T/WATER
7A			3.67	687.03	LOW STEEL
⑫			6.43	684.27	TOP U/S AT GR
⑬			7.52	683.18	C-01 T/CONC
13A			3.67	687.03	LOW STEEL
⑭			10.99	679.71	UNDER
⑮			10.57	680.13	GR @ U/S
⑯			10.61	680.09	GR @ U/S

130/200

STA	B.S.	H.I.	F.S.	ELEV.	REMARKS
BMR3-2				693.70	TBM FL3-2 CHISELED "X" ON S.W. S. WALK PLYMOUTH RD BRIDGE OVER E. HINES DR. "X" LOCATED 7.7'± N/S/ GUARD WALL & 55.5'± W/ OF E/ EDGE OF PAVEMENT
	1.89	698.59			
SET TBM "PLY"			2.12	696.47	TBM "PLY" CHISELED SQUARE ON TOP/CONC. WALL @ N.E. END / NORTHBOUND BRIDGE OVER ROUGE R. ON N. SIDE / E.
	1.02	697.49			
T.P.			14.08	683.41	
	1.85	688.26			
SET TBM "WAY"			8.17	680.09	TBM "WAY" CHISELED IN THE N.E. BOLT FOR GUARD RAIL @ N.E. END OF BRIDGE OVER MID. ROUGE RIVER, 300'± S./PLYMOUTH RD. & 100'± EAST / E. HINES DR.
	8.13	688.22			
T.P.			3.08	685.14	
	12.65	697.79			
FL3-2			4.09	693.70 ✓	BM FL3-2 SEE ABOVE

KOCH 5-12-92

131/200


GOSLING CZUBAK ASSOCIATES, P.C.
525 WEST 14th STREET
TRAVERSE CITY, MI 49684

STA	BS	H.I.	FS	ELEV
TEM "PLY"				696.47
	11.21	707.68		
0+00 ℄ RD			13.42	694.26
0+11.5 RT			13.88	693.80
0+63 RT			14.40	693.28
1+50 RT			14.69	692.99
2+00 RT			14.75	692.93
2+50 RT			14.58	693.10
3+20 RT			14.55	693.13
0+50 LT			2.41	695.27
1+00 LT			10.91	696.77
1+50 LT			9.15	698.53
2+00 LT			7.02	700.66
2+50 LT			4.84	702.84
TEM "PLY"			11.21	696.47 ✓

KOGH 5-12-92


BRIDGE B3-6
PLYMOUTH TRL &
MED. RIDGE RIVER
BRIDGE # 353

3-27-92
J. CROSS
J. LIRA



STA	BS	HI	FS	ELEV	
TBM "PZ4"				696.47	SEE PG 130/200
	0.19	696.66			
①			2.16	694.50	0+32 LT TOP/CON
②			4.2	692.5	0+32 LT CL
⑤			19.0	677.7	0+01.6 RT EP
④			21.72	674.94	0+09 LT GR @ W.
⑤			20.03	676.63	0+32.5 RT LOW STEEL
⑥			2.51	694.15	0+61 RT TOP/CON
⑦			2.92	693.74	0+31.5 RT TOP/CONC
⑧			5.45	691.21	0+31.5 RT LOW STEEL
⑨			3.34	693.32	0+03 RT TOP/CONC
⑩			3.73	692.93	0+95 LT TOP/CON.
⑪			4.5	692.2	0+95 RT GR
⑫			20.5	676.2	0+61.4 RT GR
⑬			21.61	675.02	0+60.9 RT EP @ WATT
⑭			21.35	675.31	0+60.9 RT LOW STEEL
TBM "PLY"			0.19	696.47	SEE PG 136/200

K.O6H 5-12-92



GOSLING CZUBAK ASSOCIATES, P. C.
525 WEST 14th STREET
TRAVERSE CITY, MI 49684

TRH "FLY" SEE PG. 130/200

℄ Rd 0+00
℄ Rd @ ℄ Bridge 0+33 Rt
℄ Rd @ Rt. Abut 0+65 Rt
℄ Rd 1+50 Rt
℄ Rd 2+00 Rt
℄ Rd 2+50 Rt
℄ Rd 2+60 Rt Road continues up 2%
℄ Rd 0+50 Lt
℄ Rd 1+00 Lt
℄ Rd 1+50 Lt
℄ Rd 2+00 Lt
℄ Rd 2+50 Lt Road continues up 10%
TRH "FLY" SEE PG. 130/200


STA	BS	HI	FS	ELEV.
TBM "WAY"				
	4.37	684.46		680.09
0+00 ℄ Rd.			4.36	680.10
0+21.25 RT ℄ Rd			4.39	680.07
0+41.5 RT ℄ Rd			4.38	680.08
0+72 RT ℄@ E.BT			6.21	678.25
0+89. RT ℄-℄			6.23	678.23
1+06 RT ℄ @ E.BT			7.02	677.44
1+16 RT T/BANK			5.9	678.56
1+33 FT B/BANK			8.9	675.56
2+00 RT GR.			7.4	677.1
3+00 LT GR.			6.6	677.9
0+50 LT ℄ Rd			5.0	679.5
1+50 LT ℄ Rd			4.6	679.9
2+50 LT ℄ Rd			5.0	679.5

CONT. TO, 142/200

EDGH 5-12-92

TBM WAY SEE PG. 130/200

140/200



C. J. LING CZUBAK ASSOCIATES, P. C.
525 W. ST 14th STREET
TRAVERSE CITY, MI 49684

137/200

BRIDGE B-7

BRIDGE LOCATED 1000'± PLYMOUTH TR. & 100'± E/ E HINES DR., OVER THE MID. ROUGE RIVER

NOTE. DID NOT FIND BRIDGE PLAQUE No I.D.

3-30-92
J. CROSS ☒
J. LIRA ☐

142/200

STA	BS	HI	F.S.	ELEV	
TBM "WAY"					
	4.37	684.46			
①			7.06	677.40	0+00 LOW STEEL
②			4.53	679.93	0+00 T/ABUT
③			4.53	679.93	0+42.5 T/CONC
④			4.49 ~~7.08~~	679.97	0+42.5 RT T/FEUT
⑤			7.06	677.40	0+42.5 LOW STEEL
⑥			7.08	677.38	0+51.25 [illegible]
⑦			10.4	674.1	0+42.5 GR.
⑧			11.21	673.25	0+41 GR. @ WATER
⑨			4.77	679.69	0+42.5 T/W-WALL
⑩			9.2	675.3	0+42.5 GR.
⑪			6.08	678.38	T/W-WALL END
⑫			6.5	678.0	GR
⑬			11.16	673.30	0+33RT GR@ WATER
⑭			4.82	679.64	0+00 T/W-WALL
⑮			11.17	673.29	T/WATER
⑯			6.17	678.29	T/END W/WALL
⑰			8.3	676.2	GR.
⑱			11.18	672.28	0+02LT GR. @ EDGE WATER
TBM "WAY"			4.36	680.10	END
				680.09	BEG.
				0.01' HIGH	

KCCK 5-12-92


143/200

TBM "WAY" SEE PAGE 130/200

SEE PG 130/200

GOSLING CZUBAK ASSOCIATES, P.C.
525 WEST 14th STREET
TRAVERSE CITY, MI 49684

141/200



STA.	BS	H.I	F.L.	ELEV.	
53-42				718 75 ✓	
	2.08	720.83			
T.P.			14.60	706.23	
	0.75	706.98			
T.P.			14.33	692.65	
	0.65	693.30 ~~692.70~~			
T.P.			14.56	678.74 ~~678.14~~	
	9.67	688.41 ~~687.81~~			
TBM "HAG"			10.57	677.84 ~~677.24~~	
	14.84	692.68 ~~692.08~~			
T.P.			0.27	692.41 ~~691.81~~	
	14.32	706 73 ~~706 13~~			
T.P.			0.19	706.54 ~~705.94~~	
	14.44	720.98 ~~720.38~~			
53-42			2.24	718.74	END
				718.75	CLS

ERROR = 0.01

KOCH 5-12-52

BM 53-42 SEE PG. 76/200

TBM "HAG" CHISELED SQUARE ON TOP / S.W. CONC. WALL @ THE S. END / BRIDGE OVER THE MID. ROUGE RIVER, W. SIDE / S. HAGGERTY RD.

BM 53-42 SEE PG. 76/200


STA	BS	HI	F.S.	ELEV.	
TBM HAG				677.84 ✓	
	8.36	686.20			
0+00 ℄ RD			6.90	679.30	
0+44 AB RT ℄ RD & ℄ BRIDGE			9.21	676.99	
0+88.8 RT ℄ RD			11.68	674.52	
1+50 RT ℄ RD			13.25	672.95	
2+00 RT ℄ RD			14.05	672.15	
2+50 RT ℄ RD			14.80	671.40	
3+00 RT ℄ RD			15.45	670.75	
3+50 RT ℄ RD			15.92	670.28	
0+25 LT ℄ RD			5.10	681.10	
0+50 LT ℄ RD			2.84	683.36	
0+75 LT ℄ Rd			0.06	686.14	
T.P.			0.26	685.94	
	22.27	708.21			
1+00 LT ℄ Rd			18.94	689.27	
1+25 LT ℄ Rd			16.14	692.07	
1+50 LT ℄ Rd			13.41	694.80	
1+75 LT ℄ Rd			11.01	697.20	
2+00 LT ℄ Rd			8.54	699.67	
2+25 LT ℄ Rd			6.36	701.85	
2+50 LT ℄ Rd			4.22	703.99	
TP			21.51	686.70	
	0.96	687.66			
TBM "HAG"			9.81	677.85 ✓	ERROR +0.01

ST 14th STREET
TRAVERSE CITY, MI 49684

BRIDGE B-10
HALLGERTY RD
OVER MID ROUGE RIVER
REPER WAYNE CO. RD. CO. JOB # 392-2

3-30-92
J. CROSS
J. LORA

150/200



151/200

STA	BS	HI.	F.S.	ELEV.	
TBM "HAG"				677.84	SEE PG. 146/200
	4.90	682.74			
①			2.86	679.33	0+00 T/ABUT
②			4.93	677.61	0+00 LOW STEEL 0+00
③			9.7	673.0	GR 0+18 RT
④			3.83	678.91	T/CONC 0+18 RT
⑤			5.93	676.81	LOW STEEL 0+19.8 RT
⑥			7.47	675.27	LOW STEEL 0+44.4 RT
⑦			5.15	677.59	T/CONC 0+44 RT
⑧			8.56	674.18	LOW STEEL 0+67.4 RT
⑨			6.37	676.37	T/CONC 0+67.4 RT
⑩			8.56	674.18	LOW STEEL 0+66 RT
⑪			9.82	672.92	LOW STEEL 0+88.8 RT
⑫			7.42	675.32	T/CONC 0+88.8 RT
⑬			9.42	673.32	LOW STEEL 0+82.6 RT
⑫			15.7	667.0	GR 0+75 RT
⑮			16.5	666.2	GR. 0+64.7 RT
⑯			19.6	663.1	GR 0+60 RT
⑰			20.5	662.2	GR 0+59 RT
⑱			21.84	~~660~~ 660.90	GR @ WATER
⑲			~~20.8~~ 18.8	663.9	0+18 RT GR.
⑳			21.84	660.90	0+25 RT GR @ WATER
TBM "HAG"			4.90	677.84	✓

KDGH 5-12-~~93~~ 92

GOSLING CZUBAK ASSOCIATES, P. C.
525 WEST 14th STREET
TRAVERSE CITY, MI 49684

TEN HAG" SEE PG. 146/200

LEVEL FOR 200' THEN UP 15%

ROAD CONTINUES UP 8%

SEE PG 147/200

ADGH 5-12-82

STA	BS	HI	FS	ELEV	REMARKS
TBM "HAG"				677.84 ✓	TBM "HAG." SEE PG. 156/200
	0.22	678.06		~~677.84~~	
T.P.			6.25	671.81	
	5.84	677.65			
SET TBM "JON"			2.90	674.75 +0.01	TBM "JON" - CHISSELED SQUARE ON THE TOP OF THE N.E. COR. OF THE S. CONC. WALL (R-9) OF BRIDGE. BRIDGE LOCATED 400'W/HAGGERTY LE ON E. HINES DR.
	1.92	676.67		ADJ'D 674.76	
T.P.			7.63	~~669.04~~ 669.04 +0.01	
	5.45	674.49		ADJ'D 669.05	
SET TBM "JER"			0.28	674.21 +0.01	TBM "JER" CHISSELED SQUARE (R-8) IN CONC. S. WALK @ N.E. END. ON BRIDGE OVER MID. ROUGE RIVER, S. SIDE OF E. HINES DR. & 500' EAST OF RIVERSIDE DR.
	2.15	676.36		ADJ'D 674.22	
T.P.			1.24	675.12	
	14.26	689.38			
T.P.			0.34	689.04	
	13.22	702.26			
T.P.			1.70	700.56	
	7.98	708.54 (CONT.)			

ROCH 5-12-92


STA	B.S.	HI	FS	ELEV
	CONT	708.54		
FL3-9			8.09	700.45
			S.B.	700.18
			ERROR - 0.02	

#OGH 5-12-92

GOSLING CZUBAK ASSOCIATES, P.C.
525 WEST 14th STREET
TRAVERSE CITY, MI 49684

BM LOOP
TBM "HAG" TO BM FL3-9

3-30-92
J. Cross
J. Lira


159/200
159/200

LOBBIG CZUBAK ASSOCIATES, P. C.
525 WEST 14th STREET
TRAVERSE CITY, MI 49684

BM FL3-9 N.W COR. OF C.B. GRATE
LOCATED ON THE EAST SIDE ASPECK DR.
± 35' S/E' LINDSAY DR.


STA	RS	H.I.	F.S.	ELEV.	REMARKS
TBM "JER"		680.00		674.21 ✓	TBM "JER" SEE PG. 164/200
	5.78	679.99			
0+00			6.19	673.80 01	℄ RD
0+48 RT			5.37	674.62 03	℄ RD & BRIDGE
0+96 RT			6.21	673.78 19	℄ RD
1+50 RT			6.97	673.02 03	℄ RD
2+00 RT			7.61	672.38 39	℄ RD
2+50 RT			8.47	671.52 63	℄ RD
3+00 RT			9.02	670.97 AE	℄ RD
3+50 RT			9.51	670.48 AA	RD. CONTINUES DOWN 2% ℄ RD
0+50 LT			7.20	672.79 80	℄ RD
1+00 LT			7.96	672.03 04	℄ RD
1+50 LT			8.79	671.30 21	℄ RD
2+00 LT			9.51	670.48 A9	℄ RD
2+50 LT			10.18	669.81 B2	RD. CONT. DOWN ℄ RD.
①			5.90	674.09 10	0+00 TOP LT ABUT.
②			6.6	673.4 A	0+00 GR.
③			10.4	669.66 6	0+11 RT GR.
④			14.82	665.27 18	0+23 RT EDGE/WATER @ GROUND (TOP OF WATER)
⑤			5.28	674.71 12	0+48 RT TOP/CONC.
⑥			5.89	674.10 11	0+96 RT TOP RT. ABUT.
⑦			6.4	673.6	0+96 RT GROUND
⑧			10.5	669.5	0+86 RT GR.

(CONT)

AKDG A 5-12-92

B-8

GOSLING CZUBAK ASSOCIATES, P. C.
525 WEST 14th STREET
TRAVERSE CITY, MI 49684



BRIDGE B-8
E. HINES DR. 600± E/
RIVERSIDE DR.
REFER WAYNE CO. RD CO. JOB # 395
MIDDLE ROUGE PARKWAY CROSSING
ROUGE RIVER

3-31-92
J-CROSS-T
J. LIRA

105/200

19/200

168/200

CZUBAK ASSOCIATES, I...
525 WEST 14th STREET
TRAVERSE CITY, MI 49684

165/200

STA	BS	HI	FS	ELEV.	
	(BM)	680.00 679.99			
(9)			14.86	665.13	ON S.E. GR @ H.C.
T.P.			11.51	668.48	
	2.71	671.19			
(10)			4.82	666.37	0+74 RT LOW STK
(11)			+0.75	671.94	0+48 R LOW STK
(12)			4.81	666.38	0+24 R LOW STK
(13)			4.8	666.4	0+75 L GR
(14)			5.4	665.8	0+32 GR
T.P.			2.86	668.33	
	11.62	679.95			
TEMPER			5.73	674.22	SEE PG 154/21
			S.B.	674.22	
			ERROR	+0.00	

KOGH 5-12-92

170/200

STA	BS	HI	FS	ELEV	REMARKS
TBM "JON"				674.75	TBM "JON" SEE PG. 154/200
	2.03	676.78			
0+00			5.18	671.60	℄ RD
0+48 ET			4.34	672.44	℄ RD - ℄ BRIDGE
0+96 ET			5.24	671.54	℄ RD
1+50 ET			6.10	670.68	℄ RD
2+00 RT			6.75	670.03	℄ RD
2+50 RT			7.09	669.69	℄ RD
3+00 RT			7.11	669.67	℄ RD
3+50 RT			6.68	670.10	RD. CONTINUES ℄ RD
0+50 LT			6.21	670.57	℄ RD
1+00 LT			6.94	669.84	℄ RD
1+50 LT			7.59	669.19	℄ RD
2+00 LT			7.79	668.99	℄ RD
2+50 LT			8.12	668.66	RD CONTINUES ℄ RD
①			4.79	671.99 672.00	0+00 TOP LT. ABUT
②			6.0	670.8	0+00 GR.
③			7.0	669.8	0+05 GR.
④			13.2	663.6	0+23 GR.
⑤			4.15	672.63	0+48 TOP/CONC
⑥			4.79	671.99 672.00	0+96 TOP RT ABUT
⑦			6.4	670.4 670.4	0+96 GR.
⑧			11.0	665.8	0+87 GR

KMH - 5-12-92


171/200

B-9

172/200

GOSLING CZUBAK ASSOCIATES, P.C.
525 WEST 14th STREET
TRAVERSE CITY, MI 49684

169/200



BRIDGE B-9
E. HAINE DR. (GRAVEL)
HAGGERTY RD. OVER
MSE. ROUGE RIVER
REFER WAYNE CO. RD. CO. JOB # 394

176/200

173/200

STA	BS	HI	FS	ELEV	
	CONT.	676.78[19]			
(9)			14.12	662.66[67]	0+80.4R GR@ H2O
(10)			14.11	662.67[68]	0+51 RT GR@ H2O
T.P.			10.55	666.23[29]	
	3.50	669.78[4]			
(11)			7.04	662.69[70]	0+73 LOW STEEL
(12)			+0.09	669.82[83]	0+48 LOW STEEL
(13)			6.56	663.16	0+23 LOW STEEL
T.P.			1.61	668.32[13]	
	8.92	677.94[05]			
TBM "JON"			2.28	674.76[77]	SEE PG. 154/200
			S.B.	674.75[76]	
			ERROR	+0.01	

KDGH - 5-12-92

B-9

[illegible] LEDEAK ASSOCIATES, P.C.
[illegible] WEST 14th STREET
TRAVERSE CITY, MI 49684

178/200

STA	BS	HI	FS	ELEV.	
60-45				704.02 (704.016)	BM 60-45 BRONZE DISC IN TOP/CONC. POST @ N.W. COR ECKLES RD. & PLYMOUTH RD. 56' W/@ ECKLES & 50' N/@ PLYMOUTH (W.C.R.C.)
	3.35	707.37			
T.P.			6.97	700.40	
	6.27	706.67			
T.P.			13.32	693.35	
	0.91	694.26			
W.C.R.C. B.M.			8.76	685.50	W.C.R.C. B.M. - FOUND BRASS DISC IN TOP OF CONC. WALL DISC. LOCATED 4.5' S./N. END OF S.B. I-275 BRIDGE OVER THE MIDDLE ROUGE RIVER. (WEST SIDE S.B. I-275) NO STAMPINGS EXCEPT W.C.R.C. B.M.
	10.56	696.06			
T.P.			0.48	695.58	
	12.16	707.74			
T.P.			7.45	700.29	
	7.27	707.56			
60-45			3.53	704.03	BM 60-45 SEE ABOVE
			S.B.	704.02	
			ERROR	+0.01	

K DGH 5-12-92

179/200

180/200

COLLING CZUBAK ASSOCIATES, P. C.
525 WEST 14th STREET
TRAVERSE CITY, MI 49684

177/200

BRIDGE B-11
S.B. I-275 OVER
THE M.C.O. ROUGE RIVER
REFER MDSH. JOB # 04744A

3-31-92
J. Cross
J. Lira

182/

STA	B.S.	H.I.	F.S.	ELEV.
I-275 BM-UCRC				685.50 ✓
	1.23	686.73		
0+00			3.71	683.02
0+85 RT			3.61	683.12
1+70 RT			3.49	683.24
2+50 RT			3.45	683.28
3+50 RT			3.47	683.26
4+20 RT			3.31	683.42
1+30 LT			3.80	682.93
2+00 LT			3.94	682.79
2+50 LT			4.03	682.70
①			3.90	682.83
②			7.63	679.10
③			10.3	676.4
④			3.80	682.93
⑤			7.53	679.20
⑥			3.64	683.09
⑦			7.54	679.19
⑧			11.0	675.7
T. P.			17.54	669.19
	7.89	677.08 (CONT)		

KOGH. 5-12-92

I-275 BM UCRC SEE PG. 181/200

SHOTS TAKEN ON WEST SIDE OF TO HEAVY TRAFFIC

℄ Rd 1.	
℄ Rd	
℄ Rd	
℄ Rd	
℄ Rd	
℄ Rd	
℄ Rd	
℄ Rd	
℄ Rd	
0+00	T/CONC
0+02 RT	LOW STEEL
0+02 RT	RIP. RAP
0+89.6 RT	T/CONC
0+89.6 RT	LOW STEEL
1+70 RT	T/RT. ABUT
1+68 RT	LOW STEEL
1+68 RT	RIP- RAP


181/200

184/200


STA	B.S.	HI (CONT' 677.08)	F.S.	ELEV
(9)			15.2	661.88
(10)			16.3	660.78
(11)			16.7	660.38
(12)			16.3	660.58
(13)			17.80	659.28
(14)			17.78	659.30
T.P.			1.14	675.94
	11.29	687.23		
I-275 BM. WCRC			1.75	685.48
			S.E.	685.50
			ERROR	-0.02

RDGH 5-12-92

181/200



GOURDIE-FRALEY & CZUBAK ASSOCIATES, P.C.
525 WEST 14th STREET
TRAVERSE CITY, MI 49684


186/200
187/200

[illegible] CZUBAK ASSOCIATES, P. C.
525 WEST 14th STREET
TRAVERSE CITY, MI 49684

1+31.1	GR
0+90.9	GR
0+88.3	GR
0+81.3	GR
0+79 RT	GR @ WATERS EDGE
0+49 RT	GR @ WATERS EDGE

I-275 INCREASE SEC Pg. 178/200

190/200

STA	BS	HI	FS	ELEV.
~~FL 3-2~~ 2-3	7.91	738.13		730.22
WCRC. BM M-14	8.79	738.21	8.71	729.42
~~FL 3-2~~ 2-3			8.00	730.21
			S.B.	730.22
			~~ERROR~~	0.01

4064- 5-12-92

191/200

REMARKS


SEE PG. 94/200

M-14 WCRC BM
FD BRONZE DISC IN TOP/CONC. WALL 4' WEST OF THE EAST END OF M-14 BRIDGE OVER MEL. TOWNE RIVER ON N. SIDE OF M-14.
BM ~~FL 3-2~~ 2-3 SEE PG. 94/200

GOSLING CZUBAK ASSOCIATES, P. C.
525 WEST 14th STREET
TRAVERSE CITY, MI 49684

192/200

189/200



BRIDGE B-2
M-14 OVER MID.
ROUGE RIVER
REFER MSDH JOB # 82102

3-31-92
M. Cross
J. Lira

STA	B.S.	H.I.	F.S.	ELEV	
M-14 WCR CL PK				729.42	✓
	4.36 ~~4.62~~	733.78			
0+00			7.42	726.36	
0+58.7 RT			6.65	727.13	
1+17.5 RT			5.75	728.03	
2+00 RT			4.46	729.32	
3+00 RT			2.94	730.84	
3+50 RT			2.17	731.61	Rd. CONTINUES UP 4%
1+00 LT			9.00	724.78	
2+00 LT			9.72	724.06	
2+50 LT			9.89	723.89	Rd. CONTINUES UP 2%
①			7.60	726.18	
②			13.60	720.18	
③			18.9	714.9	
④			6.95	726.83	
⑤			5.95	727.80	
⑥			11.97	721.81	
⑦			17.5	716.3	
T.P.			20.96	712.82	
	2.98	715.80			
⑧			4.9	710.9	
⑨			5.7	710.1	
		(COUNT)	EDGE		

M-14 WCR CL PK. SEE PG. 190/200


N. EDGE/Rd.	
"	
"	
"	
"	
"	
"	
"	
"	
0+00	T/LT ABUT
0+00	LOW STEEL
0+00	RIP-RAP
0+58.7 RT	T/CONC.
1+17.5 RT	T/RT ABUT
1+16.1 RT	LOW STGET
1+16.1 RT	RIP-RAP
1+02 RT	GR
0+82 RT	GR

525 WEST 14th STREET
TRAVERSE CITY, MI 49684

STA	B.S.	HI. (CONT)	F.S.	ELEV.	
		715.80			
(10)			9.9	705.9	
(11)			10.30	705.50	
(12)			+5.57	721.37	
(13)			10.29	705.51	
(14)			5.5	710.3	
(15)			4.4	711.4	
T.P.			0.65	715.15	
	18.64	733.79			
				729.42	BEG.
EM. MH WCR	BM		4.34	729.45	END
			ERROR =	0.03	

4x OLH 5-12-92

199/200



200/200

BM INDEX	ELEV.	PG.
FL2-3	730.22	94/200
FL3-1	708.03	102
WIL	716.39	102
DAM	706.40	110
FL3-160	709.84	118
R-R-	703.05	118
FL3-2	693.70	130
PLY	696.47	130
WAY	680.09	130
53-42	718.75	76
HAG	677.84	146
JON	674.76	154
JER	674.22	154
FL3-9	700.48	156
60-45	704.02	178
I-275 (WCRC)	685.50	178
M-14 (WCRC)	729.12	150

J. J. CLUNAK ASSOCIATES, P. C.
525 WEST 14th STREET
TRAVERSE CITY, MI 49684

197/200

0+72 RT	GR	
0+43.5 RT	GR @ WATER EDGE	
0+58.7 RT	LOW STEEL	
0+26 RT	GR @ WATER'S EDGE	
0+18 RT	GR	
0+10 RT	RIP-RAP	

SEE PG. 199/200



1) COUNTY: Wayne

2) STUDY NAME: City of Wyandotte

3) WATERCOURSE: Sexton - Kilfoil Drain

4) DOCUMENT TYPE: Summary



100-year

WATERCOURSE: Sexton-Kilfoil Drain (Ecorse Creek)

CITY/[illegible]: City of Wyandotte

COUNTY: Wayne

STATION	LOCATION	CWSEL	EG	Q
1	Confluence of Ecorse & Detroit Rivers	574.90	575.51	4410
30	29' u/s of confluence	574.95	575.55	4410
60	1' d/s of Jefferson Street Br.	574.99	575.60	4410
61	d/s face of Jefferson Street Br.	574.93	575.66	4410
136	u/s face of Jefferson Street Br.	575.16	575.84	4410
137	1' u/s of Jefferson Street Br.	575.34	575.88	4410
187	51' u/s of Jefferson Street Br.	575.36	575.98	4410
362	226' u/s of Jefferson Street Br.	575.94	576.25	4410
737	51' d/s of d/s face of R.R. Br. #1	576.24	576.50	4410
787	1' d/s of d/s face of R.R. Br. #1	576.20	576.62	4410
788	d/s face of (T & I) R.R. Br. #1	576.15	576.67	4410
797	u/s face of (T & I) R.R. Br. #1	576.19	576.70	4410
798	1' u/s of (T & I) R.R. Br. #1	576.32	576.73	4410
844	47' u/s of (T & I) R.R. Br. #1	576.37	576.77	4410
845	d/s face of (T & I) R.R. Br. #2	576.33	576.81	4410
859	u/s face of (T & I) R.R. Br. #2	576.38	576.85	4410
860	1' u/s of (T & I) R.R. Br, #2	576.48	576.88	4410
910	50' u/s of (T & I) R.R. Br. #2	576.56	576.92	4410
911	d/s face of (T & I) R.R. Br. #3	576.52	576.96	4410
921	u/s face of (T & I) R.R. Br. #3	576.55	576.99	4410
922	1' u/s of (T & I) R.R. Br. #3	576.66	577.02	4410
953	1' d/s of (T & I) R.R. Br. #4	576.5[illegible]	577.14	4410
954	d/s face of (T & I) R.R. Br. #4	576.44	577.29	4410
985	u/s face of (T & I) R.R. Br. #4	576.66	577.47	4410
986	1' u/s of (T & I) R.R. Br. #4	576.07	577.57	4410
1036	51' u/s of (T & I) R.R. Br. #4	577.24	577.64	4410
1736	700' d/s of confluence of N. Ecorse Ri.	577.86	578.18	4410
2436	Confluence of N. Ecorse Ri. & Sexton-Kilfoil	578.27	578.57	4410
3186	750' u/s of confluence	578.83	578.92	1760
3686	1100' u/s of confluence	578.93	579.04	1760
4186	50' d/s of Emmons Street Br.	579.06	579.19	1760
4236	d/s face of Emmons Street Br.	579.05	579.24	1760
4281	u/s face of Emmons Street Br.	579.28	579.46	1760
4931	6[illegible]0' u/s of Emmons Street Br.	579.55	579.68	1760
5956	1725' u/s of Emmons Street Br.	579.86	580.00	1760
6981	2900' u/s of Emmons Street Br.	580.19	580.32	1760
8031	51' d/s of Harrison Street Br.	580.52	580.63	1760
8082	d/s face of Harrison Street Br.	580.55	580.65	1760
8147	u/s face of Harrison Street Br.	580.73	580.83	1760
9397	1250' u/s of Harrison Street Br.	581.07	581.20	1760
10297	2000' u/s of Harrison Street Br.	581.34	581.48	1760
10897	76' d/s of Harrison Street Br. #2	581.53	581.68	1760
10973	d/s face of Harrison Street Br. #2	581.53	581.76	1760
11017	u/s face of Harrison Street Br. #2	581.98	582.19	1760
11477	51' d/s of N. Bound Fort Street Br.	582.27	582.40	1760
11528	d/s face of N. Bound Fort Street Br.	582.26	582.46	1760
11599	u/s face of N. Bound Fort Street Br.	582.55	582.74	1760
11650	d/s face of S. Bound Fort Street Br.	582.60	582.77	1760
11721	u/s face of S. Bound Fort Street Br.	582.92	583.08	1760

```
C
C      21
C      61          D/S FACE JEFFERSON STREET BRIDGE
C     136          U/S FACE JEFFERSON STREET BRIDGE
C     788          D/S FACE RR BRIDGE #1
C     797          U/S FACE RR BRIDGE #1
C     845          D/S FACE RR BRIDGE #2
C     859          U/S FACE RR BRIDGE #2
C     911          D/S FACE RR BRIDGE #3
C     921          U/S FACE RR BRIDGE #3
C     954          D/S FACE RR BRIDGE #4
C     985          U/S FACE RR BRIDGE #4
C    2436  CONFLUENCE OF THE NORTH ECORSE RIVER @ SEXTON-KILFOIL DRAIN
C    4236          D/S FACE OF EMMONS STREET BRIDGE
C    4281          U/S FACE OF EMMONS STREET BRIDGE
C    8082          D/S FACE OF HARRISON STREET BRIDGE
C    8147          U/S FACE OF HARRISON STREET BRIDGE
C   10973          D/S FACE OF HARRISON STREET BRIDGE #2
C   11017          U/S FACE OF HARRISON STREET BRIDGE #2
C   11528          D/S FACE OF NORTH BOUND FORT STREET
C   11599          U/S FACE OF NORTH BOUND FORT STREET
C   11650          D/S FACE OF SOUTH BOUND FORT STREET
C   11721          U/S FACE OF SOUTH BOUND FORT STREET
T1        CITY OF WYANDOTTE FIS 5555-73
T2        SEXTON-KILFOIL DRAIN
T3        10 YEAR FLOOD  3165 CFS
J1              2                                                    574.90
J2    -10                -1
NC 0.035   0.035    0.032     0.3      0.5
QT      4    3165     4100     4410     5160
X1      1      41      500      619
GR 576.2       0   575.9     100   576.6     200   578.5     300   581.1     400
GR 584.6     500   582.8     500   582.6     505   581.9     510   581.1     515
GR 579.2     520   575.4     525   574.8     530   572.8     535   569.2     540
GR 569.2     540   565.5   543.5   565.5   543.5   565.5     545   563.9     555
GR 566.1     560   565.3     565   565.4     570   564.1     575   566.2     580
GR 566.2     580   565.3   583.5   565.3   583.5   565.3     585   563.4     590
GR 564.4     595   565.4     600   567.7     605   571.1     610   573.5     615
GR 574.0     619   584.6     619   582.3     700   579.6     800   579.0     890
GR 578.7    1000
X1     30                                  29      29      29
X1     60      41      500      619       30      30      30
GR 576.2       0   575.9     100   576.6     200   578.5     300   581.1     400
GR 584.6     500   582.8     500   582.6     505   581.9     510   581.1     515
GR 579.2     520   575.4     525   574.8     530   572.8     535   569.2     540
GR 569.2     540   565.5   543.5   565.5   543.5   565.5     545   563.9     555
GR 566.1     560   565.3     565   565.4     570   564.1     575   566.2     580
GR 566.2     580   565.3   583.5   565.3   583.5   565.3     585   563.4     590
GR 564.4     595   565.4     600   567.7     605   571.1     610   573.5     615
GR 574.0     619   584.6     619   582.3     700   579.6     800   579.0     890
GR 578.7    1000
X1     61      41      500      619         1       1       1
BT      9   500.0   584.3   579.8   500.0   587.7   579.8   540.0   588.1   580.3
BT  543.5   588.1   580.3   560.0   588.3   580.3   580.0   588.1   580.3   583.5
BT  588.1   580.3   619.0   587.7   579.7   619.0   584.4   579.7
GR 576.2       0   575.9     100   576.6     200   578.5     300   581.1     400
GR 584.6     500   582.8     500   582.6     505   581.9     510   581.1     515
GR 579.2     520   575.4     525   574.8     530   572.8     535   569.2     540
GR 580.3     540   580.3   543.5   565.5   543.5   565.5     545   563.9     555
GR 566.1     560   565.3     565   565.4     570   564.1     575   566.2     580
GR 580.3     580   580.3   583.5   565.3   583.5   565.3     585   563.4     590
GR 564.4     595   565.4     600   567.7     605   571.1     610   573.5     615
GR 574.0     619   584.6     619   582.3     700   579.6     800   579.0     890
GR 578.7    1000
```

```
X2                                                                  1
X1   137      41      500     619       1       1       1
GR 576.2       0   575.9     100   576.6     200   578.5     300   581.1     400
GR 584.6     500   582.8     500   582.6     505   581.9     510   581.1     515
GR 579.2     520   575.4     525   574.8     530   572.8     535   569.2     540
GR 569.2     540   565.5   543.5   565.5   543.5   565.5     545   563.9     555
GR 566.1     560   565.3     565   565.4     570   564.1     575   566.2     580
GR 566.2     580   565.3   583.5   565.3   583.5   565.3     585   563.4     590
GR 564.4     595   565.4     600   567.7     605   571.1     610   573.5     615
GR 574.0     619   584.6     619   582.3     700   579.6     800   579.0     890
GR 578.7    1000
NC 0.035   0.042   0.032
X1   187      27     331     441      50      50      50
GR 575.8       0   576.6      41   578.5     141   580.6     241   583.1     331
GR 575.4     341   574.8     346   571.3     351   568.1     356   567.2     361
GR 565.7     366   565.1     371   565.5     376   565.1     381   564.7     391
GR 564.1     401   564.4     406   565.7     411   568.2     416   570.5     421
GR 572.8     426   574.8     432   580.2     441   583.6     454   581.0     541
GR 579.3     641   578.3     698
X1   362      35     244     400     175     175     175                 .27
GR 580.2       0   579.5     100   578.3     200   578.3     244   574.6     254
GR 573.6     255   571.5     260   569.8     265   568.5     270   567.6     275
GR 566.9     280   565.9     285   565.6     290   563.7     300   563.7     310
GR 564.3     320   565.8     330   568.2     340   569.8     345   571.1     350
GR 571.6     355   572.4     360   572.1     365   572.6     370   572.6     375
GR 572.8     380   572.8     385   572.9     390   574.6     395   576.9     400
GR 577.6     500   577.7     545   577.5     600   577.7     700   577.5     800
X1   737      35     244     400     375     375     375
GR 580.2       0   579.5     100   578.3     200   578.3     244   574.6     254
GR 573.6     255   571.5     260   569.8     265   568.5     270   567.6     275
GR 566.9     280   565.9     285   565.6     290   563.7     300   563.7     310
GR 564.3     320   565.8     330   568.2     340   569.8     345   571.1     350
GR 571.6     355   572.4     360   572.1     365   572.6     370   572.6     375
GR 572.8     380   572.8     385   572.9     390   574.6     395   576.9     400
GR 577.6     500   577.7     545   577.5     600   577.7     700   577.5     800
X1   787      67     795   901.6      50      50      50
GR 581.5       0   581.4      95   581.3     195   581.2     295   581.1     395
GR 581.1     495   581.1     595   581.0     695   581.0     795   575.2     795
GR 574.5     800   574.5     800   574.5     801   574.5     801   574.0     805
GR 573.2     810   573.2     810   573.2     811   573.2     811   570.8     815
GR 569.3     820   570.1     825   570.1     825   570.1     826   570.1     826
GR 566.6   829.9   566.6   829.9   566.6   831.2   566.6   831.2   565.5     835
GR 565.5     835   565.5     836   565.5     836   563.9     840   564.5     845
GR 564.5     845   564.5     846   564.5     846   564.9     850   564.9     855
GR 564.9     855   564.9     856   564.9     856   565.5     860   565.2     865
GR 565.2     865   565.2   866.3   565.3   866.3   566.0     870   566.0     875
GR 566.0     875   566.0     876   566.0     876   566.7     880   568.7     885
GR 568.3     890   569.7     895   571.7     900   571.7   901.6   581.0   901.6
GR 580.8     995   580.8    1095   580.6    1195   580.4    1295   580.1    1395
GR 579.9    1495   580.0    1540
X1   788      67     795   901.6       1       1       1
BT     4   795.0   581.0   577.2   830.0   581.0   577.2   860.0   581.0   577.2
BT 901.6   581.0   577.2
GR 581.5       0   581.4      95   581.3     195   581.2     295   581.1     395
GR 581.1     495   581.1     595   581.0     695   581.0     795   575.2     795
GR 574.5     800   575.5     800   575.5     801   574.5     801   574.0     805
GR 573.2     810   575.5     810   575.5     811   573.2     811   570.8     815
GR 569.3     820   570.1     825   575.5     825   575.5     826   570.1     826
GR 566.6     830   577.2     830   577.2   831.3   566.6   831.3   565.5     835
GR 575.5     835   575.5     836   565.5     836   563.9     840   564.5     845
GR 575.5     845   575.5     846   564.5     846   564.9     850   564.9     855
GR 575.5     855   575.5     856   564.9     856   565.5     860   565.2     865
GR 577.2     865   577.2   866.3   565.2   866.3   566.0     870   566         875
GR 575.5     875   575.5     876   566.0     876   566.7     880               85
GR 568.3     890   569.7     895   571.7     900   571.7   901.6               .6
```

GR	579.9	1495	580.0	1540					
X1	797	0	795	901.6	9	9	9		
X2							1		
X1	798	67	795	901.6	1	1	1		
GR	581.5	0	581.4	95	581.3	195	581.2	295	581.1	395
GR	581.1	495	581.1	595	581.0	695	581.0	795	575.2	795
GR	574.5	800	574.5	800	574.5	801	574.5	801	574.0	805
GR	573.2	810	573.2	810	573.2	811	573.2	811	570.8	815
GR	569.3	820	570.1	825	570.1	825	570.1	826	570.1	826
GR	566.6	829.9	566.6	829.9	566.6	831.2	566.6	831.2	565.5	835
GR	565.5	835	565.5	836	565.5	836	563.9	840	564.5	845
GR	564.5	845	564.5	846	564.5	846	564.9	850	564.9	855
GR	564.9	855	564.9	856	564.9	856	565.5	860	565.2	865
GR	565.2	865	565.2	866.3	565.3	866.3	566.0	870	566.0	875
GR	566.0	875	566.0	876	566.0	876	566.7	880	568.7	885
GR	568.3	890	569.7	895	571.7	900	571.7	901.6	581.0	901.6
GR	580.8	995	580.8	1095	580.6	1195	580.4	1295	580.1	1395
GR	579.9	1495	580.0	1540						
X1	844	58	815	924	46	46	46			
GR	583.4	0	583.4	15	583.1	115	582.9	215	582.8	315
GR	582.6	415	582.3	515	582.1	615	581.8	715	581.5	815
GR	576.1	815	574.2	820	572.7	825	570.0	829	570.0	829
GR	570.0	830	570.0	830	568.0	835	565.9	840	565.0	844
GR	565.0	844	565.0	845	565.0	845	565.0	855	566.0	864
GR	566.0	864	566.0	865	566.0	865	566.1	874	566.1	874
GR	566.1	875	566.1	875	565.8	884	565.8	884	565.8	885
GR	565.8	885	565.6	890	565.2	894	565.2	894	565.2	895
GR	565.2	895	567.6	900	570.3	905	572.0	909	572.0	909
GR	572.0	910	572.0	910	574.0	915	575.1	920	576.2	924
GR	581.4	924	581.3	1015	581.3	1115	581.1	1215	581.1	1315
GR	581.1	1415	581.2	1515	581.2	1565				
X1	845	58	815	924	1	1	1			
BT	16	815.0	581.5	578.4	829.0	581.5	578.1	830.0	581.5	578.1
BT	844.0	581.5	577.9	845.0	581.5	577.9	864.0	581.5	577.5	865.0
BT	581.5	577.5	874.0	581.4	577.4	875.0	581.4	577.4	884.0	581.4
BT	577.2	885.0	581.4	577.2	894.0	581.4	577.0	895.0	581.4	577.0
BT	909.0	581.4	576.8	910.0	581.4	576.8	924.0	581.4	576.5	
GR	583.4	0	583.4	15	583.1	115	582.9	215	582.8	315
GR	582.6	415	582.3	515	582.1	615	581.8	715	581.5	815
GR	576.1	815	574.2	820	572.7	825	570.0	829	578.1	829
GR	578.1	830	570.0	830	568.0	835	565.9	840	565.0	844
GR	577.9	844	577.9	845	565.0	845	565.0	855	566.0	864
GR	577.5	864	577.5	865	566.0	865	566.1	874	577.4	874
GR	577.4	875	566.1	875	565.8	884	577.2	884	577.2	885
GR	565.8	885	565.6	890	565.2	894	577.0	894	577.0	895
GR	565.2	895	567.6	900	570.3	905	572.0	909	576.8	909
GR	576.8	910	572.0	910	574.0	915	575.1	920	576.2	924
GR	581.4	924	581.3	1015	581.3	1115	581.1	1215	581.1	1315
GR	581.1	1415	581.2	1515	581.2	1565				
X1	859		815	924	14.5	14.5	14.5			
X2							1			
X1	860	58	815	924	1	1	1			
GR	583.4	0	583.4	15	583.1	115	582.9	215	582.8	315
GR	582.6	415	582.3	515	582.1	615	581.8	715	581.5	815
GR	576.1	815	574.2	820	572.7	825	570.0	829	570.0	829
GR	570.0	830	570.0	830	568.0	835	565.9	840	565.0	844
GR	565.0	844	565.0	845	565.0	845	565.0	855	566.0	864
GR	566.0	864	566.0	865	566.0	865	566.1	874	566.1	874
GR	566.1	875	566.1	875	565.8	884	565.8	884	565.8	885
GR	565.8	885	565.6	890	565.2	894	565.2	894	565.2	895
GR	565.2	895	567.6	900	570.3	905	572.0	909	572.0	909
GR	572.0	910	572.0	910	574.0	915	575.1	920	576.2	924
GR	581.4	924	581.3	1015	581.3	1115	581.1	1215	581.1	1315
GR	581.1	1415	581.2	1515	581.2	1565				
X1	910	64	835	942	50	50	50			

```
GR 583.3     435   583.3     535   583.2     635   583.1     735   583.1     835
GR 574.8     835   572.6     840   571.6     844   571.6     844   571.6     845
GR 571.6     845   570.7     854   570.7     854   570.7     855   570.7     855
GR 565.6     864   565.6     864   565.6     865   565.6     865   564.3     874
GR 564.3     874   564.3     875   564.3     875   564.8     884   564.8     884
GR 564.8     885   564.8     885   564.9     894   564.9     894   564.9     895
GR 564.9     895   564.0     904   564.0     904   564.0     905   564.0     905
GR 566.1     914   566.1     914   566.1     915   566.1     915   567.0     920
GR 571.0     924   571.0     924   571.0     925   571.0     925   572.4     930
GR 573.9     934   573.9     934   573.9     935   573.9     935   575.0     940
GR 574.9     942   583.0     942   582.7    1035   582.6    1135   582.3    1235
GR 582.1    1335   581.9    1435   581.8    1535   581.8    1585
X1   911      64     835     942       1       1       1
BT     6  835.0   583.1   578.6   874.0   583.1   578.6   875.0   583.1   578.6
BT 904.0   583.0   578.6   905.0   583.0   578.6   942.0   583.0   578.6
GR 583.7       0   583.6      35   583.4     135   583.3     235   583.3     335
GR 583.3     435   583.3     535   583.2     635   583.1     735   583.1     835
GR 574.8     835   572.6     840   571.6     844   575.5     844   575.5     845
GR 571.6     845   570.7     854   575.5     854   575.5     855   570.7     855
GR 565.6     864   575.5     864   575.5     865   565.6     865   564.3     874
GR 578.6     874   578.6     875   564.3     875   564.8     884   575.5     884
GR 575.5     885   564.8     885   564.9     894   575.5     894   575.5     895
GR 564.9     895   564.0     904   578.6     904   578.6     905   564.0     905
GR 566.1     914   575.5     914   575.5     915   566.1     915   567.0     920
GR 571.0     924   575.5     924   575.5     925   571.0     925   572.4     930
GR 573.9     934   575.5     934   575.5     935   573.9     935   575.0     940
GR 574.9     942   583.0     942   582.7    1035   582.6    1135   582.3    1235
GR 582.1    1335   581.9    1435   581.8    1535   581.8    1585
X1   921             835     942      10      10      10
X2                                                    1
X1   922      64     835     942       1       1       1
GR 583.7       0   583.6      35   583.4     135   583.3     235   583.3     335
GR 583.3     435   583.3     535   583.2     635   583.1     735   583.1     835
GR 574.8     835   572.6     840   571.6     844   571.6     844   571.6     845
GR 571.6     845   570.7     854   570.7     854   570.7     855   570.7     855
GR 565.6     864   565.6     864   565.6     865   565.6     865   564.3     874
GR 564.3     874   564.3     875   564.3     875   564.8     884   564.8     884
GR 564.8     885   564.8     885   564.9     894   564.9     894   564.9     895
GR 564.9     895   564.0     904   564.0     904   564.0     905   564.0     905
GR 566.1     914   566.1     914   566.1     915   566.1     915   567.0     920
GR 571.0     924   571.0     924   571.0     925   571.0     925   572.4     930
GR 573.9     934   573.9     934   573.9     935   573.9     935   575.0     940
GR 574.9     942   583.0     942   582.7    1035   582.6    1135   582.3    1235
GR 582.1    1335   581.9    1435   581.8    1535   581.8    1585
X1   953      48     600     681      31      31      31
GR 582.0       0   581.8     100   581.6     200   581.5     300   581.4     400
GR 581.2     500   581.0     600   571.0     600   568.1     605   566.9     610
GR 566.9     610   566.9   612.3   566.9   612.3   565.9     615   565.1     620
GR 565.1     620   565.1   622.3   565.1   622.3   566.3     625   566.2     630
GR 566.2     630   566.2   632.3   566.2   632.3   566.7     635   566.4     640
GR 566.1     645   566.4     650   566.4     650   566.4   652.3   566.4   652.3
GR 566.6     655   567.5     660   567.5     660   567.5   662.3   567.5   662.3
GR 567.5     665   569.9     670   569.9     670   569.9   672.3   569.9   672.3
GR 573.4     680   573.4     681   580.8     681   580.8     700   580.7     800
GR 580.6     900   580.6    1000   580.5    1100
X1   954      48     600     681       1       1       1
BT    14  600.0   581.0   577.7   610.0   581.0   577.7   612.3   581.0   577.7
BT 620.0   581.0   577.7   622.3   581.0   577.7   630.0   580.9   577.7   632.3
BT 580.9   577.7   650.0   580.9   577.6   652.3   580.9   577.6   660.0   580.9
BT 577.6   662.3   580.8   577.6   670.0   580.8   577.6   672.3   580.8   577.6
BT 681.0   580.8   577.6
GR 582.0       0   581.8     100   581.6     200   581.5     300   581.4     400
GR 581.2     500   581.0     600   571.0     600   568.1     605   566.9     610
GR 577.7     610   577.7   612.3   566.9   612.3   565.9     615   565.1     620
GR 577.7     620   577.7   622.3   565.1   622.3   566.3     625   566.2     630
```

```
GR 566.1     645   566.4     650   577.6     650   577.6   652.3   566.4   652.3
GR 566.6     655   567.5     660   577.6     660   577.6   662.3   567.5   662.3
GR 567.5     665   569.9     670   577.6     670   577.6   672.3   569.9   672.3
GR 573.4     680   573.4     681   580.8     681   580.8     700   580.7     800
GR 580.6     900   580.6    1000   580.5    1100
X1   985             600     681    30.5    30.5    30.5
X2                                                   1
X1   986      48     600     681       1       1       1
GR 582.0       0   581.8     100   581.6     200   581.5     300   581.4     400
GR 581.2     500   581.0     600   571.0     600   568.1     605   566.9     610
GR 566.9     610   566.9   612.3   566.9   612.3   565.9     615   565.1     620
GR 565.1     620   565.1   622.3   565.1   622.3   566.3     625   566.2     630
GR 566.2     630   566.2   632.3   566.2   632.3   566.7     635   566.4     640
GR 566.1     645   566.4     650   566.4     650   566.4   652.3   566.4   652.3
GR 566.6     655   567.5     660   567.5     660   567.5   662.3   567.5   662.3
GR 567.5     665   569.9     670   569.9     670   569.9   672.3   569.9   672.3
GR 573.4     680   573.4     681   580.8     681   580.8     700   580.7     800
GR 580.6     900   580.6    1000   580.5    1100
NC 0.040   0.035   0.032
X1  1036      37     565     700      50      50      50
X3    10                                     700
GR 581.9       0   581.2     100   581.2     200   580.8     300   581.0     400
GR 579.9     500   581.1     565   575.4     587   574.9     590   573.9     595
GR 572.5     600   571.0     605   569.8     610   568.8     615   568.0     620
GR 567.4     625   566.6     630   566.3     635   566.2     640   566.3     650
GR 566.8     660   568.3     670   570.2     675   570.4     680   571.7     685
GR 573.1     690   574.8     695   574.9     696   577.7     700   577.5     800
GR 576.6     900   576.6    1000   577.0    1030   576.8    1100   577.5    1200
GR 578.3    1300   579.2    1345
NC 0.060   0.035   0.032
X1  1736      40     374   492.5     700     700     700
X3    10
GR 580.4       0   580.4     167   579.5   283.7   578.8   335.3   579.1     374
GR 577.2   377.9   576.1   381.9   575.1   385.8   574.1   389.8   573.2   393.7
GR 572.4   397.7   571.5   401.6   570.3   405.6   569.4   409.5   568.4   413.5
GR 567.6   417.4   566.9   421.4   566.5   425.3   566.0   429.2   565.7   433.2
GR 565.5   437.2   565.4   441.1   565.5   445.0   565.6   449.0   565.9   453.0
GR 566.5   456.9   567.2   460.8   568.0   464.8   569.0   468.7   569.8   472.7
GR 570.6   476.6   571.7   480.6   573.4   484.5   575.1   488.5   577.5   492.5
GR 577.4     550   577.3     650   577.4     750   577.7     890   579.5     975
X1  2436      31     183     285     700     700     700
X3                                           485.0
GR 579.0       0   579.9      85   578.5     135   577.1     183   575.1     185
GR 573.5     190   572.2     195   571.1     200   570.2     205   568.5     210
GR 567.7     215   566.4     220   565.6     225   565.3     230   565.0     235
GR 564.6     240   564.8     245   565.2     250   566.4     255   567.8     260
GR 568.8     265   569.9     270   571.5     275   574.7     280   575.1     281
GR 577.4     285   577.3     385   578.2     485   577.7     557   578.6     585
GR 579.8     605
QT      4   1120    1620    1760    2055
X1  3186      25     200     300     750     750     750
X3    10                                     500
GR 580.6       0   583.1     100   581.3     200   579.6     208   575.2     216
GR 573.9     220   571.6     225   569.9     230   569.9     235   569.3     240
GR 569.1     245   568.8     250   569.2     260   570.8     270   571.1     280
GR 571.7     285   573.0     290   574.1     295   576.4     300   577.9     400
GR 579.0     500   579.1     600   578.7     625   578.7     700   578.9     800
X1  3686                             500     500     500                 .6
X3    10                                     500
NC 0.040   0.037   0.032
X1  4186      27     417     500     500     500     500
X3    10                     350             550
GR 581.8       0   580.9     100   580.6     200   580.0     300   578.9     400
GR 578.2     417   575.0     419   574.7     420   573.0     425   571.2     430
GR 570.5     435   570.4     440   570.4     445   570.3     450   570.0     455
```

GR	572.5	485	573.2	490	575.0	494	578.7	500	579.5	600
GR	581.0	700	583.0	770						
NC	0.030	0.030	0.030							
X1	4236	32	592	644	50	50	50			
X3	10			592		644				
GR	582.0	0	581.6	92	581.2	192	580.8	292	580.7	392
GR	580.0	492	580.1	592	570.2	592	569.2	597	570.0	602
GR	569.7	607	569.0	612	568.1	617	568.1	617	568.1	618.5
GR	568.1	618.5	568.9	622	568.8	627	569.2	632	570.0	637
GR	570.6	642	570.6	644	580.0	644	579.3	692	579.6	792
GR	580.4	892	580.7	992	580.5	1092	580.3	1192	580.0	1292
GR	579.6	1392	579.3	1492						
SB	1.25	1.37	2.5		50.5	1.5	400	0	568.1	568.1
X1	4281	32	592	644	45	45	45			
X2			1	577.4	580.0					
X3	10			592		644				
BT	6	592.0	580.1	577.4	617	580.0	577.3	617	580.0	568.1
BT	618.5	580.0	568.1	618.5	580.0	577.3	644.0	580.0	577.3	
GR	582.0	0	581.6	92	581.2	192	580.8	292	580.7	392
GR	580.0	492	580.1	592	570.2	592	569.2	597	570.0	602
GR	569.7	607	569.0	612	568.1	617	568.1	617	568.1	618.5
GR	568.1	618.5	568.9	622	568.8	627	569.2	632	570.0	637
GR	570.6	642	570.6	644	580.0	644	579.3	692	579.6	792
GR	580.4	892	580.7	992	580.5	1092	580.3	1192	580.0	1292
GR	579.6	1392	579.3	1492						
NC	0.040	0.037	0.032							
X1	4931	23	115	200	650	650	650			
X3	10			115		200				
GR	582.2	0	581.6	37	580.8	100	580.9	115	575.3	124
GR	574.6	125	571.5	130	570.8	135	570.5	140	570.3	145
GR	570.3	150	570.3	155	570.4	160	570.6	165	570.8	170
GR	571.1	175	571.3	180	573.1	185	573.6	190	575.3	195
GR	579.8	200	579.1	300	580.1	400				
X1	5956				1025	1025	1025		.35	
X3	10			115		200				
X1	6981	29	505	600	1025	1025	1025			
X3	10							582.6	582.0	
GR	582.8	0	581.3	100	581.3	200	580.9	300	579.7	400
GR	579.4	425	582.7	500	582.6	505	576.0	517	575.2	520
GR	572.0	525	571.8	530	572.2	535	572.3	540	571.1	545
GR	571.1	550	571.0	560	571.2	570	572.4	575	572.5	580
GR	574.2	584	575.2	588	582.0	600	579.1	700	581.5	800
GR	580.8	900	581.0	920	581.3	1000	581.2	1100		
X1	8031	27	150	246	1050	1050	1050			
X3				150		246				
GR	580.3	0	580.4	50	580.7	78	578.9	114	580.7	150
GR	579.0	155	575.2	162	573.8	166	572.8	170	572.3	175
GR	572.0	180	571.7	190	571.5	200	571.5	210	571.7	215
GR	571.8	220	572.5	225	573.6	230	575.2	235	577.8	238
GR	579.4	246	579.4	250	578.6	336	578.5	350	579.2	450
GR	578.9	492	580.5	550						
NC	0.030	0.030	0.030							
X1	8082	39	580	655	51	51	51			
X3	10			580		655				
GR	578.6	0	578.1	80	578.0	180	577.7	280	577.6	380
GR	577.9	480	580.9	580	571.8	580	572.2	585	571.7	590
GR	571.5	595	571.2	600	570.4	605	578.3	605	578.3	606.5
GR	570.4	606.5	571.4	610	571.0	615	570.9	620	571.0	625
GR	571.0	630	578.3	630	578.3	631.5	571.0	631.5	571.1	635
GR	570.9	640	570.8	645	570.3	650	569.9	655	581.1	655
GR	580.3	680	578.9	780	578.5	830	578.3	880	577.9	980
GR	577.5	1080	577.3	1180	577.7	1280	577.6	1380		
SB	1.25	1.56	2.6		75	3	519		569.9	569.9
X1	8147		580	655	65	65	65			
X2			1	578.4	580.9				.631	

```
BT      6   580.0   580.9   578.2   605.0   581.0   578.3   606.5   581.0   578.3
BT  630.0   581.0   578.3   631.5   581.0   578.3   655.0   581.1   578.4
NC  0.035   0.040   0.032
X1   9397      28     550     635    1250    1250    1250
X3                         550             635
GR  580.8       0   581.5     150   580.7     250   579.8     355   580.8     450
GR  579.3     550   578.8     555   574.7     564   573.7     570   573.2     575
GR  572.2     580   572.0     585   572.1     590   571.8     595   571.8     600
GR  571.9     605   572.2     610   572.5     615   572.8     620   573.2     625
GR  574.7     626   581.7     635   582.0     650   582.1     750   583.1     850
GR  582.6     950   582.2    1050   581.9    1150
X1  10297      29     400     480     900     900     900
X3     10                         480
GR  583.1       0   582.7     100   582.2     200   582.1     220   582.9     300
GR  583.4     400   573.8     416   572.9     420   572.0     425   572.0     430
GR  572.0     435   571.8     440   572.0     445   572.2     450   572.2     455
GR  572.5     460   572.8     465   573.4     470   574.5     475   581.9     480
GR  581.4     500   580.9     600   581.0     700   581.6     800   581.9     900
GR  582.8    1000   582.6    1100   582.9    1200   583.4    1300
NC  0.035   0.035   0.032
X1  10897      23     112     185     600     600     600
X3                     112.00             185.00
GR  580.7       0   581.2      85   580.4     112   574.8     122   574.5     123
GR  573.5     125   572.9     130   572.4     135   572.2     140   572.3     150
GR  572.7     155   572.8     160   573.2     165   573.0     170   573.0     176
GR  574.5     178   579.4     185   581.8     231   583.7     243   583.1     285
GR  584.4     355   582.6     385   583.5     477
X1  10973      30     500     552      76      76      76
X3     10                         500             552
GR  582.2       0   581.9     100   581.4     200   580.9     300   580.8     400
GR  581.2     448   581.7     500   571.7     500   571.9     505   571.8     510
GR  571.8     515   571.8     520   572.1     525   579.0     525   579.0     527
GR  572.1     527   572.6     530   573.0     535   573.7     540   573.7     545
GR  573.6     550   573.4     552   581.6     552   580.4     600   581.1     700
GR  581.4     800   581.6     900   581.8    1000   582.0    1100   582.1    1122
SB     .9    1.47     2.5              52     2.0     315            571.7   571.7
X1  11017              500     552      44      44      44
X2                       1   579.0    581.7
X3     10                         500   590.0     552   590.0
BT      4   500.0   581.7   578.9   525.0   581.7   579.0   527.0   581.7   579.0
BT  552.0   581.6   578.9
NC  0.060   0.060   0.032
X1  11477      22     155     236     460     460     460
X3                         155             255
GR  583.1       0   583.4      50   583.4     110   582.9     155   574.9     170
GR  573.9     175   573.7     180   572.8     185   572.9     190   572.9     195
GR  572.9     200   572.7     205   572.4     210   571.8     215   573.1     220
GR  574.4     225   575.5     227   581.4     236   582.6     255   582.2     265
GR  582.1     310   582.2     343
X1  11528      35     530   582.5      51      51      51
X3     10                         530             582.5
GR  584.4       0   584.8      30   584.4     130   583.9     230   583.5     330
GR  582.9     370   582.9     430   583.0     530   573.0     530   573.4     535
GR  573.0     540   572.7     545   572.5     550   572.1   555.2   580.6   555.2
GR  580.6   557.2   572.8   557.2   572.8     560   572.7     565   572.5     570
GR  572.4     575   572.6     580   572.5   582.5   582.8   582.5   582.2     630
GR  582.2     730   583.3     830   582.9     880   583.1     930   583.9    1030
GR  584.1    1130   584.4    1230   584.1    1330   583.7    1430   583.9    1439
SB   1.25    1.61     2.5              52.5     2.0     400            572.1   572.1
X1  11599              530   582.5      71      71      71
X2                       1   580.7    582.8
X3     10                         530             582.5
BT      4   530.0   583.0   580.7   555.2   582.9   580.6   557.2   582.9   580.6
BT  582.5   582.8   580.5
X1  11650      36     548     604      51      51      51
```

```
GR 584.8       0   584.5      48   584.3     148   584.1     248   583.6     348
GR 583.0     448   583.4     548   573.4     548   573.7     553   573.3     558
GR 573.0     563   572.6     568   572.6     573   572.6   573.5   580.7   573.5
GR 580.7   575.5   572.5   575.5   572.4     578   572.1     583   572.6     588
GR 572.1     593   572.6     598   572.4     601   580.5     604   583.2     604
GR 582.4     648   581.9     748   582.4     823   582.9     848   583.3     948
GR 583.8    1048   584.1    1148   584.5    1248   584.3    1348   583.9    1448
GR 584.3    1558
SB  1.25    1.61     2.5                  56     2.0     400           572.1  572.1
X1 11721             548     604      71      71      71
X2                     1   580.7   583.2
X3    10                   548              604
BT     4   548.0   583.4   580.7   573.5   583.3   580.7   575.5   583.3   580.7
BT 604.0   583.2   580.5
EJ
T1       CITY OF WYANDOTTE FIS 5555-73
T2       SEXTON-KILFOIL DRAIN
T3       50 YEAR FLOOD  4100 CFS
J1   -10       3                                                  574.90
J2     2              -1
T1       CITY OF WYANDOTTE FIS 5555-73
T2       SEXTON-KILFOIL DRAIN
T3       100 YEAR FLOOD 4410 CFS
J1   -10       4                                                  574.90
J2     3              -1
T1       CITY OF WYANDOTTE 5555-73
T2       SEXTON-KILFOIL DRAIN
T3       500 YEAR FLOOD 5160 CFS
J1   -10       5                                                  574.90
J2    15              -1


ER
```

SUMMARY PRINTOUT FOR MULTIPLE PROFILES

500 YEAR FLOOD 5160 CFS

SECTION NUMBER	CHANNEL LENGTH	MIN EL OF ROADWAY	MAX EL OF LOW CHORD	MIN EL GROUND	DISCHARGE (CFS)	CWSEL	CRIWS	EG	TOPWID	10K*S	TIME	VOL
1.00	0.00	0.00	0.00	563.40	3165.00	574.90	0.00	575.22	89.83	6.84	0.00	0.00
1.00	0.00	0.00	0.00	563.40	4100.00	574.90	0.00	575.43	89.83	11.48	0.00	0.00
1.00	0.00	0.00	0.00	563.40	4410.00	574.90	0.00	575.51	89.83	13.28	0.00	0.00
1.00	0.00	0.00	0.00	563.40	5160.00	574.90	0.00	575.74	89.83	18.18	0.00	0.00
30.00	29.00	0.00	0.00	563.40	3165.00	574.92	0.00	575.24	90.00	6.80	.00	.47
30.00	29.00	0.00	0.00	563.40	4100.00	574.94	0.00	575.47	90.11	11.36	.00	.47
30.00	29.00	0.00	0.00	563.40	4410.00	574.95	0.00	575.55	90.15	13.12	.00	.47
30.00	29.00	0.00	0.00	563.40	5160.00	574.97	0.00	575.80	90.33	17.85	.00	.47
60.00	30.00	0.00	0.00	563.40	3165.00	574.94	0.00	575.26	90.17	6.76	.00	.95
60.00	30.00	0.00	0.00	563.40	4100.00	574.98	0.00	575.50	90.44	11.23	.00	.95
60.00	30.00	0.00	0.00	563.40	4410.00	574.99	0.00	575.60	90.55	12.94	.00	.95
60.00	30.00	0.00	0.00	563.40	5160.00	575.04	0.00	575.85	91.04	17.41	.00	.96
61.00	1.00	584.30	580.30	563.40	3165.00	574.91	0.00	575.29	82.95	12.29	.00	.97
61.00	1.00	584.30	580.30	563.40	4100.00	574.93	0.00	575.56	83.07	20.54	.00	.97
61.00	1.00	584.30	580.30	563.40	4410.00	574.93	0.00	575.66	83.12	23.72	.00	.97
61.00	1.00	584.30	580.30	563.40	5160.00	574.96	0.00	575.94	83.33	32.24	.00	.97
136.00	75.00	584.30	580.30	563.40	3165.00	575.02	0.00	575.38	83.82	11.93	.01	2.08
136.00	75.00	584.30	580.30	563.40	4100.00	575.12	0.00	575.71	84.64	19.46	.01	2.09
136.00	75.00	584.30	580.30	563.40	4410.00	575.16	0.00	575.84	85.00	22.24	.01	2.10
136.00	75.00	584.30	580.30	563.40	5160.00	575.30	0.00	576.20	86.14	29.29	.01	2.11
137.00	1.00	0.00	0.00	563.40	3165.00	575.10	0.00	575.40	91.53	6.44	.01	2.10
137.00	1.00	0.00	0.00	563.40	4100.00	575.27	0.00	575.75	92.89	10.29	.01	2.11
137.00	1.00	0.00	0.00	563.40	4410.00	575.34	0.00	575.88	93.47	11.66	.01	2.11
137.00	1.00	0.00	0.00	563.40	5160.00	575.54	0.00	576.26	94.19	14.81	.01	2.13
187.00	50.00	0.00	0.00	564.10	3165.00	575.12	0.00	575.46	89.16	7.37	.01	2.90
187.00	50.00	0.00	0.00	564.10	4100.00	575.29	0.00	575.84	90.88	11.75	.01	2.93
187.00	50.00	0.00	0.00	564.10	4410.00	575.36	0.00	575.98	91.61	13.31	.01	2.94
187.00	50.00	0.00	0.00	564.10	5160.00	575.58	0.00	576.38	92.53	16.82	.01	2.98
362.00	175.00	0.00	0.00	563.97	3165.00	575.42	0.00	575.61	143.71	4.75	.03	6.10
362.00	175.00	0.00	0.00	563.97	4100.00	575.80	0.00	576.07	145.52	6.71	.02	6.27
362.00	175.00	0.00	0.00	563.97	4410.00	575.94	0.00	576.25	146.24	7.28	.02	6.34
362.00	175.00	0.00	0.00	563.97	5160.00	576.34	0.00	576.71	148.20	8.37	.02	6.53
737.00	375.00	0.00	0.00	563.70	3165.00	575.62	0.00	575.78	145.95	3.85	.06	14.31
737.00	375.00	0.00	0.00	563.70	4100.00	576.07	0.00	576.31	148.18	5.30	.05	15.00
737.00	375.00	0.00	0.00	563.70	4410.00	576.24	0.00	576.50	149.01	5.70	.04	15.27
737.00	375.00	0.00	0.00	563.70	5160.00	576.69	0.00	577.01	151.21	6.51	.04	16.01
787.00	50.00	0.00	0.00	563.90	3165.00	575.59	0.00	575.85	106.60	5.92	.06	15.32
787.00	50.00	0.00	0.00	563.90	4100.00	576.03	0.00	576.41	106.60	8.26	.05	16.08
787.00	50.00	0.00	0.00	563.90	4410.00	576.20	0.00	576.62	106.60	8.95	.05	16.37
787.00	50.00	0.00	0.00	563.90	5160.00	576.63	0.00	577.15	106.60	10.35	.04	17.18

SECTION NUMBER	CHANNEL LENGTH	MIN EL OF ROADWAY	MAX EL OF LOW CHORD	MIN EL GROUND	DISCHARGE (CFS)	CWSEL	CRIWS	EG	TOPWID	10K*S	TIME	VOL
788.00	1.00	581.00	577.20	563.90	3165.00	575.56	0.00	575.88	104.00	23.72	.06	15.34
788.00	1.00	581.00	577.20	563.90	4100.00	575.99	0.00	576.46	104.00	32.91	.05	16.10
788.00	1.00	581.00	577.20	563.90	4410.00	576.15	0.00	576.67	104.00	35.54	.05	16.39
788.00	1.00	581.00	577.20	563.90	5160.00	576.58	0.00	577.21	104.00	40.86	.04	17.20
797.00	9.00	581.00	577.20	563.90	3165.00	575.59	0.00	575.90	104.00	23.58	.06	15.49
797.00	9.00	581.00	577.20	563.90	4100.00	576.02	0.00	576.49	104.00	32.55	.05	16.25
797.00	9.00	581.00	577.20	563.90	4410.00	576.19	0.00	576.70	104.00	35.13	.05	16.55
797.00	9.00	581.00	577.20	563.90	5160.00	576.62	0.00	577.25	104.00	40.12	.04	17.37
798.00	1.00	0.00	0.00	563.90	3165.00	575.67	0.00	575.92	106.60	5.72	.06	15.50
798.00	1.00	0.00	0.00	563.90	4100.00	576.15	0.00	576.52	106.60	7.89	.05	16.27
798.00	1.00	0.00	0.00	563.90	4410.00	576.32	0.00	576.73	106.60	8.51	.05	16.57
798.00	1.00	0.00	0.00	563.90	5160.00	576.79	0.00	577.29	106.60	9.78	.04	17.39
844.00	46.00	0.00	0.00	565.00	3165.00	575.70	0.00	575.95	106.11	5.36	.06	16.34
844.00	46.00	0.00	0.00	565.00	4100.00	576.19	0.00	576.55	108.96	7.52	.05	17.16
844.00	46.00	0.00	0.00	565.00	4410.00	576.37	0.00	576.77	109.00	8.09	.05	17.48
844.00	46.00	0.00	0.00	565.00	5160.00	576.84	0.00	577.33	109.00	9.24	.05	18.35
845.00	1.00	581.40	578.40	565.00	3165.00	575.68	0.00	575.97	98.98	17.86	.07	16.36
845.00	1.00	581.40	578.40	565.00	4100.00	576.16	0.00	576.59	101.84	25.65	.05	17.18
845.00	1.00	581.40	578.40	565.00	4410.00	576.33	0.00	576.81	102.00	27.95	.05	17.50
845.00	1.00	581.40	578.40	565.00	5160.00	576.80	0.00	577.38	102.00	35.77	.05	18.37
859.00	14.50	581.40	578.40	565.00	3165.00	575.70	0.00	575.99	99.12	17.73	.07	16.60
859.00	14.50	581.40	578.40	565.00	4100.00	576.20	0.00	576.63	101.96	25.38	.05	17.44
859.00	14.50	581.40	578.40	565.00	4410.00	576.38	0.00	576.85	102.00	27.51	.05	17.76
859.00	14.50	581.40	578.40	565.00	5160.00	576.86	0.00	577.43	103.00	37.02	.05	18.65
860.00	1.00	0.00	0.00	565.00	3165.00	575.77	0.00	576.01	106.54	5.22	.07	16.62
860.00	1.00	0.00	0.00	565.00	4100.00	576.29	0.00	576.65	109.00	7.21	.05	17.46
860.00	1.00	0.00	0.00	565.00	4410.00	576.48	0.00	576.88	109.00	7.73	.05	17.78
860.00	1.00	0.00	0.00	565.00	5160.00	576.99	0.00	577.47	109.00	8.74	.05	18.67
910.00	50.00	0.00	0.00	564.00	3165.00	575.81	0.00	576.04	107.00	4.79	.07	17.55
910.00	50.00	0.00	0.00	564.00	4100.00	576.36	0.00	576.69	107.00	6.48	.06	18.46
910.00	50.00	0.00	0.00	564.00	4410.00	576.56	0.00	576.92	107.00	6.96	.05	18.81
910.00	50.00	0.00	0.00	564.00	5160.00	577.07	0.00	577.52	107.00	7.95	.05	19.76
911.00	1.00	583.00	578.60	564.00	3165.00	575.79	0.00	576.07	105.00	21.37	.07	17.57
911.00	1.00	583.00	578.60	564.00	4100.00	576.32	0.00	576.73	105.00	28.62	.06	18.48
911.00	1.00	583.00	578.60	564.00	4410.00	576.52	0.00	576.96	105.00	30.62	.05	18.83
911.00	1.00	583.00	578.60	564.00	5160.00	577.03	0.00	577.56	105.00	34.49	.05	19.78
921.00	10.00	583.00	578.60	564.00	3165.00	575.81	0.00	576.09	105.00	21.25	.07	17.74
921.00	10.00	583.00	578.60	564.00	4100.00	576.35	0.00	576.76	105.00	28.34	.06	18.66
921.00	10.00	583.00	578.60	564.00	4410.00	576.55	0.00	576.99	105.00	30.30	.05	19.02
921.00	10.00	583.00	578.60	564.00	5160.00	577.07	0.00	577.60	105.00	34.11	.05	19.98

SECTION NUMBER	CHANNEL LENGTH	MIN EL OF ROADWAY	MAX EL OF LOW CHORD	MIN EL GROUND	DISCHARGE (CFS)	CWSEL	CRIWS	EG	TOPWID	10K*S	TIME	VOL
922.00	1.00	0.00	0.00	564.00	3165.00	575.88	0.00	576.11	107.00	4.66	.07	17.76
922.00	1.00	0.00	0.00	564.00	4100.00	576.46	0.00	576.78	107.00	6.26	.06	18.68
922.00	1.00	0.00	0.00	564.00	4410.00	576.66	0.00	577.02	107.00	6.71	.05	19.04
922.00	1.00	0.00	0.00	564.00	5160.00	577.20	0.00	577.63	107.00	7.61	.05	20.00
953.00	31.00	0.00	0.00	565.10	3165.00	575.84	0.00	576.18	81.00	6.97	.07	18.30
953.00	31.00	0.00	0.00	565.10	4100.00	576.39	0.00	576.89	81.00	9.62	.06	19.26
953.00	31.00	0.00	0.00	565.10	4410.00	576.59	0.00	577.14	81.00	10.40	.06	19.63
953.00	31.00	0.00	0.00	565.10	5160.00	577.10	0.00	577.78	81.00	12.04	.05	20.63
954.00	1.00	580.80	577.70	565.10	3165.00	575.76	0.00	576.27	67.20	35.26	.07	18.31
954.00	1.00	580.80	577.70	565.10	4100.00	576.26	0.00	577.03	67.20	50.97	.06	19.27
954.00	1.00	580.80	577.70	565.10	4410.00	576.44	0.00	577.29	67.20	56.00	.06	19.64
954.00	1.00	580.80	577.70	565.10	5160.00	576.92	0.00	577.97	67.20	67.38	.05	20.65
985.00	30.50	580.80	577.70	565.10	3165.00	575.88	0.00	576.38	67.20	33.95	.07	18.70
985.00	30.50	580.80	577.70	565.10	4100.00	576.46	0.00	577.19	67.20	48.26	.06	19.68
985.00	30.50	580.80	577.70	565.10	4410.00	576.66	0.00	577.47	67.20	52.74	.06	20.06
985.00	30.50	580.80	577.70	565.10	5160.00	577.20	0.00	578.19	67.20	62.75	.05	21.09
986.00	1.00	0.00	0.00	565.10	3165.00	576.12	0.00	576.44	81.00	6.31	.07	18.71
986.00	1.00	0.00	0.00	565.10	4100.00	576.82	0.00	577.27	81.00	8.33	.06	19.70
986.00	1.00	0.00	0.00	565.10	4410.00	577.07	0.00	577.57	81.00	8.89	.06	20.08
986.00	1.00	0.00	0.00	565.10	5160.00	577.70	0.00	578.30	81.00	10.00	.05	21.11
1036.00	50.00	0.00	0.00	566.20	3165.00	576.20	0.00	576.48	114.00	7.01	.08	19.55
1036.00	50.00	0.00	0.00	566.20	4100.00	576.96	0.00	577.34	117.96	8.55	.06	20.61
1036.00	50.00	0.00	0.00	566.20	4410.00	577.24	0.00	577.64	119.39	8.87	.06	21.02
1036.00	50.00	0.00	0.00	566.20	5160.00	577.94	0.00	578.40	122.80	9.24	.05	22.13
1736.00	700.00	0.00	0.00	565.40	3165.00	576.68	0.00	576.92	111.33	5.29	.13	32.02
1736.00	700.00	0.00	0.00	565.40	4100.00	577.55	0.00	577.87	443.28	6.28	.11	35.00
1736.00	700.00	0.00	0.00	565.40	4410.00	577.86	0.00	578.18	520.85	6.20	.10	36.89
1736.00	700.00	0.00	0.00	565.40	5160.00	578.65	0.00	578.93	560.01	5.29	.10	42.14
2436.00	700.00	0.00	0.00	564.60	3165.00	577.03	0.00	577.26	101.28	4.35	.18	45.15
2436.00	700.00	0.00	0.00	564.60	4100.00	577.97	0.00	578.26	306.47	4.98	.15	50.91
2436.00	700.00	0.00	0.00	564.60	4410.00	578.27	0.00	578.57	342.12	5.02	.15	54.81
2436.00	700.00	0.00	0.00	564.60	5160.00	578.99	0.00	579.30	367.49	4.87	.15	65.56
3186.00	750.00	0.00	0.00	568.80	1120.00	577.49	0.00	577.55	160.65	1.72	.28	57.33
3186.00	750.00	0.00	0.00	568.80	1620.00	578.52	0.00	578.60	246.47	1.98	.24	66.56
3186.00	750.00	0.00	0.00	568.80	1760.00	578.83	0.00	578.92	275.40	1.95	.24	72.01
3186.00	750.00	0.00	0.00	568.80	2055.00	579.55	0.00	579.63	291.91	1.73	.24	86.75
3686.00	500.00	0.00	0.00	569.40	1120.00	577.58	0.00	577.66	125.85	2.30	.34	63.65
3686.00	500.00	0.00	0.00	569.40	1620.00	578.62	0.00	578.73	200.38	2.66	.30	75.04
3686.00	500.00	0.00	0.00	569.40	1760.00	578.93	0.00	579.04	229.09	2.61	.29	81.33
3686.00	500.00	0.00	0.00	569.40	2055.00	579.64	0.00	579.74	290.98	2.35	.30	98.33

SECTION NUMBER	CHANNEL LENGTH	MIN EL OF ROADWAY	MAX EL OF LOW CHORD	MIN EL GROUND	DISCHARGE (CFS)	CWSEL	CRIWS	EG	TOPWID	10K*S	TIME	VOL
4186.00	500.00	0.00	0.00	570.00	1120.00	577.69	0.00	577.78	81.04	2.40	.40	69.39
4186.00	500.00	0.00	0.00	570.00	1620.00	578.75	0.00	578.88	102.22	3.01	.35	82.27
4186.00	500.00	0.00	0.00	570.00	1760.00	579.06	0.00	579.19	158.27	3.06	.34	89.17
4186.00	500.00	0.00	0.00	570.00	2055.00	579.75	0.00	579.89	200.00	2.94	.34	107.98
4236.00	50.00	0.00	0.00	568.10	1120.00	577.69	0.00	577.80	52.00	2.27	.41	69.91
4236.00	50.00	0.00	0.00	568.10	1620.00	578.75	0.00	578.92	52.00	3.32	.35	82.88
4236.00	50.00	0.00	0.00	568.10	1760.00	579.05	0.00	579.24	52.00	3.56	.35	89.81
4236.00	50.00	0.00	0.00	568.10	2055.00	579.73	0.00	579.95	52.00	3.99	.35	108.71
4281.00	45.00	580.00	577.40	568.10	1120.00	577.76	0.00	577.86	52.00	2.22	.42	70.36
4281.00	45.00	580.00	577.40	568.10	1620.00	578.93	0.00	579.10	52.00	3.14	.36	83.39
4281.00	45.00	580.00	577.40	568.10	1760.00	579.28	0.00	579.46	52.00	3.33	.35	90.34
4281.00	45.00	580.00	577.40	568.10	2055.00	580.06	0.00	580.27	52.00	3.64	.35	109.28
4931.00	650.00	0.00	0.00	570.30	1120.00	577.93	0.00	578.02	78.15	2.56	.49	77.12
4931.00	650.00	0.00	0.00	570.30	1620.00	579.18	0.00	579.31	81.55	3.01	.42	91.35
4931.00	650.00	0.00	0.00	570.30	1760.00	579.55	0.00	579.68	82.55	3.05	.41	98.66
4931.00	650.00	0.00	0.00	570.30	2055.00	580.36	0.00	580.50	84.13	3.03	.41	118.41
5956.00	1025.00	0.00	0.00	570.65	1120.00	578.20	0.00	578.29	77.93	2.67	.61	88.10
5956.00	1025.00	0.00	0.00	570.65	1620.00	579.49	0.00	579.62	81.46	3.06	.52	104.73
5956.00	1025.00	0.00	0.00	570.65	1760.00	579.86	0.00	580.00	82.47	3.09	.51	112.74
5956.00	1025.00	0.00	0.00	570.65	2055.00	580.67	0.00	580.82	84.07	3.07	.50	134.07
6981.00	1025.00	0.00	0.00	571.00	1120.00	578.48	0.00	578.57	81.27	2.83	.73	98.99
6981.00	1025.00	0.00	0.00	571.00	1620.00	579.81	0.00	579.94	86.06	3.13	.62	118.15
6981.00	1025.00	0.00	0.00	571.00	1760.00	580.19	0.00	580.32	87.40	3.14	.61	126.91
6981.00	1025.00	0.00	0.00	571.00	2055.00	580.99	0.00	581.14	90.28	3.10	.60	149.86
8031.00	1050.00	0.00	0.00	571.50	1120.00	578.77	0.00	578.85	87.41	2.50	.85	110.49
8031.00	1050.00	0.00	0.00	571.50	1620.00	580.14	0.00	580.25	94.35	2.75	.73	132.50
8031.00	1050.00	0.00	0.00	571.50	1760.00	580.52	0.00	580.63	95.44	2.75	.71	142.08
8031.00	1050.00	0.00	0.00	571.50	2055.00	581.32	0.00	581.44	96.00	2.66	.70	166.82
8082.00	51.00	0.00	0.00	569.90	1120.00	578.81	0.00	578.87	75.00	2.16	.86	111.10
8082.00	51.00	0.00	0.00	569.90	1620.00	580.17	0.00	580.27	75.00	2.65	.74	133.25
8082.00	51.00	0.00	0.00	569.90	1760.00	580.55	0.00	580.65	75.00	2.75	.72	142.87
8082.00	51.00	0.00	0.00	569.90	2055.00	581.34	0.00	581.46	75.00	2.90	.70	167.68
8147.00	65.00	580.90	578.40	569.90	1120.00	578.86	0.00	578.92	75.00	2.12	.87	111.94
8147.00	65.00	580.90	578.40	569.90	1620.00	580.32	0.00	580.41	75.00	2.52	.74	134.25
8147.00	65.00	580.90	578.40	569.90	1760.00	580.73	0.00	580.83	75.00	2.59	.73	143.91
8147.00	65.00	580.90	578.40	569.90	2055.00	581.58	0.00	581.70	75.00	2.68	.71	168.81
9397.00	1250.00	0.00	0.00	571.80	1120.00	579.16	0.00	579.26	80.35	3.19	1.01	126.37
9397.00	1250.00	0.00	0.00	571.80	1620.00	580.66	0.00	580.78	83.65	3.20	.87	152.01
9397.00	1250.00	0.00	0.00	571.80	1760.00	581.07	0.00	581.20	84.18	3.15	.84	162.60
9397.00	1250.00	0.00	0.00	571.80	2055.00	581.92	0.00	582.07	85.00	3.02	.83	189.49

SECTION NUMBER	CHANNEL LENGTH	MIN EL OF ROADWAY	MAX EL OF LOW CHORD	MIN EL GROUND	DISCHARGE (CFS)	CWSEL	CRIWS	EG	TOPWID	10K*S	TIME	VOL
10297.00	900.00	0.00	0.00	571.80	1120.00	579.43	0.00	579.53	71.72	2.80	1.11	135.55
10297.00	900.00	0.00	0.00	571.80	1620.00	580.93	0.00	581.07	75.23	3.03	.95	163.60
10297.00	900.00	0.00	0.00	571.80	1760.00	581.34	0.00	581.48	76.19	3.05	.93	174.88
10297.00	900.00	0.00	0.00	571.80	2055.00	582.19	0.00	582.35	77.98	3.05	.90	203.20
10897.00	600.00	0.00	0.00	572.20	1120.00	579.61	0.00	579.72	71.59	3.36	1.17	141.50
10897.00	600.00	0.00	0.00	572.20	1620.00	581.12	0.00	581.27	73.00	3.47	1.01	171.07
10897.00	600.00	0.00	0.00	572.20	1760.00	581.53	0.00	581.68	73.00	3.45	.98	182.76
10897.00	600.00	0.00	0.00	572.20	2055.00	582.38	0.00	582.55	73.00	3.42	.96	211.96
10973.00	76.00	0.00	0.00	571.70	1120.00	579.62	0.00	579.78	52.00	6.33	1.18	142.18
10973.00	76.00	0.00	0.00	571.70	1620.00	581.12	0.00	581.34	52.00	7.20	1.01	171.90
10973.00	76.00	0.00	0.00	571.70	1760.00	581.53	0.00	581.76	52.00	7.34	.99	183.64
10973.00	76.00	0.00	0.00	571.70	2055.00	582.37	0.00	582.63	52.00	7.57	.96	212.93
11017.00	44.00	581.70	579.00	571.70	1120.00	579.76	0.00	579.91	52.00	5.96	1.18	142.54
11017.00	44.00	581.70	579.00	571.70	1620.00	581.51	0.00	581.71	52.00	6.25	1.01	172.35
11017.00	44.00	581.70	579.00	571.70	1760.00	581.98	0.00	582.19	52.00	6.29	.99	184.11
11017.00	44.00	581.70	579.00	571.70	2055.00	582.89	0.00	583.13	52.00	6.43	.96	213.45
11477.00	460.00	0.00	0.00	571.80	1120.00	580.01	0.00	580.12	73.47	3.12	1.23	146.73
11477.00	460.00	0.00	0.00	571.80	1620.00	581.80	0.00	581.92	85.22	2.91	1.06	177.75
11477.00	460.00	0.00	0.00	571.80	1760.00	582.27	0.00	582.40	93.65	2.81	1.03	189.87
11477.00	460.00	0.00	0.00	571.80	2055.00	583.20	0.00	583.34	100.00	2.63	1.01	219.94
11528.00	51.00	0.00	0.00	572.10	1120.00	580.01	0.00	580.16	50.50	5.60	1.23	147.20
11528.00	51.00	0.00	0.00	572.10	1620.00	581.79	0.00	581.98	52.50	6.21	1.06	178.36
11528.00	51.00	0.00	0.00	572.10	1760.00	582.26	0.00	582.46	52.50	6.25	1.04	190.51
11528.00	51.00	0.00	0.00	572.10	2055.00	583.18	0.00	583.41	52.50	6.38	1.01	220.67
11599.00	71.00	582.80	580.70	572.10	1120.00	580.02	0.00	580.17	50.50	5.57	1.24	147.80
11599.00	71.00	582.80	580.70	572.10	1620.00	582.01	0.00	582.20	52.50	5.74	1.07	179.12
11599.00	71.00	582.80	580.70	572.10	1760.00	582.55	0.00	582.74	52.50	5.68	1.04	191.32
11599.00	71.00	582.80	580.70	572.10	2055.00	583.55	0.00	583.76	52.50	5.73	1.02	221.56
11650.00	51.00	0.00	0.00	572.10	1120.00	580.07	0.00	580.20	53.84	4.93	1.25	148.24
11650.00	51.00	0.00	0.00	572.10	1620.00	582.06	0.00	582.23	56.00	5.00	1.07	179.68
11650.00	51.00	0.00	0.00	572.10	1760.00	582.60	0.00	582.77	56.00	4.92	1.05	191.92
11650.00	51.00	0.00	0.00	572.10	2055.00	583.60	0.00	583.79	56.00	4.91	1.02	222.22
11721.00	71.00	583.20	580.70	572.10	1120.00	580.08	0.00	580.21	53.84	4.90	1.25	148.87
11721.00	71.00	583.20	580.70	572.10	1620.00	582.31	0.00	582.47	56.00	4.57	1.08	180.50
11721.00	71.00	583.20	580.70	572.10	1760.00	582.92	0.00	583.08	56.00	4.43	1.05	192.79
11721.00	71.00	583.20	580.70	572.10	2055.00	584.00	0.00	584.18	56.00	4.39	1.03	223.19

SECTION NUMBER	DISCHARGE CFS	CWSEL	CWSEL DIFF EACH Q	CWSEL DIFF EACH SECTION	CWSEL-WSELK	TOPWID	T.W. DIFF	LENGTH
1.000	3165.000	574.900	0.000	0.000	0.000	89.833	0.000	-0.000
1.000	4100.000	574.900	0.000	0.000	0.000	89.833	0.000	-0.000
1.000	4410.000	574.900	0.000	0.000	0.000	89.833	0.000	-0.000
1.000	5160.000	574.900	0.000	0.000	0.000	89.833	0.000	-0.000
30.000	3165.000	574.922	0.000	.022	0.000	89.999	0.000	29.000
30.000	4100.000	574.939	.017	.039	0.000	90.111	-.112	29.000
30.000	4410.000	574.946	.007	.046	0.000	90.154	-.156	29.000
30.000	5160.000	574.969	.023	.069	0.000	90.332	-.333	29.000
60.000	3165.000	574.944	0.000	.022	0.000	90.169	0.000	30.000
60.000	4100.000	574.980	.035	.041	0.000	90.443	-.274	30.000
60.000	4410.000	574.995	.015	.049	0.000	90.547	-.378	30.000
60.000	5160.000	575.045	.050	.076	0.000	91.040	-.871	30.000

61.000	3165.000	574.914	0.000	-.030	0.000	82.952	0.000	1.000
61.000	4100.000	574.928	.014	-.052	0.000	83.068	-.117	1.000
61.000	4410.000	574.935	.006	-.060	0.000	83.122	-.170	1.000
61.000	5160.000	574.960	.025	-.085	0.000	83.331	-.379	1.000
136.000	3165.000	575.018	0.000	.104	0.000	83.815	0.000	75.000
136.000	4100.000	575.117	.099	.188	0.000	84.639	-.824	75.000
136.000	4410.000	575.160	.043	.225	0.000	84.999	-1.183	75.000
136.000	5160.000	575.296	.136	.336	0.000	86.136	-2.320	75.000
137.000	3165.000	575.103	0.000	.085	0.000	91.525	0.000	1.000
137.000	4100.000	575.266	.163	.149	0.000	92.887	-1.361	1.000
137.000	4410.000	575.335	.069	.176	0.000	93.466	-1.940	1.000
137.000	5160.000	575.545	.209	.249	0.000	94.192	-2.667	1.000
187.000	3165.000	575.116	0.000	.013	0.000	89.164	0.000	50.000
187.000	4100.000	575.288	.172	.022	0.000	90.884	-1.720	50.000
187.000	4410.000	575.361	.073	.026	0.000	91.611	-2.446	50.000
187.000	5160.000	575.577	.216	.033	0.000	92.526	-3.362	50.000
362.000	3165.000	575.425	0.000	.308	0.000	143.706	0.000	175.000
362.000	4100.000	575.796	.372	.508	0.000	145.523	-1.816	175.000
362.000	4410.000	575.943	.146	.582	0.000	146.238	-2.532	175.000
362.000	5160.000	576.343	.400	.766	0.000	148.198	-4.492	175.000
737.000	3165.000	575.616	0.000	.191	0.000	145.954	0.000	375.000
737.000	4100.000	576.071	.456	.275	0.000	148.176	-2.222	375.000
737.000	4410.000	576.243	.171	.300	0.000	149.010	-3.057	375.000
737.000	5160.000	576.694	.451	.351	0.000	151.210	-5.257	375.000
787.000	3165.000	575.592	0.000	-.024	0.000	106.600	0.000	50.000
787.000	4100.000	576.031	.440	-.040	0.000	106.600	0.000	50.000
787.000	4410.000	576.196	.165	-.046	0.000	106.600	0.000	50.000
787.000	5160.000	576.632	.435	-.062	0.000	106.600	0.000	50.000
788.000	3165.000	575.563	0.000	-.029	0.000	104.000	0.000	1.000
788.000	4100.000	575.990	.427	-.042	0.000	104.000	0.000	1.000
788.000	4410.000	576.151	.161	-.046	0.000	104.000	0.000	1.000
788.000	5160.000	576.577	.426	-.055	0.000	104.000	0.000	1.000
797.000	3165.000	575.586	0.000	.023	0.000	104.000	0.000	9.000
797.000	4100.000	576.023	.437	.034	0.000	104.000	0.000	9.000
797.000	4410.000	576.188	.164	.037	0.000	104.000	0.000	9.000
797.000	5160.000	576.623	.436	.046	0.000	104.000	0.000	9.000
798.000	3165.000	575.670	0.000	.084	0.000	106.600	0.000	1.000
798.000	4100.000	576.147	.477	.124	0.000	106.600	0.000	1.000
798.000	4410.000	576.324	.177	.137	0.000	106.600	0.000	1.000
798.000	5160.000	576.786	.462	.163	0.000	106.600	0.000	1.000
844.000	3165.000	575.698	0.000	.028	0.000	106.114	0.000	46.000
844.000	4100.000	576.188	.490	.041	0.000	108.956	-2.842	46.000
844.000	4410.000	576.369	.181	.045	0.000	109.000	-2.886	46.000
844.000	5160.000	576.840	.471	.054	0.000	109.000	-2.886	46.000
845.000	3165.000	575.677	0.000	-.021	0.000	98.982	0.000	1.000
845.000	4100.000	576.157	.480	-.031	0.000	101.842	-2.860	1.000
845.000	4410.000	576.335	.178	-.035	0.000	102.000	-3.018	1.000
845.000	5160.000	576.797	.462	-.044	0.000	102.000	-3.018	1.000
859.000	3165.000	575.705	0.000	.028	0.000	99.122	0.000	14.500
859.000	4100.000	576.198	.494	.042	0.000	101.960	-2.838	14.500
859.000	4410.000	576.382	.184	.048	0.000	102.000	-2.878	14.500
859.000	5160.000	576.859	.477	.062	0.000	103.000	-3.878	14.500

860.000	4100.000	576.292	.526	.094	0.000	109.000	-2.457	1.000
860.000	4410.000	576.485	.193	.102	0.000	109.000	-2.457	1.000
860.000	5160.000	576.991	.507	.133	0.000	109.000	-2.457	1.000
910.000	3165.000	575.813	0.000	.047	0.000	107.000	0.000	50.000
910.000	4100.000	576.357	.545	.065	0.000	107.000	0.000	50.000
910.000	4410.000	576.555	.198	.071	0.000	107.000	0.000	50.000
910.000	5160.000	577.071	.515	.079	0.000	107.000	0.000	50.000
911.000	3165.000	575.787	0.000	-.025	0.000	105.000	0.000	1.000
911.000	4100.000	576.322	.535	-.036	0.000	105.000	0.000	1.000
911.000	4410.000	576.517	.195	-.039	0.000	105.000	0.000	1.000
911.000	5160.000	577.026	.510	-.044	0.000	105.000	0.000	1.000
921.000	3165.000	575.810	0.000	.023	0.000	105.000	0.000	10.000
921.000	4100.000	576.354	.544	.032	0.000	105.000	0.000	10.000
921.000	4410.000	576.551	.197	.034	0.000	105.000	0.000	10.000
921.000	5160.000	577.065	.515	.039	0.000	105.000	0.000	10.000
922.000	3165.000	575.882	0.000	.073	0.000	107.000	0.000	1.000
922.000	4100.000	576.456	.574	.103	0.000	107.000	0.000	1.000
922.000	4410.000	576.663	.207	.112	0.000	107.000	0.000	1.000
922.000	5160.000	577.197	.534	.132	0.000	107.000	0.000	1.000
953.000	3165.000	575.842	0.000	-.040	0.000	81.000	0.000	31.000
953.000	4100.000	576.392	.550	-.064	0.000	81.000	0.000	31.000
953.000	4410.000	576.590	.198	-.073	0.000	81.000	0.000	31.000
953.000	5160.000	577.104	.513	-.094	0.000	81.000	0.000	31.000
954.000	3165.000	575.755	0.000	-.087	0.000	67.200	0.000	1.000
954.000	4100.000	576.261	.506	-.131	0.000	67.200	0.000	1.000
954.000	4410.000	576.444	.183	-.146	0.000	67.200	0.000	1.000
954.000	5160.000	576.922	.478	-.182	0.000	67.200	0.000	1.000
985.000	3165.000	575.881	0.000	.126	0.000	67.200	0.000	30.500
985.000	4100.000	576.456	.575	.194	0.000	67.200	0.000	30.500
985.000	4410.000	576.663	.207	.218	0.000	67.200	0.000	30.500
985.000	5160.000	577.197	.535	.275	0.000	67.200	0.000	30.500
986.000	3165.000	576.119	0.000	.238	0.000	81.000	0.000	1.000
986.000	4100.000	576.817	.699	.362	0.000	81.000	0.000	1.000
986.000	4410.000	577.066	.249	.404	0.000	81.000	0.000	1.000
986.000	5160.000	577.701	.635	.504	0.000	81.000	0.000	1.000
1036.000	3165.000	576.202	0.000	.083	0.000	114.004	0.000	50.000
1036.000	4100.000	576.964	.762	.146	0.000	117.965	-3.961	50.000
1036.000	4410.000	577.237	.273	.171	0.000	119.388	-5.384	50.000
1036.000	5160.000	577.939	.702	.237	0.000	122.798	-8.794	50.000
1736.000	3165.000	576.677	0.000	.475	0.000	111.327	0.000	700.000
1736.000	4100.000	577.553	.876	.589	0.000	443.285	-331.958	700.000
1736.000	4410.000	577.863	.310	.626	0.000	520.849	-409.522	700.000
1736.000	5160.000	578.652	.789	.713	0.000	560.015	-448.688	700.000
2436.000	3165.000	577.029	0.000	.351	0.000	101.283	0.000	700.000
2436.000	4100.000	577.971	.943	.418	0.000	306.469	-205.186	700.000
2436.000	4410.000	578.270	.299	.407	0.000	342.121	-240.838	700.000
2436.000	5160.000	578.990	.720	.338	0.000	367.491	-266.208	700.000
3186.000	1120.000	577.487	0.000	.459	0.000	160.647	0.000	750.000
3186.000	1620.000	578.521	1.033	.549	0.000	246.467	-85.820	750.000
3186.000	1760.000	578.833	.312	.563	0.000	275.404	-114.756	750.000
3186.000	2055.000	579.552	.719	.562	0.000	291.912	-131.264	750.000
3686.000	1120.000	577.579	0.000	.092	0.000	125.851	0.000	500.000

3686.000	1760.000	578.933	.310	.101	0.000	229.086	-103.235	500.000
3686.000	2055.000	579.640	.707	.088	0.000	290.981	-165.129	500.000
4186.000	1120.000	577.694	0.000	.114	0.000	81.036	0.000	500.000
4186.000	1620.000	578.755	1.061	.131	0.000	102.218	-21.182	500.000
4186.000	1760.000	579.061	.306	.128	0.000	158.272	-77.236	500.000
4186.000	2055.000	579.751	.690	.111	0.000	199.999	-118.963	500.000
4236.000	1120.000	577.695	0.000	.001	0.000	51.999	0.000	50.000
4236.000	1620.000	578.747	1.053	-.008	0.000	51.999	-.000	50.000
4236.000	1760.000	579.049	.302	-.012	0.000	51.999	-.000	50.000
4236.000	2055.000	579.725	.676	-.025	0.000	51.999	-.000	50.000
4281.000	1120.000	577.759	0.000	.064	0.000	51.999	0.000	45.000
4281.000	1620.000	578.931	1.172	.184	0.000	51.999	-.000	45.000
4281.000	1760.000	579.280	.349	.231	0.000	51.999	-.000	45.000
4281.000	2055.000	580.058	.778	.332	0.000	51.999	-.000	45.000
4931.000	1120.000	577.932	0.000	.173	0.000	78.154	0.000	650.000
4931.000	1620.000	579.182	1.250	.251	0.000	81.552	-3.398	650.000
4931.000	1760.000	579.549	.367	.269	0.000	82.548	-4.395	650.000
4931.000	2055.000	580.358	.809	.300	0.000	84.127	-5.973	650.000
5956.000	1120.000	578.198	0.000	.266	0.000	77.927	0.000	1025.000
5956.000	1620.000	579.493	1.294	.310	0.000	81.457	-3.531	1025.000
5956.000	1760.000	579.863	.370	.314	0.000	82.468	-4.542	1025.000
5956.000	2055.000	580.669	.806	.312	0.000	84.066	-6.139	1025.000
6981.000	1120.000	578.480	0.000	.281	0.000	81.273	0.000	1025.000
6981.000	1620.000	579.813	1.334	.321	0.000	86.057	-4.784	1025.000
6981.000	1760.000	580.187	.374	.325	0.000	87.402	-6.130	1025.000
6981.000	2055.000	580.993	.806	.324	0.000	90.282	-9.009	1025.000
8031.000	1120.000	578.773	0.000	.293	0.000	87.408	0.000	1050.000
8031.000	1620.000	580.143	1.370	.330	0.000	94.346	-6.938	1050.000
8031.000	1760.000	580.519	.376	.332	0.000	95.443	-8.035	1050.000
8031.000	2055.000	581.320	.800	.326	0.000	95.999	-8.591	1050.000
8082.000	1120.000	578.808	0.000	.035	0.000	74.999	0.000	51.000
8082.000	1620.000	580.174	1.366	.031	0.000	74.999	-.000	51.000
8082.000	1760.000	580.548	.374	.029	0.000	74.999	-.000	51.000
8082.000	2055.000	581.341	.793	.021	0.000	74.999	-.000	51.000
8147.000	1120.000	578.859	0.000	.051	0.000	74.999	0.000	65.000
8147.000	1620.000	580.320	1.461	.145	0.000	74.999	-.000	65.000
8147.000	1760.000	580.729	.409	.181	0.000	74.999	-.000	65.000
8147.000	2055.000	581.585	.856	.244	0.000	74.999	-.000	65.000
9397.000	1120.000	579.162	0.000	.303	0.000	80.354	0.000	1250.000
9397.000	1620.000	580.655	1.494	.336	0.000	83.648	-3.294	1250.000
9397.000	1760.000	581.067	.412	.339	0.000	84.179	-3.825	1250.000
9397.000	2055.000	581.924	.857	.339	0.000	84.999	-4.645	1250.000
10297.000	1120.000	579.431	0.000	.269	0.000	71.716	0.000	900.000
10297.000	1620.000	580.933	1.502	.278	0.000	75.234	-3.519	900.000
10297.000	1760.000	581.343	.410	.276	0.000	76.193	-4.478	900.000
10297.000	2055.000	582.191	.849	.267	0.000	77.982	-6.266	900.000
10897.000	1120.000	579.609	0.000	.178	0.000	71.589	0.000	600.000
10897.000	1620.000	581.121	1.512	.188	0.000	72.999	-1.410	600.000
10897.000	1760.000	581.530	.409	.188	0.000	72.999	-1.410	600.000
10897.000	2055.000	582.377	.847	.186	0.000	72.999	-1.410	600.000
10973.000	1120.000	579.621	0.000	.012	0.000	51.999	0.000	76.000
10973.000	1620.000	581.121	1.501	.001	0.000	51.999	-.000	76.000

10973.000	2055.000	582.367	.840	-.010	0.000	51.999	-.000	76.000
11017.000	1120.000	579.761	0.000	.140	0.000	51.999	0.000	44.000
11017.000	1620.000	581.514	1.753	.393	0.000	51.999	-.000	44.000
11017.000	1760.000	581.983	.469	.455	0.000	52.000	-.000	44.000
11017.000	2055.000	582.895	.912	.528	0.000	52.000	-.000	44.000
11477.000	1120.000	580.012	0.000	.251	0.000	73.467	0.000	460.000
11477.000	1620.000	581.797	1.785	.283	0.000	85.222	-11.755	460.000
11477.000	1760.000	582.273	.476	.290	0.000	93.646	-20.179	460.000
11477.000	2055.000	583.204	.931	.309	0.000	99.999	-26.532	460.000
11528.000	1120.000	580.013	0.000	.001	0.000	50.499	0.000	51.000
11528.000	1620.000	581.785	1.772	-.012	0.000	52.499	-2.000	51.000
11528.000	1760.000	582.257	.472	-.016	0.000	52.499	-2.000	51.000
11528.000	2055.000	583.178	.921	-.026	0.000	52.499	-2.000	51.000
11599.000	1120.000	580.025	0.000	.011	0.000	50.499	0.000	71.000
11599.000	1620.000	582.013	1.988	.228	0.000	52.499	-2.000	71.000
11599.000	1760.000	582.549	.536	.292	0.000	52.499	-2.000	71.000
11599.000	2055.000	583.546	.997	.368	0.000	52.499	-2.000	71.000
11650.000	1120.000	580.066	0.000	.041	0.000	53.836	0.000	51.000
11650.000	1620.000	582.061	1.995	.048	0.000	55.999	-2.163	51.000
11650.000	1760.000	582.598	.537	.049	0.000	55.999	-2.163	51.000
11650.000	2055.000	583.600	1.002	.054	0.000	55.999	-2.163	51.000
11721.000	1120.000	580.075	0.000	.010	0.000	53.842	0.000	71.000
11721.000	1620.000	582.314	2.239	.253	0.000	55.999	-2.157	71.000
11721.000	1760.000	582.919	.605	.321	0.000	55.999	-2.157	71.000
11721.000	2055.000	583.996	1.077	.397	0.000	55.999	-2.157	71.000

DATA FOR LAST CROSS SECTION

PROFILE	TYPE ENC	TARGET	TOP WIDTH AREA-ACRES	TOP WIDTH AREA-DIFF
1	0.000	56.000	24.359	0.000
2	0.000	56.000	35.978	11.619
3	0.000	56.000	39.108	14.749
4	0.000	56.000	41.659	17.300

```
**********************************************
HEC2 VERSION UPDATED JAN 1976
ERROR CORRECTIONS 01,02,03,04,05,06,07,08,09
MODIFICATIONS 52,53,54,55,56,57,58
**********************************************
```

```
C
1       CITY OF WYANDOTTE FIS 5555-73
T2       SEXTON-KILFOIL DRAIN
T3      10 YEAR FLOOD 3165 CFS
```

J1	ICHECK	INQ	NINV	IDIR	STRT	METRIC	HVINS	Q	WSEL	FQ
	-0.	2.	-0.	-0.	-0.000000	-0.00	-0.0	-0.	574.900	-0.000

J2	NPROF	IPLOT	PRFVS	XSECV	XSECH	FN	ALLDC	IBW	CHNIM	ITRACE
	-10.000	-0.000	-1.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000

NC	.035	.035	.032	.300	.500	-0.000	-0.000	-0.000	-0.000	-0.000
QT	4.000	3165.000	4100.000	4410.000	5160.000	-0.000	-0.000	-0.000	-0.000	-0.000
X1	1.000	41.000	500.000	619.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000
GR	576.200	0.000	575.900	100.000	576.600	200.000	578.500	300.000	581.100	400.000
GR	584.600	500.000	582.800	500.000	582.600	505.000	581.900	510.000	581.100	515.000
GR	579.200	520.000	575.400	525.000	574.800	530.000	572.800	535.000	569.200	540.000
GR	569.200	540.000	565.500	543.500	565.500	543.500	565.500	545.000	563.900	555.000
GR	566.100	560.000	565.300	565.000	565.400	570.000	564.100	575.000	566.200	580.000
GR	566.200	580.000	565.300	583.500	565.300	583.500	565.300	585.000	563.400	590.000
GR	564.400	595.000	565.400	600.000	567.700	605.000	571.100	610.000	573.500	615.000
GR	574.000	619.000	584.600	619.000	582.300	700.000	579.600	800.000	579.000	890.000
GR	578.700	1000.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000
X1	30.000	-0.000	-0.000	-0.000	29.000	29.000	29.000	-0.000	-0.000	-0.000
X1	60.000	41.000	500.000	619.000	30.000	30.000	30.000	-0.000	-0.000	-0.000
GR	576.200	0.000	575.900	100.000	576.600	200.000	578.500	300.000	581.100	400.000
GR	584.600	500.000	582.800	500.000	582.600	505.000	581.900	510.000	581.100	515.000
GR	579.200	520.000	575.400	525.000	574.800	530.000	572.800	535.000	569.200	540.000
GR	569.200	540.000	565.500	543.500	565.500	543.500	565.500	545.000	563.900	555.000
GR	566.100	560.000	565.300	565.000	565.400	570.000	564.100	575.000	566.200	580.000
GR	566.200	580.000	565.300	583.500	565.300	583.500	565.300	585.000	563.400	590.000
GR	564.400	595.000	565.400	600.000	567.700	605.000	571.100	610.000	573.500	615.000
GR	574.000	619.000	584.600	619.000	582.300	700.000	579.600	800.000	579.000	890.000
GR	578.700	1000.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000
X1	61.000	41.000	500.000	619.000	1.000	1.000	1.000	-0.000	-0.000	-0.000
BT	9.000	500.000	584.300	579.800	500.000	587.700	579.800	540.000	588.100	580.300
BT	543.500	588.100	580.300	560.000	588.300	580.300	580.000	588.100	580.300	583.500
BT	588.100	580.300	619.000	587.700	579.700	619.000	584.400	579.700	-0.000	-0.000
GR	576.200	0.000	575.900	100.000	576.600	200.000	578.500	300.000	581.100	400.000
GR	584.600	500.000	582.800	500.000	582.600	505.000	581.900	510.000	581.100	515.000
GR	579.200	520.000	575.400	525.000	574.800	530.000	572.800	535.000	569.200	540.000
GR	580.300	540.000	580.300	543.500	565.500	543.500	565.500	545.000	563.900	555.000
GR	566.100	560.000	565.300	565.000	565.400	570.000	564.100	575.000	566.200	580.000
GR	580.300	580.000	580.300	583.500	565.300	583.500	565.300	585.000	563.400	590.000
GR	564.400	595.000	565.400	600.000	567.700	605.000	571.100	610.000	573.500	615.000
GR	574.000	619.000	584.600	619.000	582.300	700.000	579.600	800.000	579.000	890.000
GR	578.700	1000.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000

X2	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	1.000	-0.000	-0.000	-0.000
X1	137.000	41.000	500.000	619.000	1.000	1.000	1.000	-0.000	-0.000	-0.000
GR	576.200	0.000	575.900	100.000	576.600	200.000	578.500	300.000	581.100	400.000
GR	584.600	500.000	582.800	500.000	582.600	505.000	581.900	510.000	581.100	515.000
GR	579.200	520.000	575.400	525.000	574.800	530.000	572.800	535.000	569.200	540.000
GR	569.200	540.000	565.500	543.500	565.500	543.500	565.500	545.000	563.900	555.000
GR	566.100	560.000	565.300	565.000	565.400	570.000	564.100	575.000	566.200	580.000
GR	566.200	580.000	565.300	583.500	565.300	583.500	565.300	585.000	563.400	590.000
GR	564.400	595.000	565.400	600.000	567.700	605.000	571.100	610.000	573.500	615.000
GR	574.000	619.000	584.600	619.000	582.300	700.000	579.600	800.000	579.000	890.000
GR	578.700	1000.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000
NC	.035	.042	.032	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000
X1	187.000	27.000	331.000	441.000	50.000	50.000	50.000	-0.000	-0.000	-0.000
GR	575.800	0.000	576.600	41.000	578.500	141.000	580.600	241.000	583.100	331.000
GR	575.400	341.000	574.800	346.000	571.300	351.000	568.100	356.000	567.200	361.000
GR	565.700	366.000	565.100	371.000	565.500	376.000	565.100	381.000	564.700	391.000
GR	564.100	401.000	564.400	406.000	565.700	411.000	568.200	416.000	570.500	421.000
GR	572.800	426.000	574.800	432.000	580.200	441.000	583.600	454.000	581.000	541.000
GR	579.300	641.000	578.300	698.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000
X1	362.000	35.000	244.000	400.000	175.000	175.000	175.000	-0.000	.270	-0.000
GR	580.200	0.000	579.500	100.000	578.300	200.000	578.300	244.000	574.600	254.000
GR	573.600	255.000	571.500	260.000	569.800	265.000	568.500	270.000	567.600	275.000
GR	566.900	280.000	565.900	285.000	565.600	290.000	563.700	300.000	563.700	310.000
GR	564.300	320.000	565.800	330.000	568.200	340.000	569.800	345.000	571.100	350.000
GR	571.600	355.000	572.400	360.000	572.100	365.000	572.600	370.000	572.600	375.000
GR	572.800	380.000	572.800	385.000	572.900	390.000	574.600	395.000	576.900	400.000
GR	577.600	500.000	577.700	545.000	577.500	600.000	577.700	700.000	577.500	800.000
X1	737.000	35.000	244.000	400.000	375.000	375.000	375.000	-0.000	-0.000	-0.000
GR	580.200	0.000	579.500	100.000	578.300	200.000	578.300	244.000	574.600	254.000
GR	573.600	255.000	571.500	260.000	569.800	265.000	568.500	270.000	567.600	275.000
GR	566.900	280.000	565.900	285.000	565.600	290.000	563.700	300.000	563.700	310.000
GR	564.300	320.000	565.800	330.000	568.200	340.000	569.800	345.000	571.100	350.000
GR	571.600	355.000	572.400	360.000	572.100	365.000	572.600	370.000	572.600	375.000
GR	572.800	380.000	572.800	385.000	572.900	390.000	574.600	395.000	576.900	400.000
GR	577.600	500.000	577.700	545.000	577.500	600.000	577.700	700.000	577.500	800.000
X1	787.000	67.000	795.000	901.600	50.000	50.000	50.000	-0.000	-0.000	-0.000
GR	581.500	0.000	581.400	95.000	581.300	195.000	581.200	295.000	581.100	395.000
GR	581.100	495.000	581.100	595.000	581.000	695.000	581.000	795.000	575.200	795.000
GR	574.500	800.000	574.500	800.000	574.500	801.000	574.500	801.000	574.000	805.000
GR	573.200	810.000	573.200	810.000	573.200	811.000	573.200	811.000	570.800	815.000
GR	569.300	820.000	570.100	825.000	570.100	825.000	570.100	826.000	570.100	826.000
GR	566.600	829.900	566.600	829.900	566.600	831.200	566.600	831.200	565.500	835.000
GR	565.500	835.000	565.500	836.000	565.500	836.000	563.900	840.000	564.500	845.000
GR	564.500	845.000	564.500	846.000	564.500	846.000	564.900	850.000	564.900	855.000
GR	564.900	855.000	564.900	856.000	564.900	856.000	565.500	860.000	565.200	865.000
GR	565.200	865.000	565.200	866.300	565.300	866.300	566.000	870.000	566.000	875.000
GR	566.000	875.000	566.000	876.000	566.000	876.000	566.700	880.000	568.700	885.000
GR	568.300	890.000	569.700	895.000	571.700	900.000	571.700	901.600	581.000	901.600
GR	580.800	995.000	580.800	1095.000	580.600	1195.000	580.400	1295.000	580.100	1395.000
GR	579.900	1495.000	580.000	1540.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000
X1	788.000	67.000	795.000	901.600	-1.000	1.000	1.000	-0.000	-0.000	-0.000
BT	4.000	795.000	581.000	577.200	830.000	581.000	577.200	860.000	581.000	577.200
BT	901.600	581.000	577.200	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000
GR	581.500	0.000	581.400	95.000	581.300	195.000	581.200	295.000	581.100	395.000
GR	581.100	495.000	581.100	595.000	581.000	695.000	581.000	795.000	575.200	795.000
GR	574.500	800.000	575.500	800.000	575.500	801.000	574.500	801.000	574.000	805.000
GR	573.200	810.000	575.500	810.000	575.500	811.000	573.200	811.000	570.800	815.000
GR	569.300	820.000	570.100	825.000	575.500	825.000	575.500	826.000	570.100	826.000
GR	566.600	830.000	577.200	830.000	577.200	831.300	566.600	831.300	565.500	835.000

GR	575.500	845.000	575.500	846.000	564.500	846.000	564.900	850.000	564.900	855.000
GR	575.500	855.000	575.500	856.000	564.900	856.000	565.500	860.000	565.200	865.000
GR	577.200	865.000	577.200	866.300	565.200	866.300	566.000	870.000	566.000	875.000
GR	575.500	875.000	575.500	876.000	566.000	876.000	566.700	880.000	568.700	885.000
GR	568.300	890.000	569.700	895.000	571.700	900.000	571.700	901.600	581.000	901.600
GR	580.800	995.000	580.800	1095.000	580.600	1195.000	580.400	1295.000	580.100	1395.000
GR	579.900	1495.000	580.000	1540.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000
X1	797.000	0.000	795.000	901.600	9.000	9.000	9.000	-0.000	-0.000	-0.000
X2	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	1.000	-0.000	-0.000	-0.000
X1	798.000	67.000	795.000	901.600	1.000	1.000	1.000	-0.000	-0.000	-0.000
GR	581.500	0.000	581.400	95.000	581.300	195.000	581.200	295.000	581.100	395.000
GR	581.100	495.000	581.100	595.000	581.000	695.000	581.000	795.000	575.200	795.000
GR	574.500	800.000	574.500	800.000	574.500	801.000	574.500	801.000	574.000	805.000
GR	573.200	810.000	573.200	810.000	573.200	811.000	573.200	811.000	570.800	815.000
GR	569.300	820.000	570.100	825.000	570.100	825.000	570.100	826.000	570.100	826.000
GR	566.600	829.900	566.600	829.900	566.600	831.200	566.600	831.200	565.500	835.000
GR	565.500	835.000	565.500	836.000	565.500	836.000	563.900	840.000	564.500	845.000
GR	564.500	845.000	564.500	846.000	564.500	846.000	564.900	850.000	564.900	855.000
GR	564.900	855.000	564.900	856.000	564.900	856.000	565.500	860.000	565.200	865.000
GR	565.200	865.000	565.200	866.300	565.300	866.300	566.000	870.000	566.000	875.000
GR	566.000	875.000	566.000	876.000	566.000	876.000	566.700	880.000	568.700	885.000
GR	568.300	890.000	569.700	895.000	571.700	900.000	571.700	901.600	581.000	901.600
GR	580.800	995.000	580.800	1095.000	580.600	1195.000	580.400	1295.000	580.100	1395.000
GR	579.900	1495.000	580.000	1540.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000
X1	844.000	58.000	815.000	924.000	46.000	46.000	46.000	-0.000	-0.000	-0.000
GR	583.400	0.000	583.400	15.000	583.100	115.000	582.900	215.000	582.800	315.000
GR	582.600	415.000	582.300	515.000	582.100	615.000	581.800	715.000	581.500	815.000
GR	576.100	815.000	574.200	820.000	572.700	825.000	570.000	829.000	570.000	829.000
GR	570.000	830.000	570.000	830.000	568.000	835.000	565.900	840.000	565.000	844.000
GR	565.000	844.000	565.000	845.000	565.000	845.000	565.000	855.000	566.000	864.000
GR	566.000	864.000	566.000	865.000	566.000	865.000	566.100	874.000	566.100	874.000
GR	566.100	875.000	566.100	875.000	565.800	884.000	565.800	884.000	565.800	885.000
GR	565.800	885.000	565.600	890.000	565.200	894.000	565.200	894.000	565.200	895.000
GR	565.200	895.000	567.600	900.000	570.300	905.000	572.000	909.000	572.000	909.000
GR	572.000	910.000	572.000	910.000	574.000	915.000	575.100	920.000	576.200	924.000
GR	581.400	924.000	581.300	1015.000	581.300	1115.000	581.100	1215.000	581.100	1315.000
GR	581.100	1415.000	581.200	1515.000	581.200	1565.000	-0.000	-0.000	-0.000	-0.000
X1	845.000	58.000	815.000	924.000	1.000	1.000	1.000	-0.000	-0.000	-0.000
BT	16.000	815.000	581.500	578.400	829.000	581.500	578.100	830.000	581.500	578.100
BT	844.000	581.500	577.900	845.000	581.500	577.900	864.000	581.500	577.500	865.000
BT	581.500	577.500	874.000	581.400	577.400	875.000	581.400	577.400	884.000	581.400
BT	577.200	885.000	581.400	577.200	894.000	581.400	577.000	895.000	581.400	577.000
BT	909.000	581.400	576.800	910.000	581.400	576.800	924.000	581.400	576.500	-0.000
GR	583.400	0.000	583.400	15.000	583.100	115.000	582.900	215.000	582.800	315.000
GR	582.600	415.000	582.300	515.000	582.100	615.000	581.800	715.000	581.500	815.000
GR	576.100	815.000	574.200	820.000	572.700	825.000	570.000	829.000	578.100	829.000
GR	578.100	830.000	570.000	830.000	568.000	835.000	565.900	840.000	565.000	844.000
GR	577.900	844.000	577.900	845.000	565.000	845.000	565.000	855.000	566.000	864.000
GR	577.500	864.000	577.500	865.000	566.000	865.000	566.100	874.000	577.400	874.000
GR	577.400	875.000	566.100	875.000	565.800	884.000	577.200	884.000	577.200	885.000
GR	565.800	885.000	565.600	890.000	565.200	894.000	577.000	894.000	577.000	895.000
GR	565.200	895.000	567.600	900.000	570.300	905.000	572.000	909.000	576.800	909.000
GR	576.800	910.000	572.000	910.000	574.000	915.000	575.100	920.000	576.200	924.000
GR	581.400	924.000	581.300	1015.000	581.300	1115.000	581.100	1215.000	581.100	1315.000
GR	581.100	1415.000	581.200	1515.000	581.200	1565.000	-0.000	-0.000	-0.000	-0.000
X1	859.000	-0.000	815.000	924.000	14.500	14.500	14.500	-0.000	-0.000	-0.000
X2	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	1.000	-0.000	-0.000	-0.000
X1	860.000	58.000	815.000	924.000	1.000	1.000	1.000	-0.000	-0.000	-0.000
GR	583.400	0.000	583.400	15.000	583.100	115.000	582.900	215.000	582.800	315.000

GR	576.100	815.000	574.200	820.000	572.700	825.000	570.000	829.000	570.000	829.000
GR	570.000	830.000	570.000	830.000	568.000	835.000	565.900	840.000	565.000	844.000
GR	565.000	844.000	565.000	845.000	565.000	845.000	565.000	855.000	566.000	864.000
GR	566.000	864.000	566.000	865.000	566.000	865.000	566.100	874.000	566.100	874.000
GR	566.100	875.000	566.100	875.000	565.800	884.000	565.800	884.000	565.800	885.000
GR	565.800	885.000	565.600	890.000	565.200	894.000	565.200	894.000	565.200	895.000
GR	565.200	895.000	567.600	900.000	570.300	905.000	572.000	909.000	572.000	909.000
GR	572.000	910.000	572.000	910.000	574.000	915.000	575.100	920.000	576.200	924.000
GR	581.400	924.000	581.300	1015.000	581.300	1115.000	581.100	1215.000	581.100	1315.000
GR	581.100	1415.000	581.200	1515.000	581.200	1565.000	-0.000	-0.000	-0.000	-0.000
X1	910.000	64.000	835.000	942.000	50.000	50.000	50.000	-0.000	-0.000	-0.000
GR	583.700	0.000	583.600	35.000	583.400	135.000	583.300	235.000	583.300	335.000
GR	583.300	435.000	583.300	535.000	583.200	635.000	583.100	735.000	583.100	835.000
GR	574.800	835.000	572.600	840.000	571.600	844.000	571.600	844.000	571.600	845.000
GR	571.600	845.000	570.700	854.000	570.700	854.000	570.700	855.000	570.700	855.000
GR	565.600	864.000	565.600	864.000	565.600	865.000	565.600	865.000	564.300	874.000
GR	564.300	874.000	564.300	875.000	564.300	875.000	564.800	884.000	564.800	884.000
GR	564.800	885.000	564.800	885.000	564.900	894.000	564.900	894.000	564.900	895.000
GR	564.900	895.000	564.000	904.000	564.000	904.000	564.000	905.000	564.000	905.000
GR	566.100	914.000	566.100	914.000	566.100	915.000	566.100	915.000	567.000	920.000
GR	571.000	924.000	571.000	924.000	571.000	925.000	571.000	925.000	572.400	930.000
GR	573.900	934.000	573.900	934.000	573.900	935.000	573.900	935.000	575.000	940.000
GR	574.900	942.000	583.000	942.000	582.700	1035.000	582.600	1135.000	582.300	1235.000
GR	582.100	1335.000	581.900	1435.000	581.800	1535.000	581.800	1585.000	-0.000	-0.000
X1	911.000	64.000	835.000	942.000	1.000	1.000	1.000	-0.000	-0.000	-0.000
BT	6.000	835.000	583.100	578.600	874.000	583.100	578.600	875.000	583.100	578.600
BT	904.000	583.000	578.600	905.000	583.000	578.600	942.000	583.000	578.600	-0.000
GR	583.700	0.000	583.600	35.000	583.400	135.000	583.300	235.000	583.300	335.000
GR	583.300	435.000	583.300	535.000	583.200	635.000	583.100	735.000	583.100	835.000
GR	574.800	835.000	572.600	840.000	571.600	844.000	575.500	844.000	575.500	845.000
GR	571.600	845.000	570.700	854.000	575.500	854.000	575.500	855.000	570.700	855.000
GR	565.600	864.000	575.500	864.000	575.500	865.000	565.600	865.000	564.300	874.000
GR	578.600	874.000	578.600	875.000	564.300	875.000	564.800	884.000	575.500	884.000
GR	575.500	885.000	564.800	885.000	564.900	894.000	575.500	894.000	575.500	895.000
GR	564.900	895.000	564.000	904.000	578.600	904.000	578.600	905.000	564.000	905.000
GR	566.100	914.000	575.500	914.000	575.500	915.000	566.100	915.000	567.000	920.000
GR	571.000	924.000	575.500	924.000	575.500	925.000	571.000	925.000	572.400	930.000
GR	573.900	934.000	575.500	934.000	575.500	935.000	573.900	935.000	575.000	940.000
GR	574.900	942.000	583.000	942.000	582.700	1035.000	582.600	1135.000	582.300	1235.000
GR	582.100	1335.000	581.900	1435.000	581.800	1535.000	581.800	1585.000	-0.000	-0.000
X1	921.000	-0.000	835.000	942.000	10.000	10.000	10.000	-0.000	-0.000	-0.000
X2	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	1.000	-0.000	-0.000	-0.000
X1	922.000	64.000	835.000	942.000	1.000	1.000	1.000	-0.000	-0.000	-0.000
GR	583.700	0.000	583.600	35.000	583.400	135.000	583.300	235.000	583.300	335.000
GR	583.300	435.000	583.300	535.000	583.200	635.000	583.100	735.000	583.100	835.000
GR	574.800	835.000	572.600	840.000	571.600	844.000	571.600	844.000	571.600	845.000
GR	571.600	845.000	570.700	854.000	570.700	854.000	570.700	855.000	570.700	855.000
GR	565.600	864.000	565.600	864.000	565.600	865.000	565.600	865.000	564.300	874.000
GR	564.300	874.000	564.300	875.000	564.300	875.000	564.800	884.000	564.800	884.000
GR	564.800	885.000	564.800	885.000	564.900	894.000	564.900	894.000	564.900	895.000
GR	564.900	895.000	564.000	904.000	564.000	904.000	564.000	905.000	564.000	905.000
GR	566.100	914.000	566.100	914.000	566.100	915.000	566.100	915.000	567.000	920.000
GR	571.000	924.000	571.000	924.000	571.000	925.000	571.000	925.000	572.400	930.000
GR	573.900	934.000	573.900	934.000	573.900	935.000	573.900	935.000	575.000	940.000
GR	574.900	942.000	583.000	942.000	582.700	1035.000	582.600	1135.000	582.300	1235.000
GR	582.100	1335.000	581.900	1435.000	581.800	1535.000	581.800	1585.000	-0.000	-0.000
X1	953.000	48.000	600.000	681.000	31.000	31.000	31.000	-0.000	-0.000	-0.000
GR	582.000	0.000	581.800	100.000	581.600	200.000	581.500	300.000	581.400	400.000
GR	581.200	500.000	581.000	600.000	571.000	600.000	568.100	605.000	566.900	610.000
GR	566.900	610.000	566.900	612.300	566.900	612.300	565.900	615.000	565.100	620.000

GR	566.200	630.000	566.200	632.300	566.200	632.300	566.700	635.000	566.400	640.000
GR	566.100	645.000	566.400	650.000	566.400	650.000	566.400	652.300	566.400	652.300
GR	566.600	655.000	567.500	660.000	567.500	660.000	567.500	662.300	567.500	662.300
GR	567.500	665.000	569.900	670.000	569.900	670.000	569.900	672.300	569.900	672.300
GR	573.400	680.000	573.400	681.000	580.800	681.000	580.800	700.000	580.700	800.000
GR	580.600	900.000	580.600	1000.000	580.500	1100.000	-0.000	-0.000	-0.000	-0.000
X1	954.000	48.000	600.000	681.000	1.000	1.000	1.000	-0.000	-0.000	-0.000
BT	14.000	600.000	581.000	577.700	610.000	581.000	577.700	612.300	581.000	577.700
BT	620.000	581.000	577.700	622.300	581.000	577.700	630.000	580.900	577.700	632.300
BT	580.900	577.700	650.000	580.900	577.600	652.300	580.900	577.600	660.000	580.900
BT	577.600	662.300	580.800	577.600	670.000	580.800	577.600	672.300	580.800	577.600
BT	681.000	580.800	577.600	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000
GR	582.000	0.000	581.800	100.000	581.600	200.000	581.500	300.000	581.400	400.000
GR	581.200	500.000	581.000	600.000	571.000	600.000	568.100	605.000	566.900	610.000
GR	577.700	610.000	577.700	612.300	566.900	612.300	565.900	615.000	565.100	620.000
GR	577.700	620.000	577.700	622.300	565.100	622.300	566.300	625.000	566.200	630.000
GR	577.700	630.000	577.700	632.300	566.200	632.300	566.700	635.000	566.400	640.000
GR	566.100	645.000	566.400	650.000	577.600	650.000	577.600	652.300	566.400	652.300
GR	566.600	655.000	567.500	660.000	577.600	660.000	577.600	662.300	567.500	662.300
GR	567.500	665.000	569.900	670.000	577.600	670.000	577.600	672.300	569.900	672.300
GR	573.400	680.000	573.400	681.000	580.800	681.000	580.800	700.000	580.700	800.000
GR	580.600	900.000	580.600	1000.000	580.500	1100.000	-0.000	-0.000	-0.000	-0.000
X1	985.000	-0.000	600.000	681.000	30.500	30.500	30.500	-0.000	-0.000	-0.000
X2	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	1.000	-0.000	-0.000	-0.000
X1	986.000	48.000	600.000	681.000	1.000	1.000	1.000	-0.000	-0.000	-0.000
GR	582.000	0.000	581.800	100.000	581.600	200.000	581.500	300.000	581.400	400.000
GR	581.200	500.000	581.000	600.000	571.000	600.000	568.100	605.000	566.900	610.000
GR	566.900	610.000	566.900	612.300	566.900	612.300	565.900	615.000	565.100	620.000
GR	565.100	620.000	565.100	622.300	565.100	622.300	566.300	625.000	566.200	630.000
GR	566.200	630.000	566.200	632.300	566.200	632.300	566.700	635.000	566.400	640.000
GR	566.100	645.000	566.400	650.000	566.400	650.000	566.400	652.300	566.400	652.300
GR	566.600	655.000	567.500	660.000	567.500	660.000	567.500	662.300	567.500	662.300
GR	567.500	665.000	569.900	670.000	569.900	670.000	569.900	672.300	569.900	672.300
GR	573.400	680.000	573.400	681.000	580.800	681.000	580.800	700.000	580.700	800.000
GR	580.600	900.000	580.600	1000.000	580.500	1100.000	-0.000	-0.000	-0.000	-0.000
NC	.040	.035	.032	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000
X1	1036.000	37.000	565.000	700.000	50.000	50.000	50.000	-0.000	-0.000	-0.000
X3	10.000	-0.000	-0.000	-0.000	-0.000	700.000	-0.000	-0.000	-0.000	-0.000
GR	581.900	0.000	581.200	100.000	581.200	200.000	580.800	300.000	581.000	400.000
GR	579.900	500.000	581.100	565.000	575.400	587.000	574.900	590.000	573.900	595.000
GR	572.500	600.000	571.000	605.000	569.800	610.000	568.800	615.000	568.000	620.000
GR	567.400	625.000	566.600	630.000	566.300	635.000	566.200	640.000	566.300	650.000
GR	566.800	660.000	568.300	670.000	570.200	675.000	570.400	680.000	571.700	685.000
GR	573.100	690.000	574.800	695.000	574.900	696.000	577.700	700.000	577.500	800.000
GR	576.600	900.000	576.600	1000.000	577.000	1030.000	576.800	1100.000	577.500	1200.000
GR	578.300	1300.000	579.200	1345.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000
NC	.060	.035	.032	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000
X1	1736.000	40.000	374.000	492.500	700.000	700.000	700.000	-0.000	-0.000	-0.000
X3	10.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000
GR	580.400	0.000	580.400	167.000	579.500	283.700	578.800	335.300	579.100	374.000
GR	577.200	377.900	576.100	381.900	575.100	385.800	574.100	389.800	573.200	393.700
GR	572.400	397.700	571.500	401.600	570.300	405.600	569.400	409.500	568.400	413.500
GR	567.600	417.400	566.900	421.400	566.500	425.300	566.000	429.200	565.700	433.200
GR	565.500	437.200	565.400	441.100	565.500	445.000	565.600	449.000	565.900	453.000
GR	566.500	456.900	567.200	460.800	568.000	464.800	569.000	468.700	569.800	472.700
GR	570.600	476.600	571.700	480.600	573.400	484.500	575.100	488.500	577.500	492.500
GR	577.400	550.000	577.300	650.000	577.400	750.000	577.700	890.000	579.500	975.000
X1	2436.000	31.000	183.000	285.000	700.000	700.000	700.000	-0.000	-0.000	-0.000
X3	-0.000	-0.000	-0.000	-0.000	-0.000	485.000	-0.000	-0.000	-0.000	-0.000

GR	573.500	190.000	572.200	195.000	571.100	200.000	570.200	205.000	568.500	210.000
GR	567.700	215.000	566.400	220.000	565.600	225.000	565.300	230.000	565.000	235.000
GR	564.600	240.000	564.800	245.000	565.200	250.000	566.400	255.000	567.800	260.000
GR	568.800	265.000	569.900	270.000	571.500	275.000	574.700	280.000	575.100	281.000
GR	577.400	285.000	577.300	385.000	578.200	485.000	577.700	557.000	578.600	585.000
GR	579.800	605.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000
QT	4.000	1120.000	1620.000	1760.000	2055.000	-0.000	-0.000	-0.000	-0.000	-0.000
X1	3186.000	25.000	200.000	300.000	750.000	750.000	750.000	-0.000	-0.000	-0.000
X3	10.000	-0.000	-0.000	-0.000	-0.000	500.000	-0.000	-0.000	-0.000	-0.000
GR	580.600	0.000	583.100	100.000	581.300	200.000	579.600	208.000	575.200	216.000
GR	573.900	220.000	571.600	225.000	569.900	230.000	569.900	235.000	569.300	240.000
GR	569.100	245.000	568.800	250.000	569.200	260.000	570.800	270.000	571.100	280.000
GR	571.700	285.000	573.000	290.000	574.100	295.000	576.400	300.000	577.900	400.000
GR	579.000	500.000	579.100	600.000	578.700	625.000	578.700	700.000	578.900	800.000
X1	3686.000	-0.000	-0.000	-0.000	500.000	500.000	500.000	-0.000	.600	-0.000
X3	10.000	-0.000	-0.000	-0.000	-0.000	500.000	-0.000	-0.000	-0.000	-0.000
NC	.040	.037	.032	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000
X1	4186.000	27.000	417.000	500.000	500.000	500.000	500.000	-0.000	-0.000	-0.000
X3	10.000	-0.000	-0.000	350.000	-0.000	550.000	-0.000	-0.000	-0.000	-0.000
GR	581.800	0.000	580.900	100.000	580.600	200.000	580.000	300.000	578.900	400.000
GR	578.200	417.000	575.000	419.000	574.700	420.000	573.000	425.000	571.200	430.000
GR	570.500	435.000	570.400	440.000	570.400	445.000	570.300	450.000	570.000	455.000
GR	570.300	460.000	570.300	465.000	570.400	470.000	570.500	475.000	571.800	480.000
GR	572.500	485.000	573.200	490.000	575.000	494.000	578.700	500.000	579.500	600.000
GR	581.000	700.000	583.000	770.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000
NC	.030	.030	.030	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000
X1	4236.000	32.000	592.000	644.000	50.000	50.000	50.000	-0.000	-0.000	-0.000
X3	10.000	-0.000	-0.000	592.000	-0.000	644.000	-0.000	-0.000	-0.000	-0.000
GR	582.000	0.000	581.600	92.000	581.200	192.000	580.800	292.000	580.700	392.000
GR	580.000	492.000	580.100	592.000	570.200	592.000	569.200	597.000	570.000	602.000
GR	569.700	607.000	569.000	612.000	568.100	617.000	568.100	617.000	568.100	618.500
GR	568.100	618.500	568.900	622.000	568.800	627.000	569.200	632.000	570.000	637.000
GR	570.600	642.000	570.600	644.000	580.000	644.000	579.300	692.000	579.600	792.000
GR	580.400	892.000	580.700	992.000	580.500	1092.000	580.300	1192.000	580.000	1292.000
GR	579.600	1392.000	579.300	1492.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000
SB	1.250	1.370	2.500	-0.000	50.500	1.500	400.000	0.000	568.100	568.100
X1	4281.000	32.000	592.000	644.000	45.000	45.000	45.000	-0.000	-0.000	-0.000
X2	-0.000	-0.000	1.000	577.400	580.000	-0.000	-0.000	-0.000	-0.000	-0.000
X3	10.000	-0.000	-0.000	592.000	-0.000	644.000	-0.000	-0.000	-0.000	-0.000
BT	6.000	592.000	580.100	577.400	617.000	580.000	577.300	617.000	580.000	568.100
BT	618.500	580.000	568.100	618.500	580.000	577.300	644.000	580.000	577.300	-0.000
GR	582.000	0.000	581.600	92.000	581.200	192.000	580.800	292.000	580.700	392.000
GR	580.000	492.000	580.100	592.000	570.200	592.000	569.200	597.000	570.000	602.000
GR	569.700	607.000	569.000	612.000	568.100	617.000	568.100	617.000	568.100	618.500
GR	568.100	618.500	568.900	622.000	568.800	627.000	569.200	632.000	570.000	637.000
GR	570.600	642.000	570.600	644.000	580.000	644.000	579.300	692.000	579.600	792.000
GR	580.400	892.000	580.700	992.000	580.500	1092.000	580.300	1192.000	580.000	1292.000
GR	579.600	1392.000	579.300	1492.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000
NC	.040	.037	.032	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000
X1	4931.000	23.000	115.000	200.000	650.000	650.000	650.000	-0.000	-0.000	-0.000
X3	10.000	-0.000	-0.000	115.000	-0.000	200.000	-0.000	-0.000	-0.000	-0.000
GR	582.200	0.000	581.600	37.000	580.800	100.000	580.900	115.000	575.300	124.000
GR	574.600	125.000	571.500	130.000	570.800	135.000	570.500	140.000	570.300	145.000
GR	570.300	150.000	570.300	155.000	570.400	160.000	570.600	165.000	570.800	170.000
GR	571.100	175.000	571.300	180.000	573.100	185.000	573.600	190.000	575.300	195.000
GR	579.800	200.000	579.100	300.000	580.100	400.000	-0.000	-0.000	-0.000	-0.000
X1	5956.000	-0.000	-0.000	-0.000	1025.000	1025.000	1025.000	-0.000	.350	-0.000
X3	10.000	-0.000	-0.000	115.000	-0.000	200.000	-0.000	-0.000	-0.000	-0.000

X1	6981.000	29.000	505.000	600.000	1025.000	1025.000	1025.000	-0.000	-0.000	-0.000
X3	10.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	582.600	582.000	-0.000
GR	582.800	0.000	581.300	100.000	581.300	200.000	580.900	300.000	579.700	400.000
GR	579.400	425.000	582.700	500.000	582.600	505.000	576.000	517.000	575.200	520.000
GR	572.000	525.000	571.800	530.000	572.200	535.000	572.300	540.000	571.100	545.000
GR	571.100	550.000	571.000	560.000	571.200	570.000	572.400	575.000	572.500	580.000
GR	574.200	584.000	575.200	588.000	582.000	600.000	579.100	700.000	581.500	800.000
GR	580.800	900.000	581.000	920.000	581.300	1000.000	581.200	1100.000	-0.000	-0.000
X1	8031.000	27.000	150.000	246.000	1050.000	1050.000	1050.000	-0.000	-0.000	-0.000
X3	-0.000	-0.000	-0.000	150.000	-0.000	246.000	-0.000	-0.000	-0.000	-0.000
GR	580.300	0.000	580.400	50.000	580.700	78.000	578.900	114.000	580.700	150.000
GR	579.000	155.000	575.200	162.000	573.800	166.000	572.800	170.000	572.300	175.000
GR	572.000	180.000	571.700	190.000	571.500	200.000	571.500	210.000	571.700	215.000
GR	571.800	220.000	572.500	225.000	573.600	230.000	575.200	235.000	577.800	238.000
GR	579.400	246.000	579.400	250.000	578.600	336.000	578.500	350.000	579.200	450.000
GR	578.900	492.000	580.500	550.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000
NC	.030	.030	.030	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000
X1	8082.000	39.000	580.000	655.000	51.000	51.000	51.000	-0.000	-0.000	-0.000
X3	10.000	-0.000	-0.000	580.000	-0.000	655.000	-0.000	-0.000	-0.000	-0.000
GR	578.600	0.000	578.100	80.000	578.000	180.000	577.700	280.000	577.600	380.000
GR	577.900	480.000	580.900	580.000	571.800	580.000	572.200	585.000	571.700	590.000
GR	571.500	595.000	571.200	600.000	570.400	605.000	578.300	605.000	578.300	606.500
GR	570.400	606.500	571.400	610.000	571.000	615.000	570.900	620.000	571.000	625.000
GR	571.000	630.000	578.300	630.000	578.300	631.500	571.000	631.500	571.100	635.000
GR	570.900	640.000	570.800	645.000	570.300	650.000	569.900	655.000	581.100	655.000
GR	580.300	680.000	578.900	780.000	578.500	830.000	578.300	880.000	577.900	980.000
GR	577.500	1080.000	577.300	1180.000	577.700	1280.000	577.600	1380.000	-0.000	-0.000
SB	1.250	1.560	2.600	-0.000	75.000	3.000	519.000	-0.000	569.900	569.900
X1	8147.000	-0.000	580.000	655.000	65.000	65.000	65.000	-0.000	-0.000	-0.000
X2	-0.000	-0.000	1.000	578.400	580.900	-0.000	-0.000	-0.000	.631	-0.000
X3	10.000	-0.000	-0.000	580.000	-0.000	655.000	-0.000	-0.000	-0.000	-0.000
BT	6.000	580.000	580.900	578.200	605.000	581.000	578.300	606.500	581.000	578.300
BT	630.000	581.000	578.300	631.500	581.000	578.300	655.000	581.100	578.400	-0.000
NC	.035	.040	.032	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000
X1	9397.000	28.000	550.000	635.000	1250.000	1250.000	1250.000	-0.000	-0.000	-0.000
X3	-0.000	-0.000	-0.000	550.000	-0.000	635.000	-0.000	-0.000	-0.000	-0.000
GR	580.800	0.000	581.500	150.000	580.700	250.000	579.800	355.000	580.800	450.000
GR	579.300	550.000	578.800	555.000	574.700	564.000	573.700	570.000	573.200	575.000
GR	572.200	580.000	572.000	585.000	572.100	590.000	571.800	595.000	571.800	600.000
GR	571.900	605.000	572.200	610.000	572.500	615.000	572.800	620.000	573.200	625.000
GR	574.700	626.000	581.700	635.000	582.000	650.000	582.100	750.000	583.100	850.000
GR	582.600	950.000	582.200	1050.000	581.900	1150.000	-0.000	-0.000	-0.000	-0.000
X1	10297.000	29.000	400.000	480.000	900.000	900.000	900.000	-0.000	-0.000	-0.000
X3	10.000	-0.000	-0.000	-0.000	-0.000	480.000	-0.000	-0.000	-0.000	-0.000
GR	583.100	0.000	582.700	100.000	582.200	200.000	582.100	220.000	582.900	300.000
GR	583.400	400.000	573.800	416.000	572.900	420.000	572.000	425.000	572.000	430.000
GR	572.000	435.000	571.800	440.000	572.000	445.000	572.200	450.000	572.200	455.000
GR	572.500	460.000	572.800	465.000	573.400	470.000	574.500	475.000	581.900	480.000
GR	581.400	500.000	580.900	600.000	581.000	700.000	581.600	800.000	581.900	900.000
GR	582.800	1000.000	582.600	1100.000	582.900	1200.000	583.400	1300.000	-0.000	-0.000
NC	.035	.035	.032	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000
X1	10897.000	23.000	112.000	185.000	600.000	600.000	600.000	-0.000	-0.000	-0.000
X3	-0.000	-0.000	-0.000	112.000	-0.000	185.000	-0.000	-0.000	-0.000	-0.000
GR	580.700	0.000	581.200	85.000	580.400	112.000	574.800	122.000	574.500	123.000
GR	573.500	125.000	572.900	130.000	572.400	135.000	572.200	140.000	572.300	150.000
GR	572.700	155.000	572.800	160.000	573.200	165.000	573.000	170.000	573.000	176.000
GR	574.500	178.000	579.400	185.000	581.800	231.000	583.700	243.000	583.100	285.000
GR	584.400	355.000	582.600	385.000	583.500	477.000	-0.000	-0.000	-0.000	-0.000

X3	10.000	-0.000	-0.000	552.000	-0.000	500.000	-0.000	-0.000	-0.000	-0.000
GR	582.200	0.000	581.900	100.000	581.400	200.000	580.900	300.000	580.800	400.000
GR	581.200	448.000	581.700	500.000	571.700	500.000	571.900	505.000	571.800	510.000
GR	571.800	515.000	571.800	520.000	572.100	525.000	579.000	525.000	579.000	527.000
GR	572.100	527.000	572.600	530.000	573.000	535.000	573.700	540.000	573.700	545.000
GR	573.600	550.000	573.400	552.000	581.600	552.000	580.400	600.000	581.100	700.000
GR	581.400	800.000	581.600	900.000	581.800	1000.000	582.000	1100.000	582.100	1122.000
SB	.900	1.470	2.500	-0.000	52.000	2.000	315.000	-0.000	571.700	571.700
X1	11017.000	-0.000	500.000	552.000	44.000	44.000	-0.000	-0.000	-0.000	-0.000
X2	-0.000	-0.000	1.000	579.000	581.700	-0.000	-0.000	-0.000	-0.000	-0.000
X3	10.000	-0.000	-0.000	500.000	590.000	552.000	-0.000	-0.000	-0.000	-0.000
BT	4.000	500.000	581.700	578.900	525.000	581.700	579.000	527.000	581.700	579.000
BT	552.000	581.600	578.900	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000
NC	.060	.060	.032	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000
X1	11477.000	22.000	155.000	236.000	460.000	460.000	-0.000	-0.000	-0.000	-0.000
X3	-0.000	-0.000	-0.000	155.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000
GR	583.100	0.000	583.400	50.000	110.000	582.900	155.000	574.900	170.000	
GR	573.900	175.000	573.700	180.000	185.000	572.800	190.000	572.900	195.000	
GR	572.900	200.000	572.700	205.000	210.000	572.400	215.000	571.800	573.100	220.000
GR	574.400	225.000	575.500	227.000	581.400	236.000	255.000	582.600	582.200	265.000
GR	582.100	310.000	582.200	343.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000
X1	11528.000	35.000	530.000	582.500	51.000	51.000	-0.000	-0.000	-0.000	-0.000
X3	10.000	-0.000	-0.000	530.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000
GR	584.400	0.000	584.800	30.000	130.000	584.400	230.000	583.500	330.000	
GR	582.900	370.000	582.900	430.000	583.000	530.000	573.000	573.400	535.000	
GR	573.000	540.000	572.700	545.000	572.500	550.000	572.100	555.200	580.600	555.200
GR	580.600	557.200	572.800	572.200	560.000	572.700	565.000	572.500	572.500	570.000
GR	572.400	575.000	572.600	580.000	572.500	582.500	582.500	582.800	582.500	630.000
GR	582.200	730.000	583.300	830.000	582.900	880.000	583.100	930.000	583.900	1030.000
GR	584.100	1130.000	584.400	1230.000	584.100	1330.000	583.700	1430.000	583.900	1439.000
SB	1.250	1.610	2.500	2.000	52.500	-0.000	400.000	-0.000	572.100	572.100
X1	11599.000	-0.000	530.000	582.500	71.000	71.000	-0.000	-0.000	-0.000	-0.000
X2	-0.000	-0.000	1.000	580.700	582.800	-0.000	-0.000	-0.000	-0.000	-0.000
X3	10.000	-0.000	-0.000	530.000	582.500	-0.000	-0.000	-0.000	-0.000	-0.000
BT	4.000	530.000	583.000	580.700	582.900	555.200	557.200	582.900	580.600	
BT	582.500	582.800	580.500	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000
X1	11650.000	36.000	548.000	604.000	51.000	51.000	-0.000	-0.000	-0.000	-0.000
X3	10.000	-0.000	-0.000	548.000	-0.000	604.000	-0.000	-0.000	-0.000	-0.000
GR	584.800	0.000	584.500	48.000	584.300	148.000	584.100	248.000	583.600	348.000
GR	583.000	448.000	583.400	548.000	573.400	548.000	573.700	553.000	573.300	558.000
GR	573.000	563.000	572.600	568.000	572.600	573.000	572.600	573.500	580.700	573.500
GR	580.700	575.500	572.500	575.500	572.400	578.000	572.100	583.000	572.600	588.000
GR	572.100	593.000	572.600	598.000	572.400	601.000	580.500	604.000	583.200	604.000
GR	582.400	648.000	581.900	748.000	582.400	823.000	582.900	848.000	583.300	948.000
GR	583.800	1048.000	584.100	1148.000	584.500	1248.000	584.300	1348.000	583.900	1448.000
GR	584.300	1558.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000
SB	1.250	1.610	2.500	2.000	56.000	-0.000	400.000	-0.000	572.100	572.100
X1	11721.000	-0.000	548.000	604.000	71.000	71.000	-0.000	-0.000	-0.000	-0.000
X2	-0.000	-0.000	1.000	580.700	583.200	-0.000	-0.000	-0.000	-0.000	-0.000
X3	10.000	-0.000	-0.000	548.000	-0.000	604.000	-0.000	-0.000	-0.000	-0.000
BT	4.000	548.000	583.400	580.700	583.300	573.500	575.500	583.300	580.700	
BT	604.000	583.200	580.500	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000
EJ	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000	-0.000

```
**********************************************
HEC2 VERSION UPDATED JAN 1976
ERROR CORRECTIONS 01,02,03,04,05,06,07,08,09
MODIFICATIONS 52,53,54,55,56,57,58
**********************************************



T1      CITY OF WYANDOTTE FIS 5555-73
T2      SEXTON-KILFOIL DRAIN
T3      100 YEAR FLOOD 4410 CFS

J1  ICHECK    INQ       NINV      IDIR      STRT      METRIC    HVINS     Q         WSEL      FQ
     -10.       4.        -0.       -0.  -0.000000    -0.00     -0.0      -0.   574.900   -0.000

J2  NPROF     IPLOT     PRFVS     XSECV     XSECH     FN        ALLDC     IBW       CHNIM     ITRACE
      3.000    -0.000    -1.000    -0.000    -0.000    -0.000    -0.000    -0.000    -0.000    -0.000

CCHV=    .300 CEHV=    .500
   SECNO     DEPTH     CWSEL     CRIWS     WSELK     EG        HV        HL        OLOSS     BANK ELEV
   Q         QLOB      QCH       QROB      ALOB      ACH       AROB      VOL       TWA     LEFT/RIGHT
   TIME      VLOB      VCH       VROB      XNL       XNCH      XNR       WTN       ELMIN       SSTA
   SLOPE     XLOBL     XLCH      XLOBR     ITRIAL    IDC       ICONT     CORAR     TOPWID      ENDST

     1.00     11.50    574.90      0.00    574.90    575.51       .61      0.00      0.00    584.60
    4410.        0.     4410.        0.        0.       701.        0.        0.        0.    584.60
     0.00      0.00      6.29      0.00      .035      .032      .035     0.000    563.40    529.17
  .001328        -0.       -0.       -0.         0         0         1      0.00     89.83    619.00

    30.00     11.55    574.95      0.00      0.00    575.55       .61       .04       .00    584.60
    4410.        0.     4410.        0.        0.       705.        0.        0.        0.    584.60
      .00      0.00      6.26      0.00      .035      .032      .035      .031    563.40    528.85
  .001312       29.       29.       29.         0         0         1      0.00     90.15    619.00

    60.00     11.59    574.99      0.00      0.00    575.60       .60       .04       .00    584.60
    4410.        0.     4410.        0.        0.       709.        0.        1.        0.    584.60
      .00      0.00      6.22      0.00      .035      .032      .035      .031    563.40    528.45
  .001294       30.       30.       30.         1         0         1      0.00     90.55    619.00

3265 DIVIDED FLOW

NORMAL BRIDGE,NRD=  9 MIN ELTRD=  584.30 MAX ELLC=  580.30

    61.00     11.53    574.93      0.00      0.00    575.66       .72       .00       .06    584.60
    4410.        0.     4410.        0.        0.       646.        0.        1.        0.    584.60
      .00      0.00      6.83      0.00      .035      .032      .035      .030    563.40    528.88
  .002372        1.        1.        1.         2         0         1      0.00     83.12    619.00

3265 DIVIDED FLOW
```

136.00	11.76	575.16	0.00	0.00	575.84	.68	.17	.01	584.60
4410.	0.	4410.	0.	0.	665.	0.	2.	0.	584.60
.01	0.00	6.63	0.00	.035	.032	.035	.031	563.40	527.00
.002224	75.	75.	75.	2	0	1	0.00	85.00	619.00

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST
137.00	11.94	575.34	0.00	0.00	575.88	.55	.00	.04	584.60
4410.	0.	4410.	0.	0.	741.	0.	2.	0.	584.60
.01	0.00	5.95	0.00	.035	.032	.035	.031	563.40	525.53
.001166	1.	1.	1.	2	0	1	0.00	93.47	619.00
187.00	11.26	575.36	0.00	0.00	575.98	.62	.06	.04	583.10
4410.	0.	4410.	0.	0.	696.	0.	3.	0.	580.20
.01	0.00	6.33	0.00	.035	.032	.042	.031	564.10	341.32
.001331	50.	50.	50.	2	0	1	0.00	91.61	432.94
362.00	11.97	575.94	0.00	0.00	576.25	.30	.17	.10	578.57
4410.	0.	4410.	0.	0.	995.	0.	6.	1.	577.17
.02	0.00	4.43	0.00	.035	.032	.042	.031	563.97	251.10
.000728	175.	175.	175.	2	0	1	0.00	146.24	397.33
737.00	12.54	576.24	0.00	0.00	576.50	.26	.24	.01	578.30
4410.	0.	4410.	0.	0.	1079.	0.	15.	2.	576.90
.04	0.00	4.09	0.00	.035	.032	.042	.032	563.70	249.56
.000570	375.	375.	375.	2	0	1	0.00	149.01	398.57
787.00	12.30	576.20	0.00	0.00	576.62	.42	.04	.08	581.00
4410.	0.	4410.	0.	0.	846.	0.	16.	2.	581.00
.05	0.00	5.21	0.00	.035	.032	.042	.032	563.90	795.00
.000895	50.	50.	50.	2	0	1	0.00	106.60	901.60

3265 DIVIDED FLOW

NORMAL BRIDGE, NRD= 4 MIN ELTRD= 581.00 MAX ELLC= 577.20

788.00	12.25	576.15	0.00	0.00	576.67	.52	.00	.05	581.00
4410.	0.	4410.	0.	0.	764.	0.	16.	2.	581.00
.05	0.00	5.77	0.00	.035	.032	.042	.032	563.90	795.00
.003554	1.	1.	1.	2	0	1	0.00	104.00	901.60

3265 DIVIDED FLOW

NORMAL BRIDGE, NRD= 4 MIN ELTRD= 581.00 MAX ELLC= 577.20

797.00	12.29	576.19	0.00	0.00	576.70	.51	.03	.00	581.00
4410.	0.	4410.	0.	0.	767.	0.	17.	2.	581.00
.05	0.00	5.75	0.00	.035	.032	.042	.032	563.90	795.00
.003513	9.	9.	9.	1	0	1	0.00	104.00	901.60

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST
798.00	12.42	576.32	0.00	0.00	576.73	.41	.00	.03	581.00
4410.	0.	4410.	0.	0.	859.	0.	17.	2.	581.00
.05	0.00	5.13	0.00	.035	.032	.042	.032	563.90	795.00
.000851	1.	1.	1.	2	0	1	0.00	106.60	901.60
844.00	11.37	576.37	0.00	0.00	576.77	.40	.04	.00	581.50
4410.	0.	4410.	0.	0.	865.	0.	17.	2.	581.40
.05	0.00	5.10	0.00	.035	.032	.042	.032	565.00	815.00
.000809	46.	46.	46.	2	0	1	0.00	109.00	924.00

3265 DIVIDED FLOW

NORMAL BRIDGE,NRD=16 MIN ELTRD= 581.40 MAX ELLC= 578.40

845.00	11.33	576.33	0.00	0.00	576.81	.48	.00	.04	581.50
4410.	0.	4410.	0.	0.	797.	0.	17.	2.	581.40
.05	0.00	5.53	0.00	.035	.032	.042	.031	565.00	815.00
.002795	1.	1.	1.	2	0	1	0.00	102.00	924.00

3265 DIVIDED FLOW

NORMAL BRIDGE,NRD=16 MIN ELTRD= 581.40 MAX ELLC= 578.40

859.00	11.38	576.38	0.00	0.00	576.85	.47	.04	.00	581.50
4410.	0.	4410.	0.	0.	802.	0.	18.	2.	581.40
.05	0.00	5.50	0.00	.035	.032	.042	.031	565.00	815.00
.002751	15.	15.	15.	2	0	1	0.00	102.00	924.00
860.00	11.48	576.48	0.00	0.00	576.88	.39	.00	.02	581.50
4410.	0.	4410.	0.	0.	877.	0.	18.	2.	581.40
.05	0.00	5.03	0.00	.035	.032	.042	.031	565.00	815.00
.000773	1.	1.	1.	2	0	1	0.00	109.00	924.00
910.00	12.56	576.56	0.00	0.00	576.92	.37	.04	.01	583.10
4410.	0.	4410.	0.	0.	908.	0.	19.	3.	583.00
.05	0.00	4.86	0.00	.035	.032	.042	.031	564.00	835.00
.000696	50.	50.	50.	1	0	1	0.00	107.00	942.00

3265 DIVIDED FLOW

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

911.00	12.52	576.52	0.00	0.00	576.96	.45	.00	.04	583.10
4410.	0.	4410.	0.	0.	823.	0.	19.	3.	583.00
.05	0.00	5.36	0.00	.035	.032	.042	.031	564.00	835.00
.003062	1.	1.	1.	2	0	1	0.00	105.00	942.00

3265 DIVIDED FLOW

NORMAL BRIDGE,NRD= 6 MIN ELTRD= 583.00 MAX ELLC= 578.60

921.00	12.55	576.55	0.00	0.00	576.99	.44	.03	.00	583.10
4410.	0.	4410.	0.	0.	826.	0.	19.	3.	583.00
.05	0.00	5.34	0.00	.035	.032	.042	.031	564.00	835.00
.003030	10.	10.	10.	1	0	1	0.00	105.00	942.00

922.00	12.66	576.66	0.00	0.00	577.02	.36	.00	.03	583.10
4410.	0.	4410.	0.	0.	919.	0.	19.	3.	583.00
.05	0.00	4.80	0.00	.035	.032	.042	.031	564.00	835.00
.000671	1.	1.	1.	2	0	1	0.00	107.00	942.00

953.00	11.49	576.59	0.00	0.00	577.14	.55	.03	.10	581.00
4410.	0.	4410.	0.	0.	738.	0.	20.	3.	580.80
.06	0.00	5.97	0.00	.035	.032	.042	.031	565.10	600.00
.001040	31.	31.	31.	2	0	1	0.00	81.00	681.00

3265 DIVIDED FLOW

NORMAL BRIDGE,NRD=14 MIN ELTRD= 580.80 MAX ELLC= 577.70

954.00	11.34	576.44	0.00	0.00	577.29	.85	.00	.15	581.00
4410.	0.	4410.	0.	0.	596.	0.	20.	3.	580.80
.06	0.00	7.40	0.00	.035	.032	.042	.031	565.10	600.00
.005600	1.	1.	1.	2	0	1	0.00	67.20	681.00

3265 DIVIDED FLOW

NORMAL BRIDGE,NRD=14 MIN ELTRD= 580.80 MAX ELLC= 577.70

985.00	11.56	576.66	0.00	0.00	577.47	.81	.17	.01	581.00
4410.	0.	4410.	0.	0.	611.	0.	20.	3.	580.80
.06	0.00	7.22	0.00	.035	.032	.042	.031	565.10	600.00
.005274	31.	31.	31.	2	0	1	0.00	67.20	681.00

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

986.00	11.97	577.07	0.00	0.00	577.57	.50	.00	.09	581.00
4410.	0.	4410.	0.	0.	777.	0.	20.	3.	580.80
.06	0.00	5.68	0.00	.035	.032	.042	.031	565.10	600.00
.000889	1.	1.	1.	2	0	1	0.00	81.00	681.00

3470 ENCROACHMENT STATIONS= .0 700.0 TYPE= 1 TARGET= 699.999

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 581.10 ELREA= 100000.00

1036.00	11.04	577.24	0.00	0.00	577.64	.40	.04	.03	581.10
4410.	0.	4410.	0.	0.	866.	0.	21.	3.	100000.00
.06	0.00	5.10	0.00	.040	.032	.035	.031	566.20	579.94
.000887	50.	50.	50.	1	0	1	0.00	119.39	699.33

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 579.10 ELREA= 577.50

1736.00	12.46	577.86	0.00	0.00	578.18	.32	.52	.03	579.10
4410.	0.	4308.	102.	0.	941.	168.	37.	8.	577.50
.10	0.00	4.58	.61	.060	.032	.035	.032	565.40	376.55
.000620	700.	700.	700.	1	0	1	0.00	520.85	897.40

3470 ENCROACHMENT STATIONS= .0 485.0 TYPE= 1 TARGET= 484.999

2436.00	13.67	578.27	0.00	0.00	578.57	.30	.39	.00	577.10
4410.	9.	4286.	115.	23.	954.	144.	55.	15.	577.40
.15	.39	4.49	.80	.060	.032	.035	.032	564.60	142.88
.000502	700.	700.	700.	2	0	1	0.00	342.12	485.00

3470 ENCROACHMENT STATIONS= .0 500.0 TYPE= 1 TARGET= 499.999

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 581.30 ELREA= 576.40

3186.00	10.03	578.83	0.00	0.00	578.92	.08	.27	.07	581.30
1760.	0.	1605.	155.	0.	668.	208.	72.	20.	576.40
.24	0.00	2.40	.75	.060	.032	.035	.032	568.80	209.39
.000195	750.	750.	750.	2	0	1	0.00	275.40	484.80

3470 ENCROACHMENT STATIONS= .0 500.0 TYPE= 1 TARGET= 499.999

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 581.90 ELREA= 577.00

3686.00	9.53	578.93	0.00	0.00	579.04	.11	.11	.01	581.90
1760.	0.	1667.	93.	0.	623.	127.	81.	23.	577.00
.29	0.00	2.68	.73	.060	.032	.035	.032	569.40	210.30
.000261	500.	500.	500.	2	0	1	0.00	229.09	439.39

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

3470 ENCROACHMENT STATIONS= 350.0 550.0 TYPE= 1 TARGET= 200.000

4186.00	9.06	579.06	0.00	0.00	579.19	.13	.14	.01	578.20
1760.	4.	1755.	2.	10.	598.	8.	89.	25.	578.70
.34	.38	2.93	.22	.040	.032	.037	.032	570.00	385.99
.000306	500.	500.	500.	1	0	1	0.00	158.27	544.26

3470 ENCROACHMENT STATIONS= 592.0 644.0 TYPE= 1 TARGET= 52.000

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 580.10 ELREA= 100000.00

4236.00	10.95	579.05	0.00	0.00	579.24	.19	.02	.03	580.10
1760.	0.	1760.	0.	0.	504.	0.	90.	25.	100000.00
.35	0.00	3.49	0.00	.030	.030	.030	.032	568.10	592.00
.000356	50.	50.	50.	1	0	1	0.00	52.00	644.00

SPECIAL BRIDGE

SB	XK	XKOR	COFQ	RDLEN	BWC	BWP	BAREA	SS	ELCHU	ELCHD
	1.25	1.37	2.50	-0.00	50.50	1.50	400.00	0.00	568.10	568.10

PRESSURE FLOW

EGPRS	EGLWC	H3	QWEIR	QPR	BAREA	ELLC	ELTRD	CLASS
579.46	579.25	.01	0.	1760.	400.	577.40	580.00	10.00

Ernons St

3470 ENCROACHMENT STATIONS= 592.0 644.0 TYPE= 1 TARGET= 52.000

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 580.10 ELREA= 100000.00

4281.00	11.18	579.28	0.00	0.00	579.46	.18	.22	0.00	580.10
1760.	0.	1760.	0.	0.	515.	0.	90.	26.	100000.00
.35	0.00	3.41	0.00	.030	.030	.030	.032	568.10	592.00
.000333	45.	45.	45.	2	0	1	0.00	52.00	644.00

3470 ENCROACHMENT STATIONS= 115.0 200.0 TYPE= 1 TARGET= 85.000

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 580.90 ELREA= 100000.00

4931.00	9.25	579.55	0.00	0.00	579.68	.13	.21	.01	580.90
1760.	0.	1760.	0.	0.	600.	0.	99.	27.	100000.00
.41	0.00	2.93	0.00	.040	.032	.037	.032	570.30	117.17
.000305	650.	650.	650.	2	0	1	0.00	82.55	199.72

3470 ENCROACHMENT STATIONS= 115.0 200.0 TYPE= 1 TARGET= 85.000

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 581.25 ELREA= 100000.00

5956.00	9.21	579.86	0.00	0.00	580.00	.13	.31	.00	581.25
1760.	0.	1760.	0.	0.	597.	0.	113.	28.	100000.00
.51	0.00	2.95	0.00	.040	.032	.037	.032	570.65	117.22
.000309	1025.	1025.	1025.	1	0	1	0.00	82.47	199.69

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 582.60 ELREA= 582.00

6981.00	9.19	580.19	0.00	0.00	580.32	.13	.32	.00	582.60
1760.	0.	1760.	0.	0.	606.	0.	127.	30.	582.00
.61	0.00	2.90	0.00	.040	.032	.037	.032	571.00	509.39
.000314	1025.	1025.	1025.	0	0	1	0.00	87.40	596.80

3280 CROSS SECTION 8031.00 EXTENDED .01 FEET

3470 ENCROACHMENT STATIONS= 150.0 246.0 TYPE= 1 TARGET= 96.000

8031.00	9.02	580.52	0.00	0.00	580.63	.11	.31	.01	580.70
1760.	0.	1760.	0.	0.	653.	0.	142.	33.	100000.00
.71	0.00	2.70	0.00	.040	.032	.037	.032	571.50	150.56
.000275	1050.	1050.	1050.	0	0	1	0.00	95.44	246.00

3280 CROSS SECTION 8082.00 EXTENDED 2.95 FEET

3470 ENCROACHMENT STATIONS= 580.0 655.0 TYPE= 1 TARGET= 75.000

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 580.90 ELREA= 100000.00

8082.00	10.65	580.55	0.00	0.00	580.65	.10	.01	.00	580.90
1760.	0.	1760.	0.	0.	688.	0.	143.	33.	100000.00
.72	0.00	2.56	0.00	.030	.030	.030	.032	569.90	580.00
.000275	51.	51.	51.	2	0	1	0.00	75.00	655.00

SPECIAL BRIDGE

SB	XK	XKOR	COFQ	RDLEN	BWC	BWP	BAREA	SS	ELCHU	ELCHD
	1.25	1.56	2.60	0.00	75.00	3.00	519.00	-0.00	569.90	569.90

3280 CROSS SECTION 8147.00 EXTENDED 3.13 FEET

PRESSURE FLOW

EGPRS	EGLWC	H3	QWEIR	QPR	BAREA	ELLC	ELTRD	CLASS
580.83	580.66	.01	0.	1760.	519.	578.40	580.90	10.00

Harrison St.

3470 ENCROACHMENT STATIONS= 580.0 655.0 TYPE= 1 TARGET= 75.000

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 580.90 ELREA= 100000.00

8147.00	10.83	580.73	0.00	0.00	580.83	.10	.18	0.00	580.90
1760.	0.	1760.	0.	0.	701.	0.	144.	33.	100000.00
.73	0.00	2.51	0.00	.030	.030	.030	.032	569.90	580.00
.000259	65.	65.	65.	2	0	1	0.00	75.00	655.00

3470 ENCROACHMENT STATIONS= 550.0 635.0 TYPE= 1 TARGET= 85.000

9397.00	9.27	581.07	0.00	0.00	581.20	.13	.36	.02	579.30
1760.	0.	1760.	0.	0.	602.	0.	163.	35.	100000.00
.84	0.00	2.92	0.00	.035	.032	.040	.032	571.80	550.00
.000315	1250.	1250.	1250.	0	0	1	0.00	84.18	634.18

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

3470 ENCROACHMENT STATIONS= .0 480.0 TYPE= 1 TARGET= 479.999

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 583.40 ELREA= 100000.00

10297.00	9.54	581.34	0.00	0.00	581.48	.14	.28	.00	583.40
1760.	0.	1760.	0.	0.	586.	0.	175.	37.	100000.00
.93	0.00	3.00	0.00	.035	.032	.040	.032	571.80	403.43
.000305	900.	900.	900.	2	0	1	0.00	76.19	479.62

3470 ENCROACHMENT STATIONS= 112.0 185.0 TYPE= 1 TARGET= 73.000

10897.00	9.33	581.53	0.00	0.00	581.68	.15	.19	.01	580.40
1760.	0.	1760.	0.	0.	559.	0.	183.	38.	100000.00
.98	0.00	3.15	0.00	.035	.032	.035	.032	572.20	112.00
.000345	600.	600.	600.	0	0	1	0.00	73.00	185.00

3470 ENCROACHMENT STATIONS= 500.0 552.0 TYPE= 1 TARGET= 52.000

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 581.70 ELREA= 100000.00

10973.00	9.83	581.53	0.00	0.00	581.76	.23	.04	.04	581.70
1760.	0.	1760.	0.	0.	454.	0.	184.	38.	100000.00
.99	0.00	3.88	0.00	.035	.032	.035	.032	571.70	500.00
.000734	76.	76.	76.	2	0	1	0.00	52.00	552.00

SPECIAL BRIDGE

SB	XK	XKOR	COFQ	RDLEN	BWC	BWP	BAREA	SS	ELCHU	ELCHD
	.90	1.47	2.50	-0.00	52.00	2.00	315.00	-0.00	571.70	571.70

Harrison St. #2

PRESSURE AND WEIR FLOW

EGPRS	EGLWC	H3	QWEIR	QPR	BAREA	ELLC	ELTRD	CLASS
582.24	581.77	.01	48.	1702.	315.	579.00	581.70	30.00

3470 ENCROACHMENT STATIONS= 500.0 552.0 TYPE= 1 TARGET= 52.000
ELENCL= 590.00 ELENCR= 590.00

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 581.70 ELREA= 590.00

11017.00	10.28	581.98	0.00	0.00	582.19	.21	.43	0.00	581.70
1760.	0.	1760.	0.	0.	478.	0.	184.	38.	590.00
.99	0.00	3.69	0.00	.035	.032	.035	.032	571.70	500.00
.000629	44.	44.	44.	2	0	3	0.00	52.00	552.00

3280 CROSS SECTION 11477.00 EXTENDED .07 FEET

3470 ENCROACHMENT STATIONS= 155.0 255.0 TYPE= 1 TARGET= 100.000

11477.00	10.47	582.27	0.00	0.00	582.40	.13	.19	.02	582.90
1760.	0.	1759.	1.	0.	606.	6.	190.	39.	581.40
1.03	0.00	2.90	.24	.060	.032	.060	.032	571.80	156.18
.000281	460.	460.	460.	2	0	1	0.00	93.65	249.82

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	LEFT/RIGHT
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

3470 ENCROACHMENT STATIONS= 530.0 582.5 TYPE= 1 TARGET= 52.500

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 583.00 ELREA= 100000.00

11528.00	10.16	582.26	0.00	0.00	582.46	.20	.02	.04	583.00
1760.	0.	1760.	0.	0.	485.	0.	191.	39.	100000.00
1.04	0.00	3.63	0.00	.060	.032	.060	.032	572.10	530.00
.000625	51.	51.	51.	2	0	1	0.00	52.50	582.50

SPECIAL BRIDGE

SB	XK	XKOR	COFQ	RDLEN	BWC	BWP	BAREA	SS	ELCHU	ELCHD
	1.25	1.61	2.50	-0.00	52.50	2.00	400.00	-0.00	572.10	572.10

PRESSURE FLOW

EGPRS	EGLWC	H3	QWEIR	QPR	BAREA	ELLC	ELTRD	CLASS
582.74	582.48	.02	0.	1760.	400.	580.70	582.80	10.00

North Bound
Fort St.

3470 ENCROACHMENT STATIONS= 530.0 582.5 TYPE= 1 TARGET= 52.500

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 583.00 ELREA= 100000.00

11599.00	10.45	582.55	0.00	0.00	582.74	.19	.28	0.00	583.00
1760.	0.	1760.	0.	0.	501.	0.	191.	39.	100000.00
1.04	0.00	3.52	0.00	.060	.032	.060	.032	572.10	530.00
.000568	71.	71.	71.	2	0	1	0.00	52.50	582.50

3470 ENCROACHMENT STATIONS= 548.0 604.0 TYPE= 1 TARGET= 56.000

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 583.40 ELREA= 100000.00

11650.00	10.50	582.60	0.00	0.00	582.77	.17	.03	.01	583.40
1760.	0.	1760.	0.	0.	525.	0.	192.	39.	100000.00
1.05	0.00	3.35	0.00	.060	.032	.060	.032	572.10	548.00
.000492	51.	51.	51.	1	0	1	0.00	56.00	604.00

SPECIAL BRIDGE

SB	XK	XKOR	COFQ	RDLEN	BWC	BWP	BAREA	SS	ELCHU	ELCHD

PRESSURE FLOW


EGPRS	EGLWC	H3	QWEIR	QPR	BAREA	ELLC	ELTRD	CLASS
583.08	582.78	.01	0.	1760.	400.	580.70	583.20	10.00

South Bound
Fort St.

3470 ENCROACHMENT STATIONS= 548.0 604.0 TYPE= 1 TARGET= 56.000

OVERBANK AREA ASSUMED NON-EFFECTIVE,ELLEA= 583.40 ELREA= 100000.00

11721.00	10.82	582.92	0.00	0.00	583.08	.16	.31	0.00	583.40
1760.	0.	1760.	0.	0.	543.	0.	193.	39.	100000.00
1.05	0.00	3.24	0.00	.060	.032	.060	.032	572.10	548.00
.000443	71.	71.	71.	2	0	1	0.00	56.00	604.00


LINCOLN PARK
ECORSE
ECORSE
ECORSE
Mud Island
Fighting Island
Grassy Island
DETROIT RIVER
CHANNEL
Ecorse Channel
Ecorse Creek
Detroit Waterworks
Radio Towers (WJBK)
Trailer Park
Trailer Park
Youth Center Park
Memorial Park
Ford Park
Playground
Playground
La Blanc Field
Park
Ecorse Park
Lincoln Park High Sch
Huff Jr High Sch
South Jr High Sch
St Francis Cabrini High Sch
Faun Sch
Smith Sch
Goodell Sch
Keppen Sch
Mixter Sch
Calvary Sch
Crowley Sch
Foote Sch
Riley Sch
Good Shepherd Sch
Hoover Sch
Le Blanc Sch
Carr Sch
Hamilton Sch
Edgewood Sch
Gerisch Sch
Shelters Sch
Schafer High Sch
Wilson Jr High Sch
Jefferson Sch
Taft Sch
Woodruff Sch
Labadie Sch
Ecorse Sch
School No 3
Munnipal Bldg
John F Kennedy Sch
Ecorse High Sch
Ecorse Sch No 2
Rapp Sch
Argo Sch
Rosedale Park
City Hall
BM 587
BM 581
BM 577
BM 578
BM 588
Light 164
Light
Lights
Light
Light
Cem
SEXTON-KILFOIL DRAIN
CITY OF WYANDOTTE FIS
5555-73
SCALE: 1" = 800'
CORPORATE BOUND.
FLOODED OUTLINE