

Fujitsu Scanners - Production Scanners



		fi-6110	fi-7180	fi-7280	fi-6770	fi-6800
ITRAC		SC14	SC12	SC13	SC06	SC15
Part Number		PA03607-B065	PA03670-B005	PA03670-B505	PA03576-B165	PA03575-B065
Image Sensor - Optics		CCD X 2	CCD X 2	CCD X 3	CCD x 3	CCD X 2
Scanning Speed	Monochrome	200 dpi	20 ppm / 40 ipm	80 ppm / 160 ipm	80 ppm / 160 ipm	90 ppm / 180 ipm (Landscape)
		300 dpi	20 ppm / 40 ipm	80 ppm / 160 ipm	80 ppm / 160 ipm	80 ppm / 160 ipm (Landscape)
	Color	150 dpi	20 ppm / 40 ipm	80 ppm / 160 ipm	80 ppm / 160 ipm	N/A
		200 dpi	20 ppm / 40 ipm	80 ppm / 160 ipm	80 ppm / 160 ipm	90 ppm / 180 ipm (Landscape)
		300 dpi	20 ppm / 40 ipm	80 ppm / 160 ipm	80 ppm / 160 ipm	60 ppm / 120 ipm (Landscape)
Resolution	Output	600 dpi	600 dpi	600 dpi	600 dpi	600 dpi
	Optical	50 to 600 dpi (adjustable by 1 dpi increments, 1200 dpi(1))	50 to 600 dpi (adjustable by 1 dpi increments, 1200 dpi(1))	50 to 600 dpi (adjustable by 1 dpi increments, 1200 dpi(1))	50 to 600 dpi (adjustable by 1 dpi increments, 1200 dpi(1))	Up to 600 dpi
Grayscale		8 bit / 256 level	8 bit / 256 level	8 bit / 256 level	8 bit / 256 level	8 bit / 256 level
Simplex/Deluxe		Duplex	Duplex	Duplex	Duplex	Duplex
ADF Capacity		50 sheets	80 Sheets	80 Sheets	200 Sheets	500 Sheets
Document Size	Maximum	8.5 x 14.17 in.	8.5 x 14 in.	8.5 x 14 in.	11 in. x 17 in.	12 in. x 17 in.
	Minimum	2.1 in. x 2.9 in.	2 x 2.13 in.	2 x 2.13 in.	2 in. x 3 in.	2.1 in. x 2.9 in.
	Long Document	Yes (120")	Yes (220")	Yes (220")	Yes (120")	Yes (120")
Embossed Card	Support	N/A	Yes (1.4 mm)	Yes (1.4 mm)	N/A	N/A
	Orientation	N/A	Portrait & Landscape	Portrait & Landscape	N/A	N/A
	Continuous	N/A	Yes - up to 3 hard cards	Yes - up to 3 hard cards	N/A	N/A
Paper Weight (Thickness)		14 - 34 lb.	7.2 to 110 lb.	7.2 to 110 lb.	N/A	N/A
Flatbed (Dim.)		N/A	N/A	Yes (8.5 x 11.69 in.)	Yes (12 x 18 in.)	N/A
Paper Protection		N/A	Yes (2x)	Yes (2x)	Yes	Yes
Multi-feed Detection		Ultra-Sonic and Length	Ultra-Sonic and Length	Ultra-Sonic and Length	Ultra-Sonic	Triple Ultra-Sonic
Multi-feed - IMFF		N/A	Manual Bypass	Manual Bypass	Yes (Automatic)	Yes (Automatic)
Color Dropout		Red, Green, Blue	Red, Green, Blue	Red, Green, Blue	Software Color Dropout	Red, Green, Blue
Interface		USB 2.0	USB 2.0	USB 3.0 / USB 2.0	Ultra SCSI (50M) / USB 2.0 / Third Party Slot	Ultra Wired SCSI & USB 2.0 / VRS Ultra Wide SCSI & VRS USB 2.0
Driver Support		PaperStream IP (TWAIN/ISIS)	Twain / ISIS® / PaperStream IP / ScanSnap Mode	Twain / ISIS® / PaperStream IP / ScanSnap Mode	PaperStream IP (TWAIN/ISIS)	PaperStream IP (TWAIN/ISIS)
Image Enhancement		N/A	PaperStream IP	PaperStream IP	PaperStream IP	PaperStream IP
Bundled Software		PaperStream IP (TWAIN/ISIS) Driver, Software Operation Panel, Error Recovery Guide, PaperStream Capture, Scanner Central Admin Agent	PaperStream IP (TWAIN/ISIS) Driver, Software Operation Panel, Error Recovery Guide, PaperStream Capture, ScanSnap Manager for fi Series, Scan to Microsoft SharePoint, ABBYY FineReader for ScanSnap, Scanner Central Admin Agent	PaperStream IP (TWAIN/ISIS) Driver, Software Operation Panel, Error Recovery Guide, PaperStream Capture, ScanSnap Manager for fi Series, Scan to Microsoft SharePoint, ABBYY FineReader for ScanSnap, Scanner Central Admin Agent	PaperStream IP (TWAIN/ISIS) Driver, Software Operation Panel, Error Recovery, PaperStream Capture, Scanner Central Admin Agent	PaperStream IP (TWAIN/ISIS) Driver, Software Operation Panel, Error Recovery Guide, PaperStream Capture, Scanner Central Admin Agent
Dimensions (W x D x H)		11.5 in. x 5.6 in. x 5.1 in.	11.8 x 6.7 x 6.4 in.	11.8 x 22.7 x 9.2 in.	27.16 in. x 19.68 in. x 13.38 in.	16.9 in. x 12.2 in x 18.1 in.
Weight (lb.)		6.61 lbs.	9.26 lb.	19.4 lb.	77.2 lb.	70.5 lbs.
Imprinter Option		N/A	Yes - PostScan	N/A	N/A	Post Imprinter (Front-side) and Post Imprinter (Back-side)
Standard Warranty		1 Year Depot	1-Year Advanced Exchange	1-Year Advanced Exchange	3 Month On-Site	3 Month On-Site

1. Scanning limitations brought about by scanning mode, document size and available memory may occur when scanning at high resolutions (600dpi or higher).