

DEPARTMENT OF LICENSING AND REGULATORY AFFAIRS

DIRECTOR'S OFFICE

GENERAL INDUSTRY SAFETY AND HEALTH STANDARD STANDARDS

Filed with the secretary of state on June 4, 2019

These rules take effect immediately upon filing with the secretary of state unless adopted under section 33, 44, or 45a(6) of the administrative procedures act of 1969, 1969 PA 306, MCL 24.233, 24.244, or 24.245a. Rules adopted under these sections become effective 7 days after filing with the secretary of state.

(By authority conferred on the director of the department of licensing and regulatory affairs by sections 16 and 21 of **the Michigan occupational safety and health act**, 1974 PA 154, MCL 408.1016 and 408.1021, and Executive Reorganization Order Nos. 1996-2, 2003-1, 2008-4, and 2011-4, MCL 445.2001, 445.2011, 445.2025, and 445.2030)

R 408.11721 and R 408.11732 of the Michigan Administrative Code are amended as follows:

PART 17. REFUSE PACKER UNITS

R 408.11721 Riding steps.

Rule 1721. (1) A riding step provided for an employee making collections on a mobile refuse packer unit ~~must shall~~ **have both of the following**:

(a) ~~A Have~~ a slip resistant surface.

(b) ~~A Have~~ a maximum height of 18 inches from the roadway with the mobile unit empty.

(2) A grab handle ~~must shall~~ be provided for each employee using a riding step as **prescribed in General Industry Safety and Health Standard Part 2. "Walking-Working Surfaces," being R 408.10201 to R 408.10241** ~~specified in rule 237 of the occupational safety standards commission standard, Part 2. Floor and Wall Openings, Stairways and Skylights, being R 408.10237 of the Michigan Administrative Code.~~

R 408.11732 Guards.

Rule 1732. (1) A hopper opening on a stationary refuse packer unit ~~must shall~~ be guarded with a **guardrail system** ~~standard barrier as prescribed in compliance with General Industry Safety and Health Standard Part 2. "Walking-Working Surfaces," being R 408.10201 to R 408.10241 rule 231 of the occupational safety standards commission standard, Part 2. Floor and Wall Openings and Stairways, being R 408.10231 of the Michigan Administrative Code.~~

(2) A pinch point exposed to contact by an employee ~~must shall~~ be enclosed or guarded.

(3) A lifting device used to empty a container at a stationary refuse packer unit ~~must shall~~ have a locking device as prescribed in R 408.11723(2).

(4) Maintenance access openings ~~must shall~~ be covered and secured on the compactor. The cover ~~must shall~~ be removable by hand tools or interlocked to the power source.

(5) A locking device used to couple a receiving box and stationary compactor unit ~~must shall~~ be capable of withstanding the rated pressure of the compactor.

(6) A receiving box loading device ~~must shall~~ provide a positive locking action to prevent dislodgement during the loading of the box on a vehicle.

(7) A receiving box loaded on a vehicle for transport ~~must shall~~ have a retaining device other than the loading device.