2020 Excavation Stand-Down Week June 15-19







SLOPE IT



Michigan Trench Cave In Fatalities 1992 - 2019





1 – Qualified Person

Rule 408.40932(4) An ongoing inspection of an excavation or trench shall be made by a qualified person. After every rainstorm or other hazard-producing occurrence, an inspection shall be made by a qualified employee for evidence of possible slides or cave-ins. Where these conditions are found, all work shall cease until additional precautions, such as additional shoring or reducing the slope, have been accomplished.



2 – Spoil Piles

Rule 408.40933(2) An excavation that an employee is required to enter shall have excavated and other material stored and retained not less than <u>2 feet</u> from the excavation edge.



3 – MISS DIG 811

- ♦ Rule 408.40931(1) An employer shall not excavate in a street, highway, public place, a private easement of a public utility, or near the location of a public utility facility owned, maintained, or installed on a customer's premises, without having first ascertained the location of all underground facilities of a public utility in the proposed area of excavation.
- Public Act 174 Prior to excavation the MISS DIG system must be contacted at least 3 Days in advance of construction.



4 – Access/Egress

Rule 408.40933(4) An excavation 4 feet or more in depth and occupied by an employee shall be provided with either a ladder or with a ramp. Lateral travel along the wall of a trench to a ladder or other means of egress shall not exceed 25 feet.



5 – Cave In Protection

♦ Rule 408.40941(1) The side of an excavation more than 5 feet deep shall be sloped as prescribed in table 1, unless supported as prescribed in this part.

Resource Links

MIOSHA

MISS DIG 811

OSHA



NUCA