

Maintenance Advisory

MA 2012-02

April 26, 2012

From Mark Geib, Engineer of Operations Field Services Division

MDOT
Operations Field Services
Division
6333 Old Lansing Road
Lansing, MI 48917

Questions regarding this
Maintenance Advisory or to
request assistance in setting
up your program should be
directed to:

Carlos Torres, P.E.
Crash Barrier Engineer
Phone/517-335-2852
TorresC@michigan.gov

Gary Mayes, Engineer of
Maintenance Services
Section
Phone/517-322-3315
MayesG@michigan.gov

Reducing Possibility of Cable Grip Slippage during Cable Barrier Repairs

Cable grips are devices typically used for pulling cables, such as the three-strand cables used in high tension cable barrier systems. Cable grips designed for servicing high tension cable barrier systems are capable of withstanding very large forces (e.g.: minimum service loads of 10,000 pounds or greater). However, when using these devices, there exists a possibility of the cable grip slipping along the cable and/or slipping completely off the cable. Should a cable grip slip along the cable and/or slip off the cable while servicing/repairing a cable barrier system, damage to nearby equipment and/or injury to nearby workers can occur. To reduce the possibility of a cable grip slipping along a cable and/or the cable grip slipping completely off the cable, the following recommendations should be followed:

- Use cable grips, of the correct size and type, equipped with safety latches.
 - Example: Klein Model 1672-10 or similar product.



- Always follow the cable grip manufacturer's recommended care and maintenance guidelines before and after each use. For example;
 - Use a wire brush or emery cloth to clean the surfaces of grip jaws.
 - Spray degreaser on the grip jaws, all joints and moving parts.
 - Use a wire brush to remove dirt and debris from the grip jaws. Completely remove any foreign material in the jaws that may cause slippage.
 - Clean and wipe grips dry with a soft cloth.
 - Lubricate all joints and moving parts according to manufacturer's specifications, but **DO NOT LUBRICATE GRIPPING SURFACES OF GRIP JAWS.**
 - Carefully inspect jaw condition and check all parts for distortion or misalignment. Check mechanical condition of entire cable grip.
 - **NEVER ATTEMPT TO REPAIR ANY GRIPS.** Grips that are bent, misaligned, or otherwise distorted should be discarded and replaced.

- C-clamps to help keep the cable grip's safety latch in place.



- U-bolt cable clamp attached to the cable directly behind the cable grip.
 - Example: Drop Forged Wire Rope Clamp for $\frac{3}{4}$ " diameter cable or similar product.



Safety latches on cable grips help keep the cable grip from slipping off the cable. As an additional precaution, securing a c-clamp to the safety latch will help keep the safety latch in place and reduce the chances of the safety latch failing if subjected to a large lateral force. Also, attaching a u-bolt cable clamp to the cable, directly behind the cable grip, will help keep the cable grip from slipping along the cable.



Original Advisory Date 4/26/2012
Updated 5/01/2018
Next Review 5/01/2023