#### MIOSHA Part 9, Excavation, Trenching, and Shoring **Five Important Safety Rules**

- 1. Must slope, bench, shore, or use a trench box if deeper than 5'. Follow Table 1 (see other side). You may need to slope at less than 5' if hazard exists.
- 2. A Competent Person must decide the proper slope for the trench and inspect it.
- 3. Inspections must be an ongoing process. If the excavation does not have the proper slope or otherwise is dangerous, do not enter until you make it safe.
- 4. Keep spoils pile at least 2' back from the trench edge.
- 5. Put a ladder or ramp in trenches 4' or deeper.

MIOSHA Consultation Education and Training Division (800) 866-4674



#### www.michigan.gov/miosha Equal opportunity employer/service provider. MIOSHA/CET 0204 (2/2024)


# LABOR & ECONOP

## MIOSHA Part 9, Excavation, Trenching, and Shoring **Five Important Safety Rules**

- 1. Must slope, bench, shore, or use a trench box if deeper than 5'. Follow Table 1 (see other side). You may need to slope at less than 5' if hazard exists.
- 2. A Competent Person must decide the proper slope for the trench and inspect it.
- 3. Inspections must be an ongoing process. If the excavation does not have the proper slope or otherwise is dangerous, do not enter until you make it safe.
- 4. Keep spoils pile at least 2' back from the trench edge.
- 5. Put a ladder in trenches deeper than 4'.
  - MIOSHA Consultation Education and Training Division (800) 866-4674



www.michigan.gov/miosha



#### MIOSHA Part 9, Excavation, Trenching, and Shoring **Five Important Safety Rules**

- 1. Must slope, bench, shore, or use a trench box if deeper than 5'. Follow Table 1 (see other side). You may need to slope at less than 5' if hazard exists.
- 2. A Competent Person must decide the proper slope for the trench and inspect it.
- 3. Inspections must be an ongoing process. If the excavation does not have the proper slope or otherwise is dangerous, do not enter until you make it safe.
- 4. Keep spoils pile at least 2' back from the trench edge.
- 5. Put a ladder in trenches deeper than 4'.
- MIOSHA Consultation Education and Training Division (800) 866-4674



#### www.michigan.gov/miosha Equal opportunity employer/service provider. LABOR & ECONOM MIOSHA/CET 0204 (2/2024)

#### MIOSHA Part 9, Excavation, Trenching, and Shoring **Five Important Safety Rules**

- 1. Must slope, bench, shore, or use a trench box if deeper than 5'. Follow Table 1 (see other side). You may need to slope at less than 5' if hazard exists.
- 2. A Competent Person must decide the proper slope for the trench and inspect it.
- 3. Inspections must be an ongoing process. If the excavation does not have the proper slope or otherwise is dangerous, do not enter until you make it safe.
- 4. Keep spoils pile at least 2' back from the trench edge.
- 5. Put a ladder in trenches deeper than 4'.
  - MIOSHA Consultation Education and Training Division (800) 866-4674 www.michigan.gov/miosha



Equal opportunity employer/service provider. MIOSHA/CET 0204 (2/2024)

## MIOSHA Part 9, Excavation, Trenching, and Shoring Five Important Safety Rules

- 1. Must slope, bench, shore, or use a trench box if deeper than 5'. Follow Table 1 (see other side). You may need to slope at less than 5' if hazard exists.
- A Competent Person must decide the proper slope for the trench and inspect it.
- 3. Inspections must be an ongoing process. If the excavation does not have the proper slope or otherwise is dangerous, do not enter until you make it safe.
- 4. Keep spoils pile at least 2' back from the trench edge.
- 5. Put a ladder in trenches deeper than 4'.

MIOSHA Consultation Education and Training Division (800) 866-4674

MIOSHA Part 9, Excavation, Trenching, and Shoring

**Five Important Safety Rules** 

1. Must slope, bench, shore, or use a trench box if deeper than 5'. Follow Table 1

2. A Competent Person must decide the proper slope for the trench and inspect it.

3. Inspections must be an ongoing process. If the excavation does not have the

proper slope or otherwise is dangerous, do not enter until you make it safe.

MIOSHA Consultation Education and Training Division (800) 866-4674

www.michigan.gov/miosha

Equal opportunity employer/service provider.

MIOSHA/CET 0204 (2/2024)

(see other side). You may need to slope at less than 5' if hazard exists.



MIOSH/

MIOSHA

MIOSHA


www.michigan.gov/miosha Equal opportunity employer/service provider. MIOSHA/CET 0204 (2/2024)



LABOR & ECONOM

## MIOSHA Part 9, Excavation, Trenching, and Shoring Five Important Safety Rules

- 1. Must slope, bench, shore, or use a trench box if deeper than 5'. Follow Table 1 (see other side). You may need to slope at less than 5' if hazard exists.
- 2. A Competent Person must decide the proper slope for the trench and inspect it.
- 3. Inspections must be an ongoing process. If the excavation does not have the proper slope or otherwise is dangerous, do not enter until you make it safe.
- 4. Keep spoils pile at least 2' back from the trench edge.
- 5. Put a ladder in trenches deeper than 4'.





www.michigan.gov/miosha Equal opportunity employer/service provider. MIOSHA/CET 0204 (2/2024)



MIOSHA Part 9, Excavation, Trenching, and Shoring Five Important Safety Rules

- 1. Must slope, bench, shore, or use a trench box if deeper than 5'. Follow Table 1 (see other side). You may need to slope at less than 5' if hazard exists.
- 2. A Competent Person must decide the proper slope for the trench and inspect it.
- 3. Inspections must be an ongoing process. If the excavation does not have the proper slope or otherwise is dangerous, do not enter until you make it safe.
- 4. Keep spoils pile at least 2' back from the trench edge.


4. Keep spoils pile at least 2' back from the trench edge.

4. Keep spoils pile at least 2' back from the trench edge.

5. Put a ladder in trenches deeper than 4'.

5. Put a ladder in trenches deeper than 4'.

5. Put a ladder in trenches deeper than 4'.



MIOSHA Part 9, Excavation, Trenching, and Shoring

Five Important Safety Rules

1. Must slope, bench, shore, or use a trench box if deeper than 5'. Follow Table 1

2. A Competent Person must decide the proper slope for the trench and inspect it.

3. Inspections must be an ongoing process. If the excavation does not have the

proper slope or otherwise is dangerous, do not enter until you make it safe.

(see other side). You may need to slope at less than 5' if hazard exists.



www.michigan.gov/miosha Equal opportunity employer/service provider. MIOSHA/CET 0204 (2/2024)

LABOR & ECONOMI


## MIOSHA Part 9, Excavation, Trenching, and Shoring **Five Important Safety Rules**

- 1. Must slope, bench, shore, or use a trench box if deeper than 5'. Follow Table 1 (see other side). You may need to slope at less than 5' if hazard exists.
- 2. A Competent Person must decide the proper slope for the trench and inspect it.
- 3. Inspections must be an ongoing process. If the excavation does not have the proper slope or otherwise is dangerous, do not enter until you make it safe.
- Keep spoils pile at least 2' back from the trench edge.

4. Keep spoils pile at least 2' back from the trench edge.

5. Put a ladder in trenches deeper than 4'.

5. Put a ladder in trenches deeper than 4'.



Equal opportunity employer/service provider. MIOSHA/CET 0204 (2/2024)


LABOR & ECONOMI

#### MIOSHA Part 9, Excavation, Trenching, and Shoring Five Important Safety Rules

- 1. Must slope, bench, shore, or use a trench box if deeper than 5'. Follow Table 1 (see other side). You may need to slope at less than 5' if hazard exists.
- 2. A Competent Person must decide the proper slope for the trench and inspect it.
- 3. Inspections must be an ongoing process. If the excavation does not have the proper slope or otherwise is dangerous, do not enter until you make it safe.
- Keep spoils pile at least 2' back from the trench edge.
- Put a ladder in trenches deeper than 4'.
- MIOSHA Consultation Education and Training Division (800) 866-4674 www.michigan.gov/miosha

Equal opportunity employer/service provider. MIOSHA/CET 0204 (2/2024)

LABOR & ECONOMI



www.michigan.gov/miosha Equal opportunity employer/service provider. MIOSHA/CET 0204 (2/2024)

LABOR & ECONOMI OPPORTUNITY

MIOSHA

MIOSHA Consultation Education and Training Division (800) 866-4674 www.michigan.gov/miosha

Equal opportunity employer/service provider. MIOSHA/CET 0204 (2/2024)

MIOSHA Part 9, Excavation, Trenching, and Shoring

Five Important Safety Rules

1. Must slope, bench, shore, or use a trench box if deeper than 5'. Follow Table 1

2. A Competent Person must decide the proper slope for the trench and inspect it.

3. Inspections must be an ongoing process. If the excavation does not have the

proper slope or otherwise is dangerous, do not enter until you make it safe.

(see other side). You may need to slope at less than 5' if hazard exists.





