MIOSHA Part 9. Excavations, Trenching, and Shoring

Table 1: Max Angle of Repose for Excavation Sides in Excess of 5' Depth



		Soil Strength (TSF)	Slope	Ratio
1	Solid rock		90°	
2	Fractured rock		75°	¼:1
3	Stiff clay	>2.5	63°	½:1
4	Firm clay	2.5	56°	2/3:1
5	Previously disturbed soil	1.5	45°	1:1
6	Granular soil wet	1.0	34°	1 ½:1
7	Saturated granular soil	<1.0	26°	2:1
8	Running soil		18°	3:1

MIOSHA Part 9. Excavations, Trenching, and Shoring

Table 1: Max Angle of Repose for Excavation Sides in Excess of 5' Depth



		Soil Strength (TSF)	Slope	Ratio
1	Solid rock		90°	
2	Fractured rock		75°	¼:1
3	Stiff clay	>2.5	63°	½:1
4	Firm clay	2.5	56°	2/3:1
5	Previously disturbed soil	1.5	45°	1:1
6	Granular soil wet	1.0	34°	1 ½:1
7	Saturated granular soil	<1.0	26°	2:1
8	Running soil		18°	3:1

MIOSHA Part 9. Excavations, Trenching, and Shoring

Table 1: Max Angle of Repose for Excavation Sides in Excess of 5' Depth



		Soil Strength (TSF)	Slope	Ratio
1	Solid rock		90°	
2	Fractured rock		75°	¼:1
3	Stiff clay	>2.5	63°	½:1
4	Firm clay	2.5	56°	2/3:1
5	Previously disturbed soil	1.5	45°	1:1
6	Granular soil wet	1.0	34°	1 ½:1
7	Saturated granular soil	<1.0	26°	2:1
8	Running soil		18°	3:1

MIOSHA Part 9. Excavations, Trenching, and Shoring

Table 1: Max Angle of Repose for Excavation Sides in Excess of 5' Depth



		Soil Strength (TSF)	Slope	Ratio
1	Solid rock		90°	
2	Fractured rock		75°	¼:1
3	Stiff clay	>2.5	63°	½:1
4	Firm clay	2.5	56°	2/3:1
5	Previously disturbed soil	1.5	45°	1:1
6	Granular soil wet	1.0	34°	1 ½:1
7	Saturated granular soil	<1.0	26°	2:1
8	Running soil		18°	3:1

MIOSHA Part 9. Excavations, Trenching, and Shoring

Table 1: Max Angle of Repose for Excavation Sides in Excess of 5' Depth



		Soil Strength (TSF)	Slope	Ratio
1	Solid rock		90°	
2	Fractured rock		75°	¼:1
3	Stiff clay	>2.5	63°	½:1
4	Firm clay	2.5	56°	2/3:1
5	Previously disturbed soil	1.5	45°	1:1
6	Granular soil wet	1.0	34°	1 ½:1
7	Saturated granular soil	<1.0	26°	2:1
8	Running soil		18°	3:1

MIOSHA Part 9. Excavations, Trenching, and Shoring

Table 1: Max Angle of Repose for Excavation Sides in Excess of 5' Depth



		Soil Strength (TSF)	Slope	Ratio
1	Solid rock		90°	
2	Fractured rock		75°	¼:1
3	Stiff clay	>2.5	63°	½:1
4	Firm clay	2.5	56°	2/3:1
5	Previously disturbed soil	1.5	45°	1:1
6	Granular soil wet	1.0	34°	1 ½:1
7	Saturated granular soil	<1.0	26°	2:1
8	Running soil		18°	3:1

MIOSHA Part 9. Excavations, Trenching, and Shoring

Table 1: Max Angle of Repose for Excavation Sides in Excess of 5' Depth



		Soil Strength (TSF)	Slope	Ratio
1	Solid rock		90°	
2	Fractured rock		75°	¼:1
3	Stiff clay	>2.5	63°	½:1
4	Firm clay	2.5	56°	2/3:1
5	Previously disturbed soil	1.5	45°	1:1
6	Granular soil wet	1.0	34°	1 ½:1
7	Saturated granular soil	<1.0	26°	2:1
8	Running soil		18°	3:1

MIOSHA Part 9. Excavations, Trenching, and Shoring

Table 1: Max Angle of Repose for Excavation Sides in Excess of 5' Depth



		Soil Strength (TSF)	Slope	Ratio
1	Solid rock		90°	
2	Fractured rock		75°	¼:1
3	Stiff clay	>2.5	63°	½:1
4	Firm clay	2.5	56°	2/3:1
5	Previously disturbed soil	1.5	45°	1:1
6	Granular soil wet	1.0	34°	1 ½:1
7	Saturated granular soil	<1.0	26°	2:1
8	Running soil		18°	3:1

MIOSHA Part 9. Excavations, Trenching, and Shoring

Table 1: Max Angle of Repose for Excavation Sides in Excess of 5' Depth



		Soil Strength (TSF)	Slope	Ratio
1	Solid rock		90°	
2	Fractured rock		75°	¼:1
3	Stiff clay	>2.5	63°	½:1
4	Firm clay	2.5	56°	2/3:1
5	Previously disturbed soil	1.5	45°	1:1
6	Granular soil wet	1.0	34°	1 ½:1
7	Saturated granular soil	<1.0	26°	2:1
8	Running soil		18°	3:1

MIOSHA Part 9. Excavations, Trenching, and Shoring

Table 1: Max Angle of Repose for Excavation Sides in Excess of 5' Depth



		Soil Strength (TSF)	Slope	Ratio
1	Solid rock		90°	
2	Fractured rock		75°	¼:1
3	Stiff clay	>2.5	63°	½:1
4	Firm clay	2.5	56°	2/3:1
5	Previously disturbed soil	1.5	45°	1:1
6	Granular soil wet	1.0	34°	1 ½:1
7	Saturated granular soil	<1.0	26°	2:1
8	Running soil		18°	3:1

MIOSHA Part 9. Excavations, Trenching, and Shoring

Five Important Safety Rules

1. Must slope, bench, shore, or use a trench box if deeper than 5'. Follow Table 1 (see other side). You may need to slope at less than 5' if hazard exists.
2. A Qualified Person must decide the proper slope for the trench and inspect it.
3. Inspections must be an ongoing process. If the excavation does not have the proper slope or otherwise is dangerous, do not enter until you make it safe.
4. Keep spoils pile at least 2' back from the trench edge.
5. Put a ladder in trenches deeper than 4'

MIOSHA Consultation Education and Training Division (800) 866-4674

www.michigan.gov/miosha

Equal opportunity employer/service provider. MIOSHA/CET #0204

MIOSHA Part 9. Excavations, Trenching, and Shoring

Five Important Safety Rules

1. Must slope, bench, shore, or use a trench box if deeper than 5'. Follow Table 1 (see other side). You may need to slope at less than 5' if hazard exists.
2. A Qualified Person must decide the proper slope for the trench and inspect it.
3. Inspections must be an ongoing process. If the excavation does not have the proper slope or otherwise is dangerous, do not enter until you make it safe.
4. Keep spoils pile at least 2' back from the trench edge.
5. Put a ladder in trenches deeper than 4'

MIOSHA Consultation Education and Training Division (800) 866-4674

www.michigan.gov/miosha

Equal opportunity employer/service provider. MIOSHA/CET #0204

MIOSHA Part 9. Excavations, Trenching, and Shoring

Five Important Safety Rules

1. Must slope, bench, shore, or use a trench box if deeper than 5'. Follow Table 1 (see other side). You may need to slope at less than 5' if hazard exists.
2. A Qualified Person must decide the proper slope for the trench and inspect it.
3. Inspections must be an ongoing process. If the excavation does not have the proper slope or otherwise is dangerous, do not enter until you make it safe.
4. Keep spoils pile at least 2' back from the trench edge.
5. Put a ladder in trenches deeper than 4'

MIOSHA Consultation Education and Training Division (800) 866-4674

www.michigan.gov/miosha

Equal opportunity employer/service provider. MIOSHA/CET #0204

MIOSHA Part 9. Excavations, Trenching, and Shoring

Five Important Safety Rules

1. Must slope, bench, shore, or use a trench box if deeper than 5'. Follow Table 1 (see other side). You may need to slope at less than 5' if hazard exists.
2. A Qualified Person must decide the proper slope for the trench and inspect it.
3. Inspections must be an ongoing process. If the excavation does not have the proper slope or otherwise is dangerous, do not enter until you make it safe.
4. Keep spoils pile at least 2' back from the trench edge.
5. Put a ladder in trenches deeper than 4'

MIOSHA Consultation Education and Training Division (800) 866-4674

www.michigan.gov/miosha

Equal opportunity employer/service provider. MIOSHA/CET #0204

MIOSHA Part 9. Excavations, Trenching, and Shoring

Five Important Safety Rules

1. Must slope, bench, shore, or use a trench box if deeper than 5'. Follow Table 1 (see other side). You may need to slope at less than 5' if hazard exists.
2. A Qualified Person must decide the proper slope for the trench and inspect it.
3. Inspections must be an ongoing process. If the excavation does not have the proper slope or otherwise is dangerous, do not enter until you make it safe.
4. Keep spoils pile at least 2' back from the trench edge.
5. Put a ladder in trenches deeper than 4'

MIOSHA Consultation Education and Training Division (800) 866-4674

www.michigan.gov/miosha

Equal opportunity employer/service provider. MIOSHA/CET #0204

MIOSHA Part 9. Excavations, Trenching, and Shoring

Five Important Safety Rules

1. Must slope, bench, shore, or use a trench box if deeper than 5'. Follow Table 1 (see other side). You may need to slope at less than 5' if hazard exists.
2. A Qualified Person must decide the proper slope for the trench and inspect it.
3. Inspections must be an ongoing process. If the excavation does not have the proper slope or otherwise is dangerous, do not enter until you make it safe.
4. Keep spoils pile at least 2' back from the trench edge.
5. Put a ladder in trenches deeper than 4'

MIOSHA Consultation Education and Training Division (800) 866-4674

www.michigan.gov/miosha

Equal opportunity employer/service provider. MIOSHA/CET #0204

MIOSHA Part 9. Excavations, Trenching, and Shoring

Five Important Safety Rules

1. Must slope, bench, shore, or use a trench box if deeper than 5'. Follow Table 1 (see other side). You may need to slope at less than 5' if hazard exists.
2. A Qualified Person must decide the proper slope for the trench and inspect it.
3. Inspections must be an ongoing process. If the excavation does not have the proper slope or otherwise is dangerous, do not enter until you make it safe.
4. Keep spoils pile at least 2' back from the trench edge.
5. Put a ladder in trenches deeper than 4'

MIOSHA Consultation Education and Training Division (800) 866-4674

www.michigan.gov/miosha

Equal opportunity employer/service provider. MIOSHA/CET #0204

MIOSHA Part 9. Excavations, Trenching, and Shoring

Five Important Safety Rules

1. Must slope, bench, shore, or use a trench box if deeper than 5'. Follow Table 1 (see other side). You may need to slope at less than 5' if hazard exists.
2. A Qualified Person must decide the proper slope for the trench and inspect it.
3. Inspections must be an ongoing process. If the excavation does not have the proper slope or otherwise is dangerous, do not enter until you make it safe.
4. Keep spoils pile at least 2' back from the trench edge.
5. Put a ladder in trenches deeper than 4'

MIOSHA Consultation Education and Training Division (800) 866-4674

www.michigan.gov/miosha

Equal opportunity employer/service provider. MIOSHA/CET #0204

MIOSHA Part 9. Excavations, Trenching, and Shoring

Five Important Safety Rules

1. Must slope, bench, shore, or use a trench box if deeper than 5'. Follow Table 1 (see other side). You may need to slope at less than 5' if hazard exists.
2. A Qualified Person must decide the proper slope for the trench and inspect it.
3. Inspections must be an ongoing process. If the excavation does not have the proper slope or otherwise is dangerous, do not enter until you make it safe.
4. Keep spoils pile at least 2' back from the trench edge.
5. Put a ladder in trenches deeper than 4'

MIOSHA Consultation Education and Training Division (800) 866-4674

www.michigan.gov/miosha

Equal opportunity employer/service provider. MIOSHA/CET #0204