



FIFRA 24(c) Special Local Need Label (SLN)

FOR DISTRIBUTION AND USE ONLY WITHIN THE STATE OF MICHIGAN

For Control of Alternaria and Gray Mold in Ginseng (Non-bearing Only)

Bravo Weather Stik®

EPA Reg. No. 66222-276

EPA SLN No. MI-190001

**KEEP OUT OF REACH OF CHILDREN
CAUTION**

This label expires and must not be distributed or used in accordance with this SLN registration after December 31, 2024.

DIRECTIONS FOR USE

- It is a violation of Federal law to use this product in a manner inconsistent with its labeling.
- This label must be in the possession of the user at the time of application.
- Follow all applicable directions, restrictions, Worker Protection Standard requirements, and precautions on the EPA-registered label.

Apply 2 pt/A of Bravo Weather Stik (1.5 lb ai) in sufficient water to obtain adequate coverage. Begin applications when disease first threatens, and repeat at 7-10 day intervals as disease pressure warrants.

Notes: (1) **DO NOT** apply more than 16 pints/A within 14 days prior to harvest. (2) For more than 16 /A pints up to 28 pints/A do not harvest within 365 days of the last application. (3) **DO NOT** apply more than 28 pints/product per acre per growing season to control diseases.

ENVIRONMENTAL HAZARDS

This product is toxic to aquatic invertebrates and wildlife. Do not apply directly to water, to areas where surface water is present, or to intertidal areas below the mean high water mark. Drift and runoff may be hazardous to aquatic organisms in neighboring areas. Do not contaminate water when disposing of equipment wash water or rinsate.

This chemical is known to leach through soil into groundwater under certain conditions as a result of label use. Use of this chemical in areas where soils are permeable, particularly where the water table is shallow, may result in groundwater contamination.

This chemical can contaminate surface water through spray drift. Under some conditions, it may also have a high potential for runoff into surface water for several days to weeks after application. These include poorly draining or wet soils with readily visible slopes toward adjacent surface waters, frequently flooded areas, areas over-laying extremely shallow ground water, areas with

infield canals or ditches that drain to surface water, areas not separated from adjacent surface waters with vegetated filter strips, and areas over-laying tile drainage systems that drain to surface water.

Bravo Weather Stik® is a trademark of ADAMA

24(c) Registrant:
Makhteshim Agan of North America, Inc. d/b/a
ADAMA
3120 Highwoods Blvd., Suite 100
Raleigh, NC 27604



11282018