

Report No. RC-1633

Report Title:

**A Manual for the
Design of Temporary Earth Retention
Systems (TERS)
for the Michigan Dept. of Transportation**

**Center for Structural Durability at
Michigan Tech – a MDOT Center of
Excellence**

FINAL REPORT

Part 2 of 2

Sponsoring Organization:

Michigan Department of Transportation

Research Agency:

Michigan Technological University
1400 Townsend Drive
Houghton, MI 49931

Principal Investigator(s):

Theresa (Tess) M Ahlborn, PhD, P.E.,
FACI, FPCI
Professor
Civil & Environmental Engineering
Director, Center for Structural Durability

R. Andrew Swartz, PhD, P.E.
Associate Professor
Civil & Environmental Engineering

Stanley J. Vitton, PhD, P.E.
Professor
Civil & Environmental Engineering

Date Submitted:

April 22, 2019



Michigan Tech

Engineering Manual Preamble

This manual provides guidance to administrative, engineering, and technical staff. Engineering practice requires that professionals use a combination of technical skills and judgment in decision making. Engineering judgment is necessary to allow decisions to account for unique site-specific conditions and considerations to provide high-quality products, within budget, and to protect the public health, safety, and welfare. This manual provides the general operational guidelines; however, it is understood that adaptation, adjustments, and deviations are sometimes necessary. Innovation is a key foundational element to advance the state of engineering practice and develop more effective and efficient engineering solutions and materials. As such, it is essential that our engineering manuals provide a vehicle to promote, pilot, or implement technologies or practices that provide efficiencies and quality products, while maintaining the safety, health, and welfare of the public. When making significant or impactful deviations from the technical information from these guidance materials, it is expected that reasonable consultations with experts, technical committees, and/or policy setting bodies occur prior to actions within the time frames allowed. It is also expected that these consultations will eliminate any potential conflicts of interest, perceived or otherwise. Michigan Department of Transportation Leadership is committed to a culture of innovation to optimize engineering solutions.

The National Society of Professional Engineers Code of Ethics for Engineering is founded on six fundamental canons. Those canons are provided below.

Engineers, in the fulfillment of their professional duties, shall:

1. Hold paramount the safety, health, and welfare of the public.
2. Perform Services only in areas of their competence.
3. Issue public statement only in an objective and truthful manner.
4. Act for each employer or client as faithful agents or trustees.
5. Avoid deceptive acts.
6. Conduct themselves honorably, reasonably, ethically, and lawfully so as to enhance the honor, reputation, and usefulness of the profession.

Inquiries concerning the information presented in this manual may be directed to:

MDOT Geotechnical Services Section
P.O. Box 30049
Lansing, Michigan 48909
(517) 636-5453

1. Report No. RC-1633	2. Government Accession No. N/A	3. MDOT Project Manager Steve Kahl	
4. Title and Subtitle <i>A Manual for the Design of Temporary Earth Retention Systems (TERS) for the Michigan Department of Transportation</i>		5. Report Date April 22, 2019	
		6. Performing Organization Code N/A	
7. Author(s) Theresa (Tess) M. Ahlborn, R. Andrew Swartz, Stanley J. Vitton		8. Performing Org. Report No. N/A	
9. Performing Organization Name and Address Michigan Technological University 1400 Townsend Drive Houghton, Michigan 49931		10. Work Unit No. (TRAIS) N/A	
		11. Contract No. 2013-0067 Z8	
		11(a). Authorization No. Z5	
12. Sponsoring Agency Name and Address Michigan Department of Transportation Office of Research and Best Practices 425 West Ottawa Street Lansing MI 48933		13. Type of Report & Period Covered FINAL Report: 10/1/2013 – 09/30/2018	
		14. Sponsoring Agency Code N/A	
15. Supplementary Notes: None			
16. Abstract The purpose of this manual is to provide basic guidance on the design of temporary earth retaining systems (TERS) used on Michigan Department of Transportation (MDOT) projects. Temporary works are designed as short-term systems during construction and are either removed after construction or, in some cases, left in place. MDOT must approve all TERS with a design height of six feet or greater before construction. This manual covers the basic design elements for a TERS by providing nine detailed design examples. The structural steel design of typical internal bracing of TERS is provided in the manual's final chapter.			
17. Key Words sheet pile, temporary construction, earth retention, soldier pile, cofferdams		18. Distribution Statement No restrictions. This document is available to the public through the Michigan Department of Transportation.	
19. Security Classification - report Unclassified	20. Security Classification – page Unclassified	21. No. of Pages 430	22. Price N/A

Disclaimer

This publication is disseminated in the interest of information exchange. The Michigan Department of Transportation (hereinafter referred to as MDOT) expressly disclaims any liability, of any kind, or for any reason that might otherwise arise out of any use of this publication or the information or data provided in the publication. MDOT further disclaims any responsibility for typographical errors or accuracy of the information provided or contained within this information. MDOT makes no warranties or representations whatsoever regarding the quality, content, completeness, suitability, adequacy, sequence, accuracy, or timeliness of the information and data provided or that the contents represent standards, specifications, or regulations.

Acknowledgments

The authors wish to thank the MDOT Research Advisory Panel for their dedication and persistence in the completion of this document. In particular, kudos to MDOT personnel Richard (Dick) Endres, Matt Chynoweth, Ryan Snook, and Tony Pietrangelo, for their detailed review of the example problems included herein, and to Steve Kahl, MDOT Project Manager, and Michael Townley, MDOT Research Manager, for their respective roles in the completion of this document.

Appendix B.1 – SupportIT Output, Case 1


Case 1 – Cantilever TERS in Cohesionless Soil with Level Backfill

Client: MDOT - Case 1 - Cantilever
 Cohesionless Soil
 Site: FOS = 1.00

Ref: Case 1
 Page: 1
 Date: 8.29.18

Sheet: PZ27
 Works: Temporary
 Pressure: Rankine
 Analysis: Gross Pressure
 Toe: Cantilever

	Maximum	d (ft)
○	483.6 psf	10.00
□	33109.1 ftlb/ft	18.13
●	1.9 in	0.00



MDOT Sheet Pile Manual



SupportIT, v2.37

© 1997 - 2015, GTSOFT Ltd.
 Tel/Fax: +44 (0)1292 477754
 Email: GTSOFT@aol.com
 Web: www.GTSOFT.org

Client: MDOT - Case 1 - Cantilever
Cohesionless Soil
Site: FOS = 1.00

Ref: Case 1
Page: 2
Date: 8.29.18

Sheet: PZ27
Works: Temporary
Pressure: Rankine
Analysis: Gross Pressure
Toe: Cantilever

Input Data

Depth Of Excavation = 10.00ft
Surcharge = 360.0psf

Depth Of Active Water = 10.00ft
Depth Of Passive Water = 10.00ft

Water Density = 62.43pcf
Minimum Fluid Density = 31.82pcf

Soil Profile

Depth (ft)	Soil Name	γ (pcf)	γ' (pcf)	C (psf)	C_a (psf)	ϕ (°)	δ (°)	K_a	K_{ac}	K_p	K_{pc}
0.00	Dense Coarse Sand	120.00	71.10	0.0	0.0	32.0	0.0	0.31	0.00	3.25	0.00

Solution

Sheet

Sheet Name	E (psi)	I (in ⁴ /ft)	f (psi)	Z (in ³ /ft)	Allowed M_{max} (ftlb/ft)	b (in)	A (in ² /ft)	W (lb/ft)	Upstand (ft)	Toe (ft)	Length (ft)
PZ27	3.04E+07	187.50	24966.8	31.00	64497.5	17.99	7.93	40.5	0.00	17.30	27.30

Maxima

	Maximum	Depth (ft)
Pressure	483.6 psf	10.00
Bending Moment	33109.1 ftlb/ft	18.13
Deflection	1.9 in	0.00
Shear Force	3527.0 lb/ft	12.28



MDOT Sheet Pile Manual

Client: MDOT - Case 1 - Cantilever
Cohesionless Soil

Site: FOS = 1.00

Ref: Case 1

Page: 3

Date: 8.29.18

Sheet: PZ27





Works: Temporary

Pressure: Rankine

Analysis: Gross Pressure

Toe: Cantilever

	Maximum	d (ft)
○	483.6 psf	10.00
□	33109.1 ftlb/ft	18.13
◇	3527.0 lb/ft	12.28
●	1.9 in	0.00



MDOT Sheet Pile Manual



Client: MDOT - Case 1 - Cantilever
 Cohesionless Soil
 Site: FOS = 1.00

Ref: Case 1
 Page: 4
 Date: 8.29.18

Sheet: PZ27
 Works: Temporary
 Pressure: Rankine
 Analysis: Gross Pressure
 Toe: Cantilever

depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)	depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)	depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)
0.00	111.6	0.0	1.9	0.0	9.16	452.6	9435.6	0.9	2591.8	18.33	-1260.9	33065.4	0.1	-191.0
0.19	119.2	2.1	1.9	23.6	9.36	459.4	9912.6	0.9	2674.9	18.52	-1298.9	32946.4	0.1	-353.5
0.39	126.0	8.2	1.9	46.0	9.55	467.0	10467.4	0.8	2769.9	18.72	-1341.7	32726.4	0.1	-528.0
0.58	133.6	20.0	1.9	72.7	9.75	474.6	11041.8	0.8	2866.4	18.91	-1379.7	32457.7	0.1	-675.8
0.78	140.4	35.1	1.8	97.7	9.94	481.4	11569.0	0.8	2953.6	19.11	-1422.4	32077.3	0.1	-833.8
0.97	148.0	57.8	1.8	127.4	10.14	448.7	12181.0	0.8	3049.6	19.30	-1465.1	31618.3	0.1	-983.0
1.17	154.8	83.0	1.8	155.0	10.33	410.7	12740.8	0.7	3127.4	19.50	-1503.1	31147.9	0.1	-1108.4
1.36	162.4	117.6	1.8	187.6	10.53	368.0	13386.7	0.7	3206.7	19.69	-1545.9	30552.8	0.1	-1241.1
1.56	170.0	159.0	1.7	221.7	10.72	330.0	13973.9	0.7	3269.8	19.89	-1583.9	29968.5	0.1	-1351.7
1.75	176.8	201.7	1.7	253.4	10.92	287.2	14647.4	0.7	3332.5	20.08	-1626.6	29253.1	0.1	-1467.9
1.95	184.4	256.8	1.7	290.4	11.11	244.5	15333.0	0.7	3386.5	20.28	-1664.6	28569.1	0.0	-1563.8
2.14	191.1	312.2	1.7	324.7	11.31	206.5	15951.0	0.6	3427.1	20.47	-1707.3	27749.3	0.0	-1663.5
2.34	198.8	382.2	1.7	364.7	11.50	163.8	16654.4	0.6	3464.6	20.67	-1750.1	26880.8	0.0	-1754.4
2.53	205.5	451.3	1.6	401.6	11.70	125.8	17285.4	0.6	3490.5	20.86	-1788.1	26071.4	0.0	-1827.8
2.73	213.1	537.2	1.6	444.6	11.89	83.0	18000.2	0.6	3511.4	21.06	-1830.8	25122.9	0.0	-1902.2
2.92	220.8	632.0	1.6	489.1	12.09	45.0	18638.6	0.6	3522.7	21.25	-1868.8	24249.5	0.0	-1961.0
3.12	227.5	724.0	1.6	530.0	12.28	2.3	19358.4	0.6	3527.0	21.45	-1911.5	23236.9	0.0	-2018.8
3.31	235.1	836.5	1.5	577.5	12.48	-40.4	20078.5	0.5	3523.5	21.64	-1949.5	22313.5	0.0	-2062.9
3.51	241.9	944.8	1.5	621.0	12.67	-78.4	20717.3	0.5	3513.1	21.84	-1992.3	21252.7	0.0	-2104.2
3.70	249.5	1076.1	1.5	671.4	12.87	-121.2	21433.0	0.5	3493.2	22.03	-2035.0	20172.9	0.0	-2136.8
3.90	256.3	1201.6	1.5	717.6	13.06	-159.2	22065.2	0.5	3468.1	22.23	-2073.0	19200.6	0.0	-2158.4
4.09	263.9	1353.0	1.4	771.0	13.26	-201.9	22770.2	0.5	3431.6	22.42	-2115.7	18096.8	0.0	-2174.4
4.29	271.5	1515.4	1.4	825.9	13.45	-239.9	23390.0	0.4	3391.8	22.62	-2153.7	17110.4	0.0	-2181.3
4.48	278.3	1669.3	1.4	876.0	13.65	-282.6	24078.0	0.4	3338.8	22.81	-2196.5	15998.7	0.0	-2180.8
4.68	285.9	1853.4	1.4	933.9	13.84	-325.4	24754.3	0.4	3277.1	23.01	-2234.5	15012.2	0.0	-2173.1
4.87	292.7	2027.1	1.4	986.7	14.04	-363.4	25344.3	0.4	3214.9	23.20	-2272.2	13908.5	0.0	-2156.1
5.07	300.3	2234.0	1.3	1047.5	14.23	-406.1	25993.8	0.4	3136.6	23.40	-2319.9	12815.4	0.0	-2130.3
5.26	307.1	2428.5	1.3	1102.9	14.43	-444.1	26557.2	0.4	3059.6	23.59	-2357.9	11856.3	0.0	-2100.0
5.46	314.7	2659.5	1.3	1166.7	14.62	-486.8	27173.5	0.3	2964.8	23.79	-2400.7	10795.5	0.0	-2057.8
5.65	322.3	2903.7	1.3	1232.0	14.82	-524.8	27704.5	0.3	2873.2	23.98	-2438.7	9872.2	0.0	-2012.8
5.85	329.1	3132.0	1.2	1291.4	15.01	-567.6	28281.2	0.3	2761.9	24.18	-2481.4	8859.6	0.0	-1954.0
6.04	336.7	3401.9	1.2	1359.7	15.21	-610.3	28834.4	0.3	2641.8	24.37	-2519.4	7986.1	0.0	-1894.4
6.24	343.5	3653.6	1.2	1421.7	15.40	-648.3	29305.0	0.3	2527.7	24.57	-2562.1	7037.6	0.0	-1819.0
6.43	351.1	3950.3	1.2	1492.9	15.60	-691.0	29808.9	0.3	2391.1	24.76	-2604.9	6129.5	0.0	-1734.9
6.63	357.8	4226.4	1.2	1557.6	15.79	-729.0	30232.8	0.3	2262.3	24.96	-2642.9	5359.7	0.0	-1652.8
6.82	365.5	4551.2	1.1	1631.7	15.99	-771.8	30681.0	0.2	2109.2	25.15	-2685.6	4540.0	0.0	-1552.2
7.02	373.1	4891.2	1.1	1707.5	16.18	-809.8	31052.5	0.2	1965.7	25.35	-2723.6	3855.9	0.0	-1455.4
7.21	379.8	5206.6	1.1	1776.1	16.38	-852.5	31438.7	0.2	1796.0	25.54	-2766.4	3140.5	0.0	-1338.2
7.41	387.5	5576.4	1.1	1854.8	16.57	-895.3	31789.4	0.2	1617.6	25.74	-2804.3	2556.3	0.0	-1226.8
7.60	394.2	5918.7	1.0	1926.1	16.77	-933.2	32069.9	0.2	1451.7	25.93	-2847.1	1961.1	0.0	-1093.1
7.80	401.8	6319.4	1.0	2007.7	16.96	-976.0	32348.8	0.2	1256.7	26.13	-2889.8	1436.1	0.0	-950.6
7.99	408.6	6689.6	1.0	2081.6	17.16	-1014.0	32562.7	0.2	1076.1	26.32	-2927.8	1031.8	0.0	-816.7
8.19	416.2	7122.3	1.0	2166.1	17.35	-1056.7	32763.4	0.2	864.6	26.52	-2970.6	651.3	0.0	-657.7
8.38	423.8	7572.5	1.0	2252.3	17.55	-1094.7	32904.9	0.2	669.3	26.71	-3008.5	382.6	0.0	-509.1
8.58	430.6	7987.4	0.9	2330.2	17.74	-1137.5	33021.0	0.1	441.3	26.91	-3051.3	162.6	0.0	-333.6
8.77	438.2	8471.3	0.9	2419.3	17.94	-1180.2	33089.8	0.1	204.5	27.10	-3089.3	43.6	0.0	-170.3
8.97	445.0	8916.8	0.9	2499.8	18.13	-1218.2	33109.1	0.1	0.0	27.30	-3127.3	0.0	0.0	0.0








MDOT Sheet Pile Manual

SupportIT, v2.37

© 1997 - 2015, GTSoft Ltd.
 Tel/Fax: +44 (0)1292 477754
 Email: GTSoftLtd@aol.com
 Web: www.GTSoft.org

Client: MDOT - Case 1 - Cantilever
 Cohesionless Soil
 Site: FOS = 1.00
 Ref: Case 1
 Page: 5
 Date: 8.29.18
 Sheet: PZ27
 Works: Temporary
 Pressure: Rankine
 Analysis: Gross Pressure
 Toe: Cantilever



MDOT Sheet Pile Manual

Client: MDOT - Case 1 - Cantilever
Cohesionless Soil

Site: FOS = 1.00

Ref: Case 1

Page: 6

Date: 8.29.18

Sheet: PZ27

Works: Temporary

Pressure: Rankine

Analysis: Gross Pressure

Toe: Cantilever



B



L



MDOT Sheet Pile Manual

SupportIT, v2.37



© 1997 - 2015, GTSOFT Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSOFT@aol.com
Web: www.GTSOFT.org

Client: MDOT - Case 1 - Cantilever
Cohesionless Soil

Site: FOS = 1.00

Ref: Case 1

Page: 7

Date: 8.29.18

Sheet: PZ27

Works: Temporary

Pressure: Rankine

Analysis: Gross Pressure

Toe: Cantilever

Design Report

1. Maximum bending moment = 33109.1ftlb/ft and $f = 24966.8\text{psi}$. MINIMUM required sheet section modulus is: $Z = 15.91\text{in}^3/\text{ft}$ ($= M/f$). Sheet section modulus in this design is $Z = 31.00\text{in}^3/\text{ft}$, and is satisfactory.
2. FOS = 1.00 (Gross Pressure)
This is the factor of safety against rotation about the toe.
The FOS can be changed using 'Defined FOS' or 'Manual' in the 'Wall' page.




MDOT Sheet Pile Manual

Client: MDOT - Case 1 - Cantilever
 Cohesionless Soil
 Site: FOS = 1.50

Ref: Case 1
 Page: 1
 Date: 8.29.18

Sheet: PZ27
 Works: Temporary
 Pressure: Rankine
 Analysis: Gross Pressure
 Toe: Cantilever

	Maximum	d (ft)
○	483.6 psf	10.00
□	33093.6 ftlb/ft	18.11
●	1.9 in	0.00



MDOT Sheet Pile Manual

SupportIT, v2.37

© 1997 - 2015, GTSOFT Ltd.
 Tel/Fax: +44 (0)1292 477754
 Email: GTSOFT@aol.com
 Web: www.GTSOFT.org

Client: MDOT - Case 1 - Cantilever
Cohesionless Soil
Site: FOS = 1.50

Ref: Case 1
Page: 2
Date: 8.29.18

Sheet: PZ27
Works: Temporary
Pressure: Rankine
Analysis: Gross Pressure
Toe: Cantilever

Input Data

Depth Of Excavation = 10.00ft
Surcharge = 360.0psf

Depth Of Active Water = 10.00ft
Depth Of Passive Water = 10.00ft

Water Density = 62.43pcf
Minimum Fluid Density = 31.82pcf

Soil Profile

Depth (ft)	Soil Name	γ (pcf)	γ' (pcf)	C (psf)	C_a (psf)	ϕ (°)	δ (°)	K_a	K_{ac}	K_p	K_{pc}
0.00	Dense Coarse Sand	120.00	71.10	0.0	0.0	32.0	0.0	0.31	0.00	3.25	0.00

Solution

Sheet

Sheet Name	E (psi)	I (in ⁴ /ft)	f (psi)	Z (in ³ /ft)	Allowed M_{max} (ftlb/ft)	b (in)	A (in ² /ft)	W (lb/ft)	Upstand (ft)	Toe (ft)	Length (ft)
PZ27	3.04E+07	187.50	24966.8	31.00	64497.5	17.99	7.93	40.5	0.00	26.16	36.16

Maxima

	Maximum	Depth (ft)
Pressure	483.6 psf	10.00
Bending Moment	33093.6 ftlb/ft	18.11
Deflection	1.9 in	0.00
Shear Force	3526.6 lb/ft	12.26



MDOT Sheet Pile Manual

SupportIT, v2.37

© 1997 - 2015, GTSoft Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSoftLtd@aol.com
Web: www.GTSoft.org

Client: MDOT - Case 1 - Cantilever
Cohesionless Soil

Site: FOS = 1.50

Ref: Case 1

Page: 3

Date: 8.29.18

Sheet: PZ27





Works: Temporary

Pressure: Rankine

Analysis: Gross Pressure

Toe: Cantilever

	Maximum	d (ft)
○	483.6 psf	10.00
□	33093.6 ftlb/ft	18.11
◇	3526.6 lb/ft	12.26
●	1.9 in	0.00



MDOT Sheet Pile Manual



Client: MDOT - Case 1 - Cantilever
 Cohesionless Soil
 Site: FOS = 1.50

Ref: Case 1
 Page: 4
 Date: 8.29.18

Sheet: PZ27
 Works: Temporary
 Pressure: Rankine
 Analysis: Gross Pressure
 Toe: Cantilever

depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)	depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)	depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)
0.00	111.6	0.0	1.9	0.0	12.14	31.3	18844.9	0.6	3524.7	24.28	-2504.6	8411.4	0.0	-1943.4
0.26	121.7	3.7	1.9	31.6	12.40	-19.0	19692.0	0.5	3526.0	24.53	-2555.0	7285.2	0.0	-1857.7
0.52	130.7	14.5	1.9	62.2	12.65	-75.6	20643.8	0.5	3514.1	24.79	-2611.6	6082.9	0.0	-1746.8
0.77	140.7	35.7	1.8	99.2	12.91	-132.3	21590.6	0.5	3486.7	25.05	-2661.9	5079.5	0.0	-1635.3
1.03	149.7	63.2	1.8	134.4	13.17	-182.6	22424.5	0.5	3449.5	25.31	-2718.6	4033.4	0.0	-1495.4
1.29	159.8	104.5	1.8	176.5	13.43	-239.2	23350.3	0.4	3393.2	25.57	-2775.2	3084.9	0.0	-1340.1
1.55	168.8	151.1	1.7	216.3	13.69	-289.6	24159.1	0.4	3330.2	25.83	-2825.5	2331.9	0.0	-1189.2
1.81	178.9	215.1	1.7	263.6	13.95	-346.2	25049.2	0.4	3244.9	26.08	-2882.2	1595.4	0.0	-1004.9
2.07	188.9	292.3	1.7	313.7	14.20	-396.6	25819.6	0.4	3156.1	26.34	-2932.5	1047.0	0.0	-828.2
2.32	197.9	372.6	1.7	360.5	14.46	-452.2	26659.2	0.4	3041.7	26.60	-2989.1	558.9	0.0	-614.9
2.58	208.0	476.6	1.6	415.7	14.72	-509.8	27466.0	0.3	2912.0	26.86	-3039.5	247.5	0.0	-412.4
2.84	217.0	581.8	1.6	467.1	14.98	-560.2	28152.3	0.3	2783.8	27.12	-3096.1	44.2	0.0	-170.1
3.10	227.0	715.3	1.6	527.6	15.24	-616.8	28885.9	0.3	2625.1	27.38	-3152.8	0.0	0.0	0.0
3.36	236.0	847.8	1.5	583.5	15.50	-667.1	29500.6	0.3	2471.1	27.63	-3203.1	0.0	0.0	0.0
3.62	246.1	1013.4	1.5	649.1	15.75	-723.8	30146.2	0.3	2283.4	27.89	-3259.7	0.0	0.0	0.0
3.87	256.2	1196.9	1.5	717.4	16.01	-774.1	30676.1	0.2	2103.6	28.15	-3310.1	0.0	0.0	0.0
4.13	265.2	1375.9	1.4	780.5	16.27	-830.8	31218.9	0.2	1886.9	28.41	-3366.7	0.0	0.0	0.0
4.39	275.2	1595.6	1.4	854.0	16.53	-887.4	31701.3	0.2	1654.8	28.67	-3417.0	0.0	0.0	0.0
4.65	284.2	1807.8	1.4	921.6	16.79	-937.7	32076.1	0.2	1435.5	28.92	-3473.7	0.0	0.0	0.0
4.91	294.3	2066.2	1.4	1000.3	17.05	-994.4	32433.0	0.2	1174.4	29.18	-3530.3	0.0	0.0	0.0
5.17	303.3	2314.1	1.3	1072.5	17.30	-1044.7	32689.6	0.2	929.4	29.44	-3580.7	0.0	0.0	0.0
5.42	313.4	2613.9	1.3	1156.3	17.56	-1101.3	32906.3	0.2	639.3	29.70	-3637.3	0.0	0.0	0.0
5.68	323.4	2936.8	1.3	1242.9	17.82	-1151.7	33031.7	0.1	368.5	29.96	-3687.6	0.0	0.0	0.0
5.94	332.4	3243.6	1.2	1322.1	18.08	-1208.3	33092.1	0.1	49.4	30.22	-3744.3	0.0	0.0	0.0
6.20	342.5	3611.9	1.2	1413.9	18.34	-1265.0	33034.8	0.1	-225.2	30.47	-3794.6	0.0	0.0	0.0
6.46	351.5	3960.3	1.2	1497.7	18.59	-1315.3	32846.2	0.1	-438.4	30.73	-3851.2	0.0	0.0	0.0
6.71	361.5	4376.7	1.1	1594.7	18.85	-1371.9	32487.6	0.1	-663.6	30.99	-3907.9	0.0	0.0	0.0
6.97	370.5	4769.0	1.1	1683.1	19.11	-1422.3	32046.7	0.1	-850.9	31.25	-3958.2	0.0	0.0	0.0
7.23	380.6	5236.1	1.1	1785.2	19.37	-1478.9	31422.5	0.1	-1047.2	31.51	-4014.9	0.0	0.0	0.0
7.49	390.7	5731.1	1.1	1890.0	19.63	-1529.2	30761.8	0.1	-1208.7	31.77	-4065.2	0.0	0.0	0.0
7.75	399.7	6195.1	1.0	1985.5	19.89	-1585.9	29908.5	0.1	-1375.9	32.02	-4121.8	0.0	0.0	0.0
8.01	409.7	6744.9	1.0	2095.5	20.14	-1642.5	28948.6	0.1	-1527.8	32.28	-4172.2	0.0	0.0	0.0
8.26	418.7	7258.7	1.0	2195.6	20.40	-1692.9	28014.2	0.0	-1649.9	32.54	-4228.8	0.0	0.0	0.0
8.52	428.8	7865.9	0.9	2310.8	20.66	-1749.5	26880.9	0.0	-1772.8	32.80	-4285.4	0.0	0.0	0.0
8.78	437.8	8432.0	0.9	2415.4	20.92	-1799.8	25808.4	0.0	-1869.1	33.06	-4335.8	0.0	0.0	0.0
9.04	447.9	9099.1	0.9	2535.8	21.18	-1856.5	24538.0	0.0	-1962.9	33.32	-4392.4	0.0	0.0	0.0
9.30	457.9	9799.2	0.9	2658.9	21.44	-1906.8	23359.9	0.0	-2033.5	33.57	-4442.8	0.0	0.0	0.0
9.56	466.9	10449.6	0.8	2770.6	21.69	-1963.4	21988.9	0.0	-2098.3	33.83	-4499.4	0.0	0.0	0.0
9.81	477.0	11213.7	0.8	2898.8	21.95	-2020.1	20579.3	0.0	-2147.8	34.09	-4549.7	0.0	0.0	0.0
10.07	471.8	11922.3	0.8	3014.3	22.21	-2070.4	19302.3	0.0	-2178.9	34.35	-4606.4	0.0	0.0	0.0
10.33	408.9	12751.4	0.7	3132.1	22.47	-2127.0	17847.7	0.0	-2199.4	34.61	-4663.0	0.0	0.0	0.0
10.59	358.6	13513.7	0.7	3223.9	22.73	-2177.4	16546.8	0.0	-2204.7	34.86	-4713.3	0.0	0.0	0.0
10.85	301.9	14396.0	0.7	3312.7	22.99	-2234.0	15083.7	0.0	-2196.1	35.12	-4770.0	0.0	0.0	0.0
11.11	245.3	15300.4	0.7	3386.1	23.24	-2284.4	13791.4	0.0	-2175.7	35.38	-4820.3	0.0	0.0	0.0
11.36	195.0	16119.6	0.6	3438.5	23.50	-2341.0	12356.1	0.0	-2138.1	35.64	-4877.0	0.0	0.0	0.0
11.62	138.3	17054.6	0.6	3482.9	23.76	-2397.6	10950.3	0.0	-2085.2	35.90	-4927.3	0.0	0.0	0.0
11.88	88.0	17894.3	0.6	3509.4	24.02	-2448.0	9733.7	0.0	-2025.3	36.16	-4977.6	0.0	0.0	0.0








MDOT Sheet Pile Manual

Client: MDOT - Case 1 - Cantilever
 Cohesionless Soil
 Site: FOS = 1.50

Ref: Case 1
 Page: 5
 Date: 8.29.18

Sheet: PZ27
 Works: Temporary
 Pressure: Rankine
 Analysis: Gross Pressure
 Toe: Cantilever



MDOT Sheet Pile Manual

SupportIT, v2.37

© 1997 - 2015, GTSOFT Ltd.
 Tel/Fax: +44 (0)1292 477754
 Email: GTSOFT@aol.com
 Web: www.GTSOFT.org

Client: MDOT - Case 1 - Cantilever
Cohesionless Soil

Site: FOS = 1.50

Ref: Case 1

Page: 6

Date: 8.29.18

Sheet: PZ27

Works: Temporary

Pressure: Rankine

Analysis: Gross Pressure

Toe: Cantilever



B



L



MDOT Sheet Pile Manual

SupportIT, v2.37

© 1997 - 2015, GTSoft Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSoftLtd@aol.com
Web: www.GTSoft.org

Client: MDOT - Case 1 - Cantilever
Cohesionless Soil

Site: FOS = 1.50

Ref: Case 1

Page: 7

Date: 8.29.18

Sheet: PZ27

Works: Temporary

Pressure: Rankine

Analysis: Gross Pressure

Toe: Cantilever

Design Report

1. Maximum bending moment = 33093.6ftlb/ft and $f = 24966.8\text{psi}$. MINIMUM required sheet section modulus is: $Z = 15.91\text{in}^3/\text{ft}$ ($= M/f$).
Sheet section modulus in this design is $Z = 31.00\text{in}^3/\text{ft}$, and is satisfactory.
2. FOS = 1.50 (Gross Pressure)
This is the factor of safety against rotation about the toe.
The FOS can be changed using 'Defined FOS' or 'Manual' in the 'Wall' page.




MDOT Sheet Pile Manual

Client: MDOT - Case 1 - Cantilever
 Cohesionless Soil
 Site: FOS = 1.50 with 10 Friction

Ref: Case 1
 Page: 1
 Date: 8.30.18

Sheet: PZ27
 Works: Temporary
 Pressure: Rankine
 Analysis: Gross Pressure
 Toe: Cantilever

	Maximum	d (ft)
○	436.8 psf	10.00
□	24631.2 ftlb/ft	16.24
●	1.1 in	0.00



MDOT Sheet Pile Manual

SupportIT, v2.37

© 1997 - 2015, GTSOFT Ltd.
 Tel/Fax: +44 (0)1292 477754
 Email: GTSOFT@aol.com
 Web: www.GTSOFT.org

Client: MDOT - Case 1 - Cantilever
 Cohesionless Soil
 Site: FOS = 1.50 with 10 Friction

Ref: Case 1
 Page: 2
 Date: 8.30.18

Sheet: PZ27
 Works: Temporary
 Pressure: Rankine
 Analysis: Gross Pressure
 Toe: Cantilever

Input Data

Depth Of Excavation = 10.00ft
 Surcharge = 360.0psf

Depth Of Active Water = 10.00ft
 Depth Of Passive Water = 10.00ft

Water Density = 62.43pcf
 Minimum Fluid Density = 31.82pcf

Soil Profile

Depth (ft)	Soil Name	γ (pcf)	γ' (pcf)	C (psf)	C_a (psf)	ϕ (°)	δ (°)	K_a	K_{ac}	K_p	K_{pc}
0.00	Dense Coarse Sand	120.00	71.10	0.0	0.0	32.0	10.0	0.28	0.00	4.20	0.00

Solution

Sheet

Sheet Name	E (psi)	I (in ⁴ /ft)	f (psi)	Z (in ³ /ft)	Allowed M _{max} (ftlb/ft)	b (in)	A (in ² /ft)	W (lb/ft)	Upstand (ft)	Toe (ft)	Length (ft)
PZ27	3.04E+07	187.50	24966.8	31.00	64497.5	17.99	7.93	40.5	0.00	19.27	29.27

Maxima

	Maximum	Depth (ft)
Pressure	436.8 psf	10.00
Bending Moment	24631.2 ftlb/ft	16.24
Deflection	1.1 in	0.00
Shear Force	3031.7 lb/ft	11.56







MDOT Sheet Pile Manual

Client: MDOT - Case 1 - Cantilever
 Cohesionless Soil
 Site: FOS = 1.50 with 10 Friction

Ref: Case 1
 Page: 3
 Date: 8.30.18

Sheet: PZ27
 Works: Temporary
 Pressure: Rankine
 Analysis: Gross Pressure
 Toe: Cantilever

	Maximum	d (ft)
○	436.8 psf	10.00
□	24631.2 ftlb/ft	16.24
◇	3031.7 lb/ft	11.56
●	1.1 in	0.00



MDOT Sheet Pile Manual

SupportIT, v2.37

© 1997 - 2015, GTSOFT Ltd.
 Tel/Fax: +44 (0)1292 477754
 Email: GTSOFT@aol.com
 Web: www.GTSOFT.org

Client: MDOT - Case 1 - Cantilever
 Cohesionless Soil
 Site: FOS = 1.50 with 10 Friction

Ref: Case 1
 Page: 4
 Date: 8.30.18

Sheet: PZ27
 Works: Temporary
 Pressure: Rankine
 Analysis: Gross Pressure
 Toe: Cantilever

depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)	depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)	depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)
0.00	100.8	0.0	1.1	0.0	9.82	431.0	10148.8	0.4	2619.6	19.65	-2254.6	14103.5	0.0	-1961.1
0.21	108.2	2.2	1.1	22.9	10.03	436.8	10665.5	0.4	2704.4	19.86	-2309.0	13152.0	0.0	-1975.0
0.42	114.7	8.5	1.0	44.8	10.24	369.1	11266.0	0.4	2791.6	20.07	-2370.2	12076.5	0.0	-1978.0
0.63	122.1	20.8	1.0	70.9	10.45	307.9	11884.2	0.3	2865.3	20.28	-2424.6	11121.5	0.0	-1969.4
0.84	128.7	36.7	1.0	95.5	10.66	253.5	12446.3	0.3	2919.4	20.49	-2485.7	10055.2	0.0	-1947.0
1.05	136.0	60.4	1.0	124.6	10.87	192.4	13090.1	0.3	2967.6	20.69	-2546.9	9004.3	0.0	-1911.2
1.25	142.6	86.9	1.0	151.9	11.08	138.0	13670.1	0.3	2999.2	20.90	-2601.3	8088.9	0.0	-1868.1
1.46	150.0	123.2	1.0	184.1	11.29	76.8	14328.9	0.3	3022.1	21.11	-2662.5	7087.1	0.0	-1806.9
1.67	157.3	166.8	1.0	218.0	11.50	22.4	14917.6	0.3	3031.1	21.32	-2716.9	6226.9	0.0	-1741.3
1.88	163.9	211.8	0.9	249.4	11.71	-38.8	15580.9	0.3	3029.4	21.53	-2778.0	5300.2	0.0	-1654.7
2.09	171.3	270.0	0.9	286.3	11.92	-99.9	16242.6	0.2	3014.9	21.74	-2832.4	4518.4	0.0	-1566.5
2.30	177.8	328.5	0.9	320.5	12.12	-154.3	16827.1	0.2	2990.8	21.95	-2893.6	3692.8	0.0	-1454.6
2.51	185.2	402.5	0.9	360.4	12.33	-215.5	17477.9	0.2	2950.9	22.16	-2954.8	2931.3	0.0	-1329.3
2.72	191.8	475.8	0.9	397.3	12.54	-269.9	18048.1	0.2	2904.2	22.37	-3009.1	2314.1	0.0	-1206.6
2.93	199.1	566.8	0.9	440.3	12.75	-331.0	18677.5	0.2	2839.1	22.58	-3070.3	1693.6	0.0	-1056.0
3.14	206.5	667.5	0.8	485.0	12.96	-385.4	19223.9	0.2	2769.8	22.79	-3124.7	1213.4	0.0	-910.7
3.34	213.1	765.3	0.8	526.0	13.17	-446.6	19821.5	0.2	2679.3	22.99	-3185.9	760.0	0.0	-734.7
3.55	220.4	885.0	0.8	573.7	13.38	-507.8	20397.8	0.2	2575.3	23.20	-3240.2	439.8	0.0	-566.9
3.76	227.0	1000.3	0.8	617.5	13.59	-562.1	20890.1	0.2	2471.6	23.41	-3301.4	179.5	0.0	-365.5
3.97	234.4	1140.3	0.8	668.2	13.80	-623.3	21418.6	0.2	2342.2	23.62	-3362.6	32.0	0.0	-150.7
4.18	240.9	1274.3	0.8	714.7	14.01	-677.7	21863.6	0.1	2216.0	23.83	-3417.0	0.0	0.0	0.0
4.39	248.3	1435.9	0.8	768.6	14.21	-738.9	22333.6	0.1	2061.2	24.04	-3478.1	0.0	0.0	0.0
4.60	255.7	1609.4	0.7	824.0	14.42	-793.2	22722.1	0.1	1912.4	24.25	-3532.5	0.0	0.0	0.0
4.81	262.2	1773.9	0.7	874.6	14.63	-854.4	23123.3	0.1	1732.4	24.46	-3593.7	0.0	0.0	0.0
5.02	269.6	1971.0	0.7	933.1	14.84	-915.6	23483.7	0.1	1538.9	24.67	-3648.1	0.0	0.0	0.0
5.23	276.2	2157.0	0.7	986.5	15.05	-970.0	23767.6	0.1	1355.6	24.88	-3709.2	0.0	0.0	0.0
5.44	283.5	2378.8	0.7	1048.1	15.26	-1031.1	24043.2	0.1	1136.7	25.08	-3770.4	0.0	0.0	0.0
5.64	290.1	2587.4	0.7	1104.2	15.47	-1085.5	24247.0	0.1	930.9	25.29	-3824.8	0.0	0.0	0.0
5.85	297.5	2835.3	0.7	1168.8	15.68	-1146.7	24427.1	0.1	686.7	25.50	-3886.0	0.0	0.0	0.0
6.06	304.8	3097.5	0.6	1235.0	15.89	-1201.1	24541.4	0.1	458.3	25.71	-3940.4	0.0	0.0	0.0
6.27	311.4	3342.8	0.6	1295.3	16.10	-1262.2	24615.7	0.1	188.7	25.92	-4001.5	0.0	0.0	0.0
6.48	318.8	3632.9	0.6	1364.6	16.31	-1323.4	24626.6	0.1	-76.1	26.13	-4055.9	0.0	0.0	0.0
6.69	325.3	3903.7	0.6	1427.5	16.51	-1377.8	24548.0	0.1	-271.7	26.34	-4117.1	0.0	0.0	0.0
6.90	332.7	4223.0	0.6	1499.9	16.72	-1439.0	24349.5	0.1	-479.1	26.55	-4178.3	0.0	0.0	0.0
7.11	339.3	4520.3	0.6	1565.6	16.93	-1493.4	24080.8	0.0	-652.1	26.76	-4232.6	0.0	0.0	0.0
7.32	346.6	4870.2	0.5	1641.0	17.14	-1554.5	23681.5	0.0	-834.2	26.97	-4293.8	0.0	0.0	0.0
7.53	354.0	5236.8	0.5	1718.1	17.35	-1608.9	23245.9	0.0	-984.7	27.18	-4348.2	0.0	0.0	0.0
7.73	360.6	5576.9	0.5	1787.9	17.56	-1670.1	22671.9	0.0	-1141.3	27.38	-4409.4	0.0	0.0	0.0
7.94	367.9	5975.8	0.5	1868.0	17.77	-1731.3	22015.9	0.0	-1284.6	27.59	-4463.7	0.0	0.0	0.0
8.15	374.5	6345.3	0.5	1940.6	17.98	-1785.6	21369.9	0.0	-1400.6	27.80	-4524.9	0.0	0.0	0.0
8.36	381.9	6778.0	0.5	2023.7	18.19	-1846.8	20579.0	0.0	-1518.5	28.01	-4586.1	0.0	0.0	0.0
8.57	388.4	7178.0	0.5	2099.0	18.40	-1901.2	19824.6	0.0	-1612.0	28.22	-4640.5	0.0	0.0	0.0
8.78	395.8	7645.7	0.4	2185.2	18.60	-1962.4	18924.9	0.0	-1704.5	28.43	-4701.6	0.0	0.0	0.0
8.99	403.2	8132.3	0.4	2273.1	18.81	-2016.7	18085.4	0.0	-1775.4	28.64	-4756.0	0.0	0.0	0.0
9.20	409.7	8581.2	0.4	2352.5	19.02	-2077.9	17102.9	0.0	-1842.5	28.85	-4817.2	0.0	0.0	0.0
9.41	417.1	9104.8	0.4	2443.4	19.23	-2139.1	16087.1	0.0	-1896.3	29.06	-4871.6	0.0	0.0	0.0
9.62	423.7	9587.0	0.4	2525.6	19.44	-2193.5	15162.2	0.0	-1932.7	29.27	-4925.9	0.0	0.0	0.0



MDOT Sheet Pile Manual






SupportIT, v2.37

© 1997 - 2015, GTSoft Ltd.
 Tel/Fax: +44 (0)1292 477754
 Email: GTSoftLtd@aol.com
 Web: www.GTSoft.org

Client: MDOT - Case 1 - Cantilever
Cohesionless Soil
Site: FOS = 1.50 with 10 Friction

Ref: Case 1
Page: 5
Date: 8.30.18

Sheet: PZ27
Works: Temporary
Pressure: Rankine
Analysis: Gross Pressure
Toe: Cantilever



MDOT Sheet Pile Manual

SupportIT, v2.37

© 1997 - 2015, GTSOFT Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSOFT@aol.com
Web: www.GTSOFT.org

Client: MDOT - Case 1 - Cantilever
Cohesionless Soil
Site: FOS = 1.50 with 10 Friction

Ref: Case 1
Page: 6
Date: 8.30.18

Sheet: PZ27
Works: Temporary
Pressure: Rankine
Analysis: Gross Pressure
Toe: Cantilever



B



L



MDOT Sheet Pile Manual

SupportIT, v2.37

© 1997 - 2015, GTSOFT Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSOFT@aol.com
Web: www.GTSOFT.org

Client: MDOT - Case 1 - Cantilever
Cohesionless Soil

Site: FOS = 1.50 with 10 Friction

Ref: Case 1

Page: 7

Date: 8.30.18

Sheet: PZ27

Works: Temporary

Pressure: Rankine

Analysis: Gross Pressure

Toe: Cantilever

Design Report

1. Maximum bending moment = 24631.2ftlb/ft and $f = 24966.8\text{psi}$. MINIMUM required sheet section modulus is: $Z = 11.84\text{in}^3/\text{ft}$ ($= M/f$).
Sheet section modulus in this design is $Z = 31.00\text{in}^3/\text{ft}$, and is satisfactory.
2. FOS = 1.49 (Gross Pressure)
This is the factor of safety against rotation about the toe.
The FOS can be changed using 'Defined FOS' or 'Manual' in the 'Wall' page.



MDOT Sheet Pile Manual

SupportIT, v2.37

© 1997 - 2015, GTSOFT Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSOFT@aol.com
Web: www.GTSOFT.org

Appendix B.2 – SupportIT Output, Case 2

Case 2 – Cantilever TERS in Cohesionless Soil with Sloped Backfill

Client: Case 2: Cantilever with Sloped Backfill

Site: FOS = 1.00

Title: MDOT - Case 2 Sloped Backfill

Page: 1

Date: 4.27.20

Sheet: PZ35


Works: Temporary

Pressure: Coulomb

Analysis: Gross Pressure

Toe: Cantilever

	Maximum	d (ft)
○	456.0 psf	10.00
□	18753.5 ftlb/ft	15.72
●	0.4 in	0.00



Your Company Name

SupportIT, v2.37

© 1997 - 2015, GTSOFT Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSOFT@aol.com
Web: www.GTSOFT.org

Client: Case 2: Cantilever with Sloped Backfill

Site: FOS = 1.00

Title: MDOT - Case 2 Sloped Backfill
Page: 2

Date: 4.27.20

Sheet: PZ35

Works: Temporary

Pressure: Coulomb

Analysis: Gross Pressure

Toe: Cantilever

Input Data

Depth Of Excavation = 10.00ft
Surcharge = 0.0psf
Slope (active) = 20.0degrees

Depth Of Active Water = 10.00ft
Depth Of Passive Water = 10.00ft

Water Density = 62.43pcf
Minimum Fluid Density = 31.82pcf

Soil Profile

Depth (ft)	Soil Name	γ (pcf)	γ' (pcf)	C (psf)	C_a (psf)	ϕ (°)	δ (°)	K_a	K_{ac}	K_p	K_{pc}
0.00	Dense Fine Sand	120.00	71.10	0.0	0.0	32.0	10.0	0.38	0.00	12.15	0.00

Active Side

Soil Profile

Depth (ft)	Soil Name	γ (pcf)	γ' (pcf)	C (psf)	C_a (psf)	ϕ (°)	δ (°)	K_a	K_{ac}	K_p	K_{pc}
0.00	Dense Fine Sand	120.00	71.10	0.0	0.0	32.0	10.0	0.29	0.00	4.57	0.00

Passive Side

Solution

Sheet

Sheet Name	E (psi)	I (in ⁴ /ft)	f (psi)	Z (in ³ /ft)	Allowed M_{max} (ftlb/ft)	b (in)	A (in ² /ft)	W (lb/ft)	Upstand (ft)	Toe (ft)	Length (ft)
PZ35	3.04E+07	369.40	24966.8	48.90	101739.5	22.64	10.28	66.0	0.00	12.52	22.52

Maxima

	Maximum	Depth (ft)
Pressure	456.0 psf	10.00
Bending Moment	18753.5 ftlb/ft	15.72
Deflection	0.4 in	0.00
Shear Force	2623.3 lb/ft	11.52



Your Company Name

SupportIT, v2.37

© 1997 - 2015, GTSOFT Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSOFT@aol.com
Web: www.GTSOFT.org

Client: Case 2: Cantilever with Sloped Backfill

Site: FOS = 1.00

Title: MDOT - Case 2 Sloped Backfill

Page: 3

Date: 4.27.20

Sheet: PZ35





Works: Temporary

Pressure: Coulomb

Analysis: Gross Pressure

Toe: Cantilever

	Maximum	d (ft)
○	456.0 psf	10.00
□	18753.5 ftlb/ft	15.72
◇	2623.3 lb/ft	11.52
●	0.4 in	0.00



Your Company Name

SupportIT, v2.37

© 1997 - 2015, GTSOFT Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSOFT@aol.com
Web: www.GTSOFT.org

Client: Case 2: Cantilever with Sloped Backfill
 Site: FOS = 1.00

Title: MDOT - Case 2 Sloped Backfill
 Page: 4
 Date: 4.27.20

Sheet: PZ35
 Works: Temporary
 Pressure: Coulomb
 Analysis: Gross Pressure
 Toe: Cantilever

depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)	depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)	depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)
0.00	0.0	0.6	0.4	0.0	7.56	344.8	3261.4	0.2	1300.3	15.12	-1072.5	18530.3	0.0	700.6
0.16	7.7	0.6	0.4	0.5	7.72	351.6	3460.0	0.2	1352.5	15.28	-1117.2	18624.8	0.0	536.7
0.32	14.5	0.8	0.4	2.1	7.88	359.3	3692.8	0.2	1412.5	15.44	-1167.5	18701.1	0.0	344.3
0.48	22.2	1.4	0.4	5.1	8.04	367.0	3935.9	0.2	1473.7	15.60	-1212.1	18741.1	0.0	166.1
0.64	29.1	2.4	0.3	8.9	8.20	373.9	4160.8	0.2	1529.3	15.76	-1262.4	18752.6	0.0	-37.6
0.80	36.8	4.3	0.3	14.4	8.36	381.6	4423.8	0.2	1593.0	15.92	-1312.6	18706.9	0.0	-201.7
0.96	43.6	6.8	0.3	20.4	8.52	388.4	4666.7	0.2	1650.7	16.08	-1357.3	18610.9	0.0	-340.4
1.13	51.3	10.9	0.3	28.3	8.68	396.1	4950.4	0.1	1716.9	16.24	-1407.6	18443.7	0.0	-488.4
1.29	59.0	16.3	0.3	37.6	8.85	403.0	5212.0	0.1	1776.8	16.40	-1452.2	18245.2	0.0	-612.9
1.45	65.9	22.6	0.3	46.9	9.01	410.7	5517.2	0.1	1845.4	16.57	-1502.5	17969.0	0.0	-744.9
1.61	73.6	31.3	0.3	58.6	9.17	418.4	5834.1	0.1	1915.4	16.73	-1547.2	17679.1	0.0	-855.1
1.77	80.4	40.9	0.3	70.1	9.33	425.2	6125.7	0.1	1978.6	16.89	-1597.4	17306.2	0.0	-971.1
1.93	88.1	53.8	0.3	84.2	9.49	432.9	6465.2	0.1	2051.0	17.05	-1647.7	16887.2	0.0	-1078.6
2.09	95.0	67.3	0.3	97.9	9.65	439.8	6777.4	0.1	2116.4	17.21	-1692.3	16478.9	0.0	-1167.0
2.25	102.7	85.0	0.3	114.5	9.81	447.5	7140.4	0.1	2191.3	17.37	-1742.6	15982.4	0.0	-1258.5
2.41	110.4	105.7	0.3	132.5	9.97	454.3	7473.7	0.1	2258.9	17.53	-1787.2	15510.7	0.0	-1332.6
2.57	117.2	126.7	0.3	149.5	10.13	412.7	7860.9	0.1	2333.3	17.69	-1837.5	14949.0	0.0	-1408.1
2.73	124.9	153.5	0.3	169.8	10.29	362.5	8259.9	0.1	2399.2	17.85	-1882.2	14424.9	0.0	-1468.0
2.89	131.8	180.2	0.3	189.0	10.45	317.8	8623.5	0.1	2450.7	18.01	-1932.4	13810.5	0.0	-1527.4
3.06	139.5	213.8	0.3	211.9	10.61	267.5	9041.2	0.1	2500.6	18.17	-1982.7	13173.3	0.0	-1578.3
3.22	146.3	247.0	0.3	233.3	10.78	222.9	9419.1	0.1	2537.8	18.33	-2027.3	12590.5	0.0	-1616.4
3.38	154.0	288.3	0.3	258.5	10.94	172.6	9850.3	0.1	2571.7	18.49	-2077.6	11919.6	0.0	-1651.3
3.54	161.7	333.9	0.3	285.1	11.10	127.9	10237.9	0.1	2594.6	18.66	-2122.3	11312.4	0.0	-1675.2
3.70	168.6	378.3	0.3	309.8	11.26	77.7	10677.5	0.1	2612.5	18.82	-2172.5	10620.3	0.0	-1694.1
3.86	176.3	432.8	0.3	338.9	11.42	27.4	11119.5	0.1	2621.8	18.98	-2217.2	9999.7	0.0	-1703.7
4.02	183.1	485.4	0.3	365.8	11.58	-17.2	11513.2	0.1	2623.0	19.14	-2267.4	9298.8	0.0	-1706.5
4.18	190.8	549.5	0.3	397.3	11.74	-67.5	11955.8	0.1	2616.3	19.30	-2317.7	8598.3	0.0	-1700.9
4.34	197.6	611.1	0.3	426.4	11.90	-112.1	12347.7	0.1	2603.3	19.46	-2362.4	7978.8	0.0	-1688.7
4.50	205.3	685.6	0.2	460.3	12.06	-162.4	12785.7	0.1	2580.5	19.62	-2412.6	7288.5	0.0	-1667.0
4.66	213.0	766.0	0.2	495.6	12.22	-207.1	13171.4	0.1	2553.2	19.78	-2457.3	6683.6	0.0	-1640.6
4.82	219.9	842.5	0.2	528.0	12.38	-257.3	13599.7	0.1	2514.5	19.94	-2507.5	6016.0	0.0	-1602.9
4.99	227.6	934.5	0.2	565.7	12.54	-307.6	14020.9	0.1	2467.3	20.10	-2552.2	5436.8	0.0	-1562.3
5.15	234.4	1021.6	0.2	600.3	12.71	-352.2	14388.1	0.1	2418.2	20.26	-2602.5	4804.4	0.0	-1508.5
5.31	242.1	1126.0	0.2	640.5	12.87	-402.5	14791.9	0.1	2354.9	20.42	-2652.7	4195.5	0.0	-1446.3
5.47	249.0	1224.6	0.2	677.3	13.03	-447.2	15141.3	0.1	2291.6	20.59	-2697.4	3677.0	0.0	-1383.9
5.63	256.7	1342.1	0.2	719.9	13.19	-497.4	15522.4	0.1	2212.3	20.75	-2747.6	3122.4	0.0	-1305.6
5.79	264.4	1467.0	0.2	763.8	13.35	-542.1	15849.5	0.1	2134.7	20.91	-2792.3	2657.5	0.0	-1228.9
5.95	271.2	1584.2	0.2	804.0	13.51	-592.3	16202.9	0.0	2039.4	21.07	-2842.6	2169.5	0.0	-1134.6
6.11	278.9	1723.5	0.2	850.4	13.67	-642.6	16539.6	0.0	1935.6	21.23	-2887.2	1769.3	0.0	-1043.7
6.27	285.8	1853.9	0.2	892.7	13.83	-687.3	16823.7	0.0	1836.2	21.39	-2937.5	1360.3	0.0	-933.4
6.43	293.5	2008.3	0.2	941.5	13.99	-737.5	17124.9	0.0	1716.4	21.55	-2987.7	998.2	0.0	-814.6
6.59	300.3	2152.5	0.2	986.0	14.15	-782.2	17375.1	0.0	1602.7	21.71	-3032.4	718.5	0.0	-701.8
6.75	308.0	2322.8	0.2	1037.3	14.31	-832.4	17635.7	0.0	1466.9	21.87	-3082.7	454.4	0.0	-567.0
6.92	315.7	2501.9	0.2	1089.9	14.47	-877.1	17847.6	0.0	1339.0	22.03	-3127.3	267.4	0.0	-440.0
7.08	322.6	2668.6	0.2	1137.7	14.64	-927.4	18062.4	0.0	1187.1	22.19	-3177.6	113.8	0.0	-289.2
7.24	330.3	2864.9	0.2	1192.8	14.80	-977.6	18251.0	0.0	1026.7	22.35	-3222.3	30.6	0.0	-147.9
7.40	337.1	3047.2	0.2	1242.8	14.96	-1022.3	18395.3	0.0	877.0	22.52	-3266.9	0.0	0.0	0.0









Your Company Name

Client: Case 2: Cantilever with Sloped Backfill
Site: FOS = 1.00

Title: MDOT - Case 2 Sloped Backfill
Page: 5
Date: 4.27.20

Sheet: PZ35
Works: Temporary
Pressure: Coulomb
Analysis: Gross Pressure
Toe: Cantilever



Your Company Name

Client: Case 2: Cantilever with Sloped Backfill

Site: FOS = 1.00

Title: MDOT - Case 2 Sloped Backfill

Page: 6

Date: 4.27.20

Sheet: PZ35

Works: Temporary

Pressure: Coulomb


Analysis: Gross Pressure

Toe: Cantilever

Δ

B

▽



Your Company Name

SupportIT, v2.37

© 1997 - 2015, GTSOFT Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSOFT@aol.com
Web: www.GTSOFT.org

Client: Case 2: Cantilever with Sloped Backfill

Site: FOS = 1.00

Title: MDOT - Case 2 Sloped Backfill
Page: 7

Date: 4.27.20

Sheet: PZ35

Works: Temporary

Pressure: Coulomb

Analysis: Gross Pressure

Toe: Cantilever

Design Report

1. The standard surcharge is 0.0psf. The Piling Handbook recommends a **minimum surcharge of 200.0psf**.
2. Maximum bending moment = 18753.5ftlb/ft and $f = 24966.8\text{psi}$. MINIMUM required sheet section modulus is: $Z = 9.01\text{in}^3/\text{ft}$ ($= M/f$). Sheet section modulus in this design is $Z = 48.90\text{in}^3/\text{ft}$, and is satisfactory.
3. FOS = 1.00 (Gross Pressure)
This is the factor of safety against rotation about the toe.
The FOS can be changed using 'Defined FOS' or 'Manual' in the 'Wall' page.



Your Company Name

SupportIT, v2.37

© 1997 - 2015, GTSoft Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSoftLtd@aol.com
Web: www.GTSoft.org

Client: Case 2: Cantilever with Sloped Backfill

Site: FOS = 1.50

Title: MDOT - Case 2 Sloped Backfill

Page: 1

Date: 4.27.20

Sheet: PZ35


Works: Temporary

Pressure: Coulomb

Analysis: Gross Pressure

Toe: Cantilever

	Maximum	d (ft)
○	456.0 psf	10.00
□	18733.7 ftlb/ft	15.73
●	0.4 in	0.00



Your Company Name

SupportIT, v2.37

© 1997 - 2015, GTSOFT Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSOFT@aol.com
Web: www.GTSOFT.org

Client: Case 2: Cantilever with Sloped Backfill

Site: FOS = 1.50

Title: MDOT - Case 2 Sloped Backfill
Page: 2

Date: 4.27.20

Sheet: PZ35

Works: Temporary

Pressure: Coulomb

Analysis: Gross Pressure

Toe: Cantilever

Input Data

Depth Of Excavation = 10.00ft
Surcharge = 0.0psf
Slope (active) = 20.0degrees

Depth Of Active Water = 10.00ft
Depth Of Passive Water = 10.00ft

Water Density = 62.43pcf
Minimum Fluid Density = 31.82pcf

Soil Profile

Soil Profile		Active Side									
Depth (ft)	Soil Name	γ (pcf)	γ' (pcf)	C (psf)	C_a (psf)	ϕ (°)	δ (°)	K_a	K_{ac}	K_p	K_{pc}
0.00	Dense Fine Sand	120.00	71.10	0.0	0.0	32.0	10.0	0.38	0.00	12.15	0.00

Soil Profile

Soil Profile		Passive Side									
Depth (ft)	Soil Name	γ (pcf)	γ' (pcf)	C (psf)	C_a (psf)	ϕ (°)	δ (°)	K_a	K_{ac}	K_p	K_{pc}
0.00	Dense Fine Sand	120.00	71.10	0.0	0.0	32.0	10.0	0.29	0.00	4.57	0.00

Solution

Sheet

Sheet Name	E (psi)	I (in ⁴ /ft)	f (psi)	Z (in ³ /ft)	Allowed M_{max} (ftlb/ft)	b (in)	A (in ² /ft)	W (lb/ft)	Upstand (ft)	Toe (ft)	Length (ft)
PZ35	3.04E+07	369.40	24966.8	48.90	101739.5	22.64	10.28	66.0	0.00	17.72	27.72

Maxima

	Maximum	Depth (ft)
Pressure	456.0 psf	10.00
Bending Moment	18733.7 ftlb/ft	15.73
Deflection	0.4 in	0.00
Shear Force	2621.6 lb/ft	11.53



Your Company Name

SupportIT, v2.37

© 1997 - 2015, GTSOFT Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSOFT@aol.com
Web: www.GTSOFT.org

Client: Case 2: Cantilever with Sloped Backfill

Site: FOS = 1.50

Title: MDOT - Case 2 Sloped Backfill

Page: 3

Date: 4.27.20

Sheet: PZ35





Works: Temporary

Pressure: Coulomb

Analysis: Gross Pressure

Toe: Cantilever

	Maximum	d (ft)
○	456.0 psf	10.00
□	18733.7 ftlb/ft	15.73
◇	2621.6 lb/ft	11.53
●	0.4 in	0.00



Your Company Name

Client: Case 2: Cantilever with Sloped Backfill
 Site: FOS = 1.50

Title: MDOT - Case 2 Sloped Backfill
 Page: 4
 Date: 4.27.20

Sheet: PZ35
 Works: Temporary
 Pressure: Coulomb
 Analysis: Gross Pressure
 Toe: Cantilever

depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)	depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)	depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)
0.00	0.0	0.6	0.4	0.0	9.31	424.5	6084.4	0.1	1970.7	18.61	-2113.9	11500.6	0.0	-1677.3
0.20	9.5	0.7	0.4	0.8	9.50	432.9	6455.0	0.1	2049.8	18.81	-2168.9	10748.3	0.0	-1700.2
0.40	17.9	1.0	0.4	3.2	9.70	442.4	6889.5	0.1	2140.7	19.01	-2230.8	9892.3	0.0	-1713.7
0.59	27.4	2.0	0.3	7.8	9.90	451.9	7343.1	0.1	2233.5	19.21	-2285.8	9127.9	0.0	-1715.0
0.79	35.8	3.9	0.3	13.5	10.10	422.8	7762.6	0.1	2316.4	19.40	-2347.7	8269.9	0.0	-1704.3
0.99	45.3	7.5	0.3	21.8	10.30	361.0	8251.9	0.1	2398.6	19.60	-2409.5	7420.1	0.0	-1680.7
1.19	53.7	12.2	0.3	30.9	10.49	306.0	8700.3	0.1	2460.8	19.80	-2464.5	6676.9	0.0	-1649.0
1.39	63.2	19.7	0.3	42.9	10.69	244.1	9217.5	0.1	2518.7	20.00	-2526.4	5860.3	0.0	-1601.1
1.58	72.7	29.9	0.3	57.0	10.89	189.1	9686.4	0.1	2559.4	20.20	-2581.4	5156.8	0.0	-1547.7
1.78	81.1	41.5	0.3	71.1	11.09	127.2	10221.8	0.1	2593.0	20.39	-2643.3	4396.3	0.0	-1475.6
1.98	90.6	57.9	0.3	88.8	11.29	65.3	10762.9	0.1	2613.7	20.59	-2698.3	3753.0	0.0	-1400.6
2.18	99.0	75.7	0.3	106.2	11.48	10.3	11246.7	0.1	2621.3	20.79	-2760.2	3071.7	0.0	-1304.1
2.38	108.5	99.7	0.3	127.7	11.68	-51.5	11791.5	0.1	2617.8	20.99	-2822.0	2441.7	0.0	-1194.8
2.57	116.9	125.0	0.3	148.4	11.88	-106.5	12274.3	0.1	2603.8	21.19	-2877.0	1929.9	0.0	-1086.8
2.77	126.4	158.1	0.3	173.6	12.08	-168.4	12813.3	0.1	2575.9	21.38	-2938.9	1414.2	0.0	-953.2
2.97	135.9	196.7	0.3	200.7	12.28	-223.4	13286.5	0.1	2540.4	21.58	-2993.9	1014.3	0.0	-823.6
3.17	144.3	235.9	0.3	226.5	12.47	-285.3	13810.1	0.1	2488.2	21.78	-3055.8	636.0	0.0	-665.7
3.37	153.8	285.8	0.3	257.4	12.67	-347.1	14321.5	0.1	2423.2	21.98	-3110.8	368.5	0.0	-514.5
3.56	162.2	335.7	0.3	286.5	12.87	-407.1	14763.9	0.1	2354.6	22.17	-3172.6	150.6	0.0	-332.3
3.76	171.7	398.4	0.3	321.1	13.07	-464.0	15245.4	0.1	2265.3	22.37	-3234.5	26.9	0.0	-137.2
3.96	180.1	460.3	0.3	353.5	13.27	-519.0	15656.9	0.1	2175.1	22.57	-3289.5	0.0	0.0	0.0
4.16	189.6	537.3	0.3	391.8	13.46	-580.9	16098.8	0.0	2061.5	22.77	-3351.4	0.0	0.0	0.0
4.36	199.1	622.5	0.3	432.1	13.66	-635.9	16470.8	0.0	1949.7	22.97	-3406.4	0.0	0.0	0.0
4.55	207.5	705.3	0.2	469.6	13.86	-697.7	16863.6	0.0	1811.8	23.16	-3468.2	0.0	0.0	0.0
4.75	217.0	807.0	0.2	513.6	14.06	-759.6	17226.6	0.0	1661.0	23.36	-3523.2	0.0	0.0	0.0
4.95	225.4	905.2	0.2	554.4	14.26	-814.6	17522.0	0.0	1516.2	23.56	-3585.1	0.0	0.0	0.0
5.15	234.9	1024.8	0.2	602.1	14.45	-876.5	17821.2	0.0	1341.1	23.76	-3647.0	0.0	0.0	0.0
5.35	243.3	1139.6	0.2	646.2	14.65	-931.5	18055.7	0.0	1174.7	23.96	-3702.0	0.0	0.0	0.0
5.54	252.8	1278.6	0.2	697.6	14.85	-993.4	18281.7	0.0	975.3	24.15	-3763.9	0.0	0.0	0.0
5.74	262.3	1428.6	0.2	751.1	15.05	-1048.4	18446.9	0.0	787.3	24.35	-3818.9	0.0	0.0	0.0
5.94	270.7	1571.3	0.2	800.2	15.25	-1110.2	18590.2	0.0	563.7	24.55	-3880.7	0.0	0.0	0.0
6.14	280.2	1742.9	0.2	857.4	15.44	-1172.1	18685.7	0.0	327.1	24.75	-3935.7	0.0	0.0	0.0
6.34	288.6	1905.6	0.2	909.8	15.64	-1227.1	18728.5	0.0	106.1	24.95	-3997.6	0.0	0.0	0.0
6.53	298.1	2100.3	0.2	970.7	15.84	-1289.0	18720.8	0.0	-114.7	25.14	-4059.5	0.0	0.0	0.0
6.73	306.5	2284.2	0.2	1026.5	16.04	-1344.0	18635.1	0.0	-290.0	25.34	-4114.5	0.0	0.0	0.0
6.93	316.0	2503.5	0.2	1091.1	16.24	-1405.8	18447.9	0.0	-475.1	25.54	-4176.3	0.0	0.0	0.0
7.13	325.5	2736.5	0.2	1157.6	16.43	-1460.8	18205.8	0.0	-628.8	25.74	-4231.3	0.0	0.0	0.0
7.33	333.9	2955.3	0.2	1218.5	16.63	-1522.7	17854.2	0.0	-789.6	25.94	-4293.2	0.0	0.0	0.0
7.52	343.4	3215.0	0.2	1288.8	16.83	-1584.6	17424.8	0.0	-937.5	26.13	-4348.2	0.0	0.0	0.0
7.72	351.8	3458.4	0.2	1352.9	17.03	-1639.6	16983.0	0.0	-1058.2	26.33	-4410.1	0.0	0.0	0.0
7.92	361.3	3746.4	0.2	1426.9	17.23	-1701.4	16424.4	0.0	-1181.9	26.53	-4471.9	0.0	0.0	0.0
8.12	369.7	4015.5	0.2	1494.3	17.42	-1756.4	15878.0	0.0	-1280.9	26.73	-4526.9	0.0	0.0	0.0
8.32	379.2	4333.3	0.2	1572.1	17.62	-1818.3	15213.1	0.0	-1380.3	26.93	-4588.8	0.0	0.0	0.0
8.51	388.7	4667.5	0.2	1651.8	17.82	-1873.3	14582.5	0.0	-1457.8	27.12	-4643.8	0.0	0.0	0.0
8.71	397.1	4978.6	0.1	1724.3	18.02	-1935.2	13834.3	0.0	-1532.8	27.32	-4705.7	0.0	0.0	0.0
8.91	406.6	5344.7	0.1	1807.7	18.22	-1997.1	13051.4	0.0	-1595.0	27.52	-4760.7	0.0	0.0	0.0
9.11	415.0	5684.9	0.1	1883.5	18.41	-2052.1	12331.6	0.0	-1639.4	27.72	-4815.7	0.0	0.0	0.0



Your Company Name







SupportIT, v2.37

© 1997 - 2015, GTSof Ltd.
 Tel/Fax: +44 (0)1292 477754
 Email: GTSofLtd@aol.com
 Web: www.GTSof.org

Client: Case 2: Cantilever with Sloped Backfill
 Site: FOS = 1.50

Title: MDOT - Case 2 Sloped Backfill
 Page: 5
 Date: 4.27.20

Sheet: PZ35
 Works: Temporary
 Pressure: Coulomb
 Analysis: Gross Pressure
 Toe: Cantilever



Your Company Name

SupportIT, v2.37

© 1997 - 2015, GTSOFT Ltd.
 Tel/Fax: +44 (0)1292 477754
 Email: GTSOFT@aol.com
 Web: www.GTSOFT.org

Client: Case 2: Cantilever with Sloped Backfill

Site: FOS = 1.50

Title: MDOT - Case 2 Sloped Backfill

Page: 6

Date: 4.27.20

Sheet: PZ35

Works: Temporary

Pressure: Coulomb

Analysis: Gross Pressure

Toe: Cantilever

Δ

B

▽



◀

L

▶



Your Company Name

SupportIT, v2.37



© 1997 - 2015, GTSOFT Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSOFT@aol.com
Web: www.GTSOFT.org

Client: Case 2: Cantilever with Sloped Backfill

Site: FOS = 1.50

Title: MDOT - Case 2 Sloped Backfill
Page: 7

Date: 4.27.20

Sheet: PZ35

Works: Temporary

Pressure: Coulomb

Analysis: Gross Pressure

Toe: Cantilever

Design Report

1. The standard surcharge is 0.0psf. The Piling Handbook recommends a **minimum surcharge of 200.0psf**.
2. Maximum bending moment = 18733.7ftlb/ft and $f = 24966.8\text{psi}$. MINIMUM required sheet section modulus is: $Z = 9.00\text{in}^3/\text{ft}$ ($= M/f$). Sheet section modulus in this design is $Z = 48.90\text{in}^3/\text{ft}$, and is satisfactory.
3. FOS = 1.50 (Gross Pressure)
This is the factor of safety against rotation about the toe.
The FOS can be changed using 'Defined FOS' or 'Manual' in the 'Wall' page.



Your Company Name

SupportIT, v2.37

© 1997 - 2015, GTSoft Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSoftLtd@aol.com
Web: www.GTSoft.org

Appendix B.3 – SupportIT Output, Case 3


Case 3 – Cantilever TERS in Stiff Clay with Level Back Slope

Client: MDOT
Site: FOS = 1.00

Title: Case 3 Cantilever Firm Clay
Page: 1
Date: 8.30.18

Sheet: PZ22
Works: Temporary
Pressure: Rankine
Analysis: Gross Pressure
Toe: Cantilever

	Maximum	d (ft)
○	318.3 psf	10.00
□	5795.5 ftlb/ft	10.60
●	0.2 in	0.00



MDOT Sheet Pile Manual

SupportIT, v2.37

© 1997 - 2015, GTSOFT Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSOFT@aol.com
Web: www.GTSOFT.org

Client: MDOT
Site: FOS = 1.00

Title: Case 3 Cantilever Firm Clay
Page: 2
Date: 8.30.18

Sheet: PZ22
Works: Temporary
Pressure: Rankine
Analysis: Gross Pressure
Toe: Cantilever

Input Data

Depth Of Excavation = 10.00ft
Surcharge = 360.0psf

Depth Of Active Water = 10.00ft
Depth Of Passive Water = 10.00ft

Water Density = 62.43pcf
Minimum Fluid Density = 31.82pcf

Soil Profile

Depth (ft)	Soil Name	γ (pcf)	γ' (pcf)	C (psf)	C_a (psf)	ϕ (°)	δ (°)	K_a	K_{ac}	K_p	K_{pc}
0.00	Firm Clay	118.37	56.00	1499.9	0.0	0.0	0.0	1.00	2.00	1.00	2.00

Solution

Sheet

Sheet Name	E (psi)	I (in ⁴ /ft)	f (psi)	Z (in ³ /ft)	Allowed M_{max} (ftlb/ft)	b (in)	A (in ² /ft)	W (lb/ft)	Upstand (ft)	Toe (ft)	Length (ft)
PZ22	3.04E+07	84.70	24966.8	18.40	38282.3	22.01	6.46	40.3	0.00	3.16	13.16

Maxima

	Maximum	Depth (ft)
Pressure	318.3 psf	10.00
Bending Moment	5795.5 ftlb/ft	10.60
Deflection	0.2 in	0.00
Shear Force	1595.5 lb/ft	10.00



MDOT Sheet Pile Manual

SupportIT, v2.37





© 1997 - 2015, GTSOFT Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSOFT@aol.com
Web: www.GTSOFT.org

Client: MDOT
 Site: FOS = 1.00

Title: Case 3 Cantilever Firm Clay
 Page: 3
 Date: 8.30.18

Sheet: PZ22
 Works: Temporary
 Pressure: Rankine
 Analysis: Gross Pressure
 Toe: Cantilever

	Maximum	d (ft)
○	318.3 psf	10.00
□	5795.5 ftlb/ft	10.60
◇	1595.5 lb/ft	10.00
●	0.2 in	0.00



MDOT Sheet Pile Manual



Client: MDOT
Site: FOS = 1.00

Title: Case 3 Cantilever Firm Clay
Page: 4
Date: 8.30.18

Sheet: PZ22
Works: Temporary
Pressure: Rankine
Analysis: Gross Pressure
Toe: Cantilever

depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)	depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)	depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)
0.00	0.0	-0.1	0.2	0.0	4.42	140.8	458.5	0.1	312.0	8.84	281.6	3668.8	0.0	1246.4
0.09	3.1	-0.1	0.1	0.2	4.51	143.6	486.4	0.1	324.5	8.93	284.4	3779.1	0.0	1271.2
0.19	5.9	0.0	0.1	0.6	4.61	146.7	519.1	0.1	338.8	9.03	287.5	3905.9	0.0	1299.5
0.28	9.1	0.0	0.1	1.3	4.70	149.9	553.1	0.1	353.5	9.12	290.3	4020.9	0.0	1324.8
0.38	11.9	0.2	0.1	2.3	4.80	152.7	584.7	0.1	366.8	9.21	293.5	4153.0	0.0	1353.7
0.47	15.0	0.5	0.1	3.6	4.89	155.8	621.6	0.1	382.0	9.31	296.6	4287.9	0.0	1382.8
0.56	17.8	0.9	0.1	5.1	4.98	158.6	655.6	0.1	395.8	9.40	299.4	4410.3	0.0	1409.0
0.66	21.0	1.4	0.1	7.0	5.08	161.8	695.4	0.1	411.7	9.50	302.5	4550.7	0.0	1438.7
0.75	24.1	2.2	0.1	9.3	5.17	164.5	732.1	0.1	426.0	9.59	305.3	4678.0	0.0	1465.4
0.85	26.9	3.1	0.1	11.5	5.27	167.7	774.8	0.1	442.4	9.68	308.5	4824.0	0.0	1495.7
0.94	30.0	4.4	0.1	14.3	5.36	170.8	819.2	0.1	459.1	9.78	311.3	4956.3	0.0	1522.9
1.03	32.8	5.7	0.1	17.1	5.45	173.6	860.1	0.1	474.3	9.87	314.4	5108.0	0.0	1553.8
1.13	36.0	7.6	0.1	20.5	5.55	176.8	907.7	0.1	491.6	9.97	317.6	5262.8	0.0	1585.1
1.22	38.8	9.5	0.1	23.8	5.64	179.6	951.4	0.1	507.2	10.06	-2686.5	5399.3	0.0	1448.3
1.32	41.9	12.0	0.1	27.8	5.74	182.7	1002.3	0.1	525.1	10.16	-2695.1	5530.7	0.0	1182.7
1.41	45.1	15.0	0.1	32.1	5.83	185.5	1049.0	0.1	541.3	10.25	-2702.7	5625.4	0.0	945.9
1.50	47.9	17.9	0.1	36.2	5.92	188.7	1103.3	0.1	559.8	10.34	-2711.2	5707.1	0.0	678.7
1.60	51.0	21.7	0.1	41.1	6.02	191.8	1159.4	0.1	578.6	10.44	-2718.8	5757.5	0.0	440.5
1.69	53.8	25.5	0.1	45.7	6.11	194.6	1210.8	0.1	595.6	10.53	-2727.3	5789.2	0.0	171.7
1.79	56.9	30.3	0.1	51.2	6.21	197.7	1270.4	0.1	615.0	10.63	-2735.9	5793.6	0.0	-3.6
1.88	59.7	35.0	0.1	56.4	6.30	200.5	1325.1	0.1	632.4	10.72	-2743.5	5761.4	0.0	-12.7
1.97	62.9	40.8	0.1	62.4	6.39	203.7	1388.4	0.0	652.4	10.81	-2752.0	5680.6	0.0	-22.2
2.07	66.0	47.2	0.1	68.8	6.49	206.5	1446.3	0.0	670.4	10.91	-2759.6	5572.5	0.0	-29.9
2.16	68.8	53.5	0.1	74.7	6.58	209.6	1513.4	0.0	691.0	11.00	-2768.2	5413.5	0.0	-37.8
2.26	72.0	61.2	0.1	81.7	6.68	212.8	1582.6	0.0	711.9	11.10	-2775.8	5242.2	0.0	-44.0
2.35	74.8	68.6	0.1	88.2	6.77	215.5	1645.8	0.0	730.7	11.19	-2784.3	5019.3	0.0	-50.3
2.44	77.9	77.6	0.1	95.7	6.86	218.7	1718.8	0.0	752.1	11.28	-2792.8	4768.3	0.0	-55.8
2.54	80.7	86.3	0.1	102.7	6.96	221.5	1785.6	0.0	771.4	11.38	-2800.4	4524.9	0.0	-59.9
2.63	83.8	96.8	0.1	110.8	7.05	224.6	1862.7	0.0	793.5	11.47	-2809.0	4231.9	0.0	-63.7
2.73	87.0	108.1	0.1	119.3	7.15	227.4	1933.1	0.0	813.3	11.57	-2816.6	3957.5	0.0	-66.4
2.82	89.8	118.9	0.1	127.1	7.24	230.6	2014.4	0.0	836.0	11.66	-2825.1	3636.7	0.0	-68.7
2.91	92.9	131.8	0.1	136.1	7.33	233.7	2097.9	0.0	858.9	11.75	-2832.7	3343.9	0.0	-70.0
3.01	95.7	144.1	0.1	144.4	7.43	236.5	2174.1	0.0	879.6	11.85	-2841.2	3009.7	0.0	-70.6
3.10	98.9	158.7	0.1	154.0	7.52	239.7	2262.0	0.0	903.1	11.94	-2849.8	2674.1	0.0	-70.4
3.20	101.7	172.6	0.1	162.8	7.62	242.4	2342.0	0.0	924.2	12.04	-2857.4	2377.9	0.0	-69.6
3.29	104.8	189.1	0.1	173.0	7.71	245.6	2434.3	0.0	948.4	12.13	-2865.9	2050.8	0.0	-67.8
3.39	107.9	206.7	0.1	183.6	7.80	248.4	2518.4	0.0	970.0	12.22	-2873.5	1768.4	0.0	-65.5
3.48	110.7	223.1	0.1	193.2	7.90	251.5	2615.3	0.0	994.7	12.32	-2882.1	1464.0	0.0	-62.1
3.57	113.9	242.7	0.1	204.3	7.99	254.7	2714.6	0.0	1019.7	12.41	-2889.7	1208.2	0.0	-58.4
3.67	116.7	261.0	0.1	214.4	8.09	257.5	2804.9	0.0	1042.2	12.51	-2898.2	940.7	0.0	-53.4
3.76	119.8	282.7	0.1	226.1	8.18	260.6	2908.9	0.0	1067.8	12.60	-2906.7	698.7	0.0	-47.6
3.86	122.6	302.9	0.1	236.8	8.27	263.4	3003.5	0.0	1090.8	12.69	-2914.3	508.1	0.0	-41.8
3.95	125.8	326.8	0.1	249.0	8.37	266.6	3112.4	0.0	1117.0	12.79	-2922.9	324.9	0.0	-34.4
4.04	128.9	352.0	0.1	261.6	8.46	269.3	3211.3	0.0	1140.5	12.88	-2930.5	193.0	0.0	-27.1
4.14	131.7	375.4	0.1	273.1	8.56	272.5	3325.1	0.0	1167.3	12.98	-2939.0	83.0	0.0	-18.1
4.23	134.8	402.9	0.1	286.2	8.65	275.6	3441.5	0.0	1194.4	13.07	-2946.6	22.5	0.0	-9.4
4.33	137.6	428.5	0.1	298.2	8.74	278.4	3547.3	0.0	1218.7	13.16	-2954.2	0.0	0.0	0.0









MDOT Sheet Pile Manual

Client: MDOT
Site: FOS = 1.00

Title: Case 3 Cantilever Firm Clay
Page: 5
Date: 8.30.18

Sheet: PZ22
Works: Temporary
Pressure: Rankine
Analysis: Gross Pressure
Toe: Cantilever



MDOT Sheet Pile Manual

Client: MDOT
Site: FOS = 1.00

Title: Case 3 Cantilever Firm Clay
Page: 6
Date: 8.30.18

Sheet: PZ22
Works: Temporary
Pressure: Rankine
Analysis: Gross Pressure
Toe: Cantilever

Δ

B

▽



MDOT Sheet Pile Manual

SupportIT, v2.37

© 1997 - 2015, GTSOFT Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSOFT@aol.com
Web: www.GTSOFT.org

Client: MDOT
Site: FOS = 1.00

Title: Case 3 Cantilever Firm Clay
Page: 7
Date: 8.30.18

Sheet: PZ22
Works: Temporary
Pressure: Rankine
Analysis: Gross Pressure
Toe: Cantilever

Design Report

1. Cohesive soil exists below the active water table. MEFD is being applied. Select 'Full Hydrostatic Head' in the 'Pressure' page to apply full hydrostatic pressure.
2. Total stress values are being used (i.e. $C > 0$). Note that the Piling Handbook and CIRIA SP95 recommend that effective stress values be used in 'long term' excavations.
3. Maximum bending moment = 5795.5ftlb/ft and $f = 24966.8$ psi. MINIMUM required sheet section modulus is: $Z = 2.79\text{in}^3/\text{ft}$ ($= M/f$). Sheet section modulus in this design is $Z = 18.40\text{in}^3/\text{ft}$, and is satisfactory.
4. FOS = 1.00 (Gross Pressure)
This is the factor of safety against rotation about the toe.
The FOS can be changed using 'Defined FOS' or 'Manual' in the 'Wall' page.



MDOT Sheet Pile Manual

SupportIT, v2.37


© 1997 - 2015, GTSoft Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSoftLtd@aol.com
Web: www.GTSoft.org

Client: MDOT
Site: FOS = 1.50

Title: Case 3 Cantilever Firm Clay
Page: 1
Date: 8.30.18

Sheet: PZ22
Works: Temporary
Pressure: Rankine
Analysis: Gross Pressure
Toe: Cantilever

	Maximum	d (ft)
○	318.2 psf	10.00
□	5792.0 ftlb/ft	10.59
●	0.2 in	0.00



MDOT Sheet Pile Manual

SupportIT, v2.37

© 1997 - 2015, GTSOFT Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSOFT@aol.com
Web: www.GTSOFT.org

Client: MDOT
Site: FOS = 1.50

Title: Case 3 Cantilever Firm Clay
Page: 2
Date: 8.30.18

Sheet: PZ22
Works: Temporary
Pressure: Rankine
Analysis: Gross Pressure
Toe: Cantilever

Input Data

Depth Of Excavation = 10.00ft
Surcharge = 360.0psf

Depth Of Active Water = 10.00ft
Depth Of Passive Water = 10.00ft

Water Density = 62.43pcf
Minimum Fluid Density = 31.82pcf

Soil Profile

Depth (ft)	Soil Name	γ (pcf)	γ' (pcf)	C (psf)	C_a (psf)	ϕ (°)	δ (°)	K_a	K_{ac}	K_p	K_{pc}
0.00	Firm Clay	118.37	56.00	1499.9	0.0	0.0	0.0	1.00	2.00	1.00	2.00

Solution

Sheet

Sheet Name	E (psi)	I (in ⁴ /ft)	f (psi)	Z (in ³ /ft)	Allowed M_{max} (ftlb/ft)	b (in)	A (in ² /ft)	W (lb/ft)	Upstand (ft)	Toe (ft)	Length (ft)
PZ22	3.04E+07	84.70	24966.8	18.40	38282.3	22.01	6.46	40.3	0.00	4.29	14.29

Maxima

	Maximum	Depth (ft)
Pressure	318.2 psf	10.00
Bending Moment	5792.0 ftlb/ft	10.59
Deflection	0.2 in	0.00
Shear Force	1594.9 lb/ft	10.00



MDOT Sheet Pile Manual

SupportIT, v2.37





© 1997 - 2015, GTSoft Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSoftLtd@aol.com
Web: www.GTSoft.org

Client: MDOT
 Site: FOS = 1.50

Title: Case 3 Cantilever Firm Clay
 Page: 3
 Date: 8.30.18

Sheet: PZ22
 Works: Temporary
 Pressure: Rankine
 Analysis: Gross Pressure
 Toe: Cantilever

	Maximum	d (ft)
○	318.2 psf	10.00
□	5792.0 ftlb/ft	10.59
◇	1594.9 lb/ft	10.00
●	0.2 in	0.00



MDOT Sheet Pile Manual

SupportIT, v2.37

© 1997 - 2015, GTSOFT Ltd.
 Tel/Fax: +44 (0)1292 477754
 Email: GTSOFT@aol.com
 Web: www.GTSOFT.org

Client: MDOT
Site: FOS = 1.50

Title: Case 3 Cantilever Firm Clay
Page: 4
Date: 8.30.18

Sheet: PZ22
Works: Temporary
Pressure: Rankine
Analysis: Gross Pressure
Toe: Cantilever

depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)	depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)	depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)
0.00	0.0	-0.1	0.2	0.0	4.80	152.8	586.5	0.1	367.6	9.59	305.6	4692.1	0.0	1468.5
0.10	3.4	-0.1	0.1	0.2	4.90	155.9	622.1	0.1	382.3	9.70	308.7	4833.2	0.0	1497.8
0.20	6.4	0.0	0.1	0.7	5.00	159.3	663.9	0.1	399.2	9.80	312.1	4995.3	0.0	1531.1
0.31	9.9	0.1	0.1	1.6	5.10	162.7	707.5	0.1	416.5	9.90	315.1	5142.4	0.0	1561.0
0.41	12.9	0.3	0.1	2.7	5.21	165.7	747.8	0.1	432.1	10.00	318.2	5311.3	0.0	1594.9
0.51	16.3	0.7	0.1	4.3	5.31	169.1	794.9	0.1	450.1	10.10	-2690.9	5468.5	0.0	1307.1
0.61	19.3	1.1	0.1	6.0	5.41	172.2	838.5	0.1	466.4	10.21	-2699.1	5582.3	0.0	1050.4
0.71	22.8	1.9	0.1	8.3	5.51	175.6	889.4	0.1	485.0	10.31	-2708.4	5681.1	0.0	760.7
0.82	26.2	2.9	0.1	10.9	5.61	178.6	936.3	0.1	501.9	10.41	-2716.6	5742.8	0.0	502.4
0.92	29.2	4.0	0.1	13.6	5.72	182.0	991.0	0.1	521.3	10.51	-2725.9	5782.8	0.0	210.8
1.02	32.6	5.6	0.1	16.9	5.82	185.4	1047.8	0.1	541.0	10.61	-2734.1	5791.3	0.0	-2.6
1.12	35.6	7.4	0.1	20.2	5.92	188.5	1100.0	0.1	558.8	10.72	-2743.4	5752.8	0.0	-13.9
1.22	39.1	9.7	0.1	24.2	6.02	191.9	1160.9	0.1	579.2	10.82	-2752.7	5660.2	0.0	-24.2
1.33	42.1	12.2	0.1	28.1	6.12	194.9	1216.8	0.1	597.6	10.92	-2760.9	5536.6	0.0	-32.5
1.43	45.5	15.4	0.1	32.8	6.23	198.3	1281.9	0.1	618.7	11.02	-2770.2	5355.6	0.0	-40.9
1.53	48.9	19.2	0.1	37.9	6.33	201.4	1341.6	0.1	637.8	11.13	-2778.4	5161.3	0.0	-47.5
1.63	52.0	23.0	0.1	42.7	6.43	204.8	1411.0	0.0	659.6	11.23	-2787.7	4909.5	0.0	-54.0
1.74	55.4	27.8	0.1	48.5	6.53	208.2	1482.7	0.0	681.7	11.33	-2795.9	4660.1	0.0	-58.9
1.84	58.4	32.7	0.1	53.9	6.63	211.2	1548.5	0.0	701.7	11.43	-2805.2	4355.3	0.0	-63.6
1.94	61.8	38.7	0.1	60.4	6.74	214.6	1624.8	0.0	724.5	11.53	-2814.5	4029.5	0.0	-67.2
2.04	64.8	44.7	0.1	66.4	6.84	217.7	1694.7	0.0	745.2	11.64	-2822.7	3726.3	0.0	-69.6
2.14	68.3	52.2	0.1	73.6	6.94	221.1	1775.6	0.0	768.7	11.74	-2832.0	3374.5	0.0	-71.4
2.25	71.7	60.4	0.1	81.1	7.04	224.1	1849.7	0.0	789.9	11.84	-2840.2	3056.1	0.0	-72.1
2.35	74.7	68.4	0.1	88.1	7.14	227.5	1935.5	0.0	814.1	11.94	-2849.5	2696.0	0.0	-72.0
2.45	78.1	78.3	0.1	96.3	7.25	230.9	2024.0	0.0	838.7	12.04	-2857.8	2378.0	0.0	-71.1
2.55	81.2	87.8	0.1	103.9	7.35	234.0	2104.8	0.0	860.9	12.15	-2867.0	2027.3	0.0	-69.1
2.65	84.6	99.3	0.1	112.8	7.45	237.4	2198.2	0.0	886.2	12.25	-2876.3	1688.6	0.0	-66.1
2.76	87.6	110.4	0.1	121.0	7.55	240.4	2283.6	0.0	908.9	12.35	-2884.5	1401.8	0.0	-62.6
2.86	91.0	123.8	0.1	130.6	7.65	243.8	2382.2	0.0	934.9	12.45	-2893.8	1099.6	0.0	-57.8
2.96	94.4	138.3	0.1	140.5	7.76	246.9	2472.3	0.0	958.3	12.55	-2902.1	853.0	0.0	-52.6
3.06	97.5	152.1	0.1	149.7	7.86	250.3	2576.2	0.0	984.9	12.66	-2911.3	604.9	0.0	-45.9
3.16	100.9	168.6	0.1	160.3	7.96	253.7	2683.1	0.0	1012.0	12.76	-2919.6	414.2	0.0	-39.1
3.27	103.9	184.3	0.1	170.1	8.06	256.7	2780.5	0.0	1036.3	12.86	-2928.9	238.0	0.0	-30.5
3.37	107.3	203.0	0.1	181.5	8.17	260.1	2892.9	0.0	1064.0	12.96	-2938.1	106.8	0.0	-20.9
3.47	110.3	220.8	0.1	191.8	8.27	263.2	2995.3	0.0	1089.0	13.06	-2946.4	32.2	0.0	-11.5
3.57	113.8	241.9	0.1	203.9	8.37	266.6	3113.3	0.0	1117.4	13.17	-2955.6	0.0	0.0	0.0
3.67	117.2	264.3	0.1	216.3	8.47	269.6	3220.8	0.0	1142.9	13.27	-2963.9	0.0	0.0	0.0
3.78	120.2	285.4	0.1	227.6	8.57	273.0	3344.7	0.0	1172.0	13.37	-2973.2	0.0	0.0	0.0
3.88	123.6	310.4	0.1	240.7	8.68	276.4	3471.7	0.0	1201.5	13.47	-2981.4	0.0	0.0	0.0
3.98	126.7	333.8	0.1	252.6	8.78	279.5	3587.2	0.0	1228.0	13.57	-2990.7	0.0	0.0	0.0
4.08	130.1	361.6	0.1	266.4	8.88	282.9	3720.3	0.0	1258.1	13.68	-2999.9	0.0	0.0	0.0
4.18	133.1	387.4	0.1	278.9	8.98	285.9	3841.2	0.0	1285.2	13.78	-3008.2	0.0	0.0	0.0
4.29	136.5	418.0	0.1	293.4	9.08	289.3	3980.5	0.0	1316.1	13.88	-3017.5	0.0	0.0	0.0
4.39	139.9	450.2	0.1	308.2	9.19	292.4	4107.0	0.0	1343.8	13.98	-3025.7	0.0	0.0	0.0
4.49	143.0	480.1	0.1	321.7	9.29	295.8	4252.5	0.0	1375.3	14.08	-3035.0	0.0	0.0	0.0
4.59	146.4	515.3	0.1	337.3	9.39	299.2	4401.4	0.0	1407.2	14.19	-3043.2	0.0	0.0	0.0
4.69	149.4	548.0	0.1	351.4	9.49	302.2	4536.6	0.0	1435.9	14.29	-3051.5	0.0	0.0	0.0

MDOT Sheet Pile Manual

SupportIT, v2.37







© 1997 - 2015, GTSOFT Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSOFT@aol.com
Web: www.GTSOFT.org



Client: MDOT
Site: FOS = 1.50

Title: Case 3 Cantilever Firm Clay
Page: 5
Date: 8.30.18

Sheet: PZ22
Works: Temporary
Pressure: Rankine
Analysis: Gross Pressure
Toe: Cantilever



MDOT Sheet Pile Manual

Client: MDOT
Site: FOS = 1.50

Title: Case 3 Cantilever Firm Clay
Page: 6
Date: 8.30.18

Sheet: PZ22
Works: Temporary
Pressure: Rankine
Analysis: Gross Pressure
Toe: Cantilever

Δ

B

▽



MDOT Sheet Pile Manual

SupportIT, v2.37

© 1997 - 2015, GTSOFT Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSOFT@aol.com
Web: www.GTSOFT.org

Client: MDOT
Site: FOS = 1.50

Title: Case 3 Cantilever Firm Clay
Page: 7
Date: 8.30.18

Sheet: PZ22
Works: Temporary
Pressure: Rankine
Analysis: Gross Pressure
Toe: Cantilever

Design Report

1. Cohesive soil exists below the active water table. MEFD is being applied. Select 'Full Hydrostatic Head' in the 'Pressure' page to apply full hydrostatic pressure.
2. Total stress values are being used (i.e. $C > 0$). Note that the Piling Handbook and CIRIA SP95 recommend that effective stress values be used in 'long term' excavations.
3. Maximum bending moment = 5792.0ftlb/ft and $f = 24966.8$ psi. MINIMUM required sheet section modulus is: $Z = 2.78\text{in}^3/\text{ft}$ ($= M/f$). Sheet section modulus in this design is $Z = 18.40\text{in}^3/\text{ft}$, and is satisfactory.
4. FOS = 1.51 (Gross Pressure)
This is the factor of safety against rotation about the toe.
The FOS can be changed using 'Defined FOS' or 'Manual' in the 'Wall' page.



MDOT Sheet Pile Manual

Appendix B.4 – SupportIT Output, Case 4


Case 4 – Anchored Cantilever TERS in Coarse-grained Soil

Client: MDOT
 Site: Case 4 Anchored Wall in Sand

Title: FOS = 1.00
 Page: 1
 Date: 8.30.18

Sheet: PZ27
 Works: Temporary
 Pressure: Rankine
 Analysis: Gross Pressure

	Maximum	d (ft)
○	855.5 psf	20.00
□	48262.5 ftlb/ft	15.61
●	1.2 in	16.08



MDOT Sheet Pile Manual

SupportIT, v2.37

© 1997 - 2015, GTSOFT Ltd.
 Tel/Fax: +44 (0)1292 477754
 Email: GTSOFT@aol.com
 Web: www.GTSOFT.org

Client: MDOT
Site: Case 4 Anchored Wall in Sand

Title: FOS = 1.00
Page: 2
Date: 8.30.18

Sheet: PZ27
Works: Temporary
Pressure: Rankine
Analysis: Gross Pressure

Input Data

Depth Of Excavation = 20.00ft
Surcharge = 360.0psf

Depth Of Active Water = 20.00ft
Depth Of Passive Water = 20.00ft

Water Density = 62.43pcf
Minimum Fluid Density = 31.82pcf

Soil Profile

Depth (ft)	Soil Name	γ (pcf)	γ' (pcf)	C (psf)	C_a (psf)	ϕ (°)	δ (°)	K_a	K_{ac}	K_p	K_{pc}
0.00	Dense Fine Sand	120.00	71.10	0.0	0.0	32.0	0.0	0.31	0.00	3.25	0.00

Solution

Sheet

Sheet Name	E (psi)	I (in ⁴ /ft)	f (psi)	Z (in ³ /ft)	Allowed M _{max} (ftlb/ft)	b (in)	A (in ² /ft)	W (lb/ft)	Upstand (ft)	Toe (ft)	Length (ft)
PZ27	3.04E+07	187.50	24966.8	31.00	64497.5	17.99	7.93	40.5	0.00	11.12	31.12

Load Model: Area Distribution

Supports

d (ft)	Type	Load (lb/ft)
2.00	Waler	6277.7

Maxima

	Maximum	Depth (ft)
Pressure	855.5 psf	20.00
Bending Moment	48262.5 ftlb/ft	15.61
Deflection	1.2 in	16.08
Shear Force	5977.0 lb/ft	2.00



MDOT Sheet Pile Manual

SupportIT, v2.37





© 1997 - 2015, GTSOFT Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSOFT@aol.com
Web: www.GTSOFT.org

Client: MDOT
 Site: Case 4 Anchored Wall in Sand

Title: FOS = 1.00
 Page: 3
 Date: 8.30.18

Sheet: PZ27
 Works: Temporary
 Pressure: Rankine
 Analysis: Gross Pressure

	Maximum	d (ft)
○	855.5 psf	20.00
□	48262.5 ftlb/ft	15.61
◇	5977.0 lb/ft	2.00
●	1.2 in	16.08



MDOT Sheet Pile Manual



Client: MDOT
 Site: Case 4 Anchored Wall in Sand

Title: FOS = 1.00
 Page: 4
 Date: 8.30.18

Sheet: PZ27
 Works: Temporary
 Pressure: Rankine
 Analysis: Gross Pressure







depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)	depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)	depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)
0.00	111.6	0.2	0.0	0.0	10.45	500.4	-39894.4	1.0	-3071.4	20.90	666.5	-37999.4	1.0	4092.9
0.22	120.3	3.0	0.0	27.3	10.67	508.1	-40522.2	1.0	-2966.7	21.12	623.1	-37163.9	1.0	4226.1
0.44	128.0	11.0	0.0	53.4	10.89	516.8	-41202.3	1.0	-2846.9	21.34	574.3	-36193.0	1.0	4365.3
0.67	136.7	26.7	0.0	84.7	11.12	525.5	-41854.3	1.0	-2725.2	21.56	531.0	-35304.4	1.0	4479.4
0.89	144.4	46.9	0.0	114.3	11.34	533.2	-42409.7	1.0	-2615.2	21.79	482.2	-34278.4	1.0	4597.0
1.11	153.1	77.2	0.0	149.5	11.56	541.9	-43007.2	1.0	-2489.6	22.01	433.4	-33226.8	0.9	4703.2
1.33	160.8	111.2	0.0	182.5	11.78	549.6	-43513.5	1.1	-2376.3	22.23	390.0	-32272.8	0.9	4788.1
1.56	169.5	157.8	0.0	221.5	12.00	558.3	-44054.8	1.1	-2246.9	22.45	341.2	-31180.1	0.9	4872.8
1.78	178.2	213.8	0.0	262.6	12.23	566.0	-44510.5	1.1	-2130.1	22.68	297.8	-30193.7	0.9	4938.5
2.00	185.9	270.1	0.0	-5977.0	12.45	574.7	-44993.9	1.1	-1996.9	22.90	249.0	-29069.2	0.9	5001.7
2.22	194.6	-1120.5	0.0	-5932.4	12.67	583.4	-45446.0	1.1	-1861.6	23.12	205.7	-28058.4	0.9	5048.3
2.45	202.3	-2347.7	0.1	-5891.2	12.89	591.1	-45821.2	1.1	-1739.6	23.34	156.9	-26911.2	0.8	5090.0
2.67	211.0	-3717.8	0.1	-5842.8	13.12	599.8	-46212.9	1.1	-1600.5	23.56	108.1	-25755.7	0.8	5120.3
2.89	218.7	-4926.1	0.1	-5798.1	13.34	607.5	-46533.7	1.1	-1475.2	23.79	64.7	-24723.7	0.8	5137.7
3.11	227.4	-6274.2	0.1	-5746.0	13.56	616.2	-46863.2	1.1	-1332.2	24.01	15.9	-23559.6	0.8	5146.4
3.33	236.1	-7609.9	0.2	-5691.8	13.78	623.9	-47128.0	1.2	-1203.5	24.23	-27.5	-22524.0	0.8	5144.6
3.56	243.8	-8786.4	0.2	-5641.9	14.01	632.6	-47393.7	1.2	-1056.7	24.45	-76.3	-21360.4	0.7	5131.7
3.78	252.5	-10097.3	0.2	-5583.9	14.23	641.3	-47625.0	1.2	-907.9	24.68	-119.6	-20329.5	0.7	5110.5
4.00	260.2	-11251.1	0.3	-5530.6	14.45	649.0	-47801.2	1.2	-774.0	24.90	-168.4	-19175.9	0.7	5075.8
4.22	268.9	-12535.7	0.3	-5468.7	14.67	657.7	-47966.1	1.2	-621.3	25.12	-217.2	-18031.3	0.7	5029.4
4.45	276.6	-13665.3	0.3	-5412.0	14.89	665.4	-48082.6	1.2	-484.0	25.34	-260.6	-17023.6	0.6	4978.6
4.67	285.3	-14921.9	0.4	-5346.3	15.12	674.1	-48179.3	1.2	-327.5	25.57	-309.4	-15903.2	0.6	4910.4
4.89	294.0	-16162.9	0.4	-5278.6	15.34	681.8	-48234.5	1.2	-186.7	25.79	-352.7	-14921.1	0.6	4840.1
5.11	301.7	-17252.5	0.4	-5216.7	15.56	690.5	-48261.6	1.2	-26.5	26.01	-401.5	-13834.3	0.6	4750.1
5.34	310.4	-18462.9	0.4	-5145.2	15.78	699.2	-48251.3	1.2	135.8	26.23	-444.9	-12886.2	0.6	4660.5
5.56	318.1	-19524.5	0.5	-5079.9	16.01	706.9	-48211.1	1.2	281.8	26.45	-493.7	-11842.2	0.5	4548.6
5.78	326.8	-20702.5	0.5	-5004.5	16.23	715.6	-48130.6	1.2	447.9	26.68	-542.5	-10824.7	0.5	4425.2
6.00	334.5	-21734.7	0.5	-4935.8	16.45	723.3	-48027.4	1.2	597.3	26.90	-585.9	-9944.6	0.5	4305.9
6.22	343.2	-22878.7	0.5	-4856.6	16.67	732.0	-47875.1	1.2	767.3	27.12	-634.7	-8984.2	0.5	4160.7
6.45	351.8	-24004.0	0.6	-4775.4	16.90	739.7	-47707.3	1.2	920.1	27.34	-678.0	-8159.1	0.4	4021.9
6.67	359.6	-24988.1	0.6	-4701.5	17.12	748.4	-47481.6	1.2	1093.9	27.57	-726.8	-7265.2	0.4	3854.8
6.89	368.2	-26076.8	0.6	-4616.4	17.34	757.1	-47216.3	1.2	1269.7	27.79	-770.2	-6503.3	0.4	3696.6
7.11	376.0	-27027.7	0.6	-4539.1	17.56	764.8	-46946.9	1.2	1427.7	28.01	-819.0	-5685.3	0.4	3507.8
7.34	384.6	-28078.0	0.7	-4450.2	17.78	773.5	-46605.7	1.2	1607.3	28.23	-867.8	-4911.1	0.3	3307.3
7.56	392.4	-28994.1	0.7	-4369.5	18.01	781.2	-46268.1	1.2	1768.7	28.46	-912.2	-4262.0	0.3	3119.4
7.78	401.0	-30004.5	0.7	-4276.8	18.23	789.9	-45849.3	1.2	1952.2	28.68	-960.0	-3578.0	0.3	2897.2
8.00	409.7	-30993.0	0.7	-4182.1	18.45	797.6	-45442.0	1.2	2117.0	28.90	-1003.3	-3013.1	0.3	2689.9
8.23	417.5	-31853.0	0.8	-4096.2	18.67	806.3	-44943.9	1.1	2304.3	29.12	-1052.1	-2428.5	0.2	2445.8
8.45	426.1	-32799.0	0.8	-3997.6	18.90	815.0	-44403.3	1.1	2493.6	29.35	-1095.5	-1956.2	0.2	2219.1
8.67	433.9	-33620.3	0.8	-3908.3	19.12	822.7	-43886.6	1.1	2663.6	29.57	-1144.3	-1480.4	0.2	1953.1
8.89	442.5	-34522.0	0.8	-3805.9	19.34	831.4	-43264.2	1.1	2856.8	29.79	-1193.1	-1065.9	0.1	1675.6
9.11	450.3	-35303.3	0.9	-3713.1	19.56	839.1	-42674.1	1.1	3030.2	30.01	-1236.5	-751.2	0.1	1419.3
9.34	458.9	-36159.1	0.9	-3606.9	19.79	847.8	-41968.4	1.1	3227.2	30.23	-1285.3	-459.8	0.1	1119.9
9.56	467.6	-36989.8	0.9	-3498.7	20.01	855.5	-41303.4	1.1	3404.0	30.46	-1328.6	-258.5	0.1	844.2
9.78	475.3	-37706.9	0.9	-3400.7	20.23	807.5	-40513.1	1.1	3597.8	30.68	-1377.4	-99.5	0.0	523.0
10.00	484.0	-38489.2	0.9	-3288.6	20.45	758.7	-39680.1	1.1	3779.9	30.90	-1420.8	-20.1	0.0	227.8
10.23	491.7	-39162.4	0.9	-3187.3	20.67	715.3	-38906.0	1.0	3932.3	31.12	-1464.2	0.0	0.0	0.0



MDOT Sheet Pile Manual

Client: MDOT
 Site: Case 4 Anchored Wall in Sand
 Title: FOS = 1.00
 Page: 5
 Date: 8.30.18

Sheet: PZ27
 Works: Temporary
 Pressure: Rankine
 Analysis: Gross Pressure





MDOT Sheet Pile Manual

Client: MDOT
Site: Case 4 Anchored Wall in Sand

Title: FOS = 1.00
Page: 6
Date: 8.30.18

Sheet: PZ27
Works: Temporary
Pressure: Rankine
Analysis: Gross Pressure



MDOT Sheet Pile Manual

Client: MDOT
Site: Case 4 Anchored Wall in Sand

Title: FOS = 1.00
Page: 7
Date: 8.30.18

Sheet: PZ27
Works: Temporary
Pressure: Rankine
Analysis: Gross Pressure

Design Report

1. Maximum bending moment = 48262.5ftlb/ft and $f = 24966.8\text{psi}$. MINIMUM required sheet section modulus is: $Z = 23.20\text{in}^3/\text{ft}$ ($= M/f$). Sheet section modulus in this design is $Z = 31.00\text{in}^3/\text{ft}$, and is satisfactory.
2. Frame primary axis bending moments checked. Users should manually check the axial load capacities and the effects of combined axial and bending stresses to confirm frames are suitable.
3. FOS = 1.00 (Gross Pressure)
This is the factor of safety against rotation about the lowest frame.
The FOS can be changed using 'Defined FOS' or 'Manual' in the 'Wall' page.



MDOT Sheet Pile Manual

SupportIT, v2.37


© 1997 - 2015, GTSOFT Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSOFT@aol.com
Web: www.GTSOFT.org

Client: MDOT
 Site: Case 4 Anchored Wall in Sand

Title: FOS = 1.50
 Page: 1
 Date: 8.30.18

Sheet: PZ27
 Works: Temporary
 Pressure: Rankine
 Analysis: Gross Pressure

	Maximum	d (ft)
○	855.4 psf	20.00
□	48320.5 ftlb/ft	15.62
●	1.7 in	18.18



MDOT Sheet Pile Manual

SupportIT, v2.37

© 1997 - 2015, GTSOFT Ltd.
 Tel/Fax: +44 (0)1292 477754
 Email: GTSOFT@aol.com
 Web: www.GTSOFT.org

Client: MDOT
Site: Case 4 Anchored Wall in Sand

Title: FOS = 1.50
Page: 2
Date: 8.30.18

Sheet: PZ27
Works: Temporary
Pressure: Rankine
Analysis: Gross Pressure

Input Data

Depth Of Excavation = 20.00ft
Surcharge = 360.0psf

Depth Of Active Water = 20.00ft
Depth Of Passive Water = 20.00ft

Water Density = 62.43pcf
Minimum Fluid Density = 31.82pcf

Soil Profile

Depth (ft)	Soil Name	γ (pcf)	γ' (pcf)	C (psf)	C_a (psf)	ϕ (°)	δ (°)	K_a	K_{ac}	K_p	K_{pc}
0.00	Dense Fine Sand	120.00	71.10	0.0	0.0	32.0	0.0	0.31	0.00	3.25	0.00

Solution

Sheet

Sheet Name	E (psi)	I (in ⁴ /ft)	f (psi)	Z (in ³ /ft)	Allowed M _{max} (ftlb/ft)	b (in)	A (in ² /ft)	W (lb/ft)	Upstand (ft)	Toe (ft)	Length (ft)
PZ27	3.04E+07	187.50	24966.8	31.00	64497.5	17.99	7.93	40.5	0.00	17.49	37.49

Load Model: Area Distribution

Supports

d (ft)	Type	Load (lb/ft)
2.00	Waler	6281.9

Maxima

	Maximum	Depth (ft)
Pressure	855.4 psf	20.00
Bending Moment	48320.5 ftlb/ft	15.62
Deflection	1.7 in	18.18
Shear Force	5980.0 lb/ft	2.00

MDOT Sheet Pile Manual



SupportIT, v2.37





© 1997 - 2015, GTSoft Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSoftLtd@aol.com
Web: www.GTSoft.org

Client: MDOT
 Site: Case 4 Anchored Wall in Sand

Title: FOS = 1.50
 Page: 3
 Date: 8.30.18

Sheet: PZ27
 Works: Temporary
 Pressure: Rankine
 Analysis: Gross Pressure

	Maximum	d (ft)
○	855.4 psf	20.00
□	48320.5 ftlb/ft	15.62
◇	5980.0 lb/ft	2.00
●	1.7 in	18.18



MDOT Sheet Pile Manual



SupportIT, v2.37

© 1997 - 2015, GTSOFT Ltd.
 Tel/Fax: +44 (0)1292 477754
 Email: GTSOFT@aol.com
 Web: www.GTSOFT.org

Client: MDOT
Site: Case 4 Anchored Wall in Sand

Title: FOS = 1.50
Page: 4
Date: 8.30.18

Sheet: PZ27
Works: Temporary
Pressure: Rankine
Analysis: Gross Pressure

depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)	depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)	depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)
0.00	111.6	0.3	0.0	0.0	12.59	579.9	-45314.7	1.4	-1918.1	25.17	-227.1	-27010.1	1.3	5107.2
0.27	122.1	4.3	0.0	33.2	12.85	589.2	-45778.3	1.4	-1771.9	25.44	-279.4	-26145.3	1.3	5089.2
0.54	131.4	16.1	0.0	65.4	13.12	599.7	-46255.9	1.5	-1604.6	25.71	-338.2	-25176.4	1.3	5064.5
0.80	141.8	39.3	0.0	104.4	13.39	610.2	-46686.0	1.5	-1434.3	25.97	-390.4	-24319.4	1.3	5038.7
1.07	151.1	69.4	0.0	141.6	13.66	619.5	-47027.8	1.5	-1280.5	26.24	-449.2	-23360.9	1.3	5005.3
1.34	161.6	114.8	0.0	186.3	13.92	629.9	-47366.1	1.5	-1104.7	26.51	-507.9	-22409.1	1.2	4967.3
1.61	170.9	165.9	0.0	228.5	14.19	639.2	-47625.0	1.5	-946.0	26.78	-560.2	-21569.5	1.2	4929.6
1.87	181.3	236.3	0.0	278.7	14.46	649.7	-47868.5	1.6	-764.6	27.05	-619.0	-20633.0	1.2	4882.7
2.14	191.8	-660.4	0.0	-5950.4	14.73	659.0	-48041.8	1.6	-601.0	27.31	-671.2	-19808.3	1.2	4837.2
2.41	201.1	-2142.8	0.1	-5901.1	15.00	669.4	-48187.5	1.6	-414.0	27.58	-730.0	-18890.1	1.1	4781.7
2.68	211.5	-3795.5	0.1	-5843.0	15.26	679.9	-48280.3	1.6	-224.2	27.85	-782.2	-18083.1	1.1	4728.4
2.95	220.8	-5250.5	0.2	-5788.8	15.53	689.2	-48317.7	1.6	-53.0	28.12	-841.0	-17186.4	1.1	4664.0
3.21	231.3	-6870.8	0.2	-5725.1	15.80	699.6	-48312.1	1.6	142.4	28.38	-899.8	-16302.4	1.0	4595.0
3.48	240.6	-8295.8	0.2	-5666.0	16.07	708.9	-48274.9	1.6	318.6	28.65	-952.0	-15527.9	1.0	4529.8
3.75	251.1	-9881.0	0.3	-5596.7	16.33	719.4	-48197.2	1.6	519.6	28.92	-1010.8	-14670.2	1.0	4452.1
4.02	261.5	-11446.2	0.3	-5524.5	16.60	728.7	-48095.6	1.6	700.7	29.19	-1063.0	-13920.6	1.0	4379.1
4.28	270.8	-12820.3	0.4	-5457.8	16.87	739.2	-47944.5	1.6	907.2	29.46	-1121.8	-13092.4	0.9	4292.5
4.55	281.3	-14345.8	0.4	-5380.0	17.14	749.6	-47753.7	1.6	1116.6	29.72	-1174.0	-12370.4	0.9	4211.7
4.82	290.6	-15683.2	0.5	-5308.4	17.41	758.9	-47550.4	1.6	1305.3	29.99	-1232.8	-11574.9	0.9	4116.5
5.09	301.0	-17166.0	0.5	-5225.1	17.67	769.4	-47283.2	1.7	1520.3	30.26	-1291.6	-10798.0	0.8	4016.5
5.36	310.3	-18464.0	0.5	-5148.6	17.94	778.7	-47011.0	1.7	1713.9	30.53	-1343.8	-10123.7	0.8	3923.8
5.62	320.8	-19901.2	0.6	-5059.7	18.21	789.1	-46665.4	1.7	1934.5	30.79	-1402.6	-9384.2	0.8	3815.1
5.89	331.2	-21313.0	0.6	-4967.9	18.48	798.4	-46322.7	1.7	2133.0	31.06	-1454.8	-8744.7	0.8	3714.6
6.16	340.5	-22545.9	0.7	-4883.8	18.74	808.9	-45896.6	1.7	2359.1	31.33	-1513.6	-8045.9	0.7	3597.2
6.43	351.0	-23907.5	0.7	-4786.4	19.01	819.3	-45427.2	1.6	2588.2	31.60	-1565.9	-7443.9	0.7	3488.9
6.69	360.3	-25094.5	0.7	-4697.4	19.28	828.6	-44973.0	1.6	2794.2	31.87	-1624.6	-6788.9	0.7	3362.6
6.96	370.8	-26403.0	0.8	-4594.4	19.55	839.1	-44420.1	1.6	3028.9	32.13	-1683.4	-6158.4	0.6	3231.8
7.23	380.1	-27541.5	0.8	-4500.4	19.82	848.4	-43890.8	1.6	3239.9	32.40	-1735.6	-5619.2	0.6	3111.6
7.50	390.5	-28793.9	0.9	-4392.0	20.08	837.3	-43252.4	1.6	3479.1	32.67	-1794.4	-5037.3	0.6	2971.9
7.77	401.0	-30015.4	0.9	-4280.5	20.35	785.0	-42647.2	1.6	3681.0	32.94	-1846.7	-4542.8	0.5	2843.9
8.03	410.3	-31074.6	0.9	-4179.0	20.62	726.3	-41926.8	1.6	3892.6	33.20	-1905.4	-4012.7	0.5	2695.5
8.30	420.7	-32235.5	1.0	-4062.0	20.89	667.5	-41167.4	1.6	4087.6	33.47	-1957.7	-3565.7	0.5	2559.7
8.57	430.0	-33239.5	1.0	-3955.6	21.15	615.3	-40462.2	1.6	4247.1	33.74	-2016.4	-3090.6	0.4	2402.6
8.84	440.5	-34336.9	1.0	-3833.0	21.42	556.5	-39637.8	1.6	4410.9	34.01	-2075.2	-2645.8	0.4	2240.8
9.10	449.8	-35283.1	1.1	-3721.6	21.69	504.2	-38879.8	1.6	4542.6	34.28	-2127.5	-2276.8	0.4	2093.1
9.37	460.2	-36313.9	1.1	-3593.5	21.96	445.5	-38001.7	1.6	4675.2	34.54	-2186.2	-1891.8	0.3	1922.5
9.64	470.7	-37308.4	1.1	-3462.5	22.23	393.2	-37200.9	1.5	4779.2	34.81	-2238.5	-1577.3	0.3	1767.0
9.91	480.0	-38161.1	1.2	-3343.5	22.49	334.5	-36280.3	1.5	4880.6	35.08	-2297.2	-1255.3	0.3	1587.6
10.18	490.5	-39084.6	1.2	-3207.0	22.76	275.7	-35341.7	1.5	4965.4	35.35	-2349.5	-998.2	0.3	1424.3
10.44	499.8	-39872.9	1.2	-3083.1	23.03	223.4	-34494.9	1.5	5027.0	35.61	-2408.3	-742.3	0.2	1236.2
10.71	510.2	-40722.4	1.3	-2940.9	23.30	164.7	-33531.1	1.5	5080.6	35.88	-2467.0	-522.7	0.2	1043.5
10.98	519.5	-41443.7	1.3	-2812.1	23.56	112.4	-32666.8	1.5	5114.4	36.15	-2519.3	-358.7	0.2	868.3
11.25	530.0	-42216.3	1.3	-2664.4	23.83	53.7	-31688.9	1.4	5136.9	36.42	-2578.1	-210.1	0.1	666.8
11.51	540.4	-42947.0	1.3	-2513.8	24.10	1.4	-30817.2	1.4	5142.9	36.69	-2630.3	-110.5	0.1	483.8
11.78	549.7	-43560.6	1.4	-2377.4	24.37	-57.4	-29836.2	1.4	5140.4	36.95	-2689.1	-36.0	0.1	273.5
12.05	560.2	-44209.9	1.4	-2221.2	24.64	-116.1	-28856.0	1.4	5133.3	37.22	-2741.3	-3.7	0.0	82.7
12.32	569.5	-44749.8	1.4	-2079.9	24.90	-168.4	-27986.2	1.4	5123.0	37.49	-2793.5	0.0	0.0	0.0








MDOT Sheet Pile Manual

SupportIT, v2.37

© 1997 - 2015, GTSoft Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSoftLtd@aol.com
Web: www.GTSoft.org

Client: MDOT
 Site: Case 4 Anchored Wall in Sand
 Title: FOS = 1.50
 Page: 5
 Date: 8.30.18

Sheet: PZ27
 Works: Temporary
 Pressure: Rankine
 Analysis: Gross Pressure





MDOT Sheet Pile Manual

Client: MDOT
Site: Case 4 Anchored Wall in Sand

Title: FOS = 1.50
Page: 6
Date: 8.30.18

Sheet: PZ27
Works: Temporary
Pressure: Rankine
Analysis: Gross Pressure



MDOT Sheet Pile Manual

Client: MDOT
Site: Case 4 Anchored Wall in Sand

Title: FOS = 1.50
Page: 7
Date: 8.30.18

Sheet: PZ27
Works: Temporary
Pressure: Rankine
Analysis: Gross Pressure


Design Report

1. Maximum bending moment = 48320.5ftlb/ft and $f = 24966.8\text{psi}$. MINIMUM required sheet section modulus is: $Z = 23.22\text{in}^3/\text{ft}$ ($= M/f$). Sheet section modulus in this design is $Z = 31.00\text{in}^3/\text{ft}$, and is satisfactory.
2. Frame primary axis bending moments checked. Users should manually check the axial load capacities and the effects of combined axial and bending stresses to confirm frames are suitable.
3. FOS = 1.50 (Gross Pressure)
This is the factor of safety against rotation about the lowest frame.
The FOS can be changed using 'Defined FOS' or 'Manual' in the 'Wall' page.



MDOT Sheet Pile Manual

SupportIT, v2.37

 © 1997 - 2015, GTSOFT Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSOFT.Ltd@aol.com
Web: www.GTSOFT.org

Appendix B.5 – SupportIT Output, Case 5


Case 5 – Anchored Cantilever TERS in Stiff Clay

Client: Case 5 Anchor in Clay with Sand Backfill

Page: 1
Date: 10.1.18 FOS = 1.0

Sheet: PZ22
Works: Temporary
Pressure: Rankine
Analysis: Gross Pressure

	Maximum	d (ft)
□	32460.7 ftlb/ft	16.20
◇	5790.0 lb/ft	25.02
●	1.3 in	15.45



MDOT Sheet Pile Manual

SupportIT, v2.37

© 1997 - 2015, GTSOFT Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSOFT@aol.com
Web: www.GTSOFT.org

Client: Case 5 Anchor in Clay with Sand Backfill

Page: 2
Date: 10.1.18 FOS = 1.0

Sheet: PZ22
Works: Temporary
Pressure: Rankine
Analysis: Gross Pressure

Input Data

Depth Of Excavation = 25.00ft
Surcharge = 360.0psf

Depth Of Active Water = 25.00ft
Depth Of Passive Water = 25.00ft

Water Density = 62.43pcf
Minimum Fluid Density = 31.82pcf

Soil Profile

Depth (ft)	Soil Name	γ (pcf)	γ' (pcf)	C (psf)	C_a (psf)	ϕ (°)	δ (°)	K_a	K_{ac}	K_p	K_{pc}
0.00	Dense Coarse Sand	115.82	68.73	0.0	0.0	40.0	0.0	0.22	0.00	4.60	0.00
5.00	Firm Clay	118.37	56.00	1499.9	0.0	0.0	0.0	1.00	2.00	1.00	2.00

Solution

Sheet

Sheet Name	E (psi)	I (in ⁴ /ft)	f (psi)	Z (in ³ /ft)	Allowed M_{max} (ftlb/ft)	b (in)	A (in ² /ft)	W (lb/ft)	Upstand (ft)	Toe (ft)	Length (ft)
PZ22	3.04E+07	84.70	24966.8	18.40	38282.3	22.01	6.46	40.3	0.00	2.54	27.54

Load Model: Area Distribution

Supports

d (ft)	Type	Load (lb/ft)
3.00	Waler	4502.7

Maxima

	Maximum	Depth (ft)
Pressure	795.2 psf	25.00
Bending Moment	32460.7 ftlb/ft	16.20
Deflection	1.3 in	15.45
Shear Force	5790.0 lb/ft	25.02

MDOT Sheet Pile Manual



SupportIT, v2.37





© 1997 - 2015, GTSoft Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSoftLtd@aol.com
Web: www.GTSoft.org

Client: Case 5 Anchor in Clay with Sand Backfill

Page: 3
Date: 10.1.18 FOS = 1.0

Sheet: PZ22
Works: Temporary
Pressure: Rankine
Analysis: Gross Pressure

	Maximum	d (ft)
○	795.2 psf	25.00
□	32460.7 ftlb/ft	16.20
◇	5790.0 lb/ft	25.02
●	1.3 in	15.45



MDOT Sheet Pile Manual



Client: Case 5 Anchor in Clay with Sand Backfill

Page: 4 FOS = 1.0
Date: 10.1.18

Sheet: PZ22
Works: Temporary
Pressure: Rankine
Analysis: Gross Pressure

depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)	depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)	depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)
0.00	79.2	0.3	0.0	0.0	9.25	294.6	-21727.1	0.9	-2819.0	18.49	589.1	-30976.1	1.2	1271.1
0.20	84.5	1.8	0.0	17.1	9.44	300.4	-22241.0	1.0	-2764.3	18.69	595.0	-30722.0	1.2	1379.9
0.39	89.1	6.2	0.0	33.1	9.64	307.0	-22807.0	1.0	-2701.5	18.89	601.5	-30411.0	1.2	1503.6
0.59	94.4	14.8	0.0	52.2	9.84	313.6	-23359.9	1.0	-2637.3	19.08	607.4	-30111.9	1.2	1614.6
0.79	99.1	25.8	0.0	70.2	10.03	319.4	-23840.1	1.0	-2579.2	19.28	614.0	-29749.7	1.2	1740.8
0.98	104.3	42.3	0.0	91.3	10.23	326.0	-24367.4	1.0	-2512.4	19.48	620.5	-29360.0	1.1	1868.4
1.18	109.0	60.6	0.0	111.1	10.43	331.8	-24824.5	1.1	-2452.0	19.67	626.4	-28990.3	1.1	1983.0
1.38	114.3	85.7	0.0	134.3	10.62	338.4	-25325.3	1.1	-2382.7	19.87	633.0	-28547.9	1.1	2113.1
1.57	119.6	115.6	0.0	158.7	10.82	344.3	-25758.3	1.1	-2319.9	20.07	638.8	-28130.8	1.1	2229.9
1.77	124.2	146.5	0.0	181.2	11.02	350.8	-26231.5	1.1	-2248.1	20.26	645.4	-27634.6	1.1	2362.7
1.97	129.5	186.4	0.0	207.6	11.21	357.4	-26689.8	1.1	-2174.8	20.46	651.2	-27169.3	1.1	2481.8
2.16	134.2	226.5	0.0	232.0	11.41	363.3	-27084.3	1.2	-2108.6	20.66	657.8	-26618.2	1.0	2617.0
2.36	139.4	277.0	0.0	260.5	11.61	369.8	-27513.5	1.2	-2032.8	20.85	664.4	-26037.7	1.0	2753.7
2.56	144.1	326.9	0.0	286.7	11.80	375.7	-27881.7	1.2	-1964.3	21.05	670.2	-25496.8	1.0	2876.3
2.75	149.4	388.9	0.0	317.2	12.00	382.3	-28280.8	1.2	-1885.9	21.25	676.8	-24859.8	1.0	3015.5
2.95	154.6	457.3	0.0	348.8	12.20	388.1	-28621.9	1.2	-1815.1	21.44	682.7	-24268.2	0.9	3140.4
3.15	159.3	-97.1	0.0	-4124.9	12.39	394.7	-28989.9	1.2	-1734.2	21.64	689.2	-23573.7	0.9	3282.1
3.34	164.6	-947.2	0.1	-4091.4	12.59	401.3	-29341.0	1.2	-1651.9	21.84	695.1	-22930.5	0.9	3409.3
3.54	169.3	-1697.0	0.1	-4060.7	12.79	407.1	-29638.8	1.2	-1577.7	22.03	701.7	-22177.5	0.9	3553.6
3.74	174.5	-2533.6	0.1	-4025.2	12.98	413.7	-29957.3	1.3	-1492.8	22.23	708.3	-21393.1	0.8	3699.3
3.93	179.2	-3271.0	0.2	-3992.6	13.18	419.5	-30225.6	1.3	-1416.2	22.43	714.1	-20669.2	0.8	3829.9
4.13	184.5	-4093.4	0.2	-3955.0	13.38	426.1	-30510.5	1.3	-1328.8	22.62	720.7	-19824.6	0.8	3978.2
4.33	189.7	-4907.8	0.2	-3916.3	13.57	432.0	-30748.5	1.3	-1250.0	22.82	726.5	-19046.8	0.8	4111.1
4.52	194.4	-5625.0	0.2	-3881.0	13.77	438.5	-30998.8	1.3	-1160.0	23.02	733.1	-18141.0	0.7	4262.0
4.72	199.7	-6424.0	0.3	-3840.2	13.97	445.1	-31230.3	1.3	-1068.6	23.21	738.9	-17308.3	0.7	4397.2
4.92	204.4	-7127.0	0.3	-3803.1	14.16	451.0	-31420.2	1.3	-986.3	23.41	745.5	-16340.2	0.7	4550.6
5.11	163.0	-7909.9	0.3	-3765.6	14.36	457.6	-31615.6	1.3	-892.4	23.61	752.1	-15338.8	0.6	4705.3
5.31	168.8	-8599.8	0.4	-3735.1	14.56	463.4	-31772.8	1.3	-807.8	23.80	758.0	-14420.3	0.6	4844.0
5.51	175.4	-9369.1	0.4	-3699.5	14.75	470.0	-31931.1	1.3	-711.3	24.00	764.5	-13355.0	0.6	5001.4
5.71	182.0	-10130.9	0.4	-3662.5	14.95	475.8	-32054.9	1.3	-624.4	24.20	770.4	-12379.4	0.6	5142.3
5.90	187.8	-10801.5	0.5	-3628.5	15.15	482.4	-32174.9	1.3	-525.4	24.39	777.0	-11249.1	0.5	5302.2
6.10	194.4	-11548.3	0.5	-3588.9	15.34	489.0	-32274.4	1.3	-425.0	24.59	782.8	-10215.3	0.5	5445.5
6.30	200.3	-12205.3	0.5	-3552.6	15.54	494.8	-32345.3	1.3	-334.6	24.79	789.4	-9019.1	0.5	5607.9
6.49	206.8	-12936.2	0.6	-3510.5	15.74	501.4	-32405.0	1.3	-231.6	24.98	795.2	-7787.5	0.4	5771.7
6.69	212.7	-13578.5	0.6	-3471.9	15.94	507.3	-32440.1	1.3	-138.9	25.18	-2219.1	-6698.2	0.4	5428.5
6.89	219.3	-14292.5	0.6	-3427.2	16.13	513.8	-32459.2	1.3	-33.4	25.38	-2237.0	-5566.5	0.4	4959.1
7.08	225.9	-14997.2	0.6	-3381.2	16.33	519.7	-32457.6	1.3	61.5	25.57	-2252.9	-4646.2	0.3	4538.6
7.28	231.7	-15615.4	0.7	-3339.1	16.53	526.3	-32433.9	1.3	169.6	25.77	-2270.7	-3708.1	0.3	4062.1
7.48	238.3	-16301.6	0.7	-3290.5	16.72	532.8	-32386.6	1.3	279.1	25.97	-2286.6	-2961.2	0.3	3635.3
7.67	244.1	-16903.0	0.7	-3246.1	16.92	538.7	-32324.5	1.3	377.5	26.16	-2304.5	-2219.6	0.2	3151.7
7.87	250.7	-17569.7	0.8	-3194.9	17.12	545.3	-32231.9	1.3	489.6	26.36	-2322.4	-1583.3	0.2	2664.2
8.07	256.6	-18153.3	0.8	-3148.3	17.31	551.1	-32129.1	1.3	590.3	26.56	-2338.2	-1106.6	0.2	2227.8
8.26	263.1	-18799.6	0.8	-3094.6	17.51	557.7	-31990.1	1.3	704.9	26.76	-2356.1	-671.2	0.1	1733.3
8.46	269.7	-19434.6	0.8	-3039.4	17.71	563.5	-31845.6	1.3	807.9	26.95	-2372.0	-374.4	0.1	1290.5
8.66	275.6	-19989.4	0.9	-2989.3	17.90	570.1	-31659.1	1.3	925.1	27.15	-2389.9	-142.9	0.1	788.9
8.85	282.1	-20602.4	0.9	-2931.6	18.10	576.7	-31447.2	1.2	1043.6	27.35	-2405.8	-28.7	0.0	339.8
9.05	288.0	-21137.1	0.9	-2879.2	18.30	582.5	-31237.1	1.2	1150.1	27.54	-2421.6	0.0	0.0	0.0

MDOT Sheet Pile Manual

SupportIT, v2.37







© 1997 - 2015, GTSoft Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSoftLtd@aol.com
Web: www.GTSoft.org



Client: Case 5 Anchor in Clay with Sand Backfill

Page: 5
Date: 10.1.18 FOS = 1.0

Sheet: PZ22
Works: Temporary
Pressure: Rankine
Analysis: Gross Pressure



MDOT Sheet Pile Manual





Client: Case 5 Anchor in Clay with Sand Backfill

Page: 6
Date: 10.1.18 FOS = 1.0

Sheet: PZ22
Works: Temporary

Pressure: Rankine
Analysis: Gross Pressure



MDOT Sheet Pile Manual

Client: Case 5 Anchor in Clay with Sand Backfill

Page: 7
Date: 10.1.18 FOS = 1.0

Sheet: PZ22
Works: Temporary
Pressure: Rankine
Analysis: Gross Pressure

Design Report

1. Cohesive soil exists below the active water table. MEFD is being applied. Select 'Full Hydrostatic Head' in the 'Pressure' page to apply full hydrostatic pressure.
2. Total stress values are being used (i.e. $C > 0$). Note that the Piling Handbook and CIRIA SP95 recommend that effective stress values be used in 'long term' excavations.
3. Maximum bending moment = 32460.7ftlb/ft and $f = 24966.8$ psi. MINIMUM required sheet section modulus is: $Z = 15.60\text{in}^3/\text{ft}$ ($= M/f$). Sheet section modulus in this design is $Z = 18.40\text{in}^3/\text{ft}$, and is satisfactory.
4. Frame primary axis bending moments checked. Users should manually check the axial load capacities and the effects of combined axial and bending stresses to confirm frames are suitable.
5. FOS = 0.99 (Gross Pressure)
This is the factor of safety against rotation about the lowest frame.
The FOS can be changed using 'Defined FOS' or 'Manual' in the 'Wall' page.



MDOT Sheet Pile Manual

SupportIT, v2.37


© 1997 - 2015, GTSoft Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSoftLtd@aol.com
Web: www.GTSoft.org

Client: Case 5 Anchor in Clay with Sand Backfill

Page: 1
Date: 10.1.18 FOS = 1.5

Sheet: PZ22
Works: Temporary
Pressure: Rankine
Analysis: Gross Pressure

	Maximum	d (ft)
□	31945.0 ftlb/ft	16.14
◇	5819.8 lb/ft	25.00
●	1.5 in	16.07



MDOT Sheet Pile Manual



SupportIT, v2.37

© 1997 - 2015, GTSOFT Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSOFT@aol.com
Web: www.GTSOFT.org

Client: Case 5 Anchor in Clay with Sand Backfill

Page: 2
Date: 10.1.18 FOS = 1.5

Sheet: PZ22
Works: Temporary
Pressure: Rankine
Analysis: Gross Pressure

Input Data

Depth Of Excavation = 25.00ft
Surcharge = 360.0psf

Depth Of Active Water = 25.00ft
Depth Of Passive Water = 25.00ft

Water Density = 62.43pcf
Minimum Fluid Density = 31.82pcf

Soil Profile

Depth (ft)	Soil Name	γ (pcf)	γ' (pcf)	C (psf)	C_a (psf)	ϕ (°)	δ (°)	K_a	K_{ac}	K_p	K_{pc}
0.00	Dense Coarse Sand	115.82	68.73	0.0	0.0	40.0	0.0	0.22	0.00	4.60	0.00
5.00	Firm Clay	118.37	56.00	1499.9	0.0	0.0	0.0	1.00	2.00	1.00	2.00

Solution

Sheet

Sheet Name	E (psi)	I (in ⁴ /ft)	f (psi)	Z (in ³ /ft)	Allowed M_{max} (ftlb/ft)	b (in)	A (in ² /ft)	W (lb/ft)	Upstand (ft)	Toe (ft)	Length (ft)
PZ22	3.04E+07	84.70	24966.8	18.40	38282.3	22.01	6.46	40.3	0.00	4.30	29.30

Load Model: Area Distribution

Supports

d (ft)	Type	Load (lb/ft)
3.00	Waler	4463.7

Maxima

	Maximum	Depth (ft)
Pressure	795.5 psf	25.00
Bending Moment	31945.0 ftlb/ft	16.14
Deflection	1.5 in	16.07
Shear Force	5819.8 lb/ft	25.00

MDOT Sheet Pile Manual

SupportIT, v2.37

© 1997 - 2015, GTSoft Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSoftLtd@aol.com
Web: www.GTSoft.org







Client: Case 5 Anchor in Clay with Sand Backfill

Page: 3
Date: 10.1.18 FOS = 1.5

Sheet: PZ22
Works: Temporary
Pressure: Rankine
Analysis: Gross Pressure

	Maximum	d (ft)
○	795.5 psf	25.00
□	31945.0 ftlb/ft	16.14
◇	5819.8 lb/ft	25.00
●	1.5 in	16.07



MDOT Sheet Pile Manual



Client: Case 5 Anchor in Clay with Sand Backfill

Page: 4 FOS = 1.5
Date: 10.1.18

Sheet: PZ22
Works: Temporary
Pressure: Rankine
Analysis: Gross Pressure

depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)	depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)	depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)
0.00	79.2	0.3	0.0	0.0	9.84	313.4	-23081.9	1.1	-2599.6	19.67	626.8	-28909.1	1.3	2030.1
0.21	84.8	2.1	0.0	18.2	10.05	319.6	-23584.9	1.1	-2537.7	19.88	633.0	-28552.7	1.3	2153.2
0.42	89.8	7.1	0.0	35.4	10.26	326.6	-24136.1	1.1	-2466.6	20.09	640.0	-28126.5	1.3	2293.2
0.63	95.4	16.8	0.0	55.9	10.47	333.6	-24671.6	1.2	-2394.0	20.30	646.2	-27724.9	1.3	2418.9
0.84	100.4	29.4	0.0	75.2	10.67	339.8	-25134.1	1.2	-2328.1	20.51	653.2	-27247.3	1.3	2561.8
1.05	106.0	48.1	0.0	98.1	10.88	346.8	-25638.8	1.2	-2252.6	20.72	660.2	-26742.1	1.2	2706.2
1.26	110.9	69.1	0.0	119.4	11.09	353.0	-26073.4	1.2	-2184.2	20.93	666.4	-26269.6	1.2	2835.8
1.47	116.5	97.8	0.0	144.6	11.30	360.0	-26546.2	1.2	-2105.7	21.14	673.4	-25711.4	1.2	2983.2
1.67	122.1	132.1	0.0	171.1	11.51	366.3	-26951.9	1.3	-2034.7	21.35	679.6	-25191.3	1.2	3115.4
1.88	127.1	167.6	0.0	195.6	11.72	373.3	-27391.5	1.3	-1953.4	21.56	686.6	-24579.1	1.2	3265.6
2.09	132.7	213.4	0.0	224.4	11.93	380.3	-27813.1	1.3	-1870.5	21.77	692.9	-24010.5	1.1	3400.4
2.30	137.7	259.5	0.0	251.0	12.14	386.5	-28172.4	1.3	-1795.5	21.98	699.9	-23343.2	1.1	3553.6
2.51	143.3	317.7	0.0	282.1	12.35	393.5	-28559.0	1.3	-1709.7	22.19	706.9	-22646.3	1.1	3708.2
2.72	148.3	375.2	0.0	310.8	12.56	399.7	-28886.7	1.3	-1632.2	22.40	713.1	-22001.7	1.1	3847.0
2.93	153.9	446.8	0.0	344.3	12.77	406.7	-29237.0	1.4	-1543.5	22.60	720.1	-21248.1	1.0	4004.5
3.14	159.5	-128.7	0.0	-4084.9	12.98	412.9	-29532.0	1.4	-1463.3	22.81	726.3	-20552.7	1.0	4145.9
3.35	164.4	-924.7	0.1	-4053.2	13.19	419.9	-29844.9	1.4	-1371.7	23.02	733.3	-19741.3	1.0	4306.4
3.56	170.0	-1812.6	0.1	-4016.3	13.40	426.9	-30137.6	1.4	-1278.6	23.23	739.5	-18994.0	1.0	4450.3
3.77	175.0	-2595.0	0.1	-3982.6	13.60	433.1	-30380.4	1.4	-1194.5	23.44	746.5	-18123.8	0.9	4613.7
3.98	180.6	-3467.2	0.2	-3943.4	13.81	440.1	-30633.8	1.4	-1098.5	23.65	753.5	-17222.1	0.9	4778.6
4.19	185.6	-4235.2	0.2	-3907.6	14.02	446.4	-30841.1	1.4	-1011.8	23.86	759.7	-16393.8	0.9	4926.5
4.40	191.2	-5090.7	0.2	-3866.1	14.23	453.4	-31054.0	1.4	-912.8	24.07	766.7	-15431.6	0.8	5094.3
4.60	196.8	-5936.9	0.3	-3823.4	14.44	459.6	-31224.9	1.4	-823.6	24.28	773.0	-14549.1	0.8	5244.8
4.81	201.8	-6681.2	0.3	-3784.4	14.65	466.6	-31396.1	1.5	-721.7	24.49	780.0	-13525.4	0.8	5415.5
5.02	160.2	-7509.2	0.4	-3740.6	14.86	473.6	-31544.8	1.5	-618.4	24.70	786.2	-12587.8	0.7	5568.5
5.23	166.4	-8237.9	0.4	-3708.6	15.07	479.8	-31657.8	1.5	-525.2	24.91	793.2	-11501.6	0.7	5742.2
5.44	173.4	-9050.0	0.4	-3671.2	15.28	486.8	-31762.9	1.5	-418.9	25.12	-2214.7	-10394.6	0.7	5641.3
5.65	179.6	-9764.8	0.5	-3636.6	15.49	493.0	-31836.6	1.5	-323.1	25.33	-2231.6	-9448.5	0.6	5390.4
5.86	186.6	-10560.8	0.5	-3596.3	15.70	500.0	-31897.1	1.5	-213.9	25.53	-2250.6	-8435.7	0.6	5106.0
6.07	193.6	-11347.8	0.5	-3554.4	15.91	506.2	-31930.5	1.5	-115.5	25.74	-2267.5	-7581.5	0.6	4851.1
6.28	199.9	-12039.5	0.6	-3515.9	16.12	513.2	-31945.0	1.5	-3.4	25.95	-2286.5	-6672.8	0.5	4562.1
6.49	206.9	-12808.5	0.6	-3471.1	16.33	520.2	-31935.9	1.5	110.2	26.16	-2303.4	-5911.9	0.5	4303.1
6.70	213.1	-13483.7	0.6	-3430.0	16.53	526.5	-31909.4	1.5	212.6	26.37	-2322.4	-5109.0	0.5	4009.5
6.91	220.1	-14233.5	0.7	-3382.3	16.74	533.5	-31858.6	1.5	329.1	26.58	-2341.4	-4362.9	0.4	3713.5
7.12	226.3	-14891.1	0.7	-3338.7	16.95	539.7	-31794.5	1.5	434.0	26.79	-2358.3	-3747.6	0.4	3448.4
7.33	233.3	-15620.6	0.7	-3288.1	17.16	546.7	-31700.8	1.5	553.5	27.00	-2377.3	-3109.8	0.4	3147.9
7.53	240.3	-16338.7	0.8	-3236.0	17.37	552.9	-31598.1	1.5	660.9	27.21	-2394.2	-2591.5	0.3	2878.7
7.74	246.5	-16967.4	0.8	-3188.3	17.58	559.9	-31460.5	1.5	783.3	27.42	-2413.3	-2063.7	0.3	2573.6
7.95	253.5	-17663.3	0.8	-3133.3	17.79	566.9	-31299.2	1.4	907.2	27.63	-2430.2	-1644.0	0.3	2300.3
8.16	259.7	-18271.7	0.9	-3083.1	18.00	573.1	-31135.7	1.4	1018.6	27.84	-2449.2	-1227.8	0.2	1990.7
8.37	266.7	-18944.2	0.9	-3025.2	18.21	580.1	-30928.9	1.4	1145.4	28.05	-2468.2	-871.5	0.2	1678.6
8.58	273.0	-19531.2	0.9	-2972.4	18.42	586.3	-30724.5	1.4	1259.4	28.26	-2485.1	-605.3	0.2	1399.1
8.79	279.9	-20179.1	0.9	-2911.5	18.63	593.3	-30471.1	1.4	1389.2	28.47	-2504.1	-363.1	0.1	1082.5
9.00	286.9	-20813.4	1.0	-2849.2	18.84	599.6	-30224.8	1.4	1505.7	28.67	-2521.0	-199.2	0.1	799.0
9.21	293.2	-21365.7	1.0	-2792.4	19.05	606.6	-29923.8	1.4	1638.4	28.88	-2540.0	-72.9	0.1	477.8
9.42	300.2	-21973.5	1.0	-2727.1	19.26	613.5	-29597.1	1.4	1772.5	29.09	-2556.9	-12.6	0.0	190.3
9.63	306.4	-22501.7	1.1	-2667.8	19.47	619.8	-29285.0	1.4	1893.1	29.30	-2573.8	0.0	0.0	0.0



MDOT Sheet Pile Manual







SupportIT, v2.37

© 1997 - 2015, GTSoft Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSoftLtd@aol.com
Web: www.GTSoft.org

Client: Case 5 Anchor in Clay with Sand Backfill

Page: 5
Date: 10.1.18 FOS = 1.5

Sheet: PZ22
Works: Temporary
Pressure: Rankine
Analysis: Gross Pressure



MDOT Sheet Pile Manual

SupportIT, v2.37



© 1997 - 2015, GTSOFT Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSOFT@aol.com
Web: www.GTSOFT.org

Client: Case 5 Anchor in Clay with Sand Backfill

Page: 6
Date: 10.1.18 FOS = 1.5

Sheet: PZ22
Works: Temporary

Pressure: Rankine
Analysis: Gross Pressure



MDOT Sheet Pile Manual

Client: Case 5 Anchor in Clay with Sand Backfill

Page: 7
Date: 10.1.18 FOS = 1.5

Sheet: PZ22
Works: Temporary
Pressure: Rankine
Analysis: Gross Pressure

Design Report

1. Cohesive soil exists below the active water table. MEFD is being applied. Select 'Full Hydrostatic Head' in the 'Pressure' page to apply full hydrostatic pressure.
2. Total stress values are being used (i.e. $C > 0$). Note that the Piling Handbook and CIRIA SP95 recommend that effective stress values be used in 'long term' excavations.
3. Maximum bending moment = 31945.0ftlb/ft and $f = 24966.8$ psi. MINIMUM required sheet section modulus is: $Z = 15.35\text{in}^3/\text{ft}$ ($= M/f$). Sheet section modulus in this design is $Z = 18.40\text{in}^3/\text{ft}$, and is satisfactory.
4. Frame primary axis bending moments checked. Users should manually check the axial load capacities and the effects of combined axial and bending stresses to confirm frames are suitable.
5. FOS = 1.49 (Gross Pressure)
This is the factor of safety against rotation about the lowest frame.
The FOS can be changed using 'Defined FOS' or 'Manual' in the 'Wall' page.



MDOT Sheet Pile Manual

SupportIT, v2.37

© 1997 - 2015, GTSOFT Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSOFT@aol.com
Web: www.GTSOFT.org

Appendix B.6 – SupportIT Output, Case 6

Case 6 – Braced Cofferdam TERS in Soft and Stiff Clay

Client: MDOT Case 6

Site: FOS = 1.00

Page: 1

Date: 10.20.18


Sheet: PZ22

Works: Temporary

Pressure: Rankine

Analysis: Gross Pressure

	Maximum	d (ft)
○	1089.7 psf	15.00
□	10650.4 ftlb/ft	10.94
●	0.1 in	10.36



MDOT Sheet Pile Manual

SupportIT, v2.37

© 1997 - 2015, GTSOFT Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSOFT@aol.com
Web: www.GTSOFT.org



Client: MDOT Case 6
Site: FOS = 1.00

Page: 2
Date: 10.20.18

Sheet: PZ22
Works: Temporary
Pressure: Rankine
Analysis: Gross Pressure

Input Data

Depth Of Excavation = 15.00ft
Surcharge = 360.0psf

Depth Of Active Water = 5.00ft
Depth Of Passive Water = 15.00ft

Water Density = 62.43pcf
Minimum Fluid Density = 31.80pcf

Soil Profile

Depth (ft)	Soil Name	γ (pcf)	γ' (pcf)	C (psf)	C_a (psf)	ϕ (°)	δ (°)	K_a	K_{ac}	K_p	K_{pc}
0.00	Loose Fine Sand	109.20	65.55	0.0	0.0	30.0	0.0	0.33	0.00	3.00	0.00
5.00	Soft Clay	118.37	56.00	500.0	0.0	0.0	0.0	1.00	2.00	1.00	2.00
15.00	Firm Clay	118.37	56.00	1000.0	0.0	0.0	0.0	1.00	2.00	1.00	2.00

Solution

Sheet

Sheet Name	E (psi)	I (in ⁴ /ft)	f (psi)	Z (in ³ /ft)	Allowed M_{max} (ftlb/ft)	b (in)	A (in ² /ft)	W (lb/ft)	Upstand (ft)	Toe (ft)	Length (ft)
PZ22	3.04E+07	84.70	24966.8	18.40	38282.3	22.01	6.46	40.3	0.00	2.42	17.42

Load Model: Area Distribution

Supports

d (ft)	Type	Load (lb/ft)
3.00	Waler	2947.7

Maxima

	Maximum	Depth (ft)
Pressure	1089.7 psf	15.00
Bending Moment	10650.4 ftlb/ft	10.94
Deflection	0.1 in	10.36
Shear Force	3457.4 lb/ft	15.01

MDOT Sheet Pile Manual

SupportIT, v2.37

© 1997 - 2015, GTSOFT Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSOFT@aol.com
Web: www.GTSOFT.org







Client: MDOT Case 6
 Site: FOS = 1.00

Page: 3
 Date: 10.20.18

Sheet: PZ22
 Works: Temporary
 Pressure: Rankine
 Analysis: Gross Pressure

	Maximum	d (ft)
○	1089.7 psf	15.00
□	10650.4 ftlb/ft	10.94
◇	3457.4 lb/ft	15.01
●	0.1 in	10.36



MDOT Sheet Pile Manual

SupportIT, v2.37

© 1997 - 2015, GTSOFT Ltd.
 Tel/Fax: +44 (0)1292 477754
 Email: GTSOFT@aol.com
 Web: www.GTSOFT.org

Client: MDOT Case 6
Site: FOS = 1.00

Page: 4
Date: 10.20.18

Sheet: PZ22
Works: Temporary

Pressure: Rankine
Analysis: Gross Pressure

depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)	depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)	depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)
0.00	118.8	0.3	0.0	0.0	5.85	186.2	-5210.8	0.1	-1754.3	11.70	699.0	-10465.9	0.1	499.6
0.12	123.5	1.2	0.0	15.9	5.97	189.9	-5413.7	0.1	-1732.4	11.82	712.8	-10403.1	0.1	581.7
0.25	127.7	3.8	0.0	30.6	6.10	194.0	-5639.0	0.1	-1707.3	11.94	728.2	-10320.8	0.1	675.9
0.37	132.4	8.7	0.0	47.7	6.22	198.2	-5861.0	0.1	-1681.7	12.07	742.0	-10237.1	0.1	761.4
0.50	136.6	15.1	0.0	63.4	6.35	201.9	-6055.4	0.1	-1658.4	12.19	757.4	-10130.9	0.1	859.4
0.62	141.3	24.4	0.0	81.6	6.47	206.0	-6271.0	0.1	-1631.7	12.32	772.9	-10011.6	0.1	959.5
0.75	145.5	34.7	0.0	98.3	6.59	209.7	-6459.6	0.1	-1607.6	12.44	786.7	-9894.4	0.1	1050.2
0.87	150.2	48.7	0.0	117.8	6.72	213.9	-6668.3	0.1	-1579.9	12.57	802.1	-9749.7	0.1	1154.0
1.00	154.9	65.2	0.0	137.8	6.84	217.6	-6850.9	0.1	-1554.8	12.69	815.9	-9609.5	0.1	1248.1
1.12	159.1	82.2	0.0	156.1	6.97	221.7	-7052.7	0.1	-1526.1	12.82	831.3	-9438.4	0.1	1355.8
1.24	163.8	103.8	0.0	177.3	7.09	225.9	-7250.7	0.1	-1496.8	12.94	845.1	-9274.4	0.1	1453.2
1.37	168.0	125.3	0.0	196.7	7.22	229.6	-7423.5	0.1	-1470.3	13.06	860.5	-9076.0	0.1	1564.7
1.49	172.7	152.3	0.0	219.0	7.34	233.8	-7614.2	0.1	-1440.0	13.19	876.0	-8862.9	0.1	1678.3
1.62	176.9	178.8	0.0	239.4	7.47	237.5	-7780.3	0.1	-1412.6	13.31	889.7	-8660.7	0.1	1780.9
1.74	181.6	211.4	0.0	262.9	7.59	241.6	-7963.4	0.1	-1381.3	13.44	905.2	-8418.8	0.1	1898.3
1.87	186.3	247.2	0.0	287.1	7.71	245.3	-8122.7	0.1	-1353.0	13.56	919.0	-8190.6	0.1	2004.3
1.99	190.5	281.6	0.0	309.1	7.84	249.5	-8297.9	0.1	-1320.7	13.69	934.4	-7919.0	0.1	2125.5
2.12	195.2	323.5	0.0	334.4	7.96	257.4	-8468.8	0.1	-1287.6	13.81	948.2	-7664.0	0.1	2234.9
2.24	199.4	363.4	0.0	357.4	8.09	271.2	-8617.1	0.1	-1256.9	13.93	963.6	-7361.7	0.1	2359.9
2.36	204.1	411.7	0.0	383.8	8.21	286.7	-8779.4	0.1	-1220.3	14.06	979.1	-7042.8	0.1	2486.9
2.49	208.2	457.5	0.0	407.9	8.34	300.4	-8919.7	0.1	-1186.1	14.18	992.8	-6745.1	0.1	2601.5
2.61	213.0	512.3	0.0	435.5	8.46	315.9	-9072.6	0.1	-1145.8	14.31	1008.3	-6394.1	0.1	2732.3
2.74	217.7	570.9	0.0	463.8	8.58	329.6	-9204.0	0.1	-1108.2	14.43	1022.0	-6067.5	0.1	2850.3
2.86	221.8	626.0	0.0	489.4	8.71	345.1	-9346.5	0.1	-1064.0	14.56	1037.5	-5683.4	0.1	2984.9
2.99	226.6	691.7	0.0	518.8	8.83	360.5	-9483.1	0.1	-1017.8	14.68	1051.3	-5327.0	0.1	3106.3
3.11	230.7	453.3	0.0	-2402.3	8.96	374.3	-9599.3	0.1	-975.0	14.81	1066.7	-4908.8	0.1	3244.7
3.23	235.4	140.7	0.0	-2371.8	9.08	389.7	-9724.0	0.1	-925.0	14.93	1082.2	-4472.3	0.1	3385.2
3.36	239.6	-133.9	0.0	-2344.2	9.21	403.5	-9829.3	0.1	-878.9	15.05	-1378.6	-4070.5	0.1	3396.9
3.48	244.3	-438.8	0.0	-2312.6	9.33	419.0	-9941.2	0.1	-825.0	15.18	-1385.9	-3632.9	0.1	3214.0
3.61	249.0	-739.6	0.0	-2280.3	9.46	432.7	-10034.7	0.1	-775.5	15.30	-1392.4	-3264.2	0.1	3050.5
3.73	253.2	-1003.4	0.0	-2251.1	9.58	448.2	-10132.9	0.1	-717.8	15.43	-1399.7	-2872.4	0.1	2865.8
3.86	257.9	-1296.1	0.0	-2217.7	9.70	463.6	-10223.4	0.1	-658.1	15.55	-1406.2	-2544.6	0.1	2700.7
3.98	262.1	-1552.6	0.0	-2187.5	9.83	477.4	-10297.2	0.1	-603.4	15.68	-1413.5	-2199.1	0.1	2514.1
4.11	266.8	-1836.9	0.0	-2152.9	9.95	492.8	-10372.5	0.1	-539.9	15.80	-1420.8	-1878.2	0.1	2326.5
4.23	271.0	-2085.8	0.0	-2121.6	10.08	506.6	-10432.3	0.1	-481.8	15.93	-1427.3	-1613.8	0.0	2159.0
4.35	275.7	-2361.4	0.0	-2085.9	10.20	522.0	-10491.5	0.1	-414.5	16.05	-1434.6	-1339.9	0.0	1969.6
4.48	280.4	-2632.2	0.0	-2049.5	10.33	535.8	-10536.6	0.1	-353.0	16.17	-1441.1	-1117.5	0.0	1800.4
4.60	284.6	-2869.0	0.0	-2016.7	10.45	551.3	-10578.7	0.1	-281.9	16.30	-1448.4	-891.1	0.0	1609.2
4.73	289.3	-3130.8	0.1	-1979.1	10.58	566.7	-10611.3	0.1	-208.7	16.42	-1454.9	-711.0	0.0	1438.4
4.85	293.5	-3359.3	0.1	-1945.3	10.70	580.5	-10632.2	0.1	-142.0	16.55	-1462.2	-532.5	0.0	1245.4
4.98	298.2	-3611.7	0.1	-1906.6	10.82	595.9	-10646.4	0.1	-65.1	16.67	-1469.6	-379.5	0.0	1051.4
5.10	162.2	-3832.3	0.1	-1885.9	10.95	609.7	-10650.4	0.1	5.0	16.80	-1476.1	-265.0	0.0	878.1
5.23	166.3	-4077.9	0.1	-1864.4	11.07	625.1	-10645.0	0.1	85.8	16.92	-1483.4	-160.6	0.0	682.3
5.35	170.5	-4320.6	0.1	-1842.4	11.20	638.9	-10631.2	0.1	159.3	17.05	-1489.9	-89.5	0.0	507.4
5.47	174.2	-4534.0	0.1	-1822.4	11.32	654.3	-10605.2	0.1	243.9	17.17	-1497.2	-34.1	0.0	309.7
5.60	178.3	-4771.1	0.1	-1799.3	11.45	669.8	-10568.0	0.1	330.5	17.29	-1503.7	-6.8	0.0	133.2
5.72	182.0	-4979.4	0.1	-1778.4	11.57	683.6	-10525.2	0.1	409.2	17.42	-1510.2	0.0	0.0	0.0



MDOT Sheet Pile Manual







SupportIT, v2.37

© 1997 - 2015, GTSOFT Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSOFT@aol.com
Web: www.GTSOFT.org

Client: MDOT Case 6
Site: FOS = 1.00

Page: 5
Date: 10.20.18

Sheet: PZ22
Works: Temporary
Pressure: Rankine
Analysis: Gross Pressure



MDOT Sheet Pile Manual

SupportIT, v2.37

© 1997 - 2015, GTSOFT Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSOFT@aol.com
Web: www.GTSOFT.org

Client: MDOT Case 6

Site: FOS = 1.00

Page: 6



Date: 10.20.18

Sheet: PZ22

Works: Temporary

Pressure: Rankine

Analysis: Gross Pressure



MDOT Sheet Pile Manual

SupportIT, v2.37

© 1997 - 2015, GTSoft Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSoftLtd@aol.com
Web: www.GTSoft.org

Client: MDOT Case 6
Site: FOS = 1.00

Page: 7
Date: 10.20.18

Sheet: PZ22
Works: Temporary
Pressure: Rankine
Analysis: Gross Pressure

Design Report

1. Minimum fluid density is 31.8pcf. The Piling Handbook **recommends 31.8pcf**.
2. Cohesive soil exists below the active water table. MEFD is being applied. Select 'Full Hydrostatic Head' in the 'Pressure' page to apply full hydrostatic pressure.
3. Total stress values are being used (i.e. $C > 0$). Note that the Piling Handbook and CIRIA SP95 recommend that effective stress values be used in 'long term' excavations.
4. Maximum bending moment = 10650.4ftlb/ft and $f = 24966.8\text{psi}$. MINIMUM required sheet section modulus is: $Z = 5.12\text{in}^3/\text{ft}$ ($= M/f$). Sheet section modulus in this design is $Z = 18.40\text{in}^3/\text{ft}$, and is satisfactory.
5. Frame primary axis bending moments checked. Users should manually check the axial load capacities and the effects of combined axial and bending stresses to confirm frames are suitable.
6. FOS = 1.00 (Gross Pressure)
This is the factor of safety against rotation about the lowest frame.
The FOS can be changed using 'Defined FOS' or 'Manual' in the 'Wall' page.



MDOT Sheet Pile Manual

SupportIT, v2.37

© 1997 - 2015, GTSoft Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSoftLtd@aol.com
Web: www.GTSoft.org

Client: MDOT Case 6

Site: FOS = 1.50

Page: 1

Date: 10.20.18


Sheet: PZ22

Works: Temporary

Pressure: Rankine

Analysis: Gross Pressure

	Maximum	d (ft)
○	1088.5 psf	15.00
□	10673.5 ftlb/ft	10.95
●	0.2 in	11.05



MDOT Sheet Pile Manual

SupportIT, v2.37

© 1997 - 2015, GTSOFT Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSOFT@aol.com
Web: www.GTSOFT.org



Client: MDOT Case 6
Site: FOS = 1.50

Page: 2
Date: 10.20.18

Sheet: PZ22
Works: Temporary
Pressure: Rankine
Analysis: Gross Pressure

Input Data

Depth Of Excavation = 15.00ft
Surcharge = 360.0psf

Depth Of Active Water = 5.00ft
Depth Of Passive Water = 15.00ft

Water Density = 62.43pcf
Minimum Fluid Density = 31.80pcf

Soil Profile

Depth (ft)	Soil Name	γ (pcf)	γ' (pcf)	C (psf)	C_a (psf)	ϕ (°)	δ (°)	K_a	K_{ac}	K_p	K_{pc}
0.00	Loose Fine Sand	109.20	65.55	0.0	0.0	30.0	0.0	0.33	0.00	3.00	0.00
5.00	Soft Clay	118.37	56.00	500.0	0.0	0.0	0.0	1.00	2.00	1.00	2.00
15.00	Firm Clay	118.37	56.00	1000.0	0.0	0.0	0.0	1.00	2.00	1.00	2.00

Solution

Sheet

Sheet Name	E (psi)	I (in ⁴ /ft)	f (psi)	Z (in ³ /ft)	Allowed M_{max} (ftlb/ft)	b (in)	A (in ² /ft)	W (lb/ft)	Upstand (ft)	Toe (ft)	Length (ft)
PZ22	3.04E+07	84.70	24966.8	18.40	38282.3	22.01	6.46	40.3	0.00	4.38	19.38

Load Model: Area Distribution

Supports

d (ft)	Type	Load (lb/ft)
3.00	Waler	2952.2

Maxima

	Maximum	Depth (ft)
Pressure	1088.5 psf	15.00
Bending Moment	10673.5 ftlb/ft	10.95
Deflection	0.2 in	11.05
Shear Force	3459.5 lb/ft	15.01

MDOT Sheet Pile Manual

SupportIT, v2.37

© 1997 - 2015, GTSOFT Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSOFT@aol.com
Web: www.GTSOFT.org







Client: MDOT Case 6
 Site: FOS = 1.50

Page: 3
 Date: 10.20.18

Sheet: PZ22
 Works: Temporary
 Pressure: Rankine
 Analysis: Gross Pressure

	Maximum	d (ft)
○	1088.5 psf	15.00
□	10673.5 ftlb/ft	10.95
◇	3459.5 lb/ft	15.01
●	0.2 in	11.05



MDOT Sheet Pile Manual



Client: MDOT Case 6

Site: FOS = 1.50

Page: 4

Date: 10.20.18

Sheet: PZ22

Works: Temporary

Pressure: Rankine

Analysis: Gross Pressure

depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)	depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)	depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)
0.00	118.8	0.3	0.0	0.0	6.51	207.2	-6342.2	0.1	-1626.5	13.01	855.2	-9542.6	0.2	1524.8
0.14	124.0	1.4	0.0	17.8	6.65	211.3	-6551.2	0.1	-1599.4	13.15	870.5	-9387.7	0.2	1636.4
0.28	128.7	4.6	0.0	34.2	6.78	215.9	-6782.2	0.1	-1568.3	13.29	887.7	-9200.2	0.2	1764.3
0.42	133.9	10.8	0.0	53.4	6.92	220.5	-7008.5	0.1	-1536.5	13.43	903.0	-9021.6	0.2	1880.2
0.55	138.6	18.7	0.0	71.1	7.06	224.7	-7205.8	0.1	-1507.7	13.57	920.2	-8806.9	0.2	2012.8
0.69	143.8	30.4	0.0	91.7	7.20	229.3	-7423.3	0.1	-1474.7	13.71	937.5	-8577.3	0.2	2148.0
0.83	148.5	43.3	0.0	110.7	7.34	233.4	-7612.5	0.1	-1444.8	13.85	952.8	-8360.6	0.2	2270.3
0.97	153.7	60.8	0.0	132.8	7.48	238.0	-7820.7	0.1	-1410.5	13.98	970.0	-8102.4	0.2	2410.2
1.11	159.0	81.6	0.0	155.7	7.61	242.1	-8001.6	0.1	-1379.4	14.12	985.3	-7859.7	0.2	2536.6
1.25	163.6	102.9	0.0	176.6	7.75	246.8	-8200.2	0.1	-1343.8	14.26	1002.5	-7571.7	0.2	2681.2
1.38	168.9	130.2	0.0	200.9	7.89	251.4	-8393.6	0.2	-1307.6	14.40	1017.8	-7302.2	0.1	2811.9
1.52	173.5	157.4	0.0	223.2	8.03	264.4	-8561.0	0.2	-1274.3	14.54	1035.0	-6983.5	0.1	2961.3
1.66	178.8	191.5	0.0	248.9	8.17	281.6	-8744.0	0.2	-1234.4	14.68	1052.2	-6648.1	0.1	3113.1
1.80	183.4	225.0	0.0	272.5	8.31	296.9	-8901.7	0.2	-1196.9	14.81	1067.5	-6335.8	0.1	3250.2
1.94	188.7	266.3	0.0	299.6	8.45	314.1	-9073.2	0.2	-1152.4	14.95	1084.7	-5968.2	0.1	3406.8
2.08	193.9	311.7	0.0	327.6	8.58	329.4	-9220.1	0.2	-1110.7	15.09	-1380.7	-5630.9	0.1	3389.7
2.22	198.5	355.5	0.0	353.1	8.72	346.6	-9378.7	0.2	-1061.4	15.23	-1388.8	-5260.8	0.1	3282.2
2.35	203.8	408.7	0.0	382.5	8.86	363.9	-9529.9	0.2	-1009.6	15.37	-1396.0	-4941.9	0.1	3186.1
2.49	208.4	459.6	0.0	409.3	9.00	379.1	-9657.9	0.2	-961.5	15.51	-1404.2	-4594.4	0.1	3077.4
2.63	213.7	521.1	0.0	440.1	9.14	396.4	-9794.3	0.2	-905.0	15.65	-1412.3	-4259.0	0.1	2968.0
2.77	218.3	579.5	0.0	468.1	9.28	411.7	-9908.5	0.2	-852.6	15.78	-1419.5	-3971.1	0.1	2870.3
2.91	223.6	649.7	0.0	500.4	9.41	428.9	-10028.8	0.2	-791.4	15.92	-1427.7	-3658.6	0.1	2759.8
3.05	228.8	581.3	0.0	-2418.8	9.55	444.2	-10128.1	0.2	-734.9	16.06	-1434.9	-3391.2	0.1	2661.0
3.18	233.5	269.8	0.0	-2388.9	9.69	461.4	-10230.8	0.2	-668.9	16.20	-1443.0	-3102.1	0.1	2549.3
3.32	238.7	-75.9	0.0	-2354.5	9.83	478.6	-10323.9	0.2	-600.5	16.34	-1450.2	-2855.4	0.1	2449.4
3.46	243.4	-378.9	0.0	-2323.3	9.97	493.9	-10398.1	0.2	-537.5	16.48	-1458.4	-2589.7	0.1	2336.5
3.60	248.6	-715.0	0.0	-2287.5	10.11	511.1	-10471.6	0.2	-464.3	16.61	-1466.5	-2336.6	0.1	2223.0
3.74	253.3	-1009.3	0.0	-2255.1	10.25	526.4	-10528.0	0.2	-397.2	16.75	-1473.7	-2122.1	0.1	2121.5
3.88	258.5	-1335.3	0.0	-2217.8	10.38	543.6	-10580.8	0.2	-319.2	16.89	-1481.8	-1892.8	0.1	2006.8
4.02	263.7	-1655.9	0.0	-2179.8	10.52	558.9	-10618.1	0.2	-247.9	17.03	-1489.1	-1699.7	0.1	1904.3
4.15	268.4	-1936.1	0.0	-2145.4	10.66	576.1	-10648.9	0.2	-165.3	17.17	-1497.2	-1494.5	0.1	1788.4
4.29	273.6	-2246.1	0.0	-2105.9	10.80	593.3	-10667.5	0.2	-80.1	17.31	-1504.4	-1322.9	0.1	1684.8
4.43	278.3	-2516.7	0.1	-2070.2	10.94	608.6	-10673.5	0.2	-2.3	17.45	-1512.5	-1142.1	0.1	1567.7
4.57	283.5	-2815.6	0.1	-2029.4	11.08	625.8	-10669.3	0.2	87.5	17.58	-1520.7	-974.3	0.1	1449.9
4.71	288.2	-3076.2	0.1	-1992.4	11.21	641.1	-10657.2	0.2	169.5	17.72	-1527.9	-836.1	0.1	1344.8
4.85	293.4	-3363.6	0.1	-1950.1	11.35	658.3	-10633.8	0.2	264.1	17.86	-1536.0	-693.0	0.0	1225.8
4.98	298.7	-3644.9	0.1	-1907.0	11.49	673.6	-10604.1	0.2	350.3	18.00	-1543.2	-577.0	0.0	1119.6
5.12	163.0	-3890.3	0.1	-1883.9	11.63	690.8	-10560.4	0.2	449.6	18.14	-1551.4	-458.9	0.0	999.4
5.26	167.6	-4163.1	0.1	-1859.8	11.77	708.0	-10505.7	0.2	551.4	18.28	-1558.6	-365.1	0.0	892.1
5.40	171.7	-4402.7	0.1	-1837.9	11.91	723.3	-10447.4	0.2	644.0	18.41	-1566.7	-272.3	0.0	770.8
5.54	176.3	-4668.7	0.1	-1812.6	12.05	740.5	-10370.9	0.2	750.6	18.55	-1574.9	-192.9	0.0	648.9
5.68	180.4	-4902.1	0.1	-1789.5	12.18	755.8	-10292.8	0.2	847.4	18.69	-1582.1	-133.7	0.0	539.9
5.82	185.1	-5161.0	0.1	-1762.9	12.32	773.0	-10193.5	0.2	958.6	18.83	-1590.2	-80.0	0.0	416.8
5.95	189.7	-5416.0	0.1	-1735.6	12.46	788.3	-10094.9	0.2	1059.6	18.97	-1597.4	-43.7	0.0	306.8
6.09	193.8	-5639.3	0.1	-1710.8	12.60	805.5	-9971.8	0.2	1175.6	19.11	-1605.6	-15.9	0.0	182.5
6.23	198.4	-5886.6	0.1	-1682.2	12.74	822.7	-9835.8	0.2	1294.1	19.25	-1612.8	-2.7	0.0	71.4
6.37	202.6	-6102.9	0.1	-1656.3	12.88	838.0	-9703.8	0.2	1401.6	19.38	-1620.0	0.0	0.0	0.0



MDOT Sheet Pile Manual







SupportIT, v2.37

© 1997 - 2015, GTSoft Ltd.
 Tel/Fax: +44 (0)1292 477754
 Email: GTSoftLtd@aol.com
 Web: www.GTSoft.org

Client: MDOT Case 6
Site: FOS = 1.50

Page: 5
Date: 10.20.18

Sheet: PZ22
Works: Temporary
Pressure: Rankine
Analysis: Gross Pressure



MDOT Sheet Pile Manual

SupportIT, v2.37

© 1997 - 2015, GTSOFT Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSOFT@aol.com
Web: www.GTSOFT.org

Client: MDOT Case 6

Site: FOS = 1.50

Page: 6



Date: 10.20.18

Sheet: PZ22

Works: Temporary

Pressure: Rankine

Analysis: Gross Pressure



MDOT Sheet Pile Manual

SupportIT, v2.37

© 1997 - 2015, GTSoft Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSoftLtd@aol.com
Web: www.GTSoft.org

Client: MDOT Case 6
Site: FOS = 1.50

Page: 7
Date: 10.20.18

Sheet: PZ22
Works: Temporary
Pressure: Rankine
Analysis: Gross Pressure

Design Report

1. Minimum fluid density is 31.8pcf. The Piling Handbook **recommends 31.8pcf**.
2. Cohesive soil exists below the active water table. MEFD is being applied. Select 'Full Hydrostatic Head' in the 'Pressure' page to apply full hydrostatic pressure.
3. Total stress values are being used (i.e. $C > 0$). Note that the Piling Handbook and CIRIA SP95 recommend that effective stress values be used in 'long term' excavations.
4. Maximum bending moment = 10673.5ftlb/ft and $f = 24966.8\text{psi}$. MINIMUM required sheet section modulus is: $Z = 5.13\text{in}^3/\text{ft}$ ($= M/f$). Sheet section modulus in this design is $Z = 18.40\text{in}^3/\text{ft}$, and is satisfactory.
5. Frame primary axis bending moments checked. Users should manually check the axial load capacities and the effects of combined axial and bending stresses to confirm frames are suitable.
6. FOS = 1.51 (Gross Pressure)
This is the factor of safety against rotation about the lowest frame.
The FOS can be changed using 'Defined FOS' or 'Manual' in the 'Wall' page.



MDOT Sheet Pile Manual

SupportIT, v2.37

© 1997 - 2015, GTSoft Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSoftLtd@aol.com
Web: www.GTSoft.org

Appendix B.7 – SupportIT Output, Case 7

Case 7 – Braced Cofferdam TERS in Cohesionless Soil

SupportIT output is included here for the four stages of construction.

Client: Case 7 - Stage 1 - 8 ft

Site: FOS = 1.0

Page: 1

Date: 3.5.19

Sheet: PZ22


Works: Temporary

Pressure: Rankine

Analysis: Gross Pressure

Toe: Cantilever

	Maximum	d (ft)
○	409.2 psf	8.00
□	14954.8 ftlb/ft	12.80
●	0.9 in	0.00



MDOT Sheetpile Manual

SupportIT, v2.37

© 1997 - 2015, GTSOFT Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSOFT@aol.com
Web: www.GTSOFT.org

Client: Case 7 - Stage 1 - 8 ft
 Site: FOS = 1.0

Page: 2
 Date: 3.5.19

Sheet: PZ22
 Works: Temporary
 Pressure: Rankine
 Analysis: Gross Pressure
 Toe: Cantilever

Input Data

Depth Of Excavation = 8.00ft
 Surcharge = 359.9psf

Depth Of Active Water = 30.00ft
 Depth Of Passive Water = 30.00ft

Water Density = 62.43pcf
 Minimum Fluid Density = 31.82pcf

Soil Profile

Depth (ft)	Soil Name	γ (pcf)	γ' (pcf)	C (psf)	C_a (psf)	ϕ (°)	δ (°)	K_a	K_{ac}	K_p	K_{pc}
0.00	Dense Coarse Sand	120.00	71.10	0.0	0.0	32.0	0.0	0.31	0.00	3.25	0.00

Solution

Sheet

Sheet Name	E (psi)	I (in ⁴ /ft)	f (psi)	Z (in ³ /ft)	Allowed M_{max} (ftlb/ft)	b (in)	A (in ² /ft)	W (lb/ft)	Upstand (ft)	Toe (ft)	Length (ft)
PZ22	3.04E+07	84.70	24966.8	18.40	38282.3	22.01	6.46	40.3	0.00	10.69	18.69

Maxima

	Maximum	Depth (ft)
Pressure	409.2 psf	8.00
Bending Moment	14954.8 ftlb/ft	12.80
Deflection	0.9 in	0.00
Shear Force	2321.3 lb/ft	9.16



MDOT Sheetpile Manual

SupportIT, v2.37

© 1997 - 2015, GTSoft Ltd.
 Tel/Fax: +44 (0)1292 477754
 Email: GTSoftLtd@aol.com
 Web: www.GTSoft.org

Client: Case 7 - Stage 1 - 8 ft

Site: FOS = 1.0

Page: 3

Date: 3.5.19

Sheet: PZ22





Works: Temporary

Pressure: Rankine

Analysis: Gross Pressure

Toe: Cantilever

	Maximum	d (ft)
○	409.2 psf	8.00
□	14954.8 ftlb/ft	12.80
◇	2321.3 lb/ft	9.16
●	0.9 in	0.00



MDOT Sheetpile Manual

SupportIT, v2.37

© 1997 - 2015, GTSOFT Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSoftLtd@aol.com
Web: www.GTSOFT.org

Client: Case 7 - Stage 1 - 8 ft

Site: FOS = 1.0

Page: 4

Date: 3.5.19

Sheet: PZ22

Works: Temporary

Pressure: Rankine

Analysis: Gross Pressure

Toe: Cantilever

depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)	depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)	depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)
0.00	111.6	0.0	0.9	0.0	6.27	345.0	3717.6	0.4	1435.7	12.55	-1196.7	14915.8	0.1	301.0
0.13	116.8	1.0	0.9	16.0	6.41	349.7	3898.4	0.4	1479.1	12.68	-1240.6	14945.0	0.1	149.5
0.27	121.4	3.8	0.9	30.9	6.54	354.9	4108.3	0.4	1528.5	12.81	-1290.1	14954.8	0.1	-16.1
0.40	126.6	9.2	0.9	48.3	6.67	360.1	4325.1	0.4	1578.7	12.95	-1334.0	14932.4	0.0	-141.7
0.53	131.3	16.1	0.9	64.5	6.81	364.7	4523.7	0.4	1623.9	13.08	-1383.5	14861.2	0.0	-276.4
0.67	136.5	26.2	0.8	83.3	6.94	370.0	4753.9	0.4	1675.5	13.21	-1432.9	14743.6	0.0	-404.3
0.80	141.1	37.5	0.8	100.6	7.07	374.6	4964.7	0.4	1721.9	13.35	-1476.9	14602.1	0.0	-512.1
0.93	146.3	52.8	0.8	120.8	7.21	379.8	5208.7	0.3	1774.9	13.48	-1526.3	14403.5	0.0	-626.8
1.07	151.6	71.0	0.8	141.7	7.34	384.4	5431.8	0.3	1822.6	13.62	-1570.3	14193.9	0.0	-723.0
1.20	156.2	89.7	0.8	161.0	7.47	389.7	5690.0	0.3	1876.9	13.75	-1619.7	13923.0	0.0	-824.6
1.33	161.4	113.5	0.8	183.3	7.61	394.9	5955.8	0.3	1932.0	13.88	-1663.7	13653.1	0.0	-909.2
1.47	166.0	137.4	0.8	203.7	7.74	399.5	6198.6	0.3	1981.5	14.02	-1713.1	13318.7	0.0	-997.7
1.60	171.3	167.4	0.8	227.4	7.88	404.7	6479.1	0.3	2038.0	14.15	-1762.6	12954.3	0.0	-1079.3
1.74	175.9	196.8	0.8	249.1	8.01	409.2	6735.1	0.3	2088.7	14.28	-1806.5	12607.0	0.0	-1146.1
1.87	181.1	233.2	0.8	274.2	8.14	358.2	7030.5	0.3	2142.1	14.42	-1856.0	12192.3	0.0	-1214.6
2.00	186.3	273.1	0.7	300.0	8.28	314.2	7299.0	0.3	2183.7	14.55	-1899.9	11804.2	0.0	-1269.7
2.14	190.9	311.7	0.7	323.5	8.41	264.8	7606.9	0.3	2223.9	14.68	-1949.4	11348.0	0.0	-1325.1
2.27	196.2	358.6	0.7	350.7	8.54	215.3	7919.9	0.3	2257.2	14.82	-1993.3	10927.0	0.0	-1368.6
2.40	200.8	403.5	0.7	375.5	8.68	171.4	8201.8	0.3	2281.0	14.95	-2042.8	10438.0	0.0	-1411.0
2.54	206.0	457.8	0.7	404.1	8.81	121.9	8522.0	0.2	2301.1	15.08	-2092.2	9935.1	0.0	-1446.4
2.67	210.6	509.4	0.7	430.1	8.94	78.0	8808.7	0.2	2313.3	15.22	-2136.2	9478.5	0.0	-1472.0
2.80	215.9	571.4	0.7	460.0	9.08	28.5	9132.6	0.2	2320.3	15.35	-2185.6	8956.2	0.0	-1494.4
2.94	221.1	637.6	0.7	490.7	9.21	-15.4	9421.0	0.2	2321.0	15.48	-2229.6	8486.2	0.0	-1508.4
3.07	225.7	700.1	0.7	518.6	9.34	-64.9	9745.3	0.2	2315.7	15.62	-2279.0	7953.1	0.0	-1517.7
3.20	230.9	774.6	0.6	550.7	9.48	-114.3	10068.3	0.2	2303.6	15.75	-2323.0	7477.4	0.0	-1520.0
3.34	235.6	844.6	0.6	579.8	9.61	-158.3	10353.8	0.2	2286.9	15.88	-2372.4	6942.3	0.0	-1516.2
3.47	240.8	927.7	0.6	613.2	9.74	-207.7	10672.0	0.2	2261.7	16.02	-2421.9	6409.6	0.0	-1505.4
3.60	245.4	1005.5	0.6	643.6	9.88	-251.7	10951.6	0.2	2233.4	16.15	-2465.8	5940.1	0.0	-1490.0
3.74	250.6	1097.7	0.6	678.4	10.01	-301.1	11261.5	0.2	2195.0	16.28	-2515.3	5418.7	0.0	-1466.1
3.87	255.8	1194.7	0.6	714.0	10.14	-345.1	11532.1	0.2	2155.1	16.42	-2559.2	4963.2	0.0	-1439.1
4.00	260.5	1285.2	0.6	746.2	10.28	-394.5	11830.3	0.2	2103.7	16.55	-2608.7	4461.8	0.0	-1402.1
4.14	265.7	1391.8	0.6	783.1	10.41	-444.0	12120.9	0.1	2045.3	16.69	-2652.6	4027.8	0.0	-1363.5
4.27	270.3	1490.9	0.6	816.6	10.55	-487.9	12372.0	0.1	1987.6	16.82	-2702.1	3555.1	0.0	-1313.4
4.40	275.5	1607.5	0.6	854.9	10.68	-537.4	12645.5	0.1	1916.1	16.95	-2751.5	3101.1	0.0	-1256.4
4.54	280.2	1715.6	0.5	889.6	10.81	-581.3	12879.9	0.1	1846.8	17.09	-2795.5	2715.2	0.0	-1200.0
4.67	285.4	1842.4	0.5	929.3	10.95	-630.8	13132.9	0.1	1762.2	17.22	-2844.9	2303.3	0.0	-1129.9
4.81	290.6	1974.8	0.5	969.7	11.08	-674.7	13347.5	0.1	1681.2	17.35	-2888.9	1958.6	0.0	-1061.8
4.94	295.2	2097.3	0.5	1006.3	11.21	-724.2	13576.6	0.1	1583.6	17.49	-2938.3	1597.4	0.0	-978.6
5.07	300.4	2240.6	0.5	1048.1	11.35	-773.6	13791.5	0.1	1479.0	17.62	-2982.3	1301.7	0.0	-898.9
5.21	305.1	2372.9	0.5	1085.9	11.48	-817.6	13970.0	0.1	1380.2	17.75	-3031.7	999.9	0.0	-802.6
5.34	310.3	2527.3	0.5	1129.1	11.61	-867.0	14155.8	0.1	1262.6	17.89	-3081.2	733.1	0.0	-699.4
5.47	314.9	2669.8	0.5	1168.1	11.75	-911.0	14306.7	0.1	1152.1	18.02	-3125.1	527.2	0.0	-601.9
5.61	320.1	2835.8	0.5	1212.6	11.88	-960.4	14459.7	0.1	1021.4	18.15	-3174.6	333.2	0.0	-485.6
5.74	325.3	3008.2	0.5	1258.0	12.01	-1004.4	14580.1	0.1	899.3	18.29	-3218.5	195.9	0.0	-376.5
5.87	330.0	3166.7	0.4	1298.8	12.15	-1053.8	14697.0	0.1	755.5	18.42	-3268.0	83.4	0.0	-247.1
6.01	335.2	3351.2	0.4	1345.5	12.28	-1103.3	14793.3	0.1	604.7	18.55	-3311.9	22.4	0.0	-126.3
6.14	339.8	3520.7	0.4	1387.7	12.41	-1147.2	14860.9	0.1	464.9	18.69	-3355.9	0.0	0.0	0.0



MDOT Sheeppile Manual

SupportIT, v2.37



© 1997 - 2015, GTSoft Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSoftLtd@aol.com
Web: www.GTSoft.org

Client: Case 7 - Stage 1 - 8 ft

Site: FOS = 1.0

Page: 5

Date: 3.5.19







Sheet: PZ22

Works: Temporary

Pressure: Rankine

Analysis: Gross Pressure

Toe: Cantilever



MDOT Sheetpile Manual

SupportIT, v2.37

© 1997 - 2015, GTSOFT Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSOFT@aol.com
Web: www.GTSOFT.org

Client: Case 7 - Stage 1 - 8 ft
Site: FOS = 1.0


Page: 6
Date: 3.5.19

Sheet: PZ22
Works: Temporary
Pressure: Rankine
Analysis: Gross Pressure
Toe: Cantilever

Δ

B

▽



MDOT Sheetpile Manual

Client: Case 7 - Stage 1 - 8 ft
Site: FOS = 1.0

Page: 7
Date: 3.5.19

Sheet: PZ22
Works: Temporary
Pressure: Rankine
Analysis: Gross Pressure
Toe: Cantilever

Design Report

1. Maximum bending moment = 14954.8ftlb/ft and $f = 24966.8\text{psi}$. MINIMUM required sheet section modulus is: $Z = 7.19\text{in}^3/\text{ft}$ ($= M/f$).
Sheet section modulus in this design is $Z = 18.40\text{in}^3/\text{ft}$, and is satisfactory.
2. FOS = 1.00 (Gross Pressure)
This is the factor of safety against rotation about the toe.
The FOS can be changed using 'Defined FOS' or 'Manual' in the 'Wall' page.



MDOT Sheetpile Manual

SupportIT, v2.37

© 1997 - 2015, GTSoft Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSoftLtd@aol.com
Web: www.GTSoft.org

Client: Case 7 - Stage 1 - 10 ft

Site: FOS = 1.0

Page: 1

Date: 3.5.19

Sheet: PZ22


Works: Temporary

Pressure: Rankine

Analysis: Gross Pressure

Toe: Cantilever

	Maximum	d (ft)
○	483.3 psf	10.00
□	25708.0 ftlb/ft	15.71
●	2.3 in	0.00



MDOT Sheetpile Manual

SupportIT, v2.37

© 1997 - 2015, GTSOFT Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSOFT@aol.com
Web: www.GTSOFT.org

Client: Case 7 - Stage 1 - 10 ft
 Site: FOS = 1.0

Page: 2
 Date: 3.5.19

Sheet: PZ22
 Works: Temporary
 Pressure: Rankine
 Analysis: Gross Pressure
 Toe: Cantilever

Input Data

Depth Of Excavation = 10.00ft
 Surcharge = 359.9psf

Depth Of Active Water = 30.00ft
 Depth Of Passive Water = 30.00ft

Water Density = 62.43pcf
 Minimum Fluid Density = 31.82pcf

Soil Profile

Depth (ft)	Soil Name	γ (pcf)	γ' (pcf)	C (psf)	C_a (psf)	ϕ (°)	δ (°)	K_a	K_{ac}	K_p	K_{pc}
0.00	Dense Coarse Sand	120.00	71.10	0.0	0.0	32.0	0.0	0.31	0.00	3.25	0.00

Solution

Sheet

Sheet Name	E (psi)	I (in ⁴ /ft)	f (psi)	Z (in ³ /ft)	Allowed M_{max} (ftlb/ft)	b (in)	A (in ² /ft)	W (lb/ft)	Upstand (ft)	Toe (ft)	Length (ft)
PZ22	3.04E+07	84.70	24966.8	18.40	38282.3	22.01	6.46	40.3	0.00	12.80	22.80

Maxima

	Maximum	Depth (ft)
Pressure	483.3 psf	10.00
Bending Moment	25708.0 ftlb/ft	15.71
Deflection	2.3 in	0.00
Shear Force	3308.4 lb/ft	11.36



MDOT Sheetpile Manual

SupportIT, v2.37

© 1997 - 2015, GTSoft Ltd.
 Tel/Fax: +44 (0)1292 477754
 Email: GTSoftLtd@aol.com
 Web: www.GTSoft.org

Client: Case 7 - Stage 1 - 10 ft

Site: FOS = 1.0

Page: 3

Date: 3.5.19

Sheet: PZ22





Works: Temporary

Pressure: Rankine

Analysis: Gross Pressure

Toe: Cantilever

	Maximum	d (ft)
○	483.3 psf	10.00
□	25708.0 ftlb/ft	15.71
◇	3308.4 lb/ft	11.36
●	2.3 in	0.00



MDOT Sheetpile Manual

Client: Case 7 - Stage 1 - 10 ft

Site: FOS = 1.0

Page: 4

Date: 3.5.19

Sheet: PZ22

Works: Temporary

Pressure: Rankine

Analysis: Gross Pressure

Toe: Cantilever

depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)	depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)	depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)
0.00	111.6	0.0	2.3	0.0	7.65	396.4	6032.4	1.1	1948.4	15.31	-1390.5	25585.5	0.2	581.6
0.16	117.9	1.5	2.3	19.6	7.82	402.0	6331.8	1.0	2009.1	15.47	-1444.1	25659.5	0.1	366.7
0.33	123.6	5.7	2.2	38.0	7.98	408.4	6679.7	1.0	2078.5	15.63	-1504.4	25703.1	0.1	115.2
0.49	130.0	13.8	2.2	59.8	8.14	414.8	7039.5	1.0	2149.0	15.79	-1558.0	25701.3	0.1	-93.7
0.65	135.6	24.2	2.2	80.0	8.30	420.4	7369.5	1.0	2212.6	15.96	-1618.3	25623.0	0.1	-297.1
0.81	142.0	39.6	2.2	103.9	8.47	426.8	7752.3	0.9	2285.1	16.12	-1678.6	25460.4	0.1	-490.2
0.98	147.6	56.8	2.1	125.9	8.63	432.4	8103.0	0.9	2350.5	16.28	-1732.3	25248.8	0.1	-653.2
1.14	154.0	80.2	2.1	151.8	8.79	438.8	8509.5	0.9	2425.1	16.45	-1792.6	24939.0	0.1	-826.8
1.30	160.3	108.2	2.1	178.7	8.96	444.4	8881.6	0.9	2492.3	16.61	-1846.2	24603.5	0.1	-972.5
1.47	166.0	136.9	2.0	203.6	9.12	450.8	9312.4	0.8	2568.9	16.77	-1906.5	24162.2	0.1	-1126.6
1.63	172.4	173.8	2.0	232.6	9.28	457.2	9756.4	0.8	2646.6	16.93	-1960.1	23716.6	0.1	-1254.9
1.79	178.0	210.8	2.0	259.3	9.44	462.8	10162.3	0.8	2716.7	17.10	-2020.5	23159.3	0.1	-1389.6
1.95	184.4	257.4	2.0	290.4	9.61	469.2	10631.6	0.8	2796.4	17.26	-2080.8	22546.9	0.1	-1513.9
2.12	190.0	303.3	1.9	318.9	9.77	474.8	11060.3	0.8	2868.3	17.42	-2134.4	21959.9	0.0	-1615.8
2.28	196.4	360.2	1.9	352.0	9.93	481.2	11555.7	0.7	2950.1	17.59	-2194.7	21255.3	0.0	-1720.6
2.44	202.7	422.8	1.9	386.2	10.10	487.6	12007.8	0.7	3022.1	17.75	-2248.3	20593.3	0.0	-1805.2
2.61	208.4	483.4	1.9	417.5	10.26	494.0	12528.8	0.7	3093.8	17.91	-2308.7	19812.2	0.0	-1890.5
2.77	214.8	557.3	1.8	453.8	10.42	500.4	13061.2	0.7	3155.2	18.07	-2362.3	19089.0	0.0	-1957.8
2.93	220.4	628.3	1.8	486.9	10.58	506.8	13542.7	0.6	3201.1	18.24	-2422.6	18247.0	0.0	-2023.7
3.09	226.8	714.2	1.8	525.2	10.75	513.2	14091.9	0.6	3243.0	18.40	-2482.9	17378.9	0.0	-2079.2
3.26	232.4	796.2	1.8	560.2	10.91	519.6	14585.6	0.6	3271.6	18.56	-2536.5	16589.1	0.0	-2120.0
3.42	238.8	894.8	1.7	600.6	11.07	526.0	15145.4	0.6	3294.0	18.73	-2596.9	15683.9	0.0	-2156.1
3.58	245.2	1000.3	1.7	642.0	11.24	532.4	15645.6	0.6	3305.3	18.89	-2650.5	14868.0	0.0	-2179.5
3.75	250.8	1100.1	1.7	679.8	11.40	538.8	16209.7	0.5	3308.3	19.05	-2710.8	13941.3	0.0	-2196.1
3.91	257.2	1219.4	1.7	723.3	11.56	545.2	16773.6	0.5	3302.1	19.21	-2764.4	13113.1	0.0	-2202.2
4.07	262.8	1331.6	1.6	762.9	11.72	551.6	17273.3	0.5	3287.9	19.38	-2824.7	12180.5	0.0	-2199.4
4.23	269.2	1465.2	1.6	808.5	11.89	558.0	17832.2	0.5	3262.1	19.54	-2885.1	11250.9	0.0	-2186.2
4.40	274.8	1590.5	1.6	849.9	12.05	564.4	18324.8	0.5	3230.6	19.70	-2938.7	10430.9	0.0	-2165.8
4.56	281.2	1739.0	1.6	897.5	12.21	570.8	18872.5	0.4	3185.4	19.87	-2999.0	9519.3	0.0	-2133.2
4.72	287.6	1895.8	1.5	946.2	12.38	577.2	19352.2	0.4	3136.5	20.03	-3052.6	8722.0	0.0	-2095.5
4.89	293.2	2042.1	1.5	990.4	12.54	583.6	19882.4	0.4	3071.8	20.19	-3112.9	7843.9	0.0	-2043.3
5.05	299.6	2214.9	1.5	1041.2	12.70	590.0	20400.7	0.4	2996.8	20.35	-3166.6	7083.3	0.0	-1988.3
5.21	305.2	2375.8	1.4	1087.3	12.86	596.4	20850.1	0.4	2921.5	20.52	-3226.9	6254.2	0.0	-1916.7
5.37	311.6	2565.2	1.4	1140.1	13.03	602.8	21341.4	0.4	2827.0	20.68	-3287.2	5457.3	0.0	-1834.8
5.54	317.2	2741.2	1.4	1187.9	13.19	609.2	21763.9	0.3	2734.3	20.84	-3340.8	4779.7	0.0	-1753.3
5.70	323.6	2947.9	1.4	1242.8	13.35	615.6	22221.7	0.3	2620.3	21.01	-3401.1	4055.7	0.0	-1651.9
5.86	330.0	3164.1	1.3	1298.8	13.52	622.0	22611.8	0.3	2510.4	21.17	-3454.8	3449.8	0.0	-1553.1
6.02	335.6	3364.4	1.3	1349.5	13.68	628.4	23029.9	0.3	2376.9	21.33	-3515.1	2814.3	0.0	-1432.2
6.19	342.0	3598.9	1.3	1407.5	13.84	634.8	23424.5	0.3	2233.1	21.49	-3568.7	2293.9	0.0	-1316.0
6.35	347.6	3815.7	1.3	1460.0	14.00	641.2	23754.1	0.3	2096.7	21.66	-3629.0	1762.5	0.0	-1175.7
6.51	354.0	4069.3	1.2	1520.0	14.17	647.6	24099.5	0.2	1933.4	21.82	-3689.3	1292.6	0.0	-1025.0
6.68	359.6	4303.3	1.2	1574.4	14.33	654.0	24382.5	0.2	1779.7	21.98	-3742.9	929.9	0.0	-882.4
6.84	366.0	4576.5	1.2	1636.5	14.49	660.4	24672.3	0.2	1596.9	22.15	-3803.3	587.8	0.0	-712.2
7.00	372.4	4860.4	1.2	1699.7	14.66	666.8	24903.1	0.2	1425.9	22.31	-3856.9	345.7	0.0	-552.3
7.16	378.0	5121.8	1.1	1756.8	14.82	673.2	25131.1	0.2	1223.7	22.47	-3917.2	147.1	0.0	-362.6
7.33	384.4	5426.4	1.1	1822.1	14.98	679.6	25323.9	0.2	1011.1	22.63	-3970.8	39.5	0.0	-185.4
7.49	390.0	5706.5	1.1	1881.0	15.14	686.0	25464.2	0.2	813.6	22.80	-4024.4	0.0	0.0	0.0



MDOT Sheeppile Manual

SupportIT, v2.37

© 1997 - 2015, GTSoft Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSoftLtd@aol.com
Web: www.GTSoft.org

Client: Case 7 - Stage 1 - 10 ft

Site: FOS = 1.0

Page: 5

Date: 3.5.19







Sheet: PZ22

Works: Temporary

Pressure: Rankine

Analysis: Gross Pressure

Toe: Cantilever



MDOT Sheetpile Manual

SupportIT, v2.37

© 1997 - 2015, GTSOFT Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSOFT@aol.com
Web: www.GTSOFT.org

Client: Case 7 - Stage 1 - 10 ft
Site: FOS = 1.0

Page: 6
Date: 3.5.19

Sheet: PZ22
Works: Temporary
Pressure: Rankine
Analysis: Gross Pressure
Toe: Cantilever



B



MDOT Sheetpile Manual

SupportIT, v2.37

© 1997 - 2015, GTSoft Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSoftLtd@aol.com
Web: www.GTSoft.org

Client: Case 7 - Stage 1 - 10 ft
Site: FOS = 1.0

Page: 7
Date: 3.5.19

Sheet: PZ22
Works: Temporary
Pressure: Rankine
Analysis: Gross Pressure
Toe: Cantilever

Design Report

1. Maximum bending moment = 25708.0ftlb/ft and $f = 24966.8\text{psi}$. MINIMUM required sheet section modulus is: $Z = 12.36\text{in}^3/\text{ft}$ ($= M/f$).
Sheet section modulus in this design is $Z = 18.40\text{in}^3/\text{ft}$, and is satisfactory.
2. FOS = 1.00 (Gross Pressure)
This is the factor of safety against rotation about the toe.
The FOS can be changed using 'Defined FOS' or 'Manual' in the 'Wall' page.



MDOT Sheetpile Manual

SupportIT, v2.37

© 1997 - 2015, GTSoft Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSoftLtd@aol.com
Web: www.GTSoft.org

Client: Case 7 - Stage 2

Site: FOS = 1.0

Page: 1

Date: 3.5.19


Sheet: PZ22

Works: Temporary

Pressure: Rankine

Analysis: Gross Pressure

	Maximum	d (ft)
○	781.2 psf	18.00
□	26669.4 ftlb/ft	13.60
●	0.9 in	13.74



MDOT Sheetpile Manual

SupportIT, v2.37

© 1997 - 2015, GTSOFT Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSOFT@aol.com
Web: www.GTSOFT.org

Client: Case 7 - Stage 2

Site: FOS = 1.0

Page: 2

Date: 3.5.19

Sheet: PZ22

Works: Temporary

Pressure: Rankine

Analysis: Gross Pressure

Input Data

Depth Of Excavation = 18.00ft
Surcharge = 359.9psf

Depth Of Active Water = 30.00ft
Depth Of Passive Water = 30.00ft

Water Density = 62.43pcf
Minimum Fluid Density = 31.82pcf

Soil Profile

Depth (ft)	Soil Name	γ (pcf)	γ' (pcf)	C (psf)	C_a (psf)	ϕ (°)	δ (°)	K_a	K_{ac}	K_p	K_{pc}
0.00	Dense Coarse Sand	120.00	71.10	0.0	0.0	32.0	0.0	0.31	0.00	3.25	0.00

Solution

Sheet

Sheet Name	E (psi)	I (in ⁴ /ft)	f (psi)	Z (in ³ /ft)	Allowed M_{max} (ftlb/ft)	b (in)	A (in ² /ft)	W (lb/ft)	Upstand (ft)	Toe (ft)	Length (ft)
PZ22	3.04E+07	84.70	24966.8	18.40	38282.3	22.01	6.46	40.3	0.00	6.95	24.95

Load Model: Area Distribution

Supports

d (ft)	Type	Load (lb/ft)
3.00	Waler	4960.7

Maxima

	Maximum	Depth (ft)
Pressure	781.2 psf	18.00
Bending Moment	26669.4 ftlb/ft	13.60
Deflection	0.9 in	13.74
Shear Force	4456.4 lb/ft	3.00



MDOT Sheetpile Manual

SupportIT, v2.37

© 1997 - 2015, GTSOFT Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSOFT@aol.com
Web: www.GTSOFT.org

Client: Case 7 - Stage 2

Site: FOS = 1.0

Page: 3

Date: 3.5.19





Sheet: PZ22

Works: Temporary

Pressure: Rankine

Analysis: Gross Pressure

	Maximum	d (ft)
○	781.2 psf	18.00
□	26669.4 ftlb/ft	13.60
◇	4456.4 lb/ft	3.00
●	0.9 in	13.74



MDOT Sheetpile Manual

SupportIT, v2.37

© 1997 - 2015, GTSOFT Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSOFT@aol.com
Web: www.GTSOFT.org

Client: Case 7 - Stage 2

Site: FOS = 1.0

Page: 4

Date: 3.5.19

Sheet: PZ22

Works: Temporary

Pressure: Rankine

Analysis: Gross Pressure

depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)	depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)	depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)
0.00	111.6	0.4	0.0	0.0	8.38	423.3	-19131.6	0.6	-2714.2	16.75	735.0	-23426.2	0.8	2141.9
0.18	118.5	2.1	0.0	21.6	8.55	429.5	-19577.7	0.6	-2643.2	16.93	741.2	-23064.0	0.8	2264.7
0.36	124.7	7.2	0.0	42.0	8.73	436.4	-20065.3	0.6	-2562.2	17.11	748.2	-22632.2	0.8	2404.2
0.53	131.7	17.1	0.0	66.2	8.91	443.4	-20537.7	0.6	-2479.8	17.29	754.3	-22226.6	0.7	2529.2
0.71	137.9	29.7	0.0	88.8	9.09	449.6	-20944.5	0.7	-2405.4	17.47	761.3	-21745.5	0.7	2671.1
0.89	144.8	48.5	0.0	115.4	9.27	456.6	-21387.3	0.7	-2320.6	17.64	768.3	-21238.0	0.7	2814.3
1.07	151.0	69.5	0.0	140.2	9.45	462.7	-21767.5	0.7	-2244.0	17.82	774.5	-20764.4	0.7	2942.6
1.25	158.0	98.2	0.0	169.3	9.62	469.7	-22180.0	0.7	-2156.7	18.00	781.2	-20206.3	0.7	3088.3
1.43	165.0	132.4	0.0	199.8	9.80	475.9	-22532.8	0.7	-2078.0	18.18	720.3	-19687.8	0.7	3212.5
1.60	171.1	167.6	0.0	227.9	9.98	482.9	-22914.0	0.7	-1988.2	18.36	654.3	-19080.8	0.7	3340.4
1.78	178.1	213.0	0.0	260.8	10.16	489.8	-23278.2	0.7	-1897.2	18.53	595.6	-18522.1	0.7	3443.8
1.96	184.3	258.6	0.0	291.2	10.34	496.0	-23587.7	0.7	-1815.1	18.71	529.6	-17874.2	0.6	3548.4
2.14	191.3	316.0	0.0	326.5	10.52	503.0	-23919.4	0.8	-1721.6	18.89	463.6	-17207.9	0.6	3640.6
2.32	197.4	372.6	0.0	359.1	10.69	509.2	-24199.4	0.8	-1637.3	19.07	404.9	-16602.0	0.6	3712.2
2.50	204.4	443.0	0.0	396.9	10.87	516.1	-24497.7	0.8	-1541.3	19.25	338.8	-15907.1	0.6	3781.1
2.67	211.4	520.5	0.0	436.1	11.05	522.3	-24747.6	0.8	-1454.9	19.43	280.2	-15279.6	0.6	3832.0
2.85	217.5	595.6	0.0	472.0	11.23	529.3	-25011.6	0.8	-1356.4	19.60	214.1	-14564.4	0.6	3877.6
3.03	224.5	481.2	0.0	-4447.1	11.41	536.2	-25257.0	0.8	-1256.7	19.78	155.5	-13922.5	0.5	3907.7
3.21	230.7	-255.3	0.0	-4409.2	11.58	542.4	-25459.3	0.8	-1166.9	19.96	89.4	-13195.2	0.5	3929.9
3.39	237.7	-1076.3	0.0	-4365.3	11.76	549.4	-25669.1	0.8	-1064.7	20.14	23.4	-12464.9	0.5	3939.8
3.56	243.8	-1799.1	0.1	-4325.2	11.94	555.6	-25839.4	0.8	-972.7	20.32	-35.3	-11814.9	0.5	3938.2
3.74	250.8	-2604.1	0.1	-4278.8	12.12	562.5	-26012.6	0.8	-868.0	20.50	-101.3	-11084.9	0.5	3924.5
3.92	257.8	-3400.4	0.1	-4231.2	12.30	568.7	-26150.1	0.8	-773.9	20.67	-160.0	-10439.0	0.5	3901.7
4.10	264.0	-4100.6	0.1	-4187.7	12.48	575.7	-26285.9	0.8	-666.7	20.85	-226.0	-9717.8	0.4	3864.3
4.28	270.9	-4879.7	0.2	-4137.6	12.65	582.6	-26401.6	0.8	-558.3	21.03	-284.7	-9083.4	0.4	3820.4
4.46	277.1	-5564.2	0.2	-4092.0	12.83	588.8	-26487.4	0.8	-460.8	21.21	-350.7	-8379.2	0.4	3759.2
4.63	284.1	-6325.1	0.2	-4039.4	13.01	595.8	-26564.3	0.8	-349.9	21.39	-416.7	-7687.4	0.4	3685.5
4.81	290.3	-6993.1	0.2	-3991.6	13.19	602.0	-26615.3	0.8	-250.2	21.56	-475.4	-7084.8	0.4	3609.3
4.99	297.2	-7735.0	0.2	-3936.5	13.37	608.9	-26652.7	0.9	-136.8	21.74	-541.4	-6422.8	0.4	3511.8
5.17	304.2	-8466.6	0.3	-3880.2	13.54	615.1	-26668.0	0.9	-34.9	21.92	-600.1	-5850.3	0.3	3414.6
5.35	310.4	-9107.9	0.3	-3829.0	13.72	622.1	-26665.0	0.9	80.9	22.10	-666.1	-5226.4	0.3	3293.3
5.52	317.3	-9819.1	0.3	-3770.2	13.90	629.0	-26640.3	0.9	198.0	22.28	-724.8	-4691.5	0.3	3174.9
5.70	323.5	-10442.0	0.3	-3716.8	14.08	635.2	-26600.1	0.9	303.2	22.46	-790.8	-4114.1	0.3	3029.9
5.88	330.5	-11132.0	0.3	-3655.6	14.26	642.2	-26533.9	0.9	422.8	22.63	-856.8	-3564.6	0.3	2872.3
6.06	336.7	-11735.7	0.4	-3600.0	14.44	648.4	-26456.5	0.8	530.2	22.81	-915.5	-3101.4	0.2	2721.7
6.24	343.6	-12403.7	0.4	-3536.3	14.61	655.3	-26348.0	0.8	652.3	22.99	-981.6	-2611.1	0.2	2540.3
6.42	350.6	-13059.6	0.4	-3471.3	14.79	661.5	-26232.5	0.8	761.9	23.17	-1040.2	-2204.3	0.2	2368.6
6.59	356.8	-13632.4	0.4	-3412.4	14.97	668.5	-26080.9	0.8	886.4	23.35	-1106.3	-1781.4	0.2	2163.5
6.77	363.7	-14265.0	0.4	-3344.9	15.15	675.4	-25906.0	0.8	1012.2	23.53	-1164.9	-1438.3	0.2	1970.6
6.95	369.9	-14816.6	0.5	-3283.8	15.33	681.6	-25730.9	0.8	1125.1	23.70	-1231.0	-1091.3	0.1	1741.8
7.13	376.9	-15424.9	0.5	-3213.9	15.51	688.6	-25511.5	0.8	1253.4	23.88	-1297.0	-787.7	0.1	1500.4
7.31	383.1	-15954.6	0.5	-3150.6	15.68	694.8	-25296.4	0.8	1368.5	24.06	-1355.7	-556.3	0.1	1275.2
7.49	390.0	-16537.8	0.5	-3078.2	15.86	701.7	-25031.7	0.8	1499.3	24.24	-1421.7	-341.3	0.1	1010.1
7.66	397.0	-17107.4	0.5	-3004.5	16.04	707.9	-24775.9	0.8	1616.6	24.42	-1480.4	-192.3	0.1	763.8
7.84	403.2	-17602.0	0.6	-2937.8	16.22	714.9	-24464.9	0.8	1749.8	24.59	-1546.4	-74.2	0.0	474.9
8.02	410.1	-18145.1	0.6	-2861.7	16.40	721.9	-24129.1	0.8	1884.3	24.77	-1605.1	-15.1	0.0	207.5
8.20	416.3	-18615.8	0.6	-2792.9	16.57	728.0	-23809.5	0.8	2004.9	24.95	-1663.8	0.0	0.0	0.0



MDOT Sheeppile Manual

SupportIT, v2.37

© 1997 - 2015, GTSoft Ltd.
 Tel/Fax: +44 (0)1292 477754
 Email: GTSoftLtd@aol.com
 Web: www.GTSoft.org

Client: Case 7 - Stage 2

Site: FOS = 1.0

Page: 5







Date: 3.5.19

Sheet: PZ22

Works: Temporary

Pressure: Rankine

Analysis: Gross Pressure



MDOT Sheetpile Manual

SupportIT, v2.37

© 1997 - 2015, GTSOFT Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSOFT@aol.com
Web: www.GTSOFT.org

Client: Case 7 - Stage 2

Site: FOS = 1.0

Page: 6



Date: 3.5.19

Sheet: PZ22

Works: Temporary

Pressure: Rankine

Analysis: Gross Pressure



MDOT Sheetpile Manual

Client: Case 7 - Stage 2
Site: FOS = 1.0

Page: 7
Date: 3.5.19

Sheet: PZ22
Works: Temporary
Pressure: Rankine
Analysis: Gross Pressure

Design Report

1. Maximum bending moment = 26669.4ftlb/ft and $f = 24966.8\text{psi}$. MINIMUM required sheet section modulus is: $Z = 12.82\text{in}^3/\text{ft}$ ($= M/f$). Sheet section modulus in this design is $Z = 18.40\text{in}^3/\text{ft}$, and is satisfactory.
2. Frame primary axis bending moments checked. Users should manually check the axial load capacities and the effects of combined axial and bending stresses to confirm frames are suitable.
3. FOS = 1.00 (Gross Pressure)
This is the factor of safety against rotation about the lowest frame.
The FOS can be changed using 'Defined FOS' or 'Manual' in the 'Wall' page.



MDOT Sheetpile Manual

SupportIT, v2.37

© 1997 - 2015, GTSoft Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSoftLtd@aol.com
Web: www.GTSoft.org

Client: Case 7 Stage 3 - Depth 25 ft

Site: FOS = 1.0

Page: 1

Date: 3.5.19


Sheet: PZ22

Works: Temporary

Pressure: Rankine

Analysis: Gross Pressure

	Maximum	d (ft)
○	1041.5 psf	25.00
□	29903.3 ftlb/ft	21.87
●	0.8 in	22.79



MDOT Sheetpile Manual

SupportIT, v2.37

© 1997 - 2015, GTSOFT Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSOFT@aol.com
Web: www.GTSOFT.org

Client: Case 7 Stage 3 - Depth 25 ft
 Site: FOS = 1.0

Page: 2
 Date: 3.5.19

Sheet: PZ22
 Works: Temporary
 Pressure: Rankine
 Analysis: Gross Pressure

Input Data

Depth Of Excavation = 25.00ft
 Surcharge = 359.9psf

Depth Of Active Water = 30.00ft
 Depth Of Passive Water = 30.00ft

Water Density = 62.43pcf
 Minimum Fluid Density = 31.82pcf

Soil Profile

Depth (ft)	Soil Name	γ (pcf)	γ' (pcf)	C (psf)	C_a (psf)	ϕ (°)	δ (°)	K_a	K_{ac}	K_p	K_{pc}
0.00	Dense Fine Sand	120.00	71.10	0.0	0.0	32.0	0.0	0.31	0.00	3.25	0.00

Solution

Sheet

Sheet Name	E (psi)	I (in ⁴ /ft)	f (psi)	Z (in ³ /ft)	Allowed M_{max} (ftlb/ft)	b (in)	A (in ² /ft)	W (lb/ft)	Upstand (ft)	Toe (ft)	Length (ft)
PZ22	3.04E+07	84.70	24966.8	18.40	38282.3	22.01	6.46	40.3	0.00	8.55	33.55

Load Model: Area Distribution

Supports

d (ft)	Type	Load (lb/ft)
3.00	Waler	2078.7
13.00	Waler	9268.6

Maxima

	Maximum	Depth (ft)
Pressure	1041.5 psf	25.00
Bending Moment	29903.3 ftlb/ft	21.87
Deflection	0.8 in	22.79
Shear Force	6742.2 lb/ft	13.00



MDOT Sheetpile Manual

SupportIT, v2.37

© 1997 - 2015, GTSoft Ltd.
 Tel/Fax: +44 (0)1292 477754
 Email: GTSoftLtd@aol.com
 Web: www.GTSoft.org

Client: Case 7 Stage 3 - Depth 25 ft

Site: FOS = 1.0

Page: 3

Date: 3.5.19





Sheet: PZ22

Works: Temporary

Pressure: Rankine

Analysis: Gross Pressure

	Maximum	d (ft)
○	1041.5 psf	25.00
□	29903.3 ftlb/ft	21.87
◇	6742.2 lb/ft	13.00
●	0.8 in	22.79



MDOT Sheetpile Manual

SupportIT, v2.37

© 1997 - 2015, GTSOFT Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSoftLtd@aol.com
Web: www.GTSOFT.org



Client: Case 7 Stage 3 - Depth 25 ft

Site: FOS = 1.0

Page: 4

Date: 3.5.19

Sheet: PZ22

Works: Temporary

Pressure: Rankine

Analysis: Gross Pressure

depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)	depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)	depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)
0.00	111.6	0.5	0.0	0.0	11.26	530.8	-1232.0	0.0	1549.4	22.53	950.0	-29721.6	0.8	629.9
0.24	120.9	3.7	0.0	29.4	11.50	539.1	-874.2	0.0	1669.2	22.77	958.3	-29575.9	0.8	843.4
0.48	129.3	13.0	0.0	57.7	11.74	548.5	-439.4	0.0	1806.2	23.01	967.7	-29360.4	0.8	1085.9
0.72	138.6	31.3	0.0	91.7	11.98	557.8	30.0	0.0	1945.5	23.25	976.0	-29122.4	0.8	1303.4
0.96	147.0	55.0	0.0	124.0	12.22	566.1	476.9	0.0	2071.3	23.49	985.3	-28802.2	0.8	1550.3
1.20	156.3	90.4	0.0	162.5	12.46	575.5	1013.5	0.0	2215.1	23.73	994.7	-28425.7	0.8	1799.6
1.44	164.6	130.3	0.0	198.8	12.70	583.8	1521.0	0.0	2344.9	23.97	1003.0	-28043.4	0.8	2023.2
1.68	174.0	185.1	0.0	241.8	12.94	593.2	2126.9	0.0	2493.2	24.21	1012.4	-27559.3	0.8	2276.9
1.92	183.4	250.9	0.0	287.2	13.18	601.5	1141.3	0.0	-6641.7	24.45	1020.7	-27080.5	0.8	2504.4
2.16	191.7	319.3	0.0	329.5	13.42	610.9	-515.0	0.1	-6489.0	24.69	1030.1	-26486.9	0.8	2762.6
2.40	201.0	407.7	0.0	379.3	13.66	620.2	-2132.6	0.1	-6334.0	24.93	1038.4	-25909.9	0.8	2994.1
2.64	209.4	497.1	0.0	425.7	13.90	628.6	-3537.5	0.1	-6194.2	25.17	983.0	-25205.0	0.8	3250.9
2.88	218.7	610.2	0.0	480.0	14.14	637.9	-5080.3	0.2	-6034.7	25.41	894.2	-24444.1	0.8	3485.9
3.12	227.0	490.3	0.0	-1548.6	14.38	646.2	-6417.8	0.2	-5891.0	25.65	815.3	-23724.7	0.8	3676.0
3.36	236.4	107.9	0.0	-1490.2	14.62	655.6	-7883.7	0.2	-5727.0	25.89	726.5	-22871.6	0.7	3868.8
3.60	245.8	-259.7	0.0	-1429.4	14.86	663.9	-9151.8	0.2	-5579.3	26.12	647.6	-22078.4	0.7	4021.4
3.83	254.1	-573.3	0.0	-1373.4	15.10	673.3	-10538.7	0.3	-5410.9	26.36	558.8	-21151.3	0.7	4171.9
4.07	263.5	-911.0	0.0	-1308.1	15.34	682.7	-11882.9	0.3	-5240.2	26.60	479.9	-20300.3	0.7	4287.0
4.31	271.8	-1197.2	0.0	-1248.1	15.58	691.0	-13041.5	0.3	-5086.4	26.84	391.1	-19317.2	0.7	4395.4
4.55	281.1	-1502.9	0.0	-1178.4	15.82	700.3	-14303.4	0.4	-4911.2	27.08	302.3	-18311.8	0.7	4481.4
4.79	289.5	-1759.8	0.0	-1114.5	16.06	708.7	-15387.9	0.4	-4753.5	27.32	223.4	-17403.5	0.6	4539.1
5.03	298.8	-2031.5	0.0	-1040.3	16.30	718.0	-16565.5	0.4	-4573.9	27.56	134.6	-16369.9	0.6	4582.9
5.27	308.2	-2284.2	0.0	-963.8	16.54	726.3	-17574.0	0.4	-4412.2	27.80	55.7	-15444.4	0.6	4603.0
5.51	316.5	-2492.6	0.0	-893.9	16.78	735.7	-18665.1	0.5	-4228.1	28.04	-33.1	-14400.5	0.6	4604.6
5.75	325.9	-2708.1	0.0	-812.9	17.02	745.1	-19709.5	0.5	-4041.6	28.28	-112.0	-13474.0	0.6	4587.3
5.99	334.2	-2882.4	0.0	-738.9	17.26	753.4	-20598.2	0.5	-3873.9	28.52	-200.8	-12437.8	0.5	4546.7
6.23	343.5	-3058.5	0.0	-653.5	17.50	762.7	-21552.9	0.6	-3683.0	28.76	-289.6	-11413.2	0.5	4483.7
6.47	351.9	-3196.8	0.0	-575.6	17.74	771.1	-22361.0	0.6	-3511.3	29.00	-368.5	-10516.1	0.5	4409.0
6.71	361.2	-3331.4	0.0	-485.8	17.98	780.4	-23223.8	0.6	-3316.0	29.24	-457.3	-9526.9	0.5	4303.9
6.95	370.6	-3443.1	0.0	-393.6	18.22	788.8	-23949.3	0.6	-3140.4	29.48	-536.2	-8669.3	0.4	4191.7
7.19	378.9	-3522.8	0.0	-309.6	18.46	798.1	-24718.2	0.6	-2940.6	29.72	-625.0	-7733.6	0.4	4044.3
7.43	388.3	-3589.9	0.0	-213.0	18.69	807.5	-25436.5	0.7	-2738.4	29.96	-703.9	-6931.7	0.4	3894.6
7.67	396.6	-3628.8	0.0	-125.0	18.93	815.8	-26032.0	0.7	-2556.7	30.20	-764.1	-6067.6	0.4	3705.2
7.91	406.0	-3649.0	0.0	-23.9	19.17	825.2	-26653.1	0.7	-2350.1	30.44	-816.7	-5248.1	0.3	3501.3
8.15	414.3	-3645.4	0.0	67.9	19.41	833.5	-27161.2	0.7	-2164.5	30.68	-863.4	-4559.4	0.3	3308.8
8.39	423.6	-3616.6	0.0	173.5	19.65	842.8	-27683.0	0.7	-1953.4	30.92	-916.0	-3832.3	0.3	3079.4
8.63	433.0	-3561.0	0.0	281.4	19.89	851.2	-28101.9	0.7	-1763.8	31.16	-962.8	-3230.6	0.3	2864.1
8.87	441.3	-3488.6	0.0	379.3	20.13	860.5	-28522.2	0.8	-1548.3	31.40	-1015.4	-2606.8	0.2	2609.2
9.11	450.7	-3380.7	0.0	491.7	20.37	869.9	-28888.0	0.8	-1330.4	31.64	-1062.2	-2101.9	0.2	2371.3
9.35	459.0	-3261.0	0.0	593.6	20.61	878.2	-29166.8	0.8	-1134.8	31.88	-1114.8	-1592.4	0.2	2090.8
9.59	468.4	-3098.8	0.0	710.4	20.85	887.6	-29427.8	0.8	-912.5	32.12	-1167.4	-1147.9	0.2	1796.9
9.83	476.7	-2929.8	0.0	816.2	21.09	895.9	-29612.7	0.8	-712.9	32.36	-1214.1	-809.7	0.1	1524.2
10.07	486.1	-2711.2	0.0	937.5	21.33	905.3	-29766.9	0.8	-486.1	32.60	-1266.7	-496.1	0.1	1204.7
10.31	495.4	-2461.8	0.0	1061.1	21.57	913.6	-29855.9	0.8	-282.6	32.84	-1313.5	-279.3	0.1	909.3
10.55	503.7	-2213.8	0.0	1173.0	21.81	922.9	-29901.2	0.8	-51.3	33.08	-1366.1	-107.7	0.1	564.3
10.79	513.1	-1904.8	0.0	1301.1	22.05	932.3	-29889.5	0.8	182.2	33.32	-1412.9	-21.8	0.0	246.2
11.03	521.4	-1602.8	0.0	1416.9	22.29	940.6	-29834.4	0.8	391.8	33.55	-1459.6	0.0	0.0	0.0



MDOT Sheeppile Manual

SupportIT, v2.37



© 1997 - 2015, GTSoft Ltd.
 Tel/Fax: +44 (0)1292 477754
 Email: GTSoftLtd@aol.com
 Web: www.GTSoft.org

Client: Case 7 Stage 3 - Depth 25 ft

Site: FOS = 1.0

Page: 5







Date: 3.5.19

Sheet: PZ22

Works: Temporary

Pressure: Rankine

Analysis: Gross Pressure



MDOT Sheetpile Manual

SupportIT, v2.37

© 1997 - 2015, GTSOFT Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSOFT@aol.com
Web: www.GTSOFT.org

Client: Case 7 Stage 3 - Depth 25 ft

Site: FOS = 1.0

Page: 6



Date: 3.5.19

Sheet: PZ22

Works: Temporary

Pressure: Rankine

Analysis: Gross Pressure



MDOT Sheetpile Manual

Client: Case 7 Stage 3 - Depth 25 ft
Site: FOS = 1.0

Page: 7
Date: 3.5.19

Sheet: PZ22
Works: Temporary
Pressure: Rankine
Analysis: Gross Pressure

Design Report

1. Maximum bending moment = 29903.3ftlb/ft and $f = 24966.8\text{psi}$. MINIMUM required sheet section modulus is: $Z = 14.37\text{in}^3/\text{ft}$ ($= M/f$). Sheet section modulus in this design is $Z = 18.40\text{in}^3/\text{ft}$, and is satisfactory.
2. Frame primary axis bending moments checked. Users should manually check the axial load capacities and the effects of combined axial and bending stresses to confirm frames are suitable.
3. FOS = 1.01 (Gross Pressure)
This is the factor of safety against rotation about the lowest frame.
The FOS can be changed using 'Defined FOS' or 'Manual' in the 'Wall' page.



MDOT Sheetpile Manual

SupportIT, v2.37

© 1997 - 2015, GTSoft Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSoftLtd@aol.com
Web: www.GTSoft.org

Client: Case 7 Stage 4 - Depth 30 ft

Site: FOS = 1.0

Page: 1

Date: 3.5.19


Sheet: PZ22

Works: Temporary

Pressure: Rankine

Analysis: Gross Pressure

	Maximum	d (ft)
○	1227.6 psf	30.00
□	30295.3 ftlb/ft	29.76
●	0.8 in	31.30



MDOT Sheetpile Manual

SupportIT, v2.37

© 1997 - 2015, GTSOFT Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSOFT@aol.com
Web: www.GTSOFT.org

Client: Case 7 Stage 4 - Depth 30 ft
 Site: FOS = 1.0

Page: 2
 Date: 3.5.19

Sheet: PZ22
 Works: Temporary
 Pressure: Rankine
 Analysis: Gross Pressure

Input Data

Depth Of Excavation = 30.00ft
 Surcharge = 359.9psf

Depth Of Active Water = 30.00ft
 Depth Of Passive Water = 30.00ft

Water Density = 62.43pcf
 Minimum Fluid Density = 31.82pcf

Soil Profile

Depth (ft)	Soil Name	γ (pcf)	γ' (pcf)	C (psf)	C_a (psf)	ϕ (°)	δ (°)	K_a	K_{ac}	K_p	K_{pc}
0.00	Dense Fine Sand	120.00	71.10	0.0	0.0	32.0	0.0	0.31	0.00	3.25	0.00

Solution

Sheet

Sheet Name	E (psi)	I (in ⁴ /ft)	f (psi)	Z (in ³ /ft)	Allowed M _{max} (ftlb/ft)	b (in)	A (in ² /ft)	W (lb/ft)	Upstand (ft)	Toe (ft)	Length (ft)
PZ22	3.04E+07	84.70	24966.8	18.40	38282.3	22.01	6.46	40.3	0.00	11.96	41.96

Load Model: Area Distribution

Supports

d (ft)	Type	Load (lb/ft)
3.00	Waler	2080.8
13.00	Waler	5542.2
22.00	Waler	12183.6

Maxima

	Maximum	Depth (ft)
Pressure	1227.6 psf	30.00
Bending Moment	30295.3 ftlb/ft	29.76
Deflection	0.8 in	31.30
Shear Force	8336.1 lb/ft	22.00



MDOT Sheetpile Manual

SupportIT, v2.37

© 1997 - 2015, GTSoft Ltd.
 Tel/Fax: +44 (0)1292 477754
 Email: GTSoftLtd@aol.com
 Web: www.GTSoft.org

Client: Case 7 Stage 4 - Depth 30 ft

Site: FOS = 1.0

Page: 3

Date: 3.5.19





Sheet: PZ22

Works: Temporary

Pressure: Rankine

Analysis: Gross Pressure

	Maximum	d (ft)
○	1227.6 psf	30.00
□	30295.3 ftlb/ft	29.76
◇	8336.1 lb/ft	22.00
●	0.8 in	31.30



MDOT Sheetpile Manual

SupportIT, v2.37

© 1997 - 2015, GTSOFT Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSOFT@aol.com
Web: www.GTSOFT.org

Client: Case 7 Stage 4 - Depth 30 ft

Site: FOS = 1.0

Page: 4

Date: 3.5.19

Sheet: PZ22

Works: Temporary

Pressure: Rankine

Analysis: Gross Pressure

depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)	depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)	depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)
0.00	111.6	0.6	0.0	0.0	14.09	635.8	-681.0	0.0	-2344.0	28.17	1160.0	-28791.5	0.7	-1864.7
0.30	123.3	5.7	0.0	37.2	14.39	646.2	-1319.7	0.0	-2164.5	28.47	1170.4	-29272.6	0.7	-1538.6
0.60	133.7	20.5	0.0	73.6	14.69	657.9	-1977.4	0.0	-1959.1	28.77	1182.2	-29704.5	0.7	-1168.2
0.90	145.4	49.8	0.0	118.1	14.99	669.6	-2569.3	0.0	-1750.0	29.07	1192.6	-29990.3	0.7	-835.9
1.20	155.8	88.0	0.0	160.8	15.29	680.0	-3039.4	0.0	-1561.0	29.37	1204.3	-30200.4	0.8	-458.5
1.50	167.5	145.7	0.0	212.2	15.59	691.7	-3504.2	0.0	-1344.9	29.67	1216.0	-30291.4	0.8	-77.5
1.80	177.9	211.0	0.0	261.1	15.89	702.2	-3859.3	0.0	-1149.8	29.97	1226.4	-30271.9	0.8	264.3
2.10	189.6	301.3	0.0	319.6	16.19	713.9	-4192.7	0.0	-926.8	30.27	1163.3	-30139.4	0.8	640.1
2.40	201.3	410.4	0.0	381.8	16.48	724.3	-4429.2	0.0	-725.4	30.57	1104.9	-29927.4	0.8	956.3
2.70	211.7	524.3	0.0	440.2	16.78	736.0	-4626.9	0.0	-495.4	30.87	1039.3	-29588.7	0.8	1292.6
3.00	223.5	672.6	0.0	-1571.4	17.08	747.7	-4751.2	0.0	-261.8	31.17	980.9	-29203.4	0.8	1574.1
3.30	233.6	238.3	0.0	-1507.2	17.38	758.1	-4799.1	0.0	-51.0	31.47	915.3	-28681.0	0.8	1871.3
3.60	245.6	-228.3	0.0	-1431.6	17.68	769.8	-4781.6	0.0	189.6	31.77	849.6	-28070.5	0.8	2147.9
3.90	256.0	-622.5	0.0	-1361.3	17.98	780.2	-4702.2	0.0	406.6	32.07	791.3	-27459.0	0.8	2376.4
4.20	267.7	-1041.9	0.0	-1278.6	18.28	791.9	-4539.8	0.0	654.2	32.37	725.6	-26699.3	0.8	2614.0
4.50	279.4	-1434.6	0.0	-1192.4	18.58	802.3	-4329.8	0.0	877.4	32.67	667.3	-25965.2	0.8	2807.8
4.80	289.8	-1760.3	0.0	-1112.6	18.88	814.0	-4018.5	0.0	1131.9	32.97	601.6	-25078.8	0.8	3006.3
5.10	301.5	-2099.5	0.0	-1019.3	19.18	825.7	-3626.7	0.0	1390.2	33.27	543.3	-24242.2	0.8	3165.4
5.40	311.9	-2375.7	0.0	-933.3	19.48	836.1	-3209.8	0.0	1622.8	33.57	477.7	-23251.8	0.7	3324.9
5.69	323.6	-2657.2	0.0	-833.1	19.78	847.8	-2662.7	0.0	1888.0	33.87	412.0	-22215.4	0.7	3463.8
5.99	334.0	-2880.3	0.0	-741.0	20.08	858.2	-2106.0	0.0	2126.8	34.17	353.7	-21260.7	0.7	3569.9
6.29	345.7	-3099.9	0.0	-633.8	20.38	870.0	-1399.4	0.0	2398.9	34.47	288.0	-20154.7	0.7	3669.7
6.59	357.4	-3285.0	0.0	-522.9	20.68	880.4	-699.2	0.0	2644.0	34.77	229.7	-19148.1	0.7	3741.1
6.89	367.8	-3419.7	0.0	-421.3	20.98	892.1	170.9	0.0	2923.1	35.07	164.0	-17995.0	0.7	3801.9
7.19	379.6	-3536.6	0.0	-303.5	21.28	903.8	1129.2	0.0	3205.9	35.37	105.7	-16956.6	0.6	3838.6
7.49	390.0	-3608.8	0.0	-195.7	21.58	914.2	2056.1	0.0	3460.3	35.67	40.0	-15779.0	0.6	3860.4
7.79	401.7	-3653.2	0.0	-70.9	21.88	925.9	3184.4	0.0	3750.1	35.97	-25.6	-14597.6	0.6	3861.4
8.09	412.1	-3659.2	0.0	43.1	22.18	936.3	2136.6	0.0	-8172.9	36.27	-84.0	-13549.4	0.6	3844.7
8.39	423.8	-3627.4	0.0	174.8	22.48	948.0	-390.7	0.1	-7876.2	36.57	-149.6	-12378.1	0.5	3805.9
8.69	435.5	-3553.7	0.0	310.2	22.78	958.4	-2558.4	0.1	-7609.3	36.87	-207.9	-11349.2	0.5	3753.7
8.99	445.9	-3452.0	0.0	433.7	23.08	970.1	-4907.6	0.1	-7305.7	37.17	-273.6	-10211.2	0.5	3674.9
9.29	457.6	-3296.0	0.0	576.1	23.38	981.8	-7160.8	0.2	-6998.3	37.47	-331.9	-9222.2	0.5	3587.2
9.59	468.0	-3119.3	0.0	705.7	23.68	992.2	-9082.1	0.2	-6722.0	37.77	-397.6	-8140.6	0.4	3468.5
9.89	479.7	-2876.8	0.0	855.1	23.98	1003.9	-11150.9	0.3	-6407.7	38.07	-463.2	-7098.2	0.4	3328.6
10.19	490.1	-2621.5	0.0	990.9	24.28	1014.3	-12906.5	0.3	-6125.2	38.37	-521.6	-6209.7	0.4	3186.5
10.49	501.8	-2288.4	0.0	1147.2	24.58	1026.1	-14786.8	0.3	-5803.9	38.66	-587.2	-5258.9	0.3	3006.7
10.79	513.5	-1905.8	0.0	1307.2	24.88	1036.5	-16373.0	0.4	-5515.3	38.96	-645.6	-4462.2	0.3	2829.2
11.09	523.9	-1523.0	0.0	1452.5	25.18	1048.2	-18060.5	0.4	-5187.0	39.26	-711.2	-3626.2	0.3	2609.4
11.39	535.6	-1043.5	0.0	1619.4	25.48	1059.9	-19644.5	0.4	-4855.1	39.56	-769.6	-2941.7	0.3	2396.3
11.69	546.1	-572.8	0.0	1770.9	25.78	1070.3	-20964.4	0.5	-4557.0	39.86	-835.2	-2243.5	0.2	2136.7
11.99	557.8	7.8	0.0	1944.8	26.08	1082.0	-22349.4	0.5	-4218.1	40.16	-900.8	-1627.6	0.2	1855.8
12.29	568.2	570.1	0.0	2102.4	26.38	1092.4	-23490.6	0.5	-3913.8	40.46	-959.2	-1154.5	0.2	1588.4
12.59	579.9	1255.9	0.0	2283.3	26.68	1104.1	-24672.4	0.6	-3567.9	40.76	-1024.8	-711.7	0.1	1267.6
12.89	591.6	1998.9	0.0	2467.8	26.98	1114.5	-25631.3	0.6	-3257.4	41.06	-1083.2	-402.7	0.1	964.7
13.19	602.0	1737.0	0.0	-2907.3	27.28	1126.2	-26605.9	0.6	-2904.6	41.36	-1148.8	-156.1	0.1	604.0
13.49	613.7	841.8	0.0	-2715.8	27.57	1137.9	-27469.0	0.6	-2548.2	41.66	-1207.2	-31.8	0.0	265.6
13.79	624.1	97.5	0.0	-2542.5	27.87	1148.3	-28141.8	0.7	-2228.2	41.96	-1265.5	0.0	0.0	0.0



MDOT Sheeppile Manual

SupportIT, v2.37



© 1997 - 2015, GTSOFT Ltd.
 Tel/Fax: +44 (0)1292 477754
 Email: GTSOFT@aol.com
 Web: www.GTSOFT.org

Client: Case 7 Stage 4 - Depth 30 ft

Site: FOS = 1.0

Page: 5







Date: 3.5.19

Sheet: PZ22

Works: Temporary

Pressure: Rankine

Analysis: Gross Pressure



MDOT Sheetpile Manual

SupportIT, v2.37

© 1997 - 2015, GTSOFT Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSOFT@aol.com
Web: www.GTSOFT.org

Client: Case 7 Stage 4 - Depth 30 ft

Site: FOS = 1.0

Page: 6



Date: 3.5.19

Sheet: PZ22

Works: Temporary

Pressure: Rankine

Analysis: Gross Pressure



MDOT Sheetpile Manual

Client: Case 7 Stage 4 - Depth 30 ft
Site: FOS = 1.0

Page: 7
Date: 3.5.19

Sheet: PZ22
Works: Temporary
Pressure: Rankine
Analysis: Gross Pressure

Design Report

1. Maximum bending moment = 30295.3ftlb/ft and $f = 24966.8$ psi. MINIMUM required sheet section modulus is: $Z = 14.56\text{in}^3/\text{ft}$ ($= M/f$). Sheet section modulus in this design is $Z = 18.40\text{in}^3/\text{ft}$, and is satisfactory.
2. Frame primary axis bending moments checked. Users should manually check the axial load capacities and the effects of combined axial and bending stresses to confirm frames are suitable.
3. FOS = 0.99 (Gross Pressure)
This is the factor of safety against rotation about the lowest frame.
The FOS can be changed using 'Defined FOS' or 'Manual' in the 'Wall' page.



MDOT Sheetpile Manual

SupportIT, v2.37

© 1997 - 2015, GTSoft Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSoftLtd@aol.com
Web: www.GTSoft.org

Client: Case 7 Stage 4 - Depth 30 ft

Site: FOS = 1.50

Page: 1

Date: 3.22.19


Sheet: PZ22

Works: Temporary

Pressure: Rankine

Analysis: Gross Pressure

	Maximum	d (ft)
○	1227.6 psf	30.00
□	30034.2 ftlb/ft	29.76
●	1.4 in	34.14



MDOT Sheetpile Manual

SupportIT, v2.37

© 1997 - 2015, GTSOFT Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSOFT@aol.com
Web: www.GTSOFT.org

Client: Case 7 Stage 4 - Depth 30 ft
 Site: FOS = 1.50

Page: 2
 Date: 3.22.19

Sheet: PZ22
 Works: Temporary
 Pressure: Rankine
 Analysis: Gross Pressure

Input Data

Depth Of Excavation = 30.00ft
 Surcharge = 359.9psf

Depth Of Active Water = 30.00ft
 Depth Of Passive Water = 30.00ft

Water Density = 62.43pcf
 Minimum Fluid Density = 31.82pcf

Soil Profile

Depth (ft)	Soil Name	γ (pcf)	γ' (pcf)	C (psf)	C_a (psf)	ϕ (°)	δ (°)	K_a	K_{ac}	K_p	K_{pc}
0.00	Dense Fine Sand	120.00	71.10	0.0	0.0	32.0	0.0	0.31	0.00	3.25	0.00

Solution

Sheet

Sheet Name	E (psi)	I (in ⁴ /ft)	f (psi)	Z (in ³ /ft)	Allowed M _{max} (ftlb/ft)	b (in)	A (in ² /ft)	W (lb/ft)	Upstand (ft)	Toe (ft)	Length (ft)
PZ22	3.04E+07	84.70	24966.8	18.40	38282.3	22.01	6.46	40.3	0.00	20.09	50.09

Load Model: Area Distribution

Supports

d (ft)	Type	Load (lb/ft)
3.00	Waler	2082.3
13.00	Waler	5535.6
22.00	Waler	12158.6

Maxima

	Maximum	Depth (ft)
Pressure	1227.6 psf	30.00
Bending Moment	30034.2 ftlb/ft	29.76
Deflection	1.4 in	34.14
Shear Force	8300.5 lb/ft	22.00



MDOT Sheetpile Manual

SupportIT, v2.37

© 1997 - 2015, GTSOFT Ltd.
 Tel/Fax: +44 (0)1292 477754
 Email: GTSOFT@aol.com
 Web: www.GTSOFT.org

Client: Case 7 Stage 4 - Depth 30 ft

Site: FOS = 1.50

Page: 3

Date: 3.22.19





Sheet: PZ22

Works: Temporary

Pressure: Rankine

Analysis: Gross Pressure

	Maximum	d (ft)
○	1227.6 psf	30.00
□	30034.2 ftlb/ft	29.76
◇	8300.5 lb/ft	22.00
●	1.4 in	34.14



MDOT Sheetpile Manual

Client: Case 7 Stage 4 - Depth 30 ft

Site: FOS = 1.50

Page: 4

Date: 3.22.19

Sheet: PZ22

Works: Temporary

Pressure: Rankine

Analysis: Gross Pressure

depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)	depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)	depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)
0.00	111.6	0.7	0.0	0.0	16.82	737.3	-4646.4	0.0	-460.5	33.63	459.9	-25636.8	1.4	3382.8
0.36	125.6	8.1	0.0	44.9	17.17	749.8	-4762.4	0.0	-212.0	33.99	390.2	-24970.6	1.4	3523.2
0.72	138.0	29.5	0.0	89.6	17.53	763.7	-4794.2	0.0	72.6	34.35	311.8	-24191.3	1.4	3653.4
1.07	152.0	72.2	0.0	144.9	17.89	777.7	-4718.8	0.0	362.4	34.70	242.1	-23476.9	1.4	3744.5
1.43	164.4	128.3	0.0	198.4	18.25	790.1	-4559.8	0.0	624.4	35.06	163.7	-22654.8	1.4	3819.1
1.79	178.4	213.6	0.0	263.7	18.60	804.1	-4275.7	0.0	924.2	35.42	85.4	-21819.4	1.3	3864.2
2.15	190.8	310.6	0.0	326.2	18.96	816.5	-3928.1	0.0	1195.0	35.78	15.7	-21070.7	1.3	3879.6
2.50	204.7	445.6	0.0	401.5	19.32	830.5	-3428.3	0.0	1504.7	36.14	-62.7	-20227.0	1.3	3877.8
2.86	218.7	609.7	0.0	482.1	19.68	842.9	-2885.8	0.0	1784.3	36.49	-132.4	-19477.8	1.3	3871.3
3.22	231.1	845.4	0.0	-1524.7	20.04	856.9	-2163.2	0.0	2103.9	36.85	-210.8	-18636.9	1.3	3858.7
3.58	245.1	-215.5	0.0	-1435.0	20.39	870.9	-1319.9	0.0	2428.7	37.21	-280.4	-17892.3	1.3	3842.8
3.94	257.5	-685.0	0.0	-1350.8	20.75	883.3	-467.3	0.0	2721.9	37.57	-358.8	-17058.7	1.3	3819.5
4.29	271.5	-1178.5	0.0	-1251.1	21.11	897.3	609.6	0.0	3056.6	37.92	-437.2	-16230.7	1.2	3790.7
4.65	283.9	-1585.0	0.0	-1158.1	21.47	909.7	1672.9	0.0	3358.6	38.28	-506.9	-15500.3	1.2	3760.3
5.01	297.9	-2004.1	0.0	-1048.5	21.82	923.7	2990.3	0.0	3703.2	38.64	-585.3	-14686.2	1.2	3720.9
5.37	311.9	-2381.0	0.0	-933.7	22.18	936.1	2242.1	0.0	-8144.6	39.00	-654.9	-13970.2	1.2	3681.1
5.72	324.3	-2678.9	0.0	-827.2	22.54	950.1	-757.1	0.1	-7790.0	39.36	-733.3	-13174.4	1.2	3631.0
6.08	338.3	-2970.5	0.0	-702.5	22.90	964.0	-3622.3	0.2	-7430.2	39.71	-803.0	-12476.5	1.1	3581.7
6.44	350.7	-3189.5	0.0	-587.2	23.26	976.5	-6055.0	0.2	-7105.9	40.07	-881.4	-11703.3	1.1	3521.0
6.80	364.7	-3388.8	0.0	-452.5	23.61	990.4	-8661.6	0.3	-6736.2	40.43	-959.8	-10943.9	1.1	3454.7
7.16	377.1	-3522.6	0.0	-328.4	23.97	1002.9	-10861.4	0.4	-6403.1	40.79	-1029.4	-10281.3	1.0	3391.0
7.51	391.1	-3622.5	0.0	-183.8	24.33	1016.8	-13202.5	0.4	-6023.5	41.14	-1107.8	-9551.2	1.0	3314.1
7.87	405.1	-3667.0	0.0	-34.0	24.69	1029.3	-15163.1	0.5	-5681.6	41.50	-1177.5	-8916.6	1.0	3241.0
8.23	417.5	-3658.4	0.0	103.6	25.04	1043.2	-17231.7	0.6	-5292.0	41.86	-1255.9	-8220.1	0.9	3153.5
8.59	431.4	-3593.1	0.0	263.3	25.40	1057.2	-19153.0	0.6	-4897.2	42.22	-1325.5	-7617.4	0.9	3070.9
8.94	443.9	-3484.1	0.0	409.7	25.76	1069.6	-20735.8	0.7	-4541.9	42.58	-1403.9	-6958.9	0.9	2972.7
9.30	457.8	-3302.4	0.0	579.4	26.12	1083.6	-22373.8	0.7	-4137.1	42.93	-1482.3	-6322.3	0.8	2868.9
9.66	470.3	-3086.8	0.0	734.6	26.48	1096.0	-23701.6	0.8	-3773.0	43.29	-1552.0	-5775.8	0.8	2772.0
10.02	484.2	-2781.6	0.0	914.2	26.83	1110.0	-25049.2	0.8	-3358.3	43.65	-1630.4	-5183.9	0.8	2657.6
10.38	498.2	-2408.3	0.0	1099.0	27.19	1122.4	-26115.8	0.9	-2985.3	44.01	-1700.0	-4679.1	0.7	2551.2
10.73	510.6	-2017.5	0.0	1267.7	27.55	1136.4	-27166.0	0.9	-2560.8	44.36	-1778.4	-4136.2	0.7	2426.1
11.09	524.6	-1510.0	0.0	1462.5	27.91	1150.4	-28056.0	1.0	-2130.9	44.72	-1848.1	-3676.9	0.6	2310.3
11.45	537.0	-996.9	0.0	1640.0	28.26	1162.8	-28710.9	1.0	-1744.5	45.08	-1926.5	-3187.5	0.6	2174.6
11.81	551.0	-348.1	0.0	1844.6	28.62	1176.8	-29292.7	1.1	-1304.7	45.44	-2004.9	-2728.1	0.6	2033.4
12.16	563.4	293.6	0.0	2031.0	28.98	1189.2	-29670.6	1.1	-909.4	45.80	-2074.5	-2346.0	0.5	1903.1
12.52	577.4	1090.6	0.0	2245.5	29.34	1203.2	-29937.2	1.1	-459.8	46.15	-2152.9	-1946.6	0.5	1751.2
12.88	591.4	1969.0	0.0	2465.4	29.70	1215.6	-30031.7	1.2	-55.7	46.51	-2222.6	-1619.9	0.4	1611.5
13.24	603.8	1443.2	0.0	-2870.4	30.05	1208.8	-30000.5	1.2	403.0	46.87	-2301.0	-1285.0	0.4	1449.0
13.60	617.8	417.0	0.0	-2640.7	30.41	1130.5	-29870.0	1.2	841.1	47.23	-2370.6	-1017.4	0.4	1299.8
13.95	630.2	-423.0	0.0	-2432.1	30.77	1060.8	-29676.2	1.3	1205.5	47.58	-2449.0	-751.3	0.3	1126.7
14.31	644.2	-1285.1	0.0	-2192.4	31.13	982.4	-29376.5	1.3	1587.7	47.94	-2527.4	-523.5	0.3	948.0
14.67	656.6	-1976.2	0.0	-1975.0	31.48	912.7	-29042.6	1.3	1902.6	48.30	-2597.1	-354.0	0.2	784.4
15.03	670.6	-2667.2	0.0	-1725.4	31.84	834.3	-28596.7	1.3	2229.1	48.66	-2675.5	-201.6	0.2	595.1
15.38	684.5	-3264.9	0.0	-1470.6	32.20	764.7	-28143.0	1.3	2494.7	49.02	-2745.1	-101.1	0.1	422.1
15.74	697.0	-3716.2	0.0	-1239.7	32.56	686.3	-27573.7	1.3	2765.6	49.37	-2823.5	-28.5	0.1	222.1
16.10	710.9	-4132.2	0.0	-974.9	32.92	607.9	-26948.4	1.3	3007.0	49.73	-2893.2	-1.0	0.0	39.6
16.46	723.4	-4419.0	0.0	-735.2	33.27	538.2	-26350.6	1.4	3196.9	50.09	-2962.9	0.0	0.0	0.0









MDOT Sheeppile Manual

SupportIT, v2.37



© 1997 - 2015, GTSoft Ltd.
 Tel/Fax: +44 (0)1292 477754
 Email: GTSoftLtd@aol.com
 Web: www.GTSoft.org





MDOT Sheetpile Manual

Client: Case 7 Stage 4 - Depth 30 ft
Site: FOS = 1.50

Page: 6
Date: 3.22.19

Sheet: PZ22
Works: Temporary

Pressure: Rankine
Analysis: Gross Pressure



MDOT Sheetpile Manual

Client: Case 7 Stage 4 - Depth 30 ft
Site: FOS = 1.50

Page: 7
Date: 3.22.19

Sheet: PZ22
Works: Temporary
Pressure: Rankine
Analysis: Gross Pressure

Design Report

1. Maximum bending moment = 30034.2ftlb/ft and $f = 24966.8\text{psi}$. MINIMUM required sheet section modulus is: $Z = 14.44\text{in}^3/\text{ft}$ ($= M/f$). Sheet section modulus in this design is $Z = 18.40\text{in}^3/\text{ft}$, and is satisfactory.
2. Frame primary axis bending moments checked. Users should manually check the axial load capacities and the effects of combined axial and bending stresses to confirm frames are suitable.
3. FOS = 1.50 (Gross Pressure)
This is the factor of safety against rotation about the lowest frame.
The FOS can be changed using 'Defined FOS' or 'Manual' in the 'Wall' page.



MDOT Sheetpile Manual

SupportIT, v2.37

© 1997 - 2015, GTSoft Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSoftLtd@aol.com
Web: www.GTSoft.org

Client: Case 7 Terzaghi & Peck Strut
Loads

Site: FOS = 1.0

Page: 1

Date: 3.5.19


Sheet: PZ35

Works: Temporary

Pressure: Terzaghi

Analysis: Gross Pressure

	Maximum	d (ft)
○	2621.6 psf	30.07
□	123027.4 ftlb/ft	32.70
●	1.6 in	35.89



MDOT Sheetpile Manual

SupportIT, v2.37

© 1997 - 2015, GTSOFT Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSOFT@aol.com
Web: www.GTSOFT.org

Client: Case 7 Terzaghi & Peck Strut
Loads
Site: FOS = 1.0

Page: 2
Date: 3.5.19

Sheet: PZ35
Works: Temporary
Pressure: Terzaghi
Analysis: Gross Pressure

Input Data

Depth Of Excavation = 30.00ft
Surcharge = 359.9psf

Depth Of Active Water = 0.00ft
Depth Of Passive Water = 30.00ft

Water Density = 62.43pcf
Minimum Fluid Density = 31.82pcf

Soil Profile

Depth (ft)	Soil Name	γ (pcf)	γ' (pcf)	C (psf)	C_a (psf)	ϕ (°)	δ (°)	K_a	K_{ac}	K_p	K_{pc}
0.00	Dense Fine Sand	120.00	71.10	0.0	0.0	32.0	0.0	0.31	0.00	3.25	0.00

Solution

Sheet

Sheet Name	E (psi)	I (in ⁴ /ft)	f (psi)	Z (in ³ /ft)	Allowed M _{max} (ftlb/ft)	b (in)	A (in ² /ft)	W (lb/ft)	Upstand (ft)	Toe (ft)	Length (ft)
PZ35	3.04E+07	369.40	24966.8	48.90	101739.5	22.64	10.28	66.0	0.00	22.59	52.59

Load Model: Area Distribution

Supports

d (ft)	Type	Load (lb/ft)
3.00	Brace	6338.5
13.00	Brace	12625.0
22.00	Brace	31700.6

Maxima

	Maximum	Depth (ft)
Pressure	2621.6 psf	30.07
Bending Moment	123027.4 ftlb/ft	32.70
Deflection	1.6 in	35.89
Shear Force	23589.8 lb/ft	22.00



MDOT Sheetpile Manual

SupportIT, v2.37

© 1997 - 2015, GTSOFT Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSOFT@aol.com
Web: www.GTSOFT.org

Client: Case 7 Terzaghi & Peck Strut
Loads

Site: FOS = 1.0

Page: 3

Date: 3.5.19





Sheet: PZ35

Works: Temporary

Pressure: Terzaghi

Analysis: Gross Pressure

	Maximum	d (ft)
○	2621.6 psf	30.07
□	123027.4 ftlb/ft	32.70
◇	23589.8 lb/ft	22.00
●	1.6 in	35.89



MDOT Sheetpile Manual

SupportIT, v2.37

© 1997 - 2015, GTSOFT Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSOFT@aol.com
Web: www.GTSOFT.org

Client: Case 7 Terzaghi & Peck Strut
Loads
Site: FOS = 1.0

Page: 4
Date: 3.5.19

Sheet: PZ35
Works: Temporary
Pressure: Terzaghi
Analysis: Gross Pressure

depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)	depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)	depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)
0.00	541.4	1.6	0.0	0.0	17.66	1644.0	-10033.6	0.0	383.8	35.31	1524.6	-117081.9	1.6	4781.6
0.38	566.0	40.0	0.0	221.1	18.03	1665.9	-9810.9	0.0	964.5	35.69	1451.5	-115494.9	1.6	5301.8
0.75	587.9	148.9	0.0	426.5	18.41	1690.6	-9316.1	0.0	1627.0	36.06	1369.2	-113517.3	1.6	5856.3
1.13	612.5	358.9	0.0	666.8	18.78	1715.2	-8559.2	0.0	2299.3	36.44	1296.1	-111597.6	1.6	6321.9
1.50	634.4	626.5	0.0	888.7	19.16	1737.1	-7663.1	0.0	2905.0	36.82	1213.8	-109266.3	1.6	6815.2
1.88	659.0	1022.1	0.0	1147.6	19.53	1761.7	-6400.4	0.0	3595.5	37.19	1131.6	-106764.5	1.6	7275.9
2.25	680.9	1460.8	0.0	1385.9	19.91	1783.6	-5048.8	0.0	4217.5	37.57	1058.4	-104406.7	1.6	7658.2
2.63	705.5	2055.8	0.0	1663.4	20.29	1808.2	-3266.7	0.0	4926.5	37.94	976.2	-101614.2	1.6	8057.7
3.01	730.2	2484.8	0.0	-4388.6	20.66	1830.1	-1447.4	0.0	5564.8	38.32	903.0	-99016.5	1.6	8385.5
3.38	752.1	994.2	0.0	-4128.2	21.04	1854.7	867.6	0.0	6292.0	38.69	820.8	-95974.5	1.6	8723.7
3.76	776.7	-572.7	0.0	-3826.2	21.41	1879.3	3470.3	0.0	7029.0	39.07	747.6	-93173.4	1.6	8997.0
4.13	798.6	-1864.8	0.0	-3549.6	21.79	1901.2	6028.4	0.0	7692.3	39.44	665.4	-89923.3	1.5	9273.9
4.51	823.2	-3201.5	0.0	-3229.2	22.16	1925.9	3628.1	0.0	-23252.9	39.82	583.1	-86579.7	1.5	9518.3
4.88	845.1	-4282.9	0.0	-2936.2	22.54	1947.8	-4431.3	0.1	-22573.4	40.20	510.0	-83538.5	1.5	9708.4
5.26	869.7	-5375.8	0.0	-2597.5	22.92	1972.4	-13211.5	0.2	-21799.7	40.57	427.7	-80049.9	1.5	9891.5
5.63	894.3	-6334.2	0.0	-2249.0	23.29	1994.3	-20758.3	0.2	-21103.8	40.95	354.6	-76898.1	1.4	10027.0
6.01	916.2	-7070.1	0.0	-1931.1	23.67	2018.9	-28954.8	0.3	-20311.8	41.32	272.3	-73305.6	1.4	10148.8
6.39	940.9	-7763.9	0.0	-1564.3	24.04	2043.5	-36836.8	0.4	-19510.1	41.70	199.2	-70079.8	1.4	10229.9
6.76	962.7	-8258.6	0.0	-1230.1	24.42	2065.4	-43575.9	0.5	-18789.2	42.07	116.9	-66424.8	1.3	10290.4
7.14	987.4	-8674.2	0.0	-845.0	24.79	2090.0	-50853.3	0.5	-17969.2	42.45	34.6	-62753.3	1.3	10318.5
7.51	1009.3	-8915.6	0.0	-494.5	25.17	2111.9	-57048.9	0.6	-17232.0	42.83	-38.5	-59485.4	1.3	10316.1
7.89	1033.9	-9039.5	0.0	-91.0	25.55	2136.5	-63708.1	0.7	-16393.6	43.20	-120.8	-55814.5	1.2	10282.2
8.26	1058.5	-9003.4	0.0	322.2	25.92	2158.4	-69348.0	0.7	-15640.2	43.58	-193.9	-52565.8	1.2	10224.3
8.64	1080.4	-8833.8	0.0	697.7	26.30	2183.1	-75375.2	0.8	-14783.4	43.95	-276.2	-48937.5	1.1	10127.9
9.02	1105.0	-8484.8	0.0	1129.2	26.67	2207.7	-81062.4	0.9	-13916.9	44.33	-349.3	-45745.3	1.1	10014.4
9.39	1126.9	-8030.9	0.0	1521.0	27.05	2229.6	-85829.0	0.9	-13138.5	44.70	-431.6	-42201.8	1.1	9855.4
9.77	1151.5	-7355.2	0.0	1970.9	27.42	2254.2	-90863.2	1.0	-12253.7	45.08	-513.8	-38720.1	1.0	9663.4
10.14	1173.4	-6605.0	0.0	2379.0	27.80	2276.1	-95043.3	1.0	-11459.0	45.46	-587.0	-35686.8	1.0	9464.9
10.52	1198.1	-5589.2	0.0	2847.2	28.17	2300.7	-99411.0	1.1	-10555.8	45.83	-669.2	-32354.2	0.9	9210.3
10.89	1222.7	-4387.8	0.0	3325.2	28.55	2322.6	-102992.6	1.1	-9744.8	46.21	-742.4	-29472.1	0.9	8956.2
11.27	1244.6	-3160.9	0.0	3758.2	28.93	2347.2	-106680.0	1.2	-8823.3	46.58	-824.6	-26330.6	0.8	8639.0
11.65	1269.2	-1598.4	0.0	4254.5	29.30	2371.9	-110001.7	1.2	-7892.0	46.96	-897.8	-23637.0	0.8	8329.3
12.02	1291.1	-44.6	0.0	4703.8	29.68	2393.7	-112644.2	1.3	-7056.1	47.33	-980.0	-20728.8	0.7	7949.7
12.40	1315.7	1892.5	0.0	5218.5	30.05	2621.6	-115264.7	1.3	-6097.7	47.71	-1062.3	-17961.0	0.7	7536.9
12.77	1337.6	3785.3	0.0	5684.1	30.43	2548.4	-117265.7	1.4	-5192.5	48.08	-1135.4	-15628.3	0.6	7142.2
13.15	1362.2	4444.6	0.0	-6407.9	30.80	2466.2	-119142.2	1.4	-4205.3	48.46	-1217.7	-13158.1	0.6	6666.9
13.52	1386.8	1968.6	0.0	-5865.2	31.18	2393.0	-120487.2	1.4	-3355.1	48.84	-1290.8	-11108.5	0.5	6216.6
13.90	1408.7	-48.1	0.0	-5374.6	31.56	2310.8	-121648.8	1.5	-2429.2	49.21	-1373.1	-8978.0	0.5	5678.8
14.28	1433.4	-2106.0	0.0	-4813.5	31.93	2228.5	-122450.4	1.5	-1535.8	49.59	-1446.2	-7249.1	0.4	5172.9
14.65	1455.2	-3744.8	0.0	-4306.6	32.31	2155.4	-122871.0	1.5	-768.8	49.96	-1528.5	-5500.2	0.4	4572.6
15.03	1479.9	-5370.7	0.0	-3727.2	32.68	2073.1	-123027.4	1.5	63.3	50.34	-1610.8	-3970.6	0.3	3939.1
15.40	1501.8	-6619.3	0.0	-3204.0	33.06	2000.0	-122908.0	1.6	775.8	50.71	-1683.9	-2804.3	0.3	3348.2
15.78	1526.4	-7799.3	0.0	-2606.3	33.43	1917.7	-122508.6	1.6	1546.6	51.09	-1766.2	-1720.7	0.2	2652.2
16.15	1551.0	-8737.5	0.0	-1998.8	33.81	1844.6	-121927.1	1.6	2204.6	51.47	-1839.3	-969.7	0.2	2005.7
16.53	1572.9	-9365.5	0.0	-1450.7	34.19	1762.3	-121028.4	1.6	2914.1	51.84	-1921.6	-374.3	0.1	1247.2
16.90	1597.5	-9836.5	0.0	-824.9	34.56	1680.0	-119882.0	1.6	3591.2	52.22	-1994.7	-75.9	0.1	545.1
17.28	1619.4	-10043.0	0.0	-260.4	34.94	1606.9	-118664.5	1.6	4165.8	52.59	-2067.8	0.0	0.0	0.0



MDOT Sheeppile Manual







SupportIT, v2.37

© 1997 - 2015, GTSOFT Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSOFT@aol.com
Web: www.GTSOFT.org

Client: Case 7 Terzaghi & Peck Strut
 Loads
 Site: FOS = 1.0

Page: 5
 Date: 3.5.19

Sheet: PZ35
 Works: Temporary
 Pressure: Terzaghi
 Analysis: Gross Pressure



MDOT Sheetpile Manual

SupportIT, v2.37

© 1997 - 2015, GTSOFT Ltd.
 Tel/Fax: +44 (0)1292 477754
 Email: GTSOFT@aol.com
 Web: www.GTSOFT.org

Client: Case 7 Terzaghi & Peck Strut
Loads

Site: FOS = 1.0

Page: 6



Date: 3.5.19

Sheet: PZ35


Works: Temporary

Pressure: Terzaghi

Analysis: Gross Pressure



Waler/brace inadequately specified.
(Define L, E and I.)



Waler/brace inadequately specified.
(Define B, I and E.)



MDOT Sheetpile Manual

SupportIT, v2.37

© 1997 - 2015, GTSoft Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSoftLtd@aol.com
Web: www.GTSoft.org

Client: Case 7 Terzaghi & Peck Strut
Loads

Site: FOS = 1.0

Page: 7

Date: 3.5.19

Sheet: PZ35

Works: Temporary

Pressure: Terzaghi

Analysis: Gross Pressure

Design Report

1. Terzaghi was used for the active pressure down to the excavation depth. Rankine was used for the active pressure below the excavation depth and the passive pressure.
2. Maximum bending moment = 123027.4ftlb/ft and $f = 24966.8\text{psi}$. MINIMUM required sheet section modulus is: $Z = 59.13\text{in}^3/\text{ft}$ (= M/f). Sheet section modulus in this design is $Z = 48.90\text{in}^3/\text{ft}$, and is **LESS THAN minimum required. Z should be increased.**
3. Bending Moment (123027.4ftlb/ft) **exceeds maximum allowed sheet moment** (101739.5ftlb/ft).
4. Frame primary axis bending moments checked. Users should manually check the axial load capacities and the effects of combined axial and bending stresses to confirm frames are suitable.
5. FOS = 1.00 (Gross Pressure)
This is the factor of safety against rotation about the lowest frame.
The FOS can be changed using 'Defined FOS' or 'Manual' in the 'Wall' page.



MDOT Sheetpile Manual

SupportIT, v2.37

© 1997 - 2015, GTSoft Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSoftLtd@aol.com
Web: www.GTSoft.org

Client: Case 7 Terzaghi & Peck Strut
Loads

Site: FOS = 1.0

Page: 1

Date: 3.5.19


Sheet: PZ22

Works: Temporary

Pressure: Terzaghi

Analysis: Gross Pressure

	Maximum	d (ft)
○	1221.0 psf	30.07
□	23189.2 ftlb/ft	30.03
●	0.6 in	31.35



MDOT Sheetpile Manual

SupportIT, v2.37

© 1997 - 2015, GTSOFT Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSOFT@aol.com
Web: www.GTSOFT.org

Client: Case 7 Terzaghi & Peck Strut
Loads
Site: FOS = 1.0

Page: 2
Date: 3.5.19

Sheet: PZ22
Works: Temporary
Pressure: Terzaghi
Analysis: Gross Pressure

Input Data

Depth Of Excavation = 30.00ft
Surcharge = 359.9psf

Depth Of Active Water = 30.00ft
Depth Of Passive Water = 30.00ft

Water Density = 62.43pcf
Minimum Fluid Density = 31.82pcf

Soil Profile

Depth (ft)	Soil Name	γ (pcf)	γ' (pcf)	C (psf)	C_a (psf)	ϕ (°)	δ (°)	K_a	K_{ac}	K_p	K_{pc}
0.00	Dense Fine Sand	120.00	71.10	0.0	0.0	32.0	0.0	0.31	0.00	3.25	0.00

Solution

Sheet

Sheet Name	E (psi)	I (in ⁴ /ft)	f (psi)	Z (in ³ /ft)	Allowed M _{max} (ftlb/ft)	b (in)	A (in ² /ft)	W (lb/ft)	Upstand (ft)	Toe (ft)	Length (ft)
PZ22	3.04E+07	84.70	24966.8	18.40	38282.3	22.01	6.46	40.3	0.00	11.71	41.71

Load Model: Area Distribution

Supports

d (ft)	Type	Load (lb/ft)
3.00	Brace	6695.9
13.00	Brace	7926.8
22.00	Brace	10535.7

Maxima

	Maximum	Depth (ft)
Pressure	1221.0 psf	30.07
Bending Moment	23189.2 ftlb/ft	30.03
Deflection	0.6 in	31.35
Shear Force	6713.9 lb/ft	22.00



MDOT Sheetpile Manual

SupportIT, v2.37

© 1997 - 2015, GTSOFT Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSOFT@aol.com
Web: www.GTSOFT.org

Client: Case 7 Terzaghi & Peck Strut
Loads

Site: FOS = 1.0

Page: 3

Date: 3.5.19





Sheet: PZ22

Works: Temporary

Pressure: Terzaghi

Analysis: Gross Pressure

	Maximum	d (ft)
○	1221.0 psf	30.07
□	23189.2 ftlb/ft	30.03
◇	6713.9 lb/ft	22.00
●	0.6 in	31.35



MDOT Sheetpile Manual

SupportIT, v2.37

© 1997 - 2015, GTSOFT Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSOFT@aol.com
Web: www.GTSOFT.org

Client: Case 7 Terzaghi & Peck Strut
 Loads
 Site: FOS = 1.0

Page: 4
 Date: 3.5.19

Sheet: PZ22
 Works: Temporary
 Pressure: Terzaghi
 Analysis: Gross Pressure

depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)	depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)	depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)
0.00	837.0	0.0	0.0	0.0	14.00	837.0	408.7	0.0	-2869.4	28.01	837.0	-21463.3	0.5	-1680.9
0.30	837.0	36.8	0.0	264.9	14.30	837.0	-366.8	0.0	-2636.7	28.30	837.0	-21904.7	0.5	-1448.1
0.60	837.0	139.1	0.0	500.4	14.60	837.0	-1161.2	0.0	-2374.8	28.60	837.0	-22323.5	0.6	-1186.3
0.89	837.0	332.5	0.0	765.3	14.90	837.0	-1873.2	0.0	-2113.0	28.90	837.0	-22626.6	0.6	-953.6
1.19	837.0	574.0	0.0	1000.8	15.19	837.0	-2436.7	0.0	-1880.3	29.20	837.0	-22889.9	0.6	-691.7
1.49	837.0	923.9	0.0	1265.7	15.49	837.0	-2992.8	0.0	-1618.4	29.50	837.0	-23070.8	0.6	-429.9
1.79	837.0	1304.5	0.0	1501.2	15.79	837.0	-3417.7	0.0	-1385.7	29.79	837.0	-23162.5	0.6	-197.1
2.09	837.0	1810.9	0.0	1766.1	16.09	837.0	-3817.8	0.0	-1123.9	30.09	1206.5	-23187.6	0.6	90.9
2.38	837.0	2400.2	0.0	2031.0	16.39	837.0	-4104.2	0.0	-891.1	30.39	1148.3	-23132.4	0.6	417.3
2.68	837.0	2993.6	0.0	2266.5	16.68	837.0	-4348.4	0.0	-629.3	30.69	1082.9	-22980.6	0.6	765.1
2.98	837.0	3738.8	0.0	-4164.8	16.98	837.0	-4510.1	0.0	-367.5	30.98	1024.8	-22770.3	0.6	1057.2
3.28	837.0	2609.0	0.0	-3932.1	17.28	837.0	-4584.6	0.0	-134.7	31.28	959.4	-22453.8	0.6	1366.4
3.58	837.0	1415.3	0.0	-3670.3	17.58	837.0	-4590.5	0.0	127.1	31.58	894.0	-22057.9	0.6	1655.2
3.87	837.0	423.0	0.0	-3437.5	17.88	837.0	-4527.3	0.0	359.9	31.88	835.9	-21643.7	0.6	1894.7
4.17	837.0	-615.9	0.0	-3175.7	18.17	837.0	-4379.5	0.0	621.7	32.18	770.5	-21112.6	0.6	2144.8
4.47	837.0	-1573.0	0.0	-2913.9	18.47	837.0	-4179.8	0.0	854.4	32.47	712.4	-20586.8	0.6	2350.0
4.77	837.0	-2354.9	0.0	-2681.1	18.77	837.0	-3878.5	0.0	1116.3	32.77	647.0	-19939.8	0.6	2561.5
5.06	837.0	-3157.2	0.0	-2419.3	19.07	837.0	-3495.9	0.0	1378.1	33.07	588.9	-19319.5	0.6	2732.3
5.36	837.0	-3801.7	0.0	-2186.6	19.37	837.0	-3087.5	0.0	1610.8	33.37	523.5	-18575.9	0.6	2905.1
5.66	837.0	-4449.3	0.1	-1924.7	19.66	837.0	-2551.4	0.0	1872.7	33.67	458.1	-17789.0	0.6	3057.5
5.96	837.0	-4956.2	0.1	-1692.0	19.96	837.0	-2006.6	0.0	2105.4	33.96	400.0	-17057.4	0.6	3175.8
6.26	837.0	-5449.1	0.1	-1430.2	20.26	837.0	-1316.9	0.0	2367.2	34.26	334.6	-16203.4	0.5	3289.6
6.55	837.0	-5860.1	0.1	-1168.3	20.56	837.0	-635.7	0.0	2600.0	34.56	276.4	-15420.9	0.5	3373.5
6.85	837.0	-6156.6	0.1	-935.6	20.86	837.0	207.5	0.0	2861.8	34.86	211.1	-14519.1	0.5	3448.6
7.15	837.0	-6412.9	0.1	-673.8	21.15	837.0	1131.9	0.0	3123.6	35.16	152.9	-13702.7	0.5	3498.2
7.45	837.0	-6571.9	0.1	-441.0	21.45	837.0	2021.9	0.0	3356.4	35.45	87.5	-12772.4	0.5	3534.7
7.75	837.0	-6673.5	0.1	-179.2	21.75	837.0	3099.9	0.0	3618.2	35.75	22.1	-11835.0	0.5	3550.7
8.04	837.0	-6695.0	0.1	53.6	22.05	837.0	3761.6	0.0	-6684.8	36.05	-36.0	-11000.0	0.5	3547.7
8.34	837.0	-6642.2	0.1	315.4	22.34	837.0	1696.1	0.0	-6423.0	36.35	-101.4	-10063.6	0.4	3524.5
8.64	837.0	-6508.1	0.1	577.2	22.64	837.0	-70.8	0.1	-6190.2	36.65	-159.5	-9238.4	0.4	3486.2
8.94	837.0	-6320.6	0.1	810.0	22.94	837.0	-1980.8	0.1	-5928.4	36.94	-224.9	-8323.1	0.4	3423.2
9.24	837.0	-6032.8	0.1	1071.8	23.24	837.0	-3808.4	0.1	-5666.5	37.24	-283.0	-7525.3	0.4	3349.7
9.53	837.0	-5708.8	0.1	1304.5	23.54	837.0	-5363.9	0.2	-5433.8	37.54	-348.4	-6650.7	0.3	3247.0
9.83	837.0	-5267.4	0.1	1566.4	23.83	837.0	-7036.0	0.2	-5172.0	37.84	-413.8	-5805.7	0.3	3123.4
10.13	837.0	-4806.8	0.1	1799.1	24.13	837.0	-8453.2	0.2	-4939.2	38.14	-471.9	-5084.0	0.3	2995.9
10.43	837.0	-4211.7	0.1	2060.9	24.43	837.0	-9969.8	0.2	-4677.4	38.43	-537.3	-4310.2	0.3	2832.6
10.73	837.0	-3535.4	0.0	2322.8	24.73	837.0	-11248.8	0.3	-4444.7	38.73	-595.4	-3660.5	0.3	2669.7
11.02	837.0	-2865.9	0.0	2555.5	25.03	837.0	-12609.9	0.3	-4182.8	39.03	-660.8	-2977.6	0.2	2466.7
11.32	837.0	-2035.9	0.0	2817.3	25.32	837.0	-13888.6	0.3	-3921.0	39.33	-719.0	-2417.6	0.2	2268.6
11.62	837.0	-1229.8	0.0	3050.1	25.62	837.0	-14956.1	0.4	-3688.3	39.62	-784.4	-1845.4	0.2	2025.9
11.92	837.0	-246.2	0.0	3311.9	25.92	837.0	-16079.4	0.4	-3426.4	39.92	-849.7	-1340.0	0.2	1762.2
12.22	837.0	696.4	0.0	3544.7	26.22	837.0	-17008.6	0.4	-3193.7	40.22	-907.9	-951.2	0.1	1510.2
12.51	837.0	1833.7	0.0	3806.5	26.52	837.0	-17976.3	0.4	-2931.9	40.52	-973.3	-586.9	0.1	1206.8
12.81	837.0	3052.3	0.0	4068.3	26.81	837.0	-18767.4	0.4	-2699.1	40.82	-1031.4	-332.3	0.1	919.4
13.11	837.0	3379.4	0.0	-3625.8	27.11	837.0	-19579.6	0.5	-2437.3	41.11	-1096.8	-129.0	0.1	576.4
13.41	837.0	2273.2	0.0	-3364.0	27.41	837.0	-20309.4	0.5	-2175.4	41.41	-1154.9	-26.3	0.0	253.7
13.70	837.0	1359.1	0.0	-3131.2	27.71	837.0	-20889.0	0.5	-1942.7	41.71	-1213.0	0.0	0.0	0.0



MDOT Sheeppile Manual

Client: Case 7 Terzaghi & Peck Strut
Loads

Site: FOS = 1.0

Page: 5







Date: 3.5.19

Sheet: PZ22

Works: Temporary

Pressure: Terzaghi

Analysis: Gross Pressure



MDOT Sheetpile Manual

SupportIT, v2.37

© 1997 - 2015, GTSOFT Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSOFT@aol.com
Web: www.GTSOFT.org

Client: Case 7 Terzaghi & Peck Strut
Loads

Site: FOS = 1.0

Page: 6



Date: 3.5.19

Sheet: PZ22


Works: Temporary

Pressure: Terzaghi

Analysis: Gross Pressure



Water/brace inadequately specified.
(Define L, E and I.)



Water/brace inadequately specified.
(Define B, I and E.)



MDOT Sheetpile Manual

SupportIT, v2.37

© 1997 - 2015, GTSoft Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSoftLtd@aol.com
Web: www.GTSoft.org

Client: Case 7 Terzaghi & Peck Strut
Loads

Site: FOS = 1.0

Page: 7

Date: 3.5.19

Sheet: PZ22

Works: Temporary

Pressure: Terzaghi

Analysis: Gross Pressure

Design Report

1. Terzaghi was used for the active pressure down to the excavation depth. Rankine was used for the active pressure below the excavation depth and the passive pressure.
2. Maximum bending moment = 23189.2ftlb/ft and $f = 24966.8\text{psi}$. MINIMUM required sheet section modulus is: $Z = 11.15\text{in}^3/\text{ft}$ ($= M/f$). Sheet section modulus in this design is $Z = 18.40\text{in}^3/\text{ft}$, and is satisfactory.
3. Frame primary axis bending moments checked. Users should manually check the axial load capacities and the effects of combined axial and bending stresses to confirm frames are suitable.
4. FOS = 1.00 (Gross Pressure)
This is the factor of safety against rotation about the lowest frame.
The FOS can be changed using 'Defined FOS' or 'Manual' in the 'Wall' page.



MDOT Sheetpile Manual

Appendix B.8 – SupportIT Output, Case 8

Case 8 – Braced Cofferdam TERS in Medium Stiff Clay

SupportIT output is included here for the four stages of construction and with a FOS = 1.5

Client: Case 8 Braced - Clay - Stage 1

Site: FOS = 1.0

Page: 1

Date: 3.11.19

Sheet: PZ22


Works: Temporary

Pressure: Rankine

Analysis: Net Pressure

Toe: Cantilever

	Maximum	d (ft)
○	471.8 psf	8.00
□	5303.4 ftlb/ft	11.60
●	0.3 in	0.00



MDOT Sheetpile Manual

SupportIT, v2.37

© 1997 - 2015, GTSOFT Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSOFT@aol.com
Web: www.GTSOFT.org

Client: Case 8 Braced - Clay - Stage 1

Site: FOS = 1.0

Page: 2

Date: 3.11.19

Sheet: PZ22

Works: Temporary

Pressure: Rankine

Analysis: Net Pressure

Toe: Cantilever

Input Data

Depth Of Excavation = 8.00ft
Surcharge = 360.0psf

Depth Of Active Water = 30.00ft
Depth Of Passive Water = 30.00ft

Water Density = 62.43pcf
Minimum Fluid Density = 31.82pcf

Soil Profile

Depth (ft)	Soil Name	γ (pcf)	γ' (pcf)	C (psf)	C_a (psf)	ϕ (°)	δ (°)	K_a	K_{ac}	K_p	K_{pc}
0.00	Soft Clay	118.37	56.00	417.6	0.0	0.0	0.0	1.00	2.00	1.00	2.00
30.00	Firm Clay	118.37	56.00	1500.0	0.0	0.0	0.0	1.00	2.00	1.00	2.00

Solution

Sheet

Sheet Name	E (psi)	I (in ⁴ /ft)	f (psi)	Z (in ³ /ft)	Allowed M_{max} (ftlb/ft)	b (in)	A (in ² /ft)	W (lb/ft)	Upstand (ft)	Toe (ft)	Length (ft)
PZ22	3.04E+07	84.70	24966.8	18.40	38282.3	22.01	6.46	40.3	0.00	10.78	18.78

Maxima

	Maximum	Depth (ft)
Pressure	471.8 psf	8.00
Bending Moment	5303.4 ftlb/ft	11.60
Deflection	0.3 in	0.00
Shear Force	1301.4 lb/ft	8.01



MDOT Sheetpile Manual

SupportIT, v2.37





© 1997 - 2015, GTSoft Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSoftLtd@aol.com
Web: www.GTSoft.org

Client: Case 8 Braced - Clay - Stage 1
 Site: FOS = 1.0

Page: 3
 Date: 3.11.19

Sheet: PZ22
 Works: Temporary
 Pressure: Rankine
 Analysis: Net Pressure
 Toe: Cantilever

	Maximum	d (ft)
○	471.8 psf	8.00
□	5303.4 ftlb/ft	11.60
◇	1301.4 lb/ft	8.01
●	0.3 in	0.00



MDOT Sheetpile Manual

Client: Case 8 Braced - Clay - Stage 1

Site: FOS = 1.0

Page: 4

Date: 3.11.19

Sheet: PZ22

Works: Temporary

Pressure: Rankine

Analysis: Net Pressure

Toe: Cantilever

depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)	depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)	depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)
0.00	0.0	-0.1	0.3	0.0	6.31	271.5	1339.8	0.1	664.5	12.61	-363.4	4930.0	0.0	0.0
0.13	4.5	-0.1	0.3	0.4	6.44	286.3	1424.9	0.1	699.5	12.75	-363.4	4830.4	0.0	0.0
0.27	8.5	0.0	0.3	1.2	6.57	303.0	1526.1	0.1	741.1	12.88	-363.4	4704.2	0.0	0.0
0.40	13.0	0.3	0.3	2.7	6.71	319.6	1633.2	0.1	785.1	13.01	-363.4	4579.5	0.0	0.0
0.54	16.9	0.7	0.3	4.6	6.84	334.5	1733.7	0.1	826.2	13.15	-363.4	4425.0	0.0	0.0
0.67	21.4	1.5	0.3	7.4	6.98	351.1	1853.1	0.1	874.6	13.28	-363.4	4255.6	0.0	0.0
0.80	25.4	2.6	0.3	10.3	7.11	366.0	1965.1	0.1	919.6	13.42	-363.4	4092.6	0.0	0.0
0.94	29.9	4.3	0.3	14.3	7.24	382.6	2097.9	0.1	972.5	13.55	-363.4	3894.9	0.0	0.0
1.07	34.4	6.6	0.3	18.8	7.38	397.5	2222.3	0.1	1021.4	13.68	-363.4	3711.2	0.0	0.0
1.21	38.4	9.2	0.2	23.4	7.51	414.1	2369.8	0.1	1078.7	13.82	-363.4	3509.2	0.0	0.0
1.34	42.9	12.9	0.2	29.2	7.65	430.8	2525.4	0.1	1138.4	13.95	-363.4	3334.5	0.0	0.0
1.48	46.9	16.8	0.2	34.8	7.78	445.6	2671.0	0.1	1193.3	14.09	-363.4	3143.4	0.0	0.0
1.61	51.3	22.2	0.2	41.8	7.92	462.3	2843.1	0.1	1257.4	14.22	-363.4	2957.8	0.0	0.0
1.74	55.3	27.8	0.2	48.5	8.05	-363.4	3003.5	0.1	1290.1	14.36	-363.4	2797.6	0.0	0.0
1.88	59.8	35.1	0.2	56.6	8.18	-363.4	3182.1	0.1	1238.9	14.49	-363.4	2622.7	0.0	0.0
2.01	64.3	43.6	0.2	65.4	8.32	-363.4	3334.7	0.1	1193.4	14.62	-363.4	2472.0	0.0	0.0
2.15	68.3	52.3	0.2	73.8	8.45	-363.4	3499.6	0.1	1142.2	14.76	-363.4	2307.7	0.0	0.0
2.28	72.8	63.3	0.2	83.7	8.59	-363.4	3657.3	0.1	1091.0	14.89	-363.4	2166.5	0.0	0.0
2.41	76.8	74.3	0.2	93.1	8.72	-363.4	3791.4	0.1	1045.5	15.03	-363.4	2012.9	0.0	0.0
2.55	81.2	88.1	0.2	104.3	8.85	-363.4	3935.5	0.1	994.3	15.16	-363.4	1865.0	0.0	0.0
2.68	85.2	101.7	0.2	114.7	8.99	-363.4	4057.5	0.1	948.8	15.29	-363.4	1738.2	0.0	0.0
2.82	89.7	118.6	0.2	127.1	9.12	-363.4	4188.0	0.1	897.6	15.43	-363.4	1601.0	0.0	0.0
2.95	94.2	137.3	0.2	140.1	9.26	-363.4	4297.9	0.1	852.1	15.56	-363.4	1483.8	0.0	0.0
3.09	98.2	155.5	0.2	152.2	9.39	-363.4	4414.7	0.1	800.9	15.70	-363.4	1357.2	0.0	0.0
3.22	102.7	177.8	0.2	166.3	9.53	-363.4	4524.3	0.1	749.7	15.83	-363.4	1249.4	0.0	0.0
3.35	106.7	199.4	0.2	179.5	9.66	-363.4	4615.7	0.0	704.2	15.97	-363.4	1133.4	0.0	0.0
3.49	111.2	225.6	0.2	194.9	9.79	-363.4	4711.7	0.0	653.0	16.10	-363.4	1023.1	0.0	0.0
3.62	115.1	250.8	0.2	209.1	9.93	-363.4	4791.0	0.0	607.5	16.23	-363.4	929.9	0.0	0.0
3.76	119.6	281.3	0.2	225.6	10.06	-363.4	4873.3	0.0	556.3	16.37	-363.4	830.2	0.0	0.0
3.89	124.1	314.1	0.2	242.8	10.20	-363.4	4940.5	0.0	510.8	16.50	-363.4	746.4	0.0	0.0
4.02	128.1	345.4	0.2	258.6	10.33	-363.4	5009.3	0.0	459.6	16.64	-363.4	657.4	0.0	0.0
4.16	132.6	383.0	0.2	277.0	10.46	-363.4	5070.8	0.0	408.4	16.77	-363.4	583.1	0.0	0.0
4.29	136.6	418.6	0.2	293.9	10.60	-363.4	5119.4	0.0	362.9	16.90	-363.4	504.8	0.0	0.0
4.43	141.1	461.2	0.2	313.5	10.73	-363.4	5167.3	0.0	311.7	17.04	-363.4	432.1	0.0	0.0
4.56	145.1	501.5	0.2	331.5	10.87	-363.4	5203.9	0.0	266.2	17.17	-363.4	372.3	0.0	0.0
4.70	149.5	549.4	0.2	352.2	11.00	-363.4	5238.2	0.0	215.0	17.31	-363.4	310.3	0.0	0.0
4.83	154.0	600.4	0.2	373.7	11.14	-363.4	5262.6	0.0	169.5	17.44	-363.4	259.9	0.0	0.0
4.96	158.0	648.2	0.2	393.2	11.27	-363.4	5283.3	0.0	118.3	17.58	-363.4	208.5	0.0	0.0
5.10	162.5	705.1	0.1	415.8	11.40	-363.4	5296.7	0.0	67.1	17.71	-363.4	167.6	0.0	0.0
5.23	166.5	758.2	0.1	436.5	11.54	-363.4	5302.6	0.0	21.6	17.84	-363.4	126.9	0.0	0.0
5.37	171.0	821.2	0.1	460.3	11.67	-363.4	5302.1	0.0	0.0	17.98	-363.4	91.9	0.0	0.0
5.50	175.1	880.0	0.1	482.0	11.81	-363.4	5291.0	0.0	0.0	18.11	-363.4	65.5	0.0	0.0
5.63	191.8	949.5	0.1	507.9	11.94	-363.4	5264.1	0.0	0.0	18.25	-363.4	41.2	0.0	0.0
5.77	208.5	1022.8	0.1	536.3	12.07	-363.4	5227.9	0.0	0.0	18.38	-363.4	24.1	0.0	0.0
5.90	223.3	1091.4	0.1	563.4	12.21	-363.4	5172.7	0.0	0.0	18.51	-363.4	10.4	0.0	0.0
6.04	240.0	1172.8	0.1	596.2	12.34	-363.4	5102.9	0.0	0.0	18.65	-363.4	3.0	0.0	0.0
6.17	254.8	1249.2	0.1	627.3	12.48	-363.4	5028.4	0.0	0.0	18.78	-363.4	0.0	0.0	0.0



MDOT Sheetpile Manual

SupportIT, v2.37

© 1997 - 2015, GTSOFT Ltd.
 Tel/Fax: +44 (0)1292 477754
 Email: GTSOFT@aol.com
 Web: www.GTSOFT.org

Client: Case 8 Braced - Clay - Stage 1

Site: FOS = 1.0

Page: 5

Date: 3.11.19







Sheet: PZ22

Works: Temporary

Pressure: Rankine

Analysis: Net Pressure

Toe: Cantilever



MDOT Sheetpile Manual

SupportIT, v2.37

© 1997 - 2015, GTSOFT Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSOFT@aol.com
Web: www.GTSOFT.org

Client: Case 8 Braced - Clay - Stage 1

Site: FOS = 1.0

Page: 6

Date: 3.11.19

Sheet: PZ22

Works: Temporary

Pressure: Rankine

Analysis: Net Pressure

Toe: Cantilever

Δ

B

▽

◀

L

▶



MDOT Sheetpile Manual

SupportIT, v2.37

© 1997 - 2015, GTSoft Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSoftLtd@aol.com
Web: www.GTSoft.org

Client: Case 8 Braced - Clay - Stage 1
Site: FOS = 1.0

Page: 7
Date: 3.11.19

Sheet: PZ22
Works: Temporary
Pressure: Rankine
Analysis: Net Pressure
Toe: Cantilever

Design Report

1. Total stress values are being used (i.e. $C > 0$). Note that the Piling Handbook and CIRIA SP95 recommend that effective stress values be used in 'long term' excavations.
2. Maximum bending moment = 5303.4ftlb/ft and $f = 24966.8$ psi. MINIMUM required sheet section modulus is: $Z = 2.55$ in³/ft (= M/f). Sheet section modulus in this design is $Z = 18.40$ in³/ft, and is satisfactory.
3. FOS = 1.00 (Net Pressure)
This is the factor of safety against rotation about the toe.
The FOS can be changed using 'Defined FOS' or 'Manual' in the 'Wall' page.



MDOT Sheetpile Manual

SupportIT, v2.37

© 1997 - 2015, GTSoft Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSoftLtd@aol.com
Web: www.GTSoft.org

Client: Case 8 Braced - Clay - Stage 1

Site: FOS = 1.50

Page: 1

Date: 3.11.19

Sheet: PZ35


Works: Temporary

Pressure: Rankine

Analysis: Net Pressure

Toe: Cantilever

	Maximum	d (ft)
○	472.8 psf	8.00
□	5293.7 ftlb/ft	11.58
●	0.1 in	0.00



MDOT Sheetpile Manual

SupportIT, v2.37

© 1997 - 2015, GTSOFT Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSOFT@aol.com
Web: www.GTSOFT.org

Client: Case 8 Braced - Clay - Stage 1
 Site: FOS = 1.50

Page: 2
 Date: 3.11.19

Sheet: PZ35
 Works: Temporary
 Pressure: Rankine
 Analysis: Net Pressure
 Toe: Cantilever

Input Data

Depth Of Excavation = 8.00ft
 Surcharge = 360.0psf

Depth Of Active Water = 30.00ft
 Depth Of Passive Water = 30.00ft

Water Density = 62.43pcf
 Minimum Fluid Density = 31.82pcf

Soil Profile

Depth (ft)	Soil Name	γ (pcf)	γ' (pcf)	C (psf)	C_a (psf)	ϕ (°)	δ (°)	K_a	K_{ac}	K_p	K_{pc}
0.00	Soft Clay	118.37	56.00	417.6	0.0	0.0	0.0	1.00	2.00	1.00	2.00
30.00	Firm Clay	118.37	56.00	1500.0	0.0	0.0	0.0	1.00	2.00	1.00	2.00

Solution

Sheet

Sheet Name	E (psi)	I (in ⁴ /ft)	f (psi)	Z (in ³ /ft)	Allowed M_{max} (ftlb/ft)	b (in)	A (in ² /ft)	W (lb/ft)	Upstand (ft)	Toe (ft)	Length (ft)
PZ35	3.04E+07	369.40	24966.8	48.90	101739.5	22.64	10.28	66.0	0.00	15.27	23.27

Maxima

	Maximum	Depth (ft)
Pressure	472.8 psf	8.00
Bending Moment	5293.7 ftlb/ft	11.58
Deflection	0.1 in	0.00
Shear Force	1299.9 lb/ft	8.01



MDOT Sheetpile Manual

SupportIT, v2.37





© 1997 - 2015, GTSoft Ltd.
 Tel/Fax: +44 (0)1292 477754
 Email: GTSoftLtd@aol.com
 Web: www.GTSoft.org

Client: Case 8 Braced - Clay - Stage 1
 Site: FOS = 1.50

Page: 3
 Date: 3.11.19

Sheet: PZ35
 Works: Temporary
 Pressure: Rankine
 Analysis: Net Pressure
 Toe: Cantilever

	Maximum	d (ft)
○	472.8 psf	8.00
□	5293.7 ftlb/ft	11.58
◇	1299.9 lb/ft	8.01
●	0.1 in	0.00



MDOT Sheetpile Manual

Client: Case 8 Braced - Clay - Stage 1

Site: FOS = 1.50

Page: 4

Date: 3.11.19

Sheet: PZ35

Works: Temporary

Pressure: Rankine

Analysis: Net Pressure

Toe: Cantilever

depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)	depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)	depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)
0.00	0.0	0.0	0.1	0.0	7.81	449.8	2713.9	0.0	1210.2	15.62	-363.4	1440.1	0.0	0.0
0.17	5.6	0.1	0.1	0.5	7.98	468.2	2906.4	0.0	1281.6	15.79	-363.4	1303.3	0.0	0.0
0.33	10.5	0.2	0.1	1.8	8.14	-363.4	3129.9	0.0	1250.6	15.96	-363.4	1157.7	0.0	0.0
0.50	16.1	0.7	0.1	4.2	8.31	-363.4	3343.2	0.0	1187.2	16.12	-363.4	1035.4	0.0	0.0
0.66	21.0	1.6	0.1	7.1	8.48	-363.4	3523.6	0.0	1130.8	16.29	-363.4	906.0	0.0	0.0
0.83	26.6	3.1	0.1	11.3	8.64	-363.4	3716.0	0.0	1067.4	16.46	-363.4	785.3	0.0	0.0
1.00	31.5	5.2	0.1	15.9	8.81	-363.4	3877.8	0.0	1011.0	16.62	-363.4	685.3	0.0	0.0
1.16	37.1	8.4	0.1	21.9	8.98	-363.4	4049.3	0.0	947.6	16.79	-363.4	580.8	0.0	0.0
1.33	42.6	12.7	0.1	28.9	9.14	-363.4	4192.5	0.0	891.2	16.95	-363.4	495.2	0.0	0.0
1.50	47.6	17.7	0.1	36.0	9.31	-363.4	4343.1	0.0	827.7	17.12	-363.4	406.9	0.0	0.0
1.66	53.1	24.6	0.1	44.8	9.47	-363.4	4482.6	0.0	764.3	17.29	-363.4	335.8	0.0	0.0
1.83	58.0	32.2	0.1	53.5	9.64	-363.4	4597.4	0.0	707.9	17.45	-363.4	264.0	0.0	0.0
1.99	63.6	42.3	0.1	64.1	9.81	-363.4	4716.0	0.0	644.5	17.62	-363.4	200.9	0.0	0.0
2.16	68.5	53.0	0.1	74.4	9.97	-363.4	4812.2	0.0	588.1	17.78	-363.4	152.0	0.0	0.0
2.33	74.1	66.9	0.1	86.9	10.14	-363.4	4909.9	0.0	524.7	17.95	-363.4	105.0	0.0	0.0
2.49	79.7	83.1	0.0	100.4	10.31	-363.4	4987.5	0.0	468.3	18.12	-363.4	70.7	0.0	0.0
2.66	84.6	99.5	0.0	113.2	10.47	-363.4	5064.3	0.0	404.9	18.28	-363.4	40.0	0.0	0.0
2.83	90.2	120.5	0.0	128.5	10.64	-363.4	5130.0	0.0	341.5	18.45	-363.4	20.0	0.0	0.0
2.99	95.1	141.4	0.0	142.9	10.80	-363.4	5179.2	0.0	285.1	18.62	-363.4	5.9	0.0	0.0
3.16	100.7	167.6	0.0	160.1	10.97	-363.4	5224.0	0.0	221.6	18.78	-363.4	0.2	0.0	0.0
3.32	105.6	193.6	0.0	176.1	11.14	-363.4	5254.5	0.0	165.3	18.95	-363.4	0.0	0.0	0.0
3.49	111.2	225.7	0.0	195.1	11.30	-363.4	5278.5	0.0	101.8	19.11	-363.4	0.0	0.0	0.0
3.66	116.7	261.3	0.0	215.0	11.47	-363.4	5290.4	0.0	45.5	19.28	-363.4	0.0	0.0	0.0
3.82	121.7	295.9	0.0	233.6	11.64	-363.4	5293.3	0.0	0.0	19.45	-363.4	0.0	0.0	0.0
3.99	127.2	338.4	0.0	255.3	11.80	-363.4	5278.3	0.0	0.0	19.61	-363.4	0.0	0.0	0.0
4.16	132.2	379.3	0.0	275.5	11.97	-363.4	5246.6	0.0	0.0	19.78	-363.4	0.0	0.0	0.0
4.32	137.7	429.2	0.0	299.1	12.13	-363.4	5190.2	0.0	0.0	19.95	-363.4	0.0	0.0	0.0
4.49	142.7	477.1	0.0	320.9	12.30	-363.4	5121.6	0.0	0.0	20.11	-363.4	0.0	0.0	0.0
4.65	148.2	535.1	0.0	346.3	12.47	-363.4	5023.6	0.0	0.0	20.28	-363.4	0.0	0.0	0.0
4.82	153.8	597.5	0.0	372.7	12.63	-363.4	4918.2	0.0	0.0	20.44	-363.4	0.0	0.0	0.0
4.99	158.7	657.0	0.0	397.0	12.80	-363.4	4778.6	0.0	0.0	20.61	-363.4	0.0	0.0	0.0
5.15	164.3	728.5	0.0	425.3	12.96	-363.4	4617.2	0.0	0.0	20.78	-363.4	0.0	0.0	0.0
5.32	169.2	796.2	0.0	451.2	13.13	-363.4	4455.8	0.0	0.0	20.94	-363.4	0.0	0.0	0.0
5.49	174.8	877.2	0.0	481.2	13.30	-363.4	4252.8	0.0	0.0	21.11	-363.4	0.0	0.0	0.0
5.65	192.8	953.8	0.0	509.9	13.46	-363.4	4054.5	0.0	0.0	21.28	-363.4	0.0	0.0	0.0
5.82	213.4	1045.5	0.0	545.5	13.63	-363.4	3810.5	0.0	0.0	21.44	-363.4	0.0	0.0	0.0
5.98	234.1	1143.7	0.0	584.8	13.80	-363.4	3585.9	0.0	0.0	21.61	-363.4	0.0	0.0	0.0
6.15	252.4	1237.0	0.0	622.7	13.96	-363.4	3341.3	0.0	0.0	21.77	-363.4	0.0	0.0	0.0
6.32	273.1	1349.2	0.0	668.8	14.13	-363.4	3105.6	0.0	0.0	21.94	-363.4	0.0	0.0	0.0
6.48	291.5	1455.9	0.0	712.7	14.29	-363.4	2903.0	0.0	0.0	22.11	-363.4	0.0	0.0	0.0
6.65	312.1	1584.3	0.0	765.6	14.46	-363.4	2683.4	0.0	0.0	22.27	-363.4	0.0	0.0	0.0
6.81	330.5	1706.4	0.0	815.6	14.63	-363.4	2495.6	0.0	0.0	22.44	-363.4	0.0	0.0	0.0
6.98	351.1	1853.4	0.0	875.3	14.79	-363.4	2292.3	0.0	0.0	22.61	-363.4	0.0	0.0	0.0
7.15	371.8	2011.0	0.0	938.6	14.96	-363.4	2118.8	0.0	0.0	22.77	-363.4	0.0	0.0	0.0
7.31	390.2	2160.6	0.0	997.9	15.13	-363.4	1931.9	0.0	0.0	22.94	-363.4	0.0	0.0	0.0
7.48	410.8	2340.1	0.0	1068.0	15.29	-363.4	1753.4	0.0	0.0	23.10	-363.4	0.0	0.0	0.0
7.65	429.2	2510.2	0.0	1133.3	15.46	-363.4	1602.1	0.0	0.0	23.27	-363.4	0.0	0.0	0.0



MDOT Sheetpile Manual

SupportIT, v2.37

© 1997 - 2015, GTSOFT Ltd.
 Tel/Fax: +44 (0)1292 477754
 Email: GTSOFT@aol.com
 Web: www.GTSOFT.org

Client: Case 8 Braced - Clay - Stage 1

Site: FOS = 1.50

Page: 5

Date: 3.11.19







Sheet: PZ35

Works: Temporary

Pressure: Rankine

Analysis: Net Pressure

Toe: Cantilever



MDOT Sheetpile Manual

SupportIT, v2.37

© 1997 - 2015, GTSOFT Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSOFT@aol.com
Web: www.GTSOFT.org

Client: Case 8 Braced - Clay - Stage 1
Site: FOS = 1.50

Page: 6
Date: 3.11.19

Sheet: PZ35
Works: Temporary
Pressure: Rankine
Analysis: Net Pressure
Toe: Cantilever



B



L



MDOT Sheetpile Manual

SupportIT, v2.37



© 1997 - 2015, GTSOFT Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSOFT@aol.com
Web: www.GTSOFT.org

Client: Case 8 Braced - Clay - Stage 1
Site: FOS = 1.50

Page: 7
Date: 3.11.19

Sheet: PZ35
Works: Temporary
Pressure: Rankine
Analysis: Net Pressure
Toe: Cantilever


Design Report

1. Total stress values are being used (i.e. $C > 0$). Note that the Piling Handbook and CIRIA SP95 recommend that effective stress values be used in 'long term' excavations.
2. Maximum bending moment = 5293.7ftlb/ft and $f = 24966.8$ psi. MINIMUM required sheet section modulus is: $Z = 2.54$ in³/ft (= M/f). Sheet section modulus in this design is $Z = 48.90$ in³/ft, and is satisfactory.
3. FOS = 1.52 (Net Pressure)
This is the factor of safety against rotation about the toe.
The FOS can be changed using 'Defined FOS' or 'Manual' in the 'Wall' page.



MDOT Sheetpile Manual

SupportIT, v2.37

 © 1997 - 2015, GTSoft Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSoftLtd@aol.com
Web: www.GTSoft.org

Client: Case 8 Braced - Clay - Stage 2

Site: FOS = 1.00

Page: 1

Date: 3.11.19


Sheet: PZ35

Works: Temporary

Pressure: Rankine

Analysis: Net Pressure

	Maximum	d (ft)
○	1537.2 psf	17.00
□	84921.4 ftlb/ft	16.43
●	1.1 in	17.57



MDOT Sheetpile Manual

SupportIT, v2.37

© 1997 - 2015, GTSOFT Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSOFT@aol.com
Web: www.GTSOFT.org

Client: Case 8 Braced - Clay - Stage 2
 Site: FOS = 1.00

Page: 2
 Date: 3.11.19

Sheet: PZ35
 Works: Temporary
 Pressure: Rankine
 Analysis: Net Pressure

Input Data

Depth Of Excavation = 17.00ft
 Surcharge = 360.0psf

Depth Of Active Water = 30.00ft
 Depth Of Passive Water = 30.00ft

Water Density = 62.43pcf
 Minimum Fluid Density = 31.82pcf

Soil Profile

Depth (ft)	Soil Name	γ (pcf)	γ' (pcf)	C (psf)	C_a (psf)	ϕ (°)	δ (°)	K_a	K_{ac}	K_p	K_{pc}
0.00	Soft Clay	118.37	56.00	417.6	0.0	0.0	0.0	1.00	2.00	1.00	2.00
30.00	Firm Clay	118.37	56.00	1500.0	0.0	0.0	0.0	1.00	2.00	1.00	2.00

Solution

Sheet

Sheet Name	E (psi)	I (in ⁴ /ft)	f (psi)	Z (in ³ /ft)	Allowed M_{max} (ftlb/ft)	b (in)	A (in ² /ft)	W (lb/ft)	Upstand (ft)	Toe (ft)	Length (ft)
PZ35	3.04E+07	369.40	24966.8	48.90	101739.5	22.64	10.28	66.0	0.00	15.80	32.80

Load Model: Area Distribution

Supports

d (ft)	Type	Load (lb/ft)
3.00	Brace	9481.2

Maxima

	Maximum	Depth (ft)
Pressure	1537.2 psf	17.00
Bending Moment	84921.4 ftlb/ft	16.43
Deflection	1.1 in	17.57
Shear Force	10004.0 lb/ft	30.01







MDOT Sheetpile Manual

SupportIT, v2.37

© 1997 - 2015, GTSoft Ltd.
 Tel/Fax: +44 (0)1292 477754
 Email: GTSoftLtd@aol.com
 Web: www.GTSoft.org

	Maximum	d (ft)
○	1537.2 psf	17.00
□	84921.4 ftlb/ft	16.43
◇	10004.0 lb/ft	30.01
●	1.1 in	17.57



MDOT Sheetpile Manual

Client: Case 8 Braced - Clay - Stage 2

Site: FOS = 1.00

Page: 4

Date: 3.11.19

Sheet: PZ35

Works: Temporary

Pressure: Rankine

Analysis: Net Pressure

depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)	depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)	depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)
0.00	0.0	0.0	0.0	0.0	11.01	828.7	-66455.6	0.9	-6218.3	22.02	701.9	-71416.6	1.0	4402.1
0.23	7.8	0.1	0.0	1.1	11.25	854.5	-67798.8	0.9	-6033.9	22.26	701.9	-70435.6	1.0	4555.6
0.47	14.8	0.5	0.0	3.6	11.48	883.7	-69260.9	0.9	-5819.8	22.49	701.9	-69291.7	1.0	4728.2
0.70	22.6	1.9	0.0	8.4	11.71	912.8	-70669.5	0.9	-5598.4	22.73	701.9	-68239.1	1.0	4881.7
0.94	29.6	4.2	0.0	14.2	11.95	938.7	-71875.2	0.9	-5395.6	22.96	701.9	-67014.7	1.0	5054.4
1.17	37.4	8.6	0.0	22.5	12.18	967.8	-73177.9	1.0	-5160.8	23.19	701.9	-65747.7	0.9	5227.0
1.41	44.4	14.4	0.0	31.5	12.42	993.7	-74286.7	1.0	-4946.0	23.43	701.9	-64585.6	0.9	5380.5
1.64	52.2	23.4	0.0	43.5	12.65	1022.8	-75477.3	1.0	-4697.5	23.66	701.9	-63238.1	0.9	5553.2
1.87	60.1	35.6	0.0	57.5	12.89	1048.7	-76483.6	1.0	-4470.7	23.90	701.9	-62004.4	0.9	5706.6
2.11	67.0	49.5	0.0	71.4	13.12	1077.8	-77555.7	1.0	-4208.8	24.13	701.9	-60576.3	0.9	5879.3
2.34	74.9	68.9	0.0	89.0	13.35	1106.9	-78562.5	1.0	-3939.7	24.37	701.9	-59271.1	0.9	6032.8
2.58	81.8	90.0	0.0	106.2	13.59	1132.8	-79401.2	1.0	-3694.5	24.60	701.9	-57762.4	0.8	6205.4
2.81	89.7	118.4	0.0	127.4	13.82	1161.9	-80279.9	1.1	-3411.8	24.83	701.9	-56211.1	0.8	6378.1
3.05	96.6	-111.1	0.0	-9333.3	14.06	1187.8	-81001.9	1.1	-3154.6	25.07	701.9	-54796.4	0.8	6531.6
3.28	104.5	-2406.1	0.0	-9308.5	14.29	1216.9	-81746.3	1.1	-2858.4	25.30	701.9	-53164.6	0.8	6704.2
3.51	112.3	-4694.7	0.1	-9281.7	14.53	1242.8	-82346.1	1.1	-2589.2	25.54	701.9	-51678.3	0.8	6857.7
3.75	119.2	-6723.3	0.1	-9256.3	14.76	1271.9	-82949.7	1.1	-2279.5	25.77	701.9	-49966.0	0.7	7030.4
3.98	127.1	-8998.7	0.1	-9225.9	14.99	1301.0	-83476.3	1.1	-1962.6	26.01	701.9	-48408.1	0.7	7183.8
4.22	134.0	-11014.8	0.1	-9197.2	15.23	1326.9	-83878.4	1.1	-1675.0	26.24	701.9	-46615.2	0.7	7356.5
4.45	141.9	-13275.2	0.2	-9163.2	15.46	1356.0	-84254.7	1.1	-1344.6	26.47	701.9	-44779.7	0.7	7529.2
4.69	148.8	-15277.3	0.2	-9131.3	15.70	1381.9	-84520.3	1.1	-1044.9	26.71	701.9	-43112.3	0.7	7682.6
4.92	156.7	-17521.1	0.2	-9093.6	15.93	1411.0	-84740.1	1.1	-701.0	26.94	701.9	-41196.3	0.6	7855.3
5.15	164.5	-19755.4	0.3	-9054.0	16.17	1436.9	-84863.7	1.1	-389.3	27.18	701.9	-39457.3	0.6	8008.8
5.39	171.5	-21733.1	0.3	-9017.2	16.40	1466.0	-84920.6	1.1	-31.8	27.41	701.9	-37460.7	0.6	8181.4
5.62	191.3	-23948.1	0.3	-8972.9	16.63	1495.1	-84888.6	1.1	332.8	27.64	701.9	-35650.2	0.6	8334.9
5.86	217.2	-25907.4	0.3	-8927.9	16.87	1521.0	-84783.9	1.1	662.9	27.88	701.9	-33573.1	0.5	8507.6
6.09	246.3	-28099.1	0.4	-8870.5	17.10	701.9	-84582.7	1.1	948.9	28.11	701.9	-31453.3	0.5	8680.2
6.33	272.2	-30034.8	0.4	-8813.5	17.34	701.9	-84359.6	1.1	1102.4	28.35	701.9	-29533.3	0.5	8833.7
6.56	301.3	-32196.8	0.4	-8742.6	17.57	701.9	-84068.5	1.1	1275.0	28.58	701.9	-27333.0	0.5	9006.4
6.79	330.4	-34340.6	0.5	-8664.5	17.81	701.9	-83773.9	1.1	1428.5	28.82	701.9	-25341.4	0.4	9159.9
7.03	356.3	-36229.5	0.5	-8589.0	18.04	701.9	-83402.2	1.1	1601.2	29.05	701.9	-23060.5	0.4	9332.5
7.26	385.4	-38334.0	0.5	-8497.4	18.27	701.9	-82987.8	1.1	1773.8	29.28	701.9	-20997.4	0.4	9486.0
7.50	411.3	-40185.1	0.5	-8410.0	18.51	701.9	-82583.7	1.1	1927.3	29.52	701.9	-18636.0	0.4	9658.6
7.73	440.4	-42244.1	0.6	-8304.8	18.74	701.9	-82088.9	1.1	2100.0	29.75	701.9	-16232.0	0.3	9831.3
7.97	466.3	-44051.9	0.6	-8205.3	18.98	701.9	-81613.2	1.1	2253.5	29.99	701.9	-14059.3	0.3	9984.8
8.20	495.4	-46059.0	0.6	-8086.6	19.21	701.9	-81037.8	1.1	2426.1	30.22	-3603.3	-11664.9	0.3	9218.0
8.43	524.5	-48036.1	0.6	-7960.8	19.45	701.9	-80490.5	1.1	2579.6	30.46	-3622.2	-9717.4	0.3	8427.7
8.67	550.4	-49766.9	0.7	-7842.9	19.68	701.9	-79834.6	1.1	2752.2	30.69	-3627.7	-7736.0	0.2	7516.5
8.90	579.5	-51682.5	0.7	-7703.5	19.91	701.9	-79136.0	1.1	2924.9	30.92	-3627.7	-6164.2	0.2	6704.2
9.14	605.4	-53355.9	0.7	-7573.6	20.15	701.9	-78479.3	1.1	3078.4	31.16	-3627.7	-4609.0	0.2	5790.3
9.37	634.5	-55203.7	0.7	-7420.7	20.38	701.9	-77700.2	1.1	3251.0	31.39	-3627.7	-3279.5	0.2	4876.4
9.61	660.4	-56814.0	0.7	-7278.8	20.62	701.9	-76971.8	1.1	3404.5	31.63	-3627.7	-2287.2	0.1	4064.1
9.84	689.5	-58587.8	0.8	-7112.4	20.85	701.9	-76112.2	1.1	3577.2	31.86	-3627.7	-1383.9	0.1	3150.2
10.07	718.6	-60319.9	0.8	-6938.8	21.09	701.9	-75312.3	1.1	3730.6	32.10	-3627.7	-770.4	0.1	2337.9
10.31	744.5	-61823.0	0.8	-6778.4	21.32	701.9	-74372.1	1.1	3903.3	32.33	-3627.7	-293.4	0.0	1424.0
10.54	773.7	-63471.3	0.8	-6591.3	21.55	701.9	-73389.3	1.0	4076.0	32.56	-3627.7	-58.9	0.0	611.6
10.78	799.5	-64897.2	0.9	-6419.0	21.79	701.9	-72479.9	1.0	4229.4	32.80	-3627.7	0.0	0.0	0.0









MDOT Sheeppile Manual

SupportIT, v2.37



© 1997 - 2015, GTSoft Ltd.
 Tel/Fax: +44 (0)1292 477754
 Email: GTSoftLtd@aol.com
 Web: www.GTSoft.org



MDOT Sheetpile Manual

SupportIT, v2.37

Client: Case 8 Braced - Clay - Stage 2

Site: FOS = 1.00

Page: 6

Date: 3.11.19


Sheet: PZ35

Works: Temporary


Pressure: Rankine

Analysis: Net Pressure


Shore/Shore




$d = 3.00$ ft
 $F = 9481.2$ lb/ft



Water/brace inadequately specified.
(Define L, E and I.)



Water/brace inadequately specified.
(Define B, I and E.)



MDOT Sheetpile Manual

SupportIT, v2.37

© 1997 - 2015, GTSoft Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSoftLtd@aol.com
Web: www.GTSoft.org

Client: Case 8 Braced - Clay - Stage 2
Site: FOS = 1.00

Page: 7
Date: 3.11.19

Sheet: PZ35
Works: Temporary
Pressure: Rankine
Analysis: Net Pressure

Design Report

1. Cohesive soil exists below the active water table. MEFD is being applied. Select 'Full Hydrostatic Head' in the 'Pressure' page to apply full hydrostatic pressure.
2. Total stress values are being used (i.e. $C > 0$). Note that the Piling Handbook and CIRIA SP95 recommend that effective stress values be used in 'long term' excavations.
3. Maximum bending moment = 84921.4ftlb/ft and $f = 24966.8$ psi. MINIMUM required sheet section modulus is: $Z = 40.82\text{in}^3/\text{ft}$ ($= M/f$). Sheet section modulus in this design is $Z = 48.90\text{in}^3/\text{ft}$, and is satisfactory.
4. Frame primary axis bending moments checked. Users should manually check the axial load capacities and the effects of combined axial and bending stresses to confirm frames are suitable.
5. FOS = 1.00 (Net Pressure)
This is the factor of safety against rotation about the lowest frame.
The FOS can be changed using 'Defined FOS' or 'Manual' in the 'Wall' page.



MDOT Sheetpile Manual

SupportIT, v2.37

© 1997 - 2015, GTSoft Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSoftLtd@aol.com
Web: www.GTSoft.org

Client: Case 8 Braced - Clay - Stage 2

Site: FOS = 1.50

Page: 1

Date: 3.11.19


Sheet: PZ35

Works: Temporary

Pressure: Rankine

Analysis: Net Pressure

	Maximum	d (ft)
○	1537.6 psf	17.00
□	83887.9 ftlb/ft	16.38
●	1.2 in	18.00



MDOT Sheetpile Manual

SupportIT, v2.37

© 1997 - 2015, GTSOFT Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSOFT@aol.com
Web: www.GTSOFT.org

Client: Case 8 Braced - Clay - Stage 2

Site: FOS = 1.50

Page: 2

Date: 3.11.19

Sheet: PZ35

Works: Temporary

Pressure: Rankine

Analysis: Net Pressure

Input Data

Depth Of Excavation = 17.00ft

Surcharge = 360.0psf

Depth Of Active Water = 30.00ft

Depth Of Passive Water = 30.00ft

Water Density = 62.43pcf

Minimum Fluid Density = 31.82pcf

Soil Profile

Depth (ft)	Soil Name	γ (pcf)	γ' (pcf)	C (psf)	C_a (psf)	ϕ (°)	δ (°)	K_a	K_{ac}	K_p	K_{pc}
0.00	Soft Clay	118.37	56.00	417.6	0.0	0.0	0.0	1.00	2.00	1.00	2.00
30.00	Firm Clay	118.37	56.00	1500.0	0.0	0.0	0.0	1.00	2.00	1.00	2.00

Solution

Sheet

Sheet Name	E (psi)	I (in ⁴ /ft)	f (psi)	Z (in ³ /ft)	Allowed M_{max} (ftlb/ft)	b (in)	A (in ² /ft)	W (lb/ft)	Upstand (ft)	Toe (ft)	Length (ft)
PZ35	3.04E+07	369.40	24966.8	48.90	101739.5	22.64	10.28	66.0	0.00	17.07	34.07

Load Model: Area Distribution

Supports

d (ft)	Type	Load (lb/ft)
3.00	Brace	9404.1

Maxima

	Maximum	Depth (ft)
Pressure	1537.6 psf	17.00
Bending Moment	83887.9 ftlb/ft	16.38
Deflection	1.2 in	18.00
Shear Force	10081.7 lb/ft	30.01



MDOT Sheetpile Manual

SupportIT, v2.37





© 1997 - 2015, GTSoft Ltd.
 Tel/Fax: +44 (0)1292 477754
 Email: GTSoftLtd@aol.com
 Web: www.GTSoft.org

Client: Case 8 Braced - Clay - Stage 2
 Site: FOS = 1.50

Page: 3
 Date: 3.11.19

Sheet: PZ35
 Works: Temporary
 Pressure: Rankine
 Analysis: Net Pressure

	Maximum	d (ft)
○	1537.6 psf	17.00
□	83887.9 ftlb/ft	16.38
◇	10081.7 lb/ft	30.01
●	1.2 in	18.00



MDOT Sheetpile Manual

SupportIT, v2.37

© 1997 - 2015, GTSOFT Ltd.
 Tel/Fax: +44 (0)1292 477754
 Email: GTSOFT@aol.com
 Web: www.GTSOFT.org

Client: Case 8 Braced - Clay - Stage 2

Site: FOS = 1.50

Page: 4

Date: 3.11.19

Sheet: PZ35

Works: Temporary

Pressure: Rankine

Analysis: Net Pressure







depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)	depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)	depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)
0.00	0.0	0.0	0.0	0.0	11.44	879.0	-68376.7	0.9	-5776.8	22.87	701.9	-67327.5	1.1	5080.4
0.24	8.1	0.1	0.0	1.2	11.68	905.9	-69669.9	1.0	-5573.7	23.12	701.9	-66249.3	1.1	5239.8
0.49	15.4	0.6	0.0	3.9	11.92	936.1	-71068.8	1.0	-5338.0	23.36	701.9	-64996.5	1.0	5419.1
0.73	23.5	2.1	0.0	9.0	12.17	966.4	-72406.5	1.0	-5094.5	23.60	701.9	-63847.4	1.0	5578.5
0.97	30.7	4.7	0.0	15.3	12.41	993.3	-73542.7	1.0	-4871.6	23.85	701.9	-62514.8	1.0	5757.9
1.22	38.9	9.6	0.0	24.3	12.65	1023.5	-74759.4	1.0	-4613.6	24.09	701.9	-61140.0	1.0	5937.2
1.46	46.1	16.1	0.0	34.0	12.90	1050.4	-75784.9	1.0	-4377.7	24.33	701.9	-59882.4	1.0	6096.6
1.70	54.2	26.2	0.0	47.0	13.14	1080.6	-76873.7	1.1	-4105.0	24.58	701.9	-58427.8	1.0	6275.9
1.95	62.4	39.9	0.0	62.0	13.38	1107.5	-77782.3	1.1	-3856.2	24.82	701.9	-57099.4	0.9	6435.3
2.19	69.6	55.4	0.0	77.1	13.63	1137.8	-78736.1	1.1	-3568.9	25.06	701.9	-55565.0	0.9	6614.7
2.43	77.7	77.2	0.0	96.0	13.87	1168.0	-79615.5	1.1	-3273.9	25.31	701.9	-54165.6	0.9	6774.1
2.68	85.0	100.8	0.0	114.6	14.11	1194.9	-80333.2	1.1	-3005.2	25.55	701.9	-52551.5	0.9	6953.4
2.92	93.1	132.7	0.0	137.5	14.36	1225.1	-81066.8	1.1	-2695.7	25.79	701.9	-50895.0	0.9	7132.7
3.16	100.3	-1170.1	0.0	-9244.5	14.60	1252.0	-81651.7	1.1	-2414.0	26.04	701.9	-49387.2	0.8	7292.1
3.41	108.5	-3531.5	0.1	-9217.8	14.84	1282.3	-82232.4	1.1	-2089.8	26.28	701.9	-47651.1	0.8	7471.5
3.65	116.6	-5885.8	0.1	-9188.9	15.09	1309.1	-82678.3	1.2	-1795.2	26.52	701.9	-46072.3	0.8	7630.9
3.89	123.9	-7972.1	0.1	-9161.5	15.33	1339.4	-83099.1	1.2	-1456.4	26.77	701.9	-44256.4	0.8	7810.2
4.14	132.0	-10311.5	0.1	-9128.7	15.57	1369.6	-83432.4	1.2	-1109.9	27.01	701.9	-42606.7	0.7	7969.6
4.38	139.2	-12383.8	0.2	-9097.8	15.82	1396.5	-83653.5	1.2	-795.4	27.25	701.9	-40711.0	0.7	8148.9
4.62	147.4	-14706.5	0.2	-9061.1	16.06	1426.7	-83816.1	1.2	-434.3	27.50	701.9	-38773.0	0.7	8328.3
4.87	154.6	-16763.0	0.2	-9026.7	16.30	1453.6	-83882.4	1.2	-106.9	27.74	701.9	-37014.9	0.7	8487.7
5.11	162.7	-19067.1	0.3	-8986.0	16.55	1483.9	-83868.8	1.2	268.8	27.98	701.9	-34997.2	0.7	8667.0
5.35	170.9	-21360.5	0.3	-8943.3	16.79	1510.8	-83781.4	1.2	609.2	28.23	701.9	-33168.2	0.6	8826.4
5.60	186.8	-23389.7	0.3	-8903.0	17.03	1541.1	-83597.2	1.2	975.7	28.47	701.9	-31070.6	0.6	9005.7
5.84	217.0	-25661.0	0.4	-8851.0	17.28	1574.8	-83348.7	1.2	1155.1	28.71	701.9	-29170.7	0.6	9165.1
6.08	243.9	-27668.0	0.4	-8798.3	17.52	1611.9	-83092.3	1.2	1314.5	28.96	701.9	-26993.4	0.6	9344.5
6.33	274.2	-29910.9	0.4	-8731.6	17.76	1652.4	-82763.9	1.2	1493.8	29.20	701.9	-24773.9	0.5	9523.8
6.57	301.0	-31889.5	0.4	-8666.0	18.01	1700.3	-82436.6	1.2	1653.2	29.44	701.9	-22765.5	0.5	9683.2
6.81	331.3	-34096.8	0.5	-8584.7	18.25	1754.6	-82028.4	1.2	1832.6	29.69	701.9	-20466.2	0.5	9862.5
7.06	361.5	-36282.5	0.5	-8495.8	18.49	1815.7	-81630.2	1.2	1992.0	29.93	701.9	-18386.9	0.5	10021.9
7.30	388.4	-38205.5	0.5	-8410.3	18.74	1883.6	-81142.3	1.2	2171.3	30.17	-3598.7	-16055.6	0.4	9469.9
7.54	418.6	-40344.9	0.6	-8306.7	18.98	1958.3	-80612.1	1.2	2350.6	30.42	-3618.4	-14148.1	0.4	8650.1
7.79	445.5	-42223.7	0.6	-8208.2	19.22	2040.7	-80105.4	1.2	2510.0	30.66	-3627.7	-12194.1	0.4	7933.0
8.03	475.8	-44309.7	0.6	-8090.1	19.47	2136.9	-79495.5	1.2	2689.4	30.90	-3627.7	-10390.0	0.3	7320.0
8.27	502.7	-46137.9	0.6	-7978.6	19.71	2240.0	-78917.9	1.2	2848.8	31.15	-3627.7	-8907.4	0.3	6775.2
8.52	532.9	-48163.6	0.7	-7845.9	19.95	2350.0	-78228.2	1.2	3028.1	31.39	-3627.7	-7375.9	0.3	6162.3
8.76	563.1	-50154.5	0.7	-7705.5	20.20	2467.9	-77579.7	1.2	3187.5	31.63	-3627.7	-6135.8	0.3	5617.5
9.00	590.0	-51893.3	0.7	-7574.1	20.44	2593.6	-76810.2	1.2	3366.8	31.88	-3627.7	-4876.9	0.2	5004.6
9.25	620.3	-53813.0	0.7	-7419.1	20.68	2727.1	-75998.5	1.2	3546.1	32.12	-3627.7	-3879.1	0.2	4459.8
9.49	647.2	-55485.4	0.8	-7274.8	20.93	2868.4	-75241.5	1.2	3705.5	32.36	-3627.7	-2892.9	0.2	3846.9
9.73	677.4	-57326.8	0.8	-7105.2	21.17	2999.5	-74350.0	1.1	3884.9	32.61	-3627.7	-2051.1	0.2	3234.0
9.98	704.3	-58926.6	0.8	-6947.9	21.41	3139.4	-73522.2	1.1	4044.3	32.85	-3627.7	-1423.9	0.1	2689.2
10.22	734.5	-60682.8	0.8	-6763.7	21.66	3288.1	-72550.9	1.1	4223.6	33.09	-3627.7	-854.8	0.1	2076.3
10.46	764.8	-62391.0	0.9	-6571.7	21.90	3440.6	-71652.1	1.1	4383.0	33.34	-3627.7	-470.0	0.1	1531.4
10.71	791.6	-63867.5	0.9	-6394.6	22.14	3596.7	-70601.1	1.1	4562.3	33.58	-3627.7	-173.5	0.1	918.5
10.95	821.9	-65479.7	0.9	-6188.0	22.39	3751.4	-69507.8	1.1	4741.7	33.82	-3627.7	-31.1	0.0	373.7
11.19	848.8	-66867.6	0.9	-5997.9	22.63	3908.7	-68500.5	1.1	4901.1	34.07	-3627.7	0.0	0.0	0.0



MDOT Sheeppile Manual

SupportIT, v2.37

© 1997 - 2015, GTSOFT Ltd.
 Tel/Fax: +44 (0)1292 477754
 Email: GTSOFT@aol.com
 Web: www.GTSOFT.org



MDOT Sheetpile Manual

SupportIT, v2.37

Client: Case 8 Braced - Clay - Stage 2

Site: FOS = 1.50

Page: 6



Date: 3.11.19

Sheet: PZ35


Works: Temporary

Pressure: Rankine

Analysis: Net Pressure



Water/brace inadequately specified.
(Define L, E and I.)



Water/brace inadequately specified.
(Define B, I and E.)



MDOT Sheetpile Manual

SupportIT, v2.37

© 1997 - 2015, GTSoft Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSoftLtd@aol.com
Web: www.GTSoft.org

Client: Case 8 Braced - Clay - Stage 2
Site: FOS = 1.50

Page: 7
Date: 3.11.19

Sheet: PZ35
Works: Temporary
Pressure: Rankine
Analysis: Net Pressure

Design Report

1. Cohesive soil exists below the active water table. MEFD is being applied. Select 'Full Hydrostatic Head' in the 'Pressure' page to apply full hydrostatic pressure.
2. Total stress values are being used (i.e. $C > 0$). Note that the Piling Handbook and CIRIA SP95 recommend that effective stress values be used in 'long term' excavations.
3. Maximum bending moment = 83887.9ftlb/ft and $f = 24966.8$ psi. MINIMUM required sheet section modulus is: $Z = 40.32\text{in}^3/\text{ft}$ ($= M/f$). Sheet section modulus in this design is $Z = 48.90\text{in}^3/\text{ft}$, and is satisfactory.
4. Frame primary axis bending moments checked. Users should manually check the axial load capacities and the effects of combined axial and bending stresses to confirm frames are suitable.
5. FOS = 1.49 (Net Pressure)
This is the factor of safety against rotation about the lowest frame.
The FOS can be changed using 'Defined FOS' or 'Manual' in the 'Wall' page.



MDOT Sheetpile Manual

SupportIT, v2.37

© 1997 - 2015, GTSoft Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSoftLtd@aol.com
Web: www.GTSoft.org

Client: Case 8 Braced - Clay - Stage 3

Site: FOS = 1.0

Page: 1

Date: 3.11.19


Sheet: PZ35

Works: Temporary

Pressure: Rankine

Analysis: Net Pressure

	Maximum	d (ft)
○	2484.1 psf	25.00
□	81633.2 ftlb/ft	22.72
●	0.6 in	23.60



MDOT Sheetpile Manual

SupportIT, v2.37

© 1997 - 2015, GTSOFT Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSOFT@aol.com
Web: www.GTSOFT.org



Client: Case 8 Braced - Clay - Stage 3

Site: FOS = 1.0

Page: 2

Date: 3.11.19

Sheet: PZ35

Works: Temporary

Pressure: Rankine

Analysis: Net Pressure

Input Data

Depth Of Excavation = 25.00ft
Surcharge = 360.0psf

Depth Of Active Water = 30.00ft
Depth Of Passive Water = 30.00ft

Water Density = 62.43pcf
Minimum Fluid Density = 31.82pcf

Soil Profile

Depth (ft)	Soil Name	γ (pcf)	γ' (pcf)	C (psf)	C_a (psf)	ϕ (°)	δ (°)	K_a	K_{ac}	K_p	K_{pc}
0.00	Soft Clay	118.37	56.00	417.6	0.0	0.0	0.0	1.00	2.00	1.00	2.00
30.00	Firm Clay	118.37	56.00	1500.0	0.0	0.0	0.0	1.00	2.00	1.00	2.00

Solution

Sheet

Sheet Name	E (psi)	I (in ⁴ /ft)	f (psi)	Z (in ³ /ft)	Allowed M_{max} (ftlb/ft)	b (in)	A (in ² /ft)	W (lb/ft)	Upstand (ft)	Toe (ft)	Length (ft)
PZ35	3.04E+07	369.40	24966.8	48.90	101739.5	22.64	10.28	66.0	0.00	10.13	35.13

Load Model: Area Distribution

Supports

d (ft)	Type	Load (lb/ft)
3.00	Brace	1284.3
13.00	Brace	19783.1

Maxima

	Maximum	Depth (ft)
Pressure	2484.1 psf	25.00
Bending Moment	81633.2 ftlb/ft	22.72
Deflection	0.6 in	23.60
Shear Force	15924.2 lb/ft	13.00







MDOT Sheetpile Manual

SupportIT, v2.37

© 1997 - 2015, GTSoft Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSoftLtd@aol.com
Web: www.GTSoft.org

	Maximum	d (ft)
○	2484.1 psf	25.00
□	81633.2 ftlb/ft	22.72
◇	15924.2 lb/ft	13.00
●	0.6 in	23.60



MDOT Sheetpile Manual

Client: Case 8 Braced - Clay - Stage 3

Site: FOS = 1.0

Page: 4

Date: 3.11.19

Sheet: PZ35

Works: Temporary

Pressure: Rankine

Analysis: Net Pressure

depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)	depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)	depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)
0.00	0.0	0.0	0.0	0.0	11.79	921.3	1032.3	0.0	2665.7	23.59	2317.8	-80840.6	0.6	2010.3
0.25	8.4	0.1	0.0	1.2	12.04	949.0	1679.0	0.0	2885.1	23.84	2345.5	-80352.5	0.6	2556.8
0.50	15.8	0.6	0.0	4.2	12.30	980.2	2468.7	0.0	3139.7	24.09	2376.7	-79660.8	0.6	3179.4
0.75	24.2	2.3	0.0	9.6	12.55	1011.4	3326.6	0.0	3402.6	24.34	2404.4	-78917.6	0.6	3739.7
1.00	31.7	5.2	0.0	16.2	12.80	1039.1	4148.0	0.0	3643.1	24.59	2435.6	-77935.4	0.6	4377.7
1.25	40.1	10.6	0.0	25.8	13.05	1070.3	3982.3	0.0	-15861.6	24.84	2466.8	-76796.5	0.6	5024.0
1.51	47.5	17.6	0.0	36.2	13.30	1098.0	295.1	0.0	-15607.3	25.09	1648.9	-75653.0	0.6	5531.5
1.76	55.9	28.7	0.0	49.9	13.55	1129.2	-3781.1	0.0	-15313.5	25.34	1648.9	-74255.2	0.6	5966.0
2.01	64.3	43.7	0.0	65.9	13.80	1156.9	-7338.6	0.1	-15045.3	25.59	1648.9	-72923.7	0.6	6352.1
2.26	71.8	60.8	0.0	82.0	14.05	1188.1	-11264.9	0.1	-14735.9	25.85	1648.9	-71325.5	0.6	6786.6
2.51	80.2	84.7	0.0	102.1	14.30	1219.3	-15108.8	0.1	-14418.3	26.10	1648.9	-69815.9	0.6	7172.7
2.76	87.6	110.6	0.0	121.9	14.55	1247.0	-18454.6	0.1	-14129.1	26.35	1648.9	-68017.4	0.6	7607.2
3.01	96.0	108.0	0.0	-1138.1	14.80	1278.2	-22136.8	0.2	-13796.0	26.60	1648.9	-66112.8	0.5	8041.6
3.26	103.5	-154.8	0.0	-1114.6	15.06	1306.0	-25335.5	0.2	-13493.0	26.85	1648.9	-64330.8	0.5	8427.8
3.51	111.9	-443.8	0.0	-1086.1	15.31	1337.1	-28848.4	0.2	-13144.3	27.10	1648.9	-62225.8	0.5	8862.2
3.76	120.3	-725.0	0.0	-1055.4	15.56	1364.9	-31893.1	0.2	-12827.5	27.35	1648.9	-60265.7	0.5	9248.3
4.01	127.7	-968.1	0.0	-1026.3	15.81	1396.1	-35228.9	0.2	-12463.3	27.60	1648.9	-57960.4	0.5	9682.8
4.27	136.1	-1233.1	0.0	-991.4	16.06	1427.2	-38467.9	0.3	-12091.0	27.85	1648.9	-55822.1	0.5	10068.9
4.52	143.6	-1460.9	0.0	-958.5	16.31	1455.0	-41263.8	0.3	-11753.0	28.10	1648.9	-53316.5	0.5	10503.4
4.77	152.0	-1707.7	0.0	-919.5	16.56	1486.1	-44313.9	0.3	-11365.1	28.35	1648.9	-50704.7	0.5	10937.8
5.02	159.4	-1918.3	0.0	-882.9	16.81	1513.9	-46938.6	0.3	-11013.4	28.61	1648.9	-48294.1	0.5	11323.9
5.27	167.8	-2144.8	0.0	-839.7	17.06	1545.1	-49792.0	0.3	-10610.0	28.86	1648.9	-45482.0	0.4	11758.4
5.52	179.7	-2359.7	0.0	-794.1	17.31	1572.8	-52238.5	0.4	-10244.5	29.11	1648.9	-42893.2	0.4	12144.5
5.77	207.5	-2540.2	0.0	-748.4	17.56	1604.0	-54887.6	0.4	-9825.5	29.36	1648.9	-39880.7	0.4	12578.9
6.02	238.6	-2729.7	0.0	-689.1	17.82	1635.2	-57425.4	0.4	-9398.4	29.61	1648.9	-37113.9	0.4	12965.1
6.27	266.4	-2884.3	0.0	-629.6	18.07	1662.9	-59586.1	0.4	-9011.8	29.86	1648.9	-33901.1	0.4	13399.5
6.52	297.6	-3040.9	0.0	-554.8	18.32	1694.1	-61907.8	0.4	-8569.1	30.11	-2647.2	-30602.6	0.4	13331.4
6.78	325.3	-3162.8	0.0	-481.5	18.57	1721.8	-63872.9	0.4	-8168.7	30.36	-2667.5	-27768.2	0.3	12708.8
7.03	356.5	-3278.7	0.0	-391.2	18.82	1753.0	-65970.8	0.5	-7710.5	30.61	-2680.8	-24741.8	0.3	11998.6
7.28	387.7	-3370.0	0.0	-292.8	19.07	1780.7	-67733.5	0.5	-7296.3	30.86	-2680.8	-22197.9	0.3	11363.0
7.53	415.4	-3428.7	0.0	-198.3	19.32	1811.9	-69599.8	0.5	-6822.5	31.12	-2680.8	-19501.0	0.3	10647.9
7.78	446.6	-3467.6	0.0	-84.3	19.57	1843.1	-71340.3	0.5	-6340.6	31.37	-2680.8	-17250.4	0.3	10012.2
8.03	474.3	-3476.4	0.0	23.9	19.82	1870.8	-72780.2	0.5	-5905.3	31.62	-2680.8	-14883.3	0.3	9297.1
8.28	505.5	-3455.2	0.0	153.5	20.07	1902.0	-74277.3	0.5	-5407.8	31.87	-2680.8	-12690.8	0.2	8582.1
8.53	533.2	-3406.8	0.0	275.5	20.33	1929.7	-75497.4	0.5	-4958.7	32.12	-2680.8	-10888.5	0.2	7946.4
8.78	564.4	-3317.4	0.0	420.5	20.58	1960.9	-76743.5	0.5	-4445.7	32.37	-2680.8	-9025.8	0.2	7231.3
9.03	595.6	-3188.9	0.0	573.8	20.83	1988.6	-77737.0	0.6	-3982.8	32.62	-2680.8	-7516.6	0.2	6595.7
9.28	623.3	-3039.9	0.0	716.9	21.08	2019.8	-78724.2	0.6	-3454.3	32.87	-2680.8	-5983.8	0.2	5880.6
9.54	654.5	-2831.5	0.0	885.7	21.33	2051.0	-79571.3	0.6	-2917.6	33.12	-2680.8	-4767.8	0.2	5245.0
9.79	682.2	-2608.1	0.0	1042.7	21.58	2078.7	-80204.8	0.6	-2433.6	33.37	-2680.8	-3564.7	0.1	4529.9
10.04	713.4	-2311.9	0.0	1227.0	21.83	2109.9	-80781.3	0.6	-1881.3	33.62	-2680.8	-2536.3	0.1	3814.8
10.29	741.1	-2007.2	0.0	1397.7	22.08	2137.6	-81170.8	0.6	-1383.5	33.88	-2680.8	-1768.7	0.1	3179.1
10.54	772.3	-1615.7	0.0	1597.5	22.33	2168.8	-81468.9	0.6	-815.8	34.13	-2680.8	-1070.0	0.1	2464.1
10.79	803.5	-1170.6	0.0	1805.6	22.58	2196.5	-81607.6	0.6	-304.2	34.38	-2680.8	-595.6	0.1	1828.4
11.04	831.2	-728.2	0.0	1997.4	22.83	2227.7	-81620.5	0.6	279.1	34.63	-2680.8	-226.7	0.0	1113.3
11.29	862.4	-176.0	0.0	2221.0	23.09	2258.9	-81488.4	0.6	870.6	34.88	-2680.8	-45.4	0.0	477.7
11.54	890.1	365.1	0.0	2426.6	23.34	2286.6	-81248.9	0.6	1403.3	35.13	-2680.8	0.0	0.0	0.0









MDOT Sheeppile Manual

SupportIT, v2.37



© 1997 - 2015, GTSoft Ltd.
 Tel/Fax: +44 (0)1292 477754
 Email: GTSoftLtd@aol.com
 Web: www.GTSoft.org



MDOT Sheetpile Manual

SupportIT, v2.37

Client: Case 8 Braced - Clay - Stage 3

Site: FOS = 1.0

Page: 6


Date: 3.11.19

Sheet: PZ35

Works: Temporary


Pressure: Rankine

Analysis: Net Pressure




Shore/Shore

$d = 13.00$ ft
 $F = 19783.1$ lb/ft



Water/brace inadequately specified.
(Define L, E and I.)



Water/brace inadequately specified.
(Define B, I and E.)



MDOT Sheetpile Manual

SupportIT, v2.37

© 1997 - 2015, GTSoft Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSoftLtd@aol.com
Web: www.GTSoft.org

Client: Case 8 Braced - Clay - Stage 3
Site: FOS = 1.0

Page: 7
Date: 3.11.19

Sheet: PZ35
Works: Temporary
Pressure: Rankine
Analysis: Net Pressure

Design Report

1. Cohesive soil exists below the active water table. MEFD is being applied. Select 'Full Hydrostatic Head' in the 'Pressure' page to apply full hydrostatic pressure.
2. Total stress values are being used (i.e. $C > 0$). Note that the Piling Handbook and CIRIA SP95 recommend that effective stress values be used in 'long term' excavations.
3. Maximum bending moment = 81633.2ftlb/ft and $f = 24966.8$ psi. MINIMUM required sheet section modulus is: $Z = 39.24\text{in}^3/\text{ft}$ ($= M/f$). Sheet section modulus in this design is $Z = 48.90\text{in}^3/\text{ft}$, and is satisfactory.
4. Frame primary axis bending moments checked. Users should manually check the axial load capacities and the effects of combined axial and bending stresses to confirm frames are suitable.
5. FOS = 1.01 (Net Pressure)
This is the factor of safety against rotation about the lowest frame.
The FOS can be changed using 'Defined FOS' or 'Manual' in the 'Wall' page.



MDOT Sheetpile Manual

Client: Case 8 Braced - Clay - Stage 3

Site: FOS = 1.50

Page: 1

Date: 3.11.19


Sheet: PZ35

Works: Temporary

Pressure: Rankine

Analysis: Net Pressure

	Maximum	d (ft)
○	2485.0 psf	25.00
□	82067.4 ftlb/ft	22.74
●	0.7 in	24.26



MDOT Sheetpile Manual

SupportIT, v2.37

© 1997 - 2015, GTSoft Ltd.
 Tel/Fax: +44 (0)1292 477754
 Email: GTSoftLtd@aol.com
 Web: www.GTSoft.org

Client: Case 8 Braced - Clay - Stage 3

Site: FOS = 1.50

Page: 2

Date: 3.11.19

Sheet: PZ35

Works: Temporary

Pressure: Rankine

Analysis: Net Pressure

Input Data

Depth Of Excavation = 25.00ft
Surcharge = 360.0psf

Depth Of Active Water = 30.00ft
Depth Of Passive Water = 30.00ft

Water Density = 62.43pcf
Minimum Fluid Density = 31.82pcf

Soil Profile

Depth (ft)	Soil Name	γ (pcf)	γ' (pcf)	C (psf)	C_a (psf)	ϕ (°)	δ (°)	K_a	K_{ac}	K_p	K_{pc}
0.00	Soft Clay	118.37	56.00	417.6	0.0	0.0	0.0	1.00	2.00	1.00	2.00
30.00	Firm Clay	118.37	56.00	1500.0	0.0	0.0	0.0	1.00	2.00	1.00	2.00

Solution

Sheet

Sheet Name	E (psi)	I (in ⁴ /ft)	f (psi)	Z (in ³ /ft)	Allowed M_{max} (ftlb/ft)	b (in)	A (in ² /ft)	W (lb/ft)	Upstand (ft)	Toe (ft)	Length (ft)
PZ35	3.04E+07	369.40	24966.8	48.90	101739.5	22.64	10.28	66.0	0.00	12.28	37.28

Load Model: Area Distribution

Supports

d (ft)	Type	Load (lb/ft)
3.00	Brace	1290.9
13.00	Brace	19814.2

Maxima

	Maximum	Depth (ft)
Pressure	2485.0 psf	25.00
Bending Moment	82067.4 ftlb/ft	22.74
Deflection	0.7 in	24.26
Shear Force	15974.4 lb/ft	13.00







MDOT Sheetpile Manual

SupportIT, v2.37

© 1997 - 2015, GTSoft Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSoftLtd@aol.com
Web: www.GTSoft.org

	Maximum	d (ft)
○	2485.0 psf	25.00
□	82067.4 ftlb/ft	22.74
◇	15974.4 lb/ft	13.00
●	0.7 in	24.26



MDOT Sheetpile Manual

Client: Case 8 Braced - Clay - Stage 3

Site: FOS = 1.50

Page: 4

Date: 3.11.19

Sheet: PZ35

Works: Temporary

Pressure: Rankine

Analysis: Net Pressure

depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)	depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)	depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)
0.00	0.0	0.0	0.0	0.0	12.52	1006.7	3130.8	0.0	3357.0	25.03	1648.9	-77114.3	0.7	5420.2
0.27	8.9	0.1	0.0	1.4	12.78	1036.2	3992.6	0.0	3611.3	25.30	1648.9	-75983.3	0.7	5830.1
0.53	16.8	0.8	0.0	4.7	13.05	1069.3	3810.5	0.0	-15908.1	25.56	1648.9	-74612.1	0.7	6291.1
0.80	25.7	2.8	0.0	10.8	13.31	1102.4	-585.2	0.0	-15604.0	25.83	1648.9	-73305.3	0.7	6700.9
1.07	33.6	6.2	0.0	18.3	13.58	1131.8	-4420.5	0.1	-15325.9	26.10	1648.9	-71736.2	0.7	7161.9
1.33	42.5	12.6	0.0	29.1	13.85	1164.9	-8651.8	0.1	-15004.3	26.36	1648.9	-70062.4	0.7	7622.9
1.60	50.5	21.1	0.0	40.8	14.11	1194.3	-12336.9	0.1	-14710.7	26.63	1648.9	-68486.6	0.7	8032.7
1.86	59.4	34.3	0.0	56.2	14.38	1227.4	-16394.6	0.1	-14371.7	26.89	1648.9	-66614.9	0.7	8493.7
2.13	68.3	52.2	0.0	74.2	14.65	1256.8	-19921.3	0.2	-14062.5	27.16	1648.9	-64863.3	0.7	8903.5
2.40	76.2	72.6	0.0	92.3	14.91	1289.9	-23796.2	0.2	-13706.0	27.43	1648.9	-62793.7	0.6	9364.5
2.66	85.1	101.2	0.0	115.0	15.18	1323.0	-27570.6	0.2	-13340.2	27.69	1648.9	-60866.2	0.6	9774.3
2.93	93.0	132.1	0.0	137.2	15.44	1352.4	-30839.2	0.2	-13007.3	27.96	1648.9	-58598.8	0.6	10235.3
3.20	101.9	-67.8	0.0	-1126.3	15.71	1385.5	-34416.7	0.3	-12624.0	28.23	1648.9	-56226.7	0.6	10696.3
3.46	109.8	-346.2	0.0	-1099.8	15.98	1414.9	-37506.2	0.3	-12275.6	28.49	1648.9	-54030.2	0.6	11106.1
3.73	118.7	-651.2	0.0	-1067.8	16.24	1448.0	-40877.7	0.3	-11874.9	28.76	1648.9	-51460.1	0.6	11567.1
3.99	127.6	-946.9	0.0	-1033.2	16.51	1477.4	-43779.9	0.3	-11510.9	29.02	1648.9	-49087.8	0.6	11976.9
4.26	135.5	-1201.4	0.0	-1000.4	16.78	1510.5	-46936.1	0.4	-11092.7	29.29	1648.9	-46319.9	0.6	12437.9
4.53	144.4	-1477.5	0.0	-961.1	17.04	1543.6	-49974.6	0.4	-10665.2	29.56	1648.9	-43771.7	0.5	12847.7
4.79	152.4	-1713.5	0.0	-924.1	17.31	1573.0	-52574.6	0.4	-10277.4	29.82	1648.9	-40806.0	0.5	13308.7
5.06	161.3	-1967.7	0.0	-880.1	17.57	1606.1	-55383.7	0.4	-9832.5	30.09	-2645.4	-37745.6	0.5	13369.8
5.33	169.2	-2183.0	0.0	-838.9	17.84	1635.6	-57775.8	0.4	-9429.2	30.36	-2666.9	-35103.6	0.5	12709.4
5.59	186.7	-2412.7	0.0	-789.7	18.11	1668.7	-60346.4	0.5	-8966.8	30.62	-2680.8	-32284.8	0.5	12090.2
5.86	219.8	-2627.6	0.0	-732.3	18.37	1698.1	-62522.3	0.5	-8548.0	30.89	-2680.8	-29883.6	0.5	11630.8
6.12	249.2	-2804.2	0.0	-673.6	18.64	1731.2	-64845.2	0.5	-8068.1	31.15	-2680.8	-27293.1	0.4	11114.0
6.39	282.3	-2984.3	0.0	-598.8	18.91	1764.3	-67033.2	0.5	-7578.9	31.42	-2680.8	-25089.0	0.4	10654.7
6.66	311.7	-3125.8	0.0	-524.5	19.17	1793.7	-68862.7	0.5	-7136.3	31.69	-2680.8	-22720.4	0.4	10137.9
6.92	344.8	-3261.9	0.0	-432.2	19.44	1826.8	-70788.9	0.6	-6629.7	31.95	-2680.8	-20469.1	0.4	9621.1
7.19	374.3	-3360.1	0.0	-342.4	19.70	1856.2	-72381.6	0.6	-6171.6	32.22	-2680.8	-18566.5	0.4	9161.7
7.46	407.3	-3442.8	0.0	-232.6	19.97	1889.3	-74036.8	0.6	-5647.4	32.49	-2680.8	-16537.1	0.4	8644.9
7.72	440.4	-3493.5	0.0	-113.6	20.24	1918.7	-75384.5	0.6	-5173.8	32.75	-2680.8	-14831.7	0.3	8185.5
7.99	469.9	-3509.8	0.0	0.0	20.50	1951.8	-76759.4	0.6	-4632.2	33.02	-2680.8	-13024.0	0.3	7668.7
8.25	503.0	-3493.0	0.0	136.5	20.77	1984.9	-77982.3	0.6	-4081.3	33.28	-2680.8	-11515.8	0.3	7209.3
8.52	532.4	-3445.2	0.0	265.6	21.04	2014.3	-78939.5	0.6	-3583.9	33.55	-2680.8	-9929.9	0.3	6692.5
8.79	565.5	-3352.0	0.0	419.6	21.30	2047.4	-79868.1	0.6	-3015.6	33.82	-2680.8	-8461.5	0.3	6175.7
9.05	594.9	-3232.1	0.0	564.3	21.57	2076.8	-80559.6	0.7	-2502.7	34.08	-2680.8	-7254.8	0.2	5716.4
9.32	628.0	-3053.3	0.0	735.7	21.83	2109.9	-81184.7	0.7	-1916.9	34.35	-2680.8	-6008.1	0.2	5199.6
9.59	661.1	-2825.3	0.0	916.4	22.10	2139.3	-81602.4	0.7	-1388.4	34.62	-2680.8	-4998.6	0.2	4740.2
9.85	690.5	-2579.4	0.0	1084.9	22.37	2172.4	-81914.8	0.7	-785.1	34.88	-2680.8	-3973.7	0.2	4223.4
10.12	723.6	-2251.7	0.0	1283.1	22.63	2205.5	-82057.9	0.7	-172.5	35.15	-2680.8	-3161.3	0.2	3764.0
10.38	753.0	-1913.0	0.0	1467.0	22.90	2235.0	-82045.7	0.7	379.7	35.42	-2680.8	-2358.3	0.1	3247.2
10.65	786.1	-1476.2	0.0	1682.7	23.17	2268.0	-81896.0	0.7	1009.7	35.68	-2680.8	-1672.7	0.1	2730.4
10.92	815.5	-1036.5	0.0	1882.2	23.43	2297.5	-81642.0	0.7	1577.5	35.95	-2680.8	-1161.8	0.1	2271.0
11.18	848.6	-481.5	0.0	2115.3	23.70	2330.6	-81218.4	0.7	2225.0	36.21	-2680.8	-698.0	0.1	1754.2
11.45	881.7	139.9	0.0	2357.7	23.97	2360.0	-80717.6	0.7	2808.3	36.48	-2680.8	-384.3	0.1	1294.9
11.72	911.1	749.9	0.0	2581.0	24.23	2393.1	-80012.5	0.7	3473.3	36.75	-2680.8	-142.3	0.0	778.1
11.98	944.2	1503.6	0.0	2840.9	24.50	2426.2	-79155.4	0.7	4147.5	37.01	-2680.8	-25.7	0.0	318.7
12.25	973.6	2235.5	0.0	3079.6	24.76	2455.6	-78264.3	0.7	4754.6	37.28	-2680.8	0.0	0.0	0.0



MDOT Sheeppile Manual

SupportIT, v2.37



© 1997 - 2015, GTSoft Ltd.
 Tel/Fax: +44 (0)1292 477754
 Email: GTSoftLtd@aol.com
 Web: www.GTSoft.org

Client: Case 8 Braced - Clay - Stage 3

Site: FOS = 1.50

Page: 5







Date: 3.11.19

Sheet: PZ35

Works: Temporary

Pressure: Rankine

Analysis: Net Pressure



MDOT Sheetpile Manual

SupportIT, v2.37

© 1997 - 2015, GTSOFT Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSOFT@aol.com
Web: www.GTSOFT.org

Client: Case 8 Braced - Clay - Stage 3

Site: FOS = 1.50

Page: 6


Date: 3.11.19

Sheet: PZ35

Works: Temporary


Pressure: Rankine

Analysis: Net Pressure




Shore/Shore

$d = 13.00$ ft
 $F = 19814.2$ lb/ft



Water/brace inadequately specified.
(Define L, E and I.)



Water/brace inadequately specified.
(Define B, I and E.)



MDOT Sheetpile Manual

SupportIT, v2.37

© 1997 - 2015, GTSoft Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSoftLtd@aol.com
Web: www.GTSoft.org

Client: Case 8 Braced - Clay - Stage 3
Site: FOS = 1.50

Page: 7
Date: 3.11.19

Sheet: PZ35
Works: Temporary
Pressure: Rankine
Analysis: Net Pressure

Design Report

1. Cohesive soil exists below the active water table. MEFD is being applied. Select 'Full Hydrostatic Head' in the 'Pressure' page to apply full hydrostatic pressure.
2. Total stress values are being used (i.e. $C > 0$). Note that the Piling Handbook and CIRIA SP95 recommend that effective stress values be used in 'long term' excavations.
3. Maximum bending moment = 82067.4ftlb/ft and $f = 24966.8$ psi. MINIMUM required sheet section modulus is: $Z = 39.44\text{in}^3/\text{ft}$ ($= M/f$). Sheet section modulus in this design is $Z = 48.90\text{in}^3/\text{ft}$, and is satisfactory.
4. Frame primary axis bending moments checked. Users should manually check the axial load capacities and the effects of combined axial and bending stresses to confirm frames are suitable.
5. FOS = 1.51 (Net Pressure)
This is the factor of safety against rotation about the lowest frame.
The FOS can be changed using 'Defined FOS' or 'Manual' in the 'Wall' page.



MDOT Sheetpile Manual

SupportIT, v2.37

© 1997 - 2015, GTSoft Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSoftLtd@aol.com
Web: www.GTSoft.org

Client: Case 8 Braced - Clay - Stage 4

Site: FOS = 1.00

Page: 1

Date: 3.11.19


Sheet: PZ27

Works: Temporary

Pressure: Rankine

Toe: No Earth Support

	Maximum	d (ft)
○	3075.9 psf	30.00
□	30950.6 ftlb/ft	27.00
●	0.4 in	34.19



MDOT Sheetpile Manual

SupportIT, v2.37

© 1997 - 2015, GTSOFT Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSOFT@aol.com
Web: www.GTSOFT.org

Client: Case 8 Braced - Clay - Stage 4
 Site: FOS = 1.00

Page: 2
 Date: 3.11.19

Sheet: PZ27
 Works: Temporary
 Pressure: Rankine
 Toe: No Earth Support

Input Data

Depth Of Excavation = 30.00ft
 Surcharge = 360.0psf

Depth Of Active Water = 30.00ft
 Depth Of Passive Water = 30.00ft

Water Density = 62.43pcf
 Minimum Fluid Density = 31.82pcf

Soil Profile

Depth (ft)	Soil Name	γ (pcf)	γ' (pcf)	C (psf)	C_a (psf)	ϕ (°)	δ (°)	K_a	K_{ac}	K_p	K_{pc}
0.00	Soft Clay	118.37	56.00	417.6	0.0	0.0	0.0	1.00	2.00	1.00	2.00
30.00	Firm Clay	118.37	56.00	1500.0	0.0	0.0	0.0	1.00	2.00	1.00	2.00

Solution

Sheet

Sheet Name	E (psi)	I (in ⁴ /ft)	f (psi)	Z (in ³ /ft)	Allowed M_{max} (ftlb/ft)	b (in)	A (in ² /ft)	W (lb/ft)	Upstand (ft)	Toe (ft)	Length (ft)
PZ27	3.04E+07	187.50	24966.8	31.00	64497.5	17.99	7.93	40.5	0.00	4.21	34.21

Load Model: Area Distribution (Hinge Method used for Shear Force, Bending Moment and Deflection)

Supports

d (ft)	Type	Load (lb/ft)
3.00	Brace	1290.0
13.00	Brace	9798.2
22.00	Brace	20537.1

Maxima

	Maximum	Depth (ft)
Pressure	3075.9 psf	30.00
Bending Moment	30950.6 ftlb/ft	27.00
Deflection	0.4 in	34.19
Shear Force	12103.6 lb/ft	22.00



MDOT Sheetpile Manual

SupportIT, v2.37





© 1997 - 2015, GTSoft Ltd.
 Tel/Fax: +44 (0)1292 477754
 Email: GTSoftLtd@aol.com
 Web: www.GTSoft.org

Client: Case 8 Braced - Clay - Stage 4
 Site: FOS = 1.00

Page: 3
 Date: 3.11.19

Sheet: PZ27
 Works: Temporary
 Pressure: Rankine
 Toe: No Earth Support

	Maximum	d (ft)
○	3075.9 psf	30.00
□	30950.6 ftlb/ft	27.00
◇	12103.6 lb/ft	22.00
●	0.4 in	34.19



MDOT Sheetpile Manual

Client: Case 8 Braced - Clay - Stage 4

Site: FOS = 1.00

Page: 4

Date: 3.11.19

Sheet: PZ27

Works: Temporary

Pressure: Rankine

Toe: No Earth Support

depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)	depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)	depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)
0.00	0.0	0.0	0.0	0.0	11.49	884.9	-3918.1	0.0	1895.1	22.97	2245.0	-10119.0	0.0	-9981.3
0.24	8.2	0.1	0.0	1.2	11.73	911.9	-3465.4	0.0	2100.4	23.22	2272.0	-12344.4	0.0	-9465.7
0.49	15.4	0.6	0.0	4.0	11.98	942.3	-2899.4	0.0	2338.7	23.46	2302.4	-14706.5	0.0	-8878.4
0.73	23.6	2.1	0.0	9.1	12.22	972.7	-2271.4	0.0	2584.8	23.71	2329.4	-16679.0	0.0	-8349.7
0.98	30.9	4.8	0.0	15.4	12.46	999.7	-1659.4	0.0	2810.2	23.95	2359.8	-18753.1	0.0	-7747.7
1.22	39.0	9.8	0.0	24.5	12.71	1030.0	-908.7	0.0	3071.0	24.19	2390.1	-20671.9	0.0	-7137.8
1.47	46.3	16.3	0.0	34.3	12.95	1057.0	-184.6	0.0	3309.4	24.44	2417.1	-22245.3	0.0	-6589.2
1.71	54.5	26.5	0.0	47.4	13.20	1087.4	-1220.5	0.0	-6011.6	24.68	2447.5	-23865.1	0.0	-5964.6
1.96	62.7	40.4	0.0	62.5	13.44	1114.4	-2568.0	0.0	-5760.1	24.93	2474.5	-25169.7	0.0	-5402.8
2.20	69.9	56.1	0.0	77.7	13.69	1144.8	-4014.4	0.0	-5469.8	25.17	2504.9	-26483.3	0.0	-4763.5
2.44	78.1	78.2	0.0	96.8	13.93	1175.2	-5385.5	0.0	-5171.7	25.42	2531.9	-27512.6	0.0	-4188.7
2.69	85.4	102.1	0.0	115.6	14.17	1202.2	-6539.2	0.0	-4900.2	25.66	2562.3	-28513.1	0.0	-3534.7
2.93	93.5	134.4	0.0	138.7	14.42	1232.5	-7762.3	0.0	-4587.4	25.91	2592.6	-29344.8	0.0	-2872.8
3.18	100.8	-135.2	0.0	-1615.4	14.66	1259.5	-8781.3	0.0	-4302.8	26.15	2619.6	-29940.8	0.0	-2278.0
3.42	109.0	-546.0	0.0	-1588.4	14.91	1289.9	-9849.2	0.0	-3975.3	26.39	2650.0	-30448.4	0.0	-1601.4
3.67	117.1	-949.6	0.0	-1559.3	15.15	1316.9	-10727.2	0.0	-3677.6	26.64	2677.0	-30753.1	0.0	-993.5
3.91	124.4	-1301.9	0.0	-1531.6	15.40	1347.3	-11632.8	0.0	-3335.3	26.88	2707.4	-30929.4	-0.1	-302.2
4.15	132.6	-1690.5	0.0	-1498.5	15.64	1377.7	-12449.7	0.0	-2985.3	27.13	2734.4	-30936.4	-0.1	318.8
4.40	139.8	-2028.7	0.0	-1467.4	15.89	1404.7	-13099.6	0.0	-2667.5	27.37	2764.8	-30774.3	-0.1	1024.8
4.64	148.0	-2400.4	0.0	-1430.3	16.13	1435.0	-13743.3	0.0	-2302.8	27.62	2795.1	-30430.1	-0.1	1738.6
4.89	155.3	-2722.6	0.0	-1395.6	16.37	1462.0	-14236.1	0.0	-1972.0	27.86	2822.1	-29969.7	-0.1	2379.6
5.13	163.4	-3075.5	0.0	-1354.6	16.62	1492.4	-14699.5	0.0	-1592.5	28.10	2852.5	-29276.1	-0.1	3108.1
5.38	171.6	-3417.7	0.0	-1311.5	16.86	1519.4	-15028.8	0.0	-1248.6	28.35	2879.5	-28502.0	-0.1	3762.2
5.62	189.7	-3712.3	0.0	-1270.6	17.11	1549.8	-15304.7	0.0	-854.4	28.59	2909.9	-27452.0	-0.1	4505.4
5.87	220.0	-4031.9	0.0	-1217.6	17.35	1580.2	-15478.4	0.0	-452.4	28.84	2936.9	-26357.9	-0.1	5172.6
6.11	247.0	-4304.0	0.0	-1164.0	17.60	1607.2	-15545.4	0.0	-88.5	29.08	2967.3	-24944.3	-0.1	5930.6
6.35	277.4	-4594.6	0.0	-1096.2	17.84	1637.5	-15522.1	0.0	328.3	29.33	2997.6	-23335.2	-0.2	6696.4
6.60	304.4	-4837.6	0.0	-1029.5	18.08	1664.5	-15414.6	0.0	705.2	29.57	3024.6	-21739.4	-0.2	7383.6
6.84	334.8	-5092.1	0.0	-947.0	18.33	1694.9	-15194.6	0.0	1136.7	29.82	3055.0	-19755.8	-0.2	8164.1
7.09	365.2	-5324.6	0.0	-856.8	18.57	1721.9	-14909.5	0.0	1526.8	30.06	-2045.7	-17825.6	-0.2	8657.7
7.33	392.2	-5511.2	0.0	-770.0	18.82	1752.3	-14486.3	0.0	1973.0	30.30	-2071.3	-15664.2	-0.2	8128.7
7.58	422.5	-5696.7	0.0	-665.1	19.06	1782.7	-13952.7	0.0	2426.9	30.55	-2085.5	-13857.4	-0.2	7652.7
7.82	449.5	-5838.3	0.0	-565.2	19.31	1809.7	-13384.2	0.0	2837.0	30.79	-2088.9	-11956.0	-0.2	7106.2
8.06	479.9	-5969.6	0.0	-445.6	19.55	1840.0	-12636.9	0.0	3305.7	31.04	-2088.9	-10194.8	-0.2	6559.6
8.31	506.9	-6059.9	0.0	-332.6	19.80	1867.0	-11875.4	0.0	3728.9	31.28	-2088.9	-8747.1	-0.3	6073.8
8.55	537.3	-6130.0	0.0	-198.2	20.04	1897.4	-10907.7	0.0	4212.3	31.53	-2088.9	-7250.8	-0.3	5527.3
8.80	567.7	-6164.7	0.0	-56.0	20.28	1924.4	-9947.2	0.0	4648.6	31.77	-2088.9	-6038.5	-0.3	5041.5
9.04	594.7	-6164.4	0.0	76.9	20.53	1954.8	-8752.1	0.0	5146.7	32.01	-2088.9	-4807.2	-0.3	4494.9
9.29	625.0	-6127.0	0.0	233.9	20.77	1985.2	-7433.8	0.0	5652.7	32.26	-2088.9	-3830.4	-0.3	4009.1
9.53	652.0	-6059.2	0.0	379.9	21.02	2012.2	-6157.2	0.0	6108.9	32.50	-2088.9	-2864.0	-0.3	3462.6
9.78	682.4	-5942.3	0.0	551.5	21.26	2042.5	-4601.2	0.0	6629.6	32.75	-2088.9	-2037.8	-0.4	2916.0
10.02	709.4	-5800.7	0.0	710.7	21.51	2069.5	-3110.2	0.0	7098.9	32.99	-2088.9	-1421.1	-0.4	2430.2
10.26	739.8	-5597.3	0.0	897.0	21.75	2099.9	-1309.6	0.0	7634.3	33.24	-2088.9	-859.8	-0.4	1883.7
10.51	770.2	-5345.1	0.0	1091.2	21.99	2126.9	401.9	0.0	8116.8	33.48	-2088.9	-478.6	-0.4	1397.9
10.75	797.2	-5078.4	0.0	1270.3	22.24	2157.3	-2087.2	0.0	-11614.3	33.73	-2088.9	-182.3	-0.4	851.3
11.00	827.5	-4728.8	0.0	1479.2	22.48	2187.6	-5004.1	0.0	-11056.4	33.97	-2088.9	-36.6	-0.4	365.5
11.24	854.5	-4372.3	0.0	1671.5	22.73	2214.6	-7476.0	0.0	-10553.9	34.21	-2088.9	0.0	-0.4	0.0









MDOT Sheeppile Manual

SupportIT, v2.37



© 1997 - 2015, GTSoft Ltd.
 Tel/Fax: +44 (0)1292 477754
 Email: GTSoftLtd@aol.com
 Web: www.GTSoft.org



MDOT Sheetpile Manual

SupportIT, v2.37

Client: Case 8 Braced - Clay - Stage 4

Site: FOS = 1.00

Page: 6


Date: 3.11.19

Sheet: PZ27

Works: Temporary


Pressure: Rankine

Toe: No Earth Support




d = 3.00 ft
F = 1290.0 lb/ft

Shore/Shore



Water/brace inadequately specified.
(Define L, E and I.)



Water/brace inadequately specified.
(Define B, I and E.)



MDOT Sheetpile Manual

SupportIT, v2.37

© 1997 - 2015, GTSoft Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSoftLtd@aol.com
Web: www.GTSoft.org

Client: Case 8 Braced - Clay - Stage 4
Site: FOS = 1.00

Page: 7
Date: 3.11.19

Sheet: PZ27
Works: Temporary
Pressure: Rankine
Toe: No Earth Support

Design Report

1. Cohesive soil exists below the active water table. MEFD is being applied. Select 'Full Hydrostatic Head' in the 'Pressure' page to apply full hydrostatic pressure.
2. Total stress values are being used (i.e. $C > 0$). Note that the Piling Handbook and CIRIA SP95 recommend that effective stress values be used in 'long term' excavations.
3. Maximum bending moment = 30950.6ftlb/ft and $f = 24966.8$ psi. MINIMUM required sheet section modulus is: $Z = 14.88$ in³/ft (= M/f). Sheet section modulus in this design is $Z = 31.00$ in³/ft, and is satisfactory.
4. FOS is less than requested FOS (1.0).
5. No Toe Design: Area Load Method selected and used for frame loads; Hinge Method used for Shear Force, Bending Moment and Deflection.
6. Frame primary axis bending moments checked. Users should manually check the axial load capacities and the effects of combined axial and bending stresses to confirm frames are suitable.
7. FOS undefined (No Toe case)
The FOS can be changed using 'Defined FOS' or 'Manual' in the 'Wall' page.



MDOT Sheetpile Manual

SupportIT, v2.37

© 1997 - 2015, GTSoft Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSoftLtd@aol.com
Web: www.GTSoft.org

Client: Case 8 Braced - Clay - Stage 4

Site: FOS = 1.50

Page: 1

Date: 3.11.19


Sheet: PZ27

Works: Temporary

Pressure: Rankine

Analysis: Net Pressure

	Maximum	d (ft)
○	3073.5 psf	30.00
□	22354.2 ftlb/ft	26.96
●	0.1 in	28.52



MDOT Sheetpile Manual

SupportIT, v2.37

© 1997 - 2015, GTSofT Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSofT Ltd@aol.com
Web: www.GTSofT.org

Client: Case 8 Braced - Clay - Stage 4

Site: FOS = 1.50

Page: 2

Date: 3.11.19

Sheet: PZ27

Works: Temporary

Pressure: Rankine

Analysis: Net Pressure

Input Data

Depth Of Excavation = 30.00ft
Surcharge = 360.0psf

Depth Of Active Water = 30.00ft
Depth Of Passive Water = 30.00ft

Water Density = 62.43pcf
Minimum Fluid Density = 31.82pcf

Soil Profile

Depth (ft)	Soil Name	γ (pcf)	γ' (pcf)	C (psf)	C_a (psf)	ϕ (°)	δ (°)	K_a	K_{ac}	K_p	K_{pc}
0.00	Soft Clay	118.37	56.00	417.6	0.0	0.0	0.0	1.00	2.00	1.00	2.00
30.00	Firm Clay	118.37	56.00	1500.0	0.0	0.0	0.0	1.00	2.00	1.00	2.00

Solution

Sheet

Sheet Name	E (psi)	I (in ⁴ /ft)	f (psi)	Z (in ³ /ft)	Allowed M_{max} (ftlb/ft)	b (in)	A (in ² /ft)	W (lb/ft)	Upstand (ft)	Toe (ft)	Length (ft)
PZ27	3.04E+07	187.50	24966.8	31.00	64497.5	17.99	7.93	40.5	0.00	5.87	35.87

Load Model: Area Distribution

Supports

d (ft)	Type	Load (lb/ft)
3.00	Brace	1289.1
13.00	Brace	9787.3
22.00	Brace	20468.0

Maxima

	Maximum	Depth (ft)
Pressure	3073.5 psf	30.00
Bending Moment	22354.2 ftlb/ft	26.96
Deflection	0.1 in	28.52
Shear Force	12018.1 lb/ft	22.00







MDOT Sheetpile Manual

SupportIT, v2.37

© 1997 - 2015, GTSoft Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSoftLtd@aol.com
Web: www.GTSoft.org

	Maximum	d (ft)
○	3073.5 psf	30.00
□	22354.2 ftlb/ft	26.96
◇	12018.1 lb/ft	22.00
●	0.1 in	28.52



MDOT Sheetpile Manual

Client: Case 8 Braced - Clay - Stage 4

Site: FOS = 1.50

Page: 4

Date: 3.11.19

Sheet: PZ27

Works: Temporary

Pressure: Rankine

Analysis: Net Pressure







depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)	depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)	depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)
0.00	0.0	0.0	0.0	0.0	12.04	950.7	1674.9	0.0	2893.7	24.08	2376.5	-11558.5	0.1	-7301.1
0.26	8.6	0.1	0.0	1.3	12.30	979.0	2390.9	0.0	3124.8	24.34	2404.8	-13243.8	0.1	-6729.0
0.51	16.2	0.7	0.0	4.4	12.55	1010.8	3263.4	0.0	3392.9	24.60	2436.7	-14975.3	0.1	-6077.3
0.77	24.7	2.5	0.0	10.0	12.81	1042.6	4209.0	0.0	3669.6	24.85	2465.0	-16366.6	0.1	-5490.8
1.02	32.4	5.5	0.0	16.9	13.07	1071.0	4527.4	0.0	-5864.6	25.11	2496.8	-17763.3	0.1	-4823.0
1.28	40.9	11.2	0.0	26.9	13.32	1102.8	2982.1	0.0	-5571.7	25.36	2528.7	-18979.5	0.1	-4146.5
1.54	48.5	18.8	0.0	37.7	13.58	1131.1	1675.6	0.0	-5304.2	25.62	2557.0	-19907.0	0.1	-3538.1
1.79	57.1	30.6	0.0	52.1	13.83	1162.9	283.3	0.0	-4995.1	25.88	2588.8	-20775.7	0.1	-2845.5
2.05	65.7	46.5	0.0	68.7	14.09	1191.2	-883.6	0.0	-4713.3	26.13	2617.1	-21390.8	0.1	-2222.6
2.31	73.3	64.7	0.0	85.4	14.35	1223.1	-2114.8	0.0	-4388.0	26.39	2648.9	-21903.9	0.1	-1513.8
2.56	81.9	90.1	0.0	106.4	14.60	1254.9	-3257.3	0.0	-4054.2	26.65	2677.3	-22199.2	0.1	-876.6
2.82	89.5	117.7	0.0	127.0	14.86	1283.2	-4196.6	0.0	-3750.4	26.90	2709.1	-22348.4	0.1	-151.6
3.07	98.0	39.6	0.0	-1136.7	15.12	1315.1	-5165.3	0.0	-3400.4	27.16	2740.9	-22322.8	0.1	581.9
3.33	105.7	-228.6	0.0	-1112.2	15.37	1343.4	-5946.5	0.0	-3082.1	27.41	2769.2	-22200.3	0.1	1241.1
3.59	114.2	-523.2	0.0	-1082.5	15.63	1375.2	-6733.3	0.0	-2716.0	27.67	2801.1	-21951.0	0.1	1990.9
3.84	122.8	-809.5	0.0	-1050.5	15.88	1403.5	-7349.0	0.0	-2383.3	27.93	2829.4	-21629.2	0.1	2664.5
4.10	130.4	-1056.6	0.0	-1020.1	16.14	1435.4	-7945.6	0.0	-2001.0	28.18	2861.2	-21153.3	0.1	3430.4
4.36	139.0	-1325.7	0.0	-983.8	16.40	1467.2	-8438.1	0.0	-1610.1	28.44	2889.5	-20627.9	0.1	4118.4
4.61	146.6	-1556.5	0.0	-949.5	16.65	1495.5	-8786.7	0.0	-1255.4	28.69	2921.4	-19920.6	0.1	4900.4
4.87	155.2	-1806.1	0.0	-908.8	16.91	1527.4	-9076.4	0.0	-848.4	28.95	2953.2	-19088.7	0.1	5691.1
5.12	162.8	-2018.7	0.0	-870.7	17.17	1555.7	-9241.1	0.0	-479.3	29.21	2981.5	-18243.6	0.1	6401.1
5.38	171.3	-2246.7	0.0	-825.6	17.42	1587.5	-9319.7	0.0	-56.1	29.46	3013.4	-17172.8	0.1	7207.9
5.64	193.5	-2462.3	0.0	-777.0	17.68	1615.8	-9293.3	0.0	327.3	29.72	3041.7	-16113.3	0.1	7932.3
5.89	221.8	-2642.3	0.0	-726.9	17.93	1647.7	-9152.9	0.0	766.8	29.98	3073.5	-14798.8	0.1	8755.3
6.15	253.7	-2829.6	0.0	-662.5	18.19	1679.5	-8893.2	0.0	1214.8	30.23	-2063.6	-13577.3	0.1	8417.1
6.41	282.0	-2980.8	0.0	-598.0	18.45	1707.8	-8560.5	0.0	1620.2	30.49	-2086.9	-12283.1	0.1	7858.5
6.66	313.8	-3131.6	0.0	-517.4	18.70	1739.7	-8069.3	0.0	2084.4	30.74	-2088.9	-11066.3	0.1	7458.1
6.92	342.1	-3246.8	0.0	-438.6	18.96	1768.0	-7527.1	0.0	2504.2	31.00	-2088.9	-10038.0	0.1	7102.1
7.17	373.9	-3353.0	0.0	-341.8	19.22	1799.8	-6796.2	0.0	2984.5	31.26	-2088.9	-8941.1	0.1	6701.6
7.43	405.8	-3432.2	0.0	-236.4	19.47	1828.1	-6037.3	0.0	3418.7	31.51	-2088.9	-8019.3	0.1	6345.6
7.69	434.1	-3478.1	0.0	-135.6	19.73	1860.0	-5058.4	0.0	3915.2	31.77	-2088.9	-7042.2	0.1	5945.1
7.94	465.9	-3500.2	0.0	-14.0	19.98	1891.8	-3945.0	0.0	4420.4	32.03	-2088.9	-6227.0	0.1	5589.1
8.20	494.2	-3491.7	0.0	101.2	20.24	1920.1	-2840.4	0.0	4876.5	32.28	-2088.9	-5369.7	0.1	5188.6
8.45	526.1	-3448.2	0.0	238.9	20.50	1951.9	-1466.4	0.0	5397.8	32.54	-2088.9	-4576.0	0.1	4788.1
8.71	554.4	-3377.7	0.0	368.5	20.75	1980.2	-126.5	0.0	5868.8	32.79	-2088.9	-3923.7	0.1	4432.1
8.97	586.2	-3260.3	0.0	522.4	21.01	2012.1	1516.2	0.0	6405.9	33.05	-2088.9	-3249.7	0.1	4031.6
9.22	618.1	-3100.6	0.0	684.9	21.26	2040.4	3098.6	0.0	6890.8	33.31	-2088.9	-2703.9	0.1	3675.6
9.48	646.4	-2921.1	0.0	836.5	21.52	2072.2	5018.3	0.0	7444.4	33.56	-2088.9	-2149.8	0.1	3275.1
9.74	678.2	-2674.9	0.0	1015.1	21.78	2104.1	7088.0	0.0	8006.7	33.82	-2088.9	-1710.6	0.1	2919.1
9.99	706.5	-2414.9	0.0	1181.1	22.03	2132.4	8443.7	0.0	-11954.4	34.07	-2088.9	-1276.3	0.1	2518.6
10.25	738.4	-2074.1	0.0	1375.9	22.29	2164.2	5298.4	0.0	-11376.0	34.33	-2088.9	-905.5	0.0	2118.1
10.50	766.7	-1726.3	0.0	1556.3	22.55	2192.5	2634.0	0.0	-10854.6	34.59	-2088.9	-629.2	0.0	1762.1
10.76	798.5	-1282.6	0.0	1767.3	22.80	2224.4	-213.7	0.0	-10260.1	34.84	-2088.9	-378.3	0.0	1361.6
11.02	830.4	-781.1	0.0	1986.9	23.06	2252.7	-2610.0	0.0	-9724.4	35.10	-2088.9	-208.5	0.0	1005.6
11.27	858.7	-285.0	0.0	2189.2	23.31	2284.5	-5151.8	0.0	-9113.6	35.36	-2088.9	-77.4	0.0	605.1
11.53	890.5	331.9	0.0	2425.0	23.57	2316.4	-7528.4	0.1	-8494.3	35.61	-2088.9	-14.1	0.0	249.1
11.79	918.8	934.3	0.0	2641.7	23.83	2344.7	-9500.3	0.1	-7936.6	35.87	-2088.9	0.0	0.0	0.0



MDOT Sheetpile Manual

SupportIT, v2.37

© 1997 - 2015, GTSoft Ltd.
 Tel/Fax: +44 (0)1292 477754
 Email: GTSoftLtd@aol.com
 Web: www.GTSoft.org



MDOT Sheetpile Manual

SupportIT, v2.37

Client: Case 8 Braced - Clay - Stage 4

Site: FOS = 1.50

Page: 6

Date: 3.11.19


Sheet: PZ27

Works: Temporary


Pressure: Rankine

Analysis: Net Pressure


Shore/Shore




$d = 3.00$ ft
 $F = 1289.1$ lb/ft



Water/brace inadequately specified.
(Define L, E and I.)



Water/brace inadequately specified.
(Define B, I and E.)



MDOT Sheetpile Manual

SupportIT, v2.37

© 1997 - 2015, GTSoft Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSoftLtd@aol.com
Web: www.GTSoft.org

Client: Case 8 Braced - Clay - Stage 4
Site: FOS = 1.50

Page: 7
Date: 3.11.19

Sheet: PZ27
Works: Temporary
Pressure: Rankine
Analysis: Net Pressure

Design Report

1. Cohesive soil exists below the active water table. MEFD is being applied. Select 'Full Hydrostatic Head' in the 'Pressure' page to apply full hydrostatic pressure.
2. Total stress values are being used (i.e. $C > 0$). Note that the Piling Handbook and CIRIA SP95 recommend that effective stress values be used in 'long term' excavations.
3. Maximum bending moment = 22354.2ftlb/ft and $f = 24966.8$ psi. MINIMUM required sheet section modulus is: $Z = 10.74\text{in}^3/\text{ft}$ ($= M/f$). Sheet section modulus in this design is $Z = 31.00\text{in}^3/\text{ft}$, and is satisfactory.
4. Frame primary axis bending moments checked. Users should manually check the axial load capacities and the effects of combined axial and bending stresses to confirm frames are suitable.
5. FOS = 1.49 (Net Pressure)
This is the factor of safety against rotation about the lowest frame.
The FOS can be changed using 'Defined FOS' or 'Manual' in the 'Wall' page.



MDOT Sheetpile Manual

SupportIT, v2.37


© 1997 - 2015, GTSoft Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSoftLtd@aol.com
Web: www.GTSoft.org

Client: Case 8 Braced - Clay - Strut
Loads Terzaghi-Peck

Page: 1
Date: 3.11.19

Sheet: PZ35
Works: Temporary
Pressure: Terzaghi (m = 1.0; a = 0.4)
Analysis: Net Pressure

	Maximum	d (ft)
○	2240.7 psf	7.50
□	22325.7 ftlb/ft	27.49
●	0.1 in	33.56



MDOT Sheetpile Manual

SupportIT, v2.37

© 1997 - 2015, GTSOft Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSOftLtd@aol.com
Web: www.GTSOft.org

Client: Case 8 Braced - Clay - Strut
Loads Terzaghi-Peck

Page: 2
Date: 3.11.19

Sheet: PZ35
Works: Temporary
Pressure: Terzaghi (m = 1.0; a = 0.4)
Analysis: Net Pressure

Input Data

Depth Of Excavation = 30.00ft
Surcharge = 360.0psf

Depth Of Active Water = 30.00ft
Depth Of Passive Water = 30.00ft

Water Density = 62.43pcf
Minimum Fluid Density = 31.82pcf

Soil Profile

Depth (ft)	Soil Name	γ (pcf)	γ' (pcf)	C (psf)	C_a (psf)	ϕ (°)	δ (°)	K_a	K_{ac}	K_p	K_{pc}
0.00	Soft Clay	118.37	56.00	417.6	0.0	0.0	0.0	1.00	2.00	1.00	2.00
30.00	Firm Clay	118.37	56.00	1500.0	0.0	0.0	0.0	1.00	2.00	1.00	2.00

Solution

Sheet

Sheet Name	E (psi)	I (in ⁴ /ft)	f (psi)	Z (in ³ /ft)	Allowed M_{max} (ftlb/ft)	b (in)	A (in ² /ft)	W (lb/ft)	Upstand (ft)	Toe (ft)	Length (ft)
PZ35	3.04E+07	369.40	24966.8	48.90	101739.5	22.64	10.28	66.0	0.00	3.59	33.59

Pressure Model: Terzaghi (m = 1.0; a = 0.4); Ignore hydrostatic pressure in cohesive soils; Rankine used on active side below excavation depth; Rankine used for bending moment

Load Model: Area Distribution

Supports

d (ft)	Type	Load (lb/ft)
3.00	Brace	10859.3
13.00	Brace	21211.3
22.00	Brace	20673.3

Maxima

	Maximum	Depth (ft)
Pressure	2240.7 psf	7.50
Bending Moment	22325.7 ftlb/ft	27.49
Deflection	0.1 in	33.56
Shear Force	13418.9 lb/ft	22.00







MDOT Sheetpile Manual

SupportIT, v2.37

© 1997 - 2015, GTSoft Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSoftLtd@aol.com
Web: www.GTSoft.org

	Maximum	d (ft)
○	2240.7 psf	7.50
□	22325.7 ftlb/ft	27.49
◇	13418.9 lb/ft	22.00
●	0.1 in	33.56



MDOT Sheetpile Manual

Client: Case 8 Braced - Clay - Strut
Loads Terzaghi-Peck

Page: 4
Date: 3.11.19

Sheet: PZ35
Works: Temporary
Pressure: Terzaghi (m = 1.0; a = 0.4)
Analysis: Net Pressure







depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)	depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)	depth (ft)	P (psf)	M (ftlb/ft)	D (in)	F (lb/ft)
0.00	360.0	0.0	0.0	0.0	11.28	2240.7	-4293.7	0.0	1711.5	22.55	2240.7	8965.5	0.0	-12207.5
0.24	423.2	0.1	0.0	1.1	11.52	2240.7	-3891.3	0.0	1907.5	22.79	2240.7	6280.2	0.0	-11712.5
0.48	479.3	0.6	0.0	3.8	11.76	2240.7	-3385.5	0.0	2135.0	23.03	2240.7	3392.5	0.0	-11148.6
0.72	542.5	2.0	0.0	8.8	12.00	2240.7	-2821.4	0.0	2370.1	23.27	2240.7	945.6	0.0	-10641.0
0.96	598.7	4.6	0.0	14.8	12.24	2240.7	-2269.7	0.0	2585.3	23.51	2240.7	-1670.6	0.0	-10062.9
1.20	661.8	9.2	0.0	23.6	12.48	2240.7	-1590.7	0.0	2834.5	23.75	2240.7	-4140.3	0.0	-9477.3
1.44	718.0	15.4	0.0	33.1	12.72	2240.7	-933.7	0.0	3062.4	23.99	2240.7	-6211.1	0.0	-8950.4
1.68	781.2	25.1	0.0	45.7	12.96	2240.7	-132.9	0.0	3325.8	24.23	2240.7	-8398.9	0.0	-8350.6
1.92	844.3	38.2	0.0	60.3	13.20	2240.7	-905.7	0.0	-4342.2	24.47	2240.7	-10216.1	0.0	-7811.1
2.16	900.5	53.1	0.0	74.9	13.44	2240.7	-1957.1	0.0	-4064.5	24.71	2240.7	-12115.4	0.0	-7197.1
2.40	963.7	74.0	0.0	93.3	13.68	2240.7	-2938.5	0.0	-3779.4	24.95	2240.7	-13673.1	0.0	-6645.0
2.64	1019.8	96.7	0.0	111.4	13.92	2240.7	-3750.5	0.0	-3519.7	25.19	2240.7	-15276.9	0.0	-6016.8
2.88	1083.0	127.2	0.0	133.6	14.16	2240.7	-4594.5	0.0	-3220.3	25.43	2240.7	-16721.7	0.0	-5381.1
3.12	1139.1	-39.5	0.0	-1621.3	14.40	2240.7	-5281.5	0.0	-2948.0	25.67	2240.7	-17870.8	0.0	-4809.7
3.36	1202.3	-444.5	0.0	-1595.2	14.64	2240.7	-5981.5	0.0	-2634.5	25.91	2240.7	-19009.9	0.0	-4159.8
3.60	1265.5	-842.7	0.0	-1567.1	14.88	2240.7	-6537.5	0.0	-2349.5	26.15	2240.7	-19884.3	0.0	-3575.8
3.84	1321.6	-1190.6	0.0	-1540.5	15.12	2240.7	-7086.8	0.0	-2021.8	26.39	2240.7	-20710.9	0.0	-2911.7
4.08	1384.8	-1574.6	0.0	-1508.6	15.36	2240.7	-7553.6	0.0	-1686.6	26.63	2240.7	-21304.6	0.0	-2315.1
4.32	1441.0	-1909.1	0.0	-1478.6	15.60	2240.7	-7897.8	0.0	-1382.3	26.87	2240.7	-21812.0	0.0	-1636.8
4.56	1504.1	-2277.1	0.0	-1442.9	15.84	2240.7	-8203.7	0.0	-1032.9	27.11	2240.7	-22147.7	0.0	-951.0
4.80	1560.3	-2596.6	0.0	-1409.4	16.08	2240.7	-8401.9	0.0	-716.0	27.35	2240.7	-22300.5	0.0	-335.1
5.04	1623.5	-2946.8	0.0	-1369.9	16.32	2240.7	-8540.2	0.0	-352.4	27.59	2240.7	-22306.7	0.0	364.9
5.28	1686.6	-3286.8	0.0	-1328.4	16.56	2240.7	-8586.5	0.0	-22.9	27.83	2240.7	-22163.5	0.0	993.4
5.52	1742.8	-3580.1	0.0	-1289.7	16.80	2240.7	-8550.6	0.0	354.9	28.07	2240.7	-21833.4	0.0	1707.6
5.76	1806.0	-3899.3	0.0	-1240.8	17.04	2240.7	-8419.9	0.0	740.2	28.31	2240.7	-21388.3	0.0	2348.8
6.00	1862.1	-4172.0	0.0	-1191.0	17.27	2240.7	-8222.7	0.0	1089.0	28.55	2240.7	-20715.2	0.0	3077.1
6.24	1925.3	-4464.8	0.0	-1127.9	17.51	2240.7	-7907.8	0.0	1488.4	28.79	2240.7	-19857.7	0.0	3813.0
6.48	1981.4	-4711.0	0.0	-1065.5	17.75	2240.7	-7543.9	0.0	1849.9	29.03	2240.7	-18939.3	0.0	4473.4
6.72	2044.6	-4970.6	0.0	-988.3	17.99	2240.7	-7038.2	0.0	2263.5	29.27	2240.7	-17728.5	0.0	5223.5
6.96	2107.8	-5209.9	0.0	-903.5	18.23	2240.7	-6501.7	0.0	2637.6	29.51	2240.7	-16492.9	0.0	5896.5
7.20	2163.9	-5404.0	0.0	-821.8	18.47	2240.7	-5798.5	0.0	3065.4	29.75	2240.7	-14922.0	0.0	6660.8
7.44	2227.1	-5599.9	0.0	-722.8	18.71	2240.7	-4988.1	0.0	3500.8	29.99	2240.7	-13363.4	0.0	7346.5
7.68	2240.7	-5752.4	0.0	-628.5	18.95	2240.7	-4176.2	0.0	3894.1	30.23	-2088.9	-11538.3	0.0	6972.1
7.92	2240.7	-5898.0	0.0	-515.3	19.19	2240.7	-3158.1	0.0	4343.7	30.47	-2088.9	-9840.3	0.0	6449.0
8.16	2240.7	-6002.9	0.0	-408.4	19.43	2240.7	-2158.6	0.0	4749.6	30.71	-2088.9	-8443.0	0.0	5971.5
8.40	2240.7	-6091.6	0.0	-281.1	19.67	2240.7	-926.2	0.0	5213.4	30.95	-2088.9	-6998.7	-0.1	5434.2
8.64	2240.7	-6147.4	0.0	-146.2	19.91	2240.7	266.8	0.0	5631.9	31.19	-2088.9	-5828.6	-0.1	4956.6
8.88	2240.7	-6167.8	0.0	-20.0	20.15	2240.7	1720.2	0.0	6109.9	31.43	-2088.9	-4640.1	-0.1	4419.2
9.12	2240.7	-6156.4	0.0	129.1	20.39	2240.7	3293.4	0.0	6595.3	31.67	-2088.9	-3697.3	-0.1	3941.6
9.36	2240.7	-6114.0	0.0	267.9	20.63	2240.7	4793.8	0.0	7033.2	31.91	-2088.9	-2764.4	-0.1	3404.3
9.60	2240.7	-6028.4	0.0	431.2	20.87	2240.7	6598.2	0.0	7532.8	32.15	-2088.9	-1967.0	-0.1	2867.0
9.84	2240.7	-5917.1	0.0	582.6	21.11	2240.7	8307.0	0.0	7983.2	32.39	-2088.9	-1371.8	-0.1	2389.3
10.08	2240.7	-5750.6	0.0	760.0	21.35	2240.7	10349.3	0.0	8497.1	32.63	-2088.9	-830.0	-0.1	1852.0
10.32	2240.7	-5538.6	0.0	945.0	21.59	2240.7	12272.5	0.0	8960.2	32.87	-2088.9	-462.0	-0.1	1374.4
10.56	2240.7	-5310.4	0.0	1115.7	21.83	2240.7	14559.3	0.0	9488.2	33.11	-2088.9	-176.0	-0.1	837.1
10.80	2240.7	-5007.2	0.0	1314.9	22.07	2240.7	15035.6	0.0	-13239.6	33.35	-2088.9	-35.3	-0.1	359.4
11.04	2240.7	-4694.9	0.0	1498.2	22.31	2240.7	12118.0	0.0	-12757.2	33.59	-2088.9	0.0	-0.1	0.0



MDOT Sheeppile Manual

SupportIT, v2.37

© 1997 - 2015, GTSOFT Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSOFT@aol.com
Web: www.GTSOFT.org




MDOT Sheetpile Manual

Client: Case 8 Braced - Clay - Strut
Loads Terzaghi-Peck


Page: 6
Date: 3.11.19

Sheet: PZ35
Works: Temporary


Pressure: Terzaghi ($m = 1.0$; $a = 0.4$)
Analysis: Net Pressure



Shore/Shore



Water/brace inadequately specified.
(Define L, E and I.)



Water/brace inadequately specified.
(Define B, I and E.)



MDOT Sheetpile Manual

SupportIT, v2.37

© 1997 - 2015, GTSoft Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSoftLtd@aol.com
Web: www.GTSoft.org

Client: Case 8 Braced - Clay - Strut
Loads Terzaghi-Peck

Page: 7
Date: 3.11.19

Sheet: PZ35
Works: Temporary
Pressure: Terzaghi (m = 1.0; a = 0.4)
Analysis: Net Pressure

Design Report

1. Cohesive soil exists below the active water table. Hydrostatic pressure is being ignored in cohesive soils. Select 'Apply Hydrostatic' in the 'Pressure' page for full hydrostatic pressure.
2. Terzaghi was used for the active pressure down to the excavation depth. Rankine was used for the active pressure below the excavation depth and the passive pressure.
3. Terzaghi was used for the frame load calculation. Rankine was used for the bending moment.
4. Total stress values are being used (i.e. $C > 0$). Note that the Piling Handbook and CIRIA SP95 recommend that effective stress values be used in 'long term' excavations.
5. Maximum bending moment = 22325.7ftlb/ft and $f = 24966.8$ psi. MINIMUM required sheet section modulus is: $Z = 10.73\text{in}^3/\text{ft}$ ($= M/f$). Sheet section modulus in this design is $Z = 48.90\text{in}^3/\text{ft}$, and is satisfactory.
6. Frame primary axis bending moments checked. Users should manually check the axial load capacities and the effects of combined axial and bending stresses to confirm frames are suitable.
7. FOS = 1.01 (Net Pressure)
This is the factor of safety against rotation about the lowest frame.
The FOS can be changed using 'Defined FOS' or 'Manual' in the 'Wall' page.



MDOT Sheetpile Manual

SupportIT, v2.37

© 1997 - 2015, GTSoft Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSoftLtd@aol.com
Web: www.GTSoft.org


Appendix B.9 – SupportIT Output, Case 9

Case 9 – Cantilevered Soldier Pile TERS in Coarse-grained soil

Title: Case 9 Soldier Pile
 Page: 1 FOS = 1.0
 Date: 3.11.19

Pile: Steel Water
 Lagging: 4" x 12" Lagging
 Works: Temporary
 Pressure: Rankine
 Analysis: Gross Pressure
 Toe: Cantilever

	Maximum	d (ft)
○	406.9 psf	8.00
□	105226.4 ftlb	13.76
●	0.7 in	0.00



MDOT Sheetpile Manual

Title: Case 9 Soldier Pile
 Page: 2 FOS = 1.0
 Date: 3.11.19

Input Data

Depth Of Excavation = 8.00ft
 Surcharge = 360.0psf

Depth Of Active Water = 8.00ft
 Depth Of Passive Water = 8.00ft

Water Density = 62.43pcf
 Minimum Fluid Density = 31.82pcf

Pile: Steel Waler
 Lagging: 4" x 12" Lagging
 Works: Temporary
 Pressure: Rankine
 Analysis: Gross Pressure
 Toe: Cantilever

Soil Profile

Depth (ft)	Soil Name	γ (pcf)	γ' (pcf)	C (psf)	C_a (psf)	ϕ (°)	δ (°)	K_a	K_{ac}	K_p	K_{pc}
0.00	Loose Fine Sand	109.20	65.55	0.0	0.0	30.0	0.0	0.33	0.00	3.00	0.00
8.00	Dense Fine Sand	118.37	68.73	0.0	0.0	35.0	0.0	0.27	0.00	3.69	0.00

Solution

Wall

Description	E (psi)	I (in ⁴)	f (psi)	Z (in ³)	Allowed M_{max} (ftlb)	b (ft)	t (ft)	w (ft)	s (ft)	Arching	n	Upstand (ft)	Toe (ft)	Length (ft)
Steel Waler	3.04E+07	904.00	32500.0	146.00	395416.7	1.167	1.167	2.000	6.00	2.80	1.50	0.00	12.54	20.54
4" x 12" Lagging	1.23E+06	64.00	1498.2	32.00	3995.4	1.001	0.331	----	----	----	----	----	----	----

Pressure Model: Rankine; Passive pressure ignored for depth n.w (= 3.00ft)

Maxima

	Maximum	Depth (ft)
Pressure	406.9 psf	8.00
Bending Moment	105226.4 ftlb	13.76
Deflection	0.7 in	0.00
Shear Force	14813.8 lb	11.01







MDOT Sheetpile Manual

Title: Case 9 Soldier Pile
 Page: 3 FOS = 1.0
 Date: 3.11.19

Pile: Steel Waler
 Lagging: 4" x 12" Lagging
 Works: Temporary
 Pressure: Rankine
 Analysis: Gross Pressure
 Toe: Cantilever

Maximum	d (ft)
○ 406.9 psf	8.00
□ 105226.4 ftlb	13.76
◇ 14813.8 lb	11.01
● 0.7 in	0.00



MDOT Sheetpile Manual

Title: Case 9 Soldier Pile
 Page: 4
 Date: 3.11.19 FOS = 1.0

Pile: Steel Waler
 Lagging: 4" x 12" Lagging
 Works: Temporary
 Pressure: Rankine
 Analysis: Gross Pressure
 Toe: Cantilever

depth (ft)	P (psf)	M (ftlb)	D (in)	F (lb)	depth (ft)	P (psf)	M (ftlb)	D (in)	F (lb)	depth (ft)	P (psf)	M (ftlb)	D (in)	F (lb)
0.00	118.8	0.0	0.7	0.0	6.90	367.4	28748.8	0.3	10084.2	13.79	-1029.9	105222.3	0.0	-159.3
0.15	124.4	7.6	0.7	112.3	7.04	372.4	30146.7	0.3	10388.7	13.94	-1062.1	105047.2	0.0	-780.3
0.29	129.3	29.2	0.7	216.9	7.19	377.9	31769.5	0.3	10736.1	14.09	-1098.3	104556.0	0.0	-1448.0
0.44	134.8	70.9	0.7	339.4	7.34	383.5	33446.1	0.3	11088.6	14.23	-1130.5	103869.5	0.0	-2013.9
0.59	139.8	124.1	0.7	452.5	7.48	388.4	34982.2	0.3	11406.2	14.38	-1166.7	102829.8	0.0	-2619.5
0.73	145.3	202.7	0.7	584.7	7.63	394.0	36762.7	0.3	11768.4	14.53	-1202.9	101521.1	0.0	-3192.3
0.88	150.3	290.0	0.7	706.5	7.78	398.9	38392.3	0.3	12094.7	14.67	-1235.1	100144.3	0.0	-3673.9
1.03	155.8	408.3	0.7	848.4	7.92	404.4	40279.4	0.3	12466.6	14.82	-1271.3	98368.6	0.0	-4184.6
1.17	161.4	548.9	0.6	995.4	8.07	318.2	42002.1	0.3	12681.8	14.97	-1303.5	96600.2	0.0	-4611.1
1.32	166.3	693.2	0.6	1130.4	8.22	282.0	43961.3	0.3	12785.4	15.11	-1339.8	94410.7	0.0	-5059.8
1.47	171.9	877.8	0.6	1287.1	8.36	245.7	45936.4	0.2	12889.9	15.26	-1371.9	92298.2	0.0	-5431.1
1.61	176.8	1062.5	0.6	1430.7	8.51	213.6	47705.6	0.2	12983.4	15.41	-1408.2	89748.3	0.0	-5817.9
1.76	182.3	1294.0	0.6	1597.2	8.66	177.3	49711.4	0.2	13089.6	15.55	-1444.4	87029.0	0.0	-6171.8
1.91	187.3	1521.6	0.6	1749.4	8.80	145.1	51508.0	0.2	13184.6	15.70	-1476.6	84481.8	0.0	-6458.8
2.05	192.8	1802.9	0.6	1925.5	8.95	108.9	53544.8	0.2	13292.4	15.85	-1512.8	81483.5	0.0	-6750.6
2.20	198.4	2111.6	0.6	2106.8	9.10	76.7	55369.3	0.2	13389.0	15.99	-1545.0	78712.1	0.0	-6982.5
2.35	203.3	2409.7	0.6	2272.2	9.24	40.5	57437.7	0.2	13498.4	16.14	-1581.2	75488.1	0.0	-7212.3
2.49	208.9	2772.5	0.6	2463.2	9.39	4.3	59523.0	0.2	13608.8	16.29	-1613.4	72539.7	0.0	-7389.1
2.64	213.8	3119.9	0.6	2637.3	9.54	-27.9	61390.9	0.2	13707.6	16.43	-1649.6	69143.3	0.0	-7556.9
2.79	219.4	3539.5	0.6	2838.0	9.68	-64.1	63508.5	0.2	13819.6	16.58	-1685.8	65677.2	0.0	-7691.9
2.93	224.3	3938.7	0.5	3020.6	9.83	-96.3	65405.3	0.2	13919.9	16.73	-1718.0	62549.8	0.0	-7784.3
3.08	229.8	4418.0	0.5	3231.0	9.98	-132.5	67555.7	0.2	14033.5	16.88	-1754.2	58992.7	0.0	-7857.3
3.23	235.4	4930.0	0.5	3446.5	10.13	-164.7	69481.9	0.2	14135.3	17.02	-1786.4	55808.2	0.0	-7894.6
3.38	240.3	5413.2	0.5	3642.4	10.27	-200.9	71665.6	0.2	14250.6	17.17	-1822.6	52213.6	0.0	-7905.5
3.52	245.9	5989.2	0.5	3867.6	10.42	-237.1	73867.1	0.2	14366.9	17.32	-1854.8	49019.3	0.0	-7887.7
3.67	250.8	6530.6	0.5	4072.1	10.57	-269.3	75839.0	0.1	14470.9	17.46	-1891.1	45440.3	0.0	-7836.6
3.82	256.4	7173.4	0.5	4307.0	10.71	-305.6	78074.5	0.1	14588.8	17.61	-1927.3	41891.3	0.0	-7752.7
3.96	261.3	7775.4	0.5	4520.2	10.86	-337.8	80076.9	0.1	14694.3	17.76	-1959.5	38773.7	0.0	-7650.5
4.11	266.9	8487.9	0.5	4764.8	11.01	-372.1	82346.9	0.1	14813.8	17.90	-1995.7	35321.8	0.0	-7504.6
4.26	272.4	9238.3	0.5	5014.5	11.15	-406.2	84344.7	0.1	14323.9	18.05	-2027.9	32314.3	0.0	-7347.3
4.40	277.4	9937.9	0.5	5240.9	11.30	-442.4	86510.1	0.1	13741.8	18.20	-2064.1	29012.8	0.0	-7139.4
4.55	282.9	10762.3	0.5	5500.3	11.45	-478.6	88583.7	0.1	13126.8	18.34	-2096.3	26162.8	0.0	-6927.0
4.70	287.8	11528.9	0.4	5735.3	11.59	-510.8	90345.7	0.1	12552.6	18.49	-2132.5	23065.1	0.0	-6657.0
4.84	293.4	12430.0	0.4	6004.4	11.74	-547.0	92231.9	0.1	11875.5	18.64	-2168.7	20096.9	0.0	-6354.2
4.99	298.3	13266.1	0.4	6248.0	11.89	-579.2	93819.4	0.1	11246.2	18.78	-2200.9	17579.2	0.0	-6057.4
5.14	303.9	14246.9	0.4	6526.9	12.03	-615.4	95500.3	0.1	10507.1	18.93	-2237.1	14896.3	0.0	-5692.6
5.28	309.4	15270.9	0.4	6810.9	12.18	-647.6	96897.3	0.1	9822.7	19.08	-2269.3	12655.9	0.0	-5340.7
5.43	314.4	16218.1	0.4	7067.7	12.33	-683.8	98354.8	0.1	9021.6	19.22	-2305.5	10311.5	0.0	-4913.9
5.58	319.9	17326.0	0.4	7361.4	12.47	-720.0	99686.9	0.1	8187.7	19.37	-2337.7	8395.7	0.0	-4506.9
5.72	324.9	18349.1	0.4	7626.8	12.62	-752.2	100761.4	0.1	7418.9	19.52	-2374.0	6443.1	0.0	-4018.0
5.87	330.4	19543.7	0.4	7930.2	12.77	-788.5	101842.5	0.1	6523.0	19.66	-2410.2	4719.6	0.0	-3496.3
6.02	335.3	20645.1	0.4	8204.2	12.91	-820.6	102685.9	0.1	5699.1	19.81	-2442.4	3391.9	0.0	-3005.0
6.16	340.9	21929.3	0.4	8517.3	13.06	-856.9	103498.1	0.1	4741.1	19.96	-2478.6	2141.8	0.0	-2421.3
6.31	346.4	23262.1	0.4	8835.6	13.21	-889.1	104094.4	0.1	3862.1	20.10	-2510.8	1258.5	0.0	-1874.8
6.46	351.4	24488.1	0.3	9122.8	13.35	-925.3	104619.5	0.1	2842.1	20.25	-2547.0	535.0	0.0	-1229.1
6.60	356.9	25914.7	0.3	9450.7	13.50	-961.5	104985.4	0.1	1789.3	20.40	-2579.2	143.6	0.0	-627.5
6.75	361.9	27225.5	0.3	9746.6	13.65	-993.7	105172.8	0.0	825.9	20.54	-2611.4	0.0	0.0	0.0









MDOT Sheeppile Manual

SupportIT, v2.37

© 1997 - 2015, GTSoft Ltd.
 Tel/Fax: +44 (0)1292 477754
 Email: GTSoftLtd@aol.com
 Web: www.GTSoft.org

Title: Case 9 Soldier Pile
 Page: 5
 Date: 3.11.19 FOS = 1.0

Pile: Steel Waler
 Lagging: 4" x 12" Lagging
 Works: Temporary
 Pressure: Rankine
 Analysis: Gross Pressure
 Toe: Cantilever




MDOT Sheetpile Manual

Title: Case 9 Soldier Pile
 Page: 6
 Date: 3.11.19 FOS = 1.0


Pile: Steel Waler
 Lagging: 4" x 12" Lagging
 Works: Temporary
 Pressure: Rankine
 Analysis: Gross Pressure
 Toe: Cantilever

4" x 12" Lagging:
 $s = 6.00$ ft $f = 1498.2$ psi
 $E = 1.23E+06$ psi $Z = 32.00$ in³
 $I = 64.00$ in⁴ $M_x = 3995.4$ ftlb



	Maximum	x (ft)
Pressure (psf)	406.9	8.00
Bending Moment (ftlb)	1831.0	2.99
Shear Force (lb)	1220.7	5.99
Deflection (in)	0.0	3.00

Min. section modulus required, $Z = 14.7$ in³



MDOT Sheetpile Manual

Title: Case 9 Soldier Pile
Page: 7
Date: 3.11.19 FOS = 1.0

Pile: Steel Waler
Lagging: 4" x 12" Lagging
Works: Temporary
Pressure: Rankine
Analysis: Gross Pressure
Toe: Cantilever

Design Report

1. Maximum bending moment = 105226.4ftlb and $f = 32500.0\text{psi}$. MINIMUM required soldier section modulus is: $Z = 38.85\text{in}^3 (= M/f)$. Soldier pile section modulus in this design is $Z = 146.00\text{in}^3$, and is satisfactory.
2. Arching factor, $A = 2.80$. Are you sure this is correct? Minimum ϕ on passive side is 30° , and $A = 0.08\phi (= 2.40)$.
3. FOS = 1.00 (Gross Pressure)
This is the factor of safety against rotation about the toe.
The FOS can be changed using 'Defined FOS' or 'Manual' in the 'Wall' page.



MDOT Sheetpile Manual


SupportIT, v2.37

© 1997 - 2015, GTSoft Ltd.
Tel/Fax: +44 (0)1292 477754
Email: GTSoftLtd@aol.com
Web: www.GTSoft.org

Title: Case 9 Soldier Pile
 Page: 1 FOS = 1.5
 Date: 3.11.19

Pile: Steel Waler
 Lagging: 4" x 12" Lagging
 Works: Temporary
 Pressure: Rankine
 Analysis: Gross Pressure
 Toe: Cantilever

	Maximum	d (ft)
○	407.1 psf	8.00
□	105397.5 ftlb	13.76
●	0.7 in	0.00



MDOT Sheetpile Manual

Title: Case 9 Soldier Pile
 Page: 2
 Date: 3.11.19 FOS = 1.5

Input Data

Depth Of Excavation = 8.00ft
 Surcharge = 360.0psf

Depth Of Active Water = 8.00ft
 Depth Of Passive Water = 8.00ft

Water Density = 62.43pcf
 Minimum Fluid Density = 31.82pcf

Pile: Steel Waler
 Lagging: 4" x 12" Lagging
 Works: Temporary
 Pressure: Rankine
 Analysis: Gross Pressure
 Toe: Cantilever

Soil Profile

Depth (ft)	Soil Name	γ (pcf)	γ' (pcf)	C (psf)	C_a (psf)	ϕ (°)	δ (°)	K_a	K_{ac}	K_p	K_{pc}
0.00	Loose Fine Sand	109.20	65.55	0.0	0.0	30.0	0.0	0.33	0.00	3.00	0.00
8.00	Dense Fine Sand	118.37	68.73	0.0	0.0	35.0	0.0	0.27	0.00	3.69	0.00

Solution

Wall

Description	E (psi)	I (in ⁴)	f (psi)	Z (in ³)	Allowed M_{max} (ftlb)	b (ft)	t (ft)	w (ft)	s (ft)	Arching	n	Upstand (ft)	Toe (ft)	Length (ft)
Steel Waler	3.04E+07	904.00	32500.0	146.00	395416.7	1.167	1.167	2.000	6.00	2.80	1.50	0.00	15.36	23.36
4" x 12" Lagging	1.23E+06	64.00	1498.2	32.00	3995.4	1.001	0.331	----	----	----	----	----	----	----

Pressure Model: Rankine; Passive pressure ignored for depth n.w (= 3.00ft)

Maxima

	Maximum	Depth (ft)
Pressure	407.1 psf	8.00
Bending Moment	105397.5 ftlb	13.76
Deflection	0.7 in	0.00
Shear Force	14832.5 lb	11.02







MDOT Sheetpile Manual

Title: Case 9 Soldier Pile
 Page: 3
 Date: 3.11.19 FOS = 1.5

Pile: Steel Waler
 Lagging: 4" x 12" Lagging
 Works: Temporary
 Pressure: Rankine
 Analysis: Gross Pressure
 Toe: Cantilever

	Maximum	d (ft)
○	407.1 psf	8.00
□	105397.5 ftlb	13.76
◇	14832.5 lb	11.02
●	0.7 in	0.00



MDOT Sheetpile Manual

Title: Case 9 Soldier Pile
 Page: 4
 Date: 3.11.19 FOS = 1.5

Pile: Steel Waler
 Lagging: 4" x 12" Lagging
 Works: Temporary
 Pressure: Rankine
 Analysis: Gross Pressure
 Toe: Cantilever

depth (ft)	P (psf)	M (ftlb)	D (in)	F (lb)	depth (ft)	P (psf)	M (ftlb)	D (in)	F (lb)	depth (ft)	P (psf)	M (ftlb)	D (in)	F (lb)
0.00	118.8	0.0	0.7	0.0	7.84	401.5	39251.5	0.3	12269.7	15.68	-1473.9	84846.1	0.0	-6458.1
0.17	125.1	9.9	0.7	128.1	8.01	407.1	41185.5	0.3	12648.0	15.85	-1510.5	81826.0	0.0	-6755.7
0.33	130.7	37.9	0.7	248.0	8.17	292.0	43408.2	0.3	12768.3	16.02	-1551.7	78274.2	0.0	-7050.4
0.50	137.0	92.2	0.7	389.3	8.34	250.8	45651.5	0.3	12886.9	16.18	-1588.3	74996.9	0.0	-7276.7
0.67	142.6	161.6	0.7	520.3	8.51	214.2	47663.1	0.2	12993.2	16.35	-1629.5	71194.9	0.0	-7491.3
0.83	149.0	264.5	0.7	674.1	8.68	173.1	49946.0	0.2	13114.0	16.52	-1670.7	67291.9	0.0	-7663.4
1.00	154.6	379.0	0.7	816.3	8.84	136.5	51993.0	0.2	13222.2	16.68	-1707.3	63755.6	0.0	-7780.8
1.17	160.9	534.6	0.6	982.6	9.01	95.3	54316.1	0.2	13345.1	16.85	-1748.4	59721.8	0.0	-7872.8
1.33	167.2	719.9	0.6	1155.6	9.18	58.7	56399.2	0.2	13455.3	17.02	-1785.0	56103.9	0.0	-7918.9
1.50	172.8	910.4	0.6	1314.9	9.34	17.5	58763.2	0.2	13580.3	17.18	-1826.2	52017.3	0.0	-7930.6
1.67	179.1	1154.8	0.6	1500.4	9.51	-23.7	61149.3	0.2	13706.5	17.35	-1862.8	48387.1	0.0	-7905.5
1.84	184.7	1399.7	0.6	1670.8	9.68	-60.3	63288.8	0.2	13819.6	17.52	-1904.0	44325.8	0.0	-7837.1
2.00	191.0	1707.4	0.6	1868.8	9.84	-101.4	65716.8	0.2	13947.9	17.68	-1945.2	40309.4	0.0	-7726.3
2.17	196.7	2010.3	0.6	2050.4	10.01	-138.0	67894.0	0.2	14062.9	17.85	-1981.8	36794.7	0.0	-7592.2
2.34	203.0	2385.4	0.6	2261.0	10.18	-179.2	70364.8	0.2	14193.4	18.02	-2022.9	32923.0	0.0	-7401.2
2.50	209.3	2797.8	0.6	2478.2	10.34	-215.8	72580.3	0.2	14310.3	18.18	-2059.5	29571.5	0.0	-7195.8
2.67	214.9	3196.7	0.6	2676.9	10.51	-257.0	75094.5	0.2	14442.9	18.35	-2100.7	25922.5	0.0	-6924.7
2.84	221.2	3682.9	0.6	2906.6	10.68	-298.2	77632.1	0.1	14576.7	18.52	-2137.3	22803.7	0.0	-6648.0
3.00	226.8	4149.1	0.5	3116.4	10.84	-334.8	79907.4	0.1	14696.6	18.68	-2178.5	19455.4	0.0	-6296.7
3.17	233.1	4713.2	0.5	3358.7	11.01	-372.1	82489.5	0.1	14832.5	18.85	-2219.7	16297.9	0.0	-5902.9
3.34	238.7	5250.6	0.5	3579.6	11.18	-412.5	84758.8	0.1	14272.5	19.02	-2256.3	13669.1	0.0	-5517.3
3.50	245.1	5896.6	0.5	3834.5	11.34	-453.7	87204.6	0.1	13601.8	19.19	-2297.4	10931.8	0.0	-5043.4
3.67	251.4	6587.8	0.5	4096.0	11.51	-490.3	89277.5	0.1	12970.0	19.35	-2334.0	8711.2	0.0	-4586.5
3.84	257.0	7241.0	0.5	4334.0	11.68	-531.5	91489.2	0.1	12219.1	19.52	-2375.2	6472.0	0.0	-4032.4
4.00	263.3	8020.5	0.5	4608.0	11.84	-572.7	93566.2	0.1	11425.8	19.69	-2411.8	4728.9	0.0	-3504.2
4.17	268.9	8754.1	0.5	4857.1	12.01	-609.3	95293.3	0.1	10685.0	19.85	-2450.3	3066.1	0.0	-2870.0
4.34	275.2	9626.2	0.5	5143.7	12.18	-650.4	97095.6	0.1	9811.6	20.02	-2494.2	1739.8	0.0	-2193.3
4.50	280.8	10443.9	0.5	5404.0	12.35	-687.0	98566.8	0.1	8999.5	20.19	-2530.8	861.3	0.0	-1556.2
4.67	287.1	11412.6	0.4	5703.1	12.51	-728.2	100067.9	0.1	8045.9	20.35	-2571.9	230.7	0.0	-799.3
4.84	293.4	12434.2	0.4	6008.9	12.68	-764.8	101259.7	0.1	7162.6	20.52	-2608.5	5.2	0.0	-90.9
5.00	299.1	13387.6	0.4	6286.2	12.85	-806.0	102433.2	0.1	6128.8	20.69	-2649.7	0.0	0.0	0.0
5.17	305.4	14512.2	0.4	6604.5	13.01	-847.2	103422.5	0.1	5052.6	20.85	-2686.3	0.0	0.0	0.0
5.34	311.0	15559.0	0.4	6893.1	13.18	-883.8	104141.2	0.1	4060.3	21.02	-2727.5	0.0	0.0	0.0
5.51	317.3	16790.7	0.4	7223.9	13.35	-924.9	104762.3	0.1	2903.9	21.19	-2768.7	0.0	0.0	0.0
5.67	322.9	17934.6	0.4	7523.5	13.51	-961.5	105142.1	0.1	1840.3	21.35	-2805.3	0.0	0.0	0.0
5.84	329.2	19277.7	0.4	7866.9	13.68	-1002.7	105368.5	0.0	603.8	21.52	-2846.4	0.0	0.0	0.0
6.01	335.5	20681.3	0.4	8217.0	13.85	-1039.3	105366.4	0.0	-360.5	21.69	-2883.0	0.0	0.0	0.0
6.17	341.1	21980.8	0.4	8533.7	14.01	-1080.5	105000.0	0.0	-1140.9	21.85	-2924.2	0.0	0.0	0.0
6.34	347.5	23502.1	0.4	8896.2	14.18	-1121.7	104241.0	0.0	-1878.9	22.02	-2960.8	0.0	0.0	0.0
6.51	353.1	24908.0	0.3	9224.1	14.35	-1158.3	103254.4	0.0	-2499.3	22.19	-3002.0	0.0	0.0	0.0
6.67	359.4	26551.1	0.3	9599.2	14.51	-1199.4	101813.5	0.0	-3157.1	22.36	-3043.2	0.0	0.0	0.0
6.84	365.0	28067.1	0.3	9938.2	14.68	-1236.0	100255.5	0.0	-3706.2	22.52	-3079.8	0.0	0.0	0.0
7.01	371.3	29836.1	0.3	10325.9	14.85	-1277.2	98210.8	0.0	-4283.9	22.69	-3120.9	0.0	0.0	0.0
7.17	377.6	31673.4	0.3	10720.2	15.01	-1313.8	96150.8	0.0	-4761.8	22.86	-3157.5	0.0	0.0	0.0
7.34	383.2	33364.9	0.3	11076.2	15.18	-1355.0	93580.4	0.0	-5259.3	23.02	-3198.7	0.0	0.0	0.0
7.51	389.5	35334.5	0.3	11483.1	15.35	-1396.2	90763.2	0.0	-5714.3	23.19	-3235.3	0.0	0.0	0.0
7.67	395.1	37145.5	0.3	11850.3	15.52	-1432.8	88069.6	0.0	-6083.2	23.36	-3271.9	0.0	0.0	0.0









MDOT Sheeppile Manual

SupportIT, v2.37

© 1997 - 2015, GTSOFT Ltd.
 Tel/Fax: +44 (0)1292 477754
 Email: GTSOFT@aol.com
 Web: www.GTSOFT.org

Title: Case 9 Soldier Pile
 Page: 5
 Date: 3.11.19 FOS = 1.5

Pile: Steel Waler
 Lagging: 4" x 12" Lagging
 Works: Temporary
 Pressure: Rankine
 Analysis: Gross Pressure
 Toe: Cantilever



MDOT Sheetpile Manual


SupportIT, v2.37

© 1997 - 2015, GTSOFT Ltd.
 Tel/Fax: +44 (0)1292 477754
 Email: GTSOFT@aol.com
 Web: www.GTSOFT.org

Title: Case 9 Soldier Pile
 Page: 6
 Date: 3.11.19 FOS = 1.5


Pile: Steel Waler
 Lagging: 4" x 12" Lagging
 Works: Temporary
 Pressure: Rankine
 Analysis: Gross Pressure
 Toe: Cantilever

4" x 12" Lagging:
 $s = 6.00$ ft $f = 1498.2$ psi
 $E = 1.23E+06$ psi $Z = 32.00$ in³
 $I = 64.00$ in⁴ $M_x = 3995.4$ ftlb



	Maximum	x (ft)
Pressure (psf)	407.1	8.00
Bending Moment (ftlb)	1831.8	2.99
Shear Force (lb)	1221.2	0.00
Deflection (in)	0.0	3.00

Min. section modulus required, $Z = 14.7$ in³



MDOT Sheetpile Manual

Title: Case 9 Soldier Pile

Page: 7

Date: 3.11.19

FOS = 1.5

Pile: Steel Waler

Lagging: 4" x 12" Lagging

Works: Temporary

Pressure: Rankine

Analysis: Gross Pressure

Toe: Cantilever

Design Report

1. Maximum bending moment = 105397.5ftlb and $f = 32500.0\text{psi}$. MINIMUM required soldier section modulus is: $Z = 38.92\text{in}^3 (= M/f)$. Soldier pile section modulus in this design is $Z = 146.00\text{in}^3$, and is satisfactory.
2. Arching factor, $A = 2.80$. Are you sure this is correct? Minimum ϕ on passive side is 30° , and $A = 0.08\phi (= 2.40)$.
3. FOS = 1.49 (Gross Pressure)
This is the factor of safety against rotation about the toe.
The FOS can be changed using 'Defined FOS' or 'Manual' in the 'Wall' page.



MDOT Sheetpile Manual

Report No. RC-1633

**A Manual for the
Design of Temporary Earth Retention Systems (TERS)
for the Michigan Dept. of Transportation**

Center for Structural Durability at Michigan Tech – a MDOT Center of Excellence

FINAL REPORT

End of document