

## **GUIDANCE DOCUMENT**

	PAGE 1 OF 1
IDENTIFIER	EFFECTIVE DATE
00004	01/18/2022
SUPERSEDES	DATED
4/17/2017 (Rev 3)	


RESPONSIBLE ORGANIZATION:

Office of Passenger Transportation

**SUBJECT:** 

**Emergency Exit Requirements** 

Minimum emergency exit dimensions: 13 inches by 19 11/16 inches	
Modified Vehicles	Emergency exits are required to be in both the front and rear sections
	of the passenger compartment for any vehicle that has been modified
	from the Original Equipment Manufacturer's design.
School Buses	For school buses registered under PA 432, MDOT will follow the
	Emergency Exit guidance of the FMCSA and will accept the number
	of emergency exits in school buses that meet the emergency exit
	standards of 393.62.
9-15 Passengers	1 Left and 1 Right Exit
	• 10,000 LB GVWR and greater needs: 1 Roof or Rear Exit
16-20 Passengers	1 Left and 1 Right Exit
	1 Roof or Rear Exit
21-40 Passengers	2 Left and 2 Right Exits
	1 Roof or Rear Exit
41-60 Passengers	3 Left and 3 Right Exits
	1 Roof or Rear Exit
61-80 passengers	4 Left and 4 Right Exits
	1 Roof or Rear Exit



The listed requirements and additional emergency exit information can be found at:

49 CFR § 571.217 - Standard No. 217; Bus emergency exits and window retention and release.